NIPER-576
October 1991
Revised January 1992

NIPER

Commitment to Excellence

**QUARTERLY TECHNICAL REPORT
FOR
JULY 1 - SEPTEMBER 30, 1991**

**VOLUME II
ENERGY PRODUCTION RESEARCH**

Work Performed for the
U. S. Department of Energy
Under Cooperative Agreement DE-FC22-83FE60149

National Institute for Petroleum and Energy Research
IIT Research Institute • P.O. Box 2128
Bartlesville, Oklahoma 74005 • (918) 336 2400

NIPER-576
Distribution Category UC-122
October 1991

QUARTERLY TECHNICAL REPORT

for
July 1—Sept. 30, 1991
Volume II
Energy Production Research

NIPER--576

DE92 007000

Work Performed for the
U.S. Department of Energy
Under Cooperative Agreement
DE-FC22-83FE60149

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

IIT Research Institute
NATIONAL INSTITUTE FOR PETROLEUM AND ENERGY RESEARCH
P.O. Box 2128
Bartlesville, Oklahoma 74005

(This page intentionally left blank)

FOREWORD

The Quarterly Technical Report, NIPER-576, is submitted in accordance with the provisions of Cooperative Agreement DE-FC22-83FF60149 between the Department of Energy and the IIT Research Institute. The report is submitted in two volumes, Volume I representing the work accomplished under Fuels Research and Volume II the work for Energy Production Research during the period July 1—Sept. 30, 1991.

(This page intentionally left blank)

TABLE OF CONTENTS

	PAGE
FOREWORD.....	iii
CHEMICAL FLOODING—SUPPORTING RESEARCH.....	1
BE4A. Development of Improved Surfactant Flooding Methods	1
BE4B. Development of Improved Alkaline Flooding Methods	4
BE4C. Development of Improved Mobility Control Methods	6
SGP41. Surfactant-Enhanced Alkaline Flooding Field Project.....	7
GAS DISPLACEMENT—SUPPORTING RESEARCH.....	10
BE5A. Gas-Miscible Displacement.....	10
BE5B. Development of Improved Immiscible Gas Displacement Methodology	13
THERMAL RECOVERY—SUPPORTING RESEARCH.....	20
BE11A. Thermal Processes for Light Oil Recovery	20
BE11B. Thermal Processes for Heavy Oil Recovery	22
SGP37. Feasibility Study of Heavy Oil Recovery in the Mid-Continent Region (Oklahoma, Kansas, Missouri).....	24
GEOSCIENCE TECHNOLOGY.....	38
BE12. Imaging Techniques Applied to the Study of Fluids in Porous Media	23
SGP43. Identification of Cross-Formational Flow in Multi-Reservoir Systems Using Isotopic Techniques (Phase I)	27
SGP42. Development of Methods for Mapping Distribution of Clays in Petroleum Reservoirs.....	27
RESOURCE ASSESSMENT TECHNOLOGY.....	27
BE1. Reservoir Assessment and Characterization.....	27
BE2. TORIS Research Support.....	36
BE9. Three-Phase Relative Permeability.....	38
SGP28. Developing a Reservoir Data Base: Phase 1	41
SGP30. EOR Incentive Projects Survey.....	42
SGP40. IPRs For Slanted and Horizontal Wells Producing From Heterogeneous Reservoirs.....	42
SGP46. Summary of Geological and Production Characteristics of Class I, Unstructured, Deltaic Reservoirs	44
SGP47. Third International Reservoir Characterization Technical Conference.....	44
MICROBIAL TECHNOLOGY.....	46
BE3. Development of Improved Microbial Flooding Methods.....	46
SGP13. Microbial Enhanced Waterflooding Field Project.....	47

TABLE OF CONTENTS (Continued)

	PAGE
ENVIRONMENTAL TECHNOLOGY	49
SGP23 Technical Analysis for Underground Injection Control	49

CHEMICAL FLOODING— SUPPORTING RESEARCH

DEVELOPMENT OF IMPROVED SURFACTANT FLOODING METHODS

Cooperative Agreement DE-FC22-83FE60149,
Project BE4A

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$600,000

Principal Investigator:
Leo A. Noll

Project Manager:
Jerry F. Casteel
Bartlesville Project Office

Reporting Period: July 1 to Sept. 30, 1991

Objectives

The objective of this year's work is to develop more effective surfactant flooding systems that have broader

tolerance to chemical composition in reservoirs. The focus is to mitigate problems which have been shown to have adverse effects on the performance and economics of surfactant flooding processes, to improve the economics of surfactant-enhanced oil recovery through the development of effective oil recovery systems that contain very low concentrations of synthetic surfactants and alkaline additives, and to investigate the application or extension of current chemical flooding technology to near-term problem solving for near-wellbore permeability improvement.

Summary of Technical Progress

Mixed Surfactant Systems

A screening method used was the selective combination of primary, secondary and ternary surfactant mixtures. For this screening, two cosurfactants were added to a primary surfactant component. The primary surfactant selected had the potential for producing high oil solubilization and low interfacial tension. The two other surfactants were selected based on the capability of balancing the effect of the secondary and tertiary surfactant components to maintain the oil and water affinity of the overall chemical system. This is similar to an hydrophilic-lipophilic balance (HLB) gradient approach.¹

For this approach, several surfactant mixtures were evaluated. The secondary components in the mixture

included several ethoxylated sulfonates, ether sulfates, ethoxylated phenols and ethoxylated nonyl phenols. Results from these studies showed favorable phase behavior in bottle samples at the conditions tested. Additional tests, such as IFT and phase behavior measurements, were conducted on potential chemical systems. Some of these mixtures showed good solubilization and fairly low IFT values.

One candidate system that was reported initially in a previous Quarterly Technical Report² contained the B-110 surfactant, an alkyl aryl sulfonate, and CS-460, an ethoxylated sulfate, and one nonionic surfactant, NP-11, an ethoxylated alcohol. Interfacial tension values of 10^{-3} mN/m were measured at 1 wt% total surfactant concentration with equal component weight mixtures of the three surfactants (1:1:1). This surfactant system was formulated with 100% North Burbank Unit (NBU) brine. This system was also used in a coreflood experiment for displacement efficiency comparison with previous selected systems because it exhibited favorable solubilization and low IFT values. The overall conclusion regarding the coreflooding experiment was that it was disappointing. Only limited oil recovery was achieved using this system. A possible reason for the failure of this system to recover more oil was the relative proximity of the solubility limit of the B-110 component in the system. Additional solubility and phase scans showed that higher proportion of the B-110 component in the formulation resulted in significant phase separation. The results of these measurements are presented in Fig. 1. The figure shows that the (1:1:1) mixture that yielded the low IFT values was at the border line of this solubility limit. Additional scans were conducted at lower component proportions to further map the phase boundaries of this system. Limited number of component combinations have been found and no significant solubilization was achieved using these combinations. This surfactant system appeared to have limited application under the conditions being tested.

Although the general results from this screening method were not favorable, the methodology still presented possibilities of different surfactant combinations that may

prove to be applicable. The concept of identifying two surfactants that can synergistically balance the oil and water affinity of the primary surfactant and the overall chemical system is promising. Additional studies will be conducted in this area.

The presence of alcohol in surfactant systems has been fairly well accepted as favorable for enhancing solution solubility but detrimental to the IFT and solubilization capacity of the overall system. Conventional chemical systems containing low-molecular-weight alcohols tend to degrade in effectiveness primarily because of the chromatographic separation of these alcohols from the surfactant system. The concern for the presence of alcohol is also true when comparing the stock B-105 with the combination of B-110/CA-207 surfactant. The phase behavior of the B-110/CA-207 is somewhat dissimilar with what the B-105 surfactant exhibited, under the conditions tested. The IFT values ranged from as high as 1 mN/m down to 10^{-2} mN/m at 100% North Burbank Unit salinity, depending on the proportions of the two components. The behavior difference can be directly attributed to the alcohol concentrations in the stock samples. The considerable amount of alcohol (> 6 wt%) in the stock B-110 and stock CA-207 surfactant shifted the phase behavior of the overall system.

A batch of the B-110/CA-207 system was also prepared, such that the total alcohol concentration was comparable to the stock B-105 sample. The results are presented in Fig. 2. This figure shows a plot of the comparison of the IFT values measured using the stock S-2 system and the B-110*/CA-207* system. The IFT and phase behavior measurements using this "distilled" system (B-110*/CA-207*) were comparable to the results using the B-105 stock sample. The IFT values using the B-110*/CA-207* and the B-105 samples ranged from 10^{-3} to 10^{-2} mN/m over the salinity range tested.

A Topical Report, entitled "Phase Behavior and Oil Recovery Investigations Using Mixed and Alkaline-Enhanced Surfactant Systems," discussing the results of this year's research has been prepared and submitted for review.

Fig. 1 Ternary diagram for the B-110/CS-460/NP-11 surfactant system with NBU crude oil at 50 °C.

Fig. 2 Comparison of the phase behavior of B-105 with the B-110*/CA-207* surfactant system with NBU crude oil at 50 °C.

Alkaline-Enhanced Mixed Surfactant Systems

Two corefloods were conducted using Berea sandstone core plugs encased in epoxy to allow the use of the computerized tomography (CT) aided imaging techniques to monitor oil saturations at various times during the progress of the coreflood. CT scanning uses X-ray energy to determine differences in material densities within a core. The experimental conditions for coreflood tests were selected to duplicate conditions of two corefloods that were conducted earlier in the year using a mixed surfactant system with alkaline additives (0.4% B-105/B-110, 37.5/62.5 ratio, in 1.02% NaCl, 0.95N NaHCO₃, 0.95N Na₂CO₃, and 2% 2-butanol). For one coreflood, recovery of Hepler oil was greater than 85%, indicating favorable conditions for oil mobilization. The second coreflood recovered NBU oil using the same surfactant formulation. However, a lower polymer concentration was used in the mobility control slug (1,200 ppm rather than 3,500 ppm biopolymer). Recovery in this case was approximately 35%, indicating much less efficient displacement of oil. For the first test using CT imaging, CT-CF 1, core permeability was relatively high, 561 mD. For the second test, CT-CF 2, core permeability was lower, 110 mD. Oil recovery results compared favorably with that of the previously conducted tests. Oil recovery for CT-CF 1 was greater than 80% and for CT-CF 2 was approximately 39%.

The oils were tagged with iododecane to provide higher contrast in the CT images between oil and brine solutions. Addition of iododecane reduced the viscosity of the Hepler oil to 39 cP compared to 56 cP but did not change the viscosity of NBU oil, 8 cP, for ambient temperature conditions.

At various stages of the coreflooding process, fluid injection was interrupted to monitor the progress of the flood using the CT scanner. CT images were taken every 8 mm, then a composite image was reconstructed of the oil

distribution along the core length. The CT images after the oil flood indicated that oil distributions were relatively uniform throughout the core plugs. After waterflooding, oil saturations appeared to be slightly greater at the core outlets than at the inlets. After injection of surfactant, an oil bank could be seen for CT-CF 1 but not for CT-CF 2. After polymer injection, the CT-CF 1 core was well swept of oil. The CT-CF 2 core, however, indicated that chemicals channeled through the center of the core leaving fairly high oil distribution along the core edges and near the outlet end of the core.

CT images may be a useful method to evaluate surfactant and polymer effectiveness in relatively short laboratory core experiments. Eventually, studies will be extended to evaluation of surfactant formulations in reservoir core.

Surfactant-Based Well Treatments

A status report, NIPER-551, "Treating Paraffin Deposits in Producing Oil Wells," by Leo A. Noll has been completed and submitted to the Department of Energy. The report summarizes the historical development of paraffin treatments, lists methods to test and evaluate treating chemicals, and provides a bibliography of references pertaining to paraffin treatment.

References

1. L. Minssiue. Surfactant Flooding with Hard Water: Case Study Solved by HLB Gradient. *SPE Res. Eng.*, Nov. 1987, pp. 605-612.
2. National Institute for Petroleum and Energy Research. *Quarterly Technical Report for April 1-June 30, 1991, vol. II, Energy Production Research*, DOE Report NIPER-545, 1991.

DEVELOPMENT OF IMPROVED ALKALINE FLOODING METHODS

Cooperative Agreement DE-FC22-83FE60149,
Project BE4B

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$150,000

Principal Investigator:
Troy R. French

Project Manager:
Thomas Reid
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objective of this project is to develop cost-effective and efficient chemical flooding formulations with surfactant-enhanced, weakly alkaline systems. Specific objectives for FY91 are: (1) to design effective injection strategies and (2) to perform studies designed to support a field test.

Summary of Technical Progress

Useful results were obtained from a study on the effects of different injection strategies on oil recovery. Oil recovery was highest when alkaline surfactant was followed by polymer. Oil recovery decreased only slightly when the alkali, surfactant, and polymer were simultaneously injected (mixed in single slug), and oil production occurred faster. Oil recovery was significantly reduced when surfactant was followed with alkaline polymer. Oil recovery was least when surfactant was followed by polymer and there was no alkali in any of the injected solutions.

The conclusion pertinent to application of surfactant-enhanced alkaline flooding in the Tucker sand of Hepler (KS) field is that alkali, surfactant, and polymer should be injected in a single slug that is preceded by injection of at least 0.1 PV of alkaline preflush.

Application to Enhanced Oil Recovery

The emerging technology in alkaline flooding for heavy oil recovery is the use of a combination of surfactant and alkali. Proper design of injection strategy can be viewed as near-term as well as long-term research. In the near term, this research will support design of the proposed surfactant-enhanced alkaline flooding field pilot test which is being conducted under the Supplemental Government Program.

Discussion

Several injection strategies have been suggested for surfactant-enhanced alkaline flooding. Some of these strategies have been compared in corefloods that were conducted while maintaining injection of the same amounts of chemicals. Each of these chemical systems contained 0.4% of a mixture of Petrostep B-series surfactants and was optimized to provide the lowest possible interfacial tension (IFT) with Hepler oil.¹ The corefloods were performed under conditions that simulated the Tucker sand of Hepler field, which is a Class I, fluvial dominated deltaic reservoir.

Experiments reported previously showed that oil recovery was much higher when alkali and surfactant were injected as a single chemical slug than when an optimized surfactant system without alkali was injected.¹ Another coreflood was conducted this quarter with a slightly different injection strategy; the alkali was contained in the polymer, rather than with the surfactant. The polymer/alkali slug was injected after the surfactant slug. This is similar to an injection strategy described by Schuler.² With this strategy, a larger total volume must be injected into porous media before IFT reaches a minimum; however, minimum IFT values between produced fluids were shown to occur over a large effluent pore volume.

When the alkali was contained in the polymer, oil recovery was 40.1% of the oil that remained after waterflooding, which is intermediate between the oil recovery with surfactant alone (26.4% OIP) and when alkali was in the same slug as the surfactant (85.0% OIP). Total oil recovery (%OOIP), which includes oil produced during waterflooding, with these three injection strategies is shown in Fig. 1. The results indicate that a synergism occurs between surfactant and alkali and that the synergism between alkali and surfactant is reduced whenever they are not mixed together in the same slug.

Effluent surfactant analysis for the coreflood conducted with alkaline polymer is shown in Fig. 2. (The origin in Fig. 2 begins with chemical injection.) Interestingly, the amount of surfactant retained in this core was 75.1% of the amount injected, which is about the same as for other

Fig. 1 Oil recovery from optimized surfactant systems.

Fig. 2 Coreflood effluent viscosity and surfactant analysis, surfactant followed with alkaline polymer.

injection strategies. Surfactant effluent analyses for the other two injection strategies are shown in Figs. 3 and 4. The major difference shown by the surfactant effluent analyses shown in Figs. 2, 3, and 4 is that surfactant was eluted sooner in the coreflood conducted with surfactant alone. It is believed that this occurred only because of differences in the cores, rather than as a result of different injection strategies.

Observations and Conclusions

The experiments discussed above are only a part of the injection study that was conducted with Hepler oil this year. The observations from the oil recovery tests that were conducted are:

1. Oil recovery was highest when alkaline surfactant was followed by polymer.
2. Oil recovery was only slightly decreased when the alkali, surfactant, and polymer were simultaneously injected (mixed in single slug), and oil production occurred faster.

Fig. 3 Coreflood effluent alkalinity and surfactant analysis, surfactant and alkali in same formulation, followed with polymer.

Fig. 4 Coreflood oil saturation, effluent oil cut, and surfactant analysis, surfactant followed with polymer (no alkali injected).

3. Oil recovery was significantly reduced when surfactant was followed with alkaline polymer.
4. Oil recovery was lowest when surfactant was followed by polymer and there was no alkali in any of the injected solutions.

When different alkaline preflush volumes were injected before injection of the main chemical slug, it was observed that:

1. Oil production increased as alkaline preflush volume was increased from 0 to 0.25 PV.
2. The alkaline preflush increased oil production in all cases, but the effect was most pronounced when the cores were saturated with brine that contained divalent ions.

The conclusion pertinent to application of surfactant-enhanced alkaline flooding in the Tucker sand of Hepler (KS) field is that alkali, surfactant, and polymer should be injected in a single slug that is preceded by injection of at least 0.1 PV of alkaline preflush.

References

1. T. R. French, *Design of Chemical Formulation for Project SGP41*. Report NIPER-530, May 1991.
2. P. J. Schuler, R. M. Lerner, and D. L. Kuehne, *Improving Chemical Flood Efficiency with Micellar/Alkaline/Polymer Processes*, paper SPE/DOE 14934 presented at the SPE/DOE Fifth Symp. on Enhanced Oil Recovery, Tulsa, Okla., Apr. 20-23, 1986.

DEVELOPMENT OF IMPROVED MOBILITY-CONTROL METHODS

Cooperative Agreement DEFC22-83FE60149,
Project BE4C

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$200,000

Principal Investigators:
Troy R. French
Hong W. Gao

Project Manager:
Jerry F. Casteel
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this project are to determine the applicability of low-molecular-weight polymer gels for mobility-control applications and to investigate the effect of a gel treatment on oil recovery in a polymer flood.

Summary of Technical Progress

Application to EOR

Mechanical degradation of high-molecular-weight polyacrylamides is a problem in field applications. A mobility-control system based on crosslinking a low-molecular-weight polyacrylamide may be much less susceptible to mechanical degradation.

Flow Behavior of Gel Systems in Bead Packs

Shear degradation, reheelability and injectivity tests of a gel system containing 15,000 ppm of HPAM1-10 polymer (MW = 400,000 daltons, 10% hydrolyzed) and 75 ppm of Cr(III) in 53 meq/L NaCl at pH=4.8 were conducted in a polystyrene bead pack (0.4 cm in diameter and 15.2 cm in length) having a brine permeability of 4.3 darcies and a porosity of 38%. This permeability was about 8.4 times lower than that of a 36-darcy bead pack used before.¹ All tests were conducted at room temperature (22.4°C). Before tests, the gel sample had shown consistent rheological properties after being agitated in a bottle for more than 1 month. Its viscosity was 10.24 cP at a shear rate of 11 sec⁻¹.

After the first passthrough the bead pack at an apparent shear rate of above 2,000 sec⁻¹ (flow rate = 0.85 mL/min), the viscosity of the gelled polymer decreased from 10.24 to

9.65 cP at a shear rate of 11 sec⁻¹. As injection continued, the pressure drop across the bead pack kept increasing and the flow rate kept decreasing. After 44 mL had passed, the flow rate decreased to 0.1 mL/min and pressure drop went up to 186 psi, indicating that strong gel was formed inside the bead pack. Strong gel was formed through further gelation of the gel sample inside the bead pack. Because of further gelation occurred inside the bead pack, injectivity of the gel system in the 4.3-darcy bead pack could not be measured and compared with that of a conventional high-molecular-weight polyacrylamide solution in a similar bead pack.² After setting in the fluid isolator for 6 days, the viscosity of the sheared gelled polymer increased to 9.95 cP at a shear rate of 11 sec⁻¹. Examination of the bead pack showed that about 10.4 cm of the bead pack was plugged by the strong gel formed inside the bead pack. After removing this plugging part of beads from the bead pack, the degraded gelled polymer was able to flow through the bead pack at high shear conditions again and the effluent viscosity decreased to 9.47 cP at a shear rate of 11 sec⁻¹. These results indicated that gelled polymer was degraded at high shear conditions and broken crosslinking bonds were rehealed at no shear or low shear conditions.

Further gelation also occurred inside a similar bead pack (4.4 darcies, porosity = 38%) at low shear conditions. Partial plugging first occurred after trying to measure the flow resistance of the above gel system at 1.1 mL/hr (apparent shear rate = 45 sec⁻¹). Because of leaks in the reservoir, no fluid came out of the bead pack over a period of 1 hour. After increasing the flow rate setting to 150 mL/hr, the gel was able to pass through the bead pack at only 10 mL/hr. After setting overnight, the pressure drop across the bead pack increased further, indicating that strong gel was formed. When the actual flow rate was about 0.05 mL/hr, the pressure drop over the bead pack was 87 psi. This pressure drop corresponded to a permeability of about 4 mD. Examination of the bead pack showed that plugging occurred in the first 1 cm of the bead pack. After removing this part of beads, brine was able to flow through freely. Strong gel formed inside the 4.3- and 4.4-darcy bead packs but not inside a 36-darcy bead pack¹ indicates that the permeability has a significant effect on the further gelation of a gel system inside a porous medium. These results also indicate that before a gel system can be applied to reservoirs, screening tests with actual reservoir cores should be conducted to select appropriate gels for mobility control.

Permeability Modification

A status report, "The Effect of Gel Treatment on Oil Recovery in a Polymer Flood," has been written and reviewed. Significant conclusions contained in this report are as follows:

1. Combined near-wellbore gel treatment and polymer flood is effective in increasing incremental oil recovery over that of a polymer flood in reservoirs with low crossflow.

2. In reservoirs with high crossflow, a polymer flood is more effective in increasing incremental oil recovery over

waterflood than combined near-wellbore gel treatment and polymer flood.

3. In reservoirs with low crossflow, a combined near-wellbore gel treatment and polymer flood is more effective in increasing incremental oil recovery over that of a polymer flood than either a deep gel placement or combined deep gel placement and polymer flood.

4. Deep gel placement or combined deep gel placement and polymer flood is not effective in increasing incremental oil recovery over that of a polymer flood in reservoirs with high crossflow.

5. Undesired permeability reduction in the low permeability layer can occur in reservoirs with low and high crossflow when a large slug size of a gel system is used. The degree of permeability reduction in the low-permeability layer increases with the increase in the slug size of the gel system and the increase in k_v/k_h (ratio of

the vertical permeability to the horizontal permeability).

6. A polymer flood initiated at the start of a waterflood gives the earliest increase in incremental oil recovery over waterflood than do those initiated after the start of a waterflood regardless of the degree of crossflow.

References

1. National Institute for Petroleum and Energy Research. *Quarterly Technical Report for January 1 - March 31, 1991, Vol. II, Energy Production Research*, DOE Report NIPER-529, pp. 25-26, May 1991.
2. National Institute for Petroleum and Energy Research. *Quarterly Technical Report for April 1 - June 30, 1991, Vol. II, Energy Production Research*, DOE Report NIPER-545, p. 8, July 1991.

SURFACTANT-ENHANCED ALKALINE FLOODING FIELD PROJECT

Cooperative Agreement DE-FC22-83FE60149,
Project SGP41

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: July 18, 1990
Anticipated Completion: Sept. 30, 1993
Funding for FY 1991: \$318,000

Principal Investigator:
Troy R. French

Project Manager:
Thomas B. Reid
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this pilot project are (1) to obtain information and data that will help to demonstrate the applicability of surfactant-enhanced alkaline flooding as a cost-effective enhanced oil recovery (EOR) method, (2) to transfer the surfactant-enhanced alkaline flooding technology that has been developed under the sponsorship of the Department of Energy (DOE) to the petroleum industry, and (3) to obtain information regarding procedures for designing and applying this technology that will assist independent producers in sustaining production from mature producing oil fields rather than abandoning marginal wells.

Summary of Technical Progress

The Tucker sand of Hepler (Kansas) field is a Class I, fluvial dominated deltaic reservoir. Corefloods were performed with a surfactant-enhanced alkaline system that contains 0.5% Chaser XP-100 surfactant, 0.45% sodium tripolyphosphate (STPP), and sodium bicarbonate. Oil recovery was 54% of the original oil in place (OOIP), when small volumes of this chemical formulation were injected into cores that had high oil saturations and permeabilities that are similar to permeabilities in Hepler field. This represents realistic conditions since very little of the OOIP in Hepler field can be produced by waterflooding because of the high viscosity of this oil, and chemical flooding will be initiated at high oil saturations.

Application to EOR

Commercial and technological benefits will be achieved for all participants in the project if it is a success. The project will help move surfactant-enhanced alkaline flooding toward commercial reality in a Class I, fluvial dominated deltaic reservoir. However, the low permeability and heterogeneity of Class I reservoirs reduce the likelihood of mobilizing large amounts of tertiary oil in this field project. If successful, the project will increase oil production in the Midcontinent region of the United States and reduce the rate of resource abandonment.

Discussion

The site selected for the field test is in Hepler (Kansas) oil field. The Tucker sand of Hepler field is a Class I, fluvial dominated deltaic reservoir. Several chemical systems were tested this year for their ability to mobilize Hepler oil. Each of these chemical systems was optimized to provide the lowest possible interfacial tension (IFT) with Hepler oil. The IFT between three of these four systems and Hepler oil is shown in Fig. 1. The

Fig. 1 Interfacial tension between Hepler (Kansas) oil and optimized chemical formulations, 23° C.

optimization procedures and results with these systems have been discussed in detail in previous reports.¹⁻²

This quarter, several corefloods were conducted with the chemical system that contains 0.5% Chaser XP-100 surfactant, 0.45% sodium tripolyphosphate (STPP), and sodium bicarbonate. This chemical system was formulated with water from a water supply well located in Hepler field. The IFT behavior is shown in Fig. 1 for 1.2% and 1.6% sodium bicarbonate concentrations, both of which produce IFT behavior that is favorable for mobilization of residual oil. Several corefloods were conducted with this chemical system and are summarized in Table 1. Two floods conducted previously with another chemical system are also summarized in the same table. Comparison of corefloods RP-2, RP-3, and RP-16 shows that oil recovery with the chemical system that contains 0.5% Chaser XP-100 surfactant, 0.45% sodium tripolyphosphate (STPP), and sodium bicarbonate is as good as the chemical system previously tested.

TABLE 1
Summary of Corefloods Conducted with Hepler (Kansas) Oil

Coreflood	Core type ¹	K, mD	Preflush solution		First chemical formulation injected	
			Composition	Vol., PV	Composition	Vol., PV
RP-2	Berea	855	1.0 g NaCl/100 mL pH 9.5 carbonate mixture	0.25	1.0 g NaCl + 0.25 g B-110 + 0.15 g B-105 + 2.03 g 2-butanol/100 mL + pH 9.5 carbonate	0.75
RP-3	Berea	1240	same as above	0.25	same as above	0.75
RP-16	Berea	497	pH 8.3 STPP/carbonate mixture	0.25	0.5 g STPP + 1.6 g NaHCO ₃ + 0.5 g XP-100/100 mL	0.75
RP-18	Berea	1359	same as above	0.10	0.5 g STPP + 1.6 g NaHCO ₃ + 0.5 g XP-100/100 mL and 2000 ppm Flopaam 3230S polymer	0.20
RP-19	Berea	96	same as above	0.10	same as above	0.20
RP-20	Berea	92	same as above	0.10	same as above	0.20
Coreflood	Second chemical formulation injected		Recovery efficiency, %			
	Composition	Vol., PV	So _{wf} , %	So _{cf} , %	C F ²	Total ³
RP-2	3,500 ppm Flocon 4800 CX biopolymer	1.0	35.2	5.0	85.9	93.6
RP-3	same as above	1.0	45.1	7.2	84.1	91.1
RP-16	3,500 ppm Flocon 4800 CX biopolymer	1.0	48.9	8.3	83.1	90.3
RP-18	Graded concentration of Flopaam 3230S	0.15	45.0	32.6	27.5	61.4
RP-19	same as above	0.15	45.8	35.4	22.8	57.2
RP-20	same as above	0.15	NA	37.4	NA	53.9

¹ Cores were saturated with synthetic brine containing 1.022 g NaCl, 0.0388 g CaCl₂, and 0.0694 g MgCl₂·6H₂O / 100 mL.

² Recovery efficiency = (oil produced during chemical flood / oil remaining after waterflood) X 100.

³ Recovery efficiency = (oil produced during waterflood and chemical flood / original oil) X 100.

Large volumes (0.75PV) of surfactant-enhanced alkali were used in these three corefloods, and high-permeability Berea cores were used. Tertiary oil recoveries were 83 - 86% of the oil that remained in the cores after waterflooding (OIP). Figures 2 and 3 show, respectively, the injection strategies and changes in oil saturations for corefloods RP-3 and RP-16, when large volumes of the two chemical systems were used. Final oil saturations were in the 7-8% range which represents exceptionally good residual oil mobilization.

Coreflood RP-18 was performed to determine the effect of reducing the amount of surfactant-enhanced alkali that was injected. Coreflood RP-18 was performed in a high-permeability Berea core. The amount of surfactant-enhanced alkali injected was reduced to 0.20 PV in this coreflood. Tertiary oil recovery was reduced to 28% OIP (see Table 1). The chemical injection sequences and changes in oil saturations for corefloods RP-16 (large chemical volumes) and RP-18 (small chemical volumes) are shown in Figs. 3 and 4, respectively. Comparison of the two figures shows that reducing the injected volume of chemicals dramatically reduced oil production.

Fig. 2 Coreflood RP-3 oil saturation and effluent oil cut.

Fig. 3 Coreflood RP-16 oil saturation and effluent oil cut.

Fig. 4 Coreflood RP-18 oil saturation and effluent oil cut.

Coreflood RP-19 was performed to determine the effect of permeability, when small volumes of chemicals were injected. Permeability of this core was 96 mD, which is nearer to Tucker sand permeability. The effect of reduced permeability was to reduce the amount of tertiary oil recovered to 23% OIP.

Coreflood RP-20 was performed to determine the effect of injecting small volumes of surfactant-enhanced alkali before the core was waterflooded to residual oil. This is realistic, because the past history of Hepler field shows that very little of the oil in Hepler field can be produced by waterflooding alone. In this case, 53.9% of the original oil in place (OOIP) was produced by chemical flooding with small volumes of injected chemicals.

Observations and Conclusions

1. A chemical system that can be mixed in water from the supply water well recovered as much oil as chemical systems previously optimized in deionized water.
2. Oil recovery was reduced when the size of the chemical slug was reduced.
3. When this chemical system was tested for ability to mobilize oil at conditions similar to those in Hepler field (high oil saturation), oil mobilization was good.

References

1. National Institute for Petroleum and Energy Research. *Quarterly Technical Report for April - June 1991, Volume II, Energy Production Research*. DOE Report NIPER - 545, pp. 10-12, August 1991.
2. T. R. French, *Design of Chemical Formulation for Project SGP41*. DOE Report NIPER-530, May 1991.

GAS DISPLACEMENT— SUPPORTING RESEARCH

GAS MISCIBLE DISPLACEMENT

Cooperative Agreement DE-FC22-83FE60149,
Project BE5A

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$200,000

Principal Investigator:
Ting-Horng Chung

Project Manager:
Jerry F. Casteel
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this project are (1) to develop methods to mitigate the deleterious effects of solid precipitation in

gas flooding and (2) to determine the effect of porous media on gas-oil phase behavior.

Summary of Technical Progress

Prediction Technique Development for the Description of Asphaltene Deposition

There are two different approaches for asphaltene precipitation modeling. One approach is based on the assumption that asphaltenes are solid particles colloidally suspended in crude oil which are stabilized by the adsorbed resin molecules. When the resin molecules are sufficiently diluted by non-polar solvents, the asphaltene particles may aggregate mechanically or by electrical means. This concept is based mainly on titration experiments which demonstrate that once the adsorption equilibrium of resins between solid (asphaltene) and liquid phases is disturbed by adding paraffinic solvents, the asphaltene particles flocculate irreversibly. Based on this assumption, a colloidal model has been developed in this work and presented in the previous quarterly report. The other approach is based on the assumption that asphaltenes are dissolved in the oil in a true liquid state, and may precipitate as a result of changing thermodynamic conditions such as temperature, pressure, and composition. Thus, asphaltene precipitation is considered to be

thermodynamically reversible. The complete dissolution of some asphaltenes in some organic solvents such as toluene and benzene supports this assumption. The reversibility assumption implies that thermodynamic models can be used to describe asphaltic phase behavior. A simple thermodynamic model was proposed by Hirschberg, et al.¹ This model described the precipitation mechanism by polymer solution theory. The asphaltene molecules are considered to be similar in structure and behavior to polymer molecules. In this approach, a vapor-liquid equilibrium calculation using equation of state is conducted to determine the composition of liquid phase, and then the Flory-Huggins model is used to calculate the amount of asphaltene precipitated from the liquid phase, assuming this precipitation does not affect the vapor-liquid equilibrium.

Although this simplified model can be used to interpret experimental results, it conflicts with the experimental evidence that the asphaltene is not a homogeneous component. The molecular weight of precipitated asphaltene is distributed in the range from 1,000 to 500,000, and depends on solvent type and precipitation conditions. Experimental results show that the precipitated asphaltene is a mixture of molecular weights forming a virtually continuous distribution. In order to formulate a continuous mixture model for asphaltene, Mansoori et al. have proposed a continuous thermodynamic model²⁻³ by applying the Scott and Magat heterogeneous polymer theory.⁴

Both the homogeneous and heterogeneous models still cannot describe some of the solubility properties of asphaltenes such as the dissolution of solid asphaltene in some organic solvents. For example, n-heptane can dissolve part of a n-pentane precipitated asphaltene, and toluene can dissolve essentially all asphaltenes. A good model should be able to predict the solubility properties of asphaltenes for such simple binary or ternary systems as well as the more complicated systems.

In this work, a new model is developed based on the thermodynamics for solid-liquid equilibria.⁵⁻⁶ This model is general for all organic deposition and dissolution including wax, resins, and asphaltenes. It also gives molecular weight distribution of the precipitated solid phase. Following the same assumption as the previous two methods that the formation of solid phase do not affect the vapor-liquid equilibrium (VLE), a VLE calculation for the crude oil is performed to obtain the composition of liquid oil. With the known liquid oil composition, a liquid-solid equilibrium (LSE) calculation is then performed to obtain the composition of solid phase.

Assuming that the solid hydrocarbon mixture is in a solution form, at solid-liquid equilibrium, the fugacity of component i in solid phase, f_i^S , must be equal to the fugacity of the same component i in liquid phase, f_i^L .

$$f_i^S = f_i^L \quad (1)$$

where the fugacities of the i -th component in solid and liquid phases are defined by:

$$f_i^S = \gamma_i^S x_i^S f_i^{\circ S} \exp \left[\int_0^P \frac{v_i^S dP}{RT} \right] \quad (2)$$

$$f_i^L = \gamma_i^L x_i^L f_i^{\circ L} \exp \left[\int_0^P \frac{v_i^L dP}{RT} \right] \quad (3)$$

where γ_i , x_i , and f_i° are the activity coefficient, mole fraction, and standard state fugacity of component i . The superscript S stands for solid phase, and L for liquid state.

The solid-liquid equilibrium coefficient, K_i^{SL} , is then derived by combining Eqs. 1, 2, and 3,

$$K_i^{SL} = \frac{x_i^S}{x_i^L} = \left(\frac{\gamma_i^L}{\gamma_i^S} \right) \left(\frac{f_i^{\circ L}}{f_i^{\circ S}} \right) \exp \int_0^P \frac{\Delta v_i dP}{RT} \quad (4)$$

where $\Delta v_i = v_i^L - v_i^S$. The first term in this equation represents the effect of composition in both phases on K_i^{SL} , the second term stands for the temperature effect, and the last term is the pressure effect. Thus, Eq. 4 is a general representation for a solid-liquid equilibrium constant.

The relation between the standard state fugacity of component i in the solid phase, $f_i^{\circ S}$, and that in the liquid phase, $f_i^{\circ L}$, can be derived by calculating the Gibbs energy change of pure component i from solid to liquid.⁵⁻⁶

$$\ln \left(\frac{f_i^{\circ L}}{f_i^{\circ S}} \right) = \frac{\Delta h^f}{RT} \left(1 - \frac{T}{T^f} \right) + \frac{\Delta C_P}{R} \left[1 - \frac{T}{T^f} + \ln \frac{T^f}{T} \right] \quad (5)$$

where Δh^f is the latent heat of fusion, T^f is the fusion temperature, and ΔC_P is the difference of heat capacity between the two phases. The second term is usually very small and can be neglected, and the fusion temperature, T^f , for high molecular-weight asphaltenes is so high that the term of T/T^f can be neglected except at high temperatures. Won¹ has developed correlations for the fusion temperature and the heat of fusion as functions of molecular weight from C₁₀ to C₇₀. His correlations will be extended to higher molecular weight components.

In Eq. 4, the activity coefficient, γ_i^S , of component- i in the solid phase is assumed to be equal to unity. A

thermodynamic model for the liquid phase activity coefficient, γ_i^L , was proposed in a previous report,⁷ i.e.,

$$\ln \gamma_i^L = \frac{v_i}{RT} (\delta_m - \delta_i)^2 + \ln \frac{\phi_i}{x_i} + 1 - \phi_i - \sum_{k \neq i}^N \frac{v_i}{v_k} \phi_k \quad (6)$$

where the solubility parameter, δ_i , and volume fraction, ϕ_i , for each component i in liquid phase are defined as,

$$\delta_i = \left(\frac{\Delta H^v - RT}{v} \right)_i^{1/2} \quad (7)$$

$$\phi_i = \frac{x_i v_i}{\sum_j x_j v_j} \quad (8)$$

and the average solubility parameter, δ_m , is

$$\delta_m = \sum \phi_i \delta_i \quad (9)$$

Under no significant change in pressure, combining Eqs. 4, 5, and 6, gives

$$K_i^{SL} = \exp \left[\frac{\Delta h_i^f}{RT} (1 - T/T_i^f) + \frac{v_i^L}{RT} (\delta_m^L - \delta_i^L)^2 + \ln \frac{\phi_i^L}{x_i^L} + 1 - \phi_i^L - \sum_{k \neq i}^N \frac{v_i^L}{v_k^L} \phi_k^L \right] \quad (10)$$

The liquid-solid equilibrium calculation is then performed by solving the following mass balance equations with Eq. 10 simultaneously,

$$F^{SL} = \sum x_i^S - \sum x_i^L = \sum \frac{z_i (K_i^{SL} - 1)}{[1 + \sum_F (K_i^{SL} - 1)]} = 0 \quad (11)$$

$$x_i^L = z_i / \left[1 + \sum_F (K_i^{SL} - 1) \right] \quad (12)$$

$$x_i^S = z_i K_i^{SL} / \left[1 + \sum_F (K_i^{SL} - 1) \right] \quad (13)$$

where z_i , x_i^L , and x_i^S are the mole fractions of component i in the crude oil (before precipitation), the equilibrium liquid oil (after precipitation) phase, and the precipitated

solid phase, respectively. S/F is the mole fraction of solid (precipitated phase) to feed (crude oil). The onset of asphaltene flocculation is the point at which the solid fraction (S/F) approaches zero. This model has been demonstrated to be accurate for wax formation prediction. The computing procedure and results were previously reported.⁷ For asphaltene precipitation prediction, the computing procedure is the same. The only difficulty is in the characterization of asphaltenes. A more detailed compositional analysis for the crude oil, which gives actual asphaltene composition and molar distribution in crude oil, is required. Two techniques: the pseudo-component method and the continuous thermodynamic method can be used to represent the C₇₊ fraction of crude oil. To determine the molar distribution of asphaltenes in solid and liquid phases, the continuous thermodynamic technique has to be employed.⁸ A thorough test of this model will be conducted in FY92 as the required data of oil analysis become available.

References

1. A. Hirschberg, L. N. J. deJong, B. A. Schipper, and J.G. Meijer. Influence of Temperature and Pressure on Asphaltene Flocculation. *Soc. Pet. Eng. J.*, pp. 283-293, June 1984.
2. G. A. Mansoori and T. S. Jiang. *Asphaltene Deposition and Its Role in Enhanced Oil Recovery Miscible Gas Flooding*. Pres. at the 3rd European Conf. on EOR, Rome, Italy, April 1985.
3. S. Kawanaka, S. J. Park, and G. A. Mansoori. *The Role of Asphaltene Deposition in EOR Gas Flooding: A Predictive Technique*. SPE/DOE paper 17363 presented at the SPE/DOE Sym. on EOR, Tulsa, Okla., Apr. 17-20, 1988.
4. R. L. Scott and M. Magat. The Thermodynamics of High-Polymer Solutions: I. The Free Energy of Mixing of Solvents and Polymers of Heterogeneous Distribution. *J. Chem. Phys.*, 13(5), pp. 172-177, May 1945.
5. K. W. Won. *Continuous Thermodynamics for Solid-Liquid Equilibria: Wax Formation from Heavy Hydrocarbon Mixtures*. Pres. at AIChE Spring National Meeting, Session 1A, Mar. 24-28, 1986, Houston, TX.
6. J. M. Prausnitz. *Molecular Thermodynamics of Fluid-Phase Equilibria*. Prentice-Hall Inc., Englewood Cliffs, NJ, 1969.
7. T-H. Chung, P. Sarathi, and R. Jones. *Modeling of Asphaltene and Wax Precipitation*. DOE Report NIPER-498, 1991.
8. T. P. J. Halpin and N. Quirke. A New Method of Continuous Thermodynamics Applied in an Equation of State. *Soc. Pet. Eng. Reservoir Engineering*, pp. 617-622, November 1990.

DEVELOPMENT OF METHODS TO IMPROVE MOBILITY CONTROL AND SWEEP EFFICIENCY IN GAS FLOODING

Cooperative Agreement DE-FC22-83FE60149,
Project BE5B

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: October 1, 1983
Anticipated Completion: September 30, 1991
Funding for FY 1991: \$440,000

Principal Investigators:
Clarence Raible
Ting-Horng Chung

Project Manager:
Jerry F. Casteel
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this project are: (1) for entrainers: address the critical issues that remain before their application in field trials can be justified. These issues include identifying the best class of compounds from which to choose the most cost-effective entrainers and identifying the best injection strategy for entrainers in gas flooding. For the latter, cyclic CO₂ processes will also be tested for potential near-term applications; (2) for other additives: evaluate unique approaches to improving sweep efficiency in gas flooding EOR processes. This year, precipitation of polymers and use of additives such as perfluorinated alkanes will be evaluated for potential mid-term applications; and (3) for foam: initiate studies to evaluate foam flow behavior in radial corefloods. Although many researchers have studied foam for mobility control, very few have actually studied the flow of foam under radial flow conditions—conditions more typical of oilfield environments.

Summary of Technical Progress

Experimental Results of Physical Properties Measurements

Cosolvents used for this study were propane, cyclohexanol, and isooctane. Fig. 1 shows the density and viscosity results of isooctane-CO₂ mixtures at miscible conditions of 60° C and 2,200 psia. As the concentration of isooctane increased, mixture density increased until the fluid density leveled at about 30 wt % with a density of 0.73 g/cm³. A density of 0.68 g/cm³ was measured for

liquid isooctane at 60° C and 2,200 psia. Also shown in Fig. 1 mixture viscosity increased with higher isooctane concentration. At 40 wt % of isooctane, the viscosity of the mixture measured 0.11 cP, a 140% increase in viscosity. A curve fit of the viscosity data was used to project and estimate the apparent viscosity at a 100% concentration of isooctane. This projection indicated a viscosity of about 0.34 cP for pure isooctane. This is a value which is close to the viscosity of liquid isooctane at 60° C (see Table 1). A viscosity of 0.4 cP was measured for isooctane at 2,200 psia and 60° C.

Viscosity and density data for cosolvent mixtures of 2-ethylhexanol from a previous study¹ also indicated a leveling of mixture density at a blend concentration of about 25 wt % of 2-ethylhexanol. The level density of 0.86 g/cm³ was also slightly above the measured liquid density of 0.833 at 20° C. A curve fit of the viscosity data gave a projected viscosity of 3.4 cP at a 100% concentration of 2-ethylhexanol. These values are also reasonably close to the density (0.835 g/cm³) and the viscosity (5.3 cP) measured for 2-ethylhexanol at a temperature of 40° C and 2,200 psig.

Inspection of data, shown in Fig. 1 and from reference 1, reveals that critical gas phase mixtures of 2-ethylhexanol had a much greater increase in viscosity and higher density than isooctane mixtures. Comparison of the fluid mixtures indicates that the more dense and viscous liquid had a higher viscosity in the miscible gas phase. The data suggest that to obtain the maximum effect for increasing the gas phase viscosity, it would be desirable to use a highly viscous fluid.

On the basis of higher density and viscosity, cyclohexanol was selected as a candidate cosolvent (see Table 1). The results of gas phase mixtures of cyclohexanol are listed in Table 2. At 2,450 psi and 40.8° C, a maximum concentration of 3.3 mol % (7.3 wt %) was measured in the gas phase saturated with cyclohexanol. The solubility of this compound was limited even at these conditions of relatively low

TABLE 1

Viscosity and Physical Properties of Cosolvents
Extrapolated from the Literature²⁻³

Compound	Viscosity (cP) (at specified temperature)			Density (20° C), g/cm ³	MW, g/mole
	20° C	40° C	60° C		
Isooctane	0.50	0.41	0.34	0.6919	114.23
2-Ethylhexanol	9.8	4.4	—	0.8332	130.23
Cyclohexanol	68.0	23.5	—	0.9624	100.16

Fig. 1 Viscosity and density of isooctane and CO₂ mixtures at 60° C and 2,200 psig.

TABLE 2

Viscosity and Density of CO₂ + Cyclohexanol Mixtures at 40.8° C and 2,450 psia

Mole fraction	Wt. fraction	Mixture Density, g/cm ³	Density Increase, %	Mixture Viscosity, cP	Viscosity Increase, %
0.000	0.000	0.7987	0.0	723.3	0.0
0.030	0.065	0.8455	5.8	870.1	22.0
0.033	0.073	0.8509	6.5	939.3	31.7

temperature and high pressure. At the conditions of gas phase saturation, the gas phase density was 6.5% higher, and viscosity increased 32% above pure CO₂ at these conditions. However, because of the limited solubility in the CO₂-rich phase, cyclohexanol should not be considered a good cosolvent candidate for reservoir applications. Cosolvent miscibility is a factor which must be considered in selection of candidate cosolvents.

Additional experiments were performed to measure the physical properties of propane-CO₂ mixtures. As shown in Fig. 2, a 30 mol % propane blend had a higher viscosity than pure CO₂ at a temperature of 60° C. The increase in viscosity changed with pressure from approximately 30% at 1,600 psia down to about 11% at 2,500 psia. Relative density of the blend also changed with pressure. As shown in Fig. 2, the density of the blend was about 20% greater than that of CO₂ at 1,600 psi and the relative density decreased with higher pressure where the density at 2,500 psi was less than that of CO₂ by about 12%. This relative decrease in viscosity and density with pressure was probably related to a difference in compressibility of CO₂ and propane. With increasing pressure, the more compressible CO₂ had a greater change in density and viscosity.

Other experiments were performed to measure the effect of propane as a cosolvent for the extraction of higher molecular weight hydrocarbons. Hexadecane was used as

the liquid or oil phase at a test temperature of 60° C. For comparison, the relative change in viscosity and density with pure CO₂ extraction of n-hexadecane is presented in Fig. 3. The figure shows the increase in gas phase density and viscosity due to CO₂ extraction of n-hexadecane with increasing pressure from 1,600 to 2,500 psia.

The results of a 30 mol % propane blend as a cosolvent are presented in Fig. 4. Curves from Figs. 2 and 3 also are shown for comparison. There was a small improvement in gas phase viscosity of the propane blend extraction over that by pure CO₂ extraction. However, it appeared that most of the increase was due to the higher viscosity of the propane blend and not the result of n-hexadecane extraction into the gas phase. Density data appeared to confirm the small quantity of n-hexadecane extraction. Only a small increase in density (less than 3%) was measured when compared with the original blend density.

Discussion of Physical Properties Results

Cosolvents can increase the viscosity and density of the gas phase by (1) direct solubility of a more dense and viscous cosolvent, or by (2) increased extraction of hydrocarbons into the gas phase. The experimental results show an interesting relationship between cosolvent mixtures and liquid cosolvent properties. First, the critical phase density will not significantly exceed the cosolvent liquid density even at high cosolvent concentrations. Second, cosolvents with high liquid viscosities will have a higher critical phase viscosity when compared to lower viscosity liquids. Although, viscosities will be influenced by the relative gas phase compressibilities of different cosolvents, this relationship can provide a guide in understanding the role of a cosolvent on the physical properties of cosolvent mixtures.

To obtain the maximum effect for increasing the gas phase viscosity with a cosolvent, it would be desirable to use a highly viscous liquid. Inspection of the literature reveals virtually no highly viscous compounds which meet all the criteria to significantly improve gas phase viscosity. For gas floods at reservoir conditions, most viscous compounds can be eliminated as cosolvents because of the requirement for high cosolvent solubility in the CO₂ gas phase. Cyclohexanol and other compounds, such as ethylene glycol,⁴ glycerol,¹ and n-decanol,¹ were not viable cosolvent candidates because they were not sufficiently soluble in the gas phase. Also, ethylene glycol and glycerol are polar compounds which have a high solubility in brine, an undesirable property for reservoir applications. On the basis of high liquid viscosity, cyclohexanol appeared to be a potential cosolvent candidate. However, limited solubility in the gas phase as well as appreciable brine solubility are factors that eliminate cyclohexanol from consideration as a cosolvent.

Previous studies¹ suggest that 2-ethylhexanol was a potential cosolvent. To some extent 2-ethylhexanol has unique properties. This compound's alcohol group

Fig. 2 Density and viscosity of a 30 mol % blend of propane and CO₂ measured at 60° C.

Fig. 3 Density and viscosity of n-hexadecane extraction with CO₂ at 60° C.

Fig. 4 Viscosity and density of n-hexadecane extraction with a 30 mol % propane/CO₂ blend at 60 C.

contributed to a fluid with a high viscosity. Also, the large branched paraffin group produced a compound that is soluble in the gas phase with relatively low solubility in brine. A compound, such as 2-ethylhexanol, will have a relatively high molecular weight and high boiling point. These compounds will partition between the vapor phase and to a larger extent partition into the crude oil liquid phase. Cosolvent partitioning into the oil phase is another factor that must be considered for cosolvent application in a reservoir. Additional studies were performed to compare enhanced heavy hydrocarbon extraction with cosolvent mixtures. The experimental results of a 30 mol % propane mixture indicated a higher viscosity due to the presence of propane in the gas phase. Gas phase extraction of n-hexadecane using a propane cosolvent mixture indicated only a minor increase in density and viscosity. Most of the change in physical properties was due to the properties of the cosolvent blend. Extracted hydrocarbons appeared to have less effect on increasing vapor phase viscosity than the solubility of the cosolvent.

Summary

In summary, cosolvents must have an appreciable solubility in carbon dioxide in order to effectively improve properties of the gas phase. Physical property studies suggest that the vapor phase solubility of the cosolvent is more important for improvement of gas phase viscosity than enhanced extraction of heavier hydrocarbons from a liquid or oil phase. Also, there appeared to be a relationship between the cosolvent liquid phase properties and the critical phase properties of density and viscosities. However, for extraction studies, the actual contribution of each of these factors for improvement in gas phase viscosity was complicated by the quantity of cosolvent that partitions into the oil phase. Cosolvent partitioning into the oil phase is a factor that must be considered for gas

flood applications in a reservoir. No attempt was made in these physical property studies to evaluate the effect of cosolvent loss due to partitioning into the oil phase. The results of coreflood experiments⁵ were reported to demonstrate that a higher molecular weight cosolvent will partition into the oil remaining in the reservoir during the CO₂ displacement process. These experiments were conducted using isooctane as the cosolvent. A large fraction of the cosolvent was bypassed even though the core-flood was limited in length (2 ft). In a reservoir, this will result in bypassing of the secondary cosolvent as the gas flood progresses through the reservoir. These corefloods indicate that higher molecular weight compounds are not viable candidates as cosolvents which largely partition into the oil phase at these conditions.

References

1. F. M. Llave and F. T. H. Chung. *The Use of Entrainers for Improving Mobility Control and Displacement Efficiency*. DOE Report NIPER-362, September 1988 (NTIS order No. DE89000704).
2. J. A. Dean. *Lange's Handbook of Chemistry*. McGraw-Hill Book Company. 12th Ed. 1979
3. R. C. Weast and M. J. Astle. *CRC Handbook of Chemistry and Physics*. 60th Ed. CRC Press, Inc. Boca Raton, Florida, 1980
4. A. Strycker and F. M. Llave. *Improvement of Sweep Efficiency and Mobility Control in Gas Flooding*. DOE Report NIPER-502, 28 pp., April 1991.
5. National Institute for Petroleum and Energy Research, *Quarterly Technical Report for April 1-June 30, 1990, vol. II, Energy Production Research*, DOE Report NIPER-545, July 1991.

THERMAL RECOVERY— SUPPORTING RESEARCH

THERMAL PROCESSES FOR LIGHT OIL RECOVERY

**Cooperative Agreement DE-FC22-83FE60149,
Project BE11A**

**National Institute for
Petroleum and Energy Research
Bartlesville, Oklahoma**

**Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$300,000**

**Principal Investigator:
David K. Olsen**

**Project Manager:
Thomas B. Reid
Bartlesville Project Office**

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this research are as follows: (1) to analyze the semianalytical numerical predictive model for

its applicability to predict light oil steamflooding behavior; (2) to analyze potential override and fingering tendencies in a 2-D model using oil and sand from Teapot Dome (Wyoming) field and compare steamflood performance with that from other light oil steamfloods; (3) to expand the evaluation of steam diverters for the light oil steamflood being conducted in the Shallow Oil Zone at NPR No. 1, Elk Hills (California); and (4) to transfer technology to others in the field of thermal oil production by participating in the Annex IV meetings between the Department of Energy (DOE) and the Venezuelan Ministry of Energy and Mines.

Summary of Technical Progress

Three tasks were pursued this quarter. The first task included the evaluation of the applicability of a semi-analytical thermal predictive model for use in light oil steamflooding. The second included design and construction of an X-ray CT scannable steamflood physical model. Parts for the model have been assembled including a data collection system, and controllers are being incorporated into the current 2-D steamflood model and the new steamflood model, which is expected to be operational in the second quarter of FY92.

The third task involved preparation and presentation of four reports. Two reports were presented at the UNITAR/UNDP 5th International Conference on Heavy

Crude and Tar Sands,¹⁻² and two topical reports³⁻⁴ were prepared for DOE. A portion of the work on the effect of wettability on steamflood oil recovery¹⁻³ is summarized as follows:

A series of steamflood experiments was conducted in a two-dimensional model using water-wet, intermediate-wet, and oil-wet porous media to investigate the steamflood potential for light oil production after waterflooding. The study evaluated the effects of changes in wettability on steamflood light oils. New London crude oil (32° API) was used in the study. Comparisons of the oil saturation profiles of the sandpacks indicated higher initial oil saturations in oil-wet sandpacks. However, waterflooding recovered less oil at a slower rate and lower oil-water ratio from oil-wet sands. Oil-wet sands showed much higher residual oil saturation after reaching waterflood residual. Steamfloods initiated at this point displaced little oil from water-wet sandpacks. However, significant oil was displaced from oil-wet sandpacks.

Laboratory waterfloods of water-wet systems behave very differently from those of oil-wet systems. In strongly water-wet porous media, oil recovery at water breakthrough is high, with little additional oil production after water breakthrough. In strongly oil-wet porous media, water breakthrough occurs much earlier, and most of the oil recovered is slowly displaced during an extended waterflood with a low oil/water ratio. This parallels what is observed in waterfloods of most sandstone reservoirs; waterfloods are less efficient in oil-wet reservoirs than in water-wet reservoirs because more water must be injected to recover the same amount of oil. As porous media becomes more oil-wet, the water relative permeability increases, and the oil relative permeability decreases. Water flows more easily than oil causing progressively earlier breakthrough and lower economic oil recovery.⁵

Most light oil reservoirs are waterflooded after primary production. To investigate the steamflood oil recovery potential after waterflooding, a series of experiments was conducted in a 2-D sandpack packed with quartz sands of various wettabilities. The experiments incorporated strongly oil-wet porous media (silylated quartz sand prepared from vapor-phase silylation with bis(dimethylamino)dimethyl silane,^{1,3} quartz sand that had been silylated to yield a surface of intermediate wettability, and untreated very strongly water-wet quartz sand. The effects of wettability are illustrated by the oil production and decline curves in Figs. 1 through 4. The oil-wet quartz sand yielded a high initial and high waterflood residual oil saturation (Figs. 1 and 4). Quartz sands of intermediate wettability showed lower initial and intermediate waterflood residual oil saturation, but they were steamflooded to a low residual oil saturation (Figs. 2 and 4). Water-wet quartz sand resulted in the lowest initial oil saturation, the lowest oil saturation after waterflood, and the lowest oil production by steamflood (Figs. 3 and 4). In each experiment, waterfloods were conducted until the water cut was greater than 97% before the start of steam injection. In the case of the oil-wet sand, the oil saturation continued

to drop as steam was injected and the water, sand, and oil were heated. The oil-water ratio abruptly increased just before steam breakthrough in the cases of intermediate and oil-wet sands. During the steamflood, the most significant oil production was seen in those sandpacks which were more oil-wet. When compared with intermediate wet sands, the oil saturation decline curve for the oil-wet sands did not decrease as sharply as expected. Comparison of the oil saturation profiles of these sandpacks indicates that waterflooding recovers more oil from sands that are more water-wet. These results from 2-D sandpacks indicate that oil recovery by steamflood of oil-wet sands looks promising.

Fig. 1 Oil production from a 2-D model packed with strongly oil-wet quartz sand, waterflood followed by steamflood.

Fig. 2 Oil production from a 2-D model packed with intermediate-wet quartz sand, waterflood followed by steamflood.

Fig. 3 Oil production from a 2-D model packed with water-wet quartz sand, waterflood followed by steamflood.

Fig. 4 Comparison of oil production from 2-D models, waterflood followed by a steamflood, in oil-wet, intermediate-wet, and water-wet quartz sandpacks.

References

1. D. K. Olsen, and M. E. Crocker. *Evaluation of Artificially Wetted Surfaces for Use in Laboratory Steamflood Experiments*. Presented as paper 109 at UNITAR/UNDP V International Conference on Heavy Oil and Tar Sands, Caracas, Venezuela, Aug. 4-9, 1991.
2. D. K. Olsen, M. E. Crocker, P. S. Sarathi and J. Betancourt. *Effects of Elevated Temperatures on Capillary Pressure and Wettability*. Presented as paper 110 at UNITAR/UNDP V International Conference on Heavy Oil and Tar Sands, Caracas, Venezuela, Aug. 4-9, 1991.
3. D. K. Olsen. *Light Oil Steamflooding—Effect of Wettability on Steamflood Performance*. DOE Report NIPER-552, September 1991.

4. S. M. Mahmood, D. K. Olsen and E. B. Ramzel. *Evaluation of Surfactants as Steam Diverters/Mobility-Control Agents in Light Oil Steamfloods: Effect of Oil Composition, Flow Rates and Experimental Conditions*. DOE Report NIPER-554, September 1991.
5. W. G. Anderson. *Wettability Literature Survey—Part 6. Effects of Wettability on Waterflooding*. *J. Pet. Tech.*, pp. 1605-1622, December 1987.

THERMAL PROCESSES FOR HEAVY OIL RECOVERY

Cooperative Agreement DE-FC22-83FE60149,
Project BE11B

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$250,000

Principal Investigator:
Partha Sarathi

Project Manager:
Thomas B. Reid
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives, scope of work, and milestones for this project have been modified to reflect the current "near-term" research priorities of the Department of Energy (DOE) Oil Research Implementation Plan. The revised project objectives for FY91 are as follows: (1) to expand and improve the thermal (steam) field operator's guide started in FY90; (2) to improve the predictive capability of the current numerical laboratory thermal simulator; (3) to upgrade the existing 2-D steamflood physical model; and (4) to enhance NIPER's thermal simulation capability.

Summary of Technical Progress

Compilation of the Steamflood Operators' Guide

The objective of developing a steamflood operators' guide is to provide independent operators considering the

use of steam to increase recovery with a ready reference that helps to answer questions on thermal oil recovery and undertake feasibility studies. The emphasis is on practical aspects of the process and on those factors that affect the technology and economics of oil recovery with steam. Information for the guide is being assembled through review of the open literature, supplemented by information from steamflood operators and equipment vendors.

This quarter, four chapters: "Steam Injection Economics," "Steam Distribution," "Cementing," and "Heat Losses and Insulated Tubulars" were written. Following is a brief overview of these chapters.

Steam Injection Economics and Costs

Enhanced recovery operations such as steamflooding on a fieldwide basis differs from secondary recovery operations, such as waterflooding, in that:

Much more effort must go into the design of a project. During the start-up of a project more attention must be focused on monitoring the process.

Special monitoring equipment unfamiliar to field engineers may be necessary. This implies training programs for supervisors, engineers, and operating personnel.

Fuel storage and adequate water supply are critical. These and other factors such as oil price significantly impact the economics of steam injection projects. This chapter briefly outlines the factors influencing the economics of steam injection and the cost of conducting a steam project.

Steam Distribution

In the past, the steam distribution network was considered merely the pipeline between steam generating equipment and injection wells. In recent years, it has been demonstrated that the network can behave as an unreliable and even unpredictable phase separator delivering high quality (100%) steam to one well and, at the same time, delivering low quality steam to another well on the same distribution line. Hence a steam distribution network must be designed so as to provide the desired steam quality at the desired flow rate to each injection well in the network.

A steam distribution network consists of the following major components: (1) Main headers; (2) Lateral steam lines; (3) wellhead steam rate controls; and (4) wellhead assembly. The design of a steam distribution system is based on the following factors:

1. The expected rate of delivery of steam to each injection well.
2. The expected system operating pressure. (This will be primarily a function of the expected reservoir injection pressure.)
3. The desired steam quality at each injection well.

The discussion within this chapter is organized into the following sections:

- a. General system pressure and temperature design requirements

- b. Wellhead assembly
- c. Lateral steam lines
- d. Support of steam lines
- e. Insulation and heat loss
- f. Effects of branching on steam quality
- g. Main steam headers
- h. Support for steam headers
- i. Expansion of the steam headers
- j. Control of individual well steam quality
- k. Maintenance and monitoring

Cementing

Thermal recovery wells are frequently less than 2,000 ft in depth. As a result, initial downhole conditions are similar to that of other shallow wells, and cement placement techniques required are also similar. However, formations associated with steamflood wells are frequently problematic. Weak and unconsolidated zones with low fracture pressures and high permeability are often present, and as a result lost circulation and fluid loss problems are often encountered. To prevent damage to a weak formation during cementing, low density cement slurries are necessary.

When heat is supplied to a well, the temperature rises. To maximize the delivery of heat to the pay zones, an insulating cement is desirable in steamflood wells. Also, strength stability is of even greater concern in steam injection wells due to the intermittent nature of steam injection operation in cyclic wells. The cementing composition after setting may undergo alternate periods of heating and cooling with temperature ranging from normal formation temperature up to 600° F.

To provide a complete, competent cement sheath in steam injection wells, proper cement formulation is needed. Cements in normal use in steam injection operations have been developed over the years. Cements typically used are API class A, G or H cement with 30 to 60% silica flour (by weight) added to halt strength retrogression. To improve the bonding properties of the cement, 10% or more by weight of sodium chloride is added to the mixing water. Sodium chloride improves the expansive properties of the cement which aids in achieving the necessary initial bond. Salt also improves the bonding to shales and bentonitic sands.

Given a good composition of thermally stable, bondable cement, the cement must then be properly placed. Bond logs have shown that chemical preflushes ahead of the cement job help to improve bonding. The chemical preflush consists of surfactant and mud thinners. When circulated at low velocity, a preflush helps remove the drilling mud and promote good bonding of cement to the formation and casing. Because of great variation in mud systems, preflush should be designed for the particular mud system in use. To ensure a good cement job, the pipe should be equipped with floating and guiding equipment and enough centralizers to produce a uniform sheath of cement.

Insulated Tubulars

Heat losses in a steam injection well can be very detrimental to a steamflood project. Unless efforts are made to minimize losses, the economics of the project can be severely impacted by increased energy costs, and for deep reservoirs, the steam quality can be reduced to an unsatisfactory level. High heat losses can also raise casing temperatures to a level that risks failure under the stress of thermal expansion.

Insulated tubing is frequently used to minimize heat loss in an injection well and maximize downhole steam quality. This will also lower longitudinal expansion and thermal stress in casing.

The object of this chapter is to discuss briefly wellbore heat losses and how they can be minimized using insulated tubing. The topics discussed include: (1) wellbore heat losses; (2) advantages of using insulated tubing; (3) insulated tubing design requirements; (4) insulated tubing construction and selection criteria; (5) insulated tubing installation procedure; (6) insulated tubing performance; and (7) insulated tubing cost effectiveness.

As an example of the benefits of insulated downhole, steam injection tubing overall heat losses were evaluated for uninsulated 2 7/8-in. tubing and similar insulated tubing in 7-in. casing. The use of insulated tubing can reduce wellbore heat loss by over 70% compared to uninsulated tubing.

An example of the cost effectiveness of insulated tubing is also presented. The case chosen is for a well 3,000 ft deep, and the steam temperature and pressure are 596° F and 1,500 psia, respectively. It was found that insulated tubing should pay out in short time as a result of savings of fuel used to generate steam. The payout time depends on oil price, well depth, and steam injection rate.

Evaluation of SUPRI Semianalytical Thermal Predictive Model

The semianalytical model developed at Stanford University to predict steamflood oil and water production was investigated. The model's predictive capability was evaluated by comparing the model's results with actual production data for four field cases. The following conclusions were derived from this study.

The model grossly overestimates field production rates. Predicted production rate data have little resemblance to observed production data. The model results in an 'oil kick' almost instantly after the start of steam injection and reaches peak production rate thereafter. Peak production rates are orders of magnitude higher than observed values. It is suspected that this behavior is likely due to assumptions used in the development of the model and the way the zone saturations are being calculated.

Because of its poor predictive capability, this model is not recommended for use as a screening tool for the selection of steamflood candidates. However, the model

may be useful for predicting laboratory steamflood behavior.

FEASIBILITY STUDY OF HEAVY OIL RECOVERY IN THE MIDCONTINENT REGION (OKLAHOMA, KANSAS, MISSOURI)

Cooperative Agreement DE-FC22-83FE60149,
Project SG237

National Institute for
Petroleum and Energy Research
Bartlesville, Oklahoma

Contract Date: Apr. 1, 1990
Anticipated Completion: June 1, 1992
Funding for FY 1991: \$603,440

Principal Investigator:
David K. Olsen

Project Manager:
Thomas B. Reid
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this feasibility study are (1) to investigate the known heavy oil resources from available informational sources in the Midcontinent, (2) to screen this resource for potential thermal or other enhanced oil recovery (EOR) application, and (3) to evaluate various economic facets that may impact the development of this resource. If the study determines that expansion of production of heavy oil is economically possible by recent advances in technology, recommendations will be made to facilitate the production of this additional resource within the next 1 to 3 years.

Summary of Technical Progress

The Permian Basin covering parts of eastern New Mexico and West Texas has been a prolific light oil producing area but has produced little heavy oil. With the exception of a few select reservoirs, heavy oil is not a major resource; a few reservoirs have produced greater than 40,000,000 barrels of heavy oil by solution gas drive and waterflooding. Although somewhat conflicting, data in the public literature suggest that much of this oil was in the 20° to 25° API gravity range. Significant heavy oil development is not anticipated in the future in the Permian basin. One of the attributes of the basin is the growing

resource that is developing as a result of development of technology for miscible and immiscible EOR displacement of light oil. In the future, development of some of the heavy oil reservoirs may be possible, many of which have API gravities in the 18° to 20° range.

NIPER engineers are finding that many of the previous studies have overestimated both heavy oil in place and heavy oil produced because states and operators report total oil and have little interest or reason to separate light and heavy oil produced. Current studies of U.S. heavy oil reservoirs indicate that Midcontinent, Permian, and Appalachian basins will be minor contributors to future heavy oil production. The major factor in these basins is the consolidated nature of the reservoir rock. The producing formations are older and typically have lower permeability than most heavy oil reservoirs currently being produced. The sandstone reservoirs, both unconsolidated and consolidated, and the carbonate reservoirs of the U. S. Gulf Coast are typically more numerous and have larger oil-in-place deposits. If the United States is to significantly increase heavy oil production, the U. S. Gulf Coast unconsolidated reservoirs extending from south Texas to western Florida and including the heavy oil fields occurring in the Nacatoch and Tokio formations in Arkansas are most likely heavy oil reservoirs to be developed with current thermal enhanced oil recovery (TEOR) technology.

While the analysis of the U. S. Gulf Coast basins is in progress and data collection is being conducted on other geologic basins in the U. S., comparisons are being made with heavy oil production in California.¹ Figure 1 shows the contribution that heavy oil has made to California total oil production. Over the past 50 years, California has been able to nearly double oil production, and heavy oil production has increased from 20 to 30% in the 1940s-1950s to 70% of the total oil production in the last half of the 1980s. Oil production corresponds with the number of producing wells, as shown in Fig. 2. Figure 3 shows the contribution for each API oil gravity range to the total production during the past 15 years. At a time when domestic oil production is rapidly declining, heavy oil has bolstered California's oil economy.

Reference

1. Conservation Committee of California Oil Producers. *Annual Review of California Oil and Gas Production*, Volumes corresponding from 1975 to 1990.

Fig. 1 California oil production since 1940 showing the total percent of heavy oil.

Fig. 2 California oil production since 1940 showing oil production corresponding with the number of active oil wells.

Fig. 3 California production showing major contribution of heavy oil and the percentage of oil in each API gravity range.

GEOSCIENCE TECHNOLOGY

IMAGING TECHNIQUES APPLIED TO THE STUDY OF FLUIDS IN POROUS MEDIA

Cooperative Agreement DE-FC22-83FE60149,
Project BE12

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contact date: Oct. 1, 1987
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$545,000

Principal Investigator:
Liviu Tomutsa

Project Manager:
Robert E. Lemmon
Bartlesville Project Office

Reporting Period: July. 1 - Sept 30, 1991

Objectives

The objectives of this research are as follows: (1) to develop a methodology to derive reservoir engineering

parameters from petrographic, computed tomography (CT) scanning, and nuclear magnetic resonance (NMR) images; (2) to apply state-of-the-art technology as it is developed to provide field support to characterize high-priority reservoirs; (3) to transfer the newly developed technology.

Summary of Technical Progress

The CT scanner has been used in support of other base programs to measure petrophysical core properties and fluid saturations in enhanced recovery experiments.

We continued to perform CT scans of whole diameter cores from the Almond formation to study the correlation between CT density and various log suites as well as minipermeameter permeability measurements. The goal of this work is to improve the use of logs in identifying the various reservoir facies and to generate improved reservoir models.

CT scans were performed to monitor the sweep efficiency of various surfactant/polymer combinations. The fingering observed was strongly dependent of the rock and fluid properties.

A video tape with the highlights of the past 2 years of flow experiments in thin slab micromodels has been completed. It will be used as a vehicle for technology transfer regarding the applicability of this technology for elucidating pore level flow mechanisms.

High Accuracy Positioning Table

To calculate saturation distributions in long cores or cores which are in coreholders, a number of scans have to be taken at precisely the same positions. A high accuracy positioning system (10 micron repeatability) has been assembled and mounted on the present CT table. The necessary software for incorporating the positioning of the table in the general experimental automation has been completed. The position of the table can be controlled from (1) the imaging workstation, (2) a 386SX PC computer situated immediately next to the CT console, and (3) a portable computer situated next to the table in the CT room. Thus, a more efficient usage can be made of the imaging workstation in analyzing the data from one core while CT scanning of another core is in progress.

A high accuracy positioning table (1 micron accuracy) for the minipermeameter has been constructed. It allows measurements of permeability distributions on an x-y grid on slabs. This will be used to provide both a calibration and a check for CT/petrographic image analysis derived permeability values needed to perform coreflood simulations.

Three-Phase Saturation Measurements

To measure fluid saturations in gasflooding experiments, a three-phase fluid saturation capability is required. Three-phase fluid saturation measurements in a porous media using CT X-ray require that the media be scanned at two different energy levels. The X-ray energy levels used in this project were 96 and 125 kv. Before using the dual energy approach to study gasflooding processes, a series of validating steps was taken. Initial experiments concentrated on establishing an accurate porosity using both energies and comparing the average CT porosity values to the volumetric value. Next, two-phase average saturations (brine and oil) were calculated using both the single energy and the dual energy approach, and the values obtained were compared to the volumetric data. Finally, the average three-phase saturations determined by the dual-energy method were compared to volumetric data. These steps are necessary because the saturation values calculated by using dual-energy CT scans are very sensitive to the CT attenuation values of the fluids present in the porous media. In the three-phase case while gas saturations were accurately predicted, discrepancies were found between the average CT-derived oil and brine saturations and the volumetric values for the cases with nonuniform fluid distributions. These discrepancies are due to the beam hardening effect on the CT attenuation value for the oil and brine depending on the position at which the voxel containing these fluids is located within the core. To remedy this problem, instead of using only one value for the attenuation number for oil and brine, a three dimensional array of attenuation values for both the oil and the brine should be used. To improve the accuracy of the oil and brine saturation measurements to the level needed in monitoring gas floods, a method is being developed to generate the fluid attenuation arrays.

Theory

The porosity distribution of the core from both energies was established by applying the following equation to each voxel of each slice at both energies.

$$\phi = (X_{bm} - X_{gm}) / (X_{brine} - X_{gas}) \quad (1)$$

where:

- ϕ = Porosity
- X_{bm} = CT attenuation of 100% brine saturated core, H.U.
- X_{gm} = CT attenuation of dry core, H.U.
- X_{brine} = CT attenuation of brine, H.U (constant)
- X_{gas} = CT attenuation of air, H.U (constant)

The equations used for calculating saturations for the single energy and dual energy methods are given below:

Single Energy Method

$$S_o = (X_{bgom} - X_{bm}) / (\phi(X_{brine} - X_{oil})) \quad (2)$$

$$S_w = 1 - S_o$$

where:

- S_o = Oil saturation
- S_w = Brine saturation
- X_{bgom} = CT attenuation of fluid saturated core, Hu
- X_{bm} = CT attenuation of 100% brine saturated core, Hu
- ϕ = Porosity, fraction
- X_{brine} = CT attenuation of brine, Hu (constant)
- X_{oil} = CT attenuation of oil, Hu (constant)

Dual Energy Method

$$S_o = A/B \quad (3)$$

$$S_w = C/B \quad (4)$$

where:

$$A = (X_{b1} - X_{g1})(X_{bgom2} - X_{gm2}) - (X_{b2} - X_{g2})(X_{bgom1} - X_{gm1})$$

$$B = \phi(X_{b1} - X_{g1})(X_{o2} - X_{g2}) - (X_{b2} - X_{g2})(X_{o1} - X_{g1})$$

$$C = (X_{bgom1} - X_{gm1})(X_{o2} - X_{g2}) - (X_{bgom2} - X_{gm2})(X_{o1} - X_{g1})$$

- X_{bgom1} = CT attenuation of fluid saturated core at 125 kV, HU
 X_{bgom2} = CT attenuation of fluid saturated core at 96 kV, HU
 X_{b1} = CT attenuation of brine at 125 kV, HU
 X_{b2} = CT attenuation of brine at 96 kV, HU
 X_{o1} = CT attenuation of oil at 125 kV, HU
 X_{o2} = CT attenuation of oil at 96 kV, HU
 X_{g1} = CT attenuation of air at 125 kV, HU
 X_{g2} = CT attenuation of air at 96 kV, HU

Experimental

A Berea sandstone core 7.6 cm long and 5.08 cm diameter was equipped with flow distribution end pieces and jacketed in epoxy. The dry core was placed on the CT table and cross-sectional slices were taken along the flow direction of the core using 125 kV and 96 kV energies at 8 mm intervals with an 8 mm slice thickness. The oil and brine attenuation numbers were determined by CT scanning a core sample with the fluids placed in tubes located within holes drilled within the sample. The average values are displayed in Table 1. The sample was then saturated with an 8% NaI brine and a volumetric porosity of 22.9% was calculated. The sample was then CT scanned at 100% brine saturation. The average porosities calculated for 125 kV and 96 kV were 22.3% and 22.2% respectively.

The brine was then displaced by oil to irreducible brine saturation followed by brine displacement to residual oil. Table 2 shows the comparison of the average saturation values obtained from volumetric, single energy, and dual energy calculations. Flood 1 consisted of injecting 1 pore volume (PV) of oil into the brine-saturated core. Flood 2 represents the same core after 9 more PV of oil was injected for a total of 10 PV. In flood 3, 10 PV of brine was injected into the core after the completion of flood 2. Flood 4 consisted of injection of 1,000 PV of gas into the core after flood 3. In flood 5, 10 PV of oil was injected after flood 4 was completed. In flood 6, 10 PV of oil was injected in reverse flow after flood 4 was

TABLE 1
CT Attenuation Values, HU

Fluid	125 kV	96 kV
Air	-499	-500
8 wt % NaI brine	562	803
47.5 wt % Bromodecane in soltrol 100	254	391

completed. Floods 1-3 were two-phase brine and oil while floods 4 through 6 were three-phase systems: brine, oil, and gas. Excellent agreement between the CT-measured values and the volumetric values was obtained for all floods for the gas saturations and for floods 2, 3 and 4 for brine and oil saturations. Discrepancies between the CT-derived brine and oil saturations and the volumetric values were observed in floods 1, 5, and 6. In all these cases, strong nonuniform fluid saturations across the core were observed. Figures 1 and 2 show the nonuniform gas distribution for floods 5 and 6. The darker areas represent zones with higher gas saturations. In Fig 2, the reverse flow causes a more uniform distribution of fluids in the core and a better agreement between the CT-determined brine and oil saturations and the volumetric values. These discrepancies are due to beam hardening which causes a variation in the CT attenuation value for the oil and brine depending on the position at which the voxel containing these fluids is located within the core. If these CT attenuation variations are not compensated, they eventually cause large errors in the saturation values because in the dual energy formulas both in numerator and the denominator, small numbers are multiplied by large numbers and the results are subtracted. To avoid this source of error, instead of using only one value for the attenuation number for oil and brine, a three-dimensional array of attenuation values for both the oil and the brine and a large attenuation contrast between the oil and brine should be used. A method is being developed to generate the fluid attenuation arrays and to select the tagging agent concentrations which optimize the CT attenuation contrast between brine and oil.

NMRI images of fluids in a native sandstone rock sample at high resolution have been obtained. The sample was a small plug of Bentheim sandstone 4 mm in diameter and 7 mm long. A Teflon core holder was made which fit snugly around the rock plug. Nylon endcaps with O-ring seals which fit tightly around small bore Teflon tubing (0.0625 in. OD) used as inlet and outlet ports permitted the exchange of fluid while the sample was inside the imaging probe inside the NMR magnet. The Bentheim plug was initially saturated with water under vacuum. The water contained 0.003M $MnCl_2$ as a relaxation agent. Longitudinal relaxation time (T_1) measurements showed the aqueous phase had a T_1 time of 47 milliseconds. Several images of the aqueous phase were made at pixel resolutions of 128 x 128 x 128 and 256 x 256 x 256. A gradient strength of 75 gauss/cm was used. At the highest resolution, the pixel size was 25 microns in the cross-sectional views with 40 microns along the axis. These are the highest resolution images obtained to date of fluids in sandstone. Soltrol mineral oil with the viscosity adjusted to 5 cP was injected into the water-saturated Bentheim plug (2 mL or about 100 vp was used). The injection was done under gravity flow with a fluid head of about 8 ft. The T_1 measurement of the oil phase gave a T_1 value of 523 milliseconds. Two images of the plug were made at a pixel resolution of 256 x 256 x 256: one showing the oil distribution (Fig. 3) and the second showing the residual

TABLE 2

Average Fluid Saturations

		Flood Number and Description					
		1 Oilflood 1 PV	2 Oilflood 10 PV	3 Brineflood 10 PV	4 Gasflood 1,000 PV	5 Oilflood 10 PV	6 Oilflood 20 PV
Brine saturation	Volumetric	0.481	0.385	0.725	0.402	0.280	0.280
	Dual energy	0.544	0.375	0.721	0.469	0.659	0.458
	125 kV	0.416	0.378	0.696			
	96 kV	0.437	0.385	0.704			
Oil saturation	Volumetric	0.519	0.615	0.275	0.264	0.604	0.615
	Dual energy	0.386	0.623	0.270	0.179	0.182	0.443
	125 kV	0.584	0.623	0.301			
	96 kV	0.563	0.615	0.296			
Gas saturation	Volumetric	0.000	0.000	0.000	0.334	0.116	0.105
	Dual energy	0.071	0.003	0.009	0.353	0.158	0.099
	125 kV	0.000	0.000	0.000			
	96 kV	0.000	0.000	0.000

Fig. 1 Non-uniform gas distribution in three-phase floods.

Fig. 2 Non-uniform gas distribution at residual water floods.

200 microns

Fig. 3 MRI microscopy images of oil distribution at residual water.

water phase using an inversion recovery imaging sequence to null the oil phase signal (Fig. 4). Note that the water appears as small isolated droplets with virtually the entire pore space being filled with the oil phase. Because of the longer T1 value for the oil and the lower signal/noise ratio for the residual water, each of these images took approximately 75 hours to acquire.

A second computer, a 25-MHz 386 PC, was obtained to separate the control of the NMR spectrometer for MRI data acquisition from the processing of the data file using the 3D-reconstruction software. This permits data to be acquired for one experiment while an earlier data set is being processed, reducing the turnaround time (acquisition plus processing) to half, which for 256 x 256 x 256 images can mean a time reduction from 48 to 24 hours.

200 microns

Fig. 4 MRI microscopy image of water distribution at residual water.

The data files are transferred between the two computers using Brooklyn Bridge software through the parallel printer ports. This permits the transfer of the large image data files to the processing computer in only a few minutes. A Syquest removeable cartridge drive was obtained for the processing computer. Several image files can be stored on one 45M Byte cartridge and efficiently transferred for the work station for imaging.

**IDENTIFICATION OF CROSS-FORMATIONAL
FLOW IN MULTIRESERVOIR SYSTEMS
USING ISOTOPIC TECHNIQUES (PHASE I)**

Cooperative Agreement DE-FC22-83FE60149,
Project SGP43

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract date: Aug. 15, 1990
Anticipated Completion: Mar. 1, 1991
Funding for FY 1990: \$42,500

Principal Investigator:
Michael Szpakiewicz

Project Manager:
Robert E. Lemmon
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objective

The objective of this project is to substantiate fluid migration patterns into, within, and out of a reservoir by

adapting natural isotopic geochemical techniques to the requirements of quantitative hydrodynamic reservoir modeling.

Summary of Technical Progress

The project was initiated in mid-August of 1990. The study has been designed to add quantitative and sometimes unique solutions to the problem of undesirable hydraulic intercommunication conventionally detected by analysis of anomalous well production and costly pressure buildup tests, interference tests, and tracer tests. The emphasis this quarter has been on review of (1) further evidence of dynamic conditions and cross-flow in multireservoir systems, (2) successful field applications of geochemical stable isotopic techniques to identify cross-formational flow, and (3) preselection of candidate HC reservoirs for isotopic study.

Phase I has now been completed, and the final report¹ has been submitted.

Reference

1. M. Szpakiewicz. *Identification of Cross-Formational Flow in Multireservoir Systems Using Isotopic Techniques (Phase I). Final Report.* DOE Report NIPER-538, May 1991.

DEVELOPMENT OF METHODS FOR MAPPING DISTRIBUTION OF CLAYS IN PETROLEUM RESERVOIRS

Cooperative Agreement DE-FC22-83FE60149,
Project SGP42

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract date: July, 1990
Anticipated Completion: January 1992
Funding for FY 1991: \$210,000

Principal Investigator:
Bijon Sharma

Project Manager:
Chandra Nautiyal
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objective

The objective of this project is to develop techniques for mapping the types and volumes of clays in clastic reservoirs from signature analysis of log responses in clayey formations. The scope of work in this project includes identification of a few clastic reservoirs where oil production has been affected by the presence of different types and volumes of clays and mathematical processing of wireline logs from the clayey formations to identify certain mathematical properties that may be correlated with the clay characteristics. The characteristics of clays under investigation are evaluated from detailed thin-section petrography, computerized tomography (CT) scans, and geological investigations.

Summary of Technical Progress

CT scanning of cores from wells Arch 121 and Arch 123 in Patrick Draw field was completed, and the CT responses of these heterogeneous cores were compared with that from Arch 120 where the agreement between CT density and the wireline log density was very good. Resolution of mapping small-scale heterogeneities by the different logs was investigated by comparing the CT response with the responses of the different wireline logs. Results of XRD analysis of core samples from Arch 120 performed by a service company were integrated with wireline log interpretation to study the effect of different clay and other minerals on wireline log responses. New core, log, and petrographic and petrophysical data were procured from a well in Louisiana to extend clay studies to formations which have abundant other types of clays besides kaolinite.

Correlation of CT Densities With Wireline Log Responses

The good agreement between the CT densities and the wireline log densities for the UA-5B sandstone in well Arch 120 reported earlier¹ was because the sandstone in this well was practically devoid of thin zones with significantly different densities, although the clay content in the sandstone was uniformly high. The average gamma ray log derived clay content was 6.9% for the entire UA-5B sandstone as against 4-5% of clays obtained from XRD analysis of seven samples (Table 1) from the sandstone cores. The lower clay percentage from XRD analysis could be either because the average from the seven samples does not represent the true average for the entire sandstone or because, as seen from XRD analysis, the higher amount of potassium feldspar in the sandstone has raised the gamma ray level that resulted in estimation of higher clay values from the gamma ray logs. The possibility that the predominantly diagenetic kaolinite clays in this well have

TABLE 1

X-Ray Diffraction Mineral Percentages of UA-5B Sandstone, Well Arch 120

Sample Identification number Well Arch 120 southwestern Wyoming	Quartz	Feldspar	Calcite	Dolomite	Siderite	Pyrite	Kaolinite	Illite &/or Mica	Mixed-Layer	Illite/Smectite	Plagioclase	Feldspar	Feldspar K
4942.4	52	3	36	1		4	2	1	1		1		2
4944.6	66	6	3	19		2	3	1	tr		3		3
4948.7	82	6	4	1		3	3	1			2		4
4949.5	88	6	1	tr		1	3	1	tr		3		3
4962.4	91	5	tr	tr		tr	4	tr	tr		3		2
4962.5	86	7	tr		tr	2	4	1	tr		3		4
496.5	85	5	tr	4		3	tr	2	1		3		2

been derived from potassium feldspar could also raise the radio activity level of the clays.

The uniform clay content of the Arch 120 sandstone is illustrated by the cross-plot of CT and wireline log densities in the well (Fig. 1). Similar plots made for Arch 121 and Arch 123 indicate much larger scatter of points with correspondingly lower correlation coefficients for the two densities compared to that in Arch 120. The larger scatter in Arch 121 and Arch 123 was mainly due to the presence of significantly large amounts of high density carbonate cemented rocks. From analysis of Arch 120 data the equation connecting CT and wireline log densities was found to be as follows:

$$Y = 1.712 + 0.00046456 X, R = 0.98446 \quad (1)$$

where Y = wireline density in g/cm^3
 X = CT density in hounsfield units
 R = correlation coefficient

Correlation of Log, CT, and Petrographic Data

From combined plots of CT densities with different log data as functions of depth, it has been seen that because of the high density, low transit times, and practically no gamma ray content, the calcite beds are fairly easily identifiable on logs provided they have a certain minimum thickness (larger than 6 in. approximately). Similarly the dolomite beds also have the same log responses as the calcite beds excepting that the dolomites may have some amount of radio activity.

From the distribution of properties of the commonly occurring clays (Table 2) it may be seen, as in Arch 120, that if the clays are kaolinites or illites, the density log may not be able to resolve the presence of these clays when the matrix rocks and the clays have nearly the same density (around 2.65 g/cm^3). The calculated standard deviation of

the wireline log density values in Arch 120 was only 0.053 g/cm^3 in spite of appreciable clay content in the sandstone pore spaces. This indicates that probably the porosity as well as the clay content in the sandstone is fairly uniform or that clay and the matrix densities of rocks are very similar.

The possibility of application of other logs besides density to identify kaolinite types of clays was also considered. Like the density log, the response of the kaolinitic clays in the sonic log was fairly uniform which could be because of uniform transit times when clay content does not vary appreciably. From Table 2, the high spectral gamma ray components and the high hydrogen content of kaolinites raise the possibility that the Table 2 radioactivity logs, gamma ray and neutron, could be used for recognizing the kaolinite types of clays.

Correlation of Clay Content With CT Densities

In Fig. 2 the plots of gamma ray log derived clay content (V_{cl}) and the CT densities for the UA-5B sandstone in Arch 120 are shown. The low standard deviations of the V_{cl} values (standard deviation = 1.1%) and the gamma ray readings (standard deviation = 3.3 API) indicate uniform clay content in the sandstone pore spaces assuming that the kaolinitic clays have recognizable gamma ray emissions. The high V_{cl} value (9.4%) at 4,954 ft is due to a thin shale layer which was not recognized on the CT density profile because the shale and the surrounding sandstone had practically the same density. This implies that the clay in the shale is probably of the kaolinitic or illitic types. Even the apparently cleanest part of the sandstone (such as at 4,950 ft, Fig. 2) had a density of 2.26 g/cm^3 , a gamma ray reading of 50 API units, XRD clay content of 4% (see Table 2) and a gamma ray clay content of 5%. From the above correlation it may be stated that the clay content in the sandstone is well recognized in the gamma ray logs although higher clay content estimations from the gamma ray logs could be due to contributions from radio active minerals other than clays.

Fig. 1 Crossplot of CT scan and wireline log density in UA-5B sandstone unit in Arch 120, Patrick Draw field, Wyoming.

Fig. 2 Correlation of CT scan density and gamma ray log derived clay content in UA-5B sandstone in Arch 120, Patrick Draw field, Wyoming.

TABLE 2
Clay Properties of Concern in Logging (Modified after Dewan, 1983)

Clay type	CEC, meq/g	CNL	$\rho/(\text{av}),$ g/cm ³	Minor constituents	Spectra GR components		
					K, %	(av), U ppm	Th, ppm
Montmorillonite	0.8-1.5	0.24	2.45	Ca,Mg,Fe	0.16	2-5	14.24
Illite	0.1-0.4	0.24	2.65	K,Mg,Fe,Ti	4.5	1.5	> 2
Chlorite	0-0.1	0.51	2.8	Mg,Fe	—	—	—
Kaolinite	0.03-0.06	0.36	2.65	—	0.42	1.5-3	6-19
CEC	- Cation exchange capacity	CNL	- Neutron porosity	Th	- Thorium		
$\rho/(\text{av})$	- Average density	K	- Potassium				
GR	- Gamma ray	U	- Uranium				

Conclusions From Correlation Studies

1. Density logs may not recognize the variations in kaolinite type of clay content or the presence of thin shale beds in most cases because of lack of contrast in density.

2. The gamma ray log recognizes the presence of the kaolinitic clays as indicated from XRD analysis of thin sections. The slightly higher clay estimations from the gamma ray logs could be due to contributions from non-clay minerals like potassium feldspar, mica, etc.

3. If the standard deviations of the wireline and CT densities are low and the gamma ray readings against the sandstone high, it probably implies high kaolinite type of clay content in the sandstone porespace. The average gamma ray reading for the entire sandstone will indicate what is the average clay content in the sandstone porespace. If the standard deviations of the gamma ray readings is low it implies uniform clay content in the sandstone porespace.

4. The possibility or the extent of contributions to gamma rays from non-clay minerals or the diagenetic clays derived from potassium feldspar will have to be determined from petrographic studies.

5. Non-clay carbonate minerals are easily distinguished on the density logs because of high density and on the sonic logs because of low sonic transit times of these minerals.

Procurement of Log, Core, Petrographic Data From Formation With Different Clay Types

The wireline log interpretations in clayey formations completed so far was predominantly in sandstones with

kaolinite type of clays with only smaller amounts of illites and smectites. To determine the wireline log responses in sandstones where other types of clays prevail, it was decided to procure core and log data from the Wilcox formation in the Louisiana Gulf Coast where besides kaolinite, significant amounts of other types of clays are known to be present.

Forty-one feet of cores from the Wilcox formation was procured from well A.C. Wyble #1 located in St. Landry Parish, Louisiana. Conventional core descriptions and interpretations of depositional environments by a service company indicate that the core is from a depositional environment which may be described as interdistributary bay. XRD analysis of eight core samples performed by a service company indicate that the types of clays are mainly illites, chlorites, and kaolinites with only a small percentage (0 to 8% of total clay) of mixed layer illite/smectite types of clays. Conventional core analysis indicates drastic reduction of porosity and permeability due to the clays, which is probably a factor in no oil or gas production from the well.

Before initiating detailed log signature interpretations of the clayey sandstones, CT-scan, SEM, thin-section, and more XRD analysis of core samples will be conducted.

References

1. National Institute for Petroleum and Energy Research *Quarterly Technical Report for April 1 - June 30, 1991, Vol. II, Energy Production Research*, DOE Report NIPER-545, July 1991, pp. 32-34.
2. J. T. Dewan. *Essentials of Modern Open-Hole Log Interpretation*, PennWell Books, Tulsa, Okla., 1983.

RESOURCE ASSESSMENT TECHNOLOGY

RESERVOIR ASSESSMENT AND CHARACTERIZATION

Cooperative Agreement DE-FC22-83FE60149,
Project BE1

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract date: Oct. 1, 1985
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$800,000

Principal Investigator:
Susan R. Jackson

Project Manager:
Edith Allison
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objective

The objective of this project is to develop an improved methodology for effective characterization of barrier island reservoirs to predict oil saturations at interwell scales and flow patterns of injected and produced fluids.

Summary of Technical Progress

Comparison of Facies Geometry and Dimensions from Other Mesotidal Shoreline Barrier Deposits Reported in Literature

Common geometries (shapes) and dimensions of seven major potentially productive tide related facies in the recent and ancient mesotidal shoreline barrier systems were compiled from several sources of literature and from NIPER's field observations. Results are illustrated in Table 1. Typically the shoreface and foreshore facies of mesotide-formed barrier islands tend to dominate volumetrically in the system due to the largest average lengths of sand bodies (2 to 12 miles), significant widths (0.6 to 4 miles) and one of greatest thicknesses (12 to 90 ft). The major barrier island facies are typically deposited in high energy environment and represent good to excellent petrophysical parameters.

Second largest sand bodies are formed as tidal deltas on the marine side (ebb tidal delta) and on the lagoonal side (flood tidal delta) of the tidal inlet cutting a barrier island perpendicular to the shoreline. Ebb tidal deltas tend to dominate volumetrically over flood tidal deltas, in particular when shoals are attached to them. Shoreface, shoal, and ebb tidal delta, if preserved, may form the most extensive sand body in the whole shoreline barrier system. The potential for collecting large amounts of fluids in such a system is excellent, however, in transgressive sequences the preservation potential of these facies is relatively low.

Tidal channels are deep erosional features and typically become filled with material deposited by strong currents and originating from redeposited marine facies.

TABLE 1
Common Shapes and Dimensions Of Major Tide Related Facies In The Recent And Ancient Mesotidal Shoreline Barrier Systems ¹

Facies Name and shape	Thickness, ft	Width, ml	Length, ml
Mesotidal barrier (Shoreface & foreshore facies); elongated oval, drumstick	12.0 to 90.0	0.6 to 4.0	2.0 to 12.0
Washover Fan & Terrace; fan or terrace	0.5 to 6.0	0.4 to 1.6	0.8 to 1.8
Spit platform; accreted cycles	3.0 to 15.0	0.5 to 3.0	0.3 to 1.0+
Tidal inlet; strait or slightly curved	5.0 to 100.0+	0.1 to 1.0+	0.6 to 4.0+
Tidal channel & Tidal Creek; convergent, sinuous	5.0 to 100.0+	0.02 to 0.8	1.0 to 3.0+
Flood tidal delta; lobate fan, tear-shaped	6.0 to 30.0	0.3 to 4.0	1.0 to 3.0
Ebb tidal delta & Shoal; lobate fan, oval	15.0 to 75.0	1.0 to 10.0	1.5 to 6.0

Preservation potential and original petrophysical properties of tidal channel deposits are very good. They represent convergent shoestring type geometry and may become excellent oil reservoirs. Volumetrically the tidal channels rank third in the tide dominated mesotidal shoreline barrier system.

Washovers and spits are genetically associated with barrier island core and typically possess good petrophysical parameters. However, their volumetric capacity to collect and transmit fluids is limited.

Comparatively, the tide-related facies of the Upper Almond formation in Patrick Draw field (UA-5 and UA-6 sandstones) and those studied in outcrops located on the southeast flank of the Rock Springs Uplift (UA-1, 2 and 3 sandstones) fall within typical dimensional limits for corresponding mesotidal facies described in the literature.

Outcrop Fracture Characterization

The difficulties in determining fracture characteristics in Patrick Draw field and in identifying a role of natural fractures in hydrocarbon production prompted the study of fracture orientation, continuity, and spacing in the outcrops of the Upper Almond formation on the east flank of the Rock Springs Uplift. Sedimentological examination of

outcrop sequences increased our confidence that the Upper Almond sandstones producing oil and gas in Patrick Draw field and those which crop out several miles to the west were deposited by similar processes acting in analogous environments of deposition. Since the regional tectonic history was similar for both outcrop and reservoir rocks, surface measurements of fracture parameters were made to determine the applicability to the Patrick Draw reservoir at depths of about 4,500 - 5,000 ft.

There are two general areas on the east flank of the Rock Springs Uplift where the Upper Almond sediments were earlier described sedimentologically in a number of surface exposures; those located west of Patrick Draw field, in a distance of 6 to 10 miles,¹ and the ones located on the southeast flank of the Rock Springs Uplift, up to 20 miles away from Patrick Draw field.² Major faults oriented nearly east-west (75°-80°) dominate in the area of Van Horn's study,¹ and some of them extend toward Patrick Draw field. (See Fig. 14 in reference 3.) There is a discrepancy in the orientation of major fault and lineament directions in Patrick Draw field shown by different authors: faults, 74° and 80°;⁴ fault, 77°;¹ lineaments, 33°, 50°, 84°, 122°, 164°.⁵

There are virtually no documented major faults in the immediate area of the outcrops located on the southeastern flank of the Rock Springs Uplift where fractures were measured for this study. However, most faults shown on the map by Greer et al.,⁴ near the crest of the Rock Springs Uplift, west and northwest of studied outcrops, are oriented differently (30-40°) than those in the area studied by Van Horn¹ on the east-central flank of the Uplift (70-80°) which tend to continue toward Patrick Draw field.

The azimuth, vertical continuity, and lateral spacing of approximately 1,000 tectonic fractures were measured at three major sandstone horizons in two outcrops along lateral distances of 800 to 1,500 ft. Obvious weathering or gravitational fractures were eliminated from the record. A strong indication of minor faults was observed in a few cases. Geological and statistical analyses of measured fractures in outcrops located on the southeastern flank of the Rock Springs Uplift have been performed, and their relationship to faults in the general area and to Patrick Draw field has been established. Results of the analysis and conclusions regarding applicability of the studied outcrop fracture patterns to the reservoir producing oil and gas at depths of about 4,500 to 5,000 ft will be reported.

Further fracture analysis in the outcrop area located immediately west of Patrick Draw field is recommended for the best possible characterization of fracture distribution, orientation, density, chronology, and permeability in the studied oil field.

Comparison of Patrick Draw and Bell Creek Sandstone Reservoir Mineralogy and Petrography

Quantitative XRD mineralogical analysis of Muddy formation samples is presented in Table 2. Individual barrier facies cannot be distinguished by either framework mineralogy or clay content alone. The high quartz content of Muddy formation barrier sandstones from Bell Creek reservoir (average = 89%) contrasts with the generally lower quartz content of reservoir sandstones from Patrick Draw field (average = 75.8%), quartz content is similar to that of the Almond outcrop samples (average 89%). Muddy formation valley fill facies also have a higher quartz content (average = 92%) than do Almond sandstones.

TABLE 2
Quantitative XRD Determination in Weight Percent of Mineralogy for Subsurface Samples from Bell Creek Field and a Nearby Outcrop (GM = Green Mountain outcrop)

Well	Depth, ft	Depositional setting	Quartz	Feldspar	Calcite	Dolomite	Anhydrite	Barite	Pyrite	Kaolinite	Illite	Smectite	Ill/Smectite	Siderite
SUBSURFACE														
C-8	4351	Lagoon	76	3	-	4	-	-	-	7	8	tr	-	2
27-16	4303-3	Washover	88	2	tr	tr	-	-	-	6	4	-	tr	tr
W-14	4309.3	U./L./Shoreface	89	3	tr	tr	-	-	tr	5	3	tr	-	-
27-14	4309.5	U. Shoreface/foreshore	94	tr	tr	tr	-	-	-	4	2	tr	-	-
27-14	4331.5	U. Shoreface/foreshore	90	2	-	2	-	-	tr	4	2	tr	1	-
W-16	4308.6	Foreshore	91	2	1	1	-	tr	-	3	3	1	-	-
W-16	4318	U. Shoreface	88	2	1	1	-	tr	-	5	3	tr	-	-
W-7	4405.5	Estuarine	88	4	-	tr	-	-	-	2	tr	6	-	-
W-7	4410.0	Estuarine	79	4	-	-	-	-	-	2	tr	15	-	-
W-7	4417.5	Swamp	92	3	-	-	-	-	-	3	tr	2	-	-
W-7	4418.9	Alluvial Channel	96	1	-	-	-	-	-	3	tr	tr	-	-
W-7	4419.5	U. Shoreface	94	2	-	-	-	-	-	2	2	tr	-	-
W-7	4431.3	U. Shoreface	91	3	-	-	-	2	-	2	2	tr	-	-
OUTCROP														
GM	0	Fluvial channel ss	93	2	-	tr	1	-	-	3	1	tr	-	-
GM	10	Fluvial channel ss	97	tr	-	-	-	-	-	2	tr	1	-	-
GM	52	Continental silts.	96	tr	-	tr	tr	-	-	2	tr	2	-	-
GM	65	Fluvial ss	97	tr	-	tr	tr	-	-	1	tr	22	-	-

Table 3

**Whole Rock X-Ray Diffraction Analysis in Weight Percent, for Samples from
Patrick Draw and Outcropping Upper Almond Formation**

Well	Strat. Depth, ft	Interval	Quartz	Plagioclase	K-Feldspar	Dolomite	Ferrous Dolomite	Siderite	Pyrite	Calcite	Gypsum	Kaolinite	Illite/Mica	Clay/Smectite
7-18-1	4,945	UA5	61	4	4	-	21	-	3	3	-	3	1	tr
45-14-3	4,450	UA5	5	-	tr	-	tr	-	-	93	-	2	tr	tr
78-14-6	4,305	UA5	78	2	3	5	tr	2	1	5	-	2	2	tr
49-1-3	4,615	UA-6	69	-	2	10	15	-	1	1	-	2	2	1
Arch 120	4,942.4	UA5	52	1	2	1	-	-	4	36	-	2	1	1
	4,944.6	UA5	66	3	3	19	-	-	2	3	-	3	1	tr
	4,948.7	UA5	82	2	4	1	-	-	3	4	-	3	1	-
	4,949.5	UA5	88	3	3	tr	-	-	1	1	-	3	1	tr
	4,962.4	UA5	91	3	2	tr	-	-	tr	tr	-	4	tr	tr
	4,962.5	UA5	86	3	4	-	-	tr	2	tr	-	4	1	tr
	4,966.5	UA5	85	3	2	4	-	-	3	tr	-	tr	2	1
OUTCROP SAMPLES														
G7-26B			89	2	3	3	-	-	-	-	-	1	1	-
G7-47			95	1	2	tr	-	-	-	tr	-	1	1	-
G7-91			83	5	8	tr	-	-	-	tr	-	1	1	-
G7-174			89	4	4	tr	-	-	-	-	tr	2	1	-
G7-191			90	3	4	1	-	tr	-	-	-	1	1	-

X-ray diffraction analysis of Muddy formation barrier island and valley fill sandstones from the subsurface and analogous outcrops revealed different clay assemblages. Within the barrier island sandstones, the clays generally exhibit a 2:1 ratio between kaolinite and illite and comprise less than 15% by weight. In valley fill sandstones and mudstones, smectite and kaolinite dominate the clay assemblage.

Reservoir sandstones from Patrick Draw are dominated by kaolinite clay and lesser amounts of illite and mixed layered illite/smectite (Table 3). The ratio of kaolinite to illite plus illite/smectite ranges from 1:1 to as much as 4:1. Data from outcrop samples indicate a general ratio of about 1:1 for kaolinite to illite and a complete absence in the analyzed data of mixed-layered illite/smectite. The greatest mineralogical difference between the analyzed Muddy and Almond formation samples is the abundance of smectite in Muddy valley fill facies, and its near absence in any of the Almond facies. Analysis of a limited number of thin sections indicates that kaolinite clay cement tends to be more common in Patrick Draw reservoir sandstones than is clay matrix. In both Muddy and Almond reservoir sandstones the presence of diagenetic kaolinite appears to be derived from the decomposition of feldspars and other less-stable grain such as rock fragments. In the Muddy formation samples, chert is the most common surviving lithic fragment, and K-feldspars are virtually the only type

of feldspar represented, accounting for no more than 2-3% of the total rock volume. In Almond reservoir sandstones chert, organic fragments, as well as sedimentary, volcanic, and metamorphic rock fragments are present. Pelitic (clay-rich) rock fragments are common in Almond reservoir sandstones. Plagioclase and K-feldspars are present in about equal proportions in Almond reservoir sandstones and outcrop samples analyzed, comprising on average 5% of reservoir sandstones and 7% of outcrop sandstones, or more than twice the amount found in Muddy formation sandstones.

When the essential framework components of sandstones are recalculated to 100% and plotted on a quartz-feldspar-rock (Q-F-R) fragments diagram (Fig. 1) comparison between Almond and Muddy formation shoreline barrier sandstones becomes apparent. The quartzose nature of Muddy reservoir sandstones contrasts with the somewhat less quartzose but low feldspathic outcrop Muddy sandstones. The Q-F-R fields for Almond reservoir sandstones and Muddy reservoir sandstones do not overlap (Fig. 1) because Almond reservoir sandstones generally have less quartz content than those from the Muddy formation. Subsurface Almond sandstones tend to have a higher average quartz content than the outcrop Almond sandstones, although the data set of outcropping Almond sandstones is very small. Because of these

BARRIER SANDSTONES

FIG. 1 Ternary plot of quartz-feldspar-rock fragment composition of outcrop and subsurface Almond and Muddy formations. Note that the Almond formation samples are generally less quartzose and are more rich in rock fragments than corresponding Muddy formation samples.

compositional differences, Almond reservoir sandstones tend to be sublitharenites, litharenites, and feldspathic litharenites while the Muddy reservoir sandstones tend to be sublitharenites, subarkoses, and some quartzarenites. Based on the data in Fig. 1, it appears that average Almond outcrop sandstones have a higher feldspar content than many Almond reservoir sandstones and a higher feldspar content than virtually all Muddy outcrop sandstones.

The diagenetic history of both the Almond and Muddy marine reservoir sandstones is complex. Nine stages have been recognized in the Almond formation.⁶ The Almond reservoir rocks are typically fine to very fine-grained and contain an appreciable amount of unstable rock fragments such as chert and shale as well as carbonate. Eight paragenetic stages have been recognized in Muddy reservoir sandstones.⁷ The fine to very fine-grained Muddy reservoir sandstones also contain some chert rock fragments;

however, petrographic analysis has indicated that most sedimentary rock fragments have been removed by dissolution often resulting in oversized pores.³ Carbonate minerals are extremely rare in the Muddy reservoir rocks, probably having been removed by the same strong early diagenetic stage of dissolution that leached rock fragments and produced the oversized pores. The relative increase in sedimentary rock fragments, particularly those of shale, tend to make the Almond formation more susceptible to compaction with attendant decreases in porosity and permeability.⁶ The Muddy formation, in contrast contains relatively few fine-grained rock fragments, however, the distribution and crystallographic habits of kaolinite and illite (in the Almond formation) and dominantly of kaolinite (in the Muddy formation) makes both barrier reservoirs sensitive to the migration of fines during completion and production.⁶⁻⁸

In both reservoirs early stage leaching was important with respect to modifications of the pore system which in turn has a strong control on the petrophysical properties of the reservoirs. At Bell Creek, early leaching may have been the dominant process controlling petrophysical properties within much of the reservoir. At Patrick Draw field, the reservoir rocks were subjected to much less intense leaching that affected the Muddy formation. The effects of early leaching at Patrick Draw appear to have been a limited leaching of feldspars, chert, and shale grains, often resulting in the creation of microporosity. In the Muddy formation reservoir at Bell Creek, virtually all diagenetic stages subsequent to early stage leaching affected the evolution of the rock in a potentially negative manner. Although early leaching was important to the evolution of petrophysical properties of the Almond reservoir at Patrick Draw, the process was not so intense as at Bell Creek. The subsequent porosity-reducing diagenetic stages, particularly compaction, cementation by calcite, dolomite, and ankerite, as well as the precipitation of clays in the Almond reservoir, had a much greater negative effect at Patrick Draw than at Bell Creek and is illustrated in the comparison of the average porosity and permeability values.⁶⁻⁷ Late-stage leaching of grains and prior cements had a potentially great positive effect on Muddy reservoir sandstones.⁷ Although late stage leaching recognized in Almond reservoir sandstones⁶ its significance has yet to be fully evaluated.

Ferroan dolomite and calcite are the most common cements in the more permeable upper Almond sandstones examined. Calcite occurs as both a pore-filling cement and as a replacement of other mineral grains. Dolomite locally replaces calcite and quartz as well as occurring as a pore filling cement. Dolomite and ferroan dolomite (ankerite) cement can locally contribute up to 35% rock volume, thereby reducing permeability to less than 1 mD.³ Calcite replacement and pore filling cement in the Muddy formation, in contrast, is only locally significant. However, where it does occur, calcite in the Muddy formation has a strong negative effect on porosity and permeability. Calcite does not exceed 20% in any examined Muddy thin sections, but when more than about 2 to 5% calcite is present, permeability is generally less than a few 10's of millidarcies. By way of contrast, calcite-poor reservoir sandstones from various depositional facies at Patrick Draw field generally contain less than 25% porosity and less than 90 mD.

References

1. M. D. Van Horn, *Stratigraphy of the Almond Formation, East-Central Flank of the Rock Springs Uplift, Sweetwater County, Wyoming: A Mesotidal Shoreline Model for the Late Cretaceous*. M.S. Thesis, Colorado School of Mines, 150 p., 1979.
2. H. W. Roehler, *The Pintail Coal Bed and Barrier Bar G - A Model for Coal of Barrier Bar - Lagoon Origin, Upper Cretaceous Almond Formation, Rock Springs Coal Field, Wyoming*. U.S. Geological Survey Professional Paper 1398, p. 1-60, 1988.

3. M. Szpakiewicz, R. Schatzinger, S. Jackson, B. Sharma, A. Cheng, and M. Honarpour. *Selection and Initial Characterization of a Second Barrier Island Reservoir System and Refining of Methodology for Characterization of Shoreline Barrier Reservoirs*. DOE Report NIPER-484, 170 p., 1991.
4. P. L. Greer, J. K. King, and A. J. Ver Ploeg. *Preliminary Map of Known Surficial Structural Features for the Rock Springs 1° x 2° Quadrangle*. USGS Open File Report 87-1N, 1987.
5. D. M. Richers, J. R. Reed, K. C. Horstman, G. D. Michels, R. N. Baker, L. Lundell, and W. Marrs. *Landsat and Geochemical Study of Patrick Draw Oil Field, Sweetwater County, Wyoming*. AAPG Bull., vol. 66, pp. 903-922, 1982.
6. C. W. Keighin, B.E. Law, and R. M. Pollastro. *Petrology and Reservoir Characteristics of the Almond Formation, Greater Green River Basin, Wyoming*, in Coalson, E. B., ed., *Petrogenesis and Petrophysics of Selected Sandstone Reservoirs of the Rocky Mountain Region*. The Rocky Mountain Assoc. of Geologists, Denver, Colorado, 1989, p. 281-298.
7. M. Honarpour. *Integrated Reservoir Assessment and Characterization*. DOE Report NIPER-390, 336 p, February 1989.
8. B. L. Priisholm, Nielson, and O. Haslund. *Fines Migration, Blocking, and Clay Swelling of Potential Geothermal Sandstone Reservoirs, Denmark*. SPE Formation Evaluation, p. 168-178 vol.2, 1987.

TORIS RESEARCH SUPPORT

Cooperative Agreement DE-FC22-83FE60149,
Project BE2

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$340,000

Principal Investigator:
James F. Pautz

Project Manager:
Chandra M. Nautiyal
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objective

The objective of this project is to provide research support to the Department of Energy (DOE) Program Manager for the Tertiary Oil Recovery Information System (TORIS) in the areas of enhanced oil recovery (EOR)

project and reservoir data base management, EOR project technology and trends analysis, and computer simulation.

Summary of Technical Progress

The DOE has released a vertical/horizontal/slant well version of the black oil simulator, BOAST.¹⁻² DOE will soon be releasing a version of this simulator, BOAST-VHS, that will run on a personal computer with 640k RAM.³ NIPER has compared the performance of this simulator to the performance of industry simulators using the results of the seventh Society of Petroleum Engineers (SPE) comparative solution (CSP) project.⁴

This CSP modeled the production from a horizontal well in a reservoir with coning tendencies due to the bottom aquifer drive. Four cases were outlined at two different horizontal well lengths (900 and 2,100 ft) to compare the effect of well length and rates of recovery for 14 participant models. Cases 1, 2, and 3 require that the horizontal well produces at a constant liquid rates of 3,000, 6,000, and 9,000 STB/day, respectively. The results of the CSP were shown in graphs of oil production rate, cumulative oil production, cumulative water production, and water oil ratio versus time for the first three problems. In the fourth problem, a substantial amount of gas would be produced so gas production and gas oil ratios were also plotted. The mean cumulative oil production after 1,500 days and standard deviation around the mean were presented for each case. These last results and the differentiating parameters of the first three cases are summarized in table 1.

TABLE 1

Cumulative Oil Production in MSTB at 1500 Days for the Seventh SPE CSP and Saturation Change Control in BOAST-VHS Simulations

	Cases					
	1a	1b	2a	2b	3a	3b
BOAST-VHS	748.4	934.6	995.1	1179.2	1097.8	1340.3
Mean	735.6	946.4	965.4	1217.8	1102.1	1349.1
Standard deviation	27.4	26.7	45.2	41.0	64.7	73.5
Production rate, STB/d	3000	3000	6000	6000	9000	9000
Well length open to flow, ft	900	2100	900	2100	900	2100
Sat'n change control (%) in BOAST-VHS	1.5	1.0	1.5	1.5	1.5	1.2

The NIPER evaluation of the DOE horizontal well simulator used the black oil fluid properties, relative permeabilities, the reservoir grid system, and the horizontal well geometry specified by the project. An equivalent wellbore radius of 3.784 ft or productivity index of 59,510 mD/ft was used in the well model for the horizontal producer. Case problems 1, 2, and 3 from the seventh SPE CSP were simulated for both horizontal well lengths. The automatic time step control based on maximum saturation change allowed in each time step was used in simulating the three cases at two well lengths.

Simulation results of BOAST-VHS agreed well with those from 14 participant models in comparative problems.

Table 1 shows the mean cumulative oil production after 1,500 days of simulated production and standard deviation for the three cases at each horizontal well length and the results of the NIPER simulations. NIPER results are within one standard deviation of the mean which indicates good agreement for this simulation end point.

The production rate and other simulation outputs also agreed. Figures 1, 2, 3, and 4 show the extreme results of the oil production rate and cumulative oil production versus time for selected cases of the CSP with NIPER results. These show that the results of the DOE simulator is well within the high and low results of the participant simulators. Figure 5 shows the water-oil ratio for case 3b which again shows the results comparable to the CSP participants.

The number of time steps required for BOAST-VHS to solve these problems was significantly higher than the participants in the CSP report. This implies that although BOAST-VHS does give similar results to those of other horizontal well simulators, it is not as efficient.

Fig. 1 Comparing oil rate and cumulative production for Case 1A from BOAST-VHS against the extremes of the CSP.

Fig. 2 Comparing oil rate and cumulative production for Case 1B from BOAST-VHS against the extremes of the CSP.

Fig. 3 Comparing oil rate and cumulative production for Case 2B from BOAST-VHS against the extremes of the CSP.

Fig. 4 Comparing oil rate and cumulative production for Case 3B from BOAST-VHS against the extremes of the CSP.

Fig. 5 Comparing water oil ratio for Case 3B from BOAST-VHS against the extremes of the CSP.

References

1. M. M. Chang. *Simulation of Production From Wells with Horizontal/Slanted Laterals*, DOE Report NIPER-326, March 1989.
2. M. M. Chang, L. Tomutsa, and M. K. Tham. *Predicting Horizontal/Slanted Well Production by Mathematical Modeling*, paper SPE 18854, presented at the SPE Production Operation Symposium, Oklahoma City, Mar. 13-14, 1989.
3. M. M. Chang, P. Sarathi, R. J. Heemstra, A. M. Cheng, and J. F. Pautz. *User's Guide and Documentation Manual for "BOAST-VHS" for the PC*, DOE Report NIPER-542, July 1991.
4. L. Nghiem, D. A. Collins, and P. Sharma. *Seventh SPE Comparative Solution Project: Modeling of Horizontal Wells in Reservoir Simulation*, paper SPE 21221, presented at the 11th SPE Symposium on Reservoir Simulation, Anaheim, Calif., Feb. 17-20, 1991.
5. D. W. Peaceman. *Representation of a Horizontal Well in Numerical Reservoir Simulation*, paper SPE 21217, presented at the 11th SPE Symposium on Reservoir Simulation, Anaheim, Calif., Feb. 17-20, 1991.

THREE-PHASE RELATIVE PERMEABILITY

Cooperative Agreement DE-FC22-83FE60149,
Project BE9

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1985
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$300,000

Principal Investigator:
Dan Maloney

Project Manager:
Edith Allison
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this project are to improve the reliability of laboratory measurements of three-phase relative permeability for steady- and unsteady-state conditions in core samples and to investigate the influence of rock, fluid, and rock-fluid properties on two- and three-phase relative permeabilities.

Summary of Technical Progress

Relative Permeability Measurements

Two- and three-phase tests to determine the steady-state relative permeability characteristics of 260-mD Berea sandstone were completed during this reporting period. The same epoxy-resin jacketed sample was used for each test. The rock was tested in the unconfined state. Between tests, the rock was cleaned with isopropyl alcohol and pentane and was dried with nitrogen gas.

The test fluids used for the two-phase oil/brine test were deionized water containing 1% by weight NaCl as the brine phase and Soltrol 100 (an isoparaffinic oil available from Phillips Petroleum Co.) tagged with 10% by weight iodododecane as the oil phase. A new technique was used to calibrate the X-ray for saturation measurements. Scans of the rock when saturated with 1% NaCl brine served as the calibration data for the condition of complete brine saturation. Additional scans were taken after the rock was flooded with a brine which had the same X-ray absorption characteristics as those of the tagged oil. Thus, X-ray calibrations were developed without saturating the rock with oil and without having to interpret fluid saturation distributions within the rock from volumetric measurements. Untagged brine was flooded through the rock to remove all traces of the tagged brine in preparation for the steady-state relative permeability test. The rock was oil-flooded to residual brine saturation conditions, then two-phase measurements were recorded for an imbibition (i1) and a second drainage (d2) saturation cycle. The microwave scanner was also used to monitor fluid saturations.

Figure 1 shows the oil/brine relative permeability results for the sample. The data were normalized with respect to the brine permeability of the sample when the sample was completely saturated with brine (260 mD). The brine relative permeability curves followed the same trend for both saturation cycles, whereas lower oil relative permeabilities resulted at intermediate saturations during the second drainage cycle. Resistivity measurements were also recorded during the test using the 2 electrode method in which the electrodes were centered 5.1 cm apart along the length of the 15.8-cm-long sample. Resistivity index results are shown in Fig. 2. The saturation exponent calculated from the imbibition data was 2.2 compared to the 2.4 result from the drainage data. Viewed collectively, the imbibition and drainage data follow the same trend. This is consistent with the brine relative permeability results. The saturation exponent for the combined imbibition and drainage data is 2.2.

After cleaning, the rock was saturated with oil, and a steady-state gas/oil test was conducted. Nitrogen gas was used as the gas phase. The limited test results are shown in Fig. 3. The rock was cleaned after the gas/oil test. The rock was saturated with brine. Steady-state gas/brine measurements were recorded for two drainage saturation cycles and one imbibition cycle.

The gas/brine two-phase results are shown in Fig. 4. The gas relative permeability curves were similar for the

Fig. 1 Steady-state oil/brine relative permeability results. Normalized with respect to $k_w = 260$ mD when $S_w = 1.0$.

Fig. 2 Resistivity results from the oil/brine steady-state test.

two drainage cycles while the imbibition results were significantly different. Upon completing the imbibition cycle, the flow direction was reversed, and the sample was flooded with brine. The significant increase in the brine permeability of the sample suggests that plugging occurred toward the end of the imbibition test. A shift in the brine relative permeability curve occurred toward the end of the second drainage cycle. This shift may also be the result of plugging although the gas relative permeability curves from the second drainage cycle are consistent with those from the first drainage cycle.

Three-phase steady-state relative permeability tests were initiated on the sample upon completing the two-phase tests. Measurements were recorded during four DDI saturation trajectories (decreasing brine and oil saturations, increasing gas saturation). After completing a saturation trajectory, the plug was waterflooded to residual gas and oil saturation conditions. A new saturation trajectory was started by establishing brine and oil flow at a target brine

fractional flow ratio before injecting gas into the rock. The target brine fractional flow ratios were selected to provide a spread of three-phase results. Initial oil and brine injection rates were adjusted to yield a pressure drop across the length of the sample that was equal to approximately half of the range of the differential pressure transmitter. The first gas rate was adjusted to yield a pressure drop across the rock sample equal to approximately 80% of the differential pressure transmitter range. Permeabilities were calculated from flow rate and pressure drop measurements while saturation distributions were calculated from X-ray and microwave scans. Saturation changes along the same saturation trajectory were established by either doubling the gas rate or halving the oil and brine rates, depending upon whether the pressure drop across the plug was closer to 50% or 80% of full scale. Additional measurements were recorded after doubling the gas rate or halving the oil and brine rates until either the brine and oil saturations were diminished to residual values or until the oil or brine injection rates were too low for practical measurement. Three-phase results are under evaluation.

Fig. 3 Oil/gas relative permeability results. Normalized with respect to $k_w = 260$ mD when $S_w = 1.0$.

Fig. 4 Gas/water steady-state results. Normalized with respect to $k_w = 260$ mD at $S_w = 1.0$.

Dual Energy X-ray Techniques for Monitoring Three-phase Saturations

One method for applying dual energy X-ray techniques for measuring saturations during multiphase relative permeability tests was described in the Jan. 1 - March 31, 1991 Quarterly Technical Report for this project.¹ The basis for the method is to add X-ray absorbants to two of the fluid phases. The absorbants are selected based on solubility considerations and to provide different attenuation characteristics at two X-ray power settings. In the example given in the Jan. 1 - March 31 Quarterly Technical Report,¹ the X-ray voltage settings of 24.7 and 41.3 kV were selected to provide intensity measurements on either side of the iodine K absorption edge which occurs with an excitation potential of 33.2 kV.

Additional calculations were performed to evaluate the suitability of using the technique for potentials above the K absorption edges of the fluids. The calculations assumed that the oil phase consisted of decane tagged with iodododecane while the brine phase consisted of KBr in water. Linear attenuation coefficients were calculated for the two fluids for potentials of 50 and 55 kV using the technique described in the Jan. 1 - March 31 Quarterly Report. The results are shown in Fig. 5.

Assume that the two fluids are tagged to have linear attenuation coefficients equal to 0.5 cm^{-1} at the 50 kV potential. To achieve this condition, the oil phase is tagged with 8% by weight iodododecane while the brine phase is tagged with 10% KBr. When the potential is stepped up to 55 kV, the oil phase linear attenuation coefficient is approximately 0.3. The brine phase linear attenuation coefficient is also about 0.3. As the attenuation coefficients for the two fluids are nearly identical at both X-ray potential settings, the tagging arrangement would not be very useful for measuring fluid saturations during three-phase tests. Reviewing the results of figure 5, for practically any KBr/brine and iodododecane/decane system in which the brine and oil phases are tagged to have similar X-ray attenuation

Fig. 5. Linear X-ray attenuation coefficients for brine tagged with KBr (w) and decane tagged with iodododecane at potentials of 50 and 55 KV.

coefficients at the 50 kV potential, the linear attenuation coefficients for the two fluids are also similar at the 55 kV potential. The best contrast in the attenuation characteristics of the two tagged fluids occurs when the X-ray operating potentials are within 5 to 10 kV on either side of a prominent absorption edge for one of the two fluids.

Reference

1. National Institute for Petroleum and Energy Research, *Quarterly Technical Report for Jan. 1-Mar. 31, 1991, Vol. II, Energy Production Research*, DOE Report NIPER-529, April 1991.

PHASE 1 - RESERVOIR DATA BASE

Cooperative Agreement DE-FC22-83FE60149,
Project SGP28

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract Date:
Anticipated Completion: May 31, 1991
Funding for FY 1991: \$23,000

Principal Investigator:
James F. Pautz

Project Manager:
Chandra M. Nautiyal
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

EOR INCENTIVE PROJECTS SURVEY

Cooperative Agreement DE-FC22-83FE60149,
Project SGP30

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract Date: Aug. 18, 1989
Anticipated Completion: May 31, 1991
Funding for FY 1991: \$4,500

Principal Investigator:
James F. Pautz

Project Manager:
Chandra M. Nautiyal
Bartlesville Project Office

Reporting Period: July 1, - Sept 30, 1991

Objective

The objective of Phase 1 research is to develop in and output criteria for a reservoir database and to a develop conceptual design for the RELIANCE DBMS environment to meet those requirements.

Summary of Technical Progress

No work was done on this project this quarter. All project work was completed last quarter.

Objective

The objective of this project is to solicit completed FE-748 forms for the active incentive projects for calendar years 1987, 1988, and 1989. The data is to be reduced to an electronic media and validated.

Summary of Technical Progress

No work was done on this project this quarter. All project work was completed last quarter.

**INFLOW PERFORMANCE RELATIONSHIPS
FOR SLANTED AND HORIZONTAL
WELLS PRODUCING FROM
HETEROGENEOUS RESERVOIRS**

Cooperative Agreement DE-FC22-83FE60149,
Project SGP40

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract date: July 1990
Anticipated Completion: October, 1991
Funding for FY 1991: \$46,500

Principal investigator:
Aaron Cheng

Project Manager:
Thomas B. Reid
Bartlesville Project Office

Reporting Period: July 1 - Sept 30, 1991

Objective

The objective of this project is to develop Vogel-type,¹ inflow performance relationships (IPRs) for slanted and horizontal wells producing from heterogeneous reservoir systems under solution-gas drive.

Summary of Technical Progress

General Physical Interpretation of IPR Curves

Based on the generated IPR data in this study and the Vogel IPR curve,¹ the generated IPR results or curves follow the typical behavior of a solution-gas drive reservoir. The basic physical interpretations of an IPR curve are as follows. A normalized IPR curve is a plot of normalized flowing bottomhole pressure p' (y-axis) vs. normalized oil flow rate q' (x-axis), with $p' = p_{wf}/p_r$ and $q' = q_o/q_{o\max}$, where p_{wf} = flowing bottomhole pressure, p_r = average reservoir pressure, q_o = oil flow rate, and $q_{o\max}$ = maximum oil flow rate. The inverse slope of an IPR curve, dq/dp , represents the oil productivity index or can be viewed as a quantity proportional to the index.

Theoretically, for a one-phase (oil) flow case, fluid flow follows Darcy equation, and the oil productivity index is constant, and the IPR curve will be a straight line. For two-phase flow (oil and gas) where the critical gas saturation is reached, as pressure is depleted, more gas evolves from the liquid oil, and oil saturation decreases and gas saturation increases, assuming the water saturation remains constant. The saturation change leads to an increase in relative permeability ratio k_{rg}/k_{ro} , where k_{rg} is the gas relative permeability and k_{ro} is the oil relative permeability. Also the viscosity ratio μ_o/μ_g is

extremely high. For instance, at low pressures, this ratio can be as high as 100 and even at high pressures the ratio will be high.² Therefore, as pressure declines in two-phase flow, the rapid increase in the permeability and viscosity ratios impedes the oil flow drastically. This translates into a decrease in oil productivity index with decrease in flowing bottomhole pressure. Mathematically, this means that an IPR curve slope increases with decrease in pressure. This explains why the original Vogel IPR curve for a vertical well is concave to the right. A useful variable that may be used to predict concavity or curvature or shifting of an IPR curve to right or left is the producing gas-oil ratio (GOR). In general, for an oil reservoir initially producing at a pressure the same as the saturation pressure, as the oil depletion (N_p/N) increases, the subsurface reservoir gas saturations increases and the GOR increases, and the IPR curvature increases or shifts to right. In Vogel's original work,¹ the IPR curves for $N_p/N = 0.1, 2, 4, 6, 8$ and 10 % overlay each other, and it is unclear whether the IPR curve shifts from left to right or right to left. Up to a certain stage of depletion, e.g., $N_p/N = 10$ %, the gas phase becomes the dominant one, and decline of reservoir pressure is not as rapid as in the beginning; the result is a less rapid decline in oil productivity index as flowing bottomhole pressure decreases. The IPR curve loses its curvature as reported by Vogel for $N_p/N > 10$ %.¹ The IPR curve shifts to left under this condition. The shift of IPR curve from left to right and then right to left is also found in the base case horizontal IPR curves generated in this study and reported earlier. It is the subsurface two-phase flow condition that governs the ultimate IPR curve shape. The most critical parameter is the gas saturation, S_g , distributions surrounding the wellbore.

Comparison of Pressure and Gas Saturation Profiles for Vertical and Horizontal Wells

Using the inflow performance relationship (IPR) simulation results obtained earlier, the reservoir pressure and gas saturation distributions of the base case vertical and horizontal wells were generated at cumulative oil production $N_p/N = 0.1$ and 6 %. These distributions were used to aid in explaining the fundamental inflow phenomenon of these wells.

Figures 1 and 2 compare the reservoir grid pressures and gas saturations along the distance (x-direction of reservoir grid) from the wellbore respectively, for the vertical and horizontal wells at a flowing bottomhole pressure, p_{wf} , of 14.7 psia. Figures 3 and 4 show these comparisons at $p_{wf} = 600$ psia. At 0.1 % oil depletion, which almost represents the very beginning of the oil production, Fig. 1 shows that the horizontal well in general has a higher pressure along the x-direction wellbore distance while the vertical well has a lower pressure around the wellbore. This corresponds to a lower and higher gas saturation for the horizontal and vertical well, respectively (Fig. 2). Fig. 5 shows the IPR curves for vertical and horizontal wells at $N_p/N = 0.1$ %, indicating the horizontal IPR curve at 0.1 % depletion is more linear than the vertical well IPR

curve and is on its left. This can be explained by Figs. 1 and 2. The relatively lower gas saturation distributions around the horizontal wellbore than the vertical wellbore leads to a less concave IPR curve and is shown in Fig. 5. The pressure and gas saturation profiles for $p_{wf} = 600$ psia are quite similar to the one at $p_{wf} = 100$ psia. In the $p_{wf} = 600$ psia case, the differences between the corresponding vertical and horizontal well saturation profiles are not as big as the $p_{wf} = 100$ psia case. This will be expected as a higher pressure drawdown at $p_{wf} = 100$ psia will lead to a higher gas saturation distributions around the wellbore than the relatively lower drawdown at $p_{wf} = 600$ psia case. Based on the current findings, the gas saturation around the wellbore is the critical parameter to determine the shape or slope and oil productivity index of an IPR curve for both vertical and horizontal wells.

References

1. J. V. Vogel. Inflow Performance Relationships for Solution Gas Drive Wells. *J. Pet. Tech.*, pp. 83-93, January 1968.
2. H. C. Slider. *Practical Petroleum Reservoir Engineering Methods*. Petroleum Publishing Company, Tulsa, 1976.

Fig. 1 Reservoir pressure along x-direction distance from wellbore. Horizontal vs. vertical well. $p_{wf} = 100$ psia.

Fig. 2 Reservoir gas saturation along x-direction distance from wellbore. Horizontal vs. vertical well. $p_{wf} = 100$ psia.

Fig. 3 Reservoir pressure along x-direction distance from wellbore. Horizontal vs. vertical well. $p_{wf} = 600$ psia.

Fig. 4 Reservoir gas saturation along x-direction distance from wellbore. Horizontal vs. vertical well. $p_{wf} = 600$ psia.

Fig. 5 Inflow performance relationship (IPR) curves for horizontal and vertical well at 0.1% oil depletion.

**SUMMARY OF GEOLOGICAL AND
PRODUCTION CHARACTERISTICS OF
CLASS I, UNSTRUCTURED, DELTAIC
RESERVOIRS**

Cooperative Agreement DE-FC22-83FE60149,
Project SGP46

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract date: Nov. 1, 1990
Anticipated Completion: May 31, 1991
Funding for FY 1991: \$200,000

Principal Investigator:
Susan Jackson

Project Manager:
Edith Allison
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

**THIRD INTERNATIONAL RESERVOIR
CHARACTERIZATION TECHNICAL
CONFERENCE**

Cooperative Agreement DE-FC22-83FE60149,
Project SGP47

National Institute for Petroleum and
Energy Research
Bartlesville, Oklahoma

Contract Date: Dec. 1, 1990
Anticipated Completion: August, 1992
Funding for FY 1991: \$33,000

Principal Investigator:
Bill Linville

Project Manager:
Edith Allison
Bartlesville Project Office

Reporting Period: Apr. 1 - June 30, 1991

Objective

The objective of this project is to summarize the geological and production characteristics of Class I, fluvio-deltaic system reservoirs. This work is not intended as an exhaustive study; rather, it is a summary of what is generally known about clastic deltaic reservoirs and what areas have the greatest potential for further investigation to preserve economic access to the resource.

Summary of Technical Progress

Phase I of SGP46 has been completed, and the final report¹ has been submitted.

Reference

1. Department of Energy. *Opportunities To Improve Oil Productivity in Unstructured Deltaic Reservoirs*. DOE Report DOE/BC-91/6/SP, 1991, NTIS order No. DE91002237.

Objectives

The objectives of the Third International Reservoir Characterization Technical Conference are: (1) to explore methods to integrate engineering and geological disciplines to improve the understanding of fluid flow in petroleum reservoirs; (2) to review current practices, procedures, and technologies applied to reservoir characterization; (3) to identify problems related to current practices and procedures for accurate reservoir descriptions and the information and technology required to solve the problems; (4) to identify emerging technologies and promising directions for future research; and (5) to provide a means for technology transfer.

Summary of Technical Progress

The final program includes four tutorials, 28 oral presentations, and 24 poster presentations. Dr. Donald A. Juckett will give the opening address. He is director of the Office of Geoscience Research, U. S. Department of Energy.

Lawrence W. Teufel of Sandia National Laboratories agreed to give a tutorial on "Geomechanics for Reservoir Management" to replace Fred Suffridge who withdrew from the program.

Invitations to the authors' breakfast and instructions were distributed to all presenting authors.

All but four of the papers scheduled for the technical sessions were received; all but two for the poster session. The manuscripts were processed for printing and delivered to the printer for publication of Preprints. The technical session papers will be printed in Volume 1, and the poster presentations, in Volume 2. Preprints should be completed by Oct. 25.

Some 5,000 copies of the program were printed and mailed. Lists were obtained from the Engineers' Society of

Tulsa and the Tulsa Geological Society, in addition to the DOE lists and NIPER lists.

A two-page article about the conference was published in the September issue of *American Oil & Gas Reporter*, and reprints were prepared.

Copies of the program were distributed at the Society of Petroleum Engineers Annual Conference in Dallas, Oct. 6-9, at the NIPER booth.

Advance registration indicates that companies will, in general, allow only one, perhaps two, staff members to attend, whereas in 1985 and 1989 several from the same organization attended. These restrictions may influence total registration. At this time, total registration is predicted to be from 150 to 200.

MICROBIAL TECHNOLOGY

DEVELOPMENT OF IMPROVED MICROBIAL FLOODING METHODS

**Cooperative Agreement DE-FC22-83FE60149,
Project BE3**

**National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma**

**Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$300,000**

**Principal Investigator:
Rebecca S. Bryant**

**Project Manager:
Fred W. Burch
Bartlesville Project Office**

Reporting Period: July 1 - Sept. 30, 1991

Objective

The objective of this project is to develop an engineering methodology for designing and applying microbial methods to improve oil recovery.

Summary of Technical Progress

One of the major constraints to MEOR technology has been the lack of simulation data to adequately describe and predict the MEOR processes both in the laboratory and in

the field. During the 1980s, researchers at the University of Oklahoma and Southern California University studied transport of several different types of bacteria to produce one-dimensional models. It became apparent that microbial transport in porous media was an extremely complex phenomenon that required laboratory and field data to adequately model. While several attempts have been made to modify existing reservoir simulators to describe microbial processes, no model has yet fully incorporated all of the complex phenomena that are believed to be important. Also, no model has integrated laboratory and field data for microbial transport processes. Thus, an accurate reservoir simulator for MEOR methods can best be developed through an integrated program of acquisition of laboratory and field data with the feedback loop being the reservoir simulation model.

The unusual complexity of oil recovery by microbial formulations will obviously require close coordination between laboratory mechanistic studies and oil displacement experiments under carefully controlled conditions to develop and validate a computer model.

NIPER has amassed a wealth of laboratory and field data on the mechanisms of oil mobilization of microbial formulations and the effects of various design parameters on oil recovery efficiency. Research using laboratory experiments in FY90 began to define key mechanisms of oil mobilization. Work in FY91 continues to develop the critical parameters, correlations, and mathematical models to describe the physical phenomena that are important in MEOR methods and development of a mathematical computer simulator to model and predict performance of microbial formulations in oil recovery applications.

Laboratory data from NIPER are being used to develop correlations and mathematical models for specific phenomena, and linear coreflooding data will be used to test

the simulator in an iterative process. The simulator development and laboratory testing aspects of this project are carefully coordinated, so that the results from testing the simulator with oil displacement experiments will be used to design laboratory experiments to clarify and quantify certain physical effects from which correlations will be refined and modified that will be incorporated into the simulator. The simulator will be the primary deliverable from this research. The overall goal of the project is to develop a method for predicting and evaluating microbial EOR processes in porous media.

Work for milestone 3, "Compare Oil Mobilization Mechanisms of Microbial Species Used for Permeability Modification with Those Used for Microscopic Oil Displacement" was completed this quarter.

Work for milestone 5, "Correlate Laboratory Displacement Test Results with Mathematical Descriptions" continued. Coreflood experiments are being conducted to obtain information on microbial transport in 11-inch length, Berea sandstone core samples for incorporation in the numerical model. It is believed that after an initial adsorption of microbes on pore surfaces, a point would be reached at which all sites of adsorption would be saturated and cell transport and recovery would increase with subsequent injection of microbes. Volumes of the microbial formulation (washed cells without nutrient) were injected into cores at a rate of $0.5 \text{ cm}^3/\text{min}$, and the microbial concentration in the core effluent was determined. Subsequent cores had increasing injection slug sizes. Microbial concentrations were monitored using selective media. Before and after each microbial injection, a tracer injection was performed to see if adsorption of microbes caused any alteration in the interstitial velocity.

As reported in the last quarterly, a linear correlation was obtained between the amount of microbes injected and the amount of microbes recovered. A similar core experiment was conducted this quarter using nutrient with microbial cells instead of washed cells. The results of this experiment are shown in Fig. 1. A recovery of 98% of the nutrient indicates that the microorganisms were not present in the core long enough to metabolize the sugar. This also indicates that the sugar was not significantly retained in the core. The amount of microorganisms recovered (31%) corresponds very well to the linear correlation obtained in the previous experiments.

Fig. 1 Microbial/nutrient retention experiment.

Work for milestone 7, "Complete Development of Mathematical Descriptions for Oil Mobilization by Microorganisms Used in Permeability Modification Tests," continued. Gas production may be more likely to account for these pressure drops. An experiment was conducted this quarter to measure gas production in a Berea sandstone core. 0.1 PV of NIPER 6A, a *Clostridium* species, and 0.2 PV of 3% sucrose was injected into an 11-in. core. A pore pressure of around 85 psi was maintained throughout the coreflood. The core was shut-in for 4 days, and then gas production was measured using fluid displacement. Figure 2 shows the results of this experiment. Gas production increased rapidly until reaching a maximum value of almost 7 cm^3 after 1 PV of brine was injected under atmospheric conditions. These data will be used for the numerical simulator.

Fig. 2 Microbial gas production in a Berea sandstone core.

MICROBIAL ENHANCED WATERFLOODING FIELD PROJECT

Cooperative Agreement DE-FC22-83FE60149,
Project SGP13

National Institute for Petroleum
and Energy Research
Bartlesville, Oklahoma

Contract Date: Oct. 1, 1983
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$419,000

Principal Investigator:
Rebecca S. Bryant

Project Manager:
Edith Allison
Bartlesville Project Office

Reporting Period: July 1 - Sept. 30, 1991

Objectives

The objectives of this project are to determine the feasibility of improving oil recovery in an ongoing waterflood using microorganisms and to expand the initial pilot and determine the economics of microbial enhanced waterflooding. The scope of work includes continued monitoring of the Phoenix field site.

Summary of Technical Progress

The expanded microbial enhanced oil recovery (MEOR) project site is in Section 8, Township 24 North, Range 17E of Rogers County, Okla. This site is part of Chelsea-Alluwe field in the Bartlesville formation and was initially developed soon after Delaware-Childers field. The site is being waterflooded and is owned by Phoenix Oil and Gas, Ltd. This field is in an isolated area, with virtually no other oil-producing leases nearby.

Fluorescein was injected as a tracer on June 6, 1990. Samples were collected from all 19 injection wells at 2-h intervals the first day. Twenty-one producers were sampled 24 h after injection of tracer, sampled daily, then weekly, once a month, and finally, quarterly. Since the second day of sampling, the tracer response has never been higher than 0.30 ppm for any of the wells. The pattern of the fluorescein response seems to follow the same trend as that observed during the monitoring of the Mink Unit. There was an initial quick response of tracer from some of the nearest production wells; the response then leveled out to very low values. Fluorescein values seemed to peak at

145 d, and are still being monitored. Figure 1 shows the fluorescein values obtained for selected producers through 421 d after injection of tracer.

Wellhead injection pressures and volumes continue to be monitored and have shown no signs of plugging or any other problems. Samples taken from the injection and production wells have shown trace amounts of molasses (<0.005 wt/wt %), and samples will continue to be collected to determine if this is just a baseline noise concentration level. Figure 2 shows oil production values of the baseline and postmicrobial injection.

The amount of molasses injected was increased June 7, 1991, after molasses determinations at the wellhead showed that a lower concentration was being injected than previously calculated. The molasses may be consumed before it reaches the wellhead. Samples for molasses concentration determinations were collected at the injection wellheads to determine the concentrations now being injected.

Fig. 1 Tracer values for selected producers in the Phoenix site.

Fig. 2 Oil production from the Phoenix site through July 1991.

ENVIRONMENTAL TECHNOLOGY

TECHNICAL ANALYSIS FOR UNDERGROUND INJECTION CONTROL

**Cooperative Agreement DE-FC22-83FE60149,
Project SGP23**

**National Institute for Petroleum
and Energy Research
Bartlesville, OK**

**Contract Date: Oct. 1, 1989
Anticipated Completion: Sept. 30, 1991
Funding for FY 1991: \$35,500**

**Principal Investigator:
Michael P. Madden**

**Project Manager:
Alex Crawley
Bartlesville Project Office**

Reporting Period: July 1 - Sept 30, 1991

Objectives

The objective of this project is to provide technical assistance to the Department of Energy (DOE) on matters

related to Underground Injection Control (UIC) or other environmental topics related to oil and gas production.

Summary of Technical Progress

Work continued on preparation of an updated edition of "Environmental Regulations Handbook for Enhanced Oil Recovery," DOE Report DOE/BC/10355-1, 1983. The final draft was reviewed and revisions were made. The completed handbook will be submitted to DOE during the first quarter of FY92.

The handbook is intended to assist owners and operators of enhanced oil recovery (EOR) operations in acquiring some introductory knowledge of the various state agencies, the U.S. Environmental Protection Agency, and the many environmental laws, rules and regulations which can have jurisprudence over their permitting and compliance activities. It is a compendium of summarizations of environmental rules. It is not intended to give readers specific working details of what is required from them, nor can it be used in that manner. Readers of the handbook are encouraged to contact environmental control offices nearest to locations of interest for current regulations affecting them.

Enhanced oil recovery is often known in the oil industry as tertiary recovery. However, because it is more commonly called enhanced oil recovery in various environmental laws, rules and regulations, that is the term

used in this text. "Tertiary recovery" is any method used to recover more oil from a petroleum reservoir than would be feasible using primary or secondary recovering methods.

In primary recovery, naturally occurring forces (such as those associated with gas and liquid expansion or influx of water from aquifers) are utilized to produce oil. Primary recovery is often termed "free flowing" and is extended to include pumping assistance, when describing a well using this method of production. Conventional, secondary recovery methods, such as waterfloods (in which water is injected to supplement original reservoir forces and sweep more oil to producing wells), are not considered to be enhanced oil recovery under this definition.

There are three major EOR processes: (1) Thermal, which comprises two alternate methods -- steam injection and in situ combustion; (2) Chemical or micellar-polymer injection; (3) Gas or CO₂ injection. Typically none of these processes are used until a well or reservoir has ceased to produce oil economically through primary or secondary recovery techniques. Enhanced oil recovery is used only in existing or abandoned wells, reservoirs, and fields. Therefore, no effort was made to identify and summarize environmental laws, rules, and regulations covering exploration, drilling, and primary or secondary recovery operations per se. This handbook is focused on those laws and regulations that specifically apply to EOR, especially considering emissions from steam generators and underground injection of chemicals.

The U.S. Environmental Protection Agency (EPA) is the primary generator of environmental laws, rules, and regulations for the United States of America. Its acts, which are ultimately enacted into law by Congress, are intended to control or prevent pollution of the environment. Their spheres of interest include:

1. Air Pollution Control:

The Clean Air Act, amended through November 15, 1990, and corresponding state laws, and federal and state regulations.

2. Water Pollution Control:

The Clean Water Act, amended through May 2, 1989, and corresponding state laws, and federal and state regulations. This includes oil and hazardous substance spill notification and clean-up requirements.

3. Protection of Underground Water:

The Safe Drinking Water Act, amended through December 20, 1989, for underground injection control. States may apply these regulations through water pollution control programs or drinking water programs.

4. Solid Waste Management:

The Resource Conservation and Recovery Act and federal regulations. States' regulations vary considerably, but none of the oil and gas producing states listed in this handbook have regulations less stringent than federal standards.

Primary EPA environmental concerns for EOR methods listed in Table 1 are cross referenced to indicate issues or activities EOR operators need to be especially aware of to avoid conflict with regulatory agencies at state and federal levels of authority. A majority of concerns directly involve the effect of EOR activity on fresh water demand and protection. Although solid waste disposal is shown to be of lesser concern to EOR operators, it is an issue of increasing importance, especially the disposal of water treatment wastes and chemicals.

EOR operators need to be aware of the following conditions during the planning phase of their projects. Special rules, are or may be, applied in certain places such as coastal areas, wetlands, habitats of endangered species, or on federal or Indian lands. Generally, environmental restrictions are more stringent in those areas with regard to facility location and construction or method of recovery. EOR operations on lands administered by a federal agency such as the U.S. Geological Survey, Corps of Engineers, or the Bureau of Indian Affairs, may be cause for the preparation of an environmental impact statement (required by the National Environmental Policy Act).

The handbook is designed to be primarily a reference source for use in planning EOR projects. It is current as of August 1991. However, users need to be made aware of the fact that federal and states' environmental protection laws, rules and regulations are constantly being changed.

Users of the handbook are admonished to contact regulatory agencies in the states directly where they plan to initiate enhanced oil recovery projects, to obtain current specific working details of permitting and compliance requirements. They are also urged to contact appropriate federal agencies, especially the nearest regional EPA office. Current addresses and telephone numbers of regional EPA offices are indicated in the handbook.

The 15 states included in this handbook comprise the major oil producing states in the lower 48 contiguous states. There are other oil- and gas-producing states that may be of interest to EOR operators. It is suggested that the regulations in those states are not vastly different from those of the 15 states contained in this handbook. Users of this handbook who need information on states not included in it should contact the nearest regional EPA office for leads toward approaching proper state agencies for their environmental protection regulations affecting enhanced oil recovery activity.

TABLE 1
Primary Environmental Concerns (by process)

MEDIA	STEAM INJECTION	IN SITU COMBUSTION	MICELLAR-POLYMER	CO ₂ INJECTION
AIR	<ul style="list-style-type: none"> • SO₂, NO_x, and TSP* emissions from steam generators • Wellhead emissions of HC 	<ul style="list-style-type: none"> • HC and CO emissions from wells • SO₂, NO_x, TSP emissions from air compressors 	<ul style="list-style-type: none"> • Fugitive emissions from on-site manufacture of chemicals • H₂S emissions from wells 	<ul style="list-style-type: none"> • Leaks of CO₂ in process use or transport
WATER USE	<ul style="list-style-type: none"> • Significant water demand 	<ul style="list-style-type: none"> • Moderate water demand 	<ul style="list-style-type: none"> • Significant water demand 	<ul style="list-style-type: none"> • Significant water
WATER	<ul style="list-style-type: none"> • Disposal of produced water 	<ul style="list-style-type: none"> • Disposal of produced water • Aquifer contamination from low pH water with trace metals resulting from corrosion of well casings 	<ul style="list-style-type: none"> • Aquifer contamination from injected chemicals • Disposal of produced water • Spills/Leaks of chemicals to surface waters 	<ul style="list-style-type: none"> • Disposal of produced water • Aquifer contamination from low pH water and corrosion of well casings
SOLID WASTE	<ul style="list-style-type: none"> • Disposal of scrubber sludges • Disposal of water treatment wastes 	<ul style="list-style-type: none"> • Disposal of wastes from wellhead gas cleaning • Disposal of water treatment wastes 	<ul style="list-style-type: none"> • Disposal of wastes from on-site chemical manufacture • Disposal of water treatment wastes 	<ul style="list-style-type: none"> • Disposal of water treatment wastes

* TSP = Total suspended particulates.

END

**DATE
FILMED**

3 / 24 / 92