SECOND AMENDMENT AND EXTENSION TO
Annex III-Evaluation of Past and Ongoing Enhanced Oil Recovery Projects

Implementing Agreement Between
THE DEPARTMENT OF ENERGY OF THE UNITED STATES OF AMERICA
And
THE MINISTRY OF ENERGY AND MINES OF THE REPUBLIC OF VENEZUELA

Submitted by:

R. Michael Ray
Deputy Director
Bartlesville Project Office
U.S. Department of Energy

Edgar Paredes, Manager
Petroleum Engineering
INTEVEP, S.A.
Filial de Petroleos de Venezuela, S.A.

Approved By:

Thomas C. Wesson, Director
Bartlesville Project Office
P.O. Box 1398
Bartlesville, OK 74005

Juan Quetglas, Technology Coordinator
Petroleos de Venezuela, S.A.
Apartado Postal 169
Caracas 1010A. Venezuela

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
United States Department of Energy

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

FOREWORD

The Infill Drilling Predictive Model (IDPM) is in a style similar to previous Enhanced Oil Recovery Predictive Models which were developed for and in conjunction with the Chemical Task Group of the National Petroleum Council (NPC) for use in the 1982–1984 NPC study on enhanced oil recovery (EOR) potential. The model is designed to conform to the methodology and structure of the suite of models used in that study. This insures that all models calculate and report predicted oil recovery and economics in an identical manner. As do the other models, the IDPM contains an extensive set of default equations to calculate non-critical reservoir properties, flood properties, and economic criteria. The Department of Energy, Bartlesville Project Office, supported the NPC and has maintained the models since the NPC study was completed.

R. Michael Ray
Department of Energy
Bartlesville Project Office
Bartlesville, Oklahoma
United States of America

TABLE OF CONTENTS

SECTION 1 SUMMARY OF THE INFILL DRILLING PREDICTIVE MODEL

1.1	Introduction.....	1-1
	Development History and Overview	1-1
	Background.....	1-2
1.2	Discussion.....	1-8
	Recovery Mechanisms of Infill Drilling	1-8
1.3	Assumptions and Features.....	1-12
1.4	Streamtube Calculations	1-13
	Technical Overview.....	1-14
	Practical Considerations	1-20
1.5	Reservoir Simulator Calculations	1-30
	Fundamental Flow Equations and Their Solution	1-31
	Relative Permeability Relationships	1-37
	Methods of Modeling Continuity.....	1-37
	SSI Method	1-38
	Additional Net Pay Method	1-40
	Comparison of Methods to Model Continuity	1-41
	Simulation Printout	1-41
	Plot Output.....	1-46
1.6	Economic Calculations	1-46
	Estimating Risk	1-47
	Profitability Indices.....	1-49

SECTION 2 IDPM DATA ENTRY

2.1	Reservoir Data.....	2-1
2.2	Economic Data	2-10

SECTION 3 DEFAULT EQUATIONS

3.1	Reservoir Data.....	3-1
	Oil Viscosity	3-1
	Solution Gas-Oil Ratio	3-2
	Oil Formation Volume Factor	3-2

TABLE OF CONTENTS (continued)

3.2	Economic Data	3-3
	IDPM Treatment of Well Capital Costs.....	3-3
	Drilling and Completion Costs.....	3-4
	Cost to Equip New Producing Well.....	3-4
	Costs of Additional Secondary Production Equipment for a Primary Well Converted to a Secondary Well.....	3-4
	Costs to Convert a Producing Well to an Injection Well.....	3-7
	Costs to Upgrade Surface Processing Equipment and Lease Facilities for Secondary Recovery Operations.....	3-7
	Direct Annual Operating Costs for Secondary Recovery Operations.....	3-7
	Costs for Offshore Operations	3-8
	Oil Price Penalties	3-8
	Windfall Profit Tax.....	3-10

SECTION 4 IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

SECTION 5 VALIDATION OF IDPM AGAINST FIELD FLOOD RESULTS

SECTION 6 IDPM SENSITIVITY ANALYSIS

Number of Model Layers.....	6-2
Areal and Vertical Heterogeneity and Sweep.....	6-2
Injectivity (Average Permeability) and Vertical Sweep (Vdp).....	6-3
Viscosity Ratio (μ_o/μ_w) and Vertical Sweep.....	6-3
Viscosity Ratio (μ_o/μ_w) and Continuity (C).....	6-3
Infill Pattern Type and Plug Back.....	6-4
Oil Price and Depth.....	6-4

SECTION 7 IDPM SUBROUTINE GLOSSARY

SECTION 8 IDPM COMMON GLOSSARY

TABLE OF CONTENTS (continued)

SECTION 9 IDPM TREE STRUCTURE

SECTION 10 REFERENCES

SECTION 11 PROGRAM LISTING

APPENDIX Ia IDPM INPUT/OUTPUT FOR IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

APPENDIX Ib SimBest II INPUT/OUTPUT FOR IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

APPENDIX IIa SPE REFERENCE PAPERS FOR IDPM VALIDATION AGAINST FIELD FLOOD RESULTS

APPENDIX IIb IDPM INPUT/OUTPUT FOR IDPM VALIDATION AGAINST FIELD FLOOD RESULTS

APPENDIX IIIa SPE REFERENCE PAPER FOR IDPM SENSITIVITY ANALYSIS

APPENDIX IIIb IDPM BASE CASE INPUT/OUTPUT FOR IDPM SENSITIVITY ANALYSIS

LIST OF TABLES

- 1-1 Summary of Infill-Drilling Incremental Recoveries
- 1-2 Comparison of Methods to Model Continuity
- 1-3 Comparison of Methods to Model Continuity
- 1-4 Comparison of Methods to Model Continuity
- 2-1 Summary of State Codes
- 2-2 Sample Input Data
- 3-1 Coefficients for Drilling and Completion Costs
- 3-2 Coefficients for Costs to Equip New Producing Well
- 3-3 Coefficients for costs of Additional Secondary Production Equipment
- 3-4 Coefficients for Costs to Convert Producing Well to Injection Well
- 3-5 Coefficients for Costs to Upgrade Surface Processing Equipment
- 3-6 Coefficients for Direct Annual Operating Costs
- 3-7 Windfall Profit Tax Rates

LIST OF FIGURES

- 1.1 Program Logic
- 1.2 Schematic of Infill Cases
- 1.3 Effect of Areal Heterogeneity on Incremental Recovery
- 1.4 IDPM Output Example, Symmetry Element, $K_y/K_x = 1$, 5-spot to 5-spot infill
- 1.5 IDPM Output Example, Streamtube Orientation, $K_y/K_x = 1$, 5-spot to 5-spot infill
- 1.6 IDPM Output Example, Symmetry Element, $K_y/K_x > 1$, 5-spot to 5-spot infill
- 1.7 IDPM Output Example, Streamtube Orientation, $K_y/K_x > 1$, 5-spot to 5-spot infill
- 1.8 IDPM Output Example, Symmetry Element, $K_y/K_x > 1$, 5-spot to 9-spot infill
- 1.9 IDPM Output Example, Streamtube Orientation, $K_y/K_x > 1$, 5-spot to 9-spot infill
- 1.10 Continuity Associated with Non-Infill and Infill Spacing
- 1.11 Modeling Continuity by Changing Net Thickness
- 1.12 Investment Efficiency
- 3.1 Regions for Drilling and Completion Costs
- 3.2 Regions for Equipment, Conversion, and Operating Costs and Secondary Facilities
- 3.3 Oil Price Reduction Factor
- 4.1 IDPM Verification Against Black-Oil Simulation (SSI's SimBest II) - Oil Rate, 1/8 5-Spot
- 4.2 IDPM Verification Against Black-Oil Simulation (SSI's SimBest II) - Water Rate, 1/8 5-spot
- 4.3 IDPM Verification Against Black-Oil Simulation (SSI's SimBest II) - Water cut vs. Cumulative Oil Produced
- 5.1 IDPM Field Data Validation - Robertson Clearfork Unit, Observed and IDPM Calculated Oil and Water Production
- 6.1 Infill Drilling Predictive Model Sensitivity Runs - No. of Model Layers

- 6.2 Infill Drilling Predictive Model Sensitivity Runs - Areal (K_y/K_x) & Vertical (V_{dp}) Sweep
- 6.3 Infill Drilling Predictive Model Sensitivity Runs - Injectivity (Average Permeability)
- 6.4 Infill Drilling Predictive Model Sensitivity Runs - Viscosity Ratio (μ_o/μ_w) & Vertical Sweep (V_{dp})
- 6.5 Infill Drilling Predictive Model Sensitivity Runs - Viscosity Ratio (μ_o/μ_w) & Continuity (C)
- 6.6 Infill Drilling Predictive Model Sensitivity Runs - Infill Pattern Type and Plug Back
- 6.7 Infill Drilling Predictive Model Sensitivity - Oil Price and Depth

SECTION 1

SUMMARY OF THE INFILL DRILLING PREDICTIVE MODEL

1.1 INTRODUCTION

Development History and Overview

The Infill Drilling Predictive Model (IDPM) was developed by Scientific Software-Intercomp (SSI) for the Bartlesville Project Office (BPO) of the United States Department of Energy (DOE). The model and certain adaptations thereof were used in conjunction with other models to support the Interstate Oil and Gas Compact Commission's (IOGCC) 1993 state-by-state assessment of the potential domestic reserves achievable through the application of Advanced Secondary Recovery (ASR) and Enhanced Oil Recovery (EOR) techniques. Funding for this study was provided by the DOE/BPO, which additionally provided technical support.

The IDPM is a three-dimensional (stratified, five-spot), two-phase (oil and water) model which uses a minimal amount of reservoir and geologic data to generate production and recovery forecasts for ongoing waterflood and infill drilling projects. The model computes water-oil displacement and oil recovery using finite difference solutions within streamtubes. It calculates the streamtube geometries and uses a two-dimensional reservoir simulation to track fluid movement in each streamtube slice. Thus the model represents a hybrid of streamtube and numerical simulators.

Features of the model include the following:

- Analysis for 5-to-5 and 5-to-9-spot drilldowns.
- Initiation of infill drilling at a user-specified water cut or date.
- Two methods of modelling the increase in continuity due to infill drilling - one based on increasing the relative permeability of the reservoir, the second based on adding another layer.
- Output includes a forecast of production complete with project economics.

The architecture of the IDPM follows that of EOR models published in the past by the DOE. For a single pattern, functions for oil and water rate versus time are computed subject to a user-specified ending water cut or date. The functions are passed to an economics routine where they are scaled up for the entire entity (field/reservoir) under consideration. Input data for drilling, completion, injection, and operating costs together with a pattern development schedule allow the computation of before- and after-tax discounted cash flow. Incremental economics are calculated by comparing the infill project to continued waterflood. A logic diagram of the software is shown on Figure 1.1.

Background

Infill drilling of pattern waterfloods has received remarkably little attention from both the public and professional communities. Given the right circumstances, this process can compete favorably with enhanced oil recovery (EOR) processes on a recovery basis for much less investment and operating cost. And yet it appears that there are no research institute programs, university projects, government programs or tax incentives to encourage the development and application of infill drilling. There is virtually no technical literature on the subject, as compared to EOR, and until recently there was very little field data to support or deny any claim concerning the benefits of infill drilling.

Over a decade ago, van Everdingen (van Everdingen, 1980) provided our industry with yet another service by raising a controversy around infill drilling. His statement that, "Infill drilling, if done properly, can be used to recover at least as much oil as the U.S. already has produced," (120 billion bbl) created a controversy that still goes on today. Although this statement may be exaggerated for the U.S. as a whole, it is interesting to note that until the IOGCC study, no comprehensive analysis had been conducted to determine just how much could be recovered. As a result of his original position papers, van Everdingen was asked by the DOE to investigate the subject further. His resulting proof was inconclusive, primarily due to a lack of good field data and reservoir description.

Holm (Holm, 1980) provided a thought-provoking discussion of van Everdingen's work, but his analysis was limited by the same lack of field data. At that time there was very little technical analysis of infill drilling as an incremental recovery process. Holm's estimate of the potential of infill drilling was much more conservative, "with our best efforts we could add to U.S. reserves about 1 to 1.5 billion bbl/yr for about 10 years." Holm's estimated national average was 34 to 47 mbbl per infill well. In our current times of reduced reserve additions from exploration, such additions would be most welcome.

A very significant paper by Barber, et.al. (Barber, 1983) confirmed Driscoll's (Driscoll, 1974) observations of 2 to 8 percent incremental recovery from infill drilling. Barber analyzed nine sets of field data showing very positive incremental recovery due to infill drilling. Two of the reservoirs, Dorward and Sand Hills, were primary projects and thus cannot be used for comparison with secondary pattern floods. The Howard-Glasscock reservoir is a peripheral flood and as such is also not directly comparable. Data from Barber, Driscoll, and Ghauri (Ghauri, 1980) are summarized in Table 1-1 for a total of 1323 wells with an average incremental recovery of 107.1 mbbl per infill well. This average is greater than Holm's by a factor of 2 to 3, but is weighted specifically for West Texas carbonates.

If Holm's more conservative estimate is correct, 10 to 15 billion bbls is still a very large number for a virtually unstudied incremental recovery process. This represents 2 to 3 percent of the national "original oil in place" of 460 billion bbls. Current field data for a limited number of projects shows estimated infill recoveries of about 5 percent OOIP. Although the true benefit of infill drilling is unknown, its potential is well established.

The National Petroleum Council (NPC) published a study on EOR potential in the U.S. (NPC, 1984) which concluded that, "as much as 14.5 billion bbl of additional oil could ultimately be recovered with the successful application of existing EOR technology, under current economic conditions." NPC's conclusion assumes a 30 \$/bbl nominal crude price and 10% minimum discounted cash flow rate of return (DCFROR). At 20 \$/bbl, the projection is as follows:

<u>EOR Process</u>	<u>Additional Recovery</u>
Thermal	4.4
Miscible	2.0
Chemical	<u>1.0</u>
Total	7.4 Billion bbl

Thus, while there is significant upside potential due to technical improvements, at 20 \$/bbl, there is insufficient incentive to develop it. With crude prices at 20 \$/bbl and below, infill drilling would appear to have equal or greater potential than EOR processes.

The combination of infill drilling and EOR in the same project can be very effective. Restine (Restine, 1987) has described an infill drilling project carried out after completion of a tertiary steamflood, and reported incremental oil recoveries of 4 to 7 percent OOIP after infilling from 1.25 to 0.625 acres per well. Alternatively, infill drilling prior to tertiary miscible or chemical process has the benefits of better pattern control, shorter project life (better ROR), and improved areal/vertical sweep. The incremental recovery generated by the infill wells may be more than sufficient to pay out these wells prior to the tertiary project's initiation.

In the foregoing, the word potential has been stressed with regard to additional recovery via infill drilling. This is because the number and quality of infill locations has never been determined on a national basis. The premise here is that a tool is needed to facilitate screening of the many available oil fields in order to quantify the national potential for added recovery and to identify candidates for field evaluations.

Accordingly, the current project was undertaken. Its objectives may be described as follows:

1. To develop the technology of a three-dimensional (stratified, five-spot), two-phase (oil and water) infill drilling predictive model (IDPM), in the form of computer software based upon the mathematics and engineering concepts to be discussed below.
2. To supply the IDPM computer software and associated documentation.

The IDPM documentation includes instructions for model use, a programming guide, model sensitivity runs, and other information as described in the Statement of Work of the original proposal. The computer software consists of IDPM source code suitable for a mainframe computer or for a IBM-compatible personal computer. A logic diagram of the software is shown on Figure 1.1.

TABLE 1-1**SUMMARY OF INFILL-DRILLING
INCREMENTAL RECOVERIES**

Project	No. of Wells	Proj. Vol. (10⁶ bbl)	Vol. per Well (10³ bbl)	Infill Spacing (acres)	Volume (bbl/acre)
Means San Andres					
20-acre infills	141	15.4	109	20	5,450
10-acre infills	16	1.2	75	10	7,500
Fullerton Clearfork	254	24.6	97	20	4,850
Robertson Clearfork	138	10.7	78	18	4,330
IAB (Menielle Penn)	17	1.7	100	40	2,500
Hewitt	15	0.4	27	5	5,400
Loudon	50	0.97	19	10	1,900
Yates Sand	247	14.6	59	10	5,900
Grayburg	17	2.44	144	20	7,200
Wasson San Andres (Denver Unit)	293	51.0	174	20	8,700
North Riley (Clearfork Unit)	91	13.2	145	20	7,250
Dollarhide Clearfork ("AB" Unit)	44	5.52	125	20	6,250
Total (or well average)	1,323	141.7	107.1	17.5	6,120

PROGRAM LOGIC

Figure 1.1

1.2 DISCUSSION

Recovery Mechanisms of Infill Drilling

Driscoll (Driscoll, 1974) ranked the factors responsible for increased oil recovery when secondary patterns are infill drilled in the following order of importance: improved reservoir continuity, improved areal sweep, improved vertical sweep, recovery of wedge edge oil, and improved economic limit.

Improved reservoir continuity is the dominant effect of infill drilling in West Texas carbonates. These reservoirs display significant geologic variation and compartmentalization, and a given well spacing leaves unswept the compartments that are not directly contacted by existing wells. Gould and Sarem (Gould, 1989) have shown that the data of Barbe and Schnobelen (Barbe, 1986), Barber et al (Barber, 1983), Driscoll (Driscoll, 1974), and Ghauri et al (Ghauri, 1980), all confirm this effect. Improved continuity is primarily responsible for the higher than average incremental recoveries per infill well reported by these authors and by Laughlin et al (Laughlin, 1987).

Improved areal sweep is accomplished by reversing the original streamlines and sweeping across previously unswept areas (sweet spots) as shown schematically in Figure 1.2 for a five-spot pattern. Figure 1.2-A shows the streamlines prior to infill drilling, and 1.2-B shows the corresponding oil saturations. In Figure 1.2-C, the original producer is converted to an injector after the completion of a new producer at the infill location. The new streamlines sweep across the area of highest oil saturation.

The amount of incremental recovery due to improved areal sweep depends on the following factors: the degrees of areal heterogeneity or anisotropy, the water cut at the economic limit, the water cut at which infilling occurs, and the mobility ratio of the flood.

SCHEMATIC OF INFILL CASES

Before Infill

Streamlines

Oil Saturations

After Infill

Streamlines

$V_{DP} = 0.60$ 3 Layer Completion

Figure 1.2

For example, Figure 1.3 shows the effect of both directional permeability and viscosity ratio on infill recovery, as determined in the simulation study of Gould and Munoz (Gould, 1982). The higher the ratio of x-direction to y-direction permeability, the greater the infill recovery. This effect is mitigated at high viscosity (mobility) ratios, as the bypassing of oil by fingering takes over.

Improved vertical sweep is usually expressed as a function of the Dykstra-Parsons coefficient of permeability variation (V_{dp}) in multilayer systems. Some idea of cross flow between layers is often an additional consideration. During an infill drilling project, new wells are completed and existing producers are converted to injectors. An opportunity exists at this point to mechanically isolate previously swept zones to maximize vertical sweep. The efficiency of these recompletions depends upon the degree of cross flow between the new (active) zones and the isolated (thief) zones.

Recovery of wedge edge oil may occur as pattern size is decreased, because more oil can be swept near the oil-water contact or stratigraphic features. This is strictly a geometry effect, but can result in flooding of virtually unswept zones.

Improved economic limit of a project which has been infilled results from changes in operating procedures. One of the significant economic benefits of infill drilling is the acceleration of oil recovery. In addition to increasing the number of producers, the field injection rate is increased by more than the well ratio might indicate since the pressure drop between injector and producer occurs over a shorter distance. The operating costs are also reduced, since the water cut is significantly decreased. The actual amount of improvement in economic limit is very company and project dependent, but could easily be in the range of one to two percent OOIP.

These recovery mechanisms form the technical basis for the oil recovery algorithm, and to a lesser degree, the economic algorithm in the IDPM.

EFFECT OF AREAL HETEROGENEITY ON INCREMENTAL RECOVERY

Figure 1.3

The IDPM is switch-selectable for either non-infill or infill cases and an option in the model allows the calculation of the incremental oil recovery and economics of infill relative to non-infill waterflooding. The architecture of the IDPM is similar to that of the other predictive models in the series: in-situ combustion, steam drive (Aydelotte, 1983), chemical flooding (Paul, 1982) and CO₂ miscible flooding (Paul, 1984). In the IDPM, an oil rate versus time function for a single pattern is computed and then is passed to the economic calculations. Data for reservoir and process development, operating costs, and a pattern schedule (if multiple patterns are desired) allow the computation of discounted cash flow and other measures of profitability.

The IDPM is a three-dimensional (stratified, five-spot), two-phase (water and oil) model which computes water-oil displacement and oil recovery using finite difference solutions within streamtubes. The program calculates the streamtube geometries and uses a two-dimensional reservoir simulation to track fluid movement in each streamtube-slice.

The IDPM computes the predicted oil recovery and the associated economics scaled to the entire field, for waterfloods including infill drilling at a user specified water cut. Recovery calculations are computed for the element of symmetry of a layered five-spot pattern.

1.3 ASSUMPTIONS AND FEATURES

The major assumptions in the IDPM include:

1. Compressible fluids and rock.
2. Streamtubes do not change shape with water cut.
3. Streamtubes are independent of mobility ratio.
4. Cross flow between layers within each streamtube.
5. Each layer is homogeneous (perm, porosity, thickness).
6. Layers are anisotropic.

IDPM features include:

1. Recovery as a function of pore volumes injected.
2. Displacement sweep calculated within streamtubes by cross section simulation in cross flow cases. (One-dimensional simulation without crossflow.)
3. Areal sweeps accounted for by streamtube shapes.
4. Streamtube shapes are a function of k_y/k_x ratio.
5. Vertical sweep by cross flow calculations.
6. Effect of connectivity (reservoir continuity) in reservoir modelled by changes in relative permeability endpoints with spacing.
7. Injectivity effects of infilling can be modelled by switching to constant pressure injection at infill after rate specification for non-fill. Alternatively the user can specify the injection rate for the infill case.
8. Economics calculated on discounted and undiscounted cash flows for non-infill, infill, and incremental cases.
9. Default reservoir and economic parameters included in the program for most input data.

1.4 STREAMTUBE CALCULATIONS

The generation of streamtubes is a critical aspect of the IDPM software. Recall from the Program Logic diagram given earlier that streamtubes are generated as the starting point both for non-infill and infill waterflood simulation. To promote clarity, the discussion will be given in two parts: (1) an overview of the theory and mathematics that form the basis for the IDPM software, and (2) a discussion of the practical aspects of its implementation and the information supplied to the user.

Technical Overview

The geometries of the streamtubes needed for the waterflooding simulation are obtained from a two-dimensional steady-state areal model of the symmetry element taken from the overall well pattern. This areal model is treated by the Finite Element Method wherein the following assumptions prevail:

1. Unit mobility ratio displacement at steady-state conditions, or, pressures alone may be computed for pseudo-steady state flow.
2. Flow is two-dimensional (x,y) and is not affected by capillarity, gravity, miscibility, phase changes, or relative permeability effects. Flow is governed by Darcy's law and the continuity equation.
3. Flow properties (transmissivity and generation terms) may vary from element to element, but not within any element. Within any element, flow is assumed to be uniform (unidirectional). Anisotropic heterogeneity is allowed, i.e. $k_y \neq k_x$
4. The finite elements themselves are triangular, and pressure is assumed to be given by a linear basis function within any element.

Formulation of this finite element model is tied to the fundamentals of reservoir fluid flow theory which will be briefly reviewed. That will be followed by a discussion of the derivation of streamtubes from the solution of the finite element problem.

The partial differential equation governing fluid flow through a porous medium is known as the diffusivity equation. In its commonly used form, it is expressed as (Matthews and Russell, 1967):

$$\nabla \left(\frac{k}{\mu} \nabla P \right) = \phi c \frac{\partial P}{\partial t}$$

where k is the permeability of the medium, μ is the fluid viscosity, P is the pressure, ϕ is the porosity, c is the compressibility, and t is time.

When the pressure profile in the reservoir stabilizes, such that no changes in pressure occur with time, the reservoir is said to be under steady-state flow conditions. This condition will eventually occur in all closed reservoirs where injection and production are balanced. The state that is reached in a closed reservoir when injection and withdrawal are not balanced is known as pseudo-steady state flow; in this instance, a point in time is reached after which the pressure declines (or increases) uniformly throughout the reservoir.

For planar flow, with constant (but not necessarily homogeneous) permeability, porosity, viscosity, compressibility, and thickness 'h', the diffusivity equation for steady-state or pseudo-steady state flow conditions may be written as

$$\nabla \cdot \left(\frac{kh}{\mu} \nabla P \right) = f$$

where f denotes a source term. The source term is 0 for steady-state flow and equal to $\phi ch \frac{\partial P}{\partial t}$ for pseudo-steady state flow. This equation is a Laplace equation for $f=0$ or a Poisson equation for $f \neq 0$, and may be solved by the finite element method.

The finite element method is a numerical procedure for dealing with boundary value problems (Zienkiewicz, 1965). It involves minimizing an appropriate integral functional and is an extension of the classical Rayleigh-Ritz methods. The method involves dividing the area over which a solution is desired into a number of elements connected by nodes. A variety of different shapes for the elements can be used; for example, triangles, rectangles, quadrilaterals, etc. Triangles provide a simple form permitting close approximation to boundary shapes and may be easily subdivided for better definition; for this reason, triangular finite elements are utilized in this study.

Within each element, a basis function describing the pressure distribution as a function of the nodal pressures (at the vertices of the triangle, or other points as needed) is assumed. This basis function could be a polynomial, or a sine or cosine expansion, or other arbitrary

functions; for simplicity and ease in programming, and to provide rapid solutions, a linear basis function has been applied. Within a typical triangular element defined by the nodes (vertices) i, j, and k, the pressure P specified by a linear basis function (i.e., linear interpolation) is

$$P(X,Y) = \frac{1}{2\Delta} \left[(a_i + b_i X + c_i Y)P_i + (a_j + b_j X + c_j Y)P_j + (a_k + b_k X + c_k Y)P_k \right]$$

$$\Delta = \frac{1}{2} \det \begin{vmatrix} 1 & X_i & Y_i \\ 1 & X_j & Y_j \\ 1 & X_k & Y_k \end{vmatrix}$$

and $a_i = X_k Y_j - X_j Y_k$, $b_i = Y_j - Y_k$, $c_i = X_j - X_k$, etc. in cyclic order ijk with ijk arranged in counter clockwise order.

As demonstrated in Zienkiewicz and Cheung, the solution of the Poisson equation

$$\frac{\partial}{\partial x} \left(K \frac{\partial P}{\partial x} \right) + \frac{\partial}{\partial Y} \left(K \frac{\partial P}{\partial Y} \right) = f$$

is determined by minimizing a functional, assuming constant K and f within any given element. The equations which result are nodal equations, for pressure as nodal values. The

contributions to each node from each element connected to that node are then added together, and ultimately a set of simultaneous linear equations is obtained:

$$[A][P]=[Q]$$

in which A is an N x N matrix (where N is the number of nodes), P is a 1 x N matrix to be determined, and Q is a (known) 1 x N matrix relating to the rate at each node.

The coefficient matrix A is determined from a subsidiary matrix S^e for each element. The S^e matrix depends only on the geometry and flow constant K of the element e. The general term of the 3x3 S matrix for the finite triangular element ijk is

$$S_{ij}^e = \frac{K^e}{4\Delta^e} (X_{jk}Y_{ki} + Y_{jk}Y_{ki})$$

when K^e is the flow constant (kh/μ for the element, Δ is the area of the element, and $X_{jk} = X_j - X_k$, etc. The S matrix is symmetric and positive definite. For non-obtuse triangular elements, the following relation holds

$$S_{ii} = -S_{ij} - S_{ik} > 0 \quad (S_{ij} \leq 0, S_{ik} \leq 0)$$

For non-obtuse triangular elements, the matrix S is thus loosely diagonally dominant ($S_{ij} \geq |S_{ij}| + |S_{ik}|$) and the coefficient matrix A will also be of this form.

The general term of the coefficient matrix A is determined by summing the contributions of the S matrices over the elements any two nodes have in common; thus,

$$A_{ij} = \sum S_{ij}^e$$

where the summation is over all elements in common between nodes i and j and where the superscript e denotes the element dependence. For $i=j$, the number of elements to be summed over will be the number of elements connected to the node i; for $i \neq j$, the number of elements to be summed over will be 0, 1, or 2, depending on how many elements are in common

between the two nodes. Because a single node will not commonly be connected to more than a few other nodes, the matrix A will generally be sparse.

The Q matrix (vector) of rates at a node is composed of two parts - a source term and a generation term. If the source at a node i is q_i and the node defines elements with generation f^e (being the right side of Poisson's equation $\nabla \cdot (K \nabla P) = f$) the general term of the Q matrix is

$$Q_i = q_i + \sum \frac{1}{3} f^e \Delta^e$$

where the summation is over all elements containing node i.

The matrices A and Q are thus seen to be known and the solution of Poisson's equation has been reduced to finding the solution of $[A] [P] = [Q]$. There are numerous methods available to solve sets of linear equations of this type. Among the properties of the coefficient matrix A are that it is symmetric ($A_{ij} = A_{ji}$), positive definite (implies a number of nice properties, such as a positive determinant, etc.), loosely diagonally dominant ($A_{ii} \geq \sum_{j \neq i} |A_{ij}| > 0$) and it is sparse. Consider a finite element network with, for example 500 nodes, with an average node connected to 6 elements; the coefficient matrix A would have $500 \times 500 = 250,000$ entries, of which only $500 \times 6 = 3000$ (about 1.2%) are non-zero.

A successive over-relaxation (SOR) scheme has been used to solve the system of linear equations. This method involves utilizing existing values of $P_1, P_2, \dots, P_{i-1}, P_{i+1}, \dots, P_n$ to compute the value of P_i , the pressure at node i from its corresponding equation. The pressure computed for the node is then over-corrected ("over-relaxed") to try to account to some extent for future corrections in other pressures. For convergence, the change in pressure at the node during the iteration should be between one and two times the computed change in pressure that yields a straight equality; that is, the over-relaxation parameter (called ω "omega") must be between 1 and 2. Iteration is continued to some maximum number of

iterations allowed, or until the change in any nodal pressure becomes less than some prescribed tolerance. Details of the method may be found in most matrix algebra texts.

Successive over-relaxation has two basic difficulties in application: first, a good initial estimate for pressure will greatly reduce computational time; second, for best results, an optimum overrelaxation parameter should be used. Neither of these drawbacks is relevant to the problem at hand. The initial estimate for pressure may be obtained using a coarse grid of elements, with interpolation to obtain an estimate for finer grids. By using this method for the types of problems the program is designed for, convergence is rapid for overrelaxation parameters in the range of 1 to 2.

Once pressure has been determined at the nodal points, it can be interpolated at any point desired. As well, the nodal pressures determine the direction of flow within an element, and its magnitude.

In order to obtain sufficient resolution of the detail for flux patterns within the areal model, one can start with a very coarse finite element mesh and, after solving the problem for that mesh, refine it and re-solve it in as many stages as required to achieve the desired level of solution detail.

The refinement of the grid is accomplished by interpolating a new node between every two connected nodes. Then, every element is divided into four new elements by connecting the interpolated nodes; the four elements replacing an original element are identical in shape to the original element, and each contains one quarter of the area. The number of elements in the fined-up grid is exactly equal to 4 times the number of elements in the original grid, while the number of nodes is multiplied by two or more.

The "final" solution to the finite element problem may be analyzed in various ways. Isobars are readily plotted from the pressure solution alone. Streamlines, which in a homogeneous medium lie orthogonal to the isobars, require a bit more computation. They would be tracings of flux lines from source to sink, based on the flux vector function for which an x-component and a y-component may be computed at any coordinate point. One

definition of a streamtube, then, would be an elongated area enclosing a bundle of streamlines, all of which start and end at the same source/sink pair, through which a known volumetric flow of fluid occurs. In simple, two-well patterns, these could be delineated by a contouring of the stream function which may be computed as the line integral of the flux vector along any given isobar. One chooses the width or density of streamtubes to fulfill his requirement for detail in analyzing flow phenomena within the finite element model.

Practical Considerations

Generation of streamtubes in the "real world" of IDPM requires a few additional considerations, superimposed on the technical picture given in the preceding section.

First, we have the matter of well rates to be imposed on the finite element model. Their magnitudes do not matter because the geometry of the streamlines varies only with their relative strengths. When there is one injector and one producer or when the permeability is isotropic, the problem is trivial. However, under anisotropic conditions and with multiple wells of a kind, the fact that we are dealing with symmetry elements requires an external knowledge of their relative magnitudes. Thus, for each of the various anisotropic cases, small black-oil simulation models of the symmetry elements were devised to obtain rates for steady-state flow for a wide range of y-direction to x-direction permeability ratios. Simulator results were treated as raw data to obtain correlations of relative well rate with permeability ratio. These correlations, usually in the form of small tables with an interpolating function, are imbedded into the IDPM source code.

In IDPM, a fine Cartesian grid is used as the medium on which to define the streamtubes. This makes it advantageous to impose a mild restriction on the shape of the triangles in the finite element mesh. By requiring them to be isocles right triangles with their legs parallel to the coordinate axes, the nodes always coincide with cell corners or cell centers in a Cartesian grid of an appropriate increment. This improves the speed and precision of the software in re-mapping the finite element solution in preparing to generate streamtubes.

The finite element solution is represented on the Cartesian grid in terms of the x-component and y-component of flux associated with each grid cell. The FORTRAN arrays QX and QY hold this information which is useful in two different ways: (1) summing (numerically integrating) the total flux crossing an arbitrary line, such as a circle around a source, and (2) tracing a streamline from any given point toward either its source or its sink.

The total flux from a source (or toward a sink) is allocated over some appropriately chosen number of streamtubes. Around any source or sink a circle may be drawn, and points on this circle where streamtube boundaries cross can be found using the QX and QY data. From these points, QX and QY data also support the computations which trace out the bounding streamlines. In principle, then, this is all that is needed to define the geometry of the streamtubes.

If there are multiple sinks and/or multiple sources, one can visualize adjacent streamtubes starting, say, at a source but ending at different sinks. There are two implied difficulties here: (1) proper allocation of the total rate to each streamtube such that no streamtube would tend to split and end at two different sinks, and (2) tracing the bounding streamline between two adjacent streamtubes that must end at different sinks. The former problem is handled by a simple search for the circle crossing point of the unstable bounding streamline to obtain the correct allocation of streamtube rates. The problem of the bounding streamline is readily solved to a good approximation by tracing streamlines that are slightly to either side of the streamtube boundary and then splitting the space between them equally. The latter technique, in fact, is used universally because there are other cases where adjacent streamtubes cannot share a common bounding streamline throughout their length.

Once the geometries of the streamtubes are known (and portions of each source and sink rate allocated to them), the only remaining step is to form the finite difference grid within each of them. The fine Cartesian grid underlies their geometric definition in that the tracing of streamlines and assigning of space between them is done in terms of tagging fine grid cells. Thus, the formation of finite difference cells is also done in terms of assigning fine grid cells to

mega-cells within each of the streamtubes. This is accomplished, streamtube by streamtube, by (1) computing for each fine grid cell its relative distance from the source and sink, (2) sorting them on their relative distances and then (3) clumping them into mega-cells of equal (as close as possible) volume. The number of these finite difference cells per streamtube is chosen by the user to give the desired level of detail in waterflood simulation results. Forming the mega-cells to have roughly equal volume minimizes the restriction which must be imposed on timestep size in order to maintain stability during waterflood simulation.

In order to allow the user to understand the reservoir mechanics of infill drilling, IDPM supplies a number of items of printed output. This starts with relative permeability tables that apply to the well spacing involved. (These will be discussed in detail in the section to follow.) Next, there is a depiction of the symmetry element to be modelled, showing its positioning in the original overall (5-spot) well pattern. After the geometric layout of the streamtubes within the symmetry element has been determined, a depiction of this geometry is presented. The printout shows exactly which cells in the fine Cartesian grid are assigned to each streamtube. After the finite difference grid within each streamtube has been formed, another printout gives a graphic depiction showing the clumping of fine grid cells into mega-cells. There is also a detailed tabular printout which gives the dimensional and positional properties of these mega-cells for each streamtube. Both of the latter two printouts can easily be omitted if they do not interest the user.

Six full-page figures follow. These show photocopy reductions of actual IDPM printout to illustrate some of the points made in the discussions above. First, there are two depictions, for isotropic permeability, of a symmetry element within the overall field showing injector and producer locations for both non-infill and infill well patterns (Figure 1.4). Next, those same two symmetry elements are shown with streamtubes depicted by means of single printer characters giving the streamtube number assigned to each of the fine grid cells (Figure 1.5). Figures 1.6 - 1.9 show the same graphics but for particular infill patterns.

IDPM OUTPUT EXAMPLE
Symmetry Element, $K_y/K_x = 1$
5-spot to 5-spot infill

Figure 1.4

IDPM OUTPUT EXAMPLE
Streamtube Orientation, Ky/Kx = 1
5-spot to 5-spot infill

Figure 1.5

IDPM OUTPUT EXAMPLE **Symmetry Element, $K_y/K_x > 1$** **5-spot to 5-spot infill**

Figure 1.6

IDPM OUTPUT EXAMPLE Streamtube Orientation, Ky/Kx > 1 5-spot to 5-spot infill

STREAM TUBES - AFTER INFILL

STREAM TUBES - BEFORE INFILL

Figure 1.7

IDPM OUTPUT EXAMPLE **Symmetry Element, $K_y/K_x > 1$** **5-spot to 9-spot infill**

Figure 1.8

IDPM OUTPUT EXAMPLE Streamtube Orientation, $K_y/K_x > 1$ 5-spot to 9-spot infill

STREAM TUBES - AFTER INFILL

STREAM TUBES - BEFORE INFILL

Figure 1.9

Finally, there is the matter of initial saturation conditions for the streamtube finite difference grids. To start the non-infill case, of course, oil saturation is uniform. At the start of the infill case, however, the oil saturation in each cell must reflect the distribution that existed at the point in time where infill would have occurred in the non-infill case. Since the geometries of the streamtubes in those two cases are never the same, the mega-cells will always overlap in an irregular manner. This is resolved by once more resorting to the fine Cartesian grid, first mapping mega-cell saturations from the non-infill grid (at the time for infill) back onto the fine grid. Then initial saturation for each infill mega-cell is obtained by volumetric averaging over its fine grid cells. (Cell volumes in the fine grid are all the same except for those on the boundary.) The result is no loss of material balance in the transition to the infill case.

1.5 RESERVOIR SIMULATOR CALCULATIONS

The production/injection performance of each well in the modelled element of symmetry is calculated by summing up the performance of each streamtube described in the previous section. The performance within each streamtube -- or stack of streamtubes for vertical communication cases -- is based on a *finite difference simulation*.

The production end of each streamtube is fixed at a constant pressure -- slightly less than the initial reservoir pressure -- and the injection end of each stream is set at a constant water injection based on the user input total pattern injection rate. For non-infill runs the allocation of the input rate to each streamtube is based on the range of stream function values within each streamtube from the calculations described in the previous section. For infill cases, if no injection rate is specified, the pressure at the injection end of each streamtube is set at the average pressure from all the injection cells in the non-infill case. In this manner the increased injectivity due to infilling is automatically calculated by the simulator.

With these boundary conditions the water-oil displacement in each streamtube -- or stack of streamtubes -- is calculated by the reservoir simulator as described below.

Fundamental Flow Equations and Their Solution

The fundamental flow equations and their solution constitute the heart of a fluid flow simulator. The derivation of the equations is simple in concept, though fraught with mathematical manipulation. The following is based on the 3-D three-phase treatment given by Breitenbach et al (Breitenbach, 1968).

A fundamental flow equation can be derived for each phase in a streamtube by combining the law of conservation of mass, the law of force, and thermodynamic relationships that describe the pressure-volume-temperature behavior of the fluid. The law of conservation of mass simply states that for each cell of porous media:

$$\begin{aligned} &(\text{Net flow of mass}) + (\text{change of mass in block}) \\ &+ (\text{mass produced}) = 0. \end{aligned}$$

In other words, it is a mass or material balance that states that no mass can be gained or lost from the system. The law of force used is Darcy's law. The thermodynamic relationships that are used are found experimentally, and consist of the slightly compressible fluid descriptions. If the following assumptions are made:

1. Isothermal, immiscible, Darcy flow,
2. Stock tank fluid densities remain constant within a time increment, and
3. Rock porosity changes with pressure follow the relationship:

$$\phi = \phi_{\text{original}} \left[1 + C_r (p - p_{\text{original}}) \right]$$

then the following equations for oil and water can be derived:

Oil:

$$\begin{aligned}
& \frac{\partial}{\partial x} \left(\frac{q_{oR}}{\beta_o} \right) \delta x + \frac{\partial}{\partial y} \left(\frac{q_{oR}}{\beta_o} \right) \delta y + \frac{\partial}{\partial z} \left(\frac{q_{oR}}{\beta_o} \right) \delta z \\
& + \text{oil production rate} \\
& + \left[\frac{S_o V_b C_r \phi_{orig}}{\beta_o} + S_o V_b \phi \frac{\partial}{\partial p_o} \left(\frac{1}{\beta_o} \right) \right] \frac{\partial p_o}{\partial t} \\
& = \frac{V_b \phi}{\beta_o} \frac{\partial S_o}{\partial t}
\end{aligned}$$

Water:

$$\begin{aligned}
& \frac{\partial}{\partial x} \left(\frac{q_{wR}}{\beta_w} \right) \delta x + \frac{\partial}{\partial y} \left(\frac{q_{wR}}{\beta_w} \right) \delta y + \frac{\partial}{\partial z} \left(\frac{q_{wR}}{\beta_w} \right) \delta z \\
& + \text{water production rate} \\
& + \left[\frac{S_w V_b C_r \phi_{orig}}{\beta_w} + S_w V_b \phi \frac{\partial}{\partial p_w} \left(\frac{1}{\beta_w} \right) \right] \frac{\partial p_w}{\partial t} \\
& = \frac{V_b \phi}{\beta_w} \frac{\partial S_w}{\partial t}
\end{aligned}$$

These equations are solved by approximating the differential equations with finite difference representations, and then solving the algebraic difference equations as an approximation to the differential equation. The finite difference representations are based on the grid cells determined for each streamtube -- or stack of streamtubes -- in the previous section. For our two phase 2-D simulator - two dimensions to include crossflow between the layers - the finite difference representations for the (n+1)th time step are:

Oil Saturation Equation:

$$\begin{aligned}
 & \frac{1}{\Delta t} \left[\left(\frac{S_o V_p}{\beta_o} \right)^{n+1} - \left(\frac{S_o V_p}{\beta_o} \right)^n \right] \\
 &= A_{oe} \left[p_e^{n+1} - P_c^{n+1} + \gamma_{oe}^n (Z_e - Z_c) \right] \\
 &+ A_{ow} \left[p_w^{n+1} - P_c^{n+1} + \gamma_{ow}^n (Z_w - Z_c) \right] \\
 &+ A_{ot} \left[p_t^{n+1} - P_c^{n+1} + \gamma_{ot}^n (Z_t - Z_c) \right] \\
 &+ A_{ob} \left[p_b^{n+1} - P_c^{n+1} + \gamma_{ob}^n (Z_b - Z_c) \right]
 \end{aligned}$$

where:

Z_c = midpoint elevation of center cell

Z_e = midpoint elevation of east cell

Z_w = midpoint elevation of west cell

Z_t = midpoint elevation of top cell

Z_b = midpoint elevation of bottom cell

$$V_p^n = \Delta X \Delta Y h \phi_{orig} \left[1 - C_r (P_{ref} - P_c^n) \right]$$

$$\gamma_{oe}^n = \left[(\rho_o(P_e^n) + \rho_o(P_c^n)) \right] / 288$$

$$A_{oe} = \frac{4.0 T_{ec} k_{ro}^u (S_o^n)}{(\beta_o(P_e^n) + \beta_o(P_c^n)) (\mu_o(P_e^n) + \mu_o(P_c^n))}$$

$$T_{ec} = \frac{0.01266 \Delta Y_c h_c k_{xc} k_{xe}}{\Delta X_c h_c k_{xe} + \Delta X_e h_c k_{xc}}$$

k_{ro}^u evaluated at upstream cell.

Similar, obvious, formulas can be written for A_{ow} , A_{ot} and A_{ob} as well as T_{wc} , T_{tc} , and T_{bc} .

Water Saturation Equation:

$$\begin{aligned} & \frac{1}{\Delta t} \left[\left(\frac{S_w V_p}{\beta_w} \right)^{n+1} - \left(\frac{S_w V_p}{\beta_w} \right)^n \right] \\ &= A_{we} [P_e^{n+1} - P_c^{n+1} + \gamma_{we}^n (Z_e - Z_c)] \\ &+ A_{ww} [P_w^{n+1} - P_c^{n+1} + \gamma_{ww}^n (Z_w - Z_c)] \\ &+ A_{wt} [P_t^{n+1} - P_c^{n+1} + \gamma_{wt}^n (Z_t - Z_c)] \\ &+ A_{wb} [P_b^{n+1} - P_c^{n+1} + \gamma_{wb}^n (Z_b - Z_c)] \end{aligned}$$

where all terms are exactly analogous to those in the oil saturation equation. Note, however, the absence of oil-water capillary pressures which would combine with oil pressure to give water pressures; we are assuming $P_w = P_o$.

Source/sink terms may appear. Their units are the same as those for their respective equation, namely, stock tank cubic feet (of fluid) per day.

Note that, after p^{n+1} values are available from solution of the forthcoming set of simultaneous linear pressure equations, all (n+1) level PVT functions can be evaluated. Thus, each saturation equation for each grid cell can be solved for its (n+1) level saturation value, independent of the values in other grid cells, or explicitly.

The task at hand now is to combine the saturation equations through use of the relation:

$$S_o + S_w = 1.0$$

and to approximate the (n+1) level PVT functions to obtain, finally, a linear equation (for each grid cell) where the only (n+1) quantities are oil pressures.

We start by multiplying each saturation equation by its corresponding β^{n+1} . For conciseness, the summation notation $\sum_{i=1}^4$ has been employed with the understanding that $i=1,2,3,4$ corresponds to the positional subscripts, e,w,t,b.

$$\beta_o^{n+1} \sum_{i=1}^4 A_{oi} \Delta \phi_{oi} = S_o^{n+1} \frac{V_p^{n+1}}{\Delta t} - \frac{S_o^n V_p^n \beta_o^{n+1}}{\beta_o^n \Delta t} - \beta_o^{n+1} q_o$$

$$\beta_w^{n+1} \sum_{i=1}^4 A_{wi} \Delta \phi_{wi} = S_w^{n+1} \frac{V_p^{n+1}}{\Delta t} - \frac{S_w^n V_p^n \beta_w^{n+1}}{\beta_w^n \Delta t} - \beta_w^{n+1} q_w$$

We will add these two equations and eliminate S_o^{n+1} , S_w^{n+1} by use of $(S_o^{n+1} + S_w^{n+1}) = 1$ and eliminate $(S_o^{n+1} V_p^{n+1}) / \beta_o^{n+1}$ by substituting the entire oil equation and similarly for $(S_w^{n+1} V_p^{n+1}) / \beta_w^{n+1}$.

After all the algebra is done, we have the following:

$$\beta_o^{n+1} \sum_{i=1}^4 A_{oi} \Delta \phi_{oi} + \beta_w^{n+1} \sum_{i=1}^4 A_{wi} \Delta \phi_{wi} = \frac{V_p^{n+1}}{\Delta t} -$$

$$\frac{V_p^n}{\Delta t} \left(\frac{S_o^n \beta_o^{n+1}}{\beta_o^n} + \frac{S_w^n \beta_w^{n+1}}{\beta_w^n} \right) - \beta_o^{n+1} q_o - \beta_w^{n+1} q_w$$

We now use the following approximations to convert the right-hand side (except for source/sink terms).

$$V_p^{n+1} = V_p^n [1 + C_r (p^{n+1} - p^n)]$$

$$\beta_o^{n+1} = \beta_o^n + (d\beta / dp) * (p^{n+1} - p^n)$$

$$\beta_w^{n+1} = \beta_w^n + (d\beta_w / dp) * (p^{n+1} - p^n)$$

This obtains the expected terms with the compressibility forms, $C_o = \frac{-1}{\beta_o^n} \frac{d\beta_o}{dp}$, similar for C_w and finally $C_t = C_r + C_o S_o + C_w S_w$.

Then the "final" pressure equation can be written. The remaining $\beta_o^{n+1}, \beta_w^{n+1}$, values are simply approximated with nth time level values.

$$\sum_{i=1}^4 (p_i^{n+1} - p_c^{n+1}) (A_{oi} \beta_o^{n+1} + A_{wi} \beta_w^{n+1}) - \frac{V_p^n C_t}{\Delta t} p_c^{n+1}$$

$$= \frac{-V_p^n C_t}{\Delta t} p_c^n - \sum_{i=1}^4 \beta_o^{n+1} A_{oi} [\gamma_{oi} (Z_c - Z_i)]$$

$$-\sum_{i=1}^4 \beta_w^{n+1} A_{wi} [\gamma_{wi} (Z_c - Z_i)] - \beta_o^{n+1} q_o - \beta_w^{n+1} q_w$$

The pressure equations form a set of simultaneous equations that are solved using an LSOR solution technique. The saturation equations are then solved explicitly one at a time.

Relative Permeability Relationships

The relative permeability in the previous discussion is computed from Corey-type equations based on user input end values:

$$UO = (1.0 - SW - SORW) / (1.0 - SWC - SORW)$$

$$KRO = XKROE * UO ** XNO$$

$$UW = (SW - SWC) / (1.0 - SWC - SORW)$$

$$KRW = XKRWE * UW ** XNW$$

XNO and XNW are curve shape parameters, with default values of 2.

Methods of Modeling Continuity

IDPM features two approaches to the calculation of continuity which are user-selectable via entries on cards R2 and R3. The first method is incorporated in the model as originally provided by SSI and calculates continuity by adjusting the relative permeability endpoint to oil, SORW in the above relationships. The second method was devised by ICF Resources Incorporated. This approach models continuity by adding an extra layer of net pay. Each of the two methods is discussed below.

SSI Method

This approach models changes in reservoir continuity -- or connectivity -- by changes in the relative permeability endpoint to oil, SORW in the relative permeability relationships described above. This technique was used to assure that the initial oil-in-place is not a

function of spacing, but the "average" final oil-in-place after a waterflood will be a function of spacing.

The input relative permeability endpoints are assumed to be laboratory values which apply at conditions of 100 percent continuity (or connectivity). The modifications to SORW require a value for the continuity fraction for both non-infill and infill. These are assumed to be dependent on the well spacing associated with those two cases. VCONEC, the user-input value, is used for non-infill. The continuity value for infill is obtained by computation of the decreased well spacing and reference to a semilog plot such as that shown in Figure 1.10. This plot is defined by user input.

CONTINUITY ASSOCIATED WITH NON-INFILL AND INFILL SPACING

Figure 1.10

The input endpoint value of SORW is then changed to make the fraction of the laboratory mobil oil phase that is discontinuous at reservoir conditions be represented by oil saturations between the input SORW and the SORW value calculated for the continuity associated with the non-infill and infill spacing:

$$\text{SORW}_{\text{used}} = \text{SORW} + (1 - \text{VCONEC}) * (1 - \text{SWI} - \text{SORW})$$

This means of treating reservoir continuity changes assures accurate calculations of ultimate recovery changes due to improved continuity for infill operations. However, the discontinuous nature of the reservoir would mean that an infill well could encounter reservoir rock at initial oil saturation - SOI. In this case the initial oil rate would be much higher in the field than in IDPM, but cumulative performance should be accurate.

Additional Net Pay Method

In this method, improved continuity is modeled as additional net pay. When the infill is initiated, an extra layer is added to the model to reflect this increase in net pay.

The effective net pay at a particular value of continuity is defined as:

$$h_e = h_i * C$$

where:

$$h_e = \text{effective net pay at continuity } C$$

$$h_i = \text{effective net pay at continuity of 1.0}$$

Values of effective net pay can be calculated using values of continuity at the original and infill spacings. The incremental net pay as a result of infill is the difference between

these values of net pay. The extra layer is assigned a thickness equal to the incremental value of net pay, an average value of permeability, and an initial oil saturation of $1.0 - S_{wc} - 0.07$. This method is shown schematically in Figure 1.11.

Comparison of Methods to Model Continuity

A comparison of the residual oil saturation and net pay methods was performed with the IDPM at three mobility ratios (1.0, 2.5, 5.0). The results are presented in Tables 1.1 through 1.3 respectively. Both continuity and VDP were varied for each mobility ratio studied.

The results show that waterflood performance is not affected by the choice of continuity method whereas infill recovery is. The net pay ("layer") method yields the highest infill recovery because it gives a higher oil rate at infill initiation. Either the "7% adjusted layer" method or the SSI method infill results are lowest depending on mobility ratio. Infill recovery is driven primarily by continuity, and thus the method used to model continuity. As expected, infill recovery was not greatly affected by mobility ratio. This is because in the IDPM (as in all streamtube models), the streamtube shapes and volumes are calculated assuming unit mobility.

Simulation Printout

IDPM offers several different types of printed output to provide the user with information about the waterflooding simulation calculations. These are available for both the non-infill case and the infill case. First, there is a summary of the in-place volumes (for all streamtubes). These volumes, like all other output from simulation, are scaled up to the size of the symmetry element which has 1/8 (if $k_y/k_x = 1$) or 1/4 (if $k_y/k_x \gg 1$) of the area of the pre-infill 5-spot well pattern.

Assume:

Net Pay = 100' (100% continuity)

Continuity = 0.80 (At original spacing)

Continuity = 0.90 (At infill spacing)

Figure 1.11 Modeling Continuity by Changing Net Thickness

Cumulative Oil Recovery, Mobility Ratio = 1.0															
VDP = 0.5								VDP = 0.8							
Continuity = 0.5				Continuity = 0.8				Continuity = 0.5				Continuity = 0.8			
Waterflood		Infill		Waterflood		Infill		Waterflood		Infill		Waterflood		Infill	
MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %	MSTB %	OOP %
227	21.5	97.6	9.3	363	34.3	45.0	4.3	163	15.4	95.9	9.1	261	24.7	45.8	4.3
SORW Method	227	21.5	92.7	8.8	362	34.3	40.3	3.8	163	15.4	69.6	6.6	261	24.7	33.8
7% Adjusted Layer Method	227	21.5	81.2	7.7	363	34.3	37.6	3.6	163	15.4	80.5	7.6	261	24.7	38.3

7. Streamtubes
 10. Layers (+1 layer for layer methods)
 11. Cells per stream tube
 OOP = 1057 MSTB
 Infill @ water cut of 0.85
 Terminate run @ water cut of 0.95

Cumulative Oil Recovery, Mobility Ratio = 1.0															
VDP = 0.5								VDP = 0.8							
Continuity = 0.5				Continuity = 0.8				Continuity = 0.5				Continuity = 0.8			
Waterflood		Infill		Waterflood		Infill		Waterflood		Infill		Waterflood		Infill	
MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP
227	21.5	97.6	9.3	363	34.3	45.0	4.3	163	15.4	95.9	9.1	261	24.7	45.8	4.3
SORW Method	227	21.5	92.7	8.8	362	34.3	40.3	3.8	163	15.4	69.6	6.6	261	24.7	33.8
7% Adjusted Layer Method	227	21.5	81.2	7.7	363	34.3	37.6	3.6	163	15.4	80.5	7.6	261	24.7	38.3

7. Streamtubes
 10. Layers (+1 layer for layer methods)
 11. Cells per stream tube
 OOIP = 1057 MSTB
 Infill @ water cut of 0.85
 Terminate run @ water cut of 0.95

COMPARISON OF METHODS TO MODEL CONTINUITY

TABLE 13

TABLE 13																
COMPARISON OF METHODS TO MODEL CONTINUITY																
Cumulative Oil Recovery, Mobility Ratio = 2.5																
VDP = 0.5																
VDP = 0.8																
Continuity = 0.5				Continuity = 0.8				Continuity = 0.5				Continuity = 0.8				
Waterflood		Infill		Waterflood		Infill		Waterflood		Infill		Waterflood		Infill		
MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	MSTB	OOIP %	
208	19.7	90.6	8.6	333	31.5	40.9	3.9	150	14.2	91.0	8.6	240	22.7	43.8	4.1	
SORW Method	208	19.7	86.7	8.2	332	31.4	39.0	3.7	151	14.3	64.0	6.1	241	22.8	30.3	2.9
7% Adjusted Layer Method	208	19.7	75.1	7.1	333	31.5	33.8	3.2	150	14.2	75.6	7.2	240	22.7	36.8	3.5
7 Steamfloods																
10 Layers (+1 layer for layer methods)																
11 Cells per stream tube																
OOIP = 1057 MSTB																
Infill @ water cut of 0.85																
Terminate run @ water cut of 0.95																

7 Streamtubes
 10 Layers (+1 layer for layer methods)
 11 Cells per stream tube
 OOIP = 1057 MSTB
 Infill @ water cut of 0.85
 Terminate run @ water cut of 0.95

TABLE 1.4

COMPARISON OF METHODS TO MODEL CONTINUITY

Cumulative Oil Recovery, Mobility Ratio = 5.0

	VDP = 0.5								VDP = 0.8							
	Continuity = 0.5				Continuity = 0.8				Continuity = 0.5				Continuity = 0.8			
	Waterflood		Infill		Waterflood		Infill		Waterflood		Infill		Waterflood		Infill	
	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP	MSTB	% OOIP
Layer Method	189	17.9	83.9	7.9	302	28.6	40.0	3.8	138	13.1	83.6	7.9	220	20.8	39.4	3.7
SORW Method	189	17.9	78.5	7.4	302	28.6	35.8	3.4	137	13.0	59.4	5.6	219	20.7	28.8	2.7
7% Adjusted Layer Method	189	17.9	68.4	6.5	302	28.6	32.9	3.1	138	13.1	68.2	6.5	220	20.8	32.3	3.1

7 Streamtubes
 10 Layers (+1 layer for layer methods)
 11 Cells per stream tube
 OOIP = 1057 MSTB
 Infill @ water cut of 0.85
 Terminate run @ water cut of 0.95

The printout also includes periodic summaries (coming at about 0.1 pore volume of injected water) of production/injection rates and cumulative volumes. These are followed by tabulations, covering every timestep, of production rates and cumulative oil, watercut, fractional recovery, etc. for both non-infill and infill.

Plot output

The EOR Plotting Package (EORPP) originally developed for use with the PC version of the DOE EOR models has been adapted for use with the IDPM. The IDPM version outputs three groups of four plots each for every economic scenario selected. Since the economic data for a given reservoir includes three scenarios (continued waterflood, infill drilling, and incremental infill drilling), a total of 36 plots are produced. The plots are designed for 11" x 14 7/8 printer paper and measure 80 lines high by 132 characters wide. The first group of plots includes pattern oil production vs. time (years), pattern water production vs. time, project oil production vs. time, and project water production vs. time. The second group contains cumulative project oil production vs. time, cumulative project water production vs. time, pattern water-oil ratio vs. time, and project water-oil ratio vs. time. The third group contains pattern water injection vs. time, project water injection vs. time, cumulative pattern water injection vs. time, and cumulative project water injection vs. time. The plots are invoked by setting the economics control switch on card R2 to a value of 2.

1.6 ECONOMIC CALCULATIONS

The IDPM economic calculations are used to convert predicted performance data from the oil recovery algorithm into a cash flow analysis extending over the life of the project. This analysis combines forecasts of revenue, costs, expenses, and taxes into an annual balance sheet (see Appendix III b). The model also permits an evaluation of the uncertainty of future earnings as a result of changes in key variables and thus an evaluation of project risk.

The economic calculations require three types of data:

1. Project definition (pattern development schedule). Once the performance of a single pattern has been determined, a schedule of the number of patterns per year to be initiated is used to superpose the pattern rates into an overall project performance. This procedure implicitly assumes that all patterns in the project perform identically (i.e., second year oil and water rates for every pattern are the same regardless of when the pattern comes on stream). Also superposed are the capital costs of drilling and equipping wells associated with developing each pattern. From this schedule, the total multiple patterns project oil, water and gas rates are calculated as well as the total amount of fluid injected. By combining the well and pattern implementation schedules, a capital investment schedule is obtained. A fraction of this capital investment schedule is obtained. A fraction of this capital requirement may be borrowed and repaid over the life of the project. The fixed and variable operating costs are then calculated based upon the project performance schedule. These latter costs include such items as maintenance costs, water treating and disposal costs, etc.
2. Economic data. These include prices, costs, tax rates, discount rate, escalation (inflation) rates, and capital schedule.
3. Range of uncertainty for key variables.

Estimating Risk

The parameter method (Davidson, 1976) is used to compute uncertainty in present value. This method deals with the parameters of the probability distributions rather than the distributions and, with reasonable assumptions about distribution form, can estimate the probability of achieving various levels of present value.

The parameter method requires that the uncertain parameters (data) must be statistically independent. For this reason, uncertainty in performance of the reservoir is

considered as a single parameter (UNCO). Other variables, such as costs, revenues and expenses, should be mutually independent. If dependence between parameters is established, the parameters should be rearranged to minimize dependence. In the IDPM, unit prices, costs, and capital are defined as the uncertain variables, in addition to the uncertainty in oil production. Escalation, inflation and tax rates are treated as certain and constant values over the life of the project.

The mean and variance of each of the uncertain variables are then estimated. The mean is the weighted average value of all possibilities found in the probability distribution of a parameter, and the variance is the weighted average of all squares of differences from the mean. Three values of a parameter are used to calculate the mean and variance:

1. Low value - a value of the parameter small enough so that only a 10 percent chance exists of a smaller value;
2. The most likely value; and
3. High value - a value large enough that there is only a 10 percent chance of a higher value.

Finally, the means and variances are combined into the quantities of interest, such as revenues, expenses, and costs. Once combined, the assumption of a resulting log-normal distribution is made. The mean and variance of the present value are known and estimations of present value at 10% (upside potential), 50%, and 90% (downside risk) probability are computed.

Profitability Indices

The calculated mean (50 percent) present value is presented in various formats to allow the direct comparison of costs and benefits. The present value of project revenues, costs and expenses are also reported to allow for an analysis of the components of project present value.

The final economic results are presented in terms of four measures of profitability:

1. Discounted Cash Flow (DCF), which represents the present value profit of the project;
2. Discounted Cash flow Rate of Return (DCFROR), which is the discount rate that reduces the DCF to zero;
3. Profit-to-Investment Ratio (P/I), which is the present value per dollar invested; and
4. Investment Efficiency, the ratio of total DCF to maximum negative DCF.

The strengths and weaknesses of these criteria are discussed in detail by Capen, et al (1976). DCF is the most widely accepted measure of project performance but it fails to recognize capital limitations and requires the specification of a discount rate. If DCF is used, a uniform discount rate should be applied to all cases considered, generally a discount rate based upon the average cost of capital.

DCFROR is a very popular economic criterion, and this measure obviates the need to specify a discount rate as in DCF. Problems with this criterion may result when comparing projects at different discount rates, since a project at a lesser DCFROR may have a greater present value at a company's costs of capital.

The P/I is the ratio of the project's total profit to the total investment required. The P/I recognizes capital limitations and gives a method of ranking projects in such a way as to maximize the profit per dollar invested. However, the sensitivity to cash flow timing is lost. A similar measure to the P/I ratio, the Profit-to-Expense Ratio (P/E), is also computed by the model.

Investment efficiency is defined as the ratio of the maximum cumulative discounted cash flow at economic life (TE in Figure 1.12) to the maximum cumulative negative discounted cash flow (at time T in Figure 1.12). Investment efficiency is an excellent ranking method for enhanced oil recovery projects, which are heavily front-end loaded with high capital and operating expenses. Investment efficiency was the basis for ranking projects used in the 1984 NPC survey.

INVESTMENT EFFICIENCY

Figure 1.12

SECTION 2

IDPM-DATA ENTRY

DATA ENTRY AND DEFAULTS

Details of reservoir and economic data entry are given here. A sample listing of input data is given as Table 2-2. This data comprises the base case for the North Riley Unit discussed further in Section 6 and Appendix IIIa. The output report and plots generated when the IDPM is run on this data are listed in Appendix IIIb.

Three types of data are indicated (no blank data allowed):

1. "Required" Data - Program will not run unless a value greater than zero is entered. Required data are API gravity (Card R7), porosity (R9 or R11), permeability (R9 or R11), net pay (R9 or R11), initial water saturation (R8), depth (R5), and pattern area (R4).
2. "Default" Data - Enter zero, unless specified otherwise, to default to the value indicated. Values greater than zero are used as specified, unless minimum/maximum bounds are indicated.
3. "No Default" Data - Any value entered, including zero, is used as specified.

2.1 RESERVOIR DATA

Card R1 *** Read Title**

READ(IR) TITLE

May be up to 80 alpha-numeric characters.

Card R2 *** Overall Controls**

READ(IR) IARRP, IANALP, ISTRMP, IECONR, NUMTUB, DYKST

- IARRP- Controls printing of simulator grid arrays in conjunction with periodic timestep output, which is controlled by IANALP.
- = 0 Do not print.
 - = 1 Do print.
- IANALP- Controls printing of simulation information such as initial in-place volumes and periodic (at 0.1 injected pore volume intervals) summaries of production and injection plus, at the end, tables of recovery information for both non-infill and infill.
- = 0 Do not print.
 - = 1 Do print.
- ISTRMP- Controls printing of information related to the generation of streamtubes. Higher values cause more detail to be printed.
- = 0 Do not print.
 - = 1 Do print, including numerical depiction of the streamtubes.
 - = 2 Do print more, including numerical depiction of finite difference cells within streamtubes and tables of tube/cell volumes, etc.
- IECONR- Economics control.
- = 0 Do not perform economics.
 - = 1 Do perform economics
 - = 2 Perform economics and generate output plots
- (No Default)
- NUMTUB- Number of streamtubes per layer for both non-infill and infill cases. For quality results, this number should relate to the anisotropy of the reservoir. See table below for defaults, minimums and maximums, depending on VANIS. The reason for maximums is to prevent useless streamtube densities, leading to numerical problems, for highly anisotropic cases. Computing time is proportional to the product of NUMTUB and

NX. The print output file displays the current maximum dimensions for NUMTUB.

VANIS LIMIT	NUMTUB VALUES		
	MINIMUM	DEFAULT	MAXIMUM
2.000	6	12	16
4.000	6	10	14
10.000	4	8	12
20.000	4	6	10
50.000	4	6	8
100.000	4	6	6

DYKST- Dykstra-Parsons VDP value for allocation of layer properties.

< 0 Read layer values for porosity, permeability, and thickness for each of ILAYER layers from cards R9 through R9+ILAYER-1. In this case the value of VDP is ignored.

>= 0 Calculate each layer's thickness and permeability, depending on ILAYER, IDYST (Card R10), VKXL, and VHL. When used for this purpose, the value of VDP must be >= 0 and < 1.

(No Default)

Note: If modeling continuity using the "LAYER" method, enter a non-negative value for DYKST.

Card R3 ***** Reservoir Type Data Card 1

READ(IR) IGOIN, ILAYER, NX, VANIS, VKZKH, IPAT9V

IGOIN- Infill plug-pack control.

= 1 Do not plug back.

= 2 Do a one-time check for plug-back needs after the first five timesteps of infill simulation. Any layer where water cut exceeds VCUT is shut in (plugged back).

(Default=1)

ILAYER- Number of layers, including extra layer if using "LAYER" method of modeling continuity. More layers give more realistic results (in theory), particularly at high values of VDP. Computing time is proportional to the number of layers.

(No Default - 5 is a reasonable value)

NX- Number of grid cells per streamtube. More grid cells will give more realistic answers (in theory). Computing time is proportional to the product of NX and NUMTUB.

(Default=15)

VANIS- Ratio of KY to KX.

(Default = 1.0)

Note: VANIS is 1.0 or greater.

VKZKH- Ratio of vertical perm to KX.

(Default=0)

(reasonable values range from 0 to 0.5)

IPAT9V- Infill pattern type.

= 0 5-spot to 5-spot

= 1 5-spot to 9-spot

Card R4 *** Reservoir Type Data Card 2**

READ(IR) VAREA, VDW100, VDBWLS, VCONEC, VRATE, VRATE1, VCUT,
CUTMAX, DTMAX

- VAREA-** Area in acres of full pattern (8 times the area modelled if VANIS=1.0; 4 times the area modelled if VANIS < 1.0). IDPM models the smallest element of symmetry for a pattern (1/8 or 1/4). In the output file, most of the information refers to the element, not the pattern. Thus the reported waterflood rate is actually 1/8 of the pattern rate (if VANIS=1.0).
(No Default)
- VDW100-** The distance between wells (feet) at which continuity is 1.0. This defines one of two points on the straight line relationship between the log of continuity and the distance between wells (see Figure 1.4).
(No Default)
- VDBWLS-** The distance between wells (feet) at which VCONEC (continuity) is entered. VDBWLS should be consistent with VAREA.
(Default=sqrt(21780 * VAREA))
- VCONEC-** Reservoir connectivity (fraction) at VDBWLS. VCONEC and VDBWLS define one of two points on the straight line relationship between the log of continuity and the distance between wells.
< 0.0 Use the "LAYER" method of modelling continuity (continuity = ABS(VCONEC)). The NXth layer will be used to model the additional pay at infill.
> 0.0 Use the "relative perm" method of modeling continuity. The relative permeability endpoints will be modified to simulate the effects of additional pay.
Note: If the model is run from other than initial conditions, i.e. SOI < (1.0 - SWC), the "LAYER" method must be used to model continuity.
(No Default)
- VRATE-** Non-infill injection rate into total pattern, STB water/day. If VRATE is entered as < 0.0, its absolute value is interpreted as the target oil rate. The

injection rate required to achieve this oil rate is calculated using the relative permeability curves. Specifying the oil rate in this fashion is useful when running the model from other than initial conditions ($SOI < 1.0 - SWC$).

(No Default)

VRATE1- Infill injection rate for the entire pattern, STB water/day.

(Default = 2 * non-infill injection rate if using the "LAYER" method;

Default = injectors are pressure-specified by internal calculation based on pre-infill pressures resulting from pre-infill injection rate if using the SSI method)

VCUT- Water cut at which infill is to occur ($Q_w/(Q_o+Q_w)$)

(No Default)

CUTMAX- Water cut to end each case - both infill and non-infill.

(Default = VCUT)

DTMAX- Maximum run time, days.

< 0 Infill will occur at $ABS(DTMAX)$ days, effectively over-riding

VCUT, and both cases will be terminated at CUTMAX.

= 0 Ignored.

> 0 Both the waterflood case and the infill case (if run) will be terminated at DTMAX days, over-riding CUTMAX.

Card R5 *** Reservoir Geological Data**

READ(IR) VCROC, VREFP, VRESP, VTOP, VTEMP

VCROC- Pore volume compressibility, $VOL/VOL/PSI$.

(Default = 3.0 E-6)

VREFP- Pressure at which porosity and oil and water densities are entered, PSIA.

If VREFP is not equal to VRESP, porosity is adjusted to reservoir conditions using VCROC.

(Default = VRESP)

VRESP- Reservoir pressure at top of formation.

(Default = 15. - VTOP * 0.433)

VTOP- Depth to top of reservoir, feet.

(No Default)

Note: Value is entered as negative.

VTEMP- Reservoir temperature, degrees F.

(Default = 60. - VTOP * 0.017)

Card R6 *** Water Properties**

READ(IR) DENWST, BWI, CMPWTR, VISWTR, SGGV

DENWST- Water density at standard conditions, LBM/FT³.

(Default = 62.4 LBM/FT³)

BWI- Water formation volume factor at VTEMP and VRESP.

(Default BWI = $1.0 + 1.2E - 4 * (VTEMP - 60) + 1.0E - 6 * (VTEMP - 60) ** 2 - 3.33 E - 6 * VRESP$)

CMPWTR- Water compressibility at reservoir conditions VOL/VOL/PSI.

(Default = 3.0 E-6)

VISWTR- Water viscosity, cp.

(Default = $-1.439 * ALOG_{10}(VTEMP) + 3.74486$)

SGGV- Gas gravity, AIR = 1.0. Used in GOR and oil density correlations, see discussion that follows Input.

(Default = $0.8 * (1.0 + 5.915 E - 5 * API * VTEMP * ALOG(64.7/114.7))$)

Card R7 *** Oil Properties**

READ(IR) APIV, BOI, CMPOIL, VISOIL, GORV

APIV- API gravity for the reservoir oil at hand..

(No Default)

BOI- Oil formation volume factor at VTEMP and VRESP.

(For default see following discussions.)

CMPOIL- Oil compressibility at reservoir conditions VOL/VOL/PSI.

(Default = 3.0 E-6)

VISOIL- Oil viscosity, cp.

(For default see following discussion.)

GORV- Solution GOR, SCF/STB used for economics only.

(For default see following discussion.)

Card R8 *** Relative Permeability Data at VCONEC=1.0**

READ(IR) VXNO, VXNW, VVKROE, VVKRWE, VSWC, VSORW, SOI

VXNO- Oil relative permeability curve exponent, fraction.

(Default = 2.0)

VXNW- Water relative permeability curve exponent, fraction.

(Default = 2.0)

VVKROE- Oil relative permeability at, VSWC, fraction.

(Default = 0.80)

VVKRWE- Water relative permeability at VSORN, fraction.

(Default = 0.20)

VSWC- Connate water saturation, fraction.

(Default = 0.2)

VSORW- Residual oil saturation to a waterflood, fraction.

(Default = 0.25)

SOI- Initial oil saturation override (fraction). This is used if the model is run from an oil saturation other than 1.-VSWC. Must be greater than VSORW

and less than or equal to 1.-VSWC. May be zero, in which case SOI = (1.-VSWC).

Card R9 *** R9 + ILAYER - Layer Properties**

If DYKST > 0 skip these cards and go to cards R10 and R11.

READ(IR) VPHI(I), VKX(I), VH1(I)

VPHI(I)- Porosity of Layer I, fraction.

(No Default)

VKX(I)- X-direction of permeability of Layer I, MD.

(No Default)

VH1(I)- Net pay of Layer I, feet.

(No Default)

Note: One card for each of the layers, 1 through ILAYER.

Card R10 *** Dykstra-Parsons Calculation Type only read if DYKST > 0**

READ(IR) IDYST

IDYST- = 1 Calculate layer K and H on basis of equal thickness per layer.

= 2 Calculate layer K and H with equal KH per layer.

(No Default)

Note: Set to 1 if using the "LAYER" method (option 2 not tested)

Card R11 *** Average Layer Properties (only read if DYKST > 0)**

READ(IR) VPHIL, VKXL, VHL

VPHIL- Average porosity for all layers, fraction.

(No Default)

VKXL- Average x-direction permeability, md.

(No Default)

VHL- Total net pay, feet.

(No Default)

2.2 ECONOMIC DATA

The following cards are to be read if IECONR>0 on Card R2, one set for non-infill, one set for infill, one set for incremental.

Card E1 ***** Read Economic Title

Read (IR) TITLE

TITLE- May be up to 80 alpha-numeric characters.

Card E2 ***** Read Case Controls

READ(IR) M, ISTATE, IDIST, IOUT, IFIT, IDAT, NCT, NCI, IDISC, ISO, IPLIF,
IDEBT

M- Number of years in the project (for all patterns). M must be ≤ 50 .

ISTATE- State code. Used to default well capital costs (drilling, completion, conversion, upgrading) by region of U.S. See Section 3.2 for explanation of defaults by region. To invoke defaults for well capital costs, enter the appropriate number 1-52 from Table 2-1. If ISTATE = 1-52 on this card, then the model penalizes oil price based on API gravity and location. See Section 3.2 for explanation of penalties. If the project is outside the U.S. or it is desired to disable oil price penalty, enter ISTATE=53 on this card.

TABLE 2-1

SUMMARY OF STATE CODES

CODE	ALPHA	STATE	CODE	ALPHA	STATE
1	AL	ALABAMA	27	NV	NEVADA
2	AZ	ARIZONA	28	NH	NEW HAMPSHIRE
3	AR	ARKANSAS	29	NJ	NEW JERSEY
4	CA	CALIFORNIA	30	NM	NEW MEXICO
5	CO	COLORADO	31	NY	NEW YORK
6	CT	CONNECTICUT	32	NC	N. CAROLINA
7	DE	DELAWARE	33	ND	N. DAKOTA
8	DC	WASH D.C.	34	OH	OHIO
9	FL	FLORIDA	35	OK	OKLAHOMA
10	GA	GEORGIA	36	OR	OREGON
11	ID	IDAHO	37	PA	PENNSYLVANIA
12	IL	ILLINOIS	38	RI	RHODE ISLAND
13	IN	INDIANA	39	SC	S. CAROLINA
14	IA	IOWA	40	SD	S. DAKOTA
15	KS	KANSAS	41	TN	TENNESSEE
16	KY	KENTUCKY	42	TX	TEXAS
17	LA	LOUISIANA	43	UT	UTAH
18	ME	MAINE	44	VT	VERMONT
19	MD	MARYLAND	45	VA	VIRGINIA
20	MA	MASS	46	WA	WASHINGTON
21	MI	MICHIGAN	47	WV	WEST VIRGINIA
22	MN	MINNESOTA	48	WI	WISCONSIN
23	MS	MISSISSIPPI	49	WY	WYOMING
24	MO	MISSOURI	50	AK	ALASKA
25	MT	MONTANA	51	HI	HAWAII
26	NE	NEBRASKA	52	PO	OFFSHORE

IDIST- District code (within a state). Used to default well costs. If outside U.S. or if ISTATE=53, Enter IDIST=0. For Texas Railroad Commission (RRC) districts, enter (RRC NO. * 10) + Y, where

Y = 1 for A

= 2 for B

= 3 for C

eg., for district 10B enter 102, etc.

IOUT- Controls printing of economic calculations (no default, see Table 2-2 and Section 4.1)

= 0, Minimum output, prints economic summary

= 1, Also prints annual cash flow, project capital schedule, and undiscounted results

= 2, Also prints escalated values of prices and costs

IFIT- Federal income tax credit option (no default)

= 0, Allows a tax credit to offset losses

= 1, No tax credit allowed

IDAT- Control for reading price and cost data

=0, Default prices and costs used, skip Cards E10-E13; see E10-E13 for default values

= 1, Read Cards E10-E13 for price and cost data

NCT- Control for reading tangible capital investment per pattern in any given year. Investments will be timed according to the pattern schedule on Card E9.

= 0, Do not read tangible capital investment on Card E14, accept default

= 1, Read tangible capital investment on Card E14

- NCI- Control for reading intangible capital investment per pattern in any given year. Investments will be timed according to pattern schedule on Card E9.
= 0, Do not read intangible capital investment on Card E15, accept default
= 1, Read intangible capital investment on Card E15
- IDISC- Control for discounting method
= 0, Year end discounting factors used
= 1, Mid-year discounting factors used
(No Default)
- ISO- Control for reading secondary oil volume
= 0, Do not read secondary oil volumes
= 1, Read secondary oil volumes
(No Default)
- IPLIF- Control on economic life
= 0, Economic life based on after tax cash flow
= 1, Economic life based on net operating income
(No Default)
- IDEBT- Control on debt calculations
= 0, No capital borrowing debt calculations
= 1, Include capital borrowing based on data input on Card E3
(No Default)

Card E3 *** Read Debt Controls**

(Read if IDEBT = 1 on Card E2)

READ(IR) PCTDBT, DBTINT, NYRRPY, NYPAID

PCTDBT- percent of capital (tangible and intangible) costs to be borrowed, percent
(default=20.)

DBTINT- Debt interest rate, percent (default=15.)

NYRRPY- Number of years before beginning debt repayment (Default=1.)

NYPAID- Number of years before completing debt repayment (default=5.)

Card E4 *** Read Operating and Plant Capital Data**

Capital for plants (CCHM, CWAT) on this card will be taken in the first year of the project and will be added to capital for wells (if any), whether latter capital is defaulted on Card E2 or read on Cards E14-E15.

READ(IR) CWAT, CWCAP, WOCOST, WTCOST

CWAT- Capital for water injection plant, M\$ (no default; estimate is $40.0 * RMAX$ M\$.)

CWCAP- Capacity of water injection plant, MMB/YR
(Default: $CWCAP=365.*RMAX/1000.0$)

WOCOST- Annual well workover cost per pattern, M\$.
(Default: $0.25*CNVT$. Assumes one workover per pattern every four years. CNVT is the cost to convert an existing producer to an injection well. See Section 3.2 for default for CNVT.

WTCOST- Produced water treating costs, \$/BBL (default=0.03)

Card E5 *** Read Operating Data**

READ(IR) WCAP, UNCO, COSTRT

WCAP- Months of working capital, months
(No Default)

UNCO- Oil rate uncertainty, fraction
(Default=0.001)

COSTRT- Project startup costs, MS
(No Default; the negative of COSTRT is used to initialize cash flow)

Card E6 *** Read Taxes and Monetary Data**

READ(IR) XDR, XINF, XROY, XSEV, XFIT, XTCR, DTIM, XSTX

XDR- Monetary discount rate

(Default=0.1)

XINF- Inflation rate

(No Default)

XROY- Royalty rate

(No Default)

XSEV- Severance tax rate

(No Default)

XFIT- Federal income tax rate

(No Default)

XTCR- Investment tax credit

(No Default)

DTIM- Investment depreciation time, yr. If DTIM = 0.0, the model uses accelerated capital recovery system (8 yr depreciation) according to 1986-1987 tax act. If DTIM >. 0.0, uses straight line depreciation from year of investment over DTIM years.

(No Default)

XSTX- State income tax rate

(No Default)

Card E7 *** Read Windfall Excise (Profit) Tax Data**

READ (IR) XWPT, WPHO, EPHO, BTIM, BPOW

XWPT- Windfall excise tax rate. If 0.0 then ignores tax. See Section 3.2 for explanation of windfall excise tax.

WPHO- Windfall tax beginning phase out date.
(Default= 1991)

EPHO- Windfall tax ending phase out date.
(Default= 1993)

BTIM- Base time for project start.
(Default= 1994)

BPOW- Base oil price at start of project for WPT calculations only, \$/BBL
(Default= $23.07 \times (1 + XINF)^{(BTIM-1983)}$)
Note: Oil Price for sales and revenue purposes is entered or defaulted on Card E10.

Card E8 *** Read Escalation Data for Prices and Costs**

READ(IR) ESCPO, ESCPG, ESCFO, ESCWT, ESCWI, ESCWO

ESCPO- Escalation rate of oil price
(No Default)

ESCPG- Escalation rate of gas price
(No Default)

ESCFO- Escalation rate of operating costs
(No Default)

ESCWT- Escalation rate of tangible capital
(No Default)

ESCWI- Escalation rate of intangible capital
(No Default)

ESCWO- Escalation rate of well workover cost
(No Default)

Card E9 *** Read Project Pattern Schedule**

READ(IR) (PATI(I),I=1,M)

PATI(I)- Number of patterns initiated each year of the project
(No Default)

IF IDAT=0 on Card E2, model uses default prices and costs;skip to Card E14.

In the names of all of the following arrays, the last letter (H, M, or L) means high, most likely, or low value of the parameter in a given year. The high and low values should be chosen to represent a confidence level of 80 percent. Low price has a 90% chance of being obtained, and the high price has only a 10% chance of being reached. See Section 1.9 for discussion of risk.

Prices and costs, whether entered or defaulted, are scaled by program (subroutine ECFTR) due to variation in oil price from \$30.00/BBL. The price factor is $FACT = (POM(1) - 30.00) / 30.$, where POM(1) is entered or defaulted on Card E10. Then:

Drilling and completion factor = $1.0 + (0.4 * FACT)$

Equipment factor = $1.0 + (0.3 * FACT)$

Operating costs factor = $1.0 + (0.2 * FACT)$

Polymer price factor = $1.0 + (0.3913 * FACT)$

Oil price factor = $1.0 + FACT$

Card E10 *** Read Oil Price Data**

READ(IR) POL(1), POM(1),POH(1)

POL(1)- Low oil price, \$/BBL (default = $POM(1) * 0.8$)

- POM(1)- Most likely oil price, \$/BBL (default = 30.00. This read or defaulted oil price may subsequently be reduced based on API gravity and location. See Section 3.2 for discussion of oil price penalties.)
- POH(1)- High oil price, \$/BBL (default = POM(1) * 1.2)

Card E11 *** Read Gas Price Data**

READ(IR) PGL(1),PGM(1),PGH(1)

PGL(1)- Low gas price, \$/MSCF
(Default = PGM(1)*0.8)

PGM(1)- Most likely gas price, \$/MSCF
(Default = POM(1)/6.0)

PGH(1)- High gas price, \$/MSCF
(Default = PGM(1)*1.2)

Card E12 *** Read Fixed Annual Operating Cost Data**

(Includes maintenance, other costs that do not depend on oil rate. For incremental case, fixed operating costs are set to zero until waterflood life exceeded.)

READ(IR) FOCL(1),FOCM(1),FOCH(1)

FOCL(1)- Low fixed operating cost per pattern, \$/yr
(Default: FOCL(1)=(CDAO+CIWO) *0.8, where CDAO (operating costs for SEC recovery) and CIWO (additional operating costs for offshore water injection Plant) are defaulted in Section 3.2).

FOCM(1)- Most likely fixed operating cost per pattern, \$/yr.
(Default: FOCM(1)=(CDAO+CIWO))

FOCH(1)- High fixed operating cost per pattern, \$/yr.
(Default: FOCH(1)=(CDAO+CIWO)*1.2)

Card E13 *** Read Variable Annual Operating Cost Data**

(Includes lifting and other costs that depend on oil production directly, but not royalty or severance.)

READ(IR) OPCL(1),OPCM(1),OPCH(1)

OPCL(1)- Low variable operating cost, \$/BBL oil produced.

(Default = 0.04)

OPCM(1)- Most likely variable operating cost, \$/BBL oil produced.

(Default = 0.05)

OPCH(1)- High variable operating cost, \$/BBL oil produced.

(Default = 0.06)

Card E14 *** Read Tangible Capital Investment (Read if NCT=1 on Card E2)**

(Flow lines, wells, roads, and production facilities.)

If well entered on Card E4, do not enter well capital costs on this card.

READ(IR) ICT,CTPL,CTPM,CTPH

ICT- Enter 1.0

CTPL- Low tangible capital cost per pattern, \$.

(No Default)

CTPM- Most likely tangible capital cost per pattern, \$.

(No Default)

CTPH- High tangible capital cost per pattern, \$.

(No Default)

Card E15 *** Read Intangible Capital Investment (Read if NCI=1 on Card E2)**

(Capital expensed in a given year.) If wells entered on Card E4, do not enter well capital costs on this card.

READ(IR) ICI,C IPL,CIPM,CIPH

ICI- Enter 1.0

C IPL- Low intangible capital cost per pattern, \$.
(No Default)

CIPM- Most likely intangible capital cost per pattern, \$.
(No Default)

CIPH- High intangible capital cost per pattern, \$.
(No Default)

Card E16 *** Read END Card**

READ (IR) END

END- "END" in columns 1-4.

******* RETURN TO CARD E1 FOR NEW CASE *******

TABLE 2-2

SAMPLE INPUT DATA

IDPM Sensitivity Analysis: North Riley Unit Base Case

0, 1, 1, 2, 0, 0.83

1, 11, 15, 1., 0.10, 0

40., 300., 933., .55, 200., 400., .75, 0.95, 0.

.000003, 3000., 2750., -6300., 107.

64.00, 0.0, .000003, .6, 0.8

32.00, 1.28, .00000735, 1.7, 330.

2., 2., .752, .40, .32, .25, 0.

1

0.0800, 10., 400.

Economics for Waterflood

40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0, 0

0.0, 0.0, 0.0, 0.03

0.0, 0.001, 0.0

0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04

0.0, 0.0, 0.0, 0.0, 23.07

0.0, 0.0, 0.0, 0.0, 0.0, 0.0

6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

16.00, 20.00, 24.00

2.67, 3.33, 4.00

33313., 41642., 49970.

.04, .05, .06

Economics for Infill Waterflood

40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0, 0

0.0, 0.0, 0.0, 0.03

0.0, 0.001, 0.0

0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04

0.0, 0.0, 0.0, 0.0, 23.07

0.0, 0.0, 0.0, 0.0, 0.0, 0.0

6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0

16.00, 20.00, 24.00

2.67, 3.33, 4.00

33313., 41642., 49970.

.04, .05, .06

TABLE 2-2 (continued)

SAMPLE INPUT DATA

Economics for Infill over Non-Infill
40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0, 0
0.0, 0.0, 0.0, 0.03
0.0, 0.001, 0.0
0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04
0.0, 0.0, 0.0, 0.0, 23.07
0.0, 0.0, 0.0, 0.0, 0.0, 0.0
6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
16.00, 20.00, 24.00
2.67, 3.33, 4.00
33313., 41642., 49970.
.04, .05, .06
END

SECTION 3

DEFAULT EQUATIONS

In Section 2, default values are documented for the input parameters, where applicable. In many cases, it is not sensible to use a single default value because there must be physical (and/or economic) consistency between certain parameter values. For those cases, the software contains built-in relationships, or equations, which are used to compute default values. This section discusses those equations.

3.1 RESERVOIR DATA

Oil Viscosity

Oil viscosity is defaulted according to API gravity and GOR (see discussion below for GOR default) using the correlation of Beggs and Robinson (1975). The model first calculates the dead oil viscosity, VISD (cp).

$$\text{VISD} = 10.0^{**}\text{X}-1,$$

where

$$\text{X} = \text{Y}/\text{TEMP}^{**}1.163,$$

$$\text{Y} = 10.0^{**}\text{Z},$$

$$\text{Z} = 3.0324-0.02023*\text{API},$$

and TEMP is the reservoir temperature, degrees F (card R5). Then the live oil viscosity is

$$\text{VISO} = \text{A}*\text{VISD}^{**}\text{B},$$

where

$$\text{A} = 10.715/(\text{GOR}+100.0)^{**}0.515$$

and

$$\text{B} = 5.44/(\text{GOR}+150.0)^{**}0.338.$$

Solution Gas-Oil Ratio

Solution gas-oil ratio, GOR, is defaulted by API gravity (Vasquez and Beggs, 1980). These correlations appear to give low values for heavy crude oils. The model first corrects the gas gravity, SGG, as input or defaulted on card R6 to a 100 psig separator condition, assuming the separator is at TEMP:

$$\text{SGG} = \text{SGG} * (1.0 + 5.912\text{E-}5 * \text{API} * \text{TEMP} * \text{ALOG}(64.7/114.7)).$$

SGG calculated from Eq. (3.3) is bounded by 0.8 and 1.4.

Then for $\text{API} \leq 0$, in SCF/STB

$$\text{GOR} = 0.0362 * \text{SGG} * (\text{PFORM}^{**1.0937}) * \text{EXP}(25.724 * (\text{API}/(\text{TEMP} + 460.))),$$

and for $\text{API} > 30$,

$$\text{GOR} = 0.0178 * \text{SGG} * (\text{PFORM}^{**1.187}) * \text{EXP}(23.931 * (\text{API}/(\text{TEMP} + 460.))).$$

Oil Formation Volume Factor

Oil formation volume factor is defaulted according to API gravity (Vasquez and Beggs, 1980). This is used to calculate the standard density of oil.

$$\text{B0} = 1.0 + \text{C1} * \text{GOR} + (\text{C2} + \text{C3} * \text{GOR}) * (\text{TEMP} - 60) * (\text{API}/\text{SGG}),$$

where for $\text{API} \leq 30$.,

$$\text{C1} = 4.677\text{E-}4$$

$$\text{C2} = 1.751\text{E-}5$$

$$\text{C3} = -1.811\text{E-}8$$

and for $\text{API} > 30$.,

$$\text{C1} = 4.67\text{E-}4$$

$$C2 = 1.1E-5$$

$$C3 = 1.337E-9.$$

3.2 ECONOMIC DATA

IDPM Treatment of Well Capital Costs

Well tangible (WCT) and intangible (WCI) capital costs are calculated as follows.

The total well capital is

$$CAP = (CINJ*WPP1)+(CINJ+CEQP)*WPP2 \\ + CSEC*WPP3+CNVT*WPP4+CREP,$$

where the WPP's are read and the CINJ, etc. are defined below. Per pattern

$$WCT = 0.28*(CEQP*WPP2+CSEC*WPP3),$$

and

$$WCI = CAP-WCT.$$

The total project intangible capital is obtained by summing the WCI over the number of patterns. A similar calculation is performed for the total project tangible capital, CTCM(I), except that the capital for water injection (CWAT) plants are included in year one of the project

$$CTCM(1) = WCT+CWAT.$$

CWAT can also be defaulted

The well capital and operating costs defaults given below were derived from correlations from the DOE/EIA-0185(82) report, "Costs and Indexes for Domestic Oil and Gas Field Equipment and Production Operations, 1990" scheduled for publication in the spring of 1994.

Drilling and Completion Costs

These costs (CINJ) include the cost of drilling and completing through the wellhead, including tubing, and are used to represent the cost of new injection wells. New producing wells have additional equipment costs which are discussed below. CINJ is defaulted according to depth and region of the U.S. (Figure 3-1). In \$/ well,

$$\text{CINJ} = A0 + A1*\text{DEPTH}^2,$$

where A0-A1 are shown in Table 3-1.

Costs to Equip New Producing Well

These costs (CEQP) consist of all costs to equip a new producing well for secondary recovery, excluding costs for tubing. CEQP is defaulted according to depth and region of the U.S. (Figure 3-2). In \$/ producing well,

$$\text{CEQP} = B0+B1*\text{DEPTH},$$

where B0 and B1 are shown in Table 3-2.

Costs of Additional Secondary Production Equipment for a Primary Well Converted to a Secondary Well

For these costs (CSEC), it is assumed that the existing processing and lease facilities are not replaced, old producing well equipment is replaced, and that costs for drilling and equipping water supply wells are included. CSEC is defaulted according to depth and region of the U.S. In \$/ well,

$$\text{CSEC} = C0+C1*\text{DEPTH},$$

where C0 and C1 are shown in Table 3-3.

Regions for Drilling and Completion Costs

Figure 3.1

**Regions for Equipment, Conversion, and
Operating Costs and Secondary Facilities**

Figure 3.2

Costs to Convert a Producing Well to an Injection Well

These costs (CNVT) include removal of producing equipment and tubing, acidizing and cleaning out the wellbore, and installing new plastic coated tubing and a waterflood packer. CNVT is defaulted by depth and region of the U.S. In \$/ well,

$$\text{CNVT} = \text{E0} + \text{E1} * \text{DEPTH},$$

where E0 and E1 are shown in Table 3-4.

Costs To Upgrade Surface Processing Equipment and Lease Facilities For Secondary Recovery Operations

These costs (CREP) include flowlines, manifolds, separators, treaters, tanks, LACT unit, disposal system and accessories. CREP is defaulted by depth and region of the U.S. In \$/ producing well,

$$\text{CREP} = \text{F0} + \text{F1} * \text{DEPTH}^2,$$

where F0-F1 are shown in Table 3-5. If WPP4=0, then the model sets CREP=0.

Direct Annual Operating Costs for Secondary Recovery Operations

These costs (CDAO) include all costs essential to the production of oil and gas, such as cost of labor, power, equipment repair and maintenance, fluid injection, treatment of oil and gas, etc. CDAO is defaulted according to depth and region of the U.S. In \$/ producing well/ year,

$$\text{CDAO} = \text{G0} + \text{G1} * \text{DEPTH},$$

where G0 and G1 are shown in Table 3-6. CDAO is used to default fixed annual operating costs.

Costs for Offshore Operations

Defaults for these costs are as follows (use ISTATE=52 for offshore):

$$\text{CINJ} = 458492.-563271*\text{DEPTH}+0.03043$$

$$*\text{DEPTH}^{**2}, \$/\text{well}$$

$$\text{CEQP} = 0.0$$

$$\text{CSEC} = 650000.+230000.*\text{RATE}-2800.*\text{RATE}^{**2},$$
$$\$/\text{well}$$

where RATE is the maximum water injection rate calculated by the model.

$$\text{CNVT} = 171366.+21.825*\text{DEPTH}, \$/\text{well},$$

$$\text{CREP} = 0.0$$

$$\text{CDAO} = \$169,000/\text{well}/\text{yr}.$$

Oil Price Penalties

The read-in (or defaulted) oil price (card E10) is penalized for API gravities less than 40 according to location. Figure 3-3 shows the multiplicative price reduction factors as a function of gravity for California (ISTATE=4) and for all other states. The latter curve in Figure 3-3 is based on mid-continent posted prices (NPC, 1984).

For projects in Alaska (ISTATE=50) oil is priced in accordance with the solid curve of Figure 3-3 less another \$9.00/bbl for transportation fees. These fees are associated with amortized capital, port of entry charges, and fixed tariffs and do not vary with oil price.

If ISTATE=53, then the API gravity penalty is disabled and the price reduction factor is 1.0 regardless of the value of API input. This feature was added to the model for projects outside the U.S., where different oil pricing scenarios may apply.

Figure 3.3

Windfall Profit Tax

The Windfall Profit Tax (WPT) effected by statute in 1980 is an excise tax on U.S. crude oil production. The WPT is applied as a percentage of the difference between the sales price of oil (POM(I) adjusted for API gravity and location) and a base price (BPOW or BPO(I)), that escalates with time. The base price varies with crude oil production method and field history.

The WPT tax rate (XWPT), also varies with production method and type of producer (major or independent). XWPT for heavy oil and/or incremental tertiary oil is 30% for majors, and 0% up to 1,000 bpd (30% over 1,000 bpd) for independents (see Table 3-7). Definitions of Tier 1 and tier 2 oil in Table 3-7 are quite complex, and may be found in "The Crude Oil Windfall Profit Tax," Price-Waterhouse, 1980.

In the PFPM, the WPT is calculated from

$$WPT(I) = VONET(I) * (1 - XSEV) * AWPP(I) * XWPT,$$

where

VONET(I) = net oil sold (less royalty), BBL

XSEV = severance tax rate

AWPP(I) = sales price - BPO(I), \$/BBL.

In the IDPM there is no WPT for API gravities of 16.0 or less.

TABLE 3-1
COEFFICIENTS FOR DRILLING AND COMPLETION COSTS

REGION (Fig. 3-1)	A0	A1
Pacific Coast	91.186	1.760E-5
Rocky Mountain	108.451	8.471E-6
Permian Basin ¹	71.736	6.433E-6
Gulf Coast ²	57.833	9.201E-6
Mid-Continent ³	69.634	5.967E-6
Northeastern	61.109	4.230E-6

1 Includes Texas RRC Districts 7-9.

2 Includes Texas RRC Districts 1-6.

3 Includes Texas RRC District 10.

TABLE 3-2**COEFFICIENTS FOR COSTS TO EQUIP NEW PRODUCING WELL**

REGION (Fig. 3-2)	B0	B1
Permian Basin	20347.0	17.165
Pacific Coast	25668.0	26.038
Rocky Mountains ¹	17504.0	18.069
Western Gulf Coast ²	20810.0	17.331
Eastern Gulf Coast ³	20266.0	17.130
Mid-Continent and Northeastern ⁴	17706.0	17.833

1 Includes New Mexico District 1.

2 Includes Texas RRC Districts 1-3.

3 Includes Florida, and Louisiana District 2.

4 Includes Texas RRC District 9.

TABLE 3-3
COEFFICIENTS FOR COSTS OF ADDITIONAL SECONDARY
PRODUCTION EQUIPMENT

REGION (Fig. 3-2)	C0	C1
Permian Basin	18997.0	19.927
Pacific Coast	23234.0	30.193
Rocky Mountains ¹	15792.0	20.950
Western Gulf Coast ²	19466.0	20.122
Eastern Gulf Coast ³	18916.0	19.887
Mid-Continent and Northeastern ⁴	16048.0	20.680

- 1 Includes New Mexico District 1.
- 2 Includes Texas RRC Districts 1-3.
- 3 Includes Florida, and Louisiana District 2
- 4 Includes Texas RRC District 9.

TABLE 3-4
COEFFICIENTS FOR COSTS TO CONVERT PRODUCING WELL TO
INJECTION WELL

REGION (Fig 3-2)	E0	E1
Permian Basin	6086.0	6.661
Pacific Coast	7713.0	6.741
Rocky Mountains ¹	6951.0	6.805
Western Gulf Coast ²	6326.0	6.596
Eastern Gulf Coast ³	6996.0	6.628
Mid-Continent and Northeastern ⁴	6741.0	6.559

- 1 Includes New Mexico District 1.
- 2 Includes Texas RRC Districts 1-3.
- 3 Includes Florida, and Louisiana District 2.
- 4 Includes Texas RRC District 9.

TABLE 3-5
COEFFICIENTS FOR COSTS TO UPGRADE
SURFACE PROCESSING EQUIPMENT

REGION (Fig. 3-2)	F0	F1
Permian Basin	22323.0	2.009E-4
Pacific Coast	47322.0	2.717E-4
Rocky Mountains ¹	31543.0	1.685E-4
Western Gulf Coast ²	31067.0	3.327E-4
Eastern Gulf Coast ³	34617.0	3.442E-4
Mid-Continent and Northeastern ⁴	24688.0	2.426E-4

- 1 Includes New Mexico District 1.
- 2 Includes Texas RRC Districts 1-3.
- 3 Includes Florida, and Louisiana District 2.
- 4 Includes Texas RRC District 9.

TABLE 3-6**COEFFICIENTS FOR DIRECT ANNUAL OPERATING COSTS**

REGION (Fig. 3-2)	G0	G1
Permian Basin	17759.0	4.801
Pacific Coast	9948.0	11.917
Rocky Mountains ¹	18894.0	4.932
Western Gulf Coast ²	21214.0	5.677
Eastern Gulf Coast ³	22461.0	5.904
Mid-Continent and Northeastern ⁴	8539.0	6.473

- 1 Includes New Mexico District 1.
- 2 Includes Texas RRC Districts 1-3.
- 3 Includes Florida, and Louisiana Districts 2.
- 4 Includes Texas RRC District 9.

TABLE 3-7

WINDFALL PROFIT TAX RATES

	TAX RATE. %		
	MAJOR	INDEPENDENT	
		<1000 bpd	>1000bpd
Tier 1			
Lower Tier Oil	70	50	70
Upper Tier Oil	70	50	70
Market Level New Crude Oil	70	50	70
Marginal Well Oil	70	50	70
Tier 2			
Stripper Well Oil	60	30	60
National Petroleum Reserve Oil	60	30	60
Tier 3			
Newly-Discovered Oil	30	0	30
Heavy Oil	30	0	30
Incremental Tertiary Oil	30	0	30

SECTION 4

IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

IDPM results were verified against SSI's SimBest II black-oil simulator. SimBest II does not allow relative permeability to change with time. In the IDPM, however, different relative permeability curves are calculated for the pre-infill and post-infill time periods because of improving connectivity.

In order to avoid possible discrepancies between IDPM and SimBest II results, the verification test case needed to have similar connectivity values for pre-infill and post-infill time periods. As a result, calculated IDPM relative permeability curves for both time periods would be very similar to each other, and this would allow input of only one relative permeability curve into SimBest II.

As Figure 1.10 in Section 1 illustrates, the higher the connectivity value at pre-infill conditions, the more horizontal the curve, and thus, the less change in connectivity as well spacing is reduced. Therefore, for this verification test, the IDPM was assigned a high initial connectivity value of .95 at 40 acre well spacing (80 acre 5-spot). Reducing the well spacing to 20 acres, increased the connectivity to .969 with slight changes in the relative permeability curves, but not enough to significantly effect comparison with SimBest II results.

The IDPM input for the verification test was as follows:

Dykstra-Parsons coefficient, $V_{dp} = .83$
No Plug Backs
4 Layers
 $K = .65$ md
 $K_y/K_x = 1$
 $K_z/K_x = .01$
5-spot (pre-infill) to 9-spot (infill)
80 acre non infill pattern area
Connectivity, $C = .95$ (at 1320 ft well spacing)

Non infill injection rate = 200 STBW/Day
Infill injection rate = 400 STBW/Day
Water cut at infill, $f_w = .60$
Water cut at economic limit, $f_{we} = .90$
Viscosity ratio, $u_o/u_w = 2$

For a more detailed listing of all parameters see the IDPM input and output for this case in Appendix Ia.

The same input parameters used in the IDPM run were used in the SimBest II decks. A 5 x 5 x 4 water-oil model was constructed, and pore volumes, transmissibilities, and kh values were reduced appropriately to simulate 1/8 of a 5-spot. Relative permeability curves were input directly from IDPM output for connectivity equal to .95. PVT values were obtained from correlations within SSI's Well Productivity Model (WPM).

The SimBest II input deck, simulation run deck, and timestep summary for this case are included in Appendix Ib. Each well was completed in all four layers. Rates were specified for each well. For the pre-infill time period (1 to 6,450 days), the injector rate was specified to be 25 STBW/Day with a bottomhole pressure constraint of 4,550 psi. The non-infill producer rate specification was 20 STBO/Day with a bottomhole pressure constraint of 100 psi. For the post-infill time period (6,450 to 17,600 days), the injector rate specification was increased to 50 STBW/Day. The non-infill producer rate specification was decreased to 10 STBO/Day, and the infill producer rate specification was 15 STBO/Day.

Figure 4.1 shows oil rate over time obtained from the IDPM as compared to SimBest II oil rate. Both IDPM and SimBest results are for 1/8 of the original 5-spot pattern. The results compare well. For the pre-infill time period, IDPM oil rate and SimBest oil rate are almost exact. At the time of infill (6,450 days), both IDPM and SimBest II calculate sharp increases in oil rate. Following infill, the oil rate calculated by SimBest II is above that calculated by IDPM, but the curve trend is identical.

Figure 4.2 illustrates the comparison of IDPM and SimBest II water production over time. As was the case for oil production, the water rate curves match closely.

Finally, Figure 4.3 shows water cut versus cumulative oil production for both IDPM and SimBest II results. The IDPM - SimBest II comparison for this plot is quite good for the pre-infill time period. However, at the time of infill, IDPM water cut continues to increase whereas SimBest II water cut drops from .64 to .59.

One would expect a decrease in water cut at the time of infill as SimBest II calculates. The IDPM water cut results are related to the high initial connectivity value. In this particular case, the high connectivity value defines an entirely continuous reservoir. As a result, IDPM water saturation values at the infill location are higher than they would be for a less continuous reservoir, everything else being equal. Sections 5 and 6 of this manual describe IDPM runs with lower initial connectivity values (.55) in which water cut at infill drops, as expected.

**IDPM Verification Against Black-Oil Simulation
(SSI's SimBest II) Oil Rate 1/8 5-Spot**

Figure 4.1

**IDPM Verification Against Black-Oil Simulation
(SSI's SimBest II) Water Rate 1/8 5-Spot**

Figure 4.2

**IDPM Verification Against Black-Oil Simulation
(SSI's SimBest II) Water Cut vs. Cumulative Oil Produced**

Figure 4.3

SECTION 5

VALIDATION OF IDPM AGAINST FIELD FLOOD RESULTS

The IDPM validation runs were made using Exxon's field data for the Robertson Clearfork Unit. Appendix IIa contains a copy of the SPE paper, "Quantitative Analysis of Infill Performance: Robertson Clearfork Unit" (SPE 15568), from which input parameters and production data were obtained for validation purposes. The paper provides concise summaries of the geology, trapping mechanism, lithology, depositional environment, and development history for the Robertson Clearfork Unit. Values for average permeability, porosity, and net pay were obtained from SPE 11023, "Infill Drilling to Increase Reserves - Actual Experience in Nine Fields in Texas, Oklahoma, and Illinois." A copy of this paper is also included in Appendix IIa.

Water flooding began in the Robertson Clearfork Unit in the early 1970's utilizing 80 acre 5-spot patterns. The unitized interval consists of the Glorieta, Upper Clearfork, and Lower Clearfork formations. By 1972, the flood included 33 water injectors. In 1976, Exxon began an infill drilling program which converted the original 5-spot patterns to 80 acre inverted 9-spot patterns. As seen in Figure 1 of SPE 15568 in Appendix IIa, a significant increase in oil production was the result of these first round of infills.

The IDPM was used to see if it would predict similar increases in oil and water production for 5-spot to 9-spot infilling. The parameters used in the validation run included the following:

- Dykstra-Parsons coefficient, $V_{dp} = .83$
- Plug Back each layer at water cut of .90
- 8 Layers
- $K = .65$ md
- $K_y/K_x = 1$
- $K_z/K_x = 0$
- 5-spot (pre-infill) to 9-spot (infill)
- 80 acre non infill pattern area
- Connectivity, $C = .55$ (at 1320 ft well spacing)

Non infill injection rate = 200 STBW/Day

Infill injection rate = 450 STBW/Day

Water cut at infill, $fw = .60$

Water cut at economic limit, $fwe = .90$

Viscosity ratio, $uo/uw = 2$

For a more detailed listing of all parameters see the Robertson Clearfork Unit IDPM input and output in Appendix IIb.

Eight layers were used in the IDPM to account for multiple pay stringers. Layers were plugged once water cut exceeded .60 for the layer. The connectivity value of .55 was obtained from Figure 1.10 in Section 1. Injection rates were calculated from withdrawals. For the 80 acre 5-spot water flooding, withdrawals were 3,900 RBOPD and 3,000 RBWPD or 6,900 RBPD. For 33 patterns, this is an average of 200 RBPD/pattern. After infilling, the 80 acre 9-spot patterns averaged withdrawals of 6,900 RBOPD and 8,000 RBWPD or 14,900 RBPD. This is an average of 450 RBPD/pattern.

Figure 5.1 illustrates the results obtained from the IDPM run compared to observed field data. IDPM output results are given for 1/8 of the original 5-spot pattern. In order to compare IDPM output with the observed field data, the IDPM output was multiplied by 8 to scale up to full pattern results and then multiplied by 33 to scale up to full field results.

IDPM results near the time of infill are quite good. The decline of oil production from 1974 to 1976 was matched, and the increase in oil production at infill was in line with the observed data. In this sense, IDPM did a very adequate job in forecasting the initial increase in oil production due to infill.

For the years 1971 through 1974, the IDPM results do not compare well with the observed data. IDPM calculated oil production was almost twice as much as observed oil production, and IDPM calculated water production was significantly lower than observed water production during this time period. In fact there was no appreciable calculated water production (more than 1,000 BWPD) until 1974.

The drastic difference between calculated and observed data during these years is related to primary production. The actual field data reflects production from initial water flood

start-up after primary depletion of the reservoir. IDPM, version 1.2 does not account for this primary production. Instead, oil saturation is at initial conditions as defined by the input connate water saturation. As water was injected in the IDPM, oil immediately was produced as should be the case in an incompressible system. An upgrade to version 1.2 should be considered to properly account for primary production.

After infilling from 5-spot to 9-spot in 1976, IDPM calculated oil and water production increased instantaneously. Both observed oil and water production data lag behind the calculated data as expected since the infills were not all completed at once. The IDPM effectively matched the 9-spot oil production increase and sustained this increase for a year before assuming a decline which was similar to 5-spot water flood decline (1974-1976).

The IDPM calculated infill response at 1976 and beyond is typical of what happens with infill drilling. However, the observed data not only shows oil production doubling, but this rate is sustained for three years until more infill drilling takes place. The observed data here is showing an effect which is due to something beyond infilling from a 5-spot to 9-spot. There may be something field related or operations related that has allowed production to make such a drastic change in character. If this is not an operational phenomenon, perhaps Figure 1.10 does not represent accurately enough the connectivity characteristics of the Robertson Clearfork Unit reservoir. In other words, the improvement in connectivity upon infilling may have been greater than what was input into the IDPM model. New reservoirs may have been tapped with the infill drilling.

Despite the differences in calculated versus observed data in the early time 5-spot and the late time 9-spot data, the IDPM successfully validated the increase in production seen at the time of infill for the Robertson Clearfork Unit.

IDPM Field Data Validation - Robertson Clearfork Unit
Observed and IDPM Calculated Oil and Water Production

Figure 5.1

SECTION 6

IDPM SENSITIVITY ANALYSIS

The IDPM sensitivity runs were conducted using Unocal's field data for the North Riley Unit. The enclosed paper by Fuller, Sarem, and Gould, "Screening Waterfloods for Infill Drilling Opportunities," explains the area in more detail (Appendix IIIa). Note that the sensitivity results described within the above mentioned paper vary slightly with those that follow. In the paper, the highest permeability layer was specified to be in the middle whereas the following sensitivity runs specify the highest permeability to be in the bottom layer.

The base case for the sensitivity runs uses the following critical parameters:

Dykstra-Parsons coefficient, $V_{dp} = .83$
No Plug Backs
11 Layers
 $K_y/K_x = 1$
 $K_z/K_x = .1$
5-spot (pre-infill) to 5-spot (infill)
40 acre non infill pattern area
Connectivity, $C = .55$ (at 933 ft well spacing)
Non infill injection rate = 200 STBW/Day
Infill injection rate = 400 STBW/Day
water cut at infill, $fw = .75$
water cut at economic limit, $fwe = .95$
Viscosity ratio, $u_o/u_w = 2.83$
IDPM Default Economic Criteria
Oil Price = \$20/STB

For a more detailed listing of all parameters see the North Riley Unit Base Case Listing in Appendix IIIb.

Number of Model Layers

As Figure 6.1 illustrates, incremental oil recovery due to infill drilling generally is the same for all layers at a given economic limit water cut (fwe). The recovery tends to level out as the number of layers increase above 8. As expected, incremental oil recovery increases with increasing fwe regardless of layer number.

Figure 6.1 also shows the profit to investment ratio (P/I) sensitivity to the number of layers in the model. With fewer layers (less than 4), even though more oil is recovered as fwe increases, P/I may decrease. For example in a 2 layer system, P/I for a fwe of .95 is less than P/I for a fwe of .90. However, this is not the case for models with more than 4 layers.

Areal and Vertical Heterogeneity and Sweep

The effects of areal heterogeneity on areal sweep were simulated within the IDPM using anisotropy (K_y/K_x). The effects of vertical heterogeneity on vertical sweep were simulated using the Dykstra-Parsons coefficient for permeability variation (Vdp). With an average permeability of 10 md for all layers combined, Vdp is used to distribute varying permeabilities to each layer.

As Figure 6.2 indicates, the trends in both the incremental recovery and P/I plots are very similar. Recovery and P/I increase with increasing anisotropy (K_y/K_x) and decreasing vertical heterogeneity (Vdp). When there is significant vertical heterogeneity (high Vdp value), thief zones dominate and overshadow the effect of areal heterogeneity. With a Vdp of .83, oil recovery is about the same regardless of K_y/K_x values. With lower Vdp values, areal heterogeneity makes a larger difference in oil recovery and P/I, especially with K_y/K_x values greater than 10.

Injectivity (Average Permeability) and Vertical Sweep (V_{dp})

Injectivity was varied within the IDPM by varying the combined average permeability for the 11 layers in the model. As Figure 6.3 illustrates, for all V_{dp} values, there is a gradual increasing trend for oil recovery as average model permeability increases from .1 md to 10 md. Oil recovery peaks at this point and begins to decline rapidly with increasing permeability. For the given conditions in the model, improving average permeability above 10 md improves the non infill 5-spot performance to the point that it becomes less attractive to infill. This same general trend is seen in the P/I plot.

Viscosity Ratio (u_o/u_w) and Vertical Sweep (V_{dp})

Figure 6.4 illustrates that the largest oil recovery and P/I occur with favorable viscosity ratios ($u_o/u_w = 1$) and low permeability variations ($V_{dp} = .4$). As expected, oil recovery and P/I decrease as viscosity ratio increases and V_{dp} increases. The only exception to this trend is in the P/I plot for a V_{dp} of .4 at viscosity ratios of 30 or more. The calculated oil recovery and P/I for high viscosity ratios (greater than 10) are not as accurate as those calculated for lesser viscosity ratios. The streamtubes within IDPM are static. With static streamtubes, it is difficult to model the viscous fingering effects which take place with high viscosity ratios. Therefore, there is some calculation error in the high viscosity ratio range. However, IDPM can still be used as an effective screening tool for these high viscosity ranges.

Viscosity Ratio (u_o/u_w) and Continuity (C)

In Figure 6.5, for favorable viscosity ratios near 1, incremental oil recovery and P/I due to infilling increase with decreasing continuity or connectivity between wells. However, as continuity decreases below .55 for the given conditions, the increase in incremental oil and P/I becomes negligible. For example, there is very little difference in the recovery and P/I for continuity values of .55 and .45. The erroneously high recovery

and P/I value for continuity equal to .45 and viscosity ratio equal to 100 demonstrates the limits of the IDPM's static stream tubes for high viscosity ratio ranges.

Infill Pattern Type and Plug Back

IDPM was used to analyze the effect of infilling a 40 acre 5-spot and converting it to a 40 acre 9-spot versus infilling to convert to a 20 acre 5-spot. The results in Figure 6.6 show that both incremental oil recovery and P/I are higher with a 5-spot to 5-spot conversion at all economic limit water cuts (fwe). The effect of plug back is also shown in this figure. In fact, plugging back watered out zones has a greater incremental effect on increasing oil recovery and P/I than does infill pattern type.

Oil Price and Depth

Figure 6.7 displays IDPM's sensitivity to oil price and depth. As expected, P/I improves with increasing oil price and decreasing depth.

Infill Drilling Predictive Model **Sensitivity Runs - No. of Model Layers**

Conditions:

5-Spot to 5-Spot Infill

Vdp = 0.83

No Plug Backs

Ky/Kx = 1.0

Kz/Kx = 0.1

Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern

C = 0.55 (at 933' Well Spacing)

Non Infill Injection Rate = 200 STB/D

Infill Injection Rate = 400 STB/D

fwi = 0.75 uo/uw = 2.83

Figure 6.1

Infill Drilling Predictive Model **Sensitivity Runs -Areal (K_y/K_x) & Vertical (V_{dp}) Sweep**

Conditions:

5-Spot to 5-Spot Infill
 11 Layers
 No Plug Backs
 $K_z/K_x = 0.1$
 Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern
 $C = 0.55$ (at 933' Well Spacing)
 Non Infill Injection Rate = 200 STB/D
 Infill Injection Rate = 400 STB/D
 $f_{wi} = 0.75$ $f_{we} = 0.95$
 $u_o/u_w = 2.83$

Figure 6.2

Infill Drilling Predictive Model **Sensitivity Runs -Injectivity (Average Permeability)**

Conditions:

5-Spot to 5-Spot Infill

11 Layers

No Plug Backs

$K_y/K_x = 1.0$ $K_z/K_x = 0.1$

Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern

$C = 0.55$ (at 933' Well Spacing)

Non Infill Injection Rate = 200 STB/D

Infill Injection Rate = 400 STB/D

$f_{wi} = 0.75$ $f_{we} = 0.95$

$u_o/u_w = 2.83$

Figure 6.3

Infill Drilling Predictive Model **Sensitivity Runs -Viscosity Ratio (μ_o/μ_w) & Vertical Sweep (V_{dp})**

Conditions:

5-Spot to 5-Spot Infill

11 Layers

No Plug Backs

$K_y/K_x = 1.0$

$K_z/K_x = 0.1$

Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern

$C = 0.55$ (at 933' Well Spacing)

Non Infill Injection Rate = 200 STB/D

Infill Injection Rate = 400 STB/D

$f_{wi} = 0.75$ $f_{we} = 0.95$

Figure 6.4

Infill Drilling Predictive Model **Sensitivity Runs -Viscosity Ratio (μ_o/μ_w) & Continuity (C)**

Conditions:
 5-Spot to 5-Spot Infill
 $V_{dp} = 0.83$
 11 Layers
 No Plug Backs
 $K_y/K_x = 1.0$ $K_z/K_x = 0.1$
 Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern
 Non Infill Injection Rate = 200 STB/D
 Infill Injection Rate = 400 STB/D
 $f_{wi} = 0.75$ $f_{we} = 0.95$

Figure 6.5

Infill Drilling Predictive Model Sensitivity Runs -Infill Pattern Type and Plug Back

Conditions:

Vdp = 0.83

11 Layers

Ky/Kx = 1.0

Kz/Kx = 0.1

Oil Price = \$20.00/STB

40 Acre Non Infill 5-Spot Pattern

C = 0.55 (at 933' Well Spacing)

Non Infill Injection Rate = 200 STB/D

Infill Injection Rate = 400 STB/D

fwi = 0.75 uo/uw = 2.83

Figure 6.6

Infill Drilling Predictive Model **Sensitivity Runs - Oil Price and Depth**

Conditions:

5-Spot to 5-Spot Infill

Vdp = 0.83

11 Layers

No Plug Backs

Ky/Kx = 1.0

Kz/Kx = 0.1

40 Acre Non Infill 5-Spot Pattern

C = 0.55 (at 933' Well Spacing)

Non Infill Injection = 200 STB/D

Infill Injection = 400 STB/D

fwi = 0.75 fwe = 0.95

uo/uw = 2.83

Figure 6.7

SECTION 7

IDPM SUBROUTINE GLOSSARY

ECONOMICS COMMONS--ECON--

COMMON /ECS/

SUMVOM	- Total Oil Produced, MBBL
CIOR	- Not used
TOTD	- Total tangible capital, present value (discounted), MM\$
SUMCI	- Total intangible capital, present value (discounted), MM\$
SVOS	- Total gross oil sold, MBBL (discounted)
SVGS	- Total gross gas sold, MMSCF (discounted)
SVIS	- Not used
SVPS	- Not used
SUMWT	- Total produced water treating cost, present value (discounted), MM\$
SINT	- Total interest cost, present value (discounted), MM\$
SPRP	- Total principal repayment, present value (discounted), MM\$
SUMOH	- Total overhead cost, present value (discounted), MM\$
USOH	- Total overhead cost (undiscounted), MM\$
DCE	- Not used
CINJ	- Cost of drilling and completion for in injection well (\$/well)
CEQP	- Cost to equip new producing well (\$/new producer)
CSEC	- Cost of additional secondary production equipment for a primary well converted to a secondary, \$/well
CNVT	- Cost to convert an existing producer to an injection well, \$/converted well
CREP	- Cost to upgrade surface processing equipment and lease facilities for secondary recovery operations, \$/producing well

CDAO	- Direct annual operating costs for secondary recovery operations, \$/producing well/yr
CIWO	- Additional annual operating costs for offshore water injection, \$/yr
URPV	- Total gross revenue (undiscounted), MM\$
UNOS	- Total net oil sales (undiscounted), MM\$
USEV	- Total severance tax (undiscounted), MM\$
USFO	- Total fixed operating cost (undiscounted), MM\$
USOPC	- Total variable operating cost (undiscounted), MM\$
USTR	- Not used
USWO	- Total well workover cost (undiscounted), MM\$
USTO	- Total operating cost, variable + fixed (undiscounted), MM\$
USIN	- Not used
USWT	- Total produced water treating cost (undiscounted), MM\$
UWCAP	- Total working capital (undiscounted), MM\$
USTC	- Total tangible capital (undiscounted), MM\$
USCI	- Total intangible capital (undiscounted), MM\$
USTI	- Total technician and instrument cost (undiscounted), MM\$
UCFB	- Total cash flow before tax (undiscounted), MM\$
UWPT	- Total windfall profits tax (undiscounted), MM\$
USIT	- Total state income tax (undiscounted), MM\$
UFIT	- Total federal income tax (undiscounted), MM\$
UATP	- Total after tax profit (undiscounted), MM\$
UINT	- Total interest cost (undiscounted), MM\$
ULOAN	- Total principal repayment (undiscounted), MM\$
SRPV	- Total revenue, present value (discounted), MM\$
SNOS	- Total net oil sales, present value (discounted), MM\$
SSEV	- Total severance tax, present value (discounted), MM\$

SUMFO	- Total fixed operating cost, present value (discounted), MM\$
SUMOPC	- Total variable operating cost, present value (discounted), MM\$
SUMTR	- Not used
SUMWO	- Total well workover cost, present value (discounted), MM\$
DCFB	- Total discounted cash flow before tax, MM\$
MUPPV	- Mean discounted cash flow, MM\$
STDDEV	- Standard deviation of the mean discounted cash flow, MM\$
PAYOUT	- Time at which after tax discounted cash flow = 0, years
PLIFE	- Project economic life, years
ROR	- Mean DCF rate of return, percent
CC	- Present value rate= $(1.+XINF)*(1.*XDR)-1$.
SUMIN	- Total injection cost, MM\$ (not used)
SUMWC	- Total working capital, present value (discounted), MM\$
DNB	- Present value of net oil sold (discounted), MBBL
SVON	- Cumulative net oil sold, MBBL
EFFINV	- Mean investment efficient = ratio of sum of positive discounted cash flows to absolute value of sum of negative discounted cash flows

COMMON /ECC/

MUVO(50)	- Mean oil volume, BBL
MUVG(50)	- Mean gas volume, MMSCF
MUVW(50)	- Mean water volume, BBL
MUVI(50)	- Not used
MUPO(50)	- Mean oil price, MM\$/BBL
MUPG(50)	- Mean gas price, MM\$/MSCF
MUPI(50)	- Not used
MUPP(50)	- Not used
MUWO(50)	- Mean well workover cost, MM\$

MUFO(50)	- Mean fixed operating cost, MM\$/yr
MUOPC(50)	- Mean variable operating cost, MM\$/BBL oil prod
MUTR(50)	- Not used
MUCT(50)	- Mean tangible capital, MM\$
MUCI(50)	- Mean intangible capital, MM\$
MUDB(50)	- Mean debt added, MM\$
MURP(50)	- Mean principal repayment, MM\$
MUIN(50)	- Mean interest payment, MM\$
MUPB(50)	- Mean principal balance at end of year (after principal payment), MM\$
SIGVO(50)	- Oil volume variance, STB/TR
SIGPO(50)	- Oil price variance, MM\$/BBL
SIGPG(50)	- Gas price variance, MM\$/MSCF
SIGPI(50)	- Not used
SIGFO(50)	- Fixed operating cost variance, MM\$/TR
SIGTR(50)	- Not used
SITRT(50)	- Tangible capital variance, MM\$/YR
SITRI(50)	- Intangible capital variance, MM\$/YR
SIGOPC(50)	- Variable operating cost variance, MM\$/BBL oil produced
SIGPP(50)	- Not used

COMMON /ECI/

M	- Number of years in the project (for all patterns)
MYR	- Number of years of production
IOUT	- Print control for economic calculations
ISTATE	- State code
IDIST	- District code (within a state)
IFIT	- Federal income tax credit option

IDISC	- Control for discounting method
IDEF	- Control for depreciation method
IPLIF	- Control on economic life
ISO	- Control for reading secondary oil volumes
CCHM	- Not used
CSCAP	- Not used
CWAT	- Capital for water injection plant, M\$
CWCAP	- Capacity of water injection plant, MMBBL/YR
WPHO	- Windfall tax beginning phase out date
EPHO	- Windfall tax ending phase out date
BTIM	- Base time for project start
BPOW	- Base oil price at start of project for purposes of WPT calculations, \$/BBL
PIPEL	- Not used
PCAP	- Not used
PDPM	- Not used
PFOC	- Not used
CPIPL	- Not used
DTIM	- Investment depreciation time, yrs
WCAP	- Months of working capital, months
UNCO	- Oil rate uncertainty, fraction
COSTRT	- Project startup costs, M\$
XDR	- Monetary discount rate, fraction
XINF	- Inflation rate, fraction
XROY	- Royalty rate, fraction
XSEV	- Severance tax rate, fraction
XWPT	- Windfall excise tax rate, fraction

XFIT	- Federal income tax rate, fraction
XTCR	- Investment tax credit, fraction
XSTX	- State income tax rate, fraction
WOCOST	- Annual well workover cost per pattern, M\$
PCTDBT	- Percent of capital (tangible and intangible) costs to be borrowed, percent
DBTINT	- Debt interest rate, percent
NYRRPY	- Number of years before beginning debt repayment
NYPAD	- Number of years before completing debt repayment
IDEBT	- Control on debt calculations
WTCOST	- Produced water treating cost, \$/BBL
ESCPO	- Escalation rate of oil price, fraction
ESCPG	- Escalation rate of gas price, fraction
ESCPI	- Not used
ESCFO	- Escalation rate of fixed operating costs, fraction
ESCTR	- Not used
ESCCT	- Not used
ESCCI	- Not used
ESCWO	- Escalation rate of well workover costs, fraction
ESCWT	- Escalation rate of tangible capital, fraction
ESCWI	- Escalation rate of intangible capital, fraction
ESCBP	- Inflation rate plus two percent
FOCPL	- Fixed operating cost per pattern, low, \$/yr
FOCPM	- Fixed operating cost per pattern, most likely, \$/yr
FOCPH	- Fixed operating cost per pattern, High, \$/yr
WPP1	- Number of injectors drilled per pattern
WPP2	- Number of producers drilled per pattern

WPP3	- Number of primary producers converted to secondary producers per pattern
WPP4	- Number of existing producers converted to injectors per pattern
OILB	- 1979 project base oil rate, MBBL/TR
OILC	- Current NON-tertiary project oil rate, MBBL/YR
DECL	- Annual oil production decline rate, fraction
OILR(50)	- Oil released, BBL
VOS(50)	- Volume of secondary oil produced per pattern, MBBL/YR
POL(50)	- Oil price, low, \$/BBL
POM(50)	- Oil price, most likely, \$/BBL
POH(50)	- Oil price, High, \$/BBL
PIL(50)	- Not used
PIM(50)	- Not used
PIH(50)	- Not used
PPL(50)	- Not used
PPM(50)	- Not used
PPH(50)	- Not used
FOCL(50)	- Fixed operating cost per pattern, low, \$/yr
FOCM(50)	- Fixed operating cost per pattern, most likely, \$/yr
FOCH(50)	- Fixed operating cost per pattern, high, \$/yr
OPCL(50)	- Variable operating cost, low, \$/BBL oil produced
OPCM(50)	- Variable operating cost, most likely, \$/BBL oil produced
OPCH(50)	- Variable operating cost, high, \$/BBL oil produced
TRPL(50)	- Not used
TRPM(50)	- Not used
TRPH(50)	- Not used
PGL(50)	- Gas price, low, \$/MSCF

PGM(50)	- Gas price, most likely, \$/MSCF
PGH(50)	- Gas price, high, \$/MSCF
CTPL(50)	- Tangible capital costs per pattern, low,
CTPM(50)	- Tangible capital costs per pattern, most likely, \$
CTPH(50)	- Tangible capital costs per pattern, high, \$
C IPL(50)	- Intangible capital costs per pattern, Low, \$
CIPM(50)	- Intangible capital costs per pattern, most likely, \$
CIPH(50)	- Intangible capital costs per pattern, high, \$
CTCL(50)	- Tangible capital costs for project, low, \$
CTCM(50)	- Tangible capital costs for project, most likely, \$
CTCH(50)	- Tangible capital costs for project, high, \$
CICL(50)	- Intangible capital costs for project, low, \$
CICM(50)	- Intangible capital costs for project, most likely, \$
CICH(50)	- Intangible capital costs for project, high, \$
VOL(50)	- Oil production for project, low, STB/yr
VOM(50)	- Oil production for project, most likely, STB/yr
VOH(50)	- Oil production for project, high, STB/yr
WO(50)	- Well workover cost per pattern, \$/yr
BPO(50)	- Base price of oil for WPT, \$/BBL
WTC(50)	- Produced water treating cost for project, \$/BBL
VGM(50)	- Gas produced for project, most likely, MMSCF/yr
VWM(50)	- Water produced for project, most likely, STB/yr
VIM(50)	- Not used
VPM(50)	- Not used
VPB(50)	- Water injected for project, most likely, MBBL
TITL(20)	- Up to 80 alpha-numeric characters to identify run
VOP(50)	- Volume oil produced, MBBL/yr/pattern

VGP(50)	- Volume gas produced, MMSCF/yr/pattern
VWCT(50)	- Year-end water cut, fraction, /yr/pattern
VWP(50)	- Volume water produced, MBBL/yr/pattern
VIP(50)	- Not used
VPP(50)	- Not used
VPBP(50)	- Volume of water injected, MBBL/yr/pattern
PATI(50)	- Number of patterns initiated each year of the project

COMMON /ECO/

DATE(50)	- Date, year
VOSLD(50)	- Annual volume of oil sold, MBBL
VONET(50)	- Annual net oil sold (less royalty), MBBL
AFUEL(50)	- Not used
VGNET(50)	- Annual net gas sold (less royalty), MMSCF
AREVO(50)	- Annual gross oil revenue, MM\$
AREVG(50)	- Annual gross gas revenue, MM\$
ARVWPT(50)	- Annual released oil revenue, MM\$
AREV(50)	- Annual gross revenue, MM\$
AOVH(50)	- Annual overhead, MM\$
AOVH1	- Annual overhead on drilling and completion, MM\$
AROY(50)	- Annual royalty, MM\$
ANET(50)	- Annual net revenue (less royalty), MM\$
ASEV(50)	- Annual severance tax, MM\$
AWTC(50)	- Annual produced water treating cost, MM\$
AINJ(50)	- Not used
AFOC(50)	- Annual fixed operating cost, MM\$
AVOC(50)	- Annual variable operating cost, MM\$

ATRC(50)	- Not used
ACOST(50)	- Annual total operating cost, MM\$
ACAP(50)	- Annual intangibles and depreciation, MM\$
AWPP(50)	- Annual windfall price difference, \$/BBL
TXCR(50)	- Annual investment tax credit, MM\$
DEPS(50)	- Annual depreciation, MM\$
AWCP(50)	- Annual working capital, MM\$
AQOR(50)	- Oil production rate, BBL/D
AQGR(50)	- Gas production rate, MSCF/D
AQWR(50)	- Water production rate, BBL/D
AQIR(50)	- Not used
ANOI(50)	- Annual net operating income before WPT and FIT, MM\$
AWPT(50)	- Annual windfall profit tax MM\$
ASTX(50)	- Annual state income tax, MM\$
ANTI(50)	- Annual net taxable income, MM\$
AFIT(50)	- Annual federal income tax, MM\$
ATPR(50)	- Annual after tax cash flow, MM\$
CFBT(50)	- Cumulative cash flow before tax, MM\$
CDBT(50)	- Cumulative cash flow before tax with constant dollars, MM\$
DCFBT(50)	- Cumulative discounted cash flow before tax, MM\$
CNOI(50)	- Cumulative net operating income, MM\$
CFAT(50)	- Cumulative cash flow after tax, MM\$
CDAT(50)	- Cumulative cash flow after tax with constant dollars, MM\$
DCFAT(50)	- Cumulative discounted cash flow after tax, MM\$
PVDF(50)	- Present value factor- $1/(1+CC)^{(I-1)}$

COMMON /OUT/

- CUMOS(5000) - Cumulative oil produced per pattern, MSTB
- CUMGS(5000) - Cumulative gas produced per pattern, MMSCF
- CUMWS(5000) - Cumulative water produced per pattern, MSTB
- CUMIB(5000) - Cumulative water injected per pattern, MSTB
- TIMS(5000) - Time, years
- EW CUT(5000) - Interpolation array for calculation of VWCT (year-end water cut)

COMMON /LIFE/

- IOPTS - Waterflood/infill drilling/incremental infill drilling control
- IWLIFE - End of waterflood, year

COMMON /LIF/

- LPAT - Estimated individual pattern life, years

SECTION 8

IDPM COMMON GLOSSARY

PARAMETERS

- IYRMAX - Maximum number of years for economic calculations. All the time dependent variables in the economic package are dimensioned to this value.
- IGDMAX - X-dimensions of the uniform grid (IGDMAX by JGDMAX) used to calculate stream flow rates for streamtube calculations, and to identify the locations of saturations and pressures from the non-infill case for interpolation of these values to the new infill streamtubes.
- JGDMAX - Y-dimensions of the uniform grid (IGDMAX by JGDMAX). See IGDMAX above.
- LGDMAX - The number of locations at which saturations and pressures are located for interpolation at infill time.
- ISTMAX - Maximum number of timesteps for the reservoir model. The reservoir model bases timestep size on the throughput through the tube/layer that has the higher ratio of injection to pore volume, but the actual number of timesteps is controlled by the ending water cut value "CUTMAX" input by the user.
- NTBMAX - Maximum number of stream tubes per layer. The most tubes used will be for the case of infill into a pattern for non-isotropic cases. NTBMAX must always be divisible by 4.
- NXMAX - Maximum number of cells per streamtube for the reservoir calculations. The trade-off in this value is the spacial truncation error versus the run time and memory requirements.
- ICRMAX - Dimension of unlabeled common in the reservoir calculations. During the reservoir calculations the saturations, flow coefficients, PVT properties, rel-perm values, pore volumes, and pressure equation coefficients are mapped into unlabeled common "A". Prior to the start of a run the size of ICRMAX is checked to determine if it is large enough for the problem.
- LAYMAX - Maximum number of layers allowed for the current program dimensions.

COMMON /INSAV/

- VP1B - Pressure values for all cells, tubes, and layers at the infill point from the non-infill case
- VS01B - Oil saturation values at the infill time from the non-infill case
- VS01B - Oil saturation values at the infill time from the non-infill case
- WSW1B - Water saturation values at the infill time from the non-infill case

COMMON /VCNTRL/

- MLAYER - At any point and time in the reservoir calculations, this is the layer being processed
- MTUBE - At any point and time in the reservoir calculations, this is the streamtube being processed
- IGOIN - Plug-back control input variable
- VCUT - Water cut when the infill case is to start
- SGGV - Gas gravity, used in defaults for oil properties
- IGOV - At any point in reservoir calculations, this is the case being run (2=non-infill, 1=infill)
- VAREA - Total pattern size in acres
- VCONEC - Reservoir connectivity at VAREA pattern size
- VCCN - Modified version of VCONEC used in subroutine WATSAT, computed once for efficiency
- RSCALE - Scaling factor for going from element of symmetry in reservoir calculations to full pattern economics

COMMON /VINPUT/

- VNX - Number of cells per tube
- VCROC - Input pore volume compressibility
- VREFP - Reference pressure, phi is at this pressure
- VYEAR - Starting date of non-infill case
- VPHI - Porosity by layer
- VKX - X-direction permeability by layer
- VKY - Y-direction permeability by layer
- VH1 - Net pay by layer, Gross = Net

VZT	- Elevation subsurface at top of each layer (negative)
VZB	- Elevation at bottom of each layer
VP1	- Pressure in each cell, tube, and layer at time > 0
VSO	- Oil saturation in each cell at time > 0
VSF	- Water saturation in each cell at time > 0
VKZKH	- Vertical permeability to X direction per ratio
VRATE1	- User-specified injection rate for entire pattern during infill
VRATE	- User-specified injection rate for entire pattern during non-infill run
VANIS	- Anisotropic value, KY/KX
ILAYER	- Total number of layers in model
VTEMP	- Reservoir temperature used in defaulting data

COMMON /WELLV/

VAOX	- Production well pressure coefficient
VRHSX	- Production well right hand side term for use in generating coefficients
VPO	- Oil production rate calculated for pressure specified well
VPW	- Water production rate calculated for pressure specified well
VPI	- Well productivity index, calculated internally
VQW.	- Water injection rate for each tube
VPWELL	- Bottomhole flowing pressure for production well

COMMON /WELLV1/

VPWEL1	- Bottomhole pressure for pressure specified injection wells in infill case
VPW1	- Calculated injection rate for pressure specified injection well
VAOX1	- Pressure coefficient term for pressure specified injection well
VRHSX1	- Right hand side term for pressure specified injector

COMMON /LOCGET/

IPROD	- Plug back indicator for each streamtube producer
IINJ	- Plug back indicator for each streamtube injector

COMMON /VMODEL/

VP	-	Pressure in each cell at time 0
VSO1	-	Oil saturations at time zero
VSW1	-	Water saturations at time zero
VTX	-	Transmissibility between cells in a streamtube
VTY	-	Not used
VZAVG	-	Cell mid-point elevations
VTZ	-	Transmissibility between layers
VPV1	-	Pore volumes at REFP for each cell in model

COMMON /VSAVE/

NGCELT	-	Reservoir tube that each streamtube grid cell is located in for the non-infill case
NGCELC	-	Reservoir grid cell that each streamtube grid cell is located in for the non-infill case
IGCELT	-	Reservoir tube that each streamtube grid cell is located in for the infill case
IGCELC	-	Reservoir grid cell that each streamtube grid cell is located in for the infill case

COMMON /CELL/

NUMTUB	-	Maximum (input) number of streamtubes in model per layer
NOTUBS	-	Actual number of streamtubes in model per layer
ATOT	-	Total volume of each streamtube
ATOTAL	-	Total volume of all cells in layer
RX	-	X-direction location of center of mass of grid cell
RY	-	Y-direction location of center of mass of grid cell
RWIDE	-	Width of each grid cell
RLENG	-	Length of each grid cell
AVOL	-	Relative volume of each grid cell
KMRKSL	-	Counter for arbitrating hits in subroutine MARKSL

COMMON /AV/

VXNO	-	Oil relative permeability curve shape factor
VXNW	-	Water relative permeability curve shape factor
VXKROE	-	Oil relative permeability at VSWC for VCONEC =1.0
VXKRWE	-	Water relative permeability at VSORW for VCONEC =1.0
VSWC	-	Water connate saturation
VSORW	-	Residual oil saturation to a waterflood

COMMON /RATEV/

OILRAT	-	Non-infill oil rate at each timestep
WATRAT	-	Non-infill water rate at each timestep
TTIME	-	Cumulative time at each timestep for non-infill
OILRT1	-	Infill oil rate at each timestep
WATRT1	-	Infill water rate at each timestep
TTIM1	-	Cumulative time at each timestep for infill
OILCM	-	Cumulative oil at each timestep for non-infill
PVIN	-	Pore volumes injected at each timestep for non-infill
OILRC	-	Oil recovery at each timestep in non-infill
WCT	-	Water cut at each timestep in non-infill
OILCM1	-	Cumulative oil at each timestep for infill
PVIN1	-	Pore volumes injected at each timestep for infill
OILRC1	-	Oil recovery at each timestep in infill
WCT1	-	Water cut at each timestep in infill

COMMON /CONT1/

IARRP	-	Array output control
IANALP	-	Reservoir calculations analysis output control
ISTRMP	-	Streamtube output control
IECONR	-	Economic calculations control
DYKST	-	Dykstra-Parsons VDP value

IDYST - Layer Dykstra-Parsons calculation method selector
ITITV - Reservoir calculations title

COMMON /BLANK/

A - Work space for reservoir calculations
ACORE - Total size of work space

COMMON /AUTO/

CUTMAX - Water cut at end of run for both non-infill and infill cases
DTMAX - Unused
DTLAST - Unused
DTPER - Unused
DSMAX - Unused
DSGIVN - Unused
DELTAT - Timestep size (constant)
CUMTIM - Cumulative time in reservoir calculations
STOPIT - Switch used to signal end to simulator run

COMMON /OIP/

OIP - Oil in place
WIP - Water in place
GIP - Unused
OIPOLD - Oil in place last timestep
WIPOLD - Water in place last timestep
GIPOLD - Unused
OIPOR - Original oil in place
WIPOR - Original water in place
ORIGPV - Original pore volume
PVTOT - Total pore volume
HCPORV - Hydrocarbon pore volume

COMMON /SIZE/

- NCORE - Size of blank common
- IEXCES - Left over work space in each section of reservoir calculations
- NWLMAX - Unused
- MISIBM - Double precision indicator - unused at present
- LASTIN - End of permanent arrays in the blank common

COMMON /SIMPLE/

- SWAT - Simple water property calculations indicator
- DENWTR - Water density at reservoir conditions
- CMPWTR - Water phase compressibility
- VISWTR - Water viscosity

COMMON /SIMOIL/

- DENOIL - Oil density at reservoir conditions
- CMPOIL - Oil phase compressibility
- VISOIL - Oil phase viscosity
- DENOST - Oil density at standard conditions
- DENWST - Water density at standard conditions
- GORV - Gas oil ratio for economics
- BOI - Oil formation volume factor at reservoir conditions
- BWI - Water formation volume factor at reservoir conditions
- APIV - API gravity of reservoir oil

COMMON /OPTION/

- METH - Pressure solution method, always =1

COMMON /GRDSIZ/

NX	-	Number of grid cells per tube
NY	-	=1
NXNY	-	= NX
REFPRE	-	Reference pressure
DATUM	-	Unused
NZ	-	Number of layers
KZ	-	Layer for which the coefficients are being calculated
NXNYNZ	-	Number of cells per streamtube cross section

COMMON /CROCK/

CROCK	-	Pore volume compressibility
-------	---	-----------------------------

COMON /COMSQZ/

NOSQZ	-	Unused
NSHRT	-	Unused
NLONG	-	Unused
IALONG	-	Unused
IASHRT	-	Unused
ISCZER	-	Start of flow coefficient storage at back of blank common
ISCPTR	-	Pointer for next flow coefficient to be stored
KSCPTR	-	Unused
LIMSCR	-	Limit of space in blank common for coefficients
NOARR	-	Unused

COMMON /RPORT4/

TOCUM	-	Total cumulative oil production
TWCUM	-	Total cumulative water production
TWICUM	-	Total cumulative water injection

TORAT - Total oil rate
TWRAT - Total water production rate
TWIRAT - Total water injection rate

COMMON /LOCAL/

ICUTC - Indicator for the time to save arrays for infill
OIPOR1 - Original oil in place for non-infill
TOTKH - Total KH of the layers
VTUBE - Relative injection rates for each streamtube
TSTEP - Timestep
XNCSTP - Increment for output (0.1 pore volume)
XSTPR - Output increment counter
PVLY - Pore volume for each streamtube

COMMON /RSTART/

NSTEP - Timestep number at any time in reservoir calculation
NSTR - Timestep number at infill start
TAPE - Unused
KEEP - Timestep number at end of non-infill run
ISTRT - Unused
NSTART - Unused
TOPT - Unused
RESTSW - Unused

COMMON /TUBE/

NONODE - Number of nodes in finite element mesh
NOELEM - Number of elements in finite element mesh

X	- X coordinate value of the nodes in the pressure and stream function calculations. These locations are where the steady state solution of pressures is performed in the "surface" routines. The values are then interpolated to the uniform pressure and stream arrays for calculation of stream tubes.
Y	- Y coordinate value of the nodes in the pressure and stream function calculations (see above)
RATE	- Specified source/sink term for calculation of steady state pressure distribution. Rates are only specified for the 1/8 and 1/4 corner wells for the element of symmetry of the 5 spot pattern.
PSPEC	- Specified pressure for the calculation of steady state pressure distribution. Pressure at the center of the grid is specified, then based on input KX/KY ratio and the rate specification locations the steady state pressure distribution is calculated.
NODE	- The nodes that form the corners of the triangle that makes up each element in the finite element solution
TRANS	- Transmissibility of each element in the finite element solution. For the calculation of stream tubes the transmissibility is immaterial in that it effects the levels of the pressures but not the shapes of the tubes for homogeneous areal systems.
NNODE	- List of the nodes that are connected to each node. <i>Note:</i> in the current code, no more than 10 nodes may be connected to any one node, i.e. no node can be in more than 10 elements.
TERM	- Flow coefficient between each of the nodes that is connected, for use in the steady-state pressure solution
PRESUR	- Pressure at each of the nodes from the steady-state finite element solution for pressure distribution
IMINGD	- Minimum X-index for each of the JGDMAX grid rows
IMAXGD	- Maximum X-index for each of the JGDMAX grid rows

COMMON /LSOR/

OMEG	- LSOR overrelaxation parameter
TSATX	- Unused
TSUMX	- Unused
OMDIFF	- Omega change value for next pressure solution iteration
OMBUG	- Unused

COMMON /ANORM/

ANORM - Normalization vector in LSOR routine
IJKLOC - Cell pointer in solution routine

COMMON /SATCOM/

IFIRST - Beginning cell of each streamtube, =1
IFINAL - Last cell of each streamtube, =NX
IPRT - Unused
SWLHS - Unused
SOLHS - Unused
PVLHS - Unused
XPOIL - Unused
XPWAT - Unused
XPGAS - Unused
CPOOLD - Unused
CPWOLD - Unused
CPGOLD - Unused
J - =1
K - Layer for which calculations are done in subroutine OVER6
IJKO - Cell and layer pointer in saturation solution
CALSAT - Master pointer for doing saturation solution
IVF - Indicator for doing vertical flow calculations
GIPALT - Unused
QPTOT - Unused

COMMON /OL6VEX/

SYMAOE - Oil flow coefficient between a cell and cell to its right in a tube
SWMAWE - Water flow coefficient between a cell and cell to its right in a tube
SYMAGE - Gas coefficient, unused in current version
RHSO - Right hand side of known terms for oil equation

RHSW	-	Right hand side of known terms for water equation
RHSG	-	Gas coefficient, unused at present
RHSP	-	Unused
SYMAPE	-	Unused at present
DG	-	Gas property pointer, unused at present
NPVT	-	Fluid property pointer

COMMON /COFCOM/

J	-	=1
K	-	Layer for which coefficients are being set up
IJKO	-	Location of calculation within a streamtube cross section
IFIRST	-	First cell in tube, =1
IFINAL	-	Last active cell in a tube, =nx

COMMON /EMPCOM/

ISTART	-	= IFIRST
IFINIS	-	= IFINAL, would be different with 0 pore volume cells in a model

COMMON /OLAVEX/

OILRHS	-	Right hand side coefficient for oil saturation equation
WTRRHS	-	Right hand side coefficient for water saturation equation
GASRHS	-	Gas equation, unused at present
AOC	-	Center cell pressure coefficient
AWC	-	Center cell water pressure coefficient
AGC	-	Gas pressure coefficient, unused at present
AON	-	Oil equation pressure coefficient for cell in next streamtube, set to zero at present
AWN	-	Water equation pressure coefficient for cell in next streamtube, set to zero at present
AGN	-	Gas coefficient, unused at present

AOS	- Oil pressure coefficient for last streamtube, unused
AWS	- Water pressure coefficient for last streamtube, unused
AGS	- Gas coefficient, unused at present
AOW	- Oil pressure coefficient for flow from cell to left
AWW	- Water pressure coefficient for flow from cell to left
AGW	- Gas coefficient, unused at present
AOE	- Oil pressure coefficient for flow to cell to right
AWE	- Water pressure coefficient for flow to cell to right
AGE	- Gas coefficient, unused at present
RPVODT	- Pore volume cell pressure equation coefficient
XTRAN	- Transmissibility between cells in a tube
YTRAN	- Transmissibility between cells in last tube, unused
DELS	- Potential gradient to cell in last tube, unused
DELE	- Potential gradient to cell to right in tube
SO	- Oil saturation
SW	- Water saturation

COMMON /FILES/

METRIC	- Not presently used, available for future extension to non-field units input and output
IR	- Logical unit for input(5)
IW	- Logical unit for tabular output (6)
IP	- Logical unit for plot output (12)
IPOUT	- Not used

SECTION 9

IDPM TREE STRUCTURE

The following tree structure of the IDPM source code was produced by SSI's PROFLOW program.

ROUTINE MAIN CALLS THE FOLLOWING ROUTINES --

OVER1	OVER2	OVER3	OVER4	OVER5
OVER6	OVER7	CUTBCK	ECONID	HALTER

ROUTINE MAIN IS CALLED BY THE FOLLOWING ROUTINES --

ROUTINE PROIL CALLS THE FOLLOWING ROUTINES --

ROUTINE PROIL IS CALLED BY THE FOLLOWING ROUTINES --

CUTBCK ACHECK EMPFUN PVTFUN

ROUTINE PORE CALLS THE FOLLOWING ROUTINES --

ROUTINE PORE IS CALLED BY THE FOLLOWING ROUTINES --

ACHECK SATSOL

ROUTINE REPLAC CALLS THE FOLLOWING ROUTINES --

ROUTINE REPLAC IS CALLED BY THE FOLLOWING ROUTINES --

ROUTINE SATDEP CALLS THE FOLLOWING ROUTINES --

WATSAT

ROUTINE SATDEP IS CALLED BY THE FOLLOWING ROUTINES --

EMPFUN

ROUTINE WATPR CALLS THE FOLLOWING ROUTINES --

ROUTINE WATPR IS CALLED BY THE FOLLOWING ROUTINES --

CUTBCK ACHECK

ROUTINE WATSAT CALLS THE FOLLOWING ROUTINES --

ROUTINE WATSAT IS CALLED BY THE FOLLOWING ROUTINES --

SATDEP CUTBCK RPTABL

ROUTINE ZEROS CALLS THE FOLLOWING ROUTINES --

ROUTINE ZEROS IS CALLED BY THE FOLLOWING ROUTINES --

INITAL LSOR2D OVER6 SATSOL

ROUTINE ECONID CALLS THE FOLLOWING ROUTINES --

INEC ECON OUTE

ROUTINE ECONID IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE UOUT CALLS THE FOLLOWING ROUTINES --

ROUTINE UOUT IS CALLED BY THE FOLLOWING ROUTINES --

INEC OUTE

ROUTINE INEC CALLS THE FOLLOWING ROUTINES --

TITLE SDINT ECFTR CHEKE STCDE

UOUT

ROUTINE INEC IS CALLED BY THE FOLLOWING ROUTINES --

ECONID

ROUTINE STCDE CALLS THE FOLLOWING ROUTINES --

ROUTINE STCDE IS CALLED BY THE FOLLOWING ROUTINES --

INEC

ROUTINE CHEKE CALLS THE FOLLOWING ROUTINES --

SDINT CIND

ROUTINE CHEKE IS CALLED BY THE FOLLOWING ROUTINES --

INEC

ROUTINE CIND CALLS THE FOLLOWING ROUTINES --

ROUTINE CIND IS CALLED BY THE FOLLOWING ROUTINES --

CHEKE

ROUTINE ECFTR CALLS THE FOLLOWING ROUTINES --

ROUTINE ECFTR IS CALLED BY THE FOLLOWING ROUTINES --

INEC

ROUTINE ECON CALLS THE FOLLOWING ROUTINES --

NEWDCF

ROUTINE ECON IS CALLED BY THE FOLLOWING ROUTINES --

ECONID

ROUTINE OUTE CALLS THE FOLLOWING ROUTINES --

UOUT TITLE

ROUTINE OUTE IS CALLED BY THE FOLLOWING ROUTINES --

ECONID

ROUTINE SDINT CALLS THE FOLLOWING ROUTINES --

ROUTINE SDINT IS CALLED BY THE FOLLOWING ROUTINES --

INEC CHEKE

ROUTINE TITLE CALLS THE FOLLOWING ROUTINES --

ROUTINE TITLE IS CALLED BY THE FOLLOWING ROUTINES --

INEC OUTE

ROUTINE NEWDCF CALLS THE FOLLOWING ROUTINES --

APRVAL

ROUTINE NEWDCF IS CALLED BY THE FOLLOWING ROUTINES --

ECON

ROUTINE APRVAL CALLS THE FOLLOWING ROUTINES --

ROUTINE APRVAL IS CALLED BY THE FOLLOWING ROUTINES --

NEWDCF

ROUTINE CUTBCK CALLS THE FOLLOWING ROUTINES --

PROIL WATPR WATSAT

ROUTINE CUTBCK IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE OVER1 CALLS THE FOLLOWING ROUTINES --

INITAL SINGLE

ROUTINE OVER1 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE INITAL CALLS THE FOLLOWING ROUTINES --

ZEROS

ROUTINE INITAL IS CALLED BY THE FOLLOWING ROUTINES --

OVER1

ROUTINE SINGLE CALLS THE FOLLOWING ROUTINES --

TITLR DPLYR HALTER RPTABL GENTUB

ROUTINE SINGLE IS CALLED BY THE FOLLOWING ROUTINES --

OVER1

ROUTINE RPTABL CALLS THE FOLLOWING ROUTINES --

WATSAT

ROUTINE RPTABL IS CALLED BY THE FOLLOWING ROUTINES --

SINGLE

ROUTINE TITLR CALLS THE FOLLOWING ROUTINES --

ROUTINE TITLR IS CALLED BY THE FOLLOWING ROUTINES --

SINGLE

ROUTINE DPLYR CALLS THE FOLLOWING ROUTINES --

ROOT3 ERFUNC

ROUTINE DPLYR IS CALLED BY THE FOLLOWING ROUTINES --

SINGLE

ROUTINE CFUN CALLS THE FOLLOWING ROUTINES --

ERFUNC

ROUTINE CFUN IS CALLED BY THE FOLLOWING ROUTINES --

ROOT3

ROUTINE FFUN CALLS THE FOLLOWING ROUTINES --

ERFUNC

ROUTINE FFUN IS CALLED BY THE FOLLOWING ROUTINES --

ROOT3

ROUTINE ERFUNC CALLS THE FOLLOWING ROUTINES --

ROUTINE ERFUNC IS CALLED BY THE FOLLOWING ROUTINES --

DPLYR CFUN FFUN

ROUTINE ROOT3 CALLS THE FOLLOWING ROUTINES --

CFUN FFUN

ROUTINE ROOT3 IS CALLED BY THE FOLLOWING ROUTINES --

DPLYR

ROUTINE GENTUB CALLS THE FOLLOWING ROUTINES --

GENFEL FELSLV GENFCG MARKST DEFTUB
DEFFDC GENMCP

ROUTINE GENTUB IS CALLED BY THE FOLLOWING ROUTINES --

SINGLE

ROUTINE GENFEL CALLS THE FOLLOWING ROUTINES --

PATTRN NODDEF NODNET HALTER

ROUTINE GENFEL IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE NODDEF CALLS THE FOLLOWING ROUTINES --

HALTER

ROUTINE NODDEF IS CALLED BY THE FOLLOWING ROUTINES --

GENFEL

ROUTINE NODNET CALLS THE FOLLOWING ROUTINES --

ROUTINE NODNET IS CALLED BY THE FOLLOWING ROUTINES --

GENFEL

ROUTINE PATTRN CALLS THE FOLLOWING ROUTINES --

ROUTINE PATTRN IS CALLED BY THE FOLLOWING ROUTINES --

GENFEL

ROUTINE FELSLV CALLS THE FOLLOWING ROUTINES --

ROUTINE FELSLV IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE GENFCG CALLS THE FOLLOWING ROUTINES --

HALTER

ROUTINE GENFCG IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE MARKST CALLS THE FOLLOWING ROUTINES --

HALTER MARKSL FOLLSL TUBAUS

ROUTINE MARKST IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE FOLLSL CALLS THE FOLLOWING ROUTINES --

MARKSL EXTEND HALTER

ROUTINE FOLLSL IS CALLED BY THE FOLLOWING ROUTINES --

MARKST

ROUTINE EXTEND CALLS THE FOLLOWING ROUTINES --

MARKSL

ROUTINE EXTEND IS CALLED BY THE FOLLOWING ROUTINES --

FOLLSL

ROUTINE MARKSL CALLS THE FOLLOWING ROUTINES --

ROUTINE MARKSL IS CALLED BY THE FOLLOWING ROUTINES --

MARKST FOLLSL EXTEND

ROUTINE DEFTUB CALLS THE FOLLOWING ROUTINES --

SEARCH TUBAUS

ROUTINE DEFTUB IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE SEARCH CALLS THE FOLLOWING ROUTINES --

HALTER

ROUTINE SEARCH IS CALLED BY THE FOLLOWING ROUTINES --

DEFTUB

ROUTINE TUBAUS CALLS THE FOLLOWING ROUTINES --

ROUTINE TUBAUS IS CALLED BY THE FOLLOWING ROUTINES --

MARKST DEFTUB DEFFDC

ROUTINE DEFFDC CALLS THE FOLLOWING ROUTINES --

HALTER UTLSRX TUBAUS

ROUTINE DEFFDC IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE UTLSRX CALLS THE FOLLOWING ROUTINES --

ROUTINE UTLSRX IS CALLED BY THE FOLLOWING ROUTINES --

DEFFDC

ROUTINE GENMCP CALLS THE FOLLOWING ROUTINES --

ROUTINE GENMCP IS CALLED BY THE FOLLOWING ROUTINES --

GENTUB

ROUTINE OVER2 CALLS THE FOLLOWING ROUTINES --

ACHECK

ROUTINE OVER2 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE ACHECK CALLS THE FOLLOWING ROUTINES --

GRIDCH GRIDC3 GRIDC2 GRIDC1 PORE
PROIL WATPR

ROUTINE ACHECK IS CALLED BY THE FOLLOWING ROUTINES --

OVER2

ROUTINE GRIDCH CALLS THE FOLLOWING ROUTINES --

ROUTINE GRIDCH IS CALLED BY THE FOLLOWING ROUTINES --

ACHECK

ROUTINE GRIDC1 CALLS THE FOLLOWING ROUTINES --

ROUTINE GRIDC1 IS CALLED BY THE FOLLOWING ROUTINES --

ACHECK

ROUTINE GRIDC2 CALLS THE FOLLOWING ROUTINES --

ROUTINE GRIDC2 IS CALLED BY THE FOLLOWING ROUTINES --

ACHECK

ROUTINE GRIDC3 CALLS THE FOLLOWING ROUTINES --

ROUTINE GRIDC3 IS CALLED BY THE FOLLOWING ROUTINES --

ACHECK

ROUTINE OVER3 CALLS THE FOLLOWING ROUTINES --

ROUTINE OVER3 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE OVER4 CALLS THE FOLLOWING ROUTINES --

EMPFUN WTRFUN INICOF OILCOF WTRCOF
FINCOF

ROUTINE OVER4 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE EMPFUN CALLS THE FOLLOWING ROUTINES --

PROIL SATDEP

ROUTINE EMPFUN IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE WTRFUN CALLS THE FOLLOWING ROUTINES --

ROUTINE WTRFUN IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE INICOF CALLS THE FOLLOWING ROUTINES --

ROUTINE INICOF IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE OILCOF CALLS THE FOLLOWING ROUTINES --

ROUTINE OILCOF IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE WTRCOF CALLS THE FOLLOWING ROUTINES --

ROUTINE WTRCOF IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE FINCOF CALLS THE FOLLOWING ROUTINES --

GETWEL SYMOUT

ROUTINE FINCOF IS CALLED BY THE FOLLOWING ROUTINES --

OVER4

ROUTINE SYMOUT CALLS THE FOLLOWING ROUTINES --

ROUTINE SYMOUT IS CALLED BY THE FOLLOWING ROUTINES --

FINCOF

ROUTINE GETWEL CALLS THE FOLLOWING ROUTINES --

ROUTINE GETWEL IS CALLED BY THE FOLLOWING ROUTINES --

FINCOF

ROUTINE OVER5 CALLS THE FOLLOWING ROUTINES --

OVER51

ROUTINE OVER5 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE LSOR2D CALLS THE FOLLOWING ROUTINES --

ZEROS TRIDIA OPTMIZ

ROUTINE LSOR2D IS CALLED BY THE FOLLOWING ROUTINES --

OVER51

ROUTINE TRIDIA CALLS THE FOLLOWING ROUTINES --

ROUTINE TRIDIA IS CALLED BY THE FOLLOWING ROUTINES --

LSOR2D

ROUTINE OPTMIZ CALLS THE FOLLOWING ROUTINES --

ROUTINE OPTMIZ IS CALLED BY THE FOLLOWING ROUTINES --

LSOR2D

ROUTINE OVER51 CALLS THE FOLLOWING ROUTINES --

LSOR2D

ROUTINE OVER51 IS CALLED BY THE FOLLOWING ROUTINES --

OVER5

ROUTINE OVER6 CALLS THE FOLLOWING ROUTINES --

INISAT ZEROS SATSOL

ROUTINE OVER6 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE INISAT CALLS THE FOLLOWING ROUTINES --

ROUTINE INISAT IS CALLED BY THE FOLLOWING ROUTINES --

OVER6

ROUTINE PVTFUN CALLS THE FOLLOWING ROUTINES --

PROIL

ROUTINE PVTFUN IS CALLED BY THE FOLLOWING ROUTINES --

SATSOL

ROUTINE SATSOL CALLS THE FOLLOWING ROUTINES --

SYMINN ZEROS PVTFUN PORE PUTWEL

ROUTINE SATSOL IS CALLED BY THE FOLLOWING ROUTINES --

OVER6

ROUTINE PUTWEL CALLS THE FOLLOWING ROUTINES --

ROUTINE PUTWEL IS CALLED BY THE FOLLOWING ROUTINES --

SATSOL

ROUTINE SYMINN CALLS THE FOLLOWING ROUTINES --

ROUTINE SYMINN IS CALLED BY THE FOLLOWING ROUTINES --

SATSOL

ROUTINE OVER7 CALLS THE FOLLOWING ROUTINES --

REPORT

ROUTINE OVER7 IS CALLED BY THE FOLLOWING ROUTINES --

MAIN

ROUTINE REPORT CALLS THE FOLLOWING ROUTINES --

ROUTINE REPORT IS CALLED BY THE FOLLOWING ROUTINES --

OVER7

ROUTINE HALTER CALLS THE FOLLOWING ROUTINES --

ROUTINE HALTER IS CALLED BY THE FOLLOWING ROUTINES --

MAIN SINGLE GENFEL NODDEF GENFCG
MARKST FOLLSL SEARCH DEFFDC

OVER1

```

INITAL
ZEROS
SINGLE
  TITLR
  DPLYR
    ROOT3
      CFUN
        ERFUNC
          FFUN
            ERFUNC
              ERFUNC
                HALTER
                RPTABL
                WATSAT
                GENTUB
                  GENFEL
                    PATTRN
                    NODDEF
                      HALTER
                      NOONET
                      HALTER
                      FELSLV
                      GENFCG
                      HALTER
                      MARKST
                      HALTER
                      MARKSL
                      FOLLSL
                        MARKSL
                        EXTEND
                          MARKSL
                          HALTER
                          TUBAUS
                          DEFTUB
                          SEARCH
                          HALTER
                          TUBAUS
                          DEFFDC
                          HALTER
                          UTLSRX
                          TUBAUS
                          GENMCP

```

OVER2

```

ACHECK
  GRIDCH
  GRIDC3
  GRIDC2
  GRIDC1
  PORE
  PROIL
  WATPR

```

OVER3

OVER4

```

EMPFUN
  PROIL
  SATDEP
    WATSAT
    WTRFUN
    INICOF
    OILCOF
    WTRCOF
    FINCOF
      GETWEL
      SYMOUT

```

```

OVER5
  OVER51
    LSOR2D
      ZEROS
      TRIDIA
      OPTMIZ

OVER6
  INISAT
  ZEROS
  SATSOL
    SYMINN
    ZEROS
    PVTFUN
      PROIL
    PORE
    PUTWEL

OVER7
  REPORT
CUTBCK
  PROIL
  WATPR
  WATSAT
ECONID
  INEC
    TITLE
    SDINT
    ECFTR
    CHEKE
      SDINT
      CIND
    STCDE
    UOUT
  ECON
    NEWDCF
      APRVAL
  OUTE
    UOUT
    TITLE

HALTER
FORTRAN STOP

```

SECTION 10

REFERENCES

Aydelotte, S. R. and Pope, G. A.: "A Simplified Predictive Model for Streamdrive Performance," J. Pet. Tech. (May 1983) 991-1002.

Abramowitz, M. and Stegun, I. A.: Handbook of Mathematical Functions, U.S. Dept. of Commerce, (1964) 927-978.

Barbe, J. A. and Schnoebelen, D. J.: "Quantitative Analysis of Infill Performance: Robertson Clearfork Unit," SPE 15568, presented at the October 1986 SPE Annual Technical Conference and Exhibition, New Orleans, LA.

A. H. Barber, et.al.: "Infill Drilling to Increase Reserves - Actual Experience in Nine Fields in Texas, Oklahoma, and Illinois," J. Pet. Tech. (Aug 1983) 1530-38.

Basuni, M. N.: "Successful Infill Drilling in Raja Field Causes Ten-Fold Increase in Production," Proceedings Indonesian Petroleum Association, June 1978.

Beggs, H. B. and Robinson, J. B.: Estimating the Viscosity of Crude Oil Systems, JPT (Sept. 1975), 1140.

Breitenbach, E. A., Thurnau, D. H., and van Poolen, H. K.: "Solution of the Immiscible Fluid Flow Simulation Equations," Society of Petroleum Engineers of AIME, Dallas Meeting, (April 22 to 23, 1968), Preprint No. SPE 2021.

Breitenbach, E. A., Thurnau, D. H., and van Poolen, H. K.: "Immiscible Fluid Flow Simulator," Society of Petroleum Engineers of AIME, Dallas Meeting, (April 22 to 23, 1968), Preprint No. SPE 2019.

Brigham, W. E. and Abbaszadeh-Dehghani, M.: "Tracer Testing for Reservoir Description," J. Pet. Tech. (May 1987) 519-527.

Buckley, S. E. and Leverett, M. C.: "Mechanism of Fluid Displacement in Sands," Trans., AIME (1942) v. 146, 107-116.

Bush, J. L. and Helander, D. P.: "Empirical Prediction of Recovery Rate in Waterflooding Depleted Sands," Trans., AIME (1968) v. 243, 933-943.

Capen, E. C. et al.: Growth Rate -- A Rate-of-Return Measure of Investment Efficiency, Technical Paper, JPT (May 1976), 531-543.

de Josselin de Jong, G.: "Generating Functions in the Theory of Flow through Porous Media," Published in Flow through Porous Media, Academic Press, New York 1969, 377-400.

Davidson, L. B. and Cooper, D. O.: "A Simple Way of Developing a Probability Distribution of Present Value," J. Pet. Tech. (Sept 1976) 1069-1078.

DOE/BC-86/7/SP, "In-Situ Combustion Predictive Model," Dec 1986, DE86000284.

DOE/BC-86/10/SP, "Polymer Predictive Model," Dec. 1986, DE87001207.

DOE/BC-86/11/SP, "Chemical Flood Predictive Model," Dec. 1986, DE87001208.

DOE/BC-86/12/SP, "CO₂ Miscible Flood Predictive Model," Dec 1986, DE87001209.

DOE/BC-86/6/SP, "Steamflood Predictive Model," Dec 1986, DE87001219.

DOE/EIA-0185 (1982) "Costs and Indexes for Domestic Oil and Gas Field Equipment and Production Operations, 1982."

Driscoll, V. J.: "Recovery Optimization Through Infill Drilling - Concepts, Analysis, and Field Results," SPE 4977, presented at 1974 SPE Fall Meeting, Houston, Texas.

Dykstra, H. and Parsons, R. L.: "The Prediction of Oil Recovery by Waterflooding," Secondary Recovery of Oil in the United States, 2nd. ed., API (1950) 160-174.

Fuller, S. M., Sarem, A. M., and Gould, T.L.,: "Screening Waterfloods for Infill Drilling Opportunities," SPE 22333 presented at the March 1992 SPE International Meeting on Petroleum Engineering, Beijing, China.

Ghuari, W. K.. et.al.: "Production Technology Experience in a Large Carbonate Waterflood, Denver Unit, Wasson San Andres Field," J. Pet. Tech. (Sept 1980) 1493-1502.

Gould, T. L. and Munoz, M. A.: "An Analysis of Infill Drilling," SPE 11021, presented at 1982 SPE Fall Meeting, New Orleans, LA.

Gould, T. L. and Sarem, A. M. Sam: "Infill Drilling for Incremental Recovery," J. Pet. Tech. (March 1989) 229-237.

Higgins, R. V. and Leighton, A. J.: "A Computer Method to Calculate Two-Phase Flow in Any Irregularly Bounded Porous Medium," Trans., AIME (1962) v. 225, 679-683.

Holm, L. W.: "Infill Drilling vs. Tertiary Oil Recovery vs. More Imports," J. Pet. Tech. (July 1980) 1169-1174.

Laughlin, B. A., Jardon, M. A. and Wu, C. H., "Infill Drilling Economic Analysis of Carbonate Oil Reservoirs in West Texas," SPE 16854, presented at 1987 SPE Fall Meeting, Dallas.

Law, J.: "Statistical Approach to the Interstitial Heterogeneity of Sand Reservoirs," Trans., AIME (1949) v. 155, 202-222.

Matthews, C. S. and Russell, D. G., "Pressure Buildup and Tests in Wells," SPE Monograph Series, 1967.

National Petroleum Council: Enhanced Oil Recovery, NPC, Washington, D.C. (1984).

Paul, G. W., Lake, L. W., Pope, G. A., and Young, G. B.: "A Simplified Predictive Model for Micellar-Polymer Flooding," paper SPE 10733, 1982 California Regional Meeting, San Francisco, March 24-26.

Paul, G. W., Lake, L. W., and Gould, T. L.: "A Simplified Predictive Model for CO₂ Miscible Flooding," SPE 13238, presented at 1984 SPE Fall Meeting, Houston, Texas.

Peterson, J. E., Paulsson, B. N. T. and McEdilly, T. V.: "Application of Algebraic Reconstruction Technique for Cross Hole Seismic Data," Geoph. Vol. 50 No. 10 Pg. 1566.

Prats, M., Mathews, C. S., Jewett, R. L. and Baker, J. D.: "Prediction of Injection Rate and Production History for Multifluid Five-Spot Floods," Trans., AIME (1959) v. 216, 98-105.

Prentice, R. S.: "Waterflooding the Grayburg Formation on the J. L. Johnson AB Lease: Experience in the Johnson Field," J. Pet. Tech. (Oct 1984) 1773-1780.

Price-Waterhouse, 1980. "The Crude Oil Windfall Profit Tax."

Restine, J. L., Graves, W. G., and Elias Jr., R.: "Infill Drilling in a Steamflood Operation: Kern River Field," SPERE (May 1987) 243-248.

Snyder, R. W. and Ramey, H. J., Jr.: "Application of Buckley-Leverett Displacement Theory to Noncommunicating Layered Systems," Trans., AIME (1967) v. 240, 1500-1506.

Stiles, L. H.: "Optimizing Waterflood Recovery in a Mature Waterflood, The Fullerton Clearfork Unit," SPE 6198, presented at 1976 SPE Fall Meeting, New Orleans, LA.

Stiles, W. E.: "The Use of Permeability Distribution in Waterflood Calculations," Trans., AIME (1949) v. 186, 9-13.

van Everdingen, A. F. and Kriss, H. S.: "A Proposal to Improve Recovery Efficiency," J. Pet. Tech. (July 1980) 1164-1168.

Vazquez, M. and Beggs, H.D.: Correlations for Fluid Physical Property Prediction, Forum, JPT, (June 1980), 968-970.

Wagner, O. R.: "The Use of Tracers in Diagnosing Interwell Reservoir Heterogeneities - Field Results," J. Pet. Tech. (Nov 1977) 1410-1416.

Zabihi, Alex. Personal communication.

Zapata, V. J. and Lake, L. W.: "A Theoretical Analysis of Viscous Crossflow," SPE 10111, presented at 1981 SPE Fall Meeting, San Antonio, Texas.

Zienkiewicz, O. C., "The Finite Element Method in Engineering Science," McGraw-Hill (1971).

Zienkiewicz, O. C. and Cheung, Y. K.: "Finite Elements in the Solution of Fluid Problems," The Engineer (Sept 24, 1965) 507-510.

SECTION 11

PROGRAM LISTING

```

C*****
C
C *****   INFILL DRILLING PREDICTIVE MODEL - IDPM
C
C   DEVELOPED BY : SCIENTIFIC SOFTWARE-INTERCOMP
C                  1801 CALIFORNIA ST, SUITE 295
C                  DENVER, COLO. 80202
C                  (303) 292-1111
C
C
C   RELEASE:   1.2.0
C
C   DATE:      SEPT 1991
C
C   ABSTRACT:  IDPM COMPUTES THE PREDICTED OIL RECOVERY AND
C               THE ASSOCIATED ECONOMICS SCALED TO ENTIRE FIELD
C               FOR WATERFLOODS INCLUDING INFILL DRILLING AT A
C               USER SPECIFIED WATER CUT.  RECOVERY CALCULATIONS
C               ARE COMPUTED FOR THE ELEMENT OF SYMMETRY OF A
C               LAYERED FIVE-SPOT PATTERN.
C
C   ASSUMPTIONS:
C       1. COMPRESSIBLE FLUIDS AND ROCK
C       2. STREAMTUBES DO NOT CHANGE SHAPE WITH WATER CUT
C       3. STREAMTUBES ARE INDEPENDENT OF MOBILITY RATIO
C       4. CROSSFLOW BETWEEN LAYERS
C       5. EACH LAYER IS HOMOGENEOUS (PERM,POROS,THICK)
C       6. LAYERS ARE ANISOTROPIC
C
C   IDPM FEATURES INCLUDE:
C       1. RECOVERY AS A FUNCTION OF PORE VOLUMES INJECTED
C       2. DISPLACEMENT SWEEP CALCULATED FROM 1-D SIMULATOR
C          WITHIN STREAMTUBES, XSEC SIMULATION IN CROSSFLOW
C          CASES.
C       3. AREAL SWEEPS ACCOUNTED FOR BY STREAMTUBE SHAPES
C       4. STREAMTUBE SHAPES ARE A FUNCTION OF KY/KX RATIO
C       5. VERTICAL SWEEP BY CROSSFLOW CALCULATIONS.
C       6. EFFECT OF CONNECTIVITY IN RESERVOIR MODELLED BY
C          CHANGES IN REL PERM END POINTS WITH SPACING
C       7. INJECTIVITY EFFECTS OF INFILLING ARE MODELLED
C          BY SWITCHING TO CONSTANT PRESSURE INJECTION AT
C          INFILL AFTER RATE SPECIFICATION FOR NON-INFILL.
C       8. ECONOMICS CALCULATED ON A DISCOUNTED AND
C          UNDISCOUNTED CASH FLOWS FOR NON-INFILL, INFILL,
C          AND INCREMENTAL CASES.
C       9. DEFAULT RESERVOIR AND ECONOMIC PARAMETERS
C          INCLUDED IN PROGRAM FOR MOST INPUT DATA
C*****
C
C -----
C
C   MAIN -- CONTROLS THE FLOW OF THE PROGRAM BY CALLING THE RESERVOIR
C           CALCULATION INPUT ROUTINES -- OVER1, INITIAL, AND SINGLE --
C           GRID SETUP ROUTINES -- OVER2, ACHECK, GRIDxx -- AND THE
C           ROUTINES THAT SOLVE THE RESERVOIR FLOW CALCULATIONS FOR
C           EACH STREAMTUBE FOR EACH TIMESTEP -- ROUTINES OVER3
C           THROUGH REPORT.  THEN THE ECONOMICS ROUTINES -- ECONID
C           THROUGH SDINT -- ARE CALLED AND THE RUN IS ENDED.
C
C -----
C

```

C PTT 6/91 THESE ARE FOR SENSITIVITY RUNS

```

    PARAMETER (NVAR=3)
    PARAMETER (NBYTE=NVAR*4)
    PARAMETER (NPACK=100)
    PARAMETER (IRLEN=NPACK*NBYTE)

    CHARACTER*80 TITLE
    CHARACTER*12 NAME
    CHARACTER*6 TNAME
C
    INTEGER*2 DAY, MONTH, YEAR
    INTEGER IREF, EXTRSW
C -mb
    COMMON /SENS/ IWP1,IWP2,UV1,UV2,UV3,ISENS,IDO_IT,XXMX,
+ TITLE,NAME,TNAME
    INCLUDE 'BOO.INC'

    DIMENSION V1(10),V2(10),V3(10)
    REAL HIST(250), THIST(250), MODEL(250)
    CHARACTER*1 CR

    CR=CHAR(10)
    IDO_IT=0
    ISW=0

C    OPEN(5,FILE='params.dat',STATUS='OLD',IOSTAT=IS)
C    IF (IS.EQ.0) THEN
C        READ(5,*) ISENS
C    ELSE
C        ISENS=0
C    ENDIF
C
C    OPEN DATE FILE
C
C    OPEN(UNIT=19,FILE='rundate.dat',STATUS='OLD')
C    READ(19,*) IREF
C    READ(19,100) MONTH,DAY,YEAR
C100  FORMAT(4X,A3,1X,A2,14X,A4)
C
C    For the PC version, call for the date w/ the provided subroutine.
C
C    CALL GETDAT(YEAR,MONTH,DAY)
C    OPEN(29,FILE='results.tab',STATUS='OLD')
C    OPEN(29,FILE='results.tab',STATUS='UNKNOWN')
C    OPEN(31,FILE='resultsx.tab',STATUS='UNKNOWN')
C    IF (ISENS.NE.0) THEN
C
C    We are doing either the optimal search or a grid search. In
C    either case, open the results.tab file to record trial values.
C    amj, 12-30-92
C
C        IF (ISENS.LT.0) THEN
C
C    CALL ASA'S OPTIMAL SEARCH
C
C        WRITE(6,321)
321    FORMAT(' About to call search routine.')
        CALL SEARCH10(IREF,MONTH,DAY,YEAR)
    ELSE
```

```

C
C DO MATRIX
C   CONNECTIVITY:
C
C       READ(5,*) IV1
C       READ(5,*) (V1(L),L=1,IV1)
C
C   VDP:
C
C       READ(5,*) IV2
C       READ(5,*) (V2(L),L=1,IV2)
C
C   KY/KX:
C
C       READ(5,*) IV3
C       READ(5,*) (V3(L),L=1,IV3)
C
C       M=IV1*IV2*IV3
C       N=0
C       ISW = 1
C       CALL COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
C       ISW = 0
C
C       DO 10 K=1,IV3
C         UV3=V3(K)
C         WRITE(TNAME,'(''_case'',I1)') K
C
C         DO 10 I=1,IV1
C           UV1=V1(I)
C           DO 10 J=1,IV2
C             UV2=V2(J)
C
C           CALL PUT1(IWP1,UV1,UV2,UV3,1.0,1,1)
C           CALL PUT2(IWP2,UV1,UV2,UV3,1.0,1,1)
C
C           N=N+1
C           WRITE(*,699) N,M,UV1,UV2,UV3
699          FORMAT('RUN ',I3,' OF ',I3,3F10.2)
C
C           CALL MAINS(UV1,UV2,UV3)
C           CALL FIXUP(THIST,HIST,NA,MODEL,NM)
C           CALL COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
C
C   10   CONTINUE
C
C   -mb   CALL PUT1(IWP1,0.0,0.0,0.0,1.0,-1,1)
C         CALL PUT2(IWP2,0.0,0.0,0.0,1.0,-1,1)
C
C   ENDIF
C   ELSE
C
C   If you get here, the first param = 0. A new, second param
C   has been entered in the next position to switch into the
C   two-pass infill routine, thusly:
C     ITWOSW = 0 for waterflood only,
C             = 1 for single-pass infill
C             = 2 for two-pass infill
C
C   READ(5,*) ITWOSW
C   ITWOSW=1

```

```

NAME='model'
TNAME='model'
TITLE=' '
IF (ITWOSW .EQ. 0) THEN
    CALL MAINS(UV1,UV2,UV3)
ELSE
    IF (ITWOSW .EQ. 2) THEN
C
C Call the rest of the model twice. First find the time step
C at which cumulative oil production is equal to the historical
C during the waterflood. Then call an infill scenario that
C begins at that time step.
C
        WRITE(6,222)
222        FORMAT(' First Pass')
        CALL MAINS(UV1, UV2, UV3)
        ENDIF
        ITWOSW = 3
C
C Open tiny file to read extrapolation switch(es).
C
223        continue
C        OPEN(43, FILE = 'extrap.sw', STATUS = 'OLD')
C223        READ(43,*,END=230) EXTRSW
C        WRITE(6,224) EXTRSW
C224        FORMAT(' Infill Pass; extrap method ',I1)
        CALL MAINS(UV1, UV2, UV3)
C        GO TO 223
230        CONTINUE
        ENDIF
    ENDIF
    STOP 'Normal termination of IDPM'
    END
    SUBROUTINE ADDIT(PART,POINTS,IFORCE,TEMP)
    INTEGER PART,POINTS,I
    CHARACTER*8 TEMP,TEMP2
    CHARACTER*1 CHR
    DIMENSION CHR(10)
    DATA (CHR(I),I=1,10) /'0','1','2','3','4','5','6','7','8','9'/
    TEMP2 = ' '
    IF (PART .EQ. 0.0) TEMP2(1:1) = '0'
10    IF ((PART .LE. 0).OR. (LENGTH8(TEMP2) .EQ. 8)) GO TO 20
        I = PART / 10
        TEMP2(LENGTH8(TEMP2)+1:LENGTH8(TEMP2)+1) = CHR(PART-I*10+1)
        PART = I
        GO TO 10
20    CONTINUE
    IF ( LENGTH8(TEMP2) .GE. POINTS) GO TO 40
        DO 35, I=LENGTH8(TEMP2)+1,POINTS
            TEMP2(I:I) = '0'
35        CONTINUE
40    CONTINUE
    IF ((IFORCE.EQ.0) .OR. (LENGTH8(TEMP2).GE.IFORCE)) GO TO 45
        K=IFORCE-LENGTH8(TEMP2)
        DO 43, I=LENGTH8(TEMP2)+K, K+1, -1
            TEMP2(I:I) = TEMP2(I-1:I-1)
43        CONTINUE
        DO 44, I=1,K
            TEMP2(I:I) = '0'
44        CONTINUE

```

```

45  CONTINUE
    J = LENGTH8(TEMP)
    K = LENGTH8(TEMP2)
    IF (J+K.GT.8) K=8-J
    DO 50, I=1, K
        TEMP (J+K+1-I:J+K+1-I) = TEMP2(I:I)
50  CONTINUE
    RETURN
END
FUNCTION CONVERT(ARG, IFORCE)
INTEGER IPART, FPART, POINTS, FPART2
REAL*8 ARG, FTEMP
CHARACTER*8 TEMP, CONVERT
TEMP = ' '
IPART = INT(ARG)
FPART = NINT( (ARG - IPART) * 10000)
IF (FPART.EQ.0) GO TO 20
FPART2 = FPART
IF (FPART2/1000.NE.0) THEN
    POINTS = 1
    FPART2 = MOD(FPART2, 1000)
END IF
IF (FPART2/100.NE.0) THEN
    POINTS = 2
    FPART2 = MOD(FPART2, 100)
END IF
IF (FPART2/10.NE.0) THEN
    POINTS = 3
    FPART2 = MOD(FPART2, 10)
END IF
IF (FPART2.NE.0) POINTS = 4
IF (POINTS.EQ.3) FPART = FPART / 10
IF (POINTS.EQ.2) FPART = FPART / 100
IF (POINTS.EQ.1) FPART = FPART / 1000
20  CONTINUE
IF (FPART.EQ.0) POINTS = IFORCE
IF (FPART.EQ.0) GO TO 15
IF ((IFORCE.EQ.0) .OR. (POINTS .LE. IFORCE)) GO TO 15
12  IF (POINTS - 1 .LE. IFORCE) GO TO 13
    FPART = FPART / 10
    POINTS = POINTS - 1
    GO TO 12
13  FPART = NINT( REAL(FPART) / 10.0)
    POINTS = IFORCE
15  CONTINUE
    CALL ADDIT(IPART, 0, 0, TEMP)
    IF (POINTS .NE. 0) THEN
        TEMP (LENGTH8(TEMP)+1:LENGTH8(TEMP)+1) = ' .'
        CALL ADDIT(FPART, POINTS, IFORCE, TEMP)
    END IF
    CONVERT = TEMP
    RETURN
END
FUNCTION LENGTH8(STRING)
CHARACTER*8 STRING
INTEGER LENGTH8, I, J
J = 0
DO 10, I=1, 8
    IF (STRING(I:I) .NE. ' ') J = I
10  CONTINUE

```

```

        LENGTH8 = J
        RETURN
    END
    FUNCTION LENGTH35 (STRING)
    CHARACTER*35 STRING
    INTEGER LENGTH35, I, J
    J = 0
    DO 10, I=1, 35
        IF (STRING(I:I) .NE. ' ') J = I
10    CONTINUE
    LENGTH35 = J
    RETURN
    END
    SUBROUTINE MAINS (UUV1, UUV2, UUV3)
C
C PTT 6/91 THESE ARE FOR SENSITIVITY RUNS
C
        CHARACTER*80 TITLE
        CHARACTER*12 NAME
        CHARACTER*6 TNAME
        CHARACTER*1 BEEP, OVERWR
        CHARACTER*51 PFILE, IFILE, OFILE
        INTEGER EXTRSW
        LOGICAL FOUND
C
C -mb
        COMMON /SENS/ IWP1, IWP2, UV1, UV2, UV3, ISENS, IDO_IT, XXMX,
+ TITLE, NAME, TNAME
C
C PTT CONTINUITY
        COMMON/FOO/ UVC, UVC1, BOK, IKBM
        INCLUDE 'BOO.INC'
        INCLUDE 'PARAM.INC'
        INCLUDE 'SIMUL.INC'
        INCLUDE 'STREAM.INC'
        INCLUDE 'FILES.INC'
C
C IR = 8
C OPEN ( IR, FILE='INPUT.DAT', STATUS='OLD' )
C IW = 9
C OPEN ( IW, FILE='OUTPUT.LIS', STATUS='UNKNOWN' )
C
        BEEP = CHAR(7)
        UV1=UUV1
        UV2=UUV2
        UV3=UUV3
        ICUTC=0

        IR = 8
        CLOSE (IR)
4000 WRITE (*, 4100)
4100 FORMAT(' Path and name for input file ',
&' (<= 51 characters)?' /)
        READ (*, 4200) IFILE
4200 FORMAT(A51)
        INQUIRE (FILE=IFILE, EXIST=FOUND)
        IF ( FOUND ) GOTO 4400
        WRITE (*, 4300) IFILE, BEEP
4300 FORMAT(1X, 'File:' /1X, A51 /, ' not found!', A1 /)
        GOTO 4000

```



```

C      OPEN ( IR, FILE='input.dat', STATUS='OLD' )
4400  OPEN (IR,FILE=IFILE,STATUS='OLD')
      READ(IR,'(A80)') NAME
      READ (IR,*) IDUM1,IDUM2,IDUM3,IECONR
      REWIND (IR)
      IW = 9
      CLOSE(IW)
C      IF (ISENS .EQ. 0) THEN
4500  WRITE(*,4600)
4600  FORMAT('// Path and name for output file ',
& ' (<= 51 characters)?'//)
      READ(*,4200) OFILE
      INQUIRE(FILE=OFILE,EXIST=FOUND)
      IF ( .NOT. FOUND ) GOTO 5000
      WRITE(*,4700) OFILE,BEEP
4700  FORMAT(1X,'File:'/1X,A51/, ' already exists!',A1/)
4750  WRITE(*,4800)
4800  FORMAT(' Do you wish to OVERWRITE this file (y or n)?'//)
      READ(*,4900) OVERWR
4900  FORMAT(A1)
      IF ( OVERWR .EQ. 'y' .OR. OVERWR .EQ. 'Y' ) GOTO 5000
      IF ( OVERWR .EQ. 'n' .OR. OVERWR .EQ. 'N' ) GOTO 4500
      GOTO 4750
5000  OPEN ( IW, FILE=OFILE, status='unknown' )
C      ELSE
C      OPEN ( IW, FILE='/dev/null', status='unknown' )
C      ENDIF
      IF (IECONR.NE.2) GOTO 6002
5500  WRITE(*,5600)
5600  FORMAT('// Path and name for plot file ',
& ' (<= 51 characters)?'//)
      READ(*,4200) PFILE
      INQUIRE(FILE=PFILE,EXIST=FOUND)
      IF ( .NOT. FOUND ) GOTO 6000
      WRITE(*,5700) PFILE,BEEP
5700  FORMAT(1X,'File:'/1X,A51/, ' already exists!',A1/)
5750  WRITE(*,5800)
5800  FORMAT(' Do you wish to OVERWRITE this file (y or n)?'//)
      READ(*,5900) OVERWR
5900  FORMAT(A1)
      IF ( OVERWR .EQ. 'y' .OR. OVERWR .EQ. 'Y' ) GOTO 6000
      IF ( OVERWR .EQ. 'n' .OR. OVERWR .EQ. 'N' ) GOTO 5500
      GOTO 5750
6000  OPEN ( 15, FILE=PFILE, status='unknown' )
C      ELSE
C      OPEN ( IW, FILE='/dev/null', status='unknown' )
C      ENDIF
6002  CONTINUE
C PTT 6/91 USE EXISING UNIT IN 'FILES.INC' FOR PLOT HEADER FILE

      IP = 12
c -mb CLOSE(IP)
c      OPEN ( IP, FILE='model.pl3', STATUS='UNKNOWN' )

      IMON = 6
      NCORE=ICRMAX
      ACORE = NCORE
C
      DO 9000 I=2,1,-1
C

```

```

C      IGOV = 2 FOR THE NON-INFILL CASE AND 1 FOR THE INFILL CASE
C
C      IGOV=I
C
C PTT 6/91 CHECK IF INFILL CASE DISABLED
C      IF(IGOV.EQ.1 .AND. INFIL.EQ.1) GOTO 9000
C
C      INPUT ROUTINES FOR THE RESERVOIR PERFORMANCE CALCULATIONS
C      STREAMTUBE CALCULATION ROUTINES ARE CALLED FROM HERE ALSO
C
C      CALL OVER1
C
C fm 9-30-92
C      by order of KB, any reservoir with an input value for
C      continuity of 1.0 has (by definition) zero infill
C      potential. UVC, passed in common block /foo/ is the
C      test value for continuity
C
C      if (UVC.ge.1.0) then
C          fmoip = 7758.*varea*fmhnet*fmpor*fmsoi/fmboi/1000.
C          fminfp = 0.
C          fmipct = 0.
C          go to 99069
C      endif
C
C
C      GRID PROPERTIES PER RESERVOIR GRID CELL FOR EACH STREAMTUBE
C
C      CALL OVER2
C
C      LOOP THROUGH ALL THE RESERVOIR CALCULATION ROUTINES ONCE TO
C      DETERMINE IF ENOUGH BLANK COMMON 'ICRMAX' HAS BEEN SPECIFIED
C      IN PARAMETER STATEMENTS TO SOLVE THE PROBLEM SIZE AS
C      DETERMINED BY THE USER INPUT DATA.
C
C      CALL OVER3
C      CALL OVER4
C      CALL OVER5
C      CALL OVER6
C      CALL OVER7
C
C      3000 CONTINUE
C
C      IN INFILL, THE LAYERS THAT ARE PRODUCING AT WATERCUTS ABOVE THE
C      SPECIFIED INFILL WATER CUT WILL BE SHUT-IN IF USER SPECIFIES.
C      THIS IS DONE AFTER 5 TIME STEPS BECAUSE OF THE LARGE CHANGES IN
C      FLOW PATHS THAT OCCURS AT INFILL MAY RESULT IN WATER CUTS THAT
C      ARE TEMPORARILY ABOVE THE WATER CUT AT NON-INFILL EVEN THOUGH
C      THESE VALUES WOULD DECREASE.
C
C      IF ( IGOV .EQ. 1 .AND. ILLAYER .GT. 1 .AND. IGOIN.EQ.2)
C      +   CALL CUTBCK ( NSTEP-NSTR )
C
C      LOOP AROUND THE RESERVOIR CALCULATIONS FOR EACH STREAMTUBE OR
C      FOR EACH VERTICAL STACK OF STREAMTUBES FOR MULTI-LAYER CASES.
C
C      STOPIT = 0
C      DO 8000 I11=1,NOTUBS
C          MTUBE= I11
C

```

```

C      INCREMENT THE TIME STEP NUMBER AND THE CUMULATIVE TIME
C
C      CALL OVER3
C
C      SET UP COEFFICIENT MATRICES FOR THE PRESSURE AND SATURATION
C      MATRIX EQUATIONS FOR EACH STREAMTUBE.
C
C      CALL OVER4
C
C      DO IMPLICIT PRESSURE EQUATIONS SOLUTION
C
C      CALL OVER5
C
C      DO EXPLICIT SATURATION EQUATIONS SOLUTION
C
C      CALL OVER6
C
C      OUTPUT RESULTS AT 0.1 PV INJECTED INTERVALS, UPDATE RECOVERY
C      VERSUS TIME COMMONS FOR ECONOMICS, AND SAVE NON-INFILL PRESSURE
C      AND SATURATION ARRAYS WHEN THE INFILL WATER CUT POINT IN TIME
C      IS REACHED
C
C      CALL OVER7
8000 CONTINUE
C
C      CHECK TO SEE THAT WE HAVE NOT EXCEEDED THE MAXIMUM NUMBER OF
C      TIMESTEPS THAT CAN BE STORED FOR ECONOMIC CALCULATIONS.
C
C      IF ( NSTEP .LT. ISTMAX)GO TO 3011
C      WRITE(IW,3012) NSTEP
3012 FORMAT (' *****',/
1      ' ',/ STopping RUN DUE TO REACHING ',/
2      ' ',/ MAXIMUM NUMBER OF TIMESTEPS ',/
3      ' ',/ MAXIMUM = ',I5,',/
4      ' *****')
C      GO TO 9000
C
C      3011 CONTINUE
C      IF ( STOPIT .EQ. 0 ) GO TO 3000
C
C      STOP RESERVOIR RUN IF NO OIL RATE - OR -
C      STOP RESERVOIR RUN IF WE HAVE EXCEEDED THE USER SPECIFIED END OF
C      RUN WATER CUT.
C
C      9000 CONTINUE
C
C      OUTPUT THE RESERVOIR PERFORMANCE FOR THE ELEMENT OF SYMMETRY FOR
C      EACH CASE.
C
C PTT 10/91 ORIGINAL OIL IN PLACE FOR RECOVERY FACTORS - BASED ON
C SWC RATHER THAN USER INPUT SATURATIONS
C
C      UPV=0.0
C      DO 777 LL=1, ILAYER
777      UPV=UPV+ VH1(LL)*VPHI(LL)
C
C PTT OOIP, 1/8
C      OOIP=7758.*VAREA*(1-VSWC)*UPV/BOK/UVCL /RSCLAE
C DJR 3/94

```

```

      IF (IKBM.EQ.0) OOIP=7758.*VAREA*(1-VSWC)*UPV/BOK /RSCALE

C
C PTT 6/91 IF WE ENDED BEFORE REACHING INFILL CUT, USE NSTEP

      IF (KEEP.EQ.0) KEEP=NSTEP
      U1=RSCALE

C
      IF ( IANALP .EQ. 0 ) GO TO 7015

C
      WRITE(IW,7000)
7000 FORMAT(1H1
&      /// 20X,' PERFORMANCE VERSUS TIME FOR NON-INFILL ',
&      / 20X,' =====',
1  ///,'      TIME      OIL RATE      WATER RATE      CUMOIL      WCUT ',
2  '      PV INJ  OIL REC ',/,',      DAYS      STB/D      STB/D',
3  '      MSTB      FRAC.      FRAC.      %OOIP ')

      DO 7010 I=1,KEEP
      WRITE(IW,7020) TTIME(I),OILRAT(I),WATRAT(I),OILCM(I)*0.001,
1      WCT(I),PVIN(I), (OILCM(I)/OOIP)*100.
7020 FORMAT( 1X,F8.2,2X,G11.4,2X,G11.4,2X,G11.4,2X,F5.3
*      ,3X,F6.2,2X,F5.1 )

C
7010 CONTINUE
C      WRITE(6,7012) STEPIN
7012 FORMAT(' STEPIN =',F7.1)
C
C PTT 6/91 SKIP IF INFILL CASE OVERRIDE IN EFFECT
C
      IF (INFIL.EQ.1) GOTO 7015

C
      WRITE(IW,7040)
7040 FORMAT(1H1
&      ///20X,' PERFORMANCE VERSUS TIME FOR INFILL ',
&      / 20X,' =====',
1  ///,'      TIME      OIL RATE      WATER RATE      CUMOIL      WCUT ',
2  '      PV INJ  OIL REC ',/,',      DAYS      STB/D      STB/D',
3  '      MSTB      FRAC.      FRAC.      %OOIP ')

      I = NSTR
      WRITE(IW,7020) TTIM1(I),OILRT1(I),WATRT1(I),OILCM1(I)*0.001,
1      WCT1(I),PVIN1(I)

C
      DO 7030 I=NSTR+1,NSTEP
      WRITE(IW,7020) TTIM1(I),OILRT1(I),WATRT1(I),OILCM1(I)*0.001,
1      WCT1(I),PVIN1(I), (OILCM1(I)/OOIP)*100.0
7030 CONTINUE
7015 CONTINUE

C PRINTOUT TOTALS - THIS IS AT THE END FOR MY CONVENIENCE (TAIL)

      U1=0.0
      IF (INFIL.EQ.0) U1=(OILCM1(NSTEP)-OILCM(KEEP))*RSCALE/1000.

      WRITE(IW,97040) OILCM(KEEP)*RSCALE/1000.,
+      OILCM1(NSTEP)*RSCALE/1000.,U1,
+      U1/((OOIP/1000)*RSCALE)*100,
+      OOIP/1000*RSCALE
97040 FORMAT(//

```

```

      + ' TOTAL PATTERN RESULTS:' /
      + ' WATERFLOOD RECOVERY          : ',F10.2,' MSTB' /
      + ' WATERFLOOD+INFILL RECOVERY : ',F10.2,' MSTB' /
      + ' INCREMENTAL OIL FROM INFILL: ',F10.2,' MSTB' /
      + ' INCREMENTAL OIL FROM INFILL: ',F10.2,' % OOIP' /
      + ' ORIGINAL OIL IN PLACE        : ',F10.2,' MSTB' //)
C
C Save incremental reserves for output elsewhere
C
      CUMOIL = OILCM(KEEP)*RSCALE/1000.
C WRITE TO SUMMARY FILE

C      OPEN(69,FILE='incre.res',STATUS='UNKNOWN')
C      WRITE(69,' (20A4)') ITITV
C      WRITE(69,97040) OILCM(KEEP)*RSCALE/1000.,
C      + OILCM1(NSTEP)*RSCALE/1000.,U1,
C      + U1/((OOIP/1000)*RSCALE)*100,
C      + OOIP/1000*RSCALE
C
      fminfp = u1
      fmipct = u1/((ooip/1000)*rscale)*100.
C
C per KB: peers have agreed that negative infill potential is a
C numerical error to be discounted
C
      if (fminfp.lt.0.0) then
        fminfp = 0.0
        fmipct = 0.0
      endif
C
      fmoip = ooip/1000*rscale
99069 continue
C
C
C SET VALUES IN NON-INFILL TO CORRECT STATE FOR COMPARISON WITH
C INFILL CASE
C
      DO 7016 I=KEEP+1,ISTMAX
        OILRAT(I)=0.0
        WATRAT(I)=0.0
        OILCM(I)=OILCM(KEEP)
        WCT(I)=0.0
        PVIN(I)=PVIN(KEEP)
        OILRC(I)=OILRC(KEEP)
7016 CONTINUE
C
C      DO ECONOMIC CALCULATIONS
C
C      WRITE ( IMON, 117 )
C 117 FORMAT ( ' END OF SIMULATION PHASES ' )
C
C      IF (IGOV .EQ. 1 .AND. IECONR .NE. 0 ) CALL ECONID
C
C      CALL HALTER ( 'MAIN ', 0 )
C
C      RETURN
C      END
C      SUBROUTINE NEWPLOT(ELEM, IP, ITIM, NUMPLOT, NUMVAR, TIMVAR,
1 BOTLABL, GRAPHTTL, IPLOTVAR, MAINTITL, PLCHAR, X)
      REAL DIFF, HSCALE, LABL, MAINTITL, MAX, SUM, TEMP1, TEMP3, VERTSCL, X

```

```

INTEGER ELEM, HBASE, HSPACE, HCOORD, I, IPLOTVAR, IVAR, J, K, LINES
INTEGER MAXLEN, MDNUM, STEP, TIMVAR, VBASE, VCOORD, FORMFEED
CHARACTER*1 PLCHAR
CHARACTER*8 CONVERT, VALUE
CHARACTER*35 BOTLABL, GRAPHTTL
CHARACTER*132 GRID
LOGICAL SIMPLE, VALVAR
PARAMETER (LINES = 34, FORMFEED = 538976268)
DIMENSION GRID(77), MAINTITL(20)
DIMENSION BOTLABL(NUMVAR), GRAPHTTL(NUMVAR), PLCHAR(NUMVAR)
DIMENSION IPLOTVAR(NUMVAR), MAX(9)
DIMENSION X(TIMVAR, ELEM)
DO 5, I=1, 77
    GRID(I) = ' '
5  CONTINUE
DO 7, I=1, NUMVAR
    MAX(I) = 0.0
7  CONTINUE
IF (NUMPLOT.LT.4) THEN
    HSPACE = 110
ELSE
    HSPACE = 55
END IF
DO 20 I = 1, NUMVAR
    DO 20 J = 1, ITIM
        IF ( X(I,J) .GT. MAX(I) ) MAX(I) = X(I,J)
20  CONTINUE
WRITE(IP, 9500) MAINTITL
9500 FORMAT(20A4)
DO 900, I=1, NUMPLOT
    IF (IPLOTVAR(I).EQ.0) GO TO 900
    IVAR = 0
    DO 43, J=1, NUMVAR
        IF (VALVAR(IPLOTVAR(I), J)) THEN
            IF (IVAR.EQ.0) THEN
                IVAR = J
            ELSE IF (MAX(J).GT.MAX(IVAR)) THEN
                IVAR = J
            END IF
        END IF
43  CONTINUE
IF ( (MOD(I,2) .NE. 1) .AND. (NUMPLOT .NE. 2) ) THEN
    HBASE = 76
ELSE
    HBASE = 10
END IF
IF ( ( (NUMPLOT.EQ.2) .AND. (I.EQ.1)) .OR.
&      ( (NUMPLOT.EQ.4) .AND. (I.LT.3)) ) THEN
    VBASE = 3
ELSE
    VBASE = 41
END IF
DO 35 J = HBASE, HBASE+HSPACE
    GRID(VBASE) (J:J) = '-'
    GRID(VBASE + LINES) (J:J) = '-'
35  CONTINUE
DO 41 J = 0, LINES
    IF ( MOD(J,2) .EQ. 0 ) THEN
        GRID(VBASE + J) (HBASE:HBASE) = '+'
        GRID(VBASE + J) (HBASE+HSPACE:HBASE+HSPACE) = '+'
    
```

```

ELSE
    GRID(VBASE + J) (HBASE:HBASE) = ' | '
    GRID(VBASE + J) (HBASE+HSPACE:HBASE+HSPACE) = ' | '
END IF
41 CONTINUE
IF (MAX(IVAR).EQ.0.0) VERTSCL = 0.2
IF (MAX(IVAR).EQ.0.0) GO TO 45
TEMP1 = INT(LOG10( LINES/MAX(IVAR))) - 0.5 )
IF ( (LOG10(LINES/MAX(IVAR))) .LT. 0.0) TEMP1=TEMP1-1
IF (MAX(IVAR)*(10**TEMP1) .LE. LINES ) VERTSCL= (10**TEMP1)
IF (MAX(IVAR)*2*(10**TEMP1) .LE. LINES ) VERTSCL= 2*(10**TEMP1)
IF (MAX(IVAR)*5*(10**TEMP1) .LE. LINES ) VERTSCL= 5*(10**TEMP1)
IF (MAX(IVAR)*10*(10**TEMP1) .LE. LINES ) VERTSCL= 10*(10**TEMP1)
IF (MAX(IVAR)*20*(10**TEMP1) .LE. LINES ) VERTSCL= 20*(10**TEMP1)
IF (MAX(IVAR)*50*(10**TEMP1) .LE. LINES ) VERTSCL= 50*(10**TEMP1)
IF (MAX(IVAR)*100*(10**TEMP1) .LE. LINES )
1 VERTSCL= 100*(10**TEMP1)
45 CONTINUE
IF ((1.0/VERTSCL) .GE. 1.0) THEN
    SIMPLE = .TRUE.
    IFORCE = 0
    ITEMP = INT((1.0 / VERTSCL) + 0.5)
ELSE
    SIMPLE = .FALSE.
    TEMP1 = 2.0/VERTSCL
    IFORCE = 1
    IF (TEMP1.LT.0.1) IFORCE = 2
    IF (TEMP1.LT.0.01) IFORCE = 3
    IF (TEMP1.LT.0.001) IFORCE = 4
    IF (TEMP1.LT.0.0001) IFORCE = 5
    IF (TEMP1.LT.0.00001) IFORCE = 6
END IF
DO 50 J=0, LINES, 2
    IF (SIMPLE) THEN
        LABL = REAL(J * ITEMP)
    ELSE
        LABL=REAL(NINT((J/VERTSCL)*10**IFORCE))/(10.0**IFORCE)
    END IF
    VALUE = CONVERT(DBLE(LABL), IFORCE)
51 IF (LENGTH8(VALUE) .EQ. 8) GO TO 53
    DO 52 K = LENGTH8(VALUE)+1, 2, -1
        VALUE(K:K) = VALUE(K-1:K-1)
52 CONTINUE
    VALUE(1:1) = ' '
    GO TO 51
53 CONTINUE
    DO 54, K= 1, 8
        GRID(LINES-J+VBASE) (HBASE-9+K:HBASE-9+K)=VALUE(K:K)
54 CONTINUE
50 CONTINUE
TEMP3 = INT(LOG10(HSPACE/X(TIMVAR, ITIM)))
IF ((X(TIMVAR, ITIM)*10**TEMP3) .LE. HSPACE) HSCALE=10**TEMP3
IF ((X(TIMVAR, ITIM)*2*10**TEMP3) .LE. HSPACE) HSCALE=2*10**TEMP3
IF ((X(TIMVAR, ITIM)*4*10**TEMP3) .LE. HSPACE) HSCALE=4*10**TEMP3
IF ((X(TIMVAR, ITIM)*5*10**TEMP3) .LE. HSPACE) HSCALE=5*10**TEMP3
IF ((X(TIMVAR, ITIM)*10*10**TEMP3) .LE. HSPACE) HSCALE=10*10**TEMP3
DIFF = 1.0E-6
DO 60, J=1, ITIM-1
    IF ((X(TIMVAR, J+1) - X(TIMVAR, J)) .GT. DIFF) THEN
        DIFF = X(TIMVAR, J+1) - X(TIMVAR, J)

```

```

        END IF
60    CONTINUE
    SUM = 0.0
    STEP = 0
70    SUM = SUM + DIFF
    STEP = STEP + 1
    IF (STEP .LT. 1) GO TO 70
    STEP = REAL(NINT(STEP*HSCALE))
    MAXLEN = LENGTH8(CONVERT(DBLE(INT(HSPACE*HSCALE)),0))
    MDNUM = 1
80    IF ( (MDNUM*STEP - 1) .GT. MAXLEN) GOTO 85
    MDNUM = MDNUM + 1
    GO TO 80
85    CONTINUE
    DO 90, J=0,INT(HSPACE/HSCALE)
        IF(MOD(J,MDNUM).EQ.0) THEN
            VALUE = CONVERT(DBLE(J),0)
            HCOORD = INT(J*HSCALE)
            IF ( LENGTH8(VALUE) .EQ. 1 ) THEN
                GRID(VBASE+LINES+1)
                & (HBASE+HCOORD:HBASE+HCOORD)=VALUE(1:1)
            ELSE
                GRID(VBASE+LINES+1)
                & (HBASE+HCOORD-1:HBASE+HCOORD-1)=VALUE(1:1)
                GRID(VBASE+LINES+1)
                & (HBASE+HCOORD:HBASE+HCOORD)= VALUE(2:2)
            END IF
            GRID(VBASE) (HBASE+HCOORD:HBASE+HCOORD)= '+'
            GRID(VBASE+LINES) (HBASE+HCOORD:HBASE+HCOORD)= '+'
        END IF
90    CONTINUE
    J = (HSPACE - LENGTH35(BOTLABL(I))) / 2
    DO 95, K=1,LENGTH35(BOTLABL(I))
        GRID(VBASE+LINES+2) (HBASE+J+K-1:HBASE+J+K-1)
        + = BOTLABL(I) (K:K)
95    CONTINUE
    J = (35 - LENGTH35(GRAPHTTL(I))) / 2
    DO 100, K=1,LENGTH35(GRAPHTTL(I))
        GRID(J+VBASE-1+K) (HBASE-9:HBASE-9) = GRAPHTTL(I) (K:K)
100    CONTINUE
    DO 110, J=1,ITIM
        DO 109, K=1,NUMVAR
            IF (VALVAR(IPLOTVAR(I),K)) THEN
                IF (X(K,J) .GE. 0.0) THEN
                    VCOORD = LINES - NINT(VERTSCL*X(K,J)) + VBASE
                    HCOORD = NINT(X(TIMVAR,J) * HSCALE) + HBASE
                    GRID(VCOORD) (HCOORD:HCOORD) = PLCHAR(K)
                END IF
            END IF
109    CONTINUE
110    CONTINUE
900    CONTINUE
    DO 1000, I=1,77
        WRITE(IP,9000) (GRID(I) (J:J),J=1,132)
1000    CONTINUE
9000    FORMAT(132A1)
    WRITE(IP,9010) FORMFEED
9010    FORMAT(A4)
    RETURN
END

```



```

SUBROUTINE OUTE
C
C -----
C
C OUTE: WRITE ECONOMIC ANALYSIS REPORTS
C
C -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'FILES.INC'
C      INCLUDE 'ECON.INC'
C      COMMON /LIF/ LPAT
C      DIMENSION DNAME1(4),DNAME2(4),DNAME3(4),DNAME4(4),DNAME5(4),
C + DNAME6(4),DNAME7(4),DNAME8(4),DNAME9(4),DNAMEA (4),DNAMEB (4),
C + DNAMEC (4),DNAMED(4),DNAMEE (4)
C      DIMENSION IDS1(50),IDS2(50)
C      DATA IDSH / 3H--- /
C
C -----
C      ***** WRITE ECONOMIC ANALYSIS REPORTS
C -----
C
C      UNIT = 1000.
C      UMM = UNIT*UNIT
C
C      ***** PRINT ANNUAL TABLE - UNDISCOUNTED VALUES
C      IF(IOUT.LE.0) GO TO 600
C      INIT = 1
C      IFIN = 10
C      IF(M.LT.IFIN) IFIN = M
C      DO 50 I=1,M
C      IDS1(I) = IDSH
C      IDS2(I) = IDSH
C      MUPO(I) = MUPO(I)*UMM
C      MUPG(I) = MUPG(I)*UMM
C      AFUEL(I) = AFUEL(I)/UNIT
C      VPM(I) = VPM(I)/UNIT
C      MUVI(I) = MUVI(I)/UNIT
C      MUVW(I) = MUVW(I)/UNIT
C      MUVG(I) = MUVG(I)/UNIT
C      MUVO(I) = MUVO(I)/UNIT
50  CONTINUE
C      CALL UOUT (MUVO,M,2,1,DNAME1,9,METRIC )
C      CALL UOUT (MUVG,M,3,0,DNAME2,15,METRIC )
C      CALL UOUT (MUVW,M,2,1,DNAME3,9,METRIC )
C      CALL UOUT (VPM ,M,10,0,DNAME4,27,METRIC )
C      CALL UOUT (AQOR,M,2,1,DNAME5,14,METRIC )
C      CALL UOUT (AQGR,M,3,0,DNAME6,12,METRIC )
C      CALL UOUT (AQWR,M,2,1,DNAME7,14,METRIC )
C      CALL UOUT (VONET,M,2,1,DNAME8,9,METRIC )
C      CALL UOUT (VGNET,M,3,0,DNAME9,15,METRIC )
C      CALL UOUT (MUPO,M,2,0,DNAMEA ,22,METRIC )
C      CALL UOUT (MUPG,M,3,1,DNAMEB ,24,METRIC )
C      CALL UOUT (BPO ,M,2,0,DNAMEC ,22,METRIC )
C      CALL UOUT (AWPP,M,2,0,DNAMEE ,22,METRIC )
C
C      CCCCC      LOUT IS PATTERN LIFE PLUS PATTERN INITIATION
C
C      DO 191 J=1,M
C      IF(PATI(J).LE.0.0) GO TO 192
191  LPADD=J

```

```

192  LOUT=LPADD+LPAT
C
C ***** TOP OF LOOP FOR ANNUAL VALUES
100  CONTINUE
      WRITE(IW,9001)
9001  FORMAT(1H1)
      WRITE(IW,9002)
9002  FORMAT(55X,34H          PROJECT ECONOMIC ANALYSIS
1 / 55X,44(1H- )
      WRITE(IW,9005) (I,I=INIT,IFIN)
9005  FORMAT(1H0,24HUNDISCOUNTED MEAN VALUES / 1X,24(1H-),15X,10I8)
      WRITE(IW,9006) (DATE(I), I=INIT,IFIN)
      WRITE(IW,9100) (IDS1(I),IDS2(I), I=INIT,IFIN)
      WRITE(IW,9010) (DNAME1(I),I=1,2), (MUVO(I), I=INIT,IFIN)
      WRITE(IW,9011) (DNAME2(I),I=1,2), (MUVG(I), I=INIT,IFIN)
      WRITE(IW,9012) (DNAME3(I),I=1,2), (MUVW(I), I=INIT,IFIN)
      WRITE(IW,9015) (DNAME5(I),I=1,2), (AQOR(I), I=INIT,IFIN)
      WRITE(IW,9016) (DNAME6(I),I=1,2), (AQGR(I), I=INIT,IFIN)
      WRITE(IW,9017) (DNAME7(I),I=1,2), (AQWR(I), I=INIT,IFIN)
      WRITE(IW,9100) (IDS1(I),IDS2(I), I=INIT,IFIN)
      WRITE(IW,9121) (DNAME8(I),I=1,2), (VONET(I), I=INIT,IFIN)
      WRITE(IW,9122) (DNAME9(I),I=1,2), (VGNET(I), I=INIT,IFIN)
      WRITE(IW,9022) (DNAMEA(I),I=1,2), (MUPO(I), I=INIT,IFIN)
      WRITE(IW,9023) (DNAMEB(I),I=1,2), (MUPG(I), I=INIT,IFIN)
      WRITE(IW,9025) (AREVO(I), I=INIT,IFIN)
      WRITE(IW,9026) (AREVG(I), I=INIT,IFIN)
      WRITE(IW,9027) (AREV(I), I=INIT,IFIN)
      WRITE(IW,9030) (AROY(I), I=INIT,IFIN)
      WRITE(IW,9033) (ANET(I), I=INIT,IFIN)
      WRITE(IW,9100) (IDS1(I),IDS2(I), I=INIT,IFIN)
      WRITE(IW,9035) (ASEV(I), I=INIT,IFIN)
      WRITE(IW,9036) (AFOC(I), I=INIT,IFIN)
      WRITE(IW,9037) (AVOC(I), I=INIT,IFIN)
      WRITE(IW,9039) (MUWO(I), I=INIT,IFIN)
      WRITE(IW,9040) (AWTC(I), I=INIT,IFIN)
      WRITE(IW,9042) (AOVH(I), I=INIT,IFIN)
      WRITE(IW,9043) (ACOST(I), I=INIT,IFIN)
      WRITE(IW,9044) (ANOI(I), I=INIT,IFIN)
      WRITE(IW,9045) (CNOI(I), I=INIT,IFIN)
      WRITE(IW,9046) (AWCP(I), I=INIT,IFIN)
      WRITE(IW,9047) (MUCT(I), I=INIT,IFIN)
      WRITE(IW,9048) (MUCI(I), I=INIT,IFIN)
      IF (IDEBT.NE.0) WRITE(IW,90481) (MUIN(I), I=INIT,IFIN)
      IF (IDEBT.NE.0) WRITE(IW,90482) (MUDB(I), I=INIT,IFIN)
      IF (IDEBT.NE.0) WRITE(IW,90483) (MURP(I), I=INIT,IFIN)
      IF (IDEBT.NE.0) WRITE(IW,90484) (MUPB(I), I=INIT,IFIN)
      WRITE(IW,9050) (CFBT(I), I=INIT,IFIN)
      WRITE(IW,9100) (IDS1(I),IDS2(I), I=INIT,IFIN)
      WRITE(IW,9052) (DNAMEC(I),I=1,2), (BPO(I), I=INIT,IFIN)
      WRITE(IW,9053) (DNAMED(I),I=1,2), (AWPP(I), I=INIT,IFIN)
      WRITE(IW,9055) (AWPT(I), I=INIT,IFIN)
      WRITE(IW,9056) (ASTX(I), I=INIT,IFIN)
      WRITE(IW,9057) (ACAP(I), I=INIT,IFIN)
      WRITE(IW,9059) (TXCR(I), I=INIT,IFIN)
      WRITE(IW,9060) (ANTI(I), I=INIT,IFIN)
      WRITE(IW,9065) (AFIT(I), I=INIT,IFIN)
      WRITE(IW,9070) (ATPR(I), I=INIT,IFIN)
      WRITE(IW,9075) (CFAT(I), I=INIT,IFIN)
C
9006  FORMAT(2X,40HYEAR ENDING ....., 10F8.0)

```

```

9010 FORMAT(2X,'ANNUAL OIL PRODUCTION, ',2A4,'.....', 10F8.2)
9011 FORMAT(2X,'ANNUAL GAS PRODUCTION, ',2A4,'.....', 10F8.2)
9012 FORMAT(2X,'ANNUAL WATER PRODUCTION, ',2A4,'.....', 10F8.0)
9015 FORMAT(2X,'OIL PRODUCTION RATE, ',2A4,'.....', 10F8.0)
9016 FORMAT(2X,'GAS PRODUCTION RATE, ',2A4,'.....', 10F8.0)
9017 FORMAT(2X,'WATER PRODUCTION RATE, ',2A4,'.....', 10F8.0)
C-----
9121 FORMAT(2X,'NET OIL SOLD (LESS ROYALTY), ',2A4,'....', 10F8.2)
9122 FORMAT(2X,'NET GAS SOLD (LESS ROYALTY), ',2A4,'....', 10F8.2)
9022 FORMAT(2X,'MEAN PRICE OF OIL, ',2A4,'.....', 10F8.2)
9023 FORMAT(2X,'MEAN PRICE OF GAS, ',2A4,'.....', 10F8.2)
9025 FORMAT(2X,40HANNUAL GROSS OIL SALES, MM$ ....., 10F8.2)
9026 FORMAT(2X,40HANNUAL GROSS GAS SALES, MM$ ....., 10F8.2)
C 90265 FORMAT(2X,40HRELEASED OIL REVENUES, MM$ ....., 10F8.2)
9027 FORMAT(2X,40HANNUAL TOTAL GROSS SALES, MM$ ....., 10F8.2)
9030 FORMAT(2X,40HANNUAL ROYALTY, MM$ ....., 10F8.2)
9033 FORMAT(2X,40HANNUAL NET SALES, MM$ ....., 10F8.2)
C-----
9035 FORMAT(2X,40HANNUAL SEVERANCE TAX, MM$ ....., 10F8.2)
9036 FORMAT(2X,40HANNUAL FIXED OPERATING COST, MM$ ....., 10F8.2)
9037 FORMAT(2X,40HANNUAL VARIABLE OPERATING COST, MM$ ....., 10F8.2)
9039 FORMAT(2X,40HANNUAL WELL WORKOVER COST, MM$ ....., 10F8.2)
9040 FORMAT(2X,40HANNUAL PROD WATER TREATING COST, MM$ ...., 10F8.2)
9042 FORMAT(2X,40HANNUAL OVERHEAD, MM$ ....., 10F8.2)
9043 FORMAT(2X,40HANNUAL TOTAL OPERATING COST, MM$ ....., 10F8.2)
9044 FORMAT(2X,40HANNUAL NET OPERATING INCOME, MM$ ....., 10F8.2)
9045 FORMAT(2X,40HCUM NET OPERATING INCOME, MM$ ....., 10F8.2)
9046 FORMAT(2X,40HANNUAL WORKING CAPITAL, MM$ ....., 10F8.2)
9047 FORMAT(2X,40HANNUAL TANGIBLE CAPITAL, MM$ ....., 10F8.2)
9048 FORMAT(2X,40HANNUAL INTANGIBLE CAPITAL, MM$ ....., 10F8.2)
90481 FORMAT(2X,40HANNUAL DEBT INTEREST COST, MM$ ....., 10F8.2)
90482 FORMAT(2X,40HANNUAL NEW BORROWING, MM$ ....., 10F8.2)
90483 FORMAT(2X,40HANNUAL PRINCIPAL REPAYMENT, MM$ ....., 10F8.2)
90484 FORMAT(2X,40HANNUAL UNAMORTIZED LOAN, MM$ ....., 10F8.2)
9050 FORMAT(2X,40HCUM CASH FLOW BEFORE TAXES, MM$ ....., 10F8.2)
C-----
9052 FORMAT(2X,'BASE PRICE OF OIL FOR WPT, ',2A4,'....', 10F8.2)
9053 FORMAT(2X,'ANNUAL WINDFALL PRICE DIFF, ',2A4,'.....', 10F8.2)
9054 FORMAT(2X,40HANNUAL NET INCOME LIMIT PRICE, $/BBL ...., 10F8.2)
9055 FORMAT(2X,40HANNUAL WINDFALL EXCISE TAX, MM$ ....., 10F8.2)
9056 FORMAT(2X,40HANNUAL STATE INCOME TAX, MM$ ....., 10F8.2)
9057 FORMAT(2X,40HANNUAL INTANGIBLES AND DEPR, MM$ ....., 10F8.2)
9059 FORMAT(2X,40HANNUAL INVESTMENT TAX CREDIT, MM$ ....., 10F8.2)
9060 FORMAT(2X,40HANNUAL NET TAXABLE INCOME, MM$ ....., 10F8.2)
9065 FORMAT(2X,40HANNUAL FEDERAL INCOME TAX, MM$ ....., 10F8.2)
9070 FORMAT(2X,40HANNUAL AFTER TAX CASH FLOW, MM$ ....., 10F8.2)
9075 FORMAT(2X,40HCUM CASH FLOW AFTER TAXES, MM$ ....., 10F8.2)
9100 FORMAT(42X, 10(2X,2A3))
C
      IF (IFIN.GE.M.OR.IFIN.GE.LOUT) GO TO 200
      INIT = IFIN+1
      IFIN=MIN0 (INIT+9,M)
      GO TO 100
200 IF (IOUT.LT.0) GO TO 600
C
C
C-----
C ***** PRINT UNDISCOUNTED VALUES - SUMMED OVER ECONOMIC LIFE
C-----
      WRITE (IW, 9001)

```

```

        WRITE(IW, 9204) PLIFE,URPV,UNOS,
        1 USEV,USFO,USOPC,USWO,USWT
9204 FORMAT(/ 4X,25HUNDISCOUNTED MEAN RESULTS / 4X,25(1H-) /
        1 5X,40HPROJECT ECONOMIC LIFE .....F10.1,8H YEARS /
        1 5X,40HTOTAL GROSS SALES .....F10.3,8H MM$ /
        2 5X,40HTOTAL NET SALES .....F10.3,8H MM$ /
        3 5X,40HTOTAL SEVERANCE TAX .....F10.3,8H MM$ /
        4 5X,40HTOTAL FIXED OPERATING COST .....F10.3,8H MM$ /
        5 5X,40HTOTAL VARIABLE OPERATING COST .....F10.3,8H MM$ /
        8 5X,40HTOTAL WELL WORKOVER COST .....F10.3,8H MM$ /
        9 5X,40HTOTAL PROD WATER TREATING COST .....F10.3,8H MM$ )

C
        TOPC = USFO+USOPC+USIN+USTR+USWO+USWT+USOH+USEV
        TINV = UWCAP + USTC + USCI
        TEXP = TOPC + TINV + UINT

C
        WRITE(IW, 9205) USOH,
        1 TOPC,UWCAP,USTC,USCI,TINV,UINT,TEXP,UCFB,
        2 UWPT,USIT,UFIT,UATP,ULOAN
9205 FORMAT(
        1 5X,40HTOTAL OVERHEAD .....F10.3,8H MM$ /
        1 5X,40HTOTAL OPERATING COST .....F10.3,8H MM$ /
        2 5X,40HTOTAL WORKING CAPITAL .....F10.3,8H MM$ /
        5 5X,40HTOTAL TANGIBLE CAPITAL .....F10.3,8H MM$ /
        6 5X,40HTOTAL INTANGIBLE CAPITAL .....F10.3,8H MM$ /
        7 5X,40HTOTAL CAPITAL INVESTMENT .....F10.3,8H MM$ /
        7 5X,40HTOTAL DEBT INTEREST EXPENSE .....F10.3,8H MM$ /
        8 5X,40HTOTAL PROJECT EXPENSE .....F10.3,8H MM$ /
        8 5X,40HTOTAL CASH FLOW BEFORE TAX .....F10.3,8H MM$ /
        7 5X,40HTOTAL WINDFALL PROFITS TAX .....F10.3,8H MM$ /
        8 5X,40HTOTAL STATE INCOME TAX .....F10.3,8H MM$ /
        8 5X,40HTOTAL FEDERAL INCOME TAX .....F10.3,8H MM$ /
        9 5X,40HTOTAL AFTER TAX CASH FLOW .....F10.3,8H MM$ /
        1 5X,40HTOTAL LOAN AMOUNT .....F10.3,8H MM$ )

C
C
C-----
C ***** PRINT ANNUAL TABLE - DISCOUNTED VALUES
C-----
C
        WRITE(IW, 9911)
9911 FORMAT(1H0/15X,25HPROJECT ECONOMIC ANALYSIS
        1 / 15X,48(1H-) )

C
        WRITE(IW, 9500)
9500 FORMAT(1H0,15X,6HPRESNT,21X,20HMEAN VALUE CASH FLOW /
        1 11X, 6X,5HVALUE, 10X,16HBEFORE TAX (MM$), 8X,
        1 5X,16HAFTER TAX (MM$) /
        2 7X,4HYEAR,5X,6HFACTOR,4X,6HANNUAL,3X,7HCONST $,3X,7HDISCNTD,
        2 4X,6HANNUAL,3X,7HCONST $,3X,7HDISCNTD /
        3 7X,4H----,5X,6H-----,4X,6H-----,3X,7H-----,3X,7H-----,
        3 4X,6H-----,3X,7H-----,3X,7H----- )

C ***** PRINT ONLY VALUES THRU ECONOMIC LIFE
        DO 500 I=1,MYR
        500 WRITE(IW, 9550) I, DATE(I),PVDF(I),CFBT(I),CDBT(I),
        1 DCFBT(I), CFAT(I),CDAT(I),DCFAT(I)
9550 FORMAT(2X,I2, F8.0, F10.4, 7F10.2 )

C
C
C-----
C ***** SUMMARY OF RESULTS

```

```

C-----
C
600 CALL TITLE(TITL)
C
COCT = 0.0
IF(SVPS.GT.0.) COCT = SVOS/SVPS
C
***** TOTAL DISCOUNTED OPERATING COST, INVESTMENT, AND EXPENSE
TOPC = SUMFO+SUMOPC+SUMIN+SUMTR+SUMWO+SUMWT+SUMOH+SSEV
TINV = SUMWC + TOTD + SUMCI
TEXP = TOPC + TINV + SINT
C
DCPDB = 0.0
IF(DNB.GT.0.) DCPDB = TEXP/DNB*UNIT
CALL UOUT (SVOS ,1,2,1,DNAME1,9,METRIC )
CALL UOUT (SVGS ,1,3,0,DNAME2,15,METRIC )
CALL UOUT (SVPS ,1,10,0,DNAME3,27,METRIC )
CALL UOUT (COCT ,1,0,1,DNAME4,32,METRIC )
CALL UOUT (SVON ,1,2,1,DNAME5,9,METRIC )
CALL UOUT (DNB ,1,2,1,DNAME6,9,METRIC )
WRITE(IW,9600) PLIFE,SVOS,DNAME1,SVGS,DNAME2,
+ SVON,DNAME5,DNB,DNAME6
9600 FORMAT(1H0, 3X,18HPRODUCTION SUMMARY / 4X,18(1H-) /
1 5X,40HPROJECT ECONOMIC LIFE .....F10.1,8H YEARS /
1 5X,40HCUMULATIVE GROSS OIL SOLD .....F10.0,2X,4A4 /
1 5X,40HCUMULATIVE GROSS GAS SOLD .....F10.0,2X,4A4 /
1 5X,40HCUMULATIVE NET OIL SOLD .....F10.0,2X,4A4 /
2 5X,40HPRESENT VALUE OF NET OIL SOLD .....F10.0,2X,4A4 )
WRITE(IW,9604) SRPV,SNOS,
1 SSEV,SUMFO,SUMOPC,SUMWO,SUMWT
9604 FORMAT(1H0, 3X,12HMEAN RESULTS / 4X,12(1H-) /
1 5X,40HPRESENT VALUE OF TOTAL GROSS SALES .....F10.3,8H MM$ /
2 5X,40HPRESENT VALUE OF TOTAL NET SALES .....F10.3,8H MM$ /
3 5X,40HTOTAL SEVERANCE TAX (PV) .....F10.3,8H MM$ /
4 5X,40HTOTAL FIXED OPERATING COST (PV) .....F10.3,8H MM$ /
5 5X,40HTOTAL VARIABLE OPERATING COST (PV) .....F10.3,8H MM$ /
8 5X,40HTOTAL WELL WORKOVER COST (PV) .....F10.3,8H MM$ /
9 5X,40HTOTAL PROD WATER TREATING COST (PV) .....F10.3,8H MM$ )
CALL UOUT (DCPDB,1,2,0,DNAME1,22,METRIC )
WRITE(IW,9605) SUMOH,TOPC,
1 SUMWC,TOTD,SUMCI,TINV,SINT,TEXP,SPRP,DCPDB,DNAME1,DCFB
9605 FORMAT(
1 5X,40HTOTAL OVERHEAD (PV) .....F10.3,8H MM$ /
1 5X,40HTOTAL OPERATING COST (PV) .....F10.3,8H MM$ /
2 5X,40HTOTAL WORKING CAPITAL (PV) .....F10.3,8H MM$ /
5 5X,40HTOTAL TANGIBLE CAPITAL INVESTED (PV) ....F10.3,8H MM$ /
6 5X,40HTOTAL INTANGIBLE CAPITAL (PV) .....F10.3,8H MM$ /
7 5X,40HTOTAL CAPITAL INVESTMENT (PV) .....F10.3,8H MM$ /
7 5X,40HTOTAL INTEREST EXPENSE (PV) .....F10.3,8H MM$ /
8 5X,40HTOTAL PROJECT EXPENSE (PV) .....F10.3,8H MM$ /
8 5X,40HTOTAL LOAN PRINCIPAL REPAYMENT (PV) ....F10.3,8H MM$ /
8 5X,40HDISCOUNTED COST PER DISC NET OIL .....F10.3,2X,4A4 /
9 5X,40HDISCOUNTED CASH FLOW BEFORE TAX .....F10.3,8H MM$ )
C
PXDR = XDR*100.
DCFL = MUPPV - 1.22*STDDEV
DCFH = MUPPV + 1.43*STDDEV
DCFGS = 0.0
RPE = 0.0
RPI = 0.0

```

```

      IF(TINV.LE.0.) GO TO 630
      RPI = MUPPV/TINV
630  IF(TEXP.LE.0.) GO TO 640
      RPE = MUPPV/TEXP
640  IF(DNB.LE.0.) GO TO 650
      DCFGS = MUPPV/DNB*UNIT
650  CONTINUE
      CALL UOUT (DCFGS,1,2,0,DNAME1,22,METRIC )
      WRITE(IW,9650) PXDR,DCFL,MUPPV,DCFH,STDDEV,
1  RPI,RPE,DCFGS,DNAME1,EFFINV,ROR
9650  FORMAT(1H0, 3X,33HPROJECT PROFITABILITY (AFTER TAX) / 4X,21(1H-) /
1  5X,40HAVERAGE MONETARY DISCOUNT RATE .....F10.2,8H PCNT /
1  5X,40H90 PCNT CONFIDENCE DCF .....F10.3,8H MM$ /
2  5X,40HMEAN DISCOUNTED CASH FLOW .....F10.3,8H MM$ /
3  5X,40H10 PCNT CONFIDENCE DCF .....F10.3,8H MM$ /
4  5X,40HSTANDARD DEVIATION OF THE MEAN DCF .....F10.3,8H MM$ /
C   5 5X,40HPAYOUT BASED ON AFTER TAX MEAN DCF .....F10.2,8H YEARS /
5 5X,40HMEAN DCF PROFIT TO INVESTMENT RATIO .....F10.3,8H P/I /
5 5X,40HMEAN DCF PROFIT TO EXPENSE RATIO .....F10.3,8H P/E /
5 5X,40HMEAN DCF PROFIT PER DISC NET OIL .....F10.3,2X,4A4 /
5 5X,40HMEAN INVESTMENT EFFICIENCY .....F10.3,8H /
6 5X,40HMEAN DCF RATE OF RETURN .....F10.2,8H PCNT )
C
      RETURN
      END
      FUNCTION SDINT (XARG,YARG,N,XVAL)
C   ***** SINGLE DIMENSIONAL LINEAR INTERPOLATION
      INCLUDE 'PARAM.INC'
      DIMENSION XARG(ISTMAX), YARG(ISTMAX)
C
      THESIN=1.0
      IF(XARG(1).GE.XARG(N)) THESIN=-1.0
C
C   ***** SEARCH FOR BOUNDING TABLE VALUES
      DO 10 I=1,N
      J=I
      IF( (THESIN*XARG(I)) - (THESIN*XVAL) ) 10,15,16
10  CONTINUE
C
15  SDINT = YARG(J)
      RETURN
C
16  IF(J.LE.1) GO TO 15
      SLOPE = (YARG(J)-YARG(J-1))/(XARG(J)-XARG(J-1))
      SDINT = YARG(J) - SLOPE*(XARG(J)-XVAL)
      RETURN
      END
      SUBROUTINE TITLE(TITL)
C
C   -----
C
C   TITLE: WRITE PROGRAM HEADER TO OUTPUT UNIT (IW)
C
C   -----
C
C   ***** PRINT TITLE
      INCLUDE 'FILES.INC'
      DIMENSION TITL(20)
C
      WRITE(IW,9000)

```

```

9000 FORMAT(1H1,
1 1X, 42H***** /
1 2X, 42H* * /
1 2X, 42H* S C I E N T I F I C S O F T W A R E * /
1 2X, 42H* - I N T E R C O M P * /
1 2X, 42H* * /
1 2X, 42H* * /
1 2X, 42H* INFILL DRILLING PREDICTION MODEL * /
1 2X, 42H* (IDPM - RELEASE 1.2.0) * /
1 2X, 42H* * /
1 2X, 42H***** / )
C
WRITE(IW,9004) TITL
9004 FORMAT(1X,20A4)
RETURN
END
SUBROUTINE NEWDCF
C
C -----
C
C NEWDCF: COMPUTE DCF RATE OF RETURN
C
C -----
C
INCLUDE 'PARAM.INC'
INCLUDE 'FILES.INC'
INCLUDE 'ECON.INC'
INTEGER ANYCHK, TECH1, TECH2
REAL KORW, KORO
REAL MAXNCF
INTEGER YR, COUNT
LOGICAL MARK, RECAL
REAL SUMPCF, SUMNCF, T1, T2, T3, DR1, DR2, XBAR,
X PV1, PV2, PVX, DELTA, CCF
C
C NEWDCF : THIS NEW VERSION OF SUBROUTINE 'DCFROR' PERFORMS
C TWO FUNCTIONS:
C 1 . IT COMPUTES INVESTMENT EFFICIENCY
C 2 . IT COMPUTES INTERNAL RATE OF RETURN ACCORDING TO
C THE METHOD OF BISECTION
C THIS SUBROUTINE CALLS A REAL VALUED FUNCTION 'APRVAL' WHICH COMPUTES
C THE PRESENT VALUE OF A PROJECT GIVEN THE UNDISCOUNTED CASH FLOW
C STREAM, PROJECT LIFE, AND DISCOUNT RATE.
C
C DELTA : TOLERANCE FACTOR FOR ROR CALCULATION
C
C DELTA=0.001
C
C THIS PROGRAM ASSUMES THAT THE NOMINAL RATE OF RETURN FOR THE RUN MAY
C BE FOUND IN VARIABLE 'XDR'
C
C COMPUTES INVESTMENT EFFICIENCY AT USERS SET DISCOUNT RATE
C
C XDR : DISCOUNT RATE FOR RUN
C CFAT(YR) : UNDISCOUNTED AFTER TAX CASH FLOW IN YEAR 'YR'
C MYR : LIFE OF PROJECT
C SUMPCF : SUM OF DISCOUNTED POSITIVE CASH FLOWS
C SUMNCF : ABSOLUTE VALUE OF SUM OF NEGATIVE CASH FLOWS
C DMUL : DISCOUNTING FACTOR
C

```

```

      CCF=0.
      SUMPCF=0.
      MARK=.FALSE.
      XINVES = MUCT(1) + MUCI(1) + COSTRT
C
      SUMNCF = XINVES
C
      MAXNCF = XINVES
C
      ATPR(1) = ATPR(1) + XINVES
      DO 201 I=2,MYR
      XX = MUCT(I) + MUCI(I)
      ATPR(I-1)=ATPR(I-1) - XX
201  ATPR(I) = ATPR(I) + XX
C
      DO 3000 YR=1,MYR
C  DON'T DISCOUNT YEAR ONE
C  1-10-84 WE DO DISCOUNT IN YR 1 SINCE INVESTMENTS ARE REMOVED
C    IF(YR.EQ.1)DMUL=1.0
C
C  DISCOUNT ALL OTHER YEARS ON THE HALF YEAR
      T1=FLOAT(YR)-0.5
C    IF(YR.GT.1)DMUL=(1.0+XDR)**T1
      DMUL = (1.0 + XDR)**T1
C
C  T2 : DISCOUNTED CASH FLOW IN YEAR
C
      T2=ATPR(YR)/DMUL
C  CCF : CUMULATIVE CASH FLOW
      CCF=CCF+T2
      IF(CCF.GE.0.)MARK=.TRUE.
C  CEASE ACCUMULATING NEGATIVES ONCE CUMULATIVE CASH FLOW GOES POSITIVE
      IF(T2.GE.0.)SUMPCF=SUMPCF+T2
      IF(MARK)GO TO 3000
      IF(T2.LT.0.)SUMNCF=SUMNCF+T2*(-1.)
C
C  CALCULATE MAXIMUM NEGATIVE CASH FLOW - MAXNCF
C
      IF(SUMNCF .GT. MAXNCF)MAXNCF = SUMNCF
C
3000  CONTINUE
C
C  COMPUTE INVESTMENT EFFICIENCY AS THE RATIO OF POSITIVE TO
C  NEGATIVE CASH FLOW SUMS
C
C  CASE WHERE THERE ARE NO NEGATIVE CASH FLOWS
      IF(SUMNCF.LE.0.0 .AND. CCF .GT. 0.0)EFFINV=1.0E03
C  ALL OTHER CASES
C
      IF(MAXNCF.GT.0.)EFFINV=CCF/MAXNCF
C
C  THIS COMPLETES COMPUTATION OF INVESTMENT EFFICIENCY
C
C  COMPUTATION OF INTERNAL RATE OF RETURN BY USING THE METHOD OF
C  BISECTION.
C  NOTE : BECAUSE CASH FLOW CHANGES SIGN , A 'CRUDE' ALGORITHM (
C  (LIKE BISECTION) IS NECESSARY. A MATHEMATICAL ALGORITHM (LIKE
C  NEWTON-RAPHSON) WILL FAIL TO CONVERGE.
C    *      *      *      *      *
C

```



```

C CHECK TO SEE IF PROJECT HAS A POSITIVE PRESENT VALUE AT
C 0 % ROR
C
C     DR1=0.
C     PV1=APRVAL(ATPR,MYR,DR1,XINVES)
C IF PRESENT VALUE IS NEGATIVE, FORGET IT.
C     IF (PV1.LT.0.)XBAR=-1.
C     IF (PV1.LT.0.)GO TO 4100
C CHECK TO SEE IF PROJECT HAS A POSITIVE NET PRESENT VALUE
C AT 100% ROR.
C
C     DR2= 1.0
C     PV2=APRVAL(ATPR,MYR,DR2,XINVES)
C
C IF PRESENT VALUE GREATER THAN 0 AT 100%, ASSIGN ROR TO 100% AND QUIT
C
C     IF (PV2.GE.0.)XBAR=1.0
C     IF (PV2.GE.0.)GO TO 4100
C
C WE NOW HAVE THE ROR AS BEING BETWEEN 0 AND 100%.
C
C     RECAL=.FALSE.
C     COUNT=1
4000 CONTINUE
C
C PICK A POINT MIDWAY BETWEEN THE VALUES
C     XBAR=(DR1+DR2)/2.
C QUIT IF ROR DIFFERENCE IS LESS THAN ESTABLISHED TOLERANCE FACTOR
C     T1=ABS(DR2-DR1)
C     IF (T1.LT.DELTA)GO TO 4100
C COMPUTE PRESENT VALUE AT MIDPOINT VALUE
C
C     PVX=APRVAL(ATPR,MYR,XBAR,XINVES)
C DON'T REPEAT FOR FIRST TRIAL
C
C     IF (COUNT.LE.1)GO TO 4010
C DON'T RECALCULATE IF NOT NECESSARY
C
C     IF (RECAL)PV1=APRVAL(ATPR,MYR,DR1,XINVES)
4010 CONTINUE
C     COUNT=COUNT+1
C FIND WHICH SIDE (+ OR -) THE ROOT LIES
C     T3=PV1*PVX
C IF T3 LESS THAN ZERO, THE ROOT LIES BETWEEN DR1 AND XBAR
C
C     IF (T3.LE.0.)DR2=XBAR
C     IF (T3.LE.0.)RECAL=.FALSE.
C
C IF T3 GREATER THAN ZERO, THE ROOT LIES BETWEEN XBAR AND DR2
C     IF (T3.GE.0.)DR1=XBAR
C     IF (T3.GE.0.)RECAL=.TRUE.
C     GO TO 4000
4100 CONTINUE
C     ROR=XBAR*100.
C     ATPR(1) = ATPR(1) - XINVES
C     DO 302 I=2,MYR
C     XX = MUCT(I) + MUCI(I)
C     ATPR(I-1) = ATPR(I-1) + XX
302 ATPR(I) = ATPR(I) - XX
RETURN

```

```

      END
      FUNCTION APRVAL(CFSTR,FIN,DISC,XINVES)
C
C  APRVAL   : COMPUTE DISCOUNTED PRESENT VALUE OF A STREAM
C             OF CASH FLOWS
C
      INTEGER FIN
      REAL CFSTR(50),DISC,APRVAL
C
C      CFSTR(Y : AFTER TAX CASH FLOW (DISCOUNTED) IN YEAR 'YR'
C      DISC : DISCOUNT RATE
C
C      FIN : PROJECT LIFE
C
      REAL NPV,DMUL
      INTEGER YR
      NPV=0.
      DO 10 YR=1,FIN
C  DON'T DISCOUNT IN YEAR ONE
C
      X1=FLOAT(YR)-0.5
C  DISCOUNT ALL YEARS BUT THE FIRST ON THE HALF YEAR
C
      DMUL = (1.0 + DISC)**X1
      NPV=NPV+CFSTR(YR)/DMUL
10  CONTINUE
      APRVAL=NPV - XINVES
      RETURN
      END
      SUBROUTINE CUTBCK ( INSTEP )
C
C  -----
C
C      CUTBCK---CHECK TO SEE IF THE COMPLETIONS IN SOME LAYERS AT THE
C      PRODUCER SHOULD BE SHUT-IN DUE TO EXCEEDING THE USER
C      SPECIFIED WATER CUT AT THE INFILL POINT.  ROUTINE
C      SETS THE INJECTION FOR THAT LAYER TO ZERO ALSO ONLY IF
C      THERE IS LITTLE OR NO VERTICAL PERMEABILITY.
C
C  -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'STREAM.INC'
      INCLUDE 'TUBE.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'FILES.INC'
      DIMENSION NODEPR(3)
C
      IF ( INSTEP .NE. 5 )   GO TO 9900
C
      NPWELS = 1
      NODEPR(1) = NODPRD(1)
      DO 1200 J = 2, NOTUBS
      DO 1100 IPWELS = 1, NPWELS
      IF ( NODEPR(IPWELS) .EQ. NODPRD(J) )   GO TO 1200
1100 CONTINUE
      NPWELS = NPWELS + 1
      NODEPR(NPWELS) = NODPRD(J)
1200 CONTINUE
C

```

```

DO 3100 IPWELS = 1, NPWELS
WCUT = 0
C
DO 3000 I=1, ILAYER
C
C      CALCULATE THE MOBILITY OF EACH COMPLETION , THEN THE WCUT, AND
C      ADD THEM UP FOR THE LAYER 'I'.
C
DO 2000 J=1, NOTUBS
IF ( NODPRD(J) .NE. NODEPR(IPWELS) ) GO TO 2000
CALL PROIL(I, J, VP(1, J, I), BO, RSO, DENO, VISO, IDUM, IDUM)
CALL WATPR(I, J, VP(1, J, I), BW, RSO, DENW, VISW, IDUM, IDUM)
CALL WATSAT(0, 0, VSW1(1, J, I), XKRW, XKRO)
OWR = VPI(J, I)*XKRO / (VISO*BO + 1.E-20)
WWR = VPI(J, I)*XKRW / (VISW*BW + 1.E-20)
WCUT = WCUT + WWR / (OWR+WWR + 1.E-20)
2000 CONTINUE
WCUT=WCUT/NOTUBS
IF ( WCUT .LT. VCUT ) GO TO 3000
INODE = NODEPR(IPWELS)
IX = X(INODE) + 0.1
IY = Y(INODE) + 0.1
WRITE(IW, 3) I, IX, IY, CUMTIM, WCUT
3 FORMAT(' *****'
*      / ' *      SHUTTING IN COMPLETIONS FOR LAYER ', I2, '      *'
*      / ' *      IN WELL AT COORD (', I3, ', ', I3, ' )      *'
*      / ' *      TIME = ', F8.1, ' DAYS      *'
*      / ' *      WATER CUT = ', F5.3, '      *'
*      / ' *****')
C
C      ALSO SHUT-IN THE INJECTOR IF KZ IS VERY SMALL
C
DO 2500 J=1, NOTUBS
IF ( NODPRD(J) .NE. NODEPR(IPWELS) ) GO TO 2500
IPROD(J, I) = 1
IF ( VKZKH .LT. 1.E-5) IINJ(J, I) = 1
2500 CONTINUE
3000 CONTINUE
3100 CONTINUE
C
GO TO 9900
C
9900 RETURN
END
SUBROUTINE OVER1
C
C      -----
C
C      OVER1 ---CONTROL ROUTINE FOR THE INPUT OF RESERVOIR DATA AND THE
C      CALCULATION OF STREAMTUBES.
C
C      -----
C
INCLUDE 'PARAM.INC'
INCLUDE 'SIMUL.INC'
C
CALL INITAL
CALL SINGLE
NXNYNZ = NXNY * NZ

```

```

C          LEAVE ROOM FOR FOUR PERMANENT ARRAYS AND LEAVE
C          CORRECT INDEX IN COMMON FOR USE BY TABLES
LASTIN = ( 4 ) * NXNYNZ + 1
IEND = LASTIN

C          IEXCESS IS THE AMOUNT OF BLANK COMMON NOT USED IN THE INPUT
C          ROUTINES.
C
IEXCES(1) = NCORE + 1 - IEND
RETURN
END
SUBROUTINE RPTABL(CONNF)

C          -----
C          RPTABL - OUTPUT TABLE OF RELATIVE PERMEABILITY INFO FOR GIVEN
C          VALUE OF CONNECTIVITY FRACTION, CONNF
C          -----
C
C          INCLUDE 'PARAM.INC'
C          INCLUDE 'STREAM.INC'
C          INCLUDE 'SIMUL.INC'
C          INCLUDE 'FILES.INC'
C
160 FORMAT(/15X,'RELATIVE PERMEABILITY TABLE '
*          /15X,'FOR CONNECTIVITY =', F8.5 / 15X,27('-') /
1 3X,'    WATER      OIL      WATER      FW      D(FW) '/' /
2 3X,'    SATURATN    KRO      KRW      (FR FLOW)    D(SW) ' /
3 3X,'    -----    -----    -----    -----    ' )
175 FORMAT(2X,3F10.4,2F11.3)
176 FORMAT (/ 15X, 'FW = MOBW / (MOBW+MOBO), WHERE'
*          / 15X, 'MOBW = KRW/VISW, MOBO = KRO/VISO' //)
C
WRITE(IW,160) CONNF
DSW = (1.0-VSORW-VSWC)/20.0
SW = VSWC - DSW
DO 3000 I=1,21
SW = SW + DSW
CALL WATSAT(0,0,SW,XKRW,XKRO)
XMOBW = XKRW / VISWTR
XMOBO = XKRO / VISOIL
FW = XMOBW / ( XMOBW + XMOBO )
IF ( I .EQ. 1 ) GO TO 2800
DFWDSW = ( FW - PREVFW ) / DSW
WRITE(IW,175) SW,XKRO,XKRW,FW,DFWDSW
GO TO 2900
2800 WRITE(IW,175) SW,XKRO,XKRW,FW
2900 PREVFW = FW
3000 CONTINUE
WRITE(IW,176)

C          RETURN
C          END
C          SUBROUTINE TITL(ITITL)
C          -----
C          TITL-- OUTPUT TITLE HEADING FOR THE RESERVOIR PORTION OF THE
C          RUN

```

```

C
C -----
C
      INCLUDE 'FILES.INC'
      DIMENSION ITITL(20)
C
      WRITE(IW,9000)
9000  FORMAT(1H1,
1 1X, 42H***** /
1 2X, 42H* * /
1 2X, 42H* S C I E N T I F I C S O F T W A R E * /
1 2X, 42H* - I N T E R C O M P * /
1 2X, 42H* * /
1 2X, 42H* * /
1 2X, 42H* I N F I L L D R I L L I N G P R E D I C T I O N M O D E L * /
1 2X, 42H* ( I D P M - R E L E A S E 1.2.0 ) * /
1 2X, 42H* * /
1 2X, 42H***** / )
C
      WRITE(IW,9004) ITITL
9004  FORMAT(1X,20A4)
      RETURN
      END
      SUBROUTINE DPLYR(ICASE,V,N,AVPERM,PAY,PERML,PAYL)
C
C -----
C THIS SUBROUTINE IS DESIGNED FOR CALCULATING PERMEABILITY AND
C THICKNESS FOR DISCRETE LAYERS FROM A GIVEN DYSTRA-PARSONS
C COEFFICIENT. BOTH METHODS, EQUAL KH AND H, ARE CONSIDERED HERE.
C REFERENCE: GEORGE J. HIRASAKI, PERSONAL COMMUNICATION.
C -----
C
C
C
      INCLUDE 'PARAM.INC'
      DIMENSION PERML(LAYMAX),PAYL(LAYMAX)
      COMMON /D/ C,F,VAR
C
      IF(ICASE.GT.1)GO TO 20
C
C ***** EQUAL THICKNESS; ICASE = 1
C
      VAR = ALOG(1.0-V)**2
      DC = 1./FLOAT(N)
      CIM1 = 0.
      FIM1 = 0.
      DO 19 L=1,N
      C = CIM1+DC
      IF(C .LT. 0.999) GO TO 13
      T = -3.5
      GO TO 14
13  X1 = -3.5
      X2 = 4.0
      X3 = 4.1
      IFT = 1
      CALL ROOT3(X1,X2,X3,T,IFT)
14  SQARG = SQRT(0.5*VAR)
      F = 0.5*(1. - ERFUNC(0.7071*T-SQARG) )
      DF = F-FIM1
      PERM = DF/DC
      PERML(L) = AVPERM*PERM

```

```

      PAYL(L) = PAY*DC
      CIM1 = C
      FIM1 = F
19    CONTINUE
      RETURN
C
C ***** EQUAL KH; ICASE = 2
C
20    VAR = ALOG(1.-V)**2
      DF = 1.0/FLOAT(N)
      CIM1 = 0.
      FIM1 = 0.
      DO 29 L=1,N
      F = FIM1+DF
      IF (F .LT. 0.999) GO TO 22
      T = -3.5
      GO TO 23
22    X1 = -3.5
      X2 = 4.0
      X3 = 4.1
      IFT = 2
      CALL ROOT3(X1,X2,X3,T,IFT)
23    C = 0.5*(1.0 - ERFUNC(0.7071*T))
      DC = C-CIM1
      PERM = DF/DC
      PERML(L) = AVPERM*PERM
      PAYL(L) = PAY*DC
      CIM1 = C
      FIM1 = F
29    CONTINUE
      RETURN
      END
      FUNCTION CFUN(T)
      COMMON /D/ C,F,VAR
C
      CFUN = 0.5*(1.0 - ERFUNC(0.7071*T)) - C
      RETURN
      END
      FUNCTION FFUN(T)
      COMMON /D/ C,F,VAR
C
      SQARG = SQRT(0.5*VAR)
      FFUN = 0.5*(1.0 - ERFUNC(0.707*T-SQARG)) - F
      RETURN
      END
      FUNCTION ERFUNC(X)
C
C-----
C ERROR FUNCTION CALCULATION FOR DYKSTRA-PARSONS PERMEABILITY VARIATION
C-----
C
C
      IF (ABS(X) .GT. 1.0E-6) GO TO 101
      ERFUNC = 0.0
      RETURN
C
101  A1 = .0705230784
      A2 = .0422820123
      A3 = .0092705272
      A4 = .0001520143

```

```

A5      = .0002765672
A6      = .0000430638
FLAG    = 1.0
XX      = X
IF(X.GE.0.0) GO TO 10
FLAG    = -1.0
XX      = -1.0*X
10 X2    = XX*XX
Y       = 1.0 + A1*XX + A2*X2 + A3*XX*X2
*       + A4*X2*X2 + A5*XX*X2*X2 + A6*X2*X2*X2
Z       = 1.0/Y**16.0
ERFUNC  = (1.0-Z)*FLAG
RETURN
END
SUBROUTINE ROOT3(X1,X2,X3,X,IFT)

C
C -----
C
C ROOT3: X3 IS SINGULARITY
C
C -----
C
C INCLUDE 'FILES.INC'
C
C INTV   = 20
C IF(X3.NE.0.) INTV = 50
C DX     = (X2-X1) / FLOAT(INTV)
C X      = X1
C IF(IFT.EQ.1) FOLD = CFUN(X1)
C IF(IFT.EQ.2) FOLD = FFUN(X1)
C XOLD   = X1-X3
C
C ***** SEARCH INTERVAL
C DO 30 I=1,INTV
C X      = X+DX
C IF(IFT.EQ.1) FVAL = CFUN(X)
C IF(IFT.EQ.2) FVAL = FFUN(X)
C XVAL   = X-X3
C SGF    = FVAL*FOLD
C SGX    = XVAL*XOLD
C IF(SGX.LT.0.0) GO TO 29
C IF(SGX.LE.0.0) GO TO 31
C 29 XOLD = XVAL
C 30 FOLD = FVAL
C WRITE(IW,9032)
C 9032 FORMAT(1H0,10X,' *** DYKSTRA-PARSONS --- NO ROOT IN INTERVAL ***')
C RETURN
C
C 31 X1    = X-DX
C X2      = X
C XDEL    = ABS(X2-X1)
C XMIN    = AMIN1(X1,X2)
C XMAX    = AMAX1(X1,X2)
C XJ      = 0.5*(X1+X2)
C IF(X.GT.XMIN+0.001*XDEL .AND. X.LT.XMAX-0.001*XDEL) XJ = X
C IF(IFT.EQ.1) FJP1 = CFUN(XJ)
C IF(IFT.EQ.2) FJP1 = FFUN(XJ)
C IF(IFT.EQ.1) FX1  = CFUN(X1)
C IF(IFT.EQ.2) FX1  = FFUN(X1)
C DFDX    = (FJP1-FX1)/(XJ-X1)

```

```

C
C      ***** ITERATIVE CONVERGENCE
DO 10 J=1,30
FJ      = FJP1
XJP1    = XJ-FJ/DFDX
IF(XJP1.LT.XMIN) XJP1 = XMIN
IF(XJP1.GT.XMAX) XJP1 = XMAX
ERROR = (XJP1-XJ) / (XDEL+1.E-06)
IF(ABS(ERROR) .LT. 1.E-3) GO TO 11
IF(IFT.EQ.1) FJP1 = CFUN(XJP1)
IF(IFT.EQ.2) FJP1 = FFUN(XJP1)
DFDX    = (FJP1-FJ) / (XJP1-XJ)
XOLD    = XJ
XJ      = XJP1
10 CONTINUE
C
      IF(IFT .EQ. 1) FJP1 = CFUN(XJP1)
      IF(IFT .EQ. 2) FJP1 = FFUN(XJP1)
      WRITE(IW,9020) XJP1, XOLD, FJP1
9020 FORMAT(1H0,'*** DYKSTRA-PARSONS -- ROOT ROUTINE FAILED ',/,
* 5X,'XJP1 =',F10.4,
1 5H XJ =, F10.4, 7H FJP1 =, F10.4)
C
C      ***** CONVERGED
11 IF(XJP1.GT.0.99999*XMAX.OR.XJP1.LT.1.00001*XMIN)
1 WRITE(IW,9021) XJP1, FJP1
X      = XJP1
9021 FORMAT(1H0,'*** DYKSTRA-PARSONS -- SOLUTION NOT WITHIN X1 AND X2',
* /,10X,' X =', F6.3,' F =', F6.3 )
C
      RETURN
      END
      SUBROUTINE FIXUP(A_TIME, A_RATE, NA, M, NM )

      DIMENSION A_TIME(NA),A_RATE(NA)
      REAL M
      DIMENSION M ( * )

      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'STREAM.INC'

      DO 69 I=1,NA
      M(I)=0.0
69 CONTINUE

      CLAST=0.0
      TLAST=0.0

      N1=1

      DO 40 J=1,NA

      UT=A_TIME(J)*365
C      IF(UT.GT.TTIME(KEEP)) GOTO 42

      DO 41 K=N1,KEEP

      IF( TTIME(K) .GE. UT ) THEN

```


C INTERPOLATE INTO MODEL DATA TO MATCH ACTUAL TIME PERIODS

```
      IF (K.GE.2) THEN
        U1= (UT-TTIME (K-1)) / (TTIME (K)-TTIME (K-1))
C      U2=OILRAT (K)-OILRAT (K-1)
        U2=OILCM (K)-OILCM (K-1)
        UC=OILCM (K-1)+ U2*U1
      ELSE
        U1=A TIME (J) /TTIME (K)
        U2=OILCM (K)
        UC=U2*U1
      ENDIF

      M(J)= ( UC-CLAST) / (UT-TLAST) ) * RSCALE
      CLAST=UC
      TLAST=UT
      N1=K
      GOTO 40

    ENDIF

41    CONTINUE
40    CONTINUE
42    CONTINUE

    NM=KEEP

    RETURN
```

END

```
SUBROUTINE GENFEL ( IPAT9, INFILL, VANISO, ISO, KASE, NCOORD )
                  *I*      *I*      *I*  *I*      *O*      *O*
```

C
C
C
C
C
C
C
C
C
C
C

GENFEL

GENERATE FINITE ELEMENT MESH FOR THE CASE AT HAND.

```
-----
INCLUDE 'PARAM.INC'
INCLUDE 'TUBE.INC'
INCLUDE 'STREAM.INC'
INCLUDE 'FILES.INC'
```

C
C
C
C
C
C
C
C

DIMENSION RATEC (9), RATER (9), QPCRNR (8), QIYDIR (8), RKYKX (8)

RATEC AND RATER ARE NON-INFIL KY/KX RATIO AND NON-INFIL
RATE RATIOS FOR THE WELL IN THE Y DIRECTION RELATIVE TO
THE WELL IN THE X DIRECTION. THE RATES FOR STREAMTUBE
CALCULATIONS ARE CALCULATED FROM THESE VALUES AND USER
INPUT KY/KX RATIO.

```
DATA RATEC / 1.,2.00,5.0,10.,20.,50.0,75.0,100.,200. /
DATA RATER / 1.,1.67,3.1,5.0,7.5,15.0,22.0,29.0,54.0 /
DATA RKYKX / 1.0, 2.0, 4.0, 8.0,12.0,20.0,30.0,200. /
DATA QPCRNR / .321,.335,.375,.448,.500,.574,.636,.840 /
DATA QIYDIR / .500,.596,.683,.765,.802,.843,.874,.965 /
```

C

```

      IF ( ISTRMP .NE. 0 )
      *   CALL PATTRN ( IW, IPAT9, INFILL, ISO )
C
      IDIM = IGDMAX
      JDIM = JGDMAX
      MINDIM = MIN0 (IDIM, JDIM)
      XANI = MINDIM
      YANI = XANI
      HXANI = (XANI-1.0)/2.0+1.0
      HYANI = HXANI
      XISO = XANI
      YISO = YANI
      KASE = 111
C
      JUMP = INFILL * 4 + (1-ISO) * 2 + IPAT9 + 1
      IF ( JUMP .GT. 8 .OR. JUMP .LT. 1 )      JUMP = 9
C
      GO TO ( 3000, 3000, 4000, 4000,
      *       5000, 6000, 7000, 8000, 9800 ), JUMP
C
      IN THE FOLLOWING DEFINITIONS OF THE STARTING FINITE ELEMENT
      MESH FOR THE SYMMETRY ELEMENT AT HAND, TWO RULES MUST BE
      OBEYED..
      (1) THAT THE MESH MAY CONTAIN ONLY RIGHT TRIANGLE(S)
      WITH THE LEGS OF SAID TRIANGLE(S) PARALLEL TO THE CARTESIAN
      COORDINATE AXES.
      (2) THAT THE LENGTH OF THE LEGS MUST BE A POWER OF TWO AND
      NO GREATER THAN THE MAXIMUM X-DIMENSION OF THE FINE GRID,
      IGDMAX WHICH IS TENTATIVELY SET AT 129.
C
      CAUTION - THERE IS NO CHECKING ON OBEDIENCE TO THESE RULES AT
      THIS POINT.  SO, PROGRAMMERS (NOT USERS) SHOULD EXERCISE
      GREAT CARE, LEST THERE BE MYSTERIOUS ERRORS/RESULTS.
C
      3000 CONTINUE
C
      =====
      ISOTROPIC CASE WITHOUT INFILL
      =====
C
      KASE = 1
      SGAREA = (XISO-1.0)**2 / 2.0
      TRANSM = 0.5
      PRATE = 200.0
      RATE1 = -PRATE
      RATE2 = PRATE
C
      CALL NODDEF (      NODE      X      Y      PSPEC      RATE
      CALL NODDEF (      1,      1.0,      YISO,      0.0,      RATE1 )
      CALL NODDEF (      2,      XISO,      1.0,      0.0,      RATE2 )
      CALL NODDEF (      3,      1.0,      1.0,      0.0,      0.0 )
C
      CALL NODNET (      ELEMENT  NODE1  NODE2  NODE3
      CALL NODNET (      1,      1,      2,      3 )
C
      RATE2 = RATE2 / PRATE
      RATE1 = RATE1 / PRATE
      IF ( ISTRMP .NE. 0 ) WRITE(IW,300)  RATE2, RATE1
300 FORMAT(////,
&      ' *****', /

```

```

&      ' * FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *',/
&      ' *          PRODUCER = ',E13.5,          ' *',/
&      ' *          INJECTOR = ',E13.5,          ' *',/
&      ' *****' )

C
GO TO 9000

C
4000 CONTINUE
C      =====
C      ANISOTROPIC CASE, WITHOUT INFILL
C      =====
C
C      RATES ARE A FUNCTION KY/KX RATIO AS DETERMINED BY RESERVOIR
C      SIMULATION RUNS.
C
DO 4100 I=2,9
  II=I
  IF ( VANISO .LT. RATEC(I) ) GO TO 4200
4100 CONTINUE
4200 RATEF=RATER(II-1)+(VANISO-RATEC(II-1))/(RATEC(II)-RATEC(II-1))
&      * (RATER(II)-RATER(II-1))
C
KASE = 2
SGAREA = (XANI-1.0)**2 / 2.0
TRANSM = 0.5
PRATE = 200.0
RATE1 = -PRATE/(1.0+RATEF)
RATE2 = -PRATE-RATE1
RATE3 = PRATE
C
C      NODE      X      Y      PSPEC      RATE
CALL NODDEF ( 1, XANI, 1.0, 0.0, RATE1 )
CALL NODDEF ( 2, 1.0, YANI, 0.0, RATE2 )
CALL NODDEF ( 3, 1.0, 1.0, 0.0, RATE3 )
C
C      ELEMENT  NODE1  NODE2  NODE3
CALL NODNET ( 1, 1, 2, 3 )
C
RATE1 = RATE1 / PRATE
RATE2 = RATE2 / PRATE
RATE3 = RATE3 / PRATE
IF ( ISTRMP .NE. 0 ) WRITE(IW,400) RATE3, RATE1, RATE2
400 FORMAT(////,
&      ' *****',/
&      ' * FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *',/
&      ' *          PRODUCER = ',E13.5,          ' *',/
&      ' *          X-DIR INJECTOR = ',E13.5,          ' *',/
&      ' *          Y-DIR INJECTOR = ',E13.5,          ' *',/
&      ' *****' )
C
GO TO 9000

C
5000 CONTINUE
C      =====
C      ISOTROPIC CASE WITH 5-SPOT INFILL
C      =====
C
KASE = 3
SGAREA = (XISO-1.0)**2 / 2.0

```

```

TRANSM = 0.5
PRATE = 200.0
RATE1 = -PRATE/2.0
RATE2 = RATE1
RATE3 = PRATE

C
C
      NODE      X      Y      PSPEC      RATE
CALL NODDEF (    1,    1.0,    YISO,    0.0,    RATE1 )
CALL NODDEF (    2,    XISO,    1.0,    0.0,    RATE2 )
CALL NODDEF (    3,    1.0,    1.0,    0.0,    RATE3 )

C
C
      ELEMENT  NODE1  NODE2  NODE3
CALL NODNET (      1,      1,      2,      3 )

C
RATE1 = RATE1 / PRATE
RATE2 = RATE2 / PRATE
RATE3 = RATE3 / PRATE
IF ( ISTRMP .NE. 0 ) WRITE(IW,500)  RATE3, RATE1, RATE2
500 FORMAT(////,
&      ' *****',/
&      ' *   FRACTIONAL WELL RATES FOR TUBE CALCULATIONS   *',/
&      ' *                               PRODUCER = ',E13.5,    ',/
&      ' *                               Y-DIR INJECTOR = ',E13.5,  ',/
&      ' *                               X-DIR INJECTOR = ',E13.5,  ',/
&      ' *****')

C
GO TO 9000

C
6000 CONTINUE

C
C
=====
ISOTROPIC CASE WITH 9-SPOT INFILL
=====

C
KASE = 4
SGAREA = (XISO-1.0)**2 / 2.0
TRANSM = 0.5
PRATE = 300.0
RATE2 = 0.334*PRATE
RATE3 = PRATE-RATE2
RATE1 = -PRATE

C
C
      NODE      X      Y      PSPEC      RATE
CALL NODDEF (    1,    1.0,    YISO,    0.0,    RATE1 )
CALL NODDEF (    2,    XISO,    1.0,    0.0,    RATE2 )
CALL NODDEF (    3,    1.0,    1.0,    0.0,    RATE3 )

C
C
      ELEMENT  NODE1  NODE2  NODE3
CALL NODNET (      1,      1,      2,      3 )

C
RATE1 = RATE1 / PRATE
RATE2 = RATE2 / PRATE
RATE3 = RATE3 / PRATE
IF ( ISTRMP .NE. 0 ) WRITE(IW,600)  RATE3, RATE2, RATE1
600 FORMAT(////,
&      ' *****',/
&      ' *   FRACTIONAL WELL RATES FOR TUBE CALCULATIONS   *',/
&      ' *                               NEW PRODUCER = ',E13.5,    ',/
&      ' *                               OLD PRODUCER = ',E13.5,    ',/
&      ' *                               INJECTOR = ',E13.5,    ',/
&      ' *****')

```

```

&      ' *****' )
C
      GO TO 9000
C
7000 CONTINUE
C
      =====
C      ANISOTROPIC CASE, 5-SPOT INFILL
C      =====
C
      RATES AT THE Y DIRECTION WELL AND THE X DIRECTION WELL ARE
C      FUNCTIONS OF KY/KX RATIO.
C
      RATEY = 0.334
      IF ( VANISO .LT. 10.0 ) RATEY = 0.25 + SQRT(VANISO-1.0)*0.028
      RATEX = 0.178
      IF ( VANISO .LT. 10.0 ) RATEX = 0.25 - SQRT(VANISO-1.0)*0.024
C
      KASE = 5
      TRANSM = 0.5
      SGAREA = (XANI-1.0)**2 / 2.0
      PRATE = 400.0
      RATE4 = PRATE
      RATE3 = -PRATE*RATEY
      RATE5 = -PRATE*RATEX
      RATE1 = -PRATE-RATE3-RATE5
C
C      NODE      X      Y      PSPEC      RATE
C      CALL NODDEF ( 1, 1.0, 1.0, 0.0, RATE1 )
C      CALL NODDEF ( 2, 1.0, HYANI, 0.0, 0.0 )
C      CALL NODDEF ( 3, 1.0, YANI, 0.0, RATE3 )
C      CALL NODDEF ( 4, HXANI, HYANI, 0.0, RATE4 )
C      CALL NODDEF ( 5, XANI, 1.0, 0.0, RATE5 )
C      CALL NODDEF ( 6, HXANI, 1.0, 1000.0, 0.0 )
C
C      ELEMENT  NODE1  NODE2  NODE3
C      CALL NODNET ( 1, 2, 3, 4 )
C      CALL NODNET ( 2, 1, 2, 4 )
C      CALL NODNET ( 3, 1, 4, 6 )
C      CALL NODNET ( 4, 4, 5, 6 )
C
      RATE1 = RATE1 / PRATE
      RATE3 = RATE3 / PRATE
      RATE4 = RATE4 / PRATE
      RATE5 = RATE5 / PRATE
      IF ( ISTRMP .NE. 0 ) WRITE(IW,700) RATE4, RATE1, RATE3, RATE5
700 FORMAT(////,
&      ' *****',/
&      ' * FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *',/
&      ' * PRODUCER = ',E13.5, ', *',/
&      ' * CORNER INJECTOR = ',E13.5, ', *',/
&      ' * Y-DIR INJECTOR = ',E13.5, ', *',/
&      ' * X-DIR INJECTOR = ',E13.5, ', *',/
&      ' *****' )
C
      GO TO 9000
C
8000 CONTINUE
C
      =====

```

```

C      ANISOTROPIC CASE, 9-SPOT INFILL
C      =====
C
C      RATES ARE A FUNCTION KY/KX RATIO AS DETERMINED BY RESERVOIR
C      SIMULATION RUNS.
C
      DO 8100 I=1,7
      II=I
      IF ( VANISO .LE. RKYKX(I+1) ) GO TO 8200
8100 CONTINUE
8200 RATLOG = ALOG10 ( VANISO/RKYKX(II) ) /
      *      ALOG10 ( RKYKX(II+1)/RKYKX(II) )
      RATEF = QIYDIR(II) + ( QIYDIR(II+1) - QIYDIR(II) ) * RATLOG
      RATEP = QPCNR(II) + ( QPCNR(II+1) - QPCNR(II) ) * RATLOG
C
      KASE = 6
      SGAREA = (XANI-1.0)**2 / 2.0
      TRANSM = 0.5
      PRATE = 400.0
      RATE1 = RATEP*PRATE
      RATE4 = PRATE-RATE1
      RATE3 = -RATEF*PRATE
      RATE5 = -PRATE-RATE3
C
C      CALL NODDEF (      NODE      X      Y      PSPEC      RATE
C      CALL NODDEF (      1,      1.0,      1.0,      0.0,      RATE1 )
C      CALL NODDEF (      2,      1.0,      HYANI,      1000.0,      0.0 )
C      CALL NODDEF (      3,      1.0,      YANI,      0.0,      RATE3 )
C      CALL NODDEF (      4,      HXANI,      HYANI,      0.0,      RATE4 )
C      CALL NODDEF (      5,      XANI,      1.0,      0.0,      RATE5 )
C      CALL NODDEF (      6,      HXANI,      1.0,      0.0,      0.0 )
C
C      CALL NODNET (      ELEMENT      NODE1      NODE2      NODE3
C      CALL NODNET (      1,      2,      3,      4 )
C      CALL NODNET (      2,      1,      2,      4 )
C      CALL NODNET (      3,      1,      4,      6 )
C      CALL NODNET (      4,      4,      5,      6 )
C
      RATE1 = RATE1 / PRATE
      RATE3 = RATE3 / PRATE
      RATE4 = RATE4 / PRATE
      RATE5 = RATE5 / PRATE
      IF ( ISTRMP .NE. 0 ) WRITE(IW,800) RATE4, RATE1, RATE3, RATE5
800 FORMAT(////,
&      ' *****',/
&      ' * FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *',/
&      ' * NEW PRODUCER = ',E13.5, ' ',/
&      ' * OLD PRODUCER = ',E13.5, ' ',/
&      ' * Y-DIR INJECTOR = ',E13.5, ' ',/
&      ' * X-DIR INJECTOR = ',E13.5, ' ',/
&      ' *****')
C
      GO TO 9000
C
9000 CONTINUE
      NCOORD = NONODE
      DMIN = 0.0
      DMAX = 0.0
      DO 9200 IN = 1, NONODE
      DMAX = AMAX1(DMAX,X(IN),Y(IN))

```

```

DMIN = AMINI(DMIN,X(IN),Y(IN))
TRANS(IN)= TRANSM
IF ( ISTRMP .EQ. 0 )          GO TO 9200
IF ( RATE(IN) .EQ. 0.0 )     GO TO 9200
I = X(IN)
J = Y(IN)
IF ( RATE(IN) .GT. 0.0 )     WRITE ( IW, 921 ) I, J
921 FORMAT ( ' *           PRODUCER AT COORD ( ', I3,',',',I3,' )', 15X, '**' )
IF ( RATE(IN) .LT. 0.0 )     WRITE ( IW, 922 ) I, J
922 FORMAT ( ' *           INJECTOR AT COORD ( ', I3,',',',I3,' )', 15X, '**' )
9200 CONTINUE
IF ( ISTRMP .NE. 0 )         WRITE ( IW, 923 )
923 FORMAT ( ' *****' )
C
GO TO 9900
C
9800 WRITE (IW,900) IPAT9, ISO, INFILL
900 FORMAT ( / ' ERROR IN -GENFEL-, ( IPAT9, ISO, INFILL ) =' , 3I5 / )
CALL HALTER ( 'GENFEL', 9800 )
C
9900 RETURN
C END GENFEL
END
SUBROUTINE NODDEF ( NUMNOD,   XVALU,   YVALU,   PVALU, QVALU )
               *I*       *I*       *I*       *I*       *I*
-----
                                N O D D E F
-----
INCLUDE 'PARAM.INC'
INCLUDE 'TUBE.INC'
INCLUDE 'STREAM.INC'
INCLUDE 'FILES.INC'
C
IX = XVALU + 0.5
IY = YVALU + 0.5
IF ( IX .GT. IGDMAX .OR. IY .GT. JGDMAX )    GO TO 9000
X(NUMNOD)      = XVALU
Y(NUMNOD)      = YVALU
PSPEC(NUMNOD)  = PVALU
RATE(NUMNOD)   = QVALU
NONODE        = NUMNOD
GO TO 9900
C
9000 WRITE (IW,900) XVALU, YVALU
900 FORMAT (/ ' ERROR IN NODDEF.. MESH COORDINATE TOO LARGE' /
*              ' ( XVALU, YVALU ) =' , 2E12.2 / )
CALL HALTER ( 'NODDEF', 9000 )
C
9900 RETURN
C END NODDEF
END
SUBROUTINE NODNET ( NUMELM, NODE1, NODE2, NODE3 )
               *I*       *I*       *I*       *I*
-----

```

[illegible]


```

*          ' |          /
*          ' |          /
*          ' |          /
*          ' |          /
*          'P-----P          P' /
C
DATA LINA / 'P          I          P' /
C
DATA PATA / 'P          I          P' /
*          ' /
*          ' /
*          ' /
*          ' /
*          ' /
*          ' /
*          ' /
*          ' /
*          ' /
*          'I          P-----I' /
C
DATA LIN5A1 / 'I          I          I' /
DATA LIN5A2 / '          P          P          ' /
C
DATA PAT5A / 'I          I          I' /
*          ' /
*          ' /
*          ' /
*          ' /
*          '          P          P          /
*          ' /
*          ' /
*          ' /
*          'I          I-----I' /
C
DATA LIN9A1 / 'P          I          P' /
DATA LIN9A2 / '          P          P          ' /
C
DATA PAT9A / 'P          I          P' /
*          ' /
*          ' /
*          ' /
*          ' /
*          '          P          P          /
*          ' /
*          ' /
*          ' /
*          'I          P-----I' /
C
C
50 FORMAT ( 21X, A )
100 FORMAT ( /// )
150 FORMAT ( //// )
200 FORMAT ( ////////// )
300 FORMAT ( 1H1 ////
*          20X, 'SYMMETRY ELEMENT WITHIN 5-SPOT, BEFORE IN-FILL'
*          /
*
* 20X, '=====

```

```

*          / )
400 FORMAT ( 1H1 ////
*          25X,'SYMMETRY ELEMENT AFTER 5-SPOT IN-FILL'
*          / 25X,'=====
*          / )
500 FORMAT ( 1H1 ////
*          25X,'SYMMETRY ELEMENT AFTER 9-SPOT IN-FILL'
*          / 25X,'=====
*          / )
800 FORMAT ( 26X,'ISOTROPIC PERMEABILITY CASE - 1/8'
*          / 26X,'=====
*          // )
900 FORMAT ( 25X,'ANISOTROPIC PERMEABILITY CASE - 1/4'
*          / 25X,'=====
*          // )

```

```

C
C          IPAT9 = 0   FOR 5-SPOT INFILL IN 5-SPOT PATTERN
C          IPAT9 = 1   FOR 9-SPOT INFILL IN 5-SPOT PATTERN
C          ISO  = 1   FOR ISOTROPIC PERM
C          ISO  = 0   FOR ANISOTROPIC PERM
C          INFILL = 0   FOR INFILL INACTIVE
C          INFILL = 1   FOR INFILL ACTIVE
C
C          JUMP = IPAT9 * 4 + (1-ISO) * 2 + INFILL + 1
C          GO TO ( 1000, 1500, 2000, 2500, 1000, 3500, 2000, 4500 ), JUMP

```

```

C
C          5-SPOT, BEFORE INFILL, ISOTROPIC

```

```

1000 CONTINUE
WRITE (IW,300)
WRITE (IW,800)
WRITE (IW, 50) PAT
WRITE (IW,200)
WRITE (IW, 50) LIN
GO TO 9000

```

```

C
C          5-SPOT, AFTER 5-SPOT INFILL, ISOTROPIC

```

```

1500 CONTINUE
WRITE (IW,400)
WRITE (IW,800)
WRITE (IW, 50) PAT5I
WRITE (IW,200)
WRITE (IW, 50) LIN5I
GO TO 9000

```

```

C
C          5-SPOT, BEFORE INFILL, ANISOTROPIC

```

```

2000 CONTINUE
WRITE (IW,300)
WRITE (IW,900)
WRITE (IW, 50) PATA
WRITE (IW,200)
WRITE (IW, 50) LINA
GO TO 9000

```

```

C
C          5-SPOT, AFTER 5-SPOT INFILL, ANISOTROPIC

```

```

2500 CONTINUE
WRITE (IW,400)
WRITE (IW,900)
WRITE (IW, 50) PAT5A
WRITE (IW,150)
WRITE (IW, 50) LIN5A2

```

```

        WRITE (IW,150)
        WRITE (IW, 50) LIN5A1
        GO TO 9000
C
C          5-SPOT, AFTER 9-SPOT INFILL, ISOTROPIC
3500 CONTINUE
        WRITE (IW,500)
        WRITE (IW,800)
        WRITE (IW, 50) PAT9I
        WRITE (IW,200)
        WRITE (IW, 50) LIN9I
        GO TO 9000
C
C          5-SPOT, AFTER 9-SPOT INFILL, ANISOTROPIC
4500 CONTINUE
        WRITE (IW,500)
        WRITE (IW,900)
        WRITE (IW, 50) PAT9A
        WRITE (IW,150)
        WRITE (IW, 50) LIN9A2
        WRITE (IW,150)
        WRITE (IW, 50) LIN9A1
        GO TO 9000
C
C
9000 WRITE (IW,200)
C
9900 RETURN
C  END  PATTRN
      END
      SUBROUTINE FELSLV (VANISO,OMEGA,ERRMAX)
C
C  -----
C
C          F E L S L V
C
C  SOLVE FOR PRESSURES IN FINITE ELEMENT PROBLEM.
C
C  ( RESULTS ANALYZED INTO ARRAYS QX AND QY, IN GENFCG )
C
C  -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'TUBE.INC'
      INCLUDE 'STREAM.INC'
      INCLUDE 'FILES.INC'
C
C          MAXIMUM NUMBER OF NODES IN THE PRESSURE SOLUTION
C
      MAXNOD = (IGDMAX/2)*(JGDMAX/2)
C
C          MAXIMUM NUMBER OF TRIANGULAR ELEMENTS IN PRESSURE SOLUTION
C
      MAXELE = (IGDMAX/2)*(JGDMAX/2)
      NOCONN = 7
      IGUESS = 0
C
3000 CONTINUE
C
C          SET UP COEFFICIENT MATRICES

```

```

C
DO 3020 N=1,NONODE
DO 3010 NC=1,NOCONN
NNODE(N,NC) = 0
TERM(N,NC) = 0.
3010 CONTINUE
3020 CONTINUE
C
C      SET FIRST VARIABLE IN NNODE ARRAY EQUAL TO NODE
C
DO 3050 N = 1,NONODE
NNODE(N,1) = N
3050 CONTINUE
NEWNOD = NONODE
C
C      COMPUTE AREA FOR EACH ELEMENT
C
DO 3400 M=1,NOELEM
N1 = NODE (1,M)
N2 = NODE (2,M)
N3 = NODE (3,M)
DET = X(N1)*(Y(N2)-Y(N3)) + X(N2)*(Y(N3)-Y(N1)) +
1 X(N3)*(Y(N1)-Y(N2))
AREA = DET/2
IF (AREA) 3110,3120,3130
3110 CONTINUE
AREA = -AREA
N = N2
N2 = N3
N3 = N
NODE(2,M) = N2
NODE(3,M) = N3
GO TO 3130
3120 CONTINUE
GO TO 9500
3130 CONTINUE
XIJ = X(N1) - X(N2)
XIK = X(N1) - X(N3)
XJK = X(N2) - X(N3)
YIJ = Y(N1) - Y(N2)
YIK = Y(N1) - Y(N3)
YJK = Y(N2) - Y(N3)
C
C      X DIRECTION TRANSMISSIVITY
C
CX = TRANS(M)/4./AREA
C
C      Y DIRECTION TRANSMISSIVITY
C
CY = TRANS(M)/(VANISO*4.0)/AREA
C
C      COMPUTE MATRIX TERMS
C
S11 = (XJK**2*CX + YJK**2*CY)
S12 = -(XJK*XIK*CX + YJK*YIK*CY)
S13 = (XJK*XIJ*CX + YJK*YIJ*CY)
S22 = (XIK**2*CX + YIK**2*CY)
S23 = -(XIK*XIJ*CX + YIK*YIJ*CY)
S33 = (XIJ**2*CX + YIJ**2*CY)
TERM(N1,1) = TERM(N1,1)+S11

```

```

        TERM(N2,1) = TERM(N2,1)+S22
        TERM(N3,1)=TERM(N3,1) +S33
        S = S12
        NC1 = N1
        NC2 = N2
        IC = 1
        GO TO 3200
3150 S = S12
        NC1 = N2
        NC2 = N1
        IC = 2
        GO TO 3200
3160 S = S13
        NC1 = N1
        NC2 = N3
        IC = 3
        GO TO 3200
3170 S = S13
        NC1 = N3
        NC2 = N1
        IC =4
        GO TO 3200
3180 S = S23
        NC1 = N2
        NC2 = N3
        IC = 5
        GO TO 3200
3190 S = S23
        NC1 = N3
        NC2 = N2
        IC = 6
3200 CONTINUE
        DO 3210 NI = 2,NOCONN
        NCHK = NNODE(NC1,NI)
        IF ( NCHK .EQ. 0) GO TO 3220
        IF ( NCHK .EQ. NC2) GO TO 3230
3210 CONTINUE
3220 CONTINUE
C
C      ADD THIS NODE TO THE LIST CONNECTED TO NODE NC1
C
        NNODE(NC1,NI) = NC2
        IF ( NC2 .GT. NC1 ) NEWNOD = NEWNOD + 1
3230 CONTINUE
C
C      ADD CONTRIBUTION TO MASTER MATRIX
C
        TERM(NC1,NI) = TERM(NC1,NI) + S
C
C      GO BACK AND ADD IN THE OTHER EFFECTS
C
        GO TO (3150,3160,3170,3180,3190,3300) IC
3300 CONTINUE
C
C      COMPLETED CONTRIBUTIONS TO TERM MATRIX, NOW DO Q MATRIX
C
3400 CONTINUE
C
C      MATRICES ARE ALL SET UP
C

```

```

C      SOLVE MATRIX EQNS FOR PRESSURES
C      GET INITIAL GUESS TO PRESSURE IF NONE SPECIFIED
C
      IF ( IGUESS .NE. 0 ) GO TO 4100
      DO 4050 N = 1, NONODE
      PRESUR(N) = RATE(N)/TERM(N,1)
      IF ( PSPEC(N) .NE. 0. ) PRESUR(N) = PSPEC(N)
4050 CONTINUE
4100 CONTINUE
      IGUESS = 1

C
C      DO SUCCESSIVE OVERRELAXATION TO SOLVE EQN'S
C
      ITER = 1
4200 ITER = ITER + 1
4210 CONTINUE
      ERROR = 0.
      DO 4300 N = 1, NONODE
      IF (PSPEC(N) .NE. 0.) GO TO 4300
      SUM = RATE(N)
      DO 4220 N1 = 2, NOCONN
      N2 = NNODE(N,N1)
      IF ( N2 .EQ. 0 ) GO TO 4230
      SUM = SUM -PRESUR(N2)*TERM(N,N1)
4220 CONTINUE
4230 CONTINUE
      PCALC = SUM/TERM(N,1)
      EPSILON = ABS(PCALC-PRESUR(N))*OMEGA
      IF ( EPSILON .GT. ERROR) ERROR = EPSILON
      PRESUR(N) = PCALC*OMEGA+PRESUR(N)*(1.-OMEGA)
4300 CONTINUE
      IF ( ERROR .LT. ERRMAX ) GO TO 4500
      IF ( ITER .GT. 400 ) GO TO 4500

C
C      CONVERGENCE NOT YET ACHIEVED, ITERATE
C
      GO TO 4200

C
C      REFINE THE FINITE ELEMENT GRID FOR BETTER RESOLUTION
C      MAXIMUM REFINEMENT IS BASED ON PARAMETER LGDMAX.
C
4500 CONTINUE
      NEWELE = NOELEM*4
      IF ( NEWNOD .LE. MAXNOD ) GO TO 8010
      GO TO 8900
8010 IF ( NEWELE .LE. MAXELE ) GO TO 8020
      GO TO 8900
8020 CONTINUE

C
C      INTERPOLATE A NODE BETWEEN TWO CONNECTED NODES
C
      NNEW = NONODE
      DO 8040 N = 1 , NONODE-1
      DO 8030 N1 = 2 , NOCONN
      N2 = NNODE(N,N1)
      IF ( N2 .LT. 1 ) GO TO 8040
      IF ( N2 .LT. N ) GO TO 8030
      NNEW = NNEW + 1
      RATE(NNEW) = 0.0
      X(NNEW) = ( X(N) + X(N2) ) / 2.

```

```

      Y(NNEW) = ( Y(N) + Y(N2) ) / 2.
      PRESUR(NNEW) = (PRESUR(N) + PRESUR(N2)) / 2.
      IF ( PSPEC(N) .EQ. PSPEC(N2) ) PSPEC(NNEW) = PSPEC(N)
      NNODE(NNEW,2) = N
      NNODE(NNEW,3) = N2
8030  CONTINUE
8040  CONTINUE
      IF ( NNEW .NE. NEWNOD ) GO TO 8900
C
C      NOW REDO ELEMENTS
C
      MNEW = NOELEM
      DO 8300 M = 1, NOELEM
      M1 = MNEW + 1
      M2 = M1 + 1
      M3 = M2 + 1
      TRANS(M1) = TRANS(M)
      TRANS(M2) = TRANS(M)
      TRANS(M3) = TRANS(M)
      N1 = NODE(1,M)
      N2 = NODE(2,M)
      N3 = NODE(3,M)
C
C      NOW FIND THREE NEW NODES
C
      IFIND = 1
      NT1 = MIN0(N1,N2)
      NT2 = MAX0(N1,N2)
      GO TO 8150
8110  N4 = N
      IFIND = 2
      NT1 = MIN0(N1,N3)
      NT2 = MAX0(N1,N3)
      GO TO 8150
8120  N5 = N
      IFIND = 3
      NT1 = MIN0(N2,N3)
      NT2 = MAX0(N2,N3)
8150  CONTINUE
      DO 8160 N = NONODE+1, NEWNOD
      IF ( NNODE(N,2) .EQ. NT1 .AND. NNODE(N,3) .EQ. NT2 ) GO TO 8170
8160  CONTINUE
      GO TO 8900
8170  GO TO ( 8110,8120,8200) IFIND
8200  CONTINUE
C
C      RESET ELEMENTS
C
      N6 = N
      NODE(1,M1) = N1
      NODE(2,M1) = N4
      NODE(3,M1) = N5
      NODE(1,M2) = N2
      NODE(2,M2) = N4
      NODE(3,M2) = N6
      NODE(1,M3) = N3
      NODE(2,M3) = N5
      NODE(3,M3) = N6
      NODE(1,M) = N4
      NODE(2,M) = N5

```

```

      NODE(3,M) = N6
      MNEW = M3
8300 CONTINUE
      IGUESS = 1
      NONODE = NEWNOD
      NOELEM = NEWELE
      IF ( MNEW .NE. NOELEM ) GO TO 8900
C
C      GO BACK AND REDO PRESSURE SOLUTION ON THE FINER GRID
C
      GO TO 3000
C
8900 CONTINUE
      GO TO 9900
C
9500 WRITE (IW,950)
      950 FORMAT ( / ' ERROR IN FINITE ELEMENT SOLN - AREA=0' / )
C
9900 RETURN
C   END FELSLV
      END
      SUBROUTINE GENFCG ( VANISO, LX, LY )
C                                     *I*  *O*  *O*
C
C -----
C                                     G E N F C G
C
C RE-MAP F-E SOLUTION ONTO A FCG (FINE CARTESIAN GRID),
C GIVING AT EACH NODAL POINT THE VALUES OF -QX- AND -QY-.
C -----
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'TUBE.INC'
C INCLUDE 'STREAM.INC'
C INCLUDE 'FILES.INC'
C
C COMPUTE X-DIR AND Y-DIR FLOW COMPONENTS ON A 'IGDMAX'
C BY 'JGDMAX' GRID FOR USE IN CALCULATING STREAMTUBES.
C
C XMIN = X(1)
C YMIN = Y(1)
C DO 6100 N = 1,NONODE
C   XMIN = AMIN1(XMIN,X(N))
C   YMIN = AMIN1(YMIN,Y(N))
6100 CONTINUE
C
C DO 6120 I = 1, IGDMAX
C DO 6110 J = 1, JGDMAX
C   QX(I,J) = 0.
C   QY(I,J) = 0.
6110 CONTINUE
6120 CONTINUE
C
C CYCLE THRU EACH ELEMENT AND ADD ITS CONTRIBUTION TO THE
C FLOW COMPONENTS AT THE GRID POINTS
C
DO 7000 M = 1,NOELEM

```



```

N1 = NODE (1,M)
N2 = NODE (2,M)
N3 = NODE (3,M)
DET = X(N1) * (Y(N2)-Y(N3)) + X(N2) * (Y(N3)-Y(N1)) +
1 X(N3) * (Y(N1)-Y(N2))
C2 = ((Y(N2)-Y(N3)) * PRESUR(N1) +
1 (Y(N3)-Y(N1)) * PRESUR(N2) +
2 (Y(N1)-Y(N2)) * PRESUR(N3)) / DET
C3 = - ((X(N2)-X(N3)) * PRESUR(N1) +
1 (X(N3)-X(N1)) * PRESUR(N2) +
2 (X(N1)-X(N2)) * PRESUR(N3)) / DET
XFLUX = -TRANS(M) / VANISO * C2
YFLUX = -TRANS(M) * C3
C
N4 = N1
N5 = N2
N6 = N3
IC = 1
GO TO 6230
6210 N4 = N3
N5 = N1
N6 = N2
IC = 2
GO TO 6230
6220 N4 = N2
N5 = N3
N6 = N1
IC = 3
6230 CONTINUE
XDIFF = X(N5) - X(N6)
IF ( ABS(XDIFF) .GT. 0.0001 ) GO TO (6210,6220,8800) IC
KORNER = N6
XLEG = X(N4) - X(KORNER)
YLEG = Y(N5) - Y(KORNER)
YDIFF = Y(N4) - Y(KORNER)
IF ( ABS(YDIFF) .GT. 0.001 ) YLEG = -YDIFF
IF ( ABS(YDIFF) .GT. 0.001 ) KORNER = N5
YDIFF = Y(N4) - Y(KORNER)
IF ( ABS(YDIFF) .GT. 0.001 ) GO TO 8800
XS = X(KORNER) - XMIN
IXS = INT(XS+0.5) + 1
XL = X(KORNER) + XLEG - XMIN
IXL = INT(XL+0.5) + 1
YS = Y(KORNER) - YMIN
IYS = INT(YS+0.5) + 1
YL = Y(KORNER) + YLEG - YMIN
IYL = INT(YL+0.5) + 1
IYINC = 1
IXINC = 1
IF ( IXL .LT. IXS ) IXINC = -1
IF ( IYL .LT. IYS ) IYINC = -1
C
YSTART = Y(KORNER)
YLAST = Y(KORNER) + YLEG
C
DO 6800 IY = IYS, IYL, IYINC
YC = FLOAT(IYINC)*0.5 + FLOAT(IY-1) + YMIN
IF ( FLOAT(IYINC)*(YC-YLAST) .GT. 0.0 ) YC = YLAST
DELY = ABS(YC-YSTART)
XSTART = X(KORNER)

```

```

      XLAST = X(KORNER) + XLEG
C
      DO 6400 IX = IXS, IXL, IXINC
      XC = FLOAT(IXINC)*0.5 + FLOAT(IX-1) + XMIN
      IF ( FLOAT(IXINC)*(XC-XLAST) .GT. 0.0 ) XC = XLAST
      DELX = ABS(XC-XSTART)
      IF ( IX .EQ. IXL ) DELX = 0.5*DELX
      DAREA = DELX * DELY
      QX(IX,IY) = QX(IX,IY) + DAREA * XFLUX
      QY(IX,IY) = QY(IX,IY) + DAREA * YFLUX
      XSTART = XC
6400 CONTINUE
      YSTART = YC
      IXL = IXL - IXINC
6800 CONTINUE
C
7000 CONTINUE
C
C      NOW SET IMINGD(*) AND IMAXGD(*) FOR LATER USE IN KNOWING
C      LOCATION OF ACTIVE GRID BOUNDARIES IN RECTANGULAR ARRAYS.
C
      LX = 1
      DO 7600 J = 1, JGDMAX
      IMINGD(J) = 0
      DO 7200 I = IGDMAX, 1, -1
      IF ( ABS(QX(I,J))+ABS(QY(I,J)) .NE. 0 ) IMINGD(J) = I
7200 CONTINUE
      IMAXGD(J) = 0
      DO 7400 I = 1, IGDMAX, +1
      IF ( ABS(QX(I,J))+ABS(QY(I,J)) .NE. 0 ) IMAXGD(J) = I
7400 CONTINUE
      IF ( IMAXGD(J) .NE. 0 ) LY = J
      IF ( IMAXGD(J) .GT. LX ) LX = IMAXGD(J)
7600 CONTINUE
C
C      NOW SCALE UP ALL BORDER ELEMENTS OF QX(*) AND QY(*) TO
C      ACCOUNT FOR THEIR HALF-WIDTHS.
C
      DO 8400 J = 1, JGDMAX
      I1 = IMINGD(J)
      IL = IMAXGD(J)
      QX(I1,J) = QX(I1,J) * 2.0
      QY(I1,J) = QY(I1,J) * 2.0
      QX(IL,J) = QX(IL,J) * 2.0
      QY(IL,J) = QY(IL,J) * 2.0
      IF ( J .NE. 1 .AND. J .NE. JGDMAX ) GO TO 8400
      DO 8200 I = I1, IL
      QX(I,J) = QX(I,J) * 2.0
      QY(I,J) = QY(I,J) * 2.0
8200 CONTINUE
8400 CONTINUE
C
      GO TO 9900
C
8800 CONTINUE
C      FAILS TO MEET REQUIREMENT THAT ALL ELEMENTS IN THE MESH
C      MUST BE RIGHT TRIANGLES WITH THEIR LEGS PARALLEL TO THE
C      CARTESIAN AXES.
C
      CALL HALTER ( 'GENFCG', 8800 )

```

```

C
  9900 RETURN
C  END  GENFCG
      END
      SUBROUTINE MARKST ( NCOORD, INFILL, IPAT9, LY, KASE, VTUBE )
C                                *I*      *I*      *I*  *I*  *I*  *O*
C
C  -----
C
C                                M A R K S T
C
C  MARK SL (STREAM LINES) THAT OUTLINE EACH ST (STREAM TUDE).
C  FORM A CIRCLE OF SL MARKERS, TWO PER ST, AROUND EACH INJECTOR
C  AT ADEQUATE RADIUS THAT AVOIDS WANTING TO HAVE TWO MARKERS IN
C  THE SAME FCG CELL. FOLLOW THE STREAM LINES FROM EACH OF THE
C  INITIAL SL/ST MARKERS BACKWARD TO THE INJECTOR AND FORWARD TO
C  A PRODUCER, MARKING EACH FCG THROUGH WHICH IT PASSES WITHIN A
C  CRITICAL DISTANCE OF THE CELL CENTER. IDENTIFY INJECTOR AND
C  PRODUCER ASSOCIATED WITH EACH ST.
C
C  -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'TUBE.INC'
      INCLUDE 'STREAM.INC'
      INCLUDE 'FILES.INC'
      DIMENSION      XARC(IGDMAX+JGDMAX), YARC(IGDMAX+JGDMAX),
*                   ASUM(IGDMAX+JGDMAX), QSUM(IGDMAX+JGDMAX),
*                   CROSSX(2*NTBMAX),   CROSSY(2*NTBMAX),
*                   QFRACT(2*NTBMAX),   VTUBE(NTBMAX)
C
      DO 2000 IN = 1, NTBMAX
        NODPRD(IN) = 0
        NODINJ(IN) = 0
      2000 CONTINUE
      DO 2200 IY = 1, JGDMAX
        DO 2100 IX = 1, IGDMAX
          INXST(IX,IY) = 0
        2100 CONTINUE
      2200 CONTINUE
C
C  COMPUTE TOTAL INJECTION RATE FOR SYMMETRY ELEMENT
C
      TRATE = 0
      INMIN = 1
      DO 2600 IN = 1, NCOORD
        IF ( RATE(IN) .GE. 0.0 ) GO TO 2600
        IF ( RATE(IN) .LT. RATE(INMIN) ) INMIN = IN
        TRATE = TRATE + RATE(IN)
      2600 CONTINUE
C
C  SELECT NUMBER OF STREAM TUBES TO BE USED FOR EACH INJECTOR
C
      NOTUBS = NUMTUB
      NOTUBS = MIN0(NOTUBS, NTBMAX)
      NTOT = 0
      XMAX = 0.0
      YMAX = 0.0
      DO 2800 IN = 1, NCOORD
        XMAX = AMAX1(XMAX, X(IN))

```

```

YMAX = AMAX1(YMAX,Y(IN))
IF ( IN .EQ. INMIN )      GO TO 2800
IF ( RATE(IN) .GE. 0.0 )  GO TO 2800
NTPWEL(IN) = ( RATE(IN) / TRATE ) * NOTUBS + 0.5
IF ( NTPWEL(IN) .LT. 1 )  NTPWEL(IN) = 1
NTOT = NTOT + NTPWEL(IN)
2800 CONTINUE
NTPWEL(INMIN) = NOTUBS - NTOT
IMAX = XMAX + 0.5
JMAX = YMAX + 0.5
ISTUBE = 0

C
C   FOR EACH INJECTOR, FORM A CIRCLE OF STREAM LINE CROSSING POINTS,
C   USING TWO STREAM LINES PER STREAM TUBE
C
DO 8800 IN = 1, NCOORD
IF ( RATE(IN) .GE. 0.0 )  GO TO 8800
IINJW = X(IN)+0.001
JINJW = Y(IN)+0.001

C
C   FIRST, OBTAIN APPROX. TOTAL FLUX (QSUM) AND SUBTENDED ANGLE
C   AROUND THIS PRODUCER
C
RADIUS = 0.20 * AMAX1(XMAX,YMAX)
ISL = IINJW
JSL = JINJW - RADIUS
ISLINC = 1
IF ( IINJW .GT. 1 ) ISLINC = -1
JSLINC = 1
IF ( JSL .LT. 0 ) JSLINC = -1
IF ( JSL .LT. 0 ) JSL = JINJW + RADIUS
ROTDIR = 1.0
IF ( JSLINC .NE. ISLINC )  ROTDIR = -1.0
RAD = SQRT ( FLOAT(ISL-IINJW)**2 + FLOAT(JSL-JINJW)**2 )
ANG = ASIN ( FLOAT ( ISL-IINJW ) / RAD )
ASUM(1) = 0.0
QSUM(1) = 0.0
ISTEP = 1
NPRDW = 0
C   ADJUST INDICES TO MOVE ALONG CIRCLE
DO 3800 KNT = 1, 1000
ISLP = ISL
JSLP = JSL
ANGP = ANG
RADP = RAD
RADI = SQRT ( FLOAT(ISL+ISLINC-IINJW)**2 + FLOAT(JSL-JINJW)**2 )
RADJ = SQRT ( FLOAT(ISL-IINJW)**2 + FLOAT(JSL+JSLINC-JINJW)**2 )
IF ( RADJ .LT. RADP )  GO TO 3100
C   CHECK FOR COMPLETION OF CIRCLE
IF ( JSLINC .GT. 0 .AND. JSL .GE. JMAX )  GO TO 4000
IF ( JSLINC .LT. 0 .AND. JSL .LE. 1 )     GO TO 4000
IF ( ISL .LE. 1 )                         GO TO 4000
IF ( ISL .GE. IMAX )                     GO TO 4000
ISLINC = -ISLINC
JSLINC = -JSLINC
GO TO 3800
3100 IF ( RADI .GT. RADJ .AND. RADI .LT. RADIUS )  GO TO 3200
ANG = ASIN ( FLOAT(ISL-IINJW) / RADJ )
JSL = JSL + JSLINC
RAD = RADJ

```

```

      GO TO 3300
3200 ANG = ASIN ( FLOAT(ISL+ISLINC-IINJW) / RAD )
      ISL = ISL + ISLINC
      RAD = RAD
3300 CONTINUE
C     WATCH FOR BOUNDARY
      IF ( ABS(QX(ISL,JSL))+ABS(QY(ISL,JSL)) .EQ. 0.0
*      .AND. ISTEP .GT. 2 ) GO TO 4000
C     UPDATE QSUM AND ASUM VALUES
      IF ( JSLINC .GT. 0 .AND. JSL .GT. JMAX ) GO TO 3800
      IF ( JSLINC .LT. 0 .AND. JSL .LT. 1 ) GO TO 3800
      IF ( ISL .LT. 1 ) GO TO 3800
      IF ( ISL .GT. IMAX ) GO TO 3800
      QXPRV = QX(ISLP,JSLP)
      QYPRV = QY(ISLP,JSLP)
      QXNOW = QX(ISL,JSL)
      QYNOW = QY(ISL,JSL)
      QDELT = 0.5*ROTDIR*(QYNOW+QYPRV)*(ISL-ISLP) +
*      0.5*ROTDIR*(QXNOW+QXPRV)*(JSLP-JSL)
      IF ( ABS(QDELT) .LT. 1.0E-6 ) GO TO 3800
      IF ( ISTEP .EQ. 1 ) XARC(1) = ISLP
      IF ( ISTEP .EQ. 1 ) YARC(1) = JSLP
      ISTEP = ISTEP + 1
      XARC(ISTEP) = ISL
      YARC(ISTEP) = JSL
      QSUM(ISTEP) = QSUM(ISTEP-1) + QDELT
      ASUM(ISTEP) = ASUM(ISTEP-1) + ANG - ANG
3800 CONTINUE
      CALL HALTER ( 'MARKST', 3800 )
C
4000 CONTINUE
      ANGL = ASUM(ISTEP)
      QLST = QSUM(ISTEP)
      NSL = 2 * NTPWEL(IN)
      ANGINC = ANGL / NSL
      ANGSUM = 0
      QFRSUM = 0
      KSTEP = 1
      DO 5200 KSL = 1, NSL
      ANGSUM = ANGSUM + ANGINC
      CPANG = ANGSUM - 0.5 * ANGINC
4700 IF ( ABS(CPANG) .LE. ABS(ASUM(KSTEP+1)) ) GO TO 4800
      IF ( KSTEP+1 .EQ. ISTEP ) GO TO 4800
      KSTEP = KSTEP + 1
      GO TO 4700
4800 FRACT = ( CPANG - ASUM(KSTEP) ) / ( ASUM(KSTEP+1) - ASUM(KSTEP) )
      CROSSX(KSL) = XARC(KSTEP) + (XARC(KSTEP+1) - XARC(KSTEP)) * FRACT
      CROSSY(KSL) = YARC(KSTEP) + (YARC(KSTEP+1) - YARC(KSTEP)) * FRACT
4900 IF ( ABS(ANGSUM) .LE. ABS(ASUM(KSTEP+1)) ) GO TO 5000
      IF ( KSTEP+1 .EQ. ISTEP ) GO TO 5000
      KSTEP = KSTEP + 1
      GO TO 4900
5000 FRACT = ( ANGSUM - ASUM(KSTEP) ) / ( ASUM(KSTEP+1) - ASUM(KSTEP) )
      QFRACT(KSL) = ( ( QSUM(KSTEP+1) - QSUM(KSTEP)) * FRACT +
*      QSUM(KSTEP) ) / QLST - QFRSUM
      QFRSUM = QFRSUM + QFRACT(KSL)
5200 CONTINUE
C
C     FOR EACH ARC-CROSSING, MARK FINE GRID CELLS ALONG STREAM LINE
C

```

```

DO 8000 KSL = 1, NSL, 2
ISTUBE = ISTUBE + 1
SLENG(ISTUBE) = 99999.0
VTUBE(ISTUBE) = (QFRACT(KSL)+QFRACT(KSL+1)) * RATE(IN) / TRATE
6000 CONTINUE
XCROSS = CROSSX(KSL)
YCROSS = CROSSY(KSL)
CALL MARKSL ( XCROSS, YCROSS, ISTUBE )
C
C   READY TO FOLLOW AND MARK STREAM LINE
MARK = 1
CALL FOLLSL ( XCROSS, YCROSS, NCOORD, IN, IINJW, JINJW,
*           ISTUBE, MARK, SLL, NPRDW, LY )
C
C   IF ( SLL .LT. SLENG(ISTUBE) ) SLENG(ISTUBE) = SLL
C
C   READY FOR NEXT STREAM LINE
8000 CONTINUE
C   READY FOR NEXT INJECTOR
8800 CONTINUE
C
C   IF ( ISTRMP .GT. 2 ) CALL TUBAUS ( NCOORD, LY, 0 )
C
9900 RETURN
C   END MARKST
END
C
C*****
C
SUBROUTINE PUT1(IW,TIME,OILRAT,OILCM,RSCALE,KEEP,ISENS)
DIMENSION TIME(KEEP),OILRAT(KEEP),OILCM(KEEP)

C WRITE AN ASCII FILE (SINGLE CASE RUN) OR A BINARY (MULTI CASE RUN)

PARAMETER (NVAR=3)
PARAMETER (NBYTE=NVAR*4)
PARAMETER (NPACK=100)
PARAMETER (LENSTR=NPACK*NBYTE/2)

CHARACTER*1 CR

REAL*4 BUFF(NVAR,NPACK)
COMMON/DTA/ BUFF
INTEGER*2 WSTR(LENSTR)
EQUIVALENCE (WSTR(1),BUFF(1,1))

INTEGER IPOS,IREC
SAVE IPOS,IREC
DATA IPOS,IREC/1,1/

CR=CHAR(13)

IF (ISENS.EQ.0) THEN

DO 100 I=1,KEEP
UUT=TIME(I)/365.
WRITE(IW,'(3E13.5,A1)') UUT,OILRAT(I)*RSCALE,
c   + OILCM(I)*RSCALE,CR
+ OILCM(I)*RSCALE
100 CONTINUE

```

```

        RETURN

ENDIF

IF (KEEP.EQ.1) GOTO 300
IF (KEEP.EQ.-1) GOTO 400

DO 200 I=1, KEEP

    BUFF (1, IPOS)=TIME (I) /365.
    BUFF (2, IPOS)=OILRAT (I) *RSCALE
    BUFF (3, IPOS)=OILCM (I) *RSCALE

    IF (IPOS.EQ.NPACK) THEN
        WRITE (IW,REC=IREC) WSTR
        IREC=IREC+1
        IPOS=0
    ENDIF

    IPOS=IPOS+1

200    CONTINUE
    RETURN

C HERE WE HAVE A HEADER RECORD ASSUME [1.0>=CONTINUITY>0.0]
C WRITE NEGATIVE NUMBER

300    CONTINUE

C WRITE HEADER INFO

    BUFF (1, IPOS)=TIME (1) * (-1)
    BUFF (2, IPOS)=OILRAT (1)
    BUFF (3, IPOS)=OILCM (1)

    IF (IPOS.EQ.NPACK) THEN
        WRITE (IW,REC=IREC) WSTR
        IPOS=0
        IREC=IREC+1
    ENDIF

    IPOS=IPOS+1

C WRITE END OF FILE MARK

    BUFF (1, IPOS)=-1000.
    RETURN

400    CONTINUE

C HERE WE ARE DONE, WRITE EOF AND FLUSH BUFFER

    BUFF (1, IPOS)=-1000.
    WRITE (IW,REC=IREC) WSTR

    RETURN
END
SUBROUTINE PUT2 (IW, TIME, OILRAT, OILCM, RSCALE, KEEP, ISENS)
    DIMENSION TIME (KEEP), OILRAT (KEEP), OILCM (KEEP)

```

C WRITE AN ASCII FILE (SINGLE CASE RUN) OR A BINARY (MULTI CASE RUN)

```
PARAMETER (NVAR=3)
PARAMETER (NBYTE=NVAR*4)
PARAMETER (NPACK=100)
PARAMETER (LENSTR=NPACK*NBYTE/2)
```

```
CHARACTER*1 CR
```

```
REAL*4 BUFF(NVAR,NPACK)
COMMON/DTA1/ BUFF
INTEGER*2 WSTR(LENSTR)
EQUIVALENCE (WSTR(1),BUFF(1,1))
```

```
INTEGER IPOS,IREC
SAVE IPOS,IREC
DATA IPOS,IREC/1,1/
```

```
CR=CHAR(13)
```

```
IF (ISENS.EQ.0) THEN
```

```
    DO 100 I=1,KEEP
        UUT=TIME(I)/365.
        WRITE(IW,'(3E13.5,A1)') UUT,OILRAT(I)*RSCALE,
c      + OILCM(I)*RSCALE,CR
      + OILCM(I)*RSCALE
100    CONTINUE
        RETURN
```

```
ENDIF
```

```
IF (KEEP.EQ.1) GOTO 300
IF (KEEP.EQ.-1) GOTO 400
```

```
DO 200 I=1,KEEP
```

```
    BUFF(1,IPOS)=TIME(I)/365.
    BUFF(2,IPOS)=OILRAT(I)*RSCALE
    BUFF(3,IPOS)=OILCM(I)*RSCALE
```

```
    IF (IPOS.EQ.NPACK) THEN
        WRITE(IW,REC=IREC) WSTR
        IREC=IREC+1
        IPOS=0
    ENDIF
```

```
    IPOS=IPOS+1
```

```
200    CONTINUE
        RETURN
```

```
C HERE WE HAVE A HEADER RECORD ASSUME [1.0>=CONTINUITY>0.0]
C WRITE NEGATIVE NUMBER
```

```
300    CONTINUE
```

```
C WRITE HEADER INFO
```

```
    BUFF(1,IPOS)=TIME(1)*(-1)
```



```

      BUFF(2,IPOS)=OILRAT(1)
      BUFF(3,IPOS)=OILCM(1)

      IF(IPOS.EQ.NPACK) THEN
        WRITE(IW,REC=IREC) WSTR
        IPOS=0
        IREC=IREC+1
      ENDIF

      IPOS=IPOS+1

C WRITE END OF FILE MARK

      BUFF(1,IPOS)=-1000.
      RETURN

400  CONTINUE

C HERE WE ARE DONE, WRITE EOF AND FLUSH BUFFER

      BUFF(1,IPOS)=-1000.
      WRITE(IW,REC=IREC) WSTR

      RETURN
      END
      SUBROUTINE SEARCH ( IPT, JPT, LX, LY, IFND, JFND )
C                                     *I*  *I*  *I*  *I*  *O*  *O*
C
C -----
C
C           S E A R C H
C
C PERFORMS CONCENTRIC-SQUARES SEARCH OUTWARD FOR NEAREST POINT
C WITH STREAM TUBE MARK, RETURNING WITH ITS LOCATION (INDICES).
C -----
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'TUBE.INC'
C INCLUDE 'STREAM.INC'
C INCLUDE 'FILES.INC'
C
C IMIN = IPT
C JMIN = JPT
C IMAX = IPT
C JMAX = JPT
C DIST = LX+LY
C IFND = 0
C JFND = 0
C
C DO 7000  KNT = 1, 10000
C   IMIN = IMIN-1
C   JMIN = JMIN-1
C   IMAX = IMAX+1
C   JMAX = JMAX+1
C   IMIN = MAX0(IMIN,1)
C   JMIN = MAX0(JMIN,1)
C   IMAX = MIN0(IMAX,LX)
C   JMAX = MIN0(JMAX,LY)
C   LMAX = MAX0(IPT-IMIN,JPT-JMIN,IMAX-IPT,JMAX-JPT)

```

```

      SLEN = LMAX
      IF ( SLEN .GE. DIST )          GO TO 8000
C
      DO 3600 I = IMIN, IMAX
      IF ( INXST(I,JMIN) .LE. 0 )    GO TO 3400
      SQI = FLOAT(IPT-I)**2
      SQJ = FLOAT(JPT-JMIN)**2
      D = SQRT(SQI+SQJ)
      IF ( D .GT. DIST )            GO TO 3400
      DIST = D
      IFND = I
      JFND = JMIN
3400 CONTINUE
      IF ( INXST(I,JMAX) .LE. 0 )    GO TO 3600
      SQI = FLOAT(IPT-I)**2
      SQJ = FLOAT(JPT-JMAX)**2
      D = SQRT(SQI+SQJ)
      IF ( D .GT. DIST )            GO TO 3600
      DIST = D
      IFND = I
      JFND = JMAX
3600 CONTINUE
C
      DO 4000 J = JMIN, JMAX
      IF ( INXST(IMIN,J) .LE. 0 )    GO TO 3800
      SQI = FLOAT(IPT-IMIN)**2
      SQJ = FLOAT(JPT-J)**2
      D = SQRT(SQI+SQJ)
      IF ( D .GT. DIST )            GO TO 3800
      DIST = D
      IFND = IMIN
      JFND = J
3800 CONTINUE
      IF ( INXST(IMAX,J) .LE. 0 )    GO TO 4000
      SQI = FLOAT(IPT-IMAX)**2
      SQJ = FLOAT(JPT-J)**2
      D = SQRT(SQI+SQJ)
      IF ( D .GT. DIST )            GO TO 4000
      DIST = D
      IFND = IMAX
      JFND = J
4000 CONTINUE
C
      7000 CONTINUE
      CALL HALTER ( 'SEARCH', 7000 )
C
      8000 CONTINUE
C
      9900 RETURN
C  END  SEARCH
      END
      SUBROUTINE PROIL ( I, J, PO, BO, RSO, DENSO, VISO, NF, NREG)
C
C -----
C  PROIL -- CALCULATE OIL PVT PROPERTIES --
C          PO -- INPUT PRESSURE
C          BO -- CALCULATED OIL FORMATION VOLUME FACTOR
C          RSO - SOLUTION GOR -- ALWAYS 0 IN IDPM CALCULATIONS
C          DENSO - OIL PHASE DENSITY AT STANDARD CONDITIONS

```

```

C          VISO - OIL VISCOSITY, CP
C
C -----
C
C  INCLUDE 'PARAM.INC'
C  INCLUDE 'SIMUL.INC'
C
C  DIMENSION      BO(1), RSO(1), DENSO(1), VISO(1)
C  DENO= DENOIL*(1.0-CMPOIL*(REFPRE-PO))
C  BO(1)      = DENOST/DENO
C  RSO(1)     = 0.
C  DENSO(1)   = DENO
C  VISO(1)    = VISOIL
C  RETURN
C  END
C  SUBROUTINE PORE ( PVCORR, PVORIG, PRES, CR )
C
C -----
C
C  PORE -- CALCULATE THE PORE VOLUME OF THE CELL WITH PRESSURE - PRES
C  PVCORR -- PORE VOLUME AT INPUT PRESSURE , PRESS, CU. FT.
C  PVORIG -- PORE VOLUME AT REFERENCE PRESSURE, CU. FT.
C  PRES -- PRESSURE FOR CALCULATION, PSI
C  CR -- PORE VOLUME COMPRESSIBILITY, VOL/VOL/PSI
C
C -----
C
C  INCLUDE 'PARAM.INC'
C  INCLUDE 'SIMUL.INC'
C
C
C  PVX = PVORIG
C  PVCORR = PVX
C  CR = CROCK
C  IF ( CR .EQ. 0 ) RETURN
C  PVCORR = PVX * ( 1.0 - CR * ( REFPRE - PRES ) )
C  RETURN
C  END
C  SUBROUTINE REPLAC(A,B,N)
C
C -----
C
C  REPLAC --UTILITY ROUTINE TO REPLACE THE VALUES IN A WITH B
C  A -- OUTPUT VECTOR OF LENGTH N
C  B -- INPUT VECTOR TO SET A EQUAL TO
C  N -- NUMBER OF ELEMENTS TO BE REPLACED
C
C -----
C
C  DIMENSION A(1),B(1)
C  DO 1 I=1,N
C  1 A(I) = B(I)
C  RETURN
C  END
C  SUBROUTINE SATDEP ( I, J, RKO, RKW, RKG,
C  * PCOW, PCOG, SO, SW )
C
C -----
C
C  SATDEP-- SET UP THE CALLS TO CALCULATE WATER AND OIL RELATIVE

```

```

C          PERMEABILITIES, IN THE COEFFICIENT GENERATION THIS IS
C          PUT INTO A VECTOR , HERE THE CALL TO WATSAT IS MADE IN
C          SCALAR.
C          ARKO -- OIL RELATIVE PERM
C          ARKW -- WATER RELATIVE PERM
C          OTHER VALUES ARE RESERVED FOR FUTURE EXPANSION TO MULTI-
C          PHASE STREAMTUBE TYPE MODEL.

```

```

-----
C          PCOG= 0
C          PCOW= 0
C          RKG = 0
C          CALL WATSAT(I, J, SW, RKW, RKO )
C          RETURN
C          END
C          SUBROUTINE WATPR ( I, J, PW, BW, RSW, DENSW, VISW, NF, NREG )

```

```

-----
C          WATPR-- CALCULATE WATER PVT PROPERTIES -- SLIGHTLY COMPRESSIBLE
C          NO GAS SOLUBILITY.
C          PW -- INPUT PRESSURE, PSI
C          BW -- WATER FORMATION VOLUME FACTOR, RB/STB, AT PW
C          RSW -- SOLUTION GOR, ALWAYS ZERO
C          DENSW --DENSITY AT STANDARD CONDITIONS, LBM./CU.FT.
C          VISW --VISCOSITY AT PW, CP

```

```

-----
C          INCLUDE 'PARAM.INC'
C          INCLUDE 'SIMUL.INC'

```

```

C          DIMENSION      BW(1), RSW(1), DENSW(1), VISW(1)
C          DENW= DENWTR*(1.0-CMPWTR*(REFPRE-PW))
C          BW(1)      = DENWST/DENW
C          RSW(1)      = 0.
C          DENSW(1)    = DENW
C          VISW(1)     = VISWTR
100 RETURN
C          END
C          SUBROUTINE WATSAT ( I, J, SWF, XKRW, XKRO )

```

```

-----
C          THIS SUBROUTINE COMPUTES OIL/WATER RELATIVE PERMS

```

VARIABLE DEFINITIONS:

```

C          SWF      = FLOWING WATER SATURATION, FRACTION
C          XKRO     = OIL   RELATIVE PERMEABILITY AT SWF
C          XKRW     = WATER RELATIVE PERMEABILITY AT SWF
C          SWC      = CONNATE WATER SATURATION, FRACTION
C          SORW     = RESIDUAL OIL SATURATION, FRACTION
C          XKROE    = OIL   RELATIVE PERMEABILITY AT SWC
C          XKRWE    = WATER RELATIVE PERMEABILITY AT SORW
C          XNO      = OIL CURVE EXPONENT
C          XNW      = WATER CURVE EXPONENT
C          VCCN     = RESERVOIR CONTINUITY FRACTION

```

```

C -----
C
C   INCLUDE 'PARAM.INC'
C   INCLUDE 'STREAM.INC'
C
C   SORW= (1.-VCCN)*(1.-VSWC) + VCCN*VSORW
C
C ***** OIL RELATIVE PERM
C
C   UO      = (1.0-SWF-SORW)/(1.-VSWC-SORW)
C   XKRO    = 0.0
C   IF(UO .LT. 1.E-6) UO = 1.E-6
C   XKRO    = VVKROE * UO**VXNO
C   IF(XKRO .LT. 1.0E-19) XKRO = 0.0
C   IF(XKRO .GT. 1.0)      XKRO = 1.0
C
C ***** WATER RELATIVE PERM
C
C   UW      = (SWF-VSWC) / (1.-VSWC-SORW)
C   XKRW    = 0.0
C   IF(UW .LT. 1.E-6) UW = 1.E-06
C   XKRW    = VVKRWE * UW**VXNW
C   IF(XKRW .GT. 1.0) XKRW = 1.0
C   IF(XKRW .GT. 1.0E-19) GO TO 91
C   XKRW    = 0.0
91  RETURN
C   END
C   SUBROUTINE ZEROS(A,N)
C
C -----
C
C   ZEROS --ROUTINE TO INITIALIZE A VECTOR, A, OF LENGTH N TO 0.0
C
C -----
C
C   DIMENSION A(1)
C   DO 1 I = 1,N
1    A(I) = 0.
C   RETURN
C   END
C   SUBROUTINE ECONID
C
C -----
C
C   ECONID--SETUP ROUTINE FOR THE ECONOMICS CALCULATION. THIS ROUTINE
C           PERFORMS THE ROLE OF INTERFACING THE ECONOMICS THE STAND
C           ALONE ECONOMICS ROUTINES TO THE RESERVOIR ROUTINES THROUGH
C           MOVEMENT OF DATA BETWEEN COMMONS.
C
C -----
C
C   INCLUDE 'PARAM.INC'
C   INCLUDE 'SIMUL.INC'
C   INCLUDE 'STREAM.INC'
C   INCLUDE 'FILES.INC'
C   INCLUDE 'ECON.INC'
C   COMMON /LIFE/ IOPTS, IWLIFE
C   COMMON /IN/  IECON, IOPT, IAROPT, ICHK, ILIT,
C   * LYROPT, NLDP, NLayer, NSTUB, NBlock,
C   * TITL1(20), BO, BW, VISW, API, TEMP, GOR, SGG, PFORM, VDP,

```

```

* PHI, PERM, PAY, SWIT, CONCP, VISP, DSP, RRF, VPMB, VIMAX,
* XKPL, DEPTH, APAT, CP, QRES,
* TOTPV, TOTOIP
COMMON /LOCALE/ BTIMV,RVBC
C
C      IOPTS = -1
C      GOR= GORV/1000.
C      RVBC=RSCALE/1000.
C      IECON =1
C
C      DO CALCULATIONS FOR THREE CASES
C          IOPTS = 0 -- NON-INFILL CASE
C          IOPTS = 1 -- INFILL CASE
C          IOPTS = 2 -- INCREMENTAL OF INFILL OVER NON-INFILL
C
C      DO 9000 IVSB=1,3
C      IOPTS=IOPTS +1
C      IF (IOPTS .NE. 0) GO TO 8500
C
C      NON-INFILL CASE
C
C      DRILL ONE PRODUCER AND ONE INJECTOR FOR THIS CASE
C
C      WPP1=1
C      WPP2=1
C      WPP3=0
C      WPP4=0
C      TZERO = 0.0
C      CUMWS(1)=WATRAT(1)*RVBC*TTIME(1)
C      DO 310 I= 1,KEEP
C      TIMS(I)=TTIME(I)/365.25
C      CUMIB(I)=PVIN(I)*ORIGPV*RVBC
C      CUMOS(I)=OILCM(I)*RVBC
C      IF (I.GT.1) CUMWS(I)=CUMWS(I-1)+WATRAT(I)*RVBC*(TTIME(I)-TTIME(I-1))
C      CUMGS(I)=OILCM(I)*GOR*RVBC
C      EWCUT(I)=WCT(I)
C      310 CONTINUE
C      ITIM=KEEP
C      CDJR TIMINC=TIMS(KEEP)/365.25
C      TIMINC=TIMS(KEEP)
C      DEPTH= -VZT(1)
C      API=DENOST/62.4
C      API=(141.5 - 131.5*API)/API
C      CALL INEC(ITIM, IECON, DEPTH, ICHK,
C      & API, IOPTS, IWLIFE,
C      & PRICEI, FDC, FEQP, FOPR, FUEL, FSUR, FPLY, FCAU, FACT, CONCP, TZERO)
C      BTIMV = BTIM + INT(TTIME(NSTR)/365.25)
C      GO TO 7000
C
C      8500 IF (IOPTS .NE. 1) GO TO 8000
C
C      INFILL CASE
C
C      DRILL ONE PRODUCER AND CONVERT ONE PRODUCER TO INJECTION
C
C      EXCEPTION - FOR 9-SPOT INFILL, NO CONVERSION NEEDED
C
C      WPP1=0
C      WPP2=2
C      WPP3=0

```

```

WPP4=1
IF ( IPAT9V .NE. 0 ) WPP4=0
TZERO = TTIME(NSTR)/365.25
ITIM = NSTEP-NSTR
CUMWS(1)=WATRT1(NSTR+1)*RVBC*(TTIM1(NSTR+1)-TTIM1(NSTR))
IVS1 = 0
DO 320 I= NSTR+1,NSTEP
IVS1 = IVS1 + 1
TIMS(IVS1)=(TTIM1(I) - TTIM1(NSTR))/365.25
CUMIB(IVS1)=PVIN1(I)*ORIGPV*RVBC - PVIN1(NSTR)*ORIGPV*RVBC
CUMOS(IVS1)=OILCM1(I)*RVBC - OILCM1(NSTR)*RVBC
IF (IVS1.GT.1) CUMWS(IVS1)=CUMWS(IVS1-1)+WATRT1(I)*RVBC*
& (TTIM1(I)-TTIM1(I-1))
CUMGS(IVS1)=OILCM1(I)*GOR*RVBC - OILCM1(NSTR)*GOR*RVBC
EWCUT(IVS1)=WCT1(I)
320 CONTINUE
CALL INEC(ITIM, IECON, DEPTH, ICHK,
& API, IOPTS, IWLIFE,
& PRICEI, FDC, FEQP, FOPR, FUEL, FSUR, FPLY, FCAU, FACT, CONCP, TZERO)
GO TO 7000
C
8000 CONTINUE
C
C INCREMENTAL CASE -- INFILL OVER NON-INFILL
C
C DRILL ONE PRODUCER AND CONVERT ONE PRODUCER TO INJECTION
C
C EXCEPTION - FOR 9-SPOT INFILL, NO CONVERSION NEEDED
C
C ***** C A U T I O N *****
C SCHEME USED HERE TO STRIP OUT SIMULATOR DATA TO DO INCREMENTAL
C ECONOMICS DEPENDS ON THE TIME STEP SIZE FOR INFILL BEING EXACTLY
C HALF THAT FOR SIMULATING NON-INFILL. (SEE SUBR. -ACHECK-.)
C ***** C A U T I O N *****
C
WPP1=0
WPP2=2
WPP3=0
WPP4=1
IF ( IPAT9V .NE. 0 ) WPP4=0
TZERO = TTIME(NSTR)/365.25
IVS1=0
IWLIFE=TIMINC
ITIM = (NSTEP-NSTR)/2
CUMWS(1) = (WATRT1(NSTR+2) - WATRT1(NSTR+1))*RVBC*
& (TTIM1(NSTR+2)-TTIM1(NSTR))
DO 330 I= NSTR+2,NSTEP,2
IVS1 = IVS1 + 1
TIMS(IVS1)=(TTIM1(I)-TTIM1(NSTR))/365.25
CUMIB(IVS1)=(PVIN1(I)-PVIN(NSTR+IVS1))*ORIGPV*RVBC
CUMOS(IVS1)=(OILCM1(I)-OILCM(NSTR+IVS1))*RVBC
IF ( IVS1 .GT. 1 ) CUMWS(IVS1)= CUMWS(IVS1-1) +
& (WATRT1(I)-WATRT1(NSTR+IVS1))*RVBC*(TTIM1(I)-TTIM1(I-2))
CUMGS(IVS1)=(OILCM1(I)-OILCM(NSTR+IVS1))*GOR*RVBC
EWCUT(IVS1)=WCT1(I)
330 CONTINUE
CALL INEC(ITIM, IECON, DEPTH, ICHK,
& API, IOPTS, IWLIFE,
& PRICEI, FDC, FEQP, FOPR, FUEL, FSUR, FPLY, FCAU, FACT, CONCP, TZERO)
7000 CALL ECON(API, PRICEI, 0.1, VALUE, 1.0,

```

\$/METER

C	21	\$/STB/D	\$/CU M/D
C	22	\$/BBL	\$/CU M
C	23	\$/KWHR	\$/KJ
C	24	\$/MCF	\$/CU M
C	25	MSCF/B	CU M/D
C	26	SCF/STB	CU M/CU M
C	27	MLB	MKG
C	28	PSI/FT	KPA/M
C	29	RB/D	CU M/D
C	30	\$/LB	\$/KG
C	31	MMB/YR	MM CU M/YR
C	32	BBL/BBL	CU M/CU M
C	33	LB/AC FT	G/M3
C	34	STB/LB	CU M/KG
C	35	LB/D	KG/D
C	36	B/D/PSI	M3/D/KPA
C	37	MBBL/D	M CU M/D
C	38	LB/CU.FT	KG/M3
C	39	BTU/LB-DEG F	KJ/KG-DEG C
C	40	SQ.FT/HR	M2/HR
C	41	1/DEG. F	1/DEG. C
C	42	1/PSI	1/KPA
C	43	STB	CU M
C	44	RES. BBL	CU M
C	45	RB/MCF	M3/M3
C	46	INCHES	CM
C	47	BTU/HR-FT2-DEG.F	KJ/HR-M2-DEG. C
C	48	CU. FT/LB	CU M/KG
C	49	BTU/LB	KJ/KG
C	50	LBM/HR	KG/HR
C	51	BCWE/DAY	M3 CWE/DAY
C	52	B/D/A/FT	M3/D/H/M
C	53	MMBTU/FT	MM KJ/M
C	54	MMBTU/D	MM KJ/D
C	55	MCF/D	CU M/D
C	56	PSI	KPA
C	57	MBCWE	M M3 CWE
C	58	BTU/UNIT	KJ/UNIT
C	59	\$/BWPD	\$/M3 WATER/D
C	60	\$/BOPD	\$/M3 OIL/D
C	61	\$/BCWE	\$/M3 CWE
C	62	B/BCWE	M3/M3 CWE
C	63	MLB/HR	MKG/HR

C		1	2	3	4	1	2	3	4
	DATA NEN1/4HFEET, 4H	, 4H	, 4H	, 4H	, 4H	, 4HPSIA, 4H	, 4H	, 4H	,
3	4HDEG , 4HF	, 4H	, 4H	, 4H	, 4H	, 4HRB/S, 4HTB	, 4H	, 4H	,
5	4HACRE, 4HS	, 4H	, 4H	, 4H	, 4H	, 4HMM.S, 4HTB	, 4H	, 4H	,
7	4HMM.R, 4HES B, 4H	, 4H	, 4H	, 4H	, 4H	, 4HHP , 4H	, 4H	, 4H	,
9	4HMSTB, 4H	, 4H	, 4H	, 4H	, 4H	, 4HMSCF, 4H/STB, 4H	, 4H	, 4H	,
1	4HSTB/, 4HMSCF, 4H	, 4H	, 4H	, 4H	, 4H	, 4HMSCF, 4H/D	, 4H	, 4H	,
3	4HMSCF, 4H/FT3, 4H	, 4H	, 4H	, 4H	, 4H	, 4HSTB/, 4HD	, 4H	, 4H	,
5	4HMMSC, 4HF	, 4H	, 4H	, 4H	, 4H	, 4H\$/HP, 4H	, 4H	, 4H	,
7	4H\$/MS, 4HCF/D, 4H	, 4H	, 4H	, 4H	, 4H	, 4H\$/BB, 4HL/D	, 4H	, 4H	,
9	4H\$/AC, 4HRE	, 4H	, 4H	, 4H	, 4H	, 4H\$/FO, 4HOT	, 4H	, 4H	,
1	4H\$/ST, 4HB/D	, 4H	, 4H	, 4H	, 4H	, 4H\$/BB, 4HL	, 4H	, 4H	,
3	4H\$/KW, 4HHR	, 4H	, 4H	, 4H	, 4H	, 4H\$/MC, 4HF	, 4H	, 4H	,
5	4HMSCF, 4H/B	, 4H	, 4H	, 4H	, 4H	, 4HSCF/, 4HSTB	, 4H	, 4H	,
7	4HMLB , 4H	, 4H	, 4H	, 4H	, 4H	, 4HPSI/, 4HFT	, 4H	, 4H	,
9	4HRB/D, 4H	, 4H	, 4H	, 4H	, 4H	, 4H\$/LB, 4H	, 4H	, 4H	,

[illegible]

```

C          *****
C          *   SET IU TO ALPHA NAME OF UNIT FOR PRINTOUT   *
C          *****
          IF (METRIC .NE. 0) GO TO 20

C
C          ENGLISH NAME
C
          DO 10 I = 1, 4
10      IU(I) = NENG(I, INAME)
          GO TO 100

C
C          METRIC NAME
C
          DO 20 I = 1, 4
20      IU(I) = NMET(I, INAME)

C          *****
C          *   IF METRIC CONVERT VALUE TO METRIC VALUE   *
C          *****
31      IF (INAME .EQ. 4 ) GO TO 100

100      RETURN
          END
          SUBROUTINE INEC(ITIM, IECON, DEPTH, ICHK, API, IOPTS, IWLIFE,
& PRICEI, FDC, FEQP, FOPR, FUEL, FSUR, FPLY, FCAU, FACT, CONCP, TZERO)

C
C          -----
C          INEC: READ ECONOMIC CASE CONTROLS
C          -----

          INCLUDE 'PARAM.INC'
          INCLUDE 'FILES.INC'
          INCLUDE 'ECON.INC'
          COMMON /LIF/ LPAT
          COMMON /LOCALE/ BTIMV, RVBC

C          DIMENSION DNAME1(4), DNAME2(4), DNAME3(4), DNAME4(4), DNAME5(4),
+              DNAME6(4), DNAME7(4), DNAME8(4), DNAME9(4), DNAMEA(4)

C          UNIT = 1000.
          READ (IR, 8000, END=9999) TITL
8000      FORMAT(20A4)
          CALL TITLE(TITL)

C          ***** READ ECONOMIC CASE CONTROLS
C          SWITCH IDEBT=0 IF NO BORROWED MONEY
C          SWITCH IDEBT=1 IF BORROWED MONEY (THEN CARD
C          FOR DEBT DATA WILL BE READ)
          READ (IR, *) M, ISTATE, IDIST, IOUT, IFIT, IDAT, NCT, NCI, IDISC,
1      ISO, IPLIF, IDEBT
          IF (IDEBT.NE.0) READ (IR, *) PCTDBT, DBTINT, NYRRPY, NYPAID

C          DO 19 KZ = 1, 50
          MUVO(KZ) = 0.0
          MUVG(KZ) = 0.0
          MUVW(KZ) = 0.0
          MUVI(KZ) = 0.0

```

```

MUPO(KZ) = 0.0
MUPG(KZ) = 0.0
MUPI(KZ) = 0.0
MUPP(KZ) = 0.0
MUWO(KZ) = 0.0
MUFO(KZ) = 0.0
MUOPC(KZ) = 0.0
MUTR(KZ) = 0.0
MUCT(KZ) = 0.0
MUCI(KZ) = 0.0
MUDB(KZ) = 0.0
MURP(KZ) = 0.0
MUIN(KZ) = 0.0
MUPB(KZ) = 0.0
SIGVO(KZ) = 0.0
SIGPO(KZ) = 0.0
SIGPG(KZ) = 0.0
SIGPI(KZ) = 0.0
SIGFO(KZ) = 0.0
SIGTR(KZ) = 0.0
SITRT(KZ) = 0.0
SITRI(KZ) = 0.0
SIGOPC(KZ) = 0.0
SIGPP(KZ) = 0.0

```

```

19 CONTINUE
C ***** COMPUTE ANNUAL PATTERN VOLUMES AND INITIALIZE
WOR = 0.
RS = 0.
COS = 0.
CGS = 0.
CWS = 0.
CWIS = 0.
CIS = 0.
CPS = 0.0
CPBS = 0.0
DO 20 I=1,50
VOL(I) = 0.0
VOM(I) = 0.0
VOH(I) = 0.0
VGM(I) = 0.0
VWM(I) = 0.0
VIM(I) = 0.0
VPM(I) = 0.0
VPB(I) = 0.0
POL(I) = 0.0
POM(I) = 0.0
POH(I) = 0.0
PGL(I) = 0.0
PGM(I) = 0.0
PGH(I) = 0.0
PIL(I) = 0.0
PIM(I) = 0.0
PIH(I) = 0.0
PPL(I) = 0.0
PPM(I) = 0.0
PPH(I) = 0.0
OPCL(I) = 0.0
OPCM(I) = 0.0
OPCH(I) = 0.0
TRPL(I) = 0.0

```

```

TRPM(I) = 0.0
TRPH(I) = 0.0
CTPL(I) = 0.0
FOCL(I) = 0.0
FOCM(I) = 0.0
FOCH(I) = 0.0
CTCL(I) = 0.0
CTCM(I) = 0.0
CTCH(I) = 0.0
CICL(I) = 0.0
CICM(I) = 0.0
CICH(I) = 0.0
CTPM(I) = 0.0
CTPH(I) = 0.0
CIPL(I) = 0.0
CIPM(I) = 0.0
CIPH(I) = 0.0
OILR(I) = 0.0
VOS(I) = 0.0
AOVH(I) = 0.0
VOP(I) = 0.0
VGP(I) = 0.0
VWP(I) = 0.0
VIP(I) = 0.0
VPBP(I) = 0.0
PATI(I) = 0.0
YR = I
CO = SDINT(TIMES,CUMOS,ITIM,YR)
CG = SDINT(TIMES,CUMGS,ITIM,YR)
CW = SDINT(TIMES,CUMWS,ITIM,YR)
CPB= SDINT(TIMES,CUMIB,ITIM,YR)
VWCT(I)= SDINT(TIMES,EWCUT,ITIM,YR)
VOP(I) = CO-COS
VGP(I) = CG-CGS
VWP(I) = CW-CWS
VPBP(I) = CPB-CPBS
IF (VPBP(I).LT.0.) VPBP(I)=0.0
CPBS = CPB
COS = CO
CGS = CG
CWS = CW

```

20 CONTINUE

C

C

C

***** READ CASE INPUT DATA AND CHECK FOR DEFAULTS

C

```

READ(IR,*) CWAT,CWCAP,WOCOST,WTCOST
READ(IR,*) WCAP,UNCO,COSTRT
READ(IR,*) XDR,XINF,XROY,XSEV,XFIT,XTCR,DTIM,XSTX
READ(IR,*) XWPT,WPHO,EPHO,BTIM,BPOW
READ(IR,*) ESCPO,ESCPG,ESCFO,
1    ESCWT,ESCWI,ESCWO

```

C

C

```

***** PROJECT PATTERN SCHEDULE
READ(IR,*) (PATI(I), I=1,M)

```

C

C

```

***** READ PRICE AND COST DATA
IF(IDAT.LE.0) GO TO 35
READ(IR,*) POL(1),POM(1),POH(1)
READ(IR,*) PGL(1),PGM(1),PGH(1)

```

```

      READ(IR,*) FOCL(1),FOCM(1),FOCH(1)
      READ(IR,*) OPCL(1),OPCM(1),OPCH(1)
C
C      ***** READ PATTERN CAPITAL SCHEDULE
35 IF(NCT.LE.0) GO TO 44
      DO 40 I=1,NCT
40 READ(IR,*) ICT,CTPL(ICT),CTPM(ICT),CTPH(ICT)
44 IF(NCI.LE.0) GO TO 50
      DO 45 I=1,NCI
45 READ(IR,*) ICI,C IPL(ICI),CIPM(ICI),CIPH(ICI)
C
C-----
C      ***** INITIALIZE VALUES AND DEFAULTS
C-----
      50 IF(ICHK.NE.0) RETURN
C
C
C      FIND MAXIMUM ANNUAL WATER INJECTION RATE, WMAX
8885 WMAX = 0.0
      DO 51 I = 1, M
      IF(VBPB(I) .GT. WMAX) WMAX = VBPB(I)
51 CONTINUE
C
C      PRICE RELATED ENERGY FACTORS
C
      PRICEI = POM(1)
      IF(PRICEI .LE. 0.0) PRICEI = 30.00
      CALL ECFTR(PRICEI,
& FDC,FEQP,FOPR,FUEL,FSUR,FPLY,FCAU,FACT , ISTATE)
C
      CALL CHEKE(ITIM,DEPTH,WMAX,API)
C
C
C      ***** WRITE CASE CONDITIONS
      WRITE(IW,9350)
9350 FORMAT(// 2X,13HECONOMIC DATA / 2X, 13(1H-) )
      CALL STCDE (JST , ISTATE)
      CALL UOUT (DEPTH,1,1,1,DNAME1,1,METRIC)
      WRITE(IW,9351) M,JST,IDIST,IOUT,IFIT,IDISC,IDEP,
1 IPLIF,DEPTH ,DNAME1
      WSUM = WPP1 + WPP2 + WPP3 + WPP4
      IF (WSUM .EQ. 0 ) GO TO 9012
      WRITE (IW,93513) WPP1,WPP2,WPP3,WPP4
9012 WRITE(IW,93510)
1 WCAP,COSTRT,UNCO
9351 FORMAT(
1 3X,37HNUMBER OF PROJECT YEARS ..... , I8 /
1 3X,37HSTATE CODE ..... , 4X,A4 /
1 3X,37HDISTRICT CODE ..... , I8 /
1 3X,37HPRINT CONTROL ..... , I8,8H IOUT /
1 3X,37HFEDERAL INCOME TAX OPTION ..... , I8,8H IFIT /
1 3X,37HDISCOUNTING METHOD ..... , I8,8H IDISC /
1 3X,37HDEPRECIATION METHOD ..... , I8,8H IDEP /
1 3X,37HPROJECT ECONOMIC LIFE METHOD ..... , I8,8H IPLIF /
1 3X,37HRESERVOIR DEPTH ..... ,F10.1,2X,4A4 )
93513 FORMAT(
1 3X,37HINJECTORS DRILLED PER PATTERN (WPP1) ..,F10.2 /
1 3X,37HPRODUCERS DRILLED PER PATTERN (WPP2) ..,F10.2 /
1 3X,37HCONVTD PRIMARY PROD PER PAT (WPP3) ... ,F10.2 /
1 3X,37HCONVTD PROD TO INJ PER PAT (WPP4) ....,F10.2 )

```

```

93510 FORMAT(
  1 3X,37HNO. OF MONTHS WORKING CAPITAL .....F10.2,10H      /
  1 3X,37HPROJECT STARTUP COSTS .....F10.1,10H    M$      /
  1 3X,37HOIL RATE UNCERTAINTY .....F10.4,10H    FRACTION )
  IF (IDEBT.EQ.0)WRITE (IW, 93511)
93511 FORMAT(
  1 3X,37HPERCENT OF CAPITAL BORROWED.....,9X,1H0,8H PERCENT)
  IF (IDEBT.NE.0)WRITE (IW, 93512)PCTDBT,DBTINT,NYRRPY,NYPAID
93512 FORMAT(
  1 3X,37HPERCENT OF CAPITAL BORROWED.....,F10.1,9H    PERCENT/
  1 3X,37HINTEREST RATE ON DEBT.....,F10.2,9H    PERCENT/
  1 3X,37HFIRST YEAR OF PRINCIPAL REPAYMENT.....,I10/
  1 3X,37HLAST YEAR OF PRINCIPAL REPAYMENT.....,I10)
  WRITE (IW, 9352) XDR,XINF,XROY,XSEV,XFIT,XTCR
  IF (IDEP .EQ. 0) WRITE (IW, 93521) DTIM
  IF (IDEP .GT. 0) WRITE (IW, 93522)
  CALL UOUT (BPOW,1,2,0,DNAME1,22,METRIC)
  WRITE (IW, 93523) XSTX,XWPT,WPHO,EPHO,BTIM,BPOW,DNAME1
9352 FORMAT(// 2X,20HTAXES AND ESCALATION / 2X,20(1H-) /
  1 3X,37HDISCOUNT RATE .....F10.3,10H    FRACTION/
  1 3X,37HINFLATION RATE .....F10.3,10H    FRACTION/
  1 3X,37HROYALTY RATE .....F10.3,10H    FRACTION/
  1 3X,37HSEVERANCE TAX RATE .....F10.3,10H    FRACTION/
  1 3X,37HFEDERAL INCOME TAX RATE .....F10.3,10H    FRACTION/
  1 3X,37HINVESTMENT TAX CREDIT .....F10.3,10H    FRACTION)
93521 FORMAT(
  1 3X,36HDEPRECIATION TIME (STRAIGHT LINE)....,F10.2,10H    YEARS  )
93522 FORMAT(
  1 3X,37HACRS DEPRECIATION SCHEDULE USED..... )
93523 FORMAT(
  1 3X,37HSTATE INCOME TAX RATE .....F10.3,10H    FRACTION/
  1 3X,37HWINDFALL EXCISE TAX RATE .....F10.3,10H    FRACTION/
  1 3X,37HWINDFALL PHASE OUT START DATE .....F10.0,10H      /
  1 3X,37HWINDFALL PHASE OUT END DATE .....F10.0,10H      /
  1 3X,37HPROJECT START DATE .....F10.0,10H      /
  1 3X,37HBASE OIL PRICE FOR WINDFALL TAX .....F10.2,2X,4A4  )
  WRITE (IW, 9355)
  1 ESCPO,ESCPG,ESCFO
9355 FORMAT(
  1 3X,37HOIL PRICE ESCALATION RATE .....F10.3,10H    FRACTION/
  1 3X,37HGAS PRICE ESCALATION RATE .....F10.3,10H    FRACTION/
  1 3X,37HOPERATING COST ESCALATION RATE .....F10.3,10H    FRACTION)

```

C

C ***** WRITE MOST LIKELY VALUES

WRITE (IW, 9450)

```

9450 FORMAT(1H1 // 2X,16HPRICES AND COSTS ,
  1 36X,7H LOW , 13H MOST-LIKELY, 10H HIGH /
  2 2X,16(1H-),
  3 36X,7H-----, 13H -----, 10H ----- )
  DUPPL = PPL(1) * FPLY
  DUPPM = PPM(1) * FPLY
  DUPPH = PPH(1) * FPLY
  DUFOCL= FOCL(1) * FOPR
  DUFOCM= FOCM(1) * FOPR
  DUFOCH= FOCH(1) * FOPR
  DUOPCL= OPCL(1) * FOPR
  DUOPCM= OPCM(1) * FOPR
  DUOPCH= OPCH(1) * FOPR
  DUTRPL= TRPL(1) * FOPR
  DUTRPM= TRPM(1) * FOPR

```



```

DUTRPH= TRPH(1) * FOPR
DUWO = WOCOST * FOPR
DUWTC = WTC(1) * FOPR
CALL UOUT (POL(1),1,2,0,DNAME1,22,METRIC)
CALL UOUT (PGL(1),1,3,1,DNAME2,24,METRIC)
CALL UOUT (DUPPL,1,10,1,DNAME3,30,METRIC)
CALL UOUT (DUOPCL,1,2,0,DNAME4,22,METRIC)
CALL UOUT (DUTRPL,1,2,0,DNAME5,22,METRIC)
CALL UOUT (DUWTC,1,2,0,DNAME6,22,METRIC)
WRITE(IW,9451)
1 (DNAME1(I),I=1,2),POL(1), POM(1), POH(1),
2 (DNAME2(I),I=1,2),PGL(1), PGM(1), PGH(1),
5 DUFOCL,DUFOCM,DUFOCH,
6 (DNAME4(I),I=1,2),DUOPCL,DUOPCM,DUOPCH,
8 DUWO, (DNAME6(I),I=1,2),DUWTC
9451 FORMAT(
1 3X,37HOIL PRICE .....2X,2A4 ,3F11.2/
1 3X,37HGAS PRICE .....2X,2A4 ,3F11.2/
1 3X,37HFIXED OPERATING COST PER PATTERN ....,10H $/YR ,3F11.0/
1 3X,37HVARIBLE OPERATING COST .....2X,2A4 ,3F11.3/
1 3X,37HWELL WORKOVER COST PER PATTERN .....10H $/YR ,
1 11X, F11.0 /
1 3X,37HPROD WATER TREATING/DISPOSAL COST ...,2X,2A4 ,
1 11X, F11.3 )
C
FOCPL = FOCL(1)
FOCPM = FOCM(1)
FOCPH = FOCH(1)
FOCL(1) = 0.0
FOCM(1) = 0.0
FOCH(1) = 0.0
C
DO 470 J=1,MYR
AOVH(J) = AOVH(J) + AOVH1 * PATI(J)
470 CONTINUE
C
IF (NCT .EQ. 0 ) GO TO 4701
WRITE (IW ,4702)
4702 FORMAT (//,20X,'TANGIBLE INVESTMENT SCHEDULE, $'
X // 10X,'YEAR LOW MOST LIKELY HIGH '
X / 10X,'-----' )
DO 4710 I=1,NCT
WRITE (IW ,4703) I,CTPL(I),CTPM(I),CTPH(I)
4710 CONTINUE
4703 FORMAT (9X,I5,3F15.2)
C
4701 CONTINUE
IF (NCI .EQ. 0 ) GO TO 4801
WRITE (IW ,4802)
4802 FORMAT (//,20X,'INTANGIBLE INVESTMENT SCHEDULE, $'
X // 10X,'YEAR LOW MOST LIKELY HIGH '
X / 10X,'-----' )
DO 4810 I=1,NCI
WRITE (IW ,4803) I,C IPL(I),CIPM(I),CIPH(I)
4810 CONTINUE
4803 FORMAT (9X,I5,3F15.2)
4801 CONTINUE
C
C ESTIMATE INDIVIDUAL PATTERN LIFE, LPAT
LPAT = 1

```

```

DO 490 J=1,MYR
C   ESTIMATE DIRECT REVENUES, M$
    REV = (POM(1) * VOP(J) + PGM(1) * VGP(J))
    & * (1. - XROY) * (1. - XSEV)
C   ESTIMATE DIRECT COSTS INCLUDING OVERHEAD OF 20%, M$
    COST= 1.2 * ( ( WTC(1)*VWP(J) + OPCM(1)*VOP(J) +
    & FOCMP/UNIT + WOCOST/UNIT ) * FOPR )
C
    IF (REV .GE. COST) LPAT = J
490 CONTINUE
C
C   CALCULATE PROJECT PERFORMANCE FROM PATTERN DATA
C
    RMAX = 0.0
    DO 550 J = 1, MYR
    SUMP = PATI(J)
    K = 0
    LYR = J + LPAT - 1
    IF (LYR .GT. MYR) LYR = MYR
    DO 500 I = J, LYR
    K = K+1
    VOL(I) = VOL(I) + VOP(K)*SUMP*(1.-UNCO)
    VOH(I) = VOH(I) + VOP(K)*SUMP*(1.+UNCO)
    VOM(I) = VOM(I) + VOP(K)*SUMP
    VGM(I) = VGM(I) + VGP(K)*SUMP
    VWM(I) = VWM(I) + VWP(K)*SUMP
    VPB(I) = VPB(I) + VPBP(K)*SUMP
    FOCL(I) = FOCL(I) + FOCPL*SUMP
    FOCM(I) = FOCM(I) + FOCPM*SUMP
    FOCH(I) = FOCH(I) + FOCPH*SUMP
C
C   ELIMINATE FIXED OPERATING COSTS IF INCREMENTAL INFILL FLOOD
C   BEFORE END OF WATERFLOOD, IWFLIFE
    IF (IOPTS .GT. 1 .AND. I .LE. IWFLIFE) FOCL(I) = 0.0
    IF (IOPTS .GT. 1 .AND. I .LE. IWFLIFE) FOCM(I) = 0.0
    IF (IOPTS .GT. 1 .AND. I .LE. IWFLIFE) FOCH(I) = 0.0
C
    CTCL(I) = CTCL(I) + CTPL(K)*SUMP*FDC/FEQP
    CTCM(I) = CTCM(I) + CTPM(K)*SUMP*FDC/FEQP
    CTCH(I) = CTCH(I) + CTPH(K)*SUMP*FDC/FEQP
    CICL(I) = CICL(I) + CIPL(K)*SUMP*FDC/FEQP
    CICM(I) = CICM(I) + CIPM(K)*SUMP*FDC/FEQP
500 CICH(I) = CICH(I) + CIPH(K)*SUMP*FDC/FEQP
    IF (VPB(J) .GT. RMAX) RMAX = VPB(J)
550 CONTINUE
    IF (RMAX .LT. 0.0 ) RMAX = 0.0
C
C
    RMAX = RMAX / 365.
    IF (CWAT .LT. 0.0) CWAT = 0.0
    IF (CWCAP .LE. 0.0) CWCAP = 365. * RMAX / UNIT
    IF (CWCAP .GT. 0.0) CWAT = CWAT * RMAX * 365. / UNIT / CWCAP
    RMAX1 = RMAX
    CCHM = 0.0
C   INCLUDE CAPITAL IN FIRST YEAR
    CTCL(1) = CTCL(1) + 0.8 * ( CWAT ) * UNIT
    CTCM(1) = CTCM(1) + ( CWAT ) * UNIT
    CTCH(1) = CTCH(1) + 1.2 * ( CWAT ) * UNIT
C
C   CALCULATE RELEASED OIL FROM SECONDARY OIL RATE AND STATUTORY DECLIN

```

```

C      FACTOR = 1.0 - .12 * (BTIM - 1979.)
      IF (FACTOR .LT. 0.0) FACTOR = 0.0
      IF (FACTOR .GT. 1.0) FACTOR = 1.0
C      OILC IS BASE RATE AT BEGINNING OF PROJECT ADJUSTED FROM BASE RATE
      OILC = OILB * FACTOR
C      OILD DEFINED AS ANNUAL REDUCTION IN BASE RATE ONCE PROJECT BEGINS
      OILD = OILB * 12. * 0.025
C      CORRECT OILC FOR MID-YEAR VALUE
      OILC = OILC + OILD / 2.
C
C      CALCULATE OIL VOLUME RELEASED, (OILR,BBLs) INCLUDING TERTIARY OIL
C      WPT PAID AT XWPT LATER FOR THE TERTIARY OIL VOLUME, VOM(I)
      DO 625 I=1,MYR
      OILC = OILC - OILD
      IF (OILC .LE. 0.0) OILC = 0.0
      OILR(I) = VOS(I) + VOM(I) - OILC
      IF (OILR(I) .LE. 0.0) OILR(I) = 0.0
625 CONTINUE
C
C
C      ***** WRITE PROJECT SCHEDULE
      IF (IOUT.LE.0) GO TO 751
      WRITE(IW,9601)
9601 FORMAT( // ' NOTE..      -PATTERN- HERE ALWAYS REFERS TO THE',
*          ' PRE-INFILL FULL 5-SPOT PATTERN' //
*          /1H0,25X,'ANNUAL PATTERN AND PROJECT VOLUMES PRODUCED'
1 / 26X,46(' ')/)
      WRITE(IW,9702) LPAT
9702 FORMAT(2X, 'PROJECT LIFE IS ', I2, ' YEARS')
      IF ( TZERO .NE. 0.0 ) WRITE (IW,9703) TZERO
9703 FORMAT(2X, 'PROJECT INITIATED AT ',
*          F5.2, ' YEARS OF NON-INFILL PROJECT')
      CALL UOUT (VOP,MYR,2,1,DNAME1,9,METRIC)
      CALL UOUT (VGP,MYR,3,0,DNAME2,15,METRIC)
      CALL UOUT (VWP,MYR,2,1,DNAME3,9,METRIC)
      CALL UOUT (VOM,MYR,2,1,DNAME5,9,METRIC)
      CALL UOUT (VGM,MYR,3,0,DNAME6,15,METRIC)
      CALL UOUT (VWM,MYR,2,1,DNAME7,9,METRIC)
      CALL UOUT (VOS,MYR,2,1,DNAME9,9,METRIC)
      CALL UOUT (OILR,MYR,2,1,DNAMEA,9,METRIC)
      WRITE(IW,9650) (DNAME1(I),I=1,2), (DNAME2(I),I=1,2),
+                   (DNAME3(I),I=1,2),
+                   (DNAME5(I),I=1,2), (DNAME6(I),I=1,2),
+                   (DNAME7(I),I=1,2)
9650 FORMAT( /
1 8X,'----- PATTERN -----',
1 6X,'----- PROJECT -----' /
2 10X,'OIL,',6X,'GAS,',6X,'WATER,',2X,
* 'YEAR-END INJ WTR,',4X, ' PATTERNS PATTERNS ', 4X,
2 'OIL,',6X,'GAS,',4X,'WATER,' /
+ 2X,'YEAR',4X,2A4,2X,2A4,2X,2A4,
* ' WTR-CUT      MSTB ',4X, ' INITIATD      TOTAL ', 4X,
* 2A4,2X,2A4,2X,2A4 /
5 2X,4H----,5(10H -----),4X,5(10H -----) )
9651 FORMAT(2X,I3, 3F10.1, F10.4, F10.1, 4X, 2F10.0, 3F10.1)
      SUMP = 0.
      DO 650 I=1,MYR
      SUMP = SUMP + PATI(I)
      IF (I.GT.LPAT) SUMP = SUMP - PATI(I-LPAT)

```

```

650 WRITE(IW,9651) I,VOP(I),VGP(I),VWP(I),
      1 VWCT(I),VPBP(I),PATI(I),SUMP,VOM(I),VGM(I),VWM(I)
C
      CALL UOUT (RMAX1,1,2,1,DNAME1,37,METRIC)
      IF ( IOPTS .LE. 1 ) WRITE (IW,96901) RMAX1,DNAME1
96901 FORMAT (/ ' MAXIMUM INJECTION RATE IS ',F8.3,1X,4A4)
C
C ***** WRITE MAJOR PROJECT COSTS AND SCHEDULE
DPP1 = CINJ
IF (WPP1 .EQ. 0.0 ) DPP1 = 0.0
DPP2 = CEQP
IF (WPP2 .EQ. 0.0 ) DPP2 = 0.0
DPP3 = CSEC
IF (WPP3 .EQ. 0.0 ) DPP3 = 0.0
DPP4 = CNVT
IF (WPP4 .EQ. 0.0 ) DPP4 = 0.0
WRITE(IW,9690)
9690 FORMAT(1H1,1X,19HMAJOR CAPITAL COSTS / 2X, 19(1H- )
      CALL UOUT (CSCAP,1,2,1,DNAME1,31,METRIC)
      CALL UOUT (CWCAP,1,2,1,DNAME2,31,METRIC)
      WRITE(IW,9691) DPP1,DPP2,DPP3,DPP4,CREP
      +      , CWCAP, DNAME2, CWAT
9691 FORMAT(
      1 3X,37HINJECTOR DRILLING COST .....F10.0,10H $/WELL /
      1 3X,37HPRODUCER EQUIPMENT COST .....F10.0,10H $/WELL /
      1 3X,37HCOST TO UPGRADE SECONDARY PROD .....F10.0,10H $/WELL /
      1 3X,37HCOST TO CONVERT PROD TO INJ .....F10.0,10H $/WELL /
      1 3X,37HCOST TO UPGRADE TO SEC. OPERATIONS ..F10.0,10H $/WELL /
      1 3X,37HCAPACITY OF WATER INJ PLANT .....F10.1,2X,4A4 /
      1 3X,37HCAPITAL FOR WATER INJ PLANT .....F10.1,9H M$ )
8801 CONTINUE
      WRITE(IW,9701)
9701 FORMAT(///15X,'PROJECT CAPITAL SCHEDULE - MOST LIKELY'
      1 / 15X, 35(1H- ) /)
      CALL UOUT (VPM,MYR,10,0,DNAME1,27,METRIC)
      WRITE(IW,9750)
9750 FORMAT(
      1 9X,17H--- PATTERN $ ---, 2X,8HPATTERNS,
      2 2X,18H--- PROJECT M$ --- /
      3 2X,4HYEAR, 10H TANGIBLE, 10H INTANGBL, 10H INITIATD,
      5 10H TANGIBLE, 10H INTANGBL /
      5 2X,4H---,3(10H -----),2(10H -----) )
9751 FORMAT(2X,I3, 1X, F9.1,F10.1, 3F10.0)
      DO 750 I=1,MYR
      UCTCM = CTCM(I)/UNIT
      UCICM = CICM(I)/UNIT
      750 WRITE(IW,9751) I,CTPM(I),CIPM(I),PATI(I),
      1 UCTCM,UCICM
      751 CONTINUE
C
C ***** ESCALATE EACH VARIABLE
SUMP = 0.0
WWOC = WO(1)
DO 700 I=1,MYR
VOL(I) = VOL(I)*UNIT
VOH(I) = VOH(I)*UNIT
VOM(I) = VOM(I)*UNIT
VGM(I) = VGM(I)*UNIT
VWM(I) = VWM(I)*UNIT
VPM(I) = VPM(I)*UNIT

```

```

VPB(I) = VPB(I)*UNIT
SUMP = SUMP + PATI(I)
IF(I.GT.LPAT) SUMP = SUMP - PATI(I-LPAT)
POL(I) = POL(1)*(1+ESCPO)**(I-1)
POM(I) = POM(1)*(1+ESCPO)**(I-1)
POH(I) = POH(1)*(1+ESCPO)**(I-1)
PGL(I) = PGL(1)*(1+ESCPG)**(I-1)
PGM(I) = PGM(1)*(1+ESCPG)**(I-1)
PGH(I) = PGH(1)*(1+ESCPG)**(I-1)
PIL(I) = PIL(1)*(1+ESCPI)**(I-1)
PIM(I) = PIM(1)*(1+ESCPI)**(I-1)
PIH(I) = PIH(1)*(1+ESCPI)**(I-1)
PPL(I) = PPL(1)*(1+ESCPI)**(I-1)
PPM(I) = PPM(1)*(1+ESCPI)**(I-1)
PPH(I) = PPH(1)*(1+ESCPI)**(I-1)
FOCL(I) = FOCL(I)*(1+ESCFO)**(I-1)
FOCM(I) = FOCM(I)*(1+ESCFO)**(I-1)
FOCH(I) = FOCH(I)*(1+ESCFO)**(I-1)
OPCL(I) = OPCL(1)*(1+ESCFO)**(I-1)
OPCM(I) = OPCM(1)*(1+ESCFO)**(I-1)
OPCH(I) = OPCH(1)*(1+ESCFO)**(I-1)
TRPL(I) = TRPL(1)*(1+ESCTR)**(I-1)
TRPM(I) = TRPM(1)*(1+ESCTR)**(I-1)
TRPH(I) = TRPH(1)*(1+ESCTR)**(I-1)
C
CTCL(I) = CTCL(I)*(1+ESCWT)**(I-1)
CTCM(I) = CTCM(I)*(1+ESCWT)**(I-1)
CTCH(I) = CTCH(I)*(1+ESCWT)**(I-1)
CICL(I) = CICL(I)*(1+ESCWI)**(I-1)
CICM(I) = CICM(I)*(1+ESCWI)**(I-1)
CICH(I) = CICH(I)*(1+ESCWI)**(I-1)
WO(I) = WWOC*SUMP*(1+ESCWO)**(I-1)
C
C ELIMINATE WELL WORKOVER COSTS FOR INCREMENTAL CASES
C UNTIL WATERFLOOD LIFE EXCEEDED
C
IF(IOPTS .GT. 1 .AND. I .LE. IWLIFE) WO(I) = 0.0
C
BPO(I) = BPO(1)*(1+ESCBP)**(I-1)
AOVH(I) = AOVH(I)*(1+ESCFO)**(I-1)
WTC(I) = WTC(1)*(1+ESCTR)**(I-1)
IF (I.EQ.1 .AND. IOPTS .LE. 0 ) DATE(I)=BTIM
IF (I.EQ.1 .AND. IOPTS .GT. 0 ) DATE(I)=BTIMV
IF (I.EQ.1) GO TO 700
DATE(I) = DATE(I-1) + 1.0
700 CONTINUE
C
RETURN
9999 STOP 'Exit during title card read.'
RETURN
END
SUBROUTINE STCDE(ST,IST)
C
C -----
C ***** GIVEN STATE ALPHA (ST), COMPUTE STATE CODE (IST)
C ***** GIVEN STATE CODE (IST), COMPUTE STATE ALPHA (ST)
C -----
C

```

```

      INTEGER ST,IST
      INTEGER STATE(53)

C
      DATA STATE /4H  AL,4H  AZ,4H  AR,4H  CA,4H  CO,4H  CT,
1      4H  DE,4H  DC,4H  FL,4H  GA,4H  ID,4H  IL,
2      4H  IN,4H  IA,4H  KS,4H  KY,4H  LA,4H  ME,
3      4H  MD,4H  MA,4H  MI,4H  MN,4H  MS,4H  MO,
4      4H  MT,4H  NE,4H  NV,4H  NH,4H  NJ,4H  NM,
5      4H  NY,4H  NC,4H  ND,4H  OH,4H  OK,4H  OR,
6      4H  PA,4H  RI,4H  SC,4H  SD,4H  TN,4H  TX,
7      4H  UT,4H  VT,4H  VA,4H  WA,4H  WV,4H  WI,
8      4H  WY,4H  AK,4H  HI,4H  PO,4H NONE /

C
      IF(IST .LE. 0) GO TO 100

C
C      ***** COMPUTE STATE ALPHA
      ST = STATE(IST)
      GO TO 999

C
C      ***** COMPUTE STATE CODE
100  IST = 0
      DO 150 I=1,53
      IF(ST.EQ.STATE(I)) IST = I
150  CONTINUE

C
999  RETURN
      END
      SUBROUTINE CHEKE(ITIM,DEPTH,WMAX,API)

C
C      -----
C
C      CHEKE: CHECK ECONOMIC DEFAULTS
C
C      -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'FILES.INC'
      INCLUDE 'ECON.INC'

C
C      PRICE REDUCTION FACTORS FOR API GRAVITY
C      OILP1 FOR ALL STATES BUT CALIFORNIA, OILP2 FOR CALIFORNIA
C
      DIMENSION API1(5),OILP1(5),API2(5),OILP2(5)
      DATA API1/ 40., 30., 20., 10., -16./
      DATA OILP1/ 1.0, .9383, .8383, .605, 0.0/
      DATA API2/ 40., 34., 20., 8., -37./
      DATA OILP2/ .875, .855, .7617, .6017, 0.0/

C
C      -----
C
C      ***** DEFAULT CHECKING - ECONOMIC DATA
C
C      -----
      UNIT = 1000.

C
C      ***** OVERALL PRICES AND COSTS
C
C      MODIFY ALL PRICES INPUT BY OIL GRAVITY FACTOR
C
      IF(POM(1) .LE. 0.0) POM(1) = 30.0
      XPRICE = POM(1)

```

```

C
C   USE GRAVITY CORRELATION FOR OIL PRICE
IF (ISTATE .EQ. 53 ) FACTOR = 1.0
IF (ISTATE .LT. 53 ) FACTOR = SDINT(API1,OILP1,5,API)
IF (ISTATE .EQ. 4) FACTOR = SDINT(API2,OILP2,6,API)
C   POM(1) = FACTOR * 30.0
C
POM(1) = FACTOR * POM(1)
IF (ISTATE .EQ. 50) POM(1) = POM(1) - 9.00
C
POL(1) = POM(1) * 0.8
POH(1) = POM(1) * 1.2
IF (PGM(1).GT.0.) GO TO 520
  PGM(1)= XPRICE /6.00
  PGL(1)= PGM(1) * 0.8
  PGH(1)= PGM(1) * 1.2
520 IF (OPCM(1).GT.0.) GO TO 530
  OPCL(1) = 0.04
  OPCM(1) = 0.05
  OPCH(1) = 0.06
530 IF (TRPM(1).GT.0.) GO TO 540
  TRPL(1) = 0.08
  TRPM(1) = 0.10
  TRPH(1) = 0.12
540 IF (PPM(1) .GT. 0.0) GO TO 560
  PPL(1) = 1.28
  PPM(1) = 1.60
  PPH(1) = 1.92
560 IF (IDEBT .EQ. 0 ) GO TO 600
  IF (PCTDBT .LE. 0.0 ) PCTDBT = 20.0
  IF (DBTINT .LE. 0.0 ) DBTINT = 15.0
  IF (NYRRPY .LE. 0 ) NYRRPY = 1
  IF (NYPaid .LE. 0 ) NYPaid = 5
C
600 CONTINUE
C   ***** DEFAULT VALUES
MYR = M
IF (WTCOST.LE.0.) WTCOST=0.03
IF (XDR .LE.0.) XDR=0.10
IF (XSEV.LE.0.) XSEV=0.0
IF (XROY.LE.0.) XROY=0.0
IF (XINF.LE.0.) XINF=0.0
IF (UNCO.LE.0.) UNCO=0.001
IF (XFIT.LE.0.) XFIT=0.0
IF (XTCR.LE.0.) XTCR=0.0
IF (XSTX.LE.0.) XSTX= 0.0
IF (WCAP.LE.0.) WCAP = 0.0
IF (DTIM .GT. 0.0 ) IDEP = 0
IF (DTIM.LE.0.) IDEP = 1
IF (DTIM.LE.0.) DTIM = 5.
IF (WPHO.LE.0.) WPHO=1991.
IF (EPHO.LE.0.) EPHO = 1993.
IF (BTIM.LE.0.) BTIM=1994.
IF (BPOW.LE.0.0) BPOW = 23.07 * (1. + XINF)**(BTIM - 1983.)
BPO(1) = BPOW
WTC(1) = WTCOST
C   ***** DEFAULT THE ESCALATION RATES
IF (ESCPO.LE.0.) ESCPO = 0.0
IF (ESCPG.LE.0.) ESCPG = 0.0
IF (ESCPI.LE.0.) ESCPI = 0.0

```

```

      IF (ESCTR.LE.0.) ESCTR = 0.0
      IF (ESCFO.LE.0.) ESCFO = 0.0
      IF (ESCWT.LE.0.) ESCWT = 0.0
      IF (ESCWO.LE.0.) ESCWO = 0.0
      IF (ESCWI.LE.0.) ESCWI = 0.0
      ESCBP = XINF + 0.02
C
C
C   CALCULATE PROCESS INDEPENDENT COST DEFAULTS
      CALL CIND(ISTATE,IDIST,DEPTH,WMAX,PGM(1),CINJ,CEQP,CSEC,CNVT,
        & CREP,CDAO,CIWO)
C
C   DEFAULT WELL COSTS HERE - IF WELL COSTS ARE INCLUDED IN THE PATTERN
C   CAPITAL COSTS (NCT & NCI), INPUT WPP1=WPP2=WPP3=WPP4=0
C   THESE COSTS (IF ANY) WILL BE ADDED TO NCT & NCI LATER
C
C   IGNORE UPGRADE TO SECONDARY OPERATIONS IF NO PRIMARY WELLS
C   CONVERTED TO SECONDARY BY WPP4
C
      IF (WPP4 .LE. 0.0) CREP = 0.0
      CAP = (CINJ * WPP1 + (CINJ + CEQP) * WPP2 + CSEC * WPP3 +
        & CNVT * WPP4 + CREP)
C
C   WCT IS TANGIBLE WELL INVESTMENT PER PATTERN
      WCT = 0.28 * (CEQP * WPP2 + CSEC * WPP3)
C
C   WCI IS INTANGIBLE WELL INVESTMENT PER PATTERN
      WCI = CAP - WCT
C
C   ***** ESCALATE THESE COSTS AT 1993 TO PROJECT START YEAR (BTIM)
C   AT ESCALATION RATES OF CAPITAL, ESCWI AND ESCWT, WITH DEFAULT
C   TO INFLATION RATE AND PROJECT START IN 1993
      ESC = 1. + XINF
      IF (ESCWI .GT. 0.0) ESC = 1. + ESCWI
      WCI = WCI * (ESC ** (BTIM - 1993.))
      IF (ESCWT .GT. 0.0) ESC = 1. + ESCWT
      WCT = WCT * (ESC ** (BTIM - 1993.))
C
C   WELL WORKOVER COSTS EQUAL COST TO CONVERT A WELL
C
C   ASSUME ONE WORKOVER PER PATTERN EACH FOUR YEARS
      IF (WOCOST .LE. 0.0)
        & WOCOST = 0.25 * CNVT
      WO(1) = WOCOST
C
      IF (FOCM(1).GT.0.) GO TO 720
      FOCL(1) = (CDAO + CIWO) * 0.8
      FOCM(1) = (CDAO + CIWO)
      FOCH(1) = (CDAO + CIWO) * 1.2
C
720 IF (CTPM(1).GT.0.) GO TO 730
      CTPL(1) = WCT * 0.8
      CTPM(1) = WCT * 1.0
      CTPH(1) = WCT * 1.2
C
730 IF (CIPM(1).GT.0.) GO TO 740
      CIPL(1) = WCI * 0.8
      CIPM(1) = WCI * 1.0
      CIPH(1) = WCI * 1.2
740 CONTINUE
C

```



```

C   INITIALIZE OVERHEAD ON D&C+E TO 3% OF WELL COST (WITH 2% ADDED
C   LATER) ONLY FOR FIRST YEAR OF EACH PATTERN
      AOVH1 = .03 * (CTPM(1) + CIPM(1)) / UNIT / UNIT
C
C
C
C   CALCULATE SECONDARY OIL PRODUCTION RATE (VOS, MB/YR) IF ISO NOT 1,
C   AND DEFAULT DECLC TO 15% IF NOT INPUT
      IF (ISO .EQ. 1) GO TO 900
      IF (DECL. LE. 0.0) DECL = 15.0
      DECL = DECL / 100.
      IF (OILB .GT. 0.0) GO TO 840
      OILB = 0.0
      OILC = 0.0
C
C   DEFAULT CURRENT SECONDARY PRODUCTION RATE TO BASE PRODUCTION RATE
C   USING CURRENT DECLINE RATE
      840 IF (OILC .LE. 0.0) OILC = OILB * (1. - DECL)**(BTIM - 1979.)
C
C   CALCULATE SECONDARY OIL PRODUCTION RATE, VOS
      DO 860 I=1,MYR
      860 VOS(I) = OILC * (1. - DECL)**(FLOAT(I) - 0.5)
      900 CONTINUE
      RETURN
      END
      SUBROUTINE CIND (ISTATE, IDIST, DEPTH, RATE, PRGAS,
      & CINJ, CEQP, CSEC, CNVT, CREP, CDAO, CIWO)
C*****
C   THIS SUBROUTINE DEFINES THE PROCESS INDEPENDENT COST PARAMETER
C   DEFAULT VALUES. THESE COSTS INCLUDE:
C
C   CINJ    - COST OF D&C FOR AN INJECTION WELL ($/WELL)
C   CEQP    - COST TO EQUIP NEW PRODUCING WELL ($/NEW PRODUCER)
C             ADDED TO CINJ FOR D&C NEW PRODUCING WELL
C   CSEC    - COST OF ADDITIONAL SECONDARY PRODUCTION EQUIPMENT
C             FOR A PRIMARY WELL CONVERTED TO A SECONDARY
C             PRODUCER ($/PRIMARY PRODUCING WELL)
C   CNVT    - COST TO CONVERT AN EXISTING PRODUCER TO AN INJECTION
C             WELL ($/CONVERTED WELL)
C   CREP    - COST TO UPGRADE SURFACE PROCESSING EQUIPMENT
C             AND LEASE FACILITIES FOR SECONDARY RECOVERY OPERATIONS
C             ($/PRODUCER)
C   CDAO    - DIRECT ANNUAL OPERATING COSTS FOR SECONDARY RECOVERY
C             OPERATIONS ($/PRODUCING WELL/YEAR)
C   CIWO    - ADDITIONAL ANNUAL OPERATING COST FOR OFFSHORE WATER
C             INJECTION ($/YEAR)
C
C   THESE COSTS DEFINED BY:
C
C   U.S. DEPT. OF ENERGY, EIA
C   DALLAS FIELD OFFICE
C   1114 COMMERCE ST. ROOM 804
C   DALLAS, TEXAS 75242
C   (214) 767-2200
C
C *** THE INPUT PARAMETERS REQUIRED ARE:
C   ISTATE - STATE CODE
C   IDIST  - DISTRICT CODE WITHIN STATE
C   DEPTH  - VERTICAL DEPTH TO RESERVOIR (FT)

```

```

CIND  2
CIND  3
CIND  4
CIND  5
CIND  6
CIND  7
CIND  8
CIND  9
CIND 10
CIND 11
CIND 12
CIND 13
CIND 14
CIND 15
CIND 16
CIND 17
CIND 18
CIND 19
CIND 20
CIND 21
CIND 22
CIND 23
CIND 24
CIND 25
CIND 26
CIND 27
CIND 28
CIND 29
CIND 30
CIND 31
CIND 32
CIND 33
CIND 34
CIND 35
CIND 36

```

C	RATE - OFFSHORE DAILY WATER INJECTION RATE (MBBL/D)	CIND	37
C	PRGAS - PRICE OF NATURAL GAS OFFSHORE (\$/MCF)	CIND	38
C		CIND	39
C	*** THE DRILLING COSTS ARE DEFINED AS FUNCTIONS OF DEPTH AND REGION.	CIND	40
C	THE U.S. IS DIVIDED INTO SEVEN REGIONS AS FOLLOWS:	CIND	41
C	1 PACIFIC COAST	CIND	42
C	2 ROCKY MOUNTAINS	CIND	43
C	3 PERMIAN BASIN	CIND	44
C	4 GULF COAST	CIND	45
C	5 MID-CONTINENT	CIND	46
C	6 NORTHEASTERN	CIND	47
C	7 OFFSHORE	CIND	48
C		CIND	49
C	*** THESE COSTS INCLUDE THE COST OF DRILLING AND COMPLETING WELLS	CIND	50
C	THROUGH THE WELLHEAD, INCLUDING TUBING, AND REPRESENT THE COSTS OF	CIND	51
C	NEW INJECTION WELLS. (NEW PRODUCING WELLS HAVE ADDITIONAL COSTS	CIND	52
C	THAT ARE ADDED TO THESE COSTS LATER)	CIND	53
C		CIND	54
C	*****	CIND	55
C			
C	INCLUDE 'FILES.INC'		
C			
	CINJ = 0.0	CIND	56
	CEQP = 0.0	CIND	57
	CSEC = 0.0	CIND	58
	CNVT = 0.0	CIND	59
	CREP = 0.0	CIND	60
	CDAO = 0.0	CIND	61
	CIWO = 0.0	CIND	62
C		CIND	63
	GO TO (60,50,60,40,50,70,70,70,60,60,50,70,70,70,30,70,60,70,	CIND	64
	& 70,70,70,70,60,70,50,30,40,70,70,20,70,70,50,70,30,40,70,70,	SRA1	11
	& 60,50,70,20,50,70,70,40,70,70,50,40,40,80), ISTATE	SRA1	12
C		SRA1	13
C	PERMIAN BASIN	SRA1	14
C	20 IF (IDIST .LT. 70 .AND. ISTATE .EQ. 42) GO TO 60	SRA1	15
	IF (IDIST .EQ. 100) GO TO 30	SRA1	16
C			
	CINJ = (71.736 + 6.433E-6 * DEPTH**2.) * 1000.		
C			
	IF (ISTATE .EQ. 42 .AND. IDIST .EQ. 90) GO TO 130	SRA1	19
	IF (ISTATE .EQ. 30 .AND. IDIST .EQ. 1) GO TO 150	SRA1	18
	GO TO 120	CIND	72
C		CIND	73
C	MID-CONTINENT_	CIND	74
C			
	30 CINJ = (69.634 + 5.967E-6 * DEPTH**2.) * 1000.		
C			
	GO TO 130	CIND	76
C		CIND	77
C	PACIFIC COAST	CIND	78
C			
	40 CINJ = (91.186 + 1.760E-5 * DEPTH**2.) * 1000.		
C			
	GO TO 140	CIND	80
C		CIND	81
C	ROCKIES	CIND	82
C			
	50 CINJ = (108.451 + 8.471E-6 * DEPTH**2.) * 1000.		
C			

C	GO TO 150	CIND 85
C	GULF COAST	CIND 86
C	60 CINJ = (57.833 + 9.201E-6 * DEPTH**2.) * 1000.	
C	GO TO 100	CIND 88
C		CIND 89
C	NORTHEAST	CIND 90
C	70 CINJ = (61.109 + 4.230E-6 * DEPTH**2.) * 1000.	
C	GO TO 130	CIND 92
C		CIND 93
C	OFFSHORE	CIND 94
C	80 CINJ = 458492 - 56.3271*DEPTH + .03043*DEPTH**2.	CIND 95
C	GO TO 180	CIND 96
C		CIND 97
C	CHECK GULF COAST LOCATION TO ASSIGN TO PROPER REGION FOR EQUIPMENT	CIND 98
C	AND OPERATING COSTS. THESE REGIONS ARE:	CIND 99
C		CIND 100
C	1 PERMIAN BASIN	CIND 101
C	2 PACIFIC COAST	CIND 102
C	3 ROCKY MOUNTAINS	CIND 103
C	4 WESTERN GULF COAST	CIND 104
C	5 EASTERN GULF COAST	CIND 105
C	6 MID-CONTINENT AND NORTHEASTERN	CIND 106
C	7 OFFSHORE	CIND 107
C		CIND 108
C	*** THE COST TO EQUIP A NEW PRODUCTION WELL (CEQP) INCLUDES ALL THE	CIND 109
C	ADDITIONAL EQUIPMENT FOR SECONDARY RECOVERY WITH THE COST OF	CIND 110
C	TUBING LEFT OUT (TUBING IS INCLUDED IN D&C COSTS)	CIND 111
C	*** THE COST OF ADDITIONAL SECONDARY RECOVERY EQUIPMENT (CSEC) ASSUME	CIND 112
C	THAT THE EXISTING PROCESSING AND LEASE FACILITIES WOULD NOT BE	CIND 113
C	REPLACED BUT OLD PRODUCING WELL EQUIPMENT IS REPLACED. THESE	CIND 114
C	COSTS INCLUDE DRILLING AND EQUIPPING WATER SUPPLY WELLS.	CIND 115
C	*** THE CONVERSION OF A PRODUCING WELL TO AN INJECTION WELL (CNVT)	CIND 116
C	INCLUDES REMOVAL OF PRODUCING EQUIPMENT (INCLUDING TUBING),	CIND 117
C	CLEANING OUT THE WELLBORE, INSTALLING PC TUBING AND PACKER	CIND 118
C	*** THE REPLACEMENT COST OF EXISTING PROCESSING EQUIPMENT AND LEASE	CIND 119
C	FACILITIES (CREP) INCLUDES FLOWLINES, MANIFOLDS, SEPARATORS,	CIND 120
C	TREATERS, TANKS, LACT UNIT, DISPOSAL SYSTEM AND ACCESSORIES	CIND 121
C	*** THE DIRECT ANNUAL OPERATING COSTS FOR SECONDARY RECOVERY (CDAO)	CIND 122
C	INCLUDES COST ASSOCIATED WITH OPERATING AND MAINTAINING	CIND 123
C	PRODUCTION, INJECTION AND DISPOSAL WELLS	CIND 124
C		CIND 125
C		CIND 126
C	100 IF(ISTATE .EQ. 9) GO TO 110	CIND 127
	IF(ISTATE .EQ. 17 .AND. IDIST .EQ. 2) GO TO 110	CIND 129
	IF(ISTATE .EQ. 42 .AND. IDIST .LE. 40) GO TO 170	SRA1 20
	GO TO 130	CIND 130
C		
C	Eastern Gulf Coast	
C		
C	110 CEQP = 20266. + 17.130 * DEPTH	
	CSEC = 18916. + 19.887 * DEPTH	
	CNVT = 6996. + 6.628 * DEPTH	
	CREP = 34617. + 3.442E-4 * DEPTH**2.	
	CDAO = 22461. + 5.904 * DEPTH	
	GO TO 200	

```

C
C Permian Basin
C
120  CEQP = 20347. + 17.165 * DEPTH
      CSEC = 18997. + 19.927 * DEPTH
      CNVT = 6086. + 6.661 * DEPTH
      CREP = 22323. + 2.009E-4 * DEPTH**2.
      CDAO = 17759. + 4.801 * DEPTH
      GO TO 200

C
C Mid-Continent and Northeastern
C
130  CEQP = 17706. + 17.833 * DEPTH
      CSEC = 16048. + 20.680 * DEPTH
      CNVT = 6741. + 6.559 * DEPTH
      CREP = 24688. + 2.426E-4 * DEPTH**2.
      CDAO = 8539. + 6.473 * DEPTH
      GO TO 200

C
C Pacific Coast
C
140  CEQP = 25668. + 26.038 * DEPTH
      CSEC = 23234. + 30.193 * DEPTH
      CNVT = 7713. + 6.741 * DEPTH
      CREP = 47322. + 2.717E-4 * DEPTH**2.
      CDAO = 9948. + 11.917 * DEPTH
      GO TO 200

C
C Rocky Mountains
C
150  CEQP = 17504. + 18.069 * DEPTH
      CSEC = 15792. + 20.950 * DEPTH
      CNVT = 6951. + 6.805 * DEPTH
      CREP = 31543. + 1.685E-4 * DEPTH**2.
      CDAO = 18894. + 4.932 * DEPTH
      GO TO 200

C
C Western Gulf Coast
C
170  CEQP = 20810. + 17.331 * DEPTH
      CSEC = 19466. + 20.122 * DEPTH
      CNVT = 6326. + 6.596 * DEPTH
      CREP = 31067. + 3.327E-4 * DEPTH**2.
      CDAO = 21214. + 5.677 * DEPTH
      GO TO 200

C
C OFFSHORE
180  CEQP = 0.
      CSEC = 650000 + 230000*RATE - 2800*RATE**2.
      CNVT = 171366 + 21.825*DEPTH
      CREP = 0.
      CDAO = 169000
      CIWO = 40200*RATE + 8080*RATE*PRGAS

C
200  CONTINUE
      RETURN
      END
      SUBROUTINE ECFTR(PRICE, FDC, FEQP, FOPR,
&                     FUEL, FSUR, FPLY, FCAU, FACT, ISTATE)
C

```

```

CIND 185
CIND 186
SRA1 26
CIND 188
CIND 189
CIND 190
CIND 191
CIND 192
CIND 193
CIND 194
CIND 195
CIND 196

```

```

C -----
C
C THIS SUBROUTINE CALCULATES THE VARIATION IN THE COST
C FACTORS USED DUE TO CHANGES IN THE OIL PRICE. A BASE
C OIL PRICE OF $30/STB (NOMINAL) IS USED.
C
C FACT      OIL PRICE FACTOR
C FDC       DRILLING & COMPLETION FACTOR
C FEQP      EQUIPMENT FACTOR
C FOPR      OPERATING COSTS FACTOR
C FUEL      FUEL FACTOR (NOT USED)
C FSUR      SURFACTANT FACTOR (NOT USED)
C FCAU      CAUSTIC FACTOR (NOT USED)
C
C -----
C
C INCLUDE 'FILES.INC'
C
C FACT = (PRICE - 30.) / 30.
C IF ( ISTATE .EQ. 53) FACT = 0.0
C FDC = 1. + (0.4 * FACT)
C FEQP = 1. + (0.3 * FACT)
C
C FEQP = 1. + (0.2 * FACT)
C IF (PRICE.LT.16.) THEN
C     FDC = 0.8133 * (1.+((PRICE-16.)/16.)*0.7)
C     FEQP = 0.9067 * (1.+((PRICE-16.)/16.)*0.6)
C ENDIF
C
C FOPR = 1. + (0.2 * FACT)
C FUEL = 1. + (1.0 * FACT)
C FSUR = 1. + (0.6209 * FACT)
C FPLY = 1. + (0.3913 * FACT)
C FCAU = 1. + (0.3855 * FACT)
C FACT = 1. + FACT
C
C NO CORRECTION FOR DEPTH OR LOCATION
C
C RETURN
C END
C SUBROUTINE ECON( API, PRICE, DISCNT,
C &  VALUE, FACT, FDC, FEQP, FOPR, FUEL, FSUR, FPLY, FCAU,CONCP)
C
C -----
C
C ECON: COMPUTE CASH FLOW AND PROFITABILITY CRITERIA
C
C -----
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'FILES.INC'
C INCLUDE 'ECON.INC'
C
C -----
C ***** COMPUTE MEAN DISCOUNTED CASH FLOW AND RATE OF RETURN
C -----
C
C INPUT VARIABLES
C -----
C MYR      - NUMBER OF YEARS OF PRODUCTION

```

C IOUT - INTERMEDIATE OUTPUT CONTROL
 C XWPT - WINDFALL PROFIT TIER I TAX RATE
 C XSEV - SEVERANCE TAX RATE
 C XFIT - TAX RATE
 C XINF - INFLATION RATE
 C XDR - DISCOUNT RATE
 C COMMON /ECI/ INCLUDES LOW, MOST LIKELY, AND HIGH VALUES

C OUTPUT VARIABLES

C -----
 C SUMVOM- TOTAL VOLUME OF OIL PRODUCED, MMBL
 C TOTD - TOTAL CAPITAL INVESTMENT
 C YC - CAPITAL RECOVERY COEFFICIENT
 C SRPV - TOTAL REVENUE PRESENT VALUE (MOST LIKELY), MM\$
 C SUMFO - TOTAL FIXED OPERATING COST(PV), MM\$
 C SUMOPC- TOTAL VARIABLE OPERATING COST(PV), MM\$
 C SUMTR - TOTAL CHEMICAL HANDLING COST(PV), MM\$
 C DCFB - TOTAL DISCOUNTED CASH FLOW BEFORE TAX
 C MUPPV - MEAN OF THE DISCOUNTED CASH FLOW, MM\$
 C STDDEV- STD DEVIATION OF THE DISCOUNTED CASH FLOW
 C PAYOUT- TIME AT WHICH DCFAT=0, YEARS
 C ROR - DCF RATE OF RETURN

C
 C CONSTANTS FOR ACCELERATED CAPITAL RECOVERY SYSTEM (ACRS)
 C DEPRECIATION ACCORDING TO 1981 TAX ACT
 C UPDATED TO REFLECT 1986-1987 NEW TAX ACT
 C ANNUAL DEPRECIATION

C	SERVICE	AS A PERCENT OF ASSET VALUE							
C	YEAR	YR 1	YR 2	YR 3	YR 4	YR 5	YR 6	YR 7	YR 8
C									
C	1981-84	15	22	21	21	21	0	0	0
C	1985	18	33	25	16	8	0	0	0
C	1986	20	32	24	16	8	0	0	0
C	1987+	14	25	17	12	9	9	9	4

C DIMENSION ACRS(8,4)

DATA ACRS/ .15, .22, .21, .21, .21, 0.0, 0.0, 0.0,
 X .18, .33, .25, .16, .08, 0.0, 0.0, 0.0,
 X .20, .32, .24, .16, .08, 0.0, 0.0, 0.0,
 X .1428, .2449, .1749, .1249, .0893, .0893, .0893, .0446/

UNIT = 1000.

UMM = UNIT*UNIT

C ***** COMPUTE THE MEAN VALUE OF EACH VARIABLE

C MUVO - MEAN OIL VOLUME, BBL
 C MUVG - MEAN GAS VOLUME, MMSCF
 C MUVW - MEAN WATER VOLUME, BBL
 C MUVI - MEAN INJECTED SLUG VOLUME, BBL
 C MUPO - MEAN OIL PRICE, MM\$/BBL
 C MUPG - MEAN GAS PRICE, MM\$/MSCF
 C MUFO - MEAN FIXED OPERATING COST, MM\$/YR
 C MUOPC- MEAN VARIABLE OPERATING COST, MM\$/BBL OIL
 C MUTR - MEAN CHEM HANDLING COST, MM\$/LBM
 C MUCT - MEAN TANGIBLE CAPITAL COSTS, MM\$
 C MUCI - MEAN INTANGIBLE CAPITAL COST, MM\$
 C MUDB - MEAN DEBT ADDED, MM\$
 C MURP - MEAN PRINCIPAL REPAYMENT, MM\$
 C MUIN - MEAN INTEREST PAYMENT, MM\$

```

C          MUPB - MEAN PRINCIPAL BALANCE AT END OF YEAR, AFTER
C          PRINCIPAL PAYMENT, MM$
      SUMVOM = 0.0
      SUMTD = 0.0
      DO 20 I=1,MYR
      MUVO(I) = (VOL(I)+2.*VOM(I)+VOH(I))/4.
      MUVG(I) = VGM(I)
      MUVW(I) = VWM(I)
      MUVI(I) = VIM(I)

C
C  CALCULATE PRICES DETERMINISTICALLY FOR NPC
C
      MUPO(I) = POM(I) * FACT
      IF(ISTATE.EQ. 50) MUPO(I) =
& ((MUPO(I) / FACT) + 9.00) * FACT - 9.00
      MUPG(I) = PGM(I) * FACT
      MUFO(I) = FOCM(I) * FOPR
      MUOPC(I) = OPCM(I) * FOPR
      MUCT(I) = CTCM(I) * FEQP
      MUCI(I) = CICM(I) * FEQP

C
      MUWO(I) = WO(I) * FOPR
      DEPS(I) = 0.0
      SUMVOM = SUMVOM + MUVO(I)/UNIT
      SUMTD = SUMTD + MUCT(I)/UMM

C          INITIALIZE DEBT VECTORS
C
      MUIN(I)=0.
      MUDB(I)=0.
      MUPB(I)=0.
      MURP(I)=0.
20  CONTINUE

C
C  ***** COMPUTE VARIANCES OF EACH VARIABLE
      DO 30 I=1,MYR
      SIGVO(I) = (VOH(I)-VOL(I))/2.65
      SIGPO(I) = (POH(I)-POL(I))/2.65/UMM
      SIGPG(I) = (PGH(I)-PGL(I))/2.65/UMM
      SIGPP(I) = (PPH(I)-PPL(I))/2.65/UMM
      SIGFO(I) = (FOCH(I)-FOCL(I))/2.65/UMM
      SIGOPC(I) = (OPCH(I)-OPCL(I))/2.65/UMM
      SIGTR(I) = (TRPH(I)-TRPL(I))/2.65/UMM
      SITRT(I) = (CTCH(I)-CTCL(I))/2.65/UMM
      SITRI(I) = (CICH(I)-CICL(I))/2.65/UMM
30  CONTINUE

C
C  ***** WRITE MEAN VALUES - IOUT.GE.2
      IF(IOUT.LE.1) GO TO 100
      WRITE(IW,9601)
9601  FORMAT(1H1,35X,31HPROJECT MEAN VALUES - ESCALATED /
1  36X,31(1H-) /)
      WRITE(IW,9050)
9050  FORMAT(
1  2X,4H      , 10H      OIL , 10H      GAS ,
2  10H  TANGIBLE, 10H  INTANGBL, 10H  FIXED ,
3  10H  VARIABLE,10H      WELL ,10H      WATER /
4  2X,4H      , 10H      PRICE , 10H      PRICE ,
4  10H  CAPITAL, 10H  CAPITAL, 10H  OPN COST,
4  10H  OPN COST, 10H  WORKOVER ,10H  TREATING /
5  2X,4HYEAR, 10H      $/BBL , 10H      $/MCF ,

```

```

      5 10H      M$/YR , 10H      M$/YR , 10H      M$/YR ,
      5 10H      $/BBL , 10H      M$/YR , 10H      $/BBL /
      7 2X,4H-----,3(10H -----),2(10H -----),3(10H -----) )
9051 FORMAT(2X,I3, 2F10.2, 3F10.0, F10.3, F10.0, F10.3)
      SUMP = 0.
      DO 50 I=1,MYR
      SUMP = SUMP + PATI(I)
      UCT = MUCT(I)/UNIT
      UCI = MUCI(I)/UNIT
      UFO = MUFO(I)/UNIT
      UWO = MUWO(I)/UNIT
      50 WRITE(IW,9051) I,MUPO(I),MUPG(I) ,UCT, UCI,
      1 UFO,MUOPC(I), UWO,WTC(I)

```

```

C
C      ***** UNITS IN $MM
100 COSTRT = COSTRT / UNIT
      DO 110 I=1,MYR
      MUPO(I) = MUPO(I)/UMM
      MUPG(I) = MUPG(I)/UMM
      MUPP(I) = MUPP(I)/UMM
      MUCT(I) = MUCT(I)/UMM
      MUCI(I) = MUCI(I)/UMM
      MUFO(I) = MUFO(I)/UMM
      MUOPC(I) = MUOPC(I)/UMM
      MUTR(I) = MUTR(I)/UMM
110 MUWO(I) = MUWO(I)/UMM

```

```

C
C
C-----
C      ***** CALC ANNUAL VALUES OF REVENUE AND COST COMPONENTS
C-----
C      AREV - ANNUAL GROSS REVENUE
C      ANET - ANNUAL NET (LESS ROYALTY) REVENUE
C      ASEV - ANNUAL SEVERANCE TAX
C      AFOC - ANNUAL FIXED OPERATING COST
C      AVOC - ANNUAL VARIABLE OPERATING COST
C      ATRC - ANNUAL CHEMICAL HANDLING COST
C      AINJ - ANNUAL CHEMICAL PURCHASE COST
C      AWTC - ANNUAL PRODUCED WATER HANDLING COST
C      ACOST - ANNUAL TOTAL COST
C      ANOI - ANNUAL NET OPERATING INCOME
C      CFBT - CASH FLOW BEFORE TAX
C      CFAT - CASH FLOW AFTER TAX
C      DCFBT - DISCOUNTED CASH FLOW BEFORE TAX
C      DCFAT - DISCOUNTED CASH FLOW AFTER TAX

```

```

C
      ILIF = 1
      CFMAX = 0.0
      CNOIM = 0.0
      CNOI(1) = 0.0
      CTXC = 0.0
      CFBT(1) = 0.0
      CFAT(1) = -COSTRT
      XWC = WCAP/12.
      OPCS = 0.0

```

```

C
C      ***** LOOP THRU M YEARS FOR ANNUAL VALUES
      DO 400 I=1,M
      M1 = I-1
      IF(M1.LE.0) M1=1

```



```

AWPP(I) = 0.0
AWPT(I) = 0.0
ARVWPT(I) = 0.0
C
C ***** UNDISCOUNTED CASH FLOW AND TAXES (WPT AND FIT)
VOSOLD = MUVO(I)
AQOR(I) = MUVO(I)/365.
AQGR(I) = MUVG(I)/365.
AQWR(I) = MUVW(I)/365.
AQIR(I) = MUVI(I)/365.
AFUEL(I) = 0.0
VOSOLD = MUVO(I)
IF(VOSOLD.LE.0.) MUFO(I)=MUFO(I)+ABS(VOSOLD)*MUPO(I)/365.
C
C ALLOW NEGATIVE OIL SALES RATE FOR INCREMENTAL CASES
C
C IF(VOSOLD.LT.0.) VOSOLD=0.
C
C VOSLD(I) = VOSOLD/UNIT
C
C ***** ANNUAL REVENUE FOR GROSS OIL (LESS FUEL) AND GAS SOLD
AREVO(I) = VOSOLD*MUPO(I)
AREVG(I) = MUVG(I)*MUPG(I)
AREV(I) = AREVO(I) + AREVG(I)
C
C ***** LESS ROYALTY GIVES NET OIL (WORKING INTEREST)
VONET(I) = VOSOLD*(1.-XROY)
VGNET(I) = MUVG(I)*(1.-XROY)/UNIT
AROY(I) = AREV(I)*XROY
ANET(I) = AREV(I) - AROY(I)
C
C ***** SEVERANCE TAX
ASEV(I) = ANET(I)*XSEV
C
C ***** ANNUAL OPERATING COST (FIXED, VARBL, CHEM PURCH/HANDLG)
AFOC(I) = MUFO(I)
AVOC(I) = MUVO(I)*MUOPC(I)
C
C
C DUMMY = 0.0
ATRC(I) = (MUVI(I)+DUMMY)*MUTR(I)
AWTC(I) = MUVW(I)*WTC(I)/UMM
AOVH(I) = .20 * (AFOC(I) + AVOC(I) + ATRC(I) + AWTC(I) + MUWO(I))
& + .02 * (MUCI(I) + MUCT(I)) + AOVH(I)
AINJ(I) = VPM(I) * MUPP(I)
ACOST(I) = AVOC(I) + ATRC(I) + AINJ(I)
& + AFOC(I) + MUWO(I) + AWTC(I) + AOVH(I) + ASEV(I)
C
C ***** ANNUAL WORKING CAPITAL
OPCI = ACOST(I)
IF(OPCI.LE.0.) OPCI = 0.0
AWCP(I) = (OPCI-OPCS)*XWC
OPCS = OPCI
C
C ***** NET OPERATING INCOME (BEFORE WINDFALL AND FEDERAL TAX)
ANOI(I) = ANET(I) - ACOST(I)
CNOI(I) = CNOI(M1) + ANOI(I)
BTINC = ANOI(I) - MUCI(I)-MUCT(I)-AWCP(I)
CFBT(I) = CFBT(M1) + BTINC
C
C ***** WINDFALL PROFIT TAX CALCS

```

```

IF (XWPT .EQ. 0.0) GO TO 356
IF (API .LE. 16.0) GO TO 356
BPONE = 16.65
XONE = (MUPO(I) * UMM - BPONE) * 0.70
IF (XONE .LE. 0.0) XONE = 0.0
XTHREE = (MUPO(I) * UMM - BPO(I))
IF (XTHREE .LE. 0.0) XTHREE = 0.0
AWPP(I) = XTHREE
XTHREE = XTHREE * XWPT
XCRED = XONE - XTHREE
IF (XCRED .LT. 0.0) XCRED = 0.0
C ***** TAX CALCS
AWPT(I) = VONET(I) * (1.-XSEV) * AWPP(I) * XWPT / UMM
IF (AWPT(I) .LT. 0.) AWPT(I) = 0.0
WPHOF = 1.0
IF (DATE(I) .LT. WPHO) GO TO 355
DIFF = EPHO - WPHO + 1.0
IF (DIFF .LE. 0.) GO TO 355
WPHOF = (EPHO - DATE(I)) / DIFF
IF (WPHOF .LE. 0.) WPHOF = 0.0
AWPT(I) = AWPT(I) * WPHOF
C GET REVENUE FROM RELEASED OIL TO OFFSET WPT
355 CONTINUE
ARVWPT(I) = OILR(I) * (1. - XROY) * XCRED * WPHOF
IF (ARVWPT(I) .LT. 0.0) ARVWPT(I) = 0.0
C DO NOT ALLOW NEGATIVE WPT IF RELEASED OIL REVENUES GREATER
AWPT(I) = AWPT(I) - ARVWPT(I)
IF (AWPT(I) .LT. 0.0) AWPT(I) = 0.0
C
356 CONTINUE
C
C ***** STATE INCOME TAX
ASTX(I) = ANOI(I) * XSTX
IF (ASTX(I) .LE. 0.0) ASTX(I) = 0.0
C
C ***** NET TAXABLE INCOME (FIT)
CINV = MUCT(I)
IF (CINV .LE. 0.) GO TO 370
C
C ***** DEPRECIATION CALCULATION
C IDEP = 0 IMPLIES STRAIGHT-LINE FROM YEAR
C OF INVESTMENT OVER DTIM YEARS
C IDEP = 1 IMPLIES ACCELERATED CAPITAL RECOVERY
C SYSTEM (ACRS) ACCORDING TO RULES OF
C 1981 TAX ACT. UPDATED TO INCORPORATE
C RULES OF 1986-1987 NEW TAX ACT
C
IF (IDEP .EQ. 0) IDT = I + DTIM - 1
IF (IDEP .EQ. 1 .AND. DATE(I) .GE. 1981.) IDT = I + 8 - 1
IF (IDT .GT. MYR) IDT = MYR
DO 360 J = I, IDT
C
C ***** STRAIGHT-LINE DEPRECIATION
C
IF (IDEP .EQ. 0 .OR. DATE(I) .LE. 1980.) DEPS(J) = DEPS(J) + CINV / DTIM
IF (IDEP .EQ. 0 .OR. DATE(I) .LE. 1980.) GOTO 360
C
C ***** ACRS DEPRECIATION
C
IF (IFIX(DATE(I)) .GE. 1981 .AND. IFIX(DATE(I)) .LE. 1984)

```

```

X      DEPS(J) = DEPS(J) + CINV*ACRS(J-I+1,1)
      IF (IFIX (DATE(I)).EQ.1985) DEPS(J) = DEPS(J) + CINV*ACRS (J-I+1,2)
      IF (IFIX (DATE(I)).EQ.1986) DEPS(J) = DEPS(J) + CINV*ACRS (J-I+1,3)
      IF (IFIX (DATE(I)).GT.1986) DEPS(J) = DEPS(J) + CINV*ACRS (J-I+1,4)
360 CONTINUE
370 ACAP(I) = MUCI(I) + DEPS(I)
C
C      ***** DEBT CALCULATIONS
C
      IF (IDEBT.EQ.0) GOTO 3799
C
      LOAN IS TAKEN AT START OF YEAR I
C
      XX=(MUCT(I)+MUCI(I))*PCTDBT/100.
      IF (XX.LE.0.001) GOTO 3799
      MUDB(I)=XX+MUDB(I)
C
      IF FIRST YEAR OF REPAYMENT IS AFTER YEAR I,
      THEN ADD ACCRUED INTEREST TO PRINCIPAL AMOUNT
      THROUGH YEAR NYRRPY
C
      J=I
      IF (J.GE.NYRRPY) GOTO 3702
C
      ADD INTEREST TO DEBT AT START OF YEAR J+1 AND INCREASE
      XX = THE LOAN PRINCIPAL TO BE AMORTIZED
C
3701 MUDB(J+1)=XX*DBTINT/100.+MUDB(J+1)
      XX=(DBTINT/100.+1.)*XX
      MUPB(J)=XX+MUPB(J)
      J=J+1
      IF (J.LT.NYRRPY) GOTO 3701
C
      REPAYMENT SCHEDULE FOR THIS INCREMENT STARTS AT THE LATER
      OF NYRRPY OR THE CURRENT YEAR
C
      CALCULATIONS FOR THIS INCREMENT WILL END AT THE
      EARLIER OF NYPAID OR MYR -- IF NYPAID > MYR, THEN
      LOAN REPAYMENT WILL NOT BE COMPLETELY FINISHED IN
      THIS ANALYSIS; IT IS THEN ASSUMED TO BE PICKED UP
      ELSEWHERE
C
3702 JL=NYRRPY
      IF (JL.LT.I) JL=I
      JU=NYPAID
      IF (JU.GT.MYR) JU=MYR
C
      LOAN REPAYMENT BY EQUAL ANNUAL INSTALLMENTS
      OF TOTAL PRINCIPAL PLUS INTEREST -- SIMILAR
      TO HOME MORTGAGE
C
      IF (NYPAID .LE. JL-1 ) GO TO 3799
      EQAP = DBTINT/100./(1.-1./(DBTINT/100.+1.))** (NYPAID-JL+1)) *XX
      DO 3703 J=JL, JU
C
      INTEREST PAYMENT IN YEAR J
C
      YY=XX*DBTINT/100.
      MUIN(J)=YY+MUIN(J)
C

```

```

C          PRINCIPAL REPAYMENT IN YEAR J
C
C          MURP (J)=EQAP-YY+MURP (J)
IF (MURP (J) .LT. 0.0 ) MURP (J) = 0.0
          XX=XX-EQAP+YY
C
C          PRINCIPAL BALANCE AT END OF YEAR J
C
C          MUPB (J)=XX+MUPB (J)
3703 CONTINUE
3799 TXCR(I) = XTCR*MUCT(I)
C          DEDUCT INTEREST PAYMENT FROM TAXABLE INCOME
C
C          ANTI(I) = ANOI(I) - AWPT(I) - ACAP(I) - ASTX(I) - MUIN(I)
C          AFIT(I) = XFIT*ANTI(I)
C          IF (AFIT(I).LT.0. .AND. IFIT.EQ.1) AFIT(I)=0.
C
C          ***** TAX CREDIT
C          TCRED = CTXC + TXCR(I)
C          IF (AFIT(I).GT.TCRED) GO TO 385
385 CTXC = 0.0
C          AFIT(I) = AFIT(I) - TCRED
C          TXCR(I) = TCRED
C
C          ***** AFTER TAX CASH FLOW
C
C          ATPR(I) = ANOI(I) - AFIT(I)-AWPT(I)-ASTX(I)
1 - MUCI(I) - MUCT(I) - AWCP(I) - MUIN(I) - MURP(I)
C
C          CFAT(I) = CFAT(M1) + ATPR(I)
C          VONET(I) = VONET(I)/UNIT
C          IF (IPLIF.LE.0 .AND. CFAT(I).LE.CFMAX) GO TO 400
C          IF (IPLIF.EQ.1 .AND. CNOI(I).LE.CNOIM) GO TO 400
C          CNOIM = CNOI(I)
C          CFMAX = CFAT(I)
C          ILIF = I
C
C          400 CONTINUE
C
C          ***** ECONOMIC LIFE
C          PLIFE = ILIF
C          IF (ILIF.GE.M) PLIFE=M
C          IF (ILIF.EQ.1.AND.CNOIM.LT.0.) PLIFE=0.0
C          MYR = ILIF
C
C          ***** PRESENT VALUE RATE
C          CC = (1+XINF) * (1+XDR) - 1.
C
C-----
C          ***** SUM THE PRESENT VALUES OF REVENUE AND COST COMPONENTS
C-----
C          DISCOUNTED VALUES
C-----
C          CCC - PRESENT VALUE FACTOR
C          SVOS - TOTAL GROSS OIL SOLD, MBBL
C          SVGS - TOTAL GROSS GAS SOLD, MMSCF
C          SVIS - TOTAL SURFACTANT PURCHASED, MMLB
C          SRPV - TOTAL GROSS OIL SALES, MM$
C          SNOS - TOTAL NET OIL SALES
C          SSEV - TOTAL SEVERANCE TAX

```

C SUMOPC- TOTAL VARIABLE OPERATING COST
 C SUMTO - TOTAL OPERATING COST (FIXED+VAR+GEN+WO)
 C SUMFO - TOTAL FIXED OPERATING COSTS
 C SUMTR - TOTAL CHEMICAL HANDLING COST
 C SUMCI - TOTAL INTANGIBLE CAPITAL COSTS
 C SUMWO - TOTAL WELL WORKOVER COSTS
 C SUMWT - TOTAL PROD WATER TREATING COST
 C SINT - TOTAL DEBT INTEREST COST
 C SPRP - TOTAL PRINCIPAL REPAYMENT
 C UNDISCOUNTED VALUES

C -----
 C URPV - TOTAL GROSS REVENUE
 C UNOS - TOTAL NET SALES
 C USEV - TOTAL SEVERENCE TAX
 C USFO - TOTAL FIXED OPERATING COST
 C USOPC - TOTAL VARIABLE OPERATING COST
 C USIN - TOTAL CHEMICAL PURCHASE COST
 C USTR - TOTAL CHEMICAL HANDLING/TREATING COST
 C USWT - TOTAL PRODUCED WATER TREATING COST
 C UWCAP - TOTAL WORKING CAPITAL
 C USTC - TOTAL TANGIBLE CAPITAL
 C USCI - TOTAL INTANGIBLE CAPITAL
 C UCFB - TOTAL CASH FLOW BEFORE TAX
 C UWPT - TOTAL WINDFALL PROFIT TAX
 C USIT - TOTAL STATE INCOME TAX
 C UFIT - TOTAL FEDERAL INCOME TAX
 C UATP - TOTAL AFTER TAX PROFIT
 C UINT - TOTAL INTERERST COST
 C ULOAN - TOTAL PRINCIPAL REPAYMENT

C SVOS = 0.
 C SVON = 0.
 C SVGS = 0.
 C SVIS = 0.0
 C SVPS = 0.0
 C SRPV = 0.
 C SNOS = 0.
 C SSEV = 0.
 C SUMTO = 0.
 C SUMTR = 0.0
 C SUMFO = 0.0
 C SUMOPC = 0.
 C SUMIN = 0.0
 C SUMTR = 0.
 C SUMWO = 0.
 C SUMWC = 0.
 C SUMCI = 0.
 C SUMWT = 0.
 C SINT = 0.0
 C SPRP = 0.0
 C DNB = 0.0
 C TOTD = 0.
 C SSIGFO = 0.
 C SSITRI = 0.
 C SSIGTR = 0.0
 C SSITRT = 0.
 C SSIGO = 0.
 C SSIGG = 0.
 C SUMOH = 0.0
 C USOH = 0.0

```

URPV = 0.
UNOS = 0.0
USEV = 0.0
USTO = 0.0
USOPC = 0.0
USIN = 0.0
USTR = 0.0
USFO = 0.0
UWCAP = 0.0
USTC = 0.0
USCI = 0.0
USWO = 0.0
USWT = 0.0
UCFB = 0.0
UWPT = 0.0
USIT = 0.0
UFIT = 0.0
UATP = 0.0
UINT = 0.0
ULOAN = 0.0
SUMVOM = 0.0
SVIS = 0.0
DCFBT(1) = 0.0
DCFAT(1) = -COSTRT
CDBT(1) = 0.0
CDAT(1) = -COSTRT
C
C   XINVES CORRECTIONS
C   XINVES = MUCT(1) + MUCI(1)
C   ATPR(1) = ATPR(1) + XINVES
C   CDAT(1) = CDAT(1) - XINVES
C   DCFAT(1) = DCFAT(1) - XINVES
C   DO 501 I=2,MYR
C   XX = MUCT(I) + MUCI(I)
C   ATPR(I-1) = ATPR(I-1) - XX
C501 ATPR(I) = ATPR(I) + XX
C
C   ***** DETERMINE PRESENT VALUES OVER PROJECT LIFE
C   IPAY = 999
C   DO 500 I=1,MYR
C   M1 = I-1
C   IF (M1.LE.0) M1=1
C
C   ***** VOLUMES PRODUCED, SOLD, AND INJECTED
C   SUMVOM = SUMVOM + MUVO(I)/UNIT
C   SVOS = SVOS + VOSLD(I)
C   SVON = SVON + VONET(I)
C   SVGS = SVGS + MUVG(I)/UNIT
C   SVIS = SVIS + MUVI(I)/UNIT
C   SVPS = SVPS + VPM(I)/UNIT
C
C   ***** PRESENT VALUE FACTOR
C   CCC = 1.0/(1.0+CC)**(I - 1)
C   CCD = 1.0/(1.0+XINF)**(I - 1)
C   IF (IDISC.LE.0) GO TO 450
C   ***** MID-YEAR DISCOUNTING
C   CCC = 1.0/(1.0+CC)**(FLOAT(I)-1.5)
C   CCD = 1.0/(1.0+XINF)**(FLOAT(I)-1.5)
450 IF (CCC .GT. 1.0) CCC = 1.0
   IF (CCD .GT. 1.0) CCD = 1.0

```

```

C      PVDF(I) = CCC
C
C      ***** CUMULATIVE AMOUNT CORRECTED TO PRESENT VALUE, MM$
C      URPV = URPV + AREV(I)
C      SRPV = SRPV + AREV(I)*CCC
C      ***** NET OIL SALES
C      UNOS = UNOS + ANET(I)
C      SNOS = SNOS + ANET(I)*CCC
C      ***** SEVERANCE TAX
C      USEV = USEV + ASEV(I)
C      SSEV = SSEV + ASEV(I)*CCC
C      ***** OPERATING COST (VARIABLE+FIXED+GEN+W/O)
C      USTO = USTO + ACOST(I)
C      SUMTO = SUMTO + ACOST(I)*CCC
C      ***** VARIABLE OPERATING COST
C      USOPC = USOPC + AVOC(I)
C      SUMOPC = SUMOPC + AVOC(I)*CCC
C      ***** CHEMICAL INJECTION COST
C      USIN = USIN + AINJ(I)
C      SUMIN = SUMIN + AINJ(I)*CCC
C      ***** CHEMICAL HANDLING COST
C      USTR = USTR + ATRC(I)
C      SUMTR = SUMTR + ATRC(I)*CCC
C      ***** FIXED OPERATING COST
C      USFO = USFO + AFOC(I)
C      SUMFO = SUMFO + AFOC(I)*CCC
C      ***** OVERHEAD
C      USOH = USOH + AOVH(I)
C      SUMOH = SUMOH + AOVH(I)*CCC
C      ***** WORKING CAPITAL
C      UWCAP = UWCAP + AWCP(I)
C      SUMWC = SUMWC + AWCP(I)*CCC
C      ***** TANGIBLE CAPITAL
C      USTC = USTC + MUCT(I)
C      TOTD = TOTD + MUCT(I)*CCC
C      ***** INTANGIBLE CAPITAL
C      USCI = USCI + MUCI(I)
C      SUMCI = SUMCI + MUCI(I)*CCC
C      ***** WELL WORKOVER COST
C      USWO = USWO + MUWO(I)
C      SUMWO = SUMWO + MUWO(I)*CCC
C      ***** WATER TREATING AND DISPOSAL COST
C      USWT = USWT + AWTC(I)
C      SUMWT = SUMWT + AWTC(I)*CCC
C      ***** WINFALL PROFIT TAX
C      UWPT = UWPT + AWPT(I)
C      ***** STATE INCOME TAX
C      USIT = USIT + ASTX(I)
C      ***** FEDERAL INCOME TAX
C      UFIT = UFIT + AFIT(I)
C      ***** INTEREST COST
C      UINT=MUIN(I)+UINT
C      SINT=MUIN(I)*CCC+SINT
C      ***** PRINCIPAL REPAYMENTS
C      ULOAN=MUDB(I)+ULOAN
C      SPRP=MURP(I)*CCC+SPRP
C      ***** DISCOUNTED NET BBL
C      DNB = DNB + VONET(I)*CCC
C
C      ***** STD DEVIATION

```

```

      SPOPV = SIGPO(I)*CCC
      SPGPV = SIGPG(I)*CCC
      SOPCP = SIGOPC(I)*CCC
      SFOPV = SIGFO(I)*CCC
      STRPV = SIGTR(I)*VIM(I)*CCC
      SCIPV = SITRI(I)*CCC
      SCTPV = SITRT(I)*CCC
C
C      ***** DAVIDSON EQN-15, ALLOWING OIL VOLUME UNCERTAINTY
      SSIGO = SSIGO + SQRT( MUVO(I)*MUVO(I)*(SPOPV**2+SOPCP**2)
1 + SIGVO(I)*SIGVO(I)*((MUPO(I)*CCC)**2+(MUOPC(I)*CCC)**2))
      SSIGG = SSIGG + MUVG(I)*SPGPV
      SSIGFO = SSIGFO+SFOPV
      SSIGTR = SSIGTR+STRPV
      SSITRI = SSITRI+SCIPV
      SSITRT = SSITRT+SCTPV
C
C      ***** CONSTANT DOLLAR AND DISCOUNTED CASH FLOW
C      DEDUCT INTEREST COST AND PRINCIPAL PAYMENT FROM BEFORE-TAX INCOME
      BTINC = ANOI(I) - MUCI(I)-MUCT(I)-AWCP(I)-MUIN(I)-MURP(I)
      UCFB = UCFB + BTINC
      CDBT(I) = CDBT(M1) + BTINC*CCD
      DCFBT(I) = DCFBT(M1) + BTINC*CCC
      UATP = UATP + ATPR(I)
      CDAT(I) = CDAT(M1) + ATPR(I)*CCD
      DCFAT(I) = DCFAT(M1) + ATPR(I)*CCC
      IF(DCFAT(I).GT.0..AND. IPAY .EQ. 999) IPAY=I
C
500 CONTINUE
C      ATPR(1) = ATPR(1) - XINVES
C      DO 502 I=2,MYR
C      XX = MUCT(I) + MUCI(I)
C      ATPR(I-1) = ATPR(I-1) + XX
C502 ATPR(I) = ATPR(I) - XX
C
C      ***** COMPUTE TOTAL CAPITAL, DEPRECIATION OVER DTIM,
C      ***** AND CAPITAL COEFFICIENT ASSUMING NO RECOVERY(SALVAGE)
C      ***** AND THAT ALL TANGIBLE CAPITAL IS EXPENDED FIRST YEAR
      YC = 0.0
      IF(TOTD.LE.0.) GO TO 550
      DEPAMT = TOTD/DTIM
      CREC = 0.0
      IF(CC .LT. 1.E-6) CC = 1.E-6
      YC = (TOTD - XFIT*DEPAMT*((1+CC)**DTIM-1.)/(CC*(1+CC)**DTIM)
1 - CREC)/TOTD
C
C      ***** COMPUTE DCF MEAN AND STD DEVIATION
C      550 DCFB = DCFBT(MYR)
      MUPPV = DCFAT(MYR)
      CIOR = 0.0
      IF(SUMVOM.LE.0.) GO TO 560
      CIOR = SVIS/SUMVOM
C
C      ***** VARIANCES
C      560 SIGO2 = SSIGO*SSIGO
      SIGG2 = SSIGG*SSIGG
      SIGFO2 = SSIGFO*SSIGFO
      SIGTR2 = SSIGTR*SSIGTR
      SITRI2 = SSITRI*SSITRI
      SITRT2 = SSITRT*SSITRT

```



```

C      ***** DAVIDSON EQN-17, ASSUMES SITRAP=0
      STDDEV = SQRT((1-XFIT)*(SIGO2+SIGG2 + SIGFO2+SITRI2+SIGTR2)
1 + YC*YC*SITRT2)
C
C      ***** PAYOUT (AFTER TAX)
      PAYOUT=IPAY
      IF ( IPAY.GE.PLIFE ) GO TO 499
      IF((DCFAT(IPAY)-DCFAT(IPAY+1)) .NE. 0.00)
& PAYOUT = IPAY+DCFAT(IPAY)/(DCFAT(IPAY)-DCFAT(IPAY+1))
      IF ( PAYOUT .LT. 0 ) PAYOUT= 0
499 IF(PAYOUT.GE.M) PAYOUT=999.99
C
C      ***** COMPUTE DCF RATE OF RETURN
      CALL NEWDCF
      IF(ROR.GT.1000.) ROR = 999.
C
      RETURN
      END
      SUBROUTINE FINCOF (      NI,      P,      PORV,
C      *      *I*      *I*      *I*
C      *      ROK,      PVT,      WTR,
C      *      *I*      *I*      *I*
C      *      PN,      PB,
C      *      *I*      *I*
C      *      PS,      PT,
C      *      *I*      *I*
C      *      AOB,      AWB,      AGB,
C      *      *I*      *I*      *I*
C      *      AOT,      AWT,      AGT,
C      *      *I*      *I*      *I*
C      *      SAOE,      SAOS,      SAOT,
C      *      *I*      *I*      *I*
C      *      SAWE,      SAWS,      SAWT,
C      *      *I*      *I*      *I*
C      *      SAGE,      SAGS,      SAGT,
C      *      *I*      *I*      *I*
C      *      WAGE,      WAGS,      WAGT,
C      *      *I*      *I*      *I*
C      *      AC,      RHS,
C      *      *O*      *O*
C      *      AW,      AN,      AB,
C      *      *O*      *O*      *O*
C      *      AE,      AS,      AT )
C      *      *O*      *O*      *O*
C
C      *****
C      *      F I N C O F      *
C      *****
C      *      FINALIZE COEFFICIENT GENERATION..      *
C      *      .   ADD SOURCE TERMS AND COMPLETE THE RHS.      *
C      *      .   TRANSMIT SYMMETRIC COEFFICIENTS TO SUBROUTINE -SATS-.      *
C      *****
C
      DIMENSION
      *      ROK(NI,7),      P(NI),      PORV(NI),
      *      PN(NI),      PVT(NI,11),      WTR(NI,6),
      *      PS(NI),      PB(NI),
      *      AOB(NI),      AWB(NI),      PT(NI),      AGB(NI),
      *      AOT(NI),      AWT(NI),      AGT(NI),

```

```

*          SAOE (NI),          SAOS (NI),          SAOT (NI),
*          SAWE (NI),          SAWS (NI),          SAWT (NI),
*          SAGE (NI),          SAGS (NI),          SAGT (NI),
*          WAGE (NI),          WAGS (NI),          WAGT (NI),
*          AC (NI),           RHS (NI),
*          AW (NI),           AN (NI),           AB (NI),
*          AE (NI),           AS (NI),           AT (NI)
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'COEF.INC'
      INCLUDE 'STREAM.INC'
      DIMENSION  RHSACC (NXMAX),  BUGRHS (NXMAX),  SACCX (NXMAX),
*              RHSO (NXMAX),      RSHW (NXMAX),      RHSG (NXMAX)
C
      EQUIVALENCE      ( RHSO (1), XTRAN (1) ),      ( RSHW (1), YTRAN (1) ),
*                    ( RHSG (1), DELE (1) ),      ( SACCX (1), DELS (1) ),
*                    ( RHSACC (1), SO (1) ),      ( BUGRHS (1), DELS (1) )
C
      DATA  IBO,      IRSO,      IGO,      IVO,      ICO      /
*          1,          2,          3,          4,          5      /,
*          ICRSO,      IBG,      IGG,      IVG,      ICG      /
*          6,          7,          8,          9,          10     /,
*          IBGLOG      /
*          11          /
      DATA  IKRO,      IKRW,      IKRG,      IPCOW,      IPCOG      /
*          1,          2,          3,          4,          5      /,
*          ISRG      /
*          6          /
      DATA  IBW,      IRSW,      IGW,      IVW,      ICW      /
*          1,          2,          3,          4,          5      /,
*          ICRSW      /
*          6          /
C
C *****
C *      INITIALIZE.      *
C *****
C
      IF ( IFINAL .EQ. 0 )          GO TO 4800
C
C *****
C *      COMPLETE THE RHS VALUES FOR ALL PHASES.      *
C *****
C
      1600 DO 1700 I = IFIRST, IFINAL
          RHSO (I)      = OILRHS (I)
          RSHW (I)      = WTRRHS (I)
      1700 CONTINUE
C
C
      DO 2000 I = IFIRST, IFINAL
          OILRHS (I)      = AOC (I) * P (I) + PVT (I, IBO) * OILRHS (I)
      2000 CONTINUE
C
      DO 2100 I = IFIRST, IFINAL
          WTRRHS (I)      = AWC (I) * P (I) + WTR (I, IBW) * WTRRHS (I)
      2100 CONTINUE
C
C *****

```

```

C      *      GET WELL CONTRIBUTIONS, IF ANY.      *
C      *****
C
      DO 2500 I = IFIRST, IFINAL
        SACX(I)      = 0
        CALL GETWEL ( SACX(I), SRHSX, SQO, SQW, SQG, I ,
          *      WTR(I,IBW),WTR(I,IVW),PVT(I,IBO),PVT(I,IVO),
          *      ROK(I,IKRO),ROK(I,IKRW) )
          RHS(I)      = RHS(I) - PVT(I,IBO) * SQO
          *      - WTR(I,IBW) * SQW
          *      + SRHSX
2500 CONTINUE
C
C      *****
C      *      FORM PRESSURE COEFFICIENTS FROM GENERATED PHASE DATA.      *
C      *****
C
      DO 3000 I = IFIRST, IFINAL
        AW(I)      = AOW(I) + AWW(I)
        AE(I)      = AOE(I) + AWE(I)
3000 CONTINUE
C
      DO 3200 I = IFIRST, IFINAL
        AN(I)      = AON(I) + AWN(I)
        AS(I)      = AOS(I) + AWS(I)
3200 CONTINUE
C
      IF ( NZ .EQ. 1 )      GO TO 3600
C
      DO 3400 I = IFIRST, IFINAL
        AB(I)      = AOB(I) + AWB(I)
        AT(I)      = AOT(I) + AWT(I)
3400 CONTINUE
C
3600 DO 3700 I = IFIRST, IFINAL
        AC(I)      = AC(I) + AOC(I) + AWC(I) + SACX(I)
3700 CONTINUE
C
      DO 3800 I = IFIRST, IFINAL
        RHS(I)      = RHS(I) + OILRHS(I) + WTRRHS(I)
        BUGRHS(I)   = RHS(I)
3800 CONTINUE
C
C      *****
C      *      WRITE SATN EQN COEF FOR USE BY SUBROUTINE -SATS-.      *
C      *****
C
4800      I1      = IFIRST
      CALL SYMOUT (      IFIRST,      IFINAL,      NFIL,
        *      NZ ,
        *      NX,
        *      SAOS(I1),      SAWS(I1),      SAE(I1),
        *      SAWE(I1),      RHSO(I1),      RHSW(I1),
        *      SAOT(I1),      SAWT(I1) )
      IF ( IFINAL .EQ. 0 )      GO TO 8600
C
C      *****
C      *      CONVERT RHS TO RESIDUALS BASED ON OLD-TIME-STEP PRESSURES.      *
C      *****
C

```

```

      INEXT      = IFIRST + 1
      ILAST      = IFINAL - 1
C
      DO 6000 I = IFIRST, IFINAL
         RHSACC(I) = RHS(I)
         RHSACC(I) = RHSACC(I) - AC(I) * P(I)
      6000 CONTINUE
C
      IF ( INEXT .GT. IFINAL )                GO TO 6500
C
      DO 6200 I = INEXT, IFINAL
         RHSACC(I) = RHSACC(I) + AW(I) * ( P(I-1) - P(I) )
      6200 CONTINUE
C
      DO 6400 I = IFIRST, ILAST
         RHSACC(I) = RHSACC(I) + AE(I) * ( P(I+1) - P(I) )
      6400 CONTINUE
C
      6500 IF ( J .EQ. 1 )                      GO TO 6700
      DO 6600 I = IFIRST, IFINAL
         RHSACC(I) = RHSACC(I) + AN(I) * ( PN(I) - P(I) )
      6600 CONTINUE
C
      6700 IF ( J .EQ. NY )                      GO TO 6900
      DO 6800 I = IFIRST, IFINAL
         RHSACC(I) = RHSACC(I) + AS(I) * ( PS(I) - P(I) )
      6800 CONTINUE
C
      6900 IF ( NZ .EQ. 1 )                      GO TO 7600
C
      IF ( K .EQ. 1 )                      GO TO 7100
      DO 7000 I = IFIRST, IFINAL
         RHSACC(I) = RHSACC(I) + AT(I) * ( PT(I) - P(I) )
      7000 CONTINUE
C
      7100 IF ( K .EQ. NZ )                      GO TO 7600
      DO 7200 I = IFIRST, IFINAL
         RHSACC(I) = RHSACC(I) + AB(I) * ( PB(I) - P(I) )
      7200 CONTINUE
C
      7600 DO 7800 I = IFIRST, IFINAL
         RHS(I) = RHSACC(I)
      7800 CONTINUE
C
      *****
C      *      WRAP UP PHASE-WEIGHTED COMPRESSIBILITY VALUES IF THIS IS      *
C      *      THE FINAL GRID ROW.                                           *
C      *****
C
      8600 CONTINUE
C
      9900 RETURN
      END
      SUBROUTINE SYMOUT (      IFIRST1,      IFINL1,      NFIL,
*                           ITWOD,      NW,
*                           SAOS,      SAWS,      SAE,
*                           SAWE,      RHO,      RSW,
*                           SAOT,      SAWT )

```

```

C
C      SYMOUT--STORE THE SATURATION EQUATION COEFFICIENTS IN EXTRA
C      SPACE AT THE BACK OF BLANK COMMON FOR USE IN THE
C      SATURATION EQUATION SOLUTION IN OVER6.
C
C      -----
C
C      DIMENSION          SAOS (NW) ,      SAWS (NW) ,      SAOE (NW) ,
*                          SAWE (NW) ,      RHSO (NW) ,      RHSW (NW) ,
*                          SAOT (NW) ,      SAWT (NW)
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'COEF.INC'
C
C      A (ISCPTR)          = IFIRST + 0.1
C      A (ISCPTR+1)        = IFINAL + 0.1
C      NXTPTR              = ISCPTR + 2 + 8 * NX
C      ISCPTR              = ISCPTR + 2
DO 4500 I = 1, NW
C      A (ISCPTR)          = SAOS (I)
C      A (ISCPTR+1)        = SAWS (I)
C      A (ISCPTR+2)        = SAOE (I)
C      A (ISCPTR+3)        = SAWE (I)
C      A (ISCPTR+4)        = RHSO (I)
C      A (ISCPTR+5)        = RHSW (I)
C      ISCPTR              = ISCPTR + 6
4500 CONTINUE
C
C      5500      IF ( NZ .LE. 1 )              GO TO 8000
C      DO 6000 I = 1, NW
C      A (ISCPTR)          = SAOT (I)
C      A (ISCPTR+1)        = SAWT (I)
C      ISCPTR              = ISCPTR + 2
6000 CONTINUE
C
C      8000      ISCPTR          = NXTPTR
C
C      9900 RETURN
C      END
C      SUBROUTINE GETWEL (SAOX, SRHSX, SQO, SQW, SQG, ICEL ,
*      BW, VW, BO, VO, RO, RW )
C
C      -----
C
C      CALCULATES THE PRODUCTION/INJECTION TERMS USED IN SUBROUTINE COEFS
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'COEF.INC'
C      INCLUDE 'STREAM.INC'
C
C      SAOX = 0
C      SRHSX = 0
C      SQO = 0
C      SQW = 0
C      SQG = 0
C      IF ( ICEL .GT. 1 .AND. ICEL .LT. NX ) RETURN

```

```

IF ( ICEL .EQ. NX ) GO TO 20
IF ( IPROD(MTUBE,K) .EQ. 1 ) RETURN

C
C
C      PRODUCTION WELL IS ALWAYS PRESSURE SPECIFIED

VPO(MTUBE,K) = VPI(MTUBE,K)*RO / (VO*BO + 1.E-20)
VPW(MTUBE,K) = VPI(MTUBE,K)*RW / (VW*BW + 1.E-20)
VAOX(MTUBE,K) = VPO(MTUBE,K)*BO + VPW(MTUBE,K)*BW
SAOX = SAOX + VAOX(MTUBE,K)
VRHSX(MTUBE,K) = VAOX(MTUBE,K) * VPWELL(MTUBE,K)
SRHSX = SRHSX + VRHSX(MTUBE,K)
      RETURN
20 CONTINUE
IF ( IINJ(MTUBE,K) .EQ. 1 ) RETURN
IF ( IGOV.EQ.1 .AND. VRATE1 .LT. 0.0001 ) GO TO 25
      SQW = SQW - VQW(MTUBE,K)
      RETURN
25 CONTINUE

C
C
C      IF THE MODEL IS TO CALCULATE INJECTIVITY DURING INFILL
C      THE INJECTION WELLS ARE SET TO PRESSURE SPECIFICATION
C      OTHERWISE ITS JUST THE KH WEIGHTED VALUES FROM THE USER
C      SPECIFIED INPUT VALUE

VPW1(MTUBE,K)=VPI(MTUBE,K)*VXKRWE/(VW*BW+1.E-20)
VAOX1(MTUBE,K)=VPW1(MTUBE,K)*BW
SAOX = SAOX + VAOX1(MTUBE,K)
VRHSX1(MTUBE,K)=VAOX1(MTUBE,K)*VPWELL1(MTUBE,K)
SRHSX = SRHSX + VRHSX1(MTUBE,K)
      RETURN
      END
      SUBROUTINE OVER5

C
C
C      -----
C
C      OVER5 --- CONTROL ROUTINE FOR THE PRESSURE SOLUTION ROUTINES
C      THIS ROUTINE CALLS OVER5A THAT DOES THE MAPPING OF
C      BLANK COMMON IN THE PRESSURE SOLUTION.
C
C      -----

      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      DIMENSION B(100)
      EQUIVALENCE ( A(1), B(1) )

C
      CALL OVER51

C
      RETURN
      END
      SUBROUTINE LSOR2D (      AO,      AE,      AS,      AW,      AN,
1          R, AWATTS, BWATTS, CWATTS, DWATTS,
2          WEXTRA,      W,      G, PORVOL,      AFR,
3          P,      ABK,      IMAX,      INCI,      JMAX,
4          INCJ, DELTAT, OMEGA, TOLSAT, TOLSUM,
5          ISWEEP, ITERMX, LWATTS, LARGE, INCFR,
6          INCBK, CORREC      )
C
C      *
C      *
C      *      GENERAL PURPOSE 2-DIMENSIONAL LSOR      *

```

```

C      *      FOR USE IN 1-D, 2-D, AND 3-D      *
C      *      PROBLEMS                          *
C      *      ARGUMENTS HAVE BEEN MADE GENERAL TO ACCOMODATE      *
C      *      ANY GRID ORIENTATION AND LINE SOR ORIENTATION      *
C      *      BUT SWEEP ALWAYS PROCEEDS IN A POSITIVE DIRECTION.  *
C      *      *****                                *
C      *      THE FOLLOWING GIVES THE PROPER PARAMETERS OF THE      *
C      *      CALLING PROGRAM FOR THE 6 DIFFERENT ORIENTATIONS.    *
C      *      *
C      *      *
C      *      PLANE--      X-Y      X-Y      X-Z      X-Z      Y-Z      Y-Z      *
C      *      LINE SOR      *
C      *      ORIENT.--- Y      X      Z      X      Z      Y      *
C      *      -----      *
C      *      ARGUMENT      *
C      *      AO      AO      AO      AO      AO      AO      AO      *
C      *      AE      AE      AS      AE      AB      AS      AB      *
C      *      AS      AS      AE      AB      AE      AB      AS      *
C      *      AW      AW      AN      AW      AT      AN      AT      *
C      *      AN      AN      AW      AT      AW      AT      AN      *
C      *      R      R      R      R      R      R      R      *
C      *      IMAX      NX      NY      NX      NZ      NY      NZ      *
C      *      INCI      1      NX      1      NXNY      NX      NXNY      *
C      *      JMAX      NY      NX      NZ      NX      NZ      NY      *
C      *      INCJ      NX      1      NXNY      1      NXNY      NX      *
C      *      -----OTHER ARGUMENTS AND THEIR ( DIMENSIONS )      *
C      *      P      ( IMAX * JMAX )      *
C      *      EITHER PRESSURE OR PRESSURE CHANGE. IF      *
C      *      PRESSURE CHANGE IS USED, IT SHOULD BE PROPERLY      *
C      *      INITIALIZED.      *
C      *      AWATTS ( IMAX )      *
C      *      BWATTS ( IMAX )      *
C      *      CWATTS ( IMAX )      *
C      *      DWATTS ( IMAX )      4 COEFFICIENTS TO COMPUTE CORREC. *
C      *      CORREC ( IMAX )      WATTS CORRECTION.      *
C      *      WEXTRA ( IMAX )      W VECTOR FOR THOMAS ALGORITM      *
C      *      USED IN COMPUTING CORREC.      *
C      *      W      ( JMAX )      WHEN -LARGE- = 0      *
C      *      OR ( IMAX * JMAX ) WHEN -LARGE- = 1      *
C      *      USED FOR NORMALIZATION DURING      *
C      *      LINE SOLUTION.      *
C      *      G      ( JMAX )      G VECTOR FOR THOMAS ALGORITHM.      *
C      *      ALSO STORES PRESSURE CHANGE FOR      *
C      *      PREVIOUS COLUMN      *
C      *      PORVOL ( IMAX * JMAX ) USED ONLY FOR CONVERGENCE      *
C      *      CRITERION.      *
C      *      *****                                *
C      *      -----SINGLE ARGUMENTS      *
C      *      IMAX      NO. OF INCREMENTS IN I DIRECTION      *
C      *      JMAX      NO. OF INCREMENTS IN J DIRECTION      *
C      *      INCI      NO. OF MEM. LOCATIONS BETWEEN I AND I+1      *
C      *      INCJ      NO. OF MEM. LOCATIONS BETWEEN J AND J+1      *
C      *      DELTAT      TIME STEP SIZE      *
C      *      OMEGA      LSOR RELAXATION FACTOR, BETWEEN 1.0 AND 2.0 *
C      *      TOLSAT      SATURATION TOLERANCE, WHEN NON-ZERO.      *
C      *      TOLSUM      TOLERANCE ON SUM OF ABS. RESIDUALS,      *
C      *      WHEN NON-ZERO.      *
C      *      ISWEEP      NO. OF TIMES TO CALL THIS 2-D SOUTION      *
C      *      ITERMX      LIMIT ON NO. OF LSOR ITERATIONS.      *
C      *      LWATTS      MAKE WATTS CORRECTION WHEN NON-ZERO.      *

```

```

C      *      LARGE      INDICATOR WHICH DETERMINES WHETHER THE      *
C      *      W ARRAY FOR THE THOMAS ALGORITHM WILL BE      *
C      *      KEPT ALL IN ARRAY -A- (LARGE = 1) OR JUST      *
C      *      KEPT FOR ONE COLUMN (LARGE = 0)      *
C      *      INCFR      INCREMENT TO ADJACENT POINT IN NEXT SLICE      *
C      *      USED TO UPDATE RESIDUALS OUTSIDE OF THE      *
C      *      PLANE ON A 3-D PROBLEM. USED IN CONJUNCTION*
C      *      WITH AFR. (FR STANDS FOR FRONT) . ZERO WHEN      *
C      *      AN UPDATE IS NOT REQUIRED.      *
C      *      INCBK      SAME AS NOTE ABOVE FOR INCFR. UPDATES      *
C      *      RESIDUAL BEHIND THE PLANE.      *
C      *      AFR      TRANSMISSIBILITY COEFFICIENT FOR (FLOW)      *
C      *      INTO THE ADJACENT POINT IN THE NEXT PLANE.      *
C      *      ABK      SIMILAR TO ABK.      *
C      *****
C      *      NOTES ----      *
C      *      1. IF -LARGE- = 1 AND -ISWEEP- = 1 THEN THE      *
C      *      W NORMALIZED VECTOR IS COMPUTED. IF      *
C      *      -LARGE- = 1 AND -ISWEEP- .GT. 1, THE W      *
C      *      COMPUTATION IS SKIPPED. THUS, THE 3-D      *
C      *      ARRAY FOR W WOULD HAVE TO BE SAVED FOR      *
C      *      THIS CASE.      *
C      *      2. IF -LWATTS- = 0 THEN ON ONE ( IMAX )      *
C      *      VECTOR HAS TO BE SAVED -- FOR CORREC      *
C      *****
C      *      WE ARE SOLVING THIS EQUATION--      *
C      *      AO*P (I,J) -AN*P (I,J-1) -AE*P (I+1,J) -AS*P (I,J+1)      *
C      *      -AW*P (I-1,J) = - R      *
C      *****
C      INCLUDE 'SOLV.INC'
C      INCLUDE 'FILES.INC'
C
C      DIMENSION AO(1), AE(1), AS(1), AW(1), AN(1),R(1), P(1),
1      1 AWATTS(1), BWATTS(1), CWATTS(1), DWATTS(1), CORREC(1),
2      2 WEXTRA(1), W(1), G(1), PORVOL(1), AFR(1), ABK(1)
      LOGICAL NORMAL, TWOD, LAST
      EQUIVALENCE ( GJ, ASP )
1      1 FORMAT (////////42X, 25HDEBUG OUTPUT FROM -PSOLV- / 42X, 25(1H-)/)
2      2 FORMAT ( ///8H OMEGA =, F7.4 // 5H ITN, 5H I, 5H J, 10X,
1      1 9HRESIDUALS / 24X, 3HMAX, 5X, 7HSUM ABS / 3(5H ---), 5X,
2      2 2(10H -----) / )
C
      DEBUG = 0.0
      IF ( TSATX .NE. 0 ) TOLSAT = TSATX
      IF ( TSUMX .NE. 0 ) TOLSUM = TSUMX
      IF ( OMEG .NE. 0 ) OMEGA = OMEG
      NODES = IMAX * JMAX
      IPALL = 0
      IPRES = 0
C      IPRES = 1
C      IPALL = 1
20      CONTINUE
      IF (IPRES .NE. 0) WRITE(IW,1)
      TSUM = TOLSUM
      TSAT = TOLSAT / DELTAT
      IF (IPRES .NE. 0 .AND. TOLSUM .EQ. 0) TSUM = 1.0E+20
      IF (IPRES .NE. 0 .AND. TOLSAT .EQ. 0) TSAT = 1.0E+20
C      SET INDICATOR IF NORMALIZED VECTOR, W, HAS BEEN
C      SAVED FROM A PREVIOUS SWEEP.

```



```

                                NORMAL = .FALSE.
IF ( LARGE .EQ. 1 .AND. ISWEEP .GT. 1 )    NORMAL = .TRUE.
                                INCW = INCJ
IF ( LARGE .EQ. 0 )    INCW = 1

                                TWOD = .FALSE.
IF ( INCFR .EQ. 0 .AND. INCBK .EQ. 0 )    TWOD = .TRUE.
    EXTRAP = 1 - OMEGA
IL = 1
JL = 1
IJL = 1
IF ( ISWEEP .GT. 1 )                                GO TO 51
IF ( IPALL .EQ. 0 ) GO TO 51
    WRITE(IW,48)
48 FORMAT (3X,1HI,4X,1HJ,9X,2HAO,13X,2HAE,13X,2HAS,13X,2HAW,13X,2HAN,
1      14X,1HR, / 2(5H ----),6(15H -----) / )
    DO 50 J = 1, JMAX
        DO 50 I = 1, IMAX
            IJ = 1 + (I-1) * INCI + (J-1) * INCJ
            WRITE(IW,49) I, J, AO(IJ), AE(IJ), AS(IJ), AW(IJ),
1              AN(IJ), R(IJ)
49 FORMAT (1X,I4,I5,6E15.5)
50 CONTINUE
51 CONTINUE
    IF ( IPRES.NE. 0 ) WRITE(IW,2) OMEGA
    N = 0
    CALL ZEROS ( CORREC, IMAX )
    CALL ZEROS ( G, JMAX )
    IF ( LWATTS .EQ. 0 )    GO TO 100
C *****
C * THE WATTS METHOD IS APPLIED ON EACH ITERATION. *
C * AN ADDITIVE CORRECTION IS COMPUTED FOR EACH COL.WHICH *
C * CAUSES THE RESIDUALS TO SUM TO ZERO FOR EACH *
C * COLUMN. THIS ACCELERATES BOTH EARLY AND *
C * ASYMPTOTIC CONVERGENCE. SEE SPE PAPER BY J. W. *
C * WATTS, PRESENTED IN DALLAS - FEB., 1970. *
C * THE FOLLOWING ARE TRI-DIAGONAL COEFFICIENTS USED TO *
C * COMPUTE THE ADDITIVE CORRECTION -CORREC- *
C *****
C COMPUTE COEFFICIENTS FOR TRI-DIAGONAL WATTS CORRECTION
DO 60 I = 1, IMAX
    AWATTS(I) = 0
    BWATTS(I) = 0
    CWATTS(I) = 0
    IJ = 1 + (I-1) * INCI - INCJ
    DO 60 J = 1, JMAX
        IJ = IJ + INCJ
        AWATTS(I) = AWATTS(I) - AW(IJ)
        BWATTS(I) = BWATTS(I) + AO(IJ) - AN(IJ) - AS(IJ)
        CWATTS(I) = CWATTS(I) - AE(IJ)
60 CONTINUE
C MAIN LOOP STARTS HERE .
100 IF ( LWATTS .EQ. 0 ) GO TO 200
C SUM RESIDUALS
DO 110 I = 1, IMAX
    IJ = 1 + (I-1) * INCI - INCJ
    DWATTS(I) = 0
    DO 110 J = 1, JMAX
        IJ = IJ + INCJ
        DWATTS(I) = DWATTS(I) + R(IJ)
110 CONTINUE

```

```

C      COMPUTE WATTS CORRECTION -CORREC-
      CALL TRIDIA ( AWATTS, BWATTS, CWATTS, DWATTS, WEXTRA,
1          CORREC, IMAX )
200 CONTINUE
C      *****
C      *   BEGIN LSOR SWEEP FROM HERE TO STMT. 300   *
C      *   RESIDUALS ARE UPDATED AS WE GO.  THE PRESSURE   *
C      *   CHANGE ON EACH ITERATION IS ADDED TO THE TOTAL   *
C      *   SOLUTION.  W IS THE W TERM IN THE THOMAS ALGORITHM *
C      *****
      N = N + 1
      DO 300 I = 1, IMAX
          IJ = 1 + (I-1) * INCI - INCJ
          JW = IJ
          IF ( LARGE .EQ. 0 )    JW = 0
          AOP = 0
          CORRI = CORREC(I)
          CORRIP = CORREC(I+1)
          DO 250 J = 1, JMAX
              IJ = IJ + INCJ
              JW = JW + INCW
C              WE HAVE SAVED THE PRES. CHANGE FROM LAST COLUMN IN G(J)
              DPLEFT = G(J)
              G(J) = 0
              IF ( AO(IJ) .EQ. 0 )    GO TO 245
              IF ( NORMAL )          GO TO 240
              W(JW) = AO(IJ)
              IF ( AOP .EQ. 0 )      GO TO 240
              W(JW) = AO(IJ) - ( AN(IJ) * ASP ) / WP
C              UPDATE RESIDUALS
240          R(IJ) = R(IJ) + AW(IJ) * DPLEFT
              *
              *           + AE(IJ) * CORRIP
              *           - ( AO(IJ) - AN(IJ) - AS(IJ) ) * CORRI
              GJ = R(IJ)
              IF ( J .NE. 1 )    GJ = GJ + AN(IJ) * G(J-1)
              G(J) = GJ / W(JW)
              WP = W(JW)
              ASP = AS(IJ)
              AOP = AO(IJ)
245          NOTE GJ AND ASP ARE EQUIVALENCED
C          250 CONTINUE
C          BACK SUBSTITUTION IN THOMAS ALGORITHM
              J = JMAX + 1
              IJ = 1 + (I-1) * INCI + JMAX * INCJ
              JW = 1 + JMAX * INCW
              IF ( LARGE .NE. 0 )    JW = IJ
259          LAST = .TRUE.
260          J = J - 1
              IJ = IJ - INCJ
              JW = JW - INCW
              IF ( J .LT. 1 )      GO TO 300
              IF ( AO(IJ) .EQ. 0 )    GO TO 259
              IF ( LAST )          GO TO 280
              G(J) = G(J) + AS(IJ) * GLAST / W(JW)
280          LAST = .FALSE.
              GLAST = G(J)
              PD = G(J) * OMEGA
C          UPDATE RESIDUALS ON ADJACENT CELLS.  PRESENT CELL
C          IS EXTRAPOLATED PAST ZERO RESIDUAL.  R = R * ( 1 - OMEGA )
              R(IJ) = R(IJ) * EXTRAP

```

```

      IF ( I .NE. 1 )      R(IJ-INCI) = R(IJ-INCI) + AE(IJ-INCI) * PD
      PD = PD + CORREC(I)
      IF ( TWOD )          GO TO 290
      IF ( INCFR .NE. 0 )  R(IJ+INCFR) = R(IJ+INCFR) +
1                          AFR(IJ+INCFR) * PD
      IF ( INCBK .NE. 0 )  R(IJ+INCBK) = R(IJ+INCBK) +
1                          ABK(IJ+INCBK) * PD
290 CONTINUE
      G(J) = PD
      P(IJ) = P(IJ) + G(J)
      GO TO 260
300 CONTINUE
      IF ( N .GE. ITERM )  GO TO 600
      IF ( OMDIFF .NE. 0 )
*      CALL OPTMIZ ( N, R(1), AO(1), NODES, 0 )
      IF ( LARGE .NE. 0 )  NORMAL = .TRUE.
      REPEAT = 0
C *****
C *      CHECK ON TOLSAT CONVERGENCE CRITERION.  THIS *
C *      ASSURES THE WORST VOLUMETRIC ERROR IN SATURATIONS *
C *      WILL BE LESS THAN TOLSAT.  SEE FORUM ARTICLE BY *
C *      R. A. WATTENBARGER IN JOUR. PET. TECH. - NOVEMBER, *
C *      1968. *
C *****
      IF ( TSAT .EQ. 0 )      GO TO 400
                                  RMAX=0
310      IF ( AO(IJL) .EQ. 0 )      GO TO 320
      IF ( ABS(R(IJL)).GT. ABS( TSAT * PORVOL(IJL) ) ) REPEAT = 1
      IF ( DEBUG .EQ. 0 )      GO TO 315
      IF (ABS(R(IJL)) .LE. ABS(RMAX)) GO TO 320
      IMAXL= IL
      JMAXL= JL
      RMAX = R(IJL)
      GO TO 320
315 IF ( REPEAT .EQ. 1 )      GO TO 400
320      IL = IL + 1
      IJL = IJL + INCI
      IF ( IL .LE. IMAX )      GO TO 310
      IL = 1
      JL = JL + 1
      IJL = 1 + ( JL - 1 ) * INCJ
      IF ( JL .LE. JMAX )      GO TO 310
      IF ( DEBUG .EQ. 0 )      GO TO 400
      IL = 1
      JL = 1
      IJL = 1
C *****
C *      CHECK SUM OF ABSOLUTE RESIDUALS FOR CONVERGENCE *
C *      CRITERION *
C *****
400 IF ( TSUM .EQ. 0 )      GO TO 500
      SUMABS = 0
      DO 450 I = 1, IMAX
      IJ = 1 - INCJ + ( I - 1 ) * INCI
      DO 450 J = 1, JMAX
      IJ = IJ + INCJ
      SUMABS = SUMABS + ABS ( R(IJ) )
450 CONTINUE
      IF ( SUMABS .GT. TSUM )      REPEAT = 1
500 CONTINUE

```

```

      IF (IPRES.NE. 0) WRITE(IW,501) N, IMAXL, JMAXL, RMAX, SUMABS
501  FORMAT (3I5,5X,2E10.2)
      IF ( REPEAT .EQ. 1 )      GO TO 100
      IF ( OMDIFF .NE. 0 )
      *   CALL OPTMIZ ( N, R(1), AO(1), NODES, 1 )
      RETURN
600  IF ( ITERMX .GT. 1 )      WRITE(IW,601) ITERMX, RMAX, SUMABS
601  FORMAT (10X,48HLSOR2D REACHED THE MAXIMUM LIMIT OF ITERATIONS,
      *   ,      7H SET AT , I10 / 10X,11HMAX RESID = , E10.2, 5X,
      *   17HSUM(ABS(RESID)) = , E10.2 )
      RETURN
      END
      SUBROUTINE TRIDIA ( A, B, C, D, W, U, N )
C *****
C *   SOLUTION OF TRI-DIAGONAL MATRIX WITH THOMAS ALGORITHM *
C *   EQUATION FORM IS - - *
C *   A * U(I-1) + B * U(I) + C * U(I+1) = D *
C *   NOTES --- *
C *   1. THE D VECTOR IS CLOBBED DURING *
C *   THE FORWARD SWEEP. *
C *   2. THE B VECTOR IS PRESERVED. *
C *   3. IF THE USER DOES NOT NEED TO SAVE *
C *   THE B VECTOR, HE MAY EQUIVALENCE *
C *   B AND W IN HIS CALLING ARGUMENTS. *
C *****
      DIMENSION A(1), B(1), C(1), D(1), W(1), U(1)
      W(1) = B(1)
      IF ( W(1) .NE. 0 )
1    D(1) = D(1) / W(1)
      DO 50 I = 2, N
        W(I) = B(I)
        IF ( W(I-1) .NE. 0 )
1    W(I) = B(I) - ( A(I) * C(I-1) ) / W(I-1)
50  CONTINUE
      DO 60 I = 2, N
        IF ( W(I) .NE. 0 )
1    D(I) = ( D(I) - A(I) * D(I-1) ) / W(I)
60  CONTINUE
C   BACK SUBSTITUTION
      J = N
      U(J) = D(J)
      DO 70 I = 2, N
        J = J - 1
        IF ( W(J) .NE. 0 )
1    U(J) = D(J) - ( C(J) * U(J+1) ) / W(J)
70  CONTINUE
      RETURN
      END
      SUBROUTINE OPTMIZ ( ITER, RES, AO, NODES, KNVRGD )
C *****
C *   ADAPTIVE AND APPROXIMATE OPTIMIZATION OF -OMEGA-, THE SOR *
C *   OVERRELAXATION PARAMETER. TECHNIQUE, DEVISED BY R.A.W., *
C *   INVOLVES ADJUSTING -OMEGA- BY SMALL INCREMENTS AT THE END *
C *   OF EACH ITERATIVE SOLUTION DEPENDING ON WHETHER -OMEGA- *
C *   VALUE WAS FOUND TO BE ABOVE OR BELOW ITS OPTIMUM. THE *

```

```

C      *      LATTER QUESTION IS ANSWERED BY OBSERVING THE VALUE OF THE      *
C      *      EXPRESSION ( RHO - OMEGA + 1.0 ). IDEALLY, ITS VALUE IS      *
C      *      ZERO WHEN -OMEGA- IS ABOVE ITS OPTIMUM. BELOW, ITS VALUE      *
C      *      SHOULD ALWAYS BE POSITIVE.                                  *
C      *      *****
C      *      CALLS WITH -KNVRGD- .EQ. 0 ---
C      *      MADE FOR EACH ITERATION TO PERMIT ACCUMULATION OF DATA
C      *      (IN -ANORM)- FOR COMPUTING -RHO-.
C      *      *****
C      *      CALL WITH -KNVRGD- .NE. 0 ---
C      *      MADE AFTER CONVERGENCE CRITERION IS MET, TO PERMIT THE
C      *      ADJUSTMENT OF -OMEGA-.
C      *      *****
C
C
C
100 FORMAT ( 25H FROM -OPTMIZ-... ITER = , I3, 9H RHO = ,
*          E12.4, 15H OLD OMEGA = , F6.3,
*          15H NEW OMEGA = , F6.3 )
C
C      OMDIFF      = 0.1      (DEFAULT)  IS SET AT INI39210
C      IF ( OMDIFF .GT. 0.2 )      OMDIFF      = 0.2
C      IF ( OMDIFF .LT. 0.01 )      GO TO 9900
C
C      IF ( KNVRGD .NE. 0 )      GO TO 8000
C
C      IF ( OMBUG .GT. 1 )      GO TO 4000
C      IF ( ITER .GT. 1 )      GO TO 3000
C
C      SCAN -RES- FOR LOCATION OF MAXIMUM ABSOLUTE VALUE
C
C      ABSMAX      = 0
C      DO 2000 I = 1, NODES
C      IF ( AO(I) .EQ. 0 )      GO TO 2000
C      IF ( ABS ( RES(I) ) .LT. ABSMAX )      GO TO 2000
C      ABSMAX      = ABS ( RES(I) )
C      IJKLOC      = I
2000 CONTINUE
C
3000      ANEW      = ABS ( RES(IJKLOC) )
C      GO TO 6000
C
C      DEBUG OPTION.. CALCULATE -ANEW- AS SUM OF ABS ( RES )
C
C      4000      ANEW      = 0
C      DO 5000 I = 1, NODES
C      IF ( AO(I) .EQ. 0 )      GO TO 5000
C      ANEW      = ANEW + ABS ( RES(I) )
5000 CONTINUE
C
C      ACCUMULATE LAST ELEVEN -ANEW- VALUES IN -ANORM-
C
C      6000      IF ( ITER .GT. 11 )      GO TO 6500
C      ANORM(ITER)      = ANEW
C      GO TO 9900
C
C      6500 DO 7000 I = 1, 10
C      ANORM(I)      = ANORM(I+1)
7000 CONTINUE
C      ANORM(11)      = ANEW

```

C
C
C
C

C
C
C

c
c
c

C

C

C

C

C

c

C

C

c
a

C

C

* MODIFIED. THE DIMENSIONS SHOWN ARE FOR A 3-D GRID. IF NZ IS 1
* OR IF THE -LAYER- OPTION IS ACTIVE, THE DIMENSIONS OF ALL

```

C      * VARIABLES WHOSE NAME ENDS WITH -T- OR -B- ARE REDUCED TO 0.      *
C      *                                                                    *
C      *          VALUES TAKEN ON BY PARAMETERS (ABOVE) FOR SIZING      *
C      *          THE PASSAROUND ARRAYS...                                *
C      *          PARAMETER      NY .GE. NZ      NY .LT. NZ              *
C      *          NYP            1                NY                    *
C      *          NZP            NZ                1                    *
C      *          *****
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'SATC.INC'
C      DIMENSION      B(100)
C      EQUIVALENCE      ( A(1), B(1) )
C
C
C      *****
C      *      INITIALIZE.      *
C      *****
C
C
C      LAYER      = NXNYNZ
C      LAYER2     = NXNYNZ * ( 1 )
C      JS        = 0
C      KT        = 0
C      JN        = NX
C      KB        = NX
C      KSUDO     = 1
C      ASSUME 2-D, SCAN BY ROWS.
C      KASE      = 1
C      K         = NZ
C      J         = 1
C      KPAROZ    = 0
C      JPAROZ    = 2
C      IF ( NZ .LE. 1 )      GO TO 1800
C      IF ( NY .LT. NZ )    GO TO 1500
C
C      FULL 2-D GRID, SCAN BY X-Z PLANES.
C
C      KASE      = 2
C      KPAROZ    = 2
C      JPAROZ    = NZ + 1
C      GO TO 1800
C      CONTINUE
1500
C
C      SCAN BY X-Y PLANES
C
C      KASE      = 3
C      K= NZ
C      KPAROZ = NY+1
C      J=1
C
C      1800      JPLANE      = NX * JPAROZ
C      KPLANE      = NX * KPAROZ
C
C      IP          = 1
C      ILOGAS      = IP + LAYER2
C      ILOGAS      = ILOGAS - LAYER

```

```

ISATO      = ILOGAS + LAYER
ISATW      = ISATO + LAYER
IPORV      = ISATW + LAYER
IPCON      = IPORV + LAYER
ITRX       = LASTIN
IPVT       = ITRX + LAYER
ISVRSO     = IPVT + 11 * NX
ISAOS      = ISVRSO + LAYER
ISAOS      = ISVRSO
ISAWS      = ISAOS + JPLANE
ISAGS      = ISAWS + JPLANE
ISAOT      = ISAGS + JPLANE
ISAWT      = ISAOT + KPLANE
ISAGT      = ISAWT + KPLANE
ILAST      = ISAGT + KPLANE
ILAST      = ILAST + 1
NZERO      = ILAST + 1 - ISAOS
2600      IF ( NCORE .EQ. -1 )          GO TO 2800
          IEXCES(6) = NCORE - ILAST
          GO TO 9900
2800      CONTINUE
          CALL INISAT ( A(ISVRSO), A(ILOGAS) )
          CALL ZEROS ( A(ISAOS), NZERO )

C
C
C *****
C *   TOP OF MAIN LOOP.   *
C *****
C
4000      IJK0      = ( J - 1 ) * NX + ( K - 1 ) * NXNY
          L         = IJK0
          LS        = L + NX
          LT        = L - NXNY
          IF ( LT .LT. 0 )          LT      = 0
          JS        = JS + NX
          IF ( JS .GE. JPLANE )     JS      = 0
          JN        = JN + NX
          IF ( JN .GE. JPLANE )     JN      = 0
          KT        = KT + NX
          IF ( KT .GE. KPLANE )     KT      = 0
          KB        = KB + NX
          IF ( KB .GE. KPLANE )     KB      = 0

C
          CALL SATSOL (      NX,      LAYER,      A(KSUDO),
*                          B(IP+L),      B(IP+LS),      B(IP+LT),
*                          A(IPORV+L),    A(IPVT),      A(ILOGAS),
*                          A(ISATO),      A(ISATW),      A(IPCON+L),
*                          A(ISAOS+JN),    A(ISAWS+JN),    A(ISAGS+JN),
*                          A(ISAOT+KB),    A(ISAWT+KB),    A(ISAGT+KB),
*                          A(ISAOS+JS),    A(ISAWS+JS),    A(ISAGS+JS),
*                          A(ISAOT+KT),    A(ISAWT+KT),    A(ISAGT+KT))

C
C
C
C      GO TO ( 8100, 8200, 8300 ),      KASE
      IF ( KASE - 2 )      8100,      8200,      8300

C
8100      J         = J + 1
          IF ( J .LE. NY )          GO TO 8500
          GO TO 8600

```



```

C
8200      K          = K - 1
          IF ( K .GT. 0 )          GO TO 8500
          K          = NZ
          J          = J + 1
          IF ( J .LE. NY )          GO TO 8500
          GO TO 8600

```

```

C
8300      J          = J + 1
          IF ( J .LE. NY )          GO TO 8500
          J          = 1
          K          = K - 1
          IF ( K .GT. 0 )          GO TO 8500
          GO TO 8600

```

```

C
8500      GO TO 4000

```

```

C
C *****
C *      END OF MAIN LOOP.      *
C *****

```

```

C
8600      CONTINUE

```

```

C
9900      CONTINUE
          RETURN
          END
          SUBROUTINE INISAT (      SAVRSO,      RSARR )
                                *O*      *I*

```

```

C
C -----
C
C      INISAT-- ZERO OUT SATURATION SOLUTION VARIABLE BEFORE EACH
C                TUBE SOLUTION OF THE SATURATION EQUATIONS
C
C -----

```

```

C
C      DIMENSION      SAVRSO(1),      RSARR(1)

```

```

C
          INCLUDE 'PARAM.INC'
          INCLUDE 'SIMUL.INC'
          INCLUDE 'STREAM.INC'
          INCLUDE 'SATC.INC'

```

```

C
          CALSAT      = 1
          IVF          = 1
          IF ( NZ .EQ. 1 )      IVF      = 0
          XPOIL        = 1
          XPWAT        = 1
          XPGAS        = 1
          IPRT         = 0
          IFIRST = 1
          IFINAL = NX
          ISCPTR      = ISCZER
          KSCPTR      = ISCZER
          SWLHS       = 0
          SOLHS       = 0
          PVLHS       = 0
          OIPOLD      = OIP
          WIPOLD      = WIP
          GIPOLD      = GIP

```

```

1200      CONTINUE
          IF (MTUBE .GT. 1 ) GO TO 9999
          OIP          = 0
          WIP          = 0
          GIP          = 0
9999 CONTINUE
          RETURN
          END
          SUBROUTINE PVTFUN ( NI,  P,  PV,  PVT )
                        *I* *I* *I* *O*
C
C
C *****
C *      A SUBROUTINE TO OBTAIN EMPIRICAL FUNCTION VALUES ( EXCEPT *
C *      FOR WATER PVT) FOR ALL ACTIVE CELLS IN THE (J,K)TH GRID      *
C *      ROW.                                                            *
C *****
C
C      DIMENSION          P (NI),    PV (NI),    PVT (NI,11)
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'SATC.INC'
C
C      DATA      IBO,      IRSO,      IGO,      IVO,      ICO      /
C      *          1,        2,        3,        4,        5        /,
C      *          ICRSO,    IBG,      IGG,      IVG,      ICG      /
C      *          6,        7,        8,        9,      10      /,
C      *          IBGLOG      /
C      *          11        /
C
C      HLFGRD      = 1.0 / 288.0
C
C      DO 1200 I = IFIRST, IFINAL
C      IJK          = IJK0 + I
C      NPVT(I)      = 1
C      PIJK         = P (I)
C
C      DUMMY GAS PROPERTY VALUES FOR FUTURE EXPANSION
C
C      PVT(I,IBG) = 1.0
C      DG(I) =0.08
C      PVT(I,IVG)= 0.01
C      PVT(I,IBGLOG) = PVT(I,IBG)
C      PVT(I,IGG)   = DG(I) * HLFGRD / PVT(I,IBG)
C      PVT(I,ICG)   = 0.001
1200 CONTINUE
C
C
C
C      DO 2000 I = IFIRST, IFINAL
C      IF ( PV(I) .EQ. 0 )
C      IJK          = IJK0 + I
C      PIJK         = P (I)
C      CALL PROIL ( I, J, PIJK, PVT(I,IBO), PVT(I,IRSO), DENSO,
C      *          PVT(I,IVO), 4, NPVT(I) )
C      PVT(I,IGO)   = HLFGRD * DENSO
C      PVT(I,ICO)   = CMPOIL
C      PVT(I,ICRSO) = 0.0

```

2000 CONTINUE

C

9900 RETURN

END

C SUBROUTINE SATSOL (NI, NA, PN,
* *I* *I* *I*
C P, PS, PT,
* *I* *I* *I*
C PORVOL, PVT, RSARR,
I *S* *IO*
C SATO, SATW, CONPOL,
IO *IO* *IO*
C SYMAON, SYMAWN, SYMAGN,
I *I* *I*
C SYMAOB, SYMAWB, SYMAGB,
I *I* *I*
C SYMAOS, SYMAWS, SYMAGS,
O *O* *O*
C SYMAOT, SYMAWT, SYMAGT)
O *O* *O*

C

C

C

C

C

C

C

C

C

SATSOL- PERFORM THE ACTUAL EXPLICIT SATURATION EQUATION SOLUTION
ONE CELL AT A TIME FOR EACH STREAMTUBE.

C DIMENSION PN (NA), P (NI), PS (NI), PT (NI),
* PORVOL (NI), PVT (NI, 11), RSARR (NA),
* SATO (NA), SATW (NA), CONPOL (NI),
* SYMAON (NI), SYMAWN (NI), SYMAGN (NI),
* SYMAOB (NI), SYMAWB (NI), SYMAGB (NI),
* SYMAOS (NI), SYMAWS (NI), SYMAGS (NI),
* SYMAOT (NI), SYMAWT (NI), SYMAGT (NI)

C

INCLUDE 'PARAM.INC'
INCLUDE 'SIMUL.INC'
INCLUDE 'STREAM.INC'
INCLUDE 'SATC.INC'

C

10 FORMAT (3I5, 5E20.8)

11 FORMAT (3I5, 6E16.8)

C

DATA IBO, IRSO, IGO, IVO, ICO /
* 1, 2, 3, 4, 5 /,
* ICRSO, IBG, IGG, IVG, ICG /
* 6, 7, 8, 9, 10 /,
* IBGLOG /
* 11 /

C

C

C

C

*****INITIALIZE FOR NEW STREAMTUBE

SYMAOW = 0
SYMAWW = 0
PIP = 0
PJP = 0
PKM = 0
BO = 1

```

      KZ          = K
C
C      GET THE SYMMETRIC FLOW COEFFICIENTS SOTRED AWAY IN SYMOUT PRIOR
C      TO THE PRESSURE SOLTUION
C
      CALL SYMINN ( IFIRST,          IFINAL,          NFIL,
*                  NZ ,          NX,
*                  SYMAOS(1),      SYMAWS(1),      SYMAOE(1),
*                  SYMAWE(1),      RHSO(1),      RHSW(1),
*                  SYMAOT(1),      SYMAWT(1)      )
      IF ( IFINAL .NE. 0 )          GO TO 100
      CALL ZEROS ( SYMAOS(1), NX )
      CALL ZEROS ( SYMAWS(1), NX )
      IF ( IVF .EQ. 0 )          GO TO 1000
      CALL ZEROS ( SYMAOT(1), NX )
      CALL ZEROS ( SYMAWT(1), NX )
      GO TO 1000
100  CONTINUE
C
C      GET PVT VALUES NEED FOR CONVERTING THE STANDARD VOLUMES FROM THE
C      SATURATION EQUATION SOLUTION TO SATURATIONS.
C
      CALL PVTFUN ( NI, P(1), PORVOL(1), PVT(1,1) )
C
      DO 999  I = 1, NX
C
C          CALCULATIONS NEEDED REGARDLESS OF WHICH PHASES ARE
C          PRESENT.
C
          IF ( I .GE. IFIRST .AND. I .LE. IFINAL )      GO TO 110
          SYMAOS(I)      = 0
          SYMAWS(I)      = 0
          SYMAOE(I)      = 0
          SYMAWE(I)      = 0
          IF ( IVF .EQ. 0 )      GO TO 999
          SYMAOT(I)      = 0
          SYMAWT(I)      = 0
          GO TO 999
110  CONTINUE
          IF (PORVOL(I) .EQ. 0)      GO TO 999
          IJK      = IJK0 + I
          PIJ      = P(I)
          IF (I .LT. NX) PIP = P(I + 1)
          IF (J .LT. NY) PJP = PS(I)
          IF (K .GT. 1) PKM = PT(I)
          DPIP      = P(I) - PIP
          DPJP      = P(I) - PJP
          DPKM      = P(I) - PKM
C
C      CELL PORE VOLUME AT PIJ
C
          CALL PORE ( PV, PORVOL(I), PIJ , ROKCMP )
          DPPV      = PV
          WATSTC     = 0
          OILSTC     = 0
          DTOPV      = DELTAT / PV
C
C      WELL CONTRIBUTIONS.
C
          SQO      = 0

```

```

SQW    = 0
SQG    = 0
CALL PUTWEL ( SQO, SQW,  SQG, I, PIJ )

C
C      WATER PHASE AND OIL PHASE SYMETRIC FLOW TERMS TIMES
C      DELTA P GIVE THE STANDARD CONDITION FLOW RATE BETWEEN
C      THIS CELL AND THE ONE TO ITS RIGHT AND ABOVE IT.
C

      IF ( I .GT. 1 ) SYMAWW = SYMAWE(I-1)
      RHSW(I)= RHSW(I) - SQW
      SYMAWE(I) = SYMAWE(I) * DPIP
      SYMAWS(I) = SYMAWS(I) * DPJP
      IF ( IVF .EQ. 0 )          GO TO 120
      SYMAWT(I) = SYMAWT(I) * DPKM
120    CONTINUE
      IF ( I .GT. 1 ) SYMAOW = SYMAOE(I-1)
      RHSO(I)= RHSO(I) - SQO
      SYMAOE(I) = SYMAOE(I) * DPIP
      SYMAOS(I) = SYMAOS(I) * DPJP
      IF ( IVF .EQ. 0 )          GO TO 140
      SYMAOT(I) = SYMAOT(I) * DPKM
140    CONTINUE
160    CONTINUE

C
C      WATER SATURATION.
C
200  CONTINUE
      BW    = DENWST/ ( DENWTR * ( 1.0 - CMPWTR *
*                               ( REFPRE - PIJ ) ) )
      RSW    = 0
      WATFLO = 0
      QWTOT  = QWTOT + SQW

C
C      WATFLO IS MASS BALANCE ON WATER
C
      WATFLO = RHSW(I) + SYMAWW      - SYMAWE(I)
*              + SYMAWN(I) - SYMAWS(I)
      IF (IVF .EQ. 0) GO TO 250
      WATFLO  = WATFLO + SYMAWB(I) - SYMAWT(I)
250  CONTINUE
      SW      = BW * DTOPV * WATFLO
      WATSTC  = DPPV * SW / BW

C
C      OIL SATURATION
C
      QOTOT  = QOTOT + SQO
      BO     = PVT(I,IBO)
      RSO    = 0
      OILFLO = 0

C
C      OILFLO IS MASS BALANCE ON OIL
C
      OILFLO = RHSO(I) + SYMAOW      - SYMAOE(I)
*              + SYMAON(I) - SYMAOS(I)
      IF (IVF .EQ. 0) GO TO 450
      OILFLO  = OILFLO + SYMAOB(I) - SYMAOT(I)
450  CONTINUE
      SO      = BO * DTOPV * OILFLO
      SG      = 1.0 - SO - SW
      SO      = SO / ( 1.0 - SG )

```

```

500      SW      = SW / ( 1.0 - SG )
      CONTINUE
      OILSTC = DPPV * SO / BO
      SATW(IJK)= SW
      SATO(IJK)= SO
C
C      GAS SATURATION.
C
      SG      = 0
900      CONTINUE
C      *****
C      *   ACCUMULATE OVERALL FLUIDS IN PLACE   *
C      *****
      OIP  = OIP + OILSTC
      WIP  = WIP + WATSTC
999      CONTINUE
C
1000     CONTINUE
      RETURN
      END
      SUBROUTINE PUTWEL (SQO, SQW, SQG, I , PIJ )
C
C      -----
C
C      PUTWEL--- CALCULATE THE WELL FLOW RATES FOR THE PRESSURE SPECIFIED
C                  WELLS BASED ON THE PRESSURE SOLUTION JUST FINISHED.  PAS
C                  THESE BACK TO THE SATURATION SOLUTION ROUTINE SATSOL
C
C      -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'STREAM.INC'
      INCLUDE 'SATC.INC'
C
      IF ( I.GT. 1 .AND. I .LT. NX ) RETURN
      IF ( I.EQ.NX ) GO TO 20
C
C      PRODUCTION WELL , DO BOTH PHASES
C
      IF ( IPROD(MTUBE,K) .EQ. 1 ) RETURN
      DP = 0.0
      DP = PIJ - VPWELL(MTUBE,K)
      QO = VPO(MTUBE,K) * DP
      VPO(MTUBE,K) = QO
      QW = VPW(MTUBE,K) * DP
      VPW(MTUBE,K) = QW
      SQO  = SQO + QO
      SQW  = SQW + QW
      RETURN
20     CONTINUE
      IF ( IINJ(MTUBE,K) .EQ. 1 ) RETURN
      IF ( IGOV .EQ. 1 .AND. VRATE1 .LT. 0.0001 ) GO TO 25
C
C      INJECTION WELL RATE SPECIFIED CASE
C
      SQW  = SQW - VQW(MTUBE,K)
      RETURN
25     CONTINUE
C

```

```

C      INJECTION WELL PRESSURE SPECIFIED CASE
C
      DP=0.0
      DP=PIJ - VPWEL1 (MTUBE,K)
      VQW (MTUBE,K) = VPW1 (MTUBE,K) *DP
      SQW = SQW + VQW (MTUBE,K)
      VQW (MTUBE,K) = -VQW (MTUBE,K)
      RETURN
      END
      SUBROUTINE SYMINN (      IFRST1,      IFNAL1,      NFIL,
*                               ITWOD,      NI,
*                               SAOS,      SAWS,      SAOE,
*                               SAWE,      RHSO,      RHSW,
*                               SAOT,      SAWT      )
C
C      -----
C      SYMINN-- MOVE THE SATURATION EQUATION SYMMETRIC FLOW TERMS BACK
C      FROM THE BAKC OF BLANK COMMON TO THE PROPER VARIABLES
C      TO USE IN THE MASS BALANCE FOR BOTH PHASES
C      -----
C
      DIMENSION      SAOS (NI),      SAWS (NI),      SAOE (NI),
*                   SAWE (NI),      RHSO (NI),      RHSW (NI),
*                   SAOT (NI),      SAWT (NI)
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'STREAM.INC'
C
      4000      IFRST      = A (ISCPTR)
               IFINAL      = A (ISCPTR+1)
               NW          = IFINAL + 1 - IFRST
               NXTPTR      = ISCPTR + 2 + 8 * NW
      4200      ISCPTR      = ISCPTR + 2
      DO 4500 I = IFRST, IFINAL
               SAOS (I)      = A (ISCPTR)
               SAWS (I)      = A (ISCPTR+1)
               SAOE (I)      = A (ISCPTR+2)
               SAWE (I)      = A (ISCPTR+3)
               RHSO (I)      = A (ISCPTR+4)
               RHSW (I)      = A (ISCPTR+5)
               ISCPTR      = ISCPTR + 6
      4500 CONTINUE
      5500      IF ( NZ .LE. 1 )                                GO TO 8000
      DO 6000 I = IFRST, IFINAL
               SAOT (I)      = A (ISCPTR)
               SAWT (I)      = A (ISCPTR+1)
               ISCPTR      = ISCPTR + 2
      6000 CONTINUE
C
      8000      ISCPTR      = NXTPTR
C
      9900 RETURN
      END
      SUBROUTINE REPORT ( FINAL, DIDIT, ACUT )
C
C      -----

```

```

C      REPORT-- SUM UP THE TOTALS FOR THE INJECTORS AND THE PRODUCER
C      FROM THE INDIVIDUAL STREAMTUBES.  OUTPUT IN-PLACE,
C      INJECTION AND PRODUCTION TOTALS, AND ARRAYS AT 0.1
C      PORE VOLUME INTERVALS BASED ON USER INPUT OUTPUT
C      CONTROLS.
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'TUBE.INC'
C      INCLUDE 'FILES.INC'
C      COMMON / RPTKOM / WELLQO(3), WELLQW(3), NWLNOD(3)
C
C      270 FORMAT ( /// 14X, 'PERIODIC REPORT ON STATUS OF SIMULATION'
C      *           / 14X, '-----'
C      *           // 8X, ' YEARS      DAYS      DELTA-T ',
C      *           ' CASE STEPS TOTAL STEPS ',
C      *           / 4X, 2F10.1, F10.3, 2X, I9, 4X, I9 )
C      189 FORMAT( ' (',G12.4,1X,G12.4,
C      *           ' - FROM WELL AT ( ',I3,',',I3,' ) )' )
C      190 FORMAT(/, ' PRODUCTION/INJECTION RATE (STB/D) CUMULATIVE'
C      *, ' PRODUCTION/INJECTION (STB)', / 3X, ' OIL WATER',
C      *, ' INJECTION OIL WATER INJECTION'
C      * , /, 1X, 3(1X,G12.4),1X,3(1X,G12.4) )
C      160 FORMAT ( / 6X, ' CURRENT IN-PLACE-VOLUMES ', 17X, 'MAXIMUM'
C      *           / 6X, ' OIL (MSTB) WATER (MSTB)', 17X, 'PRESSURE'
C      *           / 4X, G14.5, 5X, G14.5, 15X, F10.1 / )
C      200 FORMAT (//12H TIME STEP =,I4,' TUBE =',I3/)
C      210 FORMAT(/,15X, 28H A R R A Y O F N E W O ,
C      1 23H I L P R E S S U R E S, /, ' LAYER ',8X,51(1H-) )
C      240 FORMAT (/,15X, 'A R R A Y O F O '
C      * , 27H I L S A T U R A T I O N S /, ' LAYER ',8X,47(1H-) )
C      280 FORMAT (/15X,28H A R R A Y O F W A T E R
C      1 , 23H S A T U R A T I O N S, /, ' LAYER ',8X, 51(1H-) )
C
C      DIDIT = 0.0
C
C      IPANAL = 0
C      IF ( FINAL .NE. 0.0 ) IPANAL = IANALP
C      IF ( FINAL .NE. 0.0 ) GO TO 348
C
C      IF ( (NSTEP-NSTR) .GT. 1 ) GO TO 345
C      IF ( IGOV .EQ. 2 .AND. NSTEP .GT. 1 ) GO TO 345
C      IF ( MTUBE.GT.1 .OR. MLAYER .GT. 1) GO TO 345
C
C      TOCUM = 0
C      TWCUM = 0
C      TWICUM = 0
C      ITSTEP= DTCUM / DELTAT
C      XNCSTP =0.1
C      XSTPR=0.0
C      IF ( IGOV .EQ.1) XSTPR= PVIN(NSTR)
C      345 CONTINUE
C      IF ( MTUBE .NE. 1 .OR. MLAYER .NE. 1) GO TO 346
C      TORAT = 0.0
C      TWRAT = 0.0
C      TWIRAT= 0.0

```



```

DO 344 IWL = 1, 3
  NWLNOD(IWL) = 0
  WELLQO(IWL) = 0
  WELLQW(IWL) = 0
344 CONTINUE
346 CONTINUE
C
C      OBTAIN THE TOTALS FOR PRODUCTIONS AND INJECTION
C
  IF ( IPROD(MTUBE,MLAYER) .EQ. 1 ) GO TO 3997
  TORAT=TORAT + VPO(MTUBE,MLAYER)/5.614
  TWRAT=TWRAT + VPW(MTUBE,MLAYER)/5.614
  TOCUM=TOCUM + VPO(MTUBE,MLAYER)/5.614*DELTAT
  TWCUM=TWCUM + VPW(MTUBE,MLAYER)/5.614*DELTAT
  IF ( IPAT9V .EQ. 0 .OR. IGOV .NE. 1 ) GO TO 3997
  DO 3996 IN = 1, 3
    IF ( NODPRD(MTUBE) .EQ. NWLNOD(IN) ) GO TO 3995
    IF ( NWLNOD(IN) .NE. 0 ) GO TO 3996
    NWLNOD(IN) = NODPRD(MTUBE)
3995 WELLQO(IN) = WELLQO(IN) + VPO(MTUBE,MLAYER)/5.614
    WELLQW(IN) = WELLQW(IN) + VPW(MTUBE,MLAYER)/5.614
    GO TO 3997
3996 CONTINUE
3997 IF ( IINJ(MTUBE,MLAYER) .EQ. 1 ) GO TO 3998
    TWIRAT=TWIRAT + VQW(MTUBE,MLAYER)/5.614
    TWICUM=TWICUM + VQW(MTUBE,MLAYER)/5.614*DELTAT
3998 CONTINUE
    IPANAL= 0
    IOUTP=0
    IF ( MTUBE .NE. NOTUBS .OR. MLAYER .NE. ILAYER ) GO TO 348
    ACUT = (TWRAT/(TWRAT+TORAT+1.E-20))
    MOD10 = MOD(NSTEP,10)

C      IF ( IGOV .EQ. 1 .AND. MOD10 .EQ. 1 )
C      *      WRITE (IMON,113) NSTEP, ACUT
C 113 FORMAT ( ' INFILL SIMULATION, NSTEP =',I6, ' W-CUT =',F6.3 )
C      IF ( IGOV .EQ. 2 .AND. MOD10 .EQ. 1 )
C      *      WRITE (IMON,117) NSTEP, ACUT
C 117 FORMAT ( ' NON-INFILL SIMULATION, NSTEP =',I6, ' W-CUT =',F6.3 )

    IF ( (NSTEP-NSTR) .GT. 1 ) GO TO 3475
    IF ( IGOV .EQ. 2 .AND. NSTEP .GT. 1 ) GO TO 3475
    GO TO 347
3475 CONTINUE
C
C      DETERMINE NEXT OUTPUT POINT
C
    PNEXT=PVIN(NSTEP-1) + TWIRAT*DELTAT/ORIGPV
    IF ( IGOV .EQ. 1 ) PNEXT = PVIN1(NSTEP-1) + TWIRAT*DELTAT/ORIGPV
    IF ( PNEXT .LT. XSTPR ) GO TO 347
    IF ( IANALP .NE. 0 ) IPANAL = 1
    IF ( IARRP .NE. 0 ) IOUTP=1
    XSTPR = XSTPR + XNCSTP
347 CONTINUE
    IF (NSTEP .NE. (NSTR+1)) GO TO 348
    IF ( IANALP .NE. 0 ) IPANAL = 1
    IF ( IARRP .NE. 0 ) IOUTP=1
C
C 348 CONTINUE
C

```

```

      IF ( IPANAL .EQ. 0 )      GO TO 385
      DIDIT      = 1.0
      NSTI      = NSTEP - NSTR
      YEARS      = CUMTIM / 365.25
C
C      TIME SUMMARY
C
      WRITE(IW,270) YEARS , CUMTIM, DELTAT, NSTI, NSTEP
C
C      TOTAL PRODUCTION AND INJECTION SUMMARY
C
      WRITE(IW,190) TORAT, TWRAT, TWIRAT, TOCUM , TWCUM, TWICUM
C
      IF ( IPAT9V .EQ. 0 .OR. IGOV .NE. 1 )      GO TO 2089
      DO 2088 IN = 1, 3
      IF ( NWLNOD(IN) .EQ. 0 ) GO TO 2088
      NPNOD = NWLNOD(IN)
      ILOC = X(NPNOD) + 0.001
      JLOC = Y(NPNOD) + 0.001
      WRITE(IW,189) WELLQO(IN), WELLQW(IN), ILOC, JLOC
2088 CONTINUE
C
2089 CONTINUE
      WIPM      = WIP / 5615.0
      OIPM      = OIP / 5615.0
      RPMAX = 0.0
      DO 2100 I=1, NX
      DO 2100 J=1, MTUBE
      DO 2100 K=1, MLAYER
      RPMAX = AMAX1 (VP (I, J, K), RPMAX)
2100 CONTINUE
C
C      IN-PLACE OUTPUT
C
      WRITE(IW,160) OIPM , WIPM, RPMAX
C PTT CALC MB ERROR

      UMBO=(OIP + ( TOCUM*5.614 ) )/OIPOR
      UMBW=(WIP + ( (TWCUM-TWICUM)*5.614 ) )/WIPOR

      WRITE(IW,1600) UMBO , UMBW
1600 FORMAT ( / 6x, '      MATERIAL BALANCE ERROR ',
*          / 6x, '      OIL          WATER',
*          / 4x, G14.5, 5x, G14.5, / )

385 CONTINUE
C

      IF ( IOUTP .EQ. 0 ) GO TO 999
C
C      PRESSURE AND SATURATION ARRAYS
C
      DO 400 I=1, NOTUBS
      WRITE(IW,200) NSTEP, I
      WRITE(IW,210)
      DO 401 J=1, ILAYER
401 WRITE(IW,281) J, (VP (K, I, J), K=1, NX)

```

```

281 FORMAT(2X,I3,2X,4(15(1X,F7.1),/,7X) )
282 FORMAT(2X,I3,2X,4(15(1X,F7.3),/,7X) )
      WRITE(IW,240)
      DO 402 J=1,ILAYER
402  WRITE(IW,282) J, (VSO1(K,I,J),K=1,NX)
      WRITE(IW,280)
      DO 403 J=1,ILAYER
403  WRITE(IW,282) J, (VSW1(K,I,J),K=1,NX)
400  CONTINUE
999  CONTINUE
      RETURN
      END
      SUBROUTINE HALTER ( CALLER, LABEL )
               *I*      *I*
C
C
C -----
C
C               H A L T E R
C
C -----
C
      CHARACTER*6      CALLER
C
      INCLUDE 'FILES.INC'
C
      INCLUDE 'BOO.INC'
      INTEGER  EXTRSW
C
100  FORMAT ( // ' NORMAL E-O-J, INFILL DRILLING PREDICTIVE MODEL'// )
200  FORMAT ( // ' ABNORMAL E-O-J, INFILL DRILLING PREDICTIVE MODEL'
*      / ' CAUSED BY SUBROUTINE -', A, '- AT LABEL ', I6 // )
C
      IF ( LABEL .LT. 0 )      GO TO 9900
C
      if(LABEL.gt.0) then
      write(iw,8686)iref,caller,label,EXTRSW
8686  format(t2,'Reservoir ',i4,'dumped in ', A,' label',i6,i2)
      endif
C
      IF ( LABEL .EQ. 0 )      WRITE ( IW, 100 )
C
      IF ( LABEL .GT. 0 )      WRITE ( IW, 200 )  CALLER, LABEL
C
9000 STOP '9000'
C
9900 RETURN
C  END HALTER
      END
C
      SUBROUTINE SWDST1( ILAYER, UKX, UH, SW, SOR, SWC, SOI)
      DIMENSION SW(ILAYER),UKX(ILAYER),UH(ILAYER)
C  ALLOCATE A MOVABLE WATER SATURATION BASED ON KH
C  N.B. THIS ASSUMES CONSTANT POROSITY
C
      F=.90
      USR=1.-SOR
      SUMKH=0.0
      TOTH=0.0

```

```

DO 10 I=1, ILAYER
SUMKH=SUMKH+(UKX(I)*UH(I))
TOTH=TOTH+UH(I)
10 CONTINUE

CF=0.0

US=( ( 1.-SOI) -SWC) * TOTH

DO 20 I=1, ILAYER
FAC= ( UKX(I)*UH(I) ) / SUMKH
CF=CF+FAC
USW = ((FAC * US)/UH(I)) + SWC
IF (USW.GT.USR) THEN
    U1=(USW-(USR*F))*UH(I)
    US=US + U1/(1.-CF)
    USW=USR*F
ENDIF
SW(I)=USW
20 CONTINUE

RETURN
END
SUBROUTINE SWDIST( ILAYER, UKX, UH, SW, SOR, SWC, SOI, BOI, BOK)
DIMENSION SW(ILAYER),UKX(ILAYER),UH(ILAYER)

C ALLOCATE A MOVABLE WATER SATURATION BASED ON KH
C N.B. THIS ASSUMES CONSTANT POROSITY

SUMKH=0.0
TOTH=0.0

DO 10 I=1, ILAYER
SUMKH=SUMKH+(UKX(I)*UH(I))
TOTH=TOTH+UH(I)
10 CONTINUE

C ASSUME BOK=ORIGINAL BO; BOI=BO AT BEGINING OF THE MATCH WINDOW

UBO=BOI/BOK
USO=1-SWC
UL=ILAYER

R= 1.- ((SOI/USO)/UBO)
IF (R.LT.0) R=0.0
DS=0.0

DO 20 I=1, ILAYER
F=((UKX(I)*UH(I))/SUMKH)
S=(1.-(R * F*UL)) * USO * UBO - DS
IF (S.LT.SOR) THEN
    DS=(SOR-S)/(ILAYER-I)
    S=SOR
ENDIF
SW(I)=1.-S
20 CONTINUE

RETURN

```

n n

n n

ARRAY LABEL	ARRAY -A- SIZE	FOR FOLLOWING SUBROUTINES IS AS FOLLOWS - DESCRIPTION	UNITS
A1 = P	(NXNYNZ)	PRESSURE	PSI
A2 = SATO	(NXNYNZ)	OIL SATURATION	FRAC
A3 = SATW	(NXNYNZ)	WATER SATURATION	FRAC
A4 = PORVOL	(NXNYNZ)	PORE VOLUME	CF
A5 = AW	(NXNYNZ)	PRESSURE EQUATION COEFFICIENTS	
A6 = AE	(NXNYNZ)		
A7 = AB	(IF LAYERS .NE. 0 .AND. NZ .NE. 1 THEN NXNYNZ ELSE 0)		
A8 = AN	(NXNYNZ)		
A9 = AS	(NXNYNZ)		
A10 = AO	(NXNYNZ)		
A11 = AT	(IF LAYERS .NE. 0 .AND. NZ .NE. 1 THEN NXNYNZ ELSE 0)		
A12 = RHS	(NXNYNZ)		
A13 = W	(NXNY)	NORMALIZATION VECTOR	
A14 = G	(NY)	AUXILLIARY VECTOR	
A15 = WEXTRA	(NX)	DITTO	
A16 = AWATTS	(NX)	WATTS COEFFICIENTS	
A17 = BWATTS	(NX)		
A18 = CWATTS	(NX)		
A19 = DWATTS	(NX)		
A21 = EE	(NXNY)	SIP INTERMEDIATE COEFFICIENTS	
A22 = FF	(NXNY)	SIP INTERMEDIATE COEFFICIENTS	
A23 = V	(NXNY)	DIFFERENCE IN PRESSURE OVER TIME STEP	
A24 = BAND	(NXNY/2*NX)	BAND MATRIX	
A25 = ROW	(2*NX+1)	AUXILLIARY VECTOR	

```

      NXL = NX
      IF ( METH .EQ. 2 )      NXL = NY
                              NYL = NY
      IF ( METH .EQ. 2 )      NYL = NX
      IFVF = 1
      IF ( NZ .NE. 1 ) IFVF = NXNY
      XSEC = 0
      IF ( IFVF .GT. 1 .AND. NY .EQ. 1 ) XSEC = 1
      IF ( METH .NE. 2 .AND. XSEC .NE. 0 ) NYL = NZ
      IF ( METH .EQ. 2 .AND. XSEC .NE. 0 ) NXL = NZ
      NXLNYL = NXL * NYL
      IF ( IFVF .GT. 1 .AND. XSEC .EQ. 0 ) GO TO 9000
      K = NZ
      IF ( XSEC .NE. 0 ) K = 1
      LAYER = NXNYNZ + 1

```

```

1  KZ      = K
   LAYER   = LAYER - NXNY
   IF ( XSEC .NE. 0 ) LAYER = 1
   IA1     = LAYER
   IA2     = IA1 + ( 1 ) * NXNYNZ
   IA3     = IA2 + NXNYNZ
   IA4     = IA3 + NXNYNZ
   IA5     = LASTIN + LAYER - 1
   IA6     = IA5 + NXNYNZ
   IA7     = IA6 + NXNYNZ
   IA8     = IA7
   IF ( IFVF .NE. 1 ) IA8 = IA8 + NXNYNZ
   IA9     = IA8 + NXNYNZ
   IA10    = IA9 + NXNYNZ
   IA11    = IA10 + NXNYNZ
   IA12    = IA11
   IF ( IFVF .NE. 1 ) IA12 = IA12 + NXNYNZ
103 CONTINUE
      IF ( KZ .LT. NZ .AND. XSEC .EQ. 0 ) GO TO 100
   IA13    = IA12 + NXNYNZ
   IF ( METH .EQ. 4 .OR. METH .EQ. 5 ) GO TO 105
   IA14    = IA13 + NXLNLYL
   IA15    = IA14 + NYL
   IA16    = IA15 + NXL
   IA17    = IA16 + NXL
   IA18    = IA17 + NXL
   IA19    = IA18 + NXL
   IA20    = IA19 + NXL
   ILAST   = IA20 + NXL
   GO TO 115
105 CONTINUE
   IF ( METH .EQ. 5 ) GO TO 130
   IA21    = IA13 + NXLNLYL
   IA22    = IA21 + NXLNLYL
   IB22    = IA22 / 2 + 2
   ILAST   = 2 * IB22 + 2 * NXLNLYL - 1
   ILAST   = IA22 + NXLNLYL
   GO TO 115
130 CONTINUE
   IF ( NXL .LT. NYL ) GO TO 135
   M        = (NXLNLYL/2) * NYL
   MROW     = 2 * NYL + 1
   INDEX    = NYL + 1
   INCI     = 1
   INCJ     = NX
   GO TO 137
135 CONTINUE
   M        = (NXLNLYL/2) * NXL
   MROW     = 2 * NXL + 1
   INDEX    = NXL + 1
   INCI     = NX
   INCJ     = 1
137 CONTINUE
   IA23     = IA13 + M
   IA23     = IA23 + 1
C
C   ABOVE INSURES DOUBLE WORD BOUNDARY FOR ROW ARRAY, IN DOUBLE
C   PRECISION VERSIONS
C
   IA24     = IA23 + ( 1 ) * MROW

```

```

        ILAST      = IA24 + INDEX
115 CONTINUE
116 CONTINUE
        OMEGA      = 1
        IF ( NCORE .NE. -1 )      GO TO 200
        IJK0       = ( 1 - NZ ) * NXNY -1
        IF ( XSEC .NE. 0 )      IJK0      = -1
C      ADD THE OFF-DIAGONAL TERMS
        DO 80      I = 1, NXNYNZ
            IJK      = IJK0 + I
            IJK10     = IJK + IA10
            A(IJK10)  = A(IJK10) + A(IJK+IA5) + A(IJK+IA6)
1          + A(IJK+IA8) + A(IJK+IA9)
        80 CONTINUE
        IF ( IFVF .EQ. 1 )      GO TO 100
        DO 90      I = 1, NXNYNZ
            IJK      = IJK0 + I
            IJK10     = IJK + IA10
            A(IJK10)  = A(IJK10) + A(IJK+IA7) + A(IJK+IA11)
        90 CONTINUE
100 CONTINUE
        IF ( XSEC .NE. 0 ) IA8 = IA11
        IF ( XSEC .NE. 0 ) IA9 = IA7
        IF ( METH .NE. 1 ) GO TO 110
C
C      Y-DIRECTION LSOR
C      FOR ISOLATED LAYERS
C
        IAE = IA6
        IAS = IA9
        IAW = IA5
        IAN = IA8
        IMAX = NX
        INCI = 1
        JMAX = NY
        IF ( XSEC .NE. 0 ) JMAX = NZ
        INCJ = NX
        GO TO 120
110 CONTINUE
C
C      X-DIRECTION LSOR
C      FOR ISOLATED LAYERS
C
        IAE = IA9
        IAS = IA6
        IAW = IA8
        IAN = IA5
        IMAX = NY
        IF ( XSEC .NE. 0 ) IMAX = NZ
        INCI = NX
        JMAX = NX
        INCJ = 1
120 CONTINUE

```

c ptt 4/92 increase tolsat from .0001 to .001 this did not appear to have a
c bad effect on m.b., but be careful!

```

TOLSAT = 0.001
TOLSUM = 0
SVOMDF = OMDIFF

```

```

      IF ( K .NE. NZ )          OMDIFF = 0
      OMEGA = 1.8
C
      AO      AE      AS      AW      AN
C      CALL    LSOR2D (A(IA10), A(IAE), A(IAS), A(IAW), A(IAN),
C              R      AWATTS BWATTS CWATTS DWATTS
C      1      A(IA12),A(IA16),A(IA17),A(IA18),A(IA19),
C              WEXTRA      W      G      PORVOL      AFR
C      2      A(IA15),A(IA13),A(IA14),A(IA 4),      A,
C              P      ABK      IMAX      INCI      JMAX
C      3      B(IA 1),      A,      IMAX ,      INCI ,      JMAX ,
C              INCJ DELTAT      OMEGA      TOLSAT      TOLSUM
C      4      INCJ ,DELTAT , OMEGA , TOLSAT, TOLSUM,
C              ISWEEP ITERMX LWATTS      LARGE      INCFR
C      5      1 ,      200 ,      1 ,      1 ,      0 ,
C PTT BUMP TO 500
C      5      1 ,      500 ,      1 ,      1 ,      0 ,
C              INCBK      CORREC
C      6      0 ,A(IA20)      )
      OMDIFF = SVOMDF
150 CONTINUE
      K = K - 1
      IF ( K .GT. 0 )      GO TO 1
      GO TO 9999
200 IEXCES(5)      = NCORE - ILAST
      GO TO 9999
9000 CONTINUE
9999 CONTINUE
      RETURN
      END
      SUBROUTINE OVER3
C
C
C -----
C      OVER3 --- INCREMENTS TIME STEP NUMBER AND CUMULATIVE EACH TIME
C              STEP PLUS LOADS THE CORRECT TIME DEPENDENT ARRAYS INTO
C              BLANK COMMON FOR USE IN THE COEFFICIENT GENERATION AND
C              EQUATION SOLUTION ROUTINES TO FOLLOW, BASED ON WHICH
C              STREAMTUBE AND LAYER IS NEXT TO SOLVED.
C
C -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'STREAM.INC'
C
C
C *****
C      ALLOCATION OF ARRAY -A- FOR FOLLOWING SUBROUTINES IS AS FOLLOWS -
C      ARRAY LABEL      SIZE      DESCRIPTION      UNITS
C      -----
C      IA1 = P      (NXNYNZ)      PRESSURE      PSI
C      IA2 = SATO      (NXNYNZ)      OIL SATURATION      FRAC
C      IA3 = SATW      (NXNYNZ)      WATER SATURATION      FRAC
C      IA4 = PORVOL      (NXNYNZ)      PORE VOLUME      CF
C              DATA TABLES ARE INSERTED HERE
C      IA5 = AX      (NXNYNZ)      X-DIRECTION ROCK TRANSMISSABILITY      CF/PSI
C              = AE
C      IA6 = AY      (NXNYNZ)      Y-DIRECTION ROCK TRANSMISSABILITY      CF/PSI
C              = AN
C      IA7 = AZ      (NXNYNZ)      Z-DIRECTION ROCK TRANSMISSABILITY      CF/PSI
C              = AS

```



```

C   IA8 = ZAVG
C       = AW
C
C           *****
C           SET UP ARRAY INDICES
C
C       IA1 = 1
C       IA2 = IA1 + ( 1 ) * NXNYNZ
C       IA3 = IA2 + NXNYNZ
C       IA4 = IA3 + NXNYNZ
C       IA5 = LASTIN
C       IA6 = IA5 + NXNYNZ
C       IA7 = IA6 + NXNYNZ
C       IA8 = IA7 + NXNYNZ
C       IF ( NZ .LE. 1 ) IA8=IA7
C       IA9 = IA8 + NXNYNZ
C       ILAST = IA9 + NWLMAX
C       IF ( NCORE .EQ. -1 ) GO TO 200
C
C       CHECK TO SEE IF COMMON IS LARGE ENOUGH
C       IEXCES(3) = NCORE - ILAST
C       GO TO 9999
200  CONTINUE
C       I=0
C       DO 300 I2=1, ILAYER
C       DO 300 I1=1, NX
C       MLAYER=I2
C       I=I+1
C       A(IA1+I-1)= VP(I1,MTUBE,MLAYER)
C       A(IA2+I-1)= VSO1(I1,MTUBE,MLAYER)
C       A(IA3+I-1)= VSW1(I1,MTUBE,MLAYER)
C       A(IA4+I-1)= VPV1(I1,MTUBE,MLAYER)
C       A(IA5+I-1)= VTX(I1,MTUBE,MLAYER)
C       A(IA6+I-1)= VTY(I1,MTUBE,MLAYER)
C       A(IA7+I-1)= VTZ(I1,MTUBE,MLAYER)
C       A(IA8+I-1)= VZAVG(I1,MTUBE,MLAYER)
300  CONTINUE
C       IF(MTUBE.NE.1 ) GO TO 9999

C PTT 6/91 - RESTICT RUN TO A MAXIMUM CUMULATIVE TIME

C       IF(CUMTIM+DELTAT.GT.DTMAX .AND. DTMAX.GT.0.0) THEN
C           DELTAT=DTMAX-CUMTIM
C       ENDIF

C       CUMTIM = CUMTIM + DELTAT
C       NSTEP = NSTEP + 1
9999 CONTINUE
C       CONTINUE
C       RETURN
C       END
C       SUBROUTINE OVER7

C
C -----
C
C OVER7 -- WRAP-UP AND OUTPUT CONTROL ROUTINE FOR THE RESERVOIR
C          SIMULATOR TIME STEP RESULTS. CALLED AT END OF EVERY
C          TIME STEP FOR EVERY STREAMTUBE. ROUTINE SAVES PRESSURES
C          AND SATURATIONS FROM BLANK COMMON INTO APPROPRIATE
C          COMMON VECTOR FOR EACH TUBE. ALSO TOTAL CUMULATIVES AND
C          RATES ARE STORED INTO COMMONS. AFTER CALL TO OUTPUT
C          PRINT ROUTINE 'REPORT', THE ROUTINE CHECKS TO SEE IF THE
C          INFILL WATER-CUT POINT HAS BEEN REACHED, THEN SAVES THE

```

```

C          SATURATIONS AND PRESSURES AT THIS POINT TO USE IN
C          INTERPOLATING NEW PRESSURE AND SATURATIONS AT THE START
C          OF THE INFILL CASE.
C
C          -----
C

```

```

C          INCLUDE 'PARAM.INC'
C          INCLUDE 'SIMUL.INC'
C          INCLUDE 'STREAM.INC'
C          INCLUDE 'FILES.INC'

```

```

C PTT 1/92 FOR SENSITIVITY

```

```

C          CHARACTER*80 TITLE
C          CHARACTER*12 NAME
C          CHARACTER*6 TNAME

```

```

C -mb

```

```

C          COMMON /SENS/ IWP1,IWP2,UV1,UV2,UV3,ISENS,IDO_IT,XXMX,TITLE,
C          & NAME,TNAME

```

```

C

```

```

C 300 FORMAT (      23X,47HBLANK COMMON SIZE DEFINED IN THE MAIN PROGRAM D
C 1 , 29HOES NOT CORRESPOND TO NCORE = , I10 )

```

```

C 360 FORMAT (/ 53X, 25(1H*)
C *      / 53X, 1H*, 16H WELL ARRAY SIZE, I6, 1X, 1H*
C *      / 53X, 25(1H*)
C *      / 53X, 1H*, 14H COMMON SIZE      , I8, 1X, 1H*
C *      / 53X, 25(1H*)
C *      / 53X, 1H*, 3X, 7HOVERLAY, 4X, 6HCOMMON, 3X, 1H*
C *      / 53X, 1H*, 23H      NO.      REQUIRED , 1H*
C *      / 53X, 1H*, 3X, 7(1H-), 4X, 6(1H-), 3X, 1H* )

```

```

C 370 FORMAT ( 53X,1H*,I7, 7X,I6, 3X,1H* )

```

```

C 380 FORMAT ( 53X,25(1H*) )

```

```

C 382 FORMAT ( 1H1,  ////  53X, 25(1H*) )

```

```

C 385 FORMAT ( / )

```

```

C 390 FORMAT (      16X,41HBLANK COMMON SIZE IS TOO SMALL IN OVERLAY ,I4,
C 1  20H COMMON AVAILABLE = ,I7 , 27H MINIMUM COMMON REQUIRED = ,I7 )

```

```

C 1001 FORMAT (/ 1X,100(1H*), 17H FATAL ERROR NO. ,I3 )

```

```

C

```

```

C          *****
C          ALLOCATION OF ARRAY -A- CORE FOR SUBROUTINE REPORT IS AS FOLLOWS-
C          ARRAY LABEL      SIZE      DESCRIPTION      UNITS
C          -----

```

```

C          IA1 = P          (NXNYNZ)
C          IA2 = SATO        (NXNYNZ)
C          IA3 = SATW        (NXNYNZ)
C          IA4 = PORVOL      (NXNYNZ)
C          IA5 = FKX         (NXNYNZ)
C          IA6 = FKY         (NXNYNZ)
C          IA7 = FKZ         (NXNYNZ)
C          IA8 = ZAVG        (NXNYNZ)
C          IA9 = SATG        (NXNYNZ)

```

```

C

```

```

C          IA1      = 1
C          IA2      = IA1 + ( 1 ) * NXNYNZ
C          IA3      = IA2  + NXNYNZ
C          IA4      = IA3  + NXNYNZ
C          IA5      = LASTIN
C          IA6      = IA5 + NXNYNZ
C          IA7      = IA6 + NXNYNZ
C          IA8      = IA7 + NXNYNZ

```

```

      IF ( NZ .LE. 1 ) IA8=IA7
      IA9      = IA8 + NXNYNZ
      IA10     = IA9  + NXNYNZ
      ILAST    = IA10 + 99
      IF ( NCORE .EQ. -1 )      GO TO 770
C
C      CHECK TO SEE IF COMMON IS LARGE ENOUGH TO SOLVE PROBLEM
C      FOR EACH OF THE RESERVOIR ROUTINES -- OVER3 THROUGH OVER7.
C      THIS IS CHECKED ONLY AT STRT OF EACH CASE -- SEE MAIN PROGRAM.
C
      IEXCES(7)      = NCORE - ILAST
      IF ( NCORE .EQ. A(NCORE+1) )      GO TO 350
      NMESS = 700
      WRITE(IW,1001) NMESS
      WRITE(IW,300) NCORE
      NUMERR      = NUMERR + 1
350 CONTINUE
      NUSABL = NCORE
      ISCZER= NCORE - 10*NX*ILAYER - 100
      DO 400 I = 1,7
        IF ( I .LT. 3 )      GO TO 395
        IF ( NUSABL .GT. IEXCES(I) )      NUSABL = IEXCES(I)
395      MREQ      = NCORE - IEXCES(I)
        IF ( MREQ .GT. ISCZER) ISCZER=MREQ
400 CONTINUE
      LIMSCR      = NCORE -2
      NCORE      = -1
      GO TO 9999
C
C
C      UPDATE PRESSURES AND SATURATIONS FOR EACH LAYER OF THIS STREAMT
C
770 CONTINUE
      I11V = 0
C
      DO 8000 I1V=1,ILAYER
      MLAYER=I1V
C
      DO 2000 I=1,NX
      I11V=I11V+1
      VP(I,MTUBE,MLAYER)=A(IA1+I11V-1)
      VSO1(I,MTUBE,MLAYER)=A(IA2+I11V-1)
      VSW1(I,MTUBE,MLAYER)=A(IA3+I11V-1)
2000 CONTINUE
C
C      DO SUMMATIONS FOR WELLS AND OUTPUT ARRAYS TO PRINTER IN REPORT
C
      CALL REPORT ( 0.0, DIDIT, ACUT )
C
      IF ( MTUBE .NE. NOTUBS .OR. MLAYER .NE. ILAYER) GO TO 8000
C
C      UPDATE PERFORMANCE TABLE FOR EACH TIME STEP
C
      IF ( IGOV .EQ. 1 ) GO TO 2050
      OILRAT(NSTEP)= TORAT
      IF (NSTEP.NE. 1) GO TO 2042
      OIPOR1 = OIPOR
      OILCM(1)=TORAT*DELTAT
      PVIN(1)=TWIRAT*DELTAT/ORIGPV
      GO TO 2044

```

```

2042 OILCM(NSTEP)=TORAT*DELTAT + OILCM(NSTEP-1)
      PVIN(NSTEP)=TWIRAT*DELTAT/ORIGPV + PVIN(NSTEP-1)
2044 OILRC(NSTEP)=OILCM(NSTEP)/(OIPOR/5.614)
      WCT(NSTEP)=ACUT
      WATRAT(NSTEP)= TWRAT
      TTIME(NSTEP)= CUMTIM
      GO TO 2060
2050 OILRT1(NSTEP)=TORAT
      IF( NSTEP .EQ. NSTR+1 ) OILCM1(NSTEP-1)=OILCM(NSTR)
      IF( NSTEP .EQ. NSTR+1 ) PVIN1(NSTEP-1)=PVIN(NSTR)
      OILCM1(NSTEP)=TORAT*DELTAT + OILCM1(NSTEP-1)
      PVIN1(NSTEP)=TWIRAT*DELTAT/ORIGPV + PVIN1(NSTEP-1)
      OILRC1(NSTEP)=OILCM1(NSTEP)/(OIPOR1/5.614)
      WCT1(NSTEP)=ACUT
      WATRT1(NSTEP)=TWRAT
      TTIM1(NSTEP)=CUMTIM
2060 CONTINUE
      IF ( IGOV .EQ. 1 ) GO TO 8000
C
C      THIS IS TIME STEP WHERE NON-INFILL CASE HAS REACHED THE WATER
C      CUT SPECIFIED BY THE USER FOR THE BEGINNING OF THE NON-INFILL
C      CASE.
C
      IF ( ICUTC .EQ. 333) GO TO 8000

      DO 2100 I=1,NX
      DO 2100 J=1,MTUBE
      DO 2100 K=1,MLAYER
      VP1B(I,J,K)=VP(I,J,K)
      VSO1B(I,J,K)=VSO1(I,J,K)
      VSW1B(I,J,K)=VSW1(I,J,K)
2100 CONTINUE

C      IF ( ACUT .GT. VCUT .AND. DIDIT .EQ. 0.0 )
C      * CALL REPORT ( 1.0, DIDIT, ACUT )

C PTT 1/92
      IF(DTMAX.GT.0.0) THEN
      IF ( ACUT .GT. VCUT .AND. DIDIT .EQ. 0.0 )
      * CALL REPORT ( 1.0, DIDIT, ACUT )
      ENDIF

C PTT 1/92
      IF(DTMAX.LT.0) THEN
      IF ( CUMTIM.GE.ABS(DTMAX) .AND. DIDIT .EQ. 0.0 )
      * CALL REPORT ( 1.0, DIDIT, ACUT )
      ENDIF

C      IF ( ACUT .GT. VCUT ) ICUTC=333
C      IF ( ACUT .GT. VCUT ) NSTR=NSTEP

C PTT 10/90 ALLOW INFIL TO BE A SPECIFIED TIME (DTMAX ENTERED AS NEGATIVE)

      IF ( DTMAX.GT.0.0) THEN
      IF ( ACUT .GT. VCUT ) ICUTC=333
      IF ( ACUT .GT. VCUT ) NSTR=NSTEP
      ENDIF

C PTT 10/90 ALLOW INFIL TO BE A SPECIFIED TIME (DTMAX ENTERED AS NEGATIVE)

```

```

      IF ( DTMAX.LT.0.0 .AND. CUMTIM.GE.ABS(DTMAX) ) THEN
        ICUTC=333
        NSTR=NSTEP
      ENDIF

      TOPT = CUMTIM

      IF( IANALP .NE. 0 .AND. ACUT .GT. VCUT ) WRITE(IW,800)
800  FORMAT(1H1 ///
      * 7X, 'CONTINUATION OF WATERFLOOD AFTER WATER CUT FOR INFILL' /
      * 7X, 53('=' ) /// )

8000  CONTINUE

      IF ( MTUBE .NE. NOTUBS )                      GO TO 9999
C
      IF ( TORAT .LT. 0.001 )                      GO TO 9900

C PTT 6/91 CHECK CUMULATIVE TIME
      IF(CUMTIM.GE.DTMAX .AND. DTMAX.GT.0.0) GOTO 9900
C PTT 1/92 CHECK CUMULATIVE TIME PRODUCTION RUNS
      IF(CUMTIM.GE.XMX .AND. IDO_IT.EQ.1) GOTO 9900

C PTT 1/92 FOR PRODUCTION RUNS, DON'T CHECK CUT HERE
      IF(IDO_IT.EQ.1 .AND. IGOV.EQ.2 ) GOTO 9999

      IF ( (NSTEP-NSTR) .LE. 5 )                      GO TO 9999
      IF ( IGOV.EQ. 2 .AND. WCT(NSTEP) .LT. CUTMAX ) GO TO 9999
      IF ( IGOV.EQ. 1 .AND. WCT1(NSTEP) .LT. CUTMAX ) GO TO 9999
9900  CONTINUE
C
C      'KEEP' IS THE TIME STEP WHERE INFILL OCCURRED
C      PTT 11/91 ACTUALLY, KEEP IS THE LAST WATERFLOOD STEP !!!
C      NSTR IS THE STEP AT WHICH WATER FLOOD OCCURED
C
      IF (IGOV.EQ.2) KEEP = NSTEP
      IF (IGOV.EQ.1) NSTEPS = NSTEP-NSTR
      IF (IGOV.EQ.2) NSTEPS = NSTEP
      NGS = NXNYNZ * NSTEPS * ILAYER * NOTUBS
      STOPIT = 1

C
C      OUTPUT THE SUMMARY FOR THE NUMBER OF STEPS IN EACH CASE
C
      IF( IANALP .NE. 0 ) WRITE(IW,9994) NSTEPS, NGS
9994  FORMAT (// 24(1H*) /
      *      / 24H TIME STEPS EXECUTED.... ,   I10 ,
      *      / 24H GRID-CELL-TIME-STEPS... ,   I10 )
C
9999  CONTINUE
      RETURN
      END
      SUBROUTINE INITAL

C
C      -----
C
C      INITAL--INITIALIZE RESERVOIR CALCULATION VARIABLES PRIOR TO
C      CALCULATIONS.
C
C      -----
C

```

```

      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'STREAM.INC'
C
C      EMPTYX = -1.E-9
      EMPTYX = 0.0
      DO 10 I=1,NCORE
        A(I) = EMPTYX
10      CONTINUE
      CALL ZEROS ( IEXCES, 10 )
      IF(IGOV .EQ. 2 ) CUTMAX = 0.0

C PTT 6/91 THIS IS NOW USED AS MAX SIMULATION TIME, SO DON'T
C TRASH IT HERE
C      DTMAX = 0.0

      IF ( IGOV .EQ. 2 ) DELTAT = 0.0
      DTLAST = 0.0
      DTPER = 0.0
      DSMAX = 0.0
      DSGIVN = 0.0
      OIPOLD = 0.0
      GIPOLD = 0.0
      NSTART = 0
      IF ( IGOV .EQ. 2 ) NSTEP = 0
      IF ( IGOV .EQ. 2 ) NSTR = 0
      IF ( IGOV .EQ. 2 ) CUMTIM = 0.0
      IF ( IGOV .EQ. 1 ) CUMTIM = TOPT
      IF ( IGOV .EQ. 1 ) NSTEP=NSTR
      OIP = 0.0
      GIP = 0.0
      WIP = 0.0
      RETURN
      END
      SUBROUTINE GENTUB ( IPAT9, IGO, VANISO, VTUBE, NX )
                                *I*  *I*  *I*  *O*  *I*
C
C
C -----
C
C          G E N T U B
C
C          GENERATE STREAM TUBES FOR PATTERN/RATES
C          SPECIFIED IN PARAMETERS GIVEN AS INPUT
C
C          RESULTS ARE LEFT IN COMMON /STREAM/
C          FOR USE IN -OVER2- TO DO SIMULATION
C
C -----
C
C      OUTLINE OF PROCESS..
C
C      (1)  GENERATE FINITE ELEMENT MESH FOR THE CASE AT HAND.
C
C      (2)  SOLVE FOR PRESSURES IN FINITE ELEMENT PROBLEM.
C
C      (3)  RE-MAP F-E SOLUTION ONTO A FCG (FINE CARTESIAN GRID),
C           GIVING AT EACH NODAL POINT THE VALUES OF -QX- AND -QY-.
C
C      (4)  FORM A CIRCLE OF SL (STREAM LINE) MARKERS, TWO PER ST,
C           AROUND EACH INJECTOR AT ADEQUATE RADIUS THAT AVOIDS

```

```

C          WANTING TO HAVE TWO MARKERS IN THE SAME FCG CELL.
C          FOLLOW THE STREAM LINES FROM EACH OF THE INITIAL SL/ST
C          MARKERS BACKWARD TO THE INJECTOR AND FORWARD TO A
C          PRODUCER, MARKING EACH FCG THROUGH WHICH IT PASSES
C          WITHIN A CRITICAL DISTANCE OF THE CELL CENTER.
C          IDENTIFY INJECTOR AND PRODUCER ASSOCIATED WITH EACH ST.
C
C          (5)  ALLOCATE REMAINING FCG CELLS TO A ST BY MARKING CELLS
C               (NEGATIVELY IN -INXST-) WITH THE -INXST- FOR THE CLOSEST
C               ST MIDPOINT CELL.
C
C          (6)  GENERATE FINITE DIFFERENCE TUBES.
C               FOR EACH ST..
C               (A)  FOR EACH FCG CELL CALCULATE ITS RDLPD (RELATIVE
C                   DOG LEGGED PATH DISTANCE) BETWEEN INJECTOR AND
C                   PRODUCER ASSOCIATED WITH ITS ST.
C
C               (B)  SORT THE RDLPD VALUES INTO ASCENDING ORDER.
C
C               (C)  CALCULATE NUMBER OF FCG CELLS FOR EACH (SIMULATOR)
C                   MEGA-CELL. THEN ASSIGN FCG CELLS TO MEGA-CELLS IN
C                   THE ORDER OF THE SORTED LIST OF RDLPD VALUES.
C
C          (7)  COMPUTE MEGA-CELL PROPERTIES NEEDED BY SIMULATOR.
C
C          -----
C
C          INCLUDE 'PARAM.INC'
C          INCLUDE 'TUBE.INC'
C          INCLUDE 'STREAM.INC'
C          INCLUDE 'FILES.INC'
C
C          DIMENSION VTUBE (NTBMAX)
C
C          INITIALIZATION / HOUSEKEEPING
C
C          WRITE (IMON,100)
C 100 FORMAT ( ' STARTING STREAM TUBE GENERATION' )
C
C          ISO = 0
C          IF ( ABS(VANISO-1.0) .LE. 0.0001 ) ISO = 1
C          INFILL = 0
C          IF ( IGO .EQ. 1 ) INFILL = 1
C          OMEGA = 1.85
C          IF ( ISO .EQ. 0 ) OMEGA = 1.75
C          ERRMAX = 0.02
C
C          STEP 1
C
C          CALL GENFEL ( IPAT9,INFILL,VANISO,ISO,KASE,NCOORD )
C
C          STEP 2
C
C          CALL FELSLV ( VANISO,OMEGA,ERRMAX )
C
C          STEP 3
C
C          CALL GENFCG ( VANISO, LX, LY )
C
C          STEP 4

```

```

C      CALL MARKST ( NCOORD, INFILL, IPAT9, LY, KASE, VTUBE(1) )
C
C      STEP 5
C
C      CALL DEFTUB ( NCOORD, LX, LY )
C
C      STEP 6
C
C      CALL DEFFDC ( LY, NX, NCOORD )
C
C      STEP 7
C
C      CALL GENMCP ( LY, NX, INFILL, VTUBE(1) )
C
C      WRITE (IMON,900)
C      900 FORMAT ( ' FINISHED STREAM TUBE GENERATION' )
C
C      9900 RETURN
C      END GENTUB
C      END
C      SUBROUTINE TUBAUS ( NCOORD, LY, MEGA )
C
C      -----
C
C      WRITES OUT A SHADOWMAP DEPICTION OF THE STREAMTUBES
C
C      NCOORD - INITIAL NUMBER OF NODES IN FINITE ELEMENT MESH
C      LY      - VERTICAL DIMENSION OF FINE CARTESIAN GRID
C      MEGA    - ALTERNATIVE OUTPUT, THE MGA-CELL ASSIGNMENTS
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'TUBE.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'FILES.INC'
C
C      CHARACTER ICHR(30)*1
C      DATA ICHR / ' ','1','2','3','4','5','6','7','8','9',
C      *           'A','B','C','D','E','F','G','H','I','J',
C      *           'K','L','M','N','P','Q','R','S','T','U' /
C
C      50 FORMAT ( 1H1 )
C      100 FORMAT(1X,161A1)
C      200 FORMAT (///,20X,16(1H*),/,20X,
C      *           '* STREAM TUBES *' ,/,20X,16(1H*))
C      300 FORMAT (///,20X,16(1H*),/,20X,
C      *           '* F.D. CELLS *' ,/,20X,16(1H*))
C      800 FORMAT ( /// ' NOT YET DOING RIGHT TRIANGLE, NE-SW HYPOT.' // )
C      900 FORMAT ( /// ' UNKNOWN SHAPE OF SYMMETRY ELEMENT.' // )
C
C      WRITE (IW,50)
C      IF ( MEGA .EQ. 0 )   WRITE (IW,200)
C      IF ( MEGA .NE. 0 )   WRITE (IW,300)
C
C      IMX = 1
C      IMN = 1
C      JMX = 1
C      JMN = 1

```



```

DO 2000 IN = 2, NCOORD
IF ( X(IN) .GE. X(IMX) ) IMX = IN
IF ( X(IN) .LE. X(IMN) ) IMN = IN
IF ( Y(IN) .GE. Y(JMX) ) JMX = IN
IF ( Y(IN) .LE. Y(JMN) ) JMN = IN
2000 CONTINUE
XMAX = X(IMX)
IMXJMX = IMN
IMXJMN = IMN
DO 2100 IN = 1, NCOORD
IF ( Y(IN) .EQ. Y(JMX) .AND. X(IN) .GT. X(IMXJMX) ) IMXJMX = IN
IF ( Y(IN) .EQ. Y(JMN) .AND. X(IN) .GT. X(IMXJMN) ) IMXJMN = IN
2100 CONTINUE
C
JUMP = 5
IF ( ABS(Y(JMX)+Y(JMN)-2*XMAX) .LT. 0.001 ) JUMP = 1
IF ( X(IMXJMN) .EQ. Y(JMX) .AND.
*   X(IMXJMX) .EQ. 1.0 ) JUMP = 2
IF ( X(IMXJMX) .EQ. Y(JMX) .AND.
*   X(IMXJMN) .EQ. 1.0 ) JUMP = 3
IF ( X(IMXJMX) .EQ. Y(JMX) .AND.
*   X(IMXJMN) .EQ. Y(JMX) ) JUMP = 4
C
GO TO ( 2200, 4200, 6200, 8200, 9800 ) JUMP
C
C CASE OF RIGHT ISOCELES TRIANGLE WITH BASE ON Y-AXIS
C
2200 ARRAY(1) = ' | '
LYODD = MOD(LY,2)
C
DO 2600 IY = LY, LY/2+2, -1
IXL = LY+1-IY
ARRAY(IXL+2) = ' \ '
DO 2400 IX = 1, IXL
IC = INXST(IX,IY)
ARRAY(IX+1) = ICHR(IC+1)
IF ( MEGA .EQ. 0 ) GO TO 2400
ICODD = MOD(IC,2)
IF ( ICODD .EQ. 0 ) ARRAY(IX+1) = ' '
IF ( ICODD .EQ. 0 ) GO TO 2400
IM = MCNUMB(IX,IY)
ARRAY(IX+1) = ICHR(IM+1)
2400 CONTINUE
WRITE (IW,100) ( ARRAY(I),I=1,IXL+2 )
2600 CONTINUE
C
IF ( LYODD .EQ. 0 ) GO TO 3200
IXL = LY/2+1
IY = IXL
ARRAY(IXL+2) = ' | '
DO 3000 IX = 1, IXL
IC = INXST(IX,IY)
ARRAY(IX+1) = ICHR(IC+1)
IF ( MEGA .EQ. 0 ) GO TO 3000
ICODD = MOD(IC,2)
IF ( ICODD .EQ. 0 ) ARRAY(IX+1) = ' '
IF ( ICODD .EQ. 0 ) GO TO 3000
IM = MCNUMB(IX,IY)
ARRAY(IX+1) = ICHR(IM+1)
3000 CONTINUE

```

```

        WRITE (IW,100) ( ARRAY(I),I=1,IXL+2 )
C
3200 CONTINUE
    DO 3600 IY = LY/2, 1, -1
        IXL = IY
        ARRAY(IXL+2) = '/'
        DO 3400 IX = 1, IXL
            IC = INXST(IX,IY)
            ARRAY(IX+1) = ICHR(IC+1)
            IF ( MEGA .EQ. 0 )          GO TO 3400
            ICODD = MOD(IC,2)
            IF ( ICODD .EQ. 0 ) ARRAY(IX+1) = ' '
            IF ( ICODD .EQ. 0 )          GO TO 3400
            IM = MCNUMB(IX,IY)
            ARRAY(IX+1) = ICHR(IM+1)
3400 CONTINUE
        WRITE (IW,100) ( ARRAY(I),I=1,IXL+2 )
3600 CONTINUE
C
    GO TO 9900
C
C
C    CASE OF RIGHT TRIANGLE WITH NW-SE HYPOTENUSE
C
4200 ARRAY(1) = '|'
C
    INC = 1
    IF ( LY .GT. 130 )    INC = 2
    MINC = - INC
    DO 4600 IY = LY, 1, MINC
        IXL = LY+1-IY
        IA = 1
        DO 4400 IX = 1, IXL, INC
            IA = IA + 1
            IAL = IA
            IC = INXST(IX,IY)
            ARRAY(IA) = ICHR(IC+1)
            IF ( MEGA .EQ. 0 )          GO TO 4400
            ICODD = MOD(IC,2)
            IF ( ICODD .EQ. 0 ) ARRAY(IX+1) = ' '
            IF ( ICODD .EQ. 0 )          GO TO 4400
            IM = MCNUMB(IX,IY)
            ARRAY(IX+1) = ICHR(IM+1)
4400 CONTINUE
        ARRAY(IAL+1) = '\\
        WRITE (IW,100) ( ARRAY(IA),IA=1,IAL+1 )
4600 CONTINUE
C
    IXL = LY
    IA = 1
    DO 5000 IX = 1, IXL, INC
        IA = IA + 1
        IAL = IA
        ARRAY(IA) = '-
5000 CONTINUE
    ARRAY(IAL+1) = '-
    WRITE (IW,100) ( ARRAY(IA),IA=1,IAL+1 )
C
    GO TO 9900
C

```

```

C
C   CASE OF RIGHT TRIANGLE WITH NE-SW HYPOTENUSE
C
6200 ARRAY(1) = '|'
    WRITE (IW,800 )
    GO TO 9900
C
C
C   CASE OF SQUARE
C
8200 CONTINUE
    INC = 1
    IF ( LY .GT. 130 )      INC = 2
    MINC = - INC
C
    ARRAY(1) = '+'
    IA = 1
    DO 8300 IX = 1, LY, INC
    IA = IA + 1
    IAL = IA
    ARRAY(IA) = '- '
8300 CONTINUE
    ARRAY(IAL+1) = '+'
    WRITE (IW,100) ( ARRAY(IA), IA=1, IAL+1 )
C
    ARRAY(1) = '|'
    DO 8600 IY = LY, 1, MINC
    IA = 1
    DO 8400 IX = 1, LY, INC
    IA = IA + 1
    IAL = IA
    IC = INXST(IX,IY)
    ARRAY(IA) = ICHR(IC+1)
    IF ( MEGA .EQ. 0 )      GO TO 8400
    ICODD = MOD(IC,2)
    IF ( ICODD .EQ. 0 ) ARRAY(IX+1) = ' '
    IF ( ICODD .EQ. 0 )      GO TO 8400
    IM = MCNUMB(IX,IY)
    ARRAY(IX+1) = ICHR(IM+1)
8400 CONTINUE
    ARRAY(IAL+1) = '|'
    WRITE (IW,100) ( ARRAY(IA), IA=1, IAL+1 )
8600 CONTINUE
C
    IA = 1
    ARRAY(1) = '+'
    DO 9000 IX = 1, LY, INC
    IA = IA + 1
    IAL = IA
    ARRAY(IA) = '- '
9000 CONTINUE
    ARRAY(IAL+1) = '+'
    WRITE (IW,100) ( ARRAY(IA), IA=1, IAL+1 )
C
    GO TO 9900
C
C
9800 WRITE (IW,900 )
C
9900 RETURN

```

```

C   END   TUBAUS
      END
      SUBROUTINE COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
C
C   Find value of fitting criterion between waterflood model
C   and production histories.
C   amj, 22 November 1991
C
      REAL HIST( * ), THIST ( * ), MODEL( * ), RMS,SER
      SAVE ISTART,KOUNT,N
C
      real tyrl
      integer nl
      common /gdat/ tyrl,nl
C
C   ISW is an initialization switch.
C
      IF (ISW .EQ. 0) GO TO 200
C   Open history file.
C
      WRITE(*, '(A/)') ' Enter input file name.'
      READ(*, '(A)') FILENAME
      FULLNAME = FILENAME // HISTORY
      OPEN(1,FILE = FULLNAME, STATUS = 'OLD')
C
      OPEN(60,FILE='history.hst',STATUS='OLD',IOSTAT=IS)
C
      IF(IS.NE.0) THEN
        WRITE(*,'(///' HISTORY FILE NOT FOUND...'//)')
        STOP ' '
      ENDIF
C
C   Read History File.
C
      ISTART = 1
      KOUNT = 0
      QMEAN = 0.0
      qmean2=0.0
      SSQ = 0.0
      W = 1.0
      SUMW = 0.0
100  READ(60, * ,END=130) T,X
      IF (KOUNT .EQ. 0) THEN
        SAVEX = X
        tyrl=t
      ELSE
        IF (X .GT. SAVEX) THEN
          ISTART = KOUNT
          SAVEX = X
        ENDIF
      ENDIF
      KOUNT = KOUNT + 1
      HIST(KOUNT)=X
      QMEAN = QMEAN + HIST(KOUNT) * W
      qmean2=qmean2 + hist(kount)
C
      SSQ = SSQ + HIST(KOUNT)*HIST(KOUNT)*W
      ssq = ssq + hist(kount)*hist(kount)

```

```

SUMW = SUMW + W
W = W * 0.9
THIST(KOUNT) = T
c   write(55,*) 'kount,hist(kount),w,sumw,qmean,ssq'
c   write(55,*) kount,hist(kount),w,sumw,qmean,ssq
GO TO 100

130  CONTINUE
WRITE(*,112) ISTART
112  FORMAT(' Starting history match at year',I2)
N = KOUNT - ISTART + 1
n1=n
NA = KOUNT
QMEAN = QMEAN / SUMW
qmean2=qmean2/n
c   VARQ = SSQ/SUMW - QMEAN*QMEAN
varq = ssq/n-qmean2*qmean2
c   write(55,*) 'qmean , varq ',qmean,varq
CLOSE (60)
RETURN

C
C Find measures of goodness of fit.
C Computation of biased-adjusted SER added 4-16-92 by amj to find
C best-fitting slope.
C
200  CONTINUE
SSE = 0
W = 1.0
SUMW = 0.0
SSF = 0.0
SSQF = 0.0
FMEAN = 0.0
c   write(55,*) 'i,sumw,w,fmean,ssqf,ssf,sse,hist(i),model(i)'
DO 300 I = ISTART, KOUNT
SUMW = SUMW + W
c   FMEAN = FMEAN + MODEL(I) * W
fmean = fmean + model(i)
c   SSQF = SSQF + HIST(I)*MODEL(I)*W
ssqf = ssqf + hist(i)*model(i)
c   SSF = SSF + MODEL(I)*MODEL(I)*W
ssf = ssf + model(i)*model(i)
SSE = SSE + W*(HIST(I)-MODEL(I))*(HIST(I)-MODEL(I))
W = W * 0.9
c   write(55,*) i,sumw,w,fmean,ssqf,ssf,sse,hist(i),model(i)
300  CONTINUE
RMS = 100. * SQRT(SSE/SUMW) / QMEAN
c   FMEAN = FMEAN / SUMW
c   VARF = SSF/SUMW - FMEAN*FMEAN
c   COV = SSQF/SUMW - FMEAN*QMEAN
fmean = fmean/n
varf = ssf/n-fmean*fmean
cov = ssqf/n-fmean*qmean2
IF (SSF .GT. 0) THEN
SER = 100.*sqrt(abs(1-COV/VARF))
ELSE
SER = RMS
ENDIF
c   write(55,*) 'rms,qmean,varq,fmean,varf,cov,ser'
c   write(55,*) rms,qmean,varq,fmean,varf,cov,ser
RETURN

```

```

C      END
C
C      SUBROUTINE FOLLSL ( XCROSS, YCROSS, NCOORD, IN, IINJW, JINJW,
C
C          *I*      *I*      *I*      *I*      *I*      *I*
C
C      *          ISTUBE, MARK, SLL, NPROD, LY )
C
C          *I*      *I*      *O*      *O*      *I*
C
C      -----
C
C          F O L L S L
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'TUBE.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'FILES.INC'
C
C      LARGE = 1000
C      JOKE = 5
C      SLL = 0.0
C
C      IF ( MARK .EQ. 0 )          GO TO 5000
C
C      FOLLOW AND MARK STREAM LINE BACKWARD TO INJECTOR
C      XSL = XCROSS
C      YSL = YCROSS
C      ISL = XSL + 0.5
C      JSL = YSL + 0.5
C      ISLINC = 1
C      IF ( IINJW .GT. ISL )  ISLINC = -1
C      JSLINC = 1
C      IF ( JINJW .GT. JSL )  JSLINC = -1
C      DO 4600 L = 1, LARGE
C      NXTISL = ISL-ISLINC
C      NXTJSL = JSL-JSLINC
C      IF ( NXTISL .LT. IMINGD(NXTJSL) .OR.
C      *      NXTISL .GT. IMAXGD(NXTJSL) )          GO TO 4400
C
C      MAKE ONE STEP TOWARD INJECTOR
C      QXNOW = QX(ISL,JSL)
C      QYNOW = QY(ISL,JSL)
C      QRSLT = SQRT ( QXNOW**2 + QYNOW**2 )
C      XINC = 0.5 * QXNOW / QRSLT
C      YINC = 0.5 * QYNOW / QRSLT
C      XSLP = XSL
C      YSLP = YSL
C      XSL = XSL + XINC
C      YSL = YSL + YINC
C      ISL = XSL + 0.5
C      JSL = YSL + 0.5
C      QXNXT = QX(ISL,JSL)
C      QYNXT = QY(ISL,JSL)
C      QXAVE = QXNOW + QXNXT
C      QYAVE = QYNOW + QYNXT
C      QRSLT = SQRT ( QXAVE**2 + QYAVE**2 )
C      XINC = 0.5 * QXAVE / QRSLT
C      YINC = 0.5 * QYAVE / QRSLT
C      XSL = XSLP + XINC

```

```

YSL = YSLP + YINC
SLL = SLL + SQRT ( XINC**2 + YINC**2 )
ISL = XSL + 0.5
JSL = YSL + 0.5
IF ( ISL .LT. IMINGD(JSL) .OR. ISL .GT. IMAXGD(JSL) ) GO TO 4400
IF ( MARK .NE. 0 ) CALL MARKSL ( XSL, YSL, ISTUBE )
IF ( IABS(IINJW-ISL) .GT. JOKE ) GO TO 4600
IF ( IABS(JINJW-JSL) .GT. JOKE ) GO TO 4600
4400 CONTINUE
CALL EXTEND ( XSL, YSL, FLOAT(IINJW), FLOAT(JINJW),
*          ISTUBE, SLL, MARK )
IF ( MARK .NE. 0 ) NODINJ(ISTUBE) = IN
GO TO 5000
C
4600 CONTINUE
WRITE (IW,460)
460 FORMAT ( ' INFINITE LOOP ' )
CALL HALTER ( 'FOLLSSL', 4600 )
C
C FOLLOW AND MARK STREAM LINE FORWARD TO PRODUCER
5000 XSL = XCROSS
YSL = YCROSS
ISL = XSL + 0.5
JSL = YSL + 0.5
IF ( ISL .GE. IMAXGD(JSL) ) ISL = ISL - 1
DO 6800 L = 1, LARGE
C MAKE ONE STEP TOWARD PRODUCER
QXNOW = QX(ISL,JSL)
QYNOW = QY(ISL,JSL)
QRSLT = SQRT ( QXNOW**2 + QYNOW**2 )
XINC = -0.5 * QXNOW / QRSLT
YINC = -0.5 * QYNOW / QRSLT
XSLP = XSL
YSLP = YSL
XSL = XSL + XINC
YSL = YSL + YINC
ISL = XSL + 0.5
JSL = YSL + 0.5
ISLP = ISL
JSPL = JSL
IF ( JSL .LT. 1 ) YSL = 1
IF ( JSL .GT. LY ) YSL = LY
JSL = YSL + 0.5
IF ( ISL .LT. IMINGD(JSL) ) XSL = IMINGD(JSL)
IF ( ISL .GT. IMAXGD(JSL) ) XSL = IMAXGD(JSL)
ISL = XSL + 0.5
IF ( ISL .NE. ISLP .OR. JSL .NE. JSPL ) JOKE = JOKE + 1
QXNXT = QX(ISL,JSL)
QYNXT = QY(ISL,JSL)
QXAVE = QXNOW + QXNXT
QYAVE = QYNOW + QYNXT
QRSLT = SQRT ( QXAVE**2 + QYAVE**2 )
XINC = -0.5 * QXAVE / QRSLT
YINC = -0.5 * QYAVE / QRSLT
SLL = SLL + SQRT ( XINC**2 + YINC**2 )
XSL = XSLP + XINC
YSL = YSLP + YINC
ISLP = ISL
JSPL = JSL
ISL = XSL + 0.5

```

```

JSL = YSL + 0.5
IF ( JSL .LT. 1 )          YSL = 1
IF ( JSL .GT. LY )         YSL = LY
JSL = YSL + 0.5
IF ( ISL .LT. IMINGD(JSL) ) XSL = IMINGD(JSL)
IF ( ISL .GT. IMAXGD(JSL) ) XSL = IMAXGD(JSL)
ISL = XSL + 0.5
IF ( ISL .NE. ISLP .OR. JSL .NE. JSIP ) JOKE = JOKE + 1
IF ( MARK .NE. 0 ) CALL MARKSL ( XSL, YSL, ISTUBE )
DO 6600 ICOORD = 1, NCOORD
IF ( RATE(ICOORD) .LE. 0.0 )      GO TO 6600
IWELL = X(ICOORD)+0.001
JWELL = Y(ICOORD)+0.001
IF ( IABS(IWELL-ISL) .GT. JOKE )  GO TO 6600
IF ( IABS(JWELL-JSL) .GT. JOKE )  GO TO 6600
IPRODW = ICOORD
GO TO 7000
6600 CONTINUE
C
6800 CONTINUE
WRITE (IW,680)
680 FORMAT ( ' INFINITE LOOP ' )
CALL HALTER ( 'FOLLSSL', 6800 )
C
7000 CONTINUE
CALL EXTEND ( XSL, YSL, FLOAT(IWELL), FLOAT(JWELL),
*          ISTUBE, SLL, MARK )
NPROD = IPRODW
IF ( MARK .NE. 0 ) NODPRD(ISTUBE) = IPRODW
C
9900 RETURN
C  END  FOLLSSL
END
SUBROUTINE EXTEND ( XSL, YSL, XWELL, YWELL, ISTUBE, SLL,
C          *I* *I* *I* *I* *I* *IO*
C
C          MARK )
C          *I*
C
C
C          -----
C
C          E X T E N D
C
C          -----
C
C
C  INCLUDE 'PARAM.INC'
C  INCLUDE 'TUBE.INC'
C  INCLUDE 'STREAM.INC'
C  INCLUDE 'FILES.INC'
C
C  XDIST = XWELL - XSL
C  YDIST = YWELL - YSL
C  DIST = SQRT ( XDIST**2 + YDIST**2 )
C  SLL = SLL + DIST
C  NSTEPS = DIST / 0.5
C  XSTEP = 0.5 * XDIST / DIST
C  YSTEP = 0.5 * YDIST / DIST
C  XPT = XSL
C  YPT = YSL

```



```

DO 3000 N = 1, NSTEPS
XPT = XPT + XSTEP
YPT = YPT + YSTEP
IPT = XPT + 0.5
JPT = YPT + 0.5
IF ( IPT .LT. IMINGD(JPT) .OR. IPT .GT. IMAXGD(JPT) ) GO TO 3000
IF ( MARK .NE. 0 ) CALL MARKSL ( XPT, YPT, ISTUBE )
3000 CONTINUE
C
9900 RETURN
C  END  EXTEND
      END
      SUBROUTINE MARKSL ( XCOORD, YCOORD, ISTUBE )
C                                *I*      *I*      *I*
C
C  -----
C
C                                M A R K S L
C
C  -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'TUBE.INC'
      INCLUDE 'STREAM.INC'
      INCLUDE 'FILES.INC'
C
      I = XCOORD + 0.5
      J = YCOORD + 0.5
      IF ( INXST(I,J) .EQ. 0 )          GO TO 3000
      IF ( INXST(I,J) .NE. ISTUBE-1 ) GO TO 9900
      IF ( KMRKSL .EQ. 3 )              GO TO 2800
      KMRKSL = KMRKSL + 1
      GO TO 9900
2800 KMRKSL = 0
3000 XCNTR = FLOAT(I)
      YCNTR = FLOAT(J)
      DIST = SQRT ( (XCOORD-XCNTR)**2 + (YCOORD-YCNTR)**2 )
      IF ( DIST .GT. 0.5 )              GO TO 9900
      INXST(I,J) = ISTUBE
C
9900 RETURN
C  END  MARKSL
      END
      SUBROUTINE DEFTUB ( NCOORD, LX, LY )
C                                *I*      *I*      *I*
C
C  -----
C
C                                D E F T U B
C
C  ALLOCATE REMAINING FCG CELLS TO A ST (STREAM TUBE) BY MARKING
C  CELLS (NEGATIVELY IN -INXST-) WITH THE -INXST- FOR THE CLOSEST
C  ST MIDPOINT CELL.
C
C  -----
C
      INCLUDE 'PARAM.INC'
      INCLUDE 'TUBE.INC'
      INCLUDE 'STREAM.INC'

```

```

C      INCLUDE 'FILES.INC'

C      DO 4000 IY = 1, LY
C      IS = IMINGD(IY)
C      IL = IMAXGD(IY)
C      DO 3800 IX = IS, IL
C      IF ( INXST(IX,IY) .NE. 0 ) GO TO 3800
C      CALL SEARCH ( IX, IY, LX, LY, IFND, JFND )
C      INXST(IX,IY) = -INXST(IFND,JFND)
3800 CONTINUE
4000 CONTINUE

C      DO 5000 IY = 1, LY
C      IS = IMINGD(IY)
C      IL = IMAXGD(IY)
C      DO 4800 IX = IS, IL
C      INXST(IX,IY) = IABS(INXST(IX,IY))
4800 CONTINUE
5000 CONTINUE

C      IF ( ISTRMP .NE. 0 ) CALL TUBAUS ( NCOORD, LY, 0 )

C      9900 RETURN
C      END DEFTUB
C      END
C      SUBROUTINE DEFFDC ( LY, NX, NCOORD )
C               *I* *I* *I*
C
C      -----
C
C               D E F F D C
C
C      DEFINE FINITE DIFFERENCE CELLS.
C      FOR EACH ST (STREAM TUBE)..
C      (A)  FOR EACH FCG CELL CALCULATE ITS RDLDP (RELATIVE
C           DOG LEGGED PATH DISTANCE) BETWEEN INJECTOR AND
C           PRODUCER ASSOCIATED WITH ITS ST.
C
C      (B)  SORT THE RDLDP VALUES INTO ASCENDING ORDER.
C
C      (C)  CALCULATE NUMBER OF FCG CELLS FOR EACH (SIMULATOR)
C           MEGA-CELL. THEN ASSIGN FCG CELLS TO MEGA-CELLS IN
C           THE ORDER OF THE SORTED LIST OF RDLDP VALUES.
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'TUBE.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'FILES.INC'
C      DIMENSION MCSIZ(NXMAX)

C      FRAC = 0.8

C      DO 7000 IST = 1, NOTUBS

C      COMPUTE RDLDP(*) (RELATIVE DOG-LEGGED PATH DISTANCES)

C      IN = NODINJ(IST)

```

```

XINJW = X(IN)
YINJW = Y(IN)
IN = NODPRD(IST)
XPRDW = X(IN)
YPRDW = Y(IN)
SLL = FRAC * SLENG(IST)
NCELLS = 0

```

C

```

DO 3000 IY = 1, LY
IXS = IMINGD(IY)
IXL = IMAXGD(IY)
DO 2800 IX = IXS, IXL
IF ( INXST(IX,IY) .NE. IST ) GO TO 2800
NCELLS = NCELLS + 1
IXCELL(NCELLS) = IX
IYCELL(NCELLS) = IY
DINJW = SQRT( (FLOAT(IX)-XINJW)**2 + (FLOAT(IY)-YINJW)**2 )
DPRDW = SQRT( (FLOAT(IX)-XPRDW)**2 + (FLOAT(IY)-YPRDW)**2 )
RAD = SLL / 2.0
IF ( DINJW .GE. RAD ) GO TO 2200
RDLPD(NCELLS) = DINJW / RAD
GO TO 2800
2200 IF ( DPRDW .GE. RAD ) GO TO 2400
RDLPD(NCELLS) = 3.0 - DPRDW / RAD
GO TO 2800
2400 IF ( DINJW .LT. DPRDW ) GO TO 2600
RDLPD(NCELLS) = 1.0 + ( DINJW - RAD ) / ( DINJW + DPRDW - SLL )
GO TO 2800
2600 RDLPD(NCELLS) = 2.0 - ( DPRDW - RAD ) / ( DINJW + DPRDW - SLL )
2800 CONTINUE
3000 CONTINUE
IF ( NCELLS .LT. NX ) CALL HALTER ( 'DEFFDC', 3000 )

```

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

```

SORT ON RDLPD VALUES WITHIN STREAM TUBE

CALL UTLSRX ( NCELLS , RDLPD(1), INXSRT(1) )

ASSIGN MEGA-CELL NUMBERS TO FINE GRID CELLS IN STREAM TUBE

MINSIZ = NCELLS / NX
NOSIZ1 = NCELLS - MINSIZ * NX
IC1 = 1 + ( NX - NOSIZ1 ) / 2
DO 3400 IC = 1, NX
MCSIZ(IC) = MINSIZ
IF ( IC .LT. IC1 ) GO TO 3400
IF ( NOSIZ1 .EQ. 0 ) GO TO 3400
MCSIZ(IC) = MCSIZ(IC) + 1
NOSIZ1 = NOSIZ1 - 1
3400 CONTINUE

MCKNT = 0
MCELL = NX
DO 4000 IC = 1, NCELLS
ISRT = INXSRT(IC)
IX = IXCELL(ISRT)
IY = IYCELL(ISRT)
MCNUMB(IX,IY) = MCELL
MCKNT = MCKNT + 1
IF ( MCKNT .LT. MCSIZ(MCELL) ) GO TO 4000
MCELL = MCELL - 1

```

```

      MCKNT = 0
4000 CONTINUE
C
C   READY TO DO NEXT STREAM TUBE
7000 CONTINUE
C
      IF ( ISTRMP .GT. 1 ) CALL TUBAUS ( NCOORD, LY, 1 )
C
9900 RETURN
C   END DEFFDC
      END
      SUBROUTINE UTLSRX ( NVALS , X , INDEX )
C
C-----
C.
C.   ABSTRACT:
C.   -----
C.   Sorts the real X array into increasing X
C.   Returns INDEX to original position
C.
C.   Use a shell sort taken from KNUTH - VOL 3.
C.   The diminishing increments are defined recursively, as
C.   suggested by KNUTH. INCDIM(10)      = 1
C.                           INCDIM(N-1)  = 3 * INCDIM(N) + 1
C.   Max dimension is approx 2,400,000
C.
C.   ARGUMENT LIST:
C.   -----
C.   =====> NVALS   - Number of items to sort
C.   <===== X      - Real X-array
C.   <===== INDEX   - Integer array containing indices to original order
C.
C-----
C
      DIMENSION X(*) , INDEX(*)
C
      DIMENSION INCDIM(13)
      DATA INCDIM / 797161, 265720, 88573,
*                29524, 9841, 3280, 1093, 364, 121, 40, 13, 4, 1 /
C
      IF ( NVALS .LE. 1 ) GO TO 9999
C
      ***** INITIALIZE INDEX
      DO 10 J = 1 , NVALS
        INDEX(J) = J
10    CONTINUE
C
      ***** SELECT FIRST INCREMENT
      NUMBER = NVALS
900   DO 1000 I = 1, 13
        INCNDX = I
        IF ( INCDIM(I) .GE. NUMBER ) GOTO 1000
        INCNDX = MIN0 ( I + 1, 13 )
        GOTO 2000
1000  CONTINUE
2000  CONTINUE
C
      ***** BEGIN SORT
      DO 8900 LOOPS = INCNDX, 13
C

```

```

C *****
C      SET A NEW (SMALLER) VALUE OF INCDIM
C *****
C      LOOPJ          = INCDIM(LOOPS) + 1
C      IF ( LOOPJ .GT. NUMBER ) GOTO 8900
C
C      DO 8000 J      = LOOPJ, NUMBER
C          I          = J - INCDIM(LOOPS)
C          XTMP       = X(J)
C          ITMP       = INDEX(J)
C
C *****
C      LOOP DOWN IN INCREMENTS OF INCDIM(LOOPS) AND
C      MOVE X(I) TO X(I+INCDIM) UNTIL X(I) > XTMP
C      AT THIS POINT STORE XTMP IN X(I+INCDIM)
C *****
3000      CONTINUE
C          IF ( X(I) .LE. XTMP ) GO TO 6000
C          INDEX2      = I + INCDIM(LOOPS)
C          X(INDEX2)    = X(I)
C          INDEX(INDEX2) = INDEX(I)
C          I           = I - INCDIM(LOOPS)
C          IF ( I .GT. 0 ) GOTO 3000
6000      CONTINUE
C          INDEX3      = I + INCDIM(LOOPS)
C          X(INDEX3)    = XTMP
C          INDEX(INDEX3) = ITMP
8000      CONTINUE
8900      CONTINUE
C
C *****
C      ONCE INCDIM=1 THEN LIST WILL BE IN ORDER
C *****
9999      RETURN
C      END      UTLSRX
C      END
C      SUBROUTINE GENMCP ( LY, NX, INFILL, VTUBE )
C              *I* *I* *I* *I*
C
C      -----
C
C              G E N M C P
C
C      COMPUTE MEGA-CELL PROPERTIES NEEDED BY SIMULATOR.
C
C      -----
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'TUBE.INC'
C      INCLUDE 'STREAM.INC'
C      INCLUDE 'FILES.INC'
C      DIMENSION VTUBE(NTBMAX)
C
C      DO 3000 IST = 1, NTBMAX
C      IF ( NODINJ(IST) .EQ. 0 ) GO TO 3000
C      ATOT(IST) = 0.0
C      DO 2800 IMC = 1, NX
C      RX(IMC,IST) = 0.0
C      RY(IMC,IST) = 0.0

```

```

        RWIDE(IMC,IST) = 0.0
        AVOL(IMC,IST) = 0.0
2800 CONTINUE
3000 CONTINUE
C
        DO 4000 IY = 1, LY
        YFACT = 1.0
        IF ( IY .EQ. 1 .OR. IY .EQ. LY ) YFACT = 0.5
        IXS = IMINGD(IY)
        IXL = IMAXGD(IY)
C
        DO 3600 IX = IXS, IXL
        XFACT = 1.0
        IF ( IX .EQ. IXS .OR. IX .EQ. IXL ) XFACT = 0.5
        IST = INXST(IX,IY)
        IMC = MCNUMB(IX,IY)
        VOL = XFACT * YFACT
        ATOT(IST) = ATOT(IST) + VOL
        AVOL(IMC,IST) = AVOL(IMC,IST) + VOL
        RX(IMC,IST) = RX(IMC,IST) + VOL * FLOAT(IX)
        RY(IMC,IST) = RY(IMC,IST) + VOL * FLOAT(IY)
        IF ( INFILL .NE. 0 ) GO TO 3400
        NGCELT(IX,IY) = IST
        NGCELC(IX,IY) = IMC
        GO TO 3600
3400 CONTINUE
        IGCELT(IX,IY) = IST
        IGCELC(IX,IY) = IMC
3600 CONTINUE
C
4000 CONTINUE
C
        ATOTAL = 0.0
        DO 5000 IST = 1, NOTUBS
C
        ATOTAL = ATOTAL + ATOT(IST)
        DO 4600 IMC = 1, NX
        RX(IMC,IST) = RX(IMC,IST) / AVOL(IMC,IST)
        RY(IMC,IST) = RY(IMC,IST) / AVOL(IMC,IST)
        AVOL(IMC,IST) = AVOL(IMC,IST) / ATOT(IST)
4600 CONTINUE
C
5000 CONTINUE
C
        DO 7000 IST = 1, NOTUBS
        IN = NODINJ(IST)
        XINJW = X(IN)
        YINJW = Y(IN)
        IN = NODPRD(IST)
        XPRDW = X(IN)
        YPRDW = Y(IN)
C
        DO 6600 IMC = 1, NX
        DIVPRV = 2.0
        DIVNXT = 2.0
        IF ( IMC .GT. 1 ) GO TO 5200
        RXPRV = XPRDW
        RYPRV = YPRDW
        RXNXT = RX(IMC+1,IST)
        RYNXT = RY(IMC+1,IST)

```

```

      DIVPRV = 1.0
      GO TO 6000
5200 IF ( IMC .LT. NX )          GO TO 5600
      RXNXT = XINJW
      RYNXT = YINJW
      RXPRV = RX(IMC-1,IST)
      RYPRV = RY(IMC-1,IST)
      DIVNXT = .1.0
      GO TO 6000
5600 RXPRV = RX(IMC-1,IST)
      RYPRV = RY(IMC-1,IST)
      RXNXT = RX(IMC+1,IST)
      RYNXT = RY(IMC+1,IST)
6000 RLENG(IMC,IST) = SQRT ( (RX(IMC,IST)-RXPRV)**2 +
      *                      (RY(IMC,IST)-RYPRV)**2 ) / DIVPRV +
      *                      SQRT ( (RX(IMC,IST)-RXNXT)**2 +
      *                      (RY(IMC,IST)-RYNXT)**2 ) / DIVNXT
      RWIDE(IMC,IST) = AVOL(IMC,IST) * ATOT(IST) / RLENG(IMC,IST)
6600 CONTINUE
C
7000 CONTINUE
C
      OUTPUT PHYSICAL DIMENSIONS OF EACH RESERVOIR SIMULATOR
      (LINEAR) GRID (ONE PER STREAM TUBE) RELATIVE TO THE FINE
      CARTESIAN GRID.
C
      IF ( ISTRMP .LE. 1 ) GO TO 9900
C
      WRITE(IW,800)
800  FORMAT( 1H1 ///
      *      15X, 'STREAM TUBE GEOMETRIES ON FINE-GRID ' /
      *      15X, '-----' /
      *      ' FRACTION OF DIST. BETWEEN CELL WIDTH ',
      *      ' GRID-CELL CENTERS-OF-MASS ' /
      *      ' TUBE PORE VOL. CELL CENTERS ',
      *      ' X-COORD Y-COORD ' )
      DO 8000 I=1, NOTUBS
      DO 7800 J=1,NX
      WRITE(IW,810) AVOL(J,I),RLENG(J,I),RWIDE(J,I),RX(J,I),RY(J,I)
810  FORMAT ( 5(1X,E13.5) )
7800 CONTINUE
      WRITE(IW,820) I, ATOT(I), VTUBE(I)
820  FORMAT ( ' TUBE PORE VOLUME FRACTIONAL RATE ' /
      *      3X,I2,2X,E13.5,2X,E13.5 )
8000 CONTINUE
C
9900 RETURN
C  END  GENMCP
      END
      SUBROUTINE OVER2
C
C -----
C
C  OVER2--- CONTROL ROUTINE FOR THE MAPPING OF ARRAY WITHIN BLANK
C           COMMON FOR THE CALCULATION OF INDIVIDUAL RESERVOIR
C           SIMULATOR CELL PORE VOLUMES, MID-POINT ELEVATIONS, AND
C           TRANSMISSIBILITIES IN THE X AND Z DIRECTION ( ILayer
C           .GT. 1 AND KZKX .GT. 0 ).
C -----
C

```

```

C
      INCLUDE 'PARAM.INC'
      INCLUDE 'SIMUL.INC'
      INCLUDE 'STREAM.INC'

C
C      *****
C      ALLOCATION OF ARRAY -A- FOR SUBROUTINE ARRAYS IS AS FOLLOWS-
C      ARRAY LABEL SIZE DESCRIPTION UNITS
C      -----
C      IA1 = P (NXNYNZ) INITIAL PRES PSI
C      IA2 = SATO (NXNYNZ) INITIAL OIL SATURATION FRAC
C      IA3 = SATW (NXNYNZ) INITIAL WATER SATURATION FRAC
C      IA4 = PORVOL (NXNYNZ) PORE VOLUME CF
C      DATA TABLES ARE INSERTED HERE
C      IA5 = KX (NXNYNZ) X-DIRECTION TRANSMISSIBILITY MD
C      IA6 = KY (NXNYNZ) Y-DIRECTION TRANSMISSIBILITY MD
C      IA7 = KZ (NXNYNZ) Z-DIRECTION TRANSMISSIBILITY MD
C      IA8 = ZTOP (NXNYNZ) TOP FORMATION ELEVATION - NEGATIVE FT
C      IA9 = ZBOT (2NXNY) BOTTOM FORMATION ELEVATION - NEGATIVE FT
C      IA10 = HO (NXNY) OIL ZONE THICKNESS FT
C      IA11 = HG (NXNY) GAS ZONE THICKNESS FT
C      IA12 = H (NXNY) NET POROUS ZONE THICKNESS FT
C      IA13 = DELX (NX) X-DIRECTION GRID SPACING FT
C      IA14 = DELY (NY) Y-DIRECTION GRID SPACING FT
C      IA15 = TEMP (NXNY) TEMPORARY ARRAY USED FOR PRINTING MAPS
C      *****
C      KZ = 1
C      SET UP ARRAY INDICES
      IA1 = 1
      IA2 = IA1 + ( 1 ) * NXNYNZ
      IA3 = IA2 + NXNYNZ
      IA4 = IA3 + NXNYNZ
      IA5 = LASTIN
      IA6 = IA5 + NXNYNZ
      IA7 = IA6 + NXNYNZ
      IA8 = IA7
      IA9 = IA8 + NXNYNZ + NXNY
      IA10 = IA9 + NXNY
      IA11 = IA10 + NXNY
      IA12 = IA11 + NXNY
      IA13 = IA12 + NXNY
      IA14 = IA13 + NX
      IA15 = IA14 + NX
      ILAST = IA15 + NXNY - 1
100 CONTINUE
      IF ( KZ .EQ. 1 ) IL = ILAST
C      CHECK TO SEE IF COMMON IS LARGE ENOUGH
      IEXCES(2) = NCORE - ILAST
130 CONTINUE
      PVTOT = 0.0
      HCPORV = 0.0
C
      DO 8000 I11=1,NOTUBS
      MTUBE=I11
      DO 8000 J11=1,ILAYER
      MLAYER=J11
      EMPTYX = 0.0
      DO 110 I = IA9,IL
110 A(I) = EMPTYX
      CALL ACHECK

```



```

C          P      , SATO      , SATW      , PORVOL , KX      , KY      ,
*          ( A(IA1) , A(IA2) , A(IA3 ) , A(IA4 ) , A(IA5 ) , A(IA6) ,
C          KZ      , ZTOP      , ZBOT      , HO      , HG      , H      ,
*          A(IA7) , A(IA8) , A(IA9) , A(IA10) , A(IA11) , A(IA12) ,
C          DELX      , DELY      , BLK      , PVT      , ROK      , DIS      ,
*          A(IA13) , A(IA14) , A(IA3) , A(IA2) , A(IA5) , A(IA6) ,
C          XF      , YF      , FW      , FG      , TEMP      ,
*          A(IA10) , A(IA11) , A(IA5) , A(IA6) , A(IA15) )
C *****
8000 CONTINUE
9999 RETURN
      END
      SUBROUTINE ACHECK
*          (P      , SATO      , SATW      , PORO      , FKX      , FKY      ,
*          FKZ      , ZT      , ZB      , HO      , HG      , H      ,
*          DELX      , DELY      , BLK      , PVT      , ROK      , DIS2      ,
*          XF      , YF      , FW      , FG      , TEMP      , )
C
C
C -----
C          ACHECK-- CALCULATES THE INITIAL CELL PORE VOLUMES AND TRANSMIS
C          SIBILITIES FOR EACH CELL IN A STREAMTUBE.
C
C -----
C          THESE VARIABLES ARE ACTUALLY MAPPED INTO BLANK COMMON IN OVER2
C
C          DIMENSION
1          P(1)      , SATO(1) , SATW(1) , PORO(1) , ZT(1)      , ZB(1)      ,
2          FKX(1) , FKY(1) , FKZ(1) , HO(1)      , HG(1)      , H(1)      ,
3          DELX(1) , DELY(1) , BLK(1) , PVT(1) , ROK(1) , DIS2(1) ,
4          XF(1)      , YF(1)      , FW(1)      , FG(1)      , TEMP(1)
C          DIMENSION KNT(50)
C
C          INCLUDE 'PARAM.INC'
C          INCLUDE 'SIMUL.INC'
C          INCLUDE 'STREAM.INC'
C          INCLUDE 'FILES.INC'
C
C          1111 FORMAT ( 1H1 )
C
C          PVLAYR      = 0
C          HVLAYR      = 0
C          OVLAYR      = 0
C          WVLAYR      = 0
C          GVLAYR      = 0
C
C          SPREAD OUT INPUT VALUES TO VALUES FOR EACH CELL
C
C          Used to CALL GRIDC3 (FKX      , FKY      , VKX(MLAYER) , VKY(MLAYER) , NX)
C
C          SUBROUTINE GRIDC3 (ARR1,ARR2,VAL1,VAL2,NX)
C
C          -----
C          GRIDC3--CALCULATE THE PERMEABILITY BETWEEN CELLS IN THE TUBES
C          FOR KY=KX, ITS JUST A REPLACEMENT FROM THE INPUT VALUE.
C          -----
C          IF (ABS(VANIS-1.0).LE.0.0001) THEN
C              DO 1010 I = 1, NX
C                  FKX(I) = VKX(MLAYER)

```

```

      FKK(I) = VKY(MLAYER)
1010  CONTINUE
      ENDIF
C
C  Used to CALL GRIDC2 (FKX ,FKY, VKX(MLAYER),VKY(MLAYER) ,NX)
C
C  SUBROUTINE GRIDC2 (ARR1,ARR2,VAL1,VAL2,NX)
C
C  GRIDC2---CALCULATE THE PERMEABILITY BETWEEN CELLS IN THE TUBES
C  FOR KY>KX THE DIRECTION WEIGHTED AVERAGE OF KY AND KX
C  IS USED BASED ON THE FINE-GRID LOCATIONS OF THE CELL
C  CENTERS FOR EACH CELL IN THE TUBE.
C  *NOTE* ---HERE, AS IN GRIDC3 AND OTHER PLACES, DATA FOR THE
C  Y-DIMENSION OF THE SIMULATOR GRID ARE FAITHFULLY
C  SUPPLIED (VIZ.. ARR2(*)) IN ORDER TO SATISFY ANY
C  POSSIBLE REQUIREMENT WITHIN THE SIMULATOR (WHICH
C  IS/WAS A 3-D SIMULATOR) ALTHOUGH THE PROBLEM SOLVED
C  HERE USES ONLY AN X-Z GRID.
C
C  IF (ABS (VANIS-1.0) .GT.0.0001) THEN
      DO 1020 I = 1, NX
        FKY(I) = VKY(MLAYER)
1020  CONTINUE
        IL = NX / 3
        DO 2020 I = 1, IL
          DX = ABS (RX(I,MTUBE)-RX(I+1,MTUBE))
          DY = ABS (RY(I,MTUBE)-RY(I+1,MTUBE))
          FKK(I) = (DX*VKX(MLAYER) + DY*VKY(MLAYER)) / (DX+DY)
2020  CONTINUE
          I1 = IL + 1
          IL = NX - IL
          DO 2220 I = I1, IL
            DX = ABS (RX(I+1,MTUBE)-RX(I-1,MTUBE))
            DY = ABS (RY(I+1,MTUBE)-RY(I-1,MTUBE))
            FKK(I) = (DX*VKX(MLAYER) + DY*VKY(MLAYER)) / (DX+DY)
2220  CONTINUE
            I1 = IL + 1
            DO 2320 I = I1, NX
              DX = ABS (RX(I,MTUBE)-RX(I-1,MTUBE))
              DY = ABS (RY(I,MTUBE)-RY(I-1,MTUBE))
              FKK(I) = (DX*VKX(MLAYER) + DY*VKY(MLAYER)) / (DX+DY)
2320  CONTINUE
          ENDIF
          DO 1234 I = 1, NX
            PORO(I) = VPHI(MLAYER)
            H(I) = VH1(MLAYER)
            ZT(I) = VZT(MLAYER)
            ZB(I) = VZB(MLAYER)
1234  CONTINUE
C *****
C
C  CALL GRIDC1 (P ,VP1(MLAYER),NX,MTUBE,MLAYER,1)
C  CALL GRIDC1 (SATO ,VSO(MLAYER),NX,MTUBE,MLAYER,2)
C  CALL GRIDC1 (SATW ,VSW(MLAYER),NX,MTUBE,MLAYER,3)
C  This used to be
C  SUBROUTINE GRIDC1 (ARRAY,VALUE,NX,ITB,ITL,IT)
C  Modified and put in-line by amj, 2 April 1992
C
C  FILL THE ARRAY OF PRESSURES AND SATURATIONS FROM THE ENDPOINTS OF

```

```

C THE REL-PERM CURVES FOR THE NON-INFILL CASE AND BY INTERPOLATING
C FROM THE NON-INFILL ARRAYS AT INFILL TIME FOR THE INFILL CASE.
C THE INTERPOLATION IN THE LATTER CASE IS BASED ON KNOWING WHICH
C CELL AND STREAMTUBE EACH OF THE STREAMTUBE CALCULATION GRID POINTS
C ( 'IGDMAX' BY 'JGDMAX' ) WAS LOCATED IN FOR BOTH CASES.

```

```

C
C
C

```

```

      IF ( IGOV .NE. 1 ) THEN
        DO 1000 IX = 1, NX
          P(IX) = VP1(MLAYER)
          SATO(IX) = VSO(MLAYER)
          SATW(IX) = VSW(MLAYER)

```

```

1000    CONTINUE
      ELSE

```

```

C

```

```

C INFILL CASE INTERPOLATION BY CELL FOR EACH TUBE

```

```

C

```

```

      DO 2200 IX=1,NX
        P(IX) = 0
        SATO(IX) = 0
        SATW(IX) = 0
        KNT(IX)= 0
2200    CONTINUE
      DO 3300 I=1,IGDMAX
        DO 3000 J=1,JGDMAX
          IF ( IGCELT(I,J) .NE. MTUBE ) GO TO 3000
          MTUBEOL= NGCELT(I,J)
          I1OL = NGCELC(I,J)
          IF ( MTUBEOL .EQ. 0 .OR. I1OL .EQ. 0 ) GO TO 3000
          IX = IGCELC(I,J)

```

```

C

```

```

C CURRENT INFILL STREAMTUBE CELL IS ('MTUBE','IX')
C THAT LOCATION WAS IN TUBE 'MTUBEOL' AND CELL 'I1OL' IN THE
C NON-INFILL CASE

```

```

C

```

```

          KNT(IX)=KNT(IX)+1
          P(IX) = P(IX) + VP1B(I1OL,MTUBEOL,MLAYER)
          SATO(IX) = SATO(IX) + VS01B(I1OL,MTUBEOL,MLAYER)
          SATW(IX) = SATW(IX) + VSW1B(I1OL,MTUBEOL,MLAYER)

```

```

3000    CONTINUE

```

```

3300    CONTINUE

```

```

      DO 4000 IX = 1, NX
        P(IX) = P(IX) / KNT(IX)
        SATO(IX) = SATO(IX) / KNT(IX)
        SATW(IX) = SATW(IX) / KNT(IX)

```

```

4000    CONTINUE

```

```

      ENDIF

```

```

C

```

```

C      * THIS LOOP COMPUTES TRANSMISSIBILITIES AND *
C      * AVERAGE ELEVATIONS.

```

```

C

```

```

      DO 9100 I=1,NX
        IJ = I
        ZT(IJ) = ( ZT(IJ) + ZB(IJ) ) * 0.5
        PORO(IJ) = PORO(IJ)*RLENG(I,MTUBE)*RWIDE(I,MTUBE)*H(IJ)
        TEMPX = FKX(IJ)
        IF ( I .EQ. NX ) GO TO 9025
        HK1 = H(IJ) * TEMPX
        HK2 = H(IJ+1) * FKX(IJ+1)

```

```

      TEMPX = 0.01266*(RWIDE(I,MTUBE)+RWIDE(I+1,MTUBE))*HK1*HK2/
1      (RLENG(I,MTUBE)*HK2 + RLENG(I+1,MTUBE)* HK1 + 1.0E-20)
      TEMPX = 4.0 * TEMPX
      FKK(IJ)= TEMPX
9025      CONTINUE
      IF ( MLAYER .EQ. 1 .OR. VKZKH .LT. 1.E-6 ) GO TO 9036
      TEMPX1 = VKX(MLAYER)*VKZKH
      TEMPX2 = VKX(MLAYER-1)*VKZKH
      TEMPX= (VH1(MLAYER)+VH1(MLAYER-1)) /
1      ((VH1(MLAYER)/TEMPX1) + (VH1(MLAYER-1)/TEMPX2))
      VTZ(IJ,MTUBE,MLAYER)=0
      TEMPX = 4.0 * TEMPX
      VTZ(IJ,MTUBE,MLAYER) = 0.00633 * TEMPX * RLENG(IJ,MTUBE) *
1      RWIDE(IJ,MTUBE) / ( (VZT(MLAYER-1)+VZB(MLAYER-1))/2. -
2      (VZT(MLAYER)+VZB(MLAYER))/2. )
9036      CONTINUE
9100      CONTINUE
      DO 9200 I=1,NX
      VP(I,MTUBE,MLAYER)= P(I)
      VSO1(I,MTUBE,MLAYER)=SATO(I)
      VSW1(I,MTUBE,MLAYER)=SATW(I)
      VPV1(I,MTUBE,MLAYER)=PORO(I)
      VTX(I,MTUBE,MLAYER)=FKX(I)
      VTY(I,MTUBE,MLAYER)=FKY(I)
      VZAVG(I,MTUBE,MLAYER)=(VZT(MLAYER)+VZB(MLAYER))/2.
9200      CONTINUE
C      *****
C      *      COMPUTE IN-PLACE VOLUMES.      *
C      *****
      DO 9105 I = 1,NX
      IJ = I
      IJK = IJ
      PIJ=P(IJ)
      CALL PORE ( PV, PORO(IJ), PIJ, ROKCMP )
      NREG = 1
      SO= SATO(IJ)
      SW= SATW(IJ)
      PVTOT = PVTOT + PV
      HCPORV = HCPORV + PV * ( 1.0 - SW )
      CALL PROIL (I,J,P(IJ),BO,RSO,DUM,DUM,2,NREG)
      CALL WATPR (I,J,P(IJ),BW,RSW,DUM,DUM,2,NREG)
C      *****
C      *****
      DPSATO = SO
      DPSATW = SW
      DPPV = PV
      DPBO = BO
      DPBW = BW
      DPBG = 1.
      DPRSO = 0
      DPRSW = 0
      DPOIPT = DPSATO * DPPV / DPBO
      OIP = OIP + DPOIPT
      DPWIPT = DPSATW * DPPV / DPBW
      WIP = WIP + DPWIPT
      DPGIPT = DPOIPT*RSO
      GIP = GIP + DPGIPT
      PVLAYR = PVLAYR + PV
      HVLAYR = HVLAYR + PV * ( 1.0 - SW )
      OVLAYR = OVLAYR + DPOIPT

```

```

          WVLAIR      = WVLAIR + DPWIPT
          GVLAIR      = GVLAIR + DPGIPT
9105 CONTINUE
      OIPOR      = OIP
      WIPOR      = WIP
      PVLY(MTUBE,MLAYER)=PVLAIR
      PVTOTM     = PVTOT / 5615000.
      ORIGPV     = PVTOTM * 1000000.

C
      IF( IANALP .NE. 0 .AND. MLAYER .EQ. 1 .AND. MTUBE .EQ. 1 )
      * WRITE(IW,9272)  RSCALE
9272 FORMAT ( 1H1 ///
      * / 10X, ' SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES'
      * / 10X, ' ====='
      * // 14X, ' ( ALL VOLUMES/RATES GIVEN BELOW ARE FOR )'
      * / 14X, ' ( THE SYMMETRY ELEMENT WHICH HAS 1.0/ ',F3.1, ' )'
      * / 14X, ' ( OF THE AREA OF THE PRE-INFILL 5-SPOT. )'
      * /// ' IN - PLACE - VOLUMES '
      * / '
      * / ' LAYER TUBE OIL (SCF) WATER (SCF) ',
      * / ' PORE VOL. (RCF) '
      * / ' -----'
      * / ' / )
      IF( IANALP .NE. 0 )
      * WRITE(IW,9271) MLAYER,MTUBE,OVLAYR,WVLAIR,PVLAIR
9271 FORMAT( 1X, I4, I6, 3(5X,E14.5) )
      IF ( MTUBE .EQ. NOTUBS .AND. MLAYER .EQ. ILAYER
      * .AND. IANALP .NE. 0 )
      * WRITE(IW,9270) OIP , WIP , PVTOT
9270 FORMAT ( / ' TOTALS ', 3E19.5 )
      OIPM = OIP / 5615.0
      WIPM = WIP / 5615.0
      IF ( MTUBE .EQ. NOTUBS .AND. MLAYER .EQ. ILAYER
      * .AND. IANALP .NE. 0 )
      * WRITE(IW,9269) OIPM , WIPM
9269 FORMAT ( / ' (M-STB) ', 2G19.5 /// )

C
      IF( MTUBE .NE. NOTUBS .OR. MLAYER .NE. ILAYER ) GO TO 9999

C
C      CALCULATE TIME STEP SIZE BASED ON THE PORE VOLUME TO THROUGHPUT
C      RATIO OF THE STREAMTUBE THAT HAS THE LOWEST PORE VOLUME TO
C      THROUGHPUT RATIO. THIS IS TO ASSURE 'IMPES' STABILITY.
C
      IF (IGOV.EQ. 1 ) GO TO 9350
      RATIOV=1.0E+12
      DO 9290 J=1,ILAYER
      DO 9280 I=1,NOTUBS
      IF(IINJ(I,J).EQ.0) THEN
      RATIV= (PVLY(I,J))/VQW(I,J)
      ENDIF
9280 IF(RATIV .LT. RATIOV ) RATIOV=RATIV
9290 CONTINUE
      RATIOV = RATIOV/NX
C      RATIOV = DAYS TO INPUT THE PORE VOLUME OF 1 CELL IN MOST
C      RESTRICTIVE TUBE--RATE COMBINATION.

```

c ptt /4/92 divide ratioiv by 5 rather than 10. this effectivly doubles
c the time step size.

DELTAT= RATIOV /5.

C INPUT 10% OF A PORE VOLUME PER TIME STEP-- THIS IS A PRETTY BIG
C STEP SIZE AND REPRESENTS A COMPROMISE BETWEEN SPEED AND
C ACCURACY.
GO TO 9999

C ***** C A U T I O N *****
C SCHEME USED IN SUBROUTINE -ECONID- TO STRIP OUT SIMULATOR
C DATA FOR DOING INCREMENTAL ECONOMICS DEPENDS ON THE FOLLOWING
C RELATIONSHIP FOR TIME STEP SIZE IN INFILL RELATIVE TO NON-INFILL.
C ***** C A U T I O N *****

C 9350 DELTAT = DELTAT/2.0
C IN INFILL CASE THE RATES APPROXIMATELY DOUBLE AND CELL SIZES ARE
C APPROXIMATELY EQUIVALENT -- SO CUT TIME STEP IN HALF
C

9999 RETURN
END

SUBROUTINE OVER4

C *****
C * O V E R 4 *
C *****
C * DRIVER FOR COEFFICIENT GENERATION. *
C *
C * CALLS ARE MADE ON SUBROUTINES -EMPFUN-, -WTRFUN-, -INICOF-, *
C * -OILCOF-, -WTRCOF-, AND -FINCOF- FOR EACH ROW OF THE *
C * THE FINITE DIFFERENCE GRID. *
C *****
C * BLANK COMMON PARTITIONING *
C *
C *
C * PART. ARRAY SIZE DESCRIPTION *
C *
C * 1 P (NXNYNZ) PRESSURE *
C * 1A LOGAS (NXNYNZ) LOGAS (RSO + GASY BIT) *
C * 2 SATO (NXNYNZ) OIL SATURATION *
C * 3 SATW (NXNYNZ) WATER SATURATION *
C * 4 PORV (NXNYNZ) CELL PORE VOLUME *
C * 4A PCON (NXNYNZ) CONCENTRATION + (PACK!) ADS. FRAC *
C * 5 TRX (NXNYNZ) X-DIR. TRANS. * 4 (SEE OL2) *
C * AW (NXNYNZ) *
C * 6 TRY (NXNYNZ) Y-DIR. TRANS. * 4 (SEE OL2) *
C * AE (NXNYNZ) *
C * 7 TRZ (NXNYNZ) Z-DIR. TRANS. * 4 (SEE OL2) *
C * AB (NXNYNZ) *
C * 8 ZAVG (NXNYNZ) CELL MIDPOINT ELEVATION. *
C * AN (NXNYNZ) *
C * 9 AS (NXNYNZ) PRESS. EQN. *
C * 10 AC (NXNYNZ) *
C * 11 AT (NXNYNZ) COEFFICIENTS *
C * 12 RHS (NXNYNZ) *
C * 13 SAOS (NX*NZP) SYMM. OIL FLOW COEF. - SOUTH *
C * 14 SAWS (NX*NZP) SYMM. WTR FLOW COEF. - SOUTH *
C * 15 SAGS (NX*NZP) SYMM. GAS FLOW COEF. - SOUTH *
C * 16 WAGS (NX) TOTAL GAS FLOW COEF. - SOUTH *
C * 17 SAOE (NX) SYMM. OIL FLOW COEF. - EAST *
C * 18 SAWE (NX) SYMM. WTR FLOW COEF. - EAST *
C * 19 SAGE (NX) SYMM. GAS FLOW COEF. - EAST *
C * 20 WAGE (NX) TOTAL GAS FLOW COEF. - EAST *
C * 21 SAOT (NX*NYP) SYMM. OIL FLOW COEF. - TOP *

```

C      *      22      SAWT      (NX*NYP)      SYMM. WTR FLOW COEF. - TOP      *
C      *      23      SAGT      (NX*NYP)      SYMM. GAS FLOW COEF. - TOP      *
C      *      24      WAGT      (NX)          TOTAL GAS FLOW COEF. - TOP      *
C      *      25      GPCOS      (NX*NZP)      GRAV-PC FLOW FOR OIL - SOUTH      *
C      *      26      GPCWS      (NX*NZP)      GRAV-PC FLOW FOR WTR - SOUTH      *
C      *      27      GPCGS      (NX*NZP)      GRAV-PC FLOW FOR GAS - SOUTH      *
C      *      28      GPCOE      (NX)          GRAV-PC FLOW FOR OIL - EAST      *
C      *      28      GPCWE      (NX)          GRAV-PC FLOW FOR WTR - EAST      *
C      *      28      GPCGE      (NX)          GRAV-PC FLOW FOR GAS - EAST      *
C      *      29      GPCOT      (NX*NYP)      GRAV-PC FLOW FOR OIL - TOP      *
C      *      30      GPCWT      (NX*NYP)      GRAV-PC FLOW FOR WTR - TOP      *
C      *      31      GPCGT      (NX*NYP)      GRAV-PC FLOW FOR GAS - TOP      *
C      *      32      RSOCS      (NX*NZP)      RSO UPSTREAM - SOUTH      *
C      *      33      RSWCS      (NX*NZP)      RSW UPSTREAM - SOUTH      *
C      *      34      RSOCE      (NX)          RSO UPSTREAM - EAST      *
C      *      34      RSWCE      (NX)          RSW UPSTREAM - EAST      *
C      *      35      RSOCT      (NX*NYP)      RSO UPSTREAM - TOP      *
C      *      36      RSWCT      (NX*NYP)      RSW UPSTREAM - TOP      *
C      *      37      DELT      (NX)          D(ZAVG) - TOP      *
C      *      39      AOT      (NX)          *
C      *      40      AOB      (NX)          PHASE FLOW      *
C      *      41      AWT      (NX)          *
C      *      42      AWB      (NX)          COEFFICIENTS      *
C      *      43      AGT      (NX)          *
C      *      44      AGB      (NX)          TOP / BOTTOM      *
C      *      45      ROK      (NX*MYZR)      SATN. DEP. FUNCTION VALUES      *
C      *      46      PVT      (NX*MYZP)      OIL AND GAS PVT FUNCTION VALUES      *
C      *      47      WTR      (NX*MYZW)      WATER PVT FUNCTION VALUES      *
C      *      48      PDPE      (NX)          DELPOT - EAST      *
C      *      48      PDPS      (NX)          DELPOT - SOUTH ( NON-POLYMER )      *
C      *      48      PDPT      (NX)          DELPOT - TOP ( NON-POLYMER )      *
C      *          **** FOR POLYMER OPTION ONLY ****      *
C      *      49      PDPS      (NX)          DELPOT - SOUTH      *
C      *      50      PDPT      (NX)          DELPOT - TOP      *
C      *      51      GPCPS      (NX*NZP)      GRAV-PC FLOW FOR POLYMER - SOUTH      *
C      *      52      GPCPT      (NX*NYP)      GRAV-PC FLOW FOR POLYMER - TOP      *
C      *      53      SAPS      (NX*NZP)      SYMM. POLYMER FLOW COEF. - SOUTH      *
C      *      54      SAPT      (NX*NYP)      SYMM. POLYMER FLOW COEF. - TOP      *
C      *
C      * NOTE THAT THE -I***- INDEX VARIABLES, ONCE SET, ARE NOT      *
C      * MODIFIED. THE DIMENSIONS SHOWN ARE FOR A 3-D GRID, AND FOR THE      *
C      * INCLUSION OF A GAS PHASE. THIS WAS DONE TO EASE THE CONVERSION*
C      * OF IDPM FROM OIL WATER TO FULL THREE PHASE. IF NZ IS 1      *
C      * OR IF THE -LAYER- OPTION IS ACTIVE, THE DIMENSIONS OF ALL      *
C      * VARIABLES WHOSE NAME ENDS WITH -T- OR -B- ARE REDUCED TO 0.      *
C      *
C      *          VALUES TAKEN ON BY PARAMETERS (ABOVE) FOR SIZING      *
C      *          THE PASSAROUND ARRAYS...      *
C      *          PARAMETER      NY .GE. NZ      NY .LT. NZ      *
C      *          NYP      1      NY      *
C      *          NZP      NZ      1      *
C      *          MYZR      7*(NZ+1)      7*(NY+1)      *
C      *          MYZP      11*(NZ+1)      11*(NY+1)      *
C      *          MYZW      6*(NZ+1)      6*(NY+1)      *
C      *          *****
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'COEF.INC'

```

DIMENSION B(100)
EQUIVALENCE (A(1), B(1))

* INITIALIZE. *

KSCPTR = ISCZER
ISCPTR = ISCZER

LAYER = NXNYNZ
LAYER2 = NXNYNZ
JS = 0
KT = 0
IPARF = 0
IPARC = 1
INCROK = 7 * NX
INCPVT = 11 * NX
INCWTR = 6 * NX

ASSUME 2-D, SCAN BY ROWS.

KASE = 1
K = NZ
J = 0
NPAROZ = 1
KPAROZ = 0
JPAROZ = 1
KFLO = 0
IPARS = 0
IPART = 0
JFINC = 1
KFINC = 0
LFINC = NX

IF (NZ .LE. 1)

GO TO 1800

IF (NY .LT. NZ)

GO TO 1500

FULL 3-D GRID, SCAN BY X-Z PLANES.

KASE = 2
J = 0
NPAROZ = NZ
KPAROZ = 1
JPAROZ = NPAROZ
KFLO = 1
IPART = 2
JFINC = 1
KFINC = 0
LFINC = NX

GO TO 1800

1500

CONTINUE

3-D GRID, SCAN BY X-Z PLANES

JSTRT = 0
KASE = 3
K = NZ + 1
NPAROZ = NY
KPAROZ = NY
KFLO = 1
J = 1
IPARS = 2

	JF INC	= 0	
	KF INC	= -1	
	LF INC	= -NXNY	
	JSTRT	= 1	
C			
1800	JPLANE	= NX * JPAROZ	
	KPLANE	= NX * KPAROZ	
	NXKFLO	= NX * KFLO	
C			
	IP	= 1	
	ISATO	= IP + LAYER2	
	ISATW	= ISATO + LAYER	
	IPORV	= ISATW + LAYER	
	ITRX	= LASTIN	
	IAW	= ITRX	
	ITRY	= ITRX + LAYER	
	IAE	= ITRY	
	ITRZ	= ITRY + LAYER	
	IAB	= ITRZ	
	IZAVG	= ITRZ + LAYER	
	IF (KPAROZ .EQ. 0)	IZAVG = ITRZ	
	IAN	= IZAVG	
	IAS	= IZAVG + LAYER	
	IAC	= IAS + LAYER	
	IAT	= IAC + LAYER	
	IRHS	= IAT + LAYER	
	IF (KPAROZ .EQ. 0)	IRHS = IAT	
	ILAST	= IRHS	
2000	ISAOS	= ILAST + LAYER	
	ISAWS	= ISAOS + JPLANE	
	ISAGS	= ISAWS + JPLANE	
	IWAGS	= ISAGS + JPLANE	
	ISAOE	= IWAGS + NX	
	ISAW	= ISAOE + NX	
	ISAGE	= ISAW + NX	
	IWAGE	= ISAGE + NX	
	ISAOT	= IWAGE + NX	
	ISAWT	= ISAOT + KPLANE	
	ISAGT	= ISAWT + KPLANE	
	IWAGT	= ISAGT + KPLANE	
	IGPCOS	= IWAGT + NXKFLO	
	IGPCWS	= IGPCOS + JPLANE	
	IGPCGS	= IGPCWS + JPLANE	
	IGPCOE	= IGPCGS + JPLANE	
	IGPCWE	= IGPCOE	
	IGPCGE	= IGPCWE	
	IGPCOT	= IGPCGE + NX	
	IGPCWT	= IGPCOT + KPLANE	
	IGPCGT	= IGPCWT + KPLANE	
	IRSOCS	= IGPCGT + KPLANE	
	IRSWCS	= IRSOCS + JPLANE	
	IRSOCE	= IRSWCS + JPLANE	
	IRSWCE	= IRSOCE	
	IRSOCT	= IRSWCE + NX	
	IRSWCT	= IRSOCT + KPLANE	
	IDELT	= IRSWCT + KPLANE	
	IAOT	= IDELT + NXKFLO	
	IAOB	= IAOT + NXKFLO	
	IAWT	= IAOB + NXKFLO	
	IAWB	= IAWT + NXKFLO	

```

      IAGT      = IAWB + NXKFLO
      IAGB      = IAGT + NXKFLO
      IROK      = IAGB + NXKFLO
      IPVT      = IROK + INCROK * ( 1 + NPAROZ )
      IWTR      = IPVT + INCPVT * ( 1 + NPAROZ )
      IPDPE      = IWTR + INCWTR * ( 1 + NPAROZ )
      IPDPS      = IPDPE
      IPDPT      = IPDPS
      ILAST      = IPDPT + NX
C
2500      IROKT      = IROK
      IPVTT      = IPVT
      IWTRT      = IWTR
      IF ( NCORE .EQ. -1 )              GO TO 2800
      IEXCES(4)  = NCORE - ILAST
      GO TO 9900
2800      CONTINUE
3000      EMPTYX = 0.0
      DO 3200 IA = IROK, IPDPS
        A(IA)    = EMPTYX
3200      CONTINUE
C
C
C
C *****
C *      TOP OF MAIN LOOP.      *
C *****
C
4000      IJK0      = ( J - 1 ) * NX + ( K - 1 ) * NXNY
      L            = IJK0
      LS          = L + NX
      LN          = L - NX
      IF ( LN .LT. 0 )          LN          = 0
      LB          = L + NXNY
      LT          = L - NXNY
      IF ( LT .LT. 0 )          LT          = 0
      JF          = J + JFINC
      KF          = K + KFINC
      LF          = L + LFINC
C
C      NOTE THAT THE INDICES (BELOW) FOR THE PA (PASSAROUND)
C      ARRAYS CAUSE THEM TO FUNCTION LIKE CYLINDRICAL FILES
C      OF GRID ROZ (ROWS).
C
      JS          = JS + NX
      IF ( JS .GE. JPLANE )      JS          = 0
      IPARC        = IPARC + 1
      IF ( IPARC .GT. NPAROZ )   IPARC        = 0
      IPARS        = IPARS + 1
      IF ( IPARS .GT. NPAROZ )   IPARS        = 0
      IPARF        = IPARF + 1
      IF ( IPARF .GT. NPAROZ )   IPARF        = 0
      IROKC        = IROK + IPARC * INCROK
      IROKS        = IROK + IPARS * INCROK
      IROKF        = IROK + IPARF * INCROK
      IPVTC        = IPVT + IPARC * INCPVT
      IPVTS        = IPVT + IPARS * INCPVT
      IPVTF        = IPVT + IPARF * INCPVT
      IWTRC        = IWTR + IPARC * INCWTR
      IWTRS        = IWTR + IPARS * INCWTR

```

```

      IWTRF      = IWTR + IPARF * INCWTR
      IF ( KPAROZ .EQ. 0 )      GO TO 5000
      KT         = KT + NX
      IF ( KT .GE. KPLANE )      KT         = 0
      IPART      = IPART + 1
      IF ( IPART .GT. NPAROZ )    IPART      = 0
      IROKT      = IROK + IPART * INCROK
      IPVTT      = IPVT + IPART * INCPVT
      IWTRT      = IWTR + IPART * INCWTR

C
5000  IF ( KF .LT. 1 .OR. JF .GT. NY )      GO TO 6000
C
      CALL EMPFUN (  JF,      KF,      NX,
*                  B(IP+LF),  A(IPORV+LF),
*                  A(ISATO+LF), A(ISATW+LF),
*                  A(IPVTF),  A(IROKF) )
C
      CALL WTRFUN (  JF,      KF,      NX,
*                  B(IP+LF),  A(IPORV+LF),
*                  A(IPVTF),  A(IWTRF),  A(IROKF) )
C
      IF ( K .GT. NZ .OR. J .LT. 1 )      GO TO 7500
C
6000  CONTINUE
      CALL INICOF (  NX,      B(IP+L),
*                  A(IPORV+L), A(IPORV+LS), A(IPORV+LT),
*                  A(IZAVG+L), A(IZAVG+LS), A(IZAVG+LT),
*                  A(ISATO+L), A(ISATW+L),
*                  A(ITRX+L),  A(ITRY+L),  A(ITRZ+L),
*                  A(IAGB),   A(IAGT),   A(IDELT),
*                  A(IAC+L),  A(IRHS+L),
*                  A(IAE+L),  A(IAS+L),  A(IAT+L),
*                  A(IAW+L),  A(IAN+L),  A(IAB+L),
*                  A(ISAOS+JS), A(IGPCOS+JS),
*                  A(ISAWS+JS), A(IGPCWS+JS),
*                  A(ISAGS+JS), A(IGPCGS+JS),
*                  A(ISAOT+KT), A(IGPCOT+KT),
*                  A(ISAWT+KT), A(IGPCWT+KT),
*                  A(ISAGT+KT), A(IGPCGT+KT) )
C
      IF ( IFINAL .EQ. 0 )      GO TO 6500
C
      CALL OILCOF (  NX,
*                  B(IP+L),  B(IP+LS),  B(IP+LT),
*                  A(IPVTC), A(IPVTS),  A(IPVTT),
*                  A(IROKC), A(IROKS),  A(IROKT),
*                  A(ITRZ+L), A(IDELT),
*                  A(IRSOCE), A(IRSOCS+JS), A(IRSOCT+KT),
*                  A(IAOB),  A(IAOT),
*                  A(IAGB),  A(IAGT),
*                  A(IGPCOE), A(IGPCOS+JS), A(IGPCOT+KT),
*                  A(IWAGE),  A(IWAGS),  A(IWAGT),
*                  A(ISAOE),  A(ISAOS+JS), A(ISAOT+KT) )
C
      CALL WTRCOF (  NX,
*                  B(IP+L),  B(IP+LS),  B(IP+LT),
*                  A(IPVTC),
*                  A(IROKC), A(IROKS),  A(IROKT),
*                  A(IWTRC), A(IWTRS),  A(IWTRT),
*                  A(ITRZ+L), A(IDELT),

```

```

*          A (IRSWCE),      A (IRSWCS+JS),  A (IRSWCT+KT),
*          A (IPDPE),      A (IPDPS),      A (IPDPT),
*          A (IAWB),       A (IAWT),
*          A (IAGB),       A (IAGT),
*          A (IGPCWE),     A (IGPCWS+JS),  A (IGPCWT+KT),
*          A (IWAGE),      A (IWAGS),      A (IWAGT),
*          A (ISAWC),      A (ISAWS+JS),  A (ISAWT+KT) )

```

C

6500 CONTINUE

```

      CALL FINCOF ( NX,      B (IP+L),      A (IPORV+L),
*                   A (IROKC),  A (IPVTC),      A (IWTRC),
*                   B (IP+LN),      B (IP+LB),
*                   B (IP+LS),      B (IP+LT),
*                   A (IAOB),      A (IAWB),      A (IAGB),
*                   A (IAOT),      A (IAWT),      A (IAGT),
*                   A (ISAOE),     A (ISAOS+JS),  A (ISAOT+KT),
*                   A (ISAWC),     A (ISAWS+JS),  A (ISAWT+KT),
*                   A (ISAGE),     A (ISAGS+JS),  A (ISAGT+KT),
*                   A (IWAGE),     A (IWAGS),      A (IWAGT),
*                   A (IAC+L),     A (IRHS+L),
*                   A (IAW+L),     A (IAN+L),      A (IAB+L),
*                   A (IAE+L),     A (IAS+L),      A (IAT+L) )

```

C

7000 CONTINUE

```

7500      IF ( KASE - 2 )      8100,      8200,      8300

```

C

```

8100      J      = J + 1
          IF ( J .LE. NY )      GO TO 8500
          GO TO 8600

```

C

```

8200      K      = K - 1
          IF ( K .GT. 0 )      GO TO 8500
          K      = NZ
          J      = J + 1
          IF ( J .LE. NY )      GO TO 8500
          GO TO 8600

```

C

```

8300      J      = J + 1
          IF ( J .LE. NY )      GO TO 8500
          J      = JSTRT
          K      = K - 1
          IF ( K .GT. 0 )      GO TO 8500
          GO TO 8600

```

C

8500 GO TO 4000

C

C *****

C * END OF MAIN LOOP. *

C *****

C

8600 CONTINUE

C

9900 CONTINUE

RETURN

END

SUBROUTINE EMPFUN (J1, K1, NI, P, PV, SATO, SATW, PVT, ROK)

C

I *I* *I* *I* *I* *I* *I* *O* *O*

DIMENSION P (NI), PV (NI), SATO (NI), SATW (NI),

* PVT (NI, 11), ROK (NI, 7)

C

```

C *****
C * A SUBROUTINE TO OBTAIN EMPIRICAL FUNCTION VALUES ( EXCEPT *
C * FOR WATER PVT) FOR ALL ACTIVE CELLS IN THE (J,K)TH GRID *
C * ROW. ON THE FIRST TIMESTEP OF A RUN, THESE ARE GOTTEN *
C * BY CALLS ON -NORMAL- SUBROUTINES. THEREAFTER, THE VALUES *
C * ARE GOTTEN FROM A SERIAL FILE, WRITTEN DURING THE PREVIOUS *
C * TIMESTEP BY SUBROUTINE -SATS-. *
C *****
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'SIMUL.INC'
C INCLUDE 'COEF.INC'
C INCLUDE 'STREAM.INC'
C
C DIMENSION NPVT(NXMAX), DG(NXMAX), BGLOG(NXMAX)
C
C EQUIVALENCE ( NPVT(1), AOC(1) ), ( DG(1), AWC(1) ),
C * ( BGLOG(1), AGC(1) )
C
C DATA IBO, IRSO, IGO, IVO, ICO /
C * 1, 2, 3, 4, 5 //
C * ICRSO, IBG, IGG, IVG, ICG /
C * 6, 7, 8, 9, 10 //
C * IBGLOG /
C * 11 /
C DATA IKRO, IKRW, IKRG, IPCOW, IPCOG /
C * 1, 2, 3, 4, 5 //
C * ISRG, ITMOB /
C * 6, 7 /
C
C HLFGRD = 1.0 / 288.0
C KZ = K
C IJK0 = ( K - 1 ) * NXNY + ( J - 1 ) * NX
C
C 1000 ISTART = 0
C IFINIS = 0
C DO 1200 I = 1, NX
C
C MAKE SURE THAT ALL CELLS HAD CORRECT SET UP IN OVER2
C
C IF ( PV(I) .EQ. 0 ) GO TO 1200
C IF ( ISTART .EQ. 0 ) ISTART = I
C IFINIS = I
C IJK = IJK0 + I
C NPVT(I) = 1
C PIJK = P(I)
C
C DEFAULT DUMMY VALUES FOR GAS PROPERTIES-- IN FUTURE VERSION
C GAS PORPRTIES WOULD BE CALCULATED HERE
C
C DG(I) = 0.08
C PVT(I, IBG) = 1.0
C PVT(I, IVG) = 1.0
C BGLOG(I) = PVT(I, IBG)
C PVT(I, IGG) = DG(I) * HLFGRD / PVT(I, IBG)
C PVT(I, ICG) = 0.001
C

```

```

1200 CONTINUE
C
DO 2000 I = ISTART, IFINIS
  IF ( PV(I) .EQ. 0 ) GO TO 2000
  IJK = IJK0 + I
  PIJK = P(I)
  NREG = NPVT(I)
  CALL PROIL ( I, J, PIJK, BO, RSO, DENSO, VISO, 4, NREG )
  DENSO = ( DENSO + RSO * DG(I) )
C
1700 CO = CMPOIL
  CRSO = 0.0
C
C STORE AWAY THE OIL PVT DATA INTO ARRAY PVT FOR USE IN GENERATING
C FLOW COEFFICIENTS
C
1800 PVT(I, IBO) = BO
  PVT(I, IRSO) = RSO
  PVT(I, IVO) = VISO
  PVT(I, IGO) = DENSO * HLFGRD
  PVT(I, ICO) = CO
  PVT(I, ICRSO) = CRSO
  PVT(I, IBGLOG) = BGLOG(I)
C
C
2000 CONTINUE
C
C LOOK UP THE OIL AND WATER RELATIVE PERMS
C
6000 CONTINUE
DO 7000 I = ISTART, IFINIS
  IF ( PV(I) .EQ. 0 ) GO TO 7000
  CALL SATDEP ( I, J, ROK(I, IKRO), ROK(I, IKRW),
  * ROK(I, IKRG), ROK(I, IPCOW), ROK(I, IPCOG),
  * SATO(I), SATW(I) )
C
C ROK = 1 MEANS DO NOT USE HARMONIC AVERAGE IN MOBILITY
C CALCULATIONS BUT JUST SIMPLE UPSTREAM WEIGHTING.
C
  ROK(I, ITMOB) = 1.0
  ROK(I, ISRG) = 0
7000 CONTINUE
C
9900 RETURN
END
SUBROUTINE WTRFUN ( J1, K1, NI, P, PV, PVT, WTR, ROK )
  *I* *I* *I* *I* *I* *I* *O* *IO*
C
C *****
C * A SUBROUTINE TO PROVIDE WATER PVT FUNCTION VALUES FOR *
C * ALL ACTIVE GRID CELLS IN THE (J,K)TH ROW, FOR WHICH *
C * APPROPRIATE SUBARRAYS HAVE BEEN PASSED. *
C *****
C
  INCLUDE 'PARAM.INC'
  INCLUDE 'SIMUL.INC'
  INCLUDE 'COEF.INC'
  INCLUDE 'STREAM.INC'
C
  DIMENSION ROK(NI, 7)

```

```

      DIMENSION      P (NI),      PV (NI),      PVT (NI, 11),      WTR (NI, 6)
C
C
      DATA      IKRO,      IKRW,      IKRG,      IPCOW,      IPCOG      /
*      1,      2,      3,      4,      5      /,
*      ISRG,      ITMOB      /
*      6,      7      /
C
      DATA      IBW,      IRSW,      IGW,      IVW,      ICW      /
*      1,      2,      3,      4,      5      /,
*      ICRSW      /
*      6      /
      DATA      IBG,      IGG,      IVG,      IVO      /
*      7,      8,      9,      4      /
C
      HLFGRD      = 1.0 / 288.0
      KZ      = K
      IJK0      = ( K - 1 ) * NXNY + ( J - 1 ) * NX
C
      IF ( IFINIS .EQ. 0 )      GO TO 9900
      IF ( SWAT .NE. 0 )      GO TO 3000
C
C
3000      CONTINUE
C
      WATER PVT VALUES CALCULATED HERE AND PUT INTO WTR ARRAY
C
      DO 4000 I = ISTART, IFINIS
      IF ( PV(I) .EQ. 0 )      GO TO 4000
      PIJK      = P(I)
      DENW      = DENWTR * ( 1.0 - CMPWTR * ( REFPRE - PIJK ) )
      WTR(I, IBW)      = DENWST / DENW
      WTR(I, IGW)      = DENW * HLFGRD
4000 CONTINUE
C
      DO 5000 I = ISTART, IFINIS
      WTR(I, IRSW)      = 0
      WTR(I, IVW)      = VISWTR
      WTR(I, ICW)      = CMPWTR
      WTR(I, ICRSW)      = 0
5000 CONTINUE
C
      GO TO 9900
C
9900 RETURN
      END
      SUBROUTINE INICOF (      NI,      P,
C      *I*
*      PORV,      PORVS,      PORVT,
C      *I*      *I*      *I*
*      ZAVG,      ZAVGS,      ZAVGT,
C      *I*      *I*      *I*
*      SATO,      SATW,
C      *I*      *I*
*      TRX,      TRY,      TRZ,
C      *I*      *I*      *I*
*      AGB,      AGT,      DELT,
C      *O*      *O*      *O*
*      AC,      RHS,
C      *O*      *O*

```

```

C      *      AE,      AS,      AT,
      *      *O*      *O*      *O*
C      *      AW,      AN,      AB,
      *      *O*      *O*      *O*
C      *      SAOS,      GPCOS,
      *      *O*      *O*
C      *      SAWS,      GPCWS,
      *      *O*      *O*
C      *      SAGS,      GPCGS,
      *      *O*      *O*
C      *      SAOT,      GPCOT,
      *      *O*      *O*
C      *      SAWT,      GPCWT,
      *      *O*      *O*
C      *      SAGT,      GPCGT      )
C      *      *O*      *O*
C
C
C
C
C      *****
C      *      I N I C O F      *
C      *****
C      *      INITIALIZATION FOR COEF. GENER. FOR ONE GRID ROW.      *
C      *****
C
C      DIMENSION
C      *      PORV (NI) ,      P (NI) ,
C      *      ZAVG (NI) ,      PORVS (NI) ,      PORVT (NI) ,
C      *      SATO (NI) ,      ZAVGS (NI) ,      ZAVGT (NI) ,
C      *      TRX (NI) ,      SATW (NI) ,
C      *      TRZ (NI) ,
C      *      AGB (NI) ,      AGT (NI) ,      DELT (NI) ,
C      *      AC (NI) ,      RHS (NI) ,
C      *      AE (NI) ,      AS (NI) ,      AT (NI) ,
C      *      AW (NI) ,      AN (NI) ,      AB (NI) ,
C      *      SAOS (NI) ,      GPCOS (NI) ,
C      *      SAWS (NI) ,      GPCWS (NI) ,
C      *      SAGS (NI) ,      GPCGS (NI) ,
C      *      SAOT (NI) ,      GPCOT (NI) ,
C      *      SAWT (NI) ,      GPCWT (NI) ,
C      *      SAGT (NI) ,      GPCGT (NI)
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'SIMUL.INC'
C      INCLUDE 'COEF.INC'
C      INCLUDE 'STREAM.INC'
C
C      DIMENSION      INX1 (2) ,      INXL (2) ,
C      *      PV (NXMAX) ,      JBLOK (NXMAX)
C
C      EQUIVALENCE      ( PV (1) , AOS (1) ) ,      ( JBLOK (1) , AWE (1) )
C      *****
C      *      INITIALIZE.      *
C      *****
C
C      IJKO      = ( K - 1 ) * NXNY + ( J - 1 ) * NX
C
C      *****
C      *      MEASURE TRUE ROW SIZE AND ZERO -OUTSIDE- COEFFICIENTS.      *
C      *****
C

```



```

IFIRST      = 0
IFINAL      = 0
DO 2000 I = 1, NX
PV(I)       = PORV(I)
RPVODT(I)   = 0
IF ( PV(I) .EQ. 0 ) GO TO 2000
IFINAL      = I
IF ( IFIRST .EQ. 0 ) IFIRST = I
2000 CONTINUE
C
IF ( IFINAL .EQ. 0 ) GO TO 9000
C
IF ( IFIRST .EQ. 1 .AND. IFINAL .EQ. NX)GO TO 3600
C
INX1(1)     = 1
INXL(1)     = IFIRST - 1
INX1(2)     = IFINAL + 1
INXL(2)     = NX
C
DO 3500 IG = 1, 2
I1          = INX1(IG)
IL          = INXL(IG)
IF ( I1 .GT. IL ) GO TO 3500
C
C
DO 3000 I = I1, IL
RHS(I)      = 0
AC(I)       = 0
AE(I)       = 0
AW(I)       = 0
AS(I)       = 0
AN(I)       = 0
3000 CONTINUE
C
DO 3100 I = I1, IL
GPCOS(I)    = 0
GPCWS(I)    = 0
SAOS(I)     = 0
SAWS(I)     = 0
3100 CONTINUE
C
IF ( NZ .EQ. 1 ) GO TO 3500
C
DO 3400 I = I1, IL
AT(I)       = 0
AB(I)       = 0
SAOT(I)     = 0
SAWT(I)     = 0
GPCOT(I)    = 0
GPCWT(I)    = 0
3400 CONTINUE
C
3500 CONTINUE
C
3600 CONTINUE
C
*****
* OBTAIN CLEAN SATURATION, PORE VOLUME AND TRANSMISSIBILITY *
* VALUES. *
*****

```

```

C
DO 4000 I = IFIRST, IFINAL
  PV(I)      = ( PORV(I) )
  SO(I)      = ( SATO(I) )
  SW(I)      = ( SATW(I) )
4000 CONTINUE
C
DO 4100 I = IFIRST, IFINAL
  XTRAN(I)   = ( TRX(I) )
  YTRAN(I)   = ( TRY(I) )
4100 CONTINUE
C
C *****
C *   START THE VECTOR OF KNOWN TERMS FOR THE PRESSURE AND FLOW *
C *   EQUATIONS. *
C *****
4700 DO 4800 I = IFIRST, IFINAL
  RPVODT(I)  = PV(I) * ( 1.0 - CROCK * ( REFPRE - P(I) ) )
  *          / DELTAT
  RHS(I)     = -RPVODT(I) * ( 1.0 - CROCK * P(I) )
  AC(I)      = RPVODT(I) * CROCK
4800 CONTINUE
C
C *****
C *   GENERATE ELEVATION DIFFERENCES FOR EAST (CELL TO RIGHT), TOP.*
C *   MAKE SURE TRANS = 0 TO AND FROM ZERO-VOLUME GRID CELLS. *
C *****
C
4900 DO 5200 I = IFIRST, IFINAL
  TRE        = XTRAN(I)
  XTRAN(I)   = 0
  DELS(I)    = 0
  TRS        = YTRAN(I)
  YTRAN(I)   = 0
  DELE(I)    = 0
  IF ( PV(I) .EQ. 0 )                GO TO 5200
  IF ( I .EQ. IFINAL )              GO TO 5000
  IF ( PV(I+1) .EQ. 0 )              GO TO 5000
  XTRAN(I)   = TRE
  DELE(I)    = ZAVG(I+1) - ZAVG(I)
5000 IF ( J .EQ. NY )                GO TO 5200
  IF ( PORVS(I) .EQ. 0 )            GO TO 5200
  YTRAN(I)   = TRS
  DELS(I)    = ZAVGS(I) - ZAVG(I)
5200 CONTINUE
C
  IF ( NZ .EQ. 1 )                  GO TO 5600
C
DO 5500 I = IFIRST, IFINAL
  TRT        = TRZ(I)
  TRZ(I)     = 0
  DELT(I)    = 0
  IF ( PV(I) .EQ. 0 )                GO TO 5500
  IF ( K .EQ. 1 )                  GO TO 5500
  IF ( PORVT(I) .EQ. 0 )            GO TO 5500
  TRZ(I)     = TRT
  DELT(I)    = ZAVGT(I) - ZAVG(I)
5500 CONTINUE
C
5600 CONTINUE

```

```

C
      GO TO 9900
C
C *****
C *      ZERO COEF. FOR WHOLLY EMPTY ROW. IN CURRENT VERSION NO EMPTY*
C *      ROWS EXIST*
C *****
C
      9000 DO 9200 I = 1, NX
            RHS(I)      = 0
            AC(I)       = 0
            AN(I)       = 0
            AS(I)       = 0
            AE(I)       = 0
            AW(I)       = 0
            GPCOS(I)    = 0
            GPCWS(I)    = 0
            SAOS(I)     = 0
            SAWS(I)     = 0
      9200 CONTINUE
C
      IF ( NZ .EQ. 1 )              GO TO 9900
C
      DO 9400 I = 1, NX
            AB(I)      = 0
            AT(I)      = 0
            SAOT(I)    = 0
            SAWT(I)    = 0
            GPCOT(I)   = 0
            GPCWT(I)   = 0
      9400 CONTINUE
C
      9900 RETURN
      END
      SUBROUTINE OILCOF (      NI,
C                               *I*
C *                               P,          PS,          PT,
C                               *I*          *I*          *I*
C *                               PVT,        PVTS,        PVTT,
C                               *I*          *I*          *I*
C *                               ROK,        ROKS,        ROKT,
C                               *I*          *I*          *I*
C *                               TRZ,        DELT,
C                               *I*          *I*
C *                               RSOCE,      RSOCs,        RSOCT,
C                               *S*          *IO*          *IO*
C *                               AOB,        AOT,
C                               *O*          *O*
C *                               AGB,        AGT,
C                               *O*          *O*
C *                               GPCOE,      GPCOS,        GPCOT,
C                               *S*          *IO*          *IO*
C *                               WAGE,      WAGS,        WAGT,
C                               *IO*          *IO*          *IO*
C *                               SAOE,      SAOS,        SAOT )
C                               *O*          *IO*          *IO*
C
C *****
C *                               O I L C O F*

```

```

C *****
C * GENERATE FLOW COEF. FOR OIL PHASE FOR ONE GRID ROW. *
C *****
C
C DIMENSION          P (NI),          PS (NI),          PT (NI),
*                   PVT (NI, 11),      PVTS (NI, 11),      PVTT (NI, 11),
*                   ROK (NI, 7),        ROKS (NI, 7),        ROKT (NI, 7),
*                   TRZ (NI),           DELT (NI),
*                   RSOCE (NI),          RSOCs (NI),          RSOCT (NI),
*                   AOB (NI),           AOT (NI),
*                   AGB (NI),           AGT (NI),
*                   GPCOE (NI),          GPCOS (NI),          GPCOT (NI),
*                   WAGE (NI),           WAGS (NI),          WAGT (NI),
*                   SAOE (NI),           SAOS (NI),          SAOT (NI)
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'SIMUL.INC'
C INCLUDE 'COEF.INC'
C INCLUDE 'STREAM.INC'
C DIMENSION          OVODT (NXMAX),      DPOT (NXMAX),          JBLOK (NXMAX),
*                   RKOCE (NXMAX),      RKOCs (NXMAX),          RKOCT (NXMAX)
C
C EQUIVALENCE          ( OVODT (1), AWN (1) ),          ( JBLOK (1), AWE (1) ),
*                   ( DPOT (1), AWS (1) ),          ( RKOCE (1), AWN (1) ),
*                   ( RKOCs (1), AWN (1) ),          ( RKOCT (1), AWN (1) )
C
C DATA          IBO,          IRSO,          IGO,          IVO,          ICO          /
*                   1,          2,          3,          4,          5          /,
*                   ICRSO,          IBG,          IGG,          IVG,          ICG          /
*                   6,          7,          8,          9,          10          /,
*                   IBGLOG          /
*                   11          /
C DATA          IKRO,          IKRW,          IKRG,          IPCOW,          IPCOG          /
*                   1,          2,          3,          4,          5          /,
*                   ISRG,          ITMOB          /
*                   6,          7          /
C DATA          IBW,          IRSW,          IGW,          IVW,          ICW          /
*                   1,          2,          3,          4,          5          /,
*                   ICRSW          /
*                   6          /
C
C *****
C * STATEMENT FUNCTIONS. *
C *****
C
C MOBILITY BETWEEN CELL AND CEEL TO RIGHT OR ABOVE
C
C USKREL ( RK1, RKA, ALFA, TMOB, TMOBA ) = 2.0 *
*                   ( RK1* TMOBA * ALFA + RKA * TMOB * ( 1.0 - ALFA ) ) /
*                   ( TMOB + TMOBA )
C
C SYMMETRIC FLOW COEFFICIENT TERM BETWEEN TWO CELLS
C
C SYMCO ( TR4, BC, BA, USKR, VC, VA ) =
*                   TR4 * USKR / ( ( BC + BA ) * ( VC + VA ) )
C
C IF ( IFINAL .EQ. 0 ) GO TO 9900
C

```

```

C *****
C *   CENTRAL POINT.   *
C *****
C
C      DO 2200 I = IFIRST, IFINAL
C          OVODT(I)      = RPVODT(I) * SO(I)
C          AOC(I)        = OVODT(I) * PVT(I,ICO)
C          OVODT(I)      = OVODT(I) / PVT(I,IBO)
C 2200 CONTINUE
C
C      DO 2300 I = IFIRST, IFINAL
C          OILRHS(I)      = OVODT(I)
C 2300 CONTINUE
C
C *****
C *   NORTH / SOUTH (OIL)   *
C *****
C
C 2700      IF ( J .GT. 1 )                      GO TO 2900
C      DO 2800 I = IFIRST, IFINAL
C          AON(I)          = 0
C 2800 CONTINUE
C
C          GO TO 3400
C
C 2900 DO 3000 I = IFIRST, IFINAL
C          AON(I)          = PVT(I,IBO) * SAOS(I)
C 3000 CONTINUE
C
C      DO 3200 I = IFIRST, IFINAL
C          OILRHS(I)      = OILRHS(I) + ( - GPCOS(I) )
C 3200 CONTINUE
C
C 3400      IF ( J .LT. NY )                      GO TO 3800
C
C      DO 3600 I = IFIRST, IFINAL
C          AOS(I)          = 0
C          SAOS(I)         = 0
C          GPCOS(I)        = 0
C 3600 CONTINUE
C
C          GO TO 4400
C
C 3800 DO 3900 I = IFIRST, IFINAL
C          GPCOS(I)        = DELS(I) * ( PVT(I,IGO) + PVTS(I,IGO) )
C          DPOT(I)         = PS(I) - P(I) + GPCOS(I)
C 3900 CONTINUE
C
C      DO 4000 I = IFIRST, IFINAL
C          RKOCS(I)        = 1.0
C          RSOCS(I)        = PVT(I,IRSO)
C          IF ( DPOT(I) .LE. 0 )                      GO TO 4000
C          RKOCS(I)        = 0.0
C          RSOCS(I)        = PVTS(I,IRSO)
C 4000 CONTINUE
C
C      DO 4050 I = IFIRST, IFINAL
C          RKOCS(I)        = USKREL ( ROK(I,IKRO), ROKS(I,IKRO),
C          *                  RKOCS(I), ROK(I,ITMOB), ROKS(I,ITMOB) )
C 4050 CONTINUE

```

```

C
DO 4100 I = IFIRST, IFINAL
  SAOS(I) = SYMCO ( YTRAN(I), PVT(I, IBO), PVTS(I, IBO),
*                RKOCS(I), PVT(I, IVO), PVTS(I, IVO) )
4100 CONTINUE
C
DO 4200 I = IFIRST, IFINAL
  GPCOS(I) = GPCOS(I) * SAOS(I)
  AOS(I) = PVT(I, IBO) * SAOS(I)
4200 CONTINUE
C
DO 4300 I = IFIRST, IFINAL
  OILRHS(I) = OILRHS(I) + GPCOS(I)
4300 CONTINUE
C
*****
C
*   EAST / WEST   (OIL)   *
C
*****
C
4400   AOE(IFINAL) = 0
      GPCOE(IFINAL) = 0
      SAOE(IFINAL) = 0
      RSOCE(IFINAL) = 0
      ILAST = IFINAL - 1
      IF ( IFIRST .GT. ILAST ) GO TO 4950
C
DO 4600 I = IFIRST, ILAST
  GPCOE(I) = DELE(I) * ( PVT(I, IGO) + PVT(I+1, IGO) )
  DPOT(I) = P(I+1) - P(I) + GPCOE(I)
4600 CONTINUE
C
DO 4650 I = IFIRST, ILAST
  RKOCE(I) = 1.0
  RSOCE(I) = PVT(I, IRSO)
  IF ( DPOT(I) .LE. 0 ) GO TO 4650
  RKOCE(I) = 0.0
  RSOCE(I) = PVT(I+1, IRSO)
4650 CONTINUE
C
DO 4680 I = IFIRST, ILAST
  RKOCE(I) = USKREL ( ROK(I, IKRO), ROK(I+1, IKRO),
*                RKOCE(I), ROK(I, ITMOB), ROK(I+1, ITMOB) )
4680 CONTINUE
C
DO 4700 I = IFIRST, ILAST
  SAOE(I) = SYMCO ( XTRAN(I), PVT(I, IBO), PVT(I+1, IBO),
*                RKOCE(I), PVT(I, IVO), PVT(I+1, IVO) )
4700 CONTINUE
C
DO 4800 I = IFIRST, ILAST
  GPCOE(I) = GPCOE(I) * SAOE(I)
  AOE(I) = PVT(I, IBO) * SAOE(I)
4800 CONTINUE
C
DO 4900 I = IFIRST, ILAST
  OILRHS(I) = OILRHS(I) + GPCOE(I)
4900 CONTINUE
C
4950   AOW(IFIRST) = 0
      INEXT = IFIRST + 1

```

```

      IF ( INEXT .GT. IFINAL )                GO TO 5200
C
      DO 5000 I = INEXT, IFINAL
        AOW(I) = PVT(I, IBO) * SAE(I-1)
5000 CONTINUE
C
      DO 5100 I = INEXT, IFINAL
        OILRHS(I) = OILRHS(I) + ( - GPCOE(I-1) )
5100 CONTINUE
C
C *****
C * TOP / BOTTOM (OIL) *
C *****
C
5200      IF ( NZ .EQ. 1 )                      GO TO 7000
C
      IF ( K .LT. NZ )                          GO TO 5500
      DO 5400 I = IFIRST, IFINAL
        AOB(I) = 0
5400 CONTINUE
C
      GO TO 5750
C
5500 DO 5600 I = IFIRST, IFINAL
        AOB(I) = PVT(I, IBO) * SAOT(I)
5600 CONTINUE
C
      DO 5700 I = IFIRST, IFINAL
        OILRHS(I) = OILRHS(I) + ( - GPCOT(I) )
5700 CONTINUE
C
5750      IF ( K .GT. 1 )                      GO TO 5900
C
      DO 5800 I = IFIRST, IFINAL
        AOT(I) = 0
        SAOT(I) = 0
        GPCOT(I) = 0
5800 CONTINUE
      GO TO 7000
C
5900 DO 6000 I = IFIRST, IFINAL
        GPCOT(I) = DELT(I) * ( PVT(I, IGO) + PVTT(I, IGO) )
        DPOT(I) = PT(I) - P(I) + GPCOT(I)
6000 CONTINUE
C
      DO 6100 I = IFIRST, IFINAL
        RKOC(I) = 1.0
        RSOC(I) = PVT(I, IRSO)
        IF ( DPOT(I) .LE. 0 )                  GO TO 6100
        RKOC(I) = 0.0
        RSOC(I) = PVTT(I, IRSO)
6100 CONTINUE
C
      DO 6150 I = IFIRST, IFINAL
        RKOC(I) = USKREL ( ROK(I, IKRO), ROKT(I, IKRO),
*                          RKOC(I), ROK(I, ITMOB), ROKT(I, ITMOB) )
6150 CONTINUE
C
      DO 6200 I = IFIRST, IFINAL
        SAOT(I) = SYMCO ( TRZ(I), PVT(I, IBO), PVTT(I, IBO),

```

```

*
RKOCT(I), PVT(I, IVO), PVTT(I, IVO) )
6200 CONTINUE
C
DO 6300 I = IFIRST, IFINAL
    GPCOT(I) = GPCOT(I) * SAOT(I)
    AOT(I) = PVT(I, IBO) * SAOT(I)
6300 CONTINUE
C
DO 6400 I = IFIRST, IFINAL
    OILRHS(I) = OILRHS(I) + GPCOT(I)
6400 CONTINUE
C
7000 CONTINUE
C
7800 GO TO 9900
C
C
9900 RETURN
END
SUBROUTINE WTRCOF ( NI,
*
* P, PS, PT,
*
* *I* *I* *I*
*
* PVT,
*
* *I*
*
* ROK, ROKS, ROKT,
*
* *I* *I* *I*
*
* WTR, WTRS, WTRT,
*
* *I* *I* *I*
*
* TRZ, DELT,
*
* *I* *I*
*
* RSWCE, RSWCS, RSWCT,
*
* *S* *IO* *IO*
*
* DPOTE, DPOTS, DPOTT,
*
* *O* *O* *O*
*
* AWB, AWT,
*
* *O* *O*
*
* AGB, AGT,
*
* *O* *O*
*
* GPCWE, GPCWS, GPCWT,
*
* *S* *IO* *IO*
*
* WAGE, WAGS, WAGT,
*
* *IO* *IO* *IO*
*
* SAWE, SAWS, SAWT )
*
* *O* *IO* *IO*
C
C
C
C
*****
C
* W T R C O F *
C
*****
C
* GENERATE FLOW COEF. FOR WTR PHASE FOR ONE GRID ROW. *
C
*****
C
C
DIMENSION P(NI), PS(NI), PT(NI),
*
* PVT(NI, 11),
*
* ROK(NI, 7), ROKS(NI, 7), ROKT(NI, 7),
*
* WTR(NI, 6), WTRS(NI, 6), WTRT(NI, 6),
*
* TRZ(NI), DELT(NI),
*
* RSWCE(NI), RSWCS(NI), RSWCT(NI),
*
* DPOTE(NI), DPOTS(NI), DPOTT(NI),

```



```

*          AWB (NI) ,          AWT (NI) ,
*          AGB (NI) ,          AGT (NI) ,
*          GPCWE (NI) ,        GPCWS (NI) ,        GPCWT (NI) ,
*          WAGE (NI) ,        WAGS (NI) ,        WAGT (NI) ,
*          SAWE (NI) ,        SAWS (NI) ,        SAWT (NI)

C
  INCLUDE 'PARAM.INC'
  INCLUDE 'SIMUL.INC'
  INCLUDE 'COEF.INC'
  INCLUDE 'STREAM.INC'
  DIMENSION WVODT (NXMAX) ,      JBLOK (NXMAX) ,
*          RKWCE (NXMAX) ,      RKWCS (NXMAX) ,      RKWCT (NXMAX)

C
  EQUIVALENCE      ( WVODT(1) , SO(1) ) ,      ( JBLOK(1) , AWE(1) ) ,
*          ( RKWCE(1) , SO(1) ) ,      ( RKWCS(1) , SO(1) ) ,
*          ( RKWCT(1) , SO(1) )

C
C
  DATA      IBO,      IRSO,      IGO,      IVO,      ICO      /
*          1,      2,      3,      4,      5      /,
*          ICRSO,      IBG,      IGG,      IVG,      ICG      /
*          6,      7,      8,      9,      10      /,
*          IBGLOG      /
*          11      /
  DATA      IKRO,      IKRW,      IKRG,      IPCOW,      IPCOG      /
*          1,      2,      3,      4,      5      /,
*          ISRG,      ITMOB      /
*          6,      7      /
  DATA      IBW,      IRSW,      IGW,      IVW,      ICW      /
*          1,      2,      3,      4,      5      /,
*          ICRSW      /
*          6      /

C
C
*****
*      STATEMENT FUNCTIONS.      *
*****

C
  MOBILITY TERM

C
  USKREL (RK1, RKA, ALFA, TMOB, TMOBA )      =      2.0 *
*          (RK1 * TMOBA * ALFA + RKA * TMOB * ( 1.0 - ALFA ) )      /
*          ( TMOB + TMOBA )

C
  SYMMETRIC FLOW COEFFICIENT

C
  SYMCO ( TR4, BC, BA, USKR, VC, VA )      =
*          TR4 * USKR / ( ( BC + BA ) * ( VC + VA ) )

C
  IF ( IFINAL .EQ. 0 )      GO TO 9900

C
*****
*      CENTRAL POINT.      *
*****

C
  DO 2200 I = IFIRST, IFINAL
    WVODT(I)      = RPVODT(I) * SW(I)
    AWC(I)      = WVODT(I) * WTR(I, ICW)
    WVODT(I)      = WVODT(I) / WTR(I, IBW)
2200 CONTINUE
C

```

```

DO 2300 I = IFIRST, IFINAL
  WTRRHS(I) = WVODT(I)
2300 CONTINUE
C
C *****
C *   NORTH / SOUTH (WTR)   *
C *****
C
2700   IF ( J .GT. 1 )                GO TO 2900
      DO 2800 I = IFIRST, IFINAL
        AWN(I) = 0
2800 CONTINUE
C
      GO TO 3400
C
2900 DO 3000 I = IFIRST, IFINAL
      AWN(I) = WTR(I,IBW) * SAWS(I)
3000 CONTINUE
C
      DO 3200 I = IFIRST, IFINAL
        WTRRHS(I) = WTRRHS(I) + ( - GPCWS(I) )
3200 CONTINUE
C
3400   IF ( J .LT. NY )                GO TO 3800
C
      DO 3600 I = IFIRST, IFINAL
        AWS(I) = 0
        SAWS(I) = 0
        GPCWS(I) = 0
3600 CONTINUE
C
      GO TO 4400
C
3800 DO 3900 I = IFIRST, IFINAL
      GPCWS(I) = DELS(I) * ( WTR(I,IGW) + WTRS(I,IGW) ) +
*          ROK(I,IPCOW) - ROKS(I,IPCOW)
      DPOTS(I) = PS(I) - P(I) + GPCWS(I)
3900 CONTINUE
C
      DO 4000 I = IFIRST, IFINAL
        RKCWS(I) = 1.0
        RSWCS(I) = WTR(I,IRSW)
        IF ( DPOTS(I) .LE. 0 )                GO TO 4000
        RKCWS(I) = 0.0
        RSWCS(I) = WTRS(I,IRSW)
4000 CONTINUE
C
      DO 4050 I = IFIRST, IFINAL
        RKCWS(I) = USKREL ( ROK(I,IKRW), ROKS(I,IKRW),
*          RKCWS(I), ROK(I,ITMOB), ROKS(I,ITMOB) )
4050 CONTINUE
C
      DO 4100 I = IFIRST, IFINAL
        SAWS(I) = SYMCO ( YTRAN(I), WTR(I,IBW), WTRS(I,IBW),
*          RKCWS(I), WTR(I,IVW), WTRS(I,IVW) )
4100 CONTINUE
C
      DO 4200 I = IFIRST, IFINAL
        GPCWS(I) = GPCWS(I) * SAWS(I)
        AWS(I) = WTR(I,IBW) * SAWS(I)

```

```

4200 CONTINUE
C
      DO 4300 I = IFIRST, IFINAL
        WTRRHS(I)      = WTRRHS(I) + GPCWS(I)
4300 CONTINUE
C
      *****
      *      EAST / WEST      (WTR)      *
      *****
C
4400      AWE(IFINAL)      = 0
          GPCWE(IFINAL)    = 0
          SAWE(IFINAL)     = 0
          RSWCE(IFINAL)    = 0
          ILAST            = IFINAL - 1
          IF ( IFIRST .GT. ILAST )              GO TO 4950
C
      DO 4600 I = IFIRST, ILAST
        GPCWE(I)          = DELE(I) * ( WTR(I,IGW) + WTR(I+1,IGW) ) +
*                          ROK(I,IPCOW) - ROK(I+1,IPCOW)
        DPOTE(I)          = P(I+1) - P(I) + GPCWE(I)
4600 CONTINUE
C
      DO 4650 I = IFIRST, ILAST
        RKWCE(I)          = 1.0
        RSWCE(I)          = WTR(I,IRSW)
        IF ( DPOTE(I) .LE. 0 )              GO TO 4650
        RKWCE(I)          = 0.0
        RSWCE(I)          = WTR(I+1,IRSW)
4650 CONTINUE
C
      DO 4680 I = IFIRST, ILAST
        RKWCE(I)          = USKREL ( ROK(I,IKRW), ROK(I+1,IKRW),
*                                   RKWCE(I), ROK(I,ITMOB), ROK(I+1,ITMOB) )
4680 CONTINUE
C
      DO 4700 I = IFIRST, ILAST
        SAWE(I)           = SYMCO ( XTRAN(I), WTR(I,IBW), WTR(I+1,IBW),
*                                   RKWCE(I), WTR(I,IVW), WTR(I+1,IVW) )
4700 CONTINUE
C
      DO 4800 I = IFIRST, ILAST
        GPCWE(I)          = GPCWE(I) * SAWE(I)
        AWE(I)            = WTR(I,IBW) * SAWE(I)
4800 CONTINUE
C
      DO 4900 I = IFIRST, ILAST
        WTRRHS(I)        = WTRRHS(I) + GPCWE(I)
4900 CONTINUE
C
4950      AWW(IFIRST)      = 0
          INEXT            = IFIRST + 1
          IF ( INEXT .GT. IFINAL )              GO TO 5200
C
      DO 5000 I = INEXT, IFINAL
        AWW(I)            = WTR(I,IBW) * SAWE(I-1)
5000      CONTINUE
C
      DO 5100 I = INEXT, IFINAL
        WTRRHS(I)        = WTRRHS(I) + ( - GPCWE(I-1) )

```

```

5100 CONTINUE
C
C *****
C * TOP / BOTTOM (WTR) *
C *****
C
5200 IF ( NZ .EQ. 1 ) GO TO 7000
C
IF ( K .LT. NZ ) GO TO 5500
DO 5400 I = IFIRST, IFINAL
AWB(I) = 0
5400 CONTINUE
C
GO TO 5750
C
5500 DO 5600 I = IFIRST, IFINAL
AWB(I) = WTR(I, IBW) * SAWT(I)
5600 CONTINUE
C
DO 5700 I = IFIRST, IFINAL
WTRRHS(I) = WTRRHS(I) + ( - GPCWT(I) )
5700 CONTINUE
C
5750 IF ( K .GT. 1 ) GO TO 5900
C
DO 5800 I = IFIRST, IFINAL
AWT(I) = 0
SAWT(I) = 0
GPCWT(I) = 0
5800 CONTINUE
GO TO 7000
C
5900 DO 6000 I = IFIRST, IFINAL
GPCWT(I) = DELT(I) * ( WTR(I, IGW) + WTRT(I, IGW) ) +
* ROK(I, IPCOW) - ROKT(I, IPCOW)
DPOTT(I) = PT(I) - P(I) + GPCWT(I)
6000 CONTINUE
C
DO 6100 I = IFIRST, IFINAL
RKWCT(I) = 1.0
RSWCT(I) = WTR(I, IRSW)
IF ( DPOTT(I) .LE. 0 ) GO TO 6100
RKWCT(I) = 0.0
RSWCT(I) = WTRT(I, IRSW)
6100 CONTINUE
C
DO 6150 I = IFIRST, IFINAL
RKWCT(I) = USKREL ( ROK(I, IKRW), ROKT(I, IKRW),
* RKWCT(I), ROK(I, ITMOB), ROKT(I, ITMOB) )
6150 CONTINUE
C
DO 6200 I = IFIRST, IFINAL
SAWT(I) = SYMCO ( TRZ(I), WTR(I, IBW), WTRT(I, IBW),
* RKWCT(I), WTR(I, IVW), WTRT(I, IVW) )
6200 CONTINUE
C
DO 6300 I = IFIRST, IFINAL
GPCWT(I) = GPCWT(I) * SAWT(I)
AWT(I) = WTR(I, IBW) * SAWT(I)
6300 CONTINUE

```

```

C      DO 6400 I = IFIRST, IFINAL
          WTRRHS(I)      = WTRRHS(I) + GPCWT(I)
6400 CONTINUE
C
C      7000 CONTINUE
C
C      7800 GO TO 9900
C
C      9900 RETURN
          END
          SUBROUTINE PLOTIT(ITIM)
C
C      INCLUDE 'PARAM.INC'
C      INCLUDE 'ECON.INC'
C
C      INTEGER TIMVAR
C      CHARACTER*1 PLCHAR
C      CHARACTER*35 GRAPHTTL,BOTLABL
C      PARAMETER (NUMVAR=4,TIMVAR=5,NUMPLOT=4)
C      DIMENSION IPLOTVAR(NUMPLOT),BOTLABL(NUMPLOT)
C      DIMENSION X(5,50),GRAPHTTL(NUMPLOT),PLCHAR(NUMVAR)
C      DO 10, I = 1,ITIM
          X(1,I) = VOP(I)
          X(2,I) = VWP(I)
          X(3,I) = VOM(I)/1000
          X(4,I) = VWM(I)/1000
          X(5,I) = I
10     CONTINUE
          GRAPHTTL(1) = 'PATTERN OIL PROD. IN MBBL PER YR'
          GRAPHTTL(2) = 'PATTERN WATER PROD. IN MBBL PER YR'
          GRAPHTTL(3) = 'PROJECT OIL PROD. IN MBBL PER YR'
          GRAPHTTL(4) = 'PROJECT WATER PROD. IN MBBL PER YR'
          DO 15,I=1,4
              BOTLABL(I) = 'TIME IN YEARS'
15     CONTINUE
          IPLOTVAR(1) = 2
          IPLOTVAR(2) = 4
          IPLOTVAR(3) = 8
          IPLOTVAR(4) = 16
          PLCHAR(1) = 'O'
          PLCHAR(2) = 'W'
          PLCHAR(3) = 'O'
          PLCHAR(4) = 'W'
          CALL NEWPLOT(50,15,MYR,NUMPLOT,NUMVAR,TIMVAR,
1 BOTLABL,GRAPHTTL,IPLOTVAR,TITL,PLCHAR,X)
          DO 110, I = 1,ITIM
              IF(I.EQ.1) THEN
                  IF(VOM(I).GT.0.0) THEN
                      X(1,I) = VOM(I)/1000
                  ELSE
                      X(1,I) = -1.0
                  END IF
                  IF(VWM(I).GT.0.0) THEN
                      X(2,I) = VWM(I)/1000
                  ELSE
                      X(2,I) = -1.0
                  END IF
              END IF
              IF(I.GT.1) THEN

```

```

      IF (VOM(I).GT.0.0) THEN
        IF (X(1,I-1).GT.0.0) THEN
          X(1,I) = X(1,I-1) + VOM(I)/1000
        ELSE
          X(1,I) = VOM(I)/1000
        END IF
      ELSE
        X(1,I) = -1.0
      END IF
      IF (VWM(I).GT.0.0) THEN
        IF (X(2,I-1).GT.0.0) THEN
          X(2,I) = X(2,I-1) + VWM(I)/1000
        ELSE
          X(2,I) = VWM(I)/1000
        END IF
      ELSE
        X(2,I) = -1.0
      END IF
    END IF
    IF (VOP(I).LT.0.05) THEN
      X(3,I) = -1.0
    ELSE
      X(3,I) = VWP(I)/VOP(I)
    END IF
    IF (VOM(I).LT.0.05) THEN
      X(4,I) = -1.0
    ELSE
      X(4,I) = VWM(I)/VOM(I)
    END IF
110  CONTINUE
      GRAPHTTL(1) = 'CUMULATIVE PROJECT OIL IN MBBL'
      GRAPHTTL(2) = 'CUMULATIVE PROJECT WATER IN MBBL'
      GRAPHTTL(3) = 'PATTERN WATER OIL RATIO'
      GRAPHTTL(4) = 'PROJECT WATER OIL RATIO'
      PLCHAR(3) = '*'
      PLCHAR(4) = '*'
      CALL NEWPLOT(50,15,MYR,NUMPLOT,NUMVAR,TIMVAR,
1  BOTLABL,GRAPHTTL,IPLTVAR,TITL,PLCHAR,X)
      DO 200 I=1,ITIM
        X(1,I) = VPBP(I)
        X(2,I) = VPB(I)/1000
        IF (I.EQ.1) THEN
          IF (VPBP(I).GT.0.0) THEN
            X(3,I) = VPBP(I)
          ELSE
            X(3,I) = -1.0
          END IF
          IF (VPB(I).GT.0.0) THEN
            X(4,I) = VPB(I)/1000
          ELSE
            X(4,I) = -1.0
          END IF
        END IF
        IF (I.GT.1) THEN
          IF (VPBP(I).GT.0.0) THEN
            IF (X(3,I-1).GT.0.0) THEN
              X(3,I) = X(3,I-1) + VPBP(I)
            ELSE
              X(3,I) = VPBP(I)
            END IF
          END IF
        END IF
      END DO

```

```

        ELSE
            X(3,I) = -1.0
        END IF
        IF (VPB(I).GT.0.0) THEN
            IF (X(4,I-1).GT.0.0) THEN
                X(4,I) = X(4,I-1) + VPB(I)/1000
            ELSE
                X(4,I) = VPB(I)/1000
            END IF
        ELSE
            X(4,I) = -1.0
        END IF
    END IF
200  CONTINUE
    PLCHAR(1) = 'W'
    PLCHAR(2) = 'W'
    PLCHAR(3) = 'W'
    PLCHAR(4) = 'W'
    GRAPHTTL(1) = 'PATTERN WATER INJ. IN MBBL PER YEAR'
    GRAPHTTL(2) = 'PROJECT WATER INJ. IN MBBL PER YEAR'
    GRAPHTTL(3) = 'CUMULATIVE PATTERN WATER INJ. MBBL'
    GRAPHTTL(4) = 'CUMULATIVE PROJECT WATER INJ. MBBL'
    CALL NEWPLOT(50,15,MYR,NUMPLOT,NUMVAR,TIMVAR,
1  BOTLABL,GRAPHTTL,IPLOTVAR,TITL,PLCHAR,X)
    RETURN
END
SUBROUTINE SEARCH10(IREF,MONTH,DAY,YEAR)
C
C  Search for optimal continuity and Vdp.
C  allow special cases of more than 19 years:
C  Modified 31 March 1992 by amj to initial grid of 6x6.
C  Modified 4-25-92 by amj to use a 6x6 initial grid that does not
C  sample the border. The subsequent search can always approach
C  the border as a limit, so it is more efficient to set the fit
C  criterion artificially high for them and sample only a 4x4 grid
C  in the interior.
C
    REAL V(6), C(6), Y(4,4), Z(6,6), GOLD, HIST(250), THIST(250),
&  MODEL(250), RMS, SER, VHI, VLOW
C
    REAL DUM(1), LOWBND
c -mb variables used for graphing
    character*12 rname
    REAL bstfit(250)
    real tyrl
    integer nl
    common /gdat/ tyrl,nl
C
    CHARACTER*80 TITLE
    CHARACTER*12 NAME
    CHARACTER*6 TNAME
C
    INTEGER*2 DAY, MONTH, YEAR
    INTEGER IREF
C -mb
    COMMON /SENS/ IWP1,IWP2,UV1,UV2,UV3,ISENS,IDO_IT,XXMX,
+  TITLE,NAME,TNAME
C
    INTEGER OPTI, OPTJ, T(6), U(6)
    DATA VHI /0.95/

```

```

DATA VLOW /0.20/
DATA GOLD /0.618/
DATA T /1,2,3,2,3,4/
DATA U /0,0,0,2,2,2/
C
  IR = 8
  close(ir)
  OPEN ( IR, FILE='input.dat', STATUS='OLD' )
  read(ir,52) IREF, RNAME
52  format(I5,A12)
  READ(IR,111)
111  FORMAT(/)
  READ(IR,*) VAREA
  CLOSE(IR)
  WRITE(6,112) VAREA
112  FORMAT(' VAREA =',F7.2)
C
C  Open file to record model predictions.
C
  OPEN (28, FILE='predict.prd',STATUS='UNKNOWN')
C
C -mb initialize bstfit array - will store best fit for graphing
C
  do 55 iii=1,250
    bstfit(iii)=0.
55  continue
C
C  Set initial grid search size.
C
  IGSS = 6
  ISW = 1
  CALL COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
  ISW = 0
C
  WRITE(28,117) (HIST(K),K=1,19)
117  FORMAT(2X,'0  0.  0.  0.00  0.00  0.00',19F7.2)
C
  DUM(1)=1.0
  IWP1=13
  NR=0
C
C  Starting points for search.
C
  V(1) = 0.2 - 0.023
  V(6) = 0.95 + 0.023
  V(3) = V(1) + (V(6) - V(1)) * (1.0 - GOLD)
  V(2) = GOLD * V(3) + (1-GOLD) * V(1)
  V(4) = V(1) + (V(6) - V(1)) * GOLD
  V(5) = GOLD*V(4) + (1-GOLD)*V(6)
C
C  Upper and lower bounds for continuity are a function of
C  well spacing.
C
  SPACE = VAREA / 2.0
  Y1 = ALOG(0.42)
  Y2 = ALOG(0.12)
  SLOPE = (Y2 - Y1) / (160.0 - 10.0)
  LOWBND = (SPACE - 10.0) * SLOPE + Y1
  C(1) = EXP(LOWBND) - 0.023
C -mb&fm 4/30/92

```



```

        if(c(1).lt.0.00001) c(1)=0.00001
        Y1 = ALOG(1.0)
        Y2 = ALOG(0.80)
        SLOPE = (Y2 - Y1) / (160.0 - 10.0)
        UPBND = (SPACE - 10.0) * SLOPE + Y1
        C(6) = EXP(UPBND) + 0.023
c -mb&fm, 4/30/92
        if(c(6).gt.0.99999) c(6)=0.99999
        C(3) = C(1) + (C(6) - C(1)) * (1.0 - GOLD)
        C(2) = GOLD*C(3) + (1-GOLD)*C(1)
        C(4) = C(1) + (C(6) - C(1)) * GOLD
        C(5) = GOLD*C(4) + (1-GOLD)*C(6)
C
C Find minimum among the 16.
C
        BEST = 1000000.
        DO 100 I = 2, IGSS-1
            DO 100 J = 2, IGSS-1
                NR=NR+1
                CALL MAINS (C(I),V(J),DUM)
                CALL FIXUP( THIST, HIST, NA, MODEL, NM )
                CALL COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
                WRITE( *,301) NR,C(I), V(J), RMS
                WRITE(28,116) NR,C(I),V(J),RMS,SER,(2./3.)*RMS+(1./3.)*SER,
* (MODEL(K),K=1,19)
116         FORMAT(I3,2F5.3,F7.2,F7.2,F7.2,19F7.2)
                Z(I,J) = RMS
C
C         Y(I,J) = RMS
C When the initial grid is larger than 4x4, the fit values are
C temporarily stored in Z and later shifted to Y. When a 4x4 intial
C grid is used, they can go straight to Y.
C
                IF (RMS .LT. BEST) THEN
                    BEST = RMS
C                     BEST = (2./3.)*RMS+(1./3.)*SER
                    do 90 iii=1,n1
                        bstfit(iii)=model(iii)
90                     continue
                    OPTI = I
                    OPTJ = J
                ENDIF
100         CONTINUE
C
C Fill the border of Z with high values.
C
        DO 500 I = 1, 6, 5
            DO 500 J = 1, 6
                Z(I,J) = 1000000.
500         CONTINUE
        DO 520 I = 2, 5
            DO 520 J = 1, 6, 5
                Z(I,J) = 1000000.
520         CONTINUE
C
C Shift the 4x4 section of the matrix in the area of BEST to the
C Y Matrix. The T vector maps old optimal indeces to new.
C
        K = U(OPTI)
        OPTI = T(OPTI)

```

```

      L = U(OPTJ)
      OPTJ = T(OPTJ)
      DO 400 I = 1, 4
        C(I)=C(I+K)
        V(I)=V(I+L)
        DO 400 J = 1, 4
          Y(I,J) = Z(I+K,J+L)
400    CONTINUE
C
C  If min is at index of 1 or 2, drop the 4th element and
C  insert a new one between 1 & 2 and vice versa.
C
      NPASS = 0
115    NPASS = NPASS + 1
      IF (OPTI .LE. 2) THEN
        C(4) = C(3)
        C(3) = C(2)
        C(2) = C(1) + GOLD * (C(2)-C(1))
        NEWI = 2
        DO 120 J = 1, 4
          Y(4,J) = Y(3,J)
          Y(3,J) = Y(2,J)
120    CONTINUE
      ELSE
        C(1) = C(2)
        C(2) = C(3)
        C(3) = C(4) - GOLD * (C(4)-C(3))
        NEWI = 3
        DO 130 J = 1, 4
          Y(1,J) = Y(2,J)
          Y(2,J) = Y(3,J)
130    CONTINUE
      ENDIF
      IF (OPTJ .LE. 2) THEN
        V(4) = V(3)
        V(3) = V(2)
        V(2) = V(1) + GOLD * (V(2)-V(1))
        DO 140 I = 1, 4
          Y(I,4) = Y(I,3)
          Y(I,3) = Y(I,2)
140    CONTINUE
        NEWJ = 2
      ELSE
        V(1) = V(2)
        V(2) = V(3)
        NEWJ = 3
        V(3) = V(4) - GOLD * (V(4)-V(3))
        DO 150 I = 1, 4
          Y(I,1) = Y(I,2)
          Y(I,2) = Y(I,3)
150    CONTINUE
      ENDIF
C
C  Call for new matrix values.
C
      DO 200 I = 1, 4
        DO 200 J = 1, 4
          IF (I .EQ. NEWI .OR. J .EQ. NEWJ) THEN
            IF (V(J).GT.VHI .OR. V(J).LT.VLOW) THEN
              RMS = 1000000.

```

```

        ELSE
            NR=NR+1
            CALL MAINS (C(I),V(J),DUM)
            CALL FIXUP( THIST, HIST, NA, MODEL, NM )
            CALL COMPARE(RMS,SER,ISW,HIST,THIST,NA,MODEL,NM)
            WRITE( * ,301) NR,C(I), V(J), RMS
            WRITE(28,116) NR,C(I),V(J),RMS,SER,
&          (2./3.)*RMS+(1./3.)*SER, (MODEL(K),K=1,19)
            ENDIF
            if (rms.lt.best) then
                do 2000 k=1,n1
                    bstfit(k)=model(k)
2000          continue
                    best=rms
                endif
                y(i,j) = rms
            ENDIF
200  CONTINUE
C
C  Find new best.
C
        BEST = 1000000.
        DO 250 I = 1, 4
            DO 250 J = 1, 4
                IF (Y(I,J) .LT. BEST) THEN
                    BEST = Y(I,J)
                    OPTI = I
                    OPTJ = J
                ENDIF
250  CONTINUE
C
C  Check for end of search.
C
        IF (NPASS .LT. 3) GO TO 115
        IF (NPASS .EQ. 3) THEN
            GOLD = 0.5
            GO TO 115
        ENDIF
        WRITE( * ,300) C(OPTI), V(OPTJ), BEST
        IXY=999
        write( 28,118) ixy,iref,rname,varea
        WRITE( 28,119) IXY,C(OPTI), V(OPTJ), BEST,int(tyrl),n1,
+      (bstfit(k),k=1,19)
        WRITE( 29,302) C(OPTI), V(OPTJ), BEST,IREF,MONTH,DAY,YEAR
118  format(i3,2x,i5.5,2x,a12,2x,f7.2)
119  FORMAT(I3,2F5.3,F7.2,i7,i7,19F7.2)
300  FORMAT(' Optimum found at   Con =',F5.3,' Vdp =',F5.3,
+ ' RMS=',F8.3)
301  FORMAT(' Running case ',I3,' Con =',F5.3,' Vdp =',F5.3,
+ ' RMS=',F8.3)
302  FORMAT(' Optimum:  Con=',F5.3,' Vdp=',F5.3,
+ ' RMS=',F8.3,' for reference #: ',i5,' Date: ',a3,1x,a2,1x,a4)
C
        RETURN
        END
        SUBROUTINE SINGLE
C
C-----
C
C  Modified 16 October 1992 by Asa Janney to read

```

```

C cumulative oil production.
C
C Purposes:
C
C (1) INPUT THE RESERVOIR DATA WITH UNFORMATTED INPUT READS
C from file "IR" Normally, IR = 8
C (2) CHECK TO MAKE SURE that ALL DATA which cannot
C be calculated from a Default equation have been entered
C (3) CHECK inputs for range and consistency
C (4) Check the implications of inputs on capacity
C particularly THE SIZES OF ARRAYS,
C (5) If needed, CALCULATE DEFAULT VALUES BASED ON
C TEMPERATURE, DEPTH, GAS PROPERTIES
C (6) Incorporate the IDPM continuity curves
C and (7) CALL THE STREAMTUBE CALCULATION ROUTINES.
C
C -----
C
C INCLUDE 'PARAM.INC'
C INCLUDE 'SIMUL.INC'
C INCLUDE 'STREAM.INC'
C INCLUDE 'FILES.INC'
C
C PTT 6/91 THESE ARE FOR SENSITIVITY RUNS
C
C CHARACTER*80 TITLE
C CHARACTER*12 NAME
C CHARACTER*6 TNAME
C LOGICAL print
C -mb
C COMMON /SENS/ IWP1,IWP2,UV1,UV2,UV3,ISENS,IDO_IT,XXMX,
C + TITLE,NAME,TNAME
C
C fm 9-8-92
C
C real sp1,sp2,c1,c2,ccslo(11)
C
C EXTRSW is the switch for type of extrapolation.
C
C INTEGER EXTRSW
C
C PTT 9/91
C UVC IS WHERE WE SAVE CONTINUITY FOR THE LAYER (KB) METHOD
C IT IS EQUAL TO VCONEC.
C UVC1 IS CONTINUITY AFTER INFILL
C
C COMMON/FOO/ UVC,UVC1,BOII,IKBM
C CHARACTER*100 LINE
C INCLUDE 'BOO.INC'
C
C DIMENSION RANISO(6), NTBDEF(6), NTBLIM(6), NTBMIN(6)
C
C DATA RANISO / 2.1, 4.1, 10.1, 20.1, 50.1, 100.1 /
C DATA NTBDEF / 12, 10, 8, 6, 6, 6 /
C DATA NTBLIM / 16, 14, 12, 10, 8, 6 /
C DATA NTBMIN / 6, 6, 4, 4, 4, 4 /
C
C fm 9-8-92
C
C DATA CCSLO/

```

```

+ -0.25026, -0.38975, -0.32420, -0.30314, -0.57769,
+ -0.56122, -0.10159, -0.42621, -0.36430, -0.12519,
+ -0.27269/

```

C

C Division of Format Statements

C

```

2001 FORMAT ( '// STRANGE-LOOKING DATA - ONE OR MORE ITEMS MAY',
*           '// BE MISSING' //)

```

C

```

73  FORMAT (/// ECHO INPUT FILE: '/')

```

C

```

71  FORMAT(A100)

```

C

```

72  FORMAT(3X,A100)

```

C

```

117 FORMAT ( ' IDPM INPUT PROCESSING' )

```

C

```

965 FORMAT(20A4)

```

C

```

74  FORMAT (//)

```

C

```

956 FORMAT(' INVALID MAXIMUM TUBES SPECIFICATION,
+         Please RE-COMPILE ')

```

C

```

964 FORMAT( //, ' I D P M   CURRENT MAXIMUM PARAMETER VALUES', /
1         ' -----', //
1 3X, 'NUMBER OF TUBES PER LAYER.....', I10 , /
1 3X, 'NUMBER OF GRID CELLS PER TUBE.....', I10 , /
1 3X, 'NUMBER OF LAYERS.....', I10 , /
1 3X, 'NUMBER OF TIMESTEPS IN RESERVOIR RUN..', I10 , /
1 3X, 'BLANK COMMON SIZE FOR RESERVOIR RUN...', I10 , /
1 3X, 'NUMBER OF YEARS FOR ECONOMIC ANALYSIS.', I10 )

```

C

```

26  FORMAT(' INVALID OR NON-EXISTANT NUMBER OF LAYERS',
* 1X, ' ILAYER=', I6)

```

C

```

1111 FORMAT(
+      ' SOI IS INCONSISTENT WITH ENDPOINT SATURATIONS')

```

C

```

1003 FORMAT(' INVALID OR NON-EXISTANT POROSITY, VPHI = ',
1          E12.5 )

```

C

```

1004 FORMAT(' INVALID OR NON-EXISTANT PERMEABILITY, VKX = ',
1          E12.5 )

```

C

```

1006 FORMAT(' INVALID OR NON-EXISTANT NET PAY, VH1 = ', E12.5)

```

C

```

1013 FORMAT(' DYKSTRA-PARSONS VDP VALUE GREATER THAM 0.999.',
1          ' VDP =', E12.5 )

```

C

```

1001 FORMAT(' INVALID VALUE FOR DYKSTR-PARSONS AVERAGING',
* 1X, ' IDYST = ', I8)

```

C

```

5  FORMAT (////, 1X, 60(1H*))

```

C

```

6  FORMAT(1X, 60(1H*))

```

C

```

15  FORMAT ( ' INVALID OR NON-EXISTANT PATTERN AREA , VAREA = ',
1          E12.5 )

```

C

```

25   FORMAT ( ' INVALID OR NON-EXISTANT INFILL WATER CUT, VCUT = ',
1     E12.5 )
C
34   FORMAT ( ' INVALID OR NON-EXISTANT INJECTION RATE, VRATE = ',
&     E12.5 )
C
36   FORMAT ( ' INVALID OR NON-EXISTANT DEPTH TO STRUCTURE ',
1     'TOP, VTOP = ', E12.5 )
C
45   FORMAT ( ' INVALID OR NON-EXISTANT API GRAVITY',
1     ', APIV = ', E12.5 )
C
52   FORMAT ( ' INVALID RESERVOIR CONNECTIVITY',
1     ', VCONEC = ', E12.5 )
C
56   FORMAT ( ' INVALID INTER-WELL DISTANCE(S)',
1     ', VWD100 = ', E12.5, ', VDBWLS = ', E12.5 )
C
65   FORMAT ( ' INVALID ANISOTROPIC VALUE',
1     ', VANIS = ', E12.5 )
C
75   FORMAT ( ' INVALID REL BTWN SATN ENDPOINTS',
1     ', VSWC = ', E12.5, ', VSORW = ', E12.5 )
C
85   FORMAT ( ' UNREALISTIC VALUE GIVEN FOR BWI ', E12.5 )
C
95   FORMAT ( ' UNREALISTIC VALUE GIVEN FOR BOI ', E12.5 )
C
      NY      = 1
      NXNY    = NX * NY
      IERROR=0
C
C   IGOV:  indicator of the Infill Drilling Case
C           IGOV = 1:  Infill Case
C           IGOV = 2:  Non-Infill Case
C
C   set Logical variable for printing (Hard-wired into program)
C           PRINIT = .false.
C
C   fm 9-8-92
C   IGOV = 2 means the NON-INFILL CASE
C
C           IF ( IGOV .NE. 2 ) GO to 1500
C
C           if (prinit) WRITE (IMON,117)
C
C ***** CARD 1 of INPUT DATA *****
C
C   Read in the reference code of the Reservoir
C
C           READ(IR,965) ITITV
C           CALL TITLR(ITITV)
C
C   PTT 6/91 WRITE RUN HEADING FOR PLOTTING
C           If (Prinit) WRITE(IP,965) ITITV
C   PTT 6/91 ECHO INPUT FILE
C
C           if (prinit) WRITE(IW,73)

```

```

C
C      backspace(IR)
C      read(IR,99091)iref
C99091      format(t2,i4)
C
C      REWIND (IR)
C      DO 6969 I=1,5000
C          READ(IR,71,END=6970) LINE
C          WRITE(IW,72) LINE
6969      CONTINUE
6970      CONTINUE
C          WRITE(IW,74)
C          REWIND (IR)
C          READ(IR,965) ITITV
C
C          IF ( NTBMAX .LE. NTBLIM(1) ) GO TO 59
C          WRITE(IW,5)
C          WRITE(IW,956)
C          WRITE(IW,6)
C          IERROR=IERROR+1
59      WRITE(IW,964) NTBMAX,NXMAX,LAYMAX,ISTMAX,ICRMAX,IYRMAX
C
C PTT 6/91
C      variable "INFIL" ALLOWs the user to DISABLE theINFILL CASE
C      IF INFIL=1, SKIP INFILL CASE
C
C*****      CARD 2 of INPUT DATA      *****
C
C      READ(IR,*)
C      + IARRP,IANALP,ISTRMP,IECONR,NUMTUB,DYKST
C
C*****
C      Glossary for Card 2:
C*****
C      IARP: Control for printing simulator arrays (0 = dont print)
C      IANALP: Control for printing simulation info (0= dont print)
C      ISTRMP: Control for printing streamtube info (0= dont print)
C      IECONR: Control for economic analysis (0 = no economics)
C      NUMTUB: Number of Streamtubes (7 is normal)
C      DYKST: value of Vdp
C      if 0 < DYKST < 1.0 value of Vdp to be used
C*****
C      Override INFIL during two-pass infill mode.
C
C      IF (ITWOSW .EQ. 2) INFIL = 1
C      IF (ITWOSW .EQ. 3) INFIL = 0
C
C PTT 6/91 OVERRIDE VDP IF IN MULTIRUN MODE
C      IF (ISENS.NE.0) DYKST=UV2
C
C*****      CARD 3 of INPUT DATA      *****
C
C      READ(IR,*) IGOIN,ILAYER,NX,VANIS,VKZKH,IPAT9V
C
C      Open tiny file to read extrapolation switch.
C      10-19-92 turned off for now. See do loop at bottom of
C      MAIN program that calls all three values in turn.
C
C      OPEN(43, FILE = 'extrap.sw', STATUS = 'OLD')

```

```

C      READ(43,*)  EXTRSW
C      CLOSE(43)
C
C*****
C  Glossary for Card 3:
C*****
C      IGOIN: Plugging back of infill wells (1 = dont plug back)
C      ILAYER: Number of layers to use (5 is normal)
C      NX: Number of grid cells per streamtube (7 is normal)
C      VANIS: Ratio of Ky to Kx
C      VKZKH: Ky/Kx anisotropy value
C      IPAT9V: Control for pattern spacing
C      = 0: Five Spot Pattern
C      = 1: Nine spot pattern
C*****
C
C PTT 6/91 OVERRIDE KY/KX IF IN MULTIRUN MODE
C
C      IF(ISENS.NE.0) VANIS=UV3
C
C      IF ( IPAT9V .GT. 1 ) WRITE (IW,2001)
C      IF ( ILAYER .GT. 0 .AND. ILAYER .LE. LAYMAX) GO TO 29
C      WRITE(IW,5)
C      WRITE(IW,26) ILAYER
C      WRITE(IW,6)
C      IERROR=IERROR+1
29  CONTINUE
C
C      Ky/Kx (VANIS) must be 1.0 OR GREATER
C      TO CALCULATE STREAMTUBES PROPERLY
C
C      IF ( VANIS .LE. 0.0 ) VANIS = 1.0
C      IF ( VANIS .LT. 1.0 ) VANIS = 1.0/VANIS
C
C      MAKE SURE THAT THE NUMBER OF STREAM TUBES WILL WELL FOR THE
C      SPECIFIED ANISOTROPY AND ALSO FIT WITHIN THE DIMENSION LIMITS
C
C      DO 57  L = 1, 6
C      LANI = L
C      IF ( VANIS .LT. RANISO(L) ) GO TO 58
57  CONTINUE
C
58  IF ( NUMTUB .EQ. 0 )          NUMTUB = NTBDEF(LANI)
C      IF ( NUMTUB .GT. NTBLIM(LANI) ) NUMTUB = NTBLIM(LANI)
C      IF ( NUMTUB .LT. NTBMIN(LANI) ) NUMTUB = NTBMIN(LANI)
C      IF ( NUMTUB .GT. NTBMAX )    NUMTUB = NTBMAX
C
C      IF ( ILAYER .EQ. 0 ) ILAYER =1
C      IF ( ILAYER .GT. LAYMAX) ILAYER=LAYMAX
C      IF ( NX .LE. 0 ) NX = 15
C      IF ( NX .GT. NXMAX ) NX=NXMAX
C      VNX = NX
C
C ***** CARD 4 of INPUT DATA *****
C
C      READ(IR,*)
C      +VAREA,VWD100,VDBWLS,VCONEC,VRATE,VRATE1,VCUT,CUTMAX,DTMAX
C
C*****
C  Glossary for Card 4:

```



```

C*****
C   VAREA:  area in acres of a full pattern [= SPACING*2.0]
C   VWD100: distance from well at which connectivity drops below
C           100%
C   VDBWLS: well distance for which next value of connectivity
C           is given [= SQRT(0.5*VAREA*43560)]
C   VCONEC: Continuity (C) value
C           note if C is specified, it must be entered as a negative
C           -1.0.0 < VCONEC < 0.0 : use this value in analysis
C           = 1.0: solve for continuity
C   VRATE:  injection rate for a full pattern prior to infill
C           (Value of Year 1 production * -1.0)
C   VRATE1: injection rate after infill (Normally zero)
C   VCUT:   water cut at start of infill
C           parameter solving mode: 0.9999
C           infill drilling case:   0.9500
C   CUTMAX: Water cut at which case ends
C           parameter solving mode: 0.999
C           infill drilling case:   0.990
C   DTMAX:  Phil Thayer's Empirical Factor
C           "PTT 6/91 ALLOW USER TO ENTER TMAX"
C*****
C   If this is the second pass, alter DTMAX to start infill at the
C   right time step.
C
C       IF (ITWOSW .EQ. 3 .AND. DTMAX .EQ. 0) THEN
C           DTMAX = -STEPIN
C       WRITE(6,710) DTMAX
C710    FORMAT(' Second-pass DTMAX set to ',F10.0)
C       ENDIF
C
C   check on "VDBWLS"
C
C       IF ( ABS(VDBWLS) .LT. 0.00001 )
C           * VDBWLS = SQRT (2.0*( 0.5*SQRT(43560.0*VAREA))** 2)
C
C   PTT 10/91 IF VCONEC<0.0 USE LAYER METHOD
C       i.e. treat VCONEC as the actual continuity
C
C       IF ( VWD100 .LE. 0.0 .OR. VDBWLS .LE. VWD100 .OR.
C           *   ABS(VCONEC) .GT. 1.0 ) WRITE (IW,2001)
C
C ***** CARD 5 of INPUT DATA *****
C
C       READ(IR,*) VCROC,VREFP,VRESP,VTOP,VTEMP
C
C *****
C   Glossary for Card 5:
C *****
C   VCROC:  Pore Compressibility (0 = use default)
C   VREFP:  Reference Pressure (0 = use default)
C   VRESP:  Reservoir Pressure (PSIA)
C   VTOP:   Depth to Top of Formation (entered as a negative)
C   VTEMP:  Reservoir Temperature
C *****
C ***** CARD 6 of INPUT DATA *****
C
C       READ(IR,*) DENWST,BWI,CMPWTR,VISWTR,SGGV
C

```

```

C*****
C  Glossary for Card 6:
C*****
C  DENWST: Density of Water at Reservoir Conditions
C          (0 = use default)
C  BWI: Water Formation Volume Factor (0 = use default)
C  CMPWTR: Water Compressibility (0 = use default)
C  VISWTR: Water Viscosity (0 = use default)
C  SGGV: Solution Gas Gravity (0 = use default)
C*****
C          IF ( SGGV .GT. 1.5 ) WRITE (IW,2001)
C
C ***** CARD 7 of INPUT DATA *****
C
C  READ (IR,*) APIV,BOI,CMPOIL,VISOIL,GORV,BOK
C  READ (IR,*) APIV,BOI,CMPOIL,VISOIL,GORV
C
C*****
C  Glossary for Card 7:
C*****
C  APIV: API Gravity of oil
C  BOI: CURRENT oil formation factor (strange, isnt it)
C  CMPOIL: Oil Compressibility (0 = use default)
C  VISOIL: Oil Viscosity (CP)
C  GORV: Solution Gas-oil ratio (0 = use default)
C  BOK: INITIAL oil formation factor
C*****
C
C PTT 10/91
C  ADD THIS FOR KB METHOD OF SATURATION DISTRIBUTION: BOK
C
C  BOII=BOI
C
C PTT 6/91 ALLOW OVERRIDE OF INITIAL SATURATIONS
C
C ***** CARD 8 of INPUT DATA *****
C
C  READ (IR,*) VXNO,VXNW,VXKROE,VXKRWE,VSWC,VSORW,SOI
C
C*****
C  Glossary for Card 8:
C*****
C  VXNO: Oil Relative Permeability exponent
C  VXNW: Water Relative Permeability exponent
C  VXKROE: Oil Relative Permeability end point
C  VXKRWE: Water Relative Permeability end point
C  VSWC: Connate Water Saturation
C  VSORW: Residual Saturation after waterflood
C  SOI: Oil saturation at the start of the flood
C
C*****
C
C  IF (SOI.GT.0.0) THEN
C    IF (SOI.LE.VSORW .OR. (1.-SOI).LT.VSWC) THEN
C      WRITE (IW,5)
C      WRITE (IW,1111)
C      WRITE (IW,6)
C      IERROR=IERROR+1
C    ENDIF
C  ENDIF

```

```

C-----
C
      IF ( VSORW .GT. 1.0 ) WRITE (IW,2001)
C
C PTT 6/91:
      IF ( DYKST .GE. 0 ) GO TO 1010
C
      DO 1000 I=1,ILAYER
      READ(IR,*) VPHI(I), VKX(I),VH1(I)
      IF ( VPHI(I) .GT. 0.0) GO TO 1002
C
C      CHECK FOR MISSING DATA THAT HAS NO DEFAULTS
C
      WRITE(IW,5)
      WRITE(IW,1003) VPHI(I)
      WRITE(IW,6)
      IERROR=IERROR+1
1002 CONTINUE
      IF( VKX(I) .GT. 0.0) GO TO 1005
      WRITE(IW,5)
      WRITE(IW,1004) VKX(I)
      WRITE(IW,6)
      IERROR=IERROR+1
1005 CONTINUE
      IF ( VH1(I) .GT. 0.0 ) GO TO 1007
      WRITE(IW,5)
      WRITE(IW,1006) VH1(I)
      WRITE(IW,6)
      IERROR=IERROR+1
1007 CONTINUE
1000 CONTINUE
      GO TO 1020
1010 CONTINUE
      IF( DYKST .LE. 0.999) GO TO 1014
      WRITE(IW,5)
      WRITE(IW,1013) DYKST
      WRITE(IW,6)
      IERROR=IERROR+1
1014 CONTINUE
C
C ***** CARD 9 of INPUT DATA *****
C
      READ(IR,*) IDYST
C
C*****
C Glossary for Card 9:
C*****
C IDYST: Controls calculation of layer permeabilities
C      1 = layer k and h assume equal thickness
C
C*****
C
      IF ( IDYST .EQ. 1 .OR. IDYST .EQ. 2 ) GO TO 1008
      WRITE(IW,5)
      WRITE(IW,1001) IDYST
      WRITE(IW,6)
      IERROR= IERROR +1
1008 CONTINUE
C

```

```

C ***** CARD 10 of INPUT DATA *****
C
C      READ(IR,*) VPHIL,VKXL,VHL
C
C*****
C      Glossary for Card 10:
C*****
C      VPHIL: Reservoir Porosity (Fraction)
C      VKXL: Reservoir Permeability (MD)
C      VHL: Reservoir Net Pay (Ft)
C
C*****
C examination of Porosity value
C
C      IF ( VPHIL .GT. 0.0) GO TO 1012
C      WRITE(IW,5)
C      WRITE(IW,1003) VPHIL
C      WRITE(IW,6)
C      IERROR=IERROR+1
C 1012 CONTINUE
C
C examination of Permeability Value
C
C      IF( VKXL .GT. 0.0) GO TO 1015
C      WRITE(IW,5)
C      WRITE(IW,1004) VKXL
C      WRITE(IW,6)
C      IERROR=IERROR+1
C 1015 CONTINUE
C
C      fmpor=VPHIL
C
C examination of Net Pay value
C
C      IF ( VHL .GT. 0.0 ) GO TO 1017
C      WRITE(IW,5)
C      WRITE(IW,1006) VHL
C      WRITE(IW,6)
C      IERROR=IERROR+1
C 1017 CONTINUE
C
C      fmhnet=VHL
C
C
C      CALCULATE THE LAYER PERMS AND THICKNESSES BASED ON THE
C      DYKSTRA-PARSONS METHOD IF DYKST IS GREATER THAN 0.
C
C      DO 1016 I=1,ILAYER
C 1016 VPHI(I)=VPHIL
C
C PTT 9/91
C ALLOW THE KB (PFPM) METHOD OF CONTINUITY - USING AN EXTRA LAYER
C      BY READING NEGATIVE VCONEC
C
C      UVC=0.0
C      UVC1=0.0
C
C fm 9-8-92

```

```

C Apply the continuity curve methodology developed August 1992
C
C   Get the exponent
C   IRCLS:  reservoir class code
C   CCSLO(J):  continuity curve exponent (slope) for class "J"
C              based on Asa Janney's work
C   SP1:  Original spacing (=Varea/2)
C   SP2:  Infill Spacing (= SP1/2)
C   C1:  Original Continuity
C   C2:  Continuity at SP2
C
      SP1 = VAREA/2.0
      SP2 = SP1/2.0
C
C in multi-run mode, use the continuity value from the
C   fitting procedure
C
      IF (ISENS.NE.0) THEN
        VCONEC=-UV1
      ENDIF
      C1 = abs(VCONEC)
C
8000      CONTINUE
          SLOPE = ALOG ( C1 ) / ( VDBWLS -VWD100 )
          C2 = EXP ( SLOPE * ( SQRT(VDBWLS**2/2.0) - VWD100 ) )
8100      if (C2.ge.1.00) C2 = 1.00
C
C Make infill injection rate a function of increasing C.
C
C   IF (VRATE1 .EQ. 0) VRATE1 = ABS(VRATE * (C2/C1))
C   UVR=VRATE
C   UVR1=VRATE1
C   IF(VCONEC.GE.0.0) THEN
C
C Original IDPM Version
C
      IKBM=0
      CALL DPLYR(IDYST,DYKST,ILAYER,VKXL,VHL,VKX(1),VH1(1))
      UVC =VCONEC
      UVC1 = C2
C
      ELSE
C
C PFFPM Version (Now being used)
C
      IKBM=1
      UVC=ABS(VCONEC)
      IF(UVC.GE.1.00) UVC=1.00
      UVC1 = C2
      VCONEC=1.0
      CALL
+ DPLYR(IDYST,DYKST,ILAYER-1,VKXL,VHL*UVC,VKX(1),VH1(1))
      VKX(ILAYER)=VKXL
      VH1(ILAYER)=VHL*(UVC1-UVC)
      DO 2500 J=1,NUMTUB
        IPROD(J,ILAYER) = 1
        IINJ(J,ILAYER) = 1
2500      CONTINUE
      ENDIF
C

```

```

1020 CONTINUE
C
C   CHECK FOR DEFAULT VALUES FOR RESERVOIR DATA WITH ZERO VALUE
C   BUT FOR WHICH A DEFAULT IS AVAILABLE.
C
C   FIRST VARIABLES WITH NO DEFAULT
C
C   check on spacing
C
      IF ( VAREA .GT. 0.0 ) GO TO 20
        WRITE(IW,5)
        WRITE(IW,15) VAREA
        WRITE(IW,6)
        IERROR=IERROR+1
20 CONTINUE
C
C   check on ifill water cut
C
      IF ( VCUT .GT. 0 .OR. VCUT .LT. 1.0 ) GO TO 30
        WRITE(IW,5)
        WRITE(IW,25) VCUT
        WRITE(IW,6)
        IERROR=IERROR+1
30 CONTINUE
C
C   check on injection rate (VRATE)
C
      IF ( ABS(VRATE)-.001 .GT. 0.001 ) GO TO 35
        WRITE(IW,5)
        WRITE(IW,34) VRATE
        WRITE(IW,6)
        IERROR=IERROR+1
35 CONTINUE
C
C   check on depth (VTOP) - entered as a negative
C
      IF ( VTOP .LT. 0.0 ) GO TO 40
        WRITE(IW,5)
        WRITE(IW,36) VTOP
        WRITE(IW,6)
        IERROR=IERROR+1
40 CONTINUE
C
C   check on API gravity
C
      IF ( APIV .GT. 0 ) GO TO 50
        WRITE(IW,5)
        WRITE(IW,45) APIV
        WRITE(IW,6)
        IERROR=IERROR+1
50 CONTINUE
C
C   check on continuity (VCONEC)
C
      IF ( VCONEC .LE. 1.0 .AND. VCONEC .GT. 0.0 ) GO TO 55
        WRITE(IW,5)
        WRITE(IW,52) VCONEC
        WRITE(IW,6)
        IERROR=IERROR+1
55 CONTINUE

```

```

C
C check on VWD100 and VDBWLS
C
      IF ( VWD100 .GT. 0.0 .AND. VDBWLS .GT. VWD100 ) GO TO 60
      WRITE(IW,5)
      WRITE(IW,56) VWD100, VDBWLS
      WRITE(IW,6)
      IERROR=IERROR+1
60    CONTINUE
C
C Check on Ky/Kx ratio
C
      IF ( VANIS .LE. 100.0 ) GO TO 70
      WRITE(IW,5)
      WRITE(IW,65) VANIS
      WRITE(IW,6)
      IERROR=IERROR+1
70    CONTINUE
C
C check on water saturations
C
      IF ( VSWC .LE. 0.0 .OR. VSORW .LE. 0.0 ) GO TO 80
      IF ( VSWC .LT. (1.0-VSORW) ) GO TO 80
      WRITE(IW,5)
      WRITE(IW,75) VSWC, VSORW
      WRITE(IW,6)
      IERROR=IERROR+1
80    CONTINUE
C
      fmsoi = (1.0 -VSWC)
      fmboi = BOI
C
C
C check on BWI
C
      IF (BWI .LT. 1.5 ) GO TO 90
      WRITE(IW,5)
      WRITE(IW,85) BWI
      WRITE(IW,6)
      IERROR=IERROR+1
90    CONTINUE
C
C check on Boi
C
      IF ( BOI .LT. 5.0 ) GO TO 100
      WRITE(IW,5)
      WRITE(IW,95) BOI
      WRITE(IW,6)
      IERROR=IERROR+1
100   CONTINUE
C
C if any errors are found, halt processing
C
      IF ( IERROR .GT. 0 ) CALL HALTER ('SINGLE', 100 )
C
C NOW DO DEFAULT VALUES FOR VARIABLES THAT USER CHOSSES TO DEFAULT
C
      IF ( IGOIN .EQ. 0 )    IGOIN    = 1
      IF ( VKZKH .LE. 0.0 )  VKZKH    = 0.0
      IF ( CUTMAX .LE. 0.0 )  CUTMAX   = VCUT

```

```

      IF ( DENWST .LE. 0.0 ) DENWST = 62.4
      IF ( VCROC .LE. 0.0 ) VCROC = 3.E-6
      IF ( CMPWTR .LE. 0.0 ) CMPWTR = 3.E-6
      IF ( CMPOIL .LE. 0.0 ) CMPOIL = 3.E-6
      IF ( VXKROE .LE. 0.0 ) VXKROE = 0.80
      IF ( VXKRWE .LE. 0.0 ) VXKRWE = 0.20
      IF ( VXNO .LE. 0.0 ) VXNO = 2.00
      IF ( VXNW .LE. 0.0 ) VXNW = 2.00
      IF ( VSWC .LE. 0.0 ) VSWC = 0.2
      IF ( VSORW .LE. 0.0 ) VSORW = 0.25

C
C PTT 6/91 CHECK TMAX
C
      IF ( ABS(DTMAX) .LT. 0.00001 ) DTMAX = 1.0E+20
C
C PTT 1/92
C   FOR PRODUCTION CASES, HARDWIRE TIME AND SOME OTHER THINGS
C   IDO_IT IS SET WHEN SEARCH ALGORITM FINDS OPTIMUM,
C   AND CALLS MAIN ON LAST TIME
C
      IF (IDO_IT.EQ.1) THEN
C   ENABLE INFILL CASE
      INFIL=0
C   INFILL AT END OF TORIS WINDOW
      IF (DTMAX .EQ. 0) DTMAX=-(7300.)
C   SET MAXIMUM TIME - 7 YEARS BEYOND TORIS WINDOW
      XXMX=9855.
C   SET CUTMAX TO BIG
      CUTMAX=.95
      VCUT=1.1
C   TURN ON OUTPUT
      IANALP=1
c   SET TO 5 TO 9
      IPAT9V=1
C
      ENDIF
C
      GGRAD = 0.017
      PGRAD = 0.433
      IF ( VTEMP .LE. 0.0 ) VTEMP = 60. - VTOP * GGRAD
      IF ( VRESP .LE. 0.0 ) VRESP = 15. - VTOP * PGRAD
      IF ( VREFP .LE. 0.0 ) VREFP = VRESP
      SOGV = 141.5 / (131.5 + APIV )
      DENOST = 62.4 * SOGV
      PSEP=64.7
      IF ( SGGV .LE. 0.0 ) SGGV = 0.8
      SGGV = SGGV * ( 1.0 + 5.912E-5*APIV*VTEMP*ALOG(PSEP/114.7))
      IF ( SGGV .LT. 0.8) SGGV= 0.8
      IF ( SGGV .GT. 1.4 ) SGGV = 1.4
      IF ( GORV .GT. 0.0 ) GO TO 4000
      IF ( APIV .GT. 30.0 ) GO TO 3911
      GORV =
+ 0.0362*SGGV*VRESP**1.0937*EXP(25.724*APIV/(VTEMP+460.))
      GO TO 4000
3911 GORV= 0.0178*SGGV*VRESP**1.187*EXP(23.931*APIV/(VTEMP+460.))
4000 IF ( BOI .GT. 0.0 ) GO TO 3950
      IF (APIV .GT. 30.0 ) GO TO 3913
      C1 = 4.667E-4
      C2 = 1.751E-5
      C3 = -1.811E-8

```



```

      GO TO 3914
3913 C1=4.67E-4
      C2=1.1E-5
      C3= 1.337E-9
3914 CONTINUE
      BOI = 1.0 + C1*GORV + (C2+C3*GORV) * (VTEMP-60.0) * (APIV/SGGV)

C PTT 10/91 -
      IF(BOK.LE.0.0) BOK=BOI
      IF(BOK.GT.BOI) BOK=BOI
C DJR 3/94 BOK no longer read in so assign value of BOI
      BOK=BOI
3950 DENOIL = DENOST/BOI
      IF ( BWI .LE. 0.0 )
&      BWI = 1.0 + 1.2E-4*(VTEMP-60.0)+1.E-6*(VTEMP-60.0)**2 -
&      3.33E-6*VRESP
      DENWTR=DENWST/BWI
      IF ( VISOIL .GT. 0.0 ) GO TO 4300
      ZV = 3.3024 - 0.02023*APIV
      YV = 10.**ZV
      XV = YV/VTEMP**1.163
      VISDV=10.**XV-1.
      AVO = 10.715 / (GORV+100.0)**0.515
      BVO = 5.44 / (GORV+150.0)**0.338
      VISOIL = AVO*VISDV**BVO
4300 CONTINUE
      IF ( VISWTR .GT. 0.0 ) GO TO 4400
      VISWTR = -1.439*ALOG10(VTEMP) + 3.74486
4400 CONTINUE

C
C      PRINT SUMMARY OF INPUT SPECIFICATIONS
C
      WRITE(IW,9305) IARRP,IANALP,ISTRMP,IECONR
9305 FORMAT(//
1 1X,'SPECIFIED PRINTOUT CONTROLS' / 1X,27(1H-) ///
1 3X,'RESERVOIR ARRAY OUTPUT CONTROL .....', I8, 8H IARRP /
1 3X,'RESERVOIR ANALYSIS OUTPUT CONTROL ....', I8, 8H IANALP /
1 3X,'STREAMTUBE OUTPUT CONTROL .....', I8, 8H ISTRMP /
1 3X,'ECONOMIC ANALYSIS CONTROL(0-NO, 1-YES)', I8, 8H IECONR )
      WRITE(IW,9300)
9300 FORMAT(// 1X,'RESERVOIR PROPERTIES OUTPUT' / 1X,27(1H-) )
      WRITE(IW,9350) VTOP,VTEMP,VAREA,VKZKH,VANIS,DYKST,
+      VRESP,VCROC,VREFP,ILAYER,NUMTUB,NX,IPAT9V
9350 FORMAT(//
1 3X,'FORMATION DEPTH -- SUBSURFACE.....',F10.1,2X,' FEET '//
1 3X,'FORMATION TEMPERATURE .....,F10.1,2X,' DEG F '//
1 3X,'INDIVIDUAL PATTERN AREA .....,F10.1,2X,' ACRES '//
1 3X,'KV/KH VERTICAL TO HORIZONTAL PERM.....',F10.3,2X,' '//
1 3X,'KY/KX ANISOTROPIC VALUE (1.0-100.0)...',F10.3,2X,' '//
1 3X,'DYKSTRA-PARSONS COEFFICIENT .....,F10.2,2X,' VDP '//
1 3X,'PRESSURE AT FORMATION TOP .....,F10.1,2X,' PSIA '//
1 3X,'PORE VOLUME COMPRESSIBILITY .....,F10.8,2X,' 1/PSI '//
1 3X,'REFERENCE PRESSURE (POROSITY MEASURED)',F10.1,2X,' PSIA '//
1 3X,'NUMBER OF LAYERS .....,I10 ,2X,' '//
1 3X,'STREAMTUBES PER LAYER .....,I10 ,2X,' '//
1 3X,'NUMBER OF GRID CELLS PER STREAMTUBE...',I10 ,2X,' '//
1 3X,'INFILL PATTERN (0=5-SPOT, 1=9-SPOT)...',I10 ,2X,' ')
      WRITE(IW,9347)
9347 FORMAT(1H1 //
1 3X,'
      PROPERTIES BY LAYER
      ',/

```

```

1 3X,' ----- ' , /
1 3X,' POROSITY      X-DIR PERM      NET PAY ' , /
1 3X,' ----- ' )
DO 9346 I=1, ILAYER
9346 WRITE(IW, 9345) VPHI(I), VKX(I), VH1(I)
9345 FORMAT(6X, F8.4, 5X, F10.2, 5X, F8.2)
WRITE(IW, 9349) DENWST, DENWTR, BWI, CMPWTR, VISWTR
9349 FORMAT(///
1 3X,' WATER DENSITY AT STANDARD CONDITIONS..', F10.2, 2X, ' LB/CUFT' /
1 3X,' WATER DENSITY AT RESERVOIR CONDITIONS..', F10.2, 2X, ' LB/CUFT' /
1 3X,' WATER FORMATION VOLUME FACTOR.....', F10.2, 2X, ' VOL/VOL' /
1 3X,' WATER COMPRESSIBILITY AT RES. COND....', F10.8, 2X, ' 1/PSI ' /
1 3X,' WATER VISCOSITY AT RES. COND.....', F10.2, 2X, ' CP ' )
WRITE(IW, 9348) DENOST, APIV, DENOIL, BOI, CMPOIL, VISOIL, GORV, SGGV
9348 FORMAT(///
1 3X,' OIL DENSITY AT STANDARD CONDITIONS....', F10.2, 2X, ' LB/CUFT' /
1 3X,' OIL GRAVITY ....., F10.1, 2X, ' DEG API' /
1 3X,' OIL DENSITY AT RESERVOIR CONDITIONS....', F10.2, 2X, ' LB/CUFT' /
1 3X,' OIL FORMATION VOLUME FACTOR.....', F10.2, 2X, ' VOL/VOL' /
1 3X,' OIL COMPRESSIBILITY AT RES. COND.....', F10.8, 2X, ' 1/PSI ' /
1 3X,' OIL VISCOSITY AT RES. COND.....', F10.2, 2X, ' CP ' /
1 3X,' SOLUTION GAS-OIL-RATIO ....., F10.1, 2X, ' SCF/STB' /
1 3X,' GAS GRAVITY (AIR=1.0).....', F10.3, 2X, ' ' )
WRITE(IW, 9351) VRATE, VRATE1, VCUT, CUTMAX, IGOIN
9351 FORMAT(///,
1 3X,' INJECTION RATE (NON-INFILL) ....., F10.1, 2X, ' STBW/D ' /
1 3X,' INJECTION RATE (INFILL, MAY BE 0.0) ..', F10.1, 2X, ' STBW/D ' /
1 3X,' WATER CUT AT INFILL (VCUT) ....., F10.3, 2X, ' FRAC. ' /
1 3X,' WATER CUT AT END (CUTMAX) ....., F10.3, 2X, ' FRAC. ' /
1 3X,' PLUG BACK AT INFILL ( 1=NO ) ....., I10 /
1 3X,' ( 2=YES, IF LAYER W-CUT .GT. VCUT ) .'/ )
C
WRITE(IW, 9150)
9150 FORMAT(1H1 // 14X, 'RELATIVE PERMEABILITY DATA')
WRITE(IW, 9151) VSWC, VSORW, VKKROE, VKKRWE, VXNO, VXNW,
* VWD100, VDBWLS, VCONEC
9151 FORMAT(
1 3X, 37H IRREDUCIBLE WATER SATURATION ....., F10.3, 6H SWC /
1 3X, 37H RESIDUAL OIL SATN -- INPUT -- ....., F10.3, 6H SORW /
1 3X, 37H OIL RELATIVE PERM END-POINT ....., F10.3, 7H XKROE /
1 3X, 37H WATER RELATIVE PERM END-POINT ....., F10.3, 7H XKRWE /
1 3X, 37H OIL RELATIVE PERM CURVATURE ....., F10.2, 6H XNO /
1 3X, 37H WATER RELATIVE PERM CURVATURE ....., F10.2, 6H XNW /
1 3X, 37H (MAX) WELL DIST. FOR CONN.=100% ....., F10.3, 8H VWD100 /
1 3X, 37H WELL DIST. FOR CONN.=VCONEC ....., F10.3, 8H VDBWLS /
1 3X, 37H RESERVOIR CONNECTIVITY AT VDBWLS ....., F10.3, 8H VCONEC )
C
C OUTPUT THE RELATIVE PERMEABILITY TABLE
C FOR CONNECTIVITY OF UNITY
C
VCCN = 1.0
CALL RPTABL ( 1.0 )
C
NZ=ILAYER
METH=1
C
C SCALE INPUT INJECTION RATE TO THE PROPER ELEMENT OF SYMMETRY
C FOR THE CASE BEING RUN
C
RSCALE = 8.

```

```

      IF ( ABS(VANIS-1.0).GT. 0.0001) RSCALE=4.
      VRATE=VRATE*5.615/RSCALE
      VRATE1=VRATE1*5.615/RSCALE
      CROCK=VCROC
      REFPRE=VREFP
      VKY(1)=VKX(1)*VANIS
      VZT(1)=VTOP
      VZB(1)=VZT(1)-VH1(1)
C
C   Same for historical cumulative oil.
C
C      CUMOIL = CUMOIL / RSCALE
C      WRITE(6,720) CUMOIL
C720   FORMAT(' Pattern cum oil =',F10.0)
C-----
C PTT 6/91 ALLOW OVERRIDE OF SATURATIONS
C
      IF (SOI.LT.0.0001) THEN
        VSO(1)=1.-VSWC
        VSW(1)=VSWC
      ELSE
        VSO(1)=SOI
        VSW(1)=1.-SOI
      ENDIF
C-----

      VP1(1)=VRESP+ DENOIL/144.*(VZT(1) - (VZT(1)+VZB(1))/2.)
      TOTKH=VH1(1)*VKX(1)
C PTT
      TOTH= VH1(1)
C
      DO 1100 I=1,NTBMAX
        VPWELL(I,1)=VP1(1)- (VP1(1)*0.01)
      1100 VPI(I,1)=100.0
C
C      SET INITIAL CELL DIMENSIONS BASED ON THE PATTERN AREA AND NUMBER
C      OF CELLS PER TUBE FOR PORE VOLUME CALCULATIONS.
C
C      IF ( ILAYER .EQ. 1 ) GO TO 1500
C      IF ( ILAYER .EQ. 1 ) GO TO 1400
C
      DO 1200 I=2,ILAYER
        VKY(I)=VKX(I)*VANIS
        VZT(I)=VZT(I-1)-VH1(I-1)
        VZB(I)=VZT(I)-VH1(I)
        VSO(I)=VSO(I-1)
        VSW(I)=VSW(I-1)
C
C      INITIAL PRESSURES BY LAYER BASED ON OIL GRADIENT
C
      VP1(I)=VP1(I-1) + DENOIL/144.* ((VZT(I-1)+VZB(I-1))/2. -
*      (VZT(I)+VZB(I))/2.)
      TOTKH=TOTKH + VH1(I)*VKX(I)
C
      DO 1150 J=1,NTBMAX
        IPROD(J,I)=0
        IINJ(J,I)=0
        VPWELL(J,I)=VP1(I)-(VP1(I)*0.01)

```

```

1150 VPI(J,I)=100.0
1200 CONTINUE

C PTT 10/90 TAKE OUT INFILL LAYER KH
IF (IKBM.NE.0) THEN
  TOTKH=TOTKH-(VH1(ILAYER)*VKX(ILAYER))
  TOTH=TOTH-VH1(ILAYER)

  DO 2511 J=1,NUMTUB
    IPROD(J,ILAYER) = 1
    IINJ(J,ILAYER) = 1
2511 CONTINUE

  ENDIF

C PTT 9/91 IF SOI < 1-SWC, ALLOCATE INITIAL MOVABLE WATER BASED ON KH
IDIST=0
IF (SOI.GT..0001 .AND. IDIST.EQ.1) THEN

  IF (IKBM.NE.0) THEN
    IL=ILAYER-1
  ELSE
    IL=ILAYER
  ENDIF

C DISTRIBUTE INITIAL WATER SATURATION

  CALL SWDIST( IL, VKX, VH1, VSW, VSORW, VSWC, SOI, BOI, BOK)
  DO 12000 I=1,IL
    VSO(I)=1.-VSW(I)
12000 CONTINUE

  ENDIF

  IF (IKBM.NE.0) THEN

C HERE, WE ASSUME 7% PRIMARY, SO PUT IN SOME MOVABLE WATER
C THIS IS SCREWED UP IF HE IS STARTING FROM THE BEGINING, IN THAT
C CASE, JUST USE THE INITIAL SO

    IF (SOI.GT..0001) THEN
      VSO(ILAYER)=(1.0-VSWC)-.07
    ELSE
      VSO(ILAYER)=(1.0-VSWC)
    ENDIF
    VSW(ILAYER)=1.0-VSO(ILAYER)

  ENDIF

C PTT 10/91 ADD SATURATION PRINT OUT HERE HERE

  WRITE(IW,93477)
93477 FORMAT(///,
1 3X,'
1 3X,' POROSITY X-DIR PERM NET PAY SO ',
1 ' SW ',/
1 3X,' _____ ' ,
1 ' _____ ' /)

```

```

      DO 93466 I=1, ILAYER
93466 WRITE(IW, 93455) VPHI(I), VKX(I), VH1(I), VSO(I), VSW(I)
93455 FORMAT(6X, F8.4, 5X, F10.2, 5X, F8.2, 5X, F8.4, 5X, F8.4)

```

```

C IF USING LAYER MODEL SET THIS LAYER TO 1.-SWC IN CASE THE SOI OVERRIDE HAS
C BEEN USED

```

```

1400 CONTINUE

```

```

C PTT 6/90 IF VRATE < 0.0 USE ABS AS OIL RATE

```

```

      IF (VRATE.LT.0.0) THEN
        IF (IKBM.NE.0) THEN
          IL=ILAYER-1
        ELSE
          IL=ILAYER
        ENDIF
        VCCN=VCONEC

```

```

C*****

```

```

      UO=ABS (VRATE)
      SUMW=0.0
      SUMO=0.0
      SUMF=0.0

```

```

C
C Need mobility ratio for new search procedure.
C amj, 12-29-92
C

```

```

      XMOBRAT = (VKRW / VISWTR) / (VKROE / VISOIL)
C      WRITE(31, 776) XKRW, VISWTR, XKRO, VISOIL, XMOBRAT
C776   FORMAT('      XKRW VISWTR      XKRO VISOIL XMOBRAT' , /,
C      &      5F8.2)
C

```

```

      DO 777 LL=1, IL
      QF=(VKX(LL)*VH1(LL))/TOTKH
      CALL WATSAT(1, 1, VSW(LL), XKRW, XKRO)
      XMOBW = XKRW / (VISWTR)
      XMOBO = XKRO / (VISOIL)
      FO    = XMOBO / ( XMOBW + XMOBO )
      FW    = XMOBW / ( XMOBW + XMOBO )

```

```

      QO=QF*FO
      QW=QF*FW
      SUMO=SUMO+QO
      SUMW=SUMW+QW
      SUMF=SUMF+QF

```

```

777   CONTINUE
      UFAC=(BOI/BWI)/SUMO
      VRATE=-(VRATE*UFAC)
C      IF (VRATE1.LE.0.0) VRATE1=2*VRATE

```

```

C*****

```

```

      ENDIF
      IF ((VRATE1.LT.0.0001).AND.(IKBM.GT.0)) VRATE1=2*VRATE

```

```

1500    CONTINUE
C
C    end of NON-INFILL CASE
C
VCCN=VCONEC
IF ( IGOV .EQ. 1 ) VCCN = SQRT(VCONEC)

C
C    BEGIN SIMULATION FOR EITHER OF TWO CASES -
C    IGOV = 2,  NON-INFILL
C    IGOV = 1,  INFILL
C
C1500 CONTINUE

NY      = 1
NXNY    = NX * NY
NX      = VNX

C
IF ( IGOV .EQ. 2 ) WRITE (IW,1492)
1492 FORMAT ( 1H1
&          /// 10X,' -----'
&          / 10X,' N O N - I N F I L L S I M U L A T I O N'
&          / 10X,' -----'
&          / )
IF ( IGOV .EQ. 1 ) WRITE (IW,1493)
1493 FORMAT ( 1H1
&          /// 14X,' -----'
&          / 14X,' I N F I L L S I M U L A T I O N'
&          / 14X,' -----'
&          / )

C
CALL GENTUB ( IPAT9V, IGOV, VANIS, VTUBE, NX )

C
IF ( IGOV .EQ. 2 ) GO TO 2000

C
C PTT 9/91 IF USING LAYER MODEL OF CONTINUITY, TURN ON WELLS FOR
C INFILL CASE

IF (IKBM.EQ.1) THEN
DO 2501 J=1,NUMTUB
IPROD(J,ILAYER) = 0
IINJ(J,ILAYER) = 0
2501 CONTINUE
ENDIF

C PTT 10/91 ADD BACK INFILL LAYER KH
IF (IKBM.NE.0) THEN
TOTKH=TOTKH+(VH1(ILAYER)*VKX(ILAYER))
TOTH=TOTH+VH1(ILAYER)
ENDIF

VRATE = VRATE*2.

C PTT
IF (IKBM.GT.0 .AND. VRATE1.LT..00001) THEN
VRATE1=2*VRATE
GOTO 3000
ENDIF

```

```

      IF ( VRATE1 .LT. 0.00001 ) GO TO 1540
C
C      USER DID SPECIFY THE INFILL INJECTION RATE.  SO, COMPUTE
C      FIXED INJECTION RATES FOR EACH TUBE IN EACH LAYER
C
      DO 1535 I=1,NOTUBS
      VTUBE(I)=VRATE1*VTUBE(I)
      DO 1535 J=1,ILAYER
      VQW(I,J)= VTUBE(I)*VH1(J)*VKX(J)/TOTKH
1535 CONTINUE
      GO TO 3000
C
C      CALCULATE THE PRESSURE SPECIFICATIONS FOR INFILL CASE INJECTORS
C      IF THE USER DID NOT SPECIFY THE INFILL INJECTION RATE.  THIS
C      USES DATA FROM THE NON-INFILL CASE, WHERE THERE WERE NOTUBS
C      STREAM TUBES.
C
1540 DO 1590 J=1,ILAYER
      PWV=0
      DO 1550 I=1,NOTUBS
      PWV =PWV + VP1B(NX,I,J)
1550 CONTINUE
      PWV = PWV/NOTUBS
      DO 1560 I=1,NOTUBS
1560 VPWELL(I,J)= PWV + PWV*0.001
1590 CONTINUE
      GO TO 3000
C
C      NON-INFILL CASE.  COMPUTE FIXED INJECTION RATES FOR
C      EACH TUBE IN EACH LAYER
C
2000 CONTINUE

C PTT 9/91 HERE WE MUST ALLOCATE OVER NZ-1 FOR NON INFILL
C IF USING LAYER MODEL AND ADJUST KH PRODUCT

      IF(IKBM.EQ.1) THEN
        IL=ILAYER-1
      ELSE
        IL=ILAYER
      ENDIF

      DO 2200 I=1,NOTUBS
      VTUBE(I)=VRATE*VTUBE(I)
C      DO 2200 J=1,ILAYER
      DO 2200 J=1,IL
      VQW(I,J)= VTUBE(I)*VH1(J)*VKX(J)/TOTKH
2200 CONTINUE

C
C      SCALE UP THE CELL DIMENSIONS FROM THE STREAMTUBE CALCULATIONS
C      ON THE 'IGDMAX' BY 'JGDMAX' GRID TO THE ACTUAL PATTERN AREA
C
3000 CONTINUE
      VCCN = 0.0
      VLENG1 = SQRT(VAREA*43560.0/SGAREA/RSCALE)
      DO 3200 I=1,NOTUBS
      DO 3100 J=1,NX

```

```

      RLENG(J,I)=RLENG(J,I)*VLENG1
      RWIDE(J,I)=RWIDE(J,I)*VLENG1
3100 CONTINUE
3200 CONTINUE
C
      SLOPE = ALOG ( VCONEC ) / ( VDBWLS -VWD100 )
      VCCN = EXP ( SLOPE * ( SQRT(VDBWLS**2/2.0) - VWD100 ) )
      IF ( IGOV .EQ. 2 )    VCCN = VCONEC

      CALL RPTABL ( VCCN )
C
      RETURN
      END
      FUNCTION VALVAR(IPLOTVAR,I)
      INTEGER IPLOTVAR,I,ITEMP
      LOGICAL VALVAR
      ITEMP = MOD(IPLOTVAR,INT(2**(I+1)))
      ITEMP = ITEMP - MOD(ITEMP,INT(2**I))
      IF (ITEMP .NE. 0) THEN
        VALVAR = .TRUE.
      ELSE
        VALVAR = .FALSE.
      END IF
      RETURN
      END

```


APPENDIX Ia

IDPM INPUT/OUTPUT FOR IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

```

*****
*
*   S C I E N T I F I C   S O F T W A R E   *
*       -   I N T E R C O M P               *
*
*   •                                       *
*   INFILL DRILLING PREDICTION MODEL       *
*       (IDPM - RELEASE 1.2.0)             *
*
*****

```

```

IPDM DATA - VERSION 1.2 TEST: Verification Against SimBest II
IPDM DATA - VERSION 1.2 TEST: Verification Against SimBest II
0, 1, 1, 0, 0, 0.83
1, 4, 15, 1, .01, 1
80., 300.0, 1320., 0.95, 200., 400., .60, 0.90, 0.
.000003, 3000., 3000., -6500., 117.
64.00, 1.0001, .000003, .6, 0.8
32.00, 1.25, .00000735, 1.2, 300.
2., 2., .8, .2, .3, .24, 0.
1
.063, .65, 250.

```

I D P M CURRENT MAXIMUM PARAMETER VALUES

NUMBER OF TUBES PER LAYER.....	16
NUMBER OF GRID CELLS PER TUBE.....	15
NUMBER OF LAYERS.....	20
NUMBER OF TIMESTEPS IN RESERVOIR RUN..	5000
BLANK COMMON SIZE FOR RESERVOIR RUN...	10000
NUMBER OF YEARS FOR ECONOMIC ANALYSIS.	50

SPECIFIED PRINTOUT CONTROLS

RESERVOIR ARRAY OUTPUT CONTROL	0	IARRP
RESERVOIR ANALYSIS OUTPUT CONTROL	1	IANALP
STREAMTUBE OUTPUT CONTROL	1	ISTRMP
ECONOMIC ANALYSIS CONTROL(0-NO, 1-YES)	0	IECONR

RESERVOIR PROPERTIES OUTPUT

FORMATION DEPTH -- SUBSURFACE.....	-6500.0	FEET
FORMATION TEMPERATURE	117.0	DEG F
INDIVIDUAL PATTERN AREA	80.0	ACRES
KV/KH VERTICAL TO HORIZONTAL PERM.....	0.010	
KY/KX ANISOTROPIC VALUE (1.0-100.0)...	1.000	
DYKSTRA-PARSONS COEFFICIENT	0.83	VDP
PRESSURE AT FORMATION TOP	3000.0	PSIA
PORE VOLUME COMPRESSIBILITY	0.00000300	1/PSI

REFERENCE PRESSURE (POROSITY MEASURED)	3000.0	PSIA
NUMBER OF LAYERS	4	
STREAMTUBES PER LAYER	12	
NUMBER OF GRID CELLS PER STREAMTUBE...	15	
INFILL PATTERN (0=5-SPOT, 1=9-SPOT)...	1	

PROPERTIES BY LAYER

POROSITY	X-DIR PERM	NET PAY
0.0630	2.25	62.50
0.0630	0.25	62.50
0.0630	0.08	62.50
0.0630	0.02	62.50

WATER DENSITY AT STANDARD CONDITIONS..	64.00	LB/CUFT
WATER DENSITY AT RESERVOIR CONDITIONS..	63.99	LB/CUFT
WATER FORMATION VOLUME FACTOR.....	1.00	VOL/VOL
WATER COMPRESSIBILITY AT RES. COND....	0.00000300	1/PSI
WATER VISCOSITY AT RES. COND.....	0.60	CP

OIL DENSITY AT STANDARD CONDITIONS....	54.00	LB/CUFT
OIL GRAVITY	32.0	DEG API
OIL DENSITY AT RESERVOIR CONDITIONS...	43.20	LB/CUFT
OIL FORMATION VOLUME FACTOR.....	1.25	VOL/VOL
OIL COMPRESSIBILITY AT RES. COND.....	0.00000735	1/PSI
OIL VISCOSITY AT RES. COND.....	1.20	CP
SOLUTION GAS-OIL-RATIO	300.0	SCF/STB
GAS GRAVITY (AIR=1.0).....	0.800	

INJECTION RATE (NON-INFILL)	200.0	STBW/D
INJECTION RATE (INFILL, MAY BE 0.0) ..	400.0	STBW/D
WATER CUT AT INFILL (VCUT)	0.600	FRAC.
WATER CUT AT END (CUTMAX)	0.900	FRAC.
PLUG BACK AT INFILL (1=NO)	1	
(2=YES, IF LAYER W-CUT .GT. VCUT) .		

RELATIVE PERMEABILITY DATA

IRREDUCIBLE WATER SATURATION	0.300	SWC
RESIDUAL OIL SATN -- INPUT --	0.240	SORW
OIL RELATIVE PERM END-POINT	0.800	XKROE
WATER RELATIVE PERM END-POINT	0.200	XKRWE
OIL RELATIVE PERM CURVATURE	2.00	XNO
WATER RELATIVE PERM CURVATURE	2.00	XNW
(MAX) WELL DIST. FOR CONN.=100%	300.000	VWD100
WELL DIST. FOR CONN.=VCONEC	1320.000	VDBWLS
RESERVOIR CONNECTIVITY AT VDBWLS	0.950	VCONEC

RELATIVE PERMEABILITY TABLE
FOR CONNECTIVITY = 1.00000

WATER	OIL	WATER	FW	D (FW) /
-------	-----	-------	----	----------

SATURATN	KRO	KRW	(FR FLOW)	D (SW)
0.3000	0.8000	0.0000	0.000	
0.3230	0.7220	0.0005	0.001	0.060
0.3460	0.6480	0.0020	0.006	0.207
0.3690	0.5780	0.0045	0.015	0.400
0.3920	0.5120	0.0080	0.030	0.651
0.4150	0.4500	0.0125	0.053	0.971
0.4380	0.3920	0.0180	0.084	1.369
0.4610	0.3380	0.0245	0.127	1.848
0.4840	0.2880	0.0320	0.182	2.400
0.5070	0.2420	0.0405	0.251	2.998
0.5300	0.2000	0.0500	0.333	3.590
0.5530	0.1620	0.0605	0.428	4.097
0.5760	0.1280	0.0720	0.529	4.428
0.5990	0.0980	0.0845	0.633	4.502
0.6220	0.0720	0.0980	0.731	4.278
0.6450	0.0500	0.1125	0.818	3.776
0.6680	0.0320	0.1280	0.889	3.074
0.6910	0.0180	0.1445	0.941	2.282
0.7140	0.0080	0.1620	0.976	1.502
0.7370	0.0020	0.1805	0.994	0.808
0.7600	0.0000	0.2000	1.000	0.240

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

PROPERTIES BY LAYER

POROSITY	X-DIR PERM	NET PAY	SO	SW
0.0630	2.25	62.50	0.7000	0.3000
0.0630	0.25	62.50	0.7000	0.3000
0.0630	0.08	62.50	0.7000	0.3000
0.0630	0.02	62.50	0.7000	0.3000

NON - INFILL SIMULATION

SYMMETRY ELEMENT WITHIN 5-SPOT, BEFORE IN-FILL

ISOTROPIC PERMEABILITY CASE - 1/8

I
| \
| \
| \

I

I

I

```
*****
*   FRACTIONAL WELL RATES FOR TUBE CALCULATIONS   *
*           PRODUCER =  0.10000E+01                *
*           INJECTOR = -0.10000E+01                *
*****
*   INJECTOR AT COORD (  1, 65 )                    *
*   PRODUCER AT COORD ( 65,  1 )                    *
*****
```

```
*****
*   STREAM TUBES   *
*****
```

```
|1\
|19\
|35C\
|168C\
|149AC\
|1378BC\
|2457ABC\
|13679ABC\
|124689BCC\
|124578ABCC\
|1245689ABCC\
|12356789ABCC\
|12346789ABBCC\
|123456789ABCCC\
|1234567899ABCCC\
|1234567789AABCCC\
```


0.3460	0.6404	0.0022	0.007	0.232
0.3690	0.5673	0.0050	0.017	0.452
0.3920	0.4986	0.0089	0.034	0.742
0.4150	0.4343	0.0139	0.060	1.114
0.4380	0.3745	0.0199	0.096	1.578
0.4610	0.3191	0.0271	0.145	2.137
0.4840	0.2681	0.0355	0.209	2.772
0.5070	0.2216	0.0449	0.288	3.439
0.5300	0.1795	0.0554	0.382	4.062
0.5530	0.1418	0.0670	0.486	4.533
0.5760	0.1086	0.0798	0.595	4.743
0.5990	0.0798	0.0936	0.701	4.618
0.6220	0.0554	0.1086	0.797	4.152
0.6450	0.0355	0.1247	0.875	3.423
0.6680	0.0199	0.1418	0.934	2.557
0.6910	0.0089	0.1601	0.973	1.685
0.7140	0.0022	0.1795	0.994	0.904
0.7370	0.0000	0.2000	1.000	0.267
0.7600	0.0000	0.2216	1.000	0.000

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
(THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
(OF THE AREA OF THE PRE-INFILL 5-SPOT.)

IN - PLACE - VOLUMES

LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.13368E+06	0.71602E+05	0.23869E+06
2	1	0.13370E+06	0.71610E+05	0.23870E+06
3	1	0.13373E+06	0.71618E+05	0.23872E+06
4	1	0.13375E+06	0.71626E+05	0.23873E+06
1	2	0.10190E+06	0.54581E+05	0.18195E+06
2	2	0.10192E+06	0.54587E+05	0.18196E+06
3	2	0.10194E+06	0.54593E+05	0.18197E+06
4	2	0.10196E+06	0.54599E+05	0.18198E+06
1	3	0.10671E+06	0.57156E+05	0.19053E+06
2	3	0.10673E+06	0.57162E+05	0.19054E+06
3	3	0.10675E+06	0.57169E+05	0.19056E+06
4	3	0.10677E+06	0.57175E+05	0.19057E+06
1	4	0.87710E+05	0.46981E+05	0.15661E+06
2	4	0.87727E+05	0.46986E+05	0.15662E+06
3	4	0.87744E+05	0.46992E+05	0.15663E+06
4	4	0.87761E+05	0.46997E+05	0.15664E+06
1	5	0.74108E+05	0.39695E+05	0.13233E+06
2	5	0.74122E+05	0.39700E+05	0.13233E+06
3	5	0.74137E+05	0.39704E+05	0.13234E+06
4	5	0.74151E+05	0.39709E+05	0.13235E+06

1	6	0.71294E+05	0.38188E+05	0.12730E+06
2	6	0.71308E+05	0.38192E+05	0.12731E+06
3	6	0.71322E+05	0.38196E+05	0.12732E+06
4	6	0.71335E+05	0.38201E+05	0.12732E+06
1	7	0.69418E+05	0.37183E+05	0.12395E+06
2	7	0.69431E+05	0.37187E+05	0.12396E+06
3	7	0.69445E+05	0.37191E+05	0.12397E+06
4	7	0.69458E+05	0.37195E+05	0.12397E+06
1	8	0.65431E+05	0.35047E+05	0.11683E+06
2	8	0.65444E+05	0.35051E+05	0.11684E+06
3	8	0.65456E+05	0.35055E+05	0.11685E+06
4	8	0.65469E+05	0.35059E+05	0.11685E+06
1	9	0.59333E+05	0.31781E+05	0.10595E+06
2	9	0.59345E+05	0.31785E+05	0.10595E+06
3	9	0.59356E+05	0.31788E+05	0.10596E+06
4	9	0.59368E+05	0.31792E+05	0.10596E+06
1	10	0.57692E+05	0.30902E+05	0.10301E+06
2	10	0.57703E+05	0.30905E+05	0.10302E+06
3	10	0.57714E+05	0.30909E+05	0.10303E+06
4	10	0.57725E+05	0.30912E+05	0.10303E+06
1	11	0.60741E+05	0.32535E+05	0.10846E+06
2	11	0.60752E+05	0.32539E+05	0.10846E+06
3	11	0.60764E+05	0.32542E+05	0.10847E+06
4	11	0.60776E+05	0.32546E+05	0.10848E+06
1	12	0.72701E+05	0.38941E+05	0.12981E+06
2	12	0.72715E+05	0.38946E+05	0.12982E+06
3	12	0.72729E+05	0.38950E+05	0.12983E+06
4	12	0.72743E+05	0.38955E+05	0.12984E+06
TOTALS		0.38439E+07	0.20587E+07	0.68623E+07
(M-STB)		684.58	366.65	

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS	
0.4	138.2	138.246	1	1	
PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
15.15	0.9468E-11	25.00	2095.	0.1309E-08	3457.
CURRENT IN-PLACE-VOLUMES			MAXIMUM		
OIL (MSTB)	WATER (MSTB)		PRESSURE		
682.49	370.10		3430.2		
MATERIAL BALANCE ERROR					
OIL	WATER				
1.0000	1.0000				

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
0.8	276.5	138.246	2	2

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
17.91	0.4871E-05	25.00	4570.	0.6734E-03	6914.

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
680.02	373.56	3641.8

MATERIAL BALANCE ERROR	
OIL	WATER
1.0000	1.0000

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
13.6	4976.8	138.246	36	36

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
14.15	7.058	25.00	0.9393E+05	4006.	0.1244E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
590.59	487.05	4100.5

MATERIAL BALANCE ERROR	
OIL	WATER
0.99989	0.99998

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
17.8	6497.5	138.246	47	47

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
8.949	13.61	25.00	0.1097E+06	0.2209E+05	0.1625E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
574.78	507.02	4069.7

MATERIAL BALANCE ERROR	
------------------------	--

OIL	WATER
0.99983	1.0001

CONTINUATION OF WATERFLOOD AFTER WATER CUT FOR INFILL
=====

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
18.2	6635.8	138.246	1	48

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
8.778	13.74	25.00	0.1109E+06	0.2399E+05	0.1659E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
573.56	508.58	4067.8

MATERIAL BALANCE ERROR	
OIL	WATER
0.99983	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
26.9	9815.4	138.246	24	71

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
4.573	19.33	25.00	0.1301E+06	0.7943E+05	0.2454E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
554.27	532.91	4230.8

MATERIAL BALANCE ERROR	
OIL	WATER
0.99959	1.0008

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
40.5	14792.3	138.246	60	107

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
3.952	20.07	25.00	0.1510E+06	0.1779E+06	0.3699E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
533.02	559.45	4186.2

MATERIAL BALANCE ERROR	
OIL	WATER
0.99910	1.0022

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
53.7	19630.9	138.246	95	142

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
3.619	20.48	25.00	0.1692E+06	0.2760E+06	0.4909E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
514.50	582.61	4169.5

MATERIAL BALANCE ERROR	
OIL	WATER
0.99874	1.0032

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
67.0	24469.5	138.246	130	177

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
3.287	20.90	25.00	0.1860E+06	0.3761E+06	0.6119E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
497.60	603.81	4163.9

MATERIAL BALANCE ERROR	
OIL	WATER
0.99845	1.0040

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
80.6	29446.4	138.246	166	213

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
2.758	21.55	25.00	0.2011E+06	0.4817E+06	0.7363E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
482.34	622.97	4163.5

MATERIAL BALANCE ERROR	
OIL	WATER
0.99826	1.0047

TIME STEPS EXECUTED....	235
GRID-CELL-TIME-STEPS...	676800

IN F I L L S I M U L A T I O N

SYMMETRY ELEMENT AFTER 9-SPOT IN-FILL

ISOTROPIC PERMEABILITY CASE - 1/8

I

P

I

```
*****
*   FRACTIONAL WELL RATES FOR TUBE CALCULATIONS   *
*   NEW PRODUCER =    0.66600E+00                  *
*   OLD PRODUCER =    0.33400E+00                  *
*   INJECTOR =   -0.10000E+01                      *
*****
*   INJECTOR AT COORD (  1, 65 )                  *
*   PRODUCER AT COORD ( 65,  1 )                  *
*   PRODUCER AT COORD (  1,  1 )                  *
*****
```

```
*****
*   STREAM TUBES   *
*****
```

```
|1\
|1B\
|27C\
|158C\
|139AC\
|1468BC\
|23679BC\
|13479BBC\
|135789ACC\
|124578ABCC\
|1345689ABCC\
|12356789ABCC\
|12346789ABBCC\
|123456789ABCCC\
|1234567899ABCCC\
|1234567789ABBCCC\
|12345567899ABBCCC\
|12344567889AABBCCC\
|113345677899AABCCCC\
|113345667889AABBCCCC\
|1123455677899AABBCCCC\
|11234456778899AABBCCCC\
|112344556778899AABBCCCC\
|112344556778899AABBCCCC\
|1123345566778899AABBCCCC\
```


0.5760	0.1159	0.0767	0.570	4.634
0.5990	0.0866	0.0901	0.675	4.591
0.6220	0.0615	0.1044	0.772	4.221
0.6450	0.0408	0.1199	0.855	3.577
0.6680	0.0243	0.1364	0.918	2.768
0.6910	0.0120	0.1540	0.962	1.918
0.7140	0.0040	0.1727	0.988	1.131
0.7370	0.0003	0.1924	0.999	0.467
0.7600	0.0000	0.2132	1.000	0.033

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
(THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
(OF THE AREA OF THE PRE-INFILL 5-SPOT.)

IN - PLACE - VOLUMES

LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.13752E+05	0.41670E+05	0.58723E+05
2	1	0.25764E+05	0.26668E+05	0.58717E+05
3	1	0.30780E+05	0.20390E+05	0.58708E+05
4	1	0.32493E+05	0.18234E+05	0.58700E+05
1	2	0.13893E+05	0.41494E+05	0.58723E+05
2	2	0.27491E+05	0.24489E+05	0.58708E+05
3	2	0.31336E+05	0.19669E+05	0.58698E+05
4	2	0.32603E+05	0.18071E+05	0.58691E+05
1	3	0.20160E+05	0.59698E+05	0.84717E+05
2	3	0.40143E+05	0.34700E+05	0.84692E+05
3	3	0.45312E+05	0.28217E+05	0.84679E+05
4	3	0.47043E+05	0.26038E+05	0.84672E+05
1	4	0.20625E+05	0.59965E+05	0.85559E+05
2	4	0.41652E+05	0.33650E+05	0.85528E+05
3	4	0.46307E+05	0.27805E+05	0.85515E+05
4	4	0.47634E+05	0.26131E+05	0.85508E+05
1	5	0.22374E+05	0.64527E+05	0.92279E+05
2	5	0.45039E+05	0.36150E+05	0.92241E+05
3	5	0.49953E+05	0.29975E+05	0.92224E+05
4	5	0.51378E+05	0.28175E+05	0.92216E+05
1	6	0.26588E+05	0.75227E+05	0.10821E+06
2	6	0.54109E+05	0.40771E+05	0.10817E+06
3	6	0.59017E+05	0.34602E+05	0.10815E+06
4	6	0.60354E+05	0.32910E+05	0.10814E+06
1	7	0.34141E+05	0.94354E+05	0.13673E+06
2	7	0.68841E+05	0.50914E+05	0.13667E+06
3	7	0.74690E+05	0.43558E+05	0.13665E+06
4	7	0.76278E+05	0.41552E+05	0.13664E+06
1	8	0.53144E+05	0.12810E+06	0.19415E+06
2	8	0.10167E+06	0.67388E+05	0.19409E+06

3	8	0.10714E+06	0.60503E+05	0.19406E+06
4	8	0.10855E+06	0.58720E+05	0.19405E+06
1	9	0.87867E+05	0.15112E+06	0.26054E+06
2	9	0.13796E+06	0.88435E+05	0.26047E+06
3	9	0.14414E+06	0.80656E+05	0.26045E+06
4	9	0.14574E+06	0.78635E+05	0.26044E+06
1	10	0.58555E+05	0.14647E+06	0.21928E+06
2	10	0.11475E+06	0.76114E+05	0.21919E+06
3	10	0.12135E+06	0.67799E+05	0.21917E+06
4	10	0.12263E+06	0.66186E+05	0.21916E+06
1	11	0.47590E+05	0.13333E+06	0.19246E+06
2	11	0.98837E+05	0.69168E+05	0.19238E+06
3	11	0.10593E+06	0.60251E+05	0.19236E+06
4	11	0.10751E+06	0.58261E+05	0.19235E+06
1	12	0.56136E+05	0.15659E+06	0.22639E+06
2	12	0.11811E+06	0.79005E+05	0.22630E+06
3	12	0.12490E+06	0.70466E+05	0.22628E+06
4	12	0.12645E+06	0.68524E+05	0.22628E+06
TOTALS		0.32287E+07	0.28453E+07	0.68687E+07
(M-STB)		575.01	506.74	

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
18.0	6566.7	69.123	1	48

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
16.10	33.29	50.01	1113.	2301.	3457.
(8.446	26.00	- FROM WELL AT (1, 1))			
(7.656	7.293	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
573.84	507.96	5491.8

MATERIAL BALANCE ERROR	
OIL	WATER
0.99989	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
18.2	6635.8	69.123	2	49

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION

	13.66	33.59	50.01	2057.	4623.	6914.
(	6.590	25.77	- FROM WELL AT (	1, 1)	)	
(	7.073	7.820	- FROM WELL AT (	65, 1)	)	

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
572.90	509.09	5569.9

MATERIAL BALANCE ERROR	
OIL	WATER
0.99990	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
24.6	8986.0	69.123	36	83

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
7.892	40.20	50.01	0.2570E+05	0.9268E+05	0.1244E+06
(	4.677	27.64	- FROM WELL AT (	1, 1)	)
(	3.215	12.56	- FROM WELL AT (	65, 1)	)

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
549.10	538.78	5588.3

MATERIAL BALANCE ERROR	
OIL	WATER
0.99963	1.0006

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
31.2	11405.3	69.123	71	118

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
6.685	41.66	50.01	0.4326E+05	0.1918E+06	0.2454E+06
(	3.971	28.51	- FROM WELL AT (	1, 1)	)
(	2.715	13.16	- FROM WELL AT (	65, 1)	)

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
531.37	560.97	5671.4

MATERIAL BALANCE ERROR	
OIL	WATER
0.99932	1.0012

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
38.0	13893.7	69.123	107	154

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
5.927	42.61	50.01	0.5882E+05	0.2968E+06	0.3699E+06
(3.428	29.18	- FROM WELL AT (1, 1))			
(2.499	13.43	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
515.66	580.64	5601.4

MATERIAL BALANCE ERROR	
OIL	WATER
0.99905	1.0016

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
44.7	16313.0	69.123	142	189

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
5.272	43.43	50.01	0.7239E+05	0.4008E+06	0.4909E+06
(2.917	29.83	- FROM WELL AT (1, 1))			
(2.355	13.60	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
501.97	597.80	5561.3

MATERIAL BALANCE ERROR	
OIL	WATER
0.99884	1.0020

TIME STEPS EXECUTED....	160
GRID-CELL-TIME-STEPS...	460800

PERFORMANCE VERSUS TIME FOR NON-INFILL

=====

TIME DAYS	OIL RATE STB/D	WATER RATE STB/D	CUMOIL MSTB	WCUT FRAC.	PV INJ FRAC.	OIL REC %OIP
138.25	15.15	0.9468E-11	2.095	0.000	0.00	0.3
276.49	17.91	0.4871E-05	4.570	0.000	0.01	0.7
414.74	18.77	0.1074E-04	7.165	0.000	0.01	1.0
552.98	19.21	0.1169E-04	9.821	0.000	0.01	1.4
691.23	19.36	0.3668E-04	12.50	0.000	0.01	1.8
829.47	19.51	0.3241E-04	15.19	0.000	0.02	2.2
967.72	19.59	0.3397E-04	17.90	0.000	0.02	2.6
1105.97	19.67	0.3488E-04	20.62	0.000	0.02	3.0
1244.21	19.69	0.4979E-04	23.34	0.000	0.03	3.4
1382.46	19.74	0.5537E-04	26.07	0.000	0.03	3.8
1520.70	19.77	0.6221E-04	28.80	0.000	0.03	4.2
1658.95	19.81	0.5681E-04	31.54	0.000	0.03	4.6
1797.19	19.80	0.5364E-04	34.28	0.000	0.04	5.0
1935.44	19.78	0.6552E-04	37.01	0.000	0.04	5.4
2073.69	19.82	0.7129E-04	39.75	0.000	0.04	5.8
2211.93	19.81	0.6811E-04	42.49	0.000	0.05	6.2
2350.18	19.85	0.1007E-03	45.24	0.000	0.05	6.6
2488.42	19.84	0.8793E-04	47.98	0.000	0.05	7.0
2626.67	19.83	0.9590E-04	50.72	0.000	0.05	7.4
2764.91	19.84	0.9537E-04	53.46	0.000	0.06	7.8
2903.16	19.85	0.8521E-04	56.21	0.000	0.06	8.2
3041.41	19.88	0.7757E-04	58.96	0.000	0.06	8.6
3179.65	19.85	0.6805E-04	61.70	0.000	0.07	9.0
3317.90	19.83	0.6939E-04	64.44	0.000	0.07	9.4
3456.14	19.79	0.8674E-04	67.18	0.000	0.07	9.8
3594.39	19.81	0.9700E-04	69.92	0.000	0.07	10.2
3732.63	19.74	0.9506E-04	72.65	0.000	0.08	10.6
3870.88	19.67	0.1359E-03	75.37	0.000	0.08	11.0
4009.12	19.57	0.4731E-01	78.07	0.002	0.08	11.4
4147.37	19.13	0.7110	80.72	0.036	0.08	11.8
4285.62	17.84	2.356	83.18	0.117	0.09	12.2
4423.86	16.61	3.837	85.48	0.188	0.09	12.5
4562.11	16.25	4.280	87.73	0.208	0.09	12.8
4700.35	15.65	4.945	89.89	0.240	0.10	13.1
4838.60	15.10	5.741	91.98	0.276	0.10	13.4
4976.84	14.15	7.058	93.93	0.333	0.10	13.7
5115.09	12.63	9.083	95.68	0.418	0.10	14.0
5253.33	11.60	10.39	97.28	0.472	0.11	14.2
5391.58	10.91	11.27	98.79	0.508	0.11	14.4
5529.83	10.58	11.65	100.3	0.524	0.11	14.7
5668.07	10.39	11.87	101.7	0.533	0.12	14.9
5806.32	10.25	12.00	103.1	0.539	0.12	15.1
5944.56	10.17	12.16	104.5	0.545	0.12	15.3
6082.81	9.950	12.43	105.9	0.555	0.12	15.5
6221.05	9.531	12.95	107.2	0.576	0.13	15.7
6359.30	9.159	13.38	108.5	0.594	0.13	15.9
6497.55	8.949	13.61	109.7	0.603	0.13	16.0
6635.79	8.778	13.74	110.9	0.610	0.14	16.2
6774.04	8.681	13.86	112.1	0.615	0.14	16.4
6912.28	8.586	13.98	113.3	0.619	0.14	16.6
7050.53	8.436	14.22	114.5	0.628	0.14	16.7
7188.77	8.097	14.71	115.6	0.645	0.15	16.9
7327.02	7.619	15.30	116.6	0.668	0.15	17.0
7465.26	7.189	15.83	117.6	0.688	0.15	17.2
7603.51	6.832	16.31	118.6	0.705	0.16	17.3
7741.76	6.573	16.67	119.5	0.717	0.16	17.5
7880.00	6.395	16.96	120.4	0.726	0.16	17.6
8018.25	6.065	17.43	121.2	0.742	0.16	17.7

8156.49	5.643	17.96	122.0	0.761	0.17	17.8
8294.74	5.347	18.36	122.7	0.774	0.17	17.9
8432.98	5.177	18.58	123.5	0.782	0.17	18.0
8571.23	5.067	18.74	124.2	0.787	0.18	18.1
8709.48	4.965	18.86	124.8	0.792	0.18	18.2
8847.72	4.914	18.94	125.5	0.794	0.18	18.3
8985.97	4.828	19.03	126.2	0.798	0.18	18.4
9124.21	4.787	19.09	126.8	0.799	0.19	18.5
9262.46	4.728	19.15	127.5	0.802	0.19	18.6
9400.71	4.694	19.20	128.1	0.804	0.19	18.7
9538.95	4.646	19.25	128.8	0.806	0.20	18.8
9677.20	4.613	19.29	129.4	0.807	0.20	18.9
9815.45	4.573	19.33	130.1	0.809	0.20	19.0
9953.69	4.545	19.37	130.7	0.810	0.20	19.1
10091.94	4.521	19.41	131.3	0.811	0.21	19.2
10230.18	4.482	19.44	131.9	0.813	0.21	19.3
10368.43	4.470	19.46	132.6	0.813	0.21	19.4
10506.68	4.428	19.50	133.2	0.815	0.21	19.5
10644.92	4.411	19.52	133.8	0.816	0.22	19.6
10783.17	4.388	19.55	134.4	0.817	0.22	19.6
10921.41	4.365	19.58	135.0	0.818	0.22	19.7
11059.66	4.337	19.60	135.6	0.819	0.23	19.8
11197.91	4.318	19.63	136.2	0.820	0.23	19.9
11336.15	4.305	19.65	136.8	0.820	0.23	20.0
11474.40	4.287	19.68	137.4	0.821	0.23	20.1
11612.64	4.277	19.70	138.0	0.822	0.24	20.2
11750.89	4.244	19.72	138.5	0.823	0.24	20.2
11889.14	4.231	19.74	139.1	0.823	0.24	20.3
12027.38	4.225	19.76	139.7	0.824	0.25	20.4
12165.63	4.204	19.78	140.3	0.825	0.25	20.5
12303.88	4.194	19.79	140.9	0.825	0.25	20.6
12442.12	4.174	19.82	141.5	0.826	0.25	20.7
12580.37	4.162	19.83	142.0	0.827	0.26	20.8
12718.61	4.151	19.85	142.6	0.827	0.26	20.8
12856.86	4.134	19.87	143.2	0.828	0.26	20.9
12995.11	4.109	19.89	143.7	0.829	0.27	21.0
13133.35	4.091	19.90	144.3	0.830	0.27	21.1
13271.60	4.079	19.93	144.9	0.830	0.27	21.2
13409.84	4.072	19.93	145.4	0.830	0.27	21.3
13548.09	4.074	19.95	146.0	0.830	0.28	21.3
13686.34	4.051	19.97	146.6	0.831	0.28	21.4
13824.58	4.042	19.98	147.1	0.832	0.28	21.5
13962.83	4.032	19.99	147.7	0.832	0.29	21.6
14101.07	4.010	20.01	148.2	0.833	0.29	21.7
14239.32	4.008	20.02	148.8	0.833	0.29	21.7
14377.57	3.984	20.04	149.3	0.834	0.29	21.8
14515.81	3.970	20.05	149.9	0.835	0.30	21.9
14654.06	3.968	20.06	150.4	0.835	0.30	22.0
14792.30	3.952	20.07	151.0	0.835	0.30	22.1
14930.55	3.942	20.09	151.5	0.836	0.31	22.1
15068.80	3.930	20.11	152.1	0.836	0.31	22.2
15207.04	3.922	20.11	152.6	0.837	0.31	22.3
15345.29	3.918	20.13	153.2	0.837	0.31	22.4
15483.54	3.907	20.14	153.7	0.838	0.32	22.5
15621.78	3.887	20.16	154.2	0.838	0.32	22.5
15760.03	3.882	20.17	154.8	0.839	0.32	22.6
15898.27	3.878	20.18	155.3	0.839	0.33	22.7
16036.52	3.861	20.19	155.8	0.839	0.33	22.8
16174.77	3.860	20.20	156.4	0.840	0.33	22.9
16313.01	3.837	20.22	156.9	0.841	0.33	22.9

16451.26	3.833	20.22	157.4	0.841	0.34	23.0
16589.50	3.805	20.24	158.0	0.842	0.34	23.1
16727.75	3.818	20.24	158.5	0.841	0.34	23.2
16866.00	3.786	20.27	159.0	0.843	0.35	23.2
17004.24	3.796	20.27	159.5	0.842	0.35	23.3
17142.49	3.783	20.28	160.1	0.843	0.35	23.4
17280.73	3.756	20.29	160.6	0.844	0.35	23.5
17418.98	3.764	20.30	161.1	0.844	0.36	23.5
17557.23	3.747	20.32	161.6	0.844	0.36	23.6
17695.47	3.752	20.33	162.1	0.844	0.36	23.7
17833.72	3.740	20.34	162.6	0.845	0.36	23.8
17971.96	3.729	20.35	163.2	0.845	0.37	23.8
18110.21	3.710	20.37	163.7	0.846	0.37	23.9
18248.46	3.720	20.37	164.2	0.846	0.37	24.0
18386.70	3.694	20.38	164.7	0.847	0.38	24.1
18524.95	3.692	20.39	165.2	0.847	0.38	24.1
18663.20	3.673	20.41	165.7	0.847	0.38	24.2
18801.44	3.676	20.41	166.2	0.847	0.38	24.3
18939.69	3.662	20.43	166.7	0.848	0.39	24.4
19077.93	3.654	20.44	167.2	0.848	0.39	24.4
19216.18	3.647	20.45	167.7	0.849	0.39	24.5
19354.43	3.643	20.45	168.2	0.849	0.40	24.6
19492.67	3.629	20.48	168.7	0.849	0.40	24.7
19630.92	3.619	20.48	169.2	0.850	0.40	24.7
19769.16	3.614	20.49	169.7	0.850	0.40	24.8
19907.41	3.604	20.50	170.2	0.850	0.41	24.9
20045.66	3.588	20.51	170.7	0.851	0.41	25.0
20183.90	3.589	20.52	171.2	0.851	0.41	25.0
20322.15	3.577	20.53	171.7	0.852	0.42	25.1
20460.39	3.578	20.54	172.2	0.852	0.42	25.2
20598.64	3.557	20.56	172.7	0.852	0.42	25.2
20736.89	3.547	20.57	173.2	0.853	0.42	25.3
20875.13	3.545	20.58	173.7	0.853	0.43	25.4
21013.38	3.521	20.59	174.2	0.854	0.43	25.5
21151.63	3.522	20.60	174.7	0.854	0.43	25.5
21289.87	3.511	20.61	175.2	0.854	0.44	25.6
21428.12	3.507	20.62	175.6	0.855	0.44	25.7
21566.36	3.497	20.64	176.1	0.855	0.44	25.7
21704.61	3.485	20.64	176.6	0.856	0.44	25.8
21842.86	3.475	20.66	177.1	0.856	0.45	25.9
21981.10	3.480	20.66	177.6	0.856	0.45	26.0
22119.35	3.446	20.69	178.0	0.857	0.45	26.0
22257.59	3.439	20.69	178.5	0.857	0.46	26.1
22395.84	3.437	20.71	179.0	0.858	0.46	26.2
22534.09	3.430	20.72	179.5	0.858	0.46	26.2
22672.33	3.410	20.73	179.9	0.859	0.46	26.3
22810.58	3.407	20.74	180.4	0.859	0.47	26.4
22948.82	3.398	20.75	180.9	0.859	0.47	26.4
23087.07	3.388	20.77	181.4	0.860	0.47	26.5
23225.32	3.373	20.78	181.8	0.860	0.48	26.6
23363.56	3.374	20.79	182.3	0.860	0.48	26.6
23501.81	3.364	20.81	182.7	0.861	0.48	26.7
23640.05	3.336	20.82	183.2	0.862	0.48	26.8
23778.30	3.346	20.83	183.7	0.862	0.49	26.8
23916.55	3.318	20.85	184.1	0.863	0.49	26.9
24054.79	3.324	20.85	184.6	0.863	0.49	27.0
24193.04	3.301	20.88	185.0	0.863	0.49	27.0
24331.29	3.305	20.88	185.5	0.863	0.50	27.1
24469.53	3.287	20.90	186.0	0.864	0.50	27.2
24607.78	3.285	20.91	186.4	0.864	0.50	27.2

24746.02	3.259	20.93	186.9	0.865	0.51	27.3
24884.27	3.250	20.93	187.3	0.866	0.51	27.4
25022.52	3.245	20.96	187.8	0.866	0.51	27.4
25160.76	3.232	20.96	188.2	0.866	0.51	27.5
25299.01	3.213	20.97	188.7	0.867	0.52	27.6
25437.25	3.206	20.98	189.1	0.867	0.52	27.6
25575.50	3.199	21.01	189.5	0.868	0.52	27.7
25713.75	3.182	21.02	190.0	0.869	0.53	27.8
25851.99	3.169	21.04	190.4	0.869	0.53	27.8
25990.24	3.170	21.05	190.9	0.869	0.53	27.9
26128.48	3.154	21.07	191.3	0.870	0.53	28.0
26266.73	3.136	21.08	191.7	0.870	0.54	28.0
26404.98	3.130	21.09	192.2	0.871	0.54	28.1
26543.22	3.108	21.11	192.6	0.872	0.54	28.1
26681.47	3.090	21.14	193.0	0.872	0.55	28.2
26819.71	3.079	21.15	193.4	0.873	0.55	28.3
26957.96	3.059	21.17	193.9	0.874	0.55	28.3
27096.21	3.042	21.20	194.3	0.874	0.55	28.4
27234.45	3.029	21.21	194.7	0.875	0.56	28.5
27372.70	3.013	21.24	195.1	0.876	0.56	28.5
27510.95	3.002	21.25	195.5	0.876	0.56	28.6
27649.19	2.977	21.28	195.9	0.877	0.57	28.6
27787.44	2.966	21.30	196.4	0.878	0.57	28.7
27925.68	2.946	21.32	196.8	0.879	0.57	28.8
28063.93	2.927	21.35	197.2	0.879	0.57	28.8
28202.18	2.904	21.36	197.6	0.880	0.58	28.9
28340.42	2.882	21.39	198.0	0.881	0.58	28.9
28478.67	2.880	21.41	198.4	0.881	0.58	29.0
28616.91	2.866	21.43	198.8	0.882	0.59	29.0
28755.16	2.844	21.45	199.2	0.883	0.59	29.1
28893.41	2.830	21.48	199.5	0.884	0.59	29.2
29031.65	2.811	21.49	199.9	0.884	0.59	29.2
29169.90	2.792	21.52	200.3	0.885	0.60	29.3
29308.14	2.779	21.53	200.7	0.886	0.60	29.3
29446.39	2.758	21.55	201.1	0.887	0.60	29.4
29584.64	2.753	21.57	201.5	0.887	0.61	29.4
29722.88	2.735	21.59	201.8	0.888	0.61	29.5
29861.13	2.718	21.61	202.2	0.888	0.61	29.6
29999.38	2.710	21.63	202.6	0.889	0.61	29.6
30137.62	2.681	21.65	203.0	0.890	0.62	29.7
30275.87	2.682	21.66	203.3	0.890	0.62	29.7
30414.11	2.667	21.68	203.7	0.890	0.62	29.8
30552.36	2.641	21.70	204.1	0.892	0.63	29.8
30690.61	2.643	21.72	204.4	0.892	0.63	29.9
30828.85	2.620	21.74	204.8	0.892	0.63	29.9
30967.10	2.610	21.76	205.2	0.893	0.63	30.0
31105.34	2.598	21.78	205.5	0.893	0.64	30.0
31243.59	2.569	21.79	205.9	0.895	0.64	30.1
31381.84	2.571	21.81	206.2	0.895	0.64	30.1
31520.08	2.531	21.83	206.6	0.896	0.64	30.2
31658.33	2.532	21.85	206.9	0.896	0.65	30.2
31796.57	2.518	21.87	207.3	0.897	0.65	30.3
31934.82	2.493	21.90	207.6	0.898	0.65	30.3
32073.07	2.481	21.90	208.0	0.898	0.66	30.4
32211.31	2.472	21.94	208.3	0.899	0.66	30.4
32349.56	2.443	21.94	208.6	0.900	0.66	30.5
32487.80	2.426	21.98	209.0	0.901	0.66	30.5

PERFORMANCE VERSUS TIME FOR INFILL

TIME DAYS	OIL RATE STB/D	WATER RATE STB/D	CUMOIL MSTB	WCUT FRAC.	PV INJ FRAC.	OIL REC %OOIP
6497.55	3.299	25.29	109.7	0.885	0.13	
6566.67	16.10	33.29	110.8	0.674	0.14	16.2
6635.79	13.66	33.59	111.8	0.711	0.14	16.3
6704.91	13.13	33.89	112.7	0.721	0.14	16.5
6774.04	12.80	34.16	113.6	0.727	0.14	16.6
6843.16	12.65	34.28	114.4	0.731	0.15	16.7
6912.28	12.44	34.51	115.3	0.735	0.15	16.8
6981.41	12.24	34.72	116.1	0.739	0.15	17.0
7050.53	12.05	34.93	117.0	0.743	0.16	17.1
7119.65	12.00	35.01	117.8	0.745	0.16	17.2
7188.78	11.85	35.16	118.6	0.748	0.16	17.3
7257.90	11.75	35.28	119.4	0.750	0.16	17.5
7327.02	11.59	35.45	120.2	0.754	0.17	17.6
7396.15	11.46	35.60	121.0	0.756	0.17	17.7
7465.27	11.31	35.78	121.8	0.760	0.17	17.8
7534.39	11.17	35.99	122.6	0.763	0.18	17.9
7603.51	10.95	36.30	123.3	0.768	0.18	18.0
7672.64	10.63	36.73	124.1	0.776	0.18	18.1
7741.76	10.23	37.25	124.8	0.785	0.18	18.2
7810.88	9.804	37.77	125.5	0.794	0.19	18.3
7880.01	9.467	38.21	126.1	0.801	0.19	18.4
7949.13	9.206	38.55	126.7	0.807	0.19	18.5
8018.25	9.029	38.77	127.4	0.811	0.20	18.6
8087.38	8.872	38.96	128.0	0.815	0.20	18.7
8156.50	8.732	39.14	128.6	0.818	0.20	18.8
8225.62	8.630	39.27	129.2	0.820	0.20	18.9
8294.74	8.564	39.37	129.8	0.821	0.21	19.0
8363.87	8.480	39.49	130.4	0.823	0.21	19.1
8432.99	8.361	39.61	130.9	0.826	0.21	19.1
8502.11	8.299	39.68	131.5	0.827	0.21	19.2
8571.24	8.221	39.79	132.1	0.829	0.22	19.3
8640.36	8.146	39.88	132.6	0.830	0.22	19.4
8709.48	8.091	39.93	133.2	0.832	0.22	19.5
8778.61	8.045	40.01	133.8	0.833	0.23	19.5
8847.73	7.989	40.09	134.3	0.834	0.23	19.6
8916.85	7.941	40.13	134.9	0.835	0.23	19.7
8985.97	7.892	40.20	135.4	0.836	0.23	19.8
9055.10	7.833	40.26	135.9	0.837	0.24	19.9
9124.22	7.793	40.32	136.5	0.838	0.24	19.9
9193.34	7.767	40.36	137.0	0.839	0.24	20.0
9262.47	7.723	40.41	137.6	0.840	0.25	20.1
9331.59	7.667	40.46	138.1	0.841	0.25	20.2
9400.71	7.628	40.51	138.6	0.842	0.25	20.3
9469.84	7.599	40.57	139.1	0.842	0.25	20.3
9538.96	7.575	40.58	139.7	0.843	0.26	20.4
9608.08	7.514	40.64	140.2	0.844	0.26	20.5
9677.21	7.487	40.69	140.7	0.845	0.26	20.6
9746.33	7.457	40.71	141.2	0.845	0.27	20.6
9815.45	7.426	40.75	141.7	0.846	0.27	20.7
9884.57	7.388	40.80	142.2	0.847	0.27	20.8
9953.70	7.369	40.83	142.7	0.847	0.27	20.9
10022.82	7.329	40.87	143.3	0.848	0.28	20.9
10091.94	7.318	40.89	143.8	0.848	0.28	21.0
10161.07	7.282	40.92	144.3	0.849	0.28	21.1
10230.19	7.249	40.95	144.8	0.850	0.29	21.2
10299.31	7.220	40.99	145.3	0.850	0.29	21.2

10368.44	7.211	41.00	145.8	0.850	0.29	21.3
10437.56	7.173	41.05	146.3	0.851	0.29	21.4
10506.68	7.157	41.07	146.8	0.852	0.30	21.4
10575.80	7.094	41.14	147.2	0.853	0.30	21.5
10644.93	7.106	41.14	147.7	0.853	0.30	21.6
10714.05	7.063	41.20	148.2	0.854	0.31	21.7
10783.17	7.024	41.25	148.7	0.854	0.31	21.7
10852.30	7.000	41.27	149.2	0.855	0.31	21.8
10921.42	6.982	41.31	149.7	0.855	0.31	21.9
10990.54	6.922	41.37	150.2	0.857	0.32	21.9
11059.67	6.885	41.42	150.6	0.857	0.32	22.0
11128.79	6.841	41.49	151.1	0.858	0.32	22.1
11197.91	6.792	41.53	151.6	0.859	0.33	22.2
11267.04	6.771	41.57	152.0	0.860	0.33	22.2
11336.16	6.720	41.62	152.5	0.861	0.33	22.3
11405.28	6.685	41.66	153.0	0.862	0.33	22.4
11474.40	6.644	41.71	153.4	0.863	0.34	22.4
11543.53	6.625	41.75	153.9	0.863	0.34	22.5
11612.65	6.579	41.77	154.3	0.864	0.34	22.6
11681.77	6.580	41.80	154.8	0.864	0.34	22.6
11750.90	6.584	41.80	155.2	0.864	0.35	22.7
11820.02	6.545	41.82	155.7	0.865	0.35	22.8
11889.14	6.523	41.86	156.2	0.865	0.35	22.8
11958.27	6.495	41.89	156.6	0.866	0.36	22.9
12027.39	6.452	41.93	157.0	0.867	0.36	23.0
12096.51	6.458	41.93	157.5	0.867	0.36	23.0
12165.63	6.441	41.96	157.9	0.867	0.36	23.1
12234.76	6.429	41.98	158.4	0.867	0.37	23.1
12303.88	6.395	42.02	158.8	0.868	0.37	23.2
12373.00	6.373	42.04	159.3	0.868	0.37	23.3
12442.13	6.339	42.08	159.7	0.869	0.38	23.3
12511.25	6.334	42.11	160.1	0.869	0.38	23.4
12580.37	6.269	42.16	160.6	0.871	0.38	23.5
12649.50	6.263	42.19	161.0	0.871	0.38	23.5
12718.62	6.231	42.23	161.4	0.871	0.39	23.6
12787.74	6.196	42.26	161.9	0.872	0.39	23.7
12856.87	6.192	42.28	162.3	0.872	0.39	23.7
12925.99	6.148	42.33	162.7	0.873	0.40	23.8
12995.11	6.122	42.37	163.1	0.874	0.40	23.8
13064.23	6.109	42.38	163.6	0.874	0.40	23.9
13133.36	6.081	42.43	164.0	0.875	0.40	24.0
13202.48	6.030	42.47	164.4	0.876	0.41	24.0
13271.60	6.024	42.49	164.8	0.876	0.41	24.1
13340.73	6.010	42.51	165.2	0.876	0.41	24.1
13409.85	5.980	42.54	165.6	0.877	0.42	24.2
13478.97	5.961	42.56	166.1	0.877	0.42	24.3
13548.10	5.954	42.57	166.5	0.877	0.42	24.3
13617.22	5.972	42.54	166.9	0.877	0.42	24.4
13686.34	5.936	42.58	167.3	0.878	0.43	24.4
13755.46	5.931	42.60	167.7	0.878	0.43	24.5
13824.59	5.935	42.61	168.1	0.878	0.43	24.6
13893.71	5.927	42.61	168.5	0.878	0.44	24.6
13962.83	5.882	42.66	168.9	0.879	0.44	24.7
14031.96	5.852	42.68	169.3	0.879	0.44	24.7
14101.08	5.829	42.71	169.7	0.880	0.44	24.8
14170.20	5.834	42.73	170.1	0.880	0.45	24.9
14239.33	5.824	42.72	170.5	0.880	0.45	24.9
14308.45	5.809	42.75	170.9	0.880	0.45	25.0
14377.57	5.780	42.77	171.3	0.881	0.46	25.0
14446.70	5.791	42.78	171.7	0.881	0.46	25.1

14515.82	5.751	42.81	172.1	0.882	0.46	25.2
14584.94	5.745	42.82	172.5	0.882	0.46	25.2
14654.06	5.741	42.83	172.9	0.882	0.47	25.3
14723.19	5.730	42.83	173.3	0.882	0.47	25.3
14792.31	5.717	42.87	173.7	0.882	0.47	25.4
14861.43	5.694	42.89	174.1	0.883	0.47	25.4
14930.56	5.684	42.90	174.5	0.883	0.48	25.5
14999.68	5.664	42.94	174.9	0.883	0.48	25.6
15068.80	5.659	42.93	175.3	0.884	0.48	25.6
15137.93	5.622	42.97	175.7	0.884	0.49	25.7
15207.05	5.610	43.00	176.1	0.885	0.49	25.7
15276.17	5.593	43.02	176.5	0.885	0.49	25.8
15345.29	5.575	43.05	176.8	0.885	0.49	25.8
15414.42	5.545	43.07	177.2	0.886	0.50	25.9
15483.54	5.559	43.07	177.6	0.886	0.50	26.0
15552.66	5.540	43.09	178.0	0.886	0.50	26.0
15621.79	5.533	43.10	178.4	0.886	0.51	26.1
15690.91	5.487	43.16	178.8	0.887	0.51	26.1
15760.03	5.457	43.20	179.1	0.888	0.51	26.2
15829.16	5.442	43.22	179.5	0.888	0.51	26.2
15898.28	5.407	43.26	179.9	0.889	0.52	26.3
15967.40	5.401	43.28	180.3	0.889	0.52	26.3
16036.53	5.359	43.31	180.6	0.890	0.52	26.4
16105.65	5.358	43.34	181.0	0.890	0.53	26.5
16174.77	5.320	43.36	181.4	0.891	0.53	26.5
16243.89	5.301	43.40	181.7	0.891	0.53	26.6
16313.02	5.272	43.43	182.1	0.892	0.53	26.6
16382.14	5.255	43.45	182.5	0.892	0.54	26.7
16451.26	5.227	43.48	182.8	0.893	0.54	26.7
16520.39	5.228	43.51	183.2	0.893	0.54	26.8
16589.51	5.171	43.55	183.5	0.894	0.55	26.8
16658.63	5.169	43.56	183.9	0.894	0.55	26.9
16727.76	5.132	43.60	184.3	0.895	0.55	26.9
16796.88	5.132	43.62	184.6	0.895	0.55	27.0
16866.00	5.078	43.67	185.0	0.896	0.56	27.0
16935.13	5.092	43.67	185.3	0.896	0.56	27.1
17004.25	5.023	43.72	185.7	0.897	0.56	27.1
17073.37	5.030	43.73	186.0	0.897	0.57	27.2
17142.49	4.991	43.78	186.4	0.898	0.57	27.2
17211.62	4.977	43.80	186.7	0.898	0.57	27.3
17280.74	4.937	43.84	187.0	0.899	0.57	27.3
17349.86	4.936	43.85	187.4	0.899	0.58	27.4
17418.99	4.897	43.89	187.7	0.900	0.58	27.4
17488.11	4.888	43.91	188.1	0.900	0.58	27.5
17557.23	4.856	43.93	188.4	0.900	0.59	27.5

TOTAL PATTERN RESULTS:

WATERFLOOD RECOVERY	:	1671.82	MSTB
WATERFLOOD+INFILL RECOVERY	:	1507.11	MSTB
INCREMENTAL OIL FROM INFILL:		-164.72	MSTB
INCREMENTAL OIL FROM INFILL:		-3.01	% OOIP
ORIGINAL OIL IN PLACE	:	5474.04	MSTB

APPENDIX Ib

SimBest II INPUT/OUTPUT FOR IDPM VERIFICATION AGAINST BLACK-OIL SIMULATION

```

*C
*C
*C
*          *****
*C          *      S I M E A S E      *
*C          *      R E L E A S E 2.1.17      *
*C          *      INITIALIZATION DECK FOR SIMBEST II      *
*C          *          *****          *
*C          *          *
*C          *      PROJECT: IDPM/SimBest II Comparison      *
*C          *          *
*C          *      CASE:          *
*C          *          *
*C          *      DATE:      23-JAN-92      *
*C          *          *
*C          *      TIME:      15:17:28      *
*C          *          *
*C          *          *****          *
*C
*C
*C
*TITLE      Comparing IDPM to Simbest
*C
*C
*C
*C *PROJECT      Comparison
*C *CASE
*C
*C
*C ----- START OF BASIC DATA
*C
*LIST
*C
*WO
*C
*GRID      *XYZ      5      5      4
*C
*C          DWSTD      CW      BWINIT      VISW      TRSTD
*MISC      .99955      3.00000E-06      1.0010      .60000      117.00
*C
*STDCON      14.650      60.000
*C
*IDATE      01 01 70
*C
*C
*OUTPUT      *TABLES      *ARRAYS
*C
*C
*WINIT      *SKIP
*C
*CRVAR      *MATRIX      *CONSTANT      3.00000E-06
*C
*C
*C ----- END OF BASIC DATA
*C
*C
*C ----- START OF TABULAR DATA
*C
*C
*SATWO      1

```

*C	SW	KRW	KRO		
	0.300	0.0000	0.8000		
	0.323	0.0006	0.7180		
	0.346	0.0022	0.6404		
	0.369	0.0050	0.5673		
	0.392	0.0089	0.4986		
	0.415	0.0139	0.4343		
	0.438	0.0199	0.3745		
	0.461	0.0271	0.3191		
	0.484	0.0355	0.2681		
	0.530	0.0554	0.1795		
	0.553	0.0670	0.1418		
	0.576	0.0798	0.1086		
	0.599	0.0936	0.0798		
	0.622	0.1086	0.0554		
	0.645	0.1247	0.0355		
	0.668	0.1418	0.0199		
	0.691	0.1601	0.0089		
	0.714	0.1795	0.0022		
	0.737	0.2000	0.0000		
	0.760	0.2216	0.0000		
	1.000	0.2220	0.0000		
*C					
*PVT0	1	2220.58			
*API	32.0				
*C	BPT	*CO	7.35E-6	*VCO	4.0E-4
	14.70	RST	VOT	BOT	
	382.35	0.3718	9.0708	1.0189	
	749.99	86.8951	6.1412	1.0478	
	1117.64	178.4503	4.4122	1.0862	
	1485.29	271.5872	3.5390	1.1291	
	1852.94	374.2831	2.8510	1.1787	
	2220.58	446.1792	2.4834	1.2144	
	2588.23	534.8992	2.1270	1.2591	
	2955.88	670.6199	1.7270	1.3286	
	3323.53	839.9977	1.3821	1.4166	
	3691.17	1033.1050	1.1101	1.5185	
	4058.82	1260.2634	0.8847	1.6400	
	4426.47	1535.5167	0.6902	1.7899	
	4794.12	1879.7977	0.5162	1.9815	
	5161.76	2326.6694	0.3559	2.2372	
	5529.41	2934.2632	0.2042	2.5987	
	5897.06	3813.4346	0.0590	3.1517	
		5205.7295	0.0100	4.1048	
*C					
*C					
*PVTG	*BG	1	.8		
*C	BPT	BGT	VG		
	14.70	197.1380	0.0107		
	382.35	6.7240	0.0112		
	749.99	3.0475	0.0121		
	1117.64	1.8684	0.0137		
	1485.29	1.3231	0.0159		
	1852.94	1.0276	0.0187		
	2220.58	.8530	0.0220		
	2588.23	.7439	0.0254		
	2955.88	.6731	0.0289		
	3323.53	.6256	0.0320		
	3691.17	.5926	0.0348		
	4058.82	.5690	0.0372		

```

4426.47      .5512      0.0393
4794.12      .5373      0.0412
5161.76      .5257      0.0429
5529.41      .5158      0.0445
5897.06      .5068      0.0461
*C ----- END OF TABULAR DATA
*C
*C
*C ----- START OF GRID DATA
*C
*C
*C
*DXH      *XVAR
233.35      233.35      233.35      233.35      233.35
*C
*DYH      *YVAR
233.35      233.35      233.35      233.35      233.35
*C
*TH      *CON
62.5
*THNET      *CON
62.5
*C
*HTOP      *LAYER
6500 6500 6500 6500 6500
6500 6500 6500 6500 6500
6500 6500 6500 6500 6500
6500 6500 6500 6500 6500
6500 6500 6500 6500 6500
*C
*KX      *ZVAR
2.25      .25      .08      .02
*KY      *ZVAR
2.25      .25      .08      .02
*KZ      *MULT
0.01*KX
*PHI      *CON
0.063
*OVER      *PV
1      1      1      1      1      4      *MULTIPLY      .125000
2      5      1      1      1      4      *SETEQUAL      .000000
2      2      2      2      1      4      *MULTIPLY      .500000
3      5      2      2      1      4      *SETEQUAL      .000000
3      3      3      3      1      4      *MULTIPLY      .500000
4      5      3      3      1      4      *SETEQUAL      .000000
4      4      4      4      1      4      *MULTIPLY      .500000
5      5      4      4      1      4      *SETEQUAL      .000000
1      1      5      5      1      4      *MULTIPLY      .250000
5      5      5      5      1      4      *MULTIPLY      .125000
2      4      5      5      1      4      *MULTIPLY      .500000
1      1      2      4      1      4      *MULTIPLY      .500000
*C
*C ----- END OF GRID DATA
*C
*C
*C ----- NO AQUIFER DATA
*C
*C
*C

```

```

*C ----- START OF EQUIL DATA
*C
*C
*EQUIL
*C
*C      REGION    DATUM    INITIAL
*C      REGION    DATUM    PRESSURE    WOC    PCWOC    GOC    PCGOC    BPINI
*C      1    6500.00    3000.00    7000.00    .00    0.00    .00    2220.58
*C
*C ----- END OF EQUIL DATA
*C
*ENDJOB
*C *CASE
*C      *****
*C      *          S I M E A S E          *
*C      *          R E L E A S E 2.1.17    *
*C      *          RUN DECK FOR SIMBEST II  *
*C      *          *****
*C      *          PROJECT: IDPM/SimBest II Comparison *
*C      *          CASE:
*C      *          DATE:    23-JAN-92
*C      *          TIME:    15:22:24
*C      *          *****
*C
*RTITLE Comparison
*C
*C
*C *PROJECT      Comparison
*C *CASE
*C
*C
*WELL    1    *PROD    *MULT 1
*WELL    2    *INJ1    *MULT 1
*WELL    3    *PROD2    *MULT 1
*PROD    *O 1
*INJ      *W 2
*PROD    *O 3
*PERF    1    *IJK 4 5 5 1 5 5 2 5 5 3 5 5 4 17.58 1.95 0.625 .156
*PERF    2    *IJK 4 1 1 1 1 1 2 1 1 3 1 1 4 17.58 1.95 0.625 .156
*PERF    3    *IJK 4 1 5 1 1 5 2 1 5 3 1 5 4 35.17 3.91 1.25 .312
*BHP      1    100 6500
*BHP      2    4550 6500
*BHP      3    100 6500
*C
*Q      1    20.0
*Q      2    25.0
*Q      3    0.0
*C
*WI 1 .01197
*WI 2 .02394
*WI 3 .01197
*C

```

```

*TRNMOD *TY 1 1 2 5 1 4 *MULTIPLY 0.50
*TRNMOD *TZ 1 1 1 1 2 4 *MULTIPLY 0.125
*TRNMOD *TZ 1 1 2 4 2 4 *MULTIPLY 0.50
*TRNMOD *TZ 1 1 5 5 2 4 *MULTIPLY 0.125
*C
*TRNMOD *TX 2 5 5 5 1 4 *MULTIPLY 0.50
*TRNMOD *TZ 2 4 5 5 2 4 *MULTIPLY 0.50
*TRNMOD *TZ 5 5 5 5 2 4 *MULTIPLY 0.125
*C
*TRNMOD *TZ 2 2 2 2 2 4 *MULTIPLY 0.5
*TRNMOD *TZ 3 3 3 3 2 4 *MULTIPLY 0.5
*TRNMOD *TZ 4 4 4 4 2 4 *MULTIPLY 0.5
*C
*C
*WPLLOT 1
*C
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 1
*TIME 5
*TIME 10
*TIME 50
*TIME 100
*TIME 182
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 365
*C
*C
*TIME 547
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 730
*TIME 912
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 1095
*TIME 1277
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 1460
*TIME 1642
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 1825
*TIME 2190
*TIME 2555
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 2920
*TIME 3285
*TIME 3650
*TIME 4015
*TIME 4380
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 4745
*TIME 5110
*TIME 5475

```

```
*TIME 5840
*TIME 6205
*TIME 6440
*C      1 10.0
*Q      2 50.0
*Q      3 15.0
*C
*PRINT *ARRAYS *WELL *TONLY
*WMAP *TONLY
*TIME 6450
*TIME 6570
*TIME 6935
*PRINT *ARRAYS *WELL *TIME
*WMAP *TIME
*TIME 7300
*TIME 9125
*TIME 10950
*TIME 12775
*TIME 14600
*TIME 16425
*TIME 17600
*C
*ENDJOB
```

: SSI'S SIMBEST II SIMULATOR : Comparing IDPM to Simbest : DATE 30-JAN-92 TIME 16:51 :
: SCALAR VERSION 3.0 I28 S72 : Comparison : SIMULATION RUN PAGE 1 :

TIME STEP SUMMARY

=====

I	TIME		PRODUCTION		GOR	WATER	INJECTION		AVG	MATERIAL			BALANCES		MAX SATN CHG				MAX PRESS CHG				TIME I	DATA I
	STEP	DAYS	OIL STB/D	GAS MSCF/D	SCF/ STB	CUT FRACT	GAS MSCF/D	WATER STB/D	PRESS PSIA	OIL	GAS	WATER	I	J	K	DSMAX	I	J	K	DPMAX	CUTS	N	PUT	I
I	1	1.00	20	11	535	0.000	0	25	3041	1.0001	1.0001	0.9999	1	1	1	0.003	5	5	1	-312.8	0	2	PM	I
I	2	2.28	20	11	535	0.000	0	25	3042	1.0001	1.0001	0.9999	1	1	1	0.004	5	5	1	-236.2	0	2	P	I
I	3	4.45	20	11	535	0.000	0	25	3042	1.0001	1.0001	1.0000	1	1	1	0.006	1	1	2	235.4	0	2	P	I
I	4	5.00	20	11	535	0.000	0	25	3042	1.0001	1.0001	0.9999	1	1	1	-0.002	1	1	2	58.1	0	1	P	I
I	5	10.00	20	11	535	0.000	0	25	3042	1.0003	1.0003	0.9998	1	1	1	-0.016	1	1	2	376.9	0	2	P	I
I	6	15.31	20	11	535	0.000	0	25	3042	1.0003	1.0003	0.9998	1	1	1	0.017	1	1	2	311.1	0	2	P	I
I	7	22.13	20	11	535	0.000	0	19	3038	1.0003	1.0003	0.9998	1	1	1	0.018	1	1	3	227.8	0	2	P	I
I	8	34.11	20	11	535	0.000	0	16	3029	1.0002	1.0002	0.9998	1	1	1	0.026	1	1	4	230.2	0	2	P	I
I	9	50.00	20	11	535	0.000	0	15	3014	1.0001	1.0001	0.9999	1	1	1	-0.030	1	1	4	203.2	0	2	P	I
I	10	73.59	20	11	535	0.000	0	14	2991	1.0001	1.0001	0.9999	1	1	1	-0.036	5	5	4	-218.6	0	2	P	I
I	11	100.0	20	11	535	0.000	0	14	2966	1.0000	1.0000	1.0000	1	1	1	-0.033	5	5	4	-190.7	0	1	P	I
I	12	147.2	20	11	535	0.000	0	16	2927	1.0000	1.0000	1.0000	1	1	1	-0.041	5	5	4	-215.4	0	2	P	I
I	13	182.0	20	11	535	0.000	0	17	2902	1.0000	1.0000	1.0000	1	1	1	-0.024	5	5	4	-112.6	0	1	P	I
I	14	276.4	20	11	535	0.000	0	18	2845	1.0000	1.0000	1.0000	1	2	1	0.063	5	5	4	-152.7	0	1	P	I
I	15	365.0	20	11	535	0.000	0	19	2800	1.0000	1.0000	1.0000	1	2	1	0.050	3	5	2	-92.7	0	1	PM	I
I	16	547.0	20	11	535	0.000	0	21	2729	1.0000	1.0000	1.0000	1	2	1	0.062	1	5	2	-134.8	0	1	P	I
I	17	730.0	20	11	535	0.000	0	22	2681	1.0000	1.0000	1.0000	2	2	1	0.067	4	4	3	-101.2	0	1	PM	I
I	18	912.0	20	11	535	0.000	0	23	2646	1.0001	1.0001	0.9999	1	3	1	-0.053	3	5	3	-78.2	0	1	P	I
I	19	1095	20	11	535	0.000	0	24	2622	1.0001	1.0001	0.9999	2	3	1	0.042	1	5	3	-65.0	0	1	PM	I
I	20	1277	20	11	535	0.000	0	24	2604	1.0001	1.0001	0.9999	2	3	1	0.044	4	4	4	-55.1	0	1	P	I
I	21	1460	20	11	535	0.000	0	24	2592	1.0001	1.0001	0.9999	2	3	1	-0.040	2	3	1	50.5	0	1	PM	I
I	22	1642	20	11	535	0.000	0	25	2583	1.0002	1.0002	0.9999	1	4	1	0.033	4	4	4	-43.0	0	1	P	I
I	23	1825	20	11	535	0.000	0	25	2578	1.0002	1.0002	0.9999	3	3	1	0.036	1	4	1	39.2	0	1	PM	I
I	24	2008	20	11	535	0.000	0	25	2573	1.0002	1.0002	0.9999	3	3	1	-0.036	1	2	2	37.8	0	1	P	I
I	25	2190	20	11	535	0.000	0	25	2570	1.0002	1.0002	0.9999	3	3	1	-0.033	3	3	1	36.8	0	1	P	I
I	26	2373	20	11	535	0.000	0	25	2568	1.0002	1.0002	0.9999	2	4	1	-0.028	1	2	2	30.9	0	1	P	I
I	27	2555	20	11	535	0.000	0	25	2566	1.0002	1.0002	0.9999	3	4	1	-0.027	2	4	1	29.6	0	1	P	I
I	28	2738	20	11	535	0.000	0	25	2565	1.0002	1.0002	0.9999	3	4	1	0.031	1	5	1	29.9	0	1	P	I
I	29	2920	20	11	535	0.000	0	25	2564	1.0002	1.0002	0.9999	3	4	1	-0.031	1	5	1	30.3	0	1	PM	I
I	30	3103	20	11	535	0.000	0	25	2562	1.0002	1.0002	0.9999	3	4	1	-0.029	1	5	1	29.1	0	1	P	I
I	31	3285	20	11	535	0.000	0	25	2561	1.0002	1.0002	0.9999	4	4	1	0.032	1	5	1	29.1	0	1	P	I
I	32	3468	20	11	535	0.000	0	25	2559	1.0002	1.0002	0.9999	4	4	1	-0.037	5	5	1	-47.7	0	1	P	I
I	33	3650	20	11	535	0.001	0	25	2556	1.0002	1.0002	0.9999	4	4	1	-0.036	5	5	1	-84.3	0	1	P	I
I	34	3833	20	11	535	0.003	0	25	2550	1.0002	1.0002	0.9998	4	5	1	0.037	5	5	1	-109.3	0	1	P	I
I	35	4015	20	11	535	0.023	0	25	2538	1.0002	1.0002	0.9995	5	5	1	0.057	5	5	2	-164.9	0	1	P	I
I	36	4198	20	11	535	0.102	0	25	2498	1.0002	1.0002	0.9995	5	5	1	-0.086	5	5	2	-289.1	0	2	P	I
I	37	4380	18	10	535	0.226	0	25	2447	1.0002	1.0002	0.9993	5	5	1	-0.065	5	5	4	-201.0	0	2	P	I
I	38	4563	15	8	535	0.338	0	25	2419	1.0002	1.0002	0.9993	5	5	1	-0.031	4	5	4	-79.2	0	2	P	I
I	39	4745	13	7	535	0.416	0	25	2402	1.0000	1.0000	0.9991	5	5	1	0.019	4	4	4	-60.6	0	1	PM	I
I	40	4928	12	7	535	0.469	0	25	2383	1.0000	1.0000	0.9991	4	5	1	0.013	4	4	4	-53.3	0	1	P	I
I	41	5110	11	6	535	0.508	0	25	2364	1.0000	1.0000	0.9991	4	5	1	0.011	4	4	4	-46.7	0	1	P	I

: SSI'S SIMBEST II SIMULATOR : Comparing IDPM to Simbest : DATE 30-JAN-92 TIME 16:51 :
: SCALAR VERSION 3.0 I28 S72 : Comparison : SIMULATION RUN PAGE 2 :

TIME STEP SUMMARY
=====

I	TIME		PRODUCTION		GOR	WATER	INJECTION		AVG	MATERIAL BALANCES			MAX SATN CHG				MAX PRESS CHG				TIME	I	DATA	I
	STEP	DAYS	OIL STB/D	GAS MSCF/D	SCF/STB	CUT FRACT	GAS MSCF/D	WATER STB/D	PRESS PSIA	OIL	GAS	WATER	I	J	K	DSMAX	I	J	K	DEMAX	CUTS	N	PUT	I
I	42	5293	11	6	535	0.539	0	25	2346	1.0000	1.0000	0.9991	4	5	1	-0.009	4	4	4	-41.1	0	1	P	I
I	43	5475	10	5	535	0.564	0	25	2328	0.9999	0.9999	0.9991	2	2	2	0.008	3	4	4	-38.0	0	1	P	I
I	44	5658	10	5	535	0.584	0	25	2309	0.9999	0.9999	0.9992	1	3	2	0.008	3	4	4	-35.9	0	1	P	I
I	45	5840	9	5	535	0.601	0	25	2290	0.9999	0.9999	0.9992	1	3	2	0.008	3	4	4	-33.9	0	1	P	I
I	46	6023	9	5	535	0.616	0	25	2272	0.9999	0.9999	0.9992	1	3	2	-0.008	1	5	4	-33.2	0	1	P	I
I	47	6205	9	5	535	0.629	0	25	2255	0.9999	0.9999	0.9993	1	3	2	-0.007	1	5	4	-32.6	0	1	P	I
I	48	6388	9	5	535	0.641	0	25	2237	0.9999	0.9999	0.9993	1	3	2	0.007	1	5	4	-31.8	0	1	P	I
I	49	6440	9	5	535	0.643	0	25	2232	0.9999	0.9999	0.9993	1	3	2	-0.002	1	5	4	-9.1	0	1	P	I
I	50	6450	23	13	535	0.613	0	31	2196	0.9999	0.9999	0.9993	1	5	2	-0.001	1	5	1	-955.7	0	6	PM	I
I	51	6526	23	12	535	0.591	0	36	1993	0.9999	0.9999	0.9993	1	5	1	-0.021	1	5	3	-834.1	0	5	P	I
I	52	6570	23	12	535	0.587	0	38	1895	0.9999	0.9999	0.9994	1	5	1	0.010	1	5	4	-358.4	0	2	P	I
I	53	6619	22	12	535	0.586	0	40	1802	0.9999	0.9999	0.9994	1	5	1	-0.010	1	5	4	-264.5	0	2	P	I
I	54	6692	22	12	535	0.590	0	43	1683	0.9999	0.9999	0.9994	1	5	1	-0.011	1	5	4	-233.3	0	2	P	I
I	55	6818	20	11	535	0.612	0	45	1543	0.9999	0.9999	0.9995	1	5	1	-0.011	2	3	2	-261.9	0	2	P	I
I	56	6935	18	10	535	0.634	0	46	1450	0.9999	0.9999	0.9995	1	3	2	-0.008	2	3	3	-189.0	0	1	P	I
I	57	7118	16	9	535	0.661	0	47	1351	0.9999	0.9999	0.9995	1	3	2	0.012	2	2	3	-244.1	0	2	P	I
I	58	7300	15	8	535	0.680	0	47	1278	0.9997	0.9997	0.9995	1	3	2	-0.012	2	2	3	-187.8	0	1	PM	I
I	59	7483	14	8	535	0.697	0	48	1221	0.9997	0.9997	0.9996	1	3	2	-0.011	2	4	4	-134.0	0	1	P	I
I	60	7665	14	7	535	0.712	0	48	1177	0.9997	0.9997	0.9996	1	3	2	-0.011	2	3	4	-131.5	0	1	P	I
I	61	7848	13	7	535	0.725	0	48	1141	0.9997	0.9997	0.9996	2	3	2	0.011	2	3	4	-126.0	0	1	P	I
I	62	8030	12	7	535	0.736	0	49	1111	0.9997	0.9997	0.9996	2	3	2	-0.011	2	2	4	-122.8	0	1	P	I
I	63	8213	12	6	535	0.745	0	49	1086	0.9997	0.9997	0.9996	2	3	2	-0.011	2	2	4	-117.5	0	1	P	I
I	64	8395	12	6	535	0.754	0	49	1065	0.9997	0.9997	0.9997	2	3	2	0.011	2	2	4	-110.1	0	1	P	I
I	65	8578	11	6	535	0.761	0	49	1047	0.9997	0.9997	0.9997	2	3	2	0.011	1	2	4	-104.2	0	1	P	I
I	66	8760	11	6	535	0.768	0	49	1032	0.9997	0.9997	0.9997	2	3	2	-0.010	1	2	4	-97.0	0	1	P	I
I	67	8943	11	6	535	0.775	0	50	1019	0.9997	0.9997	0.9997	1	4	2	0.010	1	2	4	-88.6	0	1	P	I
I	68	9125	10	6	535	0.780	0	50	1008	0.9997	0.9997	0.9997	1	4	2	-0.010	1	2	4	-79.5	0	1	PM	I
I	69	9308	10	5	535	0.786	0	50	998	0.9997	0.9997	0.9997	1	4	2	-0.010	1	2	4	-70.1	0	1	P	I
I	70	9490	10	5	535	0.791	0	50	991	0.9997	0.9997	0.9997	1	4	2	-0.010	1	2	4	-61.0	0	1	P	I
I	71	9673	10	5	535	0.796	0	50	984	0.9997	0.9997	0.9997	1	4	2	-0.010	1	2	4	-52.3	0	1	P	I
I	72	9855	10	5	535	0.800	0	50	979	0.9997	0.9997	0.9997	1	4	2	-0.009	1	2	4	-44.6	0	1	P	I
I	73	10038	9	5	535	0.804	0	50	974	0.9997	0.9997	0.9998	1	4	2	0.009	1	2	4	-37.6	0	1	P	I
I	74	10220	9	5	535	0.808	0	50	970	0.9998	0.9998	0.9998	1	4	2	-0.009	1	2	4	-30.2	0	1	P	I
I	75	10403	9	5	535	0.812	0	50	967	0.9998	0.9998	0.9998	1	5	2	0.009	2	2	4	-24.5	0	1	P	I
I	76	10585	9	5	535	0.816	0	50	965	0.9998	0.9998	0.9998	1	5	2	-0.010	2	2	4	-20.3	0	1	P	I
I	77	10768	9	5	535	0.819	0	50	963	0.9998	0.9998	0.9998	1	5	2	-0.010	2	2	4	-16.8	0	1	P	I
I	78	10950	8	5	535	0.823	0	50	962	0.9998	0.9998	0.9998	1	5	2	0.011	2	2	4	-13.8	0	1	PM	I
I	79	11133	8	4	535	0.826	0	50	961	0.9998	0.9998	0.9998	1	5	2	0.011	2	2	3	14.9	0	1	P	I
I	80	11315	8	4	535	0.829	0	50	961	0.9998	0.9998	0.9998	1	5	2	-0.011	2	2	3	14.9	0	1	P	I
I	81	11498	8	4	535	0.832	0	50	962	0.9998	0.9998	0.9998	1	5	2	-0.011	2	2	3	15.7	0	1	P	I
I	82	11680	8	4	535	0.835	0	50	962	0.9998	0.9998	0.9998	1	5	2	0.011	2	2	3	16.5	0	1	P	I
I	83	11863	8	4	535	0.838	0	50	963	0.9998	0.9998	0.9998	1	5	2	0.011	2	2	3	17.3	0	1	P	I

: SSI'S SIMBEST II SIMULATOR : Comparing IDPM to Simbest : DATE 30-JAN-92 TIME 16:51 :
: SCALAR VERSION 3.0 I28 S72 : Comparison : SIMULATION RUN PAGE 3 :

TIME STEP SUMMARY

=====

I	TIME		PRODUCTION		GOR	WATER	INJECTION		AVG	MATERIAL BALANCES			MAX SATN CHG				MAX PRESS CHG				TIME I	DATA	I	
	STEP	DAYS	OIL STB/D	GAS MSCF/D	SCF/STB	CUT FRACT	GAS MSCF/D	WATER STB/D	PRESS PSIA	OIL	GAS	WATER	I	J	K	DSMAX	I	J	K	DPMAX	CUTS N	OUT-PUT		
I	84	12045	8	4	535	0.841	0	50	965	0.9998	0.9998	0.9998	1	5	2	0.010	2	2	3	16.1	0	1	P	I
I	85	12228	7	4	535	0.844	0	50	966	0.9998	0.9998	0.9998	1	5	2	-0.010	2	2	3	16.8	0	1	P	I
I	86	12410	7	4	535	0.847	0	50	968	0.9998	0.9998	0.9998	1	5	2	0.009	2	2	3	17.8	0	1	P	I
I	87	12593	7	4	535	0.850	0	50	969	0.9999	0.9999	0.9998	1	5	2	-0.009	2	2	3	17.8	0	1	P	I
I	88	12775	7	4	535	0.853	0	50	971	0.9999	0.9999	0.9998	1	5	2	-0.008	2	2	3	15.3	0	1	PM	I
I	89	12958	7	4	535	0.856	0	50	973	0.9999	0.9999	0.9998	1	5	2	-0.007	2	2	3	15.8	0	1	P	I
I	90	13140	7	4	535	0.859	0	50	975	0.9999	0.9999	0.9998	1	5	2	-0.007	2	2	3	15.7	0	1	P	I
I	91	13323	7	4	535	0.861	0	50	976	0.9999	0.9999	0.9998	1	5	2	-0.006	2	2	3	15.6	0	1	P	I
I	92	13505	7	4	535	0.864	0	50	978	0.9999	0.9999	0.9998	1	5	2	-0.006	2	2	3	11.9	0	1	P	I
I	93	13688	6	3	535	0.866	0	50	980	0.9999	0.9999	0.9998	1	3	3	0.006	2	2	3	12.1	0	1	P	I
I	94	13870	6	3	535	0.868	0	50	982	0.9999	0.9999	0.9998	1	3	3	0.006	2	2	3	12.0	0	1	P	I
I	95	14053	6	3	535	0.870	0	50	983	0.9999	0.9999	0.9998	1	3	3	-0.005	1	2	4	12.3	0	1	P	I
I	96	14235	6	3	535	0.872	0	50	985	0.9999	0.9999	0.9999	1	3	3	0.005	1	2	4	12.1	0	1	P	I
I	97	14418	6	3	535	0.874	0	50	986	0.9999	0.9999	0.9999	2	5	2	0.005	1	2	4	12.3	0	1	P	I
I	98	14600	6	3	535	0.876	0	50	988	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	12.5	0	1	PM	I
I	99	14783	6	3	535	0.878	0	50	989	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	12.7	0	1	P	I
I	100	14965	6	3	535	0.880	0	50	991	0.9999	0.9999	0.9999	2	5	2	0.005	1	2	4	12.8	0	1	P	I
I	101	15148	6	3	535	0.881	0	50	992	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	13.0	0	1	P	I
I	102	15330	6	3	535	0.883	0	50	993	0.9999	0.9999	0.9999	2	5	2	0.005	1	2	4	13.1	0	1	P	I
I	103	15513	6	3	535	0.884	0	50	995	0.9999	0.9999	0.9999	2	5	2	0.005	1	2	4	13.7	0	1	P	I
I	104	15695	6	3	535	0.886	0	50	996	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	13.1	0	1	P	I
I	105	15878	5	3	535	0.887	0	50	997	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	13.2	0	1	P	I
I	106	16060	5	3	535	0.888	0	50	998	0.9999	0.9999	0.9999	2	5	2	-0.005	1	2	4	13.3	0	1	P	I
I	107	16243	5	3	535	0.890	0	50	1000	0.9999	0.9999	0.9999	2	5	2	0.005	1	2	4	13.4	0	1	P	I
I	108	16425	5	3	535	0.891	0	50	1001	0.9999	0.9999	0.9999	2	5	2	-0.004	1	2	4	13.5	0	1	PM	I
I	109	16608	5	3	535	0.893	0	50	1002	0.9999	0.9999	0.9999	2	5	2	-0.004	1	2	4	13.5	0	1	P	I
I	110	16790	5	3	535	0.894	0	50	1004	0.9999	0.9999	0.9999	2	5	2	-0.004	1	2	4	13.6	0	1	P	I
I	111	16973	5	3	535	0.895	0	50	1005	0.9999	0.9999	0.9999	2	5	2	-0.004	1	2	4	13.0	0	1	P	I
I	112	17155	5	3	535	0.896	0	50	1006	0.9999	0.9999	0.9999	2	3	3	0.004	1	2	4	12.8	0	1	P	I
I	113	17338	5	3	535	0.898	0	50	1007	0.9999	0.9999	0.9999	2	3	3	-0.004	1	2	4	12.6	0	1	P	I
I	114	17520	5	3	535	0.899	0	50	1009	0.9999	0.9999	0.9999	2	3	3	0.004	1	2	4	12.5	0	1	P	I
I	115	17600	5	3	535	0.899	0	50	1009	0.9999	0.9999	0.9999	2	3	3	0.002	1	2	4	5.5	0	1	PM	I

APPENDIX IIa

SPE REFERENCE PAPERS FOR IDPM VALIDATION AGAINST FIELD FLOOD RESULTS

Quantitative Analysis of Infill Performance: Robertson Clearfork Unit

J.A. Barbe, SPE, Exxon Co. U.S.A.
D.J. Schnobelen,* Exxon Co. U.S.A.

Summary. This study analyzed the results of 218 infill wells drilled in the Robertson Clearfork Unit (RCU), Gaines County, TX. This program increased ultimate recovery by more than 23 million bbl [$3.7 \times 10^6 \text{ m}^3$]. The individual well performance, as a function of reservoir continuity, was analyzed quantitatively with pressure correlations, numerical analyses, and geologic study.

Introduction

Infill drilling has significantly increased the cumulative production, conventional remaining reserves, and EOR prospects in RCU. This paper documents the successful infill program and the techniques used to quantify reservoir performance under various well spacings and injection patterns.

RCU is a highly stratified, lenticular dolomite reservoir. Continuity of pay between wells is unusually poor, and the reservoir was only partially drained by wells on 40-acre [16-ha] spacing. Ultimately, 10-acre [4-ha] wells and 40-acre [16-ha] inverted nine-spot patterns were required for an effective waterflood. Expected recovery from the unit has been increased by more than 23 million bbl [$3.8 \times 10^6 \text{ m}^3$] by the drilling of 218 infill wells and an increase in the number of water-injection wells to form the 40-acre [16-ha] inverted nine-spot patterns. (Throughout this paper, 10-, 20-, and 40-acre [4-, 8-, and 16-ha] spacing refers to the nominal spacing of wells, although the exact areas vary.)

Three approaches were used to quantify reservoir continuity as a function of horizontal distance: geologic correlation, pressure-transient behavior, and regression analysis of infill performance. All three techniques indicate that 10-acre [4-ha] spacing can effectively drain 80 to 85% of the reservoir volume by primary production (solution gas drive). On this spacing, however, reservoir discontinuities limit the floodable volume to only 60 to 65% of the total reservoir.

These studies have permitted the operator to project the results of further infill drilling quantitatively. They also permit a realistic assessment of EOR potential based on actual floodable reservoir volume calculations.

Background

RCU became effective Jan. 1, 1970, and injection began in the first six injectors almost immediately. By mid-1971, the waterflood had been expanded throughout the unit. Full-scale injection averaged 20,000 to 30,000 BWPD [3.2×10^3 to $4.8 \times 10^3 \text{ m}^3/\text{d}$ water] throughout the 1970's, and by 1974, a degree of reservoir fill-up caused an oil production increase. The response peaked briefly in 1974 at 3,500 BOPD [$560 \text{ m}^3/\text{d}$ oil] and then began a rapid > 25%/yr decline (see Fig. 1). This precipitous decline, and the low ultimate secondary recovery it foretold, prompted the first major reservoir performance review in 1975 and 1976. This marked the beginning of the successful infill drilling program described here.

The first RCU discovery within the unit boundary was in 1946. The field was subsequently named the Doss (Upper Clearfork) field. In 1970, after additional new zone discoveries and various field consolidations by the Texas Railroad Commission, the unitized reservoir consisted of two separate regulatory fields: the Robertson, North (Clearfork 7,100) field, which included the RCU Lower Clearfork, and the Robertson field, which included the Glorieta formation and the Upper Clearfork.

The two reservoirs were first flooded under a "confluent production" program in which dually completed injectors flooded each zone separately while production was commingled in the producers. Then in 1977, the injection wells were commingled, and the entire unitized formation has been operated as a single reservoir since. Reservoir performance studies, as well as injection profile tests, indicate that the waterflood conformance was no worse under the commingled mode than under the previous operation.

The 1976 reservoir study identified two major problems in waterflood performance: inadequate completions and poor reservoir continuity. Extrapolation of production curves forecast an ultimate recovery of only 30 million bbl [$4.8 \times 10^6 \text{ m}^3$], 8.3% of the original oil in place (OOIP), with the initial operating scheme. This could be improved to 42 million bbl [$6.7 \times 10^6 \text{ m}^3$] by an extensive workover program of perforating additional intervals and selective stimulation. The problem of poor reservoir continuity, however, could be overcome only by infill drilling on closer spacing. Detailed zone-by-zone geologic correlations of porous intervals were developed with techniques reported by George and Stiles.¹ These were used to evaluate continuity between wells and thus to estimate recovery from 20-acre [8-ha] infill wells.

Reservoir Geology

Regional Overview. Geologically, the Robertson field is located on the northeastern edge of the Central Basin platform, which separated the Delaware and Midland basins during the Permian Age (Fig. 2). Production is from Permian Leonardian carbonates of the Glorieta, Upper Clearfork, and Lower Clearfork formations.

The 13 Clearfork fields shown in Fig. 2 have many similar geologic features and demonstrate the effect the Central Basin platform had on Permian carbonate development and stratigraphy. The uplift of the Central Basin platform provided a shallow platform where prolific biological activity could occur, thereby allowing the accumulation of abundant carbonate sediments. Progressive deepening of the basin and growth of a marine bank along the margin of the basin accentuated the environmental differences between the basin and shelf areas. An idealized block diagram, shown in Fig. 3, illustrates a shelf margin complex similar to the environment that produced the Robertson carbonates. Hypersaline waters were more common shoreward of the marine bank, with several areas periodically subaerially exposed. Near-normal marine conditions prevailed farther basinward along the platform. Carbonate deposition would tend to build upward and basinward, subject to later dolomitization.

Trapping Mechanism. The Robertson field is situated on a large northwest/southeast-trending anticline, though most of the trapping of hydrocarbons is controlled by lateral and vertical limits of porosity and permeability. Most Clearfork reservoirs on the Central Basin platform exhibit a similar stratigraphic trapping mechanism.²

Fig. 4 is a structural map on the top of the Lower Clearfork formation. The crest of the structure is located on the west side of

*Now at Indiana U

Fig. 1—Production history.

Fig. 2—Location map of RCU and other Clearfork reservoirs (adapted from Ref. 2).

the unit area, with a gentle dip to the east and a steeper dip to the southwest. The structural maps on other horizons are similar except for some shifting of the crest to the east as the formations become shallower.

Zonation and Lithology. The gross vertical interval at RCU is approximately 1,200 to 1,400 ft [370 to 430 m] thick and occurs from 5,800 to 7,200 ft [1770 to 2200 m] in depth. The net pay within this interval varies from 200 to 400 ft [60 to 120 m]. Fig. 5 is a type log (gamma ray/sidewall neutron porosity) that shows the unitized interval, which consists of the Glorieta, Upper Clearfork, Tubb (nonproductive), and Lower Clearfork formations. This section was subdivided further into 14 zones for detailed mapping (mainly on the basis of gamma ray log response).

In general, the unitized interval consists of dolomite, shale, and anhydrite, with minor beds of lignite and sandstone in the Glorieta. The Lower Clearfork is the most heavily dolomitized of all the formations and appears more massive than either the Glorieta or Upper Clearfork.

Porosity types are dominantly moldic and intergranular, though some vugular porosity is present in the Lower Clearfork. Average porosity is approximately 6.0%, and permeability averages 0.1 to 2.0 md.

Note that over the entire vertical interval of 1,200 to 1,400 ft [370 to 430 m], there may be 50 to 70 different individual pay stringers, ranging in thickness from 1 ft [0.3 m] to a few tens of feet. Fig. 5 shows that most porosity zones are usually only a few feet thick.

Depositional Environment. In general, the heterogeneity and stringerized nature of the carbonates in the Robertson reservoir are a result of their depositional environments. A complex mosaic of environments existed that ranged from supratidal (above mean high tide) to subtidal (below mean low tide). This range of environments would have coexisted while migrating laterally and vertically with time. This "shifting" of environments is probably represented best in the Upper Clearfork by the interbedded shales and dolomite. The cyclic nature of the Upper Clearfork is probably a result of slight variations in sea level or depositional rates as environments altered from subtidal (lime mud, now dolomites) and supratidal (shale and anhydrite). The Lower Clearfork generally appears to be more marine-dominated, although recognition of fossils and structures is difficult because of dolomitization. In contrast, the Glorieta appears to have been deposited more landward, consisting of supratidal-type deposits (shale, anhydrite, and lignite).

Overall, the carbonates built basinward with time, resulting in a regressive sequence. Within this regressive sequence, however, there are also minor transgressive cycles, especially in the Glorieta and Upper Clearfork formations. The regressive sequence can be seen by comparing the net-porosity-feet maps of each formation, as shown in Figs. 6 through 8. Note that the basin would have been toward the east and landward would have been to the west. These maps show a distinct west-to-east shift in the highest net porosity-feet values during the successive deposition of Lower Clearfork to Glorieta sediments as the carbonates progressively built basinward through time.

Fig. 3—Depositional environment schematic during Leonardian Age.

Fig. 4—Structural map—top of Lower Clearfork, RCU.

Development History

RCU was initially developed with 40 acres [16 ha] per well, with the wells generally arranged in east/west rows and north/south columns. At the time waterflood began in 1970–71, every other well was converted to injection, thus creating 80-acre [32-ha] five-spot waterflood patterns. The first round of infill drilling involved drilling one additional well on each 40-acre [16-ha] tract, resulting in a modification of the waterflood pattern to 80-acre [32-ha] inverted nine-spots. In effect, the well density was doubled (Fig. 9). The final stage of development involved drilling one well on each undrilled 10-acre [4-ha] location; i.e., one well was drilled directly north and one well directly east/west of each of the original 40-acre [16-ha] wells. This pattern would not have had adequate injectivity to balance withdrawals; therefore, the remaining original 40-acre [16-ha] producing wells were converted to injection service in this area. Thus, the final pattern, which is still in operation, consists of 40 acres [16 ha] per inverted nine-spot pattern with roughly one injection well for each three producing wells.

Pressure Performance

Since 1981, during the time of most of the 10-acre [4-ha] infill drilling at RCU, 197 buildup and falloff tests were run over a wide areal distribution throughout the unit. Analysis of these pressure-transient tests provides invaluable insight into the actual performance within the reservoir. For producing wells, these tests were generally analyzed with McKinley's³ technique because the relatively low productivity and the high stratification result in very long

Fig. 5—Type log.

periods of afterflow in an RCU producer. The typical producing well is affected by afterflow (or by wellbore storage effects) for more than 4 to 5 days after shut-in. The injection-well falloff tests, with short periods of afterflow, can be analyzed by conventional techniques. The fracture length for each of these wells was calculated with the techniques presented by Matthews and Russell.⁴ Table 1 summarizes these tests.

Fig. 6—Lower Clearfork—trend of high-quality reservoir.

Fig. 7—Upper Clearfork—trend of high-quality reservoir.

The average reservoir pressure, $\bar{p}$, which is the extrapolated pressure for the vicinity of each well, is presented in Fig. 10. This pressure history should be analyzed and viewed in light of the major modifications occurring in reservoir operations in the 1981-85 period. During this time, the number of active producing wells increased from 140 to 229, while active injectors increased from 40 to 78. Again, one of the first conclusions from these data is that the differential pressure between the injection-well extrapolation and producing-well extrapolation has decreased during the time that the average distance between wells decreased (Fig. 10); i.e., the typical spacing at RCU decreased from 20 to 10 acres [8 to 4 ha] per well during this time. Two other pertinent reservoir performance points are shown on this graph. The first is that the producing wells in the waterflooded area have maintained pressure throughout this time. This confirmed that the decision to increase injection from the 80-acre [32-ha] inverted nine-spot pattern to the 40-acre [16-ha] inverted nine-spot pattern was sound and that pressures have been

maintained. The other point to note is that the typical east/west offset to the injectors throughout this time period has shown an extrapolated pressure roughly 200 to 300 psi [1.3 to 2.1 MPa] higher than either the north/south offsets or the 20-acre [8-ha] offsets. This tends to confirm a suspected directional permeability or fracture orientation in the east/west direction.

The continuity fraction for an injector/producer pair can be estimated by analyzing their $\bar{p}$'s in terms of a simple model. The extrapolated pressures in any given wellbore are the result of an average of pressures in the multiple zones that are open at the wellbore. In injectors, some of these zones will be relatively small, undrained, and pressured to the maximum—i.e., stabilized at the bottomhole injection pressure (BHIP). Some of the zones will be continuous to producing wells and, as such, will be at a relatively lower pressure because of the drainage. A similar situation exists in the producing wells, where some discontinuous zones will indeed be completely depleted to the pumping BHP. Other zones will be effectively supported by the offsetting injection. This situation is shown schematically in Fig. 11; there the average extrapolated formation pressure, $\bar{p}$, for all injection well tests is 3,810 psi [26 MPa], which compares to the average BHIP of 4,480 psi [30.9 MPa]. Similarly, in the producing wells, the average $\bar{p}$ of 2,450 psi [16.9 MPa] compares to a pumping BHP of 590 psi [4.1 MPa]. Although the exact relationship from one zone to another is not precisely quantifiable, the overall $\bar{p}$ is approximately representative of a permeability/thickness weighted average of pressures in all the zones open in the wellbore. This assumption permits the solution of two equations with two unknowns, also shown in Fig. 11. The results shown in Fig. 11 represent the averages of all tests run from 1981 through 1985. The calculated reservoir continuity, which is the percentage of zones open in both producing wells and injection wells, is about 65%. The similar percentage of discontinuous reservoir, of course, is 35%.

The other unknown, the average pressure, which is the pressure roughly halfway between the two wells, is 3,450 psi [23.8 MPa]. As will be discussed, this is very similar to pressures identified by wireline formation pressure tests. Applying a similar technique to

TABLE 1—SUMMARY OF RCU PRESSURE-TRANSIENT TESTING
Average value per well

	Producing Wells					Injectors
	40-acre Original Producers	North/South Offsets	20-acre Infills	East/West Offsets	Edge Wells	
Skin factor	0.5	0	-0.6	-1	-0.1	-2.3
Calculated fracture length, ft	1	1	3	13	1	39
Flowing BHP, psi	1,033	601	517	884	667	4,480
Formation pressure, psi	2,610	2,280	2,450	2,860	1,820	3,810
Transmissibility, md-ft/cp	68	307	80	178	139	947

the pressure differential between injectors and producers at different spacings yields a spread from about 71% continuity at 660 ft [200 m] to less than 50% continuity at 2,000 ft [610 m]. These data are plotted in Fig. 12 and compared with estimates by other techniques.

Another interesting observation from the averages of these many pressure-transient tests is the relative lack of fractures in the producing wells even though all wells were stimulated by acid fracturing on initial completion. On the other hand, the producing wells are not damaged either, indicating mostly effective completions in the wells tested. Despite injection slightly below the fracture pressure, nearly all injectors indicate good stimulation and some fracture. It is unknown whether this results from some zones fracturing at lower-than-indicated fracture pressure or from some leaching of the carbonate by the freshwater injection, giving a fracture-like appearance on the pressure transient.

The concept of widely varying pressures in individual stringers is supported by data from wireline formation pressure tests. These tests were run in eight new infill wells from 1981 to 1984, with pressures successfully measured in more than 50 separate intervals. These pressures ranged from 644 to 4,136 psig [4.4 to 28.5 MPa]. The pressure distribution in each wellbore was random between intervals, and only rarely would two pressures fall on a hydrostatic gradient line, which would indicate that the zones were in vertical communication.

In the intervals tested, some zones appeared to be pressure-supported. The average pressures in the supported zones were 3,430 psig [23.6 MPa] in the north/south offset wells and 3,580 psig [24.7 MPa] in the east/west wells. These agree reasonably well with the 3,450-psig [23.8 MPa] pressure calculated in Fig. 11.

Infill Productivity Experience

Table 2 lists the results of a study in which the production history of each well was extrapolated to an estimated economic limit. These results were then averaged to yield the estimated ultimate recovery, called "through-the-wellbore" in Table 2, for each of the various types of infill wells. A total of 218 wells is represented in this table, and the incremental through-the-wellbore production is about 24 million bbl [$3.8 \times 10^6 \text{ m}^3$]. Col. 4 is the result of detailed calculations of interference, on existing wells, from production of the

TABLE 2—RCU INFILL DRILLING PROGRAM RESULTS			
Type of Well	Number of Wells	Average Estimated Ultimate Recovery Per Well	
		Through Wellbore Estimated Ultimate Recovery (1,000 bbl)	Most Likely Capture Estimated Ultimate Recovery (1,000 bbl)
20-acre	83	166	158
North/south offsets	56	92	87
East/west offsets	58	70	67
Irregular or edge	21	78	74
Total for all wells	218	24,600	23,400

new infills. This study determined that 95% of the through-the-wellbore recovery of an infill well is incremental capture or unique oil. This analysis is subjective, and at RCU it was complicated further by response from conversion of additional wells to injection service during the program. As discussed later, however, it is believed to be reasonably accurate.

Another approach to estimate the incremental capture resulting from the infill wells is to compare the total field estimated ultimate recovery to that predicted before any infill drilling, in this case by the 1975-76 RCU study. This study, which used existing wellbores, predicted an ultimate recovery of 22 million bbl [$3.5 \times 10^6 \text{ m}^3$] by primary and 8 million bbl [$1.3 \times 10^6 \text{ m}^3$] by secondary, for a total of 30 million bbl [$4.8 \times 10^6 \text{ m}^3$] by existing operations. The study further estimated that improvements to current operations in the existing wellbores, primarily perforating and stimulating additional intervals, could improve ultimate recovery by as much as 12 million bbl [$1.9 \times 10^6 \text{ m}^3$]. This would yield a total recovery of 42 million bbl [$6.7 \times 10^6 \text{ m}^3$] from existing 40-acre [16-ha] wells. In hindsight, this figure was probably a maximum, if not slightly optimistic. The current estimate for ultimate recovery from the total unit is between 64 and 65 million bbl [10.2×10^6 and $10.3 \times 10^6 \text{ m}^3$]. This would attribute 22 to 23 million bbl [3.5×10^6 to $3.7 \times 10^6 \text{ m}^3$] to the total of 218 new or infill wells plus the results of injection-well conversions. The value of 23 million bbl [$3.65 \times 10^6 \text{ m}^3$] is within the accuracy of the 23.4 million bbl [$3.72 \times 10^6 \text{ m}^3$] shown as the most likely capture in Table 2.

Barber *et al.*⁵ predicted that at least 79% of the through-the-wellbore recoveries would be incremental capture. They had pre-

dicted that a total of one hundred and seven 20-acre [8-ha] wells would yield an incremental capture of 10.7 million bbl [$1.7 \times 10^6 \text{ m}^3$]. More recent data, as well as the results from about 100 additional infill wells, have shown that this estimate was indeed pessimistic. Incremental capture is now estimated to be between 90 and 95% of through-the-wellbore production.

Correlations of Infill Performance to Reservoir Quality

Good infill performance can result from either unusually poor reservoir continuity in a local area or better-than-average reservoir deliverability and quality. The very good infill results at RCU would be consistent with the hypothesis that the reservoir was unusually discontinuous in some areas. The technique used to test this hypothesis involved mapping the performance of various wells, as measured by the individual well estimated ultimate recoveries. Figs. 13 through 16 show areas of better-than-average well performance by well type, 40-acre [16-ha], 20-acre [8-ha], north/south, or east/west offset infill wells. These figures show that the good 20-acre [8-ha] wells were located in the same areas as good original 40-acre [16-ha] wells. Similarly, good 10-acre [4-ha] wells are found in the same area. This coincides roughly with areas of better-than-average net pay thickness. The ratio of net pay thickness inside the good area to that in the outside area is not quite as great as the ratio of well estimated ultimate recovery performance inside the good area to other areas. This indicates that in addition to thicker net pay in this area of the field, the reservoir quality and deliverability are also better.

**TABLE 3—COMPARISON OF THROUGH-THE-WELLBORE
ESTIMATED ULTIMATE RECOVERIES**

Type of Wellbores Compared	Average Estimated Ultimate Recovery Ratio (Infill vs. Older Wells)
20-acre well to average 40-acre direct offset	0.44
North/south 10-acre well to average 40-acre direct offset	0.23
North/south 10-acre well to average 20-acre direct offset	0.50
East/west 10-acre well to average 40-acre direct offset	0.18
East/west 10-acre well to average 20-acre direct offset	0.38

Table 3 compares the ratio of individual infill well estimated ultimate recovery performance to the estimated ultimate recoveries of its offsets. Four 40-acre [16-ha] wells surrounding each 20-acre [8-ha] infill were averaged and ratioed vs. the 20-acre [8-ha] estimated ultimate recovery. Each 10-acre [4-ha] well is offset by two 20-acre [8-ha] wells and by two 40-acre [16-ha] wells. These were averaged separately for the ratios. These ratios can be used to estimate recovery from additional locations that have not yet been drilled.

Numerical Analyses of Produced Volumes

A third approach to quantitative analysis of infill performance and reservoir continuity involved a modified nonlinear regression on the performance data. For this analysis, *drainable* describes the reservoir volume that can be drained to a wellbore by solution gas drive, and *floodable* describes the reservoir volume sufficiently continuous to be waterflooded between at least one injector/producer pair.

By use of the definitions for A , B , C , D , and F_p as shown in the Nomenclature, recoveries for wells within the area of 10-acre [4-ha] development are as follows.

1. Primary per 40-acre [16-ha] well is $A+B+C+D$.
2. Secondary per 40-acre [16-ha] well is $F_p(A)$.
3. Primary per 20-acre [8-ha] well is $C+D$.
4. Secondary per 20-acre [8-ha] well is $F_p(B)$.
5. Total per 20-acre [8-ha] well is $F_p(B)+C+D$.
6. Primary per 10-acre [4-ha] well is D .
7. Secondary per 10-acre [4-ha] well is $F_p(C)$.
8. Total per 10-acre [4-ha] well is $F_p(C)+D$.

Although continuity is really a measure of reservoir PV, for simplicity, A , B , C , and D are defined in terms of primary recovery—i.e., a constant recovery factor times the affected PV.

In the area of the field fully developed on 10-acre [4-ha] spacing, the actual well recoveries are listed in Table 4. (This area is shown in Fig. 17.) The “nominal” value represents the through-the-wellbore recoveries. The range is intended to account for drainage into or away from the well because of interference with other wells.

The most likely values are based on estimates for the following.

1. Some primary recoverable oil for 40-acre [16-ha] wells was drained to infill wells and/or misallocated to the secondary project.

**TABLE 4—ACTUAL WELL RECOVERIES FOR
A FULLY DEVELOPED 10-ACRE SPACING**

Well Type and Mode	Average Recovery (1,000 bbl)		
	Nominal	Range	Most Likely
40-acre primary			
40-acre secondary			
20-acre total			
10-acre total

Fig. 17—RCU base map with area of 10-acre/well development highlighted.

2. Secondary production (40 acres [16 ha]) is essentially nominal because minor drainage to infill wells would more or less balance a possible misallocation of primary to secondary in allocating the well's estimated ultimate recovery.

3. The 20- and 10-acre [8- and 4-ha] wells produced oil that could eventually have been produced by the 40-acre [16-ha] wells.

Although the equations given earlier contain five unknowns, they can be solved approximately because of the requirement for all variables to be positive. If the most likely parameters are used, A , B , C , and D are positive only for a range of F_p between 1.39 and 1.43, with a most reasonable value of 1.395. Throughout the range of parameters, F_p could vary between 1.3 and 1.55, but the most reasonable value of 1.395 is stable within likely perturbations of the most likely value.

The derived values for A , B , C , D , and F_p can be related to reservoir continuity in two ways. The first involves comparison of recoveries, by well type and mode, with the volumetrically calculated OOIP for an average 40-acre [16-ha] tract. Estimates of continuity in this case range up to 80%. Continuity estimates for various spacings are listed in Table 5. The detailed calculations are in the Appendix.

The second correlation is based on the assumption that ratios of actual primary and secondary recovery factors to the theoretical factors equal the continuity fractions for the field spacing. For 10-acre [4-ha] spacing, this analysis yields values of 87 and 63% for drainable and floodable fractions, respectively (see the Appendix for details).

**TABLE 5—RESERVOIR CONTINUITY
BY NUMERICAL ANALYSES**

Spacing (acres/well)	Reservoir Drainable by Solution Gas Drive	Reservoir Floodable Between at Least 2 Wells
	(%)	(%)
40	56	27
20	70	43
10	80	60

Conclusions

1. Infill drilling has been a successful program at RCU, both on spacings of 20 acres [8 ha] per well and further infilling to 10 acres [4 ha] per well.
2. At RCU, with 10-acre [4-ha] spacing, about 80 to 85 % of the reservoir PV is drainable by solution gas drive; with 40-acre [16-ha] inverted nine-spot patterns, about 60 % is floodable between at least two wells.
3. The apparent difference in extrapolated transient pressures between producing wells and injection wells is a direct and correlatable function of the discontinuity between wells.
4. Pressure correlations, numerical analysis, and finely detailed geologic correlations have all been used successfully to quantify the degree of discontinuity in the reservoir formation at RCU.
5. Discontinuity must be considered in the design, planning, and operation of any EOR project because of the relatively large volumes of pay that cannot be flooded.
6. There is a preferential water movement at RCU in the east/west direction, either as a result of fracturing in the reservoir or from an in-situ directional permeability.

Nomenclature

- A = primary recovery from that fraction of reservoir that could be floodable on 40-acre [16-ha] spacing, bbl [m^3]
 B = primary recovery from that fraction of reservoir that is drainable on 40-acre [16-ha] spacing but floodable only on 20-acre [8-ha] spacing, bbl [m^3]
 C = primary recovery from that fraction of reservoir that is drainable on 20-acre [8-ha] spacing but floodable only with 10-acre [4-ha] spacing, bbl [m^3]
 D = primary recovery from that fraction of reservoir that is drainable only on 10-acre [4-ha] spacing but not floodable on 10-acre [4-ha] spacing, bbl [m^3]
 F_p = ratio of secondary to primary production from the portion of reservoir that is effectively waterflooded

References

1. George, C.J. and Stiles, L.H.: "Improved Techniques for Evaluating Carbonate Waterfloods in West Texas," *JPT* (Nov. 1978) 1547-54.
2. Galloway, W.E. et al.: *Atlas of Major Texas Oil Reservoirs*, Bureau of Economic Geology, U. of Texas, Austin (1983).
3. McKinley, R.M.: "Wellbore Transmissibility from Afterflow-Dominated Pressure Buildup Data," *JPT* (July 1971) 863-72; *Trans.*, AIME, 251.
4. Matthews, C.S. and Russell, D.G.: *Pressure Buildup and Flow Tests in Wells*, Monograph Series, SPE, Richardson, TX (1967) 1, 108.
5. Barber, A.H. Jr. et al.: "Infill Drilling to Increase Reserves—Actual Experience in Nine Fields in Texas, Oklahoma, and Illinois," *JPT* (Aug. 1983) 1530-38.
6. Staggs, H.M. Jr. and Bilhartz, H.L. Jr.: "Waterflood Correlation to Forecast Rate and Reserves," paper API 906-14-K presented at the 1969 API Southwestern District Meeting, Lubbock, March 12-14.

Appendix—Waterflood Recovery Estimate for Floodable Reservoir

Robertson reservoir parameters include the following.

- Dykstra-Parsons coefficient=0.833.
 Mobility ratio=0.96.
 Gas saturation at flood start=0.13 (in drained areas).
 Water viscosity=0.6 cp [0.6 mPa·s].
 Oil viscosity at flood start=1.17 cp [1.17 mPa·s].
 Initial oil saturation=0.708.
 Residual oil saturation=0.34.

With these parameters, waterflood conformance can be estimated by use of Staggs and Bilhartz's technique⁶ to sweep 73 % of the floodable volume. Assuming that oil resaturates 50 % of the "unswept" gas saturation (an approximation based on other detailed waterflood studies in west Texas carbonates), the calculated ultimate

recovery from the floodable portion of the formation is 31 to 32 % of the OOIP.

As discussed in the Numerical Analysis of Produced Volumes section, the ratio of secondary to primary production in the swept reservoir is 1.395. With this ratio, the primary and secondary recovery factors are estimated at 13.2 and 18.3 % of OOIP, respectively.

In the 10-acre [4-ha] infill area at RCU, average OIP is 3.36 million STB [0.53×10^6 stock-tank m^3] per 40-acre [16-ha] tract. Theoretical primary and secondary recoveries, therefore, would be $(3.36 \text{ million}) \times (13.2\%) = 444 \times 10^3$ bbl [$71 \times 10^3 \text{ m}^3$] and $(3.36 \text{ million}) \times (18.3\%) = 615 \times 10^3$ bbl [$98 \times 10^3 \text{ m}^3$], respectively, if continuity were 100 % throughout the reservoir.

The fraction of reservoir volume drainable or floodable on various spacings can then be estimated with the parameters derived by numerical analysis. The most likely parameters are

$$A = 118,000 \text{ bbl } [18.8 \times 10^3 \text{ m}^3],$$

$$B = 72,000 \text{ bbl } [11.4 \times 10^3 \text{ m}^3],$$

$$C = 38,000 \text{ bbl } [6.0 \times 10^3 \text{ m}^3],$$

$$D = 22,000 \text{ bbl } [3.5 \times 10^3 \text{ m}^3], \text{ and}$$

$$F_p = 1.395.$$

The following calculations show the drainable or floodable reservoir volume for the various well spacings.

The 40-acre [16-ha] drainable fraction is

$$\frac{A+B+C+D}{444} = \frac{118+72+38+22}{444} = 0.56.$$

The 40-acre [16-ha] floodable fraction is

$$\frac{F_p(A)}{615} = \frac{1.395(118)}{615} = 0.27.$$

The 20-acre [8-ha] drainable fraction is

$$\frac{A+B+2C+2D}{444} = \frac{118+72+2(38)+2(22)}{444} = 0.70.$$

The 20-acre [8-ha] floodable fraction is

$$\frac{F_p(A+B)}{615} = \frac{1.395(118+72)}{615} = 0.43.$$

The 10-acre [8-ha] drainable fraction is

$$\frac{A+B+2C+4D}{444} = \frac{118+72+2(38)+4(22)}{444} = 0.80.$$

The 10-acre [8-ha] floodable fraction is

$$\frac{F_p(A+B+2C)}{615} = \frac{1.395[118+72+2(38)]}{615} = 0.60.$$

The effective secondary-to-primary ratio for each 40-acre [16-ha] tract within the 10-acre [8-ha] infill area is

$$\frac{F_p(A+B+2C)}{A+B+2C+4D} = 1.0.$$

These are the actual recoveries for this area.

Total estimated ultimate recovery = 43.7 million STB [7.5×10^6 stock-tank m^3].

OOIP = 206 million STB [32.7×10^6 stock-tank m^3].

$$\text{Actual recovery factor} = \frac{47.3}{206}$$

$$= 23\%.$$

$$\text{Actual primary recovery} = 23\% \times \frac{1}{1+1}$$

at 1:1 secondary/primary

$$= 11.5\%.$$

Fraction drainable by primary

$$= 11.5\% \text{ actual primary recovery}$$

$$13.2\% \text{ theoretical primary recovery}$$

$$= 87\% \text{ drainable volume fraction.}$$

$$\begin{aligned} \text{Actual Secondary} &= 23\% \times \frac{1}{1+1} \\ &\text{at 1:1 secondary/primary} \\ &= 11.5\%. \end{aligned}$$

$$\begin{aligned} \text{Floodable volume} &= \frac{11.5\% \text{ actual secondary recovery}}{18.3\% \text{ theoretical secondary recovery}} \\ &= 63\% \text{ floodable volume fraction.} \end{aligned}$$

SI Metric Conversion Factors

acres	$\times 4.046\ 873$	E-01	= ha
bbl	$\times 1.589\ 873$	E-01	= m^3
cp	$\times 1.0^*$	E-03	= $Pa \cdot s$
ft	$\times 3.048^*$	E-01	= m
psi	$\times 6.894\ 757$	E+00	= kPa

*Conversion factor is exact.

JPT

Original SPE manuscript received for review Oct. 5, 1986. Paper accepted for publication July 6, 1987. Revised manuscript received Sept. 2, 1987. Paper (SPE 15568) first presented at the 1986 SPE Annual Technical Conference and Exhibition held in New Orleans, Oct. 5-8.

Infill Drilling To Increase Reserves— Actual Experience in Nine Fields in Texas, Oklahoma, and Illinois

A.H. Barber Jr., SPE, Exxon Co. U.S.A.

C.J. George, SPE, Exxon Co. U.S.A.

L.H. Stiles, SPE, Exxon Co. U.S.A.

B.B. Thompson, SPE, Exxon Co. U.S.A.

Summary

Evaluation of reservoir discontinuity has been used by industry to estimate potential oil recovery to be realized from infill drilling. That this method may underestimate the additional recovery potential is shown by continuity evaluation in a west Texas carbonate reservoir, as infill drilling progressed from 40-acre ($162 \times 10^3\text{-m}^2$) wells to 20-acre ($81 \times 10^3\text{-m}^2$) wells and eventually to 10-acre ($40.5 \times 10^3\text{-m}^2$) wells.

Actual production history from infill drilling in nine fields, including carbonate and sandstone reservoirs, shows that additional oil recovery was realized by improving reservoir continuity with increased well density.

Introduction

One objective of an orderly field-development program is to determine the maximum well spacing that will effectively drain oil and gas reserves. While wide spacing has proved effective in many oilfield applications, there are a growing number of examples where infill drilling, combined with water-injection pattern modifications, has provided substantial additional oil reserves. This paper deals with such fields: Means, Fullerton, Robertson, IAB (Menielle Penn), Howard Glasscock, Dorward, and Sand Hills fields in west Texas, Hewitt field in southern Oklahoma, and Loudon field in Illinois. The paper will quantify the contribution to current production and the additional reserves attributable to this action, using data available through Oct. 1981. Infill drilling has continued in most of these fields. Also revealed by infill drilling is the fact that the west Texas carbonate reservoirs are more stratified, and porous stringers are more discontinuous than revealed by initial studies.

Background

The theoretical concepts indicating that infill drilling will increase reservoir continuity and improve waterflood pattern conformance in heterogeneous west Texas carbonate reservoirs were researched and published in the early 1970's by Ghauri,¹ Ghauri *et al.*,² Stiles,³ George,⁴ and Driscoll.⁵

Detailed field studies recommending infill-drilling and waterflood-pattern modifications were made for the Means, Fullerton, and Robertson fields by Stiles and George.^{3,4} Unpublished studies were made for the other reservoirs prior to infill drilling.

Borrowed from a previous work by George and Stiles,⁴ Fig. 1 is a type cross section in the Fullerton Clearfork reservoir that illustrates the concept of "continuity," the percentage of pay in a well that is continuous to another well. The two original Wells A and B are 40-acre ($162 \times 10^3\text{-m}^2$) locations, and the center well is an infill location 660 ft (201.2 m) from either original well. Note the discontinuous nature of the porosity stringers and that correlation before the infill well was drilled would have been considerably different than it is after the infill well was drilled. The increase in net pay in the infill well, especially in the upper part of the Clearfork formation, illustrates the fact that the more wells that are drilled, the more highly stratified, discontinuous, and complex a given west Texas carbonate reservoir is found to be. This fact leads to a conservative evaluation of the potential increased recovery from an infill well.

Considerations in Infill Drilling

A progression of continuity improvement was revealed by infill drilling in the Means San Andres field. Fig. 2 is a statistical plot of continuous pay vs. horizontal distance

between wells for an area at Means that has been infilled to 10-acre ($40.5 \times 10^3 \text{ m}^2$) density. This technique was used by Shell Oil Co.⁶ and was discussed by Stiles³ in a previous paper. The top curve, made prior to infill drilling, shows the increase in apparent continuity between wells with increasing well density. Subsequent curves, made after infill drilling, show the pay development to be more discontinuous than would have been predicted. As shown by the upper curve, based on 40-acre ($162 \times 10^3 \text{ m}^2$) wells alone, an increase in continuity of 3% would be expected as spacing decreased from 20 acres ($81 \times 10^3 \text{ m}^2$) to 10 acres ($40.5 \times 10^3 \text{ m}^2$). The second curve, after 20-acre ($81 \times 10^3 \text{ m}^2$) wells were drilled, shows that with only 40-acre ($162 \times 10^3 \text{ m}^2$) and 20-acre ($81 \times 10^3 \text{ m}^2$) wells, an increase in continuity of 4% would be anticipated as spacing decreased from 20 acres ($81 \times 10^3 \text{ m}^2$) to 10 acres ($40.5 \times 10^3 \text{ m}^2$). The analysis including the 10-acre ($40.5 \times 10^3 \text{ m}^2$) wells, shown by the lower line, indicates an apparent 14% improvement in continuity. The absolute values obtained for this particular area of the field are not necessarily typical of what would be expected throughout the field but do illustrate the concept of progressive increase in continuity with closer well spacing.

The complexity of stringerization is even more obvious after Fig. 3 is examined. This is a cross section

Fig. 1—Type cross section—Fullerton Clearfork reservoir (adapted from Ref. 4).

Fig. 2—Continuity progression—Means San Andres Unit.

Fig. 3—Porosity and permeability variations—Means tertiary pilot.

through three wells in a tertiary pilot in the Means San Andres reservoir. The wells are located approximately 150 ft (45.7 m) apart, and core porosity and permeability have been correlated over the same stratigraphic interval. Porosity is plotted to the left and permeability is plotted on a log scale to the right. The pay intervals are relatively continuous between wells, but the porosity variations are significant in an individual stringer between wells. Permeability variations are even more severe. With injected fluids taking the path of least resistance, this plot serves to illustrate why, even in stringers that are continuous between wells, recovery may be lower than anticipated.

In a previous paper,³ it was stated that a pay interval must meet the following three requirements for waterflooding.

1. It must be continuous and reasonably homogeneous between an injection well and the offset producing wells.
2. It must be injection supported.
3. It must be effectively completed in the offset producing well.

In many west Texas Permian carbonate reservoirs there may be 50 or more individual pay stringers. Only rarely will all the stringers be effectively completed in a specific well. When a pay stringer is not effectively completed in a given well, a partial pattern exists for that stringer, and recovery will be less than for a complete pattern. These considerations were used to evaluate infill drilling and pattern modifications in several fields.

Infill Drilling Results

Major infill drilling programs were implemented in nine fields in west Texas, Oklahoma, and Illinois. These fields include dolomite, limestone, and sandstone reser-

voirs with porosities varying from 4 to 21% and with average permeabilities varying from 0.65 to about 184 md. Two of the fields are still on primary production, the other seven are waterflood fields. A detailed discussion of each of these fields follows.

Means San Andres Unit

One of the first fields studied was the Means San Andres reservoir in Andrews County, TX. Production is from a depth of 4,400 ft (1341 m). The San Andres is over 1,400 ft (427 m) thick, but only the upper 200 to 300 ft (61 to 91 m) is productive at Means. It is predominantly dolomite with minor shale and anhydrite. Average porosity and permeability are 9% and 20 md, respectively. Oil viscosity was 6 cp (6 mPa·s) at initial reservoir conditions. The reservoir was discovered in 1934 and drilled to 40-acre ($162 \times 10^3\text{-m}^2$) spacing. Waterflooding began in 1963 with a peripheral pattern, which was expanded to a three-to-one line drive in 1970. Following a detailed reservoir study in 1975, a large-scale infill-drilling and pattern-modification program was begun. By the 1981 study cutoff date, 141 twenty-acre ($81 \times 10^3\text{-m}^2$) and 16 ten-acre ($40.5 \times 10^3\text{-m}^2$) infill wells had been drilled. During this period the pattern was gradually changed, generally to an 80-acre ($324 \times 10^3\text{-m}^2$) inverted nine-spot.

Actual production from the 40-acre ($162 \times 10^3\text{-m}^2$) wells is shown by the lower line in Fig. 4. Production from the total unit is shown by the upper line. The area between these lines is wellbore oil production from the infill wells. The area between the dashed line and actual 40-acre ($162 \times 10^3\text{-m}^2$) well production is interference oil. Increased recovery resulting from infill drilling is that production represented by the area between the

dashed line and the total unit production. The infill wells account for 68% of the unit daily production.

Increased recovery is calculated to be 15.4 million bbl ($2.4 \times 10^6 \text{ m}^3$) oil, or 66% of the total oil produced by the infill wells. The unit was divided into 40-acre ($162 \times 10^3 \text{ m}^2$) tracts and the original oil in place (OOIP) was calculated volumetrically for each of these tracts.⁴ Additional recovery was calculated for each infill well, and as to be expected, the recoveries varied widely. In general, the additional recovery for the 20-acre ($81 \times 10^3 \text{ m}^2$) infill wells ranged from 5 to 8% OOIP in the 40-acre ($162 \times 10^3 \text{ m}^2$) tract in which the infill well was drilled.

In a smaller area in the Means field sixteen 10-acre ($40.5 \times 10^3 \text{ m}^2$) wells were drilled in two pilot areas in 1979 and 1980. Fig. 5 shows the impact of the 10-acre ($40.5 \times 10^3 \text{ m}^2$) infills on the production in the pilot areas. Decline-curve analysis indicates that additional recovery from the 10-acre ($40.5 \times 10^3 \text{ m}^2$) infills will be 1.2 million bbl ($1.9 \times 10^5 \text{ m}^3$) oil, or 67% of the wellbore recovery. Additional recovery from the 10-acre ($40.5 \times 10^3 \text{ m}^2$) infill wells is estimated to vary from 2 to 5% OOIP in the 40-acre ($162 \times 10^3 \text{ m}^2$) tract in which the infill well was drilled.

Fullerton Field

The Fullerton Clearfork Unit, also located in Andrews County, TX, produces from the Permian Clearfork and Wichita formations, which are predominantly dolomite interbedded with limestone, anhydrite, and shale. Production is from an average depth of 7,000 ft (2134 m), and the reservoir averages 10% porosity and 3-md permeability. At initial reservoir conditions, the oil viscosity was 0.75 cp (0.75 mPa·s).

Fullerton was discovered in 1942 and was originally developed on 40-acre ($162 \times 10^3 \text{ m}^2$) spacing. The Fullerton Clearfork Unit has been under water injection since 1961. The original pattern used in the largest portion of the field, the North dome, was a three-to-one line drive, with the injectors oriented north-south. The original north-south injection rows are shown in Fig. 6. Note the 80 acres ($324 \times 10^3 \text{ m}^2$) outlined by the dashed line. An 80-acre ($324 \times 10^3 \text{ m}^2$) tract in this position will be discussed further.

Based on the recommendations of a 1973 study reported by Stiles,³ a program later called the Phase I Infill Program was initiated. Under this program, the wells shown by the solid dots in Fig. 6 were drilled as infill producers, and half the adjacent row producers were converted to injection wells as shown by the solid triangles. Sixty-one Phase I wells were drilled. At the conclusion of the Phase I drilling in 1976, the average production of the Phase I wells was 88 B/D ($14 \text{ m}^3/\text{d}$) oil with a 46% water cut. Average production for the offset wells was about half, or 46 B/D ($7.3 \text{ m}^3/\text{d}$) oil, with a 68% water cut. The fact that these infill wells performed better than the offsets indicated that additional pay was being opened up, which in turn implied that less than all the pay was being flooded.

An 80-acre ($324 \times 10^3 \text{ m}^2$) tract, outlined in Fig. 6, has been enlarged and is shown in Fig. 7. The original north-south injection row is to the left and the black dot to the right fixes the location of the 61 Phase I wells. The

Fig. 4—Production datagraph—Means San Andres Unit.

Fig. 5—Production datagraph—10-acre pilot, Means San Andres Unit.

Fig. 6—Phase 1 infill drilling—Fullerton Clearfork Unit.

Fig. 7—Pilot infill drilling—Fullerton Clearfork Unit.

Fig. 8—Phase 2 infill drilling—Fullerton Clearfork Unit.

Fig. 9—Production datagraph—Fullerton Clearfork Unit.

solid triangle shows the location of the Phase I injection conversion. Prior to the Phase I program, seven wells had been drilled between 1970 and 1972 in the positions shown by the hexagons. These wells had average initial potentials of 221 B/D (35.1 m³/d) oil, and in July 1976 they were producing an average of 92 B/D (14.6 m³/d) oil and 70% water. Their offset wells were producing an average of 26 B/D (4.1 m³/d) oil. The performance of the Phase I wells and the seven earlier wells suggested that additional recovery might be obtained if wells were drilled anywhere within the pattern. In 1976, three wells were drilled in the position shown by the square. They produced an average of 115 B/D (18.3 m³/d) oil with a 74% water cut. Four of the six direct offsets to these wells had been shut in from 4 to 9 years earlier as uneconomical to produce. One was a producer testing 1 B/D (0.16 m³/d) oil and 500 B/D (79.5 m³/d) water. The sixth was an injector that had been converted in 1975 while producing 38 B/D (6 m³/d) oil.

As a result of these 10 pilot wells, a 151-well Phase II infill drilling program at Fullerton was undertaken. Phase II wells have been drilled in the position shown by the square in Fig. 8. Wells in the position captioned "Phase II Conversion" are being converted to injection as part of the Phase II program. Of the 171 wells in this conversion location, 111 were watered out by 1976. Most others were producing at very low rates. It can be concluded that Phase II wells are mostly additional recovery. The production contribution from these infill drilling programs can be seen in Fig. 9. This datagraph shows the impact of the Phase I, Phase II, and other infill wells. These wells account for 71% of the unit's current production and will result in additional recovery of 24.6 million bbl (3.9×10⁶ m³) oil. Fifty-six percent of the wellbore reserves are increased recovery and will average about 97,000 bbl (15.4×10³ m³) per infill well.

Robertson Field

The Robertson Clearfork Unit in Gaines County, TX, produces from the Permian Glorieta, Upper Clearfork, and Lower Clearfork formations, at an average depth of 6,500 ft (1981 m). The reservoir is about 1,400 ft (427 m) thick with actual net pay of about 200 to 300 ft (61 to 91 m), broken vertically into as many as 50 to 60 separate porosity stringers in any given well: Fig. 10, a cross section between two 40-acre (162×10³-m²) wells, better illustrates the extreme stringerization. The reservoir rock is predominantly dolomite with anhydrite and shale. Porosity averages 6.3% and permeability averages 0.65 md. Oil viscosity at reservoir conditions is 1.2 cp (1.2 mPa·s). Beginning in 1942, the area was drilled on 40-acre (162×10³-m²) locations. In 1969, the unit was formed for waterflooding. From 1976 through 1980, 107 infill wells were drilled on 20-acre (81×10³-m²) spacing. A 10-acre (40.5×10³-m²) drilling program has begun with 31 wells completed through Oct. 1981.

The contribution of the 20-acre (81×10³-m²) and 10-acre (40.5×10³-m²) wells is shown in Fig. 11. The dashed line represents the expected production from the 40-acre (162×10³-m²) wells had there been no infills. Infill wells provide 73% of the current production. They are expected to add additional reserves of 10.7 million

bbl ($1.7 \times 10^6 \text{ m}^3$). Increased recovery represents 79% of the wellbore reserves and is about 73,000 bbl ($11.6 \times 10^3 \text{ m}^3$) per well.

IAB Field

The IAB (Menielle Penn) field is located in Coke County, TX. The Menielle Penn reservoir produces from a depth of 5,800 ft (1768 m) and is a coarse skeletal limestone buildup with an average of 7% porosity and 27-md permeability. The oil viscosity at initial reservoir conditions was only 0.2 cp (0.2 mPa·s) at IAB. The reservoir was discovered in 1958 and was drilled initially on 80-acre ($324 \times 10^3 \text{ m}^2$) spacing. Waterflooding began in 1962 with an initial pattern which was essentially a three-to-one line drive. Fig. 12 is the production datagraph showing the impact from a 17-well 40-acre ($162 \times 10^3 \text{ m}^2$) infill drilling program that began in 1978. The dashed line is an extrapolation of what the 80-acre ($324 \times 10^3 \text{ m}^2$) wells would have done if the infill wells had not been drilled. The lower solid line shows the actual and forecasted performance of the old wells. This analysis shows that the infill wells will increase the field's reserves by 1.7 million bbl ($2.7 \times 10^6 \text{ m}^3$). This represents additional recovery of 100,000 bbl ($1.59 \times 10^5 \text{ m}^3$) per well, which is 58% of the wellbore reserves and 4% of OOIP in the affected area.

Howard-Glasscock Field

The Douthit Unit, located in Howard and Sterling Counties, TX, was formed for waterflooding the Permian Seven Rivers reservoir in the Howard-Glasscock field. The reservoir is approximately 1,400 ft (427 m) deep and is a sandstone with a porosity of 18% and a permeability of 44 md. In this reservoir, the oil viscosity of 9.4 cp (9.4 mPa·s) is relatively high for west Texas reservoirs. Development of the Seven Rivers reservoir in this area began in 1957, and it was originally drilled on 40-acre ($162 \times 10^3 \text{ m}^2$) locations. Waterflooding began in 1968 with a peripheral injection pattern. Ten-acre ($40.5 \times 10^3 \text{ m}^2$) development began in 1976, and, by the 1981 study cutoff date, 52 infill wells had been drilled. The production datagraph, Fig. 13, shows the additional production from the infills along with production from the older wells. The infill wells account for 75% of the current production, and wellbore production is 88% additional recovery. Total additional recovery of 1.0 million bbl ($1.59 \times 10^6 \text{ m}^3$) is expected.

Dorward Field

The Dorward field is located in Scurry and Garza Counties, TX. Production is commingled from the Permian San Angelo and San Andres formations at average depths of 2,350 and 2,100 ft (716 and 640 m), respectively. The San Angelo formation is mostly dolomite interbedded with shale and sandstone. The San Andres consists of dolomite, anhydrite, and shale. Apparent porosity for the San Angelo and San Andres are 15 and 13.5%, respectively. Actual porosities are probably less because of the presence of gypsum, which causes optimistic measurements of porosities in cores and logs. Average permeability is about 3 md in both reservoirs. In the San Angelo, the oil viscosity is 1.9 cp (1.9 mPa·s) while in the San Andres, it is 3.2 cp (3.2 mPa·s).

Fig. 10—Cross section—Robertson Clearfork Unit.

Fig. 11—Production datagraph—Robertson Clearfork Unit.

Fig. 12—Production datagraph—IAB (Menielle Penn) field.

Fig. 13—Production datagraph—Douthit Unit, Howard-Glasscock field.

Fig. 14—Production datagraph—Dorward field.

Fig. 15—Production datagraph—Sand Hills area.

The field was discovered in 1950 and drilled on 40-acre ($162 \times 10^3\text{-m}^2$) spacing. Although waterflooding began in 1958 in a portion of the field, most of the field has been and is currently producing primary oil by dissolved-gas drive. Peripheral and 80-acre ($324 \times 10^3\text{-m}^2$) five-spot patterns were tried. Early water breakthrough, caused by directional permeability and severe stratification, discouraged expansion of waterflooding to other areas.

Infill drilling began in 1971. At that time, 149 wells on 40-acre ($162 \times 10^3\text{-m}^2$) spacing had been drilled. An average of 49,400 bbl (7850 m^3) oil per well had been accumulated, and production had declined to an average of 4.8 B/D ($0.76\text{ m}^3/\text{d}$) oil per well for the 107 wells still producing at that time. From 1971 through 1980, there were 123 twenty-acre ($81 \times 10^3\text{-m}^2$) infill wells drilled. Ten-acre ($40.5 \times 10^3\text{-m}^2$) drilling began in 1979, and 17 wells had been drilled by the end of 1980. Fig. 14 shows the results.

Because production was nearing the economic limit when infill drilling began, essentially all production from the infill wells is considered increased recovery. The infill wells will provide additional recovery of 4.6 million bbl ($7.3 \times 10^5\text{ m}^3$) of oil or 33,000 bbl (5244 m^3) per well. The field is now being studied for further 10-acre ($40.5 \times 10^3\text{-m}^2$) development and to determine if waterflooding is feasible with increased well density.

Sand Hills

Infill drilling in the Sand Hills area of Crane County, TX has been concentrated in the Sand Hills (Tubb and McKnight) fields. The Tubb reservoir produces from the Permian Lower Clearfork formation at a depth of 4,250 ft (1295 m) and is anhydritic dolomite with a minor amount of limestone. Average porosity and permeability are 4% and 12 md, respectively. Oil viscosity in the Tubb is 1.5 cp ($1.5\text{ mPa}\cdot\text{s}$) at initial reservoir conditions. The McKnight reservoir produces from the Permian Lower San Andres at a depth of 3,200 ft (975 m) and is also mostly anhydritic dolomite. In this reservoir, average porosity and permeability are 5% and 1.3 md, respectively. In the McKnight reservoir, the oil viscosity is 1.0 cp ($1.0\text{ mPa}\cdot\text{s}$). Gross productive interval is approximately 400 ft (122 m) in the Tubb and 350 ft (107 m) in the McKnight. Both reservoirs are highly stringerized with indications of poor reservoir continuity. They are both productive throughout the area of interest.

The Sand Hills (Tubb) field was discovered in 1931 and was generally developed on 40-acre ($162 \times 10^3\text{-m}^2$) spacing. In the area of interest, most of the Tubb 40-acre ($162 \times 10^3\text{-m}^2$) drilling was between 1936 and 1941. Development of the McKnight reservoir did not begin until 1955. McKnight development was erratic, depending largely on recompletions from the depleting Tubb reservoir; however, there was some drilling along with the workovers. Most of the 40-acre ($162 \times 10^3\text{-m}^2$) McKnight activity was from 1955 to 1965 and later during the 1970's.

A 20-acre ($81 \times 10^3\text{-m}^2$) infill program was begun in 1979. By the 1981 cutoff date, 56 infill wells had been drilled, with most of them being dually completed in both reservoirs. As expected, these wells found stringers that were pressure depleted but also found stringers that

Fig. 16—Production datagraph—Hewitt Unit, Hewitt field (OK).

Fig. 17—Production datagraph—Loudon field (IL).

were only partially depleted or had not been penetrated by other wells. Forty-acre ($162 \times 10^3\text{-m}^2$) development had continued until the time when the 20-acre ($81 \times 10^3\text{-m}^2$) infill program began. Thus, a substantial amount of total production was flush production from recently drilled wells. Production from the older 40-acre ($162 \times 10^3\text{-m}^2$) locations, those drilled before 1975, was 5.5 B/D ($0.87 \text{ m}^3/\text{d}$) oil from the McKnight and 5.3 B/D ($0.84 \text{ m}^3/\text{d}$) oil from the Tubb. Remaining reserves from these wells were about 9,000 bbl (1431 m^3) per well.

Fig. 15 shows both the performance of the 20-acre ($81 \times 10^3\text{-m}^2$) infills and offset 40-acre ($162 \times 10^3\text{-m}^2$) wells, including the recently drilled ones. During 1981, the infills produced 45% of the total production. Performance to date indicates they will ultimately produce 1.6 million bbl ($2.5 \times 10^5 \text{ m}^3$) of additional oil or 28,400 bbl (4516 m^3) per well. This recovery compares favorably with the estimated remaining 9,000 bbl (1430 m^3) per well from the older 40-acre ($162 \times 10^3\text{-m}^2$) wells. Because of the extreme lenticularity of these reservoirs and difficulty in obtaining reliable porosity data, good values for OOIP are not available.

Hewitt Field

The Hewitt field, located in Carter County, OK, was discovered in 1919. Production is from 22 Pennsylvanian Hoxbar and Deese sand intervals, with a gross thickness of over 1,500 ft (457 m). The many sand intervals are separated by shale zones. Average depth to the top of the first pay interval is about 2,000 ft (610 m). The sands have an average porosity of 21% and an average permeability of 184 md. Oil viscosity in this reservoir is 8.7 cp ($8.7 \text{ mPa}\cdot\text{s}$). In the area of infill drilling, the original spacing was 2.5 acres ($10 \times 10^3\text{-m}^2$). After the field was unitized for secondary recovery operations, many of the old wells were plugged and the field was redrilled on 10-acre ($40.5 \times 10^3\text{-m}^2$) spacing. A fieldwide 20-acre ($81 \times 10^3\text{-m}^2$) five-spot water injection project was begun.⁷ Fifteen five-acre ($20 \times 10^3\text{-m}^2$) infills have been drilled and their impact is shown in Fig. 16. The infills account for 23% of current unit production. Our analysis indicates about 60% of the wellbore reserves will be increased recovery and will total about 400,000 bbl ($6.4 \times 10^4 \text{ m}^3$) from the 15 wells.

The performance of the best well of these infills is a good example of the erratic nature of the porosity development and fluid-flow characteristics of this reservoir. This well potential for 414 B/D ($65.8 \text{ m}^3/\text{d}$) oil with a 50% water cut, although one offset was producing 44 B/D ($7.0 \text{ m}^3/\text{d}$) oil with a 96% water cut, and the other was producing only 7 B/D ($1.1 \text{ m}^3/\text{d}$) oil with a 99% water cut. Overall project water cut is 97%. This type of result was obtained in a reservoir that was developed on 2.5-acre ($10 \times 10^3\text{-m}^2$) spacing with a 20-acre ($81 \times 10^3\text{-m}^2$) five-spot pattern.

Loudon Field

The Loudon field, discovered in 1937, is located in Fayette and Effingham Counties, IL, and produces from four Mississippian sandstones, the Weiler, Paint Creek, Bethel, and Aux Vases, at an average depth of 1,500 ft (457 m). Average porosity is 19%, and average permeability is about 100 md. The oil viscosity is 5 cp ($5 \text{ mPa}\cdot\text{s}$). The northern half of the field was drilled on 20-acre ($81 \times 10^3\text{-m}^2$) spacing in a sunflower pattern. The southern half of the field was drilled on 10-acre ($40.5 \times 10^3\text{-m}^2$) spacing. Waterflooding began in the early 1950's, with the north half of the field on a 70-acre ($283 \times 10^3\text{-m}^2$) nine-spot pattern and the south half on a 20-acre ($81 \times 10^3\text{-m}^2$) five-spot pattern. Subsequently, injection wells were drilled in 10-acre ($40.5 \times 10^3\text{-m}^2$) "dead" spots that are characteristic of the sunflower pattern, thus creating 10-acre ($40.5 \times 10^3\text{-m}^2$) five-spot patterns. Producing water cut is now 98%.

Beginning in 1979, 50 infill wells have been drilled in the 20-acre ($81 \times 10^3\text{-m}^2$) development area. These infills were drilled at the intersection of a line between 20-acre ($81 \times 10^3\text{-m}^2$) producing wells and a line connecting offset injection wells. This is a dead area in the flood pattern, and it was thought that these areas had been inadequately flooded. Initial production ranged from 131 B/D ($20.8 \text{ m}^3/\text{d}$) oil to 3.4 B/D ($0.54 \text{ m}^3/\text{d}$) oil, with the average being 25 B/D ($4.0 \text{ m}^3/\text{d}$) oil. Offsets were producing less than 4 B/D ($0.6 \text{ m}^3/\text{d}$) oil average prior to the drilling of the infill wells. Fig. 17 shows the impact of drilling these 50 infills. At the time of analysis these wells were producing about 600 B/D ($95.4 \text{ m}^3/\text{d}$) oil or 18% of total field production.

Because of their location and the stage of depletion of the field, essentially all production from these wells is considered increased recovery. These infills are expected to increase oil reserves by 970,000 bbl ($1.5 \times 10^5 \text{ m}^3$).

Conclusions

The conclusions formulated from this infill drilling study are as follows.

1. Infill drilling in nine fields has resulted in per-well-recovery improvements that are attractive under current economic conditions.

2. Increased oil recovery from the drilling of 870 infill wells in 9 fields ranges from 56% to 100% of their wellbore production.

3. Total additional reserves from these wells will be 60.8 million bbl ($9.7 \times 10^6 \text{ m}^3$) oil.

4. Continuity calculations made after infill drilling indicated the pay zones to be more discontinuous than when calculations were made before infill drilling.

5. The experience in these nine fields indicates that the ultimate well density in any given field can be determined only after several years of field performance provide sufficient information on reservoir continuity and recovery efficiencies.

Acknowledgments

We thank the many persons who made this paper possible by supplying data, preparing graphics, and typing the manuscript.

References

1. Ghauri, W.K.: "Production Technology Experience in a Large Carbonate Waterflood, Denver Unit, Wasson San Andres Field," *J. Pet. Tech.* (Sept. 1980) 1493-1502.
2. Ghauri, W.K., Osborne, A.F., and Magnuson, W.L.: "Changing Concepts in Carbonate Waterflooding—West Texas Denver Unit Project—An Illustrative Example," *J. Pet. Tech.* (June 1974) 595-606.
3. Stiles, L.H.: "Optimizing Waterflood Recovery in a Mature Waterflood—The Fullerton Clearfork Unit," paper SPE 6198 presented at the 1976 SPE Annual Fall Technical Conference and Exhibition, New Orleans, Oct. 3-6.
4. George, C.J. and Stiles, L.H.: "Improved Techniques for Evaluating Carbonate Waterfloods in West Texas," *J. Pet. Tech.* (Nov. 1978) 1547-54.
5. Driscoll, V.J.: "Recovery Optimization Through Infill Drilling—Concepts, Analysis, and Field Results," paper SPE 4977 presented at the 1974 SPE Annual Technical Conference and Exhibition, Houston, Oct. 6-9.
6. "Application for Waterflood Response Allowable for Wasson Denver Unit," hearing testimony before Texas Railroad Commission by Shell Oil Co., March 21, 1972, Docket 8-A-61677.
7. Ruble, David B.: "Case Study of a Multiple Sand Waterflood, Hewitt Unit, OK," *J. Pet. Tech.* (March 1982) 621-27.

SI Metric Conversion Factors

acre	×	4.046 873	E+03	=	m ²
bbl	×	1.589 873	E-01	=	m ³
ft	×	3.048*	E-01	=	m

*Conversion factor is exact.

JPT

Original manuscript received in Society of Petroleum Engineers office July 20, 1982. Paper accepted for publication Jan. 26, 1983. Revised manuscript received May 5, 1983. Paper (SPE 11023) first presented at the 1982 SPE Annual Technical Conference and Exhibition held in New Orleans, Sept. 26-29.

APPENDIX IIb

IDPM INPUT/OUTPUT FOR IDPM VALIDATION AGAINST FIELD FLOOD RESULTS

```

*****
*
*   S C I E N T I F I C   S O F T W A R E   *
*   -   I N T E R C O M P                 *
*
*
*   INFILL DRILLING PREDICTION MODEL      *
*   (IDPM - RELEASE 1.2.0)                *
*
*****

```

```

IPDM DATA - VERSION 1.2:  Field Validation using Robertson Clearfork Unit
IPDM DATA - VERSION 1.2:  Field Validation using Robertson Clearfork Unit
0, 1, 1, 0, 0, 0.83
2, 8, 15, 1, 0, 1
80., 300.0, 1320., 0.55, 200., 450., .60, 0.90, 0.
.000003, 3000., 3000., -6500., 117.
64.00, 1.0001, .000003, .6, 0.8
32.00, 1.25, .00000735, 1.2, 300.
2., 2., .8, .2, .3, .24, 0.
1
.063, .65, 250.

```

I D P M CURRENT MAXIMUM PARAMETER VALUES

NUMBER OF TUBES PER LAYER.....	16
NUMBER OF GRID CELLS PER TUBE.....	15
NUMBER OF LAYERS.....	20
NUMBER OF TIMESTEPS IN RESERVOIR RUN..	5000
BLANK COMMON SIZE FOR RESERVOIR RUN...	10000
NUMBER OF YEARS FOR ECONOMIC ANALYSIS.	50

SPECIFIED PRINTOUT CONTROLS

RESERVOIR ARRAY OUTPUT CONTROL	0	IARRP
RESERVOIR ANALYSIS OUTPUT CONTROL	1	IANALP
STREAMTUBE OUTPUT CONTROL	1	ISTRMP
ECONOMIC ANALYSIS CONTROL(0-NO, 1-YES)	0	IECONR

RESERVOIR PROPERTIES OUTPUT

FORMATION DEPTH -- SUBSURFACE.....	-6500.0	FEET
FORMATION TEMPERATURE	117.0	DEG F
INDIVIDUAL PATTERN AREA	80.0	ACRES
KV/KH VERTICAL TO HORIZONTAL PERM.....	0.000	
KY/KX ANISOTROPIC VALUE (1.0-100.0)...	1.000	
DYKSTRA-PARSONS COEFFICIENT	0.83	VDP
PRESSURE AT FORMATION TOP	3000.0	PSIA
PORE VOLUME COMPRESSIBILITY	0.00000300	1/PSI

REFERENCE PRESSURE (POROSITY MEASURED)	3000.0	PSIA
NUMBER OF LAYERS	8	
STREAMTUBES PER LAYER	12	
NUMBER OF GRID CELLS PER STREAMTUBE...	15	
INFILL PATTERN (0=5-SPOT, 1=9-SPOT)...	1	

PROPERTIES BY LAYER

POROSITY	X-DIR PERM	NET PAY
0.0630	3.81	31.25
0.0630	0.68	31.25
0.0630	0.33	31.25
0.0630	0.18	31.25
0.0630	0.10	31.25
0.0630	0.06	31.25
0.0630	0.03	31.25
0.0630	0.01	31.25

WATER DENSITY AT STANDARD CONDITIONS..	64.00	LB/CUFT
WATER DENSITY AT RESERVOIR CONDITIONS.	63.99	LB/CUFT
WATER FORMATION VOLUME FACTOR.....	1.00	VOL/VOL
WATER COMPRESSIBILITY AT RES. COND.....	0.00000300	1/PSI
WATER VISCOSITY AT RES. COND.....	0.60	CP

OIL DENSITY AT STANDARD CONDITIONS....	54.00	LB/CUFT
OIL GRAVITY	32.0	DEG API
OIL DENSITY AT RESERVOIR CONDITIONS...	43.20	LB/CUFT
OIL FORMATION VOLUME FACTOR.....	1.25	VOL/VOL
OIL COMPRESSIBILITY AT RES. COND.....	0.00000735	1/PSI
OIL VISCOSITY AT RES. COND.....	1.20	CP
SOLUTION GAS-OIL-RATIO	300.0	SCF/STB
GAS GRAVITY (AIR=1.0).....	0.800	

INJECTION RATE (NON-INFILL)	200.0	STBW/D
INJECTION RATE (INFILL, MAY BE 0.0) ..	450.0	STBW/D
WATER CUT AT INFILL (VCUT)	0.600	FRAC.
WATER CUT AT END (CUTMAX)	0.900	FRAC.
PLUG BACK AT INFILL (1=NO)	2	
(2=YES, IF LAYER W-CUT .GT. VCUT) .		

RELATIVE PERMEABILITY DATA

IRREDUCIBLE WATER SATURATION	0.300	SWC
RESIDUAL OIL SATN -- INPUT --	0.240	SORW
OIL RELATIVE PERM END-POINT	0.800	XKROE
WATER RELATIVE PERM END-POINT	0.200	XKRWE
OIL RELATIVE PERM CURVATURE	2.00	XNO
WATER RELATIVE PERM CURVATURE	2.00	XNW
(MAX) WELL DIST. FOR CONN.=100%	300.000	VWD100
WELL DIST. FOR CONN.=VCONEC	1320.000	VDBWLS
RESERVOIR CONNECTIVITY AT VDBWLS	0.550	VCONEC

RELATIVE PERMEABILITY TABLE
FOR CONNECTIVITY = 1.00000

WATER SATURATN	OIL KRO	WATER KRW	FW (FR FLOW)	D (FW) / D (SW)
0.3000	0.8000	0.0000	0.000	
0.3230	0.7220	0.0005	0.001	0.060
0.3460	0.6480	0.0020	0.006	0.207
0.3690	0.5780	0.0045	0.015	0.400
0.3920	0.5120	0.0080	0.030	0.651
0.4150	0.4500	0.0125	0.053	0.971
0.4380	0.3920	0.0180	0.084	1.369
0.4610	0.3380	0.0245	0.127	1.848
0.4840	0.2880	0.0320	0.182	2.400
0.5070	0.2420	0.0405	0.251	2.998
0.5300	0.2000	0.0500	0.333	3.590
0.5530	0.1620	0.0605	0.428	4.097
0.5760	0.1280	0.0720	0.529	4.428
0.5990	0.0980	0.0845	0.633	4.502
0.6220	0.0720	0.0980	0.731	4.278
0.6450	0.0500	0.1125	0.818	3.776
0.6680	0.0320	0.1280	0.889	3.074
0.6910	0.0180	0.1445	0.941	2.282
0.7140	0.0080	0.1620	0.976	1.502
0.7370	0.0020	0.1805	0.994	0.808
0.7600	0.0000	0.2000	1.000	0.240

FW = $\text{MOBW} / (\text{MOBW} + \text{MOBO})$, WHERE
MOBW = KRW / VISW , MOBO = KRO / VISO

PROPERTIES BY LAYER

POROSITY	X-DIR PERM	NET PAY	SO	SW
0.0630	3.81	31.25	0.7000	0.3000
0.0630	0.68	31.25	0.7000	0.3000
0.0630	0.33	31.25	0.7000	0.3000
0.0630	0.18	31.25	0.7000	0.3000
0.0630	0.10	31.25	0.7000	0.3000
0.0630	0.06	31.25	0.7000	0.3000
0.0630	0.03	31.25	0.7000	0.3000
0.0630	0.01	31.25	0.7000	0.3000

NON - INFILL SIMULATION

SYMMETRY ELEMENT WITHIN 5-SPOT, BEFORE IN-FILL

ISOTROPIC PERMEABILITY CASE - 1/8

```
*****
* FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *
*          PRODUCER =  0.10000E+01          *
*          INJECTOR = -0.10000E+01          *
*****
* INJECTOR AT COORD ( 1, 65 )                *
* PRODUCER AT COORD ( 65, 1 )                *
*****
```

```
*****
* STREAM TUBES *
*****
```

```
|1\
|19\
|35C\
|168C\
|149AC\
|1378BC\
|2457ABC\
|13679ABC\
```

[illegible]

RELATIVE PERMEABILITY TABLE
FOR CONNECTIVITY = 0.55000

WATER SATURATN	OIL KRO	WATER KRW	FW (FR FLOW)	D(FW) / D(SW)
0.3000	0.8000	0.0000	0.000	
0.3230	0.6612	0.0017	0.005	0.216
0.3460	0.5355	0.0066	0.024	0.831
0.3690	0.4231	0.0149	0.066	1.809
0.3920	0.3240	0.0264	0.140	3.246
0.4150	0.2380	0.0413	0.258	5.104
0.4380	0.1653	0.0595	0.419	6.994
0.4610	0.1058	0.0810	0.605	8.101
0.4840	0.0595	0.1058	0.780	7.633
0.5070	0.0264	0.1339	0.910	5.636
0.5300	0.0066	0.1653	0.980	3.056
0.5530	0.0000	0.2000	1.000	0.853
0.5760	0.0000	0.2380	1.000	0.000
0.5990	0.0000	0.2793	1.000	0.000
0.6220	0.0000	0.3240	1.000	0.000
0.6450	0.0000	0.3719	1.000	0.000
0.6680	0.0000	0.4231	1.000	0.000
0.6910	0.0000	0.4777	1.000	0.000
0.7140	0.0000	0.5355	1.000	0.000
0.7370	0.0000	0.5967	1.000	0.000
0.7600	0.0000	0.6612	1.000	0.000

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
(THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
(OF THE AREA OF THE PRE-INFILL 5-SPOT.)

IN - PLACE - VOLUMES

LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.66835E+05	0.35800E+05	0.11934E+06
2	1	0.66841E+05	0.35802E+05	0.11935E+06
3	1	0.66848E+05	0.35804E+05	0.11935E+06
4	1	0.66854E+05	0.35806E+05	0.11935E+06
5	1	0.66861E+05	0.35808E+05	0.11936E+06
6	1	0.66867E+05	0.35810E+05	0.11936E+06
7	1	0.66874E+05	0.35812E+05	0.11936E+06
8	1	0.66880E+05	0.35814E+05	0.11937E+06
1	2	0.50947E+05	0.27290E+05	0.90973E+05
2	2	0.50952E+05	0.27291E+05	0.90976E+05
3	2	0.50957E+05	0.27293E+05	0.90979E+05
4	2	0.50962E+05	0.27294E+05	0.90981E+05

5	2	0.50967E+05	0.27296E+05	0.90984E+05
6	2	0.50972E+05	0.27297E+05	0.90986E+05
7	2	0.50977E+05	0.27299E+05	0.90989E+05
8	2	0.50981E+05	0.27300E+05	0.90991E+05
1	3	0.53351E+05	0.28577E+05	0.95266E+05
2	3	0.53356E+05	0.28579E+05	0.95268E+05
3	3	0.53361E+05	0.28580E+05	0.95271E+05
4	3	0.53366E+05	0.28582E+05	0.95274E+05
5	3	0.53371E+05	0.28584E+05	0.95276E+05
6	3	0.53376E+05	0.28585E+05	0.95279E+05
7	3	0.53382E+05	0.28587E+05	0.95282E+05
8	3	0.53387E+05	0.28588E+05	0.95284E+05
1	4	0.43853E+05	0.23490E+05	0.78306E+05
2	4	0.43857E+05	0.23491E+05	0.78308E+05
3	4	0.43861E+05	0.23492E+05	0.78311E+05
4	4	0.43866E+05	0.23494E+05	0.78313E+05
5	4	0.43870E+05	0.23495E+05	0.78315E+05
6	4	0.43874E+05	0.23496E+05	0.78317E+05
7	4	0.43879E+05	0.23498E+05	0.78319E+05
8	4	0.43883E+05	0.23499E+05	0.78322E+05
1	5	0.37052E+05	0.19847E+05	0.66162E+05
2	5	0.37056E+05	0.19848E+05	0.66164E+05
3	5	0.37059E+05	0.19849E+05	0.66166E+05
4	5	0.37063E+05	0.19850E+05	0.66168E+05
5	5	0.37067E+05	0.19852E+05	0.66170E+05
6	5	0.37070E+05	0.19853E+05	0.66172E+05
7	5	0.37074E+05	0.19854E+05	0.66174E+05
8	5	0.37077E+05	0.19855E+05	0.66176E+05
1	6	0.35645E+05	0.19093E+05	0.63650E+05
2	6	0.35649E+05	0.19094E+05	0.63652E+05
3	6	0.35652E+05	0.19096E+05	0.63654E+05
4	6	0.35656E+05	0.19097E+05	0.63655E+05
5	6	0.35659E+05	0.19098E+05	0.63657E+05
6	6	0.35663E+05	0.19099E+05	0.63659E+05
7	6	0.35666E+05	0.19100E+05	0.63661E+05
8	6	0.35669E+05	0.19101E+05	0.63663E+05
1	7	0.34707E+05	0.18591E+05	0.61975E+05
2	7	0.34711E+05	0.18592E+05	0.61977E+05
3	7	0.34714E+05	0.18593E+05	0.61978E+05
4	7	0.34717E+05	0.18594E+05	0.61980E+05
5	7	0.34721E+05	0.18595E+05	0.61982E+05
6	7	0.34724E+05	0.18596E+05	0.61984E+05
7	7	0.34727E+05	0.18597E+05	0.61985E+05
8	7	0.34731E+05	0.18598E+05	0.61987E+05
1	8	0.32714E+05	0.17523E+05	0.58416E+05
2	8	0.32717E+05	0.17524E+05	0.58417E+05
3	8	0.32720E+05	0.17525E+05	0.58419E+05
4	8	0.32723E+05	0.17526E+05	0.58421E+05
5	8	0.32727E+05	0.17527E+05	0.58422E+05
6	8	0.32730E+05	0.17528E+05	0.58424E+05
7	8	0.32733E+05	0.17529E+05	0.58425E+05
8	8	0.32736E+05	0.17530E+05	0.58427E+05
1	9	0.29665E+05	0.15890E+05	0.52972E+05
2	9	0.29668E+05	0.15891E+05	0.52973E+05
3	9	0.29671E+05	0.15892E+05	0.52975E+05
4	9	0.29674E+05	0.15893E+05	0.52976E+05
5	9	0.29677E+05	0.15894E+05	0.52978E+05
6	9	0.29680E+05	0.15895E+05	0.52979E+05
7	9	0.29683E+05	0.15896E+05	0.52981E+05
8	9	0.29685E+05	0.15896E+05	0.52982E+05

1	10	0.28844E+05	0.15451E+05	0.51506E+05
2	10	0.28847E+05	0.15451E+05	0.51508E+05
3	10	0.28850E+05	0.15452E+05	0.51509E+05
4	10	0.28853E+05	0.15453E+05	0.51511E+05
5	10	0.28856E+05	0.15454E+05	0.51512E+05
6	10	0.28858E+05	0.15455E+05	0.51513E+05
7	10	0.28861E+05	0.15456E+05	0.51515E+05
8	10	0.28864E+05	0.15457E+05	0.51516E+05
1	11	0.30369E+05	0.16267E+05	0.54228E+05
2	11	0.30372E+05	0.16268E+05	0.54230E+05
3	11	0.30375E+05	0.16269E+05	0.54231E+05
4	11	0.30378E+05	0.16270E+05	0.54233E+05
5	11	0.30381E+05	0.16271E+05	0.54234E+05
6	11	0.30384E+05	0.16272E+05	0.54236E+05
7	11	0.30386E+05	0.16273E+05	0.54237E+05
8	11	0.30389E+05	0.16273E+05	0.54239E+05
1	12	0.36349E+05	0.19470E+05	0.64906E+05
2	12	0.36352E+05	0.19471E+05	0.64908E+05
3	12	0.36356E+05	0.19472E+05	0.64910E+05
4	12	0.36359E+05	0.19473E+05	0.64912E+05
5	12	0.36363E+05	0.19475E+05	0.64914E+05
6	12	0.36366E+05	0.19476E+05	0.64915E+05
7	12	0.36370E+05	0.19477E+05	0.64917E+05
8	12	0.36373E+05	0.19478E+05	0.64919E+05
TOTALS		0.38439E+07	0.20587E+07	0.68623E+07
(M-STB)		684.59	366.65	

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
0.2	81.5	81.466	1	1
PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)	
OIL	WATER	INJECTION	OIL	WATER
14.63	0.9142E-11	25.00	1192.	0.7447E-09
CURRENT IN-PLACE-VOLUMES			MAXIMUM	
OIL (MSTB)	WATER (MSTB)		PRESSURE	
683.39	368.68		3444.4	
MATERIAL BALANCE ERROR				
OIL	WATER			
1.0000	1.0000			

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
-------	------	---------	------------	-------------

0.4	162.9	81.466	2	2	
PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
17.27	0.6948E-05	25.00	2599.	0.5660E-03	4074.
CURRENT IN-PLACE-VOLUMES			MAXIMUM		
OIL (MSTB)	WATER (MSTB)		PRESSURE		
681.99	370.72		3789.8		
MATERIAL BALANCE ERROR					
OIL	WATER				
1.0000	1.0000				

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS	
6.9	2525.4	81.466	31	31	
PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
8.108	14.60	25.00	0.3978E+05	0.1104E+05	0.6315E+05
CURRENT IN-PLACE-VOLUMES			MAXIMUM		
OIL (MSTB)	WATER (MSTB)		PRESSURE		
644.78	418.71		4114.0		
MATERIAL BALANCE ERROR					
OIL	WATER				
0.99995	0.99990				

CONTINUATION OF WATERFLOOD AFTER WATER CUT FOR INFILL

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS	
7.1	2606.9	81.466	1	32	
PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
7.360	15.47	25.00	0.4038E+05	0.1230E+05	0.6518E+05
CURRENT IN-PLACE-VOLUMES			MAXIMUM		
OIL (MSTB)	WATER (MSTB)		PRESSURE		
644.18	419.48		4200.8		

MATERIAL BALANCE ERROR	
OIL	WATER
0.99995	0.99991

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
13.4	4887.9	81.466	29	60

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
5.452	18.13	25.00	0.5339E+05	0.5295E+05	0.1222E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
631.11	435.96	4242.2

MATERIAL BALANCE ERROR	
OIL	WATER
0.99986	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
26.8	9775.9	81.466	89	120

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
3.992	20.00	25.00	0.7795E+05	0.1442E+06	0.2444E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
606.43	467.15	4189.3

MATERIAL BALANCE ERROR	
OIL	WATER
0.99967	1.0007

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
40.1	14663.8	81.466	149	180

PRODUCTION/INJECTION RATE (STB/D)	CUMULATIVE PRODUCTION/INJECTION (STB)
-----------------------------------	---------------------------------------

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
589.21	488.92	4224.2

I N F I L L S I M U L A T I O N

SYMMETRY ELEMENT AFTER 9-SPOT IN-FILL

=====

ISOTROPIC PERMEABILITY CASE - 1/8

=====

```

*****
*   FRACTIONAL WELL RATES FOR TUBE CALCULATIONS   *
*   NEW PRODUCER = 0.66600E+00                     *
*   OLD PRODUCER = 0.33400E+00                     *
*   INJECTOR = -0.10000E+01                        *
*****
*   INJECTOR AT COORD ( 1, 65 )                    *
*   PRODUCER AT COORD ( 65, 1 )                    *
*   PRODUCER AT COORD ( 1, 1 )                     *
*****

```

```

*****
* STREAM TUBES *
*****

```

```

|1\
|1B\
|27C\
|158C\
|139AC\
|1468BC\
|23679BC\
|13479BBC\
|135789ACC\
|124578ABCC\
|1345689ABCC\
|12356789ABCC\
|12346789ABBCC\
|123456789ABCCC\
|1234567899ABCCC\
|1234567789ABBCCC\
|12345567899ABBCCC\
|12344567889AABBCCC\
|113345677899AABCCCC\
|113345667889AABBCCCC\
|1123455677899AABBCCCC\
|11234456778899AABBCCCC\
|11234456677899AABBCCCC\
|112344556778899AABBCCCC\
|1123344566778899AABBCCCC\
|11233445667788999AABBCCCC\
|112334455667788999AABBCCCC\
|112334455667788999AABBCCCC\
|112334455667788999AABBCCCC\
|11233344556677888999AABBCCCC\
|112333445566777888999AAAABBBCCCCC\
|112233445566677888999AAABBBBCCCCC\
|112233445566677888999AAABBBBCCCCC\
|112233445556677888999AAABBBBCCCCC\

```


FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
(THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
(OF THE AREA OF THE PRE-INFILL 5-SPOT.)

IN - PLACE - VOLUMES

LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.10872E+05	0.15889E+05	0.29375E+05
2	1	0.13320E+05	0.12787E+05	0.29357E+05
3	1	0.14794E+05	0.10938E+05	0.29354E+05
4	1	0.15546E+05	0.99921E+04	0.29351E+05
5	1	0.15948E+05	0.94801E+04	0.29347E+05
6	1	0.16180E+05	0.91762E+04	0.29342E+05
7	1	0.16318E+05	0.89843E+04	0.29336E+05
8	1	0.16403E+05	0.88563E+04	0.29328E+05
1	2	0.10908E+05	0.15847E+05	0.29376E+05
2	2	0.13800E+05	0.12161E+05	0.29348E+05
3	2	0.15238E+05	0.10363E+05	0.29346E+05
4	2	0.15784E+05	0.96777E+04	0.29345E+05
5	2	0.16077E+05	0.93060E+04	0.29343E+05
6	2	0.16249E+05	0.90803E+04	0.29339E+05
7	2	0.16351E+05	0.89368E+04	0.29334E+05
8	2	0.16410E+05	0.88413E+04	0.29326E+05
1	3	0.15764E+05	0.22815E+05	0.42379E+05
2	3	0.20470E+05	0.16828E+05	0.42337E+05
3	3	0.22065E+05	0.14833E+05	0.42336E+05
4	3	0.22811E+05	0.13898E+05	0.42334E+05
5	3	0.23215E+05	0.13389E+05	0.42332E+05
6	3	0.23453E+05	0.13081E+05	0.42328E+05
7	3	0.23596E+05	0.12884E+05	0.42322E+05
8	3	0.23678E+05	0.12753E+05	0.42313E+05
1	4	0.15978E+05	0.22954E+05	0.42793E+05
2	4	0.21113E+05	0.16435E+05	0.42752E+05
3	4	0.22625E+05	0.14543E+05	0.42751E+05
4	4	0.23256E+05	0.13752E+05	0.42750E+05
5	4	0.23578E+05	0.13348E+05	0.42749E+05
6	4	0.23761E+05	0.13112E+05	0.42746E+05
7	4	0.23866E+05	0.12964E+05	0.42740E+05
8	4	0.23923E+05	0.12864E+05	0.42731E+05
1	5	0.17253E+05	0.24730E+05	0.46150E+05
2	5	0.23036E+05	0.17388E+05	0.46105E+05
3	5	0.24439E+05	0.15633E+05	0.46103E+05
4	5	0.25090E+05	0.14818E+05	0.46103E+05
5	5	0.25431E+05	0.14391E+05	0.46102E+05
6	5	0.25628E+05	0.14138E+05	0.46099E+05
7	5	0.25741E+05	0.13979E+05	0.46094E+05
8	5	0.25801E+05	0.13872E+05	0.46083E+05

1	6	0.20293E+05	0.28915E+05	0.54118E+05
2	6	0.27397E+05	0.19906E+05	0.54065E+05
3	6	0.29000E+05	0.17902E+05	0.54064E+05
4	6	0.29607E+05	0.17144E+05	0.54064E+05
5	6	0.29932E+05	0.16736E+05	0.54063E+05
6	6	0.30115E+05	0.16501E+05	0.54061E+05
7	6	0.30217E+05	0.16354E+05	0.54054E+05
8	6	0.30265E+05	0.16256E+05	0.54041E+05
1	7	0.25743E+05	0.36398E+05	0.68377E+05
2	7	0.35090E+05	0.24556E+05	0.68313E+05
3	7	0.36756E+05	0.22472E+05	0.68311E+05
4	7	0.37472E+05	0.21578E+05	0.68311E+05
5	7	0.37850E+05	0.21106E+05	0.68311E+05
6	7	0.38066E+05	0.20828E+05	0.68308E+05
7	7	0.38187E+05	0.20654E+05	0.68300E+05
8	7	0.38242E+05	0.20538E+05	0.68284E+05
1	8	0.37077E+05	0.51012E+05	0.97097E+05
2	8	0.51446E+05	0.32847E+05	0.97014E+05
3	8	0.53065E+05	0.30824E+05	0.97013E+05
4	8	0.53680E+05	0.30058E+05	0.97013E+05
5	8	0.54001E+05	0.29655E+05	0.97013E+05
6	8	0.54190E+05	0.29407E+05	0.97009E+05
7	8	0.54290E+05	0.29248E+05	0.96997E+05
8	8	0.54324E+05	0.29141E+05	0.96976E+05
1	9	0.51886E+05	0.65706E+05	0.13029E+06
2	9	0.69859E+05	0.43017E+05	0.13020E+06
3	9	0.71503E+05	0.40966E+05	0.13020E+06
4	9	0.72184E+05	0.40120E+05	0.13020E+06
5	9	0.72555E+05	0.39660E+05	0.13020E+06
6	9	0.72765E+05	0.39391E+05	0.13020E+06
7	9	0.72892E+05	0.39202E+05	0.13019E+06
8	9	0.72912E+05	0.39110E+05	0.13017E+06
1	10	0.41614E+05	0.57840E+05	0.10964E+06
2	10	0.58273E+05	0.36835E+05	0.10956E+06
3	10	0.60061E+05	0.34604E+05	0.10956E+06
4	10	0.60751E+05	0.33749E+05	0.10957E+06
5	10	0.61057E+05	0.33373E+05	0.10957E+06
6	10	0.61238E+05	0.33146E+05	0.10957E+06
7	10	0.61339E+05	0.32999E+05	0.10956E+06
8	10	0.61350E+05	0.32926E+05	0.10954E+06
1	11	0.35841E+05	0.51628E+05	0.96226E+05
2	11	0.50612E+05	0.33006E+05	0.96162E+05
3	11	0.52338E+05	0.30853E+05	0.96162E+05
4	11	0.53078E+05	0.29933E+05	0.96163E+05
5	11	0.53453E+05	0.29469E+05	0.96164E+05
6	11	0.53687E+05	0.29176E+05	0.96164E+05
7	11	0.53807E+05	0.29006E+05	0.96157E+05
8	11	0.53854E+05	0.28890E+05	0.96138E+05
1	12	0.42243E+05	0.60605E+05	0.11319E+06
2	12	0.60114E+05	0.38084E+05	0.11312E+06
3	12	0.61923E+05	0.35829E+05	0.11312E+06
4	12	0.62588E+05	0.35007E+05	0.11312E+06
5	12	0.62949E+05	0.34563E+05	0.11312E+06
6	12	0.63178E+05	0.34278E+05	0.11313E+06
7	12	0.63306E+05	0.34102E+05	0.11312E+06
8	12	0.63372E+05	0.33964E+05	0.11310E+06
TOTALS		0.36207E+07	0.23508E+07	0.68668E+07
(M-STB)		644.82	418.66	

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
7.0	2566.2	40.733	1	32

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
23.80	26.36	56.26	969.5	1074.	2292.
(15.76	19.65	- FROM WELL AT (1, 1))			
(8.046	6.707	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
643.79	419.97	6478.3

MATERIAL BALANCE ERROR	
OIL	WATER
0.99990	1.0002

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
7.1	2606.9	40.733	2	33

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
21.29	27.93	56.26	1837.	2211.	4583.
(13.31	20.31	- FROM WELL AT (1, 1))			
(7.976	7.618	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
642.92	421.13	6234.2

MATERIAL BALANCE ERROR	
OIL	WATER
0.99990	1.0002

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
12.9	4725.0	40.733	54	85

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
11.50	41.83	56.26	0.3323E+05	0.8190E+05	0.1237E+06
(7.019	28.81	- FROM WELL AT (1, 1))			
(4.484	13.02	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
611.48	460.80	6035.7

MATERIAL BALANCE ERROR	
OIL	WATER
0.99981	1.0007

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
18.8	6883.9	40.733	107	138

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
8.724	45.35	56.26	0.5438E+05	0.1769E+06	0.2452E+06
(4.614	31.86	- FROM WELL AT (1, 1))			
(4.110	13.49	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
590.24	487.53	6063.8

MATERIAL BALANCE ERROR	
OIL	WATER
0.99967	1.0013

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
24.9	9083.4	40.733	161	192

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
7.425	46.96	56.26	0.7238E+05	0.2781E+06	0.3689E+06
(3.654	33.08	- FROM WELL AT (1, 1))			
(3.772	13.88	- FROM WELL AT (65, 1))			

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
572.16	510.31	6134.7

MATERIAL BALANCE ERROR

OIL
0.99955

WATER
1.0019

TIME STEPS EXECUTED.... 208

GRID-CELL-TIME-STEPS... 2396160

PERFORMANCE VERSUS TIME FOR NON-INFILL

TIME DAYS	OIL RATE STB/D	WATER RATE STB/D	CUMOIL MSTB	WCUT FRAC.	PV INJ FRAC.	OIL REC %OOIP
81.47	14.63	0.9142E-11	1.192	0.000	0.00	0.2
162.93	17.27	0.6948E-05	2.599	0.000	0.00	0.4
244.40	18.24	0.7490E-04	4.085	0.000	0.01	0.6
325.86	18.69	0.7655E-04	5.607	0.000	0.01	0.8
407.33	18.99	0.7776E-04	7.154	0.000	0.01	1.0
488.79	19.14	0.4390E-04	8.713	0.000	0.01	1.3
570.26	19.27	0.4339E-04	10.28	0.000	0.01	1.5
651.73	19.35	0.4349E-04	11.86	0.000	0.01	1.7
733.19	19.43	0.1010E-03	13.44	0.000	0.02	2.0
814.66	19.51	0.1380E-03	15.03	0.000	0.02	2.2
896.12	19.58	0.1791E-03	16.63	0.000	0.02	2.4
977.59	19.56	0.1483E-03	18.22	0.000	0.02	2.7
1059.05	19.58	0.1197E-03	19.82	0.000	0.02	2.9
1140.52	19.58	0.1389E-03	21.41	0.000	0.02	3.1
1221.99	19.62	0.1307E-03	23.01	0.000	0.03	3.4
1303.45	19.62	0.1910E-03	24.61	0.000	0.03	3.6
1384.92	19.52	0.2115E-03	26.20	0.000	0.03	3.8
1466.38	19.43	0.4265E-03	27.78	0.000	0.03	4.1
1547.85	17.99	1.957	29.25	0.098	0.03	4.3
1629.31	15.93	4.448	30.54	0.218	0.03	4.5
1710.78	14.80	5.803	31.75	0.282	0.04	4.6
1792.25	12.27	9.270	32.75	0.430	0.04	4.8
1873.71	10.57	11.45	33.61	0.520	0.04	4.9
1955.18	10.40	11.64	34.46	0.528	0.04	5.0
2036.64	10.40	11.67	35.31	0.529	0.04	5.2
2118.11	10.14	12.02	36.13	0.542	0.04	5.3
2199.57	9.318	13.04	36.89	0.583	0.05	5.4
2281.04	9.202	13.10	37.64	0.587	0.05	5.5
2362.50	9.113	13.16	38.38	0.591	0.05	5.6
2443.97	9.018	13.38	39.12	0.597	0.05	5.7
2525.44	8.108	14.60	39.78	0.643	0.05	5.8
2606.90	7.360	15.47	40.38	0.678	0.05	5.9
2688.37	7.127	15.89	40.96	0.690	0.06	6.0
2769.83	6.614	16.62	41.50	0.715	0.06	6.1
2851.30	6.003	17.44	41.99	0.744	0.06	6.1
2932.76	5.920	17.58	42.47	0.748	0.06	6.2
3014.23	5.837	17.67	42.94	0.752	0.06	6.3
3095.69	5.814	17.72	43.42	0.753	0.06	6.3
3177.16	5.757	17.79	43.89	0.755	0.07	6.4
3258.63	5.713	17.84	44.35	0.757	0.07	6.5
3340.09	5.693	17.87	44.82	0.758	0.07	6.5
3421.56	5.662	17.90	45.28	0.760	0.07	6.6
3503.02	5.609	17.93	45.73	0.762	0.07	6.7
3584.49	5.607	17.96	46.19	0.762	0.07	6.8

3665.95	5.627	17.96	46.65	0.761	0.08	6.8
3747.42	5.589	17.98	47.10	0.763	0.08	6.9
3828.89	5.587	17.98	47.56	0.763	0.08	7.0
3910.35	5.569	18.00	48.01	0.764	0.08	7.0
3991.82	5.536	18.01	48.46	0.765	0.08	7.1
4073.28	5.543	18.01	48.92	0.765	0.08	7.1
4154.75	5.531	18.05	49.37	0.765	0.09	7.2
4236.21	5.532	18.04	49.82	0.765	0.09	7.3
4317.68	5.509	18.06	50.27	0.766	0.09	7.3
4399.15	5.512	18.07	50.72	0.766	0.09	7.4
4480.61	5.507	18.07	51.16	0.766	0.09	7.5
4562.08	5.488	18.08	51.61	0.767	0.09	7.5
4643.54	5.498	18.10	52.06	0.767	0.10	7.6
4725.01	5.470	18.09	52.50	0.768	0.10	7.7
4806.47	5.461	18.11	52.95	0.768	0.10	7.7
4887.94	5.452	18.13	53.39	0.769	0.10	7.8
4969.41	5.486	18.09	53.84	0.767	0.10	7.9
5050.87	5.434	18.14	54.28	0.769	0.10	7.9
5132.34	5.470	18.13	54.73	0.768	0.11	8.0
5213.80	5.467	18.13	55.17	0.768	0.11	8.1
5295.27	5.462	18.16	55.62	0.769	0.11	8.1
5376.73	5.448	18.16	56.06	0.769	0.11	8.2
5458.20	5.441	18.16	56.51	0.769	0.11	8.3
5539.67	5.442	18.17	56.95	0.769	0.11	8.3
5621.13	5.406	18.19	57.39	0.771	0.12	8.4
5702.60	5.397	18.20	57.83	0.771	0.12	8.5
5784.06	5.418	18.20	58.27	0.771	0.12	8.5
5865.53	5.415	18.20	58.71	0.771	0.12	8.6
5947.00	5.418	18.20	59.15	0.771	0.12	8.6
6028.46	5.411	18.19	59.59	0.771	0.12	8.7
6109.93	5.370	18.22	60.03	0.772	0.13	8.8
6191.39	5.369	18.23	60.47	0.772	0.13	8.8
6272.86	5.390	18.22	60.91	0.772	0.13	8.9
6354.32	5.347	18.24	61.34	0.773	0.13	9.0
6435.79	5.345	18.24	61.78	0.773	0.13	9.0
6517.26	5.363	18.22	62.22	0.773	0.13	9.1
6598.72	5.334	18.24	62.65	0.774	0.14	9.2
6680.19	5.357	18.23	63.09	0.773	0.14	9.2
6761.65	5.353	18.25	63.52	0.773	0.14	9.3
6843.12	5.346	18.23	63.96	0.773	0.14	9.3
6924.59	5.295	18.27	64.39	0.775	0.14	9.4
7006.05	5.309	18.27	64.82	0.775	0.14	9.5
7087.52	5.293	18.29	65.25	0.776	0.15	9.5
7168.98	5.296	18.26	65.69	0.775	0.15	9.6
7250.45	5.284	18.27	66.12	0.776	0.15	9.7
7331.91	5.272	18.31	66.54	0.776	0.15	9.7
7413.38	5.273	18.30	66.97	0.776	0.15	9.8
7494.85	5.244	18.36	67.40	0.778	0.15	9.9
7576.31	5.215	18.39	67.83	0.779	0.16	9.9
7657.78	5.167	18.45	68.25	0.781	0.16	10.0
7739.24	5.108	18.52	68.66	0.784	0.16	10.0
7820.71	5.097	18.57	69.08	0.785	0.16	10.1
7902.18	5.031	18.65	69.49	0.788	0.16	10.2
7983.64	4.942	18.76	69.89	0.791	0.16	10.2
8065.11	4.902	18.81	70.29	0.793	0.17	10.3
8146.57	4.856	18.86	70.69	0.795	0.17	10.3
8228.04	4.832	18.89	71.08	0.796	0.17	10.4
8309.50	4.783	18.94	71.47	0.798	0.17	10.4
8390.97	4.761	18.96	71.86	0.799	0.17	10.5
8472.44	4.723	19.01	72.24	0.801	0.17	10.6

8553.90	4.695	19.06	72.62	0.802	0.18	10.6
8635.37	4.644	19.11	73.00	0.805	0.18	10.7
8716.83	4.630	19.14	73.38	0.805	0.18	10.7
8798.30	4.602	19.19	73.76	0.807	0.18	10.8
8879.76	4.590	19.22	74.13	0.807	0.18	10.8
8961.23	4.549	19.29	74.50	0.809	0.18	10.9
9042.70	4.498	19.35	74.87	0.811	0.19	10.9
9124.16	4.456	19.41	75.23	0.813	0.19	11.0
9205.63	4.386	19.51	75.59	0.816	0.19	11.0
9287.09	4.317	19.60	75.94	0.820	0.19	11.1
9368.56	4.227	19.69	76.28	0.823	0.19	11.1
9450.03	4.216	19.73	76.63	0.824	0.19	11.2
9531.49	4.115	19.82	76.96	0.828	0.20	11.2
9612.96	4.084	19.88	77.29	0.830	0.20	11.3
9694.42	4.055	19.92	77.62	0.831	0.20	11.3
9775.89	3.992	20.00	77.95	0.834	0.20	11.4
9857.35	3.948	20.05	78.27	0.835	0.20	11.4
9938.82	3.910	20.10	78.59	0.837	0.20	11.5
10020.29	3.912	20.12	78.91	0.837	0.21	11.5
10101.75	3.866	20.16	79.22	0.839	0.21	11.6
10183.22	3.864	20.17	79.54	0.839	0.21	11.6
10264.68	3.844	20.19	79.85	0.840	0.21	11.7
10346.15	3.816	20.22	80.16	0.841	0.21	11.7
10427.62	3.793	20.23	80.47	0.842	0.21	11.8
10509.08	3.780	20.26	80.78	0.843	0.22	11.8
10590.55	3.783	20.26	81.09	0.843	0.22	11.9
10672.01	3.752	20.29	81.39	0.844	0.22	11.9
10753.48	3.758	20.29	81.70	0.844	0.22	11.9
10834.94	3.726	20.33	82.00	0.845	0.22	12.0
10916.41	3.697	20.36	82.30	0.846	0.22	12.0
10997.88	3.715	20.35	82.61	0.846	0.23	12.1
11079.34	3.688	20.39	82.91	0.847	0.23	12.1
11160.81	3.705	20.37	83.21	0.846	0.23	12.2
11242.27	3.652	20.41	83.51	0.848	0.23	12.2
11323.74	3.681	20.41	83.81	0.847	0.23	12.2
11405.21	3.633	20.45	84.10	0.849	0.23	12.3
11486.67	3.629	20.45	84.40	0.849	0.24	12.3
11568.14	3.615	20.50	84.69	0.850	0.24	12.4
11649.60	3.591	20.52	84.98	0.851	0.24	12.4
11731.07	3.547	20.55	85.27	0.853	0.24	12.5
11812.53	3.543	20.55	85.56	0.853	0.24	12.5
11894.00	3.517	20.57	85.85	0.854	0.24	12.5
11975.47	3.502	20.59	86.13	0.855	0.25	12.6
12056.93	3.526	20.59	86.42	0.854	0.25	12.6
12138.40	3.500	20.61	86.71	0.855	0.25	12.7
12219.86	3.458	20.63	86.99	0.856	0.25	12.7
12301.33	3.451	20.64	87.27	0.857	0.25	12.8
12382.79	3.477	20.63	87.55	0.856	0.25	12.8
12464.26	3.423	20.66	87.83	0.858	0.26	12.8
12545.73	3.474	20.64	88.11	0.856	0.26	12.9
12627.19	3.425	20.69	88.39	0.858	0.26	12.9
12708.66	3.423	20.68	88.67	0.858	0.26	13.0
12790.12	3.403	20.70	88.95	0.859	0.26	13.0
12871.59	3.408	20.70	89.23	0.859	0.26	13.0
12953.06	3.417	20.70	89.51	0.858	0.27	13.1
13034.52	3.381	20.72	89.78	0.860	0.27	13.1
13115.99	3.392	20.72	90.06	0.859	0.27	13.2
13197.45	3.377	20.72	90.33	0.860	0.27	13.2
13278.92	3.369	20.74	90.61	0.860	0.27	13.2
13360.38	3.364	20.75	90.88	0.861	0.27	13.3

13441.85	3.343	20.78	91.15	0.861	0.28	13.3
13523.32	3.342	20.80	91.43	0.862	0.28	13.4
13604.78	3.319	20.80	91.70	0.862	0.28	13.4
13686.25	3.305	20.83	91.97	0.863	0.28	13.4
13767.71	3.296	20.86	92.23	0.864	0.28	13.5
13849.18	3.300	20.85	92.50	0.863	0.28	13.5
13930.65	3.256	20.88	92.77	0.865	0.29	13.6
14012.11	3.258	20.89	93.03	0.865	0.29	13.6
14093.58	3.216	20.93	93.30	0.867	0.29	13.6
14175.04	3.200	20.93	93.56	0.867	0.29	13.7
14256.51	3.178	20.97	93.81	0.868	0.29	13.7
14337.97	3.146	20.98	94.07	0.870	0.29	13.7
14419.44	3.166	21.01	94.33	0.869	0.30	13.8
14500.91	3.129	21.04	94.58	0.871	0.30	13.8
14582.37	3.118	21.05	94.84	0.871	0.30	13.9
14663.84	3.141	21.07	95.09	0.870	0.30	13.9
14745.30	3.127	21.07	95.35	0.871	0.30	13.9
14826.77	3.085	21.10	95.60	0.872	0.30	14.0
14908.24	3.077	21.13	95.85	0.873	0.31	14.0
14989.70	3.068	21.14	96.10	0.873	0.31	14.0
15071.17	3.053	21.16	96.35	0.874	0.31	14.1
15152.63	3.036	21.21	96.60	0.875	0.31	14.1
15234.10	3.005	21.23	96.84	0.876	0.31	14.2
15315.56	2.994	21.24	97.09	0.876	0.31	14.2
15397.03	2.987	21.27	97.33	0.877	0.32	14.2
15478.50	2.931	21.31	97.57	0.879	0.32	14.3
15559.96	2.941	21.32	97.81	0.879	0.32	14.3
15641.43	2.919	21.36	98.04	0.880	0.32	14.3
15722.89	2.906	21.38	98.28	0.880	0.32	14.4
15804.36	2.894	21.39	98.52	0.881	0.32	14.4
15885.83	2.837	21.44	98.75	0.883	0.33	14.4
15967.29	2.850	21.45	98.98	0.883	0.33	14.5
16048.76	2.824	21.47	99.21	0.884	0.33	14.5
16130.22	2.813	21.49	99.44	0.884	0.33	14.5
16211.69	2.779	21.52	99.67	0.886	0.33	14.6
16293.15	2.776	21.54	99.89	0.886	0.33	14.6
16374.62	2.737	21.58	100.1	0.887	0.34	14.6
16456.09	2.725	21.58	100.3	0.888	0.34	14.7
16537.55	2.709	21.63	100.6	0.889	0.34	14.7
16619.02	2.714	21.63	100.8	0.889	0.34	14.7
16700.48	2.662	21.65	101.0	0.891	0.34	14.8
16781.95	2.661	21.67	101.2	0.891	0.34	14.8
16863.41	2.656	21.69	101.4	0.891	0.35	14.8
16944.88	2.651	21.71	101.6	0.891	0.35	14.9
17026.34	2.617	21.72	101.9	0.892	0.35	14.9
17107.80	2.642	21.73	102.1	0.892	0.35	14.9
17189.27	2.611	21.75	102.3	0.893	0.35	14.9
17270.73	2.605	21.76	102.5	0.893	0.35	15.0
17352.20	2.582	21.78	102.7	0.894	0.36	15.0
17433.66	2.564	21.79	102.9	0.895	0.36	15.0
17515.13	2.571	21.78	103.1	0.894	0.36	15.1
17596.59	2.561	21.79	103.3	0.895	0.36	15.1
17678.06	2.559	21.81	103.5	0.895	0.36	15.1
17759.52	2.530	21.85	103.7	0.896	0.36	15.2
17840.99	2.529	21.85	104.0	0.896	0.37	15.2
17922.45	2.507	21.87	104.2	0.897	0.37	15.2
18003.92	2.505	21.88	104.4	0.897	0.37	15.3
18085.38	2.500	21.89	104.6	0.898	0.37	15.3
18166.85	2.491	21.90	104.8	0.898	0.37	15.3
18248.31	2.469	21.91	105.0	0.899	0.37	15.3

18329.78	2.464	21.93	105.2	0.899	0.38	15.4
18411.24	2.467	21.93	105.4	0.899	0.38	15.4
18492.71	2.468	21.96	105.6	0.899	0.38	15.4
18574.17	2.448	21.95	105.8	0.900	0.38	15.5
18655.64	2.428	21.98	106.0	0.901	0.38	15.5

PERFORMANCE VERSUS TIME FOR INFILL

=====

TIME DAYS	OIL RATE STB/D	WATER RATE STB/D	CUMOIL MSTB	WCUT FRAC.	PV INJ FRAC.	OIL REC %OOIP
2525.44	3.951	24.47	39.78	0.861	0.05	
2566.17	23.80	26.36	40.75	0.526	0.05	6.0
2606.90	21.29	27.93	41.61	0.567	0.06	6.1
2647.63	21.15	28.72	42.48	0.576	0.06	6.2
2688.37	20.95	29.32	43.33	0.583	0.06	6.3
2729.10	20.45	30.19	44.16	0.596	0.06	6.5
2769.83	21.64	28.89	45.04	0.572	0.06	6.6
2810.57	21.67	29.02	45.93	0.573	0.06	6.7
2851.30	18.22	33.51	46.67	0.648	0.07	6.8
2892.03	18.23	33.39	47.41	0.647	0.07	6.9
2932.76	22.12	28.29	48.31	0.561	0.07	7.1
2973.50	17.28	34.62	49.02	0.667	0.07	7.2
3014.23	19.99	31.25	49.83	0.610	0.07	7.3
3054.96	19.97	31.05	50.64	0.609	0.08	7.4
3095.70	16.75	35.19	51.33	0.678	0.08	7.5
3136.43	16.62	35.45	52.00	0.681	0.08	7.6
3177.16	16.05	36.12	52.66	0.692	0.08	7.7
3217.90	15.90	36.32	53.30	0.696	0.08	7.8
3258.63	15.70	36.53	53.94	0.699	0.09	7.9
3299.36	15.45	36.83	54.57	0.704	0.09	8.0
3340.09	15.24	37.12	55.19	0.709	0.09	8.1
3380.83	15.08	37.34	55.81	0.712	0.09	8.2
3421.56	14.91	37.59	56.42	0.716	0.09	8.2
3462.29	14.56	38.03	57.01	0.723	0.09	8.3
3503.03	14.38	38.27	57.60	0.727	0.10	8.4
3543.76	14.16	38.50	58.17	0.731	0.10	8.5
3584.49	14.03	38.71	58.74	0.734	0.10	8.6
3625.22	13.84	38.90	59.31	0.738	0.10	8.7
3665.96	13.77	39.01	59.87	0.739	0.10	8.7
3706.69	13.62	39.21	60.42	0.742	0.11	8.8
3747.42	13.51	39.34	60.97	0.744	0.11	8.9
3788.16	13.36	39.53	61.52	0.747	0.11	9.0
3828.89	13.18	39.75	62.05	0.751	0.11	9.1
3869.62	12.98	39.97	62.58	0.755	0.11	9.1
3910.35	12.86	40.17	63.11	0.758	0.12	9.2
3951.09	12.79	40.25	63.63	0.759	0.12	9.3
3991.82	12.72	40.31	64.15	0.760	0.12	9.4
4032.55	12.58	40.45	64.66	0.763	0.12	9.4
4073.29	12.48	40.62	65.17	0.765	0.12	9.5
4114.02	12.48	40.62	65.67	0.765	0.12	9.6
4154.75	12.39	40.75	66.18	0.767	0.13	9.7
4195.48	12.29	40.82	66.68	0.769	0.13	9.7
4236.22	12.31	40.86	67.18	0.769	0.13	9.8
4276.95	12.19	40.96	67.68	0.771	0.13	9.9
4317.68	12.19	40.94	68.17	0.771	0.13	10.0
4358.42	12.11	41.06	68.67	0.772	0.14	10.0
4399.15	12.09	41.03	69.16	0.772	0.14	10.1
4439.88	12.06	41.10	69.65	0.773	0.14	10.2

4480.62	11.98	41.17	70.14	0.775	0.14	10.3
4521.35	11.94	41.26	70.63	0.776	0.14	10.3
4562.08	11.86	41.36	71.11	0.777	0.15	10.4
4602.81	11.75	41.54	71.59	0.779	0.15	10.5
4643.55	11.68	41.63	72.06	0.781	0.15	10.5
4684.28	11.57	41.76	72.53	0.783	0.15	10.6
4725.01	11.50	41.83	73.00	0.784	0.15	10.7
4765.75	11.38	41.98	73.47	0.787	0.15	10.7
4806.48	11.26	42.12	73.93	0.789	0.16	10.8
4847.21	11.18	42.25	74.38	0.791	0.16	10.9
4887.94	11.09	42.36	74.83	0.793	0.16	10.9
4928.68	10.98	42.47	75.28	0.795	0.16	11.0
4969.41	10.95	42.56	75.73	0.795	0.16	11.1
5010.14	10.86	42.63	76.17	0.797	0.17	11.1
5050.88	10.79	42.74	76.61	0.798	0.17	11.2
5091.61	10.73	42.83	77.04	0.800	0.17	11.3
5132.34	10.60	42.99	77.48	0.802	0.17	11.3
5173.07	10.54	43.09	77.91	0.803	0.17	11.4
5213.81	10.45	43.20	78.33	0.805	0.18	11.4
5254.54	10.40	43.23	78.76	0.806	0.18	11.5
5295.27	10.31	43.33	79.18	0.808	0.18	11.6
5336.01	10.28	43.40	79.59	0.808	0.18	11.6
5376.74	10.24	43.47	80.01	0.809	0.18	11.7
5417.47	10.16	43.54	80.43	0.811	0.18	11.8
5458.21	10.13	43.58	80.84	0.811	0.19	11.8
5498.94	10.11	43.63	81.25	0.812	0.19	11.9
5539.67	10.04	43.68	81.66	0.813	0.19	11.9
5580.40	9.993	43.77	82.07	0.814	0.19	12.0
5621.14	9.925	43.84	82.47	0.815	0.19	12.1
5661.87	9.863	43.91	82.87	0.817	0.20	12.1
5702.60	9.804	44.00	83.27	0.818	0.20	12.2
5743.34	9.749	44.07	83.67	0.819	0.20	12.2
5784.07	9.655	44.20	84.06	0.821	0.20	12.3
5824.80	9.590	44.25	84.45	0.822	0.20	12.3
5865.53	9.539	44.34	84.84	0.823	0.21	12.4
5906.27	9.500	44.39	85.23	0.824	0.21	12.5
5947.00	9.499	44.41	85.61	0.824	0.21	12.5
5987.73	9.402	44.49	86.00	0.826	0.21	12.6
6028.47	9.377	44.51	86.38	0.826	0.21	12.6
6069.20	9.385	44.54	86.76	0.826	0.21	12.7
6109.93	9.338	44.57	87.14	0.827	0.22	12.7
6150.66	9.314	44.61	87.52	0.827	0.22	12.8
6191.40	9.314	44.59	87.90	0.827	0.22	12.8
6232.13	9.293	44.61	88.28	0.828	0.22	12.9
6272.86	9.267	44.65	88.66	0.828	0.22	13.0
6313.60	9.236	44.70	89.03	0.829	0.23	13.0
6354.33	9.236	44.72	89.41	0.829	0.23	13.1
6395.06	9.179	44.77	89.78	0.830	0.23	13.1
6435.79	9.143	44.82	90.16	0.831	0.23	13.2
6476.53	9.123	44.84	90.53	0.831	0.23	13.2
6517.26	9.064	44.91	90.90	0.832	0.24	13.3
6557.99	9.015	44.99	91.26	0.833	0.24	13.3
6598.73	8.988	45.00	91.63	0.834	0.24	13.4
6639.46	8.952	45.05	91.99	0.834	0.24	13.4
6680.19	8.938	45.08	92.36	0.835	0.24	13.5
6720.93	8.922	45.11	92.72	0.835	0.24	13.6
6761.66	8.919	45.14	93.09	0.835	0.25	13.6
6802.39	8.806	45.25	93.44	0.837	0.25	13.7
6843.12	8.767	45.29	93.80	0.838	0.25	13.7
6883.86	8.724	45.35	94.16	0.839	0.25	13.8

6924.59	8.684	45.39	94.51	0.839	0.25	13.8
6965.32	8.659	45.45	94.86	0.840	0.26	13.9
7006.06	8.623	45.49	95.21	0.841	0.26	13.9
7046.79	8.596	45.54	95.56	0.841	0.26	14.0
7087.52	8.578	45.56	95.91	0.842	0.26	14.0
7128.25	8.545	45.59	96.26	0.842	0.26	14.1
7168.99	8.582	45.55	96.61	0.841	0.27	14.1
7209.72	8.512	45.63	96.96	0.843	0.27	14.2
7250.45	8.502	45.63	97.30	0.843	0.27	14.2
7291.19	8.501	45.63	97.65	0.843	0.27	14.3
7331.92	8.482	45.67	98.00	0.843	0.27	14.3
7372.65	8.448	45.72	98.34	0.844	0.27	14.4
7413.38	8.466	45.68	98.68	0.844	0.28	14.4
7454.12	8.440	45.70	99.03	0.844	0.28	14.5
7494.85	8.408	45.74	99.37	0.845	0.28	14.5
7535.58	8.380	45.76	99.71	0.845	0.28	14.6
7576.32	8.423	45.74	100.1	0.844	0.28	14.6
7617.05	8.408	45.74	100.4	0.845	0.29	14.7
7657.78	8.373	45.77	100.7	0.845	0.29	14.7
7698.52	8.397	45.77	101.1	0.845	0.29	14.8
7739.25	8.364	45.76	101.4	0.845	0.29	14.8
7779.98	8.361	45.80	101.8	0.846	0.29	14.9
7820.71	8.327	45.83	102.1	0.846	0.30	14.9
7861.45	8.318	45.83	102.4	0.846	0.30	15.0
7902.18	8.293	45.87	102.8	0.847	0.30	15.0
7942.91	8.278	45.89	103.1	0.847	0.30	15.1
7983.65	8.255	45.91	103.5	0.848	0.30	15.1
8024.38	8.242	45.91	103.8	0.848	0.30	15.2
8065.11	8.222	45.94	104.1	0.848	0.31	15.2
8105.84	8.251	45.90	104.5	0.848	0.31	15.3
8146.58	8.213	45.94	104.8	0.848	0.31	15.3
8187.31	8.201	45.95	105.1	0.849	0.31	15.4
8228.04	8.180	45.96	105.5	0.849	0.31	15.4
8268.78	8.138	46.03	105.8	0.850	0.32	15.5
8309.51	8.081	46.08	106.1	0.851	0.32	15.5
8350.24	8.042	46.13	106.4	0.852	0.32	15.6
8390.97	8.040	46.15	106.8	0.852	0.32	15.6
8431.71	7.992	46.21	107.1	0.853	0.32	15.7
8472.44	7.978	46.24	107.4	0.853	0.33	15.7
8513.17	7.961	46.26	107.8	0.853	0.33	15.7
8553.90	7.961	46.27	108.1	0.853	0.33	15.8
8594.63	7.922	46.31	108.4	0.854	0.33	15.8
8635.37	7.892	46.35	108.7	0.854	0.33	15.9
8676.10	7.847	46.41	109.0	0.855	0.33	15.9
8716.83	7.859	46.41	109.4	0.855	0.34	16.0
8757.56	7.807	46.48	109.7	0.856	0.34	16.0
8798.30	7.814	46.47	110.0	0.856	0.34	16.1
8839.03	7.728	46.56	110.3	0.858	0.34	16.1
8879.76	7.681	46.60	110.6	0.858	0.34	16.2
8920.49	7.669	46.65	110.9	0.859	0.35	16.2
8961.23	7.598	46.74	111.2	0.860	0.35	16.3
9001.96	7.558	46.80	111.6	0.861	0.35	16.3
9042.69	7.490	46.88	111.9	0.862	0.35	16.3
9083.42	7.425	46.96	112.2	0.863	0.35	16.4
9124.16	7.383	47.03	112.5	0.864	0.36	16.4
9164.89	7.304	47.11	112.8	0.866	0.36	16.5
9205.62	7.281	47.17	113.1	0.866	0.36	16.5
9246.35	7.167	47.30	113.3	0.868	0.36	16.6
9287.09	7.109	47.38	113.6	0.870	0.36	16.6
9327.82	7.038	47.46	113.9	0.871	0.36	16.6

9368.55	6.969	47.54	114.2	0.872	0.37	16.7
9409.28	6.908	47.61	114.5	0.873	0.37	16.7
9450.02	6.883	47.66	114.8	0.874	0.37	16.8
9490.75	6.822	47.73	115.0	0.875	0.37	16.8
9531.48	6.792	47.76	115.3	0.875	0.37	16.9
9572.21	6.769	47.79	115.6	0.876	0.38	16.9
9612.95	6.766	47.82	115.9	0.876	0.38	16.9
9653.68	6.712	47.83	116.1	0.877	0.38	17.0
9694.41	6.685	47.89	116.4	0.878	0.38	17.0
9735.14	6.664	47.94	116.7	0.878	0.38	17.1
9775.88	6.636	47.95	117.0	0.878	0.39	17.1
9816.61	6.619	47.99	117.2	0.879	0.39	17.1
9857.34	6.594	48.03	117.5	0.879	0.39	17.2
9898.07	6.573	48.05	117.8	0.880	0.39	17.2
9938.80	6.537	48.10	118.0	0.880	0.39	17.3
9979.54	6.527	48.13	118.3	0.881	0.39	17.3
10020.27	6.454	48.20	118.6	0.882	0.40	17.3
10061.00	6.461	48.22	118.8	0.882	0.40	17.4
10101.73	6.383	48.31	119.1	0.883	0.40	17.4
10142.47	6.364	48.35	119.3	0.884	0.40	17.4
10183.20	6.312	48.41	119.6	0.885	0.40	17.5
10223.93	6.251	48.48	119.9	0.886	0.41	17.5
10264.66	6.199	48.54	120.1	0.887	0.41	17.6
10305.40	6.152	48.62	120.4	0.888	0.41	17.6
10346.13	6.093	48.68	120.6	0.889	0.41	17.6
10386.86	6.033	48.75	120.9	0.890	0.41	17.7
10427.59	5.995	48.81	121.1	0.891	0.42	17.7
10468.33	5.917	48.88	121.3	0.892	0.42	17.7
10509.06	5.851	48.95	121.6	0.893	0.42	17.8
10549.79	5.842	48.98	121.8	0.893	0.42	17.8
10590.52	5.774	49.06	122.1	0.895	0.42	17.8
10631.26	5.751	49.09	122.3	0.895	0.42	17.9
10671.99	5.705	49.15	122.5	0.896	0.43	17.9
10712.72	5.668	49.19	122.7	0.897	0.43	17.9
10753.45	5.624	49.23	123.0	0.897	0.43	18.0
10794.19	5.607	49.27	123.2	0.898	0.43	18.0
10834.92	5.581	49.29	123.4	0.898	0.43	18.0
10875.65	5.541	49.33	123.7	0.899	0.44	18.1
10916.38	5.519	49.36	123.9	0.899	0.44	18.1
10957.12	5.518	49.39	124.1	0.900	0.44	18.1
10997.85	5.456	49.42	124.3	0.901	0.44	18.2

TOTAL PATTERN RESULTS:

WATERFLOOD RECOVERY	:	847.78	MSTB
WATERFLOOD+INFILL RECOVERY	:	994.64	MSTB
INCREMENTAL OIL FROM INFILL:		146.87	MSTB
INCREMENTAL OIL FROM INFILL:		2.68	% OOIP
ORIGINAL OIL IN PLACE	:	5474.04	MSTB

APPENDIX IIIa

SPE REFERENCE PAPER FOR IDPM SENSITIVITY ANALYSIS

SPE 22333

Screening Waterfloods for Infill Drilling Opportunities

S.M. Fuller, Unocal Oil & Gas N.A.; A.M. Sarem, Unocal Science & Technology;
and T.L. Gould, Scientific Software-Intercomp

SPE Members

Copyright 1992, Society of Petroleum Engineers, Inc.

This paper was prepared for presentation at the SPE International Meeting on Petroleum Engineering held in Beijing, China, 24-27 March 1992.

This paper was selected for presentation by an SPE Program Committee following review of information contained in an abstract submitted by the author(s). Contents of the paper, as presented, have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material, as presented, does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Papers presented at SPE meetings are subject to publication review by Editorial Committees of the Society of Petroleum Engineers. Permission to copy is restricted to an abstract of not more than 300 words. Illustrations may not be copied. The abstract should contain conspicuous acknowledgment of where and by whom the paper is presented. Write Librarian, SPE, P.O. Box 833836, Richardson, TX 75083-3836 U.S.A. Telex, 730989 SPEDAL.

ABSTRACT

Infill drilling is now recognized as a viable improved recovery process. However, the reliable prediction of incremental recovery by infill drilling cannot be readily and accurately determined by present techniques.

As an alternate approach, a DOE sponsored infill drilling predictive model (IDPM) was evaluated. Its performance was improved by adjusting some of its key parameters based on the comparison of actual field recoveries with model results.

Also discussed in the paper is the sensitivity of infill recovery to areal and vertical heterogeneities. Also highlighted is the importance of applying remedial techniques is highlighted, such as near well plug backs and in-depth mobility control upon the recovery efficiency.

INTRODUCTION - CONCEPT

Infill drilling for acceleration and incremental recovery has been a common industry practice for many years. The infill drilling opportunity exists in all stages of development: primary, secondary, and tertiary. However, determining if the opportunity can be economically realized is no simple task. Previous approaches have involved overly simple streamtube models, or overly complex 3-D numerical simulators combined with separate economic analysis.

Recognizing this problem, the U.S. Department of Energy has recently created a "Predictive Model" for infill drilling of waterflood projects. This model uses a minimum amount of reservoir and geologic description to determine if an existing waterflood project would benefit from infill drilling. The predictive model is a hybrid between streamtube and numerical simulators, and provides fast, accurate predictions of waterflood infill behavior. The resulting performance prediction is combined with estimates of capital and operating cost to determine a

discounted economic assessment of a proposed project. In his way, both acceleration and incremental recovery effects can be accounted for when screening several opportunities.

The purpose of this paper is to determine if the IDPM can be used to screen for infill drilling opportunities. The use of a screening model implies acceptance of major assumptions in the formulation of the model. Since the model is only being used to determine which projects are economically better than others, it does not require a full field simulation, but assumes instead that a pattern element is representative of average reservoir behavior. However, we must be satisfied that the principal recovery mechanisms in the process are correctly simulated. A comparison should be made with an existing project to identify parameters that are sensitive and what mechanisms accurately model real behavior.

Although the predictive model matches ideal reservoir behavior under a controlled set of assumptions, it has some difficulty matching actual project performance. By comparing model behavior to actual field performance, we have determined the key factors required to make such a predictive model suitable for screening studies.

In infill drilling projects in West Texas, incremental recovery in carbonates has been attributed primarily to improved continuity between wells, and therefore more net pay contacted by the flood. During the analysis of one typical waterflood, the North Riley Unit, we discovered that both sweep efficiency and improved continuity play major roles due to the highly heterogeneous nature of the reservoir. Furthermore, through the analysis of the results, it became apparent that near well plug backs by a process such as crosslinked polymer gel injection, or in-depth mobility and permeability variation control by a process such as Mobility Controlled Caustic Flood (MCCF), could result in a significant additional recovery.

INFILL DRILLING PREDICTIVE MODEL (IDPM)

The Infill Drilling Predictive Model (IDPM) has a similar design to that of the other DOE predictive models:

References and illustrations at end of paper.

1)	Polymer flooding	(DOE/BC - 86/10/SP)
2)	Chemical flooding	(DOE/BC - 86/11/SP)
3)	CO ₂ miscible flooding	(DOE/BC - 86/12/SP)
4)	Steam flooding	(DOE/BC - 86/6/SP)
5)	Insitu combustion	(DOE/BC - 86/7/SP)

This model is a specialized model for waterflood patterns, and incorporates several recovery mechanisms:

- 1) Improved reservoir continuity
- 2) Improved areal sweep
- 3) Improved vertical sweep
- 4) Cross flow between layers
- 5) Plug back at infill of thief zones

These mechanisms are simulated to provide production and recovery forecasts for continued waterflood and infill cases. These production forecasts, consisting of oil and water rate versus time, are then passed to an economic module for individual and incremental economics. Data for drilling and completion, injection, operating cost, and a pattern schedule (to simulate field-wide development) allow the computation of before and after tax discounted cash flow. By comparing the infill project to continued waterflood, the incremental economic profitability criteria used for screening are computed, such as DCFROR and Profit to Investment ratio.

The IDPM is a hybrid between streamtube and numerical simulators, and provides fast, accurate predictions of waterflood infill behavior. The IDPM assumes that streamtubes do not change shape with water cut, and that the streamtubes are independent of mobility ratio. The IDPM is a three-dimensional two-phase simulator of a waterflood pattern element which is made up of a collection of two-dimensional slices for each streamtube. Each streamtube slice allows cross flow between layers and tracks oil and water fluid movements using a finite difference simulation. FIGURE 1 shows the streamtubes for typical conditions in 5 to 5-spot and 5 to 9-spot pattern elements before and after infill.

Streamtube shapes are computed based upon a steady-state pressure solution before and after infill using the anisotropy ratio K_y/K_x to approximate areal heterogeneity. The saturations at the infill point are mapped into the new streamtubes at infill with material balance preserved. Vertical heterogeneity is modeled by assigning layer permeability using the Dykstra-Parsons(1) coefficient (V_{dp}). The IDPM allows the user to optionally apply plug backs at the infill point to control thief zones simulating near well profile control by a water shutoff process.

Reservoir continuity is modelled by adjusting the relative permeability curves before and after infill. These curves are determined from Corey-type equations base upon end point values:

$$U_o = (1.0 - S_w - S_{orw}) / (1.0 - S_{wc} - S_{orw}) \quad (1)$$

$$K_{ro} = K_{roe} * U_o ** X_{no} \quad (2)$$

$$U_w = (S_w - S_{wc}) / (1.0 - S_{wc} - S_{orw}) \quad (3)$$

$$K_{rw} = K_{rwe} * U_w ** X_{nw} \quad (4)$$

Continuity (C), or connectivity, of 100 percent is assumed to be represented by laboratory relative permeability measurements. Under field conditions with lower continuity, the residual oil saturation due to waterflood (S_{orw}) is adjusted linearly:

$$S_{orw|used} = C * S_{orw} + (1.0 - C) * (1.0 - S_{oi}) \quad (5)$$

This means that at zero continuity, S_{orw} would equal $(1.0 - S_{oi})$ and no recovery would occur due to waterflood. As a default, each layer uses S_{oi} equal to S_{wc} . However, if a primary recovery is specified, then S_{oi} in each layer is adjusted according to V_{dp} , assuming that the most productive layers will be the greatest depleted. The relative permeabilities in Eqn's 2 and 4 are then computed before and after infill based upon S_{orw} which is tied to continuity by Eqn 5.

Continuity in turn is tied to well spacing assuming a semi-log relationship allowing 100 percent continuity at a finite well spacing. The IDPM computes the distance down each streamtube and then determines a unique relative permeability relationship, based on continuity for each tube.

PROJECT COMPARISONS

1. North Riley Field Description

The North Riley Unit is located 12 miles west of Seminole, Texas in Gaines County. The unitized interval extends from 50 feet above the top of the Upper Clearfork to 300 feet below the top of the Lower Clearfork. The North Riley Field was unitized in December of 1975. Secondary recovery operations were implemented in the north end of the Unit with the beginning of water injection in July of 1977. Water was injected into 9 wells on an inverted 9-spot pattern. The inverted 9-spot pattern was expanded to cover the central and south portions of the unit, with a total of 18 injection wells active by 1980. In 1982, the injection pattern was changed to an 80-acre 5-spot pattern with the conversion to injection of an additional 21 wells.

The nature of the reservoir is such that the wells will not produce without fracture treating, either large acid fracture treatments or propped gelled water fracture treatments. Since the injectors were the original 40-acre producers, all have been fracture treated. However, the injectors are subject to severe scaling and this tends to unbalance the patterns over time. IDPM does not include this effect, therefore the input permeability was adjusted to match flow capacity of wells.

In 1984 increased densification was begun with the drilling of 20 acre infill wells. This converted the pattern from 80-acre 5-spot patterns to inverted 9-spot patterns. The increased densification continued through 1987 with 91 20-acre infill wells drilled. Production increased from 1375 BOPD to a peak production of 4150 BOPD. With the increased fluid production from the densification, the injection to withdrawal ratio dropped below one in the major productive area of the field. In February of 1988, selected producers were converted

to water injection service. This conversion project changed the 80-acre inverted 9-spot pattern to a 40-acre 5-spot pattern. These conversions increased injection from 12,500 BWPD to in excess of 26,000 BWPD.

In the second quarter of 1990, the North Riley Unit initiated a 10-acre infill drilling project consisting of 5 wells in a North study area and 5 wells in a South study area as shown on FIGURE 2. These 10-acre locations have been completed for potentials ranging from 365 BOPD to 90 BOPD. The average IP for the 10 wells is 180 BOPD. Prior to 10-acre infill drilling, the injection to withdrawal ratio in the two study areas was approximately 4:1. Following the infill drilling, the increased fluid withdrawals dropped the injection to withdrawal ratio to approximately one.

2. Geologic Setting

The North Riley Unit is on the northern portion of a north westward gently plunging anticline. FIGURE 3 shows a three well cross section in the North Area. This stratified dolomite has a gross interval open for production in the unit covering about 1000 feet and is divided into at least 11 productive zones. As seen in the cross section, the reservoir is divided into numerous stringers that are difficult to correlate and can vary in thickness and quality from one location to the next, as well as disappear. Within the gross interval there are more than 100 beds or lenses that have widely varying permeability, porosity, thickness, water saturation, and connectivity to neighboring wells.

Core data has been taken from the central 200 feet of the interval in several wells. This data confirms high heterogeneity with wide scatter on the traditional porosity-permeability cross plots. However, Dykstra-Parsons plots of the permeability distribution seem well behaved with at least two rock types present. The higher permeability beds have a different slope than the lower permeability beds. The average slopes from several wells range from 0.71 to 0.91.

Continuity is a major factor in the success of infill drilling. However, it is very difficult to determine, and subject to interpretation. The most prevalent method to determine this factor is to use a cross section, such as FIGURE 3, and determine which beds or lenses connect between wells and which do not. Clearly, each interpreter will determine a different answer which will be subject to change as information from infill wells becomes available.

In order to provide continuity values to the IDPM, we established low (45%), most likely (55%) and high (65%) values at 20 acre well spacing. We also estimated that 100% continuity would occur at 300 foot well spacing. The resulting continuity diagram for North Riley is shown in FIGURE 4. This means that a well with 55% continuity at 20 acre spacing will improve to 71% at 10 acres. Similarly, a well with 45% continuity at 20 acre spacing will improve to 63% at 10 acres.

TABLE 1 shows the average reservoir properties that were used to initialize IDPM for the North Riley Unit. Laboratory tests to date for relative permeability show a wide variation of behavior. However, the initial saturation at connate water ($Sw_c = 0.32$) seems to be fairly consistent. The residual oil saturation to water shows some variation, and we selected $S_{orw} = 0.25$ as a reasonable average.

3. North Riley - North Area

Reservoir Description

The North Area has better primary recovery and better flow capacity than the South Area as shown in TABLE 2. The porosity-feet (ϕh) in the North Area varies widely from 18 to 50 within the 240 acre area. However, with an average of 35.4, we can estimate the original oil in place in the North Area as follows:

$$OOIP = 7758 \cdot (\phi h) \cdot S_{oi} \cdot A / B_o \quad (6)$$

Thus,

$$OOIP = 7758 \cdot 35.4 \cdot 0.68 \cdot 240 / 1.28$$

$$OOIP = 35.0 \text{ MMBO}$$

Performance Before/After Infill

FIGURE 5 shows the historical behavior of the wells in the North Area. The voidage ratio is higher than 1.0 during fillup, as expected. Prior to the 10 acre infill program, the voidage ratio reached a high of 5, due to unbalanced injection. After the infill program, the ratio begins to approach one. The data is transformed to a cumulative oil basis on FIGURE 6, in order to show the behavior of oil cut and recovery before and after infill. Using the estimated OOIP as a basis, the primary recovery in this area is 7.9%, and the cumulative recovery prior to 10 acre infill was 11.4%. The average water cut at the beginning of infill was 39%. Immediately after infill, the water cut increased to 72%. Notice on FIGURE 6 that the oil cut increases with increasing voidage ratio just prior to infill. We cannot explain this behavior, but believe that it is a sweep related phenomenon.

One of the most interesting aspects of the North Area was revealed when we performed a classical streamline calculation using total rates for the gross interval. For this purpose, a classical streamline program was used because IDPM cannot handle the entire field. FIGURE 7 shows the streamlines before infill (June 1990) and FIGURE 8 shows the streamlines after infill (December 1990). The 1000 series well numbers indicate wells in 10-acre locations. Examination of the streamlines associated with well no. 44-R, shows that injection was going in a predominately westerly direction. Following the drilling of the infill wells, the streamlines changed such that the injection into well no. 44-R is more evenly distributed. This better distribution of injected water will result in better sweep efficiency in several areas, as shown on FIGURE 8.

Although individual zones or beds will have greatly different streamline behavior depending on flow capacity and connectivity, the overall average performance of the streamlines shows that, even in an ideal reservoir, the patterns are not well balanced before infill. This means that areal sweep efficiency will be low. After infill, with improved pattern balancing, areal sweep efficiency will increase, as shown in FIGURE 8. The true location of streamlines and the actual improvement in areal sweep is impossible to determine due to the vertical and areal heterogeneities of the reservoir.

Comparison with IDPM

The infill pattern in the North Area is part way between a 5-spot and a 9-spot. The final development plan is to complete the drilling as 9-spots, but during the period of comparison, it would be reasonable to expect behavior somewhere between that of true 5-spot and true 9-spot.

In order to provide a basis of comparison with actual reservoir performance, we have shown the forecast used for AFE justification prior to infill and the actual behavior after infill. FIGURE 9 shows the IDPM predictions for a 5 to 5-spot infill project. FIGURE 10 shows the IDPM predictions for a 5 to 9-spot infill project.

4. North Riley - South Area

Reservoir Description

The South Area has less primary recovery and worse flow capacity than the North Area as shown in TABLE 2. The porosity-feet (ϕh) in the South Area varies widely from 9 to 25 within the 240 acre area. However, with an average of 19.7, we can estimate the original oil in place in the South Area as using Eqn 6:

$$\text{OOIP} = 7758 \cdot 19.7 \cdot 0.68 \cdot 240 / 1.28$$

$$\text{OOIP} = 19.5 \text{ MMBO}$$

Performance Before/After Infill

FIGURE 11 shows the historical behavior of the wells in the South Area. The voidage ratio is higher than 1.0 during fillup, as expected. Prior to the 10 acre infill program, the voidage ratio reached a high of 4, due to unbalanced injection. After the infill program, the ratio begins to approach one. The data is transformed to a cumulative oil basis on FIGURE 12, in order to show the behavior of oil cut and recovery before and after infill. Using the estimated OOIP as a basis, the primary recovery in this area is 4.5%, and the cumulative recovery prior to 10 acre infill was 7.2%. These recoveries are about half of the North area, and are attributable to several factors; lower flow capacity, lower sweep efficiency, higher heterogeneity and lower continuity. The average water cut at the beginning of infill was 49%. Immediately after infill, the water cut increase to 55%. Just as in the North Area, FIGURE 12 shows that the oil cut increases with increasing voidage ratio.

The classical streamline calculations for the South Area also showed very interesting results. FIGURE 13 shows the streamlines before infill (June 1990) and FIGURE 14 shows the streamlines after infill (March 1991). As in the North Area the 5-spot waterflood patterns are not well balanced before infill. This means that areal sweep efficiency will be low. After infill, with improved pattern balancing, areal sweep efficiency will increase, as shown in FIGURE 14. Again, examination of the area around well no. 104-R, before and after infill, the improvement in sweep efficiency is evident. The true location of streamlines and the actual improvement in areal sweep is impossible to determine due to the vertical and areal heterogeneities of the reservoir.

Comparison with IDPM

The infill pattern in the South Area is part way between a 5-spot and a 9-spot. The final development plan is to complete the drilling as 9-spots, but during the period of comparison, it would be reasonable to expect behavior somewhere between that of true 5-spot and true 9-spot.

In order to provide a basis of comparison with actual reservoir performance, we have shown the forecast used for AFE justification prior to infill and the actual behavior after infill. FIGURE 15 shows the IDPM predictions for a 5 to 5-spot infill project. FIGURE 16 shows the IDPM predictions for a 5 to 9-spot infill project.

5. Recovery Sensitivities

Layer Sensitivity

The IDPM was found to be moderately sensitive to the number of layers used to describe the reservoir. FIGURE 17 shows the behavior of predicted incremental recovery for the case of 5-spot to 5-spot infill. As the water increases, so does the general level of incremental recovery. As the layers increase, the recovery prediction decreases and levels out at about eight layers. We used 11 layers in the North Riley comparison cases, in order to better match the known geologic setting.

Areal and Vertical Sweep Sensitivity

Anisotropy (K_y/K_x) or directional permeability was used in IDPM as a method to simulate the effects of areal heterogeneity of areal sweep. The Dykstra-Parsons coefficient (V_{dp}) was used to distribute layer permeabilities, with the maximum in the center, as a method to simulate the effects of vertical heterogeneity on vertical sweep. We found that these effects were interrelated as shown on FIGURE 18. These results are consistent with previous numerical simulation results (2,3).

As high V_{dp} , the effects of anisotropy on areal sweep was washed out by the thief zones with high permeability taking all the flow. At low V_{dp} , the influence of anisotropy is much more pronounced. It is also apparent that at lower levels of K_y/K_x , anisotropy has little effect on areal sweep as measured by incremental recovery.

FIGURE 18 also reveals that the influence of V_{dp} on recovery at any given K_y/K_x value is very non-linear. At higher V_{dp} , thief zones dominate before and after infill behavior. At lower V_{dp} , the layers have more uniform flow capacity, and cross flow between layers tends to make different levels of V_{dp} behave more equally. We used a ratio of vertical to horizontal permeability throughout this study of 0.1, as indicated by core data, which promotes high cross flow between layers.

Plug Back at Infill Sensitivity

The IDPM model allows the infill well to plug back the thief zones at infill. We found that this improves the incremental recovery and stretches out the project. FIGURE 19 shows the improved oil cut versus incremental recovery predicted by IDPM for the North Area as can be done by a crosslinked polymer gel process. The plug backs were performed in the two most productive, and highest water cut, zones. High

cross flow between layers allowed the injected water to sweep layers above and below the central thief zones resulting in improved vertical sweep.

Sensitivity to Improvement of Mobility Ratio and Vdp

The IDPM model allows the variation of viscosity ratio (and therefore mobility ratio) of oil and water within the pattern, and the variation of vertical heterogeneity using Vdp. FIGURE 20 shows the result on incremental recovery at a water cut of 95%. As expected, favorable viscosity ratios or reduced Vdp, as can be achieved by the MCCF(4) process, yield increased incremental recoveries.

WHAT WE'VE LEARNED

Improved sweep efficiency alone may be enough to make infill drilling economic in some reservoirs. This would expand the reservoirs that should be screened to include those that have relatively good continuity but poor sweep efficiency. Unocal has been successful in infill drilling in other West Texas reservoirs where the continuity was not the major deciding factor. These projects have greatly benefitted from improved sweep efficiency.

When the IDPM was first run on North Riley, it inferred that there was more recoverable oil than previously thought. This led to detailed log analysis which better defined the reservoir and gave us a better estimation of the original oil in place. The increased oil in place estimate indicated that the waterflood was less efficient than previously believed. Consequently, the recovery estimates that were used for project justification were below those given by IDPM.

The first infill well potentialized for volumes similar to those seen when the field was first drilled. The average initial potential of the first 10 wells was double what was expected. This is a further indication, that the sweep efficiency prior to infill was lower than previously believed. Repeat formation testing of the infill wells indicated that the pressure distribution in the wellbore ranged from 2000 psi under hydrostatic to 50 psi over hydrostatic pressure. This vast difference was a further indicator of poor continuity between wells and of poor sweep efficiency that the flood was experiencing. Despite the poor continuity and sweep efficiency, the existing waterflood was economically very successful prior to infill.

CONCLUSIONS

1. IDPM appears to work when run with minimum data and applied to real field scale projects.
2. Layering and pattern type have major effects on IDPM results. The poorer the continuity between wells, the more the number of layers required to obtain valid simulations.
3. Low WF efficiency yields high infill.

ACKNOWLEDGEMENTS

The authors thank Jeff Glossa, Eddie Howell, and Scott Gutberlet for their valuable contributions to this paper. We also wish to thank Unocal for permission to publish this paper.

We thank Don Thurnau for additions and improvements to IDPM which made this paper possible. The IDPM was developed by SSI under a contract from the U.S. Department of Energy (BETC), DE-AC22-88BC14242.

We are grateful to Celeste Fan, Rosanne Turczynskyj, and Louise Hall for the final assembly of this paper.

NOMENCLATURE

A	=	Area, acres
Bo	=	Oil formation volume factor
C	=	Continuity (connectivity between wells), percent
Kro	=	Oil relative permeability, fraction
Kroe	=	End point (at Swc) oil relative permeability, fraction
Krw	=	Water relative permeability, fraction
Krwe	=	End point (at Sorw) water relative permeability, fraction
Ky/Kx	=	Anisotropy ratio, y-direction to x-direction permeability
OOIP	=	Original oil in place, Bbl
Soi	=	Initial oil saturation, fraction
Swc	=	Connate (irreducible) water saturation, fraction
Sorw	=	Residual oil saturation to water, fraction
Vdp	=	Dykstra-Parsons coefficient of permeability variation
Xno	=	Oil relative permeability curvature
Xnw	=	Water relative permeability curvature
ϕh	=	Porosity-net thickness product, feet

REFERENCES

1. Dykstra, H. and Parsons, R. L.: "The Prediction of Oil Recovery by Waterflood," Secondary Recovery of Oil in The United States, 2nd ed., API (1950) 160-174.
2. Gould, T. L. and Sarem, A. M.: "Infill Drilling for Incremental Recovery," JPT (March 1989) 229-237.
3. Gould, T. L. and Munoz, M. A.: "An Analysis of Infill Drilling," paper SPE 11021 presented at the 1982 SPE Annual Technical Conference and Exhibition, New Orleans, Sept. 26-27.
4. Sarem, A. M.: "Secondary and Tertiary Recovery by the MCCF Process," paper SPE 4901 presented at the 1974 California Regional SPE Meeting, San Francisco, April 4-5.

GENERAL RESERVOIR PROPERTIES USED IN PREDICTIVE MODEL

AVERAGE DEPTH	6300 FEET
FORMATION TEMP	107 DEG F
DYKSTRA-PARSONS COEF.	.83 VDP
PRESSURE AT FORMATION TOP	2750 PSIA
OIL GRAVITY	32.0 DEG API
OIL FVF	1.285
OIL VISC. AT RES. COND.	1.70 CP
SOLUTION GAS-OIL RATIO	330 SCF/STB
IRREDUCIBLE WATER SATURATION	.32
RESIDUAL OIL SATURATION	.25

TABLE 1

NORTH RILEY RESERVOIR DATA

	<u>NORTH STUDY AREA</u>	<u>SOUTH STUDY AREA</u>
AVE. NET PAY	477 FEET	266 FEET
RATIO OF GROSS/NET PAY	1.43	2.45
AVE. POROSITY	7.0	7.0
CALC. OOIP	35 MMBO	19.5 MMBO
% PRIMARY RECOVERY	7.9%	4.5%
% CUM PROD AT 6/90	11.4%	7.2%
% WATER CUT BEFORE INFILL	39.2%	49.3%
WATER CUT AT INFILL	72.0%	55.0%

TABLE 2

Figure 2

Figure 1. Before and After Infill Configurations

NORTH STUDY AREA

Figure 3

CONTINUITY

Figure 4

Figure 5

NORTH STUDY AREA

Figure 6

Figure 7. North Area Streamlines Prior to Infill

NORTH AREA IDPM PERFORMANCE 5 to 5-spot

Figure 8. North Area Streamlines After Infill

Figure 9

NORTH AREA IDPM PERFORMANCE 5 to 9-spot

Figure 10

SOUTH STUDY AREA

Figure 11

SOUTH STUDY AREA

Figure 12

Figure 13. South Area Streamlines Prior to Infill

Figure 14. South Area Streamlines After Infill

SOUTH AREA IDPM PERFORMANCE 5 to 5-spot

Figure 15

SOUTH AREA IDPM PERFORMANCE 5 to 9-spot

Figure 16

LAYER SENSITIVITY 5-SPOT TO 5-SPOT C=55% at 20 acres & Infill Water Cut=75%

Figure 17

SENSITIVITY OF AREAL & VERTICAL SWEEP

Figure 18

IDPM PLUG BACK SENSITIVITY

Figure 19

IDPM SENSITIVITY TO VISCOSITY AND V_{DP}

Figure 20

APPENDIX IIIb

IDPM BASE CASE INPUT/OUTPUT FOR IDPM SENSITIVITY ANALYSIS

```

*****
*
*   S C I E N T I F I C   S O F T W A R E   *
*   -   I N T E R C O M P                   *
*
*
*   INFILL DRILLING PREDICTION MODEL        *
*   (IDPM - RELEASE 1.2.0)                  *
*
*****

```

IDPM Sensitivity Analysis: North Riley Unit Base Case
 IDPM Sensitivity Analysis: North Riley Unit Base Case

```

0, 1, 1, 2, 0, 0.83
1, 11, 15, 1., 0.10, 0
40., 300., 933., .55, 200., 400., .75, 0.95, 0.
.000003, 3000., 2750., -6300., 107.
64.00, 0.0, .000003, .6, 0.8
32.00, 1.28, .00000735, 1.7, 330.
2., 2., .752, .40, .32, .25, 0.
1
0.0800, 10., 400.
Economics for Waterflood
40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0
0.0, 0.0, 0.0, 0.03
0.0, 0.001, 0.0
0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04
0.0, 0.0, 0.0, 0.0, 23.07
0.0, 0.0, 0.0, 0.0, 0.0, 0.0
6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
16.00, 20.00, 24.00
2.67, 3.33, 4.00
33313., 41642., 49970.
.04, .05, .06
Economics for Infill Waterflood
40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0
0.0, 0.0, 0.0, 0.03
0.0, 0.001, 0.0
0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04
0.0, 0.0, 0.0, 0.0, 23.07
0.0, 0.0, 0.0, 0.0, 0.0, 0.0
6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
16.00, 20.00, 24.00
2.67, 3.33, 4.00
33313., 41642., 49970.
.04, .05, .06
Economics for Infill over Non-Infill

```

40, 53, 0, 2, 0, 1, 0, 0, 0, 0, 0, 0
0.0, 0.0, 0.0, 0.03
0.0, 0.001, 0.0
0.1, 0.05, 0.125, 0.08, 0.46, 0.1, 5.0, 0.04
0.0, 0.0, 0.0, 23.07
0.0, 0.0, 0.0, 0.0, 0.0
6.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0
16.00, 20.00, 24.00
2.67, 3.33, 4.00
33313., 41642., 49970.
.04, .05, .06
END

I D P M CURRENT MAXIMUM PARAMETER VALUES

NUMBER OF TUBES PER LAYER.....	16
NUMBER OF GRID CELLS PER TUBE.....	15
NUMBER OF LAYERS.....	20
NUMBER OF TIMESTEPS IN RESERVOIR RUN..	5000
BLANK COMMON SIZE FOR RESERVOIR RUN...	10000
NUMBER OF YEARS FOR ECONOMIC ANALYSIS.	50

SPECIFIED PRINTOUT CONTROLS

RESERVOIR ARRAY OUTPUT CONTROL	0	IARRP
RESERVOIR ANALYSIS OUTPUT CONTROL	1	IANALP
STREAMTUBE OUTPUT CONTROL	1	ISTRMP
ECONOMIC ANALYSIS CONTROL(0-NO, 1-YES)	2	IECONR

RESERVOIR PROPERTIES OUTPUT

FORMATION DEPTH -- SUBSURFACE.....	--6300.0	FEET
FORMATION TEMPERATURE	107.0	DEG F
INDIVIDUAL PATTERN AREA	40.0	ACRES
KV/KH VERTICAL TO HORIZONTAL PERM.....	0.100	
KY/KX ANISOTROPIC VALUE (1.0-100.0)...	1.000	
DYKSTRA-PARSONS COEFFICIENT	0.83	VDP
PRESSURE AT FORMATION TOP	2750.0	PSIA
PORE VOLUME COMPRESSIBILITY	0.00000300	1/PSI
REFERENCE PRESSURE (POROSITY MEASURED)	3000.0	PSIA

NUMBER OF LAYERS 11
 STREAMTUBES PER LAYER 12
 NUMBER OF GRID CELLS PER STREAMTUBE... 15
 INFILL PATTERN (0=5-SPOT, 1=9-SPOT).... 0

PROPERTIES BY LAYER

POROSITY	X-DIR	PERM	NET	PAY
0.0800	73.58		36.36	
0.0800	15.09		36.36	
0.0800	7.96		36.36	
0.0800	4.86		36.36	
0.0800	3.15		36.36	
0.0800	2.09		36.36	
0.0800	1.39		36.36	
0.0800	0.91		36.36	
0.0800	0.56		36.36	
0.0800	0.30		36.36	
0.0800	0.10		36.36	

WATER DENSITY AT STANDARD CONDITIONS.. 64.00 LB/CUFT
 WATER DENSITY AT RESERVOIR CONDITIONS. 64.08 LB/CUFT
 WATER FORMATION VOLUME FACTOR..... 1.00 VOL/VOL
 WATER COMPRESSIBILITY AT RES. COND....0.00000300 1/PSI
 WATER VISCOSITY AT RES. COND..... 0.60 CP

OIL DENSITY AT STANDARD CONDITIONS.... 54.00 LB/CUFT
 OIL GRAVITY 32.0 DEG API
 OIL DENSITY AT RESERVOIR CONDITIONS... 42.19 LB/CUFT
 OIL FORMATION VOLUME FACTOR..... 1.28 VOL/VOL
 OIL COMPRESSIBILITY AT RES. COND.....0.00000735 1/PSI
 OIL VISCOSITY AT RES. COND..... 1.70 CP
 SOLUTION GAS-OIL-RATIO 330.0 SCF/STB
 GAS GRAVITY (AIR=1.0)..... 0.800

INJECTION RATE (NON-INFILL) 200.0 STBW/D
 INJECTION RATE (INFILL, MAY BE 0.0) .. 400.0 STBW/D
 WATER CUT AT INFILL (VCUT) 0.750 FRAC.
 WATER CUT AT END (CUTMAX) 0.950 FRAC.
 PLUG BACK AT INFILL (1=NO) 1
 (2=YES, IF LAYER W-CUT .GT. VCUT) .

RELATIVE PERMEABILITY DATA
 IRREDUCIBLE WATER SATURATION 0.320 SWC

RESIDUAL OIL SATN -- INPUT --	0.250	SORW
OIL RELATIVE PERM END-POINT	0.752	XKROE
WATER RELATIVE PERM END-POINT	0.400	XKRWE
OIL RELATIVE PERM CURVATURE	2.00	XNO
WATER RELATIVE PERM CURVATURE	2.00	XNW
(MAX) WELL DIST. FOR CONN.=100%	300.000	VWD100
WELL DIST. FOR CONN.=VCONEC	933.000	VDBWLS
RESERVOIR CONNECTIVITY AT VDBWLS	0.550	VCONEC

RELATIVE PERMEABILITY TABLE
FOR CONNECTIVITY = 1.00000

WATER SATURATN	OIL KRO	WATER KRW	FW (FR FLOW)	D(FW) / D(SW)
0.3200	0.7520	0.0000	0.000	
0.3415	0.6787	0.0010	0.004	0.193
0.3630	0.6091	0.0040	0.018	0.656
0.3845	0.5433	0.0090	0.045	1.236
0.4060	0.4813	0.0160	0.086	1.919
0.4275	0.4230	0.0250	0.143	2.667
0.4490	0.3685	0.0360	0.217	3.412
0.4705	0.3177	0.0490	0.304	4.060
0.4920	0.2707	0.0640	0.401	4.514
0.5135	0.2275	0.0810	0.502	4.701
0.5350	0.1880	0.1000	0.601	4.601
0.5565	0.1523	0.1210	0.692	4.247
0.5780	0.1203	0.1440	0.772	3.713
0.5995	0.0921	0.1690	0.839	3.088
0.6210	0.0677	0.1960	0.891	2.452
0.6425	0.0470	0.2250	0.931	1.859
0.6640	0.0301	0.2560	0.960	1.342
0.6855	0.0169	0.2890	0.980	0.910
0.7070	0.0075	0.3240	0.992	0.564
0.7285	0.0019	0.3610	0.998	0.293
0.7500	0.0000	0.4000	1.000	0.085

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

PROPERTIES BY LAYER

POROSITY	X-DIR PERM	NET PAY	SO	SW
0.0800	73.58	36.36	0.6800	0.3200
0.0800	15.09	36.36	0.6800	0.3200
0.0800	7.96	36.36	0.6800	0.3200
0.0800	4.86	36.36	0.6800	0.3200

0.0800	3.15	36.36	0.6800	0.3200
0.0800	2.09	36.36	0.6800	0.3200
0.0800	1.39	36.36	0.6800	0.3200
0.0800	0.91	36.36	0.6800	0.3200
0.0800	0.56	36.36	0.6800	0.3200
0.0800	0.30	36.36	0.6800	0.3200
0.0800	0.10	36.36	0.6800	0.3200

 N O N - I N F I L L S I M U L A T I O N

SYMMETRY ELEMENT WITHIN 5-SPOT, BEFORE IN-FILL
 =====

ISOTROPIC PERMEABILITY CASE - 1/8
 =====

I

I

I

.....

WATER SATURATN	OIL KRO	WATER KRW	FW (FR FLOW)	D(FW) / D(SW)
0.3200	0.7520	0.0000	0.000	
0.3415	0.6215	0.0033	0.015	0.691
0.3630	0.5034	0.0132	0.069	2.531
0.3845	0.3978	0.0298	0.175	4.912
0.4060	0.3045	0.0529	0.330	7.206
0.4275	0.2237	0.0826	0.511	8.445
0.4490	0.1554	0.1190	0.685	8.055
0.4705	0.0994	0.1620	0.822	6.389
0.4920	0.0559	0.2116	0.915	4.313
0.5135	0.0249	0.2678	0.968	2.494
0.5350	0.0062	0.3306	0.993	1.169
0.5565	0.0000	0.4000	1.000	0.307
0.5780	0.0000	0.4760	1.000	0.000
0.5995	0.0000	0.5587	1.000	0.000
0.6210	0.0000	0.6479	1.000	0.000

0.6425	0.0000	0.7438	1.000	0.000
0.6640	0.0000	0.8463	1.000	0.000
0.6855	0.0000	0.9554	1.000	0.000
0.7070	0.0000	1.0000	1.000	0.000
0.7285	0.0000	1.0000	1.000	0.000
0.7500	0.0000	1.0000	1.000	0.000

FW = MOBW / (MOBW+MOBO), WHERE
 MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
 (THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
 (OF THE AREA OF THE PRE-INFILL 5-SPOT.)

IN - PLACE - VOLUMES				
LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.46723E+05	0.28211E+05	0.88107E+05
2	1	0.46728E+05	0.28212E+05	0.88110E+05
3	1	0.46733E+05	0.28214E+05	0.88113E+05
4	1	0.46738E+05	0.28216E+05	0.88116E+05
5	1	0.46743E+05	0.28218E+05	0.88118E+05
6	1	0.46749E+05	0.28220E+05	0.88121E+05
7	1	0.46754E+05	0.28221E+05	0.88124E+05
8	1	0.46759E+05	0.28223E+05	0.88127E+05
9	1	0.46764E+05	0.28225E+05	0.88130E+05
10	1	0.46769E+05	0.28227E+05	0.88133E+05
11	1	0.46774E+05	0.28229E+05	0.88135E+05
1	2	0.35616E+05	0.21504E+05	0.67162E+05
2	2	0.35620E+05	0.21506E+05	0.67165E+05
3	2	0.35624E+05	0.21507E+05	0.67167E+05
4	2	0.35628E+05	0.21508E+05	0.67169E+05
5	2	0.35632E+05	0.21510E+05	0.67171E+05
6	2	0.35636E+05	0.21511E+05	0.67173E+05
7	2	0.35639E+05	0.21513E+05	0.67175E+05
8	2	0.35643E+05	0.21514E+05	0.67177E+05
9	2	0.35647E+05	0.21515E+05	0.67180E+05
10	2	0.35651E+05	0.21517E+05	0.67182E+05
11	2	0.35655E+05	0.21518E+05	0.67184E+05
1	3	0.37296E+05	0.22519E+05	0.70331E+05
2	3	0.37300E+05	0.22520E+05	0.70333E+05
3	3	0.37304E+05	0.22522E+05	0.70336E+05
4	3	0.37309E+05	0.22523E+05	0.70338E+05

5	3	0.37313E+05	0.22525E+05	0.70340E+05
6	3	0.37317E+05	0.22526E+05	0.70342E+05
7	3	0.37321E+05	0.22528E+05	0.70345E+05
8	3	0.37325E+05	0.22529E+05	0.70347E+05
9	3	0.37329E+05	0.22530E+05	0.70349E+05
10	3	0.37333E+05	0.22532E+05	0.70351E+05
11	3	0.37337E+05	0.22533E+05	0.70354E+05
1	4	0.30657E+05	0.18510E+05	0.57811E+05
2	4	0.30660E+05	0.18511E+05	0.57813E+05
3	4	0.30663E+05	0.18512E+05	0.57814E+05
4	4	0.30667E+05	0.18514E+05	0.57816E+05
5	4	0.30670E+05	0.18515E+05	0.57818E+05
6	4	0.30674E+05	0.18516E+05	0.57820E+05
7	4	0.30677E+05	0.18517E+05	0.57822E+05
8	4	0.30680E+05	0.18518E+05	0.57824E+05
9	4	0.30684E+05	0.18520E+05	0.57825E+05
10	4	0.30687E+05	0.18521E+05	0.57827E+05
11	4	0.30691E+05	0.18522E+05	0.57829E+05
1	5	0.25902E+05	0.15640E+05	0.48845E+05
2	5	0.25905E+05	0.15641E+05	0.48847E+05
3	5	0.25908E+05	0.15642E+05	0.48848E+05
4	5	0.25911E+05	0.15643E+05	0.48850E+05
5	5	0.25914E+05	0.15644E+05	0.48852E+05
6	5	0.25917E+05	0.15645E+05	0.48853E+05
7	5	0.25920E+05	0.15646E+05	0.48855E+05
8	5	0.25922E+05	0.15647E+05	0.48856E+05
9	5	0.25925E+05	0.15648E+05	0.48858E+05
10	5	0.25928E+05	0.15649E+05	0.48859E+05
11	5	0.25931E+05	0.15650E+05	0.48861E+05
1	6	0.24919E+05	0.15046E+05	0.46990E+05
2	6	0.24922E+05	0.15047E+05	0.46992E+05
3	6	0.24924E+05	0.15048E+05	0.46993E+05
4	6	0.24927E+05	0.15048E+05	0.46995E+05
5	6	0.24930E+05	0.15049E+05	0.46997E+05
6	6	0.24933E+05	0.15050E+05	0.46998E+05
7	6	0.24935E+05	0.15051E+05	0.47000E+05
8	6	0.24938E+05	0.15052E+05	0.47001E+05
9	6	0.24941E+05	0.15053E+05	0.47003E+05
10	6	0.24944E+05	0.15054E+05	0.47004E+05
11	6	0.24946E+05	0.15055E+05	0.47006E+05
1	7	0.24263E+05	0.14650E+05	0.45754E+05
2	7	0.24266E+05	0.14651E+05	0.45755E+05
3	7	0.24268E+05	0.14652E+05	0.45757E+05
4	7	0.24271E+05	0.14652E+05	0.45758E+05
5	7	0.24274E+05	0.14653E+05	0.45760E+05
6	7	0.24276E+05	0.14654E+05	0.45761E+05
7	7	0.24279E+05	0.14655E+05	0.45763E+05
8	7	0.24282E+05	0.14656E+05	0.45764E+05
9	7	0.24284E+05	0.14657E+05	0.45766E+05
10	7	0.24287E+05	0.14658E+05	0.45767E+05
11	7	0.24290E+05	0.14659E+05	0.45769E+05
1	8	0.22870E+05	0.13808E+05	0.43126E+05
2	8	0.22872E+05	0.13809E+05	0.43128E+05
3	8	0.22875E+05	0.13810E+05	0.43129E+05

4	8	0.22877E+05	0.13811E+05	0.43130E+05
5	8	0.22880E+05	0.13812E+05	0.43132E+05
6	8	0.22882E+05	0.13813E+05	0.43133E+05
7	8	0.22885E+05	0.13814E+05	0.43134E+05
8	8	0.22887E+05	0.13814E+05	0.43136E+05
9	8	0.22890E+05	0.13815E+05	0.43137E+05
10	8	0.22892E+05	0.13816E+05	0.43139E+05
11	8	0.22895E+05	0.13817E+05	0.43140E+05
1	9	0.20738E+05	0.12522E+05	0.39107E+05
2	9	0.20741E+05	0.12522E+05	0.39108E+05
3	9	0.20743E+05	0.12523E+05	0.39110E+05
4	9	0.20745E+05	0.12524E+05	0.39111E+05
5	9	0.20748E+05	0.12525E+05	0.39112E+05
6	9	0.20750E+05	0.12526E+05	0.39113E+05
7	9	0.20752E+05	0.12526E+05	0.39115E+05
8	9	0.20754E+05	0.12527E+05	0.39116E+05
9	9	0.20757E+05	0.12528E+05	0.39117E+05
10	9	0.20759E+05	0.12529E+05	0.39118E+05
11	9	0.20761E+05	0.12530E+05	0.39120E+05
1	10	0.20165E+05	0.12175E+05	0.38025E+05
2	10	0.20167E+05	0.12176E+05	0.38026E+05
3	10	0.20169E+05	0.12177E+05	0.38028E+05
4	10	0.20171E+05	0.12177E+05	0.38029E+05
5	10	0.20173E+05	0.12178E+05	0.38030E+05
6	10	0.20176E+05	0.12179E+05	0.38031E+05
7	10	0.20178E+05	0.12180E+05	0.38032E+05
8	10	0.20180E+05	0.12181E+05	0.38034E+05
9	10	0.20182E+05	0.12181E+05	0.38035E+05
10	10	0.20185E+05	0.12182E+05	0.38036E+05
11	10	0.20187E+05	0.12183E+05	0.38037E+05
1	11	0.21230E+05	0.12818E+05	0.40035E+05
2	11	0.21233E+05	0.12819E+05	0.40036E+05
3	11	0.21235E+05	0.12820E+05	0.40037E+05
4	11	0.21237E+05	0.12821E+05	0.40038E+05
5	11	0.21240E+05	0.12822E+05	0.40040E+05
6	11	0.21242E+05	0.12823E+05	0.40041E+05
7	11	0.21244E+05	0.12823E+05	0.40042E+05
8	11	0.21247E+05	0.12824E+05	0.40044E+05
9	11	0.21249E+05	0.12825E+05	0.40045E+05
10	11	0.21251E+05	0.12826E+05	0.40046E+05
11	11	0.21254E+05	0.12827E+05	0.40047E+05
1	12	0.25411E+05	0.15343E+05	0.47918E+05
2	12	0.25413E+05	0.15344E+05	0.47919E+05
3	12	0.25416E+05	0.15345E+05	0.47921E+05
4	12	0.25419E+05	0.15346E+05	0.47923E+05
5	12	0.25422E+05	0.15346E+05	0.47924E+05
6	12	0.25425E+05	0.15347E+05	0.47926E+05
7	12	0.25427E+05	0.15348E+05	0.47927E+05
8	12	0.25430E+05	0.15349E+05	0.47929E+05
9	12	0.25433E+05	0.15350E+05	0.47930E+05
10	12	0.25436E+05	0.15351E+05	0.47932E+05
11	12	0.25439E+05	0.15352E+05	0.47933E+05
TOTALS		0.36957E+07	0.22309E+07	0.69665E+07

(M-STB) 658.19 397.31

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
0.2	65.9	65.901	1	1

PRODUCTION/INJECTION RATE (STB/D)		CUMULATIVE PRODUCTION/INJECTION (STB)
OIL	WATER	OIL
21.01	0.4062E-10	1384.
		WATER
		0.2677E-08
		1648.

CURRENT IN-PLACE-VOLUMES	MAXIMUM
OIL (MSTB)	PRESSURE
656.81	2869.8
WATER (MSTB)	
398.96	

MATERIAL BALANCE ERROR
OIL
1.0000
WATER
1.0000

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
0.4	131.8	65.901	2	2

PRODUCTION/INJECTION RATE (STB/D)		CUMULATIVE PRODUCTION/INJECTION (STB)
OIL	WATER	OIL
19.68	0.2425E-04	2681.
		WATER
		0.1598E-02
		3296.

CURRENT IN-PLACE-VOLUMES	MAXIMUM
OIL (MSTB)	PRESSURE
655.51	2870.4
WATER (MSTB)	
400.61	

MATERIAL BALANCE ERROR
OIL
1.0000
WATER
1.0000

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
13.7	5008.5	65.901	76	76
PRODUCTION/INJECTION RATE (STB/D)				
OIL	WATER	INJECTION	OIL	WATER
7.024	16.00	25.00	0.6512E+05	0.4185E+05
CUMULATIVE PRODUCTION/INJECTION (STB)				
OIL				
WATER				
INJECTION				
0.1252E+06				
CURRENT IN-PLACE-VOLUMES				
MAXIMUM				
OIL (MSTB)	PRESSURE			
592.94	2885.6			
WATER (MSTB)				
480.95				

MATERIAL BALANCE ERROR	
OIL	WATER
0.99980	1.0007

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
17.5	6392.4	65.901	97	97
PRODUCTION/INJECTION RATE (STB/D)				
OIL	WATER	INJECTION	OIL	WATER
5.795	17.59	25.00	0.7389E+05	0.6523E+05
CUMULATIVE PRODUCTION/INJECTION (STB)				
OIL				
WATER				
INJECTION				
0.1598E+06				
CURRENT IN-PLACE-VOLUMES				
MAXIMUM				
OIL (MSTB)	PRESSURE			
584.13	2887.8			
WATER (MSTB)				
492.25				

MATERIAL BALANCE ERROR	
OIL	WATER
0.99973	1.0009

CONTINUATION OF WATERFLOOD AFTER WATER CUT FOR INFILL

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
17.7	6458.3	65.901	1	98

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
5.769	17.62	25.00	0.7427E+05	0.6639E+05	0.1615E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
583.75	492.75	2887.9

MATERIAL BALANCE ERROR	
OIL	WATER
0.99973	1.0009

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
27.2	9951.1	65.901	54	151

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
4.123	19.70	25.00	0.9114E+05	0.1321E+06	0.2488E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
566.82	514.49	2893.0

MATERIAL BALANCE ERROR	
OIL	WATER
0.99962	1.0012

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
40.8	14893.7	65.901	129	226

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
2.924	21.25	25.00	0.1083E+06	0.2338E+06	0.3724E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
549.65	536.52	2898.5

MATERIAL BALANCE ERROR

OIL	WATER
0.99957	1.0015

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
54.5	19902.1	65.901	205	302

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
2.238	22.13	25.00	0.1211E+06	0.3426E+06	0.4976E+06

CURRENT IN-PLACE-VOLUMES			MAXIMUM
OIL (MSTB)	WATER (MSTB)		PRESSURE
536.82	552.99		2902.2

MATERIAL BALANCE ERROR	
OIL	WATER
0.99954	1.0016

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
68.0	24844.7	65.901	280	377

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
1.805	22.73	25.00	0.1309E+06	0.4536E+06	0.6212E+06

CURRENT IN-PLACE-VOLUMES			MAXIMUM
OIL (MSTB)	WATER (MSTB)		PRESSURE
526.97	565.62		2904.5

MATERIAL BALANCE ERROR	
OIL	WATER
0.99955	1.0018

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
-------	------	---------	------------	-------------

81.6	29787.2	65.901	355	452
PRODUCTION/INJECTION RATE (STB/D)				
OIL	WATER	INJECTION	OIL	WATER
1.479	23.12	25.00	0.1389E+06	0.5671E+06
CURRENT IN-PLACE-VOLUMES				
OIL (MSTB)	WATER (MSTB)			
519.03	575.81			
CUMULATIVE PRODUCTION/INJECTION (STB)				
OIL	WATER	INJECTION	OIL	WATER
0.1389E+06	0.5671E+06	0.7448E+06	0.1389E+06	0.5671E+06

MAXIMUM
PRESSURE
2906.1

MATERIAL BALANCE ERROR
OIL
0.99961
WATER
1.0019

TIME STEPS EXECUTED.... 524
GRID-CELL-TIME-STEPS... 11412720

I N F I L L S I M U L A T I O N

SYMMETRY ELEMENT AFTER 5-SPOT IN-FILL
=====

ISOTROPIC PERMEABILITY CASE - 1/8
=====

I

P

I

```
*****
* FRACTIONAL WELL RATES FOR TUBE CALCULATIONS *
* PRODUCER = 0.10000E+01 *
* Y-DIR INJECTOR = -0.50000E+00 *
* X-DIR INJECTOR = -0.50000E+00 *
*****
* INJECTOR AT COORD ( 1, 65 ) *
* INJECTOR AT COORD ( 65, 1 ) *
* PRODUCER AT COORD ( 1, 1 ) *
*****
```

```
*****
* STREAM TUBES *
*****
```

```
1\
135\
146\
1356\
12466\
134566\
1234566\
12345666\
123445666\
1233455666\
12234455666\
1223344556666\
12233445566666\
11233445566666\
112233445566666\
1122333445566666\
11223334455666666\
```


	SATURATN	KRO	KRM	(FR FLOW)	D(SM)
	WATER	OIL	WATER	FW	D(FW) /

[illegible]

0.3200	0.7520	0.0000	0.000	
0.3415	0.6501	0.0020	0.009	0.397
0.3630	0.5556	0.0079	0.039	1.403
0.3845	0.4685	0.0178	0.097	2.711
0.4060	0.3888	0.0316	0.187	4.187
0.4275	0.3166	0.0493	0.306	5.546
0.4490	0.2518	0.0710	0.444	6.418
0.4705	0.1944	0.0967	0.585	6.545
0.4920	0.1444	0.1263	0.712	5.932
0.5135	0.1018	0.1598	0.816	4.835
0.5350	0.0666	0.1973	0.893	3.583
0.5565	0.0389	0.2387	0.946	2.425
0.5780	0.0186	0.2841	0.977	1.480
0.5995	0.0057	0.3334	0.994	0.771
0.6210	0.0002	0.3867	1.000	0.270
0.6425	0.0000	0.4439	1.000	0.009
0.6640	0.0000	0.5051	1.000	0.000
0.6855	0.0000	0.5702	1.000	0.000
0.7070	0.0000	0.6392	1.000	0.000
0.7285	0.0000	0.7122	1.000	0.000
0.7500	0.0000	0.7892	1.000	0.000

FW = MOBW / (MOBW+MOBO), WHERE
MOBW = KRW/VISW, MOBO = KRO/VISO

SIMULATED FLOODING OF SYMMETRY ELEMENT STREAM TUBES

(ALL VOLUMES/RATES GIVEN BELOW ARE FOR)
(THE SYMMETRY ELEMENT WHICH HAS 1.0/8.0)
(OF THE AREA OF THE PRE-INFILL 5-SPOT.)

		IN - PLACE - VOLUMES		
LAYER	TUBE	OIL (SCF)	WATER (SCF)	PORE VOL. (RCF)
1	1	0.97984E+04	0.14339E+05	0.26896E+05
2	1	0.99496E+04	0.14148E+05	0.26897E+05
3	1	0.10323E+05	0.13673E+05	0.26898E+05
4	1	0.10689E+05	0.13207E+05	0.26899E+05
5	1	0.11209E+05	0.12542E+05	0.26900E+05
6	1	0.11945E+05	0.11601E+05	0.26901E+05
7	1	0.12738E+05	0.10585E+05	0.26902E+05
8	1	0.13364E+05	0.97858E+04	0.26903E+05
9	1	0.13764E+05	0.92747E+04	0.26904E+05
10	1	0.14017E+05	0.89530E+04	0.26904E+05

11	1	0.14194E+05	0.87281E+04	0.26905E+05
1	2	0.13840E+05	0.20133E+05	0.37870E+05
2	2	0.14052E+05	0.19865E+05	0.37871E+05
3	2	0.14603E+05	0.19163E+05	0.37873E+05
4	2	0.15141E+05	0.18477E+05	0.37875E+05
5	2	0.15932E+05	0.17467E+05	0.37876E+05
6	2	0.17126E+05	0.15939E+05	0.37878E+05
7	2	0.18240E+05	0.14513E+05	0.37879E+05
8	2	0.18959E+05	0.13594E+05	0.37880E+05
9	2	0.19432E+05	0.12991E+05	0.37881E+05
10	2	0.19756E+05	0.12578E+05	0.37882E+05
11	2	0.19990E+05	0.12282E+05	0.37883E+05
1	3	0.15012E+05	0.21721E+05	0.40961E+05
2	3	0.15229E+05	0.21448E+05	0.40963E+05
3	3	0.15840E+05	0.20669E+05	0.40965E+05
4	3	0.16445E+05	0.19899E+05	0.40967E+05
5	3	0.17398E+05	0.18679E+05	0.40968E+05
6	3	0.18835E+05	0.16840E+05	0.40969E+05
7	3	0.19868E+05	0.15519E+05	0.40971E+05
8	3	0.20591E+05	0.14595E+05	0.40972E+05
9	3	0.21090E+05	0.13958E+05	0.40973E+05
10	3	0.21415E+05	0.13545E+05	0.40974E+05
11	3	0.21638E+05	0.13263E+05	0.40975E+05
1	4	0.18141E+05	0.26212E+05	0.49462E+05
2	4	0.18409E+05	0.25875E+05	0.49464E+05
3	4	0.19155E+05	0.24924E+05	0.49467E+05
4	4	0.19895E+05	0.23980E+05	0.49469E+05
5	4	0.21109E+05	0.22429E+05	0.49471E+05
6	4	0.22831E+05	0.20223E+05	0.49472E+05
7	4	0.24198E+05	0.18475E+05	0.49474E+05
8	4	0.25062E+05	0.17371E+05	0.49475E+05
9	4	0.25564E+05	0.16731E+05	0.49477E+05
10	4	0.25894E+05	0.16312E+05	0.49478E+05
11	4	0.26138E+05	0.16004E+05	0.49480E+05
1	5	0.20622E+05	0.29679E+05	0.56109E+05
2	5	0.20916E+05	0.29308E+05	0.56111E+05
3	5	0.21778E+05	0.28210E+05	0.56114E+05
4	5	0.22644E+05	0.27105E+05	0.56116E+05
5	5	0.24127E+05	0.25208E+05	0.56118E+05
6	5	0.26149E+05	0.22620E+05	0.56120E+05
7	5	0.27691E+05	0.20648E+05	0.56122E+05
8	5	0.28575E+05	0.19518E+05	0.56123E+05
9	5	0.29102E+05	0.18847E+05	0.56125E+05
10	5	0.29438E+05	0.18421E+05	0.56127E+05
11	5	0.29673E+05	0.18124E+05	0.56128E+05
1	6	0.33202E+05	0.47405E+05	0.89959E+05
2	6	0.33649E+05	0.46843E+05	0.89963E+05
3	6	0.35082E+05	0.45015E+05	0.89967E+05
4	6	0.36536E+05	0.43161E+05	0.89971E+05
5	6	0.39079E+05	0.39907E+05	0.89974E+05
6	6	0.42905E+05	0.35008E+05	0.89977E+05
7	6	0.45255E+05	0.32001E+05	0.89980E+05
8	6	0.46331E+05	0.30629E+05	0.89982E+05
9	6	0.46936E+05	0.29860E+05	0.89985E+05

10	6	0.47328E+05	0.29366E+05	0.89988E+05
11	6	0.47615E+05	0.29006E+05	0.89990E+05
1	7	0.28310E+05	0.37210E+05	0.73496E+05
2	7	0.28198E+05	0.37362E+05	0.73500E+05
3	7	0.29754E+05	0.35374E+05	0.73503E+05
4	7	0.31694E+05	0.32894E+05	0.73506E+05
5	7	0.36091E+05	0.27261E+05	0.73508E+05
6	7	0.38975E+05	0.23567E+05	0.73510E+05
7	7	0.39086E+05	0.23431E+05	0.73513E+05
8	7	0.39057E+05	0.23474E+05	0.73515E+05
9	7	0.39035E+05	0.23510E+05	0.73517E+05
10	7	0.39029E+05	0.23524E+05	0.73519E+05
11	7	0.39021E+05	0.23540E+05	0.73521E+05
1	8	0.23389E+05	0.30146E+05	0.60126E+05
2	8	0.23182E+05	0.30419E+05	0.60129E+05
3	8	0.24539E+05	0.28685E+05	0.60131E+05
4	8	0.26356E+05	0.26361E+05	0.60134E+05
5	8	0.30579E+05	0.20948E+05	0.60136E+05
6	8	0.31999E+05	0.19133E+05	0.60137E+05
7	8	0.31982E+05	0.19160E+05	0.60139E+05
8	8	0.31957E+05	0.19197E+05	0.60141E+05
9	8	0.31938E+05	0.19227E+05	0.60143E+05
10	8	0.31933E+05	0.19238E+05	0.60145E+05
11	8	0.31922E+05	0.19258E+05	0.60147E+05
1	9	0.22654E+05	0.28460E+05	0.57498E+05
2	9	0.22295E+05	0.28927E+05	0.57501E+05
3	9	0.23672E+05	0.27168E+05	0.57503E+05
4	9	0.25717E+05	0.24550E+05	0.57506E+05
5	9	0.29726E+05	0.19413E+05	0.57507E+05
6	9	0.30621E+05	0.18269E+05	0.57509E+05
7	9	0.30590E+05	0.18314E+05	0.57511E+05
8	9	0.30565E+05	0.18352E+05	0.57513E+05
9	9	0.30546E+05	0.18381E+05	0.57514E+05
10	9	0.30542E+05	0.18391E+05	0.57516E+05
11	9	0.30532E+05	0.18410E+05	0.57518E+05
1	10	0.19681E+05	0.23924E+05	0.49152E+05
2	10	0.19186E+05	0.24565E+05	0.49154E+05
3	10	0.20417E+05	0.22991E+05	0.49156E+05
4	10	0.22495E+05	0.20330E+05	0.49158E+05
5	10	0.25655E+05	0.16281E+05	0.49159E+05
6	10	0.26151E+05	0.15649E+05	0.49161E+05
7	10	0.26131E+05	0.15679E+05	0.49162E+05
8	10	0.26110E+05	0.15711E+05	0.49164E+05
9	10	0.26095E+05	0.15734E+05	0.49165E+05
10	10	0.26094E+05	0.15740E+05	0.49167E+05
11	10	0.26081E+05	0.15761E+05	0.49168E+05
1	11	0.19145E+05	0.22292E+05	0.46833E+05
2	11	0.18449E+05	0.23190E+05	0.46835E+05
3	11	0.19667E+05	0.21633E+05	0.46837E+05
4	11	0.22016E+05	0.18624E+05	0.46839E+05
5	11	0.24644E+05	0.15257E+05	0.46840E+05
6	11	0.24903E+05	0.14929E+05	0.46842E+05
7	11	0.24882E+05	0.14961E+05	0.46843E+05
8	11	0.24871E+05	0.14978E+05	0.46845E+05

9	11	0.24867E+05	0.14987E+05	0.46846E+05
10	11	0.24862E+05	0.14998E+05	0.46848E+05
11	11	0.24854E+05	0.15013E+05	0.46849E+05
1	12	0.18694E+05	0.20860E+05	0.44824E+05
2	12	0.17877E+05	0.21914E+05	0.44826E+05
3	12	0.19113E+05	0.20334E+05	0.44828E+05
4	12	0.21728E+05	0.16983E+05	0.44829E+05
5	12	0.23697E+05	0.14460E+05	0.44831E+05
6	12	0.23813E+05	0.14317E+05	0.44832E+05
7	12	0.23802E+05	0.14334E+05	0.44834E+05
8	12	0.23796E+05	0.14346E+05	0.44835E+05
9	12	0.23794E+05	0.14353E+05	0.44836E+05
10	12	0.23787E+05	0.14366E+05	0.44838E+05
11	12	0.23778E+05	0.14381E+05	0.44839E+05
TOTALS		0.32801E+07	0.27638E+07	0.69663E+07
(M-STB)		584.16	492.22	

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
17.6	6425.4	32.951	1	98

PRODUCTION/INJECTION RATE (STB/D)	CUMULATIVE PRODUCTION/INJECTION (STB)
OIL	OIL
15.66	515.9
WATER	WATER
30.40	1002.
INJECTION	INJECTION
50.01	1648.

CURRENT IN-PLACE-VOLUMES	MAXIMUM
OIL (MSTB)	PRESSURE
583.60	2901.1
WATER (MSTB)	
492.94	

MATERIAL BALANCE ERROR

OIL	WATER
0.99991	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
17.7	6458.3	32.951	2	99

PRODUCTION/INJECTION RATE (STB/D)	CUMULATIVE PRODUCTION/INJECTION (STB)
OIL	OIL
	WATER
WATER	WATER
INJECTION	INJECTION

15.36 30.40 50.01 1022. 2003. 3296.

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
583.09	493.58	2904.1

MATERIAL BALANCE ERROR	
OIL	WATER
0.99991	1.0001

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
24.4	8896.7	32.951	76	173

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
8.443	39.19	50.01	0.2866E+05	0.8854E+05	0.1252E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
555.36	529.15	2911.3

MATERIAL BALANCE ERROR	
OIL	WATER
0.99975	1.0005

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS	DAYS	DELTA-T	CASE STEPS	TOTAL STEPS
31.1	11367.9	32.951	151	248

PRODUCTION/INJECTION RATE (STB/D)			CUMULATIVE PRODUCTION/INJECTION (STB)		
OIL	WATER	INJECTION	OIL	WATER	INJECTION
6.299	41.93	50.01	0.4648E+05	0.1893E+06	0.2488E+06

CURRENT IN-PLACE-VOLUMES		MAXIMUM
OIL (MSTB)	WATER (MSTB)	PRESSURE
537.47	552.11	2915.6

MATERIAL BALANCE ERROR	
OIL	WATER
0.99962	1.0007

PERIODIC REPORT ON STATUS OF SIMULATION

```

-----
YEARS      DAYS      DELTA-T    CASE STEPS  TOTAL STEPS
37.9      13839.2    32.951      226         323

PRODUCTION/INJECTION RATE (STB/D)      CUMULATIVE PRODUCTION/INJECTION (STB)
OIL      WATER      INJECTION      OIL      WATER      INJECTION
5.139      43.42      50.01      0.6050E+05  0.2949E+06  0.3724E+06

CURRENT IN-PLACE-VOLUMES      MAXIMUM
OIL (MSTB)      WATER (MSTB)      PRESSURE
523.41      570.14      2917.1

MATERIAL BALANCE ERROR
OIL      WATER
0.99955      1.0009
  
```

PERIODIC REPORT ON STATUS OF SIMULATION

```

-----
YEARS      DAYS      DELTA-T    CASE STEPS  TOTAL STEPS
44.7      16343.4    32.951      302         399

PRODUCTION/INJECTION RATE (STB/D)      CUMULATIVE PRODUCTION/INJECTION (STB)
OIL      WATER      INJECTION      OIL      WATER      INJECTION
4.308      44.48      50.01      0.7229E+05  0.4050E+06  0.4976E+06

CURRENT IN-PLACE-VOLUMES      MAXIMUM
OIL (MSTB)      WATER (MSTB)      PRESSURE
511.60      585.30      2917.9

MATERIAL BALANCE ERROR
OIL      WATER
0.99951      1.0010
  
```

PERIODIC REPORT ON STATUS OF SIMULATION

```

-----
YEARS      DAYS      DELTA-T    CASE STEPS  TOTAL STEPS
51.5      18814.7    32.951      377         474

PRODUCTION/INJECTION RATE (STB/D)      CUMULATIVE PRODUCTION/INJECTION (STB)
  
```

OIL 3.704 WATER 45.29 INJECTION 50.01 OIL 0.8218E+05 WATER 0.5160E+06 INJECTION 0.6212E+06

CURRENT IN-PLACE-VOLUMES

OIL (MSTB) 501.70 WATER (MSTB) 598.00

MATERIAL BALANCE ERROR

OIL 0.99949 WATER 1.0011

MAXIMUM
PRESSURE
2918.5

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS 58.3 DAYS 21286.1 DELTA-T 32.951 CASE STEPS 452 TOTAL STEPS 549

PRODUCTION/INJECTION RATE (STB/D) CUMULATIVE PRODUCTION/INJECTION (STB)
OIL 3.220 WATER 45.90 INJECTION 50.01 OIL 0.9070E+05 WATER 0.6287E+06 INJECTION 0.7448E+06

CURRENT IN-PLACE-VOLUMES

OIL (MSTB) 493.19 WATER (MSTB) 608.92

MATERIAL BALANCE ERROR

OIL 0.99950 WATER 1.0011

MAXIMUM
PRESSURE
2918.4

PERIODIC REPORT ON STATUS OF SIMULATION

YEARS 65.1 DAYS 23790.4 DELTA-T 32.951 CASE STEPS 528 TOTAL STEPS 625

PRODUCTION/INJECTION RATE (STB/D) CUMULATIVE PRODUCTION/INJECTION (STB)
OIL 2.844 WATER 46.39 INJECTION 50.01 OIL 0.9825E+05 WATER 0.7443E+06 INJECTION 0.8701E+06

CURRENT IN-PLACE-VOLUMES

OIL (MSTB) 485.65 WATER (MSTB) 618.59

MATERIAL BALANCE ERROR

OIL WATER

MAXIMUM
PRESSURE
2918.3

0.99951

1.0012

PERIODIC REPORT ON STATUS OF SIMULATION

```

-----
      YEARS      DAYS      DELTA-T      CASE STEPS      TOTAL STEPS
      71.9      26261.7      32.951      603      700

PRODUCTION/INJECTION RATE (STB/D)      CUMULATIVE PRODUCTION/INJECTION (STB)
      OIL      WATER      INJECTION      OIL      WATER      INJECTION
      2.487      46.84      50.01      0.1048E+06      0.8595E+06      0.9937E+06

      CURRENT IN-PLACE-VOLUMES      MAXIMUM
      OIL (MSTB)      WATER (MSTB)      PRESSURE
      479.11      626.98      2918.3

      MATERIAL BALANCE ERROR
      OIL      WATER
      0.99953      1.0013

```

```

TIME STEPS EXECUTED....      609
GRID-CELL-TIME-STEPS... 13264020

```

PERFORMANCE VERSUS TIME FOR NON-INFILL

```

=====
      TIME      OIL RATE      WATER RATE      CUMOIL      WCUT      PV INJ      OIL REC
      DAYS      STB/D      STB/D      MSTB      FRAC.      FRAC.      %OOIP
      65.90      21.01      0.4062E-10      1.384      0.000      0.00      0.2
      131.80      19.68      0.2425E-04      2.681      0.000      0.00      0.4
      197.70      19.58      0.1479E-03      3.971      0.000      0.00      0.6
      263.60      19.53      0.3929E-03      5.258      0.000      0.01      0.8
      329.51      19.50      0.4520E-03      6.543      0.000      0.01      1.0
      395.41      19.49      0.3204E-03      7.828      0.000      0.01      1.2
      461.31      19.46      0.2290E-03      9.110      0.000      0.01      1.4
      527.21      19.50      0.2419E-03      10.39      0.000      0.01      1.6
      593.11      19.46      0.2878E-03      11.68      0.000      0.01      1.8
      659.01      19.50      0.4118E-03      12.96      0.000      0.01      2.0
      724.91      19.47      0.3440E-03      14.25      0.000      0.01      2.2
      790.81      19.51      0.2578E-03      15.53      0.000      0.02      2.4
      856.71      19.48      0.1879E-03      16.82      0.000      0.02      2.5
      922.62      19.46      0.2447E-03      18.10      0.000      0.02      2.7
      988.52      19.48      0.3005E-03      19.38      0.000      0.02      2.9
      1054.42      19.46      0.3546E-03      20.66      0.000      0.02      3.1

```

1120.32	18.34	1.422	21.87	0.072	0.02	3.3
1186.22	18.26	1.525	23.08	0.077	0.02	3.5
1252.12	18.41	1.333	24.29	0.068	0.03	3.7
1318.02	17.05	3.156	25.41	0.156	0.03	3.9
1383.92	17.49	2.548	26.57	0.127	0.03	4.0
1449.82	15.77	4.760	27.60	0.232	0.03	4.2
1515.73	16.56	3.721	28.70	0.183	0.03	4.4
1581.63	15.65	4.896	29.73	0.238	0.03	4.5
1647.53	15.95	4.522	30.78	0.221	0.03	4.7
1713.43	15.38	5.278	31.79	0.255	0.03	4.8
1779.33	15.28	5.410	32.80	0.262	0.04	5.0
1845.23	14.84	5.936	33.78	0.286	0.04	5.1
1911.13	14.69	6.156	34.74	0.295	0.04	5.3
1977.03	14.39	6.511	35.69	0.312	0.04	5.4
2042.94	14.15	6.832	36.63	0.326	0.04	5.6
2108.84	13.84	7.243	37.54	0.344	0.04	5.7
2174.74	13.47	7.703	38.42	0.364	0.04	5.8
2240.64	13.17	8.094	39.29	0.381	0.05	6.0
2306.54	12.89	8.449	40.14	0.396	0.05	6.1
2372.44	12.61	8.836	40.97	0.412	0.05	6.2
2438.34	12.36	9.167	41.79	0.426	0.05	6.3
2504.24	12.08	9.519	42.58	0.441	0.05	6.5
2570.14	11.81	9.859	43.36	0.455	0.05	6.6
2636.05	11.58	10.14	44.12	0.467	0.05	6.7
2701.95	11.39	10.39	44.88	0.477	0.05	6.8
2767.85	11.20	10.65	45.61	0.488	0.06	6.9
2833.75	11.02	10.89	46.34	0.497	0.06	7.0
2899.65	10.81	11.13	47.05	0.507	0.06	7.1
2965.55	10.67	11.35	47.75	0.515	0.06	7.2
3031.45	10.46	11.58	48.44	0.525	0.06	7.3
3097.35	10.31	11.78	49.12	0.533	0.06	7.4
3163.25	10.11	12.02	49.79	0.543	0.06	7.6
3229.16	9.964	12.22	50.45	0.551	0.07	7.7
3295.06	9.793	12.46	51.09	0.560	0.07	7.7
3360.96	9.660	12.63	51.73	0.567	0.07	7.8
3426.86	9.501	12.84	52.36	0.575	0.07	7.9
3492.76	9.352	13.02	52.97	0.582	0.07	8.0
3558.66	9.221	13.18	53.58	0.588	0.07	8.1
3624.56	9.076	13.39	54.18	0.596	0.07	8.2
3690.46	8.954	13.54	54.77	0.602	0.07	8.3
3756.36	8.828	13.69	55.35	0.608	0.08	8.4
3822.27	8.700	13.86	55.92	0.614	0.08	8.5
3888.17	8.599	14.00	56.49	0.619	0.08	8.6
3954.07	8.479	14.15	57.05	0.625	0.08	8.7
4019.97	8.381	14.28	57.60	0.630	0.08	8.7
4085.87	8.246	14.43	58.14	0.636	0.08	8.8
4151.77	8.169	14.55	58.68	0.641	0.08	8.9
4217.67	8.056	14.69	59.21	0.646	0.09	9.0
4283.57	7.954	14.81	59.74	0.651	0.09	9.1
4349.48	7.865	14.94	60.26	0.655	0.09	9.1
4415.38	7.758	15.06	60.77	0.660	0.09	9.2
4481.28	7.692	15.16	61.27	0.663	0.09	9.3
4547.18	7.597	15.29	61.77	0.668	0.09	9.4
4613.08	7.503	15.40	62.27	0.672	0.09	9.4

4678.98	7.425	15.50	62.76	0.676	0.09	9.5
4744.88	7.342	15.60	63.24	0.680	0.10	9.6
4810.78	7.246	15.72	63.72	0.684	0.10	9.7
4876.69	7.180	15.81	64.19	0.688	0.10	9.7
4942.59	7.101	15.91	64.66	0.691	0.10	9.8
5008.49	7.024	16.00	65.12	0.695	0.10	9.9
5074.39	6.944	16.11	65.58	0.699	0.10	9.9
5140.29	6.880	16.18	66.03	0.702	0.10	10.0
5206.19	6.797	16.29	66.48	0.706	0.10	10.1
5272.09	6.738	16.37	66.93	0.708	0.11	10.1
5338.00	6.670	16.46	67.37	0.712	0.11	10.2
5403.90	6.613	16.55	67.80	0.715	0.11	10.3
5469.80	6.541	16.62	68.23	0.718	0.11	10.3
5535.70	6.476	16.69	68.66	0.720	0.11	10.4
5601.60	6.417	16.79	69.08	0.723	0.11	10.5
5667.50	6.368	16.85	69.50	0.726	0.11	10.5
5733.40	6.296	16.93	69.92	0.729	0.12	10.6
5799.31	6.266	16.99	70.33	0.731	0.12	10.7
5865.21	6.198	17.08	70.74	0.734	0.12	10.7
5931.11	6.147	17.13	71.14	0.736	0.12	10.8
5997.01	6.088	17.21	71.55	0.739	0.12	10.8
6062.91	6.033	17.26	71.94	0.741	0.12	10.9
6128.81	5.990	17.34	72.34	0.743	0.12	11.0
6194.71	5.951	17.39	72.73	0.745	0.12	11.0
6260.61	5.902	17.45	73.12	0.747	0.13	11.1
6326.52	5.846	17.51	73.50	0.750	0.13	11.1
6392.42	5.795	17.59	73.89	0.752	0.13	11.2
6458.32	5.769	17.62	74.27	0.753	0.13	11.3
6524.22	5.714	17.71	74.64	0.756	0.13	11.3
6590.12	5.685	17.74	75.02	0.757	0.13	11.4
6656.02	5.626	17.81	75.39	0.760	0.13	11.4
6721.92	5.593	17.84	75.76	0.761	0.14	11.5
6787.83	5.544	17.92	76.12	0.764	0.14	11.5
6853.73	5.510	17.96	76.48	0.765	0.14	11.6
6919.63	5.463	18.01	76.84	0.767	0.14	11.7
6985.53	5.431	18.06	77.20	0.769	0.14	11.7
7051.43	5.382	18.11	77.56	0.771	0.14	11.8
7117.33	5.357	18.15	77.91	0.772	0.14	11.8
7183.23	5.311	18.21	78.26	0.774	0.14	11.9
7249.14	5.272	18.25	78.61	0.776	0.15	11.9
7315.04	5.229	18.31	78.95	0.778	0.15	12.0
7380.94	5.209	18.33	79.30	0.779	0.15	12.0
7446.84	5.167	18.39	79.64	0.781	0.15	12.1
7512.74	5.131	18.43	79.97	0.782	0.15	12.1
7578.64	5.093	18.47	80.31	0.784	0.15	12.2
7644.54	5.055	18.52	80.64	0.786	0.15	12.2
7710.44	5.035	18.57	80.98	0.787	0.16	12.3
7776.35	4.999	18.61	81.30	0.788	0.16	12.3
7842.25	4.974	18.64	81.63	0.789	0.16	12.4
7908.15	4.939	18.70	81.96	0.791	0.16	12.4
7974.05	4.908	18.72	82.28	0.792	0.16	12.5
8039.95	4.884	18.76	82.60	0.793	0.16	12.5
8105.85	4.840	18.81	82.92	0.795	0.16	12.6
8171.75	4.823	18.85	83.24	0.796	0.16	12.6

8237.66	4.785	18.89	83.56	0.798	0.17	12.7
8303.56	4.765	18.91	83.87	0.799	0.17	12.7
8369.46	4.723	18.96	84.18	0.801	0.17	12.8
8435.36	4.702	18.98	84.49	0.801	0.17	12.8
8501.26	4.671	19.02	84.80	0.803	0.17	12.9
8567.16	4.655	19.05	85.10	0.804	0.17	12.9
8633.06	4.592	19.10	85.41	0.806	0.17	13.0
8698.96	4.592	19.12	85.71	0.806	0.18	13.0
8764.87	4.558	19.16	86.01	0.808	0.18	13.0
8830.77	4.541	19.20	86.31	0.809	0.18	13.1
8896.67	4.507	19.23	86.61	0.810	0.18	13.1
8962.57	4.480	19.26	86.90	0.811	0.18	13.2
9028.47	4.442	19.29	87.19	0.813	0.18	13.2
9094.37	4.433	19.32	87.49	0.813	0.18	13.3
9160.27	4.396	19.37	87.78	0.815	0.18	13.3
9226.18	4.384	19.39	88.07	0.816	0.19	13.4
9292.08	4.347	19.42	88.35	0.817	0.19	13.4
9357.98	4.328	19.45	88.64	0.818	0.19	13.4
9423.88	4.301	19.48	88.92	0.819	0.19	13.5
9489.78	4.284	19.50	89.20	0.820	0.19	13.5
9555.68	4.249	19.56	89.48	0.821	0.19	13.6
9621.58	4.243	19.57	89.76	0.822	0.19	13.6
9687.49	4.209	19.60	90.04	0.823	0.20	13.7
9753.39	4.201	19.62	90.32	0.824	0.20	13.7
9819.29	4.168	19.67	90.59	0.825	0.20	13.7
9885.19	4.154	19.68	90.87	0.826	0.20	13.8
9951.09	4.123	19.70	91.14	0.827	0.20	13.8
10016.99	4.101	19.73	91.41	0.828	0.20	13.9
10082.89	4.081	19.76	91.68	0.829	0.20	13.9
10148.79	4.044	19.78	91.94	0.830	0.20	13.9
10214.70	4.038	19.82	92.21	0.831	0.21	14.0
10280.60	4.015	19.85	92.47	0.832	0.21	14.0
10346.50	4.002	19.88	92.74	0.832	0.21	14.1
10412.40	3.977	19.90	93.00	0.833	0.21	14.1
10478.30	3.958	19.93	93.26	0.834	0.21	14.1
10544.20	3.936	19.95	93.52	0.835	0.21	14.2
10610.10	3.924	19.98	93.78	0.836	0.21	14.2
10676.01	3.884	20.00	94.03	0.837	0.22	14.3
10741.91	3.881	20.04	94.29	0.838	0.22	14.3
10807.81	3.869	20.06	94.54	0.838	0.22	14.3
10873.71	3.844	20.08	94.80	0.839	0.22	14.4
10939.61	3.823	20.11	95.05	0.840	0.22	14.4
11005.51	3.800	20.13	95.30	0.841	0.22	14.5
11071.41	3.790	20.15	95.55	0.842	0.22	14.5
11137.32	3.760	20.18	95.80	0.843	0.22	14.5
11203.22	3.762	20.19	96.05	0.843	0.23	14.6
11269.12	3.723	20.23	96.29	0.845	0.23	14.6
11335.02	3.725	20.25	96.54	0.845	0.23	14.6
11400.92	3.694	20.27	96.78	0.846	0.23	14.7
11466.82	3.676	20.29	97.02	0.847	0.23	14.7
11532.72	3.673	20.32	97.26	0.847	0.23	14.7
11598.63	3.658	20.33	97.51	0.848	0.23	14.8
11664.53	3.621	20.37	97.74	0.849	0.24	14.8
11730.43	3.608	20.38	97.98	0.850	0.24	14.9

11796.33	3.588	20.42	98.22	0.851	0.24	14.9
11862.23	3.590	20.43	98.45	0.851	0.24	14.9
11928.13	3.559	20.45	98.69	0.852	0.24	15.0
11994.03	3.549	20.47	98.92	0.852	0.24	15.0
12059.93	3.530	20.49	99.16	0.853	0.24	15.0
12125.84	3.514	20.50	99.39	0.854	0.24	15.1
12191.74	3.500	20.54	99.62	0.854	0.25	15.1
12257.64	3.491	20.53	99.85	0.855	0.25	15.1
12323.54	3.466	20.58	100.1	0.856	0.25	15.2
12389.44	3.450	20.58	100.3	0.856	0.25	15.2
12455.34	3.440	20.62	100.5	0.857	0.25	15.2
12521.24	3.430	20.64	100.8	0.857	0.25	15.3
12587.15	3.407	20.66	101.0	0.858	0.25	15.3
12653.05	3.412	20.68	101.2	0.858	0.26	15.3
12718.95	3.382	20.72	101.4	0.860	0.26	15.4
12784.85	3.375	20.69	101.7	0.860	0.26	15.4
12850.75	3.350	20.74	101.9	0.861	0.26	15.4
12916.65	3.348	20.74	102.1	0.861	0.26	15.5
12982.55	3.321	20.77	102.3	0.862	0.26	15.5
13048.46	3.313	20.78	102.5	0.863	0.26	15.5
13114.36	3.302	20.80	102.7	0.863	0.26	15.6
13180.26	3.278	20.82	103.0	0.864	0.27	15.6
13246.16	3.271	20.82	103.2	0.864	0.27	15.6
13312.06	3.253	20.86	103.4	0.865	0.27	15.7
13377.96	3.251	20.87	103.6	0.865	0.27	15.7
13443.86	3.223	20.89	103.8	0.866	0.27	15.7
13509.76	3.225	20.91	104.0	0.866	0.27	15.8
13575.67	3.210	20.94	104.2	0.867	0.27	15.8
13641.57	3.188	20.94	104.5	0.868	0.27	15.8
13707.47	3.173	20.94	104.7	0.868	0.28	15.9
13773.37	3.148	20.99	104.9	0.870	0.28	15.9
13839.27	3.151	20.98	105.1	0.869	0.28	15.9
13905.17	3.131	21.01	105.3	0.870	0.28	16.0
13971.07	3.118	21.01	105.5	0.871	0.28	16.0
14036.98	3.108	21.03	105.7	0.871	0.28	16.0
14102.88	3.083	21.07	105.9	0.872	0.28	16.1
14168.78	3.079	21.07	106.1	0.872	0.29	16.1
14234.68	3.062	21.08	106.3	0.873	0.29	16.1
14300.58	3.053	21.10	106.5	0.874	0.29	16.2
14366.48	3.047	21.10	106.7	0.874	0.29	16.2
14432.38	3.029	21.13	106.9	0.875	0.29	16.2
14498.29	3.014	21.14	107.1	0.875	0.29	16.2
14564.19	3.001	21.16	107.3	0.876	0.29	16.3
14630.09	2.994	21.19	107.5	0.876	0.29	16.3
14695.99	2.976	21.18	107.7	0.877	0.30	16.3
14761.89	2.965	21.21	107.9	0.877	0.30	16.4
14827.79	2.959	21.21	108.1	0.878	0.30	16.4
14893.69	2.924	21.25	108.3	0.879	0.30	16.4
14959.59	2.946	21.23	108.5	0.878	0.30	16.4
15025.50	2.909	21.27	108.7	0.880	0.30	16.5
15091.40	2.907	21.27	108.9	0.880	0.30	16.5
15157.30	2.889	21.31	109.0	0.881	0.31	16.5
15223.20	2.895	21.29	109.2	0.880	0.31	16.6
15289.10	2.872	21.32	109.4	0.881	0.31	16.6

15355.00	2.864	21.34	109.6	0.882	0.31	16.6
15420.90	2.855	21.35	109.8	0.882	0.31	16.7
15486.81	2.852	21.37	110.0	0.882	0.31	16.7
15552.71	2.828	21.39	110.2	0.883	0.31	16.7
15618.61	2.831	21.40	110.4	0.883	0.31	16.7
15684.51	2.804	21.41	110.5	0.884	0.32	16.8
15750.41	2.793	21.42	110.7	0.885	0.32	16.8
15816.31	2.785	21.43	110.9	0.885	0.32	16.8
15882.21	2.767	21.46	111.1	0.886	0.32	16.8
15948.12	2.772	21.46	111.3	0.886	0.32	16.9
16014.02	2.743	21.48	111.5	0.887	0.32	16.9
16079.92	2.743	21.47	111.6	0.887	0.32	16.9
16145.82	2.732	21.50	111.8	0.887	0.33	17.0
16211.72	2.727	21.51	112.0	0.887	0.33	17.0
16277.62	2.707	21.53	112.2	0.888	0.33	17.0
16343.52	2.696	21.56	112.4	0.889	0.33	17.0
16409.42	2.686	21.54	112.5	0.889	0.33	17.1
16475.32	2.675	21.58	112.7	0.890	0.33	17.1
16541.22	2.676	21.58	112.9	0.890	0.33	17.1
16607.13	2.650	21.61	113.1	0.891	0.33	17.1
16673.03	2.654	21.61	113.2	0.891	0.34	17.2
16738.93	2.630	21.63	113.4	0.892	0.34	17.2
16804.83	2.635	21.63	113.6	0.891	0.34	17.2
16870.73	2.622	21.66	113.8	0.892	0.34	17.3
16936.63	2.617	21.65	113.9	0.892	0.34	17.3
17002.53	2.601	21.68	114.1	0.893	0.34	17.3
17068.43	2.594	21.69	114.3	0.893	0.34	17.3
17134.33	2.587	21.70	114.4	0.893	0.35	17.4
17200.23	2.573	21.70	114.6	0.894	0.35	17.4
17266.13	2.565	21.72	114.8	0.894	0.35	17.4
17332.03	2.563	21.72	114.9	0.894	0.35	17.4
17397.93	2.536	21.74	115.1	0.896	0.35	17.5
17463.83	2.554	21.73	115.3	0.895	0.35	17.5
17529.73	2.529	21.79	115.5	0.896	0.35	17.5
17595.63	2.532	21.77	115.6	0.896	0.35	17.5
17661.53	2.504	21.79	115.8	0.897	0.36	17.6
17727.43	2.515	21.79	115.9	0.896	0.36	17.6
17793.33	2.480	21.84	116.1	0.898	0.36	17.6
17859.23	2.507	21.82	116.3	0.897	0.36	17.6
17925.13	2.467	21.84	116.4	0.898	0.36	17.7
17991.03	2.480	21.84	116.6	0.898	0.36	17.7
18056.93	2.454	21.87	116.8	0.899	0.36	17.7
18122.83	2.464	21.86	116.9	0.899	0.37	17.7
18188.73	2.432	21.88	117.1	0.900	0.37	17.8
18254.63	2.442	21.90	117.2	0.900	0.37	17.8
18320.54	2.430	21.89	117.4	0.900	0.37	17.8
18386.44	2.417	21.90	117.6	0.901	0.37	17.8
18452.34	2.405	21.92	117.7	0.901	0.37	17.9
18518.24	2.417	21.90	117.9	0.901	0.37	17.9
18584.14	2.371	21.96	118.0	0.903	0.37	17.9
18650.04	2.407	21.93	118.2	0.901	0.38	17.9
18715.94	2.370	21.97	118.4	0.903	0.38	17.9
18781.84	2.374	21.96	118.5	0.902	0.38	18.0
18847.74	2.344	21.99	118.7	0.904	0.38	18.0

18913.64	2.379	21.97	118.8	0.902	0.38	18.0
18979.54	2.326	22.02	119.0	0.904	0.38	18.0
19045.44	2.361	21.99	119.1	0.903	0.38	18.1
19111.34	2.317	22.02	119.3	0.905	0.39	18.1
19177.24	2.336	22.00	119.4	0.904	0.39	18.1
19243.14	2.293	22.06	119.6	0.906	0.39	18.1
19309.04	2.318	22.03	119.7	0.905	0.39	18.2
19374.94	2.295	22.07	119.9	0.906	0.39	18.2
19440.84	2.299	22.07	120.0	0.906	0.39	18.2
19506.74	2.288	22.06	120.2	0.906	0.39	18.2
19572.64	2.270	22.11	120.3	0.907	0.39	18.3
19638.54	2.282	22.09	120.5	0.906	0.40	18.3
19704.44	2.258	22.10	120.6	0.907	0.40	18.3
19770.34	2.259	22.11	120.8	0.907	0.40	18.3
19836.24	2.250	22.11	120.9	0.908	0.40	18.3
19902.14	2.238	22.13	121.1	0.908	0.40	18.4
19968.04	2.237	22.13	121.2	0.908	0.40	18.4
20033.95	2.229	22.16	121.4	0.909	0.40	18.4
20099.85	2.220	22.16	121.5	0.909	0.41	18.4
20165.75	2.214	22.18	121.7	0.909	0.41	18.5
20231.65	2.200	22.19	121.8	0.910	0.41	18.5
20297.55	2.206	22.17	122.0	0.909	0.41	18.5
20363.45	2.181	22.21	122.1	0.911	0.41	18.5
20429.35	2.182	22.21	122.3	0.911	0.41	18.5
20495.25	2.177	22.22	122.4	0.911	0.41	18.6
20561.15	2.161	22.25	122.5	0.911	0.41	18.6
20627.05	2.179	22.24	122.7	0.911	0.42	18.6
20692.95	2.144	22.25	122.8	0.912	0.42	18.6
20758.85	2.154	22.23	123.0	0.912	0.42	18.6
20824.75	2.138	22.27	123.1	0.912	0.42	18.7
20890.65	2.140	22.27	123.3	0.912	0.42	18.7
20956.55	2.130	22.28	123.4	0.913	0.42	18.7
21022.45	2.113	22.31	123.5	0.913	0.42	18.7
21088.35	2.121	22.29	123.7	0.913	0.43	18.8
21154.25	2.096	22.33	123.8	0.914	0.43	18.8
21220.15	2.106	22.31	123.9	0.914	0.43	18.8
21286.05	2.094	22.33	124.1	0.914	0.43	18.8
21351.95	2.087	22.34	124.2	0.915	0.43	18.8
21417.85	2.081	22.34	124.4	0.915	0.43	18.9
21483.75	2.061	22.36	124.5	0.916	0.43	18.9
21549.65	2.069	22.37	124.6	0.915	0.43	18.9
21615.55	2.065	22.36	124.8	0.915	0.44	18.9
21681.46	2.053	22.39	124.9	0.916	0.44	18.9
21747.36	2.046	22.39	125.0	0.916	0.44	19.0
21813.26	2.050	22.40	125.2	0.916	0.44	19.0
21879.16	2.036	22.41	125.3	0.917	0.44	19.0
21945.06	2.036	22.42	125.4	0.917	0.44	19.0
22010.96	2.011	22.42	125.6	0.918	0.44	19.0
22076.86	2.031	22.42	125.7	0.917	0.44	19.1
22142.76	2.000	22.45	125.8	0.918	0.45	19.1
22208.66	2.008	22.45	126.0	0.918	0.45	19.1
22274.56	1.989	22.45	126.1	0.919	0.45	19.1
22340.46	1.996	22.45	126.2	0.918	0.45	19.1
22406.36	1.972	22.49	126.4	0.919	0.45	19.2

22472.26	1.995	22.45	126.5	0.918	0.45	19.2
22538.16	1.956	22.50	126.6	0.920	0.45	19.2
22604.06	1.982	22.47	126.8	0.919	0.46	19.2
22669.96	1.946	22.51	126.9	0.920	0.46	19.2
22735.86	1.968	22.47	127.0	0.919	0.46	19.3
22801.76	1.940	22.53	127.1	0.921	0.46	19.3
22867.66	1.955	22.52	127.3	0.920	0.46	19.3
22933.56	1.925	22.53	127.4	0.921	0.46	19.3
22999.46	1.930	22.54	127.5	0.921	0.46	19.3
23065.36	1.923	22.55	127.7	0.921	0.46	19.4
23131.26	1.919	22.56	127.8	0.922	0.47	19.4
23197.16	1.919	22.56	127.9	0.922	0.47	19.4
23263.06	1.914	22.57	128.0	0.922	0.47	19.4
23328.96	1.904	22.59	128.2	0.922	0.47	19.5
23394.87	1.901	22.56	128.3	0.922	0.47	19.5
23460.77	1.890	22.60	128.4	0.923	0.47	19.5
23526.67	1.885	22.59	128.5	0.923	0.47	19.5
23592.57	1.882	22.61	128.7	0.923	0.48	19.5
23658.47	1.874	22.63	128.8	0.924	0.48	19.5
23724.37	1.875	22.62	128.9	0.923	0.48	19.5
23790.27	1.866	22.63	129.0	0.924	0.48	19.6
23856.17	1.866	22.63	129.1	0.924	0.48	19.6
23922.07	1.852	22.64	129.3	0.924	0.48	19.6
23987.97	1.849	22.65	129.4	0.925	0.48	19.6
24053.87	1.836	22.65	129.5	0.925	0.48	19.6
24119.77	1.847	22.66	129.6	0.925	0.49	19.7
24185.67	1.826	22.67	129.8	0.925	0.49	19.7
24251.57	1.820	22.68	129.9	0.926	0.49	19.7
24317.47	1.826	22.67	130.0	0.925	0.49	19.7
24383.37	1.816	22.69	130.1	0.926	0.49	19.7
24449.27	1.808	22.71	130.2	0.926	0.49	19.7
24515.17	1.810	22.69	130.4	0.926	0.49	19.8
24581.07	1.811	22.69	130.5	0.926	0.50	19.8
24646.97	1.780	22.73	130.6	0.927	0.50	19.8
24712.87	1.792	22.70	130.7	0.927	0.50	19.8
24778.77	1.766	22.76	130.8	0.928	0.50	19.8
24844.67	1.805	22.73	130.9	0.926	0.50	19.9
24910.57	1.763	22.77	131.1	0.928	0.50	19.9
24976.47	1.787	22.74	131.2	0.927	0.50	19.9
25042.38	1.765	22.77	131.3	0.928	0.50	19.9
25108.28	1.770	22.77	131.4	0.928	0.51	19.9
25174.18	1.754	22.77	131.5	0.929	0.51	19.9
25240.08	1.764	22.77	131.6	0.928	0.51	20.0
25305.98	1.739	22.79	131.8	0.929	0.51	20.0
25371.88	1.753	22.79	131.9	0.929	0.51	20.0
25437.78	1.738	22.79	132.0	0.929	0.51	20.0
25503.68	1.736	22.81	132.1	0.929	0.51	20.0
25569.58	1.737	22.81	132.2	0.929	0.52	20.0
25635.48	1.730	22.82	132.3	0.930	0.52	20.1
25701.38	1.722	22.83	132.4	0.930	0.52	20.1
25767.28	1.709	22.84	132.6	0.930	0.52	20.1
25833.18	1.718	22.82	132.7	0.930	0.52	20.1
25899.08	1.710	22.84	132.8	0.930	0.52	20.1
25964.98	1.699	22.84	132.9	0.931	0.52	20.2

26030.88	1.712	22.84	133.0	0.930	0.52	20.2
26096.78	1.676	22.88	133.1	0.932	0.53	20.2
26162.68	1.704	22.83	133.2	0.931	0.53	20.2
26228.58	1.672	22.88	133.3	0.932	0.53	20.2
26294.48	1.693	22.86	133.4	0.931	0.53	20.2
26360.38	1.659	22.90	133.6	0.932	0.53	20.3
26426.28	1.683	22.87	133.7	0.931	0.53	20.3
26492.18	1.653	22.90	133.8	0.933	0.53	20.3
26558.08	1.680	22.89	133.9	0.932	0.54	20.3
26623.98	1.637	22.92	134.0	0.933	0.54	20.3
26689.88	1.670	22.89	134.1	0.932	0.54	20.3
26755.79	1.634	22.93	134.2	0.933	0.54	20.4
26821.69	1.659	22.89	134.3	0.932	0.54	20.4
26887.59	1.632	22.93	134.4	0.934	0.54	20.4
26953.49	1.640	22.93	134.5	0.933	0.54	20.4
27019.39	1.629	22.95	134.6	0.934	0.54	20.4
27085.29	1.647	22.92	134.8	0.933	0.55	20.4
27151.19	1.614	22.96	134.9	0.934	0.55	20.5
27217.09	1.627	22.93	135.0	0.934	0.55	20.5
27282.99	1.608	22.98	135.1	0.935	0.55	20.5
27348.89	1.605	22.97	135.2	0.935	0.55	20.5
27414.79	1.614	22.94	135.3	0.934	0.55	20.5
27480.69	1.596	22.98	135.4	0.935	0.55	20.5
27546.59	1.608	22.96	135.5	0.935	0.56	20.5
27612.49	1.597	22.98	135.6	0.935	0.56	20.6
27678.39	1.595	22.98	135.7	0.935	0.56	20.6
27744.29	1.581	23.00	135.8	0.936	0.56	20.6
27810.19	1.585	23.00	135.9	0.936	0.56	20.6
27876.09	1.576	22.99	136.0	0.936	0.56	20.6
27941.99	1.578	22.99	136.1	0.936	0.56	20.6
28007.89	1.575	23.01	136.2	0.936	0.56	20.7
28073.79	1.557	23.02	136.3	0.937	0.57	20.7
28139.69	1.564	23.00	136.4	0.936	0.57	20.7
28205.59	1.556	23.04	136.5	0.937	0.57	20.7
28271.49	1.562	23.02	136.6	0.936	0.57	20.7
28337.39	1.548	23.04	136.7	0.937	0.57	20.7
28403.29	1.540	23.05	136.8	0.937	0.57	20.8
28469.20	1.544	23.04	136.9	0.937	0.57	20.8
28535.10	1.530	23.06	137.0	0.938	0.58	20.8
28601.00	1.534	23.05	137.1	0.938	0.58	20.8
28666.90	1.523	23.08	137.2	0.938	0.58	20.8
28732.80	1.534	23.07	137.3	0.938	0.58	20.8
28798.70	1.516	23.07	137.4	0.938	0.58	20.8
28864.60	1.523	23.07	137.5	0.938	0.58	20.9
28930.50	1.508	23.09	137.6	0.939	0.58	20.9
28996.40	1.518	23.07	137.7	0.938	0.58	20.9
29062.30	1.498	23.10	137.8	0.939	0.59	20.9
29128.20	1.522	23.09	137.9	0.938	0.59	20.9
29194.10	1.491	23.10	138.0	0.939	0.59	20.9
29260.00	1.504	23.09	138.1	0.939	0.59	20.9
29325.90	1.489	23.12	138.2	0.939	0.59	21.0
29391.80	1.493	23.11	138.3	0.939	0.59	21.0
29457.70	1.479	23.13	138.4	0.940	0.59	21.0
29523.60	1.489	23.13	138.5	0.940	0.60	21.0

29589.50	1.468	23.14	138.6	0.940	0.60	21.0
29655.40	1.491	23.12	138.7	0.939	0.60	21.0
29721.30	1.457	23.16	138.8	0.941	0.60	21.1
29787.20	1.479	23.12	138.9	0.940	0.60	21.1
29853.10	1.458	23.15	139.0	0.941	0.60	21.1
29919.00	1.466	23.15	139.1	0.940	0.60	21.1
29984.90	1.450	23.16	139.2	0.941	0.60	21.1
30050.80	1.450	23.16	139.3	0.941	0.61	21.1
30116.71	1.442	23.18	139.4	0.941	0.61	21.1
30182.61	1.437	23.17	139.5	0.942	0.61	21.2
30248.51	1.441	23.17	139.6	0.941	0.61	21.2
30314.41	1.422	23.18	139.7	0.942	0.61	21.2
30380.31	1.433	23.18	139.8	0.942	0.61	21.2
30446.21	1.422	23.20	139.9	0.942	0.61	21.2
30512.11	1.426	23.19	140.0	0.942	0.61	21.2
30578.01	1.414	23.21	140.1	0.943	0.62	21.2
30643.91	1.410	23.20	140.2	0.943	0.62	21.3
30709.81	1.411	23.20	140.2	0.943	0.62	21.3
30775.71	1.411	23.20	140.3	0.943	0.62	21.3
30841.61	1.401	23.22	140.4	0.943	0.62	21.3
30907.51	1.397	23.22	140.5	0.943	0.62	21.3
30973.41	1.400	23.22	140.6	0.943	0.62	21.3
31039.31	1.385	23.24	140.7	0.944	0.63	21.3
31105.21	1.398	23.24	140.8	0.943	0.63	21.4
31171.11	1.381	23.24	140.9	0.944	0.63	21.4
31237.01	1.387	23.23	141.0	0.944	0.63	21.4
31302.91	1.379	23.25	141.1	0.944	0.63	21.4
31368.81	1.377	23.27	141.2	0.944	0.63	21.4
31434.71	1.387	23.24	141.3	0.944	0.63	21.4
31500.61	1.361	23.26	141.3	0.945	0.63	21.4
31566.51	1.369	23.24	141.4	0.944	0.64	21.4
31632.41	1.364	23.28	141.5	0.945	0.64	21.5
31698.31	1.360	23.26	141.6	0.945	0.64	21.5
31764.21	1.357	23.26	141.7	0.945	0.64	21.5
31830.12	1.347	23.29	141.8	0.945	0.64	21.5
31896.02	1.359	23.27	141.9	0.945	0.64	21.5
31961.92	1.335	23.29	142.0	0.946	0.64	21.5
32027.82	1.346	23.27	142.1	0.945	0.65	21.5
32093.72	1.330	23.30	142.1	0.946	0.65	21.6
32159.62	1.336	23.30	142.2	0.946	0.65	21.6
32225.52	1.330	23.30	142.3	0.946	0.65	21.6
32291.42	1.335	23.30	142.4	0.946	0.65	21.6
32357.32	1.318	23.33	142.5	0.947	0.65	21.6
32423.22	1.327	23.33	142.6	0.946	0.65	21.6
32489.12	1.320	23.31	142.7	0.946	0.65	21.6
32555.02	1.312	23.34	142.8	0.947	0.66	21.7
32620.92	1.313	23.33	142.8	0.947	0.66	21.7
32686.82	1.307	23.32	142.9	0.947	0.66	21.7
32752.72	1.316	23.33	143.0	0.947	0.66	21.7
32818.62	1.301	23.34	143.1	0.947	0.66	21.7
32884.52	1.296	23.34	143.2	0.947	0.66	21.7
32950.43	1.299	23.35	143.3	0.947	0.66	21.7
33016.33	1.302	23.36	143.4	0.947	0.67	21.7
33082.23	1.287	23.36	143.4	0.948	0.67	21.8

33148.13	1.295	23.36	143.5	0.947	0.67	21.8
33214.04	1.280	23.36	143.6	0.948	0.67	21.8
33279.94	1.281	23.38	143.7	0.948	0.67	21.8
33345.84	1.275	23.38	143.8	0.948	0.67	21.8
33411.74	1.281	23.38	143.9	0.948	0.67	21.8
33477.64	1.264	23.38	144.0	0.949	0.67	21.8
33543.55	1.280	23.38	144.0	0.948	0.68	21.8
33609.45	1.262	23.41	144.1	0.949	0.68	21.9
33675.35	1.284	23.38	144.2	0.948	0.68	21.9
33741.25	1.251	23.41	144.3	0.949	0.68	21.9
33807.16	1.278	23.39	144.4	0.948	0.68	21.9
33873.06	1.250	23.40	144.5	0.949	0.68	21.9
33938.96	1.274	23.39	144.5	0.948	0.68	21.9
34004.86	1.246	23.43	144.6	0.949	0.69	21.9
34070.77	1.254	23.42	144.7	0.949	0.69	21.9
34136.67	1.241	23.44	144.8	0.950	0.69	22.0
34202.57	1.243	23.42	144.9	0.950	0.69	22.0
34268.47	1.244	23.43	144.9	0.950	0.69	22.0
34334.38	1.241	23.45	145.0	0.950	0.69	22.0
34400.28	1.238	23.44	145.1	0.950	0.69	22.0
34466.18	1.236	23.43	145.2	0.950	0.69	22.0
34532.08	1.233	23.44	145.3	0.950	0.70	22.0

PERFORMANCE VERSUS TIME FOR INFILL
=====

TIME DAYS	OIL RATE STB/D	WATER RATE STB/D	CUMOIL MSTB	WCUT FRAC.	PV INJ FRAC.	OIL REC %OOIP
6392.42	2.731	25.80	73.89	0.904	0.13	
6425.37	15.66	30.40	74.40	0.660	0.13	11.3
6458.32	15.36	30.40	74.91	0.664	0.13	11.4
6491.27	15.33	30.40	75.41	0.665	0.13	11.4
6524.22	14.96	30.82	75.91	0.673	0.13	11.5
6557.17	14.97	30.81	76.40	0.673	0.14	11.6
6590.12	14.94	30.84	76.89	0.674	0.14	11.7
6623.07	15.05	30.69	77.39	0.671	0.14	11.7
6656.02	14.77	31.10	77.87	0.678	0.14	11.8
6688.97	15.09	30.66	78.37	0.670	0.14	11.9
6721.92	14.68	31.18	78.85	0.680	0.14	12.0
6754.88	15.02	30.77	79.35	0.672	0.14	12.0
6787.83	15.03	30.75	79.85	0.672	0.14	12.1
6820.78	14.85	30.99	80.33	0.676	0.15	12.2
6853.73	15.27	30.43	80.84	0.666	0.15	12.3
6886.68	14.65	31.24	81.32	0.681	0.15	12.3
6919.63	14.13	31.91	81.79	0.693	0.15	12.4
6952.58	13.90	32.22	82.24	0.699	0.15	12.5
6985.53	13.70	32.45	82.70	0.703	0.15	12.5
7018.48	13.51	32.70	83.14	0.708	0.15	12.5
7051.43	13.32	32.96	83.58	0.712	0.16	12.6
7084.38	13.11	33.22	84.01	0.717	0.16	12.7
7117.33	12.93	33.45	84.44	0.721	0.16	12.8
7150.28	12.76	33.67	84.86	0.725	0.16	12.9

7183.23	12.61	33.87	85.27	0.729	0.16	12.9
7216.18	12.45	34.06	85.68	0.732	0.16	13.0
7249.14	12.32	34.24	86.09	0.735	0.16	13.1
7282.09	12.18	34.41	86.49	0.739	0.16	13.1
7315.04	12.05	34.58	86.89	0.742	0.17	13.2
7347.99	11.96	34.73	87.28	0.744	0.17	13.2
7380.94	11.82	34.88	87.67	0.747	0.17	13.3
7413.89	11.71	35.02	88.06	0.749	0.17	13.4
7446.84	11.59	35.17	88.44	0.752	0.17	13.4
7479.79	11.48	35.30	88.82	0.755	0.17	13.5
7512.74	11.37	35.45	89.19	0.757	0.17	13.5
7545.69	11.26	35.59	89.56	0.760	0.18	13.6
7578.64	11.17	35.72	89.93	0.762	0.18	13.6
7611.59	11.05	35.84	90.30	0.764	0.18	13.7
7644.54	10.96	35.97	90.66	0.767	0.18	13.7
7677.49	10.85	36.11	91.01	0.769	0.18	13.8
7710.44	10.77	36.22	91.37	0.771	0.18	13.8
7743.40	10.67	36.36	91.72	0.773	0.18	13.9
7776.35	10.58	36.45	92.07	0.775	0.18	14.0
7809.30	10.49	36.57	92.41	0.777	0.19	14.0
7842.25	10.40	36.69	92.76	0.779	0.19	14.1
7875.20	10.33	36.78	93.10	0.781	0.19	14.1
7908.15	10.23	36.90	93.43	0.783	0.19	14.2
7941.10	10.17	37.00	93.77	0.784	0.19	14.2
7974.05	10.09	37.10	94.10	0.786	0.19	14.3
8007.00	10.00	37.20	94.43	0.788	0.19	14.3
8039.95	9.943	37.28	94.76	0.789	0.20	14.4
8072.90	9.860	37.39	95.08	0.791	0.20	14.4
8105.85	9.790	37.48	95.41	0.793	0.20	14.5
8138.80	9.719	37.56	95.73	0.794	0.20	14.5
8171.75	9.657	37.65	96.05	0.796	0.20	14.6
8204.71	9.585	37.74	96.36	0.797	0.20	14.6
8237.66	9.511	37.83	96.67	0.799	0.20	14.7
8270.61	9.460	37.90	96.99	0.800	0.20	14.7
8303.56	9.388	37.99	97.30	0.802	0.21	14.8
8336.51	9.329	38.06	97.60	0.803	0.21	14.8
8369.46	9.264	38.14	97.91	0.805	0.21	14.8
8402.41	9.198	38.22	98.21	0.806	0.21	14.9
8435.36	9.143	38.29	98.51	0.807	0.21	14.9
8468.31	9.090	38.37	98.81	0.808	0.21	15.0
8501.26	9.034	38.43	99.11	0.810	0.21	15.0
8534.21	8.974	38.51	99.41	0.811	0.22	15.1
8567.16	8.920	38.57	99.70	0.812	0.22	15.1
8600.11	8.868	38.63	99.99	0.813	0.22	15.2
8633.06	8.821	38.71	100.3	0.814	0.22	15.2
8666.01	8.766	38.77	100.6	0.816	0.22	15.3
8698.96	8.728	38.83	100.9	0.816	0.22	15.3
8731.91	8.665	38.90	101.1	0.818	0.22	15.3
8764.86	8.631	38.94	101.4	0.819	0.22	15.4
8797.81	8.559	39.04	101.7	0.820	0.23	15.4
8830.76	8.539	39.06	102.0	0.821	0.23	15.5
8863.71	8.480	39.14	102.3	0.822	0.23	15.5
8896.66	8.443	39.19	102.5	0.823	0.23	15.6
8929.61	8.398	39.26	102.8	0.824	0.23	15.6

8962.56	8.352	39.30	103.1	0.825	0.23	15.6
8995.51	8.310	39.36	103.4	0.826	0.23	15.7
9028.46	8.267	39.42	103.6	0.827	0.24	15.7
9061.41	8.225	39.46	103.9	0.828	0.24	15.8
9094.36	8.183	39.54	104.2	0.829	0.24	15.8
9127.31	8.154	39.56	104.5	0.829	0.24	15.8
9160.26	8.095	39.64	104.7	0.830	0.24	15.9
9193.21	8.075	39.67	105.0	0.831	0.24	15.9
9226.16	8.026	39.73	105.3	0.832	0.24	16.0
9259.11	7.993	39.77	105.5	0.833	0.24	16.0
9292.06	7.968	39.82	105.8	0.833	0.25	16.0
9325.01	7.916	39.87	106.0	0.834	0.25	16.1
9357.96	7.874	39.90	106.3	0.835	0.25	16.1
9390.91	7.841	39.96	106.6	0.836	0.25	16.2
9423.86	7.821	39.99	106.8	0.836	0.25	16.2
9456.81	7.765	40.05	107.1	0.838	0.25	16.2
9489.76	7.750	40.09	107.3	0.838	0.25	16.3
9522.71	7.705	40.12	107.6	0.839	0.26	16.3
9555.66	7.680	40.17	107.8	0.839	0.26	16.4
9588.61	7.641	40.21	108.1	0.840	0.26	16.4
9621.56	7.607	40.25	108.3	0.841	0.26	16.4
9654.51	7.569	40.32	108.6	0.842	0.26	16.5
9687.46	7.565	40.31	108.8	0.842	0.26	16.5
9720.41	7.499	40.39	109.1	0.843	0.26	16.5
9753.36	7.499	40.40	109.3	0.843	0.26	16.6
9786.31	7.442	40.48	109.6	0.845	0.27	16.6
9819.26	7.440	40.48	109.8	0.845	0.27	16.7
9852.21	7.385	40.55	110.1	0.846	0.27	16.7
9885.17	7.359	40.56	110.3	0.846	0.27	16.7
9918.12	7.333	40.60	110.5	0.847	0.27	16.8
9951.07	7.299	40.64	110.8	0.848	0.27	16.8
9984.02	7.276	40.67	111.0	0.848	0.27	16.8
10016.97	7.244	40.71	111.3	0.849	0.27	16.9
10049.92	7.223	40.75	111.5	0.849	0.28	16.9
10082.87	7.180	40.80	111.7	0.850	0.28	16.9
10115.82	7.178	40.82	112.0	0.850	0.28	17.0
10148.77	7.131	40.87	112.2	0.851	0.28	17.0
10181.72	7.123	40.90	112.4	0.852	0.28	17.1
10214.67	7.090	40.93	112.7	0.852	0.28	17.1
10247.62	7.055	40.97	112.9	0.853	0.28	17.1
10280.57	7.039	40.98	113.1	0.853	0.29	17.2
10313.52	7.007	41.03	113.4	0.854	0.29	17.2
10346.47	6.988	41.06	113.6	0.855	0.29	17.2
10379.42	6.962	41.07	113.8	0.855	0.29	17.3
10412.37	6.935	41.12	114.1	0.856	0.29	17.3
10445.32	6.914	41.15	114.3	0.856	0.29	17.3
10478.27	6.895	41.19	114.5	0.857	0.29	17.4
10511.22	6.865	41.22	114.7	0.857	0.29	17.4
10544.17	6.850	41.25	115.0	0.858	0.30	17.4
10577.12	6.823	41.27	115.2	0.858	0.30	17.5
10610.07	6.787	41.32	115.4	0.859	0.30	17.5
10643.02	6.769	41.33	115.6	0.859	0.30	17.5
10675.97	6.743	41.38	115.9	0.860	0.30	17.6
10708.92	6.727	41.39	116.1	0.860	0.30	17.6

10741.87	41.43	116.3	0.861	0.30	17.6
10774.82	41.44	116.5	0.861	0.31	17.7
10807.77	41.48	116.7	0.862	0.31	17.7
10840.72	41.50	117.0	0.862	0.31	17.7
10873.67	41.56	117.2	0.863	0.31	17.8
10906.62	41.55	117.4	0.863	0.31	17.8
10939.57	41.60	117.6	0.864	0.31	17.8
10972.52	41.61	117.8	0.864	0.31	17.9
11005.47	41.65	118.0	0.864	0.31	17.9
11038.42	41.67	118.3	0.865	0.32	17.9
11071.37	41.71	118.5	0.865	0.32	18.0
11104.32	41.72	118.7	0.866	0.32	18.0
11137.27	41.74	118.9	0.866	0.32	18.0
11170.22	41.77	119.1	0.867	0.32	18.1
11203.17	41.80	119.3	0.867	0.32	18.1
11236.12	41.83	119.5	0.868	0.32	18.1
11269.07	41.86	119.7	0.868	0.33	18.2
11302.02	41.88	120.0	0.868	0.33	18.2
11334.97	41.91	120.2	0.869	0.33	18.2
11367.92	41.93	120.4	0.869	0.33	18.3
11400.87	41.95	120.6	0.870	0.33	18.3
11433.82	41.99	120.8	0.870	0.33	18.3
11466.77	42.00	121.0	0.871	0.33	18.3
11499.72	42.04	121.2	0.871	0.33	18.4
11532.67	42.05	121.4	0.871	0.34	18.4
11565.63	42.09	121.6	0.872	0.34	18.4
11598.58	42.11	121.8	0.872	0.34	18.5
11631.53	42.12	122.0	0.873	0.34	18.5
11664.48	42.16	122.2	0.873	0.34	18.5
11697.43	42.16	122.4	0.873	0.34	18.6
11730.38	42.20	122.6	0.874	0.34	18.6
11763.33	42.22	122.8	0.874	0.35	18.6
11796.28	42.24	123.0	0.874	0.35	18.7
11829.23	42.27	123.2	0.875	0.35	18.7
11862.18	42.29	123.4	0.875	0.35	18.7
11895.13	42.30	123.6	0.876	0.35	18.7
11928.08	42.33	123.8	0.876	0.35	18.8
11961.03	42.35	124.0	0.876	0.35	18.8
11993.98	42.36	124.2	0.877	0.35	18.8
12026.93	42.41	124.4	0.877	0.36	18.9
12059.88	42.42	124.6	0.878	0.36	18.9
12092.83	42.44	124.8	0.878	0.36	18.9
12125.78	42.47	125.0	0.878	0.36	19.0
12158.73	42.48	125.2	0.879	0.36	19.0
12191.68	42.50	125.4	0.879	0.36	19.0
12224.63	42.54	125.6	0.879	0.36	19.0
12257.58	42.54	125.7	0.880	0.37	19.1
12290.53	42.57	125.9	0.880	0.37	19.1
12323.48	42.59	126.1	0.880	0.37	19.1
12356.43	42.61	126.3	0.881	0.37	19.2
12389.38	42.63	126.5	0.881	0.37	19.2
12422.33	42.65	126.7	0.881	0.37	19.2
12455.28	42.66	126.9	0.882	0.37	19.2
12488.23	42.70	127.1	0.882	0.37	19.3

12521.18	5.696	42.71	127.3	0.882	0.38	19.3
12554.13	5.681	42.73	127.5	0.883	0.38	19.3
12587.08	5.664	42.75	127.6	0.883	0.38	19.4
12620.03	5.661	42.77	127.8	0.883	0.38	19.4
12652.98	5.630	42.81	128.0	0.884	0.38	19.4
12685.93	5.626	42.80	128.2	0.884	0.38	19.4
12718.88	5.603	42.83	128.4	0.884	0.38	19.5
12751.83	5.585	42.85	128.6	0.885	0.39	19.5
12784.78	5.572	42.88	128.7	0.885	0.39	19.5
12817.73	5.556	42.89	128.9	0.885	0.39	19.6
12850.68	5.557	42.91	129.1	0.885	0.39	19.6
12883.63	5.529	42.92	129.3	0.886	0.39	19.6
12916.58	5.522	42.94	129.5	0.886	0.39	19.6
12949.53	5.502	42.96	129.7	0.886	0.39	19.7
12982.48	5.488	42.99	129.8	0.887	0.39	19.7
13015.43	5.479	42.99	130.0	0.887	0.40	19.7
13048.38	5.463	43.01	130.2	0.887	0.40	19.7
13081.33	5.450	43.02	130.4	0.888	0.40	19.8
13114.28	5.428	43.04	130.6	0.888	0.40	19.8
13147.23	5.410	43.06	130.7	0.888	0.40	19.8
13180.18	5.397	43.08	130.9	0.889	0.40	19.9
13213.13	5.380	43.10	131.1	0.889	0.40	19.9
13246.08	5.373	43.11	131.3	0.889	0.41	19.9
13279.04	5.359	43.14	131.4	0.889	0.41	19.9
13311.99	5.353	43.16	131.6	0.890	0.41	20.0
13344.94	5.328	43.18	131.8	0.890	0.41	20.0
13377.89	5.328	43.17	132.0	0.890	0.41	20.0
13410.84	5.305	43.21	132.1	0.891	0.41	20.0
13443.79	5.289	43.22	132.3	0.891	0.41	20.1
13476.74	5.289	43.23	132.5	0.891	0.41	20.1
13509.69	5.271	43.25	132.7	0.891	0.42	20.1
13542.64	5.264	43.26	132.8	0.892	0.42	20.1
13575.59	5.232	43.30	133.0	0.892	0.42	20.2
13608.54	5.235	43.30	133.2	0.892	0.42	20.2
13641.49	5.207	43.34	133.4	0.893	0.42	20.2
13674.44	5.218	43.32	133.5	0.892	0.42	20.2
13707.39	5.184	43.36	133.7	0.893	0.42	20.3
13740.34	5.190	43.36	133.9	0.893	0.43	20.3
13773.29	5.155	43.40	134.0	0.894	0.43	20.3
13806.24	5.165	43.41	134.2	0.894	0.43	20.4
13839.19	5.139	43.42	134.4	0.894	0.43	20.4
13872.14	5.125	43.43	134.6	0.894	0.43	20.4
13905.09	5.109	43.46	134.7	0.895	0.43	20.4
13938.04	5.101	43.47	134.9	0.895	0.43	20.5
13970.99	5.091	43.49	135.1	0.895	0.43	20.5
14003.94	5.072	43.50	135.2	0.896	0.44	20.5
14036.89	5.072	43.52	135.4	0.896	0.44	20.5
14069.84	5.054	43.54	135.6	0.896	0.44	20.6
14102.79	5.037	43.55	135.7	0.896	0.44	20.6
14135.74	5.030	43.57	135.9	0.897	0.44	20.6
14168.69	5.023	43.57	136.1	0.897	0.44	20.6
14201.64	5.001	43.61	136.2	0.897	0.44	20.7
14234.59	5.005	43.60	136.4	0.897	0.44	20.7
14267.54	4.969	43.65	136.5	0.898	0.45	20.7

14300.49	4.979	43.63	136.7	0.898	0.45	20.7
14333.44	4.956	43.66	136.9	0.898	0.45	20.8
14366.39	4.945	43.67	137.0	0.898	0.45	20.8
14399.34	4.933	43.69	137.2	0.899	0.45	20.8
14432.29	4.924	43.69	137.4	0.899	0.45	20.8
14465.24	4.919	43.72	137.5	0.899	0.45	20.9
14498.19	4.897	43.73	137.7	0.899	0.46	20.9
14531.14	4.889	43.75	137.8	0.899	0.46	20.9
14564.09	4.873	43.76	138.0	0.900	0.46	20.9
14597.04	4.870	43.79	138.2	0.900	0.46	21.0
14629.99	4.861	43.78	138.3	0.900	0.46	21.0
14662.94	4.842	43.81	138.5	0.900	0.46	21.0
14695.89	4.830	43.82	138.6	0.901	0.46	21.0
14728.84	4.817	43.83	138.8	0.901	0.46	21.0
14761.79	4.812	43.85	139.0	0.901	0.47	21.1
14794.74	4.794	43.86	139.1	0.901	0.47	21.1
14827.69	4.777	43.86	139.3	0.902	0.47	21.1
14860.64	4.778	43.89	139.4	0.902	0.47	21.1
14893.59	4.771	43.90	139.6	0.902	0.47	21.2
14926.54	4.764	43.91	139.8	0.902	0.47	21.2
14959.50	4.744	43.92	139.9	0.903	0.47	21.2
14992.45	4.745	43.93	140.1	0.903	0.48	21.2
15025.40	4.728	43.96	140.2	0.903	0.48	21.3
15058.35	4.719	43.97	140.4	0.903	0.48	21.3
15091.30	4.705	43.99	140.5	0.903	0.48	21.3
15124.25	4.701	44.01	140.7	0.903	0.48	21.3
15157.20	4.683	44.02	140.8	0.904	0.48	21.4
15190.15	4.688	44.00	141.0	0.904	0.48	21.4
15223.10	4.653	44.04	141.1	0.904	0.48	21.4
15256.05	4.661	44.03	141.3	0.904	0.49	21.4
15289.00	4.629	44.08	141.5	0.905	0.49	21.5
15321.95	4.639	44.06	141.6	0.905	0.49	21.5
15354.90	4.610	44.10	141.8	0.905	0.49	21.5
15387.85	4.613	44.08	141.9	0.905	0.49	21.5
15420.80	4.589	44.11	142.1	0.906	0.49	21.5
15453.75	4.596	44.11	142.2	0.906	0.49	21.6
15486.70	4.577	44.13	142.4	0.906	0.50	21.6
15519.65	4.568	44.15	142.5	0.906	0.50	21.6
15552.60	4.557	44.17	142.7	0.906	0.50	21.6
15585.55	4.541	44.20	142.8	0.907	0.50	21.7
15618.50	4.546	44.18	143.0	0.907	0.50	21.7
15651.45	4.530	44.21	143.1	0.907	0.50	21.7
15684.40	4.518	44.21	143.3	0.907	0.50	21.7
15717.35	4.515	44.21	143.4	0.907	0.50	21.7
15750.30	4.494	44.23	143.6	0.908	0.51	21.8
15783.25	4.491	44.24	143.7	0.908	0.51	21.8
15816.20	4.477	44.25	143.9	0.908	0.51	21.8
15849.15	4.465	44.27	144.0	0.908	0.51	21.8
15882.10	4.468	44.28	144.1	0.908	0.51	21.9
15915.05	4.442	44.32	144.3	0.909	0.51	21.9
15948.00	4.441	44.31	144.4	0.909	0.51	21.9
15980.95	4.421	44.34	144.6	0.909	0.52	21.9
16013.90	4.433	44.34	144.7	0.909	0.52	21.9
16046.85	4.416	44.36	144.9	0.909	0.52	22.0

16079.80	4.405	44.37	145.0	0.910	0.52	22.0
16112.75	4.398	44.38	145.2	0.910	0.52	22.0
16145.70	4.385	44.41	145.3	0.910	0.52	22.0
16178.65	4.383	44.41	145.5	0.910	0.52	22.1
16211.60	4.355	44.44	145.6	0.911	0.52	22.1
16244.55	4.373	44.43	145.7	0.910	0.53	22.1
16277.50	4.332	44.48	145.9	0.911	0.53	22.1
16310.45	4.360	44.44	146.0	0.911	0.53	22.1
16343.40	4.308	44.48	146.2	0.912	0.53	22.2
16376.35	4.327	44.48	146.3	0.911	0.53	22.2
16409.30	4.300	44.49	146.5	0.912	0.53	22.2
16442.26	4.310	44.49	146.6	0.912	0.53	22.2
16475.21	4.284	44.54	146.7	0.912	0.54	22.3
16508.16	4.294	44.53	146.9	0.912	0.54	22.3
16541.11	4.260	44.54	147.0	0.913	0.54	22.3
16574.06	4.271	44.53	147.2	0.912	0.54	22.3
16607.01	4.244	44.58	147.3	0.913	0.54	22.3
16639.96	4.268	44.56	147.4	0.913	0.54	22.4
16672.91	4.220	44.61	147.6	0.914	0.54	22.4
16705.87	4.249	44.58	147.7	0.913	0.54	22.4
16738.82	4.208	44.63	147.9	0.914	0.55	22.4
16771.77	4.226	44.60	148.0	0.913	0.55	22.4
16804.72	4.196	44.65	148.1	0.914	0.55	22.5
16837.67	4.214	44.62	148.3	0.914	0.55	22.5
16870.62	4.169	44.66	148.4	0.915	0.55	22.5
16903.57	4.182	44.66	148.6	0.914	0.55	22.5
16936.52	4.155	44.69	148.7	0.915	0.55	22.5
16969.47	4.176	44.66	148.8	0.914	0.56	22.6
17002.43	4.144	44.71	149.0	0.915	0.56	22.6
17035.38	4.158	44.69	149.1	0.915	0.56	22.6
17068.33	4.117	44.73	149.2	0.916	0.56	22.6
17101.28	4.141	44.73	149.4	0.915	0.56	22.7
17134.23	4.110	44.74	149.5	0.916	0.56	22.7
17167.18	4.117	44.75	149.6	0.916	0.56	22.7
17200.13	4.095	44.78	149.8	0.916	0.56	22.7
17233.08	4.101	44.76	149.9	0.916	0.57	22.7
17266.04	4.083	44.79	150.0	0.916	0.57	22.8
17298.99	4.080	44.79	150.2	0.917	0.57	22.8
17331.94	4.067	44.81	150.3	0.917	0.57	22.8
17364.89	4.065	44.82	150.5	0.917	0.57	22.8
17397.84	4.042	44.83	150.6	0.917	0.57	22.8
17430.79	4.044	44.84	150.7	0.917	0.57	22.9
17463.74	4.040	44.84	150.9	0.917	0.58	22.9
17496.69	4.011	44.87	151.0	0.918	0.58	22.9
17529.64	4.024	44.86	151.1	0.918	0.58	22.9
17562.60	4.004	44.88	151.2	0.918	0.58	22.9
17595.55	4.003	44.89	151.4	0.918	0.58	23.0
17628.50	3.983	44.91	151.5	0.919	0.58	23.0
17661.45	3.988	44.92	151.6	0.918	0.58	23.0
17694.40	3.973	44.93	151.8	0.919	0.58	23.0
17727.35	3.964	44.93	151.9	0.919	0.59	23.0
17760.30	3.958	44.94	152.0	0.919	0.59	23.1
17793.25	3.945	44.95	152.2	0.919	0.59	23.1
17826.21	3.936	44.98	152.3	0.920	0.59	23.1

17859.16	3.934	44.97	152.4	0.920	0.59	23.1
17892.11	3.924	44.99	152.6	0.920	0.59	23.1
17925.06	3.917	45.01	152.7	0.920	0.59	23.2
17958.01	3.917	45.00	152.8	0.920	0.60	23.2
17990.96	3.896	45.02	152.9	0.920	0.60	23.2
18023.91	3.891	45.03	153.1	0.920	0.60	23.2
18056.86	3.876	45.06	153.2	0.921	0.60	23.2
18089.81	3.884	45.05	153.3	0.921	0.60	23.3
18122.77	3.853	45.09	153.5	0.921	0.60	23.3
18155.72	3.865	45.07	153.6	0.921	0.60	23.3
18188.67	3.850	45.09	153.7	0.921	0.60	23.3
18221.62	3.841	45.09	153.8	0.921	0.61	23.3
18254.57	3.829	45.11	154.0	0.922	0.61	23.3
18287.52	3.829	45.11	154.1	0.922	0.61	23.4
18320.47	3.824	45.13	154.2	0.922	0.61	23.4
18353.42	3.811	45.14	154.3	0.922	0.61	23.4
18386.38	3.801	45.15	154.5	0.922	0.61	23.4
18419.33	3.783	45.16	154.6	0.923	0.61	23.4
18452.28	3.793	45.15	154.7	0.922	0.61	23.5
18485.23	3.765	45.18	154.8	0.923	0.62	23.5
18518.18	3.779	45.17	155.0	0.923	0.62	23.5
18551.13	3.764	45.19	155.1	0.923	0.62	23.5
18584.08	3.750	45.21	155.2	0.923	0.62	23.5
18617.03	3.757	45.20	155.3	0.923	0.62	23.6
18649.98	3.740	45.24	155.5	0.924	0.62	23.6
18682.94	3.727	45.23	155.6	0.924	0.62	23.6
18715.89	3.730	45.25	155.7	0.924	0.63	23.6
18748.84	3.715	45.27	155.8	0.924	0.63	23.6
18781.79	3.723	45.26	155.9	0.924	0.63	23.6
18814.74	3.704	45.29	156.1	0.924	0.63	23.7
18847.69	3.694	45.29	156.2	0.925	0.63	23.7
18880.64	3.691	45.29	156.3	0.925	0.63	23.7
18913.59	3.672	45.29	156.4	0.925	0.63	23.7
18946.54	3.670	45.32	156.6	0.925	0.63	23.7
18979.50	3.673	45.33	156.7	0.925	0.64	23.8
19012.45	3.672	45.33	156.8	0.925	0.64	23.8
19045.40	3.644	45.36	156.9	0.926	0.64	23.8
19078.35	3.656	45.34	157.0	0.925	0.64	23.8
19111.30	3.639	45.35	157.2	0.926	0.64	23.8
19144.25	3.628	45.38	157.3	0.926	0.64	23.8
19177.20	3.640	45.38	157.4	0.926	0.64	23.9
19210.15	3.609	45.40	157.5	0.926	0.65	23.9
19243.11	3.617	45.40	157.6	0.926	0.65	23.9
19276.06	3.604	45.40	157.8	0.926	0.65	23.9
19309.01	3.597	45.42	157.9	0.927	0.65	23.9
19341.96	3.580	45.44	158.0	0.927	0.65	24.0
19374.91	3.594	45.43	158.1	0.927	0.65	24.0
19407.86	3.578	45.44	158.2	0.927	0.65	24.0
19440.81	3.565	45.46	158.3	0.927	0.65	24.0
19473.76	3.560	45.47	158.5	0.927	0.66	24.0
19506.71	3.549	45.48	158.6	0.928	0.66	24.0
19539.67	3.547	45.47	158.7	0.928	0.66	24.1
19572.62	3.545	45.49	158.8	0.928	0.66	24.1
19605.57	3.526	45.50	158.9	0.928	0.66	24.1

19638.52	3.533	45.50	159.0	0.928	0.66	24.1
19671.47	3.499	45.53	159.2	0.929	0.66	24.1
19704.42	3.520	45.50	159.3	0.928	0.67	24.2
19737.37	3.495	45.55	159.4	0.929	0.67	24.2
19770.32	3.509	45.53	159.5	0.928	0.67	24.2
19803.28	3.483	45.56	159.6	0.929	0.67	24.2
19836.23	3.494	45.55	159.7	0.929	0.67	24.2
19869.18	3.480	45.56	159.8	0.929	0.67	24.2
19902.13	3.478	45.56	160.0	0.929	0.67	24.3
19935.08	3.463	45.59	160.1	0.929	0.67	24.3
19968.03	3.464	45.59	160.2	0.929	0.68	24.3
20000.98	3.450	45.59	160.3	0.930	0.68	24.3
20033.93	3.444	45.60	160.4	0.930	0.68	24.3
20066.88	3.441	45.62	160.5	0.930	0.68	24.3
20099.84	3.432	45.62	160.6	0.930	0.68	24.4
20132.79	3.417	45.64	160.8	0.930	0.68	24.4
20165.74	3.425	45.64	160.9	0.930	0.68	24.4
20198.69	3.406	45.67	161.0	0.931	0.69	24.4
20231.64	3.415	45.65	161.1	0.930	0.69	24.4
20264.59	3.403	45.66	161.2	0.931	0.69	24.4
20297.54	3.401	45.68	161.3	0.931	0.69	24.5
20330.49	3.386	45.69	161.4	0.931	0.69	24.5
20363.45	3.394	45.68	161.5	0.931	0.69	24.5
20396.40	3.380	45.71	161.7	0.931	0.69	24.5
20429.35	3.381	45.70	161.8	0.931	0.69	24.5
20462.30	3.360	45.72	161.9	0.932	0.70	24.5
20495.25	3.360	45.70	162.0	0.932	0.70	24.6
20528.20	3.342	45.73	162.1	0.932	0.70	24.6
20561.15	3.362	45.72	162.2	0.931	0.70	24.6
20594.10	3.327	45.77	162.3	0.932	0.70	24.6
20627.05	3.345	45.72	162.4	0.932	0.70	24.6
20660.01	3.316	45.78	162.5	0.932	0.70	24.6
20692.96	3.342	45.75	162.6	0.932	0.71	24.7
20725.91	3.303	45.79	162.8	0.933	0.71	24.7
20758.86	3.316	45.77	162.9	0.932	0.71	24.7
20791.81	3.289	45.79	163.0	0.933	0.71	24.7
20824.76	3.305	45.78	163.1	0.933	0.71	24.7
20857.71	3.268	45.82	163.2	0.933	0.71	24.7
20890.66	3.304	45.79	163.3	0.933	0.71	24.8
20923.62	3.266	45.85	163.4	0.933	0.71	24.8
20956.57	3.291	45.82	163.5	0.933	0.72	24.8
20989.52	3.252	45.85	163.6	0.934	0.72	24.8
21022.47	3.284	45.82	163.7	0.933	0.72	24.8
21055.42	3.245	45.86	163.8	0.934	0.72	24.8
21088.37	3.263	45.85	163.9	0.934	0.72	24.9
21121.32	3.231	45.89	164.1	0.934	0.72	24.9
21154.27	3.248	45.86	164.2	0.934	0.72	24.9
21187.22	3.225	45.87	164.3	0.934	0.73	24.9
21220.18	3.225	45.90	164.4	0.934	0.73	24.9
21253.13	3.221	45.89	164.5	0.934	0.73	24.9
21286.08	3.220	45.90	164.6	0.934	0.73	25.0
21319.03	3.202	45.91	164.7	0.935	0.73	25.0
21351.98	3.202	45.92	164.8	0.935	0.73	25.0
21384.93	3.194	45.95	164.9	0.935	0.73	25.0

21417.88	3.204	45.92	165.0	0.935	0.73	25.0
21450.83	3.176	45.97	165.1	0.935	0.74	25.0
21483.79	3.206	45.93	165.2	0.935	0.74	25.1
21516.74	3.156	45.99	165.3	0.936	0.74	25.1
21549.69	3.192	45.94	165.4	0.935	0.74	25.1
21582.64	3.153	45.98	165.5	0.936	0.74	25.1
21615.59	3.166	45.96	165.6	0.936	0.74	25.1
21648.54	3.142	46.00	165.7	0.936	0.74	25.1
21681.49	3.149	45.97	165.8	0.936	0.75	25.1
21714.44	3.126	46.00	165.9	0.936	0.75	25.2
21747.39	3.150	45.98	166.0	0.936	0.75	25.2
21780.35	3.123	46.01	166.1	0.936	0.75	25.2
21813.30	3.136	45.99	166.3	0.936	0.75	25.2
21846.25	3.117	46.03	166.4	0.937	0.75	25.2
21879.20	3.118	46.01	166.5	0.937	0.75	25.2
21912.15	3.114	46.04	166.6	0.937	0.75	25.3
21945.10	3.095	46.06	166.7	0.937	0.76	25.3
21978.05	3.117	46.03	166.8	0.937	0.76	25.3
22011.00	3.077	46.09	166.9	0.937	0.76	25.3
22043.96	3.111	46.05	167.0	0.937	0.76	25.3
22076.91	3.080	46.08	167.1	0.937	0.76	25.3
22109.86	3.089	46.08	167.2	0.937	0.76	25.4
22142.81	3.079	46.09	167.3	0.937	0.76	25.4
22175.76	3.074	46.09	167.4	0.937	0.77	25.4
22208.71	3.071	46.09	167.5	0.938	0.77	25.4
22241.66	3.064	46.11	167.6	0.938	0.77	25.4
22274.61	3.066	46.10	167.7	0.938	0.77	25.4
22307.56	3.051	46.12	167.8	0.938	0.77	25.4
22340.52	3.058	46.11	167.9	0.938	0.77	25.5
22373.47	3.035	46.14	168.0	0.938	0.77	25.5
22406.42	3.045	46.12	168.1	0.938	0.77	25.5
22439.37	3.020	46.16	168.2	0.939	0.78	25.5
22472.32	3.032	46.14	168.3	0.938	0.78	25.5
22505.27	3.031	46.15	168.4	0.938	0.78	25.5
22538.22	3.007	46.17	168.5	0.939	0.78	25.5
22571.17	3.024	46.15	168.6	0.938	0.78	25.6
22604.13	3.002	46.18	168.7	0.939	0.78	25.6
22637.08	3.012	46.16	168.8	0.939	0.78	25.6
22670.03	2.984	46.21	168.9	0.939	0.78	25.6
22702.98	3.003	46.19	169.0	0.939	0.79	25.6
22735.93	2.975	46.22	169.1	0.940	0.79	25.6
22768.88	2.986	46.21	169.2	0.939	0.79	25.7
22801.83	2.983	46.22	169.3	0.939	0.79	25.7
22834.78	2.966	46.22	169.4	0.940	0.79	25.7
22867.73	2.963	46.23	169.5	0.940	0.79	25.7
22900.69	2.960	46.23	169.6	0.940	0.79	25.7
22933.64	2.955	46.25	169.7	0.940	0.80	25.7
22966.59	2.951	46.25	169.8	0.940	0.80	25.7
22999.54	2.943	46.26	169.9	0.940	0.80	25.8
23032.49	2.942	46.26	169.9	0.940	0.80	25.8
23065.44	2.924	46.27	170.0	0.941	0.80	25.8
23098.39	2.931	46.27	170.1	0.940	0.80	25.8
23131.34	2.928	46.28	170.2	0.941	0.80	25.8
23164.29	2.923	46.29	170.3	0.941	0.80	25.8

23197.25	2.912	46.31	170.4	0.941	0.81	25.8
23230.20	2.893	46.32	170.5	0.941	0.81	25.9
23263.15	2.923	46.29	170.6	0.941	0.81	25.9
23296.10	2.896	46.33	170.7	0.941	0.81	25.9
23329.05	2.898	46.32	170.8	0.941	0.81	25.9
23362.00	2.888	46.35	170.9	0.941	0.81	25.9
23394.95	2.894	46.34	171.0	0.941	0.81	25.9
23427.90	2.875	46.36	171.1	0.942	0.82	25.9
23460.86	2.887	46.34	171.2	0.941	0.82	26.0
23493.81	2.865	46.36	171.3	0.942	0.82	26.0
23526.76	2.873	46.36	171.4	0.942	0.82	26.0
23559.71	2.858	46.36	171.5	0.942	0.82	26.0
23592.66	2.865	46.37	171.6	0.942	0.82	26.0
23625.61	2.840	46.39	171.7	0.942	0.82	26.0
23658.56	2.854	46.37	171.8	0.942	0.82	26.0
23691.51	2.844	46.39	171.9	0.942	0.83	26.1
23724.46	2.842	46.40	172.0	0.943	0.83	26.1
23757.42	2.828	46.41	172.1	0.942	0.83	26.1
23790.37	2.844	46.39	172.2	0.943	0.83	26.1
23823.32	2.813	46.42	172.3	0.943	0.83	26.1
23856.27	2.822	46.42	172.4	0.943	0.83	26.1
23889.22	2.798	46.44	172.5	0.943	0.84	26.2
23922.17	2.815	46.42	172.6	0.943	0.84	26.2
23955.12	2.800	46.44	172.7	0.943	0.84	26.2
23988.07	2.790	46.46	173.0	0.944	0.84	26.2
24021.03	2.792	46.46	173.1	0.943	0.84	26.2
24053.98	2.796	46.46	173.2	0.944	0.84	26.3
24086.93	2.758	46.47	173.3	0.944	0.85	26.3
24119.88	2.790	46.44	173.4	0.944	0.85	26.3
24152.83	2.757	46.48	173.5	0.944	0.85	26.3
24185.78	2.778	46.47	173.6	0.944	0.85	26.3
24218.73	2.744	46.51	173.7	0.945	0.85	26.3
24251.68	2.763	46.48	173.8	0.944	0.85	26.3
24284.63	2.750	46.50	173.9	0.944	0.85	26.3
24317.59	2.747	46.51	174.0	0.945	0.86	26.4
24350.54	2.732	46.52	174.1	0.945	0.86	26.4
24383.49	2.747	46.51	174.2	0.945	0.86	26.4
24416.44	2.729	46.53	174.3	0.945	0.86	26.4
24449.39	2.729	46.53	174.4	0.945	0.86	26.4
24482.34	2.724	46.57	174.5	0.945	0.86	26.4
24515.29	2.724	46.54	174.6	0.945	0.86	26.4
24548.24	2.710	46.55	174.7	0.945	0.86	26.4
24581.20	2.714	46.54	174.8	0.945	0.86	26.4
24614.15	2.695	46.56	174.9	0.945	0.86	26.4
24647.10	2.707	46.55	175.0	0.945	0.86	26.5
24680.05	2.693	46.57	175.1	0.946	0.87	26.5
24713.00	2.683	46.60	175.2	0.946	0.87	26.5
24745.95	2.699	46.58	175.3	0.946	0.87	26.5
24778.90	2.675	46.61		0.946	0.87	26.5
24811.85	2.669	46.62		0.946	0.87	26.5
24844.80	2.671	46.60		0.946	0.87	26.5
24877.76	2.667	46.62		0.946	0.87	26.6
24910.71	2.669	46.60		0.946	0.88	26.6
24943.66	2.657	46.61		0.946	0.88	26.6

24976.61	2.656	46.61	175.4	0.946	0.88	26.6
25009.56	2.646	46.64	175.5	0.946	0.88	26.6
25042.51	2.646	46.61	175.6	0.946	0.88	26.6
25075.46	2.633	46.66	175.6	0.947	0.88	26.6
25108.41	2.647	46.63	175.7	0.946	0.88	26.6
25141.37	2.621	46.65	175.8	0.947	0.88	26.7
25174.32	2.628	46.68	175.9	0.947	0.89	26.7
25207.27	2.625	46.67	176.0	0.947	0.89	26.7
25240.22	2.630	46.66	176.1	0.947	0.89	26.7
25273.17	2.605	46.70	176.2	0.947	0.89	26.7
25306.12	2.626	46.67	176.2	0.947	0.89	26.7
25339.07	2.601	46.71	176.3	0.947	0.89	26.7
25372.02	2.610	46.67	176.4	0.947	0.89	26.8
25404.97	2.590	46.72	176.5	0.947	0.90	26.8
25437.93	2.610	46.70	176.6	0.947	0.90	26.8
25470.88	2.577	46.73	176.7	0.948	0.90	26.8
25503.83	2.599	46.71	176.8	0.947	0.90	26.8
25536.78	2.570	46.75	176.8	0.948	0.90	26.8
25569.73	2.578	46.71	176.9	0.948	0.90	26.8
25602.68	2.566	46.73	177.0	0.948	0.90	26.8
25635.63	2.577	46.71	177.1	0.948	0.90	26.9
25668.58	2.550	46.76	177.2	0.948	0.91	26.9
25701.54	2.573	46.71	177.3	0.948	0.91	26.9
25734.49	2.529	46.77	177.3	0.949	0.91	26.9
25767.44	2.573	46.72	177.4	0.948	0.91	26.9
25800.39	2.532	46.78	177.5	0.949	0.91	26.9
25833.34	2.556	46.74	177.6	0.948	0.91	26.9
25866.29	2.524	46.78	177.7	0.949	0.91	26.9
25899.24	2.536	46.76	177.8	0.949	0.92	27.0
25932.19	2.520	46.80	177.9	0.949	0.92	27.0
25965.14	2.529	46.76	177.9	0.949	0.92	27.0
25998.10	2.507	46.79	178.0	0.949	0.92	27.0
26031.05	2.524	46.78	178.1	0.949	0.92	27.0
26064.00	2.498	46.81	178.2	0.949	0.92	27.0
26096.95	2.515	46.81	178.3	0.949	0.92	27.0
26129.90	2.487	46.83	178.3	0.950	0.92	27.0
26162.85	2.518	46.81	178.4	0.949	0.93	27.1
26195.80	2.484	46.85	178.5	0.950	0.93	27.1
26228.75	2.506	46.82	178.6	0.949	0.93	27.1
26261.71	2.487	46.84	178.7	0.950	0.93	27.1
26294.66	2.495	46.85	178.8	0.949	0.93	27.1
26327.61	2.477	46.86	178.8	0.950	0.93	27.1
26360.56	2.468	46.85	178.9	0.950	0.93	27.1
26393.51	2.469	46.85	179.0	0.950	0.94	27.1
26426.46	2.469	46.83	179.1	0.950	0.94	27.2
26459.41	2.460	46.87	179.2	0.950	0.94	27.2

TOTAL PATTERN RESULTS:

WATERFLOOD RECOVERY	:	1162.20	MSTB
WATERFLOOD-INFILL RECOVERY	:	1433.33	MSTB
INCREMENTAL OIL FROM INFILL:		271.13	MSTB
INCREMENTAL OIL FROM INFILL:		5.14	% OOIP
ORIGINAL OIL IN PLACE	:	5275.44	MSTB

```

*****
*
*  S C I E N T I F I C  S O F T W A R E
*    -   I N T E R C O M P
*
*
*  INFILL DRILLING PREDICTION MODEL
*    (IDPM - RELEASE 1.2.0)
*
*****

```

Economics for Waterflood

ECONOMIC DATA

```

-----
NUMBER OF PROJECT YEARS ..... 40
STATE CODE ..... NONE
DISTRICT CODE ..... 0
PRINT CONTROL ..... 2 IOUT
FEDERAL INCOME TAX OPTION ..... 0 IFIT
DISCOUNTING METHOD ..... 0 IDISC
DEPRECIATION METHOD ..... 0 IDEP
PROJECT ECONOMIC LIFE METHOD ..... 0 IPLIF
RESERVOIR DEPTH ..... 6300.0 FEET
INJECTORS DRILLED PER PATTERN (WPP1). 1.00
PRODUCERS DRILLED PER PATTERN (WPP2). 1.00
CONVTD PRIMARY PROD PER PAT (WPP3) .. 0.00
CONVTD PROD TO INJ PER PAT (WPP4) ... 0.00
NO. OF MONTHS WORKING CAPITAL ..... 0.00
PROJECT STARTUP COSTS ..... 0.0 MS
OIL RATE UNCERTAINTY ..... 0.0010 FRACTION
PERCENT OF CAPITAL BORROWED..... 0 PERCENT

```

TAXES AND ESCALATION

```

-----
DISCOUNT RATE ..... 0.100 FRACTION
INFLATION RATE ..... 0.050 FRACTION
ROYALTY RATE ..... 0.125 FRACTION
SEVERANCE TAX RATE ..... 0.080 FRACTION
FEDERAL INCOME TAX RATE ..... 0.460 FRACTION
INVESTMENT TAX CREDIT ..... 0.100 FRACTION
DEPRECIATION TIME (STRAIGHT LINE)... 5.00 YEARS
STATE INCOME TAX RATE ..... 0.040 FRACTION
WINDFALL EXCISE TAX RATE ..... 0.000 FRACTION
WINDFALL PHASE OUT START DATE ..... 1991.
WINDFALL PHASE OUT END DATE ..... 1993.
PROJECT START DATE ..... 1994.
BASE OIL PRICE FOR WINDFALL TAX ..... 23.07 $/BBL
OIL PRICE ESCALATION RATE ..... 0.000 FRACTION
GAS PRICE ESCALATION RATE ..... 0.000 FRACTION
OPERATING COST ESCALATION RATE ..... 0.000 FRACTION

```

PRICES AND COSTS		LOW	MOST-LIKELY	HIGH
-----		-----	-----	-----
OIL PRICE	\$/BBL	16.00	20.00	24.00
GAS PRICE	\$/MCF	2.67	3.33	4.00
FIXED OPERATING COST PER PATTERN	\$/YR	33313.	41642.	49970.
VARIABLE OPERATING COST	\$/BBL	0.040	0.050	0.060
WELL WORKOVER COST PER PATTERN	\$/YR		12013.	
PROD WATER TREATING/DISPOSAL COST ...	\$/BBL		0.030	

NOTE.. -PATTERN- HERE ALWAYS REFERS TO THE PRE-INFILL FULL 5-SPOT PATTERN

0 ANNUAL PATTERN AND PROJECT VOLUMES PRODUCED

PROJECT LIFE IS 40 YEARS

YEAR	PATTERN			YEAR-END WTR-CUT	INJ WTR, MSTB	PATTERNS		PROJECT		
	OIL, MSTB	GAS, MMSCF	WATER, MSTB			INITIATD	TOTAL	OIL, MSTB	GAS, MMSCF	WATER, MSTB
1	57.9	19.1	0.0	0.0000	73.1	6.	6.	347.5	114.7	0.0
2	56.9	18.8	0.0	0.0000	73.1	0.	6.	341.5	112.7	0.0
3	56.5	18.7	0.5	0.0451	73.1	0.	6.	339.2	111.9	2.8
4	50.9	16.8	7.6	0.2237	73.1	0.	6.	305.7	100.9	45.8
5	45.6	15.1	14.5	0.2787	73.1	0.	6.	273.9	90.4	86.7
6	41.2	13.6	20.1	0.3681	73.1	0.	6.	247.2	81.6	120.9
7	36.5	12.0	26.3	0.4522	73.1	0.	6.	218.8	72.2	157.7
8	32.7	10.8	31.1	0.5100	73.1	0.	6.	196.2	64.7	186.8
9	29.8	9.8	34.8	0.5589	73.1	0.	6.	178.8	59.0	209.1
10	27.3	9.0	38.1	0.5985	73.1	0.	6.	163.7	54.0	228.6
11	25.2	8.3	40.8	0.6300	73.1	0.	6.	151.4	50.0	244.5
12	23.5	7.7	43.0	0.6575	73.1	0.	6.	140.8	46.5	258.0
13	22.0	7.3	44.9	0.6803	73.1	0.	6.	132.0	43.6	269.4
14	20.7	6.8	46.6	0.7005	73.1	0.	6.	124.0	40.9	279.5
15	19.5	6.4	48.0	0.7180	73.1	0.	6.	117.2	38.7	288.3
16	18.5	6.1	49.3	0.7327	73.1	0.	6.	111.2	36.7	296.0
17	17.7	5.8	50.4	0.7456	73.1	0.	6.	106.0	35.0	302.6
18	16.9	5.6	51.4	0.7570	73.1	0.	6.	101.4	33.5	308.6
19	16.2	5.3	52.3	0.7677	73.1	0.	6.	97.2	32.1	314.0
20	15.6	5.1	53.1	0.7776	73.1	0.	6.	93.4	30.8	318.8
21	15.0	4.9	53.9	0.7860	73.1	0.	6.	89.9	29.7	323.2
22	14.5	4.8	54.6	0.7934	73.1	0.	6.	86.8	28.6	327.4
23	14.0	4.6	55.2	0.8010	73.1	0.	6.	83.8	27.7	331.2
24	13.5	4.5	55.8	0.8079	73.1	0.	6.	81.0	26.7	334.5
25	13.1	4.3	56.3	0.8143	73.1	0.	6.	78.4	25.9	337.8
26	12.7	4.2	56.8	0.8200	73.1	0.	6.	76.0	25.1	340.9
27	12.3	4.1	57.3	0.8255	73.1	0.	6.	73.7	24.3	343.8
28	11.9	3.9	57.7	0.8309	73.1	0.	6.	71.5	23.6	346.4
29	11.6	3.8	58.2	0.8357	73.1	0.	6.	69.6	23.0	349.1
30	11.3	3.7	58.6	0.8405	73.1	0.	6.	67.7	22.3	351.6

31	11.0	3.6	59.0	0.8446	73.1	0.	6.	65.9	21.7	354.0
32	10.7	3.5	59.4	0.8493	73.1	0.	6.	64.2	21.2	356.2
33	10.4	3.4	59.7	0.8529	73.1	0.	6.	62.6	20.6	358.4
34	10.2	3.4	60.0	0.8567	73.1	0.	6.	61.0	20.1	360.3
35	9.9	3.3	60.4	0.8598	73.1	0.	6.	59.7	19.7	362.4
36	9.7	3.2	60.7	0.8635	73.1	0.	6.	58.2	19.2	364.2
37	9.5	3.1	61.0	0.8664	73.1	0.	6.	56.9	18.8	365.8
38	9.3	3.1	61.3	0.8700	73.1	0.	6.	55.6	18.3	367.5
39	9.0	3.0	61.5	0.8732	73.1	0.	6.	54.2	17.9	369.0
40	8.8	2.9	61.8	0.8761	73.1	0.	6.	53.0	17.5	370.5

MAXIMUM INJECTION RATE IS 1.201 MMBL/D

MAJOR CAPITAL COSTS

INJECTOR DRILLING COST	327062.	\$/WELL
PRODUCER EQUIPMENT COST	128487.	\$/WELL
COST TO UPGRADE SECONDARY PROD	0.	\$/WELL
COST TO CONVERT PROD TO INJ	0.	\$/WELL
COST TO UPGRADE TO SEC. OPERATIONS ..	0.	\$/WELL
CAPACITY OF WATER INJ PLANT	0.4	MMB/YR
CAPITAL FOR WATER INJ PLANT	0.0	M\$

PROJECT CAPITAL SCHEDULE - MOST LIKELY

YEAR	--- PATTERN \$ --- TANGIBLE	INTANGBL	PATTERNS INITIATD	--- PROJECT M\$ --- TANGIBLE	INTANGBL
1	37775.0	783965.4	6.	227.	4704.
2	0.0	0.0	0.	0.	0.
3	0.0	0.0	0.	0.	0.
4	0.0	0.0	0.	0.	0.
5	0.0	0.0	0.	0.	0.
6	0.0	0.0	0.	0.	0.
7	0.0	0.0	0.	0.	0.
8	0.0	0.0	0.	0.	0.
9	0.0	0.0	0.	0.	0.
10	0.0	0.0	0.	0.	0.
11	0.0	0.0	0.	0.	0.
12	0.0	0.0	0.	0.	0.
13	0.0	0.0	0.	0.	0.
14	0.0	0.0	0.	0.	0.
15	0.0	0.0	0.	0.	0.
16	0.0	0.0	0.	0.	0.
17	0.0	0.0	0.	0.	0.
18	0.0	0.0	0.	0.	0.
19	0.0	0.0	0.	0.	0.
20	0.0	0.0	0.	0.	0.
21	0.0	0.0	0.	0.	0.
22	0.0	0.0	0.	0.	0.
23	0.0	0.0	0.	0.	0.
24	0.0	0.0	0.	0.	0.

25	0.0	0.0	0.	0.	0.
26	0.0	0.0	0.	0.	0.
27	0.0	0.0	0.	0.	0.
28	0.0	0.0	0.	0.	0.
29	0.0	0.0	0.	0.	0.
30	0.0	0.0	0.	0.	0.
31	0.0	0.0	0.	0.	0.
32	0.0	0.0	0.	0.	0.
33	0.0	0.0	0.	0.	0.
34	0.0	0.0	0.	0.	0.
35	0.0	0.0	0.	0.	0.
36	0.0	0.0	0.	0.	0.
37	0.0	0.0	0.	0.	0.
38	0.0	0.0	0.	0.	0.
39	0.0	0.0	0.	0.	0.
40	0.0	0.0	0.	0.	0.

PROJECT MEAN VALUES - ESCALATED

YEAR	OIL PRICE \$/BBL	GAS PRICE \$/MCF	TANGIBLE CAPITAL M\$/YR	INTANGBL CAPITAL M\$/YR	FIXED OPN COST M\$/YR	VARIABLE OPN COST \$/BBL	WELL WORKOVER M\$/YR	WATER TREATING \$/BBL
1	20.00	3.33	227.	4704.	250.	0.050	72.	0.030
2	20.00	3.33	0.	0.	250.	0.050	72.	0.030
3	20.00	3.33	0.	0.	250.	0.050	72.	0.030
4	20.00	3.33	0.	0.	250.	0.050	72.	0.030
5	20.00	3.33	0.	0.	250.	0.050	72.	0.030
6	20.00	3.33	0.	0.	250.	0.050	72.	0.030
7	20.00	3.33	0.	0.	250.	0.050	72.	0.030
8	20.00	3.33	0.	0.	250.	0.050	72.	0.030
9	20.00	3.33	0.	0.	250.	0.050	72.	0.030
10	20.00	3.33	0.	0.	250.	0.050	72.	0.030
11	20.00	3.33	0.	0.	250.	0.050	72.	0.030
12	20.00	3.33	0.	0.	250.	0.050	72.	0.030
13	20.00	3.33	0.	0.	250.	0.050	72.	0.030
14	20.00	3.33	0.	0.	250.	0.050	72.	0.030
15	20.00	3.33	0.	0.	250.	0.050	72.	0.030
16	20.00	3.33	0.	0.	250.	0.050	72.	0.030
17	20.00	3.33	0.	0.	250.	0.050	72.	0.030
18	20.00	3.33	0.	0.	250.	0.050	72.	0.030
19	20.00	3.33	0.	0.	250.	0.050	72.	0.030
20	20.00	3.33	0.	0.	250.	0.050	72.	0.030
21	20.00	3.33	0.	0.	250.	0.050	72.	0.030
22	20.00	3.33	0.	0.	250.	0.050	72.	0.030
23	20.00	3.33	0.	0.	250.	0.050	72.	0.030
24	20.00	3.33	0.	0.	250.	0.050	72.	0.030
25	20.00	3.33	0.	0.	250.	0.050	72.	0.030
26	20.00	3.33	0.	0.	250.	0.050	72.	0.030
27	20.00	3.33	0.	0.	250.	0.050	72.	0.030
28	20.00	3.33	0.	0.	250.	0.050	72.	0.030
29	20.00	3.33	0.	0.	250.	0.050	72.	0.030
30	20.00	3.33	0.	0.	250.	0.050	72.	0.030
31	20.00	3.33	0.	0.	250.	0.050	72.	0.030

32	20.00	3.33	0.	0.	250.	0.050	72.	0.030
33	20.00	3.33	0.	0.	250.	0.050	72.	0.030
34	20.00	3.33	0.	0.	250.	0.050	72.	0.030
35	20.00	3.33	0.	0.	250.	0.050	72.	0.030
36	20.00	3.33	0.	0.	250.	0.050	72.	0.030
37	20.00	3.33	0.	0.	250.	0.050	72.	0.030
38	20.00	3.33	0.	0.	250.	0.050	72.	0.030
39	20.00	3.33	0.	0.	250.	0.050	72.	0.030
40	20.00	3.33	0.	0.	250.	0.050	72.	0.030

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	1 1994.	2 1995.	3 1996.	4 1997.	5 1998.	6 1999.	7 2000.	8 2001.	9 2002.	10 2003.
<hr/>										
ANNUAL OIL PRODUCTION, MSTB	347.51	341.50	339.23	305.66	273.87	247.22	218.78	196.17	178.85	163.75
ANNUAL GAS PRODUCTION, MMSCF	114.68	112.69	111.95	100.87	90.38	81.58	72.20	64.73	59.02	54.04
ANNUAL WATER PRODUCTION, MSTB	0.	0.	3.	46.	87.	121.	158.	187.	209.	229.
OIL PRODUCTION RATE, STB/D	952.	936.	929.	837.	750.	677.	599.	537.	490.	449.
GAS PRODUCTION RATE, MSCF/D	314.	309.	307.	276.	248.	224.	198.	177.	162.	148.
WATER PRODUCTION RATE, STB/D	0.	0.	8.	126.	238.	331.	432.	512.	573.	626.
<hr/>										
NET OIL SOLD (LESS ROYALTY), MSTB ...	304.08	298.81	296.83	267.45	239.64	216.32	191.43	171.65	156.49	143.28
NET GAS SOLD (LESS ROYALTY), MMSCF ...	100.34	98.61	97.95	88.26	79.08	71.38	63.17	56.64	51.64	47.28
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	6.95	6.83	6.78	6.11	5.48	4.94	4.38	3.92	3.58	3.27
ANNUAL GROSS GAS SALES, MM\$	0.38	0.38	0.37	0.34	0.30	0.27	0.24	0.22	0.20	0.18
ANNUAL TOTAL GROSS SALES, MM\$	7.33	7.21	7.16	6.45	5.78	5.22	4.62	4.14	3.77	3.45
ANNUAL ROYALTY, MM\$	0.92	0.90	0.89	0.81	0.72	0.65	0.58	0.52	0.47	0.43
ANNUAL NET SALES, MM\$	6.42	6.30	6.26	5.64	5.06	4.56	4.04	3.62	3.30	3.02
<hr/>										
ANNUAL SEVERANCE TAX, MM\$	0.51	0.50	0.50	0.45	0.40	0.37	0.32	0.29	0.26	0.24
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.31	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	1.17	0.91	0.91	0.86	0.81	0.77	0.73	0.69	0.67	0.65
ANNUAL NET OPERATING INCOME, MM\$	5.25	5.39	5.35	4.79	4.25	3.79	3.31	2.93	2.63	2.38
CUM NET OPERATING INCOME, MM\$	5.25	10.64	16.00	20.78	25.03	28.82	32.13	35.06	37.69	40.07
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	4.70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	0.32	5.71	11.07	15.85	20.10	23.89	27.20	30.13	32.76	35.14
<hr/>										
BASE PRICE OF OIL FOR WPT, \$/BBL	23.07	24.68	26.41	28.26	30.24	32.36	34.62	37.05	39.64	42.41
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.21	0.22	0.21	0.19	0.17	0.15	0.13	0.12	0.11	0.10
ANNUAL INTANGIBLES AND DEPR, MM\$	4.75	0.05	0.05	0.05	0.05	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.29	5.13	5.10	4.55	4.03	3.64	3.18	2.81	2.53	2.28

ANNUAL FEDERAL INCOME TAX, MM\$	0.11	2.36	2.34	2.09	1.85	1.68	1.46	1.29	1.16	1.05
ANNUAL AFTER TAX CASH FLOW, MM\$	0.00	2.82	2.80	2.50	2.22	1.97	1.72	1.52	1.37	1.23
CUM CASH FLOW AFTER TAXES, MM\$	0.00	2.81	5.61	8.11	10.33	12.30	14.02	15.53	16.90	18.13

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	11 2004.	12 2005.	13 2006.	14 2007.	15 2008.	16 2009.	17 2010.	18 2011.	19 2012.	20 2013.
ANNUAL OIL PRODUCTION, MSTB	151.40	140.83	132.04	124.02	117.15	111.18	105.98	101.42	97.25	93.40
ANNUAL GAS PRODUCTION, MMSCF	49.96	46.47	43.57	40.93	38.66	36.69	34.97	33.47	32.09	30.82
ANNUAL WATER PRODUCTION, MSTB	245.	258.	269.	279.	288.	296.	303.	309.	314.	319.
OIL PRODUCTION RATE, STB/D	415.	386.	362.	340.	321.	305.	290.	278.	266.	256.
GAS PRODUCTION RATE, MSCF/D	137.	127.	119.	112.	106.	101.	96.	92.	88.	84.
WATER PRODUCTION RATE, STB/D	670.	707.	738.	766.	790.	811.	829.	846.	860.	873.
NET OIL SOLD (LESS ROYALTY), MSTB ...	132.48	123.22	115.53	108.52	102.51	97.28	92.74	88.74	85.09	81.73
NET GAS SOLD (LESS ROYALTY), MMSCF ...	43.72	40.66	38.13	35.81	33.83	32.10	30.60	29.28	28.08	26.97
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	3.03	2.82	2.64	2.48	2.34	2.22	2.12	2.03	1.94	1.87
ANNUAL GROSS GAS SALES, MM\$	0.17	0.15	0.15	0.14	0.13	0.12	0.12	0.11	0.11	0.10
ANNUAL TOTAL GROSS SALES, MM\$	3.19	2.97	2.79	2.62	2.47	2.35	2.24	2.14	2.05	1.97
ANNUAL ROYALTY, MM\$	0.40	0.37	0.35	0.33	0.31	0.29	0.28	0.27	0.26	0.25
ANNUAL NET SALES, MM\$	2.80	2.60	2.44	2.29	2.16	2.05	1.96	1.87	1.80	1.72
ANNUAL SEVERANCE TAX, MM\$	0.22	0.21	0.20	0.18	0.17	0.16	0.16	0.15	0.14	0.14
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.63	0.61	0.60	0.59	0.58	0.57	0.56	0.55	0.55	0.54
ANNUAL NET OPERATING INCOME, MM\$	2.17	1.99	1.84	1.70	1.59	1.48	1.40	1.32	1.25	1.18
CUM NET OPERATING INCOME, MM\$	42.24	44.22	46.06	47.77	49.35	50.84	52.23	53.55	54.80	55.98
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	37.31	39.29	41.13	42.84	44.42	45.91	47.30	48.62	49.87	51.05
BASE PRICE OF OIL FOR WPT, \$/BBL	45.38	48.56	51.96	55.60	59.49	63.65	68.11	72.87	77.98	83.43
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.09	0.08	0.07	0.07	0.06	0.06	0.06	0.05	0.05	0.05
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	2.08	1.91	1.77	1.63	1.52	1.43	1.34	1.27	1.20	1.14
ANNUAL FEDERAL INCOME TAX, MM\$	0.96	0.88	0.81	0.75	0.70	0.66	0.62	0.58	0.55	0.52
ANNUAL AFTER TAX CASH FLOW, MM\$	1.12	1.03	0.95	0.88	0.82	0.77	0.72	0.68	0.65	0.61
CUM CASH FLOW AFTER TAXES, MM\$	19.26	20.29	21.24	22.12	22.94	23.71	24.44	25.12	25.77	26.38

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	21 2014.	22 2015.	23 2016.	24 2017.	25 2018.	26 2019.	27 2020.	28 2021.	29 2022.	30 2023.
ANNUAL OIL PRODUCTION, MSTB	89.89	86.81	83.82	81.03	78.40	75.96	73.75	71.53	69.59	67.68
ANNUAL GAS PRODUCTION, MMSCF	29.66	28.65	27.66	26.74	25.87	25.07	24.34	23.61	22.96	22.33
ANNUAL WATER PRODUCTION, MSTB	323.	327.	331.	335.	338.	341.	344.	346.	349.	352.
OIL PRODUCTION RATE, STB/D	246.	238.	230.	222.	215.	208.	202.	196.	191.	185.
GAS PRODUCTION RATE, MSCF/D	81.	78.	76.	73.	71.	69.	67.	65.	63.	61.
WATER PRODUCTION RATE, STB/D	886.	897.	907.	916.	926.	934.	942.	949.	957.	963.
NET OIL SOLD (LESS ROYALTY), MSTB ...	78.65	75.96	73.34	70.90	68.60	66.47	64.53	62.59	60.89	59.22
NET GAS SOLD (LESS ROYALTY), MMSCF ...	25.96	25.07	24.20	23.40	22.64	21.93	21.30	20.66	20.09	19.54
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	1.80	1.74	1.68	1.62	1.57	1.52	1.47	1.43	1.39	1.35
ANNUAL GROSS GAS SALES, MM\$	0.10	0.10	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.07
ANNUAL TOTAL GROSS SALES, MM\$	1.90	1.83	1.77	1.71	1.65	1.60	1.56	1.51	1.47	1.43
ANNUAL ROYALTY, MM\$	0.24	0.23	0.22	0.21	0.21	0.20	0.19	0.19	0.18	0.18
ANNUAL NET SALES, MM\$	1.66	1.60	1.55	1.50	1.45	1.40	1.36	1.32	1.28	1.25
ANNUAL SEVERANCE TAX, MM\$	0.13	0.13	0.12	0.12	0.12	0.11	0.11	0.11	0.10	0.10
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.54	0.53	0.53	0.52	0.52	0.52	0.51	0.51	0.51	0.50
ANNUAL NET OPERATING INCOME, MM\$	1.12	1.07	1.02	0.97	0.93	0.89	0.85	0.81	0.78	0.75
CUM NET OPERATING INCOME, MM\$	57.11	58.18	59.20	60.17	61.10	61.99	62.84	63.65	64.43	65.17
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	52.18	53.25	54.27	55.24	56.17	57.06	57.91	58.72	59.50	60.24
BASE PRICE OF OIL FOR WPT, \$/BBL	89.27	95.52	102.21	109.36	117.02	125.21	133.98	143.35	153.39	164.13
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.04	0.04	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.03
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	1.08	1.03	0.98	0.93	0.89	0.85	0.82	0.78	0.75	0.72
ANNUAL FEDERAL INCOME TAX, MM\$	0.50	0.47	0.45	0.43	0.41	0.39	0.38	0.36	0.34	0.33
ANNUAL AFTER TAX CASH FLOW, MM\$	0.58	0.56	0.53	0.50	0.48	0.46	0.44	0.42	0.40	0.39
CUM CASH FLOW AFTER TAXES, MM\$	26.96	27.52	28.05	28.55	29.03	29.49	29.93	30.36	30.76	31.15

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	31 2024.	32 2025.	33 2026.	34 2027.	35 2028.	36 2029.	37 2030.	38 2031.	39 2032.	40 2033.
ANNUAL OIL PRODUCTION, MSTB	65.90	64.22	62.57	61.04	59.70	58.25	56.93	55.56	54.21	53.01
ANNUAL GAS PRODUCTION, MMSCF	21.75	21.19	20.65	20.14	19.70	19.22	18.79	18.33	17.89	17.49

ANNUAL WATER PRODUCTION, MSTB	354.	356.	358.	360.	362.	364.	366.	368.	369.	371.
OIL PRODUCTION RATE, STB/D	181.	176.	171.	167.	164.	160.	156.	152.	149.	145.
GAS PRODUCTION RATE, MSCF/D	60.	58.	57.	55.	54.	53.	51.	50.	49.	48.
WATER PRODUCTION RATE, STB/D	970.	976.	982.	987.	993.	998.	1002.	1007.	1011.	1015.
NET OIL SOLD (LESS ROYALTY), MSTB	57.67	56.19	54.75	53.41	52.24	50.97	49.81	48.61	47.43	46.39
NET GAS SOLD (LESS ROYALTY), MMSCF	19.03	18.54	18.07	17.62	17.24	16.82	16.44	16.04	15.65	15.31
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	1.32	1.28	1.25	1.22	1.19	1.16	1.14	1.11	1.08	1.06
ANNUAL GROSS GAS SALES, MM\$	0.07	0.07	0.07	0.07	0.07	0.06	0.06	0.06	0.06	0.06
ANNUAL TOTAL GROSS SALES, MM\$	1.39	1.35	1.32	1.29	1.26	1.23	1.20	1.17	1.14	1.12
ANNUAL ROYALTY, MM\$	0.17	0.17	0.17	0.16	0.16	0.15	0.15	0.15	0.14	0.14
ANNUAL NET SALES, MM\$	1.22	1.19	1.16	1.13	1.10	1.08	1.05	1.03	1.00	0.98
ANNUAL SEVERANCE TAX, MM\$	0.10	0.09	0.09	0.09	0.09	0.09	0.08	0.08	0.08	0.08
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.50	0.50	0.50	0.49	0.49	0.49	0.49	0.48	0.48	0.48
ANNUAL NET OPERATING INCOME, MM\$	0.72	0.69	0.66	0.63	0.61	0.59	0.56	0.54	0.52	0.50
CUM NET OPERATING INCOME, MM\$	65.89	66.58	67.24	67.87	68.48	69.07	69.63	70.17	70.69	71.19
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	60.96	61.65	62.31	62.94	63.55	64.14	64.70	65.24	65.76	66.26
BASE PRICE OF OIL FOR WPT, \$/BBL	175.61	187.91	201.06	215.14	230.20	246.31	263.55	282.00	301.74	322.86
ANNUAL WINDELL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDELL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.03	0.03	0.03	0.03	0.02	0.02	0.02	0.02	0.02	0.02
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.69	0.66	0.63	0.61	0.59	0.56	0.54	0.52	0.50	0.48
ANNUAL FEDERAL INCOME TAX, MM\$	0.32	0.30	0.29	0.28	0.27	0.26	0.25	0.24	0.23	0.22
ANNUAL AFTER TAX CASH FLOW, MM\$	0.37	0.36	0.34	0.33	0.32	0.30	0.29	0.28	0.27	0.26
CUM CASH FLOW AFTER TAXES, MM\$	31.52	31.87	32.22	32.54	32.86	33.17	33.46	33.74	34.01	34.26

UNDISCOUNTED MEAN RESULTS

PROJECT ECONOMIC LIFE	40.0	YEARS
TOTAL GROSS SALES	108.808	MM\$
TOTAL NET SALES	95.207	MM\$
TOTAL SEVERANCE TAX	7.617	MM\$
TOTAL FIXED OPERATING COST	9.994	MM\$
TOTAL VARIABLE OPERATING COST	0.258	MM\$
TOTAL WELL WORKOVER COST	2.883	MM\$
TOTAL PROD WATER TREATING COST	0.328	MM\$
TOTAL OVERHEAD	2.939	MM\$
TOTAL OPERATING COST	24.019	MM\$
TOTAL WORKING CAPITAL	0.000	MM\$

TOTAL TANGIBLE CAPITAL 0.227 MM\$
 TOTAL INTANGIBLE CAPITAL 4.704 MM\$
 TOTAL CAPITAL INVESTMENT 4.930 MM\$
 TOTAL DEBT INTEREST EXPENSE 0.000 MM\$
 TOTAL PROJECT EXPENSE 28.949 MM\$
 TOTAL CASH FLOW BEFORE TAX 66.258 MM\$
 TOTAL WINDELL PROFITS TAX 0.000 MM\$
 TOTAL STATE INCOME TAX 2.848 MM\$
 TOTAL FEDERAL INCOME TAX 29.146 MM\$
 TOTAL AFTER TAX CASH FLOW 34.264 MM\$
 TOTAL LOAN AMOUNT 0.000 MM\$

0

PROJECT ECONOMIC ANALYSIS

YEAR	PRESNT VALUE FACTOR	BEFORE TAX (MM\$)		MEAN VALUE CASH FLOW		AFTER TAX (MM\$)	
		ANNUAL	CONST \$	ANNUAL	DISCNTD	ANNUAL	CONST \$
		-----	-----	-----	-----	-----	-----
1 1994.	1.0000	0.32	0.32	0.32	0.00	0.00	0.00
2 1995.	0.8658	5.71	5.45	4.99	2.81	2.68	2.44
3 1996.	0.7496	11.07	10.31	9.00	5.61	5.22	4.53
4 1997.	0.6490	15.85	14.45	12.11	8.11	7.38	6.16
5 1998.	0.5619	20.10	17.94	14.49	10.33	9.21	7.41
6 1999.	0.4865	23.89	20.91	16.34	12.30	10.75	8.36
7 2000.	0.4212	27.20	23.38	17.73	14.02	12.03	9.08
8 2001.	0.3647	30.13	25.46	18.80	15.53	13.11	9.64
9 2002.	0.3158	32.76	27.24	19.63	16.90	14.03	10.07
10 2003.	0.2734	35.14	28.78	20.28	18.13	14.82	10.41
11 2004.	0.2367	37.31	30.11	20.80	19.26	15.51	10.67
12 2005.	0.2049	39.29	31.27	21.20	20.29	16.12	10.88
13 2006.	0.1774	41.13	32.29	21.53	21.24	16.65	11.05
14 2007.	0.1536	42.84	33.20	21.79	22.12	17.12	11.19
15 2008.	0.1330	44.42	34.00	22.00	22.94	17.53	11.30
16 2009.	0.1152	45.91	34.71	22.17	23.71	17.90	11.39
17 2010.	0.0997	47.30	35.35	22.31	24.44	18.23	11.46
18 2011.	0.0863	48.62	35.93	22.43	25.12	18.53	11.52
19 2012.	0.0747	49.87	36.44	22.52	25.77	18.80	11.57
20 2013.	0.0647	51.05	36.91	22.60	26.38	19.04	11.60
21 2014.	0.0560	52.18	37.34	22.66	26.96	19.26	11.64
22 2015.	0.0485	53.25	37.72	22.71	27.52	19.46	11.66
23 2016.	0.0420	54.27	38.07	22.75	28.05	19.64	11.69
24 2017.	0.0364	55.24	38.39	22.79	28.55	19.81	11.71
25 2018.	0.0315	56.17	38.67	22.82	29.03	19.96	11.72
26 2019.	0.0273	57.06	38.94	22.84	29.49	20.09	11.73
27 2020.	0.0236	57.91	39.17	22.86	29.93	20.21	11.74
28 2021.	0.0204	58.72	39.39	22.88	30.36	20.33	11.75
29 2022.	0.0177	59.50	39.59	22.89	30.76	20.43	11.76
30 2023.	0.0153	60.24	39.77	22.90	31.15	20.52	11.76
31 2024.	0.0133	60.96	39.94	22.91	31.52	20.61	11.77
32 2025.	0.0115	61.65	40.09	22.92	31.87	20.69	11.77
33 2026.	0.0099	62.31	40.23	22.93	32.22	20.76	11.78
34 2027.	0.0086	62.94	40.35	22.94	32.54	20.83	11.78
35 2028.	0.0075	63.55	40.47	22.94	32.86	20.89	11.78
36 2029.	0.0065	64.14	40.58	22.94	33.17	20.94	11.78

0

37	2030.	0.0056	64.70	40.67	22.94	33.46	20.99	11.79
38	2031.	0.0048	65.24	40.76	22.95	33.74	21.04	11.79
39	2032.	0.0042	65.76	40.84	22.95	34.01	21.08	11.79
40	2033.	0.0036	66.26	40.92	22.95	34.26	21.12	11.79

 *
 * S C I E N T I F I C S O F T W A R E *
 * - I N T E R C O M P *
 *
 *
 * I N F I L L D R I L L I N G P R E D I C T I O N M O D E L *
 * (I D P M - R E L E A S E 1 . 2 . 0) *
 *

Economics for Waterflood

0 PRODUCTION SUMMARY

PROJECT ECONOMIC LIFE	40.0	YEARS
CUMULATIVE GROSS OIL SOLD	5157.	MSTB
CUMULATIVE GROSS GAS SOLD	1702.	MMSCF
CUMULATIVE NET OIL SOLD	4512.	MSTB
PRESENT VALUE OF NET OIL SOLD	1604.	MSTB

0 MEAN RESULTS

PRESENT VALUE OF TOTAL GROSS SALES	38.684	MM\$
PRESENT VALUE OF TOTAL NET SALES	33.848	MM\$
TOTAL SEVERANCE TAX (PV)	2.708	MM\$
TOTAL FIXED OPERATING COST (PV)	1.856	MM\$
TOTAL VARIABLE OPERATING COST (PV)	0.092	MM\$
TOTAL WELL WORKOVER COST (PV)	0.535	MM\$
TOTAL PROD WATER TREATING COST (PV)	0.027	MM\$
TOTAL OVERHEAD (PV)	0.749	MM\$
TOTAL OPERATING COST (PV)	5.967	MM\$
TOTAL WORKING CAPITAL (PV)	0.000	MM\$
TOTAL TANGIBLE CAPITAL INVESTED (PV) ...	0.227	MM\$
TOTAL INTANGIBLE CAPITAL (PV)	4.704	MM\$
TOTAL CAPITAL INVESTMENT (PV)	4.930	MM\$
TOTAL INTEREST EXPENSE (PV)	0.000	MM\$
TOTAL PROJECT EXPENSE (PV)	10.897	MM\$
TOTAL LOAN PRINCIPAL REPAYMENT (PV)	0.000	MM\$
DISCOUNTED COST PER DISC NET OIL	6.793	\$/BBL
DISCOUNTED CASH FLOW BEFORE TAX	22.951	MM\$

0 PROJECT PROFITABILITY (AFTER TAX)

AVERAGE MONETARY DISCOUNT RATE	10.00	PCNT
90 PCNT CONFIDENCE DCF	6.773	MM\$
MEAN DISCOUNTED CASH FLOW	11.789	MM\$
10 PCNT CONFIDENCE DCF	17.670	MM\$
STANDARD DEVIATION OF THE MEAN DCF	4.112	MM\$
MEAN DCF PROFIT TO INVESTMENT RATIO	2.391	P/I
MEAN DCF PROFIT TO EXPENSE RATIO	1.082	P/E
MEAN DCF PROFIT PER DISC NET OIL	7.349	\$/BBL
MEAN INVESTMENT EFFICIENCY	3.908	


```
*****
MEAN DCF RATE OF RETURN .....
*****
*
* S C I E N T I F I C   S O F T W A R E
* -   I N T E R C O M P
*
*
* INFILL DRILLING PREDICTION MODEL
*      (IDPM - RELEASE 1.2.0)
*
* *****
```

ECONOMIC DATA

TAXES AND ESCALATION

DISCOUNT RATE	0.100	FRACTION
INFLATION RATE	0.050	FRACTION
ROYALTY RATE	0.125	FRACTION
SEVERANCE TAX RATE	0.080	FRACTION
FEDERAL INCOME TAX RATE	0.460	FRACTION
INVESTMENT TAX CREDIT	0.100	FRACTION
DEPRECIATION TIME (STRAIGHT LINE)	5.00	YEARS
STATE INCOME TAX RATE	0.040	FRACTION
WINDEALL EXCISE TAX RATE	0.000	FRACTION
WINDEALL PHASE OUT START DATE	1991.	
WINDEALL PHASE OUT END DATE	1993.	
PROJECT START DATE	1994.	
BASE OIL PRICE FOR WINDEALL TAX	23.07	\$/BBL
OIL PRICE ESCALATION RATE	0.000	FRACTION
GAS PRICE ESCALATION RATE	0.000	FRACTION
OPERATING COST ESCALATION RATE	0.000	FRACTION

PRICES AND COSTS		LOW	MOST-LIKELY	HIGH
OIL PRICE	\$/BBL	16.00	20.00	24.00
GAS PRICE	\$/MCF	2.67	3.33	4.00
FIXED OPERATING COST PER PATTERN	\$/YR	33313.	41642.	49970.
VARIABLE OPERATING COST	\$/BBL	0.040	0.050	0.060
WELL WORKOVER COST PER PATTERN	\$/YR		12013.	
PROD WATER TREATING/DISPOSAL COST ...	\$/BBL		0.030	

NOTE.. -PATTERN- HERE ALWAYS REFERS TO THE PRE-INFILL FULL 5-SPOT PATTERN

0 ANNUAL PATTERN AND PROJECT VOLUMES PRODUCED

PROJECT LIFE IS 40 YEARS
PROJECT INITIATED AT 17.50 YEARS OF NON-INFILL PROJECT

YEAR	OIL, MSTB	GAS, MMSCF	PATTERN WATER, MSTB	YEAR-END WTR-CUT	INJ WTR, MSTB	PATTERNS INITIATD	PATTERNS TOTAL	PROJECT OIL, MSTB	GAS, MMSCF	WATER, MSTB
1	44.0	14.5	89.8	0.6719	146.1	6.	6.	264.3	87.2	538.8
2	40.9	13.5	93.7	0.7218	146.1	0.	6.	245.6	81.1	562.2
3	35.2	11.6	101.0	0.7552	146.1	0.	6.	211.4	69.8	606.1
4	31.7	10.5	105.6	0.7797	146.1	0.	6.	190.1	62.7	633.3
5	29.0	9.6	109.0	0.7981	146.1	0.	6.	173.8	57.4	654.2
6	26.8	8.9	111.7	0.8128	146.1	0.	6.	161.0	53.1	670.5
7	25.1	8.3	113.9	0.8243	146.1	0.	6.	150.8	49.8	683.5
8	23.7	7.8	115.7	0.8340	146.1	0.	6.	142.4	47.0	694.3
9	22.6	7.4	117.2	0.8420	146.1	0.	6.	135.3	44.7	703.3
10	21.5	7.1	118.5	0.8494	146.1	0.	6.	129.2	42.6	711.0
11	20.6	6.8	119.7	0.8556	146.1	0.	6.	123.9	40.9	718.0
12	19.9	6.6	120.7	0.8612	146.1	0.	6.	119.1	39.3	724.1
13	19.1	6.3	121.6	0.8662	146.1	0.	6.	114.9	37.9	729.7
14	18.5	6.1	122.5	0.8712	146.1	0.	6.	110.8	36.6	734.8
15	17.9	5.9	123.2	0.8755	146.1	0.	6.	107.2	35.4	739.5
16	17.3	5.7	124.0	0.8794	146.1	0.	6.	103.7	34.2	743.8
17	16.8	5.5	124.6	0.8831	146.1	0.	6.	100.6	33.2	747.9
18	16.3	5.4	125.3	0.8866	146.1	0.	6.	97.6	32.2	751.7
19	15.8	5.2	125.9	0.8900	146.1	0.	6.	94.8	31.3	755.2
20	15.4	5.1	126.4	0.8930	146.1	0.	6.	92.2	30.4	758.5
21	15.0	4.9	127.0	0.8959	146.1	0.	6.	89.7	29.6	761.8
22	14.6	4.8	127.5	0.8987	146.1	0.	6.	87.4	28.8	764.8
23	14.2	4.7	128.0	0.9014	146.1	0.	6.	85.1	28.1	767.7
24	13.8	4.6	128.4	0.9038	146.1	0.	6.	83.1	27.4	770.4
25	13.5	4.5	128.8	0.9063	146.1	0.	6.	81.0	26.7	772.9
26	13.2	4.3	129.2	0.9085	146.1	0.	6.	79.0	26.1	775.4
27	12.9	4.2	129.7	0.9106	146.1	0.	6.	77.2	25.5	778.0
28	12.6	4.1	130.1	0.9129	146.1	0.	6.	75.3	24.9	780.3
29	12.3	4.1	130.4	0.9148	146.1	0.	6.	73.7	24.3	782.6

30	12.0	4.0	130.8	0.9168	146.1	0.	6.	72.0	23.8	784.7
31	11.7	3.9	131.1	0.9189	146.1	0.	6.	70.3	23.2	786.8
32	11.4	3.8	131.5	0.9207	146.1	0.	6.	68.7	22.7	788.9
33	11.2	3.7	131.8	0.9225	146.1	0.	6.	67.1	22.1	791.0
34	10.9	3.6	132.1	0.9244	146.1	0.	6.	65.6	21.7	792.9
35	10.7	3.5	132.5	0.9257	146.1	0.	6.	64.2	21.2	794.8
36	10.5	3.5	132.8	0.9276	146.1	0.	6.	62.8	20.7	796.6
37	10.2	3.4	133.0	0.9291	146.1	0.	6.	61.4	20.3	798.3
38	10.0	3.3	133.3	0.9307	146.1	0.	6.	60.2	19.9	799.9
39	9.8	3.2	133.6	0.9320	146.1	0.	6.	59.0	19.5	801.5
40	9.6	3.2	133.8	0.9335	146.1	0.	6.	57.8	19.1	803.0

MAXIMUM INJECTION RATE IS 2.402 MBBL/D

MAJOR CAPITAL COSTS

INJECTOR DRILLING COST	0.	\$/WELL
PRODUCER EQUIPMENT COST	128487.	\$/WELL
COST TO UPGRADE SECONDARY PROD	0.	\$/WELL
COST TO CONVERT PROD TO INJ	48050.	\$/WELL
COST TO UPGRADE TO SEC. OPERATIONS ..	30297.	\$/WELL
CAPACITY OF WATER INJ PLANT	0.9	MMB/YR
CAPITAL FOR WATER INJ PLANT	0.0	M\$

PROJECT CAPITAL SCHEDULE - MOST LIKELY

YEAR	--- PATTERN \$ ---		PATTERNS INITIATD	--- PROJECT M\$ ---	
	TANGIBLE	INTANGBL		TANGIBLE	INTANGBL
1	75550.1	963365.7	6.	453.	5780.
2	0.0	0.0	0.	0.	0.
3	0.0	0.0	0.	0.	0.
4	0.0	0.0	0.	0.	0.
5	0.0	0.0	0.	0.	0.
6	0.0	0.0	0.	0.	0.
7	0.0	0.0	0.	0.	0.
8	0.0	0.0	0.	0.	0.
9	0.0	0.0	0.	0.	0.
10	0.0	0.0	0.	0.	0.
11	0.0	0.0	0.	0.	0.
12	0.0	0.0	0.	0.	0.
13	0.0	0.0	0.	0.	0.
14	0.0	0.0	0.	0.	0.
15	0.0	0.0	0.	0.	0.
16	0.0	0.0	0.	0.	0.
17	0.0	0.0	0.	0.	0.
18	0.0	0.0	0.	0.	0.
19	0.0	0.0	0.	0.	0.
20	0.0	0.0	0.	0.	0.
21	0.0	0.0	0.	0.	0.
22	0.0	0.0	0.	0.	0.
23	0.0	0.0	0.	0.	0.

24	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25	0.0	0.0	0.0	0.0	0.0	0.0	0.0
26	0.0	0.0	0.0	0.0	0.0	0.0	0.0
27	0.0	0.0	0.0	0.0	0.0	0.0	0.0
28	0.0	0.0	0.0	0.0	0.0	0.0	0.0
29	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30	0.0	0.0	0.0	0.0	0.0	0.0	0.0
31	0.0	0.0	0.0	0.0	0.0	0.0	0.0
32	0.0	0.0	0.0	0.0	0.0	0.0	0.0
33	0.0	0.0	0.0	0.0	0.0	0.0	0.0
34	0.0	0.0	0.0	0.0	0.0	0.0	0.0
35	0.0	0.0	0.0	0.0	0.0	0.0	0.0
36	0.0	0.0	0.0	0.0	0.0	0.0	0.0
37	0.0	0.0	0.0	0.0	0.0	0.0	0.0
38	0.0	0.0	0.0	0.0	0.0	0.0	0.0
39	0.0	0.0	0.0	0.0	0.0	0.0	0.0
40	0.0	0.0	0.0	0.0	0.0	0.0	0.0

PROJECT MEAN VALUES - ESCALATED

YEAR	OIL PRICE \$/BBL	GAS PRICE \$/MCF	TANGIBLE CAPITAL M\$/YR	INTANGIBLE CAPITAL M\$/YR	FIXED OPN COST M\$/YR	VARIABLE OPN COST \$/BBL	WELL WORKOVER M\$/YR	WATER TREATING \$/BBL
1	20.00	3.33	453.	5780.	250.	0.050	72.	0.030
2	20.00	3.33	0.	0.	250.	0.050	72.	0.030
3	20.00	3.33	0.	0.	250.	0.050	72.	0.030
4	20.00	3.33	0.	0.	250.	0.050	72.	0.030
5	20.00	3.33	0.	0.	250.	0.050	72.	0.030
6	20.00	3.33	0.	0.	250.	0.050	72.	0.030
7	20.00	3.33	0.	0.	250.	0.050	72.	0.030
8	20.00	3.33	0.	0.	250.	0.050	72.	0.030
9	20.00	3.33	0.	0.	250.	0.050	72.	0.030
10	20.00	3.33	0.	0.	250.	0.050	72.	0.030
11	20.00	3.33	0.	0.	250.	0.050	72.	0.030
12	20.00	3.33	0.	0.	250.	0.050	72.	0.030
13	20.00	3.33	0.	0.	250.	0.050	72.	0.030
14	20.00	3.33	0.	0.	250.	0.050	72.	0.030
15	20.00	3.33	0.	0.	250.	0.050	72.	0.030
16	20.00	3.33	0.	0.	250.	0.050	72.	0.030
17	20.00	3.33	0.	0.	250.	0.050	72.	0.030
18	20.00	3.33	0.	0.	250.	0.050	72.	0.030
19	20.00	3.33	0.	0.	250.	0.050	72.	0.030
20	20.00	3.33	0.	0.	250.	0.050	72.	0.030
21	20.00	3.33	0.	0.	250.	0.050	72.	0.030
22	20.00	3.33	0.	0.	250.	0.050	72.	0.030
23	20.00	3.33	0.	0.	250.	0.050	72.	0.030
24	20.00	3.33	0.	0.	250.	0.050	72.	0.030
25	20.00	3.33	0.	0.	250.	0.050	72.	0.030
26	20.00	3.33	0.	0.	250.	0.050	72.	0.030
27	20.00	3.33	0.	0.	250.	0.050	72.	0.030
28	20.00	3.33	0.	0.	250.	0.050	72.	0.030
29	20.00	3.33	0.	0.	250.	0.050	72.	0.030
30	20.00	3.33	0.	0.	250.	0.050	72.	0.030

31	20.00	3.33	0.	0.	250.	0.050	72.	0.030
32	20.00	3.33	0.	0.	250.	0.050	72.	0.030
33	20.00	3.33	0.	0.	250.	0.050	72.	0.030
34	20.00	3.33	0.	0.	250.	0.050	72.	0.030
35	20.00	3.33	0.	0.	250.	0.050	72.	0.030
36	20.00	3.33	0.	0.	250.	0.050	72.	0.030
37	20.00	3.33	0.	0.	250.	0.050	72.	0.030
38	20.00	3.33	0.	0.	250.	0.050	72.	0.030
39	20.00	3.33	0.	0.	250.	0.050	72.	0.030
40	20.00	3.33	0.	0.	250.	0.050	72.	0.030

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

[illegible]

ANNUAL NET TAXABLE INCOME, MM\$	-2.27	3.51	2.95	2.60	2.34	2.22	2.06	1.92	1.80	1.70
ANNUAL FEDERAL INCOME TAX, MM\$	-1.09	1.61	1.36	1.20	1.08	1.02	0.95	0.88	0.83	0.78
ANNUAL AFTER TAX CASH FLOW, MM\$	-1.54	1.99	1.68	1.50	1.35	1.20	1.11	1.04	0.97	0.92
CUM CASH FLOW AFTER TAXES, MM\$	-1.54	0.45	2.13	3.63	4.98	6.18	7.29	8.33	9.30	10.22

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	11 2021.	12 2022.	13 2023.	14 2024.	15 2025.	16 2026.	17 2027.	18 2028.	19 2029.	20 2030.
ANNUAL OIL PRODUCTION, MSTB	123.87	119.14	114.85	110.78	107.15	103.68	100.58	97.64	94.82	92.24
ANNUAL GAS PRODUCTION, MMSCF	40.88	39.32	37.90	36.56	35.36	34.22	33.19	32.22	31.29	30.44
ANNUAL WATER PRODUCTION, MSTB	718.	724.	730.	735.	739.	744.	748.	752.	755.	759.
OIL PRODUCTION RATE, STB/D	339.	326.	315.	304.	294.	284.	276.	267.	260.	253.
GAS PRODUCTION RATE, MSCF/D	112.	108.	104.	100.	97.	94.	91.	88.	86.	83.
WATER PRODUCTION RATE, STB/D	1967.	1984.	1999.	2013.	2026.	2038.	2049.	2060.	2069.	2078.
NET OIL SOLD (LESS ROYALTY), MSTB ...	108.39	104.25	100.50	96.93	93.76	90.72	88.01	85.43	82.96	80.71
NET GAS SOLD (LESS ROYALTY), MMSCF ...	35.77	34.40	33.16	31.99	30.94	29.94	29.04	28.19	27.38	26.63
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	2.48	2.38	2.30	2.22	2.14	2.07	2.01	1.95	1.90	1.84
ANNUAL GROSS GAS SALES, MM\$	0.14	0.13	0.13	0.12	0.12	0.11	0.11	0.11	0.10	0.10
ANNUAL TOTAL GROSS SALES, MM\$	2.61	2.51	2.42	2.34	2.26	2.19	2.12	2.06	2.00	1.95
ANNUAL ROYALTY, MM\$	0.33	0.31	0.30	0.29	0.28	0.27	0.27	0.26	0.25	0.24
ANNUAL NET SALES, MM\$	2.29	2.20	2.12	2.05	1.98	1.91	1.86	1.80	1.75	1.70
ANNUAL SEVERANCE TAX, MM\$	0.18	0.18	0.17	0.16	0.16	0.15	0.15	0.14	0.14	0.14
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.60	0.60	0.59	0.58	0.58	0.57	0.57	0.56	0.56	0.56
ANNUAL NET OPERATING INCOME, MM\$	1.68	1.60	1.53	1.46	1.40	1.34	1.29	1.24	1.19	1.15
CUM NET OPERATING INCOME, MM\$	27.81	29.41	30.94	32.41	33.81	35.15	36.44	37.68	38.87	40.02
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	21.58	23.18	24.71	26.17	27.57	28.92	30.20	31.44	32.63	33.78
BASE PRICE OF OIL FOR WPT, \$/BBL	45.38	48.56	51.96	55.60	59.49	63.65	68.11	72.87	77.98	83.43
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.07	0.06	0.06	0.06	0.06	0.05	0.05	0.05	0.05	0.05
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	1.62	1.54	1.47	1.40	1.34	1.29	1.24	1.19	1.14	1.10
ANNUAL FEDERAL INCOME TAX, MM\$	0.74	0.71	0.68	0.65	0.62	0.59	0.57	0.55	0.53	0.51
ANNUAL AFTER TAX CASH FLOW, MM\$	0.87	0.83	0.79	0.76	0.73	0.70	0.67	0.64	0.62	0.59
CUM CASH FLOW AFTER TAXES, MM\$	11.10	11.93	12.72	13.48	14.20	14.90	15.57	16.21	16.83	17.42

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	21 2031.	22 2032.	23 2033.	24 2034.	25 2035.	26 2036.	27 2037.	28 2038.	29 2039.	30 2040.
ANNUAL OIL PRODUCTION, MSTB	89.75	87.38	85.14	83.06	80.99	79.03	77.18	75.34	73.65	72.00
ANNUAL GAS PRODUCTION, MMSCF	29.62	28.84	28.09	27.41	26.73	26.08	25.47	24.86	24.30	23.76
ANNUAL WATER PRODUCTION, MSTB	762.	765.	768.	770.	773.	775.	778.	780.	783.	785.
OIL PRODUCTION RATE, STB/D	246.	239.	233.	228.	222.	217.	211.	206.	202.	197.
GAS PRODUCTION RATE, MSCF/D	81.	79.	77.	75.	73.	71.	70.	68.	67.	65.
WATER PRODUCTION RATE, STB/D	2087.	2095.	2103.	2111.	2117.	2124.	2132.	2138.	2144.	2150.
NET OIL SOLD (LESS ROYALTY), MSTB ...	78.53	76.46	74.49	72.68	70.86	69.15	67.53	65.92	64.44	63.00
NET GAS SOLD (LESS ROYALTY), MMSCF ...	25.91	25.23	24.58	23.98	23.38	22.82	22.29	21.75	21.27	20.79
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	1.79	1.75	1.70	1.66	1.62	1.58	1.54	1.51	1.47	1.44
ANNUAL GROSS GAS SALES, MM\$	0.10	0.10	0.09	0.09	0.09	0.09	0.08	0.08	0.08	0.08
ANNUAL TOTAL GROSS SALES, MM\$	1.89	1.84	1.80	1.75	1.71	1.67	1.63	1.59	1.55	1.52
ANNUAL ROYALTY, MM\$	0.24	0.23	0.22	0.22	0.21	0.21	0.20	0.20	0.19	0.19
ANNUAL NET SALES, MM\$	1.66	1.61	1.57	1.53	1.50	1.46	1.42	1.39	1.36	1.33
ANNUAL SEVERANCE TAX, MM\$	0.13	0.13	0.13	0.12	0.12	0.12	0.11	0.11	0.11	0.11
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.55	0.55	0.54	0.54	0.54	0.54	0.53	0.53	0.53	0.53
ANNUAL NET OPERATING INCOME, MM\$	1.11	1.07	1.03	0.99	0.96	0.92	0.89	0.86	0.83	0.80
CUM NET OPERATING INCOME, MM\$	41.12	42.19	43.21	44.20	45.16	46.08	46.98	47.84	48.67	49.47
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	34.89	35.95	36.98	37.97	38.93	39.85	40.74	41.60	42.44	43.24
BASE PRICE OF OIL FOR WPT, \$/BBL	89.27	95.52	102.21	109.36	117.02	125.21	133.98	143.35	153.39	164.13
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.03	0.03	0.03
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	1.06	1.02	0.99	0.95	0.92	0.89	0.86	0.83	0.80	0.77
ANNUAL FEDERAL INCOME TAX, MM\$	0.49	0.47	0.45	0.44	0.42	0.41	0.39	0.38	0.37	0.36
ANNUAL AFTER TAX CASH FLOW, MM\$	0.57	0.55	0.53	0.51	0.50	0.48	0.46	0.45	0.43	0.42
CUM CASH FLOW AFTER TAXES, MM\$	18.00	18.55	19.08	19.59	20.09	20.57	21.03	21.48	21.91	22.33

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	31 2041.	32 2042.	33 2043.	34 2044.	35 2045.	36 2046.	37 2047.	38 2048.	39 2049.	40 2050.
ANNUAL OIL PRODUCTION, MSTB	70.32	68.70	67.10	65.61	64.21	62.79	61.45	60.16	59.00	57.76

ANNUAL GAS PRODUCTION, MMSCF	23.20	22.67	22.14	21.65	21.19	20.72	20.28	19.85	19.47	19.06
ANNUAL WATER PRODUCTION, MSTB	787.	789.	791.	793.	795.	797.	798.	800.	801.	803.
OIL PRODUCTION RATE, STB/D	193.	188.	184.	180.	176.	172.	168.	165.	162.	158.
GAS PRODUCTION RATE, MSCF/D	64.	62.	61.	59.	58.	57.	56.	54.	53.	52.
WATER PRODUCTION RATE, STB/D	2156.	2161.	2167.	2172.	2177.	2183.	2187.	2192.	2196.	2200.
NET OIL SOLD (LESS ROYALTY), MSTB ...	61.53	60.11	58.71	57.41	56.18	54.94	53.77	52.64	51.62	50.54
NET GAS SOLD (LESS ROYALTY), MMSCF ...	20.30	19.84	19.38	18.95	18.54	18.13	17.74	17.37	17.03	16.68
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	1.41	1.37	1.34	1.31	1.28	1.26	1.23	1.20	1.18	1.16
ANNUAL GROSS GAS SALES, MM\$	0.08	0.08	0.07	0.07	0.07	0.07	0.07	0.07	0.06	0.06
ANNUAL TOTAL GROSS SALES, MM\$	1.48	1.45	1.42	1.38	1.35	1.32	1.30	1.27	1.24	1.22
ANNUAL ROYALTY, MM\$	0.19	0.18	0.18	0.17	0.17	0.17	0.16	0.16	0.16	0.15
ANNUAL NET SALES, MM\$	1.30	1.27	1.24	1.21	1.19	1.16	1.13	1.11	1.09	1.07
ANNUAL SEVERANCE TAX, MM\$	0.10	0.10	0.10	0.10	0.09	0.09	0.09	0.09	0.09	0.09
ANNUAL FIXED OPERATING COST, MM\$	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL PROD WATER TREATING COST, MM\$...	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
ANNUAL OVERHEAD, MM\$	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
ANNUAL TOTAL OPERATING COST, MM\$	0.52	0.52	0.52	0.52	0.51	0.51	0.51	0.51	0.51	0.50
ANNUAL NET OPERATING INCOME, MM\$	0.78	0.75	0.72	0.70	0.67	0.65	0.62	0.60	0.58	0.56
CUM NET OPERATING INCOME, MM\$	50.25	51.00	51.72	52.41	53.08	53.73	54.36	54.96	55.54	56.11
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	44.01	44.76	45.48	46.18	46.85	47.50	48.12	48.73	49.31	49.87
BASE PRICE OF OIL FOR WPT, \$/BBL	175.61	187.91	201.06	215.14	230.20	246.31	263.55	282.00	301.74	322.86
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.02	0.02
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.74	0.72	0.69	0.67	0.64	0.62	0.60	0.58	0.56	0.54
ANNUAL FEDERAL INCOME TAX, MM\$	0.34	0.33	0.32	0.31	0.30	0.29	0.28	0.27	0.26	0.25
ANNUAL AFTER TAX CASH FLOW, MM\$	0.40	0.39	0.37	0.36	0.35	0.34	0.32	0.31	0.30	0.29
CUM CASH FLOW AFTER TAXES, MM\$	22.73	23.12	23.49	23.85	24.20	24.53	24.86	25.17	25.47	25.76

UNDISCOUNTED MEAN RESULTS

PROJECT ECONOMIC LIFE	40.0	YEARS
TOTAL GROSS SALES	90.923	MM\$
TOTAL NET SALES	79.557	MM\$
TOTAL SEVERANCE TAX	6.365	MM\$
TOTAL FIXED OPERATING COST	9.994	MM\$
TOTAL VARIABLE OPERATING COST	0.215	MM\$
TOTAL WELL WORKOVER COST	2.883	MM\$
TOTAL PROD WATER TREATING COST	0.887	MM\$
TOTAL OVERHEAD	3.108	MM\$
TOTAL OPERATING COST	23.451	MM\$

TOTAL WORKING CAPITAL	0.000	MM\$
TOTAL TANGIBLE CAPITAL	0.453	MM\$
TOTAL INTANGIBLE CAPITAL	5.780	MM\$
TOTAL CAPITAL INVESTMENT	6.233	MM\$
TOTAL DEBT INTEREST EXPENSE	0.000	MM\$
TOTAL PROJECT EXPENSE	29.685	MM\$
TOTAL CASH FLOW BEFORE TAX	49.873	MM\$
TOTAL WINDFALL PROFITS TAX	0.000	MM\$
TOTAL STATE INCOME TAX	2.244	MM\$
TOTAL FEDERAL INCOME TAX	21.864	MM\$
TOTAL AFTER TAX CASH FLOW	25.765	MM\$
TOTAL LOAN AMOUNT	0.000	MM\$

0

PROJECT ECONOMIC ANALYSIS

0

		PRESNT	MEAN VALUE CASH FLOW					
		VALUE	BEFORE TAX (MM\$)			AFTER TAX (MM\$)		
	YEAR	FACTOR	ANNUAL	CONST \$	DISCNTD	ANNUAL	CONST \$	DISCNTD
1	2011.	1.0000	-2.48	-2.48	-2.48	-1.54	-1.54	-1.54
2	2012.	0.8658	1.27	1.09	0.77	0.45	0.35	0.18
3	2013.	0.7496	4.44	3.97	3.15	2.13	1.88	1.44
4	2014.	0.6490	7.25	6.39	4.97	3.63	3.17	2.41
5	2015.	0.5619	9.78	8.48	6.39	4.98	4.29	3.17
6	2016.	0.4865	12.10	10.29	7.52	6.18	5.23	3.76
7	2017.	0.4212	14.24	11.89	8.42	7.29	6.05	4.23
8	2018.	0.3647	16.24	13.31	9.15	8.33	6.79	4.60
9	2019.	0.3158	18.12	14.58	9.74	9.30	7.45	4.91
10	2020.	0.2734	19.89	15.73	10.23	10.22	8.04	5.16
11	2021.	0.2367	21.58	16.76	10.62	11.10	8.58	5.37
12	2022.	0.2049	23.18	17.70	10.95	11.93	9.07	5.54
13	2023.	0.1774	24.71	18.55	11.23	12.72	9.51	5.68
14	2024.	0.1536	26.17	19.33	11.45	13.48	9.91	5.80
15	2025.	0.1330	27.57	20.03	11.64	14.20	10.28	5.89
16	2026.	0.1152	28.92	20.68	11.79	14.90	10.61	5.97
17	2027.	0.0997	30.20	21.27	11.92	15.57	10.92	6.04
18	2028.	0.0863	31.44	21.81	12.03	16.21	11.20	6.10
19	2029.	0.0747	32.63	22.30	12.12	16.83	11.45	6.14
20	2030.	0.0647	33.78	22.76	12.19	17.42	11.69	6.18
21	2031.	0.0560	34.89	23.18	12.25	18.00	11.91	6.21
22	2032.	0.0485	35.95	23.56	12.30	18.55	12.10	6.24
23	2033.	0.0420	36.98	23.91	12.35	19.08	12.29	6.26
24	2034.	0.0364	37.97	24.23	12.38	19.59	12.45	6.28
25	2035.	0.0315	38.93	24.53	12.41	20.09	12.61	6.30
26	2036.	0.0273	39.85	24.80	12.44	20.57	12.75	6.31
27	2037.	0.0236	40.74	25.05	12.46	21.03	12.88	6.32
28	2038.	0.0204	41.60	25.28	12.48	21.48	13.00	6.33
29	2039.	0.0177	42.44	25.49	12.49	21.91	13.11	6.34
30	2040.	0.0153	43.24	25.69	12.50	22.33	13.21	6.34
31	2041.	0.0133	44.01	25.87	12.51	22.73	13.30	6.35
32	2042.	0.0115	44.76	26.03	12.52	23.12	13.39	6.35
33	2043.	0.0099	45.48	26.19	12.53	23.49	13.47	6.36
34	2044.	0.0086	46.18	26.32	12.53	23.85	13.54	6.36
35	2045.	0.0075	46.85	26.45	12.54	24.20	13.60	6.36

MEAN INVESTMENT EFFICIENCY	2.336
MEAN DCF RATE OF RETURN	53.47 PCNT

* S C I E N T I F I C S O F T W A R E *

* - I N T E R C O M P *

* INFILL DRILLING PREDICTION MODEL *

* (IDPM - RELEASE 1.2.0) *

Economics for Infill over Non-Infill

ECONOMIC DATA

NUMBER OF PROJECT YEARS	40
STATE CODE	NONE
DISTRICT CODE	0
PRINT CONTROL	2 IOUT
FEDERAL INCOME TAX OPTION	0 IFIT
DISCOUNTING METHOD	0 IDISC
DEPRECIATION METHOD	0 IDEP
PROJECT ECONOMIC LIFE METHOD	0 IPLIF
RESERVOIR DEPTH	6300.0 FEET
INJECTORS DRILLED PER PATTERN (WPP1) ..	0.00
PRODUCERS DRILLED PER PATTERN (WPP2) ..	2.00
CONVTD PRIMARY PROD PER PAT (WPP3) ..	0.00
CONVTD PROD TO INJ PER PAT (WPP4) ...	1.00
NO. OF MONTHS WORKING CAPITAL	0.00
PROJECT STARTUP COSTS	0.0 M\$
OIL RATE UNCERTAINTY	0.0010 FRACTION
PERCENT OF CAPITAL BORROWED.....	0 PERCENT

TAXES AND ESCALATION

DISCOUNT RATE	0.100 FRACTION
INFLATION RATE	0.050 FRACTION
ROYALTY RATE	0.125 FRACTION
SEVERANCE TAX RATE	0.080 FRACTION
FEDERAL INCOME TAX RATE	0.460 FRACTION
INVESTMENT TAX CREDIT	0.100 FRACTION
DEPRECIATION TIME (STRAIGHT LINE)...	5.00 YEARS
STATE INCOME TAX RATE	0.040 FRACTION
WINDFALL EXCISE TAX RATE	0.000 FRACTION
WINDFALL PHASE OUT START DATE	1991.
WINDFALL PHASE OUT END DATE	1993.
PROJECT START DATE	1994.
BASE OIL PRICE FOR WINDFALL TAX	23.07 \$/BBL
OIL PRICE ESCALATION RATE	0.000 FRACTION
GAS PRICE ESCALATION RATE	0.000 FRACTION

OPERATING COST ESCALATION RATE 0.000 FRACTION

PRICES AND COSTS		LOW	MOST-LIKELY	HIGH
OIL PRICE	\$/BBL	16.00	20.00	24.00
GAS PRICE	\$/MCF	2.67	3.33	4.00
FIXED OPERATING COST PER PATTERN	\$/YR	33313.	41642.	49970.
VARIABLE OPERATING COST	\$/BBL	0.040	0.050	0.060
WELL WORKOVER COST PER PATTERN	\$/YR		12013.	
PROD WATER TREATING/DISPOSAL COST ...	\$/BBL		0.030	

NOTE.. -PATTERN- HERE ALWAYS REFERS TO THE PRE-INFILL FULL 5-SPOT PATTERN

0 ANNUAL PATTERN AND PROJECT VOLUMES PRODUCED

PROJECT LIFE IS 40 YEARS
PROJECT INITIATED AT 17.50 YEARS OF NON-INFILL PROJECT

YEAR	OIL, MSTB	GAS, MMSCF	PATTERN WATER, MSTB	YEAR-END WTR-CUT	INJ WTR, MSTB	PATTERNS INITIATED	PATTERNS TOTAL	PROJECT OIL, MSTB	GAS, MMSCF	WATER, MSTB
1	27.5	9.1	38.3	0.6754	73.1	6.	6.	165.0	54.4	229.6
2	25.0	8.3	41.2	0.7218	73.1	0.	6.	150.3	49.6	247.1
3	20.0	6.6	47.8	0.7553	73.1	0.	6.	119.8	39.5	286.5
4	17.0	5.6	51.5	0.7799	73.1	0.	6.	101.8	33.6	309.0
5	14.8	4.9	54.3	0.7982	73.1	0.	6.	88.5	29.2	325.7
6	13.1	4.3	56.4	0.8127	73.1	0.	6.	78.6	25.9	338.3
7	11.9	3.9	57.9	0.8243	73.1	0.	6.	71.1	23.5	347.7
8	10.9	3.6	59.2	0.8339	73.1	0.	6.	65.3	21.6	355.4
9	10.1	3.3	60.2	0.8419	73.1	0.	6.	60.6	20.0	361.1
10	9.4	3.1	61.0	0.8495	73.1	0.	6.	56.5	18.6	366.2
11	8.9	2.9	61.7	0.8557	73.1	0.	6.	53.4	17.6	370.5
12	8.4	2.8	62.4	0.8614	73.1	0.	6.	50.5	16.7	374.1
13	8.0	2.6	62.9	0.8662	73.1	0.	6.	48.1	15.9	377.2
14	7.6	2.5	63.3	0.8710	73.1	0.	6.	45.7	15.1	379.9
15	7.3	2.4	63.7	0.8755	73.1	0.	6.	43.8	14.4	382.4
16	7.0	2.3	64.1	0.8794	73.1	0.	6.	41.9	13.8	384.6
17	6.7	2.2	64.4	0.8832	73.1	0.	6.	40.3	13.3	386.6
18	6.4	2.1	64.8	0.8866	73.1	0.	6.	38.6	12.8	388.6
19	6.2	2.0	65.1	0.8898	73.1	0.	6.	37.3	12.3	390.3
20	6.0	2.0	65.3	0.8932	73.1	0.	6.	35.9	11.9	392.0
21	5.8	1.9	65.6	0.8959	73.1	0.	6.	34.9	11.5	393.7
22	5.6	1.9	65.8	0.8987	73.1	0.	6.	33.8	11.1	395.0
23	5.5	1.8	66.1	0.9014	73.1	0.	6.	32.7	10.8	396.5
24	5.3	1.8	66.3	0.9038	73.1	0.	6.	31.9	10.5	397.8
25	5.1	1.7	66.5	0.9063	73.1	0.	6.	30.8	10.2	399.1
26	5.0	1.6	66.6	0.9084	73.1	0.	6.	30.0	9.9	399.8
27	4.9	1.6	66.9	0.9111	73.1	0.	6.	29.1	9.6	401.4
28	4.7	1.6	67.1	0.9132	73.1	0.	6.	28.4	9.4	402.4

29	4.6	1.5	67.3	0.9151	73.1	0.	6.	27.6	9.1	403.5
30	4.5	1.5	67.4	0.9169	73.1	0.	6.	26.8	8.9	404.3
31	4.3	1.4	67.5	0.9188	73.1	0.	6.	26.0	8.6	405.2
32	4.2	1.4	67.7	0.9210	73.1	0.	6.	25.2	8.3	406.2
33	4.1	1.3	67.9	0.9225	73.1	0.	6.	24.5	8.1	407.3
34	4.0	1.3	68.0	0.9243	73.1	0.	6.	23.8	7.9	408.2
35	3.9	1.3	68.2	0.9257	73.1	0.	6.	23.1	7.6	409.2
36	3.8	1.2	68.3	0.9277	73.1	0.	6.	22.5	7.4	409.9
37	3.6	1.2	68.4	0.9291	73.1	0.	6.	21.9	7.2	410.6
38	3.5	1.2	68.6	0.9306	73.1	0.	6.	21.3	7.0	411.3
39	3.5	1.1	68.6	0.9318	73.1	0.	6.	20.8	6.9	411.7
40	3.4	1.1	68.7	0.9331	73.1	0.	6.	20.3	6.7	412.4

MAJOR CAPITAL COSTS

INJECTOR DRILLING COST	0.	\$/WELL
PRODUCER EQUIPMENT COST	128487.	\$/WELL
COST TO UPGRADE SECONDARY PROD	0.	\$/WELL
COST TO CONVERT PROD TO INJ	48050.	\$/WELL
COST TO UPGRADE TO SEC. OPERATIONS ..	30297.	\$/WELL
CAPACITY OF WATER INJ PLANT	0.4	MMB/YR
CAPITAL FOR WATER INJ PLANT	0.0	M\$

PROJECT CAPITAL SCHEDULE - MOST LIKELY

YEAR	--- PATTERN \$ ---		PATTERNS INITIATD	--- PROJECT M\$ ---	
	TANGIBLE	INTANGBL		TANGIBLE	INTANGBL
1	75550.1	963365.7	6.	453.	5780.
2	0.0	0.0	0.	0.	0.
3	0.0	0.0	0.	0.	0.
4	0.0	0.0	0.	0.	0.
5	0.0	0.0	0.	0.	0.
6	0.0	0.0	0.	0.	0.
7	0.0	0.0	0.	0.	0.
8	0.0	0.0	0.	0.	0.
9	0.0	0.0	0.	0.	0.
10	0.0	0.0	0.	0.	0.
11	0.0	0.0	0.	0.	0.
12	0.0	0.0	0.	0.	0.
13	0.0	0.0	0.	0.	0.
14	0.0	0.0	0.	0.	0.
15	0.0	0.0	0.	0.	0.
16	0.0	0.0	0.	0.	0.
17	0.0	0.0	0.	0.	0.
18	0.0	0.0	0.	0.	0.
19	0.0	0.0	0.	0.	0.
20	0.0	0.0	0.	0.	0.
21	0.0	0.0	0.	0.	0.
22	0.0	0.0	0.	0.	0.
23	0.0	0.0	0.	0.	0.
24	0.0	0.0	0.	0.	0.

YEAR	OIL PRICE \$/BBL	GAS PRICE \$/MCF	TANGIBLE CAPITAL M\$/YR	INTANGIBLE CAPITAL M\$/YR	FIXED OPN COST M\$/YR	VARIABLE OPN COST \$/BBL	WELL WORKOVER M\$/YR	WATER TREATING \$/BBL
25	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.030
26	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
27	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
28	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
29	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
30	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
31	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
32	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
33	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
34	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
35	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
36	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
37	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
38	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
39	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
40	0.0	0.0	0.0	0.0	0.0	0.050	0.0	0.030
PROJECT MEAN VALUES - ESCALATED								
1	20.00	3.33	453.	5780.	0.	0.050	0.	0.030
2	20.00	3.33	0.	0.	0.	0.050	0.	0.030
3	20.00	3.33	0.	0.	0.	0.050	0.	0.030
4	20.00	3.33	0.	0.	0.	0.050	0.	0.030
5	20.00	3.33	0.	0.	0.	0.050	0.	0.030
6	20.00	3.33	0.	0.	0.	0.050	0.	0.030
7	20.00	3.33	0.	0.	0.	0.050	0.	0.030
8	20.00	3.33	0.	0.	0.	0.050	0.	0.030
9	20.00	3.33	0.	0.	0.	0.050	0.	0.030
10	20.00	3.33	0.	0.	0.	0.050	0.	0.030
11	20.00	3.33	0.	0.	0.	0.050	0.	0.030
12	20.00	3.33	0.	0.	0.	0.050	0.	0.030
13	20.00	3.33	0.	0.	0.	0.050	0.	0.030
14	20.00	3.33	0.	0.	0.	0.050	0.	0.030
15	20.00	3.33	0.	0.	0.	0.050	0.	0.030
16	20.00	3.33	0.	0.	0.	0.050	0.	0.030
17	20.00	3.33	0.	0.	0.	0.050	0.	0.030
18	20.00	3.33	0.	0.	0.	0.050	0.	0.030
19	20.00	3.33	0.	0.	0.	0.050	0.	0.030
20	20.00	3.33	0.	0.	0.	0.050	0.	0.030
21	20.00	3.33	0.	0.	0.	0.050	0.	0.030
22	20.00	3.33	0.	0.	0.	0.050	0.	0.030
23	20.00	3.33	0.	0.	0.	0.050	0.	0.030
24	20.00	3.33	0.	0.	0.	0.050	0.	0.030
25	20.00	3.33	0.	0.	0.	0.050	0.	0.030
26	20.00	3.33	0.	0.	0.	0.050	0.	0.030
27	20.00	3.33	0.	0.	0.	0.050	0.	0.030
28	20.00	3.33	0.	0.	0.	0.050	0.	0.030
29	20.00	3.33	0.	0.	0.	0.050	0.	0.030
30	20.00	3.33	0.	0.	0.	0.050	0.	0.030
31	20.00	3.33	0.	0.	0.	0.050	0.	0.030

32	20.00	3.33	0.	0.	0.	0.050	0.	0.030
33	20.00	3.33	0.	0.	0.	0.050	0.	0.030
34	20.00	3.33	0.	0.	0.	0.050	0.	0.030
35	20.00	3.33	0.	0.	0.	0.050	0.	0.030
36	20.00	3.33	0.	0.	0.	0.050	0.	0.030
37	20.00	3.33	0.	0.	0.	0.050	0.	0.030
38	20.00	3.33	0.	0.	0.	0.050	0.	0.030
39	20.00	3.33	0.	0.	0.	0.050	0.	0.030
40	20.00	3.33	0.	0.	0.	0.050	0.	0.030

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	1 2011.	2 2012.	3 2013.	4 2014.	5 2015.	6 2016.	7 2017.	8 2018.	9 2019.	10 2020.
ANNUAL OIL PRODUCTION, MSTB	165.00	150.27	119.75	101.84	88.53	78.57	71.12	65.31	60.56	56.50
ANNUAL GAS PRODUCTION, MMSCF	54.45	49.59	39.52	33.61	29.21	25.93	23.47	21.55	19.99	18.65
ANNUAL WATER PRODUCTION, MSTB	230.	247.	287.	309.	326.	338.	348.	355.	361.	366.
OIL PRODUCTION RATE, STB/D	452.	412.	328.	279.	243.	215.	195.	179.	166.	155.
GAS PRODUCTION RATE, MSCF/D	149.	136.	108.	92.	80.	71.	64.	59.	55.	51.
WATER PRODUCTION RATE, STB/D	629.	677.	785.	847.	892.	927.	953.	974.	989.	1003.
NET OIL SOLD (LESS ROYALTY), MSTB ...	144.37	131.49	104.79	89.11	77.46	68.75	62.23	57.15	52.99	49.44
NET GAS SOLD (LESS ROYALTY), MMSCF ...	47.64	43.39	34.58	29.41	25.56	22.69	20.54	18.86	17.49	16.31
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	3.30	3.01	2.40	2.04	1.77	1.57	1.42	1.31	1.21	1.13
ANNUAL GROSS GAS SALES, MM\$	0.18	0.17	0.13	0.11	0.10	0.09	0.08	0.07	0.07	0.06
ANNUAL TOTAL GROSS SALES, MM\$	3.48	3.17	2.53	2.15	1.87	1.66	1.50	1.38	1.28	1.19
ANNUAL ROYALTY, MM\$	0.44	0.40	0.32	0.27	0.23	0.21	0.19	0.17	0.16	0.15
ANNUAL NET SALES, MM\$	3.05	2.77	2.21	1.88	1.63	1.45	1.31	1.21	1.12	1.04
ANNUAL SEVERANCE TAX, MM\$	0.24	0.22	0.18	0.15	0.13	0.12	0.11	0.10	0.09	0.08
ANNUAL FIXED OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL VARIABLE OPERATING COST, MM\$	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.31	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TOTAL OPERATING COST, MM\$	0.57	0.24	0.19	0.17	0.15	0.13	0.12	0.11	0.11	0.10
ANNUAL NET OPERATING INCOME, MM\$	2.47	2.53	2.02	1.71	1.49	1.32	1.19	1.09	1.01	0.94
CUM NET OPERATING INCOME, MM\$	2.47	5.01	7.02	8.74	10.22	11.54	12.73	13.82	14.84	15.78
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	5.78	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	-3.76	-1.23	0.79	2.50	3.99	5.31	6.50	7.59	8.60	9.55
BASE PRICE OF OIL FOR WPT, \$/BBL	23.07	24.68	26.41	28.26	30.24	32.36	34.62	37.05	39.64	42.41
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.10	0.10	0.08	0.07	0.06	0.05	0.05	0.04	0.04	0.04
ANNUAL INTANGIBLES AND DEPR, MM\$	5.87	0.09	0.09	0.09	0.09	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	-3.50	2.34	1.85	1.55	1.34	1.26	1.14	1.05	0.97	0.91

ANNUAL FEDERAL INCOME TAX, MM\$	-1.65	1.08	0.85	0.71	0.61	0.58	0.53	0.48	0.45	0.42
ANNUAL AFTER TAX CASH FLOW, MM\$	-2.21	1.36	1.09	0.93	0.81	0.68	0.62	0.57	0.52	0.49
CUM CASH FLOW AFTER TAXES, MM\$	-2.21	-0.85	0.24	1.17	1.98	2.66	3.28	3.85	4.37	4.86

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	11 2021.	12 2022.	13 2023.	14 2024.	15 2025.	16 2026.	17 2027.	18 2028.	19 2029.	20 2030.
ANNUAL OIL PRODUCTION, MSTB	53.38	50.53	48.10	45.72	43.76	41.88	40.26	38.65	37.26	35.94
ANNUAL GAS PRODUCTION, MMSCF	17.62	16.67	15.87	15.09	14.44	13.82	13.29	12.75	12.30	11.86
ANNUAL WATER PRODUCTION, MSTB	370.	374.	377.	380.	382.	385.	387.	389.	390.	392.
OIL PRODUCTION RATE, STB/D	146.	138.	132.	125.	120.	115.	110.	106.	102.	98.
GAS PRODUCTION RATE, MSCF/D	48.	46.	43.	41.	40.	38.	36.	35.	34.	32.
WATER PRODUCTION RATE, STB/D	1015.	1025.	1033.	1041.	1048.	1054.	1059.	1065.	1069.	1074.
NET OIL SOLD (LESS ROYALTY), MSTB ...	46.71	44.21	42.09	40.01	38.29	36.64	35.23	33.82	32.60	31.45
NET GAS SOLD (LESS ROYALTY), MMSCF ...	15.41	14.59	13.89	13.20	12.63	12.09	11.63	11.16	10.76	10.38
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	1.07	1.01	0.96	0.91	0.88	0.84	0.81	0.77	0.75	0.72
ANNUAL GROSS GAS SALES, MM\$	0.06	0.06	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04
ANNUAL TOTAL GROSS SALES, MM\$	1.13	1.07	1.01	0.96	0.92	0.88	0.85	0.82	0.79	0.76
ANNUAL ROYALTY, MM\$	0.14	0.13	0.13	0.12	0.12	0.11	0.11	0.10	0.10	0.09
ANNUAL NET SALES, MM\$	0.99	0.93	0.89	0.84	0.81	0.77	0.74	0.71	0.69	0.66
ANNUAL SEVERANCE TAX, MM\$	0.08	0.07	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.05
ANNUAL FIXED OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TOTAL OPERATING COST, MM\$	0.10	0.09	0.09	0.08	0.08	0.08	0.08	0.07	0.07	0.07
ANNUAL NET OPERATING INCOME, MM\$	0.89	0.84	0.80	0.76	0.73	0.69	0.67	0.64	0.62	0.59
CUM NET OPERATING INCOME, MM\$	16.67	17.51	18.31	19.07	19.80	20.49	21.16	21.80	22.42	23.01
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	10.44	11.28	12.08	12.84	13.56	14.26	14.93	15.57	16.18	16.78
BASE PRICE OF OIL FOR WPT, \$/BBL	45.38	48.56	51.96	55.60	59.49	63.65	68.11	72.87	77.98	83.43
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.04	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.85	0.81	0.77	0.73	0.70	0.67	0.64	0.61	0.59	0.57
ANNUAL FEDERAL INCOME TAX, MM\$	0.39	0.37	0.35	0.34	0.32	0.31	0.29	0.28	0.27	0.26
ANNUAL AFTER TAX CASH FLOW, MM\$	0.46	0.44	0.41	0.39	0.38	0.36	0.35	0.33	0.32	0.31
CUM CASH FLOW AFTER TAXES, MM\$	5.32	5.76	6.17	6.57	6.94	7.30	7.65	7.98	8.30	8.61

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	21 2031.	22 2032.	23 2033.	24 2034.	25 2035.	26 2036.	27 2037.	28 2038.	29 2039.	30 2040.
ANNUAL OIL PRODUCTION, MSTB	34.89	33.78	32.74	31.89	30.77	29.98	29.14	28.40	27.59	26.85
ANNUAL GAS PRODUCTION, MMSCF	11.51	11.15	10.80	10.53	10.16	9.89	9.62	9.37	9.11	8.86
ANNUAL WATER PRODUCTION, MSTB	394.	395.	396.	398.	399.	400.	401.	402.	404.	404.
OIL PRODUCTION RATE, STB/D	96.	93.	90.	87.	84.	82.	80.	78.	76.	74.
GAS PRODUCTION RATE, MSCF/D	32.	31.	30.	29.	28.	27.	26.	26.	25.	24.
WATER PRODUCTION RATE, STB/D	1079.	1082.	1086.	1090.	1093.	1095.	1100.	1103.	1106.	1108.
NET OIL SOLD (LESS ROYALTY), MSTB ...	30.53	29.56	28.65	27.91	26.93	26.23	25.50	24.85	24.15	23.49
NET GAS SOLD (LESS ROYALTY), MMSCF ...	10.07	9.75	9.45	9.21	8.89	8.66	8.41	8.20	7.97	7.75
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	0.70	0.68	0.65	0.64	0.62	0.60	0.58	0.57	0.55	0.54
ANNUAL GROSS GAS SALES, MM\$	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.03	0.03	0.03
ANNUAL TOTAL GROSS SALES, MM\$	0.74	0.71	0.69	0.67	0.65	0.63	0.61	0.60	0.58	0.57
ANNUAL ROYALTY, MM\$	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.07	0.07	0.07
ANNUAL NET SALES, MM\$	0.64	0.62	0.60	0.59	0.57	0.55	0.54	0.52	0.51	0.50
ANNUAL SEVERANCE TAX, MM\$	0.05	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04	0.04
ANNUAL FIXED OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TOTAL OPERATING COST, MM\$	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06
ANNUAL NET OPERATING INCOME, MM\$	0.58	0.56	0.54	0.53	0.51	0.49	0.48	0.47	0.45	0.44
CUM NET OPERATING INCOME, MM\$	23.59	24.15	24.69	25.21	25.72	26.21	26.69	27.15	27.61	28.05
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	17.35	17.91	18.45	18.98	19.48	19.98	20.46	20.92	21.37	21.81
BASE PRICE OF OIL FOR WPT, \$/BBL	89.27	95.52	102.21	109.36	117.02	125.21	133.98	143.35	153.39	164.13
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.55	0.54	0.52	0.50	0.49	0.47	0.46	0.45	0.43	0.42
ANNUAL FEDERAL INCOME TAX, MM\$	0.25	0.25	0.24	0.23	0.22	0.22	0.21	0.21	0.20	0.19
ANNUAL AFTER TAX CASH FLOW, MM\$	0.30	0.29	0.28	0.27	0.26	0.26	0.25	0.24	0.23	0.23
CUM CASH FLOW AFTER TAXES, MM\$	8.91	9.20	9.48	9.75	10.01	10.27	10.51	10.76	10.99	11.22

PROJECT ECONOMIC ANALYSIS

OUNDISCOUNTED MEAN VALUES

YEAR ENDING	31 2041.	32 2042.	33 2043.	34 2044.	35 2045.	36 2046.	37 2047.	38 2048.	39 2049.	40 2050.
ANNUAL OIL PRODUCTION, MSTB	26.00	25.24	24.52	23.80	23.12	22.54	21.86	21.27	20.83	20.29
ANNUAL GAS PRODUCTION, MMSCF	8.58	8.33	8.09	7.85	7.63	7.44	7.21	7.02	6.88	6.70

ANNUAL WATER PRODUCTION, MSTB	405.	406.	407.	408.	409.	410.	411.	411.	412.	412.
OIL PRODUCTION RATE, STB/D	71.	69.	67.	65.	63.	62.	60.	58.	57.	56.
GAS PRODUCTION RATE, MSCF/D	24.	23.	22.	22.	21.	20.	20.	19.	19.	18.
WATER PRODUCTION RATE, STB/D	1110.	1113.	1116.	1118.	1121.	1123.	1125.	1127.	1128.	1130.
NET OIL SOLD (LESS ROYALTY), MSTB ...	22.75	22.08	21.46	20.82	20.23	19.72	19.13	18.61	18.23	17.76
NET GAS SOLD (LESS ROYALTY), MMSCF ...	7.51	7.29	7.08	6.87	6.68	6.51	6.31	6.14	6.02	5.86
MEAN PRICE OF OIL, \$/BBL	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00	20.00
MEAN PRICE OF GAS, \$/MCF	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
ANNUAL GROSS OIL SALES, MM\$	0.52	0.50	0.49	0.48	0.46	0.45	0.44	0.43	0.42	0.41
ANNUAL GROSS GAS SALES, MM\$	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.02	0.02	0.02
ANNUAL TOTAL GROSS SALES, MM\$	0.55	0.53	0.52	0.50	0.49	0.48	0.46	0.45	0.44	0.43
ANNUAL ROYALTY, MM\$	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06	0.05	0.05
ANNUAL NET SALES, MM\$	0.48	0.47	0.45	0.44	0.43	0.42	0.40	0.39	0.38	0.37
ANNUAL SEVERANCE TAX, MM\$	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.03	0.03	0.03
ANNUAL FIXED OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL VARIABLE OPERATING COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WELL WORKOVER COST, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL PROD WATER TREATING COST, MM\$...	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
ANNUAL OVERHEAD, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TOTAL OPERATING COST, MM\$	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
ANNUAL NET OPERATING INCOME, MM\$	0.43	0.41	0.40	0.39	0.38	0.37	0.36	0.35	0.34	0.33
CUM NET OPERATING INCOME, MM\$	28.47	28.89	29.29	29.67	30.05	30.42	30.77	31.12	31.46	31.78
ANNUAL WORKING CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL TANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INTANGIBLE CAPITAL, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CUM CASH FLOW BEFORE TAXES, MM\$	22.24	22.65	23.05	23.44	23.82	24.18	24.54	24.88	25.22	25.55
BASE PRICE OF OIL FOR WPT, \$/BBL	175.61	187.91	201.06	215.14	230.20	246.31	263.55	282.00	301.74	322.86
ANNUAL WINDFALL PRICE DIFF, \$/BBL	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL WINDFALL EXCISE TAX, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL STATE INCOME TAX, MM\$	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01
ANNUAL INTANGIBLES AND DEPR, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL INVESTMENT TAX CREDIT, MM\$	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ANNUAL NET TAXABLE INCOME, MM\$	0.41	0.40	0.38	0.37	0.36	0.35	0.34	0.33	0.32	0.32
ANNUAL FEDERAL INCOME TAX, MM\$	0.19	0.18	0.18	0.17	0.17	0.16	0.16	0.15	0.15	0.15
ANNUAL AFTER TAX CASH FLOW, MM\$	0.22	0.21	0.21	0.20	0.20	0.19	0.18	0.18	0.18	0.17
CUM CASH FLOW AFTER TAXES, MM\$	11.44	11.65	11.86	12.06	12.26	12.45	12.63	12.81	12.99	13.16

UNDISCOUNTED MEAN RESULTS

PROJECT ECONOMIC LIFE	40.0	YEARS
TOTAL GROSS SALES	40.688	MM\$
TOTAL NET SALES	35.602	MM\$
TOTAL SEVERANCE TAX	2.848	MM\$
TOTAL FIXED OPERATING COST	0.000	MM\$
TOTAL VARIABLE OPERATING COST	0.096	MM\$
TOTAL WELL WORKOVER COST	0.000	MM\$
TOTAL PROD WATER TREATING COST	0.452	MM\$
TOTAL OVERHEAD	0.421	MM\$
TOTAL OPERATING COST	3.818	MM\$
TOTAL WORKING CAPITAL	0.000	MM\$

TOTAL TANGIBLE CAPITAL	0.453	MM\$
TOTAL INTANGIBLE CAPITAL	5.780	MM\$
TOTAL CAPITAL INVESTMENT	6.233	MM\$
TOTAL DEBT INTEREST EXPENSE	0.000	MM\$
TOTAL PROJECT EXPENSE	10.052	MM\$
TOTAL CASH FLOW BEFORE TAX	25.550	MM\$
TOTAL WINDFALL PROFITS TAX	0.000	MM\$
TOTAL STATE INCOME TAX	1.271	MM\$
TOTAL FEDERAL INCOME TAX	11.123	MM\$
TOTAL AFTER TAX CASH FLOW	13.156	MM\$
TOTAL LOAN AMOUNT	0.000	MM\$

0

PROJECT ECONOMIC ANALYSIS

0

		PRESNT	MEAN VALUE CASH FLOW					
		VALUE	BEFORE TAX (MM\$)			AFTER TAX (MM\$)		
	YEAR	FACTOR	ANNUAL	CONST \$	DISCNTD	ANNUAL	CONST \$	DISCNTD
1	2011.	1.0000	-3.76	-3.76	-3.76	-2.21	-2.21	-2.21
2	2012.	0.8658	-1.23	-1.35	-1.57	-0.85	-0.91	-1.03
3	2013.	0.7496	0.79	0.48	-0.06	0.24	0.07	-0.22
4	2014.	0.6490	2.50	1.96	1.06	1.17	0.87	0.39
5	2015.	0.5619	3.99	3.18	1.89	1.98	1.54	0.84
6	2016.	0.4865	5.31	4.22	2.53	2.66	2.08	1.17
7	2017.	0.4212	6.50	5.11	3.03	3.28	2.54	1.43
8	2018.	0.3647	7.59	5.88	3.43	3.85	2.94	1.64
9	2019.	0.3158	8.60	6.57	3.75	4.37	3.30	1.81
10	2020.	0.2734	9.55	7.17	4.01	4.86	3.61	1.94
11	2021.	0.2367	10.44	7.72	4.22	5.32	3.89	2.05
12	2022.	0.2049	11.28	8.21	4.39	5.76	4.15	2.14
13	2023.	0.1774	12.08	8.66	4.54	6.17	4.38	2.21
14	2024.	0.1536	12.84	9.06	4.65	6.57	4.59	2.27
15	2025.	0.1330	13.56	9.43	4.75	6.94	4.78	2.32
16	2026.	0.1152	14.26	9.76	4.83	7.30	4.95	2.37
17	2027.	0.0997	14.93	10.07	4.90	7.65	5.11	2.40
18	2028.	0.0863	15.57	10.35	4.95	7.98	5.26	2.43
19	2029.	0.0747	16.18	10.60	5.00	8.30	5.39	2.45
20	2030.	0.0647	16.78	10.84	5.04	8.61	5.51	2.47
21	2031.	0.0560	17.35	11.06	5.07	8.91	5.62	2.49
22	2032.	0.0485	17.91	11.26	5.09	9.20	5.73	2.50
23	2033.	0.0420	18.45	11.44	5.12	9.48	5.82	2.51
24	2034.	0.0364	18.98	11.61	5.14	9.75	5.91	2.52
25	2035.	0.0315	19.48	11.77	5.15	10.01	5.99	2.53
26	2036.	0.0273	19.98	11.92	5.17	10.27	6.07	2.54
27	2037.	0.0236	20.46	12.05	5.18	10.51	6.14	2.55
28	2038.	0.0204	20.92	12.17	5.19	10.76	6.20	2.55
29	2039.	0.0177	21.37	12.29	5.19	10.99	6.26	2.55
30	2040.	0.0153	21.81	12.40	5.20	11.22	6.32	2.56
31	2041.	0.0133	22.24	12.50	5.21	11.44	6.37	2.56
32	2042.	0.0115	22.65	12.59	5.21	11.65	6.42	2.56
33	2043.	0.0099	23.05	12.67	5.22	11.86	6.46	2.57
34	2044.	0.0086	23.44	12.75	5.22	12.06	6.50	2.57
35	2045.	0.0075	23.82	12.82	5.22	12.26	6.54	2.57
36	2046.	0.0065	24.18	12.89	5.22	12.45	6.57	2.57

37	2047.	0.0056	24.54	12.95	5.23	12.63	6.60	2.57
38	2048.	0.0048	24.88	13.00	5.23	12.81	6.63	2.57
39	2049.	0.0042	25.22	13.06	5.23	12.99	6.66	2.57
40	2050.	0.0036	25.55	13.11	5.23	13.16	6.69	2.57

*
* S C I E N T I F I C S O F T W A R E *
* - I N T E R C O M P *
*
*
*
* INFILL DRILLING PREDICTION MODEL *
* (IDPM - RELEASE 1.2.0) *
*

Economics for Infill over Non-Infill

0 PRODUCTION SUMMARY

PROJECT ECONOMIC LIFE	40.0	YEARS
CUMULATIVE GROSS OIL SOLD	1928.	MSTB
CUMULATIVE GROSS GAS SOLD	636.	MMSCF
CUMULATIVE NET OIL SOLD	1687.	MSTB
PRESENT VALUE OF NET OIL SOLD	613.	MSTB

0 MEAN RESULTS

PRESENT VALUE OF TOTAL GROSS SALES	14.786	MM\$
PRESENT VALUE OF TOTAL NET SALES	12.938	MM\$
TOTAL SEVERANCE TAX (PV)	1.035	MM\$
TOTAL FIXED OPERATING COST (PV)	0.000	MM\$
TOTAL VARIABLE OPERATING COST (PV)	0.035	MM\$
TOTAL WELL WORKOVER COST (PV)	0.000	MM\$
TOTAL PROD WATER TREATING COST (PV)	0.071	MM\$
TOTAL OVERHEAD (PV)	0.333	MM\$
TOTAL OPERATING COST (PV)	1.474	MM\$
TOTAL WORKING CAPITAL (PV)	0.000	MM\$
TOTAL TANGIBLE CAPITAL INVESTED (PV) ...	0.453	MM\$
TOTAL INTANGIBLE CAPITAL (PV)	5.780	MM\$
TOTAL CAPITAL INVESTMENT (PV)	6.233	MM\$
TOTAL INTEREST EXPENSE (PV)	0.000	MM\$
TOTAL PROJECT EXPENSE (PV)	7.707	MM\$
TOTAL LOAN PRINCIPAL REPAYMENT (PV)	0.000	MM\$
DISCOUNTED COST PER DISC NET OIL	12.569	\$/BBL
DISCOUNTED CASH FLOW BEFORE TAX	5.230	MM\$

0 PROJECT PROFITABILITY (AFTER TAX)

AVERAGE MONETARY DISCOUNT RATE	10.00	PCNT
90 PCNT CONFIDENCE DCF	0.518	MM\$
MEAN DISCOUNTED CASH FLOW	2.573	MM\$
10 PCNT CONFIDENCE DCF	4.982	MM\$
STANDARD DEVIATION OF THE MEAN DCF	1.685	MM\$
MEAN DCF PROFIT TO INVESTMENT RATIO	0.413	P/I
MEAN DCF PROFIT TO EXPENSE RATIO	0.334	P/E
MEAN DCF PROFIT PER DISC NET OIL	4.196	\$/BBL
MEAN INVESTMENT EFFICIENCY	1.573	

MEAN DCF RATE OF RETURN 29.54 PCNT

Economics for Waterflood

P
R
O
J
E
C
T
O
I
L
P
R
E
P
A
R
E
D
.N
M
B
L
P
E
R
Y

Economics for Waterflood

P
A
T
E
R
N
W
A
T
E
R
I
O
R
A
T
I
O

Economics for Waterflood

Economics for Infill Waterflood

Economics for Infill Waterflood

Economics for Infill Waterflood

Economics for Infill over Non-Infill

Economics for Infill over Non-Infill

Economics for Infill over Non-Infill