DOE/ER/40271--T3

DOE/ER/40271--T3

DE93 006065

PROGRESS REPORT

Central Collisions of Heavy Ions

October 1, 1991 to September 31, 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

prepared by

Sun-yiu Fung

Principal Investigator

University of California, Riverside

Riverside CA 92521

DOE Nuclear Science Program

Grant Number DE-FG03-86ER40271

October 1992

MASTER

25

1 Introduction

This report describes the activities of the Heavy Ion Physics Group at the University of California, Riverside from October 1, 1991 to September 30, 1992. During this period, our program focused on particle production at AGS energies, and correlation studies at the Bevalac in nucleus nucleus central collisions. As part of the PHENIX collaboration, we contributed to the Preliminary Conceptual Design Report (pCDR), and worked on a RHIC silicon microstrip detector R&D project.

2 Heavy-ion Collisions Study at AGS energies

We continue our study of heavy-ion collisions at the AGS with a series of experiments, E802/E859/E866. In this period, the E859 completed its production run, collecting data for particle correlation study, strange particle production, and high momentum transfer phenomenon, with the full implementation of a second level particle identification trigger. The E859 along with the E802 collaboration is continuing works on several data analyses, including the intermittency study carried out at Riverside. We have started on the third phase of the particle production study with the newly installed gold beam (E866). We are also planning an upgrade multiplicity detector for the E866 gold beam experiment.

2.1 Results from E802

The Riverside Group has been a part of the BNL E802 collaboration since 1986. This is the first major experiment utilizing the 14.5 GeV/c heavy ion beam at the AGS. Its goal is to study particle production in nucleus nucleus central collisions. The apparatus consists of a large aperture magnetic spectrometer, with segmented Cherenkov counters, scintillation counter arrays, time projection chamber and wire chamber for tracking and particle identification; a smaller aperture gas Cherenkov system tuned to identify higher momentum particles; a lead glass array to measure total neutral energy; a streamer tube array to determine total multiplicity and measure pseudorapidity of emerging particles; and a small total absorption sampling calorimeter to measure the total kinetic energy of the projectile fragments at small forward angles. The data collection for E802 was completed in 1989, and investigations on many aspects of particle production were carried out.

2.1.1 Intermittency analysis for E802

A large concentration of particles in narrow rapidity regions was observed in ultra high energy cosmic ray experiment such as JACEE. The concept of intermittency was applied to this data analysis to understand the underlying physics of multiparticle production. Subsequently, this phenomenon was studied in electron-positron hadron-hadron, hadron-nucleus, and nucleus-nucleus collisions. However, the interpretation and the cause of intermittency is far from clear. In the Brookhaven experiment E-802, Target Multiplicity Array (TMA) can measure particle pseudorapidity η from -1.2 to 3.1 with almost full azimuthal coverage. An intermittency analysis was carried out on these data to study short range multiparticle correlations. Factorial moments for the central collisions between 14.6 A-GeV/c ^{16}O projectiles and targets of Al, Cu and Ag have been calculated with bin size up to $\delta\eta = 0.06$. An intermittency behaviour, power-law growth of moments with decreasing bin size, was seen up to $\delta\eta \sim 0.1$, with stronger effect in lighter target than heavier target. Results from this analysis were presented by Kang in an evening session at the NATO Advanced Study Institute (July 12-21, 1992, Italy). Also a paper has been written for this analysis and will be submitted for publication (Appendix A). Further intermittency studies are planned using such methods as strip correlation integral by P. Carruthers, and higher dimensional analysis. Also feasibility of the intermittency analysis using new data from the gold beam (E866) will be studied.

2.1.2 Forward and transverse energies for Si+Al and Au+Au collisions

A negative correlation was observed between the forward energy measured by the Zero Degree Calorimeter and the transverse energy registered in the Lead Glass Array. The highest transverse energy Au events are associated with complete absence of forward energy, consistent with the picture of projectile stopping. In the case of Al target, no projectile stopping is observed even for zero impact parameter. In peripheral collisions, transverse energy production is only weakly target dependent, suggesting the dominance of single independent collisions. A FRITIOF event generator shows that subsequent collisions after the first are much less effective for pion production, which manifests as transverse energy. These results were published in Physical Review C (Appendix B).

2.1.3 Anti-proton production for Si+A collisions

The anti-proton yield, due to the large annihilation cross section, is sensitive to the baryon density and hadronic formation times. The invariant cross section of anti-proton was measured in Si+Al and Si+Au collisions, and fitted to an exponential in transverse mass. The inverse slope parameter for anti-proton was found to be the smallest in comparison with pion, kaon and proton, 140 ± 1.4 MeV, and similar to that in pp and pA collisions. This result is not consistent with the hydrodynamic model, which predicts

a similar slope parameter for anti-proton and proton. The ratios of anti-proton to pion and kaon decrease with increasing target mass. The cause could be due to the large anti-proton annihilation cross section, the degradation of projectile energies while traversing the medium. This study is limited by statistics; the total sample of anti-proton is $\sim 1,000$. We are collecting a much larger sample in E859 for further investigation. These results were published in Physics Letters (Appendix C).

2.1.4 Global transverse energy distributions

The global transverse energy distribution was studied for various beam/ target combination in the central rapidity region. Beams of protons, O and Si and targets of Be, C, Al, Cu, Ag and Au were used. The proton-nucleus spectra from Be to Au are quite similar. The ratios of differential cross section between gold and lower mass nucleus A is approximately constant, deviating very little from the value $(197/A)^{2/3}$. This general universality of p+A spectra is not observed at 200A GeV/c. The nucleus-nucleus spectra do depend on the geometry of the collision. For lighter target such as Al, the transverse energy tail does not reach its saturated value; whereas for Cu or heavier targets, the tails reach similar values, indicating a fair amount of projectile "stopping" in the sense of exhaustion of particle production. The ratio of differential cross section between Au and Ag at high transverse energy values is simply the geometric ratio of areas. The projectile, but not the target dependence can be described by the rescaling predicted by the Fireball model. The nucleus-nucleus distributions are fitted with the convolutions of p-nucleus spectra, using a wounded projectile nucleon model (MPNM). This worked well for Cu or heavier target. These results were published in Physical Review C (Appendix D).

2.1.5 Comparison of p+A and Si+Au collisions

The considerably enhanced yield of K^+/π^+ in central Si+Au collisions, in comparison with that in p+p collisions, is very intriguing. To study this phenomenon in greater details, data were collected and analyzed for p+A (where A is either Be, Al, Cu or Au) and Si+Au collisions.

The invariant cross sections with respect to the transverse kinetic energy are all exponential in form. The inverse slopes are similar for proton, kaons and pions in p+A reactions, ~ 140 -180 MeV. There is little change in inverse slope for π^+ in terms of target dependency. For Si+Au, pions have similar slopes. The distribution of proton slope changes gradually with target, increasing from 150 to 175 MeV. For Si+Au, the proton and the K^+ slopes have even larger values, ~ 200 -240 MeV at $1.2 \leq y \leq 1.6$. The particle yields as function of rapidity are extracted with the assumption of a single exponential function for each of the invariant cross section distribution. Within the measured rapidity, the ratio of the integrated yield for Au and Be targets is obtained:

1.08 ± 0.03 for π^+ , 1.81 ± 0.18 for K^+ and 1.95 ± 0.02 for proton. Thus, from Be to Au, the π^+ yield remains practically constant while the K^+ yield rises as strongly as protons. The K^+/p ratios exhibit a remarkable target independence, which provides a stringent test for any reaction models. The K^+ yield per nucleon for Si+Au is even higher. For p+Be, the rapidity spectra are rather broad. For gold targets, the peaks shift towards and below the participant rapidity. This investigation will be expanded to cover a larger rapidity range in E859.

These results were published in the Physical Review (Appendix E). The features associated with K^+ production - the large slope parameter, the spectrum shape and magnitude - should present a challenge and powerful constraint to any proposed theory for nucleus nucleus collisions at AGS energies.

2.1.6 π -correlation in Si+Al and Si+Au collisions

Hanbury-Brown-Twiss (HBT) interferometry technique was applied to the pion pairs of identical charges, both positive and both negative, to extract the interaction source size. Four functional forms were used to fit fully corrected correlation functions. All parametrizations of the correlation function are consistent with a spherically symmetric source of rms radius 3.5 ± 0.4 fm and lifetime of ~ 2 fm/c. The observation of a larger transverse radius reflects rather a nonzero lifetime of the source. The "chaoticity" parameter, λ , is greater than 0.5, and depends strongly on the assumed functional form of the correlation function. These results were published in the Physical Review Letters (Appendix F).

2.2 E859 Status

E859H collaboration extends the investigation of particle production started by E802 towards rarer events associated with high transverse momentum, interactions with small cross sections such as strange particle and anti-proton production and multi-particle correlation. The major addition to the E802 apparatus is a second level on-line programmable trigger for particle identification. The runs for E859 were completed and the data collected are being processed and analyzed.

2.2.1 Second Level Particle Identification Trigger

For the second E859 run, a second level trigger associated with the magnetic spectrometer is implemented to select specific event topologies and to fully utilize higher intensity AGS heavy ion beams. This enabled us to obtain significantly more statistics in the measurements of inclusive spectra (π , K, p, d) and two-particle correlations ($\pi\pi$, KK). The input from the wire chambers as well as time of flight modules was processed for

each track. The resulting data were fed into pre-calculated look-up tables, stored in five sets of Memory Look-up Units (MLU), to extract the momentum and the mass of this track. Information from all tracks emerging from the magnetic spectrometer was combined to form, for example, K^+ , K^- /anti-proton, 2π , $2K^-$, K^+K^- triggers. The operation of this trigger is programmable at run time. J. Kang is a member of the Second Level trigger group. He carried out the simulation of particle trajectories through the spectrometer system for hit locations in wire chambers and time of flight modules, developed the code to generate the look-up tables, and maintained a set of particle identification tables.

During the last year, more accurate geometry of the time of flight wall was installed into this Monte Carlo code and also the code were modified to handle higher momentum particles (up to 10 GeV) by only providing allowed combinations of trigger chamber wires and TOF slats without the PID information for such tracks. With this extended momentum coverage, higher transverse momentum tails in the inclusive spectra can be measured with more statistics. The final run taken place in May was very successful.

2.2.2 E859 Runtime Equipment Status Monitor

The E859 program FSACLE was resurrected by P. Beery for the spring 1991 heavy ion run at BNL. The program underwent major revision to enhance its performance as a real-time monitor of the data acquisition hardware. It displays beam and trigger rates on-line from scalers coming from the AGS and the detector electronics. This allowed "experts" including those not at the counting house to determine when a failure occurred and to initiate remedial actions much sooner. FSACLE was fully operational for the 1991 run. More histogram features as well as fault checking routines were added by Beery for the 1992 run.

2.2.3 E859 Pass12 Data Preprocessing Analysis

As was mentioned in the last report, UCR was able to participate in the Pass12 data processing (reconstruction of the E859 data), because of the computer resources bought with the initial complement given to R. Seto. Pass12 augments the raw data chamber hits with tracking and momentum information. The data is then used for subsequent physics analysis. UCR shared 1/3 of the data processing in 1991. However, the E859 software has since increased in sophistication and in CPU requirements by almost an order of magnitude with new, more accurate reconstruction routines needed by the correlation analysis. These routines deal more accurately with closely spaced tracks and the high multiplicities present in the gold beam data. The new more powerful CPU's being introduced by DEC have made this possible. MIT, Nevis and BNL have already purchased some of these computers and software is tailored to these more powerful machines. In order to continue to do analysis efficiently here at UCR we will need to

purchase at least one new DEC 4000 model 60 or model 90, and to add upgrades to the new Alpha workstation. This is the rationale behind the request in additional funding for computing. Although some parts of the E859/E866 software is available on UNIX computers, the collaboration continues to be committed to the VMS operating system, especially since the price/performance now available from DEC will in the near future match that of UNIX machines.

2.2.4 Resonance with strangeness final states

One of the interesting finds of E859 was the detection of ϕ in the K^+K^- channel at 14 degrees. An enhancement in its production cross section was seen by NA38 at CERN energies. We are particularly interested in the production of ϕ and other vector mesons such as the K^* . These are of interest for two reasons. First their cross sections are expected to be enhanced for the same reasons that the K 's are expected to be enhanced. Secondly, their masses and widths might be affected in highly dense strongly-interacting matter. However, present data does not allow us to calculate the cross section with sufficient accuracy. E859 spent several days running a two K trigger at 5 degrees where the yield of ϕ 's should be greater. We also took some triggers with a minimum bias trigger so that cross sections between central and peripheral events can be directly compared. The initial passes for the reconstruction of this data are now in progress.

2.3 E866 detector upgrade

Last June the new booster at BNL made available for the first time gold beams for heavy ion experiments. This maiden run proved to be very successful. E866 uses the E802/E859 detector, upgraded to handle higher multiplicities, and is building a brand new small aperture forward spectrometer.

We are investigating how to upgrade the Target Multiplicity Array (TMA). For gold beams TMA is expected to be hit by 500 particles in the forward wall; the existing streamer tube granularity is too coarse for this environment. Some tests were done by Richard Seto in conjunction with Lou Remsberg looking at the TMA using various target thicknesses to study the background produced by δ rays. This data is being examined by James Chang, now a post-doc with the UCR group stationed at BNL. Our initial results indicate that the δ ray problem will be severe in E866, with the contamination being of the order of 10 percent or greater. In the past we have thought about replacing TMA with silicon detectors in the forward rapidity region. However, these results show that the number of delta rays produced would render the detector useless for an event by event measurement. δ rays are produced by the electromagnetic interaction of the gold beam and the target. The number of δ rays scales like Z^2 of the projectile. Hence this was not a problem for Si beams, but becomes a major problem when using gold beams. Up to 100 δ electrons are produced when a gold nucleus passes through a 1% gold

target without interacting. These have a energy spectrum that ranges up to greater than 50 MeV and are produced primarily forward for mid-rapidity. The number is directly proportional to the thickness of the target. If the interaction happens very early in the target, there will be relatively few δ electrons; however, for an interaction happening near the end of the target one gets the full 100 δ 's. This means that for central collisions producing about 500 charged particles, there will be a 20% uncertainty in the total multiplicity depending on the number of δ rays produced, meaning that the detector is not suitable for an event by event measurement. We have abandoned the idea of using silicon detectors for this project, however our work in this area proceeds because of our involvement with the PHENIX Silicon vertex detector.

The present spectrometer, designated the "Henry Higgins" can only be used at angles greater than 19° because of the large multiplicities in AU-AU collisions. A second spectrometer with $1/5$ of the acceptance of the Henry Higgins, designated the Eliza, will be used to cover angles between 3° and 19° . August Smith, an undergraduate who has won an NSF award for minority students has been working with R. Seto on the calculation of the acceptance of the phi in E866. His preliminary calculations show that the acceptance of the Eliza spectrometer at 3° is equivalent to the Henry Higgins at 14° making it possible to detect the phi in E866 given enough statistics. We are now looking into the possibility of triggering both spectrometers.

2.3.1 Motivation for Target Multiplicity Array upgrade

As it is presently configured, E866 has only one global event trigger, namely the Zero-Degree Calorimeter (ZCAL). A hardware trigger of $E_{ZCAL} < 400$ GeV (the most central 4% of the cross-section) was used in the Spring 1992 run effectively, and it is expected that this trigger will continue as the primary trigger in future runs. ZCAL provides basic information about the geometry of the collision; however, it is desirable to add complementary information for further cuts. Of great interest are those events with high density, either energy density or baryon density, since this is expected to be necessary for the appearance of new types of physics, such as a phase transition. Produced particles are a good measure of the energy density and may be used as the complementary trigger.

R. Seto spent one full month at BNL this summer primarily to study the possible ways of building a new TMA for the high multiplicity environment. Figure 1 shows a contour plot of $ET(L+R)$ versus E_{ZCAL} , where $ET(L+R)$ is the transverse energy of the PBGL in pre-E866 summed over both the big and small buggies. Most interesting is the upturn toward large ET and the lowest E_{ZCAL} . In particular, the range in ET values for a given E_{ZCAL} is greatest here. A double cut on low E_{ZCAL} and high ET would choose those events for which the geometry is central and the fluctuation in produced particle production is high. This is possible in software for the Spring 1992 data for those runs in which the PBGL was included in the readout, but is not possible for the full E866 as it is presently set up.

We propose adding a multiplicity array to E866 for the purpose of triggering on

events with a large number of produced particles (mostly pions.)

2.3.2 Upgraded TMA design goals

In addition to the obvious constraint of making the detector fit into the existing E866 setup, our goals in designing the detector are:

1. To count produced particles (pions) and not nucleons. This issue is discussed in the section below on Detector Materials.
2. To have a large coverage in pseudorapidity, η , and as much coverage in azimuthal angle, ϕ , as is practical. Since the Au+Au pion $dn/d\eta$ distribution is peaked near $\eta = +1.9$ ($\theta = 17$ degrees) and is symmetric about this point, we choose to cover from $\eta = +1.9$ backwards to $\eta = -1.9$. ($\eta < -1.9$ is irrelevant for pions.)
3. To keep any possible sources of background for the tracking in the spectrometers far enough away from the target in order to make them easily distinguishable from the target itself. To this end, we choose to place all elements of the detector on the order of 1 m from the target.
4. To keep the total mass of the detector as low as possible in order to keep down the background to the spectrometers and to make the mechanical support easier. For these reasons, lead-glass has been ruled out for the detector material. A full study of the background using Geant will need to be performed.
5. To deal with the δ ray problem.

2.3.3 New TMA detector materials

We are considering the use of a Cerenkov radiator behind a layer of a conversion material, probably lead, of thickness of order of one radiation length. With the proper choice of the index of refraction of the radiator, most charged pions as well as the conversion electrons from gammas (from neutral pions) will be above threshold – and therefore be counted – whereas most protons will be below threshold.

Figure 2 shows the results of a Fritiof 1.7 calculation for Au+Au at the AGS with impact parameter, $b < 2$ fm. Figure 2a shows the distribution in η of both protons and π^0 for all values of velocity β ; over the range $\eta < +1.9$ the ratio of π^0 /proton is roughly 4. Fig. 2b is the same plot with a β cut of 0.8 or higher. The proton distribution changes mostly in the back-angle regions; for $\eta < +1.9$ the ratio of π^0 /proton is roughly 10. In Fig. 2c, the β cut is at 0.6 and the ratio of π^0 /proton is about 6. The total π /proton ratio is about 3 times higher than π^0 /proton, so a β -cutoff of 0.6-0.8 gives a total π /proton ratio of about 20 or 30. One choice of a radiator is lucite ($n=1.5$) 2 cm thick, but the possibility of using other materials such as liquids has been discussed.

In front of the lead we plan to put two other layers. First will be a thin (few mm) layer of steel to absorb δ rays; this steel can be part of the support structure. Between the steel and the lead will be a layer (5 mm) of plastic scintillator to count the number of charged particles, an additional piece of information.

The optimal thicknesses of the layers, especially the lead, still need to be determined from Monte Carlo calculations. The goal is to have a π^0 give the same signal, on average, as a charged pion; this insures that fluctuations between pion species will not affect our measurement. Another question to be studied is the effectiveness of the δ -ray absorption.

2.3.4 Proposed new TMA configuration

The detector consists of two arrays: one above and one below the target. Each array covers the region $-1.9 < \eta < +1.9$ and is shaped as a partial hemisphere. A schematic cross-sectional view of the top array, as seen from the side, is shown in Figure 3. The radius of the hemispheres is 86 cm, chosen for clearance of the spectrometers. The array is subdivided in the polar angle (θ) direction in an uneven manner such that the multiplicity per subdivision is the same for all subdivisions. The exact manner for doing this remains to be worked out. The plastic scintillators could be curved planks, one for each polar angular subdivision of the array. A photo-multiplier tube is on both ends of each plastic scintillator plank. The Cerenkov radiator (lucite or whatever) is more finely segmented in the azimuthal direction; in one scheme each radiator element has a photomultiplier tube directly attached to the back. (Some Cerenkov radiation also arises from the front face of the PMT itself, so this has to be considered carefully in the design.) An alternative scheme uses wavelength-shifting fibers to bring the signals to a multi-anode PMT. Due to severe space constraints, the arrays will be supported from the rear only; thus the weight of the detectors should be minimized as much as possible.

3 Phenix Proposal and R&D

Riverside has joined the PHENIX collaboration to carry out future RICH experiments. Our interests lie in the measurement of as many potential signatures of the Quark-Gluon-Plasma (QGP) as possible. These include the di-lepton production, direct and indirect photon production, hadron spectra, and global observables such as multiplicity, rapidity density.

In the past year, we joined the inner tracking detector subgroup to work on specifically the silicon vertex detector and to prepare the preConceptual Design Report.

3.1 Mechanical support for vertex detector

UCR has taken the responsibility for fabricating the mechanical support for the Phenix Silicon Strip detector which will be used primarily to locate the interaction vertex. The silicon detector wafers will be supported on Rohacell cages, which will in turn be supported on graphite epoxy struts mounted to the pole tips of the magnet. Rohacell is a lightweight, rigid polymethacrylimide foam developed by the aerospace industry. Three samples (51 WF, 51 IG, and 71 IG) were obtained from the Rohm corporation to study potential difficulties in machining and mechanical properties. The numbers indicate density and IG is the standard grade while WF is heat treated so that it can be autoclaved. Rohacell is thermally very stable with a CTE of less than 2×10^{-5} . Our tests confirm this. Square cages with ribs of 1/4" and 1/8" were successfully machined though care had to be taken in the clamping of the 1/8" sample while machining since the structure was fragile. We were cautioned by Rohm to make sure the surface of all machinery was clean and free of oil, and that a vacuum system was set up to collect the dust produced in the machining. Aside from these precautions the machinist found the material relatively easy to machine. We foresee no problem in machining cages with 1/8" ribs in the lightest of the samples (51 IG). The 71 IG gives a structure that is much sturdier than that made of the 51 weight material. 71 IG has a radiation length of 550 cm and a density of 4.7 lbs/ft^3 ; 51 has a density of 3.2 lbs/ft^3 .

One of the problems with Rohacell is that it is known to absorb water readily. To study this aspect, Dale Thompson, an undergraduate working with our group, built a humidity chamber. Since Rohacell is thermally very stable, the chamber temperature was held at 90 degrees centigrade for ease of water evaporation. The sample was dried completely by placing it in the chamber and purging with nitrogen for several days. Then the sample was weighed and measured with calipers inside the chamber. Water was introduced to increase the humidity and the sample was measured again after 24 hours. Water absorption was found to rise quickly after about 50% relative humidity. As of this time the tests have reached 80% relative humidity in which the samples have increased in weight by about 10% and in volume by about 1%. The tests will continue for the next week until 100% relative humidity is reached. The results are summarized below.

Weight Change (percent)

	51 WF	51IG	71IG
50% RH	2.0	3.0	1.0
75% RH	8.0	11.0	10.0

Volume Change (percent)

	51 WF	51IG	71IG
50% RH	0.25	0.25	0.5
75% RH	2.0	1.0	2.0

3.2 Silicon detector and electronics work

We have been setting up a system at UCR to read out some "off the shelf" silicon detectors using the SVX-D chip that has been made for CDF at FNAL. We are pursuing this course for the following reasons. 1) We anticipate that the readout scheme for the chip finally designed for use with our detector will be similar in many respects to the SVX chip. I note here that FNAL will be going to beam crossing times of 130 ns, implying that the new SVX-II chip will have the correct shaping times for RHIC. In any case work with the SVX chip will give us a chance to familiarize ourselves with a readout scheme and the necessary programming of readout modules. 2) The use of the SVX chip gives us the ability to readout prototype detectors for testing purposes. 3) There is a very strong D0 silicon detector group at UCR which provides us with equipment (probe station, bonder, clean room) and a great deal of expertise. We have purchased at UCR several SVX-D chips, two Silicon detectors and the necessary readout modules (the SDA, SRS, port card and receiver card). Two students (Warren Eldridge and Micheal Towne) together with a post doc have worked to set up the system which includes a vax for readout and communication with the SRS and SDA modules and a planned laser test box with an X-Y stand which will eventually be computer controlled. (The test stand is not made and is part of the R and D request for next year.) A board has been designed for the mounting of the SVX chip and detector. Bonding is taking place now. Preliminary work has been done in communicating with the readout modules, and real tests of the setup will begin when the bonding is complete.

4 R&D Plans for 1993

4.1 Mechanical fabrication

A 1% change in volume or 0.33 percent change in length is clearly not tolerable for the Silicon strip detector. We will be trying several types of coatings which include polyurethane, and a two part polyurethane with amine curing agent to seal the Rohacell. Further tests need to be performed which include assembling mock up assemblies to test the mechanical properties and possibilities for cooling of the Silicon+Rohacell units. These tests will be done in conjunction with Los Alamos Group. In addition real prototypes will have to be constructed for beam tests. We plan to fabricate in the machine shop at UCR 6 full cages out of 51 and 71 weight Rohacell for these purposes. This will also give the machinists more experience before embarking on the construction of the full cage.

4.2 Silicon detector and electronics

A laser test stand with an X-Y table is being designed and built. We will construct two stands, one of which will be for use at Los Alamos. For the stand at UCR, a laser diode and accompanying power supply and optics will be needed.

This setup will then be used for the following tests: 1) To study cross talk between adjacent or nearby strips, particularly in the case of non-minimum ionizing particles. 2) To study angle of incidence problems and corrections that need to be made to get a accurate measure of the multiplicity from the detector. 3) To give us a method to test many channels of prototypes in a systematic way. The setup will also give us a base from which to test new chips and their associated readout modules.

4.3 MC simulation for PHENIX

For the PHENIX experiment Monte Carlo simulations using GEANT have been installed over the last several months. The program is called PISA (PHENIX Integrated Simulation Application) and detector specific subroutines have been provided by contact persons for each detector. Kang, as a contact person for the silicon vertex detector simulation, have written few subroutines for this detector. The vertex detector is for the precision measurements of vertex positions in the collider, using micro-strips with $100\mu\text{m}$ read-out pitch. Future plan on this effort will be the studies of vertex resolutions, backgrounds in the vertex detector from curled-ups (in magnetic fields) of lower momentum particles, and backgrounds to the other detectors by electrons converted in the vertex detector.

Richard Seto, a member of the initial Conceptual Design Group (CDG I), has been heavily involved in the planning of the Phenix Detector. This work consisted of studying the possibilities of detecting di-electrons. Di-electrons are an attractive signature in heavy -ion physics because of their lack of a color interaction, making them good probes of the interior of the fireball formed during the interaction, in a similar way that neutrino's are a good probe of the processes in the interior of the sun. The vector mesons (ρ , ω , ϕ , Ψ , and Υ) all have branching ratios to e^+e^- that can be detected, allowing PHENIX to study the vector meson suppression/enhancement that has been seen at lower energies. More importantly it will allow us to study the mass and widths of the various resonances. It is believed that the masses and widths will change as the phase transition to a chirally symmetric state is reached. Finally, dileptons will give us the possibility to measure the initial temperature directly via the thermal di-electron spectrum. Dalitz decays of π^0 and η^0 mesons are the primary backgrounds for these signals, and the rejection of this background was the focus of this work. The conclusion was that the vector mesons can be studied without special measures taken to reject the background. For the thermal spectrum where there is no characteristic Breit-Wigner peak, a special detector will be needed whose primary purpose is to measure the low energy electrons coming from dalitz decays. A silicon detector is under consideration as

an upgrade to the present Phenix detector for this purpose.

5 Study of particle production at Bevalac energy

5.1 Pair correlation study with HISS

We carried out the proton proton correlation analysis using the data of 1.2 GeV/A La+La collisions collected with the HISS at the Bevalac. As we had already studied the π^- correlations, this would give a unique set of data where both pion and proton interferometry was studied under the same physics and experimental conditions, and provide some insight of the dynamics of the collision of heavy ions at high energies. James Chang has completed this work as his Ph.D. dissertation (Appendix G).

5.1.1 Results of p-p correlation study

In E684X, a time-of-flight system was implemented to allow identification of positive charged particles, mostly protons and deuterons. The proton-proton correlation analysis was carried out. The correlation between the background protons was obtained using the event-mixing method. This method automatically takes care of the acceptance correction. The data was fitted by a calculated correlation function derived numerically from interactions between two protons and the Koonin's Gaussian source distribution. The interactions considered are Reid soft-core nuclear and Coulomb, as well as the Fermi-Dirac statistics. The numerical calculation for a range of parameters r_0 was done by Guang Hwa Xu. Figure 4 shows the results of the proton-proton correlation studies. For the Ar + KCl central collision, the extracted parameter r_0 is 3.32 ± 0.10 fm. For the La + La central collision, $r_0 = 4.00 \pm 0.18$ fm. To interpret these results, systematic comparisons were made.

First, the results from the pion-pion correlation were compared to the the proton-proton results. The general trend is that the pion case gives a larger value of radius r_0 than the proton case. The pion case yielded $r_0 = 4.30 \pm 0.14$ fm for the Ar + KCl, and $r_0 = 5.97 \pm 0.24$ fm for the La + La. So for Ar + KCl, the ratio of parameters between proton case and pion case is 0.77; for La + La, this ratio is 0.67. The two important observations are made: (1) Radius r_0 obtained via pion-pion correlation is larger than that obtained via proton-proton correlation, and (2) The ratio of the r_0 's between the proton case and pion case decreases as the colliding system gets larger. Both of these observations can be explained by the fact that pions have a shorter mean free path length than the protons. This means that observed pions are emitted mostly from the outer shell of the collision interaction region. The protons, on the other hand, are easier to escape all the way from the center of the core. The thickness of this pion-emission shell

is constant, meaning that as the interaction sphere gets larger, the apparent radius of the pion-emitting source grows at a slower pace than that of the proton-emitting source.

Another comparison made was between all existing proton-proton correlation results. This time, the extracted parameter r_o is converted to the RMS radius $r_{RMS} = \sqrt{3/2}r_o$, for easier comparison to the r_{RMS} obtainable from the nucleon number A . That is, $r_{RMS} = 0.82A^{1/3} + 0.58$ fm, valid for $A > 20$. Figure 5 shows the plot of measured r_{RMS} (y -axis) vs the expected r_{RMS} (x -axis) where one includes all the nucleons of both projectile and target nuclei. The experiment and collision system for each point is given in the legend. One can immediately see that as the system gets large, the measured r_{RMS} tend to be smaller than expected. The most obvious is the La + La (684X) case, which is the largest system in the comparison. The facts that Ar + KCl (684) fits right in the trend, and that both data sets are from virtually identical setup and analysis lead one to believe that the effect in La + La is not an artifact of analysis error. A plausible scenario is that, where in the large systems, not all the nucleons are involved (in central collisions). For a asymmetric projectile/target system, the small projectile nucleus drills a bore out of the larger target nucleus, and only the projectile and the core are included in the interaction system. The nucleon number and its corresponding r_{RMS} can be calculated, and has been done in the Chang's thesis. It turns out that this scenario does not include enough nucleons. One can then compensate by including a barrel around the drilled-out core. This makes sense, since one should expect some excitation of nucleons in this barrel region. For a large symmetric collision, there is no such thing as a bore. The explanation in this case is given by having the two colliding spheres not overlap completely. Only the overlapping region is then considered as an interaction region. Obviously, more experimental data are needed to confirm and characterize these phenomena just described.

The implication of the comparison study is that for large colliding systems, proton-proton correlation becomes sensitive to the relative sizes of the projectile and target nuclei. This may be a good way to characterize the collision participants and spectators. Whatever the case, future proton-proton correlation measurements must be interpreted carefully.

5.1.2 Ongoing analysis of E684X

One of the offsprings of the proton-proton correlation analysis is the set of reduced compact data files that have particles identified along with momentum information. These reduced data make it easy for one to look at the inclusive distributions of various particles. For example, one can extract the temperature parameter from the distribution of the transverse kinetic energy distribution. This work is currently being done by a Riverside undergraduate student Albert Gomez.

5.2 Collective flow study with streamer chamber

5.2.1 Higher order collective flow

To study the properties of the equation of state (EOS) of compressed nuclear matter, many observables such as pion production, kaon production, collective sideward deflection of the reaction product in terms of flow angles, transverse momenta have been proposed. In the past, we have analysed our streamer chamber data with the transverse flow analysis proposed by Danielewicz and Odnies. However, the accuracy of this method depends heavily on the definite particle identification, and the small dispersion of the reaction plane which is affected by track finding efficiency.

To overcome these difficulties, an azimuthal correlation function analysis is adopted. We show that this correlation is sensitive to the parameters of the equation of state. We extended the two-particle azimuthal correlation to multi-fragment azimuthal correlation on a sample of 325 Ar+Pb collisions at 400 A MeV. Through a simulation study based on the FRESCO statistical event generator, we found that more than 70% of the forward-going fragments carry a component of collective motion. These results were published in Phys. Rev. Letters (Appendix H).

5.2.2 Energy dependence of collective motion in Ar+Pb

The energy dependence of flow effects and rapidity distributions was studied in central collisions at 0.4, 0.8 and 1.8 GeV/A. The rapidity distributions for π and p exhibited Gaussian behavior; whereas that for deuterons had a double-hump structure at the two higher energies. The dip coincided with the normalized rapidity value of least flow. The temperatures inferred by the widths are 50, 85(45), 150(66) MeV for proton(pion) at .4, .8 and 1.8 GeV/A respectively. The maxima of the average in-plane transverse momentum per nucleon were measured to be 100, 150, and 170 MeV/c at the three incident energies. The collective motion is found to be saturated around 0.8 GeV/A, evidenced by the larger increase in total momentum transfer per event and flow angle between the lower energies. These results will be a challenge for future models to explain the dynamics of relativistic heavy ion collisions, and were published in Physical Review C (Appendix I).

5.3 Spatial information in pion interferometry

We investigated the effects of source density distributions assumed by the pion-emitting source on the fitted radius parameter. A Gaussian, a uniform spherical surface and a uniform spherical volume and a Kopylov type distribution were used. We found that the average radius is preferable to the rms radius to describe the spatial extent of the

source under various assumed source density distributions. These results were published in Physical Review C (Appendix J).

6 Personnel changes

P. Berry has taken a position with the University of Notre Dame to work on the STAR project for RHIC. James Chang has completed his Ph.D. and taken a postdoctoral appointment in our group. He is stationed at BNL, soon to be joined by a visiting scientist, G.H. Xu. In October Quian Zhu, a graduate from Rice University, will join our group as a postdoc. Also working with us are two graduate students, W. Eldridge and M. Towne, and four undergraduates, A. Gomez, M. Noriega, D. Thompson and A. Smith.

7 Summary and Outlook

We have applied the intermittency analysis to the E802 oxygen data. The results are being written up for publication. We shall continue to investigate in depth this phenomenon at AGS energies. For the E859 we will take on the study of K^+K^- and K^* resonance formation. For the upgrade of E866 experiment, we will investigate the feasibility and the practicality of implementing a cerenkov detector to replace the streamer tube TMA wall. We continue our work on the adaptation of a silicon strip detector as a vertex detector in PHENIX and our *R&D* efforts for RHIC. We will continue our Bevalac experimental analyses on both the HISS and the streamer chamber data.

Figure 2: Pseudorapidity distributions from Fritiof 1.7 for Au+Au at 11.6 A GeV/c and impact parameter $b < 2$ fm. The open histogram is for π^0 and the filled histogram is for protons. a) for all values of beta b) for $\beta > 0.8$ c) for $\beta < 0.6$

3

PRELIMINARY SKETCH OF MULTIPLICITY ARRAY FOR E866

B. MOSKOWITZ
28 AUG '96
REVISED

Figure 3: Top: Schematic cross-sectional view of the top array, as seen from the side. Also shown is an individual curved plank.

Figure 4: Top: Proton-proton correlation result from the 1.8 GeV/A Ar + KCl data. The extracted parameter is $r_o = 3.32 \pm 0.10$ fm. Bottom: For the 1.2 GeV/A La + La, $r_o = 4.00 \pm 0.18$ fm.

Figure 5: Survey plot of measured r_{RMS} vs expected r_{RMS} when all of the projectile and target nucleons are included.

**DATE
FILMED**

02/19/93