WSRC-TR--91-503

DE93 004295

503

**NUCLEAR REACTOR TECHNOLOGY
AND SCIENTIFIC COMPUTATIONS**

KEY WORDS: Diffusion Theory
Transport Solutions
Benchmarking
Eigenvalues

RETENTION PERIOD: PERMANENT

**VERIFICATION, VALIDATION, AND
BENCHMARKING REPORT FOR GILDA:
An Infinite Lattice
Diffusion Theory Calculation (U)**

By

T. T. Le

ISSUED: SEPTEMBER 1991

**WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY
AIKEN, SC 29808**

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY UNDER CONTRACT DE-AC09 89SR18035

MASTER

PROJECT: **PHYSICS CODE CERTIFICATION**

TASK: **CERTIFICATION OF GILDA**

DOCUMENT: **WSRC-TR-91-503**

TITLE: **VERIFICATION, VALIDATION, AND BENCHMARKING
REPORT FOR GILDA: An Infinite Lattice Diffusion Theory
Calculation (U)**

APPROVALS

R. E. PEVEY, TECHNICAL REVIEWER DATE: 4/2/92

C. E. APPERSON, MANAGER
REACTOR PHYSICS GROUP DATE: 4-9-92

M. R. BUCKNER, MANAGER
SCIENTIFIC COMPUTATIONS SECTION DATE: 4-10-92

Table of Contents

TABLE OF CONTENTS

	P a g e
Table of Contents	1
Summary	3
I Introduction to GILDA	4
II Verification	4
III Validation	4
IV. Benchmark Problems	5
IV.1 7-Hex Control-Mark22 Problem for k_{eff} Search	5
IV.2 7-Hex Control-Mark22 Problem for Buckling Search	8
IV.3 7-Hex Control-Mark16-31 Problem for k_{eff} Search	10
IV.4 7-Hex Control-Mark16-31 Problem for Buckling Search	13
IV.5 49-Homogenized-Hex k_{eff} Search Problem From Control-Mark22 Lattice	16
IV.6 49-Homogenized-Hex Buckling Search Problem From Control-Mark22 Lattice	18
IV.7 49-Homogenized-Hex k_{eff} Search Problem From Control-Mark16-31 Lattice	19
IV.8 49-Homogenized-Hex Buckling Search Problem From Control-Mark16-31 Lattice	21
V Conclusions	22

Table of Contents

VI Figures	23
References	25

Verification, Validation, and Benchmarking Report for GILDA (U)

SUMMARY

This report concerns the verification and validation of GILDA, a static two dimensional infinite lattice diffusion theory code. The verification was performed to determine if GILDA was applying the correct theory and that all the subroutines function as required. The validation was performed to determine the accuracy of the code by comparing the results of the code with the integral transport solutions (GLASS¹) of benchmark problems. Since GLASS uses multigroup integral transport theory, a more accurate method than fewgroup diffusion theory, using solutions from GLASS as reference solutions to benchmark GILDA is acceptable. Eight benchmark problems used in this process are infinite mixed lattice problems. The lattice is constructed by repeating an infinite number of identical super-cells (zones). Two types of super-cell have been used for these benchmark problems: one consists of six Mark22 assemblies surrounding one control assembly and the other consists of three Mark16 fuel assemblies and three Mark31 target assemblies surrounding a control assembly.

Since the differences in the results between GLASS and GILDA calculations are due to the approximation in interface net leakages of diffusion theory used in GILDA, the errors of Control-Mark16-Mark31 lattice problem are expected to be larger than the errors of the Control-Mark22 lattice problem. In this benchmark process, the maximum acceptable discrepancies in k_{eff} (Δk_{eff}) between GILDA and GLASS calculations are set to 1.5% for the Control-Mark16-Mark31 lattice and 0.5% for the Control-Mark22 lattice. The equivalent maximum acceptable discrepancies in buckling (ΔB^2) are approximated from Δk_{eff} by the relationship $k_{\text{eff}} - 1 = M^2 B^2$ where M^2 is the equivalent migration area, a function of the problem's parameters. Since the results of these benchmark solutions were comparable to the GLASS transport solutions, it is the conclusion of this study that GILDA was correctly implemented and is ready to submit to SCMS.

Verification, Validation, and Benchmarking Report for GILDA (U)

I INTRODUCTION TO GILDA

GILDA is a static two-dimensional diffusion theory code which is written to perform either buckling (B^2) or effective multiplication factor (k_{eff}) calculations for an infinite lattice. An infinite lattice is constructed by repeating an infinite number of identical super-cells with translational or a combination of translational and rotational symmetry as shown in Figures 1 and 2. A super-cell has one homogenized cell at the center and six other homogenized cells around where a cell can be a homogenized hex or a patch of seven identical homogenized hexes. GILDA was written by J. W. Stewart in 1973 and was considered as a derivative of GRIMHX², a static three dimensional reactor analysis code. The calculational flow and the theory implemented in GILDA are discussed in Reference 3.

II VERIFICATION

As part of the certification process, GILDA has to be verified, a process to ensure that the coding correctly implements the intended calculational methods⁴. Since GILDA is a small computer code using neutron diffusion theory, a well known theory which can be found in many nuclear engineering books⁵⁻⁶, the verification process was performed by comparing the code line by line with the theory from open literature, and the ARCHY⁷ utility was used to analyze and define all the variables in the code. GILDA is now ready to submit into SCMS and is able to process the information as required.

III VALIDATION

Validation refers to the process in which the accuracy of the whole code is determined. This process can be performed by comparing the code results with experimental data, controlled experiments, operational data, or more accurate calculational methods (benchmarks)⁴. GILDA is a derivative of GRIMHX, a static three dimensional reactor analysis code which has been validated⁸. GILDA performs a GRIMHX-like calculation on a GLASS lattice pattern; it is acceptable to validate GILDA by comparing its results with the GLASS which uses multigroup integral transport theory. Since GLASS uses a more accurate method than the fewgroup diffusion theory

Verification, Validation, and Benchmarking Report for GILDA (U)

used in GILDA, the convergence of GILDA results to exact GLASS results are not expected, but the general trends and overall response should be consistent. Since the mesh geometries of 1, 3, and 6 points per hex are different in shape and number of surfaces around a mesh point, the results of 1, 3, and 6 points per hex are not expected to lie on any curve. Also, since the "translation and rotation" geometry has never been used in the past and will not be used in the near future, the validation of this geometry option is not performed at this time. Users who try to use the "translation and rotation" geometry option will be informed by a warning message in the computer output that this option is not validated.

Eight benchmark problems used in this process are infinite mixed lattice problems in which the effective multiplication factor and buckling are calculated. The lattice represents an infinite number of identical super-cells. Two types of super-cell have been used for these benchmark problems; one consists of six Mark22 assemblies surrounding one control assembly as shown in Figure 3 and the other consists of three Mark16 fuel assemblies and three Mark31 target assemblies surrounding a control assembly as shown in Figure 4. Since the differences in the results between GLASS and GILDA calculations are due to the approximation in interface net leakages of diffusion theory used in GILDA, the errors of Control-Mark16 - Mark31 lattice problem are expected to be higher than the errors of the Control-Mark22 lattice problem. In this benchmark process, the maximum acceptable discrepancies in k_{eff} (Δk_{eff}) between GILDA and GLASS calculations are set to 1.5% for the Control-Mark16-Mark31 lattice and 0.5% for the Control-Mark22 lattice. The equivalent maximum acceptable discrepancies in buckling (ΔB^2) are approximated from Δk_{eff} by the relationship $k_{eff}-1 = M^2 B^2$.

IV. Benchmark Problems

IV.1 7-HEX CONTROL-MARK22 PROBLEM FOR K-EFF. SEARCH

The first benchmark problem is a k_{eff} search problem for which the geometry is shown in Figure 3. Each super-cell is a combination of one control hex at the center and six Mark22 hexes around it. The homogenized material parameters in each hex are calculated by

Verification, Validation, and Benchmarking Report for GILDA (U)

GLASS and are listed in Table 1.

GILDA calculates k_{eff} for cases of 1, 3, and 6 points per hex with both standard and coarse mesh finite difference methods. These results are listed in Table 2 together with k_{eff} predicted from GLASS and the percent difference between the two codes. For the case of one point per hex, it is clear from Table 2 that the coarse mesh finite difference method produces much better result than the standard finite difference method; for cases of three and six points per hex solutions, the errors of both coarse mesh and standard difference methods are all acceptable.

TABLE 1: Two Group Cell Homogenized Cross Sections

1. Control Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.14669E-01	:20.43232E-04	:00.00000E+00	:00.00000E+00
2	:85.29994E-02	:18.94356E-03	:00.00000E+00	:00.00000E+00

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:31.10570E-02
2	:18.51508E-06

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

1	:10.75265E-03
2	:42.42715E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)

2. MARK22 Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.44793E-01	:17.21529E-04	:10.41157E-04	:25.43805E-04
2	:86.71967E-02	:11.74667E-03	:10.77175E-03	:26.20981E-03

SCATTERING CROSS-SECTION TO FINAL GROUP		1
INITIAL GROUP	SIGMA-SCATTER	
1	:30.64537E-02	
2	:20.05546E-06	

SCATTERING CROSS-SECTION TO FINAL GROUP		2
INITIAL GROUP	SIGMA-SCATTER	
1	:77.86083E-04	
2	:41.38132E-02	

FISSION MATRIX (CHI) INTO FINAL GROUP		1
INITIAL GROUP	CHI	
1	:10.00000E-01	
2	:10.00000E-01	

FISSION MATRIX (CHI) INTO FINAL GROUP		2
INITIAL GROUP	CHI	
1	:00.00000E+00	
2	:00.00000E+00	

TABLE 2: Summary of GLASS and GILDA k_{eff} .

METHOD	GILDA			GLASS
	1	3	6	
Transport				0.97248
STD	0.984338 (+1.22%)	0.972088 (-0.04%)	0.970784 (-0.17%)	
CM	0.972117 (-0.04%)	0.969704 (-0.29%)	0.969985 (-0.26%)

Verification, Validation, and Benchmarking Report for GILDA (U)

IV.2 7-HEX CONTROL-MARK22 PROBLEM FOR BUCKLING SEARCH

The second benchmark problem is a buckling search problem in which the geometry and boundary conditions are the same as for Problem 1 above. In this problem, k_{eff} is set to 1.0 and the buckling (B^2) eigenvalue is found. Table 3 lists the material parameters input for GILDA which are calculated by GLASS and Table 4 lists the buckling values predicted by GLASS and GILDA and the percent difference between the two codes. The 18% in ΔB^2 in Table 4 is the maximum acceptable percent difference between the two codes which is equivalent to 0.5% in Δk_{eff} of Problem 1.

The results from Table 4 show that coarse mesh finite difference method for cases of 1, 3, and 6 points per hex are all acceptable. For the standard finite difference method, however, only 3 and 6 points per hex results are acceptable.

TABLE 3: Two Group Cell Homogenized Cross Sections

1. Control Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
-----	-----	-----	-----	-----
1	:13.14522E-01	:20.55576E-04	:00.00000E+00	:00.00000E+00
2	:85.26599E-02	:18.94545E-03	:00.00000E+00	:00.00000E+00
SCATTERING CROSS-SECTION TO FINAL GROUP			1	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:31.09983E-02		
2		:18.40667E-06		
SCATTERING CROSS-SECTION TO FINAL GROUP			2	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:10.84630E-03		
2		:42.44044E-02		
FISSION MATRIX (CHI) INTO FINAL GROUP			1	
INITIAL GROUP		CHI		
-----		-----		
1		:00.00000E+00		
2		:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

2. MARK22 Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.44586E-01	:17.32892E-04	:10.46241E-04	:25.56103E-04
2	:86.68174E-02	:11.75060E-03	:10.77757E-03	:26.22399E-03

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:30.64320E-02
2	:19.94114E-06

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

1	:78.69367E-04
2	:41.39511E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

1	:10.00000E-01
2	:10.00000E-01

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)**TABLE 4: Summary of GLASS and GILDA Buckling**

METHOD	GILDA			GLASS
	1	3	6	
Transport				-173.29E-6
ΔB^2				18%
STD	-101.613E-6 (-41.3625%)	-182.753E-6 (+05.4608%)	-191.274E-6 (+10.3780%)	
CM	-182.472E-6 (+05.2986%)	-198.357E-6 (+14.4654%)	-196.475E-6 (+13.3793%)	

IV.3 7-HEX CONTROL-MARK16-31 PROBLEM FOR K-EFF. SEARCH

The third benchmark problem is also a k_{eff} search problem, but the geometry is different from Problem 1 above. Figure 4 shows the geometry for this problem. Each super-cell is a combination of one control assembly at the center, three fuel assemblies (Mark16) and three target assemblies (Mark31) around it. The homogenized material parameters in each hex are calculated by GLASS and are listed in Table 5.

Table 6 lists the resulting k_{eff} for the GLASS transport solution and for the solutions from GILDA with the percent difference between the two codes noted. As in problem 1, Table 6 shows that the coarse mesh finite difference method produces much better results than the standard finite difference method for the case of one point per hex, but only a little improvement for the case of six points per hex.

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 5: Two Group Cell Homogenized Cross Sections

1. Control Assembly

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:12.51417E-01	:66.26922E-05	:00.00000E+00	:00.00000E+00
2	:83.14587E-02	:11.68838E-03	:00.00000E+00	:00.00000E+00

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:33.13738E-02
2	:14.24422E-06

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

1	:12.65533E-03
2	:44.29283E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

2. MARK16 Fuel Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.61796E-01	:64.30891E-05	:95.70768E-05	:23.38424E-04
2	:85.87756E-02	:43.26423E-04	:14.96418E-03	:36.41081E-03

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:30.34509E-02
2	:14.87921E-06

Verification, Validation, and Benchmarking Report for GILDA (U)

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

-----	-----
1	:71.20253E-04
2	:41.46963E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

-----	-----
1	:10.00000E-01
2	:10.00000E-01

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

-----	-----
1	:00.00000E+00
2	:00.00000E+00

3. MARK31 Target Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
-----	-----	-----	-----	-----
1	:11.83299E-01	:35.82110E-04	:40.09870E-05	:10.57306E-04
2	:84.64826E-02	:83.62398E-04	:31.37440E-04	:76.34014E-04

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

-----	-----
1	:34.04278E-02
2	:12.49950E-06

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

-----	-----
1	:93.00760E-04
2	:42.98627E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

-----	-----
1	:10.00000E-01
2	:10.00000E-01

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

-----	-----
1	:00.00000E+00
2	:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 6: Summary of GLASS and GILDA k_{eff} .

METHOD	GILDA			GLASS
	1	3	6	
Transport				1.09321
STD	1.13944 (+4.23%)	1.09918 (+0.55%)	1.10271 (+0.87%)	
CM	1.10407 (+0.99%)	1.09488 (+0.15%)	1.10154 (+0.76%)	

IV.4 7-HEX CONTROL-MARK16-31 PROBLEM FOR BUCKLING SEARCH

The fourth benchmark problem is a buckling search problem in which the geometry and boundary conditions are the same as for Problem 3. In this problem, k_{eff} is set to 1.0 and the buckling (B^2) eigenvalue is found. Table 7 lists the material parameters input for GILDA which are calculated by GLASS and Table 8 lists the buckling values predicted by GLASS and GILDA and the percent difference between the two codes. The 18% in ΔB^2 in Table 8 is the maximum acceptable percent difference between the two codes, which is equivalent to 1.5% in Δk_{eff} of Problem 3.

Similar to Problem 2, the results from Table 8 show that coarse mesh finite difference method for cases of 1, 3, and 6 points per hex are all acceptable. For the standard finite difference method, however, only 3 and 6 points per hex results are acceptable.

Verification, Validation, and Benchmarking Report for GILDA (U)**TABLE 7: Two Group Cell Homogenized Cross Sections**1. Control Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:12.51957E-01	:65.02920E-05	:00.00000E+00	:00.00000E+00
2	:83.26072E-02	:11.65610E-03	:00.00000E+00	:00.00000E+00

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:33.15027E-02
2	:14.59076E-06

SCATTERING CROSS-SECTION TO FINAL GROUP 2
INITIAL GROUP SIGMA-SCATTER

1	:12.34602E-03
2	:44.24869E-02

FISSION MATRIX (CHI) INTO FINAL GROUP 1
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

FISSION MATRIX (CHI) INTO FINAL GROUP 2
INITIAL GROUP CHI

1	:00.00000E+00
2	:00.00000E+00

2. MARK16 Fuel Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.62436E-01	:63.28163E-05	:94.30934E-05	:23.04594E-04
2	:87.01322E-02	:43.17615E-04	:14.92537E-03	:36.31638E-03

SCATTERING CROSS-SECTION TO FINAL GROUP 1
INITIAL GROUP SIGMA-SCATTER

1	:30.34739E-02
2	:15.23132E-06

Verification, Validation, and Benchmarking Report for GILDA (U)

SCATTERING CROSS-SECTION TO FINAL GROUP	2
INITIAL GROUP	SIGMA-SCATTER
1	:68.94659E-04
2	:41.42142E-02

FISSION MATRIX (CHI) INTO FINAL GROUP	1
INITIAL GROUP	CHI
1	:10.00000E-01
2	:10.00000E-01

FISSION MATRIX (CHI) INTO FINAL GROUP	2
INITIAL GROUP	CHI
1	:00.00000E+00
2	:00.00000E+00

3. MARK31 Target Assembly:

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:11.83851E-01	:35.64831E-04	:40.42971E-05	:10.67365E-04
2	:84.75477E-02	:83.37693E-04	:31.27365E-04	:76.09501E-04

SCATTERING CROSS-SECTION TO FINAL GROUP	1
INITIAL GROUP	SIGMA-SCATTER
1	:34.05237E-02
2	:12.80223E-06

SCATTERING CROSS-SECTION TO FINAL GROUP	2
INITIAL GROUP	SIGMA-SCATTER
1	:90.45199E-04
2	:42.94670E-02

FISSION MATRIX (CHI) INTO FINAL GROUP	1
INITIAL GROUP	CHI
1	:10.00000E-01
2	:10.00000E-01

FISSION MATRIX (CHI) INTO FINAL GROUP	2
INITIAL GROUP	CHI
1	:00.00000E+00
2	:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 8: Summary of GLASS and GILDA Buckling

METHOD	GILDA			GLASS
	1	3	6	
Transport				511.95E-6
ΔB^2				18%
STD	794.818E-6 (+55.2531%)	561.221E-6 (+09.6242%)	582.244E-6 (+13.7306%)	
CM	588.573E-6 (+14.9669%)	536.629E-6 (+04.8206%)	575.756E-6 (+12.4633%)	

**IV.5 49-HOMOGENIZED-HEX K-EFF SEARCH PROBLEM FROM
CONTROL-MARK22 LATTICE**

The fifth benchmark problem is a k_{eff} search problem for which the geometry is shown in Figure 1. Each super-cell is a combination of one cell (7 hexes) at the center and six cells around the center cell. All seven cells are identical and the homogenized material parameters in each cell are the lattice average material parameters of a Control-Mark22 lattice calculated by a GLASS k_{eff} search and are listed in Table 9. Since this is a homogeneous problem in which the lattice average material parameters have been used, there is no error in the approximation of net interface leakage couplings of diffusion theory, the results of GLASS and GILDA calculations are expected to be identical within computer truncation error.

GILDA calculates k_{eff} for cases of 1, 3, and 6 points per hex with both standard and coarse mesh finite difference methods. These results are listed in Table 10 together with k_{eff} predicted from GLASS. In this table, k_{eff} of GLASS and GILDA calculations are identical as expected.

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 9: Two Group Lattice Average Cell Homogenized Cross Sections

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.87980E-01	:17.55720E-04	:93.05014E-05	:22.73447E-04
2	:89.82700E-02	:12.82011E-03	:91.65104E-04	:22.30052E-03
SCATTERING CROSS-SECTION TO FINAL GROUP			1	
INITIAL GROUP		SIGMA-SCATTER		
1		:30.69429E-02		
2		:19.82571E-06		
SCATTERING CROSS-SECTION TO FINAL GROUP			2	
INITIAL GROUP		SIGMA-SCATTER		
1		:81.01373E-04		
2		:41.53731E-02		
FISSION MATRIX (CHI) INTO FINAL GROUP			1	
INITIAL GROUP		CHI		
1		:10.00000E-01		
2		:10.00000E-01		
FISSION MATRIX (CHI) INTO FINAL GROUP			2	
INITIAL GROUP		CHI		
1		:00.00000E+00		
2		:00.00000E+00		

TABLE 10: Summary of GLASS and GILDA k_{eff} .

METHOD	GILDA			GLASS
	1	3	6	
Transport				0.97248
STD	0.972479 (+0.00%)	0.972480 (+0.00%)	0.972480 (+0.00%)	
CM	0.972479 (+0.00%)	0.972480 (+0.00%)	0.972480 (+0.00%)

Verification, Validation, and Benchmarking Report for GILDA (U)IV.6 49-HOMOGENIZED-HEX BUCKLING SEARCH PROBLEM FROM
CONTROL-MARK22 LATTICE

The sixth benchmark problem is a buckling search problem for which the geometry is the same as Problem 5 above. The homogenized material parameters in each cell are the lattice average material parameters of Control-Mark22 lattice calculated by a GLASS buckling search and are listed in Table 11.

GILDA calculates B^2 when k_{eff} is set to 1.0 for cases of 1, 3, and 6 points per hex with both standard and coarse mesh finite difference methods. The results are listed in Table 12 together with B^2 predicted from GLASS and the percent difference between the two codes. These percent differences are almost zero as expected.

**TABLE 11: Two Group Lattice Average Cell Homogenized
Cross Sections**

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.88495E-01	:17.67248E-04	:93.48501E-05	:22.83959E-04
2	:89.81830E-02	:12.82388E-03	:91.69847E-04	:22.31206E-03
SCATTERING CROSS-SECTION TO FINAL GROUP			1	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:30.69182E-02		
2		:19.71224E-06		
SCATTERING CROSS-SECTION TO FINAL GROUP			2	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:81.86314E-04		
2		:41.55104E-02		
FISSION MATRIX (CHI) INTO FINAL GROUP			1	
INITIAL GROUP		CHI		
-----		-----		
1		:10.00000E-01		
2		:10.00000E-01		
FISSION MATRIX (CHI) INTO FINAL GROUP			2	
INITIAL GROUP		CHI		
-----		-----		
1		:00.00000E+00		
2		:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)**TABLE 12: Summary of GLASS and GILDA Buckling .**

METHOD	GILDA			GLASS
	1	3	6	
Transport				-173.29E-6
STD	-173.296E-6 (+00.0035%)	-173.298E-6 (+00.0046%)	-173.276E-6 (-00.0081%)	
CM	-173.288E-6 (-00.0012%)	-173.298E-6 (+00.0046%)	-173.273E-6 (-00.0098%)	

**IV.7 49-HOMOGENIZED-HEX K-EFF SEARCH PROBLEM FROM
CONTROL-MARK16-31 LATTICE**

The seventh benchmark problem is a k_{eff} search problem for which the geometry is the same as problem 5 above. However, the cell homogenized material parameters in each cell are the lattice average material parameters of a Control-Mark16-Mark31 lattice calculated by a GLASS k_{eff} search. These material parameters are listed in Table 13.

GILDA calculates k_{eff} for cases of 1, 3, and 6 points per hex with both standard and coarse mesh finite difference methods. These results are listed in Table 14 together with k_{eff} predicted from GLASS. The table shows that k_{eff} of GLASS and GILDA calculations are identical as expected.

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 13: Two Group Lattice Average Cell Homogenized Cross Sections

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.14513E-01	:17.43201E-04	:64.38263E-05	:16.02040E-04
2	:88.33018E-02	:73.14826E-04	:72.50513E-04	:17.64194E-03
SCATTERING CROSS-SECTION TO FINAL GROUP			1	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:32.03428E-02		
2		:13.70222E-06		
SCATTERING CROSS-SECTION TO FINAL GROUP			2	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:85.45027E-04		
2		:42.60157E-02		
FISSION MATRIX (CHI) INTO FINAL GROUP			1	
INITIAL GROUP		CHI		
-----		-----		
1		:10.00000E-01		
2		:10.00000E-01		
FISSION MATRIX (CHI) INTO FINAL GROUP			2	
INITIAL GROUP		CHI		
-----		-----		
1		:00.00000E+00		
2		:00.00000E+00		

TABLE 14: Summary of GLASS and GILDA k_{eff} .

METHOD	GILDA			GLASS
	1	3	6	
Transport				1.09321
STD	1.09321 (+0.00%)	1.09321 (+0.00%)	1.09321 (+0.00%)	
CM	1.09321 (+0.00%)	1.09321 (+0.00%)	1.09321 (+0.00%)

Verification, Validation, and Benchmarking Report for GILDA (U)IV.8 49-HOMOGENIZED-HEX BUCKLING SEARCH PROBLEM FROM
CONTROL-MARK16-31 LATTICE

The eighth benchmark problem is a buckling search problem for which the geometry is the same as Problem 7 above. The homogenized material parameters in each cell are the lattice average material parameters of a Control-Mark16-Mark31 lattice calculated by a GLASS buckling search and are listed in Table 15.

GILDA calculates B^2 when k_{eff} is set to 1.0 for cases of 1, 3, and 6 points per hex with both standard and coarse mesh finite difference methods. The results are listed in Table 16 together with B^2 predicted from GLASS and the percent difference between the two codes. These percent differences are almost zero as expected.

**TABLE 15: Two Group Lattice Average Cell Homogenized
Cross Sections**

GROUP	D	CAPTURE	FISSION	NU*FISSION
1	:13.13564E-01	:17.27977E-04	:63.87485E-05	:15.90487E-04
2	:88.37451E-02	:72.94420E-04	:72.32578E-04	:17.59830E-03
SCATTERING CROSS-SECTION TO FINAL GROUP			1	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:32.03629E-02		
2		:14.03135E-06		
SCATTERING CROSS-SECTION TO FINAL GROUP			2	
INITIAL GROUP		SIGMA-SCATTER		
-----		-----		
1		:82.94472E-04		
2		:42.55764E-02		
FISSION MATRIX (CHI) INTO FINAL GROUP			1	
INITIAL GROUP		CHI		
-----		-----		
1		:10.00000E-01		
2		:10.00000E-01		
FISSION MATRIX (CHI) INTO FINAL GROUP			2	
INITIAL GROUP		CHI		
-----		-----		
1		:00.00000E+00		
2		:00.00000E+00

Verification, Validation, and Benchmarking Report for GILDA (U)

TABLE 16: Summary of GLASS and GILDA Buckling .

METHOD	GILDA			GLASS
	1	3	6	
Transport				511.95E-6
STD	511.983E-6 (+00.0064%)	511.983E-6 (+00.0064%)	511.949E-6 (+00.0002%)	
CM	511.984E-6 (+00.0066%)	511.982E-6 (+00.0063%)	512.011E-6 (+00.1192%)	

V CONCLUSIONS

GILDA has been verified and validated by comparing the results of benchmark problems to the more accurate transport solutions. For both k_{eff} and buckling searches, GILDA solutions show that the coarse mesh finite difference method is good for all cases but the standard finite difference method is good only for cases of 3 and 6 points per hex only. It is recommended by this study that the standard finite difference method with one point per hex should not be used in GILDA.

VI FIGURES

Figure 1: Symmetry by translation.

Figure 2: Symmetry by translation and rotation.

Figure 3: A Super-cell of Control-Mark22 Problem

Figure 4: A Super-cell of Control-Mark16-Mark31 Problem

Reference

References

1. W. E. Graves, GLASS User's Manual, DPSTM-89-100-1, July 1989.
2. Module GRIMHX - Generalized Reactor Iterative Module in Hexagonal Geometry, Joshua Manual, Volume 10, DPSTM-500, November 1973.
3. T. T. Le, User's Manual for GILDA: An Infinite Lattice Diffusion Theory Calculation, WSRC-TR-91-481, August 1991.
4. H. Toffer, R. D. Crowe, K. N. Schwinkendorf, R. E. Pevey, Verification and Validation Plan for Reactor Analysis Computer Code (U), WSRC-RP-89-1249, November 1989.
5. Bell, G. I. and Glasstone, S., Nuclear Reactor Theory, Huntington, New York: Robert E. Krieger Publishing Company 1979.
6. Lamarsh, J. R., Introduction to Nuclear Reactor Theory, Reading, Mass.: Addison-Wesley Publishing Co., Inc. 1966.
7. J. E. Aull, G. L. Hire, and R. E. Pevey, ARCHY User's Manual (U), WSRC-RP-90-1129, November 1990.
8. R. D. Crowe, H. Toffer, E. F. Trumble, GRIMHX Verification and Validation Summary Report, WSRC-TR-91-358, May 1991.

END

DATE
FILMED
21/01/93