0006438

1 OF 1

2
NOV 02 1992

DOE/PC/91043--T4

DOE/PC/91043--T4

DE93 006438

**AN INVESTIGATION OF THE ROLE OF WATER ON
RETROGRADE/CONDENSATION REACTIONS AND ENHANCED
LIQUEFACTION YIELDS**

**By
Francis P. Miknis**

October 1992

Quarterly Progress Report for the Period July 1, 1992 - September 30, 1992

Work Performed Under DOE Contract, DE-AC22-91PC91043

**By
Western Research Institute
Laramie, Wyoming**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BACKGROUND

The overall objectives of this work are to conduct research that will provide the basis for an improved liquefaction process, and to facilitate our understanding of those processes that occur when coals are initially dissolved. Changes in coal structure that occur during coal drying and steam pretreatments will be measured in order to determine what effect water has on retrograde/condensation reactions, and to determine the mechanism by which water enhances coal reactivity toward liquefaction. Different methods for coal drying will be investigated to determine if drying can be accomplished without destroying coal reactivity toward liquefaction, thereby making coal drying a relatively economical and efficient method for coal pretreatment. Coal drying methods will include conventional thermal drying, microwave drying, and chemical drying at low temperature. State-of-the-art solid-state nuclear magnetic resonance (NMR) techniques using combined rotation and multiple pulse spectroscopy (CRAMPS) and cross polarization with magic-angle spinning (CP/MAS) will be employed: (1) to measure changes in coal structure brought about by the different methods of drying and by low temperature oxidation, and (2) to obtain direct measurements of changes in the aromatic hydrogen-to-carbon ratio of the solid/semisolid material formed or remaining during pretreatment and the initial stages of liquefaction. The aromatic hydrogen-to-carbon ratios are difficult, if not impossible, to measure without the use of solid-state NMR, and as a result this ratio will be used to monitor the retrograde/condensation reactions that take place during coal liquefaction in the presence and absence of steam and various inert gases.

RESULTS

The objectives for this quarter were to begin coal drying experiments using thermal, microwave, and chemical methods. The initial coal drying experiments are being conducted on an Eagle Butte coal from the Powder River Basin near Gillette,

Wyoming and a Usibelli coal from Alaska. Both coals are subbituminous rank. In addition, a stirred microautoclave reactor system was acquired during the quarter. This reactor will be used for some of the liquefaction experiments that are planned. Work on each of the subtasks is described in separate paragraphs.

Coal Preparation

In order to study the effects of different methods for drying coal on moisture removal, a master batch sample (~500 g) of Eagle Butte coal was prepared by grinding and screening to -20, +100 mesh particle size. This sample was placed in a wide mouth jar and placed in an oven with a beaker of water, and allowed to equilibrate at 40°C for 24 hrs. The sample was then removed from the oven and placed in a humidifier until aliquots were taken for the different drying tests.

Thermal Drying

Little effort was devoted to thermal drying during the quarter. Previous work had demonstrated that a large oven that had been used at WRI for coal drying was not satisfactory. Presently, we are testing a small, controlled-temperature furnace to determine whether more reasonable heating rates and more consistent weight losses can be achieved. Currently, we are accepting the weight loss after 24 hrs as the as determined moisture values for the coals.

Microwave Drying

A number of microwave drying experiments using Eagle Butte subbituminous coal were conducted during the quarter. Most of the experiments were conducted using a CEM model MDS 81-D laboratory microwave oven that is equipped with facilities to introduce different gaseous environments. A few experiments were conducted using in a conventional microwave oven used for cooking.

An objective of the microwave drying subtask is to determine whether microwave drying alters the structure of the coal, and hence its behavior toward liquefaction. This work was prompted by earlier work of Silver and Frazee (1985) that indicated a change in the liquefaction behavior of Clovis Point coal after ~ 75% of the moisture was removed by microwave drying (Figure 1). Preliminary results obtained in the present study (Figures 2 and 3) using our microwave apparatus, qualitatively confirm the temperature behavior of coals dried by microwaves, in that there is a rapid temperature rise after removal of ~ 75 % of the moisture. At 100% microwave power (Figure 3) moisture removal is very rapid, attaining 75% removal in about 2 minutes. Microwave drying experiments for longer periods of time (Figure 4) indicated that greater levels of moisture were removed compared to thermal drying. However, we were not able to discern any major changes in the carbon structure using CP/MAS ^{13}C NMR measurements (Figure 5).

The NMR data in Figure 5 do hint at possible slight changes in carbon structure in that there is less "resolution" of phenolic carbons (~155 ppm) in the microwaved coals compared to the starting coal. We hope to investigate this more thoroughly next quarter using ^1H NMR measurements. In addition, we hope to begin liquefaction tests on the microwaved coals to determine to what extent drying affects the liquefaction behavior.

Some exploratory microwave heating experiments were performed on model compounds to determine whether microwaves interact with certain functional groups in coals, particularly OH groups which have a strong dipole moment. Standard microwave ovens operate at 2450 MHz which is the optimum frequency for microwave absorption of water molecules. Therefore, it would be of interest to know whether hydroxyl components in the coal structure also absorb at 2450 MHz. Consequently, exploratory experiments were performed on model compounds: phenol ($\text{C}_6\text{H}_5\text{OH}$), benzoic acid ($\text{C}_6\text{H}_5\text{COOH}$), stearic acid ($\text{CH}_3(\text{CH}_2)_{16}\text{COOH}$), and stearyl alcohol ($\text{CH}_3(\text{CH}_2)_{16}\text{COH}$). All materials are solids at room temperature. About 2 grams of the model compounds were placed in the microwave oven and irradiated for

1 hr at 100 % power, after which the % weight loss was determined. The results are summarized below.

<u>Compound</u>	<u>mp, °C</u>	<u>bp, °C</u>	<u>Weight Loss, %</u>
Benzoic Acid	122-123	249	0.053
Phenol	40-42	182	13.07
Stearic Acid	67-69	183-184	0.345
Stearyl Alcohol	60-61	170-171	0.186

Except for benzoic acid, which showed the smallest weight loss, all compounds melted during microwave heating. In addition, phenol appeared to have undergone a chemical reaction as evidenced by a color change from white to red. The other compounds resolidified to their original colors when returning to room temperature.

Chemical Drying

Chemical drying experiments were conducted on Eagle Butte and Usibelli subbituminous coals using 2,2-dimethoxypropane as a drying agent, and following the methodology described in the previous quarterly, but modified to measure the moisture content as a function of time. The modification is as follows: one-half gram of coal was weighed into a 10 mL centrifuge tube followed by 2 mL of 0.2 N $\text{CH}_3\text{SO}_3\text{H}$ in CH_3OH and 1 mL of the reference standard cycloheptane. Four mL of dimethoxypropane was then added to the mixture. The total mixture was stirred, then centrifuged for 10 minutes. After 2, 4, 6, and 8 hours, one-half mL aliquots were removed, diluted with one-half mL CDCl_3 , and the ^1H NMR spectrum recorded. The solution was stirred and centrifuged prior to removing the aliquots.

The results of these experiments are summarized in Figure 6. As expected, the measured moisture content increased with time and reached a maximum after about 8 hrs. The data suggest that two types of water are removed sequentially. Free or surface sorbed water is rapidly removed upon contact with the drying agent, followed by removal of more tightly bound water as the reagents diffuse into the

micropore structure. There appears to be an induction period of about 4 hrs for the Eagle Butte coal before the moisture content increases more rapidly due to removal of the more tightly bound water. Experiments next quarter will confirm or refute this preliminary observation.

The chemical drying experiment was repeated twice for the Usibelli coal. In the first experiment, aliquots were removed sequentially, and in the second experiment, separate coal samples were prepared and allowed to stand until the appropriate time for acquisition of the ^1H NMR spectrum. The data show excellent reproducibility.

Both coals were thermally dried at 110°C for 1 hour. The moisture content was determined by weight loss. Eagle Butte coal had an as determined moisture content of 16.6 wt% and the Usibelli had an as determined moisture content of 14.1 wt%. These values are close to the early time moisture contents determined by chemical drying.

Miscellaneous

During the quarter WRI acquired a "Borgialli" microreactor from the Wilsonville Two-Stage Advanced Coal Liquefaction Research Facility. This is a magnetically-stirred, microautoclave system developed at the University of Wyoming by Mr. Ron Borgialli under an EPRI coal liquefaction contract (Silver and Frazee 1985). Subsequently, one of these systems was purchased by the Southern Company Services, Inc. for use at the Wilsonville Coal Liquefaction R&D facility. WRI acquired this reactor after the Wilsonville facility was shutdown earlier this year.

The key features of this reactor system are: rapid heating through submergence in a fluidized sandbath, pneumatic control of the extent of autoclave submergence, and continuous stirring using a magnetically-coupled stirrer.

The original autoclave had a capacity of 75 cc with an inside diameter of 1.75 cm. This system was modified at Wilsonville to increase the volume and, as a result, improve material balances. The improved system, called VaSTeC for Variable Submergence Temperature Control because temperature excursions were controlled by varying submergence (see Figure 7), was used extensively and reliably to predict and augment test results from the Wilsonville thermal liquefaction unit (TLU)(Catalytic, Inc. 1986). The VaSTeC system is large enough to provide adequate materials for post-experiment analyses, yet is small enough to provide the rapid heating and cooling required for kinetic experiments.

The repeatability of product yields from the VaSTeC autoclave is excellent as is shown in Table 1 (Catalytic, Inc. 1986)

Table 1. VaSTeC Autoclave Repeatability

<u>Product</u>	<u>Repeatability, 1 σ</u>
H ₂	±0.08%
H ₂ O	±1.1%
H ₂ S	±0.01%
CO ₂ +CO	±0.3%
C ₁ -C ₃	±0.3%
C ₄ -1000°F	±2.4%
Resid	±2.1%
*UC	±0.5%

* UC = Unconverted Carbon

One problem with the VaSTeC autoclave system is the tendency to distribute sandbath sand generously throughout the laboratory. A visit with Mr. Borgialli revealed that he had modified his design to eliminate the sandbath, using instead a

standard laboratory furnace. He stated that this change had little, if any, affect on the sample heating rate. This modification is currently being made to WRI's autoclave system. A new temperature control system is being installed as part of the modification. The rest of the VaSTeC autoclave system will closely mimic the Wilsonville setup shown in Figure 7. The design is simple and eliminates excess system volume to maximize the fraction of product gases in the final gas mixture. Nonvolatile products are removed after cooling and depressurization. Shakedown and operation of the autoclave system will commence in the next quarter.

The principal investigator and two other key personnel visited PETC and attended the Coal Liquefaction Contractor's Meeting in Pittsburgh, September 22-24, 1992.

REFERENCES

Catalytic Inc, 1986, Development of VaSTeC Autoclave Technique and Applications to Pilot Plant Guidance, Catalytic Inc., Wilsonville, AL, April, 1986, Topical Report, prepared for U.S. DOE (Contract No DE-AC22-82PC50041) and EPRI (Contract No. RP1234-1-2).

Silver, H.F., and W.S. Frazee, 1985, Integrated Two-Stage Coal Liquefaction Studies, Laramie, WY, August 1985, Final Report, EPRI project RP2147-3.

Figure 1. Coal Temperature as a Function of Moisture Removed in Microwave Drying Experiments of Silver and Frazee (1985).

Figure 2. Coal Temperature as a Function of Moisture Removed at 300 Watts of Power.

Figure 3. Coal Temperature as a Function of Moisture Removed at 600 Watts of Power.

Figure 4. Percent Moisture Removed as Function of Microwave Drying Time.

Figure 5. Solid-State ^{13}C NMR Spectra of Eagle Butte Coal Subjected to Microwave Drying for Different Periods of Time (weight loss from thermal drying = 22.5 %).

Figure 6. Chemical Moisture Determinations Versus Time in Eagle Butte and Usibelli Coals.

Figure 7. Schematic of VaSTec Autoclave System.

END

DATE
FILMED
319193