PNL--7980

DE93 006445

SUMMARY OF RESEARCH ON
MICROBIOLOGICAL PROCESSES

INTERNATIONAL ENERGY AGENCY
SUBTASK D FINAL REPORT

A. L. Winters

September 1992

Prepared by
Department of Biological Sciences
University of Alabama
for Pacific Northwest Laboratory
under Contract DE-AC06-76RLO 1830
with the U.S. Department of Energy
Subcontract 005383-A-M

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

GENERAL INTRODUCTION

IMPLEMENTING AGREEMENT ENERGY STORAGE

The following report is one of the Subtask Reports of Annex VI to the International Energy Agency's Implementing Agreement Energy Storage.

The Implementing Agreement Energy Storage is an Agreement established in 1979 between a number of IEA countries with the aim of cooperative research, development, demonstrations and exchanges through energy storage. The full name reads: "Implementing Agreement for a Programme of Research and Development on Energy Conservation through Energy Storage".

The separate activities put into execution within the framework of an Implementing Agreement are called Tasks or Annexes. Signing of the Implementing Agreement does not commit to participation in all Annexes, but has to be seen as a declaration of intention to contribute to the attainment of the objectives of the Implementing Agreement by participating in one or more Annexes.

HISTORICAL BACKGROUND ANNEX VI

Annex VI to the Implementing Agreement Energy Storage entered into force on February 1, 1987. At that moment the aquifer heat storage project SPEOS at Dorigny (Switzerland) had been working for 5 years. This project had been included as a pilot project in the framework of Annex III to the same Implementing Agreement. Similarly, the exchange of information concerning pilot projects in Denmark (Horsholm project) and the United States of America (St. Paul field test facility) were also part of Annex III. Experience so far with these and other aquifer thermal energy storage projects had shown clearly that precipitation of chemical substances was the principal technical problem. The reliability of the applied water treatment methods was also questionable because of the lack of information on slow underground chemical reactions and the possible interactions between microbiological and chemical processes.

From experience with surface water injected into aquifers for drinking water it is well known that growth of bacteria in and around the well can cause serious clogging problems. Such problems had not yet arisen at heat storage projects, but they could occur in the future nevertheless, especially within the realm of low-temperature storage.

Furthermore, growth of bacteria in and around the well might render the water from the source unsuitable for human consumption.

Addition of hydrochloric acid, as applied at the SPEOS project for instances, seemed to be an effective water treatment method to prevent calcification. But this method can have adverse effects on the groundwater quality.

The resultant environmental impact could present a serious obstruction to the implementation of larger scale underground thermal energy storage projects.

Because the storage of thermal energy in aquifers is both technically and economically feasible, high priority must be attached to improving the reliability of the storage system by solving such (bio)geochemical and environmental problems. So, eight countries decided to broaden the scope of the activities within the Implementing Agreement Energy Storage to include the systematic investigation of the chemical, microbiological, and environmental impacts of aquifer thermal energy storage, and subsequently to the development of reliable, environmentally sound water treatment methods.

With this, Annex VI entitled "Environmental and Chemical Aspects of Thermal Energy Storage in Aquifers and Research and Development of Water Treatment Methods" was a reality.

ANNEX VI

The storage of heat in an aquifer causes underground changes in temperature and a flow of the groundwater (including the chemical substances and microorganisms). The distribution of groundwater and heat in the soil do not form part of the research within the

framework of Annex VI. Sufficient information is already available from other research in these areas.

The Annex VI research is directed at:

- The consequences of temperature changes and groundwater flows on chemical processes and equilibria underground.
- The consequences of temperature changes and groundwater flows on microbiological processes and equilibria underground.
- The interaction between the chemical and microbiological composition of sediment and groundwater.
- The effectiveness of water treatment to prevent precipitation and microbial clogging.
- The adverse effects on the environment of chemical and microbiological changes caused by heat storage, as well as the applied water treatment method.
- Corrosion of materials applied in wells, mains, and heat exchangers as a result of contact with groundwater (whether treated or not).

The connection between the different facets of Annex VI has been given in the following outline.

The objectives of Annex VI have been formulated as follows:

- A. To develop and verify a simulation model that calculates the space and time dependent mass-transport of discrete chemical constituents in an aqueous medium in soil.
- B. To analyze by theory and experiment the (bio)geochemical reactions and related environmental impacts caused by heat storage in different aquifers.
- C. To classify and analyze different water treatment techniques for heat storage with respect to environmental impacts, long-term efficiency, and costs.
- D. To analyze, by theory and experiment, the microbiological process during thermal energy storage in relation to hygienics, bacterial clogging processes, and relevant treatment techniques.
- E. To analyze scaling and corrosion problems in installations connected to aquifer heat stores (heat exchangers, mains, and screens) in relation to water chemistry and water treatment.
- F. To test selected water treatment techniques and evaluate their environmental effects in laboratory and field experiments.
- G. To develop a generically applicable procedure for the choice of an optimized water treatment method to be used at future aquifer heat storage sites.

Annex VI has been subdivided into Subtasks. These Subtasks have been numbered A up to and including G. The objective of Subtask A has been formulated as under above mentioned item A, of Subtask B under item B, etc.

The research activities started in 1987 concerned Subtasks A up through and including Subtask E. These Subtasks together constitute the first phase of Annex VI with a duration of about 3 years. The second phase of Annex VI includes Subtasks F and G. An exact formulation of the activities to be included in Phase II can only be made after the completion of Phase I. The estimated term for phase II is 2 years.

PARTICIPATING COUNTRIES

Of the countries having signed the Implementing Agreement Energy Storage, the following participate in Annex VI:

<u>Country</u>	<u>Contracting Party</u>
Canada	Public Works Canada
Denmark	The Ministry of Energy
Finland	The Department of Energy
Germany	Kernforschungsanlage Julich GmbH
The Netherlands	The Management Office for Energy Research PEO
Sweden	The Swedish Council for Building Research
United States of America	The Department of Energy

ABSTRACT

Storage of thermal energy in aquifers has obvious benefits of saving energy and decreasing the consumption of fossil fuels. However, aquifer thermal energy storage (ATES), which involves groundwater aquifers as the storage medium for heat or chill, impinges on the environment. A literature review of pertinent microbiology publications (Hicks and Stewart, 1988) identified the potential for the interaction of ATES systems and microbiological processes to create a source of infectious diseases and the potential for damage to the environment. In addition, the review identified a potential for microbiological processes to develop conditions that would interfere with the operation of an ATES system. As a result of this research effort, investigators from Finland, Germany, Switzerland, and the United States have examined several ATES systems in operation and have observed that the ATES systems studied do not contribute to infectious disease transmission, do not adversely affect the environment, and do not contribute significantly to biofouling or biocorrosion.

SUMMARY

This work was performed for the International Energy Agency (IEA) "Implementing Agreement for a Programme of Research and Development on Energy Conservation through Energy Storage", Annex VI "Environmental and Chemical Aspects of Thermal Energy Storage in Aquifers and Research and Development of Water Treatment Methods", Subtask D - Microbiological Processes. The objective of Annex VI is to assemble sufficient knowledge and information for confident selection of water treatment methods for aquifer thermal energy storage (ATES) systems, if or when necessary. Such knowledge and information must be obtained from a systematic investigation of the chemical, microbiological, and environmental impacts associated with water treatment methods considered for use at prospective sites. Subtask D specifically deals with the analysis, by theory and experiment, of the principal microbiological processes. The countries contributing to IEA Annex VI, Subtask D, include Finland, Germany, Switzerland, and the United States.

As chairman for Subtask D, the United States Department of Energy through its Pacific Northwest Laboratory is responsible for preparing a consolidated report from all participants. Pacific Northwest Laboratory is operated for the U.S. Department of Energy by Battelle Memorial Institute under contract DE-AC06-76RL0 1830. A contract has been placed with Dr. Alvin L. Winters of the University of Alabama for this activity. This document fulfills that obligation and details the contributions from each participant country and their subsequent findings and conclusions. Significant findings include:

- Adverse environmental effects caused by microbiological processes have not been observed in the ATES systems examined.
- Significant biofouling was not observed in the ATES systems examined.

- Pathogenic bacteria were not observed in the ATEs systems examined.
- An ATEs model system that was contaminated with coliform bacteria did not generate significant increases in the bacterial population.

CONTENTS

GENERAL INTRODUCTION	iii
ABSTRACT	ix
SUMMARY	xi
GLOSSARY	xvii
INTRODUCTION	1
INTRODUCTION TO MICROBIOLOGICAL TERMS	2
METHODS	5
RESULTS AND DISCUSSION	7
HUMAN EXPOSURE TO PATHOGENIC MICROORGANISMS	7
Germany	7
Switzerland	7
United States	12
MODIFICATION OF AQUIFER NORMAL FLORA	21
Heat Storage	21
Germany	21
Switzerland	29
United States (University of Minnesota)	30
Chill Storage	31
United States (University of Alabama)	31
BIOFOULING OF HEAT EXCHANGERS AND AQUIFER POROSITY DURING ATEs SYSTEM OPERATION	32
Germany	32
Finland	33
SCALING AND CORROSION CAUSED BY MICROBIOLOGICAL ACTIVITY DURING ATEs SYSTEM OPERATION	34
CONCLUSIONS	35
REFERENCES	37
APPENDIX - PAPER BY MONTANDON AND ANTONIETTI	A.1

FIGURES

1	The Dorigny ATES (SPEOS; Stockage pilote d' énergie par ouvrage souterrain) System - Loading and Unloading Cycles	9
2	Small-Scale Model of the Dorigny ATES System	10
3	Effect of Incubation Temperature on a Suspension of a Fecal Coliform in a Small-Scale Model of the Dorigny ATES System	11
4	Design of the UA-ATES System and Location of Sample Collection Sites During the Chill Storage Cycle	14
5	Design of the UA-ATES System and Location of Sample Collection Sites During the Chill Recovery Cycle	15
6	Dimensions of the UA-ATES System and the Chilled-Aquifer Plume at Week 14 (March 6, 1989) of the 72-Week Study Period (12/88 - 4/90)	16
7	Pumping Patterns During the 72-Week UA-ATES Study Period (12/88 - 4/90)	18
8	UA-ATES Coliform Quantification During the 72-Week Period (12/88 - 4/90)	19
9	Legionella Species Detected in Conventional Cooling Towers Outside the UA-ATES System During the Study Period (12/88 - 10/90)	20
10	Dimensions and Design of the Impounded ATES System at the Institute of Thermodynamics and Heating Technique at the University of Stuttgart	22
11	Population of Heterotrophs at the Stuttgart Impounded ATES System - Storage Water versus Circulation Water	24
12	Large-Scale Model of the Stuttgart ATES System	25
13	Taxonomic Groups of Heterotrophic Bacterial Flora in Different Temperature Zones of the Large-Scale Model of the Stuttgart ATES System	27
14	Small-Scale Model of the Stuttgart ATES System	28

15	Effect of Heating Dorigny Aquifer Sand in Small-Scale Models	29
16	Heterotroph Quantification During the Study Period at the UA-ATES System (12/88 - 4/90)	33

TABLES

1	Water-Associated Pathogens Targeted for Isolation and Identification in the UA-ATES System	17
---	---	----

GLOSSARY

aerobes - organisms that grow in the presence of oxygen.

anaerobes - organisms that grow in the absence of oxygen.

antibody - a protein present in the serum that combines specifically with components of the microbial cell. The specific binding can be used to identify microorganisms.

ATP (adenosine triphosphate) - a compound that serves a major and central role in the energy transfer within a cell. Quantification of ATP is indicative of the amount of cells present, whether the cells can or cannot be cultured.

clinical - founded on actual observation and treatment of patients.

epidemiology - the study of incidence, transmission, and causative agents in populations.

facultative - indicates that an organism is able to grow either in the presence or absence of an environmental factor.

indigenous - occurring or living native to the local environment, not introduced by human activity.

mesophiles - bacteria that grow optimally at approximately 37°C.

opportunistic pathogen - the organism is usually harmless, but under certain conditions it will cause disease.

pathogenic - capable of causing disease.

psychrophiles - bacteria that grow at low temperatures (0 to 10°C).

thermophiles - bacteria that grow optimally at 55°C or higher.

thermoduric - a mesophilic organism that usually doesn't grow at higher temperatures (>60°C), but will survive and grow when the temperature is lowered.

INTRODUCTION

The storage of thermal energy, either heat or chill, in natural or impounded aquifers has demonstrated the potential for notable energy savings as compared to currently used energy consuming technologies (Reilly, 1980). However, aquifer thermal energy storage (ATES) systems using natural aquifers impinge on the microorganisms indigenous to the aquifer by creating a local perturbation in the environmental properties of the aquifer and by creating an artificial two-way communication between the aquifer penetrated by ATES system wells and the surface environment near the ATES system site. The local changes of the surface and subsurface environment that are associated with ATES systems have the potential for creating four broad microbiological problems as listed below. The order of this listing does not imply a ranking to the importance of the problems.

1. Human exposure to pathogens and opportunistic pathogens can occur by interaction with ATES system water obtained from a contaminated aquifer. ATES system operation may or may not contribute to the contamination.
 - A. The human exposure could occur by ingestion of contaminated water; however, the usual design of ATES systems would reduce the opportunity for ingestion, i.e., the water is directly re-injected into the aquifer or is disposed of in a manner that would prevent ingestion.
 - B. A more probable human exposure would occur when aerosols generated by cooling towers are dispersed in the general vicinity of human activities and inhaled.
2. Major modification of aquifer normal flora by ATES operation with adverse environmental impact.
3. Biofouling of heat exchangers and aquifer porosity during ATES system operation.
4. Scaling and corrosion caused by microbiological activity during ATES system operation.

Potential problems associated with ATES system operation can be subdivided further into the problems that are unique to chill-storage and heat-storage systems. Both chill-storage and heat-

storage systems are likely to cause problems in the areas of disease transmission and modification of aquifer normal flora. Additional problems, such as biofouling, scaling, and corrosion, will be associated with heat and chill storage operation. All of these problems will directly affect the design, development, and operation of ATES systems.

Investigation of these potential problems has been performed by laboratories in Germany, Switzerland, the United States, and Finland. Both operating ATES systems and laboratory models of ATES systems have been examined. The observations made to date by the research groups in Annex VI, Subtask D indicate that current ATES system operation is not significantly affected by the potential problems listed above. Adverse environmental effects caused by microbiological processes have not been observed in the ATES systems examined in Germany, Switzerland, and the United States.

INTRODUCTION TO MICROBIOLOGICAL TERMS

- **Colony forming units (CFU)** - The basic life form of bacteria is a single cell of microscopic dimensions. When placed under the appropriate culture conditions, such as on the surface of a bacteriological culture medium (a solidified agar gel containing the appropriate nutrients), each single bacterial cell is capable of dividing in an exponential manner, 1 cell begets 2 cells and 2 cells beget 4 cells, etc. This rapid method of growth forms a macroscopically visible mat of bacterial cells. This localized mat of growth is referred to as a colony. A single cell may or may not grow depending on the environment of the culture; consequently, the quantification of microorganisms by counting colonies is conditional. The relative number of bacterial cells in a water sample is quantified by colony counts and is referred to as the number of colony forming units (CFU), rather than the total number of cells. The concentration of bacteria in water samples is expressed as CFU/ml. The exponential characteristic of bacterial growth requires that caution be used in interpreting differences in the bacterial concentrations reported as CFU/ml, i.e., the difference between 1 CFU/ml and 16 CFU/ml is only four cell divisions and those four cell divisions frequently can occur within 2 hours.
- **Gram-positive and Gram-negative Bacteria** - Most of the single cell bacteria have evolved with one of two types of biochemically distinct cell wall structures in order to cope with internal osmotic pressure that is generated when bacteria

grow in most natural waters. This biochemical difference in cell wall structures can be detected with a relatively simple staining procedure called the Gram stain. This procedure is used to initiate the classification of bacteria as either gram-positive or gram-negative. Additional tests are then performed for further classification.

Relatively few species of gram-positive and gram-negative bacteria are associated with human disease, and most of the bacteria in these groups do not interact with the human. The toxins, symptoms, and diseases associated with the relatively few, disease-causing bacteria are very distinct in their presentation and depend on whether the species has a gram-positive or gram-negative cell wall. Thus, the gram stain reaction is an integral part of determining the epidemiological and clinical significance of bacterial isolates obtained from water samples.

• **Pathogenic Microorganisms** - The term pathogenic refers to the ability of a microorganism to cause disease. A specific microorganism that is usually associated with infection and disease is referred to as a pathogen. The use of the term pathogenic or pathogen in this report refers specifically to the ability of the microorganism to cause human disease. Some microorganisms will not cause disease in the normal, healthy individual, but will cause disease in individuals that have been exposed to unusually high numbers of the microorganism, or are predisposed to infection by injury (such as burns or cuts in the skin) or disease (such as chronic heart disease) or old age. Organisms placed in this category are called opportunistic pathogens. Pathogens or opportunistic pathogens can be transmitted to the human from contaminated water by direct contact with the skin, ingestion, or inspiration of aerosols/droplets. An opportunistic pathogen in the water usually does not cause disease unless the microorganism is present in relatively high concentrations ($> 10,000$ CFU/ml). Each pathogen usually has a very specific mechanism of transmission. Enteric pathogens are associated with intestinal infections and are transmitted by fecal contamination of water. Fecal coliforms are bacteria that are normal flora of the human and domestic animal gut and their presence in water indicates the potential for enteric pathogen transmission. Coliforms are bacteria that have nutritional requirements and culture characteristics that are similar to fecal coliforms, but they are not specifically gut-associated. Their presence in water does not indicate the potential for enteric pathogen transmission, but their levels in water generally have an inverse relationship to the quality of water, i.e., a low CFU/ml indicates a high quality of water.

- **Heterotrophic Bacteria** - Heterotrophic bacteria or heterotrophs is an operational classification that includes many diverse taxonomic groups of gram-positive and gram-negative bacteria. All heterotrophs are capable of utilizing organic compounds for an energy source and for synthesis of their organic constituents. The concentration of heterotrophic bacteria in water generally has an inverse relationship to the quality of water, i.e., a low CFU/ml indicates a high quality of water.

METHODS

The microbiological studies of ATEs systems involve careful coordination of several operations. These are sample collection, transport, processing, culture, and counting or identification. Many of the techniques associated with water microbiology (heterotroph and coliform counts) have been standardized (American Public Health Association, 1989), while other techniques for human pathogens, such as *Legionella pneumophila*, vary from laboratory to laboratory.

Water or sand samples must be obtained using techniques that ensure the resulting types and amounts of growth are representative of sample microbiota. Because of the ubiquitous nature of microorganisms, extreme care is taken in obtaining samples, i.e., flushing fully opened water spigots for 15 minutes before collecting the specimen or collecting sand or precipitates using aseptic techniques similar to a surgeon. Elaborate precautions in sample collection are necessary because a small particle (1.0 mm^3) of extraneous material could contain up to 10^9 CFU.

The sample must then be transported to a laboratory for culture of the microorganisms. As discussed in the "Introduction to Microbiological Terms" section, microorganisms multiply in an exponential manner, thus even a small amount of growth during transport can affect the interpretation of the results. Changes in the microbial content of a sample are avoided by rapidly chilling the sample to near 0°C or by rapid transport (10 to 15 min) to the laboratory.

Processing of samples is modification of the sample to permit countable numbers or detection of the microorganism to be obtained. Water samples are usually filtered through specialized filters called membrane filters to increase the concentration of the microorganisms. The microorganisms are trapped on the surface of the filter and are either cultured directly on the filter or washed free of the filter for culturing. Standard volumes filtered are 100 ml and 1,000 ml. Adherent microorganism are released from the sand

or precipitate for culture by vigorous agitation of the particles in water or a specialized growth medium.

Culturing microorganisms is relatively complex and the degree of complexity depends on the type of microorganism targeted for study. Specific nutrient agar-based media are used to immobilize the cells on the agar surface. After appropriate incubation time, the colonies are counted directly on the agar-based plates or membranes that have been placed on agar-based plates. If the microorganism targeted for detection is present in very low numbers, the membrane filter or sand may be placed in a liquid enrichment medium. These media allow only one or two cells to grow to easily observed concentrations.

Identification of the species of a given microorganisms is based on many tests. These include the gram-stain morphology, fermentation of sugars, biochemical tests, growth in the presence of inhibitory substances, and reactions with antibodies.

Finally, all of the above procedures must be performed using aseptic techniques to avoid contamination of the samples and to prevent infection of laboratory personnel. The procedures described not only detect and enumerate the target microorganism, but also allow the growth of the microorganisms to unnaturally high concentrations. When pathogenic microorganisms, such as *Legionella pneumophila*, are suspected, the procedures are performed in biological containment cabinets.

RESULTS AND DISCUSSION

As part of the IEA, Annex VI, Subtask D "Microbiological Processes" effort, researchers from Finland, Germany, Switzerland, and the United States investigated four broad, potential, microbiological problems associated with the operation of ATES systems: human exposure to pathogenic microorganisms, modification of aquifer normal flora with adverse environmental impact, biofouling of heat exchangers and aquifer porosity during ATES system operation, and scaling and corrosion caused by microbiological activity during ATES system operation. Each of the four problems and the results of the IEA investigation into each problem is discussed below.

HUMAN EXPOSURE TO PATHOGENIC MICROORGANISMS

Germany

A large-scale model of an impounded ATES system was constructed at the Institute for Urban Hydrotechnic, Water-, and Waste Treatment - Biology Division, University of Stuttgart (Institut Für Siedlungswasserbau, Wassergüte- und Abfallwirtschaft - Abteilung Biologie - Universität Stuttgart). The rationale for construction and design of the large-scale model is described below. The investigators noted that coliforms were found in all samples at a *constant low level*. The enteric bacteria originated from the test plants (sewage treatment) that were in the immediate vicinity of the large-scale model. It is very probable that the enteric bacteria were fecal coliforms. This observation is extremely important, because it demonstrates that continued ATES system operation under a variety of temperatures does not increase the levels of enteric bacteria within the ATES system.

Switzerland

The Laboratory for Water Supply, Neuchâtel (Laboratoire du service des Eaux de la Ville, Neuchâtel) and the Laboratory of Microbiology, University of Neuchâtel (Laboratoire de Microbiologie,

Université de Neuchâtel) in Switzerland are examining the possibility of accidental contamination of ATES system aquifers with facultative thermophilic or thermophilic bacteria with potential for transmitting human infections. The investigation examined the pilot ATES system located at Dorigny, Switzerland (Miserez, 1989; Aragno et al., 1990). This ATES system was designed for heat storage at temperature of 50 to 80°C (Figure 1). Two stages of ATES were examined. In the first ATES stage (1982 to 1985), heat was stored in the upper aquifer. In the second ATES stage (1985 to 1991), heat was stored in the lower aquifer. Microbiological studies were performed during the second stage (October 1989 to January 1990).

Sand was obtained from wells drilled in the aquifer. Although coliform-like bacteria were isolated from the sand, coliforms or fecal coliforms were not isolated. Small-scale models of the Dorigny ATES system were constructed and connected to the ATES system (Figure 2). These models used water directly from the ATES system and allowed the investigation of the effects of aquifer water and temperatures on known laboratory bacteria without contaminating the ATES system. When a fecal coliform (*Escherichia coli*, strain B, Neu 1006) was added to Dorigny aquifer sand and incubated at temperatures measured in the operating ATES system, the bacterium did not survive (Figure 3). A second bacterium in a taxonomic group associated with fecal contamination (*Enterococcus* species) demonstrated a similar pattern of cell death.

Two opportunistic pathogens were targeted for additional study. The specific organisms were *Pseudomonas aeruginosa* and *Legionella pneumophila*. *Legionella pneumophila* is found in environments with elevated temperatures and is associated with lung infections in the human (pneumonia) after inspiration of droplets from contaminated water. *Pseudomonas aeruginosa* is associated with skin, mammary gland, and urinary tract infections after bathing in contaminated water (Zwadyk, 1988). The laboratories in Switzerland have established procedures for the detection of *Pseudomonas* species and are currently developing procedures for the detection of *Legionella*

Figure 1. The Dorigny ATEs (SPEOS, Stockage pilote d' énergie par ouvrage souterrain) System - Loading and Unloading Cycles

SAND FILTER DESIGN

SAND FILTER PLUMBING

Figure 2. Small-Scale Model of the Dorigny ATES System

Figure 3. Effect of Incubation Temperature on a Suspension of a Fecal Coliform in a Small-Scale Model of the Dorigny ATES System

species. *Pseudomonas* were indigenous in the Dorigny aquifer. Studies were next directed toward developing a procedure for the treatment of a single large volume of wastewater that could be stored and used in subsequent thermal inactivation studies. The methods of membrane filtration, autoclaving (sterilization by heat), and a combination of filtering and autoclaving were examined, but conclusive results were not obtained.

The survival of *Legionella* spp. in ATES system water from the SPEOS heat storage site, near Lausanne, was investigated by Montandon et al. (see Appendix). Clinical isolates of *L. pneumophila* and *L. micdadei*, when introduced to autoclaved ATES system water, were shown to decrease from an initial population of 3160 CFU/ml to about 300 CFU/ml when incubated at 37°C. In

autoclaved and filtered ATES system water, the introduced clinical isolates were reduced to below detection level in 2 weeks. In nonsterile and nonfiltered ATES system water, the indigenous heterotrophic population increased 3000-fold while the introduced *L. pneumophila* decreased tenfold in 10 days. Although the results suggested that *Legionella* spp. could survive in an ATES system, they also indicated that *Legionella* spp. may not be able to compete with indigenous bacteria. Furthermore, growth of the introduced clinical *Legionella* spp. in the ATES water was not found. Considering that there is no indication that *Legionella* spp. were found to be indigenous in the ATES portion of the Dorigny aquifer, human exposure to *Legionella* spp. in the ATES operation appears to be insignificant.

United States

University of Alabama (UA)

The potential for propagation of pathogens in an ATES system has been reviewed comprehensively by Hicks and Stewart (1988). The UA-ATES system has an inherent potential for propagating and transmitting human pathogens because of the formation of aerosols associated with water chilling in a conventional cooling tower. A laboratory in the United States [Department of Biological Sciences (formerly Department of Microbiology), University of Alabama, Tuscaloosa, Alabama] examined the chill-water UA-ATES system for the presence of pathogenic microorganisms. This ATES system has been operating at The University of Alabama Student Recreation Center since 1982 (Midkiff, Song, and Brett, 1991). This system chills and stores 60,000 to 75,000 m³ of water in the Tuscaloosa aquifer during the winter months and uses the chilled water for air conditioning [52 kW (148 tons)] during the summer months. The aquifer layer lies above the indurated Pottsville formation, which acts as an aquiclude and limits the downward migration of groundwater. The lower part of the layer is marked with siliceous sand and clay, and becomes more gravelly and less sandy toward the surface, which is mostly red clay. Approximately 30 m of alluvial material overlies the Pottsville formation at the UA-ATES site with the saturated zone

occupying the lower 10 m. Warm water was pumped from Wells 1, 2, and/or 3, and chilled in a conventional cooling tower (Figure 4). When the water was chilled to $\leq 9^{\circ}\text{C}$, it was pumped into Wells 4, 5, and/or 6 for storage in the aquifer (Figure 5). The plume of chilled water migrated laterally approximately 1.1 meters per week (Figure 6).

The UA-ATES system was modified for microbiological studies. Stainless steel spigots were added to the existing pipes for collection of water at designated sites in the ATES system (Figures 4 and 5).

Specimens were collected at designated sites to assess the effects of the major components in the UA ATES system water circuit:

- Site A - Aquifer water before entry into the conventional cooling tower. This water was pumped directly from the aquifer and would contain adherent bacteria dislodged from aquifer sand by the physical action of pumping and free-floating nonadherent bacteria.
- Site B - Water after chilling in the conventional cooling tower. (The water essentially was not recirculated in the cooling tower.)
- Site C - Chilled water after filtration through a sand filter and before injection into the aquifer.
- Site D - Chilled water recovered from the aquifer before entering the air handling units in the Student Recreation Center.
- Site E - Chilled water after passage through the air handling units.
- Well #K4E - A head well outside of the chilled water plume.
- Well #H1W - A head well within the chilled water plume.

UA-ATES SYSTEM

(Chill Storage Cycle)

Figure 4. Design of the UA-ATES System and Location of Sample Collection Sites During the Chill Storage Cycle

UA-ATES SYSTEM

(Chill Recovery Cycle)

Figure 5. Design of the UA-ATES System and Location of Sample Collection Sites During the Chill Recovery Cycle

Figure 6. Dimensions of the UA-ATES System and the Chilled-Aquifer Plume at Week 14 (March 6, 1989) of the 72-Week Study Period (12/88 - 4/90). The isotherm contour plots are 6 m above the Pottsville formation.

Water specimens were obtained biweekly for 72 weeks from Sites A, B, and C during the active winter cycle of operation and Sites D and E during the active summer cycle of operation. Adherent microbiota were sampled in head wells #H4E and #H1W using a variety of sterilized surfaces and aquifer sand. The sterilized surfaces and sand were attached to a sampling device, lowered into the aquifer, and incubated in the aquifer for 1 to 4 weeks.

Procedures were developed to detect specific pathogens and opportunistic pathogens that historically are associated with water-borne infectious diseases (Table 1).

Table 1. Water-Associated Pathogens Targeted for Isolation and Identification in the UA-ATES System

<u>Organism(s)</u>	<u>Notes on the Detection Procedure</u>
<i>Salmonella</i> , <i>Shigella</i> , and <i>Vibrio</i> species:	Detects the most common enteric pathogens, this procedure also detects fecal coliforms and coliforms that may be opportunistic pathogens.
<i>Campylobacter jejuni</i> :	Detects the specific enteric pathogen.
<i>Yersinia enterocolitica</i> :	Detects the specific enteric pathogen.
<i>Pseudomonas aeruginosa</i> :	Detects the specific opportunistic pathogen that is usually associated with skin disease after water exposure.
<i>Mycobacterium</i> species, nontuberculosis:	Detects opportunistic pathogens associated with skin, soft tissue, and lung disease.
<i>Legionella</i> species:	Detects the specific opportunistic pathogens associated with lung disease.

The UA-ATES system was tested for the pathogenic microorganisms listed in Table 1 over a complete seasonal cycle of 72 weeks (Figure 7). Coliforms that are associated with uncontaminated groundwater were routinely isolated; however, the CFU/ml was extremely low (Figure 8). Coliforms were detected for the most part when warm water was being pumped from the aquifer; thus, the chill water plume apparently reduced the number of coliforms. Fecal coliforms were not detected in 68 separate samplings of the UA-ATES system.

Pathogens were not detected during the study period, except for an organism that lies in the gray area between pathogen and opportunistic pathogen, *Mycobacterium chelonae* (a nontuberculosis

Figure 7. Pumping Patterns During the 72-Week UA-ATES Study Period (12/88 - 4/90)

species). This microorganism was detected only six times from the stored chilled water during the study period. In each isolation, the CFU/ml was extremely low, i.e., < 0.01 CFU/ml. No *Legionella* species were detected in any of the 68 samplings of the UA-ATES system. This negative observation is notably significant because during the chilled water recovery cycle of the study period, *Legionella* species were detected in all five conventional cooling towers tested on the University of Alabama campus (Figure 9). Thus, the operation of the UA-ATES system does not contribute to the growth of the microorganisms targeted for study and may, in some instances, even inhibit their growth.

Figure 8. UA-ATES Coliform Quantification During the 72-Week Period (12/88 - 4/90)

University of Minnesota (UM)

A laboratory at the University of Minnesota examined a hot-water ATES (UM-ATES) system for potential propagation of human pathogens associated with water. The UM-ATES system uses a confined aquifer for storage and recovery of hot water (>100°C) and does not permit the water to come in contact with open air, humans, or conventional cooling towers; thus, the system is characterized as being a "closed system". The potential for propagation of pathogens in a closed system is very low; however, the microbiology of the UM-ATES system was examined from 1982 through 1989 as a condition of

Figure 9. *Legionella* Species Detected in Conventional Cooling Towers Outside the UA-ATES System During the Study Period (12/88 - 10/90). Each symbol represents a cooling tower at different locations on the UA campus.

the operating permit issued by the Minnesota Department of Health. Testing for coliform organisms was performed from 1982 through 1990.

Water samples from the UM-ATES system were analyzed for coliforms in accordance with the membrane filtration technique described in Standard Methods for Examination of Water and Waste Water (American Public Health Association, 1976). The water obtained immediately after installation of the UM-ATES wells was contaminated with coliforms (3 and 4 CFU/100 ml). This contamination probably resulted from well installation. In 14 individual tests of aquifer water performed from November 1982 through November 1983, the coliform counts were < 1 CFU/100 ml (Walton, et al. 1991). In addition, high-calcium limestone particles were collected from the

UM-ATES heat-exchanger complex and were examined for adherent coliforms. Very low coliform counts were obtained (< 1 CFU/50 grams of particles). Coliform counts of ≥ 1.0 CFU/100 ml indicate potential pollution with animal fecal material; thus, operation of the UM-ATES system did not propagate potential human pathogens.

MODIFICATION OF AQUIFER NORMAL FLORA

Heat Storage

Heat storage in the aquifer involves introduction of high temperatures in addition to the high pressures associated with the depth of the injection drains/wells. The temperatures used for water injection (60°C to 100°C) preclude survival of microbiota normally found in the aquifer, except in the volume of moderate temperatures ($< 45^{\circ}\text{C}$) at the very periphery of the heat-storage volume. Because of the cyclic nature of the ATES system heat storage mass, and in some cases, the lateral movement of the heat-storage volume in the aquifer, sampling the microbiota in the periphery of the dynamic heat-storage volume of moderate temperatures would be difficult, i.e., a large number of sampling wells would have to be drilled to sample the periphery of the heat-storage volume as it shrinks, expands, or migrates laterally.

Germany

An impounded ATES system pilot plant constructed for thermodynamic studies at the University of Stuttgart, Stuttgart, Germany, provided a unique opportunity to examine the effects of ATES system operation on the microbiota of an aquifer (Adinolfi, Thome, and Ruck, 1990). This ATES system was impounded to prevent ATES system interaction with the surrounding subsurface environment (Figure 10). The aquifer store consisted of a volume of $1,050 \text{ m}^3$ filled with locally obtained gravel from the bed of the Rhine River and water from Lake Constance. This impounded ATES system permitted control of the chemical composition of the rock and water. The locally obtained water and rock seeded the ATES system with

Figure 10. Dimensions and Design of the Impounded ATES System at the Institute of Thermodynamics and Heating Technique at the University of Stuttgart

indigenous microorganisms. In addition, the flow of the water within the system could be carefully controlled and characterized. Finally, the storage volume was impounded with a high density polyethylene liner, a substance that is relatively inert with respect to the common aquifer microorganisms. The one disadvantage of this study system was that the temperature cycles were controlled by concurrent thermodynamic studies and, therefore, could not be manipulated specifically for microbiological studies.

Microbiological studies of the impounded ATES system were performed at the Institut Für Siedlungswasserbau, Wassergüte- und Abfallwirtschaft - Abteilung Biologie - Universität Stuttgart. The ATES system was sampled by drawing water from throughout the store from a point near the central well at about 2.5 to 3 m depth. The

temperature differential between Storage and Circulation averaged 1.2°C. Water specimens were analyzed for the CFU/ml of heterotrophs, an estimate of overall microbial growth in water. The representation of individual taxonomic groups of bacteria within the samples was examined also. Taxonomic groups of bacteria known to inhabit natural water were identified and quantified as a percentage of the total colony count (see Figure 13 for an example of data).

The water drawn from Storage demonstrated consistently higher CFU/ml than the circulating water. However, both sampling sites demonstrated the same overall patterns of microbial growth levels (Figure 11). An interesting phenomenon was noted. When the water temperature was raised to approximately 37°C, organisms capable of forming colonies at 37°C appeared. The taxonomic representation shifted also. However, it is very important to note that the microbial growth shifted back to previous levels when the temperature of the ATES system was lowered and the organisms capable of forming colonies at 37°C disappeared. These transitions took place within an 11-week period.

A large-scale model of the Stuttgart ATES system was constructed to obtain a simulation of the system that could be manipulated by microbiologists (Figure 12). The large-scale model consisted of a 4.0-m high stoneware column with an inner diameter of 45 cm. The column was filled with the same gravel and water that was used in the impounded aquifer. A heat exchanger was installed in the circulation loop to control the temperature of the water. Sampling ports were included over the length of the column to allow specimens to be taken throughout the temperature differential that occurs as the temperature of the water is perturbed. The column was fully instrumented for temperature measurements and organic materials in contact with the water were avoided. The only metal contacting the water was the galvanized steel in the heat exchanger tubes. Finally, the flow velocity (5 to 10 m/d) was designed to approximate the flow rate of the impounded aquifer and natural aquifers.

Figure 11. Population of Heterotrophs at the Stuttgart Impounded ATEs System - Storage Water versus Circulation Water (7/87 - 6/90)

The large-scale model was run for a 15-week period with a water temperature of 18 to 23°C to establish an equilibrated microbial flora. The CFU/ml of the water leaving the column during circulation for equilibration was slightly higher than the CFU/ml of the water used to fill the column. The taxonomic groups represented in the circulating water were slightly more diverse when compared to the water used to fill the column. No unusual taxonomic groups were observed and the microorganisms represented in the column closely resembled the larger impounded ATEs system, except for representation by two additional taxonomic groups commonly indigenous to natural water, i.e., *Alcaligenes* and *Acinetobacter*.

Figure 12. Large-Scale Model of the Stuttgart ATES System

The large-scale model was then switched to 40°C input water and the microorganisms were allowed to adapt for approximately 2 weeks. Two types of samples were obtained from various points within the column that represented a temperature differential (40°C at the top and 20°C at the bottom). Water was obtained as before and assayed for CFU/ml. In addition, gravel samples were obtained from the sampling points and treated with ultrasonic sound to release the adherent bacteria into the water for detection.

The CFU/ml and the taxonomic groups detected in the water samples did not change significantly after the temperature shift. The taxonomic groups represented in the microbial population that adhered to the gravel resembled the microorganisms detected in the

water. However, the numbers of microorganisms adhering to the gravel exceeded the number in the water by 100- to 1,000-fold. It should be noted that the representative taxonomic groups in the adherent population were slightly different when compared to the water population, but were groups normally associated with water. Although gram-negative bacteria were the predominate representatives in both the water and adherent microbial populations, the lower temperatures (17°C) associated with the bottom of the column appeared to stratify microbial growth with an increased representation by gram-positive microorganisms (Figure 13).

The input water of the large-scale model was then switched to 50 to 55°C and the microorganisms were allowed to adapt. The water exited the column at 20°C. Although there was a slight decrease in the CFU/ml, the general pattern of CFU/ml and taxonomic group representation of both the water and the gravel was similar to the results obtained when the column was charged with 40°C water.

The input water of the large-scale model was then switched to 65 to 70°C with the water exiting the column at 20°C and the microorganisms were allowed to adapt. The CFU/ml exiting the column remained similar to the previous studies. The taxonomic groups represented in the higher temperatures (top of the column) were restricted as compared to previous studies. Gram-positive microorganisms were in the majority. Pathogenicity of gram-positive bacteria is extremely species-specific because the infectious disease process of gram-positive bacteria is dependent on production of toxins that exhibit highly specific activities and target tissue. Thus, the increased representation of gram-positive microorganisms in the effluent water of the large-scale ATEs system model may or may not predict an increased risk for infectious diseases. At lower temperatures, the taxonomic representation was more diverse. Again the taxonomic groups represented were common for water.

TAXONOMIC GROUP LEGEND

- 1 - pseudomonads, gram-negative
- 2 - Flavobacter/Cytophagales, gram-negative
- 3 - Alcaligenes, gram-negative
- 4 - Acinetobacter, gram-negative
- 5 - Spirillum/Azospirillum, gram-negative
- 6 - Vibrio, gram-negative
- 7 - Hyphomicrobium, gram-negative

- 8 - Arthrobacter, gram-positive
- 9 - Nocardia, gram-positive
- 10 - coryneforms, gram-positive
- 11 - Kurthia, gram-positive
- 12 - Micrococcus, gram-positive
- 13 - Bacillus/sporeformers, gram-positive
- 14 - actinomycetes, gram-positive
- 15 - yeasts, gram reaction not relevant

Figure 13. Taxonomic Groups of Heterotrophic Bacterial Flora in Different Temperature Zones of the Large-Scale Model of the Stuttgart ATES. Cultures were incubated at 30°C. Biofilm = adherent bacteria.

Small-scale models of the Stuttgart impounded ATEs system were designed to allow an even greater manipulation of the experimental system. The models were cylinders 65-cm high and 15-cm in diameter (Figure 14). The small models were constructed avoiding the use of organic materials. These models were filled with sediment from the Stuttgart site and two additional sites in Germany that have the potential for future ATEs development. The columns were filled with the same water used previously and the microorganisms were allowed to adapt without added heat as before. The CFU/ml reached levels similar to the initial observations of all previous studies. To date only biofouling has been examined with the models. An initial study of biofouling in the small model will be discussed later.

Figure 14. Small-Scale Model of the Stuttgart ATEs System.

Switzerland

Sand removed from the Dorigny aquifer was tested for heterotrophic bacteria by determining the CFU/g of sand. In addition, total biomass was estimated by a chemical assay for ATP, a high energy compound that is unique to living cells. The estimated total biomass in the Dorigny aquifer sand exceeded the biomass that would be predicted by CFU/g of sand by approximately 100-fold. This finding indicates that the vast majority of bacterial cells in the aquifer do not give rise to colonies upon culture. When the sand was heated from 25 to 60°C over a 4-day period, the CFU of thermophilic bacteria decreased when the cultured samples were incubated at 60°C (Figure 15). In contrast, the CFU of mesophilic bacteria increased 10,000-fold.

Figure 15. Effect of Heating Dorigny Aquifer Sand in Small-Scale Models

Small-scale models of the Dorigny ATES system described previously gave an opposite pattern, i.e., the mesophilic bacteria decreased and the thermophilic bacteria increased. Thus, increasing the temperature of sand samples over a 4-day period probably mimics the events that occur at the periphery of the hot water plume and the small-scale models mimics the events occurring in the central volume of the hot water plume. The ATP concentration in the small-scale models remained essentially constant and indicates the biomass remained constant; thus, the increase of the thermophilic heterotrophs took place at the expense of the mesophilic heterotrophs and vice versa.

United States (University of Minnesota)

The total number of aerobic bacteria in water was examined to establish the bacteriological profile of the water during UM-ATES system operation. Water samples were analyzed for aerobic organisms in accordance with the membrane filtration technique described in Standard Methods for Examination of Water and Waste Water (American Public Health Association 1976). This determination cannot be used as an indicator for either pollution or water quality. However, the total aerobic bacteria content of well water should be extremely low relative to surface water.

Total aerobic bacteria content in the various samples was determined at incubation temperatures of 7 and 35°C to characterize the organisms as psychrophilic or mesophilic. The vast majority (about 90%) of the organisms isolated were psychrophilic gram-negative rods (Walton, et al. 1991). The counts ranged from <1 to 8.2×10^4 CFU/ml, but a general pattern of increased or decreased counts did not occur during the period of operation. Thus, operation of the UM-ATES system does not appear to affect the environment adversely.

Chill Storage

Chill storage in the aquifer involves introduction of low temperatures into the aquifer. The temperatures used for water injection (4 to 12°C) would preserve the viability of most microbial groups and also would retard their growth within the aquifer. Because of the cyclic nature of the ATEs system chill storage mass, and in some cases, the lateral movement of the chill-storage volume in the aquifer, sampling the microbiota in the periphery of the dynamic chill-storage volume would be difficult, i.e., a large number of sampling wells would have to be drilled to sample the periphery as the chill-storage volume shrinks, expands, or migrates laterally. An alternate approach would be to compare the microbiota in the water before chilling and injection with the microbiota in the water recovered from the chill storage mass.

United States (University of Alabama)

Laboratories in the United States [Department of Biological Sciences (formerly the Department of Microbiology), University of Alabama, Tuscaloosa, Alabama, and the Environmental Sciences Department, Terrestrial Sciences Section, Pacific Northwest Laboratory^(s), Richland, Washington] have examined the chill-water UA-ATES system in operation at the Student Recreation Center on the campus of the University of Alabama for the presence of heterotrophic bacteria. Duplicate water samples were analyzed by the University of Alabama and Pacific Northwest Laboratory. In general, the Pacific Northwest Laboratory analysis revealed slightly higher CFU/ml values than the University of Alabama analysis. It is speculated that the slight increases were probably caused by heterotrophic bacterial cell division during the 2-day shipment of duplicate specimens from the state of Alabama to the state of Washington.

Chilling the water by passage through the cooling tower did not modify the warm-water well microbiota significantly. This can be seen by comparing Figure 16 with CFU/ml values obtained from sites A and C (illustrated in Figure 4). The UA-ATES system appears to have reduced heterotrophic concentrations after an extended (4 to 6 week) exposure to the lower temperatures in the chilled aquifer. However, once exposure to the lower aquifer temperature stopped, the heterotroph CFU/ml counts apparently revert to previous levels by the next chilling cycle. The #H1W head well in the chilled water plume also demonstrated fewer numbers and types of adherent heterotrophic bacteria, when compared to the #H4E head well immediately outside the UA-ATES system.

BIOFOULING OF HEAT EXCHANGERS AND AQUIFER POROSITY DURING ATES SYSTEM OPERATION

Germany

Small-scale models of the impounded ATES system developed at the University of Stuttgart, Stuttgart, Germany, have been used to study biofouling of aquifer porosity during ATES system operation (Adinolfi, Thome, and Ruck, 1990). The design of the small models was described previously. The small-scale models provide increased experimental manipulations to the microbiologist that are not feasible for investigation in large-scale models or in the impounded ATES system. The small-scale ATES model studies are in their initial stages, but they have demonstrated biofouling of aquifer porosity. Ferrous iron and iron bacteria that were obtained by enriching groundwater were added to a small-scale ATES model, and the flow through the column was reduced to a minimum. Thus, the small-scale ATES models have the potential for defining many of the factors that are important in development of biofouling and may

(a) Operated for the U.S. Department of Energy by Battelle Memorial Institute under Contract DE-AC06-76RLO 1830.

Figure 16. Heterotroph Quantification During the Study Period at the UA-ATES System (12/88 - 4/90)

provide the means to test different protocols for the prevention or reversal of biofouling. However, none of the laboratories have reported biofouling of actual operational heat or chill ATES systems.

Finland

Should biofouling problems arise in the future, investigators should consult the comprehensive, state-of-the-art review on the iron and manganese bacteria by Seppänen, Ala-Peijari, and Iihola (1988). This report explains the types of microorganisms that have potential for creating biofouling problems in ATES systems, the microbiological chemistry involved in biofouling, and well design and operation to prevent biofouling.

SCALING AND CORROSION CAUSED BY MICROBIOLOGICAL ACTIVITY DURING ATEs
SYSTEM OPERATION

None of the laboratories have reported scaling or corrosion caused by microbiological activities in actual operational heat or chill ATEs systems.

CONCLUSIONS

Although the interaction of microorganisms with operational ATES systems has the potential for creating health hazards, an adverse environmental impact, and biofouling, these concerns have not been realized. To date the combined microbiological research of the IEA Annex VI, Subtask D (Microbiological Processes) by Finland, Germany, Switzerland, and the United States has not identified adverse microbiological problems associated with ATES systems. In addition, microbiological problems in ATES system operation have not been reported by other members of the IEA Annex. However, because of the ubiquitous nature and the multifaced biological and biochemical activities of microorganisms, investigators should continue to be vigilant for potential microbiological problems in the development of ATES.

The information generated by the IEA, Annex VI, Subtask D supports the current use of both heat and chill ATES. If microbiological problems associated with ATES should arise in the future, the information generated by IEA, Annex VI, Subtask D will provide a knowledge base for a rational approach to these problems. In summary, the findings of the IEA, Annex VI, Subtask D fully support the continued development of ATES.

REFERENCES

- Adinolfi M., L. Thome, and W. Ruck. 1990. Microbial Ecology in ATEs-Systems - Experiments in Large-Scale Experimental Plants. International Energy Agency, Annex XI, Doc No. 40-D. Prepared by Institut für Siedlungswasserbau, Wassergüte und Abfallwirtschaft, University of Stuttgart, Stuttgart for the KFA Forschungszentrum Jülich GmbH, BEO, Federal Republic of Germany.
- American Public Health Association, American Water Works Association, and Water Pollution Federation. 1976. Standard Methods for the Examination of Water and Wastewater. 14th edition. American Public Health Association, Washington, D.C.
- American Public Health Association, American Water Works Association, and Water Pollution Federation. 1989. Standard Methods for the Examination of Water and Wastewater. 17th edition. L.S. Clesceri, A.E. Greenberg, R.R. Trussell (eds.). American Public Health Association, Washington, D.C.
- Aragno, M., Orlandini, A., B. Schlunegger, and R. Stettler. 1990. Synthèse des résultats obtenus durant la phase préparatoire. Projet AIE Annexe VI Bis. Université Neuchâtel, Neuchâtel, Switzerland.
- Hicks R. J., and D. L. Stewart. 1988. Environmental Assessment of the Potential Effects of Aquifer Thermal Energy Storage on Microorganisms in Groundwater. PNL-6492, Pacific Northwest Laboratory, Richland, Washington.
- Midkiff, K.C., Y.K. Song, and C.E. Brett. 1991. "Thermal Performance and Challenges for a Seasonal Chill Energy Storage Based Air-Conditioning System." In Proceedings of the National Heat Transfer Conference. American Society of Mechanical Engineering, New York.
- Miserez, J.-J. 1989. Researches Performed in Switzerland. International Energy Agency, Annex XI, Phase I Final Report. Prepared by J.-J. and F. Miserez, Ingenieurs Chimistes-Conseils SA, La Chaux-de-Fonds, for Federal Office of Energy, Switzerland.
- Reilly, R. W. 1980. A Descriptive Analysis of Aquifer Thermal Energy Storage Systems. PNL-3298, Pacific Northwest Laboratory, Richland, Washington.
- Seppanen, H., T. Ala-Peijari, and H. Iihola. 1988. State of the Art Report: Iron and Manganese in Groundwater, Finland. IEA, Annex VI, Subtask D, Document No 10-C,D/Fin. Prepared by H. Seppanen, Dept. Limnology, University of Helsinki, and T. Ala-Peijari and H. Iihola, Vesi-Hydro, Consulting Engineers. Financed by the Ministry of Trade and Industry, Dept. of Energy, Finland.

Walton, M., M. C. Hoyer, S. J. Eisenreich, N. L. Holm, T. R. Holm, R. Kanivetsky, M. A. Jirsa, H. C. Lee, J. L. Lauer, R. T. Miller, J. L. Norton, and H. Runke. 1991. The University of Minnesota Aquifer Thermal Energy Storage (ATES) Field Test Facility - System Description, Aquifer Characterization, and Results of Short-Term Test Cycles. PNL-7220, Prepared by Minnesota Geological Survey, University of Minnesota, Minneapolis, Minnesota for Pacific Northwest Laboratory, Richland, Washington.

Zwadyk, P. 1988. "Pseudomonads." In Zinsser Microbiology, 19th edition, W.K. Joklik, H.P. Willett, D.B. Amos, and C.M. Wilfert, (eds.), pp. 487-492. Appleton & Lange, Norwalk, Connecticut.

APPENDIX

PAPER BY MONTANDON AND ANTONIETTI

EXPERT MEETING LA CHAUX-DE-FONDS
27-29th NOVEMBER 1991

**SURVIVAL OF THERMOTOLERANT AND POTENTIALLY PATHOGEN MICROORGANISMS IN
CONDITIONS OF AN AQUIFER THERMAL ENERGY STORAGE (ATES)**

Paul-Etienne MONTANDON⁽¹⁾ and Claude ANTONIETTI⁽²⁾, Service de l'Hygiene et de l'environnement,
av. L.-Robert 36⁽¹⁾, Ingénieurs chimistes-conseils, av. L.-Robert 80⁽²⁾, 2300 La Chaux-de-Fonds,
SWITZERLAND

Studies were carried out to investigate the survival and / or multiplication of *Legionella* spp. in water from the ATES system located at Dorigny (SPEOS). Clinical isolates of *Legionella pneumophila* and *Legionella micdadei* were incubated in laboratory microcosms containing nonsterile or sterile water from the Dorigny ATES. The results show that *Legionella pneumophila* and *Legionella micdadei* survived in these conditions. The loss of viability in log units per 2 weeks, as measured by colony forming cells, was 1 and 3.5 for *Legionella pneumophila* which was incubated in autoclaved and respectively in autoclaved and membrane-filtrated water. Similar data were obtained with *Legionella micdadei*. These data suggest that filtration removes a necessary growth factor. Finally, it was found that *Legionella pneumophila* survived in water containing indigenous microorganisms. In these conditions, the rate of decay was 1 log unit in 10 days. These experiments suggest that *Legionella* spp. may survive in an ATES system.

INTRODUCTION

The ATES system located at Dorigny, Switzerland, was designated for heat storage at temperatures of 50 to 80°C. Heat storage in an aquifer leads to the warming of the subsurface and of the nearby aquifer. The transfer of heat to some distance from the main well does occur in Dorigny, since the water is slowly moving. We expect that microbial flora would be modified in the aquifer nearby the main well, as a consequence of the warming.

It was shown in a previous report (Miserez 1989) that the population of thermophilic bacteria increased in small scale models of the Dorigny ATES system at 60°C while that of mesophyllic bacteria decreased. Thus, we could ask whether thermotolerant, ubiquitous and potentially pathogen microorganisms, like *Legionella* and *Pseudomonas*, would grow in conditions of an ATES (Miserez 1990). Survival or multiplication of *Legionella* spp. and/or *Pseudomonas* spp. would likely represent a biological hazard. As a model system, we choose to study the behavior of *Legionella* spp. in conditions of an ATES.

Gram-negative bacilli belonging to the genus *Legionella* (34 species) have been isolated from many man-made and natural environments, namely from ponds, streams, lakes, soils, hydrothermal areas and from many domestic hot water systems. The best known representative microorganism of the genus *Legionella*, *Legionella pneumophila*, usually causes subclinical infections in man, but sometimes may induce fever (95%) and pneumonia (5%), 15% of which have a lethal issue (for a review see: Rodgers and Pasculle 1991; Win 1988). In order to estimate whether *Legionella* would represent a biological hazard in or near an ATES system, we carried out in vitro experiments with water from the Dorigny ATES. We found out that these bacteria would survive in conditions which are found nearby the main well.

EXPERIMENTAL APPROACH

Cells

Clinical isolates of *Legionella pneumophila* and *Legionella micdadei* were kindly provided by Dr Roupas (Geneva).

Preparation of Legionella stock cultures

Legionella are grown on agar plates containing BCYE medium (Dennis 1988). After 3 to 5 days at 37°C, cells are removed from agar plates with 0.01 M ACES buffer at pH 6.9. Cells are washed twice by centrifugation (2000 xg for 20 minutes) and resuspended in ACES buffer to an optical density of about 0.1 at 420 nm (Hussong et al. 1987).

Laboratory microcosms

Water from the Dorigny aquifer is kept frozen. One volume of the *Legionella* suspension is added per 1000 volumes of autoclaved or autoclaved and membrane-filtrated water from the Dorigny aquifer. Laboratory microcosms are incubated at 37°C in a water bath with a slow stirring device to maintain uniformity (Hussong et al. 1987).

Quantitation of *Legionella* is made by plating 100 µl of microcosm aliquots (or 100 µl aliquots of different dilutions) on BCYE agar plates containing antibiotics (Dennis 1988). Enumeration of colonies on agar plates takes place after 5 days of incubation at 37°C.

RESULTS

Habitats of Legionella

Table 1 shows that *Legionella* have been isolated from rivers, streams, natural thermal ponds and from diverse man-made environments. These studies also indicated that *Legionella* is more commonly found in water in the temperature range of 36 to 70°C than in cooler water. *Legionella* spp. probably do not grow in water at temperatures higher than 50 to 55°C. Therefore, *Legionella* detected in waters with temperatures as high as 70°C are likely associated with biofilms which are washed from cooler areas of growth (Verissimo et al. 1991). *Legionella* are aquatic bacteria which survive at temperature that are not tolerated by most other aquatic organisms.

Conditions for optimal growth in vitro

The growth of *Legionella pneumophila* *in vitro* requires specific physicochemical and biological parameters (Table 2). *Legionella pneumophila* multiplies *in vitro* at temperatures between 25 and 37°C, at a pH level of 5.5 to 9.2 and at concentrations of dissolved oxygen of 6 to 6.7 mg/l. In addition, free-living amoeba and ciliated protozoa (tetrahymena) were reported to support the multiplication of *Legionella pneumophila*.

Search for Legionella spp. in the Dorigny aquifer

The pH, temperature and dissolved oxygen values of the aquifer near the main well (Jollien and Miserez 1990) are in the range of the values which are compatible for growth of *Legionella pneumophila* *in vitro*. To determine whether *Legionella* spp. are present in the aquifer, we analyzed water from the lower and the upper

bed of the main well in January 1992. We measured the temperature, the oxygen content and the pH of the water samples. The temperature was 36.3°C in the lower bed and 23.2°C in the upper bed. The values for the oxygen content and the pH were 0.5 and 1.6 mg/ml and respectively 6.4 and 7.08. We did not detect any *Legionella* spp. in either water sample. However, we cannot conclude from this single analysis that the SPEOS waters are not conducive to the survival of *Legionella* spp. because fluctuations in temperature, oxygen content and changes in water chemistry may influence the microbial population within the system. In fact, the oxygen content of both samples was lower than usual. We should, therefore, re-examine the SPEOS waters at regular intervals to take account of such fluctuations before drawing any definitive conclusions.

Behavior of *Legionella* in microcosms

Although we did not find *Legionella* in the main well of the Dorigny ATEs, we had to evaluate whether these bacteria would grow in the warm water found nearby the main well. To answer that question, we carried out *in vitro* growth experiments with *Legionella pneumophila* and *Legionella micdadei* in laboratory microcosms containing sterile Dorigny water as described in experimental approach section. Figure 1 shows that *Legionella pneumophila* survived quite well in water which has been sterilized by autoclaving. The rate of decay of *Legionella pneumophila* is less than 1 log unit in 2 weeks. In contrast, *Legionella pneumophila* decays more rapidly in water which was membrane-filtrated; in these conditions, the rate of decay was 3.5 log units in 2 weeks. We obtained similar data with *Legionella micdadei* (Figure 2). These results suggest that filtration removes a necessary growth factor.

Finally, we tested whether *Legionella pneumophila* cells would survive in a microcosm containing indigenous microorganisms. *Legionella pneumophila* cells obtained from a frozen stock were incubated as described above, but in unsterilized water. Enumeration of *Legionella* was made as described in experimental approach section, but after acid-treatment of the aliquot to be analyzed on agar plates. Heterotrophic plate counts were determined by plating aliquots of appropriate dilutions on agar plates containing nutrient agar. Figure 3 shows that the population of indigenous bacteria increases by about 3.5 log units while that of *Legionella pneumophila* decreased by 1 log unit in 10 days. Thus, presence of bacteria alive does not appear to influence *Legionella* survival in this type of laboratory microcosm.

DISCUSSION

In the present study, we had to evaluate whether *Legionella* spp. could represent a biological hazard in an ATEs system, i.e. to determine whether these bacteria could multiply nearby the main well and/or whether they could invade the plumbing fixtures.

We did not find *Legionella* spp. in water of the main well of the Dorigny ATEs. As discussed above, we should re-analyze this water before definitively stating that it is not conducive to the growth of *Legionella* spp. We showed, however, that *Legionella* spp. survived quite well in laboratory microcosms containing water from the Dorigny ATEs. We used, as a source of *Legionella*, clinical isolates that were grown on artificial medium. Other studies revealed similar growth behavior. Hussong et al. (1987) observed that one isolate of *Legionella pneumophila* showed long-term survival while *Legionella pneumophila* strain Philadelphia 2 multiplied in sterilized tap water. These 2 strains were grown on artificial medium before their addition to the laboratory microcosms. Furthermore Yee et al. (1982) and Wadowsky et al. (1985) found that naturally occurring *Legionella* multiplied in unsterilized and in sterilized tap water. We can conclude from these studies that multiplication of *Legionella* in laboratory microcosms containing tap water mainly depends on the strain used. Therefore, the growth behavior of different strains should be studied in laboratory microcosms containing Dorigny water before stating that this water does not promote multiplication of *Legionella*.

As discussed above, it has been documented that various *Legionella* serogroups and subgroups species can exist in plumbing systems (Alari and Joly 1991; Wadowsky et al. 1985; Nahapetian et al. 1991; Lück et al. 1991), when the water temperature is between 30 and 50°C. Recently, Lück et al. (1991) showed that a *Legionella pneumophila* serogroup 6 strain was regularly isolated during a 3-year surveillance from a warm water supply at a school of medicine. Thus, we may ask whether *Legionella* spp. could invade the plumbing system which is used to distribute sanitary water. Sanitary water and water used for heating are warmed up through a heat exchanger with hot water stored in the Dorigny ATES. The final temperature of the sanitary water varies between 30°C and 50°C. Since it was demonstrated that *Legionella* spp. may even be present in drinking water (Hsu et al. 1984), i.e. in the water used to prepare sanitary water, it is possible that *Legionella* multiply in tanks used to store warm water, providing that physicochemical and/or biological parameters are optimal for their growth. If the presence of *Legionella* spp. in the plumbing system would be established, one should take means by which these bacteria can be eliminated. In practice, effective disinfection would imply chlorinating the stored hot water (Hsu et al. 1984) and/or superheating of the water at 70°C (Table 3).

In conclusion, we have presented and discussed data which show that *Legionella* spp. may conceivably represent a biological hazard in an ATES system, e.g. nearby the main well of an ATES like SPEOS and in the plumbing fixtures, if specific physicochemical and biological conditions, as defined above, are found at these sites.

ACKNOWLEDGMENTS

We gratefully acknowledge Dr A. Roupas (Geneva) for *Legionella* strains and Mrs F. Miserez for critical reading of the manuscript. We thank Ms D. Arnoux for typing the manuscript.

This work was supported by the Swiss Federal Office of Energy and by the City of La Chaux-de-Fonds.

REFERENCES

- (1) Alari, M., and Joly, J.R. (1991). Appl. Environ. Microbiol. 57: 2360-2367
- (2) Bercovier, H., Steigerwalt, A.G., Derhi-Cochin, Moss, W, Wilkinson, H.W., Benson, R.F., and Brenner, D.J. (1986) Int. J. Syst. Bacteriol. 36: 368-371
- (3) Bornstein, N., Marmet, D., Surgot, M., Nowicki, M., Arslan, A., Esteve, J., and Fleurette, J., (1989) Epidermiol. Infect 102: 31-36
- (4) Dennis, P.J.L (1988), In : A laboratory manual for *Legionella*, p. 31 - 44. T.G. Harrison and A.G. Taylor (ed). John Wiley and Sons Ltd, London.
- (5) Holden, E.P., Winkler, H., O'Wood, D., and Leinbach, E.D (1984) Infect. Imm. 45:18-24
- (6) Hsu, S.C., Martin, R., and Wentworth, B.B. (1984) Appl. Environ Microbiol. 48: 830-832
- (7) Hussong, D., Colwell, R.R, O'Brien, M., Weiss, E., Pearson, A.D., Weiner, R.M., and Burge, W.D. (1987). BIO/TECHNOLOGY 5: 947-950
- (8) Jollien, L., and Miserez, F. (1990) In : Chimie et Microbiologie dans le domaines du stockage de l'énergie en nappe aquifere. Annexes au rapport de la phase intermédiaire de l'annexe VI, Miserez (ed), Agence internationale de l'énergie.

- (9) Lück, P.C., Bender, L., Ott, M., Helbig, J.H., and Hacker, J., (1991) Appl. Environ. Microbiol. 57: 3226-3231
- (10) Miserez, F. (1990). Chimie et Microbiologie dans le domaine de stockage de l'énergie en nappe aquifère. Rapport de la phase intermédiaire de l'annexe VI, Agence internationale de l'énergie.
- (11) Miserez, J.J. (1989). Chimie et Microbiologie dans le domaine de stockage de l'énergie en nappe aquifère. Rapport de la phase I de l'annexe VI, Agence internationale de l'énergie
- (12) Morris, G.K., Patton, C.M., and Freely, J.C. (1979). Ann. Intern. Med. 90: 664-666
- (13) Nahapetian, K., Challemel, O., Beurtin, D., Dubrou, S., Gounon, P., and Squinazi, F., (1991). Res. Microbiol. 142: 677-685
- (14) Negron - Alvira, A, Pérez-Suarez, I., and Hazen, T.C. (1988) Appl. Environ Microbiol. 54: 2231-2234
- (15) Paszko - Kolva, C., Yamamoto, H., Shahamat, M., Sawger, T.K, Morris, G., and Colwell R.R. (1988) Appl. Environ. Microbiol. 57:163-167
- (16) Rodgers, F.G., and Pasculle, A.W. (1991). In: Manual of Clinical Microbiology 5th edition, p. 442-453. Balows, Hausler, Herrmann, Isenberg, and Shadomy (ed), American Society for Microbiology, Washington DC.
- (17) Smith - Somerville, H., E. Huryn, V., B. Walker, C., and Winters, A.L., (1991) Appl. Environ. Microbiol 57: 2742-2749
- (18) Steele, T.W., Moore, C.V., and Sangster, N. (1990) Appl. Environ. Microbiol. 56: 2984-2988
- (19) States, S.J., Conley, L.F., Ceraso, M., Stephenson, T.E., Wolford, R.S., Wadowsky, R.M., Mc Namara, A.M., and Yee, R.B., (1985) Appl. Environ. Microbiol. 50:1149-1154.
- (20) Tremp, E., (1990) Umwelttechnik 2: 5-6
- (21) Yee, R.B., and Wadowsky, R.M., (1982) Appl. Environ. Microbiol. 43: 1330-1334
- (22) Verissimo, A., Marrao, G., Gomes Da Silva, F., and Da Costa, M.S., (1991). Appl. Environ. Microbiol. 57: 2921-2927
- (23) Wadowsky, R.M., Wolford, R., Mc Namara, A.M., and Yee, R.B. (1985). Appl. Environ. Microbiol. 49: 1197-1205
- (24) Wadowsky, R.M., Wilson, T.M., Kapp, N.J., West, A.J., Kuchta, J.M., States, S.J., Dowling, J.N., and Yee, R.B. (1991) Appl. Environ. Microbiol. 57:1950-1955.
- (25) Winn, W.C., (1988). Clin. Microbiol. Rev. 1: 60-81

TABLE 1

HABITATS OF LEGIONELLA

HABITAT	LEGIONELLA	REFERENCES
Domestic hot water system	<i>Legionella pneumophila</i>	Alari and Joly 1991
Showerhead	<i>Legionella pneumophila</i>	Yee and Wadowsky 1982
Hot-water tank	<i>Legionella pneumophila</i>	Wadowsky et al. 1985
Hospital plumbing system	<i>Legionella pneumophila</i>	Nahapetian et al. 1991
Eye-wash stations	<i>Legionella pneumophila</i>	Paszko-Kolva et al. 1991
Cooling towers	<i>Legionella pneumophila</i>	Negron-Alvira et al. 1988
Streams	<i>Legionella pneumophila</i>	Morris et al. 1979
Fishponds	<i>Legionella israelensis</i>	Bercovier et al. 1986
Potting mixtures and soil	<i>Legionella longbeachae</i>	Steele et al. 1990
Hydrothermal aeras and warm spa water	<i>Legionella pneumophila</i> , <i>L. bozemanii</i> , <i>L. micadadei</i> , <i>L. dumofii</i> , <i>L. moravica</i> , <i>L. oakridgensis</i> , <i>L. sancricrusis</i> , <i>L. sainthelensi</i> , <i>L. londoniensis</i> , <i>L. nautarum</i>	Verissimo et al. 1991 Bornstein et al. 1986

TABLE 2

Physico-chemical and biological parameters that influence the growth and / or the survival of *Legionella pneumophila* in tap water

PARAMETER	GROWTH REQUIREMENT			REFERENCES
	minimum	maximum	optimum	
pH	5.5	9.2	6.0 to 6.5	Wadowsky et al. 1985
temperature (°C)	<25	45	32 to 37	Yee and Wadowsky 1982
oxygen (mg/l)	2.2	-	6.0 to 6.7	Wadowsky et al. 1985
potassium (mg/l)	0.05	>100	10	States et al. 1985
iron (mg/l)	0.05	10	1	States et al. 1985
zinc (mg/l)	0.05	10	0.5 to 1	States et al. 1985
<i>Acanthamoeba castellanii</i> (amoebae)	-	-	A.c/L.p = 1	Holden et al. 1984
<i>Hartmannella vermiformis</i> (amoebae)	-	-	H.v/L.p = 15	Wadowsky et al. 1991
Killed <i>Pseudomonas</i> <i>paucimobilis</i> (bacteria)	-	-	P.p/L.p = 10 ⁴	Wadowsky et al. 1991
Amoebae (<i>Naegleria</i> sp)	-	-	presence	Nahapetian et al. 1991
<i>Tetrahymena pyriformis</i> (ciliate)	-	-	T.p/L.p = 1	Nahapetian et al. 1991
<i>Tetrahymena vovax</i> (cold water ciliate)	-	-	T.v/L.p = 1/10 ⁴	Smith-Sommerville et al. 1991

TABLE 3

Temperature-dependent decay of *Legionella pneumophila* in tap water

TEMPARTURE (°C)	HALF-LIFE OF <i>LEGIONELLA PNEUMOPHILA</i> (min.)	REFERENCE
55	19	Tremp 1990
57.5	6	Tremp 1990
60	2	Tremp 1990

Figure 1

Figure 2

Figure 3

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

U.S. Department of Energy
Attn: R. Eaton
Office of Energy Management
Forrestal Bldg, CE-142 5F-064
Washington, DC 20585

U.S. Department of Energy
Attn: K. Klunder
Office of Energy Management
Forrestal Bldg, CE-142 5F-064
Washington, DC 20585

U.S. Department of Energy
Attn: E. Reimers
Office of Energy Management
Forrestal Bldg, CE-142 5F-064
Washington, DC 20585

12 DOE/Office of Scientific and
Technical Information

Auburn University
Attn: F. J. Molz
School of Engineering
Auburn, AL 36830

Lawrence Berkeley Laboratory
Attn: C-F. Tsang
University of California
Bldg. 90, Room 1012-H
1 Cyclotron Road
Berkeley, CA 94720

Charles F. Meyer
1141 Cima Linda Lane
Santa Barbara, CA 93108

New York State Energy
Research & Development
Agency
Attn: G. Walmet
2 Rockefeller Plaza
Albany, NY 12223

Oak Ridge National Laboratory
Attn: J. Tomlinson
Building 9204-1, MS 8045
Y-12 Plant, Box 2009
Oak Ridge, TN 37831-8045

Office of Congressman
Sid Morrison
1330 Longworth Bldg.
Washington, DC 20515

Office of Congressman
Tom Bevil
2302 Rayburn Bldg.
Washington, DC 20515

Oregon State University
Attn: S. W. Childs
Dept. of Soil Science
Corvallis, OR 97331

Sandia National Laboratories
Technical Library
Division 3141
Albuquerque, NM 87185

Southern Company Services, Inc.
Attn: K. Vakhshoorzadeh
PO Box 2625
Birmingham, AL 35202

The California State University
Attn: Mr. Edward Kripe, P.E.
Chief of Energy and Utilities
Programs
Seal Beach, CA 90740-7502

University of Alabama
Attn: E. Brett
School of Mines and Energy
Development
Box 870164
Tuscaloosa, AL 35487-0164

Distr.1

*Do Not
Microfiche*

No. of
Copies

5 University of Alabama
Attn: A. Winters
Department of Biological Sciences
280 Nott
Box 870334
Tuscaloosa, AL 35487-0334

University of Massachusetts
at Amherst
Attn: J. E. Sunderland
Dept. of Mechanical Eng.
Eng. Laboratory Bldg.
Amherst, MA 01003

University of Minnesota
Attn: R. L. Sterling
Underground Space Center
Dept. of Civil and Mineral Eng.
790 Civil and Mineral Eng. Bldg.
Minneapolis, MN 55455

US Department of Interior
Attn: Natural Resources
Library
Serials Branch (G/E)
Washington, DC 20240

No. of
Copies

Wehran Engineering
Attn: R. Miller
666 E. Main St.
PO Box 2006
Middletown, NY 10940

Wilke and Associates
Attn: D. Wilke
38 Roosevelt Avenue
Glen Head, NY 11545

ONSITE

DOE Richland Field Office

D. R. Segna, A5-90

28 Pacific Northwest Laboratory

M. K. Drost , K5-20
E. A. Jenne, K6-81 (3)
L. D. Kannberg, K5-20 (15)
S. W. Li, K4-06
B. L. Mohler, K5-02
G. L. Work, K7-02
Publishing Coordination
Technical Report Files (5)

END

DATE
FILMED

3 / 17 / 93