DETERMINATION OF FLOW-REGIME BOUNDARIES FOR COHESIVE PARTICLES

**Project 61093 Quarterly Report
For the Period December 20, 1990 Through March 19, 1991**

by

**T. M. Knowlton
J. G. Findlay**

**INSTITUTE OF GAS TECHNOLOGY
3424 SOUTH STATE STREET
CHICAGO, ILLINOIS 60616-3896**

for

**UNITED STATES DEPARTMENT OF ENERGY
PITTSBURGH ENERGY TECHNOLOGY CENTER
P. O. BOX 10940
PITTSBURGH, PENNSYLVANIA 15236**

DOE Contract No.: DE-AC22-88PC88951

January 1992

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

SUMMARY

Cohesive powders are composed of fine particles (particles generally less than 44 microns in size). Interparticle forces are extremely large and cause clumping, sticking, and channeling when attempts are made to fluidize these powders. These solids do not flow freely in pipes and bridge extremely easily.

Although flow problems can be experienced in the transport of free-flowing solids, they pale in comparison to the problems experienced with the flow of cohesive powders. Because of these flow problems, most process designers have shied away from using cohesive powders. However, cohesive powders are often produced in processes by attrition, and then concentrated in solids-collection equipment such as cyclones. Also, because cohesive solids have an extremely high surface area per unit volume, they are potentially desirable feed stocks for many processes. In addition, recent research has shown that beneficiation of oil shale and coal is possible after grinding these materials down to the cohesive size range.

Although there is much interest in cohesive powders at present, there is little information in the literature on the gas-solid, two-phase flow behavior of cohesive solids. Much information is needed in all cohesive solid flow regimes in order to characterize them. Possibly the most important information for plant designers, however, is knowledge of where the cohesive solids pass from dilute-phase flow into a dense-phase or choking flow. Cohesive solids can be handled more easily in dilute-phase than in dense-phase. In dense-phase flow, cohesive solids clump and bridge and often do not flow at all.

The purpose of this work is to develop a hydrodynamic model capable of predicting the choking/non-choking flow regime boundary for cohesive solids. There are six tasks in this study:

- Task 1. Preparation of a Project Work Plan
- Task 2. Hydrodynamic Model Development
- Task 3. Determination of Solid Rheological Properties for Incorporation Into the Hydrodynamic Model

- Task 4. Small-Scale Flow Tests
- Task 5. Large-Scale Flow Tests
- Task 6. Comparison of Model with Data and Preparation of Final Report

This quarter, tests were conducted with a Laser-Doppler velocimeter (LDV) with cohesive oil shale particles to determine the particle size distribution simultaneously with the determination of the particle velocity in a pipe at a superficial gas flow rate of 15 SCFM.

In addition, a cold-flow test unit was constructed and operated to determine the best method of controlling the flow rate of cohesive solids through a standpipe and slide valve. It was found that the cohesive solids would not flow well unless aeration was pulsed into the standpipe immediately above the slide valve. When aeration was pulsed into the standpipe, the solids flow was steady and controllable. Capability to pulse the aeration into the standpipe was then added to the 12-inch-diameter standpipe in the large-scale test unit.

TABLE OF CONTENTS

	<u>Page</u>
OBJECTIVES	1
INTRODUCTION	2
TECHNICAL PROGRESS REPORT	4
Task 1. Preparation of Project Work Plan	4
Task 2. Hydrodynamic Model Development	4
Task 3. Determination of Solid Rheological Properties for Incorporation Into the Hydrodynamic Model	4
Subtask 3.1. Parameter Determination	4
Subtask 3.2. Fluidization and Flow Testing	4
Task 4. Small-Scale Flow Tests	4
Laser-Doppler Velocimeter Experimental Unit	4
Theory of Operation	4
Measurement of Particle Size With an LDV	9
Noise Rejection	10
Time Discrimination	11
Period Discrimination	11
Particle-Size Calibration Curve	11
Solid Concentration Measurement Using the LDV	12
Experimental Equipment	13
Experimental Results	17
Task 5. Large-Scale Flow Tests	40
Task 6. Comparison of Model With Data and Preparation of Final Report	40
NOMENCLATURE	42
LITERATURE CITED	44

LIST OF FIGURES

<u>Figure No.</u>		<u>Page</u>
1	Schematic Drawing of Laser-Doppler Velocimeter	6
2	Schematic Drawing of Laser-Doppler Velocimeter Operating Principle	7
3	Light Intensity Variation in the LDV	8
4	Schematic Drawing of Solids Recirculation LDV Test Loop	14
5	Schematic Drawing of Jet-Pump Eductor	16
6	Particle Size Calibration Curve for the LDV	18
7	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.032)	19
8	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.226)	20
9	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.290)	21
10	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.548)	22
11	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.806)	23
12	Particle Size Distribution Measured With the LDV (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.935)	24
13	Particle Size Variation With Radius (Gas Flow Rate: 15 SCFM)	25
14	Probability Density as a Function of Particle Velocity (Gas Flow Rate: 5 SCFM)	27
15	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: < 7 Microns)	28
16	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: 7 to 15 Microns)	29
17	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: 15 to 30 Microns)	30

LIST OF FIGURES

<u>Figure No.</u>		<u>Page</u>
18	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: 30 to 45 Microns)	31
19	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: > 45 Microns)	32
20	Mean and Fluctuating Gas Velocity as a Function of Pipe Radius (Particle Size: Feed Distribution)	33
21	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.032)	34
22	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.226)	35
23	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.290)	36
24	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.548)	37
25	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.806)	38
26	Particle Velocity as a Function of Particle Size (Q = 15 SCFM, Dimensionless Radius: 0.935)	39
27	Schematic Drawing of Cold-Flow Model	41

OBJECTIVES

The overall objective of this program is the development of a hydrodynamic model to predict the choking/non-choking flow regime boundary of fine, cohesive (i. e., Geldart Group C) powders. Specific objectives are to:

1. Develop a two-dimensional hydrodynamic model that can be applied to cohesive solids.
2. Generate large-scale solids-flow data that will be used to verify the model.

INTRODUCTION

The objectives of this program are to -

1. Develop a two-dimensional, hydrodynamic model that can be applied to cohesive solids.
2. Generate large-scale solids-flow data that will be used to verify the model.

The research is divided into six tasks:

- Task 1. Preparation of a Project Work Plan
- Task 2. Hydrodynamic Model Development
- Task 3. Determination of Solid Rheological Properties for Incorporation Into the Hydrodynamic Model
- Task 4. Small-Scale Flow Tests
- Task 5. Large-Scale Flow Tests
- Task 6. Comparison of Model With Data and Preparation of Final Report.

In Task 1, a detailed Project Work Plan describing the tests to be conducted will be prepared and sent to the Department of Energy (DOE) for review and approval.

An existing, two-dimensional mathematical model will be extended to include interparticle forces such as exist in cohesive solids in Task 2. The equations to be programmed into the model will be derived from experimental measurements made in Task 3.

In Task 3, the rheological properties of a cohesive oil shale test material will be determined and incorporated into the hydrodynamic model to improve its capability for predicting gas and solid velocity profiles for gas and cohesive solids in two-phase flow. In addition, the fluidization and flow characteristics of the cohesive oil-shale powders will be determined.

A small-scale (3-inch-diameter), solids-flow test facility will be modified in Task 4. The facility will be operated with cohesive solids to provide solids concentration and gas velocity data to fine-tune the hydrodynamic model.

In Task 5, cohesive flow tests will be conducted in a large-scale (12-inch-diameter) solids flow unit to obtain data for comparison with model predictions. The large-diameter line should minimize wall effects that can be substantial in smaller units.

In Task 6, the hydrodynamic model will be compared with the results from both the small-scale and large-scale test units. The model will be fine-tuned, and then used to predict gas and solids velocity profiles both near and far away from choking. The final report for the project will also be prepared in this task.

TECHNICAL PROGRESS REPORT

Task 1. Preparation of Project Work Plan

This task has been completed.

Task 2. Hydrodynamic Model Development

The derivation of the two-phase gas-solid equations for continuity, momentum, and the fluctuating energy of the particle phase is complete. The model will now be used to compare its predictions with the data from the large-scale test unit when the data become available in sufficient quantities.

Task 3. Determination of Solid Rheological Properties for Incorporation Into the Hydrodynamic Model

Subtask 3.1 Parameter Determination

No work was conducted in this subtask this month.

Subtask 3.2 Fluidization and Flow Testing

The testing in this task has now been completed.

Task 4. Small-Scale Flow Tests

Laser-Doppler Velocimeter Experimental Unit

This quarter, tests with the Laser-Doppler Velocimeter were continued with cohesive oil shale particles to determine the particle size distribution simultaneously with the determination of the particle velocity at a superficial gas flow rate through the pipe of 15 SCFM. Tests with a gas flow rate of 5 SCFM were conducted last quarter. Particle size and particle velocity distributions of the cohesive oil shale were determined as a function of radial position in the pipe. A description of the operating principle of the LDV and the test results obtained are presented below.

Theory of Operation

Light scattered by a moving particle is "Doppler" shifted in frequency. By measuring the amount of this shift, the velocity of the particle may be determined. The high intensity and monochromaticity of laser light is well suited for this type of measurement. The method is non-intrusive, and can measure particle velocities accurately and with high spatial resolution.

The principal advantages of this method of measurement are the lack of probes, which could otherwise disturb the flow, and the ability to measure a

wide range of velocities (from a few millimeters per second to supersonic flow), without the need for calibration. The drawback, however, is that optical access is a necessity, and thus, applying the method to complex geometries is difficult. A schematic diagram of the Laser Doppler Velocimeter is shown in Figure 1.

In a dual-beam LDV, the laser beam is split by a beam splitter into two beams of equal intensity, both of which are focused at the measuring point. The LDV used in this study utilized a beam from a Helium-Neon Laser (15 mW at a wavelength of 6328 Å). The two beams were 50 mm apart, and passed through a focusing lens of 250 mm focal length. Inside the focusing volume, the two light beams intersect, and interfere with each other to form a fringe, where light intensity varies periodically in space (Figures 2 and 3).

The fringe space, d_f , is given by -

$$d_f = \frac{\lambda}{2 \sin \kappa} \quad (1)$$

where λ is the wavelength of the laser light, and κ is the half angle between the two beams.

When a moving particle passes through this fringe area, the intensity of the scattered light reflected from the particle surface varies in time to form the Doppler Burst Signal. This Doppler burst is received by the photodetector, and its frequency, f_d , is proportional to the velocity of the moving particle. The frequency is given by the relation,

$$f_d = \frac{U}{d_f} = \frac{2 U \sin \kappa}{\lambda} \quad (2)$$

where U is the particle velocity component perpendicular to the optical axis. The Doppler signal output from the photomultiplier tube typically has a Gaussian envelope. The mean value, which also has a Gaussian shape, is referred to as the pedestal, and is usually filtered out.

Thus, by measuring the Doppler frequency, it is possible to determine the particle velocity without any calibration. When measuring the velocity of

F900806

Figure 1. SCHEMATIC DRAWING OF LASER-DOPPLER VELOCIMETER

F900808

Figure 2. SCHEMATIC DRAWING OF LASER-DOPPLER VELOCIMETER OPERATING PRINCIPLE

F900809

Figure 3. LIGHT INTENSITY VARIATION IN THE LDV

gas flowing through a pipe, the gas must be seeded with small particles, since the LDV actually measures a particle velocity. The particles must be small enough (usually less than 1 micron) in order to ensure that its velocity is essentially the same as the gas velocity.

Measurement of Particle Size With an LDV

There have been several attempts to measure the particle-size distribution simultaneously with measuring particle velocity with the LDV. It can be demonstrated theoretically, that the shape of the Doppler Burst signal is determined by the size, shape, and the surface properties of the particles, the optical system alignment, the optical properties of the particle, and the actual path that the particle takes while passing through the focusing volume.

For a fixed optical system alignment, the Doppler signal still depends on the individual particle size in a complex way. There are two approaches discussed in the literature which deal with the attempt to obtain the relationship between the particle size and certain signal characteristics:

1. the visibility of the Doppler-Burst signal (1,2), and
2. the amplitude of the Doppler-Burst signal (3).

In this work, a new theory was developed to interpret the Doppler signal which is based on obtaining particle-size information from the amplitude of the Doppler-Burst signal.

It is assumed that no more than one particle can pass through the focusing volume at any time. This means that each Doppler-Burst will correspond to only one particle in the focusing volume at the precise measuring moment. When several particles appear in the focusing volume, they are considered to be moving as clusters, and are treated as one big particle. This assumption should be true in the case of very dilute gas-solid flows, and when the optical focusing volume very small.

The dual-beam LDV used in this work has an oval-shaped focusing volume, with a short-axis length of 184 microns and a long-axis length of 1890 microns. The fringe space length, d_f , is 3.2 microns. Light intensity is distributed across the focusing volume in a Gaussian distribution.

In a system with a fixed optical alignment, the amplitude of the Doppler-Burst, A_d , then depends only on the particle size, D_p , and the

position of the path as it travels through the focusing volume. Let l be the effective path-length. Then different path-lengths will represent a different position of the path (Figure 3). Therefore,

$$A_d = \text{function}(D_p, l) \quad (3)$$

In general, a larger particles will generate a stronger signal than smaller particles. For the same size of particle, when it travels through the center of the focusing volume, the strongest signal will be generated. Farmer (1) obtained an expression for the light intensity distribution in the focusing volume based on the Mie Scatter Theory. It is given below:

$$I_o = 2 I \exp \left[-2 \left(\frac{x_o^2}{b_o^2} + \frac{y_o^2}{b_o^2} + \frac{z_o^2 \kappa^2}{b_o^2} \right) \right] \left[\cosh \left(\frac{A y z \kappa}{b_o^2} \right) + \cos \left(2\pi \frac{y}{d_f} \right) \right] \quad (4)$$

where b_o is the e^{-2} dimension of the focusing volume in the direction perpendicular to the light axis.

If it is assumed that the velocity component of the particle perpendicular to the laser-beam plane can be neglected, the expression above results in the following expression for $A_d(D_p, l)$

$$A_d(D_p, l) = A_{d0}(D_p) \exp \left[-2 \left(1 - \frac{l^2}{l_{\max}^2} \right) \right] \quad (5)$$

where $A_{d0}(D_p)$ is the Doppler signal amplitude generated by a particle with diameter, D_p , passing through the center of the focusing volume. Because the effective path length, l , is proportional to the actual number of peaks within one Doppler-burst, N , the equation above may be written as:

$$A_{d0}(D_p) = A_d(D_p, l) \exp \left[2 \left(1 - \frac{N^2}{N_{\max}^2} \right) \right] \quad (6)$$

Thus, for any Doppler-Burst, A_{d0} calculated from this burst will be proportional to the size of the particle which caused the burst.

Noise Rejection

Even after implementing the techniques described above, there is substantial noise (from the various electronic devices employed in the testing) among the received Doppler signals. Two criteria (time and period discrimination) are used to discriminate the electronic noise.

Time Discrimination

Reasonable Doppler signals should last longer than a certain minimum time duration, i. e.,

$$\tau_{\min} \leq \tau \quad (7)$$

where τ is the duration of the individual Doppler burst, and $\tau_{\min}$ is the required minimum time duration to minimize noise. $\tau_{\min}$ is determined from the experimental measurements.

Period Discrimination

All Doppler bursts oscillate at the same frequency. Therefore, they all have the same period. For accelerating particles, the relative standard deviation of the periods of each Doppler burst should be less than some critical value (determined from measurements). If not, the bursts are treated as noise. Thus,

$$\left[\frac{1/N \sum_{i=1}^N (\Delta\tau_i - \overline{\Delta\tau})^2}{\overline{\Delta\tau}} \right]^{1/2} \leq \text{Critical Value} \quad (8)$$

where $\Delta\tau_i$ is the i th period in the Doppler burst, and $\overline{\Delta\tau}$ is the average period in the Doppler burst.

Only after both the time and the period criteria are satisfied can a particular Doppler burst be considered as a reasonable signal.

In actual testing, an HP 5404 digitizing oscilloscope was used to record the Doppler signals. The signals were then stored and transferred to an IBM 386-type computer for data processing.

Particle-Size Calibration Curve

It is nearly impossible to determine the particle-size versus electric signal voltage curve theoretically. This is because the light intensity/voltage signal relationship is unknown, and the electric signals have been amplified before they are recorded. Therefore, the following procedure was used to obtain a calibration curve for particle-size analysis:

1. The actual particle-size distribution of the particles being used in the experiment were determined using a Coulter Counter or other particle-size analyzer.

2. A reference flow condition was then chosen, and a large number of random Doppler signals were recorded with solids flowing through the experimental pipe, to make data processing statistically significant.
3. An electronic filter was used to remove the very high frequency components of the signal which are considered as noise, as well as the low-frequency components (pedestals).
4. The time and period criteria were then used to discriminate the remaining signal to remove further noise.
5. The burst amplitude of each Doppler burst, A_{d0} , was then calculated using Equation 6.
6. A statistical analysis was then performed to determine the accumulative signal number distribution as a function of signal amplitude.
7. The signal-amplitude distribution was then compared with the reference particle-size distribution obtained in Step 2.
8. The particle-size calibration curve was then constructed by choosing the signal amplitude and particle size values corresponding to the same accumulative signal number distribution (signal number percentage).

The resulting calibration curve allows the determination of the size of particle which causes a particular Doppler burst.

A TSI photodetector and frequency counter amplified the signals and filtered out the high and low frequency components of the raw signals. However, waveforms on the HP 5404 digitizing oscilloscope showed that some high and low frequency components still existed after filtering. Therefore, a computer program was developed to further filter the signals. After being filtered via the computer, the resulting signals were acceptable.

Solid Concentration Measurement Using the LDV

As well as obtaining the particle size distribution, it is also possible to obtain information about the solid-phase volume (number) concentration at the measuring point. Because the particle velocity and the particle size are measured, it is possible to calculate the solid flux and then obtain the solid volume concentration from the solid flux and velocity.

Within the sampling time period, T_s , the total volume of solids passing through the intersection area, A_f , of the focusing volume is ΔV ,

$$\Delta V = \sum_{i=1}^{N_s} \frac{\pi}{6} D_{pi}^3 \quad (9)$$

where N_s is the total number of sample bursts received within the sampling time period, T_s . Thus, the solids flux through A_f is

$$\text{Flux} = \frac{\Delta V}{T_s A_f} \quad (10)$$

During this period, the average solid velocity is U_{ave} ,

$$U_{ave} = \frac{1}{N_s} \sum_{i=1}^{N_s} U_{pi} \quad (11)$$

Therefore,

$$\epsilon_s = 1 - \epsilon_f = \frac{\text{Flux}}{U_{ave}} = \frac{N_s}{T_s A_f} \frac{\sum_{i=1}^{N_s} \frac{\pi}{6} D_{pi}^3}{\sum_{i=1}^{N_s} U_{pi}} \quad (12)$$

where ϵ_s is the solid volume concentration, and ϵ_f is the void fraction.

Experimental Equipment

A schematic drawing of the experimental test unit is shown in Figure 4. The test unit consists of five major parts: 1) the primary gas flow inlet, 2) the solids feed section, 3) the solids/gas mixing chamber, (4) the measurement (test) section, and 5) the cyclone and solids recirculation section.

The primary gas flow inlet section consists of four filters to remove water and oil droplets from the compressed air, a pressure regulator to lower the high-pressure air (80 to 120 psig) to the desired operating pressure (20 to 30 psig), and a flow meter to measure the total air flow rate.

F900807

Figure 4. SCHEMATIC DRAWING OF SOLIDS RECIRCULATION LDV TEST LOOP

In the solids feed section, solids particles from a storage hopper were fed into the test unit via a feed screw. A Penberthy jet-pump eductor (Figure 5) was used to create the pressure gradient required to overcome the cohesiveness of the particles and cause the solids to flow. The jet pump creates a negative pressure zone after the nozzle, which causes the particles to flow into the test unit.

The mixing chamber consisted of a 2-foot-long section of 2-inch-diameter pipe. The mixing section was added to the test unit to allow the solids to mix well with the gas before the mixture entered the test section.

A 10-foot-long section of 2-inch-diameter clear PVC pipe oriented vertically, served as the test section in the unit. The test section was located after a 3.5-foot-long section which allowed the solids and the gas to accelerate to their steady-state value. A pair of optical-glass windows 180 degrees apart were mounted in the test section after the acceleration section, to allow the laser beam to penetrate into the test section. The 20-mm-diameter window was designed to prevent accumulation of particles in front of the window. Differential pressure transmitters and gauges were distributed along the riser to measure the axial pressure distribution and pressure fluctuation during the tests. Near the bottom of the riser, spherical polystyrene tracer particles (0.96 microns in size) were added to the riser by a TSI atomizer, to allow the measurement of the gas velocity.

Following the test section, the solids were collected in two cyclones connected in series. A cloth filter captured the extremely fine particles which escaped through the cyclone. The solids collected by the cyclones were recirculated back to the feed system through two standpipes. Ball valves in the standpipes enabled the solids circulation rate to be controlled.

In a typical test, both ball valves in the recirculation standpipe were opened completely, and 300 grams of soil shale particles were loaded into the system. The frequency shift of the laser beam was set at zero. After this adjustment was completed, all of the settings on the photodetector and the frequency counter were set. The gas volumetric flow rate was then adjusted to the desired value. The LDV was then used to measure the particle velocity and the particle size. The axial pressure profile and the pressure fluctuations in the riser were also measured.

Figure 5. SCHEMATIC DRAWING OF JET-PUMP EDUCTOR

Different steady-state gas and solid flow rates were obtained by adjusting the gas flow rate through the system or by adjusting the ball valves in the cyclone recirculation standpipes.

Experimental Results

As described above, the calibration of the LDV to measure particle size distribution requires a reference flow condition. It was assumed that the reference particle-size distribution obtained using a Coulter Counter was the same as that obtained at a gas flow rate of 5 SCFM.

It was found that the shale particle-size ranged from 0.3 microns to 70 microns, with an average size of 13.6 microns. The calibration curve (Figure 6) showing the relationship between particle size and the amplitude of the signal from the LDV, was obtained using the technique described above.

Due to different mixing characteristics near the wall compared to the center of the pipe, the particle-size distribution is not uniform across the diameter of the pipe. Therefore, the particle-size distribution and the particle velocity were measured with the LDV at six different radial positions in the 2-inch-diameter test section: 0.032, 0.226, 0.290, 0.548, 0.806, and 0.935 inches from the centerline of the pipe. At each location, 1000 Doppler bursts were collected for a statistical analysis of the data. Last quarter, the experimental particle-size distributions as a function of radial position were obtained at 5 SCFM. The experimental particle-size distributions were obtained at each radial location this quarter at a higher gas flow rate of 15 SCFM, and are shown in Figures 7, 8, 9, 10, 11, and 12.

The radial profile of the particle size obtained at a gas flow rate of 15 SCFM is given in Figure 13. Very few large particles (or agglomerates) were found near the wall probably because of particle collision (and subsequent breakup) with the wall. Large particles were measured at other radial locations except at the location 0.290 inches from the centerline. At this location, only very small particles were detected. At this location, it was found that there was a sharp change in the particle velocity. This indicates a shear interaction within the particle phases, and would tend to cause agglomerates at these locations to be more unstable and break up. This

Figure 6. PARTICLE SIZE CALIBRATION CURVE FOR THE LDV

Figure 7. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
(Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.032)

Figure 8. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
 (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.226)

Figure 9. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
(Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.290)

Figure 10. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
(Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.548)

PSDVSR5A

Figure 11. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
 (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.806)

PSDVSR6A

Figure 12. PARTICLE SIZE DISTRIBUTION MEASURED WITH THE LDV
 (Gas Flow Rate: 15 SCFM, Dimensionless Radius: 0.935)

DPVSR15

Figure 13. PARTICLE SIZE VARIATION WITH RADIUS
(Gas Flow Rate: 15 SCFM)

could explain why larger particle sizes were rarely measured at this location. It is not known at this time why the particle shear interaction exists at this location.

Probability density distributions of the particle velocity at each radial location in the test section were obtained. A typical plot of probability density versus particle velocity is shown in Figure 14 for a gas flow rate of 5 SCFM. The average (mean) as well as the fluctuating (standard deviation) velocity were calculated for five different particle size ranges from the probability function. The particle size ranges used were:

- Group 1: less than 7 microns
- Group 2: from 7 to 15 microns
- Group 3: from 15 to 30 microns
- Group 4: from 30 to 45 microns
- Group 5: greater than 45 microns

Figures 15, 16, 17, 18, 19, and 20 show the radial profiles of the mean and fluctuating particle velocities as a function of particle size, for a gas flow rate of 15 SCFM. The dashed lines on the curves indicate that not enough data points were obtained in these regions to generate statistically meaningful results. In general, plug-flow was found to occur throughout the pipe, except at the location 0.29 inches away from the centerline. At this location, the mean and fluctuating particle velocities in particle-size Groups 2 and 3 went through a minimum. As discussed above, no particles from Groups 4 and 5 were measured at this location. The same type of behavior can be seen from a plot of particle velocity versus particle size at each radial position (Figures 21, 22, 23, 24, 25, 26).

For the 5 SCFM flow-rate data shown last quarter, the maximum of the mean and fluctuating velocities was at the center of the pipe. For the 15 SCFM flow-rate data, only those particle sizes greater than 30 microns had maximum mean and fluctuating velocities at the pipe center. For the smaller particles, the maximum of the mean and fluctuating velocities occurred between the centerline and the wall of the pipe.

Figure 14. PROBABILITY DENSITY AS A FUNCTION OF PARTICLE VELOCITY
 (Gas Flow Rate: 5 SCFM)

PW5R7A

Figure 15. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: < 7 Microns)

PW/SR15A

Figure 16. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: 7 to 15 Microns)

PW5R30A

Figure 17. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: 15 to 30 Microns)

PWSR45A

Figure 18. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: 30 to 45 Microns)

PWSR60A

Figure 19. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: > 45 Microns)

PVSRMXA

Figure 20. MEAN AND FLUCTUATING GAS VELOCITY AS A FUNCTION OF PIPE RADIUS
 (Particle Size: Feed Distribution)

WSDPR1A

Figure 21. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
(Q = 15 SCFM, Dimensionless Radius: 0.032)

WSDPR2A

Figure 22. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
(Q = 15 SCFM. Dimensionless Radius: 0.226)

WSDPR3A

Figure 23. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
(Q = 15 SCFM, Dimensionless Radius: 0.290)

wsdpr4

Figure 24. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
(Q = 15 SCFM, Dimensionless Radius: 0.548)

Figure 25. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
(Q = 15 SCFM, Dimensionless Radius: 0.806)

WSDPR6

Figure 26. PARTICLE VELOCITY AS A FUNCTION OF PARTICLE SIZE
 (Q = 15 SCFM, Dimensionless Radius: 0.935)

Task 5. Large-Scale Flow Tests

This quarter, a cold-flow model of the downcomer section of the large-scale test unit was constructed to determine the best method of controlling the flow rate of cohesive solids through the standpipe and slide valve. The cohesive solids were fluidized in a 12-inch-diameter Plexiglas column, and were allowed to flow by gravity through a 3-inch-diameter clear PVC pipe approximately 14 feet long. A slide valve at the bottom of the standpipe controlled the flow rate of solids through the pipe. Four aeration ports were drilled into the standpipe immediately above the slide valve. Gas was pulsed into the standpipe at this point to see if it would influence the solids flow rate. A schematic drawing of the cold-flow model is given in Figure 27.

It was found that the cohesive oil shale particles would not flow well unless aeration was pulsed into the standpipe. When aeration was pulsed into the standpipe, the flow was steady and controllable. The pulsing sequence which appeared to give the best results was approximately 0.2 seconds on, and 1 to 2 seconds off. The 12-inch-diameter standpipe in the large-scale test unit was then modified to add pulse-aeration ports above the controlling slide valve.

Task 6. Comparison of Model With Data and Preparation of Final Report

No work was performed on this task this quarter.

PULSCFM

Figure 27. SCHEMATIC DRAWING OF COLD-FLOW MODEL

NOMENCLATURE

A_d	= Doppler burst amplitude
A_{do}	= amplitude of Doppler signal generated by particle passing through the center of the focusing volume
A_f	= intersection area
b_o	= e^{-2} dimension of focusing volume
d_f	= fringe space
d_p	= particle diameter
d_{pi}	= particle diameter of size i
E_x	= photon energy
f_d	= Doppler burst frequency
g_o	= radial distribution function
G	= solids mass flux
I	= radiation intensity
I_o	= initial radiation intensity
l	= path length of particle
l_{max}	= maximum path length of particle in fringe space
N_s	= total number of sample bursts
P	= pressure
Q	= gas volumetric flow rate
T_s	= sampling time period
t	= thickness of absorbing material
U	= particle velocity component perpendicular to optical axis
U_{ave}	= average solid velocity
U_{pi}	= particle velocity of particle size i
V	= volume
ΔV	= total volume of solids passing through the intersection area

V_p = solids velocity
 W_i = weight fraction of component i
 W_p = weight of powder
 α = radiation wavelength
 $\Delta\tau_i$ = average time period of a Doppler burst
 $\Delta\tau_i$ = i^{th} period in a Doppler burst
 δ = linear-absorption coefficient
 ϵ_f = gas volume fraction of fluid
 ϵ_i = volume fraction of component i
 ϵ_s = solids volume fraction
 γ = mass absorption coefficient
 γ_{mix} = mixture absorption coefficient
 γ_a = mass absorption coefficient for air
 γ_s = mass absorption coefficient for solid
 γ_i = mass absorption coefficient for component i
 ρ = absorber density
 ρ_{mix} = density of absorbing mixture
 ρ_p = particle density
 ρ_s = solid absorber density

Subscripts

g = gas phase
 s = solid phase

LITERATURE CITED

1. Farmer, W. M., Measurement of Particle Size, Number Density and Velocity Using a Laser Interferometer, Applied Optics, 11, No. 11, p. 2603, 1972.
2. Farmer, W. M., Measurement of Particle Size and Concentration Using LDV Techniques, Proceedings of the Dynamic Flow Conference, 1978.
3. Lee, S. L, and Srinivasan, J., Measurement of Local Size and Velocity Probability Density Distribution in Two-Phase Suspension Flows by Laser-Doppler Techniques, Int. J. Multiphase flow, 4, p. 141, 1978.

END

**DATE
FILMED**

4 / 06 / 92