BNL--48478

DE93 006675

Study on the Results from SYNCH and MAD Programs in Calculating Lattice with Coordinate Rotation

Jianming Xu

December 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ived by CCTI

EB O 2 1993

R H I C P R O J E C T

Brookhaven National Laboratory
Associated Universities, Inc.
Upton, NY 11973

MASTER

Under Contract No. DE-AC02-76CH00016 with the
UNITED STATES DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Study on the Results from SYNCH and MAD Programs in Calculating Lattice with Coordinate Rotation

Jianming Xu

Brookhaven National Laboratory
December 1992

1. Introduction

In some lattices, it is necessary to introduce coordinate rotation around the beam axis, for example, in such a lattice, where the horizontal deflection and the change in level are mixed. The results from SYNCH and MAD programs in calculating such a lattice have been studied and some discrepancies have been found. The output of SYNCH is shown in Table 1 and outputs from MAD are shown in Table 2 and Table 3. The arrangement of this simple lattice is shown in these outputs. The dispersion functions are discussed first and then the Twiss Parameters (β 's and α 's).

2. Dispersion Functions

1. Dispersion functions before coordinate rotation at L_{32} .

The dispersion functions before rotation $\eta_{x0}, \eta'_{x0}, \eta_{y0}, \eta'_{y0}$ from the outputs of MAD and SYNCH are shown as:

MAD output (Table 2 and 3)

$$\begin{aligned}\eta_{x0} &= 1.146593631, & \eta'_{x0} &= 0.02084258749; \\ \eta_{y0} &= 0.08803616920, & \eta'_{y0} &= 0.01253036558.\end{aligned}\tag{1}$$

SYNCH TRKB (Track Betatron Function) Output (Table 1)

$$\begin{aligned}\eta_{x0} &= 1.146593, & \eta'_{x0} &= 0.020843; \\ \eta_{y0} &= 0.088036, & \eta'_{y0} &= 0.012530.\end{aligned}\tag{2}$$

SYNCH MMM (Matrix Multiplication) Output (Table 1, WST)

$$\begin{aligned} m_{16} = \eta_{x0} = 1.14670914, \quad \eta'_{x0} = m_{26} = 0.02083611; \\ m_{36} = \eta_{y0} = 0.08803616, \quad m_{46} = \eta'_{y0} = 0.01253036. \end{aligned} \quad (3)$$

From above results, it is clear that without coordinate rotation, the dispersion functions from MAD and SYNCH TRKB output coincide with each other, but η_{0x} and η'_{0x} from SYNCH MMM result differ little from both MAD and SYNCH TRKB outputs.

2. Dispersion functions after a rotation around the beam axis by an angle ξ

The relation between dispersion functions $\eta_x, \eta'_x, \eta_y, \eta'_y$ after rotation and $\eta_{x0}, \eta'_{x0}, \eta_{y0}$ and η'_{y0} before rotation can be expressed as follows

$$\eta_x = \eta_{x0} \cos \xi + \eta_{y0} \sin \xi \quad (4)$$

$$\eta'_x = \eta'_{x0} \cos \xi + \eta'_{y0} \sin \xi \quad (5)$$

$$\eta_y = -\eta_{x0} \sin \xi + \eta_{y0} \cos \xi \quad (6)$$

$$\eta'_y = -\eta'_{x0} \sin \xi + \eta'_{y0} \cos \xi \quad (7)$$

Putting Eq. (1), the MAD output before rotation into Eqs. (4)-(7), we get ($\xi = 0.05$ rad).

MAD by matrix multiplication

$$\begin{aligned} \eta_x = 1.149560662, \quad \eta'_x = 0.02144279695; \\ \eta_y = 0.0306203495, \quad \eta'_y = 0.01147301068. \end{aligned} \quad (8)$$

The MAD outputs (from Tables 2 and 3 at R_1) are

$$\begin{aligned} \eta_x = 1.149560662, \quad \eta'_x = 0.02144279695; \\ \eta_y = 0.03062034973, \quad \eta'_y = 0.01147301068. \end{aligned} \quad (9)$$

The MAD output (9) coincides with the result from matrix multiplication, Eq. (8).

Using the SYNCH TRKB output before rotation (Eq. (2)) as initial value by means of matrix multiplication Eqs. (4)-(7), we get

SYNCH TRKB by matrix multiplication

$$\begin{aligned}\eta_x &= 1.149560023, & \eta'_x &= 0.02144319067; \\ \eta_y &= 0.030620212, & \eta'_y &= 0.01147262494.\end{aligned}\tag{10}$$

But the SYNCH TRKB output after rotation at R_1 is thoroughly different. They are as follows (from Table 1)

$$\begin{aligned}\eta_x &= -1.102947, & \eta'_x &= -0.020049; \\ \eta_y &= -0.084685, & \eta'_y &= -0.012053.\end{aligned}\tag{11}$$

The SYNCH TRKB output after coordinate rotation does not fulfill the coordinate rotation relationship, Eq. (4)-(7). It is wrong apparently.

The relation between the SYNCH MMM output before rotation [Eq. (3)] and after rotation (from Table 1, WSRT) fulfill the coordinate rotation relationship [Eqs. (4)-(7)]. The MMM output after rotation (Table 1, WSRT) is

$$\begin{aligned}\eta_x &= 1.14967602, & \eta'_x &= 0.02143632; \\ \eta_y &= 0.03061457, & \eta'_y &= 0.01147333.\end{aligned}\tag{12}$$

The data in Eq. (12) differ from those in Eq. (9) (MAD output), because the data before rotation from SYNCH MMM output Eq. (3) differ from both SYNCH TRKB output Eq. (2) and MAD output Eq. (1).

3. Conclusion about dispersion function calculation.

For lattice without coordinate rotation, the MAD TWISS output coincides with SYNCH TRKB output but the SYNCH MMM output differs from them. After coordinate rotation, the MAD TWISS output fulfills the coordinate rotation relationship but SYNCH TRKB output does not fulfill. The SYNCH MMM output after rotation fulfill the coordinate rotation relationship but its data differs from MAD output because its data before rotation differs from both MAD and SYNCH TRKB output. It seems that, the dispersion functions from MAD output are reliable.

3. Twiss Parameters β, α

1. We use the following initial conditions.

$$\begin{aligned}\beta_{xi} &= 40.755237, & \alpha_{xi} &= 1.992883, & \gamma_{xi} &= 0.12198635; \\ \beta_{yi} &= 16.997687, & \alpha_{yi} &= -1.04618, & \gamma_{yi} &= 0.12322221.\end{aligned}\tag{13}$$

Before rotation, the output of MAD and SYNCH TRKB (at L32) coincides with each other. They are as follows:

MAD output (from Table 2 and Table 3)

$$\begin{aligned}\beta_{x0} &= 11.78884158, & \alpha_{x0} &= 0.6635168614; \\ \beta_{y0} &= 54.09318824, & \alpha_{y0} &= -2.370235501.\end{aligned}\tag{14}$$

SYNCH TRKB output (from Table 1)

$$\begin{aligned}\beta_{x0} &= 11.7888, & \alpha_{x0} &= 0.663517; \\ \beta_{y0} &= 54.0932, & \alpha_{y0} &= -2.370235.\end{aligned}\tag{15}$$

The initial Twiss parameter Eq. (13) and the final Twiss parameters Eq. (14) or (15) should fulfill the following relation

$$\begin{pmatrix} \beta_0 \\ \alpha_0 \\ \gamma_0 \end{pmatrix} = \begin{pmatrix} m_{11}^2 & -2m_{11}m_{12} & m_{12}^2 \\ -m_{11}m_{21} & 1 + 2m_{12}m_{21} & -m_{12}m_{22} \\ m_{21}^2 & -2m_{21}m_{22} & m_{22}^2 \end{pmatrix} \begin{pmatrix} \beta_i \\ \alpha_i \\ \gamma_i \end{pmatrix}\tag{16}$$

where m 's are the transfer matrix elements. Using the corresponding 4×4 matrix from SYNCH MMM output (Table 1 WST) from Eqs. (13) and (16) we can calculate the β 's, α 's at L32. The calculated results are shown as following which well coincide with the MAD and SYNCH TRKB output.

$$\begin{aligned}\beta_{x0} &= 11.78884092, & \alpha_{x0} &= 0.66351697; \\ \beta_{y0} &= 54.09318664, & \alpha_{y0} &= -2.370235431.\end{aligned}\tag{17}$$

The above result shows that without rotation the β 's, α 's from MAD and SYNCH TRKB and the 4×4 transfer matrix from SYNCH MMM output are all reliable.

2. The 4×4 transfer matrix after rotation from SYNCH MMM output (Table 2, WSRT) fulfill the coordinate rotation relation. The 4×4 matrix after rotation ($\xi = 0.05$) can be got by matrix multiplication, the result is shown as follows:

$$M = \begin{pmatrix} 0.660723045 & 18.98334088 & -0.119785867 & 1.40630563 \\ -0.121925944 & -1.99336127 & -0.006135546 & 0.051179119 \\ -0.03306371 & -0.949958808 & -2.393720579 & 28.10267027 \\ 0.00610138 & 0.099751203 & -0.122608639 & 1.022729245 \end{pmatrix} \quad (18)$$

The SYNCH MMM output is as follows (Table 1, WSRT)

$$M = \begin{pmatrix} 0.66072304 & 18.98334088 & -0.11978587 & 1.40630563 \\ -0.12192595 & -1.99336127 & -0.00613555 & 0.05117912 \\ -0.03306371 & -0.94995881 & -2.39372058 & 28.10267027 \\ 0.006160138 & 0.09975120 & -0.12260864 & 1.02272924 \end{pmatrix} \quad (19)$$

Eq. (19) well coincides with Eq. (18). It shows that the 4×4 matrix from SYNCH MMM output is reliable after rotation also.

3. The projection of the 4-dimensional emittance ellipsoid after rotation on xx' and yy' planes.

From the inverse transformation matrix after rotation (Table 1, IWSR) we can get the 4-dimensional emittance ellipsoid after rotation and then get its projection on xx' and yy' planes. They are expressed as follows:

$$0.120795313x^2 + 2 \times 0.648550256xx' + 11.76053439x'^2 = 1.0113922\epsilon_0 \quad (20)$$

$$0.120966214y^2 - 2 \times 2.336044532yy' + 53.3794012y'^2 = 1.0113922\epsilon_0 \quad (21)$$

where ϵ_0 is the initial x and y emittance. The projections depend upon the ratio of the initial x and y emittance. Here we take the ratio to be one. The corresponding β, α value of these projections are

$$\begin{aligned} \beta_x &= 11.76053439, & \alpha_x &= 0.648550256; \\ \beta_y &= 53.3794012, & \alpha_y &= -2.336044532. \end{aligned} \quad (22)$$

4. β, α values after rotation from SYNCH and MAD (at R_1)

SYNCH TRKB output (Table 1)

$$\begin{aligned}\beta_x &= 10.9084, & \alpha_x &= 0.613963; \\ \beta_y &= 50.0533, & \alpha_y &= -2.193219.\end{aligned}\tag{23}$$

MAD Twiss output (Table 2)

$$\begin{aligned}\beta_x &= 11.75939402, & \alpha_x &= 0.6635168614; \\ \beta_y &= 54.09318824, & \alpha_y &= -2.370235501.\end{aligned}\tag{24}$$

From MAD Twiss couple output (Table 3)

$$\begin{aligned}\beta_1 &= 17.82817229, & \alpha_1 &= 1.890607154; \\ \beta_2 &= 120.7788642, & \alpha_2 &= -5.465936926.\end{aligned}\tag{25}$$

There is large difference between the above three sets of Twiss parameters for the same lattice same initial conditions and none of them coincides with the corresponding parameters of the projections of the 4-dimensional emittance ellipsoid on xx' and yy' plane. When the rotation angle ξ is smaller, the discrepancy is smaller but they do not coincide with each other also. For example, if $\xi = 0.0002735$ rad, the results are shown as follows:

Projections on xx' and yy' planes

$$\begin{aligned}\beta_x &= 11.78884012, & \alpha_x &= 0.663516342; \\ \beta_y &= 54.0931771, & \alpha_y &= -2.370234907.\end{aligned}\tag{26}$$

SYNCH TRKB output

$$\begin{aligned}\beta_x &= 11.7859, & \alpha_x &= 0.663354; \\ \beta_y &= 54.07999, & \alpha_y &= -2.369653.\end{aligned}\tag{27}$$

MAD Twiss output

$$\begin{aligned}\beta_x &= 11.78844069, & \alpha_x &= 0.6635168117; \\ \beta_y &= 54.09318420, & \alpha_y &= -2.370235323.\end{aligned}\tag{28}$$

MAD Twiss couple output

$$\begin{aligned}\beta_1 &= 11.79540445, & \alpha_1 &= 0.668622315; \\ \beta_2 &= 54.25392611, & \alpha_2 &= -2.377879573.\end{aligned}\tag{29}$$

The discrepancy is clear even though the rotation is as small as 0.0002735 rad. This fact means that, in lattices with transverse coupling, in different programs the β 's and α 's have different meaning and different value. One has to use these programs carefully in calculating or matching lattices with transverse coupling.

Acknowledgments

The author would like to thank Dr. J. Claus and Dr. H. Foelsche for their support and valuable discussions.

SIZE	7	Ø
------	---	---

[illegible]

POS	S	QX	BX	AX	X	DX	QY	BY	AY	Y	DY
0	0.0000	0.000000	40.7552	1.992883	0.000108	-0.000010	0.000000	16.9977	-1.046180	0.000000	0.000000
1 L01	10.9104	0.082917	11.7898	0.661959	0.000000	-0.000010	0.058353	54.4943	-2.390583	0.000000	0.000000
2 W1D	14.5680	0.135874	11.7918	-0.662573	0.081856	0.045950	0.068490	54.5027	2.385442	0.000000	0.000000
3 L12	28.6197	0.229372	54.5080	-2.377362	0.727537	0.045950	0.162557	11.6676	0.659848	0.000000	0.000000
4 W2F	32.2773	0.239503	54.5133	2.376071	0.893115	0.020928	0.216181	11.6386	-0.651090	0.000000	0.000000
5 L31	38.3888	0.263638	30.0242	1.631025	0.981018	0.020928	0.275545	24.1663	-1.398794	0.000000	0.000000
6 DP1	40.2176	0.274386	24.4620	1.410159	1.019215	0.020843	0.286419	29.6916	-1.622532	0.011457	0.012530
7 L32	46.3290	0.332978	11.7888	0.663517	1.146593	0.020843	0.310785	54.0932	-2.370235	0.088036	0.012530
8 R1	46.3290	0.832978	10.9084	0.613963	-1.102947	-0.020049	0.810785	50.0533	-2.193219	-0.084685	-0.012053

*** CALL // WAT

TRANSFER MATRICES

R(I,J)

ELEMENT	X	DX/DS	Y	DY/DS	-DS	DP/P	1
	0.66154981	19.00709480	0.00000000	0.00000000	0.00000000	1.14670914	0.00000000
	-0.12207851	-1.99585557	0.00000000	0.00000000	0.00000000	0.02083611	0.00000000
WST	0.00000000	0.00000000	-2.39671585	28.13783524	0.00000000	0.08803616	0.00000000
	0.00000000	0.00000000	-0.12276206	1.02400899	0.00000000	0.01253036	0.00000000
	-0.15377267	-2.68469968	0.01922422	-0.26242750	1.00000000	-0.03605821	0.00000000
	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000	0.00000000
	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000

LENGTH = 46.32903400 THETA = 0.07473136

TRANSFER MATRICES

R(I,J)

ELEMENT	X	DX/DS	Y	DY/DS	-DS	DP/P	1
	0.66072304	18.98334088	-0.11978587	1.40630563	0.00000000	1.14967602	0.00000000
	-0.12192595	-1.99336127	-0.00613555	0.05117912	0.00000000	0.02143632	0.00000000
WSRT	-0.03306371	-0.94995881	-2.39372058	28.10267027	0.00000000	0.03061457	0.00000000
	0.00610138	0.09975120	-0.12260864	1.02272924	0.00000000	0.01147333	0.00000000
	-0.15377267	-2.68469968	0.01922422	-0.26242750	1.00000000	-0.03605821	0.00000000
	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000	0.00000000
	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000

LENGTH = 46.32903400 THETA = 0.07473136

*** CALL // INM

TRANSFER MATRICES

R(I,J)

ELEMENT	X	DX/DS	Y	DY/DS	-DS	DP/P	1
	-1.99585557	-19.00709480	0.00000000	0.00000000	0.00000000	2.68469968	0.00000000

IWS

0.12207851	0.66154981	0.00000000	0.00000000	0.00000000	-0.15377267	0.00000000
0.00000000	0.00000000	1.02240089	-28.13783524	0.00000000	0.26242750	0.00000000
0.00000000	0.00000000	0.12276206	-2.39671585	0.00000000	0.01922422	0.00000000
0.02083611	-1.14670914	0.01253036	-0.08803616	1.00000000	0.03605821	0.00000000
0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000	0.00000000
0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000

LENGTH = -46.32903400 THETA = -0.07473136

TRANSFER MATRICES

ELEMENT	X	DX/DS	Y	DY/DS	-DS	DP/P	1
IWSR	-1.99336127	-18.98334088	0.09975120	0.94995881	0.00000000	2.68469968	0.00000000
	0.12192595	0.66072304	-0.00610138	-0.03306371	0.00000000	-0.15377267	0.00000000
	0.05117912	-1.40630563	1.02272924	-28.10267027	0.00000000	0.26242750	0.00000000
	0.00613555	-0.11978587	0.12260864	-2.39372058	0.00000000	0.01922422	0.00000000
	0.02143632	-1.14967602	0.01147333	-0.03061457	1.00000000	0.03605821	0.00000000
	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000	0.00000000
0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	0.00000000	1.00000000	

LENGTH = -46.32903400 THETA = -0.07473136

*** FIN // CORE USE SUMMARY MAXIMUM USED UNUSED

Table 2. MAD TWISS output

TITLE, "UWVGM A4 BNL.MAD JUL/30/92 AGS RHIC Beam Tr Line U+W+G LINE";
 ! PARAMETER DEFINITION

L01: DRIFT, L=10.910434
 W1D: RBEND, L=3.657600, ANGLE=0.043630780, K1=-0.02351628
 L12: DRIFT, L=14.05170
 W2F: RBEND, L=3.657600, ANGLE=0.043630780, K1=0.02351628
 L31: DRIFT, L=6.11145
 W1P: RBEND, L=1.82880, ANGLE=0.012530235, TILT
 L32: DRIFT, L=6.111450
 R1: SROT, ANGLE=0.05

WL: LINE=(L01, W1D, L12, W2F, L31, W1P, L32, R1)
 TWISS, BETX=40.756237, ALFX=1.992883, BETY=16.997687, &
 ALFY=-1.04618, DX=-0.0010772, DPX=-9.8343E-6, DY=0.00, &
 DPY=0.00, TAPE

DELTA(P)/P = 0.000000 SYMM = F PAGE 1

ELEMENT SEQUENCE		H O R I Z O N T A L						I				V E R T I C A L							
POS. NO.	ELEMENT NAME	NO.	DIST I [M]	I	BETAX [M]	ALFAX [1]	MUX [2PI]	X(CO) [MM]	PX(CO) [MM]	DX [M]	DPX I [1]	I	BETAY [M]	ALFAY [1]	MUY [2PI]	Y(CO) [MM]	PY(CO) [MM]	DY [M]	DPY [1]
BEGIN	WL	1	0.000		40.755	1.993	0.000	0.000	0.000	0.000	0.000		16.998	-1.046	0.000	0.000	0.000	0.000	0.000
1	L01	1	10.910		11.790	0.662	0.083	0.000	0.000	0.000	0.000		54.494	-2.391	0.058	0.000	0.000	0.000	0.000
2	W1D	1	14.568		11.792	-0.663	0.136	0.000	0.000	0.000	0.046		54.503	2.389	0.068	0.000	0.000	0.000	0.000
3	L12	1	28.620		54.508	-2.377	0.229	0.000	0.000	0.000	0.046		11.668	0.660	0.163	0.000	0.000	0.000	0.000
4	W2F	1	32.277		54.513	2.376	0.240	0.000	0.000	0.000	0.021		11.639	-0.651	0.216	0.000	0.000	0.000	0.000
5	L31	1	38.389		30.024	1.631	0.264	0.000	0.000	0.000	0.021		24.166	-1.399	0.276	0.000	0.000	0.000	0.000
6	WP1	1	40.218		24.462	1.410	0.274	0.000	0.000	0.000	0.021		29.692	-1.623	0.286	0.000	0.000	0.011	0.013
7	L32	1	46.329		11.789	0.664	0.333	0.000	0.000	0.000	0.021		54.093	-2.370	0.311	0.000	0.000	0.088	0.013
8	R1	1	46.329		11.759	0.662	0.333	0.000	0.000	0.000	0.021		53.958	-2.364	0.311	0.000	0.000	0.031	0.011
END	WL	1	46.329		11.759	0.662	0.333	0.000	0.000	0.000	0.021		53.958	-2.364	0.311	0.000	0.000	0.031	0.011
TOTAL LENGTH =			46.329034				MUX	=	0.332978				MUY	=		0.310785			
DELTA(S) =			0.000000		mm		DMUX	=	-0.289565				DMUY	=		-0.525197			
							BETAX (MAX)	=	54.513329				BETAY (MAX)	=		54.502705			
							DX (MAX)	=	1.149561				DY (MAX)	=		0.088036			

WARNING ## TWISS1: TWISS PARAMETERS FOR DELTA(P)/P = 0.000000000 MAY BE WRONG DUE TO COUPLING.

INITIAL
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
1.99288300E+00 4.07552370E+01 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
-1.04618000E+00 1.69976870E+01 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
DRIFT L01
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
10.910434
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
6.61958969E-01 1.178975894E+01 8.291732427E-02 4.235189138E-07-9.83430000E-06
-2.390587812E+00 5.449431539E+01 5.835336206E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
RBEND W1D 3.657600 4.363078000E-02-2.351628000E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
-6.625729332E-01 1.179179474E+01 1.358738998E-01 8.185562552E-02 4.595041089E-02
2.388542037E+00 5.450270480E+01 6.849037676E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
DRIFT L12 14.051700
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
-2.377361680E+00 5.450804395E+01 2.293720334E-01 7.275370142E-01 4.595041089E-02
6.598476797E-01 1.166764703E+01 1.625567451E-01 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
RBEND W2F 3.657600 4.363078000E-02 2.351628000E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
2.376071221E+00 5.451332857E+01 2.395034915E-01 8.531150845E-01 2.092845051E-02
-6.510899602E-01 1.163857385E+01 2.161809221E-01 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
DRIFT L31 6.111450
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
1.631024961E+00 3.002416061E+01 2.636382729E-01 9.810182634E-01 2.092845051E-02
-1.398793640E+00 2.416633498E+01 2.755453954E-01 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
RBEND WP1 1.828800 1.253023500E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
1.570796327E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
1.410158863E+00 2.446200698E+01 2.743864553E-01 1.019215199E+00 2.084258701E-02
-1.622531821E+00 2.969159039E+01 2.864194321E-01 1.145749847E-02 1.253040058E-02
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
DRIFT L32 6.111450
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
6.635168641E-01 1.178884146E+01 3.329783392E-01 1.146593628E+00 2.084258701E-02
-2.370235501E+00 5.409318824E+01 3.107848662E-01 8.803641511E-02 1.253040058E-02
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
SR0T R1 0.000000
0.00000000E+00 5.00000000E-02 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 1.175939391E+01 3.329783392E-01 1.149560671E+00 2.144279822E-02
6.618594538E-01 1.175939391E+01 3.329783392E-01 1.149560671E+00 2.144279822E-02
-2.364314848E+00 5.395806793E+01 3.107848662E-01 3.062059551E-02 1.147304566E-02
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00 0.00000000E+00
-6.663191159E-01 3.329783392E-01-2.895654389E-01 5.451332857E+01 1.149560671E+00
-6.864956584E-01 3.107848662E-01-5.251966506E-01 5.450270480E+01 8.803641511E-02

Table 3. MAD Twiss Couple Output

! PARAMETER DEFINITION

L01: DRIFT, L=10.910434
W1D: RBEND, L=3.657600, ANGLE=0.043630780, K1=-0.02351628
L12: DRIFT, L=14.05170
W2F: RBEND, L=3.657600, ANGLE=0.043630780, K1=0.02351628
L31: DRIFT, L=6.11145
W1P: RBEND, L=1.82880, ANGLE=0.012530235, TILT
L32: DRIFT, L=6.111450
R1: SROT, ANGLE=0.05
!
WL: LINE=(L01, W1D, L12, W2F, L31, W1P, L32, R1)
TWISS, BETX=40.756237, ALFX=1.992883, BETY=16.997687, &
ALFY=-1.04618, DX=0.0010772, DPX=-9.8343E-6, DY=0.00, &
DPY=0.00, TAPE, couple
0.000000 SYMM = F

DELTA(P)/P =

POS. NO.	ELEMENT NAME	SEQUENCE OCC. NO.	DIST [M]	M O D E S				C O U P L I N G				I	O R B I T				D I S P E R S I O N			
				BETA1 [M]	ALFA1 [1]	MU1 [2PI]	I	R(1,1) [1]	R(1,2) [M]	COSPHI [1]	SINPHI [1]		X(CO) [MM]	Y(CO) [MM]	PX(CO) [.001]	PY(CO) [.001]	DX [M]	DY [M]	DPX [1]	DPY [1]
BEGIN	WL	1	0.000	46.765	1.993	0.000	I	1.000	0.000	1.000	0.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
1	L01	1	10.910	11.790	0.662	0.083	I	0.000	1.000	0.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
2	W1D	1	14.568	54.494	-2.391	0.058	I	0.000	1.000	1.000	0.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
3	L12	1	28.620	54.503	2.389	0.068	I	-0.172	1.298	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
4	W2F	1	32.277	54.508	-2.377	0.229	I	-1.748	43.571	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
5	L31	1	38.389	54.513	2.376	0.240	I	3.015	64.260	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
6	W1P	1	40.218	30.024	1.631	0.264	I	5.274	82.185	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
7	L32	1	46.329	24.166	-1.399	0.274	I	0.370	5.948	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
8	R1	1	46.329	29.692	-1.623	0.286	I	0.370	5.272	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
END	WL	1	46.329	11.789	0.664	0.333	I	8.219	64.169	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
				54.093	-2.370	0.311	I	0.370	3.011	1.000	1.000	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
				17.828	1.891	1.279	I	12.355	96.797	0.663	1.249	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
				120.779	-5.466	0.320	I	0.558	4.499	1.249	0.663	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
				17.828	1.891	1.279	I	12.355	96.797	0.663	1.249	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
				120.779	-5.466	0.320	I	0.558	4.499	1.249	0.663	I	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

TOTAL LENGTH =	46.329034	MU1	=	1.278829	MU2	=	0.320316
DELTA(S)	0.000000 mm	BETAX(MAX)	=	54.513329	BETAY(MAX)	=	120.778865
		DX(MAX)	=	1.149561	DY(MAX)	=	0.088036

[illegible]

END

**DATE
FILMED**

3 / 18 / 93