Final Report on U.S. Dept. of Energy Grant No.
DE-FG02-89ER53298, for Research on
"Magnetofluid Transport," at Dartmouth College,
Hanover, NH (David Montgomery, PI)

This report summarizes the work carried out under the above grant, which ended September 29, 1992. The original funding came in response to a proposal under the Tokamak Transport Initiative, and was envisioned as the beginning of an extended program to test the hypothesis that large-scale convection is the dominant loss mechanism in tokamak operation. The original funding was for a period of two years. Before the first year of grant activity had ended, the PI was notified that not only would the grant not be renewed, but also that the second year's budget would have to be for \$30,000 less than had been initially awarded.

Thus, even before the second year's activity had begun, it became necessary to think in terms of closing out the operation. The PI had been previously notified that the original proposal had received the second highest rating in the competition from the original panel that evaluated the TTI proposals. The books were balanced by two means: (i) the PI took an accumulated sabbatical term at JET in England, using Dartmouth funds instead of DOE funds for the quarter's support; and (ii) the postdoctoral research associate, who had been hired as one of the principal items in the budget, was told that he would have to leave six months earlier than the end of what he had initially been led to believe was at least a two year appointment. So despite the fact that, as will appear below, quite a bit of work got supported in part by the grant, it did not have a chance to develop into the rather novel effort that was envisioned in the original proposal.

Abstracts of published papers supported in part by this and another DOE Grant (DE-FGO2-85ER53194) are collected in an Appendix, and citation numbers in parentheses refer to this collection of abstracts. Based on previous work with non-ideal MHD instabilities upon resistive MHD equilibria (1), the PI had concluded that at the thresholds of the instabilities, flows and finite velocity fields become an inherent part of resistive MHD equilibrium. The thresholds depend only upon Hartmann number and zero-flow axisymmetric pinch ratio (or in tokamak language, upon the reciprocal of the safety factor evaluated at the minor radius), and so become easier to reach the hotter the plasma becomes (2,3). This is due to the fact that both conductivity and Hartmann number increase with increasing temperature (4). The magnetofluid does not burst into turbulence until far above this threshold, as in the case, for example, of the reversed field pinch. Rather, the equilibrium bifurcates, and the

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED. *ds*

preferred branch is one in which the velocity field is non-zero. This statement is consistent with the rather large velocity fields recently reported in JET, though of course no MHD description can accurately describe all of the complex features of a non-MHD nature that go on in JET.

The nature of the flows that characterize this second regime of driven, dissipative MHD equilibrium is of importance. They are paired helical vortices characterized by poloidal and toroidal mode numbers (m,n) that are associated with the first linearly unstable mode to appear as the current is raised. In real life, they may be expected to be superimposed upon the poloidal and toroidal rotations that accompany a charge imbalance (5) in the plasma, and may be seen in pure form most easily in computer simulations which adopt an inherently charge-density-free mathematical description at the outset. The velocity streamlines, projected into a poloidal plane, appear much as the pairs of large counter-rotating vortices that are now well known to characterize the high Reynolds number states of two-dimensional Navier-Stokes flows (6). That is, they connect the hot geometrical center of the plasma column with its cool perimeter, and as such constitute an extremely efficient heat loss mechanism, even in the limit in which no particles are lost: more efficient than any "anomalous thermal conductivity" might be imagined to be.

The appearance of the paired helical vortices (actually only a rather more specific version of the "convection cells" that were conjectured for confinement devices in the late 1950s) has so far been seen theoretically within two mathematical frameworks: (i) that of "reduced," or Strauss approximation, MHD with a locally variable temperature; or (ii) incompressible one-fluid MHD. Both descriptions lack crucial features that may be present in the full laboratory setting: The "reduced" MHD description has been shown to miss the bifurcated steady helical states (7), and incompressible one-fluid MHD lacks the capability of locally spatially and temporarily varying transport coefficients.

It was the original hope for this grant that the phenomena of interest might be apprehended from a computational standpoint through a full set of MHD equations that contained an energy equation and locally-varying Braginskii transport coefficients. This is quite an ambitious project, since even the simplest axisymmetric zero-flow equilibria have not been treated in this way. The one paper generated by Michael Goodman (the postdoctoral hired on this grant, who has now left to take a job with NASA) may be the only one so far to treat resistive MHD equilibrium at this level (8). The paper is full of puzzles which would need to be sorted out before attempting any dynamical computations about what happens to the equilibrium beyond its stability thresholds. It can only be a source

of regret that this problem, which will have to be taken up by somebody eventually if an understanding of tokamak energy balance is ever to be achieved, could not be pursued further under this grant.

To summarize some achievements related to these considerations that were supported in part by this grant, we may list the following items. (i) Development of a spectral-method, fully three-dimensional MHD code in cylindrical geometry based on an expansion in Chandrasekhar-Kendall eigenfunctions of the curl, a code which is now functioning well on a variety of problems (2,3). (ii) A rather extraordinary clarification, within the framework of MHD, of how inadequate spatial resolution, in a finite mode number approximation to a set of nonlinear partial differential equations, can lead to an apparent "chaos" which disappears when the retained mode number becomes adequate (9). (iii) Verification of the relaxation to a "most probable" state for an electrostatic guiding center plasma (6). (iv) Establishment of the theorem that for resistive equilibria, the stability threshold is determined by the Hartmann number and axisymmetric pinch ratio alone, and thus it is never correct to calculate or estimate thresholds by ignoring viscous effects; indeed, the large uncertainties that exist, in which of the various (10) alternatives to choose for a viscous stress tensor, may presently stand as the largest single uncertainty involved in theoretical and computational MHD.

- [1] Helical, Dissipative, Magnetohydrodynamic States With Flow
D. Montgomery, L. Phillips, and M. Theobald, *Phys. Rev. A*, **40**, 1515-1523 (1989).

It is shown that for an axially periodic column of magnetofluid driven by an applied axial electric field, the total rate of energy dissipation (Ohmic plus viscous) can be lowered by permitting a helical component with vortical flow in the solution. The principle of minimum energy-dissipation rate suggests that this partially helical state will be preferred to the axisymmetric one that exists for the same parameters. The result is consistent with the repeated appearance of such partially-helical states in several fully three-dimensional numerical computations and is not inconsistent with the data from some confinement experiments.

- [2] Nonlinear Magnetohydrodynamics by Galerkin - Method Computation
X. Shan, D. Montgomery, and H. Chen, *Phys. Rev. A*, **44**, 6800-6818
(1991).

A fully spectral numerical code is used to explore the properties of voltage-driven dissipative magnetofluids inside a periodic cylinder with circular cross section. The trial functions are orthonormal eigenfunctions of the curl (Chandrasekhar-Kendall functions). Transitions are observed from axisymmetric resistive equilibria without flow to helically deformed laminar states with flow, and between pairs of helical laminar states with different pairs of poloidal and toroidal m and n numbers. States of minimum energy-dissipation rate seem to be preferred. At high values of the pinch ratio, fully developed magnetohydrodynamic turbulence is observed.

- [3] Ideal and Resistive MHD Equilibria and States of Minimum Dissipation
X. Shan, H. Chen, and D. Montgomery, in *Nonlinear and Relativistic Effects in Plasmas*, ed. by V. Stefan; American Institute of Physics, New York, 1992; pp. 168-197.

Ideal magnetohydrodynamic equilibria have been the organizing conceptual framework for interpreting fusion confinement experiments. In hydrodynamics, bounded, ideal equilibria are equally plentiful, but the only ones even approximately attainable in the laboratory are those which lie close to equilibria with small but non-zero dissipation coefficients. If the same criteria are demanded in MHD, the range of possibilities is greatly restricted. If the additional common requirements of axisymmetry and zero equilibrium flow velocity are demanded, we are left with a nearly empty set of solutions, and not very interesting ones at that. For example, in cylindrical periodic geometry with a dielectric-coated conducting liner, the sole possibility seems to be the uniform-current-density profile, if uniform resistivity is assumed. It has begun to seem likely that interesting MHD equilibria may all contain flows: and not just small-scale, turbulent, "dynamo" velocities, but organized flows that can affect the current distribution over its channel. These states seem to be approximatable as states of minimum energy dissipation rate. Experimental searches for flow velocities, on MHD plasmas cool enough to permit internal probes, seem to be indicated. Issues of MHD equilibrium, at a level more sophisticated than ideal, axisymmetric assumptions permit, need to

be re-opened. "At present, the most important and revealing experiments that can be done seem to be numerical ones.

- [4] Nonideal, Helical, Vortical Magnetohydrodynamic Steady States
A.Z. Agim and D. Montgomery, *Plasma Phys. & Contr. Fusion*, **33**, 881-902 (1991).

The helically-deformed profiles of driven, dissipative magnetohydrodynamic equilibria (Montgomery et al., 1989, Phys. Rev. A 40, 1515) are constructed through second order in helical amplitude. The resultant plasma configurations are presented in terms of contour plots of magnetic flux function, pressure, current flux function and the mass flux function, along with the stability boundary at which they are expected to appear. For the Wisconsin Phaedrus-T Tokamak, plasma profiles with significant $m = 3$, $n = 1$ perturbation seem feasible; for these, the plasma pressure peaks off-axis. For the smaller aspect ratio case, the configuration with $m = 1$, $n = 1$ is thought to be relevant to the density perturbation observed in JET after a pellet injection.

- [5] Effects of Uniform Rotation on Helically - Deformed, Resistive, Magnetohydrodynamic Equilibria
D. Montgomery, H. Chen, and X. Shan, *Plasma Phys. & Contr. Fusion*, **33**, 1871-1875 (1991).

Previous calculations and computations of resistive magnetohydrodynamic equilibria have revealed helically-deformed steady states with flow, just above critical current thresholds. The poloidal flow pattern consists of paired macroscopic vortices, which effectively transport fluid elements from the center of the plasma column to the perimeter and back. The appearance of the helically-deformed states with vortices can be suppressed by a rigid poloidal rotation, entirely within the magnetohydrodynamic framework. Velocity shear is not required.

- [6] Relaxation in Two Dimensions and the "sinh - Poisson" Equation
D. Montgomery, W.H. Matthaeus, W.T. Stribling, D. Martinez and S. Oughton, *Phys. Fluids*, **A4**, 3-6 (1992).

Long-time states of a turbulent, decaying, two-dimensional, Navier-Stokes flow are shown numerically to relax toward maximum-entropy configurations, as defined by the "sinh-Poisson" equation. The large-scale Reynolds number is about 14,000, the spatial

resolution is $(512)^2$, the boundary conditions are spatially periodic, and the evolution takes place over nearly 400 large-scale eddy-turnover times.

- [7] "Reduced" Magnetohydrodynamics and Minimum Dissipation Rates
D. Montgomery, *Phys. Fluids*, **B4**, 292-293 (1992).

It is demonstrated that all solutions of the equations of "reduced" magnetohydrodynamics approach a uniform-current, zero-flow state for long times, given a constant wall electric field, uniform scalar viscosity and resistivity, and uniform mass density. This state is the state of minimum energy dissipation rate for these boundary conditions. No steady-state turbulence is possible. The result contrasts sharply with results for full three-dimensional magnetohydrodynamics before the reduction occurs.

- [8] On Driven, Dissipative, Energy Conserving Magnetohydrodynamic Equilibria
M.L. Goodman, accepted for publication in *J. Plasma Phys.* (1992).

A cylindrically symmetric, electrically driven, dissipative, energy conserving magnetohydrodynamic equilibrium model is considered. The high magnetic field Braginskii electron electrical resistivity (η) parallel to a constant axial magnetic field B , and ion thermal conductivity (κ) perpendicular to B are included in an energy equation and in Ohm's law. The expressions for η and κ depend on number density and temperature which are functions of radius that are obtained as part of the equilibrium solution. The model has plasma confining solutions, by which is meant a solution characterized by the separation of the plasma into two regions separated by a relatively thin transition region that is an internal boundary layer across which temperature and current density vary rapidly. The inner region has a temperature, pressure, and current density which are much larger than in the outer region. The number density and thermal conductivity attain their minimum values in the transition region. The model has an intrinsic value of β , about 6.6%, which must be exceeded in order that a plasma confining solution exist. The model has an intrinsic length scale which, for plasma confining solutions, is a measure of the thickness of the transition region separating the inner and outer regions of plasma. A larger class of transport coefficients is modeled by artificially changing η and κ by changing the constant coefficient, η_0 and κ_0 , that occur in their

expressions. Increasing κ_0 transforms a state that does not exhibit confinement into one that exhibits confinement, improves the confinement in a state that already exhibits confinement, and leads to an increase in κ in the confined region of plasma. The improvement in confinement consists of a decrease in the thickness of the transition region. Decreasing η_0 , subject to certain constraints, also transforms a state that does not exhibit confinement into one that exhibits confinement, improves the confinement in a state that already exhibits confinement, and leads to a decrease in η in the confined region of plasma. Increasing η_0 up to a critical point increases the current, temperature, and volume of the confined region of plasma, and causes the thickness of the transition region to increase. If η_0 is increased beyond the critical point, a plasma confining state cannot exist. In all cases it is found that an increase in κ and a decrease in η in the confined region of plasma are associated with an improvement in the confinement properties of the equilibrium state. If the pressure and temperature are given on the cylinder wall the equilibrium bifurcates when the electric field decreases below a critical value. The equilibrium can bifurcate into a state that exhibits confinement, and a state that does not exhibit confinement.

- [9] Galerkin Approximation for Dissipative Magnetohydrodynamics
H. Chen, X. Shan, and D. Montgomery, *Phys. Rev.*, **A42**, 6158-6165 (1990).

A Galerkin approximation scheme is proposed for voltage-driven, dissipative magnetohydrodynamics. The trial functions are exact eigenfunctions of the linearized continuum equations and represent helical deformations of the axisymmetric, zero-flow, driven steady state. In this paper, the lowest nontrivial truncation is explored: One axisymmetric trial function and one helical trial function each for the magnetic and velocity fields. The system resembles the Lorenz approximation to Benard convection, but in the region of believed applicability its dynamical behavior is rather different, including relaxation to a helically deformed state similar to those that have emerged in the much higher resolution computations of Dahlburg et al. [*Phys. Rev. Lett.* 57, 428 (1986); *J. Plasma Phys.* 37, 299 (1987); 40, 39 (1988)]. In the region of applicability, the dynamical behavior is to seek out the steady state of lowest energy dissipation rate.

- [10] Magnetohydrodynamic Stability Thresholds as a Function of Hartmann Number and Pinch Ratio
D. Montgomery, Plasma Phys. & Contr. Fusion, 34, 1157-1162 (1992).

The linear instabilities of an incompressible, uniform-density magnetofluid are considered in the periodic straight cylinder approximation. Spatially-dependent resistivity and viscosity profiles are regarded as fixed, but their magnitudes and the magnitudes of the currents driven in the plasma are not. It is shown that the stability boundary is determined by only two dimensionless numbers; the Hartmann number and the axisymmetric, zero-flow pinch ratio, which is inversely proportional to the safety factor at the wall. The result is analogous to the well known result from the theory of hydrodynamic shear flows that the Reynolds number governs the onset of hydrodynamic activity.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

DATE
FILMED

3 / 23 / 93