DOE progress report 1993

MEDIUM ENERGY MEASUREMENTS OF N-N PARAMETERS

Progress Report

April 1, 1992 - March 31, 1993

David Ambrose, Mark Bachman,
Patrick Coffey, George Glass, Bernard Jobst,
Kok Heong McNaughton, Chau Nguyen,
Peter J. Riley

Department of Physics,
University of Texas at Austin,
Austin, Texas, 78712-1081

Principal Investigator,

Peter J. Riley

December, 1992

MASTER

RECEIVED

FEB 11 1993

OSTI

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Submitted to the United States Department of Energy

Under Grant No. DE-FG05-88ER40446

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE OF CONTENTS

I. OVERVIEW.....	1
II. PROGRESS ON RESEARCH PROJECTS	5
A. LAMPF E876 and E1092	5
LAMPF E876, Spin Transfer Measurements in np Elastic Scattering	5
LAMPF E1072, P-P Elastic Differential Cross-Section Measurements	7
References.....	14
B. TRIUMF E372, Single pion production in np scattering.....	15
Experimental layout.....	16
Tracking and Event Reconstruction	18
Initial Results	20
Comparisons to Theory.....	22
Continuing Analysis	24
References.....	25
C. LAMPF E1097, Single pion production in np scattering.....	27
E1097 Overview.....	27
E1097 Detector System.....	27
E1097 Phase 0 Preparation (Spring, 1992)	28
E1097 Phase 0 Results (Summer, 1992).....	31
E1097 Phase 1 Preparation (Fall, 1992).....	38
D. BNL E871, A New Search for Rare Kaon Decays	43
BNL E871 Overview	43
$K_L \rightarrow \mu \mu$	45
$K_L \rightarrow ee$	46
Results of E791.....	46
Overview of The New Experiment, E871.....	46
A Lead Glass Array for E871.....	50
E791 Experience and Potential Improvements.....	50
Mechanical Assembly.....	51
Phototubes and Cables.....	52
Gain Monitoring and Calibration	52
BNL Experiment 888	52
References.....	53
E. STAR, Solenoidal Detector at RHIC.....	55
III. PERSONNEL WORKING ON PROJECT	57
IV. PUBLICATIONS	59
V. TITLE PAGES OF PUBLICATIONS.....	61

MEDIUM ENERGY MEASUREMENTS OF N-N PARAMETERS

I. OVERVIEW

This progress report requests continued support for the Medium-Energy nucleon-nucleon (N-N) physics program of the University of Texas at Austin, the major part of which, up to now, involved research done at the Nucleon Physics Laboratory (NPL) at the Los Alamos Meson Physics Facility (LAMPF). Other research has been and will be continued to be carried out at BNL. We are also analyzing data from a TRIUMF experiment in which we participated, but we have no further plans for experimental work at TRIUMF. Our Progress Report will describe work done during 1992, and will focus on problems that we face with existing experiments, or on experiments in which we hope to participate in the coming year.

Broadly speaking, the aim of the N-N experimental program has been the determination of the nucleon-nucleon amplitudes at medium energies. The required data include both elastic and inelastic experiments, and in addition the measurement of polarization and polarization transfer parameters. The experiments at BNL are not nucleon-nucleon experiments, and we will discuss them later.

Our recent LAMPF nucleon-nucleon measurements have consisted of the following three measurements:

(1) Spin transfer measurements in np elastic scattering (E876). This experiment was carried out in two phases. Phase 1, completed during the summer of 1991, consisted of the measurement of the four spin-transfer observables K_{LL} , K_{SS} , K_{SL} and K_{LS} at 485, 635, and 788 MeV. The data and their analyses, are described in two recent Physical Review C publications[1, 2]. In Phase 2, completed during the summer of 1992, the observables A_N , P , and K_{NN} were measured at the same three energies. Analyses of these data are now complete and manuscripts are being written for publication. Both Phase I and Phase II data are proving invaluable in fixing the isospin 0 phase shifts and amplitudes.

In addition, our measurements of the neutron beam polarization for E876 uncovered a significant disagreement with our previous measurements of $K_{LL}(d)$ at 800 MeV, suggesting that our previous LAMPF np elastic analyzing power data should be renormalized. Consequently, we carried out new measurements of the spin-transfer parameter K_{LL} at 0° which clarified the normalization discrepancy. These

measurements, which are in good agreement with theoretical predictions, have also been published[3].

(2) p-p elastic absolute cross section measurements (E1072), with the goal of measuring the p-p differential cross section at LAMPF energies to an absolute accuracy of 1%. The experimental measurements were carried out during the summer of 1988. Analysis has required careful evaluation of detector efficiencies, backgrounds, and a thorough study of beam attenuation in the target and surrounding materials. Data analyses are now completed.

(3) n-p inelastic polarization measurements (E1097), "Single Pion Production in np Scattering," designed to measure the cross section and analyzing powers for the reaction $np \rightarrow pp\pi^-$. Crucial to this experiment is a cylindrical drift chamber which will surround the target, and much of our current efforts have been involved with the testing and development of this chamber. We carried out preliminary testing of our chamber and its associated electronics at LAMPF during the summer of 1991, and completed this work during 1992. Phase I running, which will employ an unpolarized liquid hydrogen target, was expected to be carried out during the summer of 1993, and phase II running, using a polarized (frozen spin) target, in 1994.

E1097 was reviewed "in depth" by the LAMPF PAC on August 18, 1992, and received, as it had before, an A⁻ priority. The subcommittee report read, in part, *"The subcommittee is of the opinion that successful measurements of the differential cross section would contribute significantly to the understanding of the $I = 0$ NN interaction and of pion production processes... All efforts should be directed to the cross-section measurements, but there is a risk that they will not be attained by the end of 1993. ...Recommendation: 500 hours of 800-MeV beam in BR with A⁻ priority."*

Subsequently, Peter Barnes, the Director of LAMPF, in reviewing the PAC recommendation, made the following comments *"I concur with the Subcommittee's recommendation of 500 hours of 800 MeV beam with A⁻ priority... I also note that substantial MP-Division resources will be required for implement this experiment. I urge you to explore ways of augmenting the manpower on the experiment. I request a written update in early November, 1992, addressing the manpower question ... At that time I will decide if further MP-Division resources can be committed to your experiment."*

We met with Cyrus Hoffman, LAMPF Associate Director for Research, in early November. By then the Ron Ransome, Rutgers, and Charles Davis, University of Manitoba, had made strong commitments to E1097, so that we felt we most certainly had addressed the manpower question. We had carried out comprehensive GEANT simulations, which indicated that we could measure successfully the $np \rightarrow pp\pi^-$ differential cross section measurements, and finally, we had shown that we could

successfully use multiplexing to reduce FERA and cable costs without seriously compromising the experiment measurements. However, Peter Barnes' decision, based by Cyrus Hoffman's report, was negative, and read in part: *"...E-1097 requires a significant investment of LAMPF funds, for electronics, cryogenics, and mechanical assembly, that simply are not available this year... As a result of this decision, no further LAMPF resources will be spent on E-1097. In fact, some of the FERA electronics previously bought for E-1097 may well be needed elsewhere in the LAMPF program..."*

Essentially, after three years development work, we now have a working detector but no experiment, and must conclude that, in spite of all our work, E-1097 is no longer a viable project. Consequently, David Ambrose and Patrick Coffey, both of whom expected to carry out their Ph. D. dissertation research on this experiment, will no longer be able to do so.

During the past three years we have been involved in a neutron-proton inelastic scattering experiment at TRIUMF (E372) "Single Pion Production in np Scattering," designed, as was LAMPF experiment 1097, to measure the cross section and analyzing powers for the reaction $np \rightarrow pp\pi^-$. This experiment measures the same quantities as E1097, Phase I, proposed at the higher LAMPF energies. Our data taking runs for E372 were carried out during September, 1990, and February, 1991. The data are now being analyzed here at the University of Texas by Mark Bachman, whose Ph. D. dissertation will be based on the data and its analyses.

We are also participating in an experiment at Brookhaven National Laboratory, "Study of Very Rare K_L^0 Decays," (BNL 871). An engineering run has been approved for 1993, with data runs to follow in 1994 and 1995. Fabrication and testing of detector components are in progress.

Recently, we have joined a large collaborative group working on the RHIC experiment STAR (Solenoidal Detector at RHIC) at BNL. Our role in this project, which for the next several years will emphasize the design and fabrication of a very large, complex collider detector, is not yet fully defined. The STAR detector is presently conceived of as a combination of a silicon vertex tracker (SVT), a Time Projection chamber (TPC), a set of trigger scintillators, and time of flight (TOF) counters. There are also an external TPC (XTPC) and some MWPCs. In addition, an electromagnetic calorimeter has been proposed, which would not only allow the detection of gammas, but would allow for some important measurements of spin dependence at high P_T (>10 GeV/c) with polarized colliding protons that relate to the gluon spin structure functions. Both George Glass and Kok Heong McNaughton are expected to participate in the design, development, and fabrication of this calorimeter.

In the following section we describe in more detail recent progress on the three LAMPF experiments, E876, E1097, and E1234, the one TRIUMF experiment, E372, and on the BNL experiments, E871 and STAR.

References

1. M.W. McNaughton *et al.*, Phys. Rev. **C44**, 2267 (1991).
2. M.W. McNaughton *et al.*, Phys. Rev. **C45**, 2564 (1992).
3. K.H. McNaughton *et al.*, Phys. Rev. **C46**, 47 (1992).

II. PROGRESS ON RESEARCH PROJECTS

A. LAMPF E876 and E1092

LAMPF E876, Spin Transfer Measurements in np Elastic Scattering

A major goal at LAMPF has been to determine the nucleon-nucleon isospin-zero ($NN\ I=0$) phase shifts and amplitudes in the energy range 400–800 MeV. During the summer of 1990 we measured four isospin-transfer observables which, when combined with previous spin dependent data near 800 MeV, led to stable phase shift solutions[1]. In 1991 we obtained similar data at 485 and 635 MeV. These new experimental data allowed improvements in the phase shift analyses similar to that provided by the earlier 788 MeV data[2]. As recently as 1988 Arndt[3] had stated that above 500 MeV the $NN\ I=0$ phase shifts were “essentially undefined”. Bugg[4] pointed out that the spin transfer observables K_{LL} , K_{SS} , and K_{NN} , in addition to the cross section and analyzing power, were needed to establish stable, well determined solutions, allowing the determination of the five complex scattering amplitudes. Since our experimental method measures K_{LS} simultaneously with K_{LL} and K_{SL} simultaneously with K_{SS} , we measured these four observables. This over determination also allows some cross-checking of possible systematic errors.

Nucleon-nucleon data bases and phase shift analyses are maintained by Arndt[5], Bugg[4], Bystricky, Lehar and Leluc[6], and by Hoshizaki[7,8]. With the inclusion of our new MeV data, the phase shift analyses show “an immense improvement” and are well determined with well behaved error matrices for the first time. Correlations in the error matrix have almost disappeared.

The E876 apparatus, shown in figure 1, is essentially the same as had been used in previous LAMPF experiments[9-11]. Briefly, polarized protons are focused onto a liquid deuterium target and neutrons, polarized by spin transfer, are collimated at zero degrees and directed onto a 15 liter liquid hydrogen target (the largest ever used at LAMPF). Scattered neutrons are detected in a large high-efficiency neutron detector. Recoil protons are detected in the Scylla spectrometer, which serves a dual purpose: 1) to measure the momentum and 2) to precess the recoil protons from L-spin to N-spin. Finally, the proton spin is analyzed in the Janus polarimeter.

Figure 1: E876 detector system

During the summer of 1992 we used a different E876 configuration from that of the previous two years. The magnet Vartola replaced Scylla to allow for a horizontal bend instead of a vertical bend of the particles to measure K_{NN} , A_N and by extension, P for the reaction $np \rightarrow pn$.

Data were taken at 33 angles at 2 different energies: 788 MeV and 635 MeV, and at 30 angles at 485 MeV. Analyses of these data are now complete and the final results of K_{NN} and A_N are shown in Figures 2 through 7. Final calculations of the polarization parameter P are in progress. The analyses of the A_N data led to a proposal for a new experiment to measure A_N at 4 different energies (*i.e.*, at all 3 energies above plus 725 MeV) in the forward neutron-angle regions (less than 60° c.m.). This proposal is being submitted to the PAC (proposal # 1293).

Our 1992 data [A_N , K_{NN} , and P], like our spin transfer data of the past two years, have about an order of magnitude more statistical weight than the best previous data,

and are in fact the most precise np data in the world. This high precision was made possible by the high intensity beam (up to 1 μ A average) from the optically pumped polarized source OPPIS. To summarize, near 500 MeV the data agree well with the previous data[12] and with recent analyses by Arndt[13] and Bugg[14]. Above 500 MeV these data are unique and complete the set of spin-dependent parameters needed to determine the scattering amplitudes.

The mixing parameter ϵ_1 determines the tensor force and the structure of the deuteron, and is strongly constrained by these new data. After including these data the uncertainty in ϵ_1 decreased by a factor of two. Arndt's and Bugg's solutions for ϵ_1 now agree within 0.5 degrees.

Our new data have also allowed us to resolve significant discrepancies between previous existing np data sets. The older TRIUMF data[12] disagree with more recent TRIUMF data[15], apparently as a result of an error in the angle calibration of the older data. Our new LAMPF new data (figures 1-3) agree with the calibration of the more recent TRIUMF data within 0.1 degrees. The more recent TRIUMF data also disagree with the normalization of the older LAMPF data[16]. Our new LAMPF measurements, combined with last year's double scattering experiment, add considerable weight to the conclusion that the older LAMPF data were incorrectly normalized.

With the new data in place the isospin-0 phase shift solutions are becoming consistent for the first time. Arndt's single energy phase shift analysis (November 1992) now agrees to 1 degree with Bugg's. We expect to resolve the few remaining discrepancies in the coming year to complete the determination of the $I = 0$ nucleon-nucleon phase shifts and amplitudes up to 800 MeV.

LAMPF E1072, P-P Elastic Differential Cross-Section Measurements

E1072 measured pp cross-sections at 5 different energies (492, 575, 642, 728 and 793 MeV) to an accuracy never before attempted. The analysis are being finalized and a manuscript is being written. Figures 7-11 shows the most current cross-section results plotted against Bugg's and Arndt's fits. Figure 12 shows our cross-section measurements at 90° cm angle with world data for a range of energies.

The 0.5 percent precision of these data is comparable to that of the total cross section data and so determines the total inelastic cross section to this precision. They also pin down the absolute normalization of the energy dependent data from Saclay[17] and the forward angle data from LAMPF[18]. When these data are finalized this will complete the determination of the isospin-1 phase shifts and amplitudes to 800 MeV.

Figure 1: Analysing Power at 485 MeV

Figure 2: Analysing Power at 635 MeV

Figure 3: Analysing Power at 788 MeV

Figure 4: K_{nn} at 485

Figure 5: K_{NN} at 635

Figure 6: K_{NN} at 788

Figure 7: pp cross-section at 492 MeV

Figure 8: pp cross-section at 575 MeV

Figure 9: pp cross-section at 642 MeV

Figure 10: pp cross-section at 728 MeV

Figure 11: pp cross-section at 793 MeV

Figure 12: pp cross-section at 90° cm with Arndt's FA92 phase-shift

References

1. M. W. McNaughton, *et al.*, Phys. Rev. C44, 2267, (1991)1.
2. K. H. McNaughton, *et al.*, Phys. Rev. C46, 47, (1992).
3. R. A. Arndt, *et al.*, Phys. Rev. D35, 128, (1987).
4. D. V. Bugg, Phys. Rev. C41, 2708, (1990).
5. R. A. Arndt, Phys. Rev. D37, 2665, (1988).
6. J. Bystricky, C. Leluc, and F. Lehar, J. Phys. 48, 199, (1987).
7. N. Hoshizaki, Prog. Theor. Phys. 60, 1796 (1978)
8. N. Hoshizaki *et al.*, Proc. of Workshop on expts by KEK Pol. Prot. and Electron Beams (KEK, Ibaraki, Japan, Oct. 1988).
9. R. Ransome *et al.*, NIM 201, 309, (1982).
10. M. W. McNaughton *et al.*, Phys. Rev. C41, 2809, (1990).
11. C. L. Hollas *et al.*, Phys. Rev. C30, 1251, (1984).
12. D. Axen *et al.*, Phys. Rev. C21, 988 (1980).
13. R.A. Arndt *et al.*, Phys. Rev. D45, 3995 (1992).
14. D.V. Bugg and R.A. Bryan, Nucl. Phys. A540, 449 (1992).
15. Bandyopadhyay *et al.*, Phys. Rev. C40, 2684 (1980).
16. C.R. Newsom *et al.*, Phys. Rev. C39, 965 (1989).
17. M. Garcon *et al.*, Nucl. Phys. A445, 669 (1985).
18. G.W. Hoffmann *et al.*, Phys. Rev. C37, 397 (1988).

B. TRIUMF E372, Single pion production in np scattering

The purpose of TRIUMF experiment E372 was to measure the differential cross section and analyzing power of the reaction $np \rightarrow pp\pi^-$ at 440 MeV. This reaction is useful to study because it helps shed light on the role of non-resonant and $I=0$ channels in the process of pion production in nucleon-nucleon systems. The N-N system has two isospin channels which may contribute to the dynamics of particle production. Our current understanding of pion production relies extensively on the dominant $I=1$ channel where phase shift information is more available and the delta (Δ) isobar dominates over other processes. It is experimentally impossible to create an N-N system in a pure $I=0$ state, so we are left to deduce the role of $I=0$ from the np reaction which is an equal mixture of $I=0$ and $I=1$ states.

Various models have been proposed for the simultaneous description of elastic and inelastic nucleon-nucleon scattering in the intermediate energy region (300–1000 MeV) [1–6]. Most are coupled-channel models with long range pion exchange, and the short range described by heavier meson exchange with appropriate vertex functions parametrized by cutoffs. These models predict analyzing powers which compare at best only “fairly” with observed data for reactions such as $pp \rightarrow np\pi^+$. Dubach, Kloeet and Silbar (DKS) have published predictions of both pp and np pion production which have varying levels of agreement with data. One of the limitations of their code is that it includes only πN p-wave pion production. Fits to experimental data for other than p-wave production are unavailable, and thus there is no clear indication as to which πN channels beyond the P_{33} and P_{11} would be most significant. The problem of knowing which approximations are important in treating the $NN\pi$ interaction, especially in the off-shell cases, remains unsolved. The need for detailed studies of the effects of “minor” amplitudes, especially the s-wave πN interactions, has been emphasized by difficulties in calculations of pion absorption on $I=1$ and $I=0$ nucleon pairs in S- and P-shell nuclei [7–9]. The $np \rightarrow pp\pi^-$ reaction provides an excellent opportunity for resolving the problem of the “minor” amplitudes in the $NN \rightarrow NN\pi$ system, as well as providing direction to the importance of the $I=0$ contribution to pion production.

Very little data exists for the $np \rightarrow pp\pi^-$ reaction. Initial measurements suffered from poor statistics or limited phase-space [10–12]. Until recently, there were no measurements of spin observables for this reaction, due to the difficulty in obtaining a high intensity polarized neutron beam. Terrien, et al. from Saturne [13], are publishing analyzing powers as a function of pion angle and p-p invariant mass at beam energies of 572, 784, and 1012 MeV. Our measurements at 440 MeV add to these data providing the beginning of a useful set of observables which reflect on the $I=0$ contribution to pion production in the nucleon-nucleon system. In addition to these inclusive measurements (which represent integrals over two phase-space variables), we

are extracting analyzing powers for exclusive points in phase-space. Furthermore, we are extracting the first exclusive differential cross section for this reaction.

Experimental layout

Our experiment took useful data during two periods in September 1990 and March 1991. During the first period we were able to write about 36 million events to tape; during the second period, we wrote about 50 million. The data included calibration runs, target empty runs, and neutron polarization states of N, S and L. The degree of neutron polarization for the runs was typically 27%, which was less than hoped for, but adequate to do the measurement. We accepted a neutron beam flux of about 4×10^4 neutrons/cm²/sec which amounted to approximately 1 million neutrons per second incident on our liquid hydrogen target.

Figure 1 shows the layout of the beam line; figure 2 shows the main components of our detector. The proton beam was bunched, chopped, accelerated to 457 MeV, then extracted. During this process of bunching and chopping, known as the MERO tune, over 90% of the beam was discarded, leaving the remaining beam with an extremely tight time structure. Every 43 nanoseconds, the protons came in a pulse less than 500 picoseconds wide which gave us a very clean neutron signal and established the neutron energy to within 13 MeV. The polarization of these protons was typically 40% with orientation normal to the cyclotron plane. A superconducting solenoid (JANIS) precessed the proton polarization to sideways just before the beam collided with an LD₂ production target. Neutrons scattered at 9° by the reaction ${}^2\text{H}(p,n)2p$ retain approximately -71% of the sideways component of proton polarization. The 9° neutrons were collimated by a large steel and cement collimator then passed through two precession magnets to produce polarized neutrons with spins oriented normal, sideways or longitudinal (N, S, L). The neutron beam spot at our target was approximately 6 x 6 cm². We used two proton polarimeters in the proton beam and two neutron polarimeters in the neutron beam to monitor the beam polarization.

Figure 1: Beam line at TRIUMF for E372

Figure 2: Experimental apparatus for TRIUMF for E372

Our experimental apparatus consisted of a large tracking detector and scintillator hodoscope which sat behind a liquid hydrogen target. The target was a 5 mil mylar flask, 5 cm in diameter, 16 cm in height, which sat in a vacuum vessel. Upstream of the target was a scintillator which served as a charged particle veto. Immediately downstream of the target was a thin, low mass, delay line drift chamber to ensure that charged particles came from the LH_2 target and not from the small 1/16 in. scintillator which followed, and which served as the "start" for time-of-flight measurements. Downstream of these was a twelve-plane multiwire drift chamber for tracking the charged particles. After this, 120 cm downstream from the target, sat a curved array of 18 scintillator bars, each $200 \times 3 \times 10.2 \text{ cm}^3$, which provided the trigger as well as time-of-flight information. We also used multiwire proportional chambers on either side of the target to detect wide scattering pions.

Pulses from two scintillator bars in coincidence with the start scintillator and in anti coincidence with the veto served as our trigger. The reaction $np \rightarrow pp\pi^-$ is the only np reaction with two or more charged particles in the final state, and the kinematics at 438 MeV constrain the protons to fall within the geometry defined by our scintillators, so this (in principle) is a clean signal. We also included special triggers for calibration purposes: events from small (1 cm^2) axis defining scintillators, events from "button" scintillators at precisely known locations, and a fraction (1%) of single track events.

Tracking and Event Reconstruction

Using the trajectories of the charged particles, we were able to reconstruct the vertices and kinematics of the reactions. The tracking relied extensively on the over-constraining nature of the 12-plane drift chamber which had four planes in the x -coordinate, four in the y -coordinate, and four planes at 45° to both x and y . Although the tracks were over-determined in principle, the large cell size (2 inches), inefficiencies and cross talk made tracking a formidable computational task. In fact, tracking proved to be the single most difficult hurdle in the analysis of the data. During the summer of 1991, we developed a tracking code which could track the events with about 85%–90% efficiency. Tracking and subsequent vertex reconstruction (shown in figure 3) was surprisingly good, but revealed that many of the events came from background sources, most notably the target flask walls, the delay line chamber and the “start” scintillator. Requiring good vertex reconstruction and vertices which fall within the target volume cuts out almost 90% of the data.

Figure 3: Vertex reconstruction for E372. This example shows the top view for a target empty run.

The kinematics of each event could be reconstructed using the times-of-flight and directions of the measured tracks. This information alone, however, was not sufficient to adequately resolve the kinematics so dE/dx information from the scintillator ADCs was used as well. A kinematic χ^2 was defined using these measurements and minimized to resolve the kinematics for each event. Poor χ^2 s correlated well to vertices in the walls and scintillator; good χ^2 s correlated to the interior of the target vessel as one would expect. The result of the χ^2 and vertex cut is a clean signal. During the runs, we took almost 40% of our data with the target empty. In light of our ability to extract a clean signal, it is clear that this fraction was far too high.

The tracking and subsequent event reconstruction required extensive calibrations. We spent much of the summer of 1992 improving these calibrations, especially for the ADCs of the scintillator bars. A parametrized fit to a function resembling the Bethe–

Bloch expression proved to be the best way of extracting the energy deposited in the bars. The nature of the χ^2 minimization routine corrected for the energy lost by the particles in the LH_2 .

Figure 4: ADC calibrations for E372. Solid lines represent expected ΔE in bars calculated from the particle velocity. Scattered points are the actual ΔE as measured.

Due to the sheer magnitude of computations necessary to perform the analysis of E372 data, we could not do analysis in Austin. We use a Vaxstation 3100 for most of our numerical applications, but analysis on this machine proved to be far too slow. We attempted for some time to convert the analysis code from VAX Fortran to Fortran-77 for use on UNIX based machines such as an IBM RISC 6000. This proved to be difficult at best since most of the codes and data structures had been highly optimized for VAX/VMS. Furthermore, the data files from TRIUMF had been written by a VAX/VMS machine in binary format. The "hi-lo" ordering of bytes in binary files written by VAX/VMS is opposite that of UNIX, so all of our data files would have to be converted. After an initial attempt to overcome these problems, we finally decided that it would be more profitable to seek faster VAX/VMS machines elsewhere. We eventually were able to use LAMPF computers in Los Alamos. The computers there were not necessarily faster than our own, but since there were many available, we could run analysis jobs on more than one machine at a time, effectively doubling or tripling our analysis rate. Furthermore, the LAMPF computing facilities allow

temporary storage of large data files which is necessary for doing our analysis, since we not only read large data files, but write them as well. To make optimal use of LAMPF computers, we constructed the analysis to do event "reduction" and convert the raw data into files containing meaningful kinematic information (actually the "reduced" files are larger than the originals). That way, we could bin the data in Austin (which takes relatively little CPU time) and leave the CPU intensive work of kinematic reduction for the LAMPF computers. All of the LAMPF analysis was done remotely from Austin through the computer networks.

In addition to fast (or plentiful) CPU time, the analysis of our data required large amounts of disk space. Each run takes up about 120 Mbytes of space (we had written to 8mm tape which has huge storage capacity), and the "reduced" file takes up a little more. To accommodate the reduced files from LAMPF as they were analyzed, we stored them on a ~1 Gbyte disk drive in Austin, then wrote them to 8mm tapes when the disk was filled. We used this drive exclusively for storing the incoming reduced data (then writing to 8mm "summary" tapes). We used a second drive to hold temporary files for binning (and rebinning) the data without stopping or interrupting the analysis.

During this time, the Manitoba group began shipping their copies of the data tapes to LAMPF so we could copy the tapes and analyze all the E372 data at LAMPF. This actually took much more time than we expected since Manitoba was hesitant about shipping the only copy of the data through the mail. It was done in stages, each shipment sent only after we could confirm the safe arrival of the last. We copied the tapes over the summer and into the fall of 1992.

Initial Results

Initial results of E372 analysis are presented in figure 5. We extracted 370,000 events (from about 16 million) which came from target full runs and which satisfied our vertex and kinematic χ^2 cuts. These were collected into bins of Θ , Φ , and M_{pp} , where Θ and Φ are the polar angles of the pion in the CMS, and M_{pp} is the invariant mass of the p-p system. The neutron beam polarization orientation was flipped between "normal" and "reverse" every two minutes. This information and the azimuthal distribution allowed us to calculate the analyzing power as a function of Θ and M_{pp} , since the dependence of the asymmetry with the azimuthal angle Φ is well known. A_x was determined to be zero as expected; A_y is shown in the diagram. These results are preliminary and intended only to show the general features of the data. The absolute normalization for the analyzing power may require a correction of 15% or more.

Figure 5: Preliminary results for E372. Results of Terrien, *et al.* are shown for comparison.

The most glaring feature of our preliminary results is our apparent disagreement with the published results of Terrien, *et al.* at 572 MeV. Terrien's measurements show the analyzing power to be almost completely antisymmetric for the invariant mass cut around $M_{\pi\pi}=1888$ MeV, whereas ours are almost perfectly symmetric about 90° at all mass cuts. However, this may not be as strange as it first appears. Our energy of 438 MeV and Terrien's energy of 572 are not really very close (the difference is 134 MeV). In the CMS system, for a conjugate particle of 1888 MeV, our pion may have only 54 MeV and the number of angular momentum states allowed in the final state is restricted accordingly. The same pion in the 572 MeV reaction can have a kinetic energy of 106 MeV, (almost twice as much) so more states are allowed, including perhaps, interference terms which show up as antisymmetry. Higher $M_{\pi\pi}$ cuts put the pion at lower relative energy; for these, Terrien's data show no antisymmetry.

Comparisons to Theory

We can compare our results with predictions by W. M. Kloet and E. Loman and predictions by J. Dubach, W. Kloet and R. Silbar. The model of Dubach, Kloet and Silbar (DKS) is an extension of the model by Arron, Amado and Young[14] applied to the $NN\pi$ final state. It preserves both two- and three-body unitarity and allows two-body interactions in the P_{11} and P_{33} πN subchannels[15]. The model of Kloet and Loman is a coupled isobar model where the short-range interaction is described with a boundary condition on the wave function at 0.7 fm as dictated by the internal quark degrees of freedom[16].

R. Silbar[17] and W. M. Kloet[18] have provided us with T-matrix files from their models for 440 MeV. To convert these files into observables, we used the code written by Dubach, Kloet and Silbar called PIPROD85 which accepts Silbar's or Kloet's T-matrices as input and performs the necessary angular momentum algebra. The resulting output are observables for specific points in phase-space. Since PIPROD85 accepts kinematic input in lab coordinates (which happen to be inconvenient for us), and since PIPROD85 does only exclusive predictions, we modified the code to work as a subroutine in two different integration programs.

The first integration method we used was a Monte Carlo technique. This technique was outlined in last year's progress report; the basic idea is as follows. Points are selected from phase-space at random (with uniform probability) then converted to lab coordinates. Event is input to PIPROD85 which determines the differential cross-section ($d\sigma$) and analyzing power (A) for that point. A probability is determined by

$$P(event) = d\sigma(1+AP),$$

where **P** is the beam polarization and is assumed to be 100% normal. Each event *may* be written to disk, with **P** the probability that the event will be written. The Metropolis algorithm[19] is used to create the sample.

After creating a Monte Carlo data set, we were then able to bin the simulated data in the same way we bin the real data for comparison. This gave us the distinct advantage of having great flexibility over our what prediction we wanted to see and allowing direct comparisons between theory and experiment. The disadvantage was that it takes a great deal of computer time to create the data set, and we had to run the code on many computers. This technique was only used for the case where we integrated over four kinematic variables, as Monte Carlo is not really efficient for lower dimensional integrations. Mark Bachman presented this technique as part of a talk concerning E372 at the N-N Workshop at Los Alamos in February 1992.

Figure 6: Monte Carlo integration of DKS predictions for $np \rightarrow pp\pi^-$ at 477 MeV. Integration was over all variables except the pion CMS angle.

The second technique we did was to select points in Gottfried-Jackson coordinates (or the variation of interest to us where the pion coordinates are defined in the CMS frame and the p-p system is defined as another reference frame), then do the direct integration

$$\bar{A} = \int A \frac{d\sigma}{d\Omega} d\Omega / \int \frac{d\sigma}{d\Omega} d\Omega.$$

To check that this version of PIPROD85 still produced correct results, we compared exclusive predictions provided by Wim Kloet to predictions using the new code. They agreed. Using this variation of PIPROD85 we generated predictions with $M_{pp}=1900$ MeV and for the same pion CMS angles as for our data, then integrated over the two remaining variables. The resulting (integrated) predictions are shown in figure 7. It is clear that Kloet's predictions do not agree with our data at 440 MeV, although curiously, they seem to agree with the 572 MeV data of Terrien *et al.* We will be communicating this result to Wim Kloet soon.

Figure 7: Initial predictions by Wim Kloet for $np \rightarrow pp\pi^-$ at 440 MeV. $M_{pp} = 1900$ MeV.

Continuing Analysis

To improve our determination of analyzing power, especially when looking for exclusive measurements where we expect poorer statistics, we intend to use a maximum likelihood approach. This technique attempts to fit a function to the scattering distribution without binning and so makes maximum use of the available information. The form of this function (for beam polarization normal) is

$$f(\Phi) = \eta N_0 (1 + AP \cos \Phi),$$

where A is the analyzing power, P is the beam polarization and η is an efficiency which depends on Φ . The fit maximizes the likelihood function

$$L(A, \Phi) = \log(f(\Phi_1)) + \log(f(\Phi_2)) + \dots + \log(f(\Phi_n)),$$

and so is a function of the analyzing power A , and all the data points in a given sample.

In addition to analyzing power, we are extracting the differential cross section. Doing this requires that we calculate the detector efficiency over all phase-space. This is a difficult procedure since the detector efficiency (which depends on both hardware and software efficiency) has a complicated dependence which is not at all obvious. We are proceeding with careful Monte Carlo studies to try and establish the relative efficiency.

Mark Bachman is writing his dissertation on the work he has done for TRIUMF E372. He expects to defend this dissertation in the spring of 1993.

References

1. W. M. Kloet and R. R. Silbar, Nucl. Phys. **A338**, 281 (1980).
2. W. M. Kloet and R. R. Silbar, Phys. Rev. Lett. **45**, 970 (1980).
3. T.-S. Lee, Phys. Rev. Lett. **50**, 1571 (1983).
4. E. van Faassen and J. A. Tjon, Phys. Rev. C **30**, 285 (1984).
5. F. Sammarucca and T. Mizutani, Phys. Rev. C **41**, 2286 (1990).
6. Ch. Elster, K. Holinde, D. Schutte, and R. Machleidt, Phys. Rev. C **38**, 1828 (1988).
7. M. A. Moinester et al., Phys. Rev. Lett. **52**, 1203 (1984).
8. H. Yokota et al., Phys. Rev. Lett. **57**, 8067 (1986).
9. O. V. Maxwell and C. Y. Cheung, Nucl. Phys. **A454**, 606 (1986).
10. R. Handler et al., Phys. Rev. B **138**, 1230 (1965).
11. M. Kleinschmidt et al., Zeit. fur. Phys. A **298**, 253 (1980).
12. W. Thomas et al., Phys. Rev. D **24**, 1736 (1981).
13. Y. Terrien et al., To be published (1992).
14. R. Aaron, R. D. Amado and J.E. Young, Phys. Rev. **174** (1968) 2022.
15. J. Dubach, W. M. Kloet and R. Silbar, Nuclear Physics **A466**, 573 (1987).
16. W. M. Kloet and E. L. Loman, Phys. Rev. C **43**, 1575 (1991).
17. R. R. Silbar, Private communication
18. Wim Kloet, Private communication.
19. Metropolis et al., Jou. of Chem. Phys. **21**, 1087 (1953).

C. LAMPF E1097, Single pion production in np scattering

E1097 Overview

In recent years, there has been a major effort in both the experimental and theoretical investigation of the coupled NN-NN π problem. This set of reactions is one of the simplest inelastic processes available for study. It sheds light on the NN and N π interactions and is key to understanding pion production in more complex systems. There are four independent channels available in the NN-NN π reaction. These channels can be expressed in terms of the total isospin of the initial (I) and final (I') state nucleons (I,I'): (1,0), (1,1), (0,1), (0,0). The dominant channel for pion production is through the (1,0) resonance, since the famous Δ^{++} (I=3/2, P=3/2) can proceed through this channel. The role of the non-resonant amplitudes, particularly the (0,1) channel, remains elusive. The reaction $np \rightarrow pp\pi^-$ may proceed through the (1,1) and (0,1) channels, which avoid the Δ^{++} , making it an ideal reaction for studying the non-resonant contributions to pion production. The reaction is experimentally accessible, since all final state particles are charged, allowing efficient and precise determination of all outgoing trajectories.

LAMPF Experiment 1097 will measure the differential cross section, σ , and the spin observables A_{NO} , A_{LO} , A_{SO} , A_{OL} , A_{SL} , A_{NL} , and A_{LL} for the single pion production reaction $np \rightarrow pp\pi^-$ at neutron beam energies in the range 500–800 MeV. These data should allow a first order partial wave analysis of the $I = 0$ inelastic amplitudes. E1097 will run in two separate phases. Phase I, planned for 1993, will use a polarized neutron beam and a liquid hydrogen target; Phase II, expected to run in 1994, will use a polarized frozen spin hydrogen target to enable the spin correlation parameters to be measured. In August, 1992, 500 hours of beam at 800 MeV were approved for Phase I of the experiment. The Phase I measurements are the same as those of TRIUMF E372 at lower energy (438 MeV), and many of the E372 collaborators are also participating in E1097. In addition, the Saturne group under Y. Terrien, also studying this reaction, have measured asymmetries at several neutron beam energies between 572 and 1134 MeV. The Saturne group used a polarized neutron beam, but not a polarized target; it will be of interest to compare their measurements, as well as those of TRIUMF E372, with Phase I of E1097. We hope that the data from the three experiments will have a major impact on our understanding of the NN-NN π system at medium energies.

E1097 Detector System

Figure 1 shows the primary component of the E1097 detector apparatus, the cylindrical wire chamber, with the LH2 target at the center. The chamber, about 1 meter long with a 30 cm radius, has a vertical acceptance of $\pm 60^\circ$ and a horizontal acceptance of up to $\pm 180^\circ$, and should detect all three final state particles for more than 50% of phase space. Each of the 448 sense wires of the detector, divided into 8 cylindrical planes, measures a particle track's perpendicular distance from the wire via drift time, while

determining the distance of the track along the wire through charge division. Thus, we must read the charge from each end of the wire with ADC's, while timing these pulses relative to the start of the event with a TDC.

Figure 1: E1097 Experimental Detector

The second element of the detector system consists of a thin, curved scintillator (S1), mounted between the target and wire chamber, and a large array of 21 vertical scintillator bars, placed behind the chamber, used for the event trigger. Additionally, we will measure the phototube signals from the scintillator array with ADC's to provide particle identification. For Phase 0, we use a smaller, 5-bar array in conjunction with S1 to provide a simple event trigger.

E1097 Phase 0 Preparation (Spring, 1992)

Phase 0, the testing and development phase of the experiment, consisted of four major goals. First, we tested the overall performance and stability of the chamber, specifically its ability to hold high voltage over an extended period of time without breakdown, which had proven troublesome the previous year. Second, we measured the horizontal

and vertical chamber resolutions, to see if they satisfied the proposed resolutions needed for Phases 1 and 2. Third, we determined the wire hit efficiency of the chamber, and attempted to maximize this value. The value of the efficiency is not only crucial to obtaining good data, but must be known precisely in order to extract a differential cross section. Finally, we tested the overall tracking ability of the chamber directly with cosmic and beam particle data, and are in the process of extrapolating the total chamber efficiency and resolution further through Monte Carlo analysis.

Figure 2: Phase 0 Parasitic Operation

To accomplish these goals, we ran the chamber in parasitic mode, behind the existing E876 apparatus (see Figure 2), where a horizontal flux of recoil protons from the E876 LH2 target could pass through the chamber. Eleven modules of sense wires (16 wires each) were added to the eight from the previous year, so that the entire downstream half of the chamber and four upstream modules could be used. The upstream modules, centered between the Phase 2 target insert holes in the chamber walls, allowed the tracking of particles through the entire chamber, as well as testing with a Sr beta source (which cannot penetrate the walls). For the majority of the summer, the number of FERA units (see below) available limited us to 10 chamber modules, which we called the "Base 10" configuration and arranged in a way to provide tracking of recoil protons entering and leaving the chamber as well as scattered protons from a block of CH_2 placed in the target area. Additionally, thin horizontal scintillators, placed before and

after the chamber and vertically adjustable, provided for testing of the chamber performance along the length of the wires.

The major task needing completion prior to Phase 0 operation involved the replacement of the existing wire chamber electronics, which had proven unsatisfactory in previous runs, with that of the LAMPF MEGA collaboration. These electronics consist of preamps (PA) mounted on the chamber, which are connected to a module of 16 sense wires with short leads (see Figure 3). A preamp mount (PM) holds the PA close to the appropriate module, minimizing the length of the sense wire leads, and provides it with power. The PA amplifies the chamber pulses, and sends these signals along a 15 ft. coaxial flat cable to the shaping amps (SA), housed in powered crates. Here, the SA broadens the pulses and sends the passive addition of top and bottom sense wire signals to the discriminator board (DB), which forms the TDC stop signal. These functions take place in the experimental area, and the two ADC pulses and TDC stop signal from each wire are carried to the counting house by 250 ft twisted pair flat cable.

Figure 3: Wire Chamber Electronics

We perform the ADC and TDC operations with the LeCroy FERA (Fast Encoding and Readout ADC) system. Each sense wire module uses two 16-channel FERA for the top and bottom ADC's and a TFC (Time to FERA Converter) / FERA combination for the TDC. The TFC feeds the FERA an amount of charge, in the form of a square pulse, linearly proportional to the arrival time of the DB stop signal. A FERA DRV (Driver) provides the FERA modules with gate information, and transfers the ADC output to a memory module (MEM), read by the computer between beam bunches. A single CAMAC high powered crate holds the DRV, MEM, and 18 FERA, bypassing the problem of branching FERA crates found previously.

To link the MEGA electronics with our FERA system, we found that a receiver board (RB) is needed, which performs 3 basic functions. First, the RB reverses the polarity of the SA output signals before input to the FERA. Next, a capacitor between the FERA signal and ground inputs stops the injected pedestal charge from bleeding to ground. Lastly, a transformer decouples the FERA from the 250' flat cable, to prevent an observed smearing of the pedestal. These necessities had been discovered independently by the LAMPF NMS group, which uses the same flat cable and FERA system and had manufactured 16-channel RB's for that purpose. We were able to borrow some of these boards in time for Phase 0 operation.

Therefore, we were able to integrate the MEGA electronics into our existing system without direct modification of the MEGA boards. In so doing, we also discovered a major source of electronics noise in the chamber high voltage system, which produced an oscillation on the sense wires detectable as a significant broadening of the ADC pedestal. By simply adding a 1 Megaohm resistor in series with the HV wires, we eliminated this ripple, improving our charge resolution by a factor of ten. The charge resolution of a single wire, derived from the ADC pedestal width, was then found to be less than 1%.

E1097 Phase 0 Results (Summer, 1992)

In June and July, we ran the detector with both cosmic and beam particles to accomplish the Phase 0 goals. Testing the overall chamber stability, our first goal, we maintained the "Base 10" modules, over a third of the chamber, for the duration of the summer. We learned to diagnose and fix chamber voltage problems quickly and efficiently. These problems usually involved the breakdown of the plastic inserts holding the HV wires at either end, which we solved easily by simply replacing the wire.

To determine the vertical and horizontal resolutions of the chamber, we invented a series of calibrations performed on each wire individually, since every wire's electronics have slightly different properties (amplifier gain, wire resistance, discriminator level, etc.). For the horizontal component (see Figure 4), measured via drift time, we define not a drift distance but a drift angle, due to the cylindrical

geometry of the chamber (which causes wire cells on separate layers to have slightly different size). This value defines the angle between the sense wire and the intersection of the particle track with the sense wire cylindrical plane, so that, dividing by the total wire cell angle, we define a drift angle ratio ranging from 0 to 1 that is the same for all wires. We can calibrate each wire individually if we assume that the distribution of drift ratios (and therefore the flux of particles) is uniform over the sense wire cell. We then integrate the TDC values to fill a uniform distribution. To test this calibration, we define a drift residual using the cylindrical angle of the particle track. For a layer pair of hits, the sum of the two drift ratios, plus the track dependent angle ($\Delta\Phi$), should equal the total angle between the sense wires. Dividing by twice the cell angle, and subtracting 1, we arrive at a residual peaked at 0, with a spread proportional to the drift resolution. Using such a method (see Figure 5), we found a resolution near 10% of the total drift cell (or about 1mm in distance), satisfying the original proposal's requirements but still in need of refinement. Figure 5 also shows an example event, with the circles showing the hit wire positions, and the crosses denoting the hits with added drift angles, which align well to reveal a single track through the center of the chamber.

Figure 4: Horizontal (Drift) position Geometry

Figure 5: Drift Calibration and Resolution

The vertical component (Z-position) for track hits is determined through charge division of the top and bottom ADC signals from a given wire, which we can derive rather simply assuming that the resistive wire and associated electronics behave as a DC circuit:

$$Z = Z_0 \frac{Q_t - Q_b}{Q_t + Q_b} \rightarrow Z_0 = \frac{L}{2} + \frac{R_p}{\lambda}.$$

Here, Q_t and Q_b are the top and bottom charges, and the parameter Z_0 is a function of the wire length (L), the preamp resistance (R_p), and the wire resistance per length (λ). The resolution (ΔZ) is parabolic in Z-position (with a minimum at $Z = 0$) and linear in the charge resolution, or ratio of charge error to total charge, ($\Delta Q/Q$):

$$\Delta Z = \sqrt{2(Z_0^2 + Z^2)} \frac{\Delta Q}{Q}.$$

Using this formula for Z , a first order calibration, which measures and subtracts the individual ADC pedestal values from each wire, correctly aligns the Z-position spectra for the wires over the entire range of the chamber, and produces a resolution under 2% (see Figure 6). We calculate this Z-resolution by plotting the residual deviations of individual wire hit values from the track Z-positions. A look at the ADC spectra shows why the resolution cannot improve further; the ADC pedestal width, while clearly separated from the hit spectra, produces a charge resolution greater than 1%. Since the single-wire charge resolution is less than 1% (as stated above), this pedestal

broadening clearly reveals the effect of crosstalk between the wires, which we must remove in order to achieve the desired resolution.

Figure 6: First Order Vertical (Z-position) Calibration

Inspection of this crosstalk shows that it actually occurs from two independent processes. The first source, a true crosstalk between wires within a module (since these channels share a common ground throughout the electronics), results in a positive shift of pedestal values if a given wire within the module receives a large negative pulse. This effect, however, is not consistent enough to be removed. The second source of the pedestal broadening, we believe, results from a feedback between the top and bottom amplifiers of the electronics through the sense wires, which we can observe with an oscilloscope as a 50 MHz ripple, and produces an oscillation in the pedestal value of the ADC's. A strong correlation in this oscillation exists between the top amplifiers, which are in turn anti-correlated with the bottom amps. Because of this correlation, we can determine the phase of the oscillation for a given event, and subtract it from the ADC values, to reduce the overall charge resolution to the desired 1%.

We perform a final calibration to take care of asymmetries between the top and bottom electronics of an individual wire. If we assume that this asymmetry results from differences in the preamp input impedances (which may be as large as 10%), then the charge division equation becomes:

$$Z = \frac{Z_t Q_t - Z_b Q_b}{Q_t + Q_b} \rightarrow Z_t = \frac{L}{2} + \frac{R_t}{\lambda}, \text{ etc.}$$

where Z_t and Z_b are the top and bottom preamp resistances. Using an iterative procedure, the Z parameters of a wire are adjusted relative to each other to bring the

wire's hits in line with groups of other hits from the same track. When all calibrations are performed, the Z-resolution can be reduced to under 1% to achieve the proposal's requirement (Figure 7).

Figure 7: Higher Order Z-position Calibrations

Investigation of the chamber efficiency, our third Phase 0 goal, showed two factors of importance. The first factor results from the proximity of the wires to the chamber carbon walls, which are held at ground and therefore alter the HV field, lowering the wire efficiency as expected. Fortunately, this effect occurs only for the inner and outer sense wire planes, and can be compensated for, somewhat, by raising the HV level in these planes. In general, the inner planes have efficiencies around 97–99%, while the outer planes range from 80–90%. Second, the Z-position of the hits along the wire also affects the efficiency; since the top and bottom chamber plates are, like the walls, held at ground, the HV field and therefore the efficiency should deteriorate towards the chamber ends. However, we found the average efficiency fairly uniform along the wire, up to about 8 cm from the chamber endplates.

The final goal of the Phase 0 runs was to test the tracking ability of the chamber. The majority of events recorded came from single recoil protons or cosmic particles traversing the entire chamber. The tracking software, working on or off-line, proved successful in reconstructing these events (see Figure 8). For a few runs, when the beam intensity was high, we observed elastic scattering events from a CH₂ target placed in the chamber center, distinguishable by a 90° separation of the final state particles (Figure 9). We also recorded a candidate inelastic event (3-particle final state), but these scattering events were rare due to the limited acceptance region of the “Base-10” modules.

Figure 8: Beam and Cosmic Particle Events

Figure 9: Elastic and Inelastic Scattering Events

We presented these results to the LAMPF PAC on August 19, 1992, which recommended 500 hours of 800-MeV beam for 1993 with A- priority. The committee, concentrating on the progress and prospects for Phase 1, expressed the opinion that a 10–20% measurement of the differential cross section would “contribute significantly to the understanding of the $I = 0$ NN interaction and of pion production processes”. The PAC also stressed the need for more manpower to achieve this goal.

E1097 Phase 1 Preparation (Fall, 1992)

We are currently involved in several projects in preparation for Phase 1 operation in 1993. Of primary importance, due to budgetary constraints, has been the implementation of multiplexing, which reduces the number of FERA and 250' flat cable needed, two of the major costs associated with the chamber, by sharing these items between modules. We perform this multiplexing most easily by making a passive flat cable connection between modules after the SA, since we do not need to save on MEGA electronics. If each sense wire retains its own TDC stop signal (and hence its identity), we can then multiplex groups of wires in which only one hit is predicted. This situation occurs in the pion region of phasespace, beyond a scattering angle of about 60° (totaling $2/3$ of the chamber). The obvious effects of this multiplexing are a reduction in the signal size and an adding of the signal noise, which hurts the resolution. The multiplexed modules can be run at a higher voltage to minimize the signal loss, so that the total loss of resolution is only about 0.2%.

Another factor affecting the budgetary limitations concerns the redesign of the scintillator array. This revision uses existing scintillator bars and phototubes similar to those used in Phase 0 to create a 21-bar array. We have sacrificed the ability to measure particle flight times (proposed originally) and will rely instead on particle identification through analysis of the phototube signal charge, measured with FERA ADC's. We can therefore move the scintillator bars closer to the chamber to increase their acceptance. At this stage, the designs for the array and stand (and also the new wire chamber stand) have been completed (Figure 10), and the stand is under construction.

Next, we have finalized the designs for the double level trigger system electronics (see Figure 11). The first level, formed by the scintillator array, signals the start of the event, and sets the gates for the FERA electronics. This trigger involves a coincidence between S1 and a programmable multiplicity of bar hits in the scintillator array (probably $N \geq 2$) combined with a rudimentary pattern logic within the array. This pattern design satisfies conservation of momentum while minimizing the occurrence of triggering on neutron conversion in the bars (which can fire neighboring scintillators). Since certain background events (for instance, $nn \rightarrow np\pi^-$) can mimic a 2-bar trigger, a second level trigger uses multiplicity units to count the number of chamber wire hits in order to determine 3-track events (which can only occur for $np \rightarrow pp\pi^-$). Failure to

satisfy this condition stops the event and resets the electronics within a few μsec , which reduces the dead-time involved in reading out the FERA data.

Figure 10: Phase 1 Scintillator and Chamber Stands

Finally, to determine the detector resolution and efficiency as a function of phasespace, we must input the single-wire values found above to a Monte Carlo simulation linked to the current tracking and reconstruction software. These calculations will be used to derive the differential cross section, now a major motivation for Phase 1, as emphasized by the PAC report.

Figure 11: First and Second Level Triggers

For this purpose, we have implemented the CERN library code GEANT, which generates particle 4-momenta for events, including the physical processes of energy loss, multiple scattering, and particle decays. The existing tracking program then converts the simulated 4-momenta to detector hits, incorporating the efficiencies and resolutions measured in Phase 0. Lastly, we perform the tracking and event reconstruction on the simulated hits to deduce the tracking efficiency and resolution as a function of phasespace. Figure 12 shows a typical $np \rightarrow pp\pi^-$ event, generated by GEANT and propagated through the detector apparatus, where the pion has decayed prior to entering the chamber.

Figure 12: Monte Carlo Simulation Event

D. BNL E871, A New Search for Rare Kaon Decays

BNL E871 Overview

The kaon system is one of the best laboratories for the study of conservation laws in particle physics and in particular for the search for processes forbidden in the Standard Model. The experimental absence of processes which violate separate lepton number (i.e., electron, muon, or tau lepton number), also called lepton flavor or lepton family number, has led to its conservation being formalized in the Standard Model. The underlying basis for such a conservation law remains mysterious. In a gauge theory, a globally conserved quantity is associated with the existence of a massless boson. In the case of charge conservation, the associated boson is the photon. Separate lepton number conservation has no associated massless boson and is therefore, according to current theoretical thinking, unlikely to be exact. It is more likely that lepton flavor transitions are highly suppressed in some dynamical process which lies outside the Standard Model. This is the general motivation for searches for separate lepton number violating processes, such as $\mu \rightarrow e\gamma$, $\mu \rightarrow eee$, $\mu^- A \rightarrow e^- A$, (muon-electron conversion in the field of a nucleus), and in the kaon system, the decays $K_L \rightarrow \mu e$ and $K^+ \rightarrow \pi^+ \mu e$.

Even as the Standard Model continues to pass every test, the theory is generally considered to be incomplete. The reasons for this view can be traced to several problems: (1) there are nineteen free parameters in the theory, (2) there is no explanation of why the quarks and leptons appear in three generations, or why there should not be more, (3) there is no explanation of how the quarks and leptons are related, (4) there is a technical difficulty known as the "gauge hierarchy problem," which refers to the need for unnatural fine-tuning of parameters, (5) there is no unification of the strong and electroweak interactions (and gravity is not in the picture at all). Attempts to repair these difficulties have led to a number of proposed extensions to the Standard Model, including supersymmetry[1], technicolor[2], right-left symmetry[3], horizontal gauge symmetry[4,5], compositeness[6], and some superstring inspired models[7]. Typically, lepton flavor violation occurs in these extensions. The process $K_L \rightarrow \mu e$ is one of the most sensitive probes for lepton flavor violation.

The decay $K_L \rightarrow \mu e$ or other separate lepton number violating processes, can occur in the Standard Model if the neutrino masses are not zero or degenerate. In a gauge theory such as the Weinberg-Salam electroweak model, the eigenstates of the weak interaction need not be mass eigenstates. As discussed earlier, the quark weak eigenstates differ from the mass eigenstates and are connected through the unitary CKM mixing matrix. The same sort of mixing among the leptons would be expected[8] were it not for the fact that the neutrinos are massless or very nearly so. However, existing limits on neutrino masses and couplings imply[9] $B(K_L \rightarrow \mu e) < 10^{-25}$, which is unobservable.

Consequently, observation of $K_L \rightarrow \mu e$ depends on new physics outside the Standard Model.

In considering a search for lepton flavor violation in $K_L \rightarrow \mu e$, it is reasonable to ask to what extent other measurements probe the same possible new interactions. Related processes include: (1) $\mu \rightarrow e \gamma$, (2) $\mu \rightarrow e e e$, (3) $\mu A \rightarrow e A$ (muon conversion on a nucleus), (4) Δm_K (the K_L - K_S mass difference) and (5) the decay $K^+ \rightarrow \pi^+ \mu e$. Processes such as $\mu \rightarrow e \gamma$ and $\mu \rightarrow e e e$ only involve leptons (no quarks) in the initial or final state, so that any interaction depending upon the participation of quarks (e.g., generation number conserving interactions, composite models) are not probed at all. While the process $\mu A \rightarrow e A$ is a very powerful probe in many models, it also does not involve a generation-change in the quark sector, so that an important class of interactions is not tested. The small value of Δm_K (3.5×10^{-15} GeV) is a serious constraint in a broad range of models. However, a sensitivity of 10^{-12} for $K_L \rightarrow \mu e$ is beginning to be competitive with Δm_K , as discussed below. Also, leptoquark exchange, since it cannot induce a $K^0 - \bar{K}^0$ transition, is not constrained at all by Δm_K . Finally, the decay $K^+ \rightarrow \pi^+ \mu e$, while suffering from smaller phase space than $K_L \rightarrow \mu e$ and the shorter K^+ lifetime, is ultimately complimentary to $K_L \rightarrow \mu e$ rather than competitive with it, since the former probes a scalar or vector interaction and the latter a pseudoscalar or axial-vector interaction.

In order to make this discussion more quantitative, we will use the often cited model of Cahn and Harari[5] for generation-changing gauge bosons to illustrate the relative power and present status of limits from the various lepton flavor violating processes. Table 1 lists the best present limit for each process and the mass scale probed by that limit in the Cahn and Harari model. The bottom row shows the mass reach of the new experiment (E871).

Table 1: Mass reach of separate lepton number violating processes in the Cahn and Harari model. The β 's are generation mixing angles and are unconstrained.

Process and Present Value	Mass Reach
$\Delta m_K (3.5 \times 10^{-15} \text{ GeV})$	400 TeV $\sin \beta_D$
$\text{Br}(\mu \rightarrow e \gamma) < 1.7 \times 10^{-11} [10]$	20 TeV $ \sin \beta_L \cos \beta_L ^{1/2}$
$\text{Br}(\mu \rightarrow e e e) < 1 \times 10^{-12} [11]$	80 TeV $ \sin \beta_L \cos \beta_L ^{1/2}$
$\Gamma(\mu A \rightarrow e A) / \Gamma(\mu A \rightarrow \nu A) < 4.6 \times 10^{-12} [12]$	190 TeV $ \sin \beta_{LU} - \sin \beta_{LU} ^{1/2}$
$\text{Br}(K^+ \rightarrow \pi^+ e^- \mu^+) < 2.1 \times 10^{-10} [13]$	40 TeV
$\text{Br}(K_L \rightarrow \mu e) < 8.4 \times 10^{-11} [14]$	70 TeV
$\text{Br}(K_L \rightarrow \mu e) < 2.0 \times 10^{-12} \text{ (E871 planned)}$	180 TeV

$K_L \rightarrow \mu \mu$

The decay $K_L \rightarrow \mu \mu$ played a major role in the development of the Standard Model, as its small value led to the GIM mechanism which invoked the existence of a fourth quark, charm. The decay rate is dominated by the 2-photon intermediate state, as seen from the fact that the branching ratio is consistent with the absorptive (imaginary) amplitude ($K_L \rightarrow \gamma \gamma \rightarrow \mu \mu$) alone, a value usually referred to as the unitarity bound. The standard value of the unitarity bound[15] is given by

$$\Gamma(K_L \rightarrow \mu \mu)_{abs} = 1.2 \times 10^{-5} \Gamma(K_L \rightarrow \gamma \gamma).$$

The Particle Data Group[16] lists $(5.70 \pm 0.27) \times 10^{-4}$ as the branching ratio for $K_L \rightarrow \gamma \gamma$. Therefore, the unitarity bound is about 6.8×10^{-9} . (There is a theoretical uncertainty at the 10 to 20% level, on top of the experimental uncertainty of $\text{Br}(K_L \rightarrow \gamma \gamma)$, so this is not a rigid bound.) Recent measurements of $K_L \rightarrow \mu \mu$, which are dominated by E791, are close to this value, so that the dispersive amplitude is evidently small.

Interpretation of the $K_L \rightarrow \mu \mu$ branching ratio is made difficult by the long-distance nature of the dominant 2- γ contribution. Short-distance contributions to $K_L \rightarrow \mu \mu$ have been evaluated[17] and the general consequence of a small dispersive amplitude for $K_L \rightarrow \mu \mu$ is to limit the magnitude of the real part of the CKM product $V_{ts}^* V_{td}$ as a function of the top mass. Some recent theoretical analyses[18] use the recent results from BNL and CERN on the $K_L \rightarrow e e \gamma$ form factor in estimating the long distance part of the $K_L \rightarrow \mu \mu$ dispersive amplitude. They then derive constraints on the short distance part, using the $K_L \rightarrow \mu \mu$ branching ratio, which in turn constrains CKM parameters. One conclusion of this analysis is that the branching ratio for $K^+ \rightarrow \pi^+ \nu \bar{\nu}$ is probably smaller than previously expected.

$K_L \rightarrow ee$

The decay $K_L \rightarrow ee$ also receives a contribution from the $2\text{-}\gamma$ process that dominates $K_L \rightarrow \mu\mu$. However, this contribution is helicity suppressed, so that the expected branching ratio is much smaller than $K_L \rightarrow \mu\mu$. The suppression, however, is not simply a factor of (m_e^2/m_μ^2) , which would reduce it to the 2×10^{-13} level. Instead, there is a logarithmic singularity as $m_l \rightarrow 0$ in the total electrodynamic cross section for $\gamma\gamma \rightarrow l^+l^-$ which modifies the naive factor by more than an order of magnitude. Consequently, it is expected[15] that $K_L \rightarrow ee$ occurs at a branching ratio of about 3×10^{-12} . The range between this value and the $K_L \rightarrow \mu\mu$ level is a window for observing a new flavor changing neutral current interaction, such as the pseudoscalar leptoquarks that appear in extended technicolor theories[19]. Of course, part of this window has already been closed, as discussed in the next section.

Results of E791

Three experiments have been active over the last few years in the search for the rare modes $K_L \rightarrow \mu e$, $K_L \rightarrow \mu\mu$, and $K_L \rightarrow ee$. They were BNL E780, KEK E137 (in Japan), and BNL E791.

AGS Experiment 791 took data in three consecutive years of running—1988, 1989 and 1990. No $K_L \rightarrow \mu e$ or $K_L \rightarrow ee$ candidates were found. Final results have not been published yet, but preliminary values of final results are given in Table 2. The table also includes, for comparison, the final results from both AGS E780 and KEK E137. As is clear from the table, E791 has dominated this research. The new experiment, E871, to be carried out by substantially the same collaboration, will improve upon E791 by more than an order of magnitude.

Table 2: Results from recent $K_L \rightarrow \mu e$ searches.

	BNL780[20]	KEK137[21]	BNL791
$K_L \rightarrow \mu e$ limit	1.9×10^{-9}	9.4×10^{-11}	3.3×10^{-11}
$K_L \rightarrow ee$ limit	1.2×10^{-9}	1.6×10^{-10}	4.1×10^{-11}
$K_L \rightarrow \mu\mu$ sample	~ 8 events	178 ± 13 events	717 ± 27 events

Overview of The New Experiment, E871

E871 will improve upon E791 by more than an order of magnitude in sensitivity. We will re-use a significant part of the existing E791 detector, thereby moderating the cost and time scale. The major data-taking will be during the 1994 and 1995 SEB periods. We expect to be able to set a limit on $K_L \rightarrow \mu e$ at or below 2×10^{-12} , if no signal is observed. At this sensitivity, we would observe a few $K_L \rightarrow ee$ events.

Figure 1: Plan view of the E871 detector.

Our approach to the new experiment depends on detector modifications which will provide significantly increased acceptance and the ability to run with a factor of about four more beam (over E791). In addition, improvements to several parts of the experiment will decrease losses due to inefficiencies and deadtimes. The key features of the new experiment are:

- The decay volume will be lengthened from 8 meters to 11 meters and detector apertures will be increased by using the existing 96D40 magnet as the upstream spectrometer magnet. (A large aperture second dipole will be used; it appears that this magnet will be a 100D36 which will be obtained from Fermilab.) These changes account for more than a factor of two improvement in acceptance.
- A beam stop, or plug, will be inserted in the 96D40 to stop the neutral beam. Extensive beam tests carried out during the 1991 AGS SEB running demonstrated that our beam plug design is viable. The plug will reduce rates in detector elements downstream of the 96D40, by eliminating K_L decays inside the spectrometer, beam scraping on detector frames, neutron interactions in the gas, etc. The net effect will be clearer particle identification. Also, the enormous reduction in dose to the lead glass (to levels well below E791, even at the increased Booster intensity) will make it possible to re-use that system.
- The two dipoles will be operated with opposite fields, but tuned to provide a net p_T -kick of about 220 MeV, which will make daughters from 2-body K_L decays approximately parallel to the beam direction. (This parallelism will be used in forming the Level 1 trigger.) The events that will be accepted are the so-called "in-bends", in which both charged particles bend toward the beam in the upstream dipole. The "out-bends", which first bend away from the beam, will not be accepted in this magnet configuration.
- New tracking chambers will be built. The four upstream-most tracking stations will be straws with wire spacing approximately 1/2 of E791 (i.e., 0.5 cm diameter cells). We will have three, rather than two, planes of x measuring wires in each chamber; E791 experience shows that this added redundancy in the bend plane of the magnets will provide improved background rejection. The smaller cell size will reduce the occupancy of each channel by a factor of four. An additional reduction of approximately a factor of two will be obtained by using a faster gas than in E791.
- The fifth and sixth chambers, those downstream of both magnets, are sufficiently distant from the plug that rate is not a problem. For these chambers, a 1 cm pitch should be acceptable and conventional drift chambers following closely the E791 design will be built.
- A new Cerenkov counter, with improved optical properties, will be built.

- The E791 lead glass array will be reused, but reconfigured and substantially upgraded.
- A new muon trigger hodoscope will be built. The muon momentum threshold in E871 will be 1.0 GeV (rather than 1.6 GeV in E791), thereby increasing acceptance. The existing E791 muon hodoscope counters will be re-used in several locations throughout the muon steel and muon rangefinder to improve timing resolution for muons.
- The muon rangefinder will be reconfigured to increase the momentum range it covers and improve the resolution of the range measurement by approximately a factor of two over E791.
- The Level 3 trigger will be upgraded by replacing the farm of eight SLAC 3081/E processors with eight (or more if appropriate) modern RISC processors, resulting in an approximate order of magnitude increase in on-line computing power.

The result of these changes will be an experiment with larger acceptance and a capability to run with much higher beam intensity with improved background rejection compared to E791. The layout of the new experiment is shown in Figure 1.

We have adopted a method of estimating E871 sensitivity that we believe is both realistic and reliable. We have scaled from a well-understood data set in E791. Details of this estimate can be found in the E871 proposal and are not reproduced here. Since the modes $K_L \rightarrow e\bar{e}$, $K_L \rightarrow \mu\mu$, and $K_L \rightarrow \mu e$ have different acceptances and are affected differently by changes in particle identification efficiencies, they are listed separately in the Table 3. The 1989 E791 sensitivities for observing a single event of the types $K_L \rightarrow \mu e$ and $K_L \rightarrow e\bar{e}$, and the actual number of $K_L \rightarrow \mu\mu$ events observed, are given. The table also shows the full improvement factor for each mode and the expected sensitivities for the proposed experiment.

Table 3: Sensitivity of the new experiment.

	E791 1989 Data	Improvement	E871
$K_L \rightarrow \mu e$ sensitivity (single event)	3.6×10^{-11}	43	8.4×10^{-13}
$K_L \rightarrow ee$ sensitivity (single event)	4.8×10^{-11}	56	8.5×10^{-13}
$K_L \rightarrow \mu\mu$ observed	284 events	34.5	9800 events

A Lead Glass Array for E871

The principle function of the lead glass is electron identification. The E791 lead glass system suffered significant radiation damage during both the 1989 and 1990 runs. However, the considerably reduced dose that will be sustained in E871 with the plug in place makes it possible to reuse this system in E871 (after some annealing with UV lights). Reuse of the existing E791 lead glass in E871 has several advantages associated with it. These include: (1) the cost of upgrading the system is considerably less than any replacement system that one could contemplate, (2) experience with the E791 system suggests what improvements are needed, and (3) a large software base already exists for calibration, monitoring, etc.

E791 Experience and Potential Improvements

The experience of building and maintaining the E791 lead glass system, as well as calibrating it and using it for particle identification, has provided several lessons on how to do things better. The single largest improvement we plan is eliminating photomultiplier tubes (PMT's) whose performance has proved marginal. Other improvements include building new PMT bases (E791 bases were recycled from previous experiments). The new bases will provide more reliable performance and will probably be designed with additional amplified output (approximate gain of 30) to provide signals for muons in the glass. This will provide a considerably enhanced ability to calibrate the system (muons were effectively inaccessible in E791 for calibration purposes). We also plan improvements to the laser-based flasher system and the light-tight, temperature-controlled enclosure which houses the array. The combined effect of these changes will be to improve the function and make maintenance of this system significantly easier. Figure 2 shows the ratio of electromagnetic shower energy as measured by the lead glass to track momentum as measured by the magnetic spectrometer for Cerenkov tagged electrons for two regions of the E791 lead glass array. One region has several of the marginal PMTs, which will be replaced, while the other region has mostly good PMTs. The potential improvement from the PMT upgrade is obviously significant.

Figure 2: E/p for electrons in the E791 lead glass for two regions; the left plot shows the performance of marginal PMTs, which will be replaced in E871.

Mechanical Assembly

The E871 lead glass array needs to cover a horizontal x width of 186 cm and a vertical y height of 174 cm, both centered on the beam centerline. The array itself should be somewhat larger to account for electromagnetic shower spreading. By reconfiguring the system to include 222 blocks (40 front converter blocks and 182 back absorber blocks) an area of 200 cm x 180 cm can be covered by the converters and 210 cm x 195 cm by the back; since showers spread mainly in the back, the larger size makes sense.

While we do not expect significant radiation damage in E871, the option of UV curing between E871 runs should be maintained. This will have significant implications for the design of the new frame and enclosure. In E791, the converter layers and back block layers were separately movable on rails, to allow access to regions of the array for the UV curing process.

Phototubes and Cables

Phototubes in the E791 lead glass were obtained at no cost from numerous sources (i.e., defunct detectors). This was probably a false economy, since a price was paid in both degradation of the performance of the system and the difficulty of maintaining it. To cover the area described above with good PMT's, it will be necessary to purchase about 50 5 inch PMTs. We also believe the converter layer PMTs should be replaced. An adequate number of cables (signal, delay, and HV) exist from E791 for us to implement our new plan.

Gain Monitoring and Calibration

The custom E791 ADC's are sensitive to charge up to about 90 pC. The calibration of a typical block in E791 was 12 pC/GeV. A muon deposits the equivalent of about 80 MeV in the converters and double that in back blocks. Therefore, muon pulse height is only about 1 pC in converters. Muon peaks are not well measured under these circumstances. In the future, we believe the common approach of two ranges (a LOW range and a HI range) should be used. This would allow us to place the muon peak in the center of the ADC range. This information would be very helpful in establishing a starting point for a more sophisticated calibration algorithm, which relies on momentum tagged electrons from the decay $K_L \rightarrow \pi e \nu$. We expect to design the amplifier into the new bases for the lead glass PMTs. An adequate number of E791 ADC's exist to implement this plan.

BNL Experiment 888

The E871 collaboration has been joined by physicists from Princeton, UCLA, and BNL to conduct a search at the AGS, using the E791 spectrometer, for an H dibaryon. Data were taken in June, 1992. The H is a hypothetical six-quark ($uuddss$) state. The E888 experiment consists of two distinct searches for the H . One uses the E791 spectrometer to look for single $\Lambda \rightarrow p\pi$ decays in the neutral beam in the vacuum decay region. These Λ 's could come from H decays such as $H \rightarrow \Lambda n$. This search method is sensitive to H 's with lifetimes in the range of 10^{-7} to 10^{-9} seconds. The second search involves significant rearrangement of the E791 spectrometer and looks for H interactions which produce two Λ 's through diffractive dissociation in an active (scintillator) "dissociator" placed in the neutral beam. This method is sensitive to H lifetimes above 10^{-8} . Results from this experiment are expected to be available in the next year.

References

1. H. Haber and G. L. Kane, Phys. Rep. 117, 75 (1985); B. A. Campbell, Phys. Rev D28, 209 (1983); J. C. Romao et al., Nucl. Phys. B250, 295 (1985).
2. E. Farhi and L. Susskind, Phys. Rep. 74, 277(1981); E. Eichten and K. Lane, Phys. Lett. 90B, 125(1980); J. Ellis et al., Nucl. Phys. B182, 529(1981); A. Masiero, E. Papantonopoulos, and T. Yanagida, Phys. Lett. 115B, 229(1982); B. Holdom, Phys. Lett. 143B, 227(1984); E. Eichten et al., Phys. Rev. D34, 1547(1986).
3. J. C. Pati and A. Salam, Phys. Rev. D10, 275(1974); A. Barroso, G. C. Branco, and M. C. Bento, Phys. Lett. 134B, 123(1984).
4. T. Maehara and T. Yanagida, Prog. Theo. Phys. 60, 1434(1979); A. Davidson and K. C. Wali, Phys. Rev. Lett. 26, 691(1981); Wei-Shu Hou and A. Soni, Phys. Rev. Lett. 54, 2083(1985).
5. R. N. Cahn and H. Harari, Nucl. Phys. B176, 135(1980).
6. Z. Y. Zhu, Z. Phys. C13, 321(1982); I. Bars, M. J. Bowick, and K. Freese, Phys. Lett. 138B, 159(1984); O. W. Greenberg, R. N. Mohapatra, and S. Nussinov, Phys. Lett. 148B, 465(1984); J. C. Pati, Phys. Rev. D30, 1144(1984).
7. B. A. Campbell et al., Int. J. Mod. Phys. A2, 831(1987).
8. B. W. Lee and R. E. Schrock, Phys. Rev. D16, 1444(1977); T. P. Cheng and L. F. Li, Phys. Rev. D16, 1425(1977).
9. P. Langacker, S. U. Sankar, and K. Schilcher, Phys. Rev. D38, 2841(1988).
10. R. D. Bolton et al., Phys. Rev. Lett. 56, 2461(1986).
11. U. Bellgardt et al., Nucl. Phys. B299, 1(1988).
12. D. A. Bryman et al., Phys. Rev. Lett. 55, 465(1985).
13. A. M. Lee et al., Phys. Rev. Lett. 64, 165(1990).
14. J. L. Ritchie, Proceedings of the 18th SLAC Summer Institute on Particle Physics; July, 1990, p. 259; W. R. Molzon, invited talk at TRIUMF workshop, UCI90-52, July, 1990; W. R. Molzon, invited talk at the XXV International Conference on High Energy Physics, Singapore, August, 1990; A. Schwartz, invited talk at the 4th Conference on the Intersections between Particle and Nuclear Physics, Tucson, Arizona, June, 1991; S. Kettell, invited talk at the Vancouver DPF Meeting, August, 1991.
15. L. M. Sehgal, Phys. Rev. 183, 1511(1969); B. R. Martin, E. de Rafael and J. Smith, Phys. Rev D2, 179(1970).
16. Review of Particle Properties, K. Hikasa et al., Phys. Rev. D45, S1(1992).
17. M. K. Gaillard, B. W. Lee, and R. E. Schrock, Phys. Rev. D13, 2674(1976); R. E. Schrock and M. B. Voloshin, Phys. Lett. 87B, 375(1979); T. Inami and C. S. Lim, Prog. Theor. Phys. 65, 279, 1772(E), (1981).

18. G. Belanger and C. Q. Geng, TRI-PP-58, July, 1990; L. Bergstrom, E. Masso, and P. Singer, CERN-TH-5803/90.
19. O. Shanker, Nucl. Phys. B206, 253(1982).
20. S. F. Schaffner et al., Phys. Rev. D30, 990(1989).
21. T. Inagaki et al., Phys. Rev. D40, 1712(1989).

E. STAR, Solenoidal Detector at RHIC

Recently, we have joined a large collaborative group working on the RHIC experiment STAR (Solenoidal Detector at RHIC) at BNL. Our role in this project, which for the next several years will emphasize the design and fabrication of a very large, complex collider detector, is not yet fully defined, but will clearly involve the principal efforts of both George Glass and of Kok Heong McNaughton at Los Alamos as well as of U.T. graduate students. The STAR detector is presently conceived of as a combination of a silicon vertex tracker (SVT), a Time Projection chamber (TPC), a set of trigger scintillators, and time of flight (TOF) counters. There are also an external TPC (XTPC) and some MWPCs. The lack of calorimetry in this combination is undesirable, especially when gammas are produced. The source of spin in the proton has been a major issue recently, and direct photon detection would allow for some important measurements of spin dependence with polarized colliding protons that relate to the gluon spin structure function. Funds for engineering and prototyping for an electromagnetic calorimeter are being sought from DOE by John Harris and Tim Hallman within nuclear physics. The Argonne group, led by A. Yokosawa, has embarked on this phase of development for STAR. George Glass has been asked by John Harris, as well as by Hal Spinka of ANL, to join in this development effort. Both he and Kok Heong McNaughton are expected to participate in the design, development, and fabrication of this calorimeter. The task ahead will require a serious engineering study with major prototyping and testing. Further, a major effort is needed for simulation studies that would establish the detectability of the direct gammas and the associated jets within the plethora of tracks generated in the high luminosity environment anticipated for RHIC.

III. PERSONNEL WORKING ON PROJECT

Peter J. Riley, Professor of Physics

Kok Heong McNaughton, Computer Programmer (3/4 time)

Chau Nguyen, Postdoctoral, (1/2 time)

George Glass, Research Scientist (Starting Sept. 1, 1992)

David Ambrose, Graduate Student

Mark Bachman, Graduate Student

Patrick Coffey, Graduate Student

Bernard Jobst, Graduate Student, Graduated (M.Sc.) August, 1992.

Most of Peter Riley's time during 1992 was spent on E1097 work, although he participated in E791 and E871 work at BNL. Kok Heong McNaughton lives and works in Los Alamos, and has been responsible for the software for our experiments there. In addition, she has assisted in data acquisition runs, and in data analyses at LAMPF. Chau Nguyen works entirely on BNL E871, and there has concentrated his efforts on the lead glass array. He divides his time, as dictated by the experimental needs, between Austin and BNL. Half of his support is provided by this grant, and half by Jack Ritchie's grant. George Glass, who joined our group effective September 1, 1992, lives and works in Los Alamos. He has participated in all of our recent LAMPF experiments. During 1993 he expects to become involved design studies for the electromagnetic calorimeter for STAF. David Ambrose has been responsible for the development of the E1097 tracking and event reconstruction software, as well as for much of the development work on the E1097 cylindrical drift chamber. Until November, 1992, he expected to base his Ph. D. research on LAMPF E1097. He will now probably work on E871 at BNL. Mark Bachman, whose Ph. D. thesis research is based on TRIUMF E372, has spent the past year at U.T. Austin working on the E372 data analyses. He expects to complete his Ph. D. dissertation in mid-1993. Patrick Coffey graduated with a B.S. in physics in December, 1991, and then spent the first half of 1992 working at LAMPF on the E1097 drift chamber. He entered U.T. as a physics graduate student in September, 1992. He will probably base his Ph. D. research on the rare kaon decay experiment, E871, at BNL. Bernard Jobst, a foreign exchange student from Germany, completed his M.Sc. thesis this past summer working with our group on E876 at LAMPF.

IV. PUBLICATIONS

PUBLICATIONS

"np elastic spin transfer measurements at 788 MeV," M. W. McNaughton, K. Kock, I. Supek, N. Tanaka, K. H. McNaughton, P. J. Riley, D. A. Ambrose, J. D. Johnson, A. Smith, G. Glass, J. C. Hiebert, L. C. Northcliffe, A. J. Simon, D. L. Adams, R. D. Ransome, D. B. Clayton, H. M. Spinka, R. H. Jeppeson, and G. E. Tripard, *Physical Review C* **44**, 2267, (1991).

"Elastic scattering of N-, L-, and S-type polarized 794 MeV protons from an ND₃ target polarized in the S-L plane," E. Gulmez, D. L. Adams, S. Beedoe, M. Bleszynski, A. J. Bystricky, V. Ghazikhanian, G. Igo, T. Jaroszewicz, A. G. Ling, M. Nasser, M. W. McNaughton, S. Penttila, G. Glass, G. Kahrmanis, W. F. Kielhorn, K. H. McNaughton, P. J. Riley, S. Sen, and D. Wolf, *Physical Review C* **45**, 22, (1992).

"²H(p,n)2p spin transfer from 305 to 788 MeV," M. W. McNaughton, K. Kock, I. Supek, N. Tanaka, K. H. McNaughton, P. J. Riley, D. A. Ambrose, P. Coffey, K. Johnson, G. Glass, J. C. Hiebert, L. C. Northcliffe, A. J. Simon, D. L. Adams, D. J. Mercer, H. M. Spinka, R. H. Jeppeson, G. E. Tripard and H. Woolvertaon, *Physical Review C* **45**, 2564, (1992).

"np elastic spin-transfer measurements at 485 and 635 MeV," K. H. McNaughton, D. A. Ambrose, P. Coffey, K. Johnston, P. J. Riley, M. W. McNaughton, K. Koch, I. Supek, N. Tanaka, G. Glass, J. C. Hiebert, L. C. Northcliffe, A. J. Simon, D. J. Mercer, D. L. Adams, H. Spinka, R. H. Jeppesen, G. E. Tripard, and H. Woolverton, *Physical Review C* **46**, 47, (1992).

SUBMITTED FOR PUBLICATION

"Absolute pp-elastic cross sections from 492 to 793 MeV," A. J. Simon, G. Glass, M. W. McNaughton, T. Noro, K. H. McNaughton, P. J. Riley, E. Gulmez, C. A. Whitten, Jr., V. R. Cupps, R. D. Ransome, and D. L. Adams, submitted for publication in *Physical Review C*.

"np-Elastic analyzing power A_{no} and spin transfer K_{nn} ," M. W. McNaughton, K. Johnston, D. Swenson, D. Tupa, R. York, D. A. Ambrose, P. Coffey, K. H. McNaughton, G. Glass, J. C. Hiebert, R. H. Jeppeson, H. Spinka, I. Supek, G. E. Tripard, and H. Woolverton, submitted for publication in *Physical Review C*.

"Improved Upper Limit on the Branching Ratio $K_L^0 \rightarrow \mu e$," K. Arisaka, L. B. Auerbach, S. Axelrod, J. Belz, K. A. Biery, P. Buchholz, M. D. Chapman, R. D. Cousins, M. V. Diwan, M. Eckhause, J. F. Ginkel, C. Guss, A. D. Hancock, A. P. Heinson, V. L. Highland, G. W. Hoffmann, J. Horvath, G. M. Irwin, D. Joyce, T. Kaarsberg, J. R. Kane, C. J. Kenney, S. H. Kettell, W. W. Kinnison, P. Knibbe, J. Konigsberg, Y. Kuang, K. Lang, D. M. Lee, J. Margulies, C. Mathiazhagan, W. K. McFarlane, R. J. McKee, P. Melese, E. C. Milner, W. R. Molzon, D. A. Ouimette, P. J. Riley, J. L. Ritchie, P. Rubins, G. H. Sanders, A. J. Schwarz, M. Sivertz, W. E. Slater, J. Urheim, W. F. Vulcan, D. L. Wagner, R. E. Welsh, R. J. Whyley, R. G. Winter, M. T. Witkowski, S. G. Wojcicki, A. Yamashita, and H. J. Ziock, submitted for publication in *Physical Review Letters*.

V. TITLE PAGES OF PUBLICATIONS

*Removed + cycled
separately*

END

**DATE
FILMED**

4 / 28 / 93