**DOE/PC/88874-T15
(DE92009615)**

**THEORETICAL APPROACH FOR ENHANCED MASS TRANSFER EFFECTS IN
DUCT FLUE GAS DESULFURIZATION PROCESSES**

Topical Report for Task 4—Novel Techniques

**By
Wojciech Jozewicz
Gary T. Rochelle**

**September 17, 1991
Date Prepared**

Work Performed Under Contract No. AC22-88PC88874

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Acurex Corporation
Research Triangle Park, North Carolina**

and

**The University of Texas at Austin
Austin, Texas**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

THEORETICAL APPROACH FOR ENHANCED MASS TRANSFER EFFECTS IN DUCT FLUE GAS DESULFURIZATION PROCESSES

Topical Report for Task 4--Novel Techniques

DOE/PC/ 88874--T15

Prepared for:

DE92 009615

DOE Project Manager
Richard E. Tischer
Environmental Control Division
Pittsburgh Energy Technology Center
U.S. Department of Energy
Pittsburgh, Pennsylvania 15236

Under Contract No. DE-AC22-88PC88874
Date Prepared: September 17, 1991

Prepared by:

Wojciech Jozewicz
Acurex Corporation
Environmental Systems Division
4915 Prospectus Drive
P.O. Box 13109
Research Triangle Park, NC 27709

and

Gary T. Rochelle
Department of Chemical Engineering
The University of Texas at Austin
Austin, Texas 78712

ABSTRACT

Novel techniques designed for the enhancement of $\text{Ca}(\text{OH})_2$ utilization in dry-sorbent injection (DSI) and duct-spray drying (DSD) were investigated in the Long Time Differential Reactor (LTDR), Short Time Differential Reactor (STDR), and 50-cfm pilot plant. At 2,000-ppm SO_2 and 60 percent relative humidity, the presence of up to 30-percent initial free moisture significantly increased sorbent reactivity with SO_2 , compared to sorbent with equilibrium amount of moisture. The conversion decreased when the initial free moisture increased beyond 30-50 percent. The initial free moisture content and corresponding level of maximum sorbent conversion with SO_2 varied with the surface area of the sorbent. Sorbent moisture capacity tests indicated that agglomeration of damp calcium silicate sorbent was a function of sorbent pore volume. Critical moisture content was increasing with specific surface area. Very little improvement in SO_2 removal was obtained by DSI recycle operation downstream of humidification. Significant enhancement was achieved by DSI recycle upstream of humidification. Grinding of DSI solids with and without fly ash resulted in significant increase of surface area and pore volume and resulting reactivity with SO_2 . Organic buffer additives were tested as potential enhancement of $\text{Ca}(\text{OH})_2$ utilization during the DSD process. Bench-scale results suggested that organic acids should be effective additives to enhance SO_2 in slurry if SO_2 absorption was controlled significantly by liquid film resistance. Pilot-plant tests did not demonstrate significant enhancement of $\text{Ca}(\text{OH})_2$ conversion during spray drying as a result of buffer additives. Grinding of simulated DSD solids resulted in significant enhancement of $\text{Ca}(\text{OH})_2$ reactivity with SO_2 .

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
ABSTRACT	i
1.0 INTRODUCTION	1
2.0 EXPERIMENTAL	3
2.1 Long Time Differential Reactor	3
2.2 Short Time Differential Reactor	6
2.3 Pilot-Plant Equipment	8
3.0 ENHANCEMENT OF DRY SORBENT INJECTION: MOIST SOLIDS	12
3.1 Theory	12
3.1.1 Assumptions for Theoretical Development	12
3.1.2 Derivation	13
3.1.3 Effects of Equilibrium Reaction	16
3.1.4 Derivation of Modified Equilibrium Conversion Estimate	18
3.2 Long Time Differential Reactor Results and Discussion	18
3.2.1 Sorbents with Ambient Moisture	19
3.2.2 Sorbents with Initial Free Moisture	25
3.2.3 Comparison: Additive Model vs. Experiment	38
3.2.4 Comparison: Interactive Model vs. Experiment	45
3.2.5 Conversion of $\text{Ca}(\text{OH})_2$ /Fly Ash Sorbent by Reaction with CO_2	56
3.2.6 Conclusions	56
3.3 Short Time Differential Reactor Results and Discussion	59
3.3.1 Effect of Sorbent Type	61
3.3.2 Combined Effect of the Amount of Initial Free Moisture and Sorbent Surface Area	71
3.3.3 Effect of the Approach to Saturation	77
3.3.4 Effect of Fly Ash Source	80
3.3.5 Conclusions	84
4.0 ENHANCEMENT OF DRY-SORBENT INJECTION: OTHER TECHNIQUES	85
4.1 Hydration Modifications	85
4.2 Recycle Operation	87
4.2.1 Dry-Sorbent Injection Downstream of Humidification	87
4.2.2 Dry-Sorbent Injection Upstream of Humidification	89
4.2.3 Conclusions	91
4.3 Grinding of Dry-Sorbent Injection Material	91
4.3.1 Grinding of Spent $\text{Ca}(\text{OH})_2$	91
4.3.2 Grinding of Spent $\text{Ca}(\text{OH})_2$ /Fly Ash	94
4.3.3 Conclusions	95

(continued)

TABLE OF CONTENTS (concluded)

<u>Section</u>	<u>Page</u>
5.0 SOLIDS MOISTURE CAPACITY	98
5.1 Introduction	98
5.2 Theory of Agglomeration	99
5.3 Approach	100
5.4 Results for Individual Reactants and Dry Mixtures	102
5.5 Results for Sorbents Prepared from Slurry	110
6.0 ENHANCEMENT OF DUCT SPRAY DRYING	130
6.1 Buffer Additives	130
6.1.1 Bench-Scale Methods	130
6.1.2 Bench-Scale Results	130
6.1.3 Pilot-Scale Results	134
6.1.4 Conclusions	135
6.2 Slaking Modifications	137
6.2.1 Slaking With Water	137
6.2.2 Slaking with Water/Additives	140
6.2.3 Conclusions	
6.3 Recycle Reactivation	
6.3.1 Wet Grinding	143
7.0 References	146

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
2-1. Schematic of LTDR system.	4
2-2. Fixed-bed reactor.	5
2-3. Schematic of modified Short Time Differential Reactor.	7
2-4. Comparison of TGA-detected moisture contents with actual moisture contents.	9
2-5. Schematic of dry-injection pilot plant.	10
3-1. Predicted conversion in the presence of liquid H ₂ O: (Ca(OH) ₂ fly ash sorbent containing 3.65x10 ⁻³ moles Ca/g sorbent).	17
3-2. Conversion of Ca(OH) ₂ /fly ash sorbent containing ambient moisture (1,000-ppm SO ₂ in flue gas, 70 °C, 3.5-percent initial moisture on sorbent).	21
3-3. Conversion of Ca(OH) ₂ sorbents containing ambient moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 1.0-percent initial moisture on sorbents, 58- to 67-percent relative humidity in flue gas).	22
3-4. Comparison of Ca(OH) ₂ /fly ash and Mississippi Ca(OH) ₂ sorbent (5,000-ppm SO ₂ in flue gas, 70 °C, 1.0-percent initial moisture on Mississippi Ca(OH) ₂ , 3.5 percent on Ca(OH) ₂ /fly ash, 60- to 67-percent relative humidity in flue gas).	23
3-5. Effect of Ca dispersion on sorbent conversion (5,000-ppm SO ₂ in flue gas, 70 °C, 1.0-percent initial moisture on Mississippi Ca(OH) ₂ , 3.5 percent on Ca(OH) ₂ /fly ash, 60- to 67-percent relative humidity in flue gas).	26
3-6. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (1,000-ppm SO ₂ in flue gas, 70 °C, 10-s reaction).	27
3-7. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (1,000-ppm SO ₂ in flue gas, 70 °C, 60-s reaction).	28
3-8. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (1,000-ppm SO ₂ in flue gas, 70 °C, 120-s reaction).	29
3-9. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 10-s reaction, 58- to 63-percent relative humidity).	31
3-10. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 60-s reaction, 58- to 68-percent relative humidity).	32
3-11. Conversion of Ca(OH) ₂ /fly ash sorbent with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 120-s reaction, 58- to 62-percent relative humidity).	33
3-12. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 10-s reaction, 56- to 66-percent relative humidity).	34
3-13. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 60-s reaction, 58- to 69-percent relative humidity).	35
3-14. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000-ppm SO ₂ in flue gas, 70 °C, 120-s reaction, 58- to 64-percent relative humidity).	36
3-15. Comparison of theoretical and observed conversions of Ca(OH) ₂ /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO ₂ in flue gas, 70 °C, 120-s reaction, 55- to -65-percent relative humidity).	39

(continued)

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
3-16. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 0-percent relative humidity).	40
3-17. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 80- to 90-percent relative humidity).	41
3-18. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 80- to 90-percent relative humidity).	42
3-19. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 80- to 90-percent relative humidity).	43
3-20. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction, 55- to 60-percent relative humidity).	44
3-21. Determination of instantaneous sorbent conversion rate for $\text{Ca}(\text{OH})_2$ sorbents (5,000-ppm SO_2 in flue gas, 70 °C 55- to 65-percent relative humidity).	47
3-22. Determination of instantaneous sorbent conversion rate for $\text{Ca}(\text{OH})_2$ /fly ash sorbent (1,000-5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity).	48
3-23. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (1,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).	50
3-24. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (1,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).	51
3-25. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).	52
3-26. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).	53
3-27. Interactive Model of $\text{Ca}(\text{OH})_2$ conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).	54
3-28. Interactive Model of $\text{Ca}(\text{OH})_2$ conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).	55
3-29. Reaction of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with CO_2 (1,000-ppm SO_2 in flue gas, 70 °C, 55-to 65-percent relative humidity).	57
3-30. SEM photomicrograph of "as-received" Clinch River fly ash sample, x 5,000.	62
3-31. SEM photomicrograph of ground Clinch River fly ash sample, x 5,000.	63
3-32. Baseline tests with dry Meredosia fly ash added to dry Mississippi $\text{Ca}(\text{OH})_2$ (STDR, 2,000-ppm SO_2 , 60-percent relative humidity).	65
3-33. $\text{Ca}(\text{OH})_2$ physically mixed with Meredosia fly ash (STDR, 2,000-ppm SO_2 , 60-percent relative humidity).	66

(continued)

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
3-34. The effect of initial free moisture on the reactivity of chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000-ppm SO_2 , 60-percent relative humidity).	68
3-35. Reactivity comparison for physically mixed and chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000-ppm SO_2 , 60-percent relative humidity, 12-14.7 percent at limited moisture contents).	69
3-36. The effect of an initial moisture on the reactivity of physically mixed and reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000-ppm SO_2 , 60-percent relative humidity, 5-s contact time).	70
3-37. Effect of initial free moisture on the reactivity with SO_2 of 27.4- m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).	72
3-38. Effect of initial free moisture on the reactivity with SO_2 of 33.2- m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).	73
3-39. Effect of initial free moisture on the reactivity with SO_2 of 47.0- m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).	75
3-40. Effect of sorbent-specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).	76
3-41. Effect of the approach to saturation on the reactivity of 30.2- m^2/g sorbent with 30 weight percent initial free moisture (ground Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 2,000-ppm SO_2).	78
3-42. Effect of the approach to saturation on the reactivity of 27.4- m^2/g sorbent with 60 weight percent initial free moisture (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 2,000-ppm SO_2).	79
3-43. Effect of the approach to saturation on the reactivity of 27.4- m^2/g sorbent with equilibrium moisture (ground Meredosia fly ash, $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 2,000-ppm SO_2).	81
3-44. Effect of fly ash source on reactivity of sorbent with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 30-weight percent initial free moisture, 2,000-ppm SO_2 , 60-percent relative humidity).	82
3-45. Combined effect of fly ash source and initial free moisture content on sorbent's reactivity with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 2,000-ppm SO_2 , 60-percent relative humidity, 5-s contact time).	83
4-1. Dry-sorbent injection upstream of the humidifier (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ mixture).	88
4-2. SO_2 removal for recycle operation during the DSI downstream of the humidification zone.	90
4-3. Comparison of DSI upstream and downstream of humidifier	92
4-4. Results for DSI recycle tests upstream of humidifier.	93
4-5. Reactivation of spent Mississippi $\text{Ca}(\text{OH})_2$ baghouse catch by dry grinding baghouse catch/Beverly fly ash (mixed at the weight ratio of 3:5:1).	96

(continued)

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
4-6. Reactivation of spent $\text{Ca}(\text{OH})_2$ /Beverly fly ash solids by dry-grinding in a bench-scale attritor (reactor: 60-percent relative humidity, 2,000-ppm SO_2).	97
5-1. Typical results for sieve tests of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (critical moisture content 17 percent, Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio slurried for 8 h at 92 °C).	104
5-2. Correlation of the moisture data (points represent all fly ash/ $\text{Ca}(\text{OH})_2$ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).	105
5-4. Correlation of particle pore volume with specific surface area (solid symbols represent data for fly ash/ $\text{Ca}(\text{OH})_2$ sorbents prepared and tested by Acurex Corporation; open symbols are for sorbents represented in Figure 5-3; the dotted line and equation are a least-squares fit of the data).	108
5-5. Critical moisture content of reactant and dry mixtures ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, Harrington fly ash, Clinch River fly ash, $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$, ground Clinch River fly ash, and 20-m ² /g $\text{Ca}(\text{OH})_2$).	109
5-6. Effect of slurry time and fly ash/ $\text{Ca}(\text{OH})_2$ ratio on critical moisture content of sorbent from low-calcium fly ash (open symbols are the 3:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; solid symbols are 4:1 ratio).	112
5-7. Effect of CaSO_3 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ with CaSO_3 on sorbents from low-calcium fly ash (solid symbols are 4:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open squares 4:1:4 fly ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$; triangles 4:1:3:1 fly ash/ $\text{Ca}(\text{OH})_2$ / CaSO_3 / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	113
5-8. Effect of CaSO_3 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ with CaSO_3 on solution composition of low-calcium fly ash slurry (solid symbols 4:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open squares 4:1:4 fly ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$; triangles 4:1:3:1 fly ash/ $\text{Ca}(\text{OH})_2$ / CaSO_3 / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	114
5-9. Effect of fly ash grinding and the presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ /g $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ /g $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	116
5-10. Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and CaSO_3 on sorbent from ground low-calcium fly ash (solid symbols 1:1 ground Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open symbols 4:4:3:1 fly ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	117
5-11. Effect of fly ash fraction on sorbent from ground low-calcium fly ash (all samples slurried for 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted $\text{Ca}(\text{OH})_2$).	118
5-12. Effect of fly ash fraction and slurry time on surface area of sorbent from ground low-calcium fly ash (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted $\text{Ca}(\text{OH})_2$).	119
5-13. Effect of fly ash fraction on solution composition of ground low-calcium fly ash slurry (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1).	121

(continued)

LIST OF FIGURES (concluded)

<u>Figure</u>		<u>Page</u>
5-14.	Critical moisture content of sorbent prepared from high-calcium fly ash alone, and fly ash with $\text{Ca}(\text{OH})_2$ ("Ash Alone": Harrington fly ash slurried without $\text{Ca}(\text{OH})_2$ at 26 percent solids, "With $\text{Ca}(\text{OH})_2$ ": weight ratio of Harrington fly ash/ $\text{Ca}(\text{OH})_2$ slurried at 92 °C at 26-percent solids).	123
5-15.	Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content of sorbent prepared from high-calcium fly ash ("Ash Alone": average values of data shown in Figure 5-14 for sorbent prepared from Harrington fly ash, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, " $\text{Ca}(\text{OH})_2$ & Gypsum": 3:1:0.67 Harrington ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	124
5-16.	Solution composition of slurries with high-calcium fly ash ("Ash Alone": Harrington fly ash slurried without $\text{Ca}(\text{OH})_2$ at 23 percent solids, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot \text{H}_2\text{O}$ weight ratio).	125
5-17.	Effect of $\text{Ca}(\text{OH})_2$ loading on sorbent prepared from high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ (constant Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio of 3:0:6 and slurry time of 8 h except points at 0.33 loading, which are 9-h samples).	126
5-18.	Effect of $\text{Ca}(\text{OH})_2$ loading on solution composition for slurry of high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ present (same experiment shown in Figure 5-17).	128
6-1.	Effect of sodium acetate on SO_2 absorption into clear solution containing 3-mM $\text{Ca}(\text{OH})_2$ and 0.1 M CaCl_2 at 55 °C.	133
6-2.	Effect of sodium acetate on SO_2 absorption into clear solution containing 17-mM $\text{Ca}(\text{OH})_2$ and 0.1-M CaCl_2 at 55 °C.	136
6-3.	Combined effect of slurry solids percentage and slaking temperature on the median particle size of slaked $\text{Ca}(\text{OH})_2$	138
6-4.	The effect of alcohol-to-water ratio on median particle size of slaked $\text{Ca}(\text{OH})_2$	141
6-5.	The effect of calcium lignosulfonate concentration on the median particle size of slaked $\text{Ca}(\text{OH})_2$	142
6-6.	Reactivation of spent $\text{Ca}(\text{OH})_2$ /fly ash by wet grinding (reactor: 2,000-ppm SO_2 , 60-percent relative humidity).	145

LIST OF TABLES

<u>Table</u>	<u>Page</u>
3-1. Properties of Sorbents Used in the Course of LTDR Work	20
3-2. Rate of Sorbent Conversions for Interactive Mode	46
3-3. Structural Properties of Fly Ashes used to Produce Fly Ash/Ca(OH) ₂ Sorbents	60
3-4. Structural Properties of Fly Ash/Ca(OH) ₂ Sorbents	61
3-5. Effect of Specific Surface Area on Reactivity of Moist Sorbent with SO ₂ (Meredosia Fly Ash/Ca(OH) ₂ Weight Ratio of 3:1, 90 °C Slurrying)	77
4-1. Structural Properties of Dry Hydrated Ca(OH) ₂ Sorbents	86
4-2. Thermogravimetric Characterization of Dry Hydrated Ca(OH) ₂ Sorbents	86
4-3. Pilot Plant Operating Conditions	87
4-4. Structural Properties of Pilot-Plant Solids	94
4-5. Structural Properties of Dry Ground Baghouse Catch/Beverly Fly Ash Solids	95
5-1. Chemical Composition of Silica Sources (From Energy Dispersive Spectroscopy)	101
6-1. Enhancement of SO ₂ Absorption I 3-mM Ca(OH) ₂ /0.1 M CaCl ₂	131
6-2. Enhancement of SO ₂ Absorption in 17-mM Ca(OH) ₂ /0.1 M CaCl ₂	132
6-3. Buffer Additives Tests	135
6-4. Structural Properties of CaO used for Slaking	139
6-5. Structural Properties of Wet-Ground Baghouse Catch/Beverly Fly Ash Solids	143

SECTION 1

INTRODUCTION

Previous pilot- and bench-scale work has determined that $\text{Ca}(\text{OH})_2$ and Ca-based sorbents have significant potential for application in dry-sorbent injection (DSI) and duct-spray drying (DSD) SO_2 abatement systems. The effectiveness of these solids in the DSI process can be enhanced by increasing the surface moisture content of the sorbent as a function of the relative humidity of the ductwork. Operational difficulties that arise when flue gas is treated with reactive sorbent at high relative humidities limit the applicability of such processes to tightly controlled conditions (Babu, et al., 1988; Drummond, et al., 1988; Yoon, et al., 1988). Improvements to sorbent reactivity are possible by increasing the surface area of the sorbent and the availability of reactive species that may fix the SO_2 in a condensed state (Jorgensen, et al., 1987; Peterson, et al., 1987; Drummond, et al., 1988; White, 1989).

In DSD, reactive sorbent contacts flue gas as a slurry, as a damp sorbent, and as a dry sorbent in equilibrium with flue gas relative humidity. Duct injection of dried sorbents in DSI process utilizes only the third stage of DSD reactivity; sorbent with initial free moisture, which utilizes 2 of the 3 stages, presents a significant improvement over equilibrium sorbent. Equilibrium sorbent used in pilot facilities often scavenges liquid water that is present to humidify the gas, and in the presence of this liquid water, the equilibrium sorbent presents a significant improvement over bench-scale sorbent that does not scavenge liquid water.

The reactivity with SO_2 of sorbents with an initial free moisture was investigated as a means of enhancing DSI. The Long Time Differential Reactor (LTDR) and the Short Time Differential Reactor

(STDR) were used for the above testing and are described in Section 2. The results of LTDR and STDR reactivity testing of sorbents with an initial free moisture are presented in Section 3. Other techniques investigated that could potentially increase conversion of Ca(OH)_2 -based sorbents with SO_2 in the DSI were: hydration modifications, recycle, and grinding. The results are given in Section 4.

Solids moisture capacity was evaluated for a variety of Ca(OH)_2 -based sorbents intended for potential use in DSI. The capacity correlated well with the surface area and pore volume of sorbents tested, and results are given in Section 5.

Section 6 presents techniques used to test the enhancement of DSD. These techniques include use of buffer additives, slaking modifications, and recycle reactivation by grinding. Relevant references are listed in Section 7.

SECTION 2

EXPERIMENTAL

2.1 LONG TIME DIFFERENTIAL REACTOR

The Long Time Differential Reactor (LTDR) experimental system used to perform this study consisted primarily of a flue-gas preparation/delivery system and a fixed-bed reactor. The flue-gas preparation/delivery system included:

- Mass-flow controllers to maintain constant flow rates of the various gases used in the simulated flue gas
- Furnace and evaporator to evaporate water and mix the steam into the flue gas
- Constant-rate syringe pump to provide water to the evaporator
- Water bath and several heat exchangers to maintain constant temperature during reaction
- Scrubber to remove any unreacted SO_2 from the gas stream
- Analyzer to determine the SO_2 concentration in the gas

Figure 2-1 shows the schematic of LTDR system.

The fixed-bed reactor is presented in Figure 2-2. This reactor system was inserted into the flue-gas line in the space marked "REACTOR" shown in Figure 2-1. The fixed-bed reactor was composed of 3 individual reactor units, with common intake and outlet manifolds. The individual reactors were isolated from each other and the manifolds by stainless steel ball valves. The interior volume of each of the 3 reactors was approximately 5.7 cm^3 . The reactors were constructed from 1/2-in stainless steel tubing. Wet sorbents that were loaded into the 3 reactors were equilibrated to the

Figure 2-1. Schematic of LTDR system.

Figure 2-2. Fixed-bed reactor.

reaction temperature without being exposed to hot flue gas. Using this reactor design, 3 experiments could be run consecutively at nearly identical conditions of sorbent H_2O content, relative humidity, and SO_2 concentration.

Sorbents with initial free moisture were prepared by weighing approximately 10 mg of sorbent into a small glass vial. The sorbents and H_2O were mixed using a stainless steel spatula, and a sample of damp sorbent was removed. The sample was weighed immediately to determine its mass while wet, and then oven-dried at approximately 100 °C. The initial H_2O content of the sample was determined by weight difference. The vial containing the wet sorbent was capped and stored in a refrigerator at approximately 10 °C.

To begin an experiment, supported wet sorbent was loaded into each of the 3 reactor units in the fixed-bed reactor, which were sealed and inserted into the flue gas delivery system. The fixed-bed reactor was allowed to equilibrate to the reaction temperature in the water bath for approximately 10 min prior to the introduction of flue gas. The supported sorbent with initial free moisture was prepared by adding approximately 3 g of 60-mesh silica sand and 2 small (0.25-cm dia.) glass beads to each of the 3 vials, and then adding a weighed quantity of sorbent with initial free moisture from the refrigerated storage vial. Prior to experimentation, the sand was acid-washed with dilute HCl and rinsed with water to remove any Ca-containing species. To initiate an experiment, flue gas was directed into the reactor housing, and 1 reactor unit was opened by opening its 2 ball valves. The reaction was stopped by directing flue gas flow away from the reactor and closing the ball valves on each end of the reactor.

2.2 SHORT TIME DIFFERENTIAL REACTOR

The Short Time Differential Reactor (STDR), previously used to identify the rate limiting step for the reaction of dry $\text{Ca}(\text{OH})_2$ with SO_2 , was modified to allow for testing of solids with free moisture. The miniature fixed-bed reactor with stainless steel mesh bottom was inserted into the STDR. No conditioning of solids prior to the contact with SO_2 has been implemented. The schematic of modified STDR is shown in Figure 2-3.

Figure 2-3. Schematic of modified Short Time Differential Reactor.

Wet solids were prepared by weighing a known amount of solids and water in a glass vial. The solids and water were then mixed thoroughly with a spatula and the vial was closed and stored in an ice bath. Moist solids were dispersed on quartz wool and placed in the miniature sand-bed reactor. Exposure to the SO_2 -containing process gas was preceded by a thorough dispersion of solids on quartz wool. The amount of an excess moisture (free moisture) is reported for total solids based on a thermogravimetric measurement (TGA), i.e., weight loss detected by TGA upon heating from room temperature to 100 °C. The amount of free moisture detected by TGA correlates positively with actual moisture contents, indicating that most of the moisture is released when the wet solids are heated to 100 °C in the TGA. The comparison of TGA-detected amount of moisture and actual moisture contents is shown in Figure 2-4. The solid line in Figure 2-4 indicates 100-percent detection of actual moisture by the TGA.

2.3 PILOT-PLANT EQUIPMENT

The pilot-plant facility (Figure 2-5) used to evaluate sorbents for DSI process consisted of a gas humidifier equipped with a rotary atomizer for atomization of water to control the gas temperature and humidity. Air flow was drawn from ambient air through an air filter and an electrical heater. The air, heated to 149 °C, entered the humidifier through an air disperser located in the center of the chamber roof. After leaving the humidifier, the cooled gas stream flowed through a heat-traced and -insulated section of duct to a pulse-jet baghouse for collection of solids. For certain runs, a cyclone was installed immediately upstream of the baghouse. Gaseous SO_2 was injected into the heated air stream before the humidifier to simulate the flue gas emanating from the boiler burning sulfur-containing fuel. Sorbents were injected by a screw feeder into the duct downstream of the humidifier. The 5-cm diameter, 24.5-m long duct transported the humidified gas stream with entrained solids to the pulse-jet baghouse. The flue-gas residence time in the duct is estimated to be 2 s.

The SO_2 concentration was measured at the humidifier outlet, baghouse inlet, and baghouse outlet. The measurement at the baghouse inlet was used to determine the amount of in-duct SO_2

Figure 2-4. Comparison of TGA-detected moisture contents with actual moisture contents.

Figure 2-5. Schematic of dry injection pilot plant.

removal. Total SO_2 removal across the system was determined from the baghouse outlet concentration. The approach to saturation was obtained from the wet-bulb and dry-bulb temperatures of the humidified gas stream. The wet-bulb temperature was measured by a thermocouple covered with a wick-like material saturated with water and inserted into the gas flow downstream of the humidifier. The calculated approach to saturation was then held constant throughout the system. Precise control of the temperature was accomplished by heat tracing on the duct and the baghouse.

SECTION 3

ENHANCEMENT OF DRY SORBENT INJECTION: MOIST SOLIDS

3.1 THEORY

The key variables that affect the gas-solid reaction between SO_2 and $\text{Ca}(\text{OH})_2$ -based sorbents during dry-sorbent injection (DSI) are flue-gas relative humidity, sorbent water content, flue-gas SO_2 concentration, and sorbent surface structure. Previous spray-dryer studies involved the reactivity of sorbent particles suspended in liquid droplets, which, as they dried, passed through the liquid, free moisture, and equilibrium stages of reactivity. In the equilibrium stage, the particle is assumed to contain surface water in equilibrium with the relative humidity of the flue gas. While the total reactivity of such a solid has been studied, there have been no efforts to decouple these effects. Mass transfer theory may be applied to the gas-solid reaction system in the presence of moisture in excess of equilibrium on the surface of a reactive sorbent. The theoretical model below describes the reaction occurring when a wet solid is drying and relates the evaporative drying and the SO_2 capture mechanisms.

3.1.1 Assumptions for Theoretical Development

The reaction between sorbent with an initial free moisture and SO_2 is assumed to be fast compared to gas-phase mass transfer of SO_2 to the particle surface. The transfer is assumed to occur by Knudsen diffusion within the pores of the reactive sorbent. The following assumptions also are necessary for the development of the model:

- Liquid water present on the solid with initial free moisture is present predominantly in the pores of the solid.

- The resistance to mass transfer for both the evaporation process and the SO₂ capture process is controlled by diffusion in the gas phase.
- Reaction between SO₂ and a sorbent with initial free moisture which dries during the course of reaction occurs in 2 separate stages, the effects of which are additive.
 - These 2 stages are: reaction in the presence of excess surface moisture (sorbent with initial free moisture), and reaction in the presence of equilibrium moisture (sorbent in equilibrium with flue-gas relative humidity).
- The bulk flow contribution to the overall mass flux of the exchanged species is negligible during pore diffusion.

3.1.2 Derivation

The evaporation of water from the pores of the solid and the transport of SO₂ through the pores to the gas-liquid interface can be represented by:

$$\frac{d(\text{SO}_2/\text{area})}{dt} = N_{\text{SO}_2} = -(D_{\text{SO}_2}) \frac{dC_{\text{SO}_2}}{dx} \quad 3-1$$

$$\frac{d(\text{H}_2\text{O}/\text{area})}{dt} = N_{\text{H}_2\text{O}} = -(D_{\text{H}_2\text{O}}) \frac{dC_{\text{H}_2\text{O}}}{dx} \quad 3-2$$

where:

N_i = molar flux ; [mole l/(area-time)],

x = diffusion distance ; [length],

D = mass diffusion coefficient; [length²/time], and

C_i = concentration i ; [mole l/volume].

These expressions are based on a rectangular coordinate system and a 1-dimensional concentration gradient. The mechanism assumes that the reaction occurs in a liquid droplet at the

bottom of a pore. Because no reaction will occur at the walls of the pore, it is not necessary to model diffusion in the radial direction.

Transport of H_2O and SO_2 is assumed to occur by Knudsen diffusion, which is a valid assumption if the gas/liquid interface is located within small pores in the sorbent. Knudsen diffusion is applicable when the mean free path over which a molecule can travel is greater than the pore diameter through which it is diffusing. The mean free path of a molecule is defined as follows:

$$l = \frac{1}{\sqrt{2} \pi d^2 n} \quad 3-3$$

where:

l = mean free path; [length],

d = particle diameter; [length], and

n = concentration of molecules; [number molecules/volume].

The Knudsen diffusion coefficient is defined by:

$$D_{AK} = 97 r \sqrt{\frac{T}{M_k}} \quad 3-4$$

where:

D_{AK} = Knudsen diffusion coefficient; [length²/time],

r = radius of diffusing particle ; [length],

T = system temperature, and

M_A = diffusing particle molecular weight; [mass].

The pore irregularities traditionally are handled using an empirical factor, the tortuosity of a pore, along with the particle porosity. These factors are ignored here as the ratio of the 2 flux expressions will be taken, and the tortuosities and porosities will cancel from the final expression. It is now possible to insert the Knudsen diffusion coefficient into the flux expressions and, taking the ratio of the 2, the following relationship holds:

$$\frac{N_{SO_2}}{N_{H_2O}} = \frac{D_{SO_2}K(dSO_2/dx)}{D_{H_2O}K(dH_2O/dx)} \quad 3-5$$

The relationship between the water evaporated from the solid surface and the SO_2 captured is determined by integrating this expression, as follows:

$$\frac{\Delta SO_2}{\Delta H_2O} = \frac{D_{SO_2}K(P_{SO_2})}{D_{H_2O}K(P_{H_2O}^* - P_{H_2O})} \quad 3-6$$

where:

ΔSO_2 = SO_2 captured; [moles],

ΔH_2O = H_2O evaporated; [moles],

P_{SO_2} = partial pressure SO_2 in bulk gas; [atm],

P_{H_2O} = partial pressure H_2O in bulk gas; [atm], and

$P_{H_2O}^*$ = partial pressure H_2O at gas-liquid interface; [atm].

The model allows one to predict the conversion of the porous sorbent as a function of the quantity of water evaporated from the sorbent while in contact with SO_2 . This representation does not account for reaction that occurs when the sorbent contains water in equilibrium with the flue-gas relative humidity.

In each experiment, the initial weight percent water on the reactive sorbent, the relative humidity of the flue gas, and the SO_2 content of the flue gas are noted. The aforementioned expression is modified to predict the Ca utilization of the sorbent based on these parameters. The modified predictive expression is:

$$\frac{\Delta SO_2}{\Delta H_2O} = \frac{0.53(P_{SO_2})}{(P_{H_2O}^* - P_{H_2O})} \left(\frac{\Delta H_2O}{Ca} \right) \quad 3-7$$

where:

Ca = Ca content of the sorbent; [moles/gram sorbent].

Figure 3-1 shows the conversions predicted by the model under typical experimental conditions. These results assume that all H_2O initially present on the surface of the solid evaporates from the solid. The results do not include reaction between the sorbent and SO_2 in the absence of excess moisture on the surface of the sorbent. The model predicts a linear increase in conversion of sorbent as a function of its initial moisture.

J.1.3 Effects of Equilibrium Reaction

The effects of the wet reaction and the reaction occurring in the presence of equilibrium moisture may not be additive, but rather the presence of liquid moisture on the sorbent surface may affect the reaction with equilibrium moisture. Initial free moisture on the surface of the sorbent occupies free surface area otherwise available for reaction attributable to equilibrium moisture. If the conversion observed during the equilibrium moisture reaction is significant, the conversion attained in the combined wet/equilibrium-moisture system will be lower than a linear combination of the expected results for the independent wet and equilibrium-moisture systems.

The conversion predicted as a function of initial free moisture on the surface of the sorbent is considered correct, but the magnitude of the equilibrium-moisture reaction's contribution must be adjusted to reach a correct total conversion. To calculate the conversion that will occur by the equilibrium-moisture reaction, the results of equilibrium-moisture reaction studies will be analyzed to determine the instantaneous rate of sorbent conversion as a function of sorbent conversion. For each experiment to be modeled, the conversion expected attributable to liquid water will be noted, and the instantaneous conversion rate corresponding to this conversion level will be used to calculate the conversion attributable to equilibrium-moisture reaction. The initial free moisture on the sorbent surface is assumed to evaporate instantly during reaction, the differential expression for conversion attributable to reaction in the presence of equilibrium moisture must be integrated over the entire reaction time. The resulting conversion predicted attributable to reaction in the presence of equilibrium moisture will be added to the conversion expected attributable to wet reaction in order to determine the total conversion of the sorbent. This model will be referred to as the Additive Model.

Figure 3-1. Predicted conversion in the presence of liquid H_2O : $(\text{Ca}(\text{OH})_2)$ fly ash sorbent containing 3.65×10^{-3} moles Ca/g sorbent).

3.1.4 Derivation of Modified Equilibrium Conversion Estimate

The expression that predicts sorbent conversion attributable to excess moisture is shown in Equation 3.7. The expression for total sorbent conversion is:

$$\text{Pred. conversion} = a_{H_2O} + g_{EQ} \quad 3-8$$

where:

a_{H_2O} = conversion due to excess H_2O : [mole SO_2 /mole Ca], and

g_{EQ} = equilibrium-moisture conversion; [moles SO_2 /mole Ca].

It is possible to evaluate g_{EQ} as follows:

$$g_{EQ} = h_{EQ}(t + t_0) - a_{H_2O} \quad 3-9$$

where:

t_0 = time required to achieve f_{H_2O} conversion by the equilibrium-moisture mechanism; [s],

t = time available for equilibrium-moisture reaction; [s], and

$h_{eq}(t + t_0)$ = instantaneous rate of conversion by equilibrium-moisture mechanism evaluated at $(t + t_0)$; [(moles S/mole Ca)/(s)].

When the ambient-moisture portion of the total conversion is predicted using this method, the model will be referred to as the Interactive Model.

3.2 LONG TIME DIFFERENTIAL REACTOR RESULTS AND DISCUSSION

The Long Time Differential Reactor (LTDR) experimental work addressing the SO_2 -removal performance of $Ca(OH)_2$ -based sorbents with initial free moisture under DSI conditions was performed in 2 stages. In the first stage, sorbents containing moisture in equilibrium with laboratory relative humidity (~ 50 percent) were exposed to flue gas of varying relative humidity and SO_2 content. In the second stage, water was added to the sorbent so that its water content was above that attained through equilibrium with the room humidity. Four sorbents, of varying surface properties and chemical

composition, were used, and the flue gas SO_2 content and relative humidity were varied during both stages of testing.

In the course of LTDR work, 2 different gas-phase SO_2 concentrations were used: 1,000 and 5,000 ppm. At 1,000 ppm, significant Ca-utilizations were expected in the $\text{Ca}(\text{OH})_2$ /fly ash sorbent when both equilibrium moisture and moisture in excess of the equilibrium condition were applied to the reaction system. The sorbent was not expected to approach 100-percent Ca-utilization under these conditions. When 5,000-ppm SO_2 was present in the flue gas, significant Ca-utilizations were expected in all of the sorbents for reactions utilizing sorbent containing both equilibrium moisture and moisture in excess of the equilibrium quantity. Because of the possibility that the lime/fly ash sorbent would approach 100-percent Ca-utilization if significant quantities of moisture were present on the sorbent during reaction with 5,000-ppm flue gas, a limited amount of water was added to this sorbent during the 5,000-ppm testing.

Several different sorbents were used in this study. Their properties are presented in Table 3-1. The reactivities of Mississippi $\text{Ca}(\text{OH})_2$ and the $\text{Ca}(\text{OH})_2$ /fly ash material have been studied by researchers at The University of Texas at Austin (Peterson and Rochelle, 1988). The other 2 sorbents were selected to determine the effects of surface area and porosity on the reaction with SO_2 . The sorbents are made from $\text{Ca}(\text{OH})_2$ that has been calcinated and subsequently hydrated in the presence of alcohol (double hydration) to promote the formation of high surface area, high porosity $\text{Ca}(\text{OH})_2$.

3.2.1 Sorbents with Ambient Moisture

Presented below is experimental work performed with sorbents containing moisture in equilibrium with laboratory temperature and relative humidity. The results presented in Figures 3-2, 3-3, and 3-4 are the culmination of the work done to investigate sorbent reactivity when the sorbent contains moisture in equilibrium with laboratory relative humidity. Initially, the sorbents contained moisture in equilibrium with the laboratory relative humidity. When the flue gas was introduced into the

TABLE 3-1. PROPERTIES OF SORBENTS USED IN THE COURSE OF LTDR WORK

Sorbent Name	Surface Area [m ² /g]	Porosity [cm ³ /g]	Formation Conditions
Ca(OH) ₂ /Fly ash	16	0.21	3:1 ratio Clinch River fly ash Mississippi Ca(OH) ₂ slurried at 90 °C for 12 h
Mississippi Ca(OH) ₂	17	0.19	
Ca(OH) ₂ "A"	74	0.47	hydrated (alcohol present) at 74 °C for 50 min, N ₂ blanket for 41 min
Ca(OH) ₂ "B"	51	0.25	hydrated (alcohol present) at 74 °C for 35 min, N ₂ blanket for 26 min

reactors, the sorbents' moisture content shifted to attain equilibrium with the flue-gas relative humidity. The magnitude of the change in the sorbent's surface moisture content was presumed negligible during this process.

Figure 3-2 indicates that increasing the relative humidity of the flue gas and increasing the gas-sorbent contact time enhances the conversion (moles S captured/mol Ca) of the Ca(OH)₂/fly ash sorbent. At the higher relative humidities, conversions reach 0.50 and 0.20 for 120- and 10-s reactions, whereas the average sorbent conversion for 120-s gas/solid contact time is 0.30 at approximately 60-percent relative humidity. The increase in sorbent conversion with increasing reaction time is not as significant for the lower relative humidities as for the higher relative humidities, implying that for a given reaction time, greater surface moisture content of the sorbent results in greater conversion.

The surface area of Ca(OH)₂ sorbent "A" is 74 m²/g, of Ca(OH)₂ sorbent "B" is 51 m²/g, of Mississippi Ca(OH)₂ sorbent is 17 m²/g, and of Ca(OH)₂/fly ash is 16 m²/g. A corresponding increase in sorbent porosity occurs with increasing surface area for the aforementioned sorbents. Figure 3-3

Figure 3-2. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent containing ambient moisture (1,000-ppm SO_2 in flue gas, 70 °C, 3.5-percent initial moisture on sorbent).

Figure 3-3. Conversion of $\text{Ca}(\text{OH})_2$ sorbents containing ambient moisture (5,000-ppm SO_2 in flue gas, 70 °C, 1.0-percent initial moisture on sorbents, 58- to 67-percent relative humidity in flue gas).

Figure 3-4. Comparison of $\text{Ca}(\text{OH})_2$ /fly ash and Mississippi $\text{Ca}(\text{OH})_2$ sorbent (5,000-ppm SO_2 in flue gas, 70 °C, 1.0-percent initial moisture on Mississippi $\text{Ca}(\text{OH})_2$, 3.5 percent on $\text{Ca}(\text{OH})_2$ /fly ash, 60- to 67-percent relative humidity in flue gas).

shows that the equilibrium conversion of the $\text{Ca}(\text{OH})_2$ sorbents increases with increasing sorbent surface area, and the conversion of lower-surface-area sorbents does not approach that of the high-surface-area sorbents at short or long times. The conversion of $\text{Ca}(\text{OH})_2$ sorbents increases slightly with increasing reaction time, although the effect is not as significant as for the $\text{Ca}(\text{OH})_2$ /fly ash sorbent in the 1,000-ppm flue gas (Figure 3-2).

Significant conversion of the $\text{Ca}(\text{OH})_2$ sorbents occurs, ranging to approximately 0.22 and 0.33, for 10- and 120-s reactions at approximately 61-percent relative humidity with the high-surface-area $\text{Ca}(\text{OH})_2$. The high surface area provides adequate space for instantaneous reaction, but the formation and precipitation of product on the particle surface limits additional conversion. In Figure 3-4, a comparison is presented of $\text{Ca}(\text{OH})_2$ /fly ash sorbent's reactivity with that of Mississippi $\text{Ca}(\text{OH})_2$. 5,000-ppm SO_2 was in the flue gas during these tests, which were conducted at approximately 60-percent relative humidity. The conversion of the $\text{Ca}(\text{OH})_2$ /fly ash sorbent was superior to that of the Mississippi $\text{Ca}(\text{OH})_2$ at all reaction times, although the surface areas of the 2 sorbents are similar. In contrast to its performance in the presence of low concentrations of SO_2 , the conversion of the $\text{Ca}(\text{OH})_2$ /fly ash sorbent did not increase drastically with increasing reaction time in the presence of 5,000-ppm SO_2 . The conversion of the $\text{Ca}(\text{OH})_2$ /fly ash sorbent is approximately the same for the 120-s reaction, although the 10- and 60-s reactions provide significantly higher conversions in the presence of the 5,000-ppm SO_2 than the 1,000-ppm SO_2 , which was not expected. With 5,000-ppm SO_2 in the flue gas, the conversion occurring during the short-time reactions of all the sorbents studied appears to be the dominant conversion, with incremental reactions occurring at long times.

The gas-solid reaction in the presence of equilibrium moisture on the sorbent surface is possibly controlled by the effective surface area of the sorbent. Increasing sorbent conversion reduces the rate of additional conversion, probably because of product precipitation on the reactive surface. The instantaneous conversion of a high-surface-area sorbent is high, but additional conversion is incremental by comparison when 5,000 ppm SO_2 is in the flue gas. With lower SO_2 contents in the flue gas, the instantaneous reaction is less significant than in the high- SO_2 cases, but the additional

conversion is more significant at the low SO_2 levels than at the high levels. The conversions of the high-surface-area $\text{Ca}(\text{OH})_2$ and the $\text{Ca}(\text{OH})_2$ /fly ash sorbent are approximately the same at all conditions, implying that the sorbent conversion is controlled by the dispersion of Ca throughout this surface area. Such a mechanism would result in:

- Higher SO_2 capture on high-surface-area sorbents compared to low-surface-area sorbents.
- An inverse relationship, for a given surface area, between the Ca content of sorbents and their conversions.
- High-sorbent conversions for short-time reactions, which occur when the sorbent surface area is not blocked by the formation of a product layer, followed by incremental increases in conversion for longer-time reactions, when the sorbent surface area has been reduced by product layer formation.

Figure 3-5 presents a comparison between the m^2 sorbent/mole $\text{Ca}(\text{OH})_2$ and sorbent conversion in 5,000-ppm SO_2 flue gas when the sorbent contains moisture in equilibrium with flue gas relative humidity. The $\text{Ca}(\text{OH})_2$ /fly ash and $\text{Ca}(\text{OH})_2$ sorbents fall approximately on the same curves, implying that the dispersion of the $\text{Ca}(\text{OH})_2$ over the sorbent surface area is more important than the quantity of $\text{Ca}(\text{OH})_2$ applied.

3.2.2 Sorbents with Initial Free Moisture

Figures 3-6, 3-7, and 3-8 present the results obtained using $\text{Ca}(\text{OH})_2$ /fly ash sorbent with an initial free moisture in 1,000-ppm SO_2 for 10, 60, and 120 s. The results shown are for work performed at 0-, 54- to 64-, and 80- to 91-percent relative humidity. For all cases shown, the sorbent conversion increases with increasing moisture content and increasing flue-gas relative humidity.

At 0-percent relative humidity, the magnitude of the sorbent conversions attained is not high, so that while the beneficial effect of initial free moisture is clearly visible, the slope of the increase is less certain than it appears on the plots. At the intermediate relative humidity, the effect of initial free

Figure 3-5. Effect of Ca dispersion on sorbent conversion (5,000-ppm SO₂ in flue gas, 70 °C, 1.0-percent initial moisture on Mississippi Ca(OH)₂, 3.5 percent on Ca(OH)₂/fly ash, 60- to 67-percent relative humidity in flue gas).

Figure 3-6. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (1,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction).

Figure 3-7. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (1,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction).

Figure 3-8. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (1,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction).

moisture levels off above ~25-percent initial free moisture in the 60-s plot, and, anomalous data notwithstanding, in the 10-s plot as well. In the 120-s plot, the conversion of sorbent containing 3.5-percent moisture is not likely as great as the data present, and the conversions attained at the higher moisture contents are essentially independent of the moisture content. At high relative humidity, the sorbent conversion increases greatly with increasing initial free moisture content for all reaction times.

Sorbents with high initial free moisture contents were not expected to dry completely in the short (10-s) reaction time, negating the beneficial effect of the initial free moisture. The increase in sorbent conversion with increasing initial free moisture at the 10-s reaction time was still significant for all relative humidities, indicating that the initial free moisture promoted sorbent reactivity. At high initial free moisture contents, moisture was expected to be lost from the sorbent surface and to absorb onto the sand during the sorbent preparation process. The data taken at 55- to 65-percent relative humidity contain points at which this water loss may have occurred (~50-percent initial free moisture). Loss of moisture prior to the reaction could explain why the increase in sorbent conversion is not as significant at the high-moisture content than at the lower levels, although the intermediate-moisture results support the trend that conversion levels off with increasing moisture.

The initial free moisture may possibly evaporate very rapidly at the lower relative humidities, resulting in high instantaneous conversion of the sorbent, but blockage of the surface area by product and limited reaction because of equilibrium moisture after the sorbent has dried. Also, the evaporation rate at the low relative humidities possibly is competitive with the rate of dissolved SO_2 migration within the initial free moisture, resulting in a saturated liquid phase and limited SO_2 absorption into the free moisture. At the higher relative humidity, the free moisture remains on the particle for longer time periods, resulting in increased H_2O available for SO_2 absorption.

Figures 3-9 through 3-14 present the results using sorbents with initial free moisture in 5,000-ppm SO_2 . Neither the $\text{Ca}(\text{OH})_2$ /fly ash sorbent nor the $\text{Ca}(\text{OH})_2$ sorbents reacting in 5,000-ppm flue gas showed the expected significant increase in conversion with increasing initial free moisture content. The conversion increase of the $\text{Ca}(\text{OH})_2$ sorbents with increasing initial free moisture content is not

Figure 3-9. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 58- to 63-percent relative humidity).

Figure 3-10. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 58- to 68-percent relative humidity).

Figure 3-11. Conversion of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction, 58- to 62-percent relative humidity).

Figure 3-12. Conversion of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 56- to 66-percent relative humidity).

Figure 3-13. Conversion of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 58- to 69-percent relative humidity).

Figure 3-14. Conversion of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (5,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction, 58- to 64-percent relative humidity).

significant, and within the data spread the conversion can be considered essentially constant with increasing initial free moisture content of the moderate-surface-area Ca(OH)_2 . Conversion of the highest-surface-area Ca(OH)_2 decreases with increasing initial free moisture content of the sorbent, whereas the conversion of the low-surface-area Ca(OH)_2 increases with increasing initial free moisture content.

These results indicate that, for Ca(OH)_2 , the presence of initial free moisture on the sorbent surface interferes with the reaction occurring by the equilibrium-moisture mechanism on the sorbent surface. For the high-surface-area materials, the surface reaction occurring with the equilibrium moisture is significant and results in high sorbent conversions. The addition of free moisture reduces the sorbent surface area available for equilibrium-type reaction, and after the free moisture has evaporated, the product formed blocks the sorbent surface area and continues to inhibit the equilibrium-moisture reaction. Whereas the reaction is very fast in the presence of free moisture, the reaction occurring after free moisture evaporation is greatly reduced by the surface products, consequently reducing the net benefit of adding free moisture to the high-surface-area Ca(OH)_2 . The addition of free moisture increases the sorbent conversion of the low-surface-area Ca(OH)_2 , in which the equilibrium moisture conversion is not significant, the conversion of all Ca(OH)_2 sorbents clearly is approximately the same when large quantities of initial free moisture are added. This result implies that the reaction due to free moisture is independent of sorbent surface area and that overall conversion in the presence of significant quantities of free moisture is dominated by the wet-reaction mechanism.

For the Ca(OH)_2 /fly ash sorbent, the conversions at low-moisture contents are significantly greater in the 5,000-ppm flue gas than for the 1,000-ppm flue gas for both the 10- and 60-s reactions at 56- to 68-percent relative humidity. The conversions at higher sorbent moisture contents are approximately equal between the 5,000- and 1,000-ppm SO_2 flue gas. An instantaneous reaction appears to occur when 5,000-ppm SO_2 is in the flue gas. Upon completion of this reaction, additional sorbent conversion, with increasing reaction time or increasing moisture content, provides incremental additional conversion. The instantaneous reaction with 1,000 ppm SO_2 , is not significant, so significant

additional conversion can be accomplished by increasing the reaction time or moisture content of the sorbent.

3.2.3 Comparison: Additive Model vs. Experiment

An expression describing the effect of excess moisture on the conversion of damp sorbent is presented below:

$$\frac{\Delta SO_2}{Ca} = \frac{D_{SO_2K}(P_{SO_2})}{D_{H_2OK}(P_{H_2O}^* - P_{H_2O})} \left(\frac{\Delta H_2O}{Ca} \right) \quad 3-10$$

The total conversion of the sorbent is the combination of the reactions occurring because of the moisture in excess of the equilibrium (with the flue gas relative humidity) quantity and the reaction occurring due to moisture in equilibrium with the flue gas relative humidity. The Additive Model assumes that excess moisture on the sorbent does not interfere with the equilibrium-moisture reaction. To predict the sorbent's total conversion with the Additive Model, conversion values from equilibrium-moisture studies must be added to the conversion predicted because of the excess moisture on the sorbent.

Comparisons of theoretical and observed conversions of solids with initial free moisture for various conditions of SO₂ concentration, relative humidity, and contact time are presented in Figures 3-15 through 3-20. The Additive Model correctly predicts the conversion of the Ca(OH)₂/fly ash sorbent at 0-percent relative humidity in 1,000-ppm SO₂ flue gas for 60-s reaction. At these conditions, the effect of the equilibrium-moisture reaction is nearly negligible, and the sorbent conversion increases linearly with increasing moisture content. For the other conditions presented, the Additive Model consistently overpredicts the sorbent conversion at high-sorbent-moisture contents. At low initial moisture contents, the observed effect of free moisture is small compared with the equilibrium-moisture

Figure 3-15. Comparison of theoretical and observed conversions of Ca(OH)_2 /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction, 55- to 65-percent relative humidity).

Figure 3-16. Comparison of theoretical and observed conversions of Ca(OH)_2 /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 0-percent relative humidity).

Figure 3-17. Comparison of theoretical and observed conversions of Ca(OH)_2 /fly ash sorbent with initial free moisture (Additive Model, 1,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 80- to 90-percent relative humidity).

Figure 3-18. Comparison of theoretical and observed conversions of Ca(OH)_2 sorbents with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 10-s reaction, 80- to 90-percent relative humidity).

Figure 3-19. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 60-s reaction, 80- to 90-percent relative humidity).

Figure 3-20. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (Additive Model, 5,000-ppm SO_2 in flue gas, 70 °C, 120-s reaction, 55- to 60-percent relative humidity).

reaction. At these low-moisture contents, the Additive Model is essentially the equilibrium-moisture conversion. For high free moisture contents, the overpredictions are usually less than the equilibrium-moisture contribution to the overall predicted conversion, implying that the effect of free moisture is correctly approximated, but not the effect of the wet reaction on the equilibrium-moisture reaction. The results of the 5,000-ppm study with $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture do not fall into this category. The Additive Model grossly overpredicts the sorbent utilization, implying that the effect of initial free moisture is not as significant as expected with the $\text{Ca}(\text{OH})_2$ /fly ash sorbent at these conditions.

The assumption appears to be erroneous that the initial free moisture on the surface of the sorbents does not interfere with the equilibrium-moisture reaction mechanism, which is the basis for the Additive Model. Significant quantities of moisture on the sorbent surface significantly reduce the surface area available for equilibrium-moisture reaction, and the equilibrium-moisture reaction likely does not begin until significant amounts of the free moisture have evaporated and the product has blocked the sorbent surface.

In the Additive Model, the sorbent conversion expected for a sorbent reacting in equilibrium moisture is added to the conversion predicted because of the initial free moisture. However, the model probably could be made more accurate by adjusting the equilibrium-moisture component to account for the reduced surface area and reduced reaction time available. Because the model correctly predicts sorbent conversions when either the free-moisture or equilibrium-moisture reactions are dominant, properly adjusting the 2 additive portions probably will provide accurate predictions.

3.2.4 Comparison: Interactive Model vs. Experiment

The Interactive Model uses the same expression as the Additive Model to account for sorbent conversion with free moisture on the sorbent surface. The difference between the 2 lies in the relationship between the equilibrium-moisture mechanism and the wet-sorbent mechanism. In both models, the predictions accounting for the wet and equilibrium-moisture effects are additive, although the Additive Model assumes that excess moisture does not alter the extent of reaction occurring by the

equilibrium-moisture pathway, whereas the Interactive Model assumes that the equilibrium-moisture reaction does not occur with free moisture on the sorbent surface.

The Interactive Model also assumes that the rate of sorbent conversion by the equilibrium-moisture mechanism is a function of the amount of product present on the sorbent surface.

The Interactive Model requires expressions for the rate of conversion by the equilibrium-moisture mechanism as a function of sorbent conversion. The plots used to generate these expressions are presented in Figures 3-21 and 3-22. The expressions are presented in Table 3-2. To use the Interactive Model, the conversion attained by the wet-reaction mechanism is noted and the expressions presented in Table 3-2 are manipulated to determine the time required to attain this conversion by the equilibrium-moisture mechanism (t_0). The free moisture is then assumed to evaporate instantly from the sorbent surface upon introduction of the flue gas, so that the time available for reaction by the equilibrium-moisture mechanism is approximately the original reaction time (t). The rate expressions presented in Table 3-2 are evaluated twice, at time = ($t_0 + t$) and time = (t_0). The conversion expected

TABLE 3-2. RATE OF SORBENT CONVERSIONS FOR INTERACTIVE MODE

Sorbent Type	ppm SO ₂ in Flue Gas	RH [%]	Value of Slope	Value of Intercept
Ca(OH) ₂ /Fly Ash	1,000	0	3.62×10^{-2}	-2.36×10^{-2}
Ca(OH) ₂ /Fly Ash	1,000	51-64	0.19	-0.14
Ca(OH) ₂ /Fly Ash	1,000	80-90	0.26	-0.11
Ca(OH) ₂ /Fly Ash	5,000	51-64	3.64×10^{-2}	0.18
Ca(OH) ₂ "A"	5,000	58-67	7.32×10^{-2}	0.15
Ca(OH) ₂ "B"	5,000	58-67	0.12	1.61×10^{-2}
Miss. Ca(OH) ₂	5,000	58-67	4.61×10^{-2}	5.38×10^{-2}

Figure 3-21. Determination of instantaneous sorbent conversion rate for $\text{Ca}(\text{OH})_2$ sorbents (5,000-ppm SO_2 in flue gas, 70 °C 55- to 65-percent relative humidity).

Figure 3-22. Determination of instantaneous sorbent conversion rate for $\text{Ca}(\text{OH})_2$ /fly ash sorbent (1,000-, 5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity).

at t_0 is then subtracted from that expected at $t_0 + t$ to determine the conversion occurring by the equilibrium-moisture mechanism after the wet reaction is complete.

Figures 3-23 through 3-28 present comparisons between the conversions predicted by the Interactive Model and the experimentally observed conversions with 1,000- and 5,000-ppm SO_2 at 55- to 65-percent relative humidity and 10-s and 120-s contact times. The model underpredicts $\text{Ca}(\text{OH})_2/\text{fly}$ ash conversion with 1,000-ppm SO_2 in the flue gas at long times at 55- to 65-percent relative humidity. At these conditions, the equilibrium-moisture conversions are significant. The Additive Model overpredicted the system performance at these conditions, whereas the Interactive Model, which incorporates into the final result a significantly lower contribution due to the equilibrium-moisture reaction, underpredicted system performance. The wet reaction apparently influences the equilibrium-moisture reaction and the model has overcompensated for this effect.

The model flaw may be attributed to inaccuracy in determining the instantaneous rate of sorbent conversion. In Figures 3-21 and 3-22, the best-fit lines do not always accurately represent the data. Errors in the projected slopes of these lines will influence the expected equilibrium-moisture conversion used in the Interactive Model.

The Interactive Model overpredicts, as does the Additive Model, the attained conversions using $\text{Ca}(\text{OH})_2/\text{fly}$ ash sorbent in 5,000-ppm SO_2 flue gas. The overprediction apparently is generated within the expression for conversion as a function of initial moisture content, which has proven reliable with the other sorbents and with the $\text{Ca}(\text{OH})_2/\text{fly}$ ash sorbent at low- SO_2 content. The wet reaction occurring on $\text{Ca}(\text{OH})_2/\text{fly}$ ash with high- SO_2 contents is inhibited, falling outside the gas-phase controlled pattern.

Considering the $\text{Ca}(\text{OH})_2$ sorbents, the Additive Model slightly overpredicts the conversion of the high-surface-area sorbent and underpredicts the conversion of the low-surface-area sorbent at high moisture contents, independent of reaction time. The high-surface-area sorbent achieved high conversion because of the equilibrium-moisture reaction, which was inhibited by the wet

Figure 3-23. Interactive Model of Ca(OH)_2 /fly ash conversion (1,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).

Figure 3-24. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (1,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).

Figure 3-25. Interactive Model of $\text{Ca}(\text{OH})_2$ /fly ash conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).

Figure 3-26. Interactive Model of Ca(OH)₂/fly ash conversion (5,000-ppm SO₂ in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).

Figure 3-27. Interactive Model of $\text{Ca}(\text{OH})_2$ conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 10-s reaction).

Figure 3-28. Interactive Model of $\text{Ca}(\text{OH})_2$ conversion (5,000-ppm SO_2 in flue gas, 70 °C, 55- to 65-percent relative humidity, 120-s reaction).

reaction to a greater degree than the Interactive Model allowed. The low-surface-area $\text{Ca}(\text{OH})_2$ achieved minimal conversion due to the equilibrium-moisture reaction, but the Interactive Model overcompensated for the reduction in this reaction.

3.2.5 Conversion of $\text{Ca}(\text{OH})_2$ /Fly Ash Sorbent by Reaction with CO_2

The $\text{Ca}(\text{OH})_2$ /fly ash sorbent contained CO_2 in the form of carbonate prior to reaction with the 1,000-ppm- SO_2 , 10-percent- CO_2 flue gas. The initial carbonate content of the sorbent was 2×10^{-4} moles CO_2 /mol Ca. Significant additional CO_2 capture was not discovered for short- or long-time reactions in the presence of initial free moisture on the sorbent surface (Figure 3-29). Within the ability to experimentally determine CO_2 capture on the sorbent, no CO_2 capture occurred, and more importantly, the Ca-conversion by CO_2 was much lower than conversion by SO_2 with 10-percent CO_2 and 1,000-ppm SO_2 in the flue gas.

3.2.6 Conclusions

Based on the aforementioned results, several conclusions may be drawn:

- With low-concentration SO_2 , the addition of initial free moisture to $\text{Ca}(\text{OH})_2$ /fly ash sorbents significantly increases their conversion over that attained without excess moisture.
- With high-concentration SO_2 , the addition of initial free moisture to $\text{Ca}(\text{OH})_2$ /fly ash sorbents does not increase significantly, and may decrease slightly, the sorbent conversion in comparison with that attained without excess moisture.
- The conversion of low-surface-area $\text{Ca}(\text{OH})_2$ increases with increasing initial free moisture content of the sorbent, whereas the conversion of high-surface-area $\text{Ca}(\text{OH})_2$ remains the same or decreases slightly with the addition of initial free moisture.
- The reaction between $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture and low concentrations of SO_2 is gas-phase, mass-transfer-controlled until the moisture has evaporated from the sorbent surface.

Figure 3-29. Reaction of Ca(OH)₂/fly ash sorbent with CO₂ (1,000-ppm SO₂ in flue gas, 70 °C, 55- to 65-percent relative humidity).

- The reaction between Ca(OH)_2 sorbent with initial free moisture and high concentrations of SO_2 is gas-phase, mass-transfer-controlled until the moisture has evaporated from the sorbent surface.
- The reaction between Ca(OH)_2 /fly ash sorbent with initial free moisture and high concentrations of SO_2 is not gas-phase, mass-transfer-controlled.
- Sorbent conversion because of wet reaction is not a strong function of sorbent surface area.
- Overall conversion of Ca(OH)_2 /fly ash sorbent with initial free moisture at times ranging from 10-120 s is a stronger function of relative humidity (sorbent drying time) than of SO_2 content in the flue gas.
- The reaction occurring between Ca(OH)_2 /fly ash and Ca(OH)_2 sorbents in the presence of initial free moisture is a combination of the equilibrium-moisture reaction and the wet reaction.
- The conversion of the Ca(OH)_2 and Ca(OH)_2 /fly ash sorbents because of wet reactions affects the surface properties of the sorbents and the extent of equilibrium-moisture conversion that occurs upon evaporation of the free moisture.
- The equilibrium-moisture conversion of the Ca(OH)_2 and Ca(OH)_2 /fly ash sorbents increases with increasing surface area/mole Ca(OH)_2 of the sorbent.
- Sorbents that attain high conversions because of equilibrium-moisture reaction do not show increased reactivity at long times with initial free moisture, although the wet reaction occurs much more quickly than the equilibrium-moisture reaction.
- Reaction can be adequately modeled between Ca(OH)_2 /fly ash sorbent, with initial free moisture and low-concentration SO_2 and Ca(OH)_2 sorbents with initial free moisture and high-concentration SO_2 , assuming that the wet reaction is gas-phase, mass-transfer-controlled and that the products of the wet reaction affect the progress of the equilibrium-moisture reaction.

- Up to 10-percent CO_2 in flue gas containing 1,000-ppm SO_2 does not inhibit the sorbent- SO_2 reaction.

3.3 SHORT TIME DIFFERENTIAL REACTOR RESULTS AND DISCUSSION

The Short Time Differential Reactor (STDR) previously used to identify a rate-limiting step for the reaction of dry Ca(OH)_2 with SO_2 was used for testing solids with free moisture. Two types of sorbents were used to study the effect of initial free moisture on the conversion with SO_2 : Ca(OH)_2 physically mixed with fly ash and Ca(OH)_2 reacted with fly ash. Even small amounts of free moisture are known to deteriorate the handling properties of Ca(OH)_2 , which tends to agglomerate and become a paste unsuitable for DSI. Because previous work on fundamental mass-transfer mechanisms indicated that the conversion of Ca(OH)_2 increased with increases in initial moisture on the solids, an alternative means of moisture delivery was used. The modified STDR was used to simulate the moist-duct injection (MDI) moisture delivery system. To simulate the MDI, 6 mg of dry Mississippi Ca(OH)_2 was physically mixed with 20 or 30 mg of moist fly ash prepared in the manner described in the previous section. (Actual TGA-Detected moisture contents of a commercial Mississippi Ca(OH)_2 was 0.55 wt percent.) Meredosia fly ash was used for MDI experiments.

Another type of sorbent tested was chemically reacted fly ash with Ca(OH)_2 . These sorbents were produced by slurring fly ash with reagent grade Ca(OH)_2 at varying weight ratios, elevated temperature, and prolonged slurring time. Previous work indicated that using ground rather than unground fly ash can increase significantly the reactivity of sorbent for any given slurring conditions. Therefore, ground fly ash was used to produce some Ca(OH)_2 /fly ash sorbents. Sorbents produced by slurring fly ash with Ca(OH)_2 (calcium silicate sorbents) were capable of holding 20-30 wt percent moisture without significant deterioration of handling properties.

Several sorbents produced by reacting fly ash with Ca(OH)_2 were used. The 3 fly ashes used throughout this study, Clinch River, Meredosia, and Beverly result from combustion of eastern bituminous coal. For some sorbents, the fly ash was ground prior to reaction with Ca(OH)_2 . The weight

ratio of fly ash to Ca(OH)_2 was varied to produce sorbents with varying surface areas. Table 3-3 shows the structural properties of fly ashes used to produce sorbents.

TABLE 3-3. STRUCTURAL PROPERTIES OF FLY ASHES USED TO PRODUCE FLY ASH/ Ca(OH)_2 SORBENTS

Fly Ash Source	Fly Ash Type	Surface Area [m^2/g]	Pore Volume [cm^3/g]	Median Pore Size [$\text{\AA}$]	Median Particle Size [μm]
Meredosia	U ^a	1.2	0.003	91	11.10
Meredosia	G ^b	6.8	0.027	159	2.00
Clinch River	U	2.2	0.005	92	12.05
Clinch River	G	5.6	0.020	145	4.96
Beverly	U	0.7	0.001	-	12.70
Beverly	G	7.6	0.026	-	7.20

^aU = Unground fly ash

^bG = Ground fly ash

As indicated in Table 3-3, the structural properties of Meredosia, Clinch River, and Beverly fly ashes were similar before grinding. Grinding significantly increased surface area and porosity for 3 of them.

Both ground and unground fly ashes were used to produce sorbents. These sorbents' slurring conditions and structural properties are presented in Table 3-4. Sorbents with similar structural properties were produced by slurring ground Meredosia or ground Clinch River fly ash for 3 h at 90 °C, using a 3:1 weight ratio of fly ash to Ca(OH)_2 . The surface area and pore volume for Meredosia- and Clinch River-based sorbents produced at the aforementioned conditions were 27 m^2/g and 0.122 cm^3/g , and 30 m^2/g and 0.132 cm^3/g , respectively. Sorbent produced by slurring ground Beverly fly ash and Ca(OH)_2 at the same conditions had somewhat lower surface area and pore volume (18.6 m^2/g and 0.082 cm^3/g). All sorbents produced by slurring ground fly ash and Ca(OH)_2 had higher surface area and pore volume than the sorbent produced with unground fly ash. For a given source and type of fly ash, increasing the weight ratio of fly ash to Ca(OH)_2 resulted in a sorbent with greater surface area and pore volume.

Scanning Electron Microscope (SEM) photomicrographs of "as-received" and ground Clinch River fly ash are shown in Figures 3-30 and 3-31, respectively. The typical microscope field of "as-received" Clinch River fly ash in Figure 3-30 shows spherical particles with smooth surfaces. The median particle size of this sample measured by X-ray sedimentation (Sedigraph) was 12.05 μm .

As Figure 3-31 shows, grinding changed significantly the morphology of Clinch River fly ash. All particles visible in the SEM field are smaller than 10 μm , and most have an irregular shape. The Sedigraph method yielded a median particle size of 4.96 μm .

TABLE 3-4. STRUCTURAL PROPERTIES OF FLY ASH/ $\text{Ca}(\text{OH})_2$ SORBENTS

Fly Ash Source	Fly Ash Type	Slurrying		Fly Ash/ $\text{Ca}(\text{OH})_2$ Weight Ratio [g/g]	Sorbent		
		Time [h]	Temperature [$^{\circ}\text{C}$]		Surface Area [m^2/g]	Pore Vol. [cm^3/g]	Median Pore Size [$\text{\AA}$]
Meredosia	U ^a	8	90	3:1	6.9	0.039	225
Meredosia	G ^b	3	90	3:1	27.4	0.122	178
Meredosia	G	3	90	2:1	17.5	0.100	229
Meredosia	G	3	90	1:1	16.6	0.132	239
Meredosia	G	8	90	3:1	33.2	0.167	201
Meredosia	G	24	90	3:1	47.0	0.213	180
Clinch River	G	3	90	3:1	30.2	0.132	174
Beverly	G	3	90	3:1	18.6	0.082	-

U = Unground fly ash

G = Ground fly ash

3.3.1 Effect of Sorbent Type

Moist sorbents were exposed to 2,000-ppm SO_2 in the STDR operated at 11 $^{\circ}\text{C}$ approach to saturation, which corresponded to approximately 60-percent relative humidity. The contact time in the STDR varied from 0.5-5 s with occasional experiments performed at 60 and 400 s. Baseline experiments were done first with 6 mg of dry Mississippi $\text{Ca}(\text{OH})_2$ only, and then with 6 mg of

Figure 3-30. SEM photomicrograph of "as-received" Clinch River fly ash sample, x 5,000.

Figure 3-31. SEM photomicrograph of ground Clinch River fly ash sample, x 5,000.

dry Mississippi $\text{Ca}(\text{OH})_2$ physically mixed with 20 mg of dry Meredosia fly ash. The results are shown in Figure 3-32. No significant difference was detected (except for an outlying data point for 3-s contact time) in conversion of dry $\text{Ca}(\text{OH})_2$ and dry $\text{Ca}(\text{OH})_2$ physically mixed with dry fly ash.

Following baseline tests, solids were prepared by physically mixing $\text{Ca}(\text{OH})_2$ and moist Meredosia fly ash to yield 3 levels of initial free moisture: 3.9, 12.4, and 18.3 percent. The results are presented in Figure 3-32, which presents the conversion of calcium as a function of contact time. Baseline results for dry $\text{Ca}(\text{OH})_2$ also are shown in Figure 3-32 for comparison. Higher conversions were measured for sorbents with increased levels of initial free moisture than for dry $\text{Ca}(\text{OH})_2$. For a given contact time, the conversion generally increased with increased initial free moisture contents of solids. The results of additional experiments performed at 60- and 400-s contact times also are shown in Figure 3-32. The effect of initial free moisture was more pronounced at longer contact times (60 and 400 s). For example, the conversion was 2.18 and 4.72 percent at 5-s contact time for dry Mississippi $\text{Ca}(\text{OH})_2$ and the conversion was 7.27 and 36.3 percent at 400-s contact time for a physical mixture of dry Mississippi $\text{Ca}(\text{OH})_2$ and moist Meredosia fly ash with 18.3 percent initial free moisture.

In the next series of experiments, chemically reacted fly ash with $\text{Ca}(\text{OH})_2$ was used. The sorbent was microwaved after slurring to ensure dryness. Baseline experiments were done first with dry solids produced by slurring ground Clinch River fly ash and $\text{Ca}(\text{OH})_2$ (3:1 weight ratio, 90 °C, 3 h, 30.2 m^2/g overall dry-sorbent surface area). Considerably higher conversions were measured for dry sorbent produced by slurring $\text{Ca}(\text{OH})_2$ and ground fly ash than for dry $\text{Ca}(\text{OH})_2$ alone. For example, following the 5 s contact time the conversion of dry fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was 7.35 percent, compared with 2.18 percent for dry Mississippi $\text{Ca}(\text{OH})_2$.

Following baseline tests, solids were prepared by re-wetting chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent to yield 3 levels of initial free moisture: 8.5, 12, and 40 percent. The results are shown in

Figure 3-32. Baseline tests with dry Meredosia fly ash added to dry Mississippi Ca(OH)_2 (STDR, 2,000-ppm SO_2 , 60-percent relative humidity).

Figure 3-33. Ca(OH)_2 physically mixed with Meredosia fly ash (STD, 2,000-ppm SO_2 , 60-percent relative humidity).

Figure 3-34, which presents the conversion of calcium as a function of contact time with 2,000-ppm SO_2 at approximately 60-percent relative humidity (11 °C approach to saturation). For each initial moisture content tested, the conversion increased with increased contact time. Except for 0.3-s contact time, the conversion after any contact time increased with increased initial free moisture contents.

The comparison of conversions measured for 2 types of sorbent is shown in Figure 3-35. Both sorbents had a comparable amount of initial free moisture: 12 percent in the chemically reacted sorbent and 12.4 percent in the physically mixed fly ash and $\text{Ca}(\text{OH})_2$. For the contact time range tested, chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent consistently had higher conversions than physically mixed fly ash/ $\text{Ca}(\text{OH})_2$ sorbent. The difference between the 2 sorbents was more pronounced for longer contact times (60 and 400 s). Notably, the 2 sorbents tested had different surface areas (32 m^2/g overall for chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and 17 m^2/g for Mississippi $\text{Ca}(\text{OH})_2$ used for physical mixture). However, preliminary results with a physical mixture of fly ash and $\text{Ca}(\text{OH})_2$, using in-house-produced 70- m^2/g surface area $\text{Ca}(\text{OH})_2$, indicate only marginally increased conversion because of the increased specific surface area of $\text{Ca}(\text{OH})_2$ (5.2- and 4.7-percent conversion after 5-s contact time when 70 and 17 m^2/g $\text{Ca}(\text{OH})_2$ was used for physical mixture, respectively).

In Figure 3-36, more data are presented comparing the effect of the initial free moisture on the conversion of 2 sorbents under consideration. The physical mixture of fly ash/ $\text{Ca}(\text{OH})_2$ was tested with up to approximately 20-percent initial free moisture. Chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ was tested with up to approximately 40-percent initial free moisture. Attempts were unsuccessful to produce a physical mixture of $\text{Ca}(\text{OH})_2$ and fly ash with initial free moisture contents above 20 percent. Figure 3-36 presents calcium conversion after 5-s contact time in the STDR with 2,000-ppm SO_2 and approximately 60-percent relative humidity (11 °C approach to saturation). For any initial free moisture tested, reacted $\text{Ca}(\text{OH})_2$ /fly ash sorbent revealed higher conversion than physically mixed $\text{Ca}(\text{OH})_2$ and

Figure 3-34. The effect of initial free moisture on the reactivity of chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000-ppm SO_2 , 60-percent relative humidity).

Figure 3-35. Reactivity comparison for physically mixed and chemically reacted fly ash/Ca(OH)₂ (STDR, 2,000-ppm SO₂, 60-percent relative humidity, 12-14.7 percent at limited moisture contents).

Figure 3-36. The effect of an initial moisture on the reactivity of physically mixed and reacted fly ash/ Ca(OH)_2 (STDR, 2,000-ppm SO_2 , 60-percent relative humidity, 5-s contact time).

fly ash. The 5-s conversion of reacted $\text{Ca}(\text{OH})_2$ /fly ash appears to level off at 30-percent initial free moisture contents.

3.3.2 Combined Effect of the Amount of Initial Free Moisture and Sorbent Surface Area

Results for Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent indicate that increasing the amount of initial free moisture up to 30-40 weight percent results in increased calcium conversion with SO_2 . This range of the initial free moisture content has been expanded up to 60 weight percent.

Figure 3-37 presents results for the sorbent produced by slurring ground Meredosia fly ash and $\text{Ca}(\text{OH})_2$ for 3 h (sorbent's surface area of $27.4 \text{ m}^2/\text{g}$). Conditions in the reactor were 60-percent relative humidity (11°C approach to saturation) and 2,000-ppm SO_2 . The initial free moisture of the sorbent was varied from equilibrium (no moisture added) up to 60 weight percent. Maximum conversion, measured for longer residence times (3 and 5 s) of $27.4\text{-m}^2/\text{g}$ fly ash/ $\text{Ca}(\text{OH})_2$ sorbent in the STDR, occurred for solids with 30-weight percent initial moisture. The effect was rather weak of initial free moisture at short (0.5- and 1-s) residence times in the STDR. The solid line in Figure 3-37 represents the conversion of equilibrium and moist solids increased as residence times in the STDR increased.

The same conditions in the STDR were used to test the effect of initial free moisture on reactivity of ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with $33.2\text{-m}^2/\text{g}$ surface area (sorbent preparation conditions: weight ratio = 3:1, 90°C , 8 h). Figure 3-38 presents the results for equilibrium to 60 weight percent initial free moisture range. For this sorbent, the maximum conversion was measured at 40 weight percent initial free moisture. The results for $33.2\text{-m}^2/\text{g}$ sorbent, with equilibrium amount of initial free moisture only, are represented by the solid line in Figure 3-38. For all residence time/initial free moisture conditions tested, the addition of moisture resulted in increased conversion with SO_2 compared with levels measured for the sorbent with equilibrium moisture. Similar to $27.4\text{-m}^2/\text{g}$ sorbent (Figure 3-37), the difference between conversions measured for equilibrium and moist solids increased as residence time in the STDR increased. However, a stronger effect occurred for initial free

Figure 3-37. Effect of initial free moisture on the reactivity with SO_2 of $27.4\text{-m}^2/\text{g}$ sorbent (ground Mercedosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).

Figure 3-38. Effect of initial free moisture on the reactivity with SO_2 of $33.2\text{-m}^2/\text{g}$ sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).

moisture at short residence time than for 27.4-m²/g sorbent. Maximum conversions measured for 5-s residence time in the STDR were 15.2 and 17.5 percent, for 27.4 and 33.2 m²/g, respectively.

Another fly ash/Ca(OH)₂ sorbent, which was tested in the STDR operated at 60-percent relative humidity with 2,000-ppm SO₂, was prepared by slurring ground Meredosia fly ash with Ca(OH)₂ at a weight ratio of 3:1, at 90 °C for 24 h, and sorbent surface area of 47 m²/g. Figure 3-39 shows reactivity results for this sorbent with an initial free moisture content ranging from equilibrium to 60-weight percent. For all residence time/initial free moisture conditions tested, the addition of moisture resulted in increased conversion with SO₂ compared with levels measured for the equilibrium-moisture sorbent. Maximum conversion of 25.1 percent following 5-s contact time with SO₂ was measured for a sorbent with an initial free moisture of 50 weight percent.

Data presented in Figures 3-37 to 3-39 were combined with those for sorbent produced by slurring unground Meredosia fly ash with Ca(OH)₂ at the same weight ratio of 3:1 (slurring conditions: 90 °C, 8 h) and having a surface area of only 6.9 m²/g. Figure 3-40 shows conversions measured after 5-s contact time in the STDR, operated at 60 percent relative humidity and with 2,000-ppm SO₂. Initial free moisture content tested ranged from equilibrium to 60 percent. Maximum conversion with SO₂ measured for each sorbent increased as sorbent-specific surface area increased. For 6.9-, 27.4-, 33.2-, and 47.0-m²/g sorbents tested, the corresponding maxima were 12.3, 15.2, 17.5, and 25.1 percent respectively. The initial free moisture content, for which the maximum conversion for a given sorbent was measured, varied with the sorbent's specific surface area. The initial free moisture contents of the 4 aforementioned sorbents, for which the maximum conversion with SO₂ was measured, were 30, 30, 40, and 50 percent, respectively. The reactivity differential between 40- and 60-percent initial free moisture increased, resulting in a steeper slope between 40- and 60-percent initial free moisture, as the sorbent's surface area increased. For example, for 6.9- and 47.0-m²/g sorbents, the reactivity differentials between 40- and 60-weight percent were 1.7 and 12.9 percent, respectively. Table 3-5

Figure 3-39. Effect of initial free moisture on the reactivity with SO_2 of $47.0\text{-m}^2/\text{g}$ sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).

Figure 3-40. Effect of sorbent-specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60-percent relative humidity, 2,000-ppm SO_2).

compares the aforementioned data.

TABLE 3-5. EFFECT OF SPECIFIC SURFACE AREA ON REACTIVITY OF MOIST SORBENT WITH SO_2 (MEREDOSIA FLY ASH/ $\text{Ca}(\text{OH})_2$ WEIGHT RATIO OF 3:1, 90 °C SLURRYING)

Sorbent Surface Area [m ² /g]	Pore Volume [cm ³ /g]	Maximum Measured Conversion with SO_2 [percent] ^a	Corresponding Initial Free Moisture [weight percent]	Reactivity Differential [percent] ^b
6.9	0.039	12.3	30	1.7
27.4	0.122	15.2	30	-0.8
33.2	0.167	17.5	40	7.0
47.0	0.213	25.1	50	12.9

^aConversion after 5 s in the STDR, 60-percent relative humidity, 2,000-ppm SO_2

^bMeasured reactivity differential for sorbent with 40- and 60-percent initial free moisture

3.3.3 Effect of the Approach to Saturation

Experiments with equilibrium-moisture $\text{Ca}(\text{OH})_2$ indicated that conversion of $\text{Ca}(\text{OH})_2$ with an equilibrium amount of moisture increased as the approach to saturation decreased. Sorbents were produced by slurring ground Clinch River fly ash and $\text{Ca}(\text{OH})_2$ at the weight ratio of 3:1 at 90 °C for 3 h with sorbent-specific surface area of 30.2 m²/g and with 30-weight percent initial free moisture. Test results of these sorbents revealed weak effect of approach to saturation (2.8 °C to 22 °C approach) on conversion of the sorbent with SO_2 . When the sorbent with 30-weight percent initial free moisture was exposed to dry gas with 2,000 ppm SO_2 , conversion decreased for longer (3- and 5-s) contact times in the STDR, compared with conversion measured for moist gas. No decrease was measured for short (0.5- and 1-s) contact times in the STDR. These results are shown in Figure 3-41.

A sorbent produced with ground Meredosia fly ash was used to investigate the effect of the approach to saturation on the conversion of sorbents with 60-weight percent initial free moisture and with only equilibrium-moisture content. Ground Meredosia fly ash was slurried with $\text{Ca}(\text{OH})_2$ at a weight ratio of 3:1 at 90 °C for 3 h and sorbent-specific surface area of 27.4 m²/g. Figure 3-42 shows the results of experiments with the sorbent containing 60-weight percent initial free moisture. Similar to the results presented in Figure 3-41, only a very weak effect was detected of an approach to saturation

Figure 3-41. Effect of the approach to saturation on the reactivity of 30.2-m²/g sorbent with 30 weight percent initial free moisture (ground Clinch River fly ash/Ca(OH)₂ weight ratio of 3:1, 2,000-ppm SO₂).

Figure 3-42. Effect of the approach to saturation on the reactivity of 27.4-m²/g sorbent with 60 weight percent initial free moisture (ground Meredosia fly ash/Ca(OH)₂ weight ratio of 3:1; reactor: 2,000-ppm SO₂).

(2.8 to 22 °C range) on the conversion with 2,000-ppm SO₂ gas. No significant effect was detected of an approach to saturation on conversion with SO₂ for long (5-s) contact time in the STDR. At short (0.5- and 1-s) contact times, higher conversions were measured for sorbent exposed to dry gas than for sorbent exposed to humid gas.

Finally, conversion of the 27.4-m²/g sorbent with equilibrium moisture only was measured in the STDR with 2,000-ppm SO₂. Figure 3-43 presents the results of the approach to saturation, which varied from 2.8 to 22 °C, and for the dry gas. Conversion with SO₂ increased as approach to saturation decreased. Conversion measured after the contact with dry gas was less than 1 percent.

3.3.4 Effect of Fly Ash Source

Sorbents were produced using 2 different fly ashes to compare the effect of fly ash source on their reactivity. Both fly ashes (Clinch River and Meredosia) were ground to approximately the same extent prior to reacting them with Ca(OH)₂ at the same time/temperature conditions (3 h at 90 °C), and at the same fly ash-to-Ca(OH)₂ weight ratio of 3:1. The resulting sorbents developed similar specific surface areas of 30.2 and 27.4 m²/g using Clinch River and Meredosia fly ash, respectively. Both sorbents were loaded with moisture to yield 30 weight percent of initial free moisture content. The sorbents were then exposed to SO₂ in the STDR operated at 60-percent relative humidity (11 °C approach to saturation) and with 2,000-ppm SO₂. Figure 3-44 presents results for STDR contact times from 0.5 to 5 s. For a given contact time, no significant difference was detected in reactivity with SO₂ for the sorbents produced with the 2 fly ashes.

In the next step, both sorbents, with initial free moisture content varying from 10- to 60-weight percent, were reacted with SO₂. STDR results for 5-s contact time, shown in Figure 3-45, are similar to the results presented in Figure 3-44. For the aforementioned 2 fly ashes tested, fly ash source had no significant effect on sorbent reactivity with SO₂. The data points at approximately 5-weight percent initial free moisture represent conditions for "dry" sorbents at equilibrium with the gas. The slightly higher reactivity of sorbent produced with ground Clinch River fly ash in comparison with ground Meredosia fly ash may be a consequence of the former sorbent's somewhat higher specific surface

Figure 3-43. Effect of the approach to saturation on the reactivity of 27.4-m²/g sorbent with equilibrium moisture (ground Meredosia fly ash, Ca(OH)₂ weight ratio of 3:1; reactor: 2,000-ppm SO₂).

Figure 3-44. Effect of fly ash source on reactivity of sorbent with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 30-weight percent initial free moisture, 2,000-ppm SO_2 , 60-percent relative humidity).

Figure 3-45. Combined effect of fly ash source and initial free moisture content on sorbent's reactivity with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 2,000-ppm SO_2 , 60-percent relative humidity, 5-s contact time).

area. (For equilibrium sorbents, conversion increases with increasing surface area.)

For both sorbents, an optimum initial free moisture content was detected for maximum conversion with SO_2 at conditions tested in the STDR. For solids produced with ground Clinch River fly ash, the maximum conversion occurred with initial free moisture contents of 30- and 40-weight percent. For solids produced with Meredosia fly ash, the maximum conversion occurred at 30-weight percent initial free moisture content. This maximum conversion was approximately 15 percent for both sorbents after 5-s contact time in the STDR operated at 11 °C approach to saturation and with 2,000-ppm SO_2 .

3.3.5 Conclusions

The aforementioned results indicate that:

- At 2,000-ppm SO_2 and 60-percent relative humidity (11 °C approach to saturation), the presence of up to 30 percent initial free moisture significantly increased sorbent reactivity with SO_2 , compared with sorbent reactivity with equilibrium amount of moisture.
- For any initial free moisture content tested, chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was more reactive than physically mixed fly ash/ $\text{Ca}(\text{OH})_2$ sorbent.
- Maximum conversion for 5-s contact time in the STDR and 60-percent relative humidity (11 °C approach to saturation) was measured for sorbents with 30- to 50-weight percent initial free moisture.
- The conversion decreased when the initial free moisture increased beyond 30- to 50-weight percent.
- The initial free moisture content and corresponding level of maximum sorbent conversion with SO_2 varied with the surface area of the sorbent.
- Conversion of solids with initial free moisture was not affected by the approach to saturation in the STDR for short contact times of 0.5 and 1 s. With longer contact time of 5 s, conversion in the STDR increased with decreasing approach to saturation.
- For sorbents with comparable surface areas, fly ash source (2 fly ashes tested) did not have a significant effect on reactivity of solids with initial free moisture.

SECTION 4

ENHANCEMENT OF DRY-SORBENT INJECTION: OTHER TECHNIQUES

4.1 HYDRATION MODIFICATIONS

In the process of "CaO hydration," dry calcium hydroxide is produced by the adding sufficient amounts of water to chemically complete the hydration of CaO and account for water losses due to evaporation. The amount of water usually is limited by the need to have dry powder at the completion of hydration. The temperature of hydration can affect the efficiency of hydration and quality of product Ca(OH)_2 .

Several sorbents were produced to investigate the effect of temperature on the structural properties and sorbent reactivity with SO_2 under conditions typical for DSI. Hydrates discussed in this section were produced in a laboratory-scale hydrator consisting of a 0.4-L Pyrex beaker suspended in a constant-temperature oil bath. A mechanical stirrer was used to mix the water and CaO. Each hydration was conducted by loading 10 g of Mississippi CaO into the hydrator and allowing CaO to achieve thermal equilibrium in the bath. The stirrer was started, and a single addition of water was syringed rapidly into the hydrator at the desired molar ratio of $\text{H}_2\text{O}/\text{CaO}$. After 15 min, the hydration vessel was purged of remaining water vapor with nitrogen, leaving a thoroughly dry product. The amount of water used was 2.6 times the amount stoichiometrically required, and the temperature of solids and liquid was varied from 25 to 100 °C.

Table 4-1 presents structural properties of dry hydrated sorbents produced in the laboratory using Mississippi CaO. For the hydration parameters used, little effect was detected of solids temperature or of water temperature on the surface area and porosity. The surface area varied from 31 to 32 m^2/g and porosity from 0.23 to 0.31.

Each sorbent produced was characterized by thermogravimetry to measure the amount of surface moisture, chemically bound water, and recarbonation. The results are presented in Table 4-2.

TABLE 4-1. STRUCTURAL PROPERTIES OF DRY HYDRATED Ca(OH)_2 SORBENTS

Sorbent	Temperature		Stoichiometric Ratio [mol H_2O / mol CaO]	Specific Surface Area [m^2/g]	Porosity [-]
	Solids [$^{\circ}\text{C}$]	Water [$^{\circ}\text{C}$]			
Miss12	100	100	2.6	31	0.23
Miss13	100	25	2.6	32	0.28
Miss14	25	100	2.6	37	0.31
Miss15	25	25	2.6	36	0.30

The weight loss at 100, 545, and 700 $^{\circ}\text{C}$ was assumed to correspond to the amount of surface water, chemically bound water, and recarbonation, respectively. As evident from Table 4-2, the amount of surface water measured was always below 1-weight percent. The extent of hydration varied from 74 percent for sample prepared at 25/25 $^{\circ}\text{C}$ conditions (18.03-percent weight loss at 545 $^{\circ}\text{C}$) to 95 percent for sample prepared at 100/100 $^{\circ}\text{C}$ conditions (23.09-percent weight loss at 545 $^{\circ}\text{C}$). The weight loss resulting from the decomposition of recarbonated sorbent varied between 0.51-1.63 percent.

Sorbents produced during the hydration experiments were tested in the STDR operated at 11 $^{\circ}\text{C}$ approach to saturation (approximately 60-percent relative humidity), 2,000-ppm SO_2 , and 5-s contact time in the STDR. The conversion of sorbents varied from 3.6 to 4.7 percent after 5-s contact time in the STDR. From the limited amount of data available, no correlation was evident of reactivity with SO_2 to hydration conditions.

TABLE 4-2. THERMOGRAVIMETRIC CHARACTERIZATION OF DRY HYDRATED Ca(OH)_2 SORBENTS

Sorbent	Weight Loss [%]		
	at 100 $^{\circ}\text{C}$	at 545 $^{\circ}\text{C}$	at 700 $^{\circ}\text{C}$
Miss12	0.33	23.09	0.88
Miss13	0.21	22.89	0.85
Miss14	0.35	22.70	1.63
Miss15	-	18.03	0.51

4.2 RECYCLE OPERATION

4.2.1 Dry-Sorbent Injection Downstream of Humidification

Pilot plant (50 cfm) was used for evaluation of dry-sorbent injection (DSI) mass-transfer enhancement by the recycle operation. The first test series was to evaluate the baseline performance to establish the $\text{Ca}(\text{OH})_2$ utilization and data reproducibility of once-through operations for DSI downstream of the humidifier. The major operating parameters are listed in Table 4-3. Fly ash from the Meredosia Power Plant was injected into the flue gas at a rate equivalent to 1.1 gr/acf dust loading. Mississippi $\text{Ca}(\text{OH})_2$ was used as the sorbent and was injected into the duct after the humidifier. Therefore, no sorbent wetting was expected by water droplet/sorbent particulate collision. The average SO_2 removal observed after 6 runs on the pilot plant was about 27 percent at a calcium-to-sulfur ratio of 2.0. Therefore, the lime utilization was about 13.5 percent. The results are presented in Figure 4-1. In addition, 2 runs were conducted to evaluate the reactivity of Meredosia fly ash toward SO_2 .

TABLE 4-3. PILOT PLANT OPERATING CONDITIONS

Operation	Conditions
Flue gas temperature	149 °C
Flue gas SO_2 concentration	2,000 ppm
Simulated fly ash loading	1.1 gr/acf at 149 °C
Duct residence time	~ 2 s
Calcium-to-sulfur ratio	2.0
Approach to saturation	11 °C
Recycle ratio	2.0

As shown in Figure 4-1 by the data point represented by the triangle, almost no SO_2 removal resulted from injecting only Meredosia fly ash as the sorbent. Meredosia fly ash apparently is quite inert toward SO_2 . This conclusion is further supported by the lack of difference in SO_2 removal between runs with and without fly ash.

Following establishment of the baseline once-through operation, the effect was evaluated of recycle on DSI downstream of the humidification zone. The product collected from the previous

Figure 4-1. Dry-sorbent injection upstream of the humidifier (Mercedosia fly ash/ $\text{Ca}(\text{OH})_2$ mixture).

baseline (once-through) tests was used as the recycle material. The recycle material was mixed with fresh $\text{Ca}(\text{OH})_2$ and fly ash before duct injection. The mixing ratio was controlled so that the fresh calcium-to-sulfur ratio would be 2.0 at a recycle ratio of 2.0. As shown in Figure 4-2, approximately 42 percent SO_2 removal efficiency was accomplished during the first recycle test. However, the SO_2 removal declined to 28 percent during the second and third recycle tests, which used as recycle material the product from the first and second recycle tests. Compared with the baseline SO_2 removal (27 percent), the pilot-plant data show that very little improvement in SO_2 removal was accomplished by recycle operation during the third recycle test, which should provide a fairly close simulation of the long-term, steady-state recycle operation.

To further investigate the effect of recycle operation, pilot-plant tests were conducted with recycle material only (i.e., no fresh $\text{Ca}(\text{OH})_2$). As shown in Figure 4-2 by crosses, the recycle material used by the first recycle test yielded approximately 15-percent SO_2 removal. However, the recycle materials used by the second and third recycle tests yielded only 2-percent SO_2 removal. The pilot-plant data indicate that the recycle material rapidly lost its reactivity toward SO_2 after the first pass. The absorbed SO_2 is suspected to form CaSO_3 crystals on the surface of $\text{Ca}(\text{OH})_2$, which tends to blind the active surface and plug the pores. As a result, the recycled $\text{Ca}(\text{OH})_2$, although less than 30-percent utilized, became almost nonreactive toward SO_2 after the second pass.

4.2.2 Dry-Sorbent Injection Upstream of Humidification

In the next series of pilot plant runs, the effect was evaluated of the recycle operation on DSI upstream of the humidifier. The major operating parameters were the same as for DSI downstream of the humidifier (Table 4-3). Fly ash from the Meredosia Power Plant was injected into the flue gas at a rate equivalent to 1.1-gr/acf dust loading. The sorbent, Mississippi $\text{Ca}(\text{OH})_2$, was injected into the duct upstream of (before) the humidifier. Therefore, significant wetting was expected by water droplet/sorbent particulate collision. Initially, considerable difficulties were encountered for once-through DSI upstream of humidification, including wet deposits on the walls, pluggage of sorbent dispersion section, and sorbent build-up around the spraying section. After significant hardware modifications

Figure 4-2. SO₂ removal for recycle operation during the DSI downstream of the humidification zone.

and several trial-and-error tests, stable operation of pilot testing was sustainable for up to 4 h at an approach to saturation temperature of 14 to 17 °C. Figure 4-3 presents the baseline performance of DSI upstream of the humidifier at a 2.0 calcium-to-sulfur ratio. As indicated, higher SO₂ removal was accomplished when the sorbent was injected upstream rather than downstream.

Following the once-through DSI tests upstream of the humidifier, the effectiveness of recycle was evaluated with sorbent and recycle material injected upstream of the humidifier. The recycle material was generated from the baseline (once-through) test conducted previously. Again, considerable operating problems included wet deposits on the walls, pluggage of sorbent dispersion section, and sorbent build-up around the spraying section. The high dust loading because of the recycle operation seemed to aggravate the problems when compared with baseline tests. After several trial-and-error tests and some modifications of operating procedures, stable operation was sustainable for up to 33 h at an approach to saturation of 14 to 17 °C. Figure 4-4 compares the SO₂ removal from recycle tests with that from baseline tests, indicating that significant SO₂ removal enhancement was achieved by DSI recycle upstream of the humidifier.

4.2.3 Conclusions

Based on the aforementioned results, the following conclusions may be drawn:

- Pilot-plant data indicate that the recycle material lost its reactivity toward SO₂ after the first pass.
- Very little improvement in SO₂ removal was accomplished by DSI recycle downstream of the humidifier.
- Significant SO₂-removal enhancement was achieved for DSI recycle upstream of the humidifier.

4.3 GRINDING OF DRY-SORBENT INJECTION MATERIAL

4.3.1 Grinding of Spent Ca(OH)₂

As discussed, DSI recycle downstream of the humidifier was not significantly beneficial. The majority of the Ca(OH)₂ recycled remains unused after the particulate collector. The absorbed SO₂

Figure 4-3. Comparison of DSI upstream and downstream of humidifier.

Figure 4-4. Results for DSI recycle tests upstream of humidifier.

likely forms CaSO_3 crystals on the surface of Ca(OH)_2 , reducing the active surface area and average pore size of the sorbent. Therefore, even though Ca(OH)_2 is only partially used, it may have lost its reactivity. As a result, the reinjection of the partially used Ca(OH)_2 does not result in significant additional SO_2 removal. By grinding partially reacted Ca(OH)_2 , the active surface area may possibly be restored, resulting in additional SO_2 removal.

Sample of spent Ca(OH)_2 was generated by injecting Mississippi Ca(OH)_2 downstream of the humidification zone in the 50-cfm pilot plant. Once-through injection resulted in 26-percent SO_2 removal in the duct (2-s residence time) at $\text{Ca/S} = 2$, 11 °C approach to saturation, and 2,000-ppm SO_2 concentration. The pilot-plant run was made with the cyclone in line between the duct and the fabric filter. Solids intended for dry grinding were taken from the baghouse catch and dry ground in a bench-scale attrition grinder for 15 min. Following grinding, the increase in specific surface area and porosity was measured. Table 4-4 presents structural properties of "as-received" and dry-ground, pilot-plant solids.

TABLE 4-4. STRUCTURAL PROPERTIES OF PILOT-PLANT SOLIDS

Solids	Specific Surface Area [m^2/g]	Pore Volume [cm^3/g]
"As-received" ^a	9.1	0.051
Ground for 15 min ^b	13.9	0.065

^afrom the pilot plant

^bin the bench-scale attrition grinder

Reactivity of ground solids with SO_2 was tested in the STDR operated at 60-percent relative humidity (11 °C approach to saturation) and with 2,000-ppm SO_2 . The reactivity of "as-received" baghouse catch was measured first, followed by solids ground for 15 min. Results are presented in Figure 4-5. Reactivity with SO_2 was significantly enhanced by dry grinding baghouse catch.

4.3.2 Grinding of Spent Ca(OH)_2 /Fly Ash

Following DSI, solids from the baghouse catch would contain inherent fly ash and spent Ca(OH)_2 . To simulate the effect of fly ash on reactivity of ground spent Ca(OH)_2 , baghouse catch solids were dry mixed with fly ash prior to grinding.

Reactivity of ground, spent $\text{Ca}(\text{OH})_2$ /fly ash solids with SO_2 was tested in the STDR operated at 60-percent relative humidity (11 °C approach to saturation) and with 2,000 ppm SO_2 . "As-received" baghouse catch reactivity was measured first, followed by reactivity of dry mixture of baghouse catch/Beverly fly ash at the weight ratio of 3.5:1, which was intended to simulate the recycle material from the DSI process. No significant reactivity difference was detected between baghouse catch alone and dry mixture of baghouse catch/Beverly fly ash, as evident in Figure 4-6. Finally, the reactivity of baghouse catch/Beverly fly ash solids dry-ground in the bench-scale attritor was measured for 15 min. Under conditions of the STDR, 15-min dry ground solids were significantly more reactive with SO_2 than unground solids. Reactivity difference was more pronounced at larger residence times in the STDR (3 and 5 s), as evident in Figure 4-6.

TABLE 4-5. STRUCTURAL PROPERTIES OF DRY GROUND BAGHOUSE CATCH/BEVERLY FLY ASH SOLIDS

Solids Type	Surface Area [m ² /g]	Pore Volume [cm ³ /g]
Baghouse Catch	9.1	0.051
Baghouse Catch/Beverly fly ash dry-mixed	7.1	0.037
Baghouse Catch/Beverly fly ash dry-mixed and dry-ground for 15 min	14.8	0.064

4.3.3 Conclusions

In summary, a significant increase of surface area and pore volume resulted from dry grinding of baghouse catch/fly ash solids. Ground solids were significantly more reactive than unground solids with the SO_2 in the STDR.

Figure 4-5. Reactivation of spent Mississippi $\text{Ca}(\text{OH})_2$ baghouse catch by dry grinding baghouse catch/Beverly fly ash (mixed at the weight ratio of 3:5:1).

Figure 4-6. Reactivation of spent $\text{Ca}(\text{OH})_2$ /Beverly fly ash solids by dry-grinding in a bench-scale attritor (reactor: 60-percent relative humidity, 2,000-ppm SO_2).

SECTION 5

SOLIDS MOISTURE CAPACITY

5.1 INTRODUCTION

As shown in previous sections, $\text{Ca}(\text{OH})_2$ sorbent reactivity is enhanced by free moisture on the sorbent. However, large amounts of moisture may adversely affect sorbent handling and utilization, and system reliability. As duct-injection technology begins large pilot-scale and demonstration-scale development, these effects assume greater significance.

The duct-injection process using solids with initial free moisture consists of the following steps: preparation of sorbent as a slurry; blending of the slurry with dry recycle materials to create solids with initial free moisture; injection of the solids into the duct; reaction and drying of the solids with flue gas in the duct; collection in particulate control equipment; and, finally, recycle of dry solids with some bleed to disposal. The moisture content of the solids at each step affects system performance.

The hydrothermal reaction of fly ash with $\text{Ca}(\text{OH})_2$ produces calcium silicates that are more reactive than $\text{Ca}(\text{OH})_2$ toward SO_2 (Jozewicz and Rochelle, 1986) because of the greater surface area, amorphous surface structure, and molecular moisture of the calcium silicates (Jozewicz et al., 1988a). The moisture content of the slurry leaving the reaction tank must be reduced. The proposed method is to mix dry recycle material with the slurry. Recycle of unreacted sorbent would increase its utilization. However, as the moisture content of the mixture is reduced by addition of more recycle material, the load on the particulate control device increases, which may affect its performance. Furthermore, reactivity of the sorbent is generally reduced by decreasing its moisture content. As the moisture content of the slurry is decreased, it becomes a paste, making handling and injection difficult. Further

drying eventually would produce a dry powder. Exploration of the gap between a poorly manageable paste and a dry powder is the focus of this section.

5.2 THEORY OF AGGLOMERATION

Several forces may contribute to particle agglomeration. A particle in a dry atmosphere will experience the following forces: (1) Van der Waals forces caused by fluctuating dipoles, (2) electrostatic attractions caused by excess charge on nonconducting materials, (3) mechanical interactions caused by particle interlocking and solid bridges formed from crystallizing salt, sintering, or chemical reactions, and (4) magnetic forces between particles of certain materials. For particles with radii less than 100 μm , the van der Waals force is much greater than the electrostatic attraction (Rumpf, 1977). Magnetic attractions can cause very significant interactions between certain particles, but are not evident with calcium-based sorbents.

These forces can be reduced significantly by materials acting as spacers between the particles (Dutta and Dullea, 1989). Spacers could include fine particles or adsorbed gas molecules. A particle in equilibrium with relative humidity but with no free moisture would experience an increase in the van der Waals force because the adsorbed vapor acts as part of the particle and thus reduces the interparticle distance. However, electrostatic forces would decrease because of the conductivity of the humid air, and frictional resistance to particle movement might decrease by action of the adsorbed layer as a lubricant.

When liquid is present on the surface of particles, the reduction in surface energy from merging liquid films results in particle agglomeration. The cohesive strength of such agglomerates has been found to be directly proportional to the surface tension of the binding liquid (Newitt and Conway-Jones, 1958). Agglomerates are strengthened further by capillary pressure from liquid in the void volume of the agglomerate. The opportunity for agglomeration depends on the amount of contact between particles. The size of agglomerates formed from damp particles was shown to increase with time in a tumbling contactor (Newitt and Conway-Jones, 1958).

The cohesive strength of an agglomerate increases with moisture content, reaching a maximum when the void volume of the agglomerate is almost completely filled with liquid (Newitt and Conway-Jones, 1958). The strength also is dependent on whether the moisture content in the void volume is reached by absorption or drainage (Rumpf, 1977).

5.3 APPROACH

Calcium silicate sorbents were prepared by slurring fly ash with Ca(OH)_2 and analyzed for critical moisture, surface area, and pore volume. Critical moisture quantifies a powder's capacity for moisture and is defined by the test procedure described below. Slurry liquids were analyzed for pH and various ions to monitor the fly ash/ Ca(OH)_2 reaction.

The slurries generally contained a silica source—fly ash or silica fume—and Ca(OH)_2 . Calcium sulfite hemihydrate ($\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$) and gypsum ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) sometimes were added; they represented species present in recycle material. Two types of fly ash were used: a low-calcium ash from eastern bituminous coal and a high-calcium ash from western subbituminous coal. The former was a sample of Clinch River fly ash taken in October 1986 from the Appalachian Power Company's Clinch River plant (Peterson, 1987). Because the composition of the ash may vary slightly depending on sample date, the composition of the ash used in this study is listed in Table 5-1. The second type of fly ash was high-calcium Harrington fly ash taken in July 1987 from the Southwestern Electric Power Company's Harrington Station where subbituminous coal from the Powder River basin of Wyoming was burned. The ash also was used by Peterson (1990). The ash had a surface area of $2 \text{ m}^2/\text{g}$; its composition is listed in Table 5-1.

Silica fume, a by-product from the manufacture of silicon metal, was used in place of fly ash in some experiments, and material also was used by Peterson (1990). The silica fume was obtained from the University of Texas' Ferguson Structural Engineering Laboratory. The material was 92-percent SiO_2 and non-crystalline, with a $20\text{-m}^2/\text{g}$ surface area (Peterson, 1990).

The Ca(OH)_2 used in nearly all experiments was commercial Mississippi Rotary Ca(OH)_2 (Code MR200) from the Mississippi Lime Company. $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ used in experiments was reagent-grade

material from the Aldrich Chemical Company. $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ used in experiments was prepared in the laboratory by adding 1 M CaCl_2 to 1 M Na_2SO_3 . The gypsum and calcium sulfite had surface areas of 2 and 6 m^2/g , respectively. Calcium silicate sorbents were prepared by slurrying solid reactants in a 500-mL stainless steel vessel. Slurry samples were drawn (usually about 50 mL) at times ranging from 15 min to 24 h.

TABLE 5-1. CHEMICAL COMPOSITION OF SILICA SOURCES
(FROM ENERGY-DISPERSIVE SPECTROSCOPY)

Silica Source	CaO	SiO_2	Al_2O_3	Fe_2O_3	(Na&K) Na_2O
Clinch River Fly Ash	4	57	27	8	
Harrington Fly Ash	30	32	22	5	1.7*
Silica Fume	0.1	92	3	2	0.3

Critical moisture, as defined here, quantifies a powder's capacity for moisture before exceeding a specified degree of agglomeration. Most powder tests measure the cohesiveness of a powder and alternatively, the ability of a powder to flow. A more cohesive powder is less freely flowing and, therefore, the 2 measures are related (Carr, 1970). Flow characteristics are commonly evaluated by simple tests to determine the angle of repose, angle of fall and, to evaluate adhesiveness to a dissimilar surface, the angle of slide.

Powder cohesiveness can be evaluated by measuring shear yield strength, compressibility, or retention by sieves. Shear strength is measured in a split-cell shear cell with a vertical compressive force (Jenike et al., 1960). The procedure is derived from soils testing and is not practical for samples with very low cohesiveness. The yield strength is affected by the water content and particle size distribution of the material. A second measure, compressibility, is determined by comparing the loosely packed bulk density of a material with its packed density. Cohesive powders are more compressible (Carr, 1970). A third method for evaluating the cohesiveness of a powder measures retention on a nest of 60-, 100-, and 200-mesh sieves (Carr, 1965). The procedure involves placing 2 g of material on the nest and vibrating for 20 to 120 s according to the density of the material. The sieve sizes also

can be altered for varying density materials. If the entire 2 g of sample remains on the 60-mesh sieve, cohesion is 100 percent. Cohesion is zero if all the material passes through the 200-mesh sieve.

In this study, a 5-g sample was placed on an 80-mesh sieve (177 μm between wires) and shaken for 10 min. Tests were run on samples with varying amounts of moisture to determine the amount of moisture that caused half the sample to be retained by the 80-mesh sieve. This amount was called the critical moisture (grams of water/g of wet solids expressed as a percentage).

A standard, 8-in diameter, full-height (2-in depth to cloth), 80-mesh sieve with pan and cover from Brainard-Kilman was used. Water was added dropwise to 5 g of a dry powdered sample in a glass beaker. The water was mixed in manually with a metal chemical spatula. The mixture was spread against the beaker wall and repeatedly chopped in an attempt to distribute the water uniformly and break any clumps. The sample was weighed before water was added and after it was mixed in to determine the initial moisture content. After the moist sample was weighed, subsequent steps were performed without delay to minimize evaporation. Each complete test took about 15 min.

The moist sample was spread uniformly over the sieve, the lid placed on, and the assembly placed in a mechanical sieve shaker (without a tapping device) and shaken for 10 min. After 10 min the material retained by the sieve and the material collected in the pan was weighed. This procedure usually was repeated on 3 or more samples at different moisture contents until the critical moisture was bracketed and could be determined by linear interpolation. A fresh sample was used for each test, but all samples came from the same experiment.

5.4 RESULTS FOR INDIVIDUAL REACTANTS AND DRY MIXTURES

This section addresses results of experiments with low-calcium fly ash, ground low-calcium fly ash, and high-calcium fly ash. Presented in Figure 5-1 are data for a standard sorbent (3 g of Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ slurried for 8 h at 92 °C) tested over a wide range of moisture content. The critical moisture content is determined by linear interpolation between the 2 points closest to the horizontal line indicating 50-percent passing. The value determined from Figure 5-1 is 17 percent. Values are rounded to a whole number because of uncertainty in the number.

A sorbent was subjected, on average, to 3 sieve tests at different moisture contents. When critical moisture content was determined more than once for a particular sorbent, the values were reproducible within a range of 3 percentage points. The critical moisture content was measured more than once for 13 sorbents and reactant mixtures. The values differed by 2 or less in all but 1 case. Multiple values of critical moisture were determined on separate occasions.

The average sample recovery after sieve tests was 94.4 percent of the initial wet weight. Losses were due to evaporation, dispersion of fines, and retention by the sieve. Evaporative losses were measured in 14 tests in which the sample was subjected to 15 min of sieving. The samples initially contained from 7.3- to 29.7-percent moisture. The average evaporative loss was 3.9 percent of the initial wet weight. Although critical moisture content was based on the initial moisture content, the amount passing through a sieve was affected by the final moisture content. Therefore, a faster drying material would be expected to have increased critical moisture content. The change is insignificant except in samples with a low critical moisture, although those samples would be expected to lose moisture at the slowest rate because of the small driving force.

To relate critical moisture content to a more commonly measured sorbent property, values were plotted against specific surface area. Figure 5-2 shows that critical moisture content increases with surface area. The data are from all calcium silicate sorbents tested in this study, and, therefore, reflect a broad range of preparation conditions. Deviations from the general cluster are random and are discussed in the sections following for each silica source.

Most of the surface area of these sorbents occurs in the particle pore space, which is filled, to some degree, by water when it is added to the dry sorbent. When moist sorbent agglomerates, much of the moisture may be hidden in the particle pore space. Therefore, critical moisture content may

Figure 5-1. Typical results for sieve tests of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (critical moisture content 17 percent, Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio slurried for 8 h at 92 °C).

Figure 5-2. Correlation of the moisture data (points represent all fly ash/ $\text{Ca}(\text{OH})_2$ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).

correspond more directly to pore volume than to surface area. Figure 5-3 shows the results of critical moisture tests, expressed as a ratio of water-to-dry solid, plotted versus particle-specific pore volume. The relationship is nearly 1:1; that is, each mL of pore space corresponds roughly to 1 mL of absorbed water at the critical moisture content. If the pore space was completely filled with water, the moisture ratio at the critical moisture content would be greater than the pore volume because water is needed outside the pore space to cause agglomeration. However, water added to a dry solid does not necessarily fill all the pore space, so the critical volume of water need not equal the pore volume.

Pore volume and surface area are related by the cylindrical pore model. Figure 5-4 shows the relation between the values for fly ash/ $\text{Ca}(\text{OH})_2$ sorbents. The data in Figure 5-4 indicate an effective pore radius of 110 Å. Surface-area measurements require much less time than pore-volume measurements and are routinely measured. Therefore, all further critical moisture results are correlated with surface area.

The critical moisture content of unreacted reagents and their mixtures has been compared to surface area, as shown in Figure 5-5. Most of the reactants are relatively low-surface-area materials with correspondingly low critical moisture. The exception is $\text{Ca}(\text{OH})_2$ which has an area of 20 m²/g, yet has a critical moisture content of zero; that is, only half of an oven-dried sample with no water added will pass through an 80-mesh sieve during 10 min of sieving. The anomaly cannot be attributed to large particles. The median particle size of Mississippi $\text{Ca}(\text{OH})_2$ has been reported as 2.9 µm (Rochelle et al., 1990), whereas unground Clinch River fly ash has a 12-µm median diameter and a 2-percent critical moisture. Another example is that of ground Clinch River fly ash, which has a median diameter smaller than that of unground fly ash yet also has a lower critical moisture content of zero percent. Conversely, $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$, which has a large diameter of 25 µm (Tseng and Rochelle, 1986), has a critical moisture of 5 percent. The zero-value critical-moisture content for the small

Figure 5-3. Correlation of critical moisture ratio at the critical moisture content.

Figure 5-4. Correlation of particle pore volume with specific surface area (solid symbols represent data for fly ash/ $\text{Ca}(\text{OH})_2$ sorbents prepared and tested by Acurex Corporation; open symbols are for sorbents represented in Figure 5-3; the dotted line and equation are a least-squares fit of the data).

Figure 5-5. Critical moisture content of reactant and dry mixtures ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, Harrington fly ash, Clinch River fly ash, $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$, ground Clinch River fly ash, and $20\text{-m}^2/\text{g}$ $\text{Ca}(\text{OH})_2$).

particles may occur because these particles can pack closer, allowing attractive forces to exert a greater influence.

The poor critical moisture content of $\text{Ca}(\text{OH})_2$ can be diluted by mixing it with other materials. A dry mixture of ground Clinch River fly ash and $\text{Ca}(\text{OH})_2$ (4:1 weight ratio) had, not surprisingly, a critical moisture of zero. The same mixture with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ added (44 percent) had a critical moisture of 2 percent. Without $\text{Ca}(\text{OH})_2$, the critical moisture of the mixture (now 50-percent calcium sulfite and gypsum) increased to 5 percent. Although the critical moisture of each subsequent mixture increased, the surface area of each mixture decreased, probably because of dilution of the large area of $\text{Ca}(\text{OH})_2$. The same increase in critical moisture with $\text{Ca}(\text{OH})_2$ dilution was seen with unground fly ash. Therefore, whereas $\text{Ca}(\text{OH})_2$ has a poor critical moisture content (it falls below the correlation with surface area), its effect on mixtures can be diluted. The behavior of dry mixtures is not accurately predicted by simply averaging on a mass basis the values of the pure reagents. However, the uncertainty of critical-moisture and surface-area measurements at low values may be at fault.

The correlation presented in Figure 5-2 shows that a discussion of surface-area development also can be considered a discussion of critical-moisture development. Therefore, previous research on fly ash/ $\text{Ca}(\text{OH})_2$ sorbent preparation, which reported surface area data, now can be used to indicate moist-sorbent behavior. The remainder of this section focuses on the critical-moisture content of sorbents prepared from a variety of slurry compositions.

5.5 RESULTS FOR SORBENTS PREPARED FROM SLURRY

Sorbent preparation from Clinch River fly ash and the reactivity of those sorbents toward SO_2 has been studied extensively at Acurex Corporation and the University of Texas. Therefore, Clinch River fly ash was used as a baseline material in this study. Previous work has shown that sorbent reactivity increases with slurry time and temperature (Jozewicz and Rochelle, 1986). However, a limit is achieved with pressure hydration and dependent on the fly ash/ $\text{Ca}(\text{OH})_2$ ratio, beyond which reactivity decreases (Jozewicz et al., 1988b). This limit is believed to be due to the formation of

another phase with less molecular water and a more crystalline structure. A slurry temperature of 92 °C was chosen for this study to maximize the reaction rate at atmospheric pressure and to allow direct comparison with the results of Peterson (1990). Sorbents were prepared with 3 g and 4 g of fly ash/g $\text{Ca}(\text{OH})_2$. These compositions commonly are used by others in bench- and pilot-scale work. Figure 5-6 shows that the critical moisture content of the sorbents increased with slurry time up to 8 h. A significant difference in values was not detected between sorbents prepared from 3:1 and 4:1 ratios, and values were comparable for the same composition prepared on different occasions.

The presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in slurries of high-calcium fly ash with $\text{Ca}(\text{OH})_2$ has been shown to enhance the surface area and reactivity of the product solids (Peterson, 1990). $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ appears to interact selectively with the aluminum of the fly ash to reduce its reaction with $\text{Ca}(\text{OH})_2$ and to reduce the formation of low-surface-area calcium-aluminate materials. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ is not expected to be as great with low-calcium fly ash because aluminum dissolution occurs to a lesser extent (Peterson, 1990). $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ also has been shown to have a beneficial effect, although the effect is believed due to $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, which is present in small amounts in laboratory-prepared calcium sulfite. Figure 5-7 shows that $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an effect on either critical-moisture content or surface area. $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ mixed with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an appreciable effect on critical moisture, although surface area was greater at 12 h. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ may be more pronounced at longer slurry times. Figure 5-8 shows that dissolved calcium essentially was spent after 12 h in slurries without $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, but was still available for calcium silicate production in the slurry containing $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. Results from ground Clinch River ash (discussed below), which reacts faster than unground ash, show that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture after 8 h. The presence of $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in slurries did not alter the relationship between critical moisture and surface area. All samples prepared with unground Clinch River fly ash generally correlate (Figure 5-2).

Figure 5-6. Effect of slurry time and fly ash/ $\text{Ca}(\text{OH})_2$ ratio on critical moisture content of sorbent from low-calcium fly ash (open symbols are the 3:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; solid symbols are 4:1 ratio).

Figure 5-7. Effect of CaSO_3 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ with CaSO_3 on sorbents from low-calcium fly ash (solid symbols are 4:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open squares 4:1:4 fly ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$; triangles 4:1:3:1 fly ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_3/\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-6. Effect of slurry time and fly ash/ $\text{Ca}(\text{OH})_2$ ratio on critical moisture content of sorbent from low-calcium fly ash (open symbols are the 3:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; solid symbols are 4:1 ratio).

Ground fly ash has a greater silica dissolution rate than unground fly ash, which results in greater production of calcium silicates (Peterson, 1990). Sorbents prepared from ground fly ash have greater surface area and are more reactive with SO_2 than sorbents prepared from unground ash (Petersen et al., 1989; Hall et al., 1991). In this study, ground Clinch River fly ash produced sorbents with a greater critical-moisture content than those from unground ash. The increase in critical moisture over that of sorbents from unground fly ash is shown in Figure 5-9 for several slurry compositions. Also shown is the enhancement of critical moisture after 8 h of reaction with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and calcium sulfite in the slurry. Figure 5-10 shows that recycle materials enhanced surface area after only 6 h of slurry reaction with ground ash, whereas unground ash (Figure 5-7) required 12 h.

The fly ash/ $\text{Ca}(\text{OH})_2$ ratio in the slurry is an important process variable. Previous work with unground Clinch River fly ash showed that $\text{Ca}(\text{OH})_2$ conversion (moles SO_2 /mole $\text{Ca}(\text{OH})_2$) increases as the fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio increases over a range from 0.8:1 to 15.9:1 (Jozewicz et al., 1988c). In addition to an increase in conversion, surface area is reported to increase from $9.9 \text{ m}^2/\text{g}$ to $19.2 \text{ m}^2/\text{g}$ when the ratio is increased from 2:1 to 10:1 (slurrying 8 h at 90°C) and from about $12 \text{ m}^2/\text{g}$ to $20 \text{ m}^2/\text{g}$ when the ratio is increased from 1:2 to 5:1 (slurrying 2 h at 150°C) (Jozewicz et al., 1988a). With Clinch River fly ash ground to $5.0 \text{ m}^2/\text{g}$, increasing the ratio from 2:1 to 3:1 results in increased surface area; for unground ash the change in ratio does not cause a significant change in surface area (Peterson, 1990).

Figure 5-11 shows the effect on both critical moisture and surface area of varying the fly ash/ $\text{Ca}(\text{OH})_2$ ratio over the range from 1:4 to 4:1 in slurries of ground fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$. Solids from a slurry with no $\text{Ca}(\text{OH})_2$ also were tested. A maximum in both critical moisture and surface area occurred at a 1:1 fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio (0.50 fly ash fraction) when the slurry time was 8 h. Critical moisture data at shorter times are insufficient, but surface area data at 2, 4 and 8 h are shown in Figure 5-12. The surface area of 4- and 2-h samples

Figure 5-9. Effect of fly ash grinding and the presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ /g $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ /g $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-10. Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and CaSO_3 on sorbent from ground low-calcium fly ash (solid symbols 1:1 ground Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open symbols 4:4:3:1 fly ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}/\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-11. Effect of fly ash fraction on sorbent from ground low-calcium fly ash (all samples slurried for 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted $\text{Ca}(\text{OH})_2$).

Figure 5-12. Effect of fly ash fraction and slurry time on surface area of sorbent from ground low-calcium fly ash (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted $\text{Ca}(\text{OH})_2$).

remained constant or decreased slightly as the fly ash/ $\text{Ca}(\text{OH})_2$ ratio was increased. The 2-h data follow a line between the endpoints that dry mixtures would be expected to follow, which suggests minimal reaction at 2 h. The decreasing values of surface area are contradictory to the results of other values discussed above. However, these values differ because the slurries in this study contained $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$. The 8-h data show increasing area as the fly ash/ $\text{Ca}(\text{OH})_2$ ratio was increased except at a 0.80 fly ash fraction. The lower surface area may be attributed to a low pH value. Figure 5-13 shows solution data for the slurries. Calcium concentrations always were adequate for calcium silicate formation and pH values were consistently high except at 8 h in the slurry with a 0.80 fraction. The pH dropped below levels of $\text{Ca}(\text{OH})_2$ saturation between 2 and 8 h. Solution equilibria was then controlled probably by calcium-aluminate-silicate solids. The rate of ash dissolution and surface area development would decrease.

The high $\text{Ca}(\text{OH})_2$ fraction in some slurries did not necessarily produce sorbents with poor critical moisture relative to their surface area. Critical moisture correlates with surface area (Figure 5-2) as well for those sorbents as for others. One exception is the sorbent produced after 8 h of slurrying with 80-percent $\text{Ca}(\text{OH})_2$ and no $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ or $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ (sample with: 38 m^2/g and 8 percent critical moisture). Unreacted $\text{Ca}(\text{OH})_2$ was probable even at 8 h, which could have a deleterious effect on the critical moisture. Data points for other sorbents also lie off the correlation, but the deviations appear to be independent of slurry composition because similar sorbents at different slurry times lie on the correlation.

The high availability of silica and large calcium content in high-calcium fly ash suggest that it would make an attractive reagent for sorbent production (Peterson and Rochelle, 1988). When high-calcium fly ash is slurried alone (e., without $\text{Ca}(\text{OH})_2$) the product solids are more reactive (SO_2 capture) with SO_2 than solids prepared similarly from low-calcium fly ash, and also have greater surface area. However, with both types of fly ash, the addition of $\text{Ca}(\text{OH})_2$ to the slurry enhances surface area (Peterson, 1987). The development of critical moisture with slurry time for a slurry of Harrington

Figure 5-13. Effect of fly ash fraction on solution composition of ground low-calcium fly ash slurry (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1).

fly ash (high-calcium fly ash) with no Ca(OH)_2 present is shown in Figure 5-14. The critical moisture increased with slurry time, although only slightly, after 4 h. Results for a sorbent prepared with Ca(OH)_2 in a 3:1 fly ash/ Ca(OH)_2 ratio also are shown. Both sorbents developed the same critical moisture at 8 h, and surface-area development was similar.

The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in the slurry on critical moisture is shown in Figure 5-15. Critical moisture was about the same at long times (12 and 24 h) for sorbents produced from slurries of fly ash alone and from slurries of fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. The result was similar when $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ was used instead of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. Surface area was lower when $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ or $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ was present ($14 \text{ m}^2/\text{g}$ at 8 h versus $19 \text{ m}^2/\text{g}$ for fly ash slurried alone). Dissolved sodium concentrations reflect the values of surface area. Figure 5-16 shows that sodium increased with slurry time, which reflects its release from reacting fly ash during calcium silicate formation (surface area development). The concentration at 8 and 12 h was greater in the slurry without $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, as was the surface area of the sorbents. A relationship between surface area and sodium concentration was displayed by all the data from experiments with Harrington fly ash. The pH values in Figure 5-16 are dependent on gypsum concentrations as well as sodium (as NaOH) concentrations, and, therefore, do not correlate with surface area. All of the solution data indicate Ca(OH)_2 saturation, even when ash was slurried alone.

Another result shown in Figure 5-15 is that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture, as it did surface area, in slurries of ash with Ca(OH)_2 . The data in Figure 5-15 indicate that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was not beneficial unless Ca(OH)_2 was present. To investigate that behavior the Ca(OH)_2 loading (g $\text{Ca(OH)}_2/\text{g}$ fly ash) was varied in slurries with constant amounts of fly ash and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. Figure 5-17 shows that both critical moisture and surface area remained about the same for loadings from 0.07 to 0.33 (fly ash/ Ca(OH)_2 ratios from 15:1 to 3:1). As the loading was decreased further both properties decreased. A minimum amount of Ca(OH)_2 appears to be required to achieve fly ash activation, but

Figure 5-14. Critical moisture content of sorbent prepared from high-calcium fly ash alone, and fly ash with Ca(OH)_2 ("Ash Alone": Harrington fly ash slurried without Ca(OH)_2 at 26 percent solids, "With Ca(OH)_2 ": weight ratio of Harrington fly ash/ Ca(OH)_2 slurried at 92 °C at 26-percent solids).

Figure 5-15. Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content of sorbent prepared from high-calcium fly ash ("Ash Alone": average values of data shown in Figure 5-14 for sorbent prepared from Harrington fly ash, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, " $\text{Ca}(\text{OH})_2$ & Gypsum": 3:1:0.67 Harrington fly ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-16. Solution composition of slurries with high-calcium fly ash ("Ash Alone": Harrington fly ash slurred without $\text{Ca}(\text{OH})_2$ at 23 percent solids, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot \text{H}_2\text{O}$ weight ratio).

Figure 5-17. Effect of Ca(OH)_2 loading on sorbent prepared from high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ (constant Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio of 3:0:6 and slurry time of 8 h except points at 0.33 loading, which are 9-h samples).

greater amounts were of no additional benefit, a conclusion supported by pH values in Figure 5-18.

These values were relatively low and constant until the loading reached 0.07, which also was the point at which surface area reached its ultimate value. The sodium concentrations simply reflect increased ash activation as pH increased.

5.6 CONCLUSIONS

The results presented previously indicate:

- Agglomeration of damp calcium silicate sorbents is a function of sorbent pore volume. Greater specific pore volume allows a sorbent to carry more water before forming the same size agglomerates as a sorbent with less pore volume (critical moisture, which increases with pore volume). The correlation of critical moisture with pore volume suggests that most of the water added to a sorbent exists in the pore space, with only a minor fraction existing outside and causing agglomeration.
- Critical moisture also increases with specific surface area. The correlation between critical moisture and surface area is independent of fly ash type (low- and high-calcium ash), fly ash grinding and recycle materials.
- The slurry time required for $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ to enhance critical moisture and surface area is dependent on fly ash properties, which is probably related to the rate of aluminum dissolution from the ash. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was evident after 8 h when ground Clinch River fly ash was slurried. Sorbent prepared from high-calcium fly ash benefitted from $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ after 3 h.
- Sorbents prepared by slurrying ground fly ash for 8 h with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ exhibited a maximum in both critical moisture and surface area when the fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio was 1:1. Values for sorbents with 2- and 4-h slurry times did not exhibit a maximum; they decreased as the fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio was increased from 1:4 to 4:1.

Figure 5-18. Effect of Ca(OH)_2 loading on solution composition for slurry of high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ present (same experiment shown in Figure 5-17).

- High-calcium fly ash, slurried without Ca(OH)_2 , is marginally effective as raw material for sorbent. The sorbent prepared after 8 h of slurrying had a critical moisture and surface area similar to that of sorbent prepared with a Ca(OH)_2 loading of 0.33-g/g fly ash.
- $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ did not enhance critical moisture or surface area when added to a slurry of high-calcium ash alone; however, when present in slurries of ash and Ca(OH)_2 , $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced both critical moisture and surface area.
- High-calcium fly ash appears to require a catalytic amount of Ca(OH)_2 to initiate formation of calcium silicates, but greater amounts are of no additional benefit.

SECTION 6

ENHANCEMENT OF DUCT SPRAY DRYING

6.1 BUFFER ADDITIVES

6.1.1 Bench-Scale Methods

Experiments have been performed in the stirred tank reactor (detailed description of the reactor is in the Topical Report for Task 2.1, December 15, 1990) to determine the effect of acetic acid on SO_2 absorption. The experiment methods were identical to those reported in previous progress reports. The experiments were performed over a range of liquid agitation and SO_2 concentration with clear solutions of 3- and 17-mM $\text{Ca}(\text{OH})_2$ in 0.1 M calcium chloride at 55 °C. Previous work has shown that $\text{Ca}(\text{OH})_2$ has a solubility of 17 mM in 0.1-M CaCl_2 . Experiments were performed without acetate and with the addition of 20-mM sodium acetate. In commercial practice, the addition of acetic acid to $\text{Ca}(\text{OH})_2$ slurry would yield calcium acetate as the active additive. Gas-phase agitation was kept at its maximum rate.

For each experiment, the SO_2 flux was calculated from a gas-phase material balance. SO_2 gas concentration at the gas/liquid interface was calculated from the measured bulk gas concentration, the measured flux, and the previously measured gas-phase, mass-transfer coefficient. The enhancement factor was calculated from the known Henry's constant and the previously measured liquid film coefficient.

6.1.2 Bench-Scale Results

Tables 6-1 and 6-2 summarize the experimental results. Figure 6-1 compares the enhancement factor with and without 20-mM acetate in 3-mM $\text{Ca}(\text{OH})_2$. Without acetate, the

enhancement factor varies from 5 at high SO₂ to 20 at low SO₂. With 20-mM acetate, 6 consistent data occur at high SO₂ concentration, showing an increase in the enhancement factor to the range of 13-40.

TABLE 6-1. ENHANCEMENT OF SO₂ ABSORPTION I 3 mM Ca(OH)₂/0.1 M CaCl₂

No Sodium Acetate					
P _{SO2} (bar)	k _l x 10 ⁵ (m/sec)	Enhancement Factor	Agitation (rpm)	P _{SO2} (bar)	1/[SO ₂] (l/mol)
3.68E-03	6.86	10.4	1042	5.16E-03	542
3.11E-03	6.86	9.75	1042	6.01E-03	642
2.50E-03	6.86	9.65	1042	6.48E-03	798
3.96E-03	5.41	6.33	715	5.70E-03	504
4.58E-03	5.41	6.73	715	5.12E-03	436
5.01E-03	5.41	7.82	715	4.40E-03	398
5.91E-03	3.34	9.03	332	3.04E-03	338
5.56E-03	3.34	7.51	332	3.78E-03	359
4.78E-03	3.34	7.43	332	4.53E-03	418
With 20 mM Sodium Acetate					
1.40E-03	6.86	36.5	1042	3.46E-03	1426
1.01E-03	6.86	38.5	1042	4.71E-03	1976
9.35E-04	6.86	30.8	1042	5.61E-03	2134
1.65E-03	5.41	20.5	715	4.17E-03	1210
2.51E-03	5.41	16.5	715	3.24E-03	795
3.27E-03	5.41	15.8	715	2.24E-03	610
4.91E-03	3.34	13.2	332	1.58E-03	407
4.13E-03	3.34	13	332	1.88E-03	483
2.95E-03	3.34	15.9	332	2.53E-03	677

TABLE 6-2. ENHANCEMENT OF SO₂ ABSORPTION IN 17 mM Ca(OH)₂/0.1 M CaCl₂

No Sodium Acetate					
P _{SO₂} (bar)	k _l × 10 ⁵ (m/sec)	Enhancement Factor	Agitation (rpm)	P _{SO₂} (bar)	1/[SO ₂] (l/mol)
6.94E-04	6.86	79.3	1042	1.92E-03	2872
5.90E-04	6.86	68.6	1042	1.49E-03	3378
5.54E-04	6.86	54	1042	1.22E-03	3597
1.35E-03	5.41	25.8	715	1.96E-03	1472
1.66E-03	5.41	27.5	715	2.46E-03	1195
1.93E-03	5.41	31.6	715	3.00E-03	1031
3.59E-03	3.34	21.8	332	4.46E-03	545
2.64E-03	3.34	24.6	332	3.36E-03	741
1.52E-03	3.34	36.1	332	2.12E-03	1298
9.10E-04	6.86	29.1	1042	2.11E-03	2190
7.41E-04	6.86	53.8	1042	1.63E-03	2690
7.40E-04	6.86	39.7	1042	1.39E-03	2693
1.18E-03	5.41	30	715	1.81E-03	1684
1.49E-03	5.41	35.4	715	2.31E-03	1332
2.16E-03	5.41	27.5	715	3.20E-03	921
3.92E-03	3.34	19	332	4.74E-03	499
3.03E-03	3.34	20.3	332	3.71E-03	645
2.14E-03	3.34	23.9	332	2.70E-03	922
With 20 mM Sodium Acetate					
5.47E-04	6.86	102	1042	2.32E-03	3638
4.93E-04	6.86	82.6	1042	2.75E-03	4025
5.73E-04	6.86	51.9	1042	3.72E-03	3463
1.05E-03	5.41	34	715	2.61E-03	1881
1.23E-03	5.41	28.7	715	2.07E-03	1601
1.48E-03	5.41	42.8	715	1.69E-03	1329
2.75E-03	3.34	31.8	332	1.24E-03	709
1.97E-03	3.34	35.5	332	1.40E-03	988
1.74E-03	3.34	30.3	332	1.79E-03	1114

Figure 6-1. Effect of sodium acetate on SO₂ absorption into clear solution containing 3-mM Ca(OH)₂ and 0.1 M CaCl₂ at 55 °C.

Figure 6-2 shows the effect of 20-mM acetate in 17-mM $\text{Ca}(\text{OH})_2$. The effect is not clear and is barely discernible from the noise in the data. The data are not inconsistent showing an increase of 6 units in the enhancement factor without acetate at high SO_2 . At high SO_2 , the enhancement factor without acetate was about 20.

The diffusion coefficient of acetate is about 5 times less than that of hydroxide. Given the dependence of mass transfer on the root of diffusivity, one would expect 3 mM- $\text{Ca}(\text{OH})_2$ (6-meq/l) to be equivalent to about 15-mM acetate. Therefore, the observed effect of acetate is not unexpected. The amount of acetate added to the 17-mM $\text{Ca}(\text{OH})_2$ was not adequate to produce a significant effect, but more acetate, perhaps 50 mM, would be expected to enhance SO_2 absorption significantly.

6.1.3 Pilot-Scale Results

Several buffer additives were evaluated for their ability to enhance SO_2 absorption in DSD process. Mississippi $\text{Ca}(\text{OH})_2$ slurry (13.6-percent solids) was atomized in a 50-cfm spray dryer facility operated at 149 °C spray dryer inlet temperature. The inlet concentration of SO_2 was 2,000 ppm and stoichiometric ratio of calcium-to-sulfur was 9:10. Approach to saturation, as measured on the baghouse inlet, was 22 °C. Baseline performance test was conducted first to establish the percentage of SO_2 removal and data reproducibility of $\text{Ca}(\text{OH})_2$ slurry-only operation. The average SO_2 removal observed after 5 runs on the pilot plant with Mississippi $\text{Ca}(\text{OH})_2$ slurry was 32.7 percent.

After the baseline was established, 4 additives were tested: acetic acid, adipic acid, boric acid, and ethylene glycol. Each additive was used at a concentration of 50 mmol/L of slurry. Only a weak effect of acetic acid and adipic acid on SO_2 removal could be measured, as shown in Table 6-3. Considering a weak effect of buffer additives, SO_2 absorption is likely not controlled significantly by liquid film resistance nor gas-film controlled. In a spray dryer vessel, gas phase mixing is provided by the disperser and controlled gas/liquid contact which reduces the gas film resistance. Therefore, the spray dryer represents the best case for liquid film control. In other words, if the SO_2 removal is mostly gas film controlled in the spray dryer, the chance of liquid film control for duct injection is even less.

TABLE 6-3. BUFFER ADDITIVES TESTS
(Ca/S = 0.9, SO₂ = 2,000 ppm, Δts = 22 °C, Additive = 50 mmol/L)

Additive	No. of Tests	Mean SO ₂ Removal [percent]	Standard Deviation
none	5	32.7	1.2
Acetic Acid	3	36.9	1.4
Adipic Acid	2	37.0	0.4
Boric Acid	5	32.4	2.8
Ethylene Glycol	2	35.6	0.4

6.1.4 Conclusions

The aforementioned results indicate:

- Acetic acid, or other comparable organic acids such as adipic acid, should be effective additives to enhance SO₂ absorption in slurry injection if SO₂ absorption is controlled significantly by liquid film resistance.
- Organic acids should be used at a concentration greater than 50 meq/l to have a significant effect on Ca(OH)₂ slurries.
- Previous analyses of fundamental and field data strongly suggest that SO₂ absorption into Ca(OH)₂ slurries is controlled usually by gas film resistance. Liquid film resistance will be most significant in the limit of high SO₂ concentration and low Ca(OH)₂ stoichiometry and, perhaps, with shorter drying times (larger approach to saturation). Initial test of organic acid additives should explore their effects at these conditions.
- Organic acid test could be used to test the hypothesis that the SO₂ absorption is gas-film-controlled. If no effect is detected of the organic acid on SO₂ absorption, SO₂ absorption likely is gas-film controlled.
- Only a weak enhancement of SO₂ removal could be measured when acetic or adipic acid were used. Since the spray-dryer tests represented the best case for liquid film control, the chance of liquid film control for DSD is slim.

Figure 6-2. Effect of sodium acetate on SO₂ absorption into clear solution containing 17-mM Ca(OH)₂ and 0.1-M CaCl₂ at 55 °C.

6.2 SLAKING MODIFICATIONS

Conventional slaking processes aim for fast and efficient conversion of CaO to Ca(OH)_2 , which is an exothermic reaction, with the purpose of producing a suspension of 3- to 5- μm particles of Ca(OH)_2 in water. This normally is done by optimizing the temperature and the solids content in the slurry, i.e., using a temperature of 85-95 °C and a solids content of about 25 percent (use of a paste slaker even allows handling of 30-35 percent solids). The particle size of the produced Ca(OH)_2 normally can be controlled to some extent by adjusting temperature and solids content during slaking. A too-low slaking temperature, however, would normally increase the risk of producing a coarse particle suspension with a significant amount of unconverted CaO .

6.2.1 Slaking With Water

A test program was undertaken to evaluate techniques for producing very fine particulate Ca(OH)_2 during slaking with the assumption that very fine Ca(OH)_2 slurry in the DSD process would be more reactive toward SO_2 than conventionally slaked material. Slaking was conducted in a laboratory-scale slaker consisting of a 0.4-L Pyrex beaker suspended in a constant-temperature oil bath. Similarly to the dry-hydration technique, a mechanical stirrer was used to mix the water and CaO . Each slaking was conducted by loading 10 g of Mississippi CaO into the slaker and allowing it to achieve thermal equilibrium in the bath. The stirrer was then started, and a single addition of water was syringed rapidly into the slaker at the desired ratio of $\text{H}_2\text{O}/\text{CaO}$. The amount of water used was sufficient to yield 10- to 50-percent solids in a slurry. The solids and water temperature was 25 or 100 °C. After completion of slaking, the sample was vacuum filtered and microwave-dried. Particle-size distribution was determined on the prepared sample. The particle-size distribution of slaked Ca(OH)_2 sample after drying was measured by the X-ray sedimentation technique.

The results of slaking experiments are presented in Figure 6-3, giving median particle size of slaked lime as a function of a slurry concentration for 2 slaking temperatures. No significant effect could be found of slurry solids percentage on median particle size (except for 40 percent slaking at 25 °C). Slaking at 100 °C resulted in a significantly finer product than that obtained as a result

Figure 6-3. Combined effect of slurry solids percentage and slaking temperature on the median particle size of slaked $\text{Ca}(\text{OH})_2$.

of slaking at 25 °C. For the range of slurry solids percentage tested, the median particle size of slaked Ca(OH)_2 was approximately 3 and 6 μm for 100 and 25 °C slaking, respectively.

The source of the CaO used in the slaking modification experiments was a commercial Mississippi CaO. In the next set of experiments, 3 CaO samples with dissimilar structural properties were produced. The production involved calcination of Mississippi CaCO_3 and subsequent slaking of CaO under conditions that yielded 2.92- μm Ca(OH)_2 when the commercial Mississippi CaO (100 °C, 26-percent solids slurry) was used. Structural properties of 3 CaO samples and of commercial Mississippi CaO are given in Table 6-4. The median particle size of Mississippi CaCO_3 used for calcinations at 1,000, 800, and 700 °C was 11.9 μm . As shown in Table 6-4, 3 CaO samples produced in-house had higher surface areas than commercial CaO. The last column of Table 6-4 presents a median particle size of Ca(OH)_2 resulting from slaking of CaO at 100 °C in 26 percent solids slurry. Generally, the median particle size of slaked Ca(OH)_2 decreased with increasing surface area of CaO used for slaking. Somewhat larger median particle size of Ca(OH)_2 resulting from slaking or 11.1 m^2/g CaO can result from higher initial amounts of surface water and CO_2 on this CaO as compared with

TABLE 6-4. STRUCTURAL PROPERTIES OF CaO USED FOR SLAKING

CaO Type	Surface Area [m^2/g]	CaO		Surface H_2O^c [wt%]	Combined H_2O^d [wt%]	Ca(OH)_2	
		Porosity	D_{50} [μm] ^b			CO_2^e [wt%]	D_{50}^f [μm]
Commercial	1.2	0.03	6.45	0.05	2.8	0.7	2.92
1,000 °C, 16h ^a	2.0	0.02	6.99	0.02	0.2	0.2	1.37
800 °C, 16h ^a	8.5	0.08	4.30	0.09	1.1	0.2	0.66
700 °C, 16 h ^a	11.1	0.14	5.83	0.12	1.1	1.8	0.88

^a CaCO_3 calcination conditions

^bMedian particle size of CaO

^cTGA weight loss 20-100 °C

^dTGA weight loss 300-540 °C

^eTGA weight loss 540-700 °C

^fMedian particle size of Ca(OH)_2 resulting from slaking (100 °C and 26-percent slurring)

8.5-m²/g CaO. Notably, a commercial CaO revealed the highest degree of rehydration (probably resulting from the contact of CaO with the surrounding air) among 4 CaO under consideration (2.8 weight percent, as detected by TGA). The extent of rehydration combined with relatively low surface area (1.2 m²/g) might have been the reason for considerably larger median particle size of slaked Ca(OH)₂ produced with commercial CaO.

6.2.2 Slaking with Water/Additives

Two surface-active additives were tested with the intention of decreasing median particle size of the resulting slaked Ca(OH)₂. Methyl alcohol was used to reduce the surface tension of slaking water. In turn, reduced surface tension of water would tend to increase the nucleation rate. Another additive tested was calcium lignosulfonate (trade name Lignonsite), known to enhance dispersion of dry-hydrated Ca(OH)₂. The source of CaO was a commercial Mississippi CaO.

In the first series of experiments, methyl alcohol and D.I. water were used for slaking. The ratio of alcohol-to-water varied from 1:10-2:1, and the slaking temperature was maintained at 74 °C. The results are presented in Figure 6-4, which shows the effect of alcohol-to-water ratio on median particle size of slaked Ca(OH)₂, as measured by X-ray sedimentation of a dried slurry powder. The lowest median particle size of 2.8 µm was measured for solids slaked with a mixture of alcohol-to-water at the ratio of 1:2. Slaking with water only produced slaked Ca(OH)₂ with a median particle size of 3.14 µm.

In the second series of experiments, 0.1- to 9-weight percent (CaO-based) calcium lignosulfonate was used. Calcium lignosulfonate was dissolved in water first and the solution was added to CaO. Slaking temperature was 100 °C. The results are presented in Figure 6-5, which presents the median particle size of slaked Ca(OH)₂ as a function of calcium lignosulfonate concentration. No significant decrease, compared with water-only slaking, of median particle size of slaked Ca(OH)₂ resulted from using surface-active additives during slaking.

Figure 6-4. The effect of alcohol-to-water ratio on median particle size of slaked Ca(OH)_2 .

Figure 6-5. The effect of calcium lignosulfonate concentration on the median particle size of siaked $\text{Ca}(\text{OH})_2$.

6.2.3 Conclusions

The following conclusions can be drawn from the slaking experiments discussed previously:

- Limited decrease of a median particle size of slaked $\text{Ca}(\text{OH})_2$ was possible when CaO with increased surface area was used for slaking.
- No significant decrease of a median particle size of slaked $\text{Ca}(\text{OH})_2$ was measured as a result of additives tested.

6.3 RECYCLE REACTIVATION

6.3.1 Wet Grinding

Wet grinding of spent Mississippi $\text{Ca}(\text{OH})_2$ and Beverly fly ash was tested to simulate the recycle reactivation during the DSD. Sample of spent $\text{Ca}(\text{OH})_2$ was generated by injecting Mississippi $\text{Ca}(\text{OH})_2$ downstream of the humidification point in the 50-cfm pilot plant. Once-through injection resulted in 26-percent SO_2 removal in the duct (2-s residence time) at $\text{Ca/S} = 2$, 11 °C approach to saturation, and 2,000-ppm SO_2 concentration. The pilot-plant run was made with the cyclone in line between the duct and the fabric filter. Solids intended for wet grinding were taken from the baghouse catch and dry-mixed with Beverly fly ash prior to wet grinding in the bench-scale attritor to simulate recycle reactivation in the DSD. Following 1 h and 15 min wet grinding of the baghouse catch/Beverly fly ash (weight ratio of 3.5:1), significant increases in the surface area and pore volume were measured. Structure properties of wet, ground baghouse catch/Beverly fly ash solids are shown in Table 6-5.

TABLE 6-5. STRUCTURAL PROPERTIES OF WET-GROUND BAGHOUSE CATCH/BEVERLY FLY ASH SOLIDS

Solids Type	Surface Area [m^2/g]	Pore Volume [cm^3/g]
Dry-Mixed, Unground	7.1	0.037
Dry-Mixed, Wet-Ground, 15 min	12.8	0.072
Dry-Mixed, Wet-Ground, 1 h	21.9	0.117

Reactivity of ground solids with SO_2 was tested in the STDR operated at 60-percent relative humidity (11 °C approach to saturation) and with 2,000-ppm SO_2 . Reactivity of the dry mixture of

baghouse catch/Beverly fly ash at the weight ratio of 3.5:1 was measured first. The reactivity of baghouse catch/Beverly fly ash solids wet ground in the bench-scale attritor was measured next. Under conditions of the STDR, 1 h and 15 min wet-ground solids were significantly more reactive with SO_2 than unground solids. Complete results are presented in Figure 6-6. Reactivity difference between 15 min and 1 h wet-ground solids was not significant.

6.3.2 Conclusions

The following conclusions can be drawn from the results presented previously:

- Significant increases in surface area and pore volume occurred as a result of 1 h and 15 min wet grinding.
- Wet-ground solids were significantly more reactive than unground solids.

Figure 6-6. Reactivation of spent $\text{Ca}(\text{OH})_2$ /fly ash by wet grinding (reactor: 2,000-ppm SO_2 , 60-percent relative humidity).

SECTION 7

REFERENCES

1. Babu, M., J. College, and D. Kanary, "1.0 Million BTU Combustor Testing: Test Results Part II," Report to DOE, Contract No. DE-AC22-85PC81012, December 1988.
2. Carr, R.L., "Evaluating Flow Properties of Solids," *Chemical Engineering*, 72, 163-168, January 18, 1965.
3. Carr, R.L., "Particle Behaviour Storage and Flow," *British Chemical Engineering*, 15, 1541-1549, December 1970.
4. Drummond, C.J., ed., "Duct Injection Technologies for SO₂ Control," Presented at First Combined FGD and Dry SO₂ Control Symposium, St. Louis, MO, 1988.
5. Dutta, A. and L.V. Dullea, "A Comparative Evaluation of Negatively and Positively Charged Submicron Particles As Flow Conditioners for a Cohesive Powder," presented at the AIChE 1989 Annual Meeting, San Francisco, CA, November 1989.
6. Hall, B.W., C. Singer, W. Jozewicz, C.B. Sedman, and M.A. Maxwell, "Current Status of ADVACATE Process for Flue Gas Desulfurization," presented at the 1991 Annual Meeting of the Air and Waste Management Association, Vancouver, B.C., June 1991.
7. Jenike, A.W, P.J. Elsey, and R.H. Woolley, "Flow Properties of Bulk Solids," *A.S.T.M. Proceedings*, 60, 1168-1181, 1960.
8. Jorgensen, C., J.C.S. Chang, T.G. Brna, and C.B. Sedman, "Small-Scale Pilot Evaluation of Calcium- and Sodium-Based Sorbents for Dry SO₂ Removal," presented at AIChE National Meeting, Houston, TX, April 1987.
9. Jozewicz, W. and G.T. Rochelle, "Fly Ash Recycle in Dry Scrubbing," *Environmental Progress*, 5, 218-223, November 1986.
10. Jozewicz, W., J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Silica-Enhanced Sorbents for Dry Injection Removal of SO₂ from Flue Gas," *JAPCA*, 38, 1027-1034, August 1988a.
11. Jozewicz, W., J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Characterization of Advanced Sorbents for Dry SO₂ Control," *Reactivity of Solids*, 6, 243-262, December 1988b.

12. Jozewicz, W., C. Jorgensen, J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Development and Pilot Plant Evaluation of Silica-Enhanced Lime Sorbents for Dry Flue Gas Desulfurization," *JAPCA*, **38**, 796-805, June 1988c.
13. Newitt, D.M. and J.M. Conway-Jones, "A Contribution to the Theory and Practice of Granulation," *Trans. Instn. Chem. Engrs.*, **36**, 422-440, December 1958.
14. Peterson, T., J. Peterson, H.T. Karlsson, and I. Bjerle, "Physical and Chemical Activation of Fly Ash to Produce Reagent for Dry FGD Processes," *Proceedings: First Combined Flue Gas Desulfurization and Dry SO₂ Control Symposium*, EPRI GS-6307, **2**, 7-165, April 1989.
15. Peterson, J.R., "Aqueous Reaction of Fly Ash and Ca(OH)₂ to Produce Calcium Silicate Absorbent for Flue Gas Desulfurization," M.S. Thesis, The University of Texas at Austin, August 1987.
16. Peterson, J.R. and G.T. Rochelle, "Aqueous Reaction of Fly Ash and Ca(OH)₂ to Produce Calcium Silicate Absorbent for Flue Gas Desulfurization," *Environ. Sci. Technol.*, **22**, 1299-1304, November 1988.
17. Rumpf, H., "Particle Adhesion," *Agglomeration 77: Proceedings of the 2nd International Symposium on Agglomeration*, K.V.S. Sastry, ed., American Institute of Mining, Metallurgical, and Petroleum Engineers, Inc., New York, NY, 1977.
18. White, W.G., "Differential Reaction of SO₂ in Flue Gas with Lime-Based Sorbents at 66 °C for 10 to 7200 Seconds," M.S. Thesis, The University of Texas at Austin, 1989.

END

**DATE
FILMED**

5 / 5 / 92