CAP 113-ATF-94C

Inverse Free-Electron Laser Accelerator Development

A. Fisher, J. Gallardo, A. van Steenberg
NSLS and Department of Physics, BNL

J. Sandweiss
Department of Physics, Yale University

and

J.-M. Fang
Department of Applied Physics, Columbia University

June 1994

CENTER FOR ACCELERATOR PHYSICS

BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.

Under Contract No. DE-AC02-76CH00016 with the

UNITED STATES DEPARTMENT OF ENERGY

6th Workshop on Adv. Accel. Concepts, Lake Geneva, WI, June 12-18, 1994

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Inverse Free-Electron Laser Accelerator Development*

A. Fisher, J. Gallardo, A. van Steenberg
National Synchrotron Light Source and Department of Physics
Brookhaven National Laboratory
Upton, NY 11973

J. Sandweiss
Department of Physics,
Yale University
New Haven, CT 06511

Jyan-Min Fang
Department of Applied Physics,
Columbia University
New York, NY 10027

Abstract

We present a design of a short accelerator module making use of the Accelerator Test Facility, high brightness, 50 MeV linac and its high power CO₂ laser.

The study of the INVERSE FREE ELECTRON LASER, as a potential mode of electron acceleration, has been pursued at Brookhaven National Laboratory for a number of years. More recent studies focused on the development of a low energy (few GeV), high gradient, multistage linear accelerator.¹ We are presently designing a short accelerator module, which will make use of the 50 MeV linac beam and high power (2×10^{11} W) CO₂ laser beam of the Accelerator Test Facility (ATF) at the Center for Accelerator Physics (CAP), Brookhaven National Laboratory. These elements will be used in conjunction with a fast excitation (300 μ sec pulse duration) variable period wiggler, to carry out an accelerator demonstration stage experiment.

The wiggler makes use of alternating stacks of Vanadium Permanganate (VaP) ferromagnetic laminations, periodically interspersed with conductive, nonmagnetic laminations, which act as eddy current induced "field reflectors."² A typical period length taper for the IFEL experiment is $\lambda = 3.0 - 5.0$ cm, $\frac{d\lambda}{dz} \approx 4\%$. Maximum field enhancement of approximately a factor of 2 is obtained with the use of the field reflectors.³ Other wiggler parameters are: gap = 4 mm; $B_{max} \approx 14$ kG ($I = 6$ kA) and maximum field variation pole-to-pole, $\sigma(\Delta B/B) \approx 0.2\%$. The wiggler configuration is illustrated in Fig. 1. The CO₂ laser beam will be transported through the IFEL interaction region

*Work performed under the auspices of the U.S. Department of Energy.

MASTER

REPRODUCED FROM DOCUMENT BNL-61342

Figure 1: Variable period wiggler consistent of stackable, interleaved VaP laminations and Cu eddy current 'field reflectors'

by means of a low loss dielectric coated metallic rectangular waveguide or a dielectric circular waveguide. Waveguide test sections have been constructed and have been tested using a low power cw CO₂ laser ($\lambda = 10.6 \mu m$). The results are indicated in Fig. 2. For a 1 m long, 2.8 mm i.d., circular dielectric, single crystal extruded Al₂O₃ (sapphire) guide, an attenuation coefficient α [defined by $\frac{P(z)}{P_0} = \exp(-2\alpha z)$] of 0.18 dB/m has been measured. In parallel with the low loss guide experimental program, 2D diffraction type calculations are in progress, preliminary results of which support the feasibility of coupling efficiently the laser Gaussian beam into the desired low loss guide mode, in a coupling guide length of ≈ 0.5 m. The IFEL design is supported by the development and use of 1D and 3D simulation programs. The 1D program has been used to define an optimal tapered wiggler for given values of laser power P , synchronous phase Ψ and wiggler magnetic field B_{max} ; and has been used to calculate bucket acceptance and bucket leakage of a single or multistage accelerator for a number of laser power, guide losses, wiggler errors and electron beam energy spread and emittance cases. The 3D code has been used to study beam walk-off, displacement and steering; and transverse phase space and emittance growth. An example of the IFEL simulation is given in Fig. 3. An experimental test of IFEL electron beam acceleration is scheduled to be carried out at the BNL ATF during the latter part of the year 1994. Initially, this will be done with a CO₂ laser power of 5×10^9 W, limiting the energy gain of the electron beam (45 MeV) to 2.5 MeV. Subsequently, making use of a power upgraded CO₂ laser, enhanced electron beam energy gain should be achievable, as indicated in Table I.

Figure 2: Waveguide transmission of CO_2 laser beam with a waist at the entrance of $\omega_o = 1$ mm. a) Radius, b) Transmission as a function of the length of the waveguide

Table 1. Parameters for an IFEL experiment at the Accelerator Test Facility

Electron Beam		
Injection energy		48.9 MeV
Exit energy		87.95 MeV
Mean accelerating field		89 MV/m
Current, nominal		5 mA
N (bunch)		$6 \times 10^9 e^-$
I (max)		100 A
$\Delta E/E$ (1 σ)		$\pm 3 \times 10^{-3}$
Emittance (1 σ)		7×10^{-8} m-rad
Beam radius		0.3 mm
Wiggler Parameters		
Wiggler length		0.47 m
Section length		0.6 m
Period length		2.86-4.32 cm
Gap		4 mm
Field (constant B mode)		1.25 T
Horiz. max. amplitude		0.17-0.22 mm
Laser parameters		
Power		2×10^{11} W
Wavelength, λ		10.2 μm
Max. Field		1.36×10^4 MV/m
Guide loss par. α		0.025 m^{-1}
Field attenuation/section		0.13 dB
Pulse length (FWHM)		6 ps

Figure 3: 3-D simulation results; first figure (clockwise, starting from the top-left) shows the number of accelerated and non-accelerated particles; next figure is the $\gamma - \Psi$ phase space; following is the vertical transverse phase space ($y - y'$) and the last one is ($x - x'$)

The experimental arrangement to be used is shown in Fig. 4.

Figure 4: Experimental setup of an IFEL experiment at the Accelerator Test Facility

REFERENCES

1. A. Fisher, J. Gallardo, J. Sandweiss, A. van Steenbergen, "Inverse Free Electron Laser Accelerator," III Workshop on Advanced Accelerator Concepts, Port Jefferson, NY, June 1992.
2. A. van Steenbergen, Patent Application 368618, June '89 (issued Aug. 1990).
3. A. van Steenbergen, J. Gallardo, T. Romano, M. Woodle, "Fast Excitation Variable Period Wiggler," Proc. PAC. IEEE, San Francisco, CA 1991, p. 2794.