EGG-EP--10295

DE93 005239

Electric and Hybrid Vehicle Program

Site Operator Program

Quarterly Progress Report for January through March 1992 (Second Quarter of Fiscal Year 1992)

J. F. Warren

Published May 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415**

**Prepared for the
U.S. Department of Energy
Assistant Secretary for Conservation and Renewable Energy (CE)
Under DOE Idaho Field Office
Contract No. DE-AC07-76ID01570**

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED *eb*

CONTENTS

Summary	v
Significant Items	vi
Advisory Information	vi
Site Operators	
Arizona Public Service	1
Kansas State University	1
Orcas Power & Light Company	2
Pacific Gas & Electric	5
Platte River Power Authority	17
Public Service Electric & Gas Company	18
Southern California Edison	19
University of South Florida	23
York Technical College	28

APPENDICES

A. Arizona Public Service - Operating, Maintenance & Cost	A-1
B. Pacific Gas & Electric Co. - Minutes of G-Van User Group Meeting	B-1
C. Public Service Gas & Electric Co. - G-Van Operating Data	C-1

SUMMARY

Activities during the second quarter included the second meeting of the Site Operators in Phoenix, AZ in late April. The meeting was organized and hosted by Arizona Public Service (APS) and was held in conjunction with the Solar and Electric 500 Race activities.

Delivery of vehicles ordered previously has begun, although two of the operators are experiencing some delays in receiving their vehicles. Public demonstration activities continue, with an apparent increasing level of awareness and interest being displayed by the public.

Initial problems with the Site Operator Database have been corrected and revised copies of the program have been supplied to the Program participants. Operating and Maintenance data is being supplied and submitted to INEL on a monthly basis.

Interest in the Site Operator Program is being reflected in requests for information from several organizations from across the country, representing a wide diversity of interests. These organizations have been referred to existing Site Operators with the explanation that the program will not be adding new participants, but that most of the existing organizations are willing to work with other groups. The exception to this was the addition of Potomac Electric Power Company (PEPCO) to the program. PEPCO has been awarded a subcontract to operate and maintain the DOE owned G-Van and Escort located in Washington, DC. They will provide data on these vehicles, as well as a Solectria Force which PEPCO has purchased.

The Task Force intends to be actively involved in the infrastructure development in a wide range of areas. These include, among others, personnel development, safety, charging, and servicing. Work continues in these areas. York Technical College (YORK) has completed the draft outline for the EV Technician course. This is being circulated to organizations around the country for comments. Kansas State University (KSU) is working with a private sector company to develop a energy dispensing meter for opportunity charging in public areas. The prototype of the meter has been shown to several organizations and has been well received. Preliminary indications are for an initial need for several thousand of the meters which would be used at locations around the country. Pacific Gas and Electric (PG&E) is working with several organizations on the

development of inductive charging systems. Initial test results are promising, providing high efficiencies and increased safety.

Several of the Operators reported increasing awareness and interest in EVs by the public. This was reflected in the number of persons visiting, and the questions being asked, at EV displays and "Ride and Drive" demonstrations.

SIGNIFICANT ITEMS

None

ADVISORY INFORMATION

One of the vehicles entered in the Electric Stock Car Race at the Solar and Electric 500 races was powered by a Johnson Controls Zinc Bromine battery. Approximately 90 minutes into the two hour race the battery malfunctioned and discharged a cloud of Bromine gas onto the race track. The driver and fifteen other individuals were admitted to a local hospital as a result of Bromine inhalation. The driver was in serious condition, the others were released shortly after admission. The driver recovered and was released the following week. The incident is under investigation and further information on the cause will be provided as it becomes available.

The significant item is in the treatment of batteries. There has been an awareness of the safety issues surrounding the high voltages involved with the current generation of EVs. With the increasing use of high temperature and exotic materials in the batteries, this awareness must be extended.

SITE OPERATORS

Arizona Public Service (APS) has discussed the possibility of using four electric busses at the Grand Canyon National Park. Park officials are very interested in the idea. Discussions are continuing.

APS reports getting a range of over 100 miles from one of their EVcorts. The Sonnenschein pack in this vehicle has been in the car for over 12,000 miles.

APS reports that they are now getting approximately 40 miles range on their G-Vans. Based on the performance to date they are expecting in the range of 8000 miles life on the Chloride batteries. They are talking with Conceptor about the possibility of testing Sonnenscheins in the vans. APS also reports that their Solectria Force is providing a range of 15-17 miles. The vehicle has been driven less than 2000 miles and has had one module replaced. APS also reports one of their EVcorts, with approximately 10,000 miles on the Sonnenschein pack was driven 83 miles without opportunity charging while being demonstrated in Flagstaff.

Operating, maintenance, and cost data for the APS fleet are included as Appendix A to this report.

Kansas State University (KSU) has seen a significant increase in both the private and public sector's interest in electric vehicle transportation. KSU has been involved in EV demonstrations for groups including Federal and local government representatives, senior Corporate executives, and students. The response to these demonstrations indicates personal interest is growing in the electric vehicle marketplace. KSU reports the most often asked questions are: 'When are electric vehicles going to be available to the public and what will the cost be?'

KSU recognizes that market preparation for this new product is extremely important to market acceptance. Further, this preparation is necessary to minimize efforts in order to maintain reasonable product pricing. As such, providing the public with an early opportunity to evaluate this product, offer comments and establish the necessary infrastructure in an orderly manner are

all key elements in the development of electric vehicles. KSU is involved in all facets of these operations.

KSU is presently working with Grumman Allied and Unique Mobility to establish a working agreement for the research and development of a pure electric postal vehicle. KSU has worked on the design of this vehicle for the past year and is working to establish the appropriate consortium to bring this vehicle to commercial realization. The U.S. Postal Service, with its large standardized vehicle fleet and short range requirements, is seen as an ideal setting for the introduction of electric vehicles.

KSU is working to establish infrastructure support for electric vehicles. Presently, a Kansas company is working with KSU to bring its patented low-cost vehicle metering product to market. An anticipated second year DOE project would provide 100 electric metering stations to Southern California for a large scale electric vehicle infrastructure demonstration project. This project would allow a parking lot(s) to be made EV ready. These electric metering stations are not a revolutionary but rather evolutionary step in providing support for the introduction of large numbers of electric vehicles throughout the United States. The general public, or specific state or commercial businesses would then have the opportunity to use these meters on a day-to-day basis for test and evaluation. Customer feedback would be used to provide improvements, as necessary, for the next generation of electric vehicle metering stations.

KSU's Site Operator Program continues to get the "word out" about electric vehicles. KSU's G-Van has logged an average eighteen miles per day while maintaining a full schedule of public relations tours within the state of Kansas and Missouri. KSU has now been contacted by companies in Nebraska and Iowa requesting information and involvement in this program.

Orcas Power and Light Company (OPALCO) is a rural electric coop serving 9000 customers on 20 islands in northwest Washington State. As a result of vehicle delivery schedules, this is the first quarterly report covering activities of OPALCO. It covers activities during September, October, November and December of 1991. During this period OPALCO has operated two EVs and, as have other Site Operators, reports increase in public interest. This is significant as public exposure is one of the main goals of the OPALCO EV program.

Significant Events.

A. Notification of Grant Award

In September OPALCO was notified that the company had been selected to participate in the Site Operator Program. This allowed OPALCO to proceed with the purchase of their G-Van.

B. Fleet Mechanic to Conceptor Headquarters for Training

One of the OPALCO fleet mechanics attended an in depth G-Van training session in Newmarket, Ontario. The intent was to provide OPALCO with sufficient understanding of the G-Van motor, controller and batteries so as to allow them to perform as much maintenance and/or repairs as possible on site, independent of Conceptor. As a result of meeting with the factory people OPALCO is also better suited to work with Conceptor over the phone on diagnostics. The workability of this relationship is a key to the ultimate viability of electric vehicles, particularly in locations remote from large metropolitan areas.

C. Took Delivery of First Electric Vehicle

On October 16th OPALCO took delivery of G-Van Number 98.

D. Took Delivery of Second Vehicle, a Solectria Force

This vehicle was picked up in Everett, Washington by a Solectria representative who lives on Orcas Island. The size difference between the Solectria and the G-Van resulted in an immediate popularity for the Solectria vehicle.

OPALCO has not attended any of the Site Operator or Task Force meetings. This is the result of limited travel budgets within the company. OPALCO will negotiate with DOE to modify the funding level to support attending future meetings.

The electric vehicle program has been a subject at many local meetings. Some of those include Orcas Power and Light Company board meetings, Lions Club, School Classes, Employee Meetings, Senior Citizen lunches and neighborhood meetings.

Publicity prior to the vehicle's arrival created a definite interest in them as evidenced by phone calls, people stopping by the office and, perhaps most often, in contacts with employees outside the work environment.

New Vehicles/Components/Batteries - As noted above, OPALCO has received two vehicles in this quarter; a G-Van and a Solectria Force. In addition to the much smaller size, the Force differs from the G-Van in that it is equipped with an on board charger, automatic regenerative braking and a dashboard mounted governor on the battery discharge rate. The on board charger, in particular, has proved to be very popular with users.

The batteries in both vehicles are lead acid. The G-Van batteries are automatically topped off by connecting a watering trolley. The Solectria batteries are watered in the traditional manner. There are fewer batteries in the Solectria and replacements are available at Sears.

Operations and Activities - Both vehicles are available for use by all employees. Typical uses include bank, mail and airport runs by the administrative people, and field trips by the Engineering Department.

The van is always used when space, weight or seating capacity requires it. The Solectria is selected when all else is equal and preference and maneuverability are the basis for the operators decision.

Maintenance of both vehicles has been made easier by Conceptor's involvement with the G-Van and a local representative for Solectria.

The G-Van has had the motor and controller replaced. This work was recommended by Conceptor after analysis was done by Conceptor over the phone with the OPALCO mechanic. The problem was that the motor would not run. We have not received word back on any suspected cause. Intermittent starting also resulted in Conceptor overnight mailing to OPALCO some relays. When these were installed the problem was solved.

Operations Date Vehicle Number 1 (DOE #50) G-Van

Total Miles Driven	733
Miles per Day	16.4
Miles per Month	209
Average kWh/Mi.	1.60

Operations Date Vehicle Number 2 (DOE #51) Solectria

Total Miles Driven	268
Miles per Day	19.1
Miles per Month	268
Average kWh/Mi.	.20

Summary and Conclusion - OPALCO EV drivers report that "Getting used to the van first gave us all an impression of 'the electric vehicle' from that perspective. That is, the G-Van is large, heavy and not as maneuverable as most individual's personal cars. While it is not an impression that is created by the 'electric' aspect of the vehicle, it is something that takes place in a driver's mind."

"When the Solectria arrived it immediately became the vehicle of choice when payload and space were not a factor. Again, this is not for any technical, range or electric reason but just maneuverability and similarity to a driver's personal car."

"In conclusion, our program will result in sufficient use of the EV's to find just where their niche is. This first quarter of activity has left us with added enthusiasm toward the future of our program and of EV technology. Public interest is the highlight of the program for the last three months."

Pacific Gas and Electric (PG&E) continues its active involvement in electric vehicle (EV) evaluation and infrastructure development. PG&E activities are concentrated in two primary areas:

1. Testing and evaluating pre-commercial and limited-production commercially available EVs and advanced EV components.

2. Development and evaluation of mechanisms to safely and efficiently supply electricity for EVs while minimizing the impact of these vehicles on the transmission and distribution system.

Activities in the first quarter of 1992 range from in-house R&D projects to active participation in the Electric Power Research Institute's (EPRI's) national Infrastructure Working Committee (IWC) and the California statewide Electric Vehicle Task Force.

The goals of PG&E's electric vehicle program are to support EV introduction and to develop the infrastructure necessary for the successful introduction of these vehicles. Participation in the Department of Energy (DOE) Electric and Hybrid Vehicle Site Operator Program is a major component of this EV program.

Significant Events - Pacific Gas & Electric (PG&E) operates three electric G-Vans as part of the DOE Electric and Hybrid Vehicle Site Operator Program. PG&E bought the three vehicles from Conceptor Industries, Canada, during 1989 and 1991. The first vehicle purchased was a prototype G-Van. The other two vehicles are production G-Vans--one cargo and one passenger version.

The prototype G-Van is used primarily for research and development activities at PG&E's R&D facility in San Ramon, California. Test applications investigated with the G-Van include:

- A. Installation of a variable-speed air conditioner yielding a 10% improvement in efficiency over the original equipment (OE) model.
- B. Development and retrofitting of an inductive charging system. The first version of the inductive charger was tested to be 93% efficient, with a charging time of 3.5 hours.

During installation and testing of this inductive charging system, the G-Van controller was damaged. The controller was subsequently replaced by PG&E R&D staff in August 1991. Following the controller replacement, an accidental explosion damaged two monoblocs in the

battery pack. The cause of the explosion has been investigated and final results should be available in the next quarterly report. David Harris of Chloride EV Systems replaced the monoblocs, with help from PG&E R&D.

In October, the inductive charging unit was modified. It is currently being tested for efficiency, power quality, and electromagnetic field (EMF) strength.

The production cargo G-Van is used in a fleet operation. Having met the requirement for limited service and mission requirements, the Sonoma County School District (SCSD) was awarded use of the cargo G-Van for one year. The vehicle is used for deliveries and has logged 1,700 miles since it entered service in May 1991. User response has been very positive.

Beginning in October, average daily mileage between charges began to diminish. This range reduction was greater than Conceptor had predicted on the basis of lower ambient air temperature. Around this time, Conceptor announced a problem with the ferroresonant charger. This problem prevented the vehicle from receiving a full charge. A charger control chip was replaced and internal tapping settings were also changed.

The passenger G-Van is operated by PG&E's clean air vehicle department. There were initial problems with the vehicle on delivery:

- faulty shift selector
- body damage
- brake-fluid leak

These problems were not associated with the electric conversion and were corrected at a GMC dealership. This G-Van was used for public demonstrations during April-December 1991.

On November 15, 1991 PG&E hosted a G-Van User Group meeting. During this meeting, Conceptor explained the charger problem discussed above and outlined corrective actions. For information on G-Van experiences among a group of operators, the minutes from this meeting are included as Appendix B.

Described below are significant events for the second quarter of FY-1992.

In January, the prototype G-Van (DOE 301) experienced a traction motor failure. After the vehicle did not respond to setting the selector in forward or reverse, PG&E technicians performed the trouble-shooting procedures outlined in the manufacturer's service manual. At the conclusion of these procedures, it was determined that the traction motor had failed. Dave Harris of Chloride was informed of the event and concurred with these findings after a review of trouble-shooting/diagnostic procedures.

This was the second motor failure in this G-Van. The original motor failed due to a stripped spline shaft causing slippage in both forward and reverse, which resulted in complete motor failure. The failed replacement motor was removed from the vehicle for further evaluation. The motor evidenced only slight wear, the failure being caused by cracked brushes. After complete motor inspection, it was determined that repairs could be made by using parts from the original motor. Parts were swapped and the failed motor was rebuilt. Specific components and their repairs follow:

1. Commutator refaced
2. Brushes and field replaced with those from the original motor
3. Commutator reinsulated with high-temperature silicon

The rebuilt motor is working, and its resistance and voltage readings are in accord with the manufacturer's specifications.

In February, a six-month inspection was performed on EPRI's G-Van 3001 as per the manufacturer's maintenance schedule. The only abnormal finding was that five battery hold-downs were cracked. These parts were replaced in March (3/9/92).

During the first quarter of 1992, the G-Van used by SCSD experienced a significant reduction in range. A number of efforts were made to bring the range of the Sonoma G-Van back up to a satisfactory level:

1. Range tests were conducted at PG&E's San Ramon R&D facility.
2. A Spiegel charger was used for charging at San Ramon, rather than the CEN charger that had been used in Sonoma. The use of the Spiegel charger resulted in an immediate range improvement from 9 miles to 40 miles.
3. The vehicle was refumed to Sonoma county, after Sonoma's CEN charger was upfitted with a new microprocessor chip and its tappings settings were changed.
4. Range deteriorated after the vehicle was returned to Sonoma, and the vehicle was returned to San Ramon R&D. R&D will conduct range evaluations using a CEN ferroresonant charger. The performance of both the CEN charger and the G-Van will be monitored by PG&E staff.

PG&E R&D continued its work on the inductive charger. The charger is currently undergoing testing in the following areas:

1. Efficiency
2. Power factor
3. Power quality
4. Electromagnetic fields (EMF)
5. Noise
6. Misalignment effects

Tests to optimize performance have been completed. Work is continuing on power factor correction. Charging time is approximately 3-4 hours, however, this charging time is the same as that of the Spiegel charger, indicating low battery capacity. The remaining tests will be performed using a different G-Van battery pack.

In addition to testing this charger, PG&E has negotiated with Hughes to use and evaluate the Hughes prototype inductive charger.

PG&E is also developing a public charging demonstration in cooperation with Bay Area Rapid Transit (BART). The project includes the use of an electric "station car" and a dedicated charging facility located at a BART station.

Meetings/Publicity - PG&E participated in a wide range of EV meetings during this reporting period. Subjects covered in these meetings included:

- Development of new EV programs
- Infrastructure development
- State EV programs and initiatives
- EV and battery technology
- New product availability

A list of the meetings follows.

January 8	Meeting with BART to discuss station car concept and evaluate possible vehicle options for demonstration project.
14	Meeting with California Electric Vehicle Task Force to discuss EV commercialization. Discussed NHTSA notice of proposed rule making. PG&E representative Dan Fitzgerald was elected co-chair of task force.
15	Meeting with Toyota R&D to discuss their electric vehicle program.
16	Meeting with Placer County officials and Auburn PG&E Service Center to discuss EV technology and options for implementing a plan to incorporate EVs into fleet and individual use. Public education was identified as a major goal. An Alternative Fuel Day event was planned to increase public awareness.
20	Meeting with Sutter Bay Development Group to discuss EV technology in general, along with distributed generation technologies such as photovoltaic and wind energy. The Sutter Bay group is very interested in a neighborhood vehicle concept.
21	EPRI Task Force and Working Group meetings. Topics covered include: lead-acid, Ni-Fe, Ni-Cd, Ni metal hydride, Na/S, Zn-air, Ni/Zn, and lithium polymer battery testing; the Hughes inductive charging unit; the Nissan FEV and fast charger projects; power quality and EMF testing protocols; LA's 10-point plan to be EV friendly; and the LA301.

- 22 Meeting between PG&E's R&D and Clean Air Vehicle (CAV) departments to discuss plans for a public charging demonstration at a BART station. The initial work scope and schedule were created.
 - 24 Meeting with Andy Frank of UC Davis and Fang Chen of ORNL regarding electric vehicle HVAC. They are proposing a project to look at an integrated passive and active vehicle heating and cooling design.
 - 30 Meeting with Hope Technologies to discuss solid-state, rechargeable lithium batteries.
- February 3 Meeting with John Dabbles of GM regarding GM EVs.
- 5 Meeting with EPRI to discuss inductive charging projects.
 - 6 Meeting with Ray Bemardi regarding EV charger technology.
 - 12 Meeting with EPRI to discuss USABC.
 - Meeting with Bob Davis to discuss Chrysler EV program.
 - 13 Presentation to the ASME student body chapter at Cal Poly and to the Central Coast ASME chapter in San Luis Obispo. The presentation covered air emission regulations, EV and NGV technology, and PG&E's CAV program.
 - 14 Meeting with John Wallace to discuss the Ford EV program.
 - 19 Meeting with CAVTC management regarding installation of EV charging facilities.
 - 21 Meeting with BART regarding station car concept.
 - 27 Meeting with Jack Guy of EPRI to discuss USABC.
 - 28 Meeting with Tom Lippo of the University of Wisconsin to discuss advanced motors for EVs.
- March 2 Meeting with Kurt Bell regarding EMF testing equipment and procedures.
- 4 Meeting of R&D and CAV departments with the New Energy and Industrial Technology Development Organization (NEDO) to discuss PG&E's electric vehicle program and NEDO's lithium battery development.
 - 13 Meeting with California Electric Vehicle Task Force. Discussed EV infrastructure, vehicle test results, industry activities, and task force EV activities.

- 18 Meeting with Technobeam Corp. to discuss an advanced electric vehicle propulsion system.
- 20 Follow-up meeting on PG&E/BART public charging station project.
- 23 Meeting with EPRI to discuss EV Center concept.
- 24 Meeting with Hughes regarding inductive charging project.
- 25 EPRI Infrastructure Working Committee meetings. Four subcommittees were formed: Connecting, Building Codes, Power Quality and EMF, and Utility Information and Customer Education. PG&E representative Roland Risser is the chairman of the PQ and EMF subcommittee and is a member of the Connecting subcommittee.

Publicity - PG&E has participated in a large number of G-Van demonstrations. Below is a partial list of the meetings and events at which the G-Van was displayed or demonstrated. At these events, PG&E personnel were available to answer questions about electric vehicles and the G-Van.

Reactions from G-Van riders and spectators are commonly positive. Most people are very excited about the advent of electric vehicles and nearly every person asks when these vehicles will be available to the general public. Although some people are discouraged by the G-Van's limited range, when they hear that range will increase with future vehicles, their excitement is somewhat renewed. Generally, people are supportive of the EV movement and are excited about owning an EV in the future.

In addition to media coverage of specific events, PG&E's loan of a G-Van to the Sonoma County School District was reported by local radio station KNOX.

<u>Date</u>	<u>Event</u>
April 10	Apple Computer Transportation Fair in Cupertino, California
17	Stock holders' meeting, San Francisco, Masonic Auditorium
19	Dow Chemical in Antioch
23	Earth Day at Livermore High School

May	3-5	Wilderness Society Meeting, Yosemite Valley
	6-7	Annual Customer Service Meeting, Monterey
July	12-14	Big Foot Car Classic Auto Show, Willow Creek
August	12	California Energy Commission Demonstration Program Workshop, Sacramento
	21	Freeway Dedication (John T. Knox Freeway - 580), Richmond
	26	Opening of new Water District Office, Monterey
Sept.	9	Lawrence Livermore Laboratory Energy Fair, Livermore
	9-11	Solar Energy Expo and Rally, Willits
	13	Transportation Fair, Concord
	20	Ride Share Week, Sacramento
	23	ESL Transportation Fair, Sunnyvale
	24	Lockheed Transportation Fair, Sunnyvale
October	5	San Jose Solar Fair, San Jose
	12	Columbus Day Parade, Martinez
	26	Third Annual Clean Air Fair, Reno, Nevada
	30	Lockheed Transportation Fair, Palo Alto
Nov.	21	Renewables are Ready Exhibit, De Anza College, Cupertino
December		Published and distributed Electric Vehicle brochure

Because of extensive R&D vehicle use, publicity use of the G-Van was limited during the first quarter of 1992. Major activities included:

January 17 Energy Expo 2000

February 1 Asian New Year's Parade

In addition to the public displays and events listed above, PG&E participated in two G-Van user group meetings organized by EVDC. In August, a representative of PG&E's clean air vehicle staff attended the South Central EV Symposium meeting and participated in the G-Van User Group. In November, PG&E sponsored a G-Van User Group meeting in San Francisco, California. Representatives from PG&E's clean air vehicle and R&D departments were present.

PG&E is also supporting national and statewide EV activities. We are active on the California EV Task Force, and have been an active member of both EPRI's Infrastructure Working Committee and EVDC's Product Introduction Committee.

New Vehicles/Components/Batteries - As a result of testing an inductive charging system, both the controller and two monoblocs needed to be replaced in the prototype G-Van (purchased by PG&E in 1989). During testing, the system was shorted, damaging the controller. PG&E's R&D facility installed a new controller in August 1991. After the controller was replaced, two monoblocs exploded. With R&D's assistance, David Harris of Chloride EV Systems installed the two new monoblocs in September 1991. A subsequent load test showed very good performance. The battery pack capacity was 202 amp-hours; 98.9% of rated capacity.

The inductive charging system being tested operated at 240 volts, single phase, and 60 amps. The system could fully charge the battery pack in 3.5 hours, with an average efficiency of 93%. The inductive charging tests were very successful, and as a result the design was modified to a lighter, more compact configuration. The new design has been reinstalled and is currently being tested for efficiency, power factor, power quality, EMF, and misalignment effects. This charging system is automated, making it an attractive tool for high-power fast charging. PG&E's work with inductive charging has prompted vehicle manufacturers to consider it as an option to the conventional plug and cord system.

Negotiations for new vehicles are under way, and PG&E has agreed to lease five Ford Ecotars for delivery in 1993. PG&E is also communicating with GM and Chrysler, as well as with Japanese and European manufacturers. PG&E will continue to test and evaluate new vehicles, analyzing their impact on the utility grid and working with the manufacturers to ensure efficient and compatible vehicle and charging systems.

Operations and Activities - Much of the servicing performed in 1991 was required by the prototype G-Van. Two new component installations were a direct result of R&D modifications. The other servicing requirements were routine or as a result of a Conceptor design modification.

The biggest operational problem was the production G-Van charger. Until October, the performance of the vehicle was good. Then, the average ambient air temperature dropped to 40°F (10 °C) during overnight charging. Although Conceptor admits that cool ambient temperatures do affect the battery capacity up to 1% per °C below 30 °C, the decrease in range was significantly greater than this adjustment would suggest. In other words, if the normal average range were 40 miles, then the adjusted range should have been 32 miles. However, the vehicle range was reduced to as little as 9 miles per day.

Several other production G-Vans had been experiencing the same problem. After an investigation, Conceptor announced that the chargers needed modifying. A control chip was redesigned and the internal tappings were changed to increase the initial and final charging voltages. This modification would increase the overall charging voltage and allow sufficient time to charge the batteries to full capacity.

The other major maintenance requirement has been the routine six-month service. This service requires a full eight-hour day for one person, with the help of several assistants at various times. The six-month service includes: inspection of the traction motor, the AC motor brushes, and the commutators; inspection of the charger plug and all drive belts; and inspection, cleaning, and measurement of the batteries.

Watering the vans has not presented a problem. The watering trolleys have worked as expected, and the average watering time is 20 minutes. Both the prototype and the passenger vans have required large amounts of water at various times, and occasionally have taken extremely unequal amounts on the two sides of the pack. To date, there is no explanation from Conceptor for this behavior.

Except as noted below, operations have been uneventful. The vehicles have performed as expected and continue to serve productive purposes.

<u>Date</u>	<u>Service</u>
January 28	Power steering controller modification on prototype G-Van
February 11	Modification on traction motor, installation of spacer and machining of pinion gear on prototype G-Van
July 31	Installation of upfit kit on production passenger G-Van

The major G-Van operational problem has been the vehicles' limited range. The degradation in range from 40 miles to 9 miles for the SCSD G-Van (# 302/) is under investigation. Areas being examined by PG&E and Conceptor Industries include:

1. Effects of ambient air temperature on Chloride battery performance - PG&E is evaluating data that indicate a strong direct relationship between daily range and ambient air temperature.
2. Charger performance - Line voltage variation, tap settings and suboptimal charging profiles appear to have contributed to reduced range.
3. Effects of over- and undercharging on battery performance and cycle-life. EPRI, Conceptor, and Argonne National Laboratory are investigating whether suboptimal charging can cause physical damage to battery packs.

PG&E performed the six-month inspection on EPRI's G-Van. No major problems were identified during this inspection, however, five of the six battery hold-downs appeared to be cracked. New hold-downs were ordered and subsequently installed.

Vehicle use during January through March was reduced due to range problems. As noted earlier, causes of and solutions for range reduction are under investigation. Total vehicle mileage through March 1992 for the three vans is 12,193.

Summary/Conclusions - PG&E's program continues to be successful. Information obtained from the three G-Vans is providing PG&E with operational information on EV use, technology, and infrastructure requirements. Generally, the G-Vans have been meeting expectations. The initial problems present upon vehicle delivery were not associated with the G-Van EV conversion. Of concern, however, has been the recent degradation of range in the cargo G-Van placed with the Sonoma County School District.

PG&E will continue its active involvement with EV development and commercialization through national and statewide organizations, and will continue to assess the purchase, testing, and evaluation of new vehicles and the impacts such vehicles will have on the utility grid.

PG&E continues to explore additional electric vehicle options and applications through such projects as the discussions with BART to support an electric station car. PG&E is also keeping in contact with both domestic and foreign automobile manufacturers regarding the availability of EVs for demonstration and evaluation.

On January 6, 1992, Platte River Power Authority (PRPA) received specification and cost information from the Soleq Corporation for two Soleq Corp. manufactured EVcorts. On January 14, PRPA issued a purchase order for the two EVcorts at a total cost of \$107,230. Platte River made a 50 percent prepayment of \$53,615. In order to obtain the options required on the base vehicle, the two Ford Escort station wagons had to be factory ordered. Due to the long lead time involved with factory ordering, the Ford Escort base vehicles and the GE DC electric motors, the delivery date for the EVcorts is planned for June 1992.

During the first quarter of 1992, PRPA and the DOE executed a revision to the Financial Assistance agreement to authorize PRPA to operate a DOE-owned 1984 Griffon van for a period of twelve months. The Griffon van is equipped with an AC battery heating system which operates during battery charging. The battery heating system is designed to increase the Griffon's range during cold weather operation. The Griffon van is currently at the Idaho National Engineering Laboratory pending replacement of a number of bad batteries.

To date, Platte River has no EVs in its vehicle fleet. For this reason, operation and maintenance data are not available for this quarter.

Recent Developments - On April 10, 1992, Platte River received the DOE Griffon van from the INEL. Personnel from the INEL visited PRPA to provide instructions on the vehicle use.

For the period from September 30, 1991 to December 31, 1991, Public Service Electric & Gas Company (PSE&G) operated eight (8) Conceptor G-Vans. Of the eight (8) vehicles, three (3) were consigned to the Electric Distribution Department as service vans. Two (2) vehicles were assigned to electric generating stations as delivery vans and to transport personnel. One (1) vehicle was assigned to PSE&G's Research and Testing Laboratory for evaluation and test. One (1) vehicle was assigned to PSE&G's Energy Technology Development Center (ETDC) for battery evaluation and test. One (1) vehicle and two (2) chargers were loaned to the State of NJ Department of Environmental Protection and Energy for mail delivery and transporting personnel. All eight of the vehicles were used for public demonstration at various times and locations.

During the period of operation the cold weather severely reduced the driving range of the vehicle. In addition, the energy consumption increased. This was brought to the attention of the manufacturer who attributed the problem to the battery performance, a battery charger and control malfunction. Although the manufacturer replaced the control circuit board on four chargers, the problem still persisted. PSE&G is checking each vehicle battery pack to determine if the problem is related to battery performance. Because of the limited range problem during the winter months, many of the vehicles were not driven on a regular basis.

During the reporting period PSE&G held a number of public displays and ride-and-drive demonstrations of the vehicles. In addition, PSE&G joined the US Advanced Battery Consortium, through its membership in EPRI, to support electric vehicle battery research.

During the reporting period the data collection procedures were not followed on a consistent basis. As a consequence, it appears that the most useful data are only available for the month of December 1991. For the month of December, the total mileage driven for all eight vehicles was 2,139. PSE&G is considering an automatic on board portable data collection system to more reliably collect energy use and miles traveled. Details will be provided in the next Quarterly Report. The operating and maintenance data for January, February, and March 1992 are presented in Appendix C.

Summary/Conclusions - During the reporting period PSE&G had a number of successful public demonstrations of the G-Vans. The vehicles were used as part of PSE&G's normal fleet applications. However, during the cold weather period the service of the vehicles was limited due to a severe reduction in range. The problem is being investigated and the solution may require opportunity charging and/or battery replacement. PSE&G is working with the manufacturer and EPRI to find a solution. PSE&G is assessing the possibility of using a nickel-cadmium battery in one G-Vans pending tests currently underway by EPRI. The nickel-cadmium battery option would not be considered until late 1992.

Publicity - PSE&G's pamphlet titled, "For PSE&G's Latest Contribution to the Environment Turn Here" provides a brief description of EVs in general and detail specifications of the G-Van. The pamphlets were distributed during the public displays and alternate fuel shows in New Jersey. The pamphlet highlights "PSE&G's Clean Energy For Clean Air" theme to focus on the clean air and zero pollution advantages for New Jersey residents.

The Southern California Edison Company (SCE) has purchased and placed into service seventeen G-Vans. The first two were purchased from Cars and Concepts as "proof-of-concept" vehicles. These were received in 1988 and remain in service. The following fifteen vehicles were

purchased from Vehma and received in the Fall of 1989. These fifteen are "preproduction" issues and are very similar to the production vehicles sold by Vehma thereafter. All fifteen remain in service.

SCE performed several modifications and encountered certain shortfalls of the G-Vans during the first six months of operation. These activities are documented in an SCE report titled "Operation and Maintenance of Fifteen Pre-Production Electric G-Vans; A Six Month Experience" published in November 1990. This report also presents design and performance data for the G-Van. Copies of this report are available upon request.

SCE has purchased two TEVans. However, SCE has had only occasional and brief possession of the two vehicles. At this time the two vehicles are being upgraded by Pentastar and will undergo further testing by Chrysler before being returned to SCE.

Vehicles Operations and Maintenance - The SCE G-Van fleet has logged approximately 110,000 miles in over two years of operation. Table 1 summarizes the operating statistics and current status for each SCE G-Van.

Overall, the G-Vans have been available for service the majority of the time. Also, the G-Van drive train was the heart of the first all electric float in the Pasadena Rose Parade. This float was sponsored by SCE shareholders and won a Special Award for the January 1, 1992 event.

However, significant failures of the SCE G-Van fleet include pre-production battery hydrogen ignitions in January and June of 1991, numerous problems with the pre-production traction motors and transfer cases, undersizing of the 12 volt charging system, and continued unreliability of the air conditioning system. Parts have frequently been exchanged between vehicles in to order to maximize vehicle availability. This complicates tabulation and presentation of maintenance and reliability records.

Major maintenance activities undertaken on the G-Vans since their delivery include:

1. additional sound proofing

2. replacement of all preproduction traction motors and transfer cases on the fifteen vans purchased from Vehma (including installation of an auxiliary cooling air fan)
3. replacement of most of the preproduction battery packs on the fifteen vans purchased from Vehma (the remaining one will be replaced in the near future).

Major maintenance issues still underway include:

1. replacement of pre-production motor controllers with production issues as they fail or as otherwise determined
2. efforts to improve air conditioning motor reliability
3. continuing evaluation of the long term reliability of the production battery packs, controllers, traction motors and transfer cases.

Vehicle Loan and Demonstration Activities - SCE has demonstrated the attributes of electric vehicles to the public. SCE has participated in many events such as auto show's, civic ceremonies, and sporting events. SCE provided electric vehicles for these events as well as knowledgeable representatives. These events allowed the public to ride in an electric vehicle and to get answers to questions they had concerning electric vehicles.

Electric vehicles are also loaned to fleet operators throughout SCE service territory. The length of the loan period can vary from just a few days to several weeks depending on the needs of SCE and the recipient. Before being loaned or demonstrated, each vehicle is thoroughly inspected by the SCE Transportation Services Division. Recipients are interviewed to determine how they intend to use the vehicle. At the conclusion of the loan period recipients complete surveys which indicate the level of operator satisfaction with the vehicle. SCE representatives meet with the recipients to determine how the vehicles performed for the use intended, and to determine where improvements are needed.

These activities are valuable to SCE in providing insight into what types of SCE customers might buy electric vehicles, and how these vehicles will be used and recharged. This information is needed so SCE can take the appropriate steps in planning and operating its electricity production, transmission and distribution system.

At this time all data collected through December 31, 1991 on SCE's loan and demonstration activities is being reviewed and summarized. This summary will be presented in the next quarterly progress report.

Vehicle and Component Testing and Development Activities - SCE is very active in the development and testing of prototype vehicles and components. Component development work includes high efficiency air conditioning, a G-Van noise suppression retrofit package, testing of G-Van heater emissions, and testing of advanced traction motor technology. The status of these efforts is discussed below.

The prototype high efficiency air conditioning system has not yet reliably operated. Efforts are underway to correct this; however, no efficiency data is available at this time.

SCE G-Van noise suppression activities are complete and were moderately successful. These efforts are documented in the aforementioned "Operation and Maintenance of Fifteen Pre-Production Electric G-Vans; A Six Month Experience" report. The change to production issue motors and transfer cases is also believed to have slightly reduced noise. Follow-up noise testing of G-Vans retrofitted with the production motors and transfer cases is planned for this Spring. Test results will be forwarded when available.

Emissions from the G-Van's diesel fueled space heater were analyzed in January 1991. Copies of the test report are available upon request.

Advanced traction motor technology testing is underway with California State University, Los Angeles. Testing is expected to be completed and a final report issued by August 1, 1992.

Prototype vehicles which SCE helped to develop include the G-Van, the Los Angeles Initiative LA 301 vehicle, a Shuttle Bus, and the TEVan. Information on the G-Van, TEVan, and Los Angeles Vehicle Initiative is publicly available from a several sources. A report of the Shuttle Bus development is available from SCE upon request. Currently, SCE is in the preliminary design phase of a mini-truck gasoline-to-battery retrofit, a "K" car retrofit, and a school bus retrofit.

Recently, three G-Vans from the SCE fleet were fitted with three different types of lead-acid batteries for test and evaluation. Records of this testing are now being collected and will be included in a future report.

Significant events within the University of South Florida (USF) program during the period August 1991 to March 1992 include the following:

Task I

Ordered and took delivery of two G-Vans from Courtesy Pontiac of Tampa, FL on October 18, 1991. These vehicles were manufactured by GM and converted to electric by VEHMA Corp. of Canada. When received these vehicles were in proper working order, except for a non-functioning heater in one vehicle. This condition was corrected by the manufacturer within a week. During this period the two G-Vans have been used by the Department of Electrical Engineering as light pick-up and delivery vehicles as well as commuting vehicles by two faculty members. See Appendix A for usage statistics.

During January three (3) new electric vehicles were ordered. An order was placed with the Solar Car Corporation of Melbourne, FL for two (2), 1992 Chevy S-10 Electric pickup trucks, for delivery in May 1992. These vehicles will be equipped with air conditioning, regenerative braking, and 110 Volt on-board battery charger.

An order was placed also with the Soleq Corporation of Chicago, IL. for one (1) Evcort Electric LX Station wagon, for delivery in July 1992. This vehicle will be equipped with air conditioning, two stage regenerative braking, and on-board charging.

In February, Florida Power Corp. received, from the U.S. Department of Transportation, a two year extension for the use, on public roads, of two (2) Griffon Electric Vans. The vans will be added to the USF testing program.

Task II

The design of the photovoltaic systems, charging and test facility was completed. Detailed engineering drawings, electrical and architectural, are complete and have been released to several area contractors for formal bids. The design of the test lab was completed and the mobile unit which will be used to house the lab has been ordered. The project plan for the site was prepared by USF Physical Plant and submitted to the Florida State Office of Capital Programs for approval. Approval was received, and the contract was released for formal bids. Forty Seven (47) ARCO M55 Photovoltaic (PV) modules were received from the U.S. Navy base on Bermuda. They were tested and 1 was found to be defective. The test characteristics will be used to properly match the modules for further assembly.

The contract for construction of the charging and test facility was placed and work began in January. The laboratory trailer was delivered and set up on the site. A 500 KVA transformer was installed on the site by Tampa Electric Corp. to be used with the charging facility. The structure to be used for the photovoltaic panels was erected and all necessary conduits for vehicle charging and test points to the lab trailer were installed. In addition metering for individual chargers to vehicles, with connections to the data acquisition system in the lab, were installed.

Task III

A cost effective Data Acquisition System (MDAS) has been designed for use with the EVs. The system is microprocessor based with 16 channel capability. A prototype system has been built and debugged with the required software. The type of data to be monitored on the EVs and the PV system and the technical description of the MDAS are shown in Appendix D.

Two (2) of the Data Acquisition Systems (MDAS) have been built and debugged. One of the data acquisition systems was installed in the G-van (DOE #651) with the required sensors. Initial test run data of speed vs time, and battery current vs time were taken by the MDAS and plotted, with excellent results.

Task IV

In conjunction with The Center for Urban Transportation Research (CUTR) of USF, a study of possible users of EVs has been started. Agencies that have been interviewed are the Hillsborough County Social Services, USF Purchasing, receiving and athletics departments, and printing and scientific stores.

In preparation for formal testing of the vehicles we are preparing manuals for orientation and instruction sessions for vehicle drivers. In addition, formal emergency procedures are being developed with the University Transportation Department.

Task V

Driver and maintenance logs have been generated for each vehicle currently in use, and all drivers have been instructed on the required data to be taken. Driver and maintenance logs, with driving and charging information, are now being used on the G-vans.

Meetings/Publicity - One or both G-Vans have been demonstrated to the following groups:

1. Florida Energy Conference attendees at USF - 10/23/91
2. Gulf Ridge Scout Council at MacDill AFB on 11/2/91
3. Florida Electric Power Coordinating Group at USF - 11/6/91
4. St. Petersburg Times at USF - 11/6/91
5. Tampa TV station WFT-A at USF - 11/18/91
6. Albert Chesnes, Assistant Secretary DOE, at USF - 1/6/92
7. Energy Exposition at USF 2/14-15/92
8. Electric Power Corporate Planning Group at USF - 3/31/92

Presentations describing the USF electric vehicle program were given to the following groups:

1. Automotive Society National Conference for Automotive
2. Technology, Daytona Beach, FL 1/13/92
3. Florida Energy Office, Tallahassee, FL 2/3/92
4. American Planning Association Energy Expo., Tallahassee, FL 2/4/92
5. Solar Car Corp. Melbourne, FL 2/7/92

Meetings were held at USF with representatives from Electronic Power Associates Corp. on April 2, 1992, and Norvik Technologies Inc. on April 7, 1992 to assess fast battery charging technologies.

A paper titled "Data Acquisition for Electric Vehicles- Recent Developments" was presented by Robert Stewart of our staff at the Southcon/92 in Orlando, FL

On December 12 and 13th the meetings of the DOE Site Operator Program members and the Electric Vehicle Users Group were held on the USF campus in Tampa. The USF program was reviewed with the group.

We have prepared an exhibit that describes the program in layman terms for use at an Energy Conference sponsored by the American Planning Association for the Florida legislature in February 1992.

The following papers were written by the staff and have been or will be presented at energy and electric vehicle conferences during 1992.

"Utility Interactive PV charging system for electric vehicles" Solar 92 The National Solar Energy Conference June 13-18, 1992 Cocoa Beach, Fl.

"A Utility Interconnected PV system for charging electric vehicles" The 11th International Electric Vehicle Symposium Florence, Italy Sept. 27-30, 1992

"Data Acquisition for Electric Vehicles-Recent Developments" Southcon/92 March 10-12, 1992 Orlando, FL.

New Vehicles/Components/Batteries - As previously noted we purchased 2 G-Vans which were delivered in October 1992. With the vans we purchased 2 Chloride battery chargers, and 1 watering trolley.

As previously noted under significant events, orders have been placed for three additional vehicles, two Chevy S-10 pick-up trucks and one Evcort LX station wagon. Delivery of these vehicles is expected during the next quarter. We have received a battery capacity tester on loan from the DOE Idaho National Engineering Lab. It has been installed in the testing lab.

Operations/Activities - The 2 G-Vans have been in operation since October 18, 1991 and are used by the Electrical Engineering Department of the University as light delivery and commuter vehicles. Total mileage as of March 31, 1992 was 1349.8 on DOE vehicle #650, and 686.8 on DOE vehicle #651. The vehicles have been overnight and opportunity charged as needed, and the batteries have been watered per the Chloride specifications. There were no unusual occurrences to report, and since our charging lab is not operational, we have not been able to take performance data.

At approximately 400 miles G-Van DOE #651 had a non working air conditioning unit. An inspection revealed that the 20 amp fuses in the A/C control box were open. After discussions with Mr. Ron Mitchell of Conceptor, a new A/C drive motor was sent and installed. The problem reoccurred immediately and further investigation showed that a defective connector socket in the control box was the problem. A new control box was installed to correct the problem.

Summary/Conclusions - As covered under significant events the program is in the set-up phase and on schedule. We expect the charging facility and the laboratory to be operational during the next quarter.

It is also expected that the data acquisition system be installed and operational by the same time, and operational testing to begin on vehicle performance and photovoltaic charging.

The building phase of the test and charging facilities is approximately two months behind the original plans. We project that we will be starting formal vehicle testing in April 1992. We are in the process of adding additional vehicles to the program to provide as much data on different vehicle models as possible. The excellent initial results on the automated data acquisition system will allow us to obtain and reduce large amounts of data with minimum manual intervention.

York Technical College, during the second quarter, was able to complete the first phase of the curriculum development process. The DACUM was developed through a cooperative effort with eight senior EV technicians from throughout the United States. The implementation of the information collected into the educational process should provide a solid and valuable basis for the training of electric vehicle technicians in this country.

The college was able to deliver the G-Van to PEPCO in Washington, D.C. and was able to receive the DOE owned Escort from Washington. York Tech will do the work to convert this vehicle to nickel cadmium batteries. The batteries will be loaned to the Site Operator Program by SAFT America, who will operate the vehicle in conjunction with PEPCO when it is returned to Washington, DC.

Numerous presentations were made during this period to highlight the development of electric vehicles. The college was able to negotiate the placement of an electric vehicle with Discovery Place in Charlotte, North Carolina.

APPENDIX A

ARIZONA PUBLIC SERVICE

OPERATING, MAINTENANCE, AND COST

Table 2 APS ELECTRIC VEHICLE FLEET

	DOE VEHICLE NO.	APS VEHICLE NO.	TYPE	NO. OF MODULES	System Voltage	CHARGE REQUIREMENTS		
						VOLTS	AMPS	TIME HOURS
1.	250	100	Unique Sedan (white)	16	96	110	15	12
2.	251	101	Detroit Sedan	14	84	110	30	5
3.	252	102	G-Van (Cargo)	36	216	208	50	8
4.	253	103	G-Van (Cargo)	36	216	208	50	8
5.	254	104	Solectria	12	144	110	12	8
6.	263		Solar Car	11	132	110	30	6
7.	258	298	Unique Sedan (yellow)	16	96	110	15	12
8.	260	300	EVcort Sedan (brown)	18	108	110	30/20/16	8/10/12
9.	261	301	EVcort Sedan (silver)	18	108	110	30/20/16	8/10/12
10	262	302	EVcort Sedan (tan)	18	108	110	30/20/16	8/10/12
11	259	305	Jet Escort Sedan	16	96	220	25	7
12	257		Honda CRX	4	150	220	200	3
13	255	3045	G-Van (Passenger)	36	216	208	50	8
14	256	3051	G-Van (Passenger)	36	216	208	50	8

File: \DOE\VEHDATA\EVFLEET

Graph 2 EV & IC Sedan Comparison

Variable cost per Mile
Cost of Energy is \$.07 per KWH

Excludes Battery Pack Amortization
File: HG\DOERPT5

Graph 3 EVcort & IC Sedan Comparison

Variable cost per Mile

Cost of Energy is \$.07 per KWH

Excludes Battery Pack Amortization
File: HG\DOERPT7

Graph 4 EVcort Energy Consumption

Energy Efficiency

Graph 6 EV Sedan Routine Maintenance

1991 Labor

Maintenance Variable Cost is \$0.16/Mile

Hourly Labor Rate is \$23/hour
File: SedanM91

Graph 7 Electric Sedan Maintenance Maintenance Labor Cost Breakdown Maintenance Variable Cost is \$0.16/Mile

Labor Rate: APS=\$23/hr, Contract=\$42/hr
File: Hg\Sedan1

Graph 8 Sonnenschein Battery

Battery Capacity Test vs Miles Driven
Test Results through Fourth Quarter 1991

INEL provided 6v160 for EVcort 300
Battery Packs still in operation
File: HG\BattSon

Graph 9 Trojan Battery

Battery Capacity Test vs Miles Driven
Test Results through Fourth Quarter 1991

Battery Packs in Operation

File: H3\BatTrojan

Graph 12 Chloride Battery

Battery Capacity Test vs Miles Driven

Test Results through Fourth Quarter 1991

Left & Right side tests are totaled
 Battery Packs still in operation
 File: HG\BattChlr

Capacity Test Minutes/# Pack Modules

Battery Capacity Test Report

Trojan

		<u>Unique 100</u>	<u>Unique 298</u>
<u>Date Installed</u>		Oct '90	January '90
<u>Battery Model</u>		T-145	T-145
<u>Odometer @ Install.</u>	<i>Miles</i>	9,590	20,027
<u>Batt Design Spec @ 75 Amp</u>	<i>Minutes</i>	145	145
<u>1st Capacity Test:</u>			
<u>Date Tested</u>		02/22/91	10/18/90
<u>Battery Capacity</u>	<i>Minutes</i>	117	87
<u>Odometer</u>	<i>Miles</i>	11,056	22,122
<u>Miles driven</u>	<i>Miles</i>	1,466	2,095
<u>Battery Cycles</u>		76	85
<u>% of Design Spec</u>		81%	60%
<u>Batteries Replaced</u>		0	0
<u>2nd Capacity Test:</u>			
<u>Date Tested</u>		05/21/91	02/22/91
<u>Battery Capacity</u>	<i>Minutes</i>	124	91
<u>Odometer</u>	<i>Miles</i>	11,482	24,702
<u>Miles driven</u>	<i>Miles</i>	1,892	4,675
<u>Battery Cycles</u>		93	152
<u>% of Design Spec</u>		86%	63%
<u>Batteries Replaced</u>		0	0
<u>3rd Capacity Test:</u>			
<u>Date Tested</u>		08/19/91	05/20/91
<u>Battery Capacity</u>	<i>Minutes</i>	127	94
<u>Odometer</u>	<i>Miles</i>	11,626	25,351
<u>Miles driven</u>	<i>Miles</i>	2,036	5,324
<u>Battery Cycles</u>		105	181
<u>% of Design Spec</u>		88%	65%
<u>Batteries Replaced</u>		0	0
<u>4th Capacity Test:</u>			
<u>Date Tested</u>			12/13/91
<u>Battery Capacity</u>	<i>Minutes</i>		79
<u>Odometer</u>	<i>Miles</i>		28,140
<u>Miles driven</u>	<i>Miles</i>		8,113
<u>Battery Cycles</u>			278
<u>% of Design Spec</u>			54%
<u>Batteries Replaced</u>			1 (#16)

Battery Capacity Test Report

Sonnenschein

		<u>EVcort 300</u>	<u>EVcort 301</u>	<u>EVcort 302</u>
<i>Date Installed</i>		Jan '90	March '90	Feb '91
<i>Battery Model</i>		6v160	6v180	6v180
<i>Odometer @ Install.</i>	<i>Miles</i>	6,986	5,271	5,775
<i>Batt Design Spec @ 75 Amp</i>	<i>Minutes</i>	92	104	104
<u>1st Capacity Test:</u>				
<i>Date Tested</i>		08/07/90	08/07/90	04/25/91
<i>Battery Capacity</i>	<i>Minutes</i>	82	55	86
<i>Odometer</i>	<i>Miles</i>	8,877	6,525	7,482
<i>Miles driven</i>	<i>Miles</i>	1,891	1,254	1,707
<i>Battery Cycles</i>		73	52	64
<i>% of Design Spec</i>		89%	53%	83%
<i>Batteries Replaced</i>		1 (#14)	2 (#18,#14)	0
<u>2nd Capacity Test:</u>				
<i>Date Tested</i>		01/25/91	10/27/90	06/25/91
<i>Battery Capacity</i>	<i>Minutes</i>	70	74	82
<i>Odometer</i>	<i>Miles</i>	10,900	7,675	8,554
<i>Miles driven</i>	<i>Miles</i>	3,914	2,404	2,779
<i>Battery Cycles</i>		151	104	91
<i>% of Design Spec</i>		76%	71%	79%
<i>Batteries Replaced</i>		0	0	0
<u>3rd Capacity Test:</u>				
<i>Date Tested</i>		05/17/91	02/08/91	09/24/91
<i>Battery Capacity</i>	<i>Minutes</i>	78	96	88
<i>Odometer</i>	<i>Miles</i>	12,164	9,610	9,252
<i>Miles driven</i>	<i>Miles</i>	5,178	4,339	3,477
<i>Battery Cycles</i>		211	164	111
<i>% of Design Spec</i>		85%	92%	85%
<i>Batteries Replaced</i>		0	0	0
<u>4th Capacity Test:</u>				
<i>Date Tested</i>		08/19/91	05/20/91	12/03/91
<i>Battery Capacity</i>	<i>Minutes</i>	94	102	58
<i>Odometer</i>	<i>Miles</i>	13,478	11,871	9,831
<i>Miles driven</i>	<i>Miles</i>	6,492	6,600	4,056
<i>Battery Cycles</i>		241	231	127
<i>% of Design Spec</i>		102%	98%	56%
<i>Batteries Replaced</i>		1 (#5)	1 (#13)	0
<u>5th Capacity Test:</u>				
<i>Date Tested</i>		12/05/91	08/21/91	
<i>Battery Capacity</i>	<i>Minutes</i>	90	90	
<i>Odometer</i>	<i>Miles</i>	14,771	13,401	
<i>Miles driven</i>	<i>Miles</i>	7,785	8,130	
<i>Battery Cycles</i>		276	286	
<i>% of Design Spec</i>		98%	87%	
<i>Batteries Replaced</i>		0	1 (#13)	
<u>6th Capacity Test:</u>				
<i>Date Tested</i>			12/03/91	
<i>Battery Capacity</i>	<i>Minutes</i>		73	
<i>Odometer</i>	<i>Miles</i>		15,070	
<i>Miles driven</i>	<i>Miles</i>		9,799	
<i>Battery Cycles</i>			345	
<i>% of Design Spec</i>			70%	
<i>Batteries Replaced</i>			0	

Battery Capacity Test Report

Chloride

		<u>G-Van 102</u>	<u>G-Van 103</u>	<u>G-Van 3045</u>	<u>G-Van 3051</u>
<u>Date Installed</u>		February '91	February '91	July '91	July '91
<u>Battery Model</u>		3ET205	3ET205	3ET205	3ET205
<u>Odometer @ Install.</u>	<i>Miles</i>	0	0	0	0
<u>Batt Design Spec @ 75 Amp</u>	<i>Minutes</i>	132	132	132	132
<u>1st Capacity Test:</u>					
<u>Date Tested</u>		05/23/91	05/21/91	12/13/91	12/11/91
<u>Battery Capacity (Left)</u>	<i>Minutes</i>	128	141	127	113
<u>Battery Capacity (Right)</u>	<i>Minutes</i>	128	134	122	115
<u>Odometer</u>	<i>Miles</i>	1,070	1,418	1,506	1,461
<u>Miles driven</u>	<i>Miles</i>	1,070	1,418	1,506	1,461
<u>Battery Cycles</u>		28	34	38	38
<u>% of Design Spec (Left)</u>		97%	107%	96%	86%
<u>% of Design Spec (Right)</u>		97%	102%	92%	87%
<u>Batteries Replaced</u>		0	0	0	0
<u>2nd Capacity Test:</u>					
<u>Date Tested</u>		08/16/91	08/20/91		
<u>Battery Capacity (Left)</u>	<i>Minutes</i>	137	143		
<u>Battery Capacity (Right)</u>	<i>Minutes</i>	127	139		
<u>Odometer</u>	<i>Miles</i>	1,807	2,525		
<u>Miles driven</u>	<i>Miles</i>	1,807	2,525		
<u>Battery Cycles</u>		50	66		
<u>% of Design Spec (Left)</u>		104%	108%		
<u>% of Design Spec (Right)</u>		96%	105%		
<u>Batteries Replaced</u>		0	0		
<u>3rd Capacity Test:</u>					
<u>Date Tested</u>		12/04/91	12/08/91		
<u>Battery Capacity (Left)</u>	<i>Minutes</i>	109	99		
<u>Battery Capacity (Right)</u>	<i>Minutes</i>	110	103		
<u>Odometer</u>	<i>Miles</i>	3,670	6,384		
<u>Miles driven</u>	<i>Miles</i>	3,670	6,384		
<u>Battery Cycles</u>		106	195		
<u>% of Design Spec (Left)</u>		83%	75%		
<u>% of Design Spec (Right)</u>		83%	78%		
<u>Batteries Replaced</u>		0	0		

Battery Capacity Test Report

12 Volt Battery Systems

Solectria
Sears Marine
Die Hard

Date Installed		10/01/91	
Battery Model			
Modules in Pack		12	
Odometer @ Install.	Miles		0
Batt Design Spec @ 25 Amp	Minutes		25
<u>1st Capacity Test:</u>			
Date Tested		12/03/91	
Battery Capacity	Minutes		25
Odometer	Miles		1,416
Miles driven	Miles		1,416
Battery Cycles			93
% of Design Spec			100%
Batteries Replaced			0
<u>2nd Capacity Test:</u>			
Date Tested			
Battery Capacity	Minutes		
Odometer	Miles		
Miles driven	Miles		
Battery Cycles			
% of Design Spec			
Batteries Replaced			
<u>3rd Capacity Test:</u>			
Date Tested			
Battery Capacity	Minutes		
Odometer	Miles		
Miles driven	Miles		
Battery Cycles			
% of Design Spec			
Batteries Replaced			

BATTERY TABLE for 1991

Vehicle	1988	1989	1990	1991
	J F M A M J J A S O N D	J F M A M J J A S O N D	J F M A M J J A S O N D	J F M A M J J A S O N D
300	N1	E	N3	N3
301	N1	E	N3	N3
302	N2	E	E	E
100	N1	E	N4	N4
288	N1	E	N4	N4
305	N1	E	N4	N4
102	N1	E	N4	N4
103	N1	E	N4	N4
3045	N1	E	N4	N4
3051	N1	E	N4	N4
284	N5	E	N6	N6
285	N5	E	N6	N6
289	N5	E	N6	N6
304	N5	E	N6	N6
289	N5	E	N6	N6
290	N5	E	N6	N6
104	N5	E	N6	N6

- Code: N: New Battery Pac
E: End of Pac Life
X: Explosion in Pac
- Battery Pacs:
- 1 - Concorde 6180, 6250 suspended Electrolyte 97amphours, 140amphours
 - 2 - Johnson Control Gel Cells Phase III, Phase IV Gel Electrolyte 86amphours, 104 amphours
 - 3 - Sonnenschein 6v180, 6v180; Gel Electrolyte; rating 92amphours, 104amphours
 - 4 - Trojan T145; Flooded Electrolyte; rating 145 amphours
 - 5 - ALCO 2200; Flooded Electrolyte; rating 107 amphours
 - 6 - Exide GC-5; Flooded Electrolyte; rating 135 amphours
 - 7 - Chloride 3ET205; Flooded Electrolyte; rating 165 amphours in 2 Hours
 - 8 - Sears 12v Marine Die Hard

APPENDIX B

PACIFIC GAS AND ELECTRIC COMPANY

MINUTES OF G-VAN USER GROUP MEETING

ATTENDEES
G-VAN USER GROUP MEETING
NOVEMBER 15, 1991

<u>NAME</u>	<u>ORGANIZATION</u>	<u>PHONE</u>
Manuel Celaya	Salt River Project	
Bill Farmer	SMUD	(916) 732-5283
Dan Fitzgerald	P G & E	(415) 973-1354
Dave Harris	CEVS	(517) 548-2605
Chris Haslund	P G & E	(510) 866-5868
B. L. Kansal	CPUC	(415) 703-2039
J. Willard King	Georgia Power	(404) 253-0218
T. Michael Lechner	Hart, McMurphy & Parks	(415) 949-2970
Jerry Mader	E V D C	(408) 253-5262
Kevin Morrow	Salt River Project	(602) 236-5638
Ron Mitchell	Conceptor	(416) 836-4611
Stan Stellwagen	Salt River Project	(602) 236-5307
Ken Tenure	E V D C	(408) 253-5262

EVDC G-VAN USER GROUP MEETING MINUTES

The third G-Van User group meeting was held on November 15, 1991, at Pacific Gas & Electric in San Francisco, California. Thirteen individuals representing nine organizations attended the meeting.

Summary

The meeting convened at 9:40 with introductions and a review of the meeting purpose and agenda.

The purpose of the user group meeting was the discussion of G-Van user experiences and maintenance issues. Based on the information exchanged during the meeting, it appeared the G-Van continues to operate effectively in the field and is meeting owner/user expectations.

User Presentations

Each organization presented information regarding the use, performance, and maintenance of their G-Van(s). Rather reiterate on each presentation, these minutes will cover the salient points raised during each presentation and ensuing discussions.

Conceptor Product/Maintenance Update

o Charger

Conceptor (and its suppliers) are investigating three separate G-Van charger issues:

1. Premature charger shutdown for specific charger profiles.

Conceptor has identified the cause and initiated corrective action (reprogramming the microprocessor).

2. Low range for specific charging conditions.

This situation is in the process of being corrected by revising the resonant capacitor multiple tap settings.

3. Newer chargers have 2 tap setting (vs. 4 in earlier models).

Chargers with 4 settings will be updated to the current design level.

(Note: Prior to publication of these meeting minutes, Conceptor issued a service bulletin addressing the above issues. Please reference Electric G-Van Production Service Bulletin # 91005, November 1991, for additional information.)

Special Projects

- o Salt River Project (SRP) equipped their G-Vans with a Campbell CR10 data acquisition system. The system monitors 33 different data points and uses a Lotus software format.

The development of the data acquisition system was a joint effort between SRP and New Mexico State University. Collaborative efforts with universities (such as the co-development of a data acquisition system) were described as a way to leverage financial resources to expand G-Van activities and support programs.

- o PG&E has equipped their prototype G-Van with an inductive charging system. The charging system was described as a "rough cut" system. The charger is controlled from the ignition and adds about 100 pounds to the G-Van. Charging of the G-Van from 20% to 80% charge takes approximately 3.5 hours.
- o A number of organizations are conducting informal EMF measurements on the G-Van. No definitive conclusions are currently available.

Vehicle Performance

- o kWh/mile performance ranged from .9 - 1.5. The consensus seems to be at 1.2+
- o G-Vans are operating successfully in daily missions of 25-40 miles. SRP reported a range of 72 miles with the air conditioner on high and an outside ambient air temperature of 110 degrees F.

Maintenance and Technical Issues

- o SRP experienced cupping of tires. SRP recommended frequent tire rotation. No other users reported a similar problem. (Cupping may be affected by the

extremely high operating temperatures in the SRP service area.)

- o Intermittent regenerative braking problem resulting from a "sticking" potentiometer. Conceptor is correcting this problem by using a teflon sleeve on the potentiometer. The timing for full implementation of this improvement was not specified.
- o The scissor lift, a special service tool to raise and lower the battery pack, has experienced failures. This condition is under investigation.
- o The heater warms up very slowly. No corrective action is planned at this time.
- o SRP reported the bolts holding the battery pack were stretching. It is recommended that during maintenance the bolts be inspected and replaced if necessary.
- o Both PG&E and SRP reported range problems with certain G-Vans. The cause of the reduction in range was related to the transformer tap setting in the charger unit.
- o AC fuses blowing. This is a known problem that has been corrected by Conceptor (replacement of the air conditioner motor).
- o Miscellaneous maintenance issues/reports incidents:
 1. Coolant recovery for the heater leaking at the reservoir seam.
 2. Acid damage observed on the battery as a result of over-filling.
 3. Sliding door latch not holding up to heavy use.
 4. An SRP technician recommended purchasing a charge adapter cable, a special service tool enabling charging of the battery pack when removed from the vehicle. The charge adapter cable is available through Conceptor.
- o Users unanimously commended Conceptor for its rapid response to product problem reports.

Product Improvement Update

- o Shift selector improvements are undergoing final testing. This should improve shift selector performance and

correct the quick shifting problem reported at earlier user group meetings.

- o Brake potentiometer sticking (see above). Teflon sleeve will be used to correct problem.
- o Investigating improving O-rings on water trolley.

Product Use and Market Update

- o A GMC dealership expressed interest in having a G-Van in its showroom.
- o SRP used the G-Van to support President Bush's visit to the Grand Canyon on September 18. The G-Van received significant attention from participating officials. G-Vans continue to be well received at public events.
- o Sacramento Municipal Utility District (SMUD) has been very active in loaning out its G-Van. The typical loan period is three weeks. SMUD also has an active G-Van public display program for the state fair, energy expos, solar rallies, etc. SMUD requires organizations wishing to borrow the G-Van to sign a liability release form.
- o The PG&E G-Van loan program includes Yosemite National Park and a one-year loan to Sonoma County, where the G-Van is in daily mail and support service.
- o Georgia Power is also loaning its G-Van to organizations in its service area. The City of Atlanta recently completed a three-month loan.
- o Georgia Power suggested investigating the use of electric vehicles and the upcoming Olympics in Atlanta. User group members enthusiastically accepted this idea and will begin investigating EV use opportunities.
- o All organizations agreed the G-Van is being enthusiastically accepted at public displays, ride and drives, etc. Vehicle pricing is the major barrier to translating this enthusiasm into greater sales.

Administrative Issues

- o User group members reviewed the current data forms. Comments made during the meeting will be incorporated, where possible, in future form revisions.
- o EVDC reiterated to all users to please have G-Van drivers complete and return the User Response Questionnaires.

- o Any range problems should be reported to Conceptor as soon as possible. Range reduction is not necessarily a vehicle or battery problem (it may be a charger-related).

The meeting adjourned at 3:00 P.M. No date was set for the next G-Van user group meeting.

APPENDIX C

PUBLIC SERVICE GAS AND ELECTRIC COMPANY

G-VAN OPERATING DATA

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

SALEM NEWARK HUDSON ESSEX MAPLEWOOD NJDEPE ELIZABETH TRETON

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

*NO CORRELATION BETWEEN kWh AND MILEAGE BECAUSE OF MISSING DATA

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

*NO CORRELATION BETWEEN kWh AND MILEAGE BECAUSE OF MISSING DATA

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

US DOE ELECTRIC & HYBRID VEHICLE SITE OPERATORS PROGRAM

*NO CORRELATION BETWEEN kWh AND MILEAGE BECAUSE OF MISSING DATA

END

DATE
FILMED

3 / 24 / 93