006487

1 OF 1

END

DOE/PC/91286--T4

DOE/PC/91286--T4

DE93 006487

**THE ROLE OF CATALYST PRECURSOR ANIONS
IN COAL GASIFICATION**

Fourth Quarterly Report

Received by GCH

JAN 29 1993

**Godfried M.K. Abotsi
Principal Investigator**

**Research Center for Science and Technology
Clark Atlanta University
Atlanta, GA 30314**

**PREPARED FOR
UNITED STATES DEPARTMENT OF ENERGY
UNDER CONTRACT NO. DE-FG22-91PC91286**

10028

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

fr

DISTRIBUTION

Received by GSTI

JAN 23 1983

Dr. Kamalendu Das
U.S. Department of Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, WV 26505

Marilyn Keane
OM-40, MS922-206
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Cynthia Y. Mitchell
Contract Specialist
AD-22, 921-165
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Kay Downey
Office of Technology Transfer
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

The aims of the proposed project are to enrich our understanding of the roles of various aqueous soluble catalyst precursor anions on the surface electrical properties of coal and to ascertain the influence of the surface charge on the adsorption, dispersion, and activities of calcium and potassium. These goals will be achieved by impregnating a demineralized North Dakota lignite (PSOC 1482) with calcium or potassium catalyst precursors containing acetate (CH_3COO^-), chloride (Cl^-), nitrate (NO_3^-), sulfate (SO_4^{2-}), and carbonate (CO_3^{2-}) anions.

In the past quarter, the effects of CH_3COO^- , Cl^- , NO_3^- , CO_3^{2-} or SO_4^{2-} on the surface charge properties of the coal has been initiated using the calcium salts of these anions. Like the corresponding potassium compounds investigated previously, increasing anion concentrations produce less negative charge on the coal surface through the interaction of calcium ions with the surface. This was confirmed by metal adsorption and chemical analysis of the filtered coal particles. The extent of metal adsorption was strongly dependent on the catalyst precursor. For potassium, maximum metal uptake from solution was obtained using potassium carbonate, followed by potassium acetate, while the lowest metal loadings were obtained when using the chloride, nitrate or the sulfate of potassium. The adsorption data are generally in agreement with the zeta potential results and suggest electrostatic attraction between the metal cation and the anionic coal surface. Fourier transform infrared studies are in progress to elucidate the coal-catalyst interactions.

INTRODUCTION

Coal gasification activity is generally attributed to the metal components of catalyst precursors. However, there is evidence that the anion of the catalytic salt plays a significant role in the performance of the catalyst. It has been reported (1) that for the same metal, the chlorides, acetates, or hydroxides of sodium, potassium, magnesium, and calcium exhibited different char reactivities. The catalysts were loaded from aqueous solution. For example, at 1223K, the order of reactivity for the sodium compounds was $\text{NaOH} > \text{NaAc} > \text{NaCl}$. These findings were rationalized in terms of the influence of the various anions on the diffusivities of the cations (Na^+ , K^+ , Mg^{2+} , and Ca^{2+} produced by dissociation of the metal precursors at gasification temperatures) through the pores of the chars. The variations in the activities of the catalysts were also ascribed to differences in the extent of deactivation as a result of the catalyst reaction with inorganic materials in the coal, and to the presence or absence of coal surface metal-oxygen complexes which have been hypothesized as essential prerequisites for coal char reactivity (2-7). It has also been suggested that the metal ion of the catalyst salt reacts with the carbon in the char to form active intermediates for gasification and that the anion of the salt favorably modifies the structure of the active species. However, the composition and structure of the active intermediates are unknown (8).

Since coal is normally impregnated with catalyst from solution, the variations in the activities of different catalyst precursors may be due to the influence of different anions during the adsorption of the metal ions onto the coal. The surface charge properties of aqueous suspensions of coal is well known. However, the effects of catalyst precursor anions on coal electrokinetic properties, catalyst adsorption, dispersion and activity have not been determined. The goal of this project is to investigate these parameters in relation to catalyzed coal gasification.

EXPERIMENTAL

The effects of the surface charge properties of the coal on the adsorption of potassium from CH_3COOK , KCl , KNO_3 , K_2CO_3 or K_2SO_4 solutions have been ascertained by agitation for 24h of 4.0 g of a North Dakota lignite with 100 mL of solution containing 0.1 mol/L potassium metal. The catalyst precursors were used separately. Following the adsorptions, the coal particles were filtered and the potassium content was determined by Galbraith Laboratories.

The influence of CH_3COO^- , Cl^- , NO_3^- , CO_3^{2-} or SO_4^{2-} on the zeta potentials of the coals is being determined using the calcium salts of these anions. The experimental procedure is analogous to that of the corresponding potassium compounds described in a previous report (9).

RESULTS AND DISCUSSION

As reported previously (9), varying effects of anions on the zeta potentials of the North Dakota Lignite were observed when different concentrations of acetate, chloride, carbonate, nitrate, and sulfate anions were applied. The potassium compounds of these anions were used in that study (9). During the foregoing quarter, zeta potential studies have been initiated to determine the effects of these anions on coal surface charge when using the corresponding calcium compounds as the sources of the anions. The results for chloride anions (using CaCl_2) are presented in Figure 1. As can be observed from this figure, the charge density on the coal particles becomes progressively more negative, in the absence of added chloride anions, as the pH of the slurry was raised from acidic to basic. However, addition of 0.01 or 0.001 mol/L chloride anions significantly reduced the net negative surface charge on the coal particles, especially at the higher chloride anion concentration. Since the original coal particles are negatively charged, chloride

anion adsorption will be hindered as a result of electrostatic repulsion between the coal surface and the Cl^- anion. Thus, the reduction in surface charge must arise from the adsorption of calcium ions produced from the dissociation of calcium chloride, the driving force for the adsorption being coulombic attraction between the anionic coal surface and the calcium cations.

The effects of acid leaching on the zeta potentials of the coal in calcium chloride solution are shown in Figure 2. In this figure, plots A and B are for raw and the acid-leached coals, respectively, in the presence of 0.01 mol/L Cl^- , while plots C and D show the variation of the zeta potentials in 0.001 mol/L Cl^- solution for the unleached coals. Compared to the original coal in the absence of CaCl_2 , addition of this salt to the unleached and the leached coals again produced less negative zeta potentials on both coals. A more distinct difference is obtained for plots C and D, presumably due to the lower calcium ion concentration which minimizes interaction with the coal surface.

The variation of zeta potentials in the presence of the potassium salts (CH_3COOK , KCl , KNO_3 , K_2CO_3 and K_2SO_4) has been discussed in the previous report (9). The influence of the surface electrical properties of the coal (a North Dakota lignite) on potassium adsorption from aqueous solutions of these salts has been investigated and presented in Figure 3. The potassium uptake shows two distinct features: (1) a strong dependence on coal slurry pH, and (2) a dependence of potassium salt used. For all the compounds, potassium adsorption was maximum around pH 2, it was maximum at $\sim$ pH 10 and intermediate at pHs between 5 and 6. From Figure 3, it appears that at a given pH, the metal uptake can be classified into three groups according to the potassium precursor used: KCl , KNO_3 and K_2SO_4 fall into one group, while KOOCCH_3 and K_2CO_3 belong to separate groups. It is evident from Figure 3 that the highest potassium loading was obtained at all pHs when adsorption was effected using potassium carbonate solution. The second highest metal uptake occurred when potassium acetate precursor

was used and approximately the same level of potassium was adsorbed from potassium chloride, potassium nitrate and potassium acetate solutions.

As can be seen from Figure 4, the net negative surface charge density on the coal is significantly reduced in 0.1 mol/L CO_3^{2-} solution when K_2CO_3 was used as the carbonate anion precursor. In fact, the isoelectric point for the coal occurs at $\sim \text{pH } 6$; the surface of the coal is positively charged below this pH value while it is negatively charged about it. A similar reduction in the net negative surface charge for the coal was observed for the other potassium salts, although the change is more prominent for potassium carbonate. Thus, the surface charge on the coal clearly plays a role in potassium uptake. However, the reasons for the variations in metal adsorption as a function of anion type are not known at this time and are the subjects of continuing research.

In conclusion, it has been shown that the negative charge density on a North Dakota lignite is reduced in the presence of CH_3COOK , KCl , KNO_3 , K_2CO_3 and K_2SO_4 solutions. For each compound, the reduction becomes more prominent as the salt concentration is increased, the phenomenon being particularly distinct for K_2CO_3 . Adsorption studies show that the highest potassium adsorption occurs from K_2CO_3 solution, thus confirming the zeta potential results which become less negative with increase in K_2CO_3 concentration. Work to date shows that a similar behavior is observed for the coal when using calcium chloride solution.

Fourier transform infrared studies are in progress to gain insight into the interaction between the coal surface and the metal ions. A preliminary spectrum obtained after potassium acetate adsorption onto the coal is shown in Figure 5. The effects of various parameters such as coal drying conditions, KBr to coal ratio, instrument purging time, and number of scans are being investigated to enhance the spectra and facilitate interpretation of the results.

REFERENCES

1. Calahorro, C.V.; Gonzalez, C.F.; Garcia, A.B.; Serrano, V.G., Fuel 1987, 66, 216.
2. Wigmans, T.; Haringa, H.; Moulijn, J.A., Fuel 1983, 62, 185.
3. Hashimoto, K; Miura, K.; Xu, J. -J.; Watanabe, A.; Masukami, H. Fuel 1986, 65, 489.
4. Wigmans, T.; van Craneburgh, H.; Elfring, R.; Moulijn, J.A., Carbon 1983, 21, 23.
5. Yuh, S.J.; Wolf, E.E., Fuel 1983, 62, 252.
6. Fredriks, I.L.C.; van Wechem, H.M.H.; Stuiver, J.C.M.; Bouwman, R., Fuel 1981, 60, 463.
7. Mims, C.A.; Rose, K.D.; Melchior, M. T.; Pabst, J.K., J. Am. Chem. Soc., 1982, 104, 6886.
8. Wood, B.J. and Sancier, K.M. Catal. Rev. Sci. Eng. 1984, 26(2), 233.
9. Abotsi, G.M.K., "The Role of Catalyst Precursor Anions in Coal Gasification" 3rd Quarterly Report Prepared for Department of Energy, Grant No. DE-FG22-91PC91286.

Figure 1. Dependence of zeta potential on chloride anion concentration using calcium chloride as the source of the chloride.

Figure 2. Effects of coal Demineralization (Dem.) and chloride anion concentration on the zeta potential of a North Dakota Lignite. A and B: 0.01 mol/L chloride; A = Raw coal; B = Dem. coal; C and D: 0.001 mol/L chloride; C = Raw coal; D = Dem. coal; E = Raw coal with no added chloride. Calcium chloride was used as the source of chloride.

Figure 3. Influence of various anions and adsorption pH on the uptake of potassium by an unleached Norht Dakota Lignite.

Figure 4. Variation of coal zeta potential with pH and carbonate anion concentration.

Figure 5. Fourier transform infrared spectrum of North Dakota lignite loaded with potassium acetate.

END

DATE
FILMED

3 / 4 / 93