URBAN CONSORTIUM

THE URBAN CONSORTIUM

PTI's Urban Consortium is a partnership for changes. With leaders from 50 of the nation's largest cities and counties, the Urban Consortium is dedicated to all urban areas that are the foundation of America's economic and social health. Top elected and appointed officials join together in a Consortium that seeks new partnerships to ensure that the obstacles to a secure, healthy and safe life are removed for citizens as well as businesses to flourish. Established in 1974 to explore the application of technology to pressing problems in large urban jurisdictions, the Urban Consortium (UC) has pioneered the development of many groundbreaking management systems and technologies for communities. Many of these solutions enforce and support the concept of Public Enterprise; a term coined by PTI to describe an entrepreneurial approach to improving services to citizens while generating non-tax revenues.

The Urban Consortium Energy Task Force (UCETF)

For over ten years, the UCETF has been a leader in developing local strategies responsive to the national energy situation and critical environmental concerns. The mission of the Task Force is to:

- improve energy efficiency, cut costs and develop revenue from local energy assets
- develop innovative yet practical approaches in energy management
- create sustainable programs that balance the economic vitality of local governments with energy, environment and quality of life issues
- provide a stimulating arena where local government officials can share experiences and gain valuable perspectives on energy technologies
- address the overlap between energy and environmental policy issues

UCETF membership includes elected officials, management and technical professionals from urban cities and counties. Its links to national organizations, such as the National Association of State Energy Officials (NASEO), the National League of Cities, National Association of Counties, and the International City/County Management Association assures the wide-spread exchange of information and technology. The UCETF applied research and development program, funded in part by the US Department of Energy, has successfully addressed diverse energy problems, identifying solutions for our nation's largest urban cities and counties. Some of the UCETF's achievements include:

- saving local governments and citizens millions of dollars by lowering energy bills
- developing and implementing sustainable energy planning methods and programs for cities and counties
- testing environmentally sound alternative fuels and means for fuel distribution in municipal fleets
- making existing and new buildings more energy efficient by using new technologies and education programs
- creating joint utility and local government programs to offer residential, commercial and industrial sector incentives for sound energy management practices
- evaluating and combining project results for replication in other cities and counties
- building the capability of local government staff and leveraging public funds with private investments

Public Technology, Inc.

PTI is a non-profit institution created in 1971 by the major national associations of local and state governments. Our mandate is to create and disseminate new technology in society, responsive to the needs of local governments. Today, the National League of Cities, the National Association of Counties, and the International City/County Management Association provide policy leadership and sponsor the efforts of PTI.

PTI uses a consortium of entrepreneurial and innovative cities and counties to provide an effective and coordinated urban laboratory in the technology research, development and commercialization cycle. PTI also seeks to involve local government in technology standard setting processes. PTI's work is conducted through 3 task forces, Energy, Environment and Telecommunications and Information.

PUBLIC TECHNOLOGY, INC.

1301 Pennsylvania Ave., NW
Washington, DC 20004-1793
202.626-2400
800.852.4934
FAX 202.626-2498

COMPRESSED NATURAL GAS FUELED VEHICLES:

THE HOUSTON EXPERIENCE

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Urban Consortium Energy Task Force

Office of Energy Management
Finance and Administration Department
City of Houston

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PREFACE

YEAR 11 ETF PUBLICATION

The Urban Consortium for Technologies (UC) is composed of over forty of the largest cities and urban counties by population in the United States. The Consortium provides a unique forum to define urban problems common to its member governments and to develop, apply transfer and commercialize technologies and innovative management techniques to address those problems.

The Urban Consortium conducts its work program under the guidance of Task Forces structured according to the functions and concerns of local governments. The Urban Consortium Energy Task Force (UCETF), with a core membership of 20 large cities and counties, was formed in 1979 to help improve urban energy management decision-making through applied research and technology transfer. The UCETF focuses on developing and sharing new approaches and innovative solutions to energy management problems with interested local governments. Projects with similar subjects are organized into Units with each unit managed by a selected Task Force member.

A description of the Units and projects included in the 1990 program are as follows:

ALTERNATIVE VEHICLE FUELS

Alternative vehicle fuels offer a very strong potential to aid in the reduction of US dependence on foreign oil supplies, with the concomitant benefits of decreased air pollution in urban areas. Local governments can play an instrumental role in realizing this potential through practical applied research and highly visible demonstrations for alternative fuel and technology options. Projects in this topic area place a strong emphasis on the examination of all

potential alternate fuels with support from teaming and partnership activities among cities and counties, utilities and other relevant private sector organizations that have matching interests. The 1990 Alternative Vehicle Fuels unit consists of:

Albuquerque, NM -- *Alternative Fuel Vehicles in Municipal Duty Cycles*

Broward County, FL -- *Dual Fuel Conversion Demonstration*

Detroit, MI -- *Assessment of AFV Availability to Meet Emergency Contingency Planning and Long Term Public Fleet Integration*

Denver, CO -- *Alternative Fuels and Transportation Management Associations*

Houston, TX -- *CNG Fueled Vehicle Comparison*

New York, NY -- *Alternative Transportation Fuels: Infrastructure Issues*

Pittsburgh, PA -- *Compressed Natural Gas as an Alternative Vehicle Fuel*

San Diego, CA -- *Siting Alternative Fuel Filling and Maintenance Stations*

ELECTRICITY MANAGEMENT

Energy costs can place a severe burden on residents and limit economic growth for both energy-intensive industries and the vital small business sector that provides the majority of today's employment opportunities. Urban governments, therefore, need to have the ability to manage both the use and demand for electricity supplies. The emphases on the 1990 electricity management projects include attention to broad issues of electricity cost as an economic factor in commercial development decisions, procedures for the design of major new public facilities, and the feasibility of emerging decentralized and/or alternative sources of electrical energy. This 1990 unit consists of:

Chicago, IL -- *Central Station DHC Phase I Feasibility Analysis*

Columbus, OH -- *Electricity Demand Impacts of New Indoor Air Quality Standards*

Dade County, FL -- *Global, Automated Urban Government Energy System (GAUGES)*

Detroit, MI -- *Hydraulic Waste Energy Recovery City of Detroit Water Distribution System*

Kansas City, MO -- *Use of Cogeneration System to Control Electrical Demand*

Montgomery County, MD -- *Integrated Energy Planning for a New Detention Center*

New York, NY -- *Strategies to Reduce Electricity Cost in New Commercial Construction*

ENERGY, ENVIRONMENT AND ECONOMIC DEVELOPMENT

Today's urban centers face critical and continuing problems that constrain their ability to provide affordable housing, to reduce congested highways, and to improve air quality, waste management, and economic development. The efficient use of energy and the development of alternate, clean energy resources can help address these broad community problems and contribute significantly to achieve truly sustainable, environmentally responsible, and economically viable communities. This unit, therefore, deals with community problems, from affordable housing to alternate clean energy resources. Urban strategies to improve energy-sustainability will require attention to both broad based institutional changes, as well as specific projects designed to encourage the application of appropriate technology and community development practices. This 1990 unit consists of:

Phoenix, AZ -- *Impact of Heat Islands on Cooling and Environment*

Los Angeles, CA -- *Heat Island Mitigation*

Pima County, AZ -- *Tucson Solar Village*

Portland, OR -- *The Sustainable City: Phase II*

San Jose, CA -- *The Sustainable City: Phase II*

San Francisco, CA -- *The Sustainable City: Phase II*

St. Louis, MO -- *Pilot Program for Energy Efficient Mortgages*

Washington, DC -- *Energy Efficiency in Public Housing*

WASTE MANAGEMENT

Effective and environmentally sound waste management is a concern of local government that only promises to grow in its significance through the decade. Urban strategies for waste management are evolving into coherent approaches that integrate traditional collection and disposal practices with new emphases on waste source reduction, separation and isolation of hazardous wastes, and practical recycling procedures. This year's unit consists of:

Hennepin County, MN -- *Household Hazardous Waste Processing - Phase II*

Houston, TX -- *Solid Waste Integrated Cost Analysis Model: An Applied Decision Making Tool for Municipalities*

Memphis, TN -- *Sludge Storage Lagoon Biogas Recovery*

New Orleans, LA -- *Pyrolysis Disposal of Scrap Tires*

San Diego, CA -- *Mixed Plastics Recycling*

Seattle, WA -- *Evaluation of Hazardous Waste Management Programs*

Reports from each of these projects are specifically designed to aid the transfer of proven experience to other local governments. Readers interested in obtaining any of these reports or further information about the Energy Task Force and the Urban Consortium should contact:

Energy Program

Public Technology, Inc.

1301 Pennsylvania Avenue, NW

Washington, DC 20004

ACKNOWLEDGEMENTS

There are many persons responsible for parts of a project of this scope, magnitude and duration. The project literally would not have been conducted without the daily work of the project manager, Ralph Egbuonu and the continuing support of the project directors, initially Dave Robertson and subsequently Dewayne Huckabay, who also wrote the project report. The project would have been impossible without the support of various City drivers, mechanics, and supervisors who tested the vehicles and provided data and perspectives on the operating and maintenance aspects of the project.

The peer review, critical comments, shared experiences, and expertise provided by the members of the Alternative Fuels Unit of the Energy Task Force during the project duration were invaluable, and particularly the leadership of the unit managers, Creighton Lederer and Chuck Clinton.

Members of the project team focusing on emission issues included Steven Fritz of Southwest Research, Alan Jones and David Hitchcock of the Houston Advanced Research Center, Dr. Maria Morandi and Dr. Thomas Stock of the University of Texas School of Public Health, and Bill Wallace of Wallace Engineering. Their expertise and analysis were essential to the project results and mid-course modifications, and their efforts were greatly appreciated.

There were a number of private groups which actively participated in all phases of the project. Without the support of these groups, the project would have been much less useful in determining the failures and successes which will shape the compressed natural gas fueled market in Houston and elsewhere. In particular, the support of Susan Smith and Gert Rudel of Entex, Lee Pappayotti of Enron (and subsequently Enfuels), Chip Plomteaux of Enfuels, Charles Rumsey of American Natural

Gas Power, Inc., and Lloyd Austin and Don Gollog of Stewart and Stevenson needs to be acknowledged.

As noted in the report, this project was funded by a number of public and private sources, and these financial commitments were all essential to the project scope, duration, and results. The financial support of the Urban Consortium Energy Task Force (and the Department of Energy), the Governor's Energy Management Office, the Environmental Protection Agency, Entex, Enron, American Natural Gas Power, Stewart and Stevenson, and the Gas Research Institute are greatly appreciated, as well as the various departments of the City of Houston which participated in the demonstration project.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	i
CHAPTER ONE - OVERVIEW	1
1.1 Abstract	1
1.2 Project purpose	3
1.3 Report organization	5
CHAPTER TWO - PROJECT CONCEPT	9
2.1 Background	9
2.2 Project definition	11
2.3 Alternate fueled vehicle technology options and choice	12
2.4 Research focus questions	16
CHAPTER THREE - PROJECT CONDUCT	19
3.1 Project organization and management	19
3.2 Data collection procedures	22
3.3 Participant orientation and training	24
3.4 Phase one research	27
3.5 Baseline vehicle selection and testing	28
3.6 Compressed natural gas conversion kit selection	30
3.7 Initial CNG conversion kits	31
3.8 CNG conversions and fuel tanks	31
3.9 CNG fueling station	39
3.10 Selection of emission testing facilities	41
3.11 Emission testing procedures	42
3.12 Initial emission results	46
3.13 Phase one emission results and project revisions	58
3.14 Revised phase one research	60
3.15 Phase two research	63
3.16 Uniform CNG codes and standards	64
3.17 Natural gas composition standard	64
3.18 Industrywide and national standards and codes	65
3.19 State codes, standards, and model specifications	66
3.20 CNG vehicle fuel tank constraints	67
3.21 Phase two CNG vehicles	70
3.22 Phase two emission results	74
3.23 CNG fueling infrastructure issues	78
3.24 Evaluations of CNG vehicle performance	81
3.25 CNG vehicle safety	83
CHAPTER FOUR - CRITICAL CNG FUELED VEHICLE ISSUES	85
4.1 Demonstration of positive emission results	85
4.2 Resolution of vehicle range limitations	87
4.3 Compressed natural gas fueling infrastructure	88
4.4 Competitive CNG vehicle, kit and fuel costs	89

CHAPTER FIVE - LESSONS LEARNED	95
5.1 Project schedule and duration	95
5.2 CNG fueled vehicle technology	96
5.3 Partnership approaches	99
CHAPTER SIX - HOUSTON APPROACH	101
6.1 Research focus question answers	101
6.2 Houston alternative fueled fleet strategy	103
APPENDIX A - RESEARCH FOCUS QUESTIONS	107
APPENDIX B - EMISSION RESULTS	113
APPENDIX C - MODEL CNG CONVERSION KIT SPECIFICATIONS	125

LIST OF EXHIBITS

Exhibit 3 - 1	Driver/field operation survey	23
Exhibit 3 - 2	Fleet supervisor monthly survey	25
Exhibit 3 - 3	Underhood CNG conversion	32
Exhibit 3 - 4	CNG fuel storage tanks	34
Exhibit 3 - 5	Converted F700 test truck	35
Exhibit 3 - 6	Converted GMC 8.2 test truck	37
Exhibit 3 - 7	GMC 6V92 OEM dual fueled (CNG-diesel) test truck	38
Exhibit 3 - 8	CNG compressor fueling station	40
Exhibit 3 - 9	EPA emissions testing driving cycle	44
Exhibit 3 -10	Emission results - light duty truck #173173	47
Exhibit 3 -11	Emission results - light duty truck #172955	48
Exhibit 3 -12	Emission results - light duty truck #362911	49
Exhibit 3 -13	Emission results - light duty truck #185384	50
Exhibit 3 -14	Emission results - OEM CNG light duty truck	51
Exhibit 3 -15	Emission results - medium duty gas truck #CNG05	52
Exhibit 3 -16	Emission results - medium duty gas truck #CNG06	53
Exhibit 3 -17	Emission results - medium diesel truck #CNG07	54
Exhibit 3 -18	Emission results - medium diesel truck #CNG08	55
Exhibit 3 -19	Emission results - heavy duty OEM dual fuel truck #2285	56
Exhibit 3 -20	Emission results - heavy duty OEM dual fuel truck #2288	57
Exhibit 3 -21	Converted Dodge Ram 250 test truck	72
Exhibit 3 -22	Converted Chevrolet Cheyenne 350 test truck	73
Exhibit 3 -23	GMC Sierra OEM dedicated CNG test truck	75
Exhibit 3 -24	Wrecked CNG fueled vehicle	84
Exhibit 4 - 1	Natural gas vs. gasoline cost comparison	91

CHAPTER ONE - OVERVIEW

ABSTRACT

The report describes the experience of the City of Houston in defining the compressed natural gas fueled vehicle research scope and issues. It details the ways in which the project met initial expectations, and how the project scope, focus, and duration were adjusted in response to unanticipated results. It provides examples of real world successes and failures in efforts to commercialize basic research in adapting a proven technology (natural gas) to a noncommercially proven application (vehicles).

Phase one of the demonstration study investigates, develops, documents, and disseminates information regarding the economic, operational, and environmental implications of utilizing compressed natural gas (CNG) in various truck fueling applications. The four (4) truck classes investigated are light duty gasoline trucks, medium duty gasoline trucks, medium duty diesel trucks and heavy duty diesel trucks. The project researches aftermarket CNG conversions for the first three vehicle classes and original equipment manufactured (OEM) CNG vehicles for light duty gasoline and heavy duty diesel classes.

In phase two of the demonstration project, critical issues are identified and assessed with respect to implementing use of CNG fueled vehicles in a large vehicle fleet. These issues include defining changes in local, state, and industry CNG fueled vehicle related codes and standards; addressing vehicle fuel storage limitations; using standardized vehicle emission testing procedures and results; and

resolving CNG refueling infrastructure implementation issues and related cost factors. All of these critical issues must be satisfactorily resolved to use CNG as a fuel in vehicle fleets.

The report identifies which CNG vehicle fueling options were tried and failed and which were tried and succeeded, with and without modifications. The conclusions include a caution regarding overly optimistic assessments of CNG vehicle technology at the initiation of the project and the related overly optimistic schedule for completion (an eighteen month project became a thirty-six month project).

In general, this project concludes that most current CNG fueled vehicle technology requires further development to effectively compete with gasoline and diesel fueled vehicles without mandated alternative fuels fleet requirements, from both an environmental as well as an economic perspective. The most effective current CNG fueled vehicle technology is OEM light duty vehicles, based on the project emission and economic analyses. Current aftermarket CNG conversion technology (with one or two exceptions) did not prove to be environmentally or economically competitive in this project. The report identifies vehicle types (carbureted vehicles, diesel vehicles, medium and heavy duty vehicles) in which current CNG vehicle technology does not appear to be a viable option. It also identifies vehicle types (OEM light duty vehicles) in which CNG technology appears to be very competitive with petroleum based fuels. The report recognizes the rapidly changing nature of CNG vehicle technology, which is adapting to address problems and obstacles identified through this research project (among others). It recommends use of CNG specifications requiring documented acceptable

emission results from an independent source for the relevant vehicle type.

The report further identifies successful solutions to refueling infrastructure and industry standards issues. It identifies the importance of verifiable emission results for CNG fueled vehicle technologies. It points out continuing issues regarding vehicle fuel storage limits. It identifies the limitations and positive experiences from the use of CNG fueled vehicles, from operational, environmental, and economic perspectives. It concludes that any fleet based clean air compliance strategy in the Houston region (including CNG fueled vehicles) has limited effectiveness, because of the sources and types of air quality problems here.

PROJECT PURPOSE

The initial purpose of the project was to field test four types of vehicles converted to compressed natural gas with a control group of the same four vehicle types to determine and compare the economic, operational, maintenance, and environmental impacts over a specified time period. The initial scope of the project included eleven CNG conversions and OEM vehicles and eight control vehicles, as follows:

- CNG fueled vehicles
 - . Two OEM dedicated two-cycle CNG heavy duty trucks
 - . Three converted four-cycle CNG medium duty trucks
 - . Three converted CNG medium duty trucks
 - . Three converted CNG light duty trucks
- Control vehicles
 - . Two two-cycle diesel heavy duty trucks
 - . Two four-cycle diesel medium duty trucks
 - . Two gasoline medium duty trucks
 - . Two gasoline light duty trucks

Previous investigations on natural gas application in vehicle fueling had centered on light duty passenger cars. This investigation was

designed to specifically investigate light, medium and heavy duty trucks. It also included installation of a "fast-fill" refueling site to be provided by Entex, the local gas distribution company and partner in the demonstration project, at a City location, and vehicle emission testing at EPA-certified testing facilities.

During the conduct of the project, the number of vehicles and types of CNG fueled vehicle technologies tested were revised, an OEM light duty vehicle was included in the project, and an OEM dual fuel (CNG and diesel) heavy duty vehicle was substituted for the OEM dedicated heavy duty vehicle. During phase two of the project, continuing CNG fueled vehicle technology developments required the inclusion of later generation CNG conversion kits and an OEM dedicated CNG light duty vehicle to the initial mix of vehicle types. In addition, pre- and post-conversion emission tests were completed in lieu of control vehicles. The project eventually conducted a total of fifteen emission tests on ten converted and two OEM vehicles, testing six different CNG conversion kit applications and two OEM CNG vehicles.

The project purpose and scope were modified by the phase two proposal. Phase two assessed the following barriers to effective market penetration of CNG fueled vehicles in fleets identified in phase one:

- Changes in local, state, and industry codes and standards required to encourage use of natural gas vehicles;
- Alternative natural gas vehicle storage devices (tanks) with comparable weight/range characteristics as gasoline;
- Use of standard emissions testing procedures to insure emissions reductions for CNG aftermarket conversions and OEM CNG vehicles; and
- Resolution of refueling station and other natural gas infrastructure cost and implementation issues.

Phase two focused on efforts to define the most viable market niche (vehicle type) for compressed natural gas and resolve issues associated with these vehicle types for fleet applications, through a collaborative effort of public and private partners in Houston.

REPORT ORGANIZATION

This report on the City of Houston's demonstration project and its experiences with compressed natural gas fueled vehicles is organized into the following chapters.

Chapter 1 presents an overview of the project including an abstract, the definition of the initial and revised purposes of the project, and the organization and presentation of the report.

Chapter 2 provides additional information on the project concept, including how and why the project was initiated and modified. It identifies the key questions which the research project is designed to answer. It focuses on developing reliable and accurate information for selecting what percentage of the overall City fleet should be converted to alternate fuels to meet various mandates, including Clean Air Act, National Energy Policy Act, and Texas alternative fuels legislation.

The chapter also presents a very broad, generic overview of alternate fuel vehicle technology options, including compressed natural gas, electricity, methanol, ethanol and reformulated fuels. It also identifies focus questions to be answered by this study - both questions specific to Houston and questions applicable in other areas.

Chapter 3 details the conduct of the research project from its conceptualization to its conclusion. It includes an introductory section which describes Houston's specific air quality problems and characteristics, the composition of the City of Houston's fleet, the

City limited demonstration approach and time constraints regarding conversion of its fleet to alternative fueled vehicles. This chapter presents a review of the project including funding and scope issues, kit selection and vehicle conversion technology, personnel training and data gathering process. The emission testing approach, related logistical issues, and emission results are highlighted.

Chapter 3 also describes the modifications and adjustments to the project scope, issues, and timelines associated with phase two. The rationale for the Texas emphasis on natural gas is reviewed and natural gas marketability issues are discussed, including infrastructure and other related cost issues. Barriers and solutions for implementing large scale fleet natural gas utilization through public/private partnerships in ozone nonattainment areas like Houston are identified and evaluated. The project results regarding codes and standards, vehicle performance, and vehicle safety are also described.

Chapter 4 addresses various critical issues relating to natural gas fueled vehicles. These issues include emission results relative to carbureted engines, conversion kits for diesel engines, dual fueled engine technology, and after market conversions compared to OEM vehicles. The issues of CNG tanks relative to vehicle weight/cost, range, pressure standards and other problems observed are also discussed. Refueling and related infrastructure issues relative to public/private sector partnerships are reviewed. The chapter concludes with cost analyses of OEM CNG related incremental costs, aftermarket conversion costs and cost comparison to other options.

Chapter 5 presents observations and lessons learned from this study. It notes the over-optimistic schedule of the project and the

overassessment of the state of the art in natural gas technology at the beginning of the study. The rapid advancements in natural gas vehicle technology are reviewed, and the contribution of this project toward attracting industrywide and statewide responses are noted. The report recommends approaches regarding CNG fueled vehicle acquisitions, based on the project experience. Successes and limitations in using public/private partnerships in the Houston region to address critical natural gas issues are described.

Chapter 6 presents conclusions drawn from this demonstration which relate to City of Houston choices regarding fleet alternative fuel mandates. It answers the initial research focus questions as they relate to Houston's experience with compressed natural gas fueled vehicles, and discusses recommendations and costs regarding the City of Houston fleet and its alternative fueled vehicle options.

CHAPTER TWO - PROJECT CONCEPT

BACKGROUND

In May, 1989 the Texas Legislature passed two bills (SB 740 and SB 769) "relating to the adoption of regulations to encourage and require the use of natural gas and other alternative fuels". SB 740 impacts state agencies and school districts; SB 769 impacts transit authorities initially and subsequently all fleets of more than 25 vehicles (except law enforcement and emergency vehicles) in air quality nonattainment areas. Both laws specify mandated percentage requirements for conversion of fleet vehicles to "compressed natural gas or other alternative fuels which result in comparably lower emissions of oxides of nitrogen, volatile organic compounds, carbon monoxide, or particulates or any combination thereof." The mandated conversion percentages range from 30 percent of fleet vehicles to 90 percent of fleet vehicles, with different compliance timelines for each group of agencies, but with a 90 percent compliance required of all groups by September 1, 2002. While other federal alternative fuel fleet mandates were expected at the project initiation, it was correctly anticipated that none of these mandates (Clean Air Act Amendments and National Energy Policy Act) would exceed the Texas requirements.

The Texas legislation was driven by economic as well as environmental concerns - Texas has an abundance of natural gas, which has historically been underpriced in comparison to gasoline. It was anticipated that this legislation would stimulate the market for

natural gas in a new application (vehicles) and also help solve air quality problems in large Texas cities.

The City of Houston vehicle fleet consists of approximately 9,500 vehicles of various types, sizes, models, and ages. The average vehicle is six years old, with approximately 80,000 miles of use, although this varies widely by type of vehicle. Approximately two-thirds of the total fleet are light duty vehicles, including patrol cars. The medium and heavy duty one-third is predominantly fueled by diesel, and includes a wide variety of vehicles, ranging from street sweepers and garbage trucks to backhoes and mowers. The portion of the City fleet which is impacted by the Texas alternative fuels legislation (which excludes law enforcement and emergency vehicles) is approximately 8,000 vehicles, of which approximately 4,500 are light duty vehicles and 3,500 are medium and heavy duty vehicles.

Houston, like 100 other metropolitan areas, fails to meet one or more Environmental Protection Agency ambient air quality standards for specified pollutants. An estimated 150 million people are affected by these air quality problems. The Clean Air Act specifies steps and actions that need to be taken in non-attainment areas to bring them into compliance, depending on the types of air quality problems and their severity. Included in these steps are various requirements to reduce vehicle related pollution, including some mandates for clean fuels in covered fleets in specified areas like Houston.

The air quality problem in the Houston region relates to ozone formation. Houston complies with national air quality standards for carbon monoxides, sulfur dioxides, nitrogen dioxides, lead and particulates. However, the Houston region is a severe non-attainment

area with respect to the national ambient air quality standard for ozone. While the ozone standard was only exceeded for 52 hours (out of 8,760 hours) in 1990, the amount of the exceedance was almost twice the national standard of 12 ppm, which made the Houston region the second worst area in terms of ozone formation in the country.

Therefore, clean air compliance strategies in the Houston region focus on prevention of ozone formation and its precursors, volatile organic compounds (VOCs) and nitrogen oxides (NOx). In 1989, the Senate Committee on the Environment stated forty percent of all air pollution worldwide comes from engine exhaust and forty percent of all engine exhaust comes from cars, trucks and buses in North America. However, unlike most other large urban areas, the portion of Houston's air quality problems associated with vehicles is relatively small. In 1990, only fourteen percent of VOCs and eighteen percent of the NOx in the Houston region were generated from vehicles. A major reason for this anomaly is the concentration of petroleum and chemical processing plants in the Houston Gulf Coast region. Any vehicular or fleet-based clean air compliance options must be evaluated in the Houston region based on their ability to reduce volatile organic compounds and nitrogen oxides and address Houston specific ozone problems.

PROJECT DEFINITION

The aforementioned state legislation (coupled with expected federal alternative fueled fleet mandates) created the impetus for the City of Houston to implement the compressed natural gas fueled vehicle demonstration project. The City determined it needed accurate and objective information on compressed natural gas fueled vehicles and experience in dealing with related issues, such as fueling sites, operation and

maintenance concerns, vehicle performance, driver acceptance, environmental impacts, and costs. The primary objective of the Houston CNG fueled vehicle research project was to provide the information to answer the question, "What part of the City fleet should be converted to compressed natural gas as a vehicle fuel?".

The city decided it wanted to conduct a small scale, limited demonstration project to obtain the information needed to make sound decisions regarding the mandated alternative fueled vehicle conversions before it incurred substantial costs of conversion and compliance. Based on the City fleet composition, it was decided to evaluate various types of vehicles, with an emphasis on medium and heavy duty vehicles. Because of the City's status as a severe non-attainment area for ozone, a major emphasis in the research project was devoted to obtaining reliable and accurate emissions information from any alternative fueled vehicle types selected for the demonstration, and on comparing alternative fuel emissions to previous gasoline and diesel emissions to determine air quality impacts of the vehicle conversions.

ALTERNATIVE FUELED VEHICLE TECHNOLOGY OPTIONS AND CHOICE

The Texas alternative fuels legislation indicated a specific preference for "compressed natural gas" as the benchmark against which other alternative vehicle fuels would be measured. However, the City reviewed other alternative fueled vehicle technology options readily available at the time of project initiation prior to selecting compressed natural gas as the demonstration project alternative fuel. Alternative fueled vehicle technology options which were considered included ethanol, methanol, electricity, reformulated fuel (gasoline and diesel), and

liquified and compressed natural gas.

Ethanol and other oxygenates were considered and evaluated as effective in addressing carbon monoxide air quality problems, such as in Denver, Albuquerque, Phoenix, and Las Vegas. However, other research indicated that these alternative fuels not only did not help in addressing ozone air quality problems, but there was some evidence that they might increase ozone forming potential. Since Houston's air quality problem was ozone related, these alternative fuel options were not researched any further in this project.

Methanol was considered primarily because of the extensive prior research and demonstration work conducted in California, and because a number of original equipment manufacturers were developing methanol based dedicated and flexible fueled vehicles. It was not selected for the Houston demonstration because of concerns with safety and fuel handling, increased emissions of highly reactive ozone precursors, the lack of any possible fuel cost savings, and the lack of interest on the part of any Texas based private firms in participating in a methanol demonstration.

Electricity was also assessed as an alternative vehicle fuel for inclusion in the demonstration project. The strongest justification for use of electric vehicles is the lack of any emissions from the vehicle itself. Although there are emissions from the electricity generating stations (which can be substantial, depending on the fuel source used to generate the electricity), the amount of any additional emissions from the generating stations associated with electric vehicles is limited, since most would be refueled at off peak times. However, electric vehicles were not included in the demonstration project

because of the prohibitively high cost of the vehicles, the current status of vehicle battery technology (and associated cost and range issues), the incompatibility of the typical City vehicle duty cycle with range limitations of electric vehicles, and lack of any electric vehicle partners financially willing to participate in this project.

Reformulated fuels (both gasoline and diesel) are considered clean fuels by the Clean Air Act, but they are not considered alternative fuels by the National Energy Policy Act. Whether they meet the criteria for the Texas alternative fuels law is subject to interpretation. Reformulated fuels were considered for the demonstration project, but they were not included, since they were not available in the Houston Gulf Coast market at the time of project initiation. In addition, it was contemplated that reformulated fuels could be tested without the need for a special demonstration project, since they can use existing fueling infrastructure, existing vehicle technology, and existing operational and maintenance procedures.

Both liquified and compressed natural gas fueled vehicle technologies were reviewed for consideration in the research project. Natural gas has a number of benefits over the other alternative fuels considered. These include:

- . natural gas produces no evaporative emissions,
- . theoretically natural gas burns cleaner than the other fuels (and thus produces fewer emissions and requires less vehicle maintenance),
- . natural gas is the only alternative fuel which has historically been less expensive than gasoline or diesel, and
- . there are abundant existing supplies of domestic natural gas plus an existing national pipeline distribution system.

From an initial review of literature and prior research, natural gas appears to have a competitive advantage over other alternative

fuels from safety, operational, environmental, and economic perspectives.

The City selected compressed natural gas as the alternative fuel to use in the demonstration, partly to verify the initial review and assessment noted above. A major factor in using compressed natural gas fueled vehicles was the active support and participation of the private sector in the Houston region. Alternative uses of natural gas are encouraged for economic development purposes in Houston and Texas.

Metro, the regional transit authority, decided to use liquified natural gas and "force the technology" as its alternative fuel of choice in response to the Texas alternative fuel law. Its decision to use liquified instead of compressed natural gas was based on its vehicle types (heavy duty buses) and range requirements (300 miles per day routes), coupled with concerns about CNG tank weight and the variable composition of compressed natural gas. The City did not select liquified natural gas because of concerns with safety, the state of the technology compared to compressed natural gas technology, issues of boil-off and venting, the reliability of the supply, and the unavailability of the product in Houston at project initiation.

Partly because the state mandate required use of alternative fuels in large portions of the entire fleet (not just new purchases) in a relatively short timeframe (six years from 30 percent to 90 percent of total fleet compliance), the City project focused on aftermarket conversion kits, as the most probable method of achieving compliance in the prescribed timelines. In addition, at the time of initiation of the project, there were no original equipment manufactured compressed natural gas vehicles available, although several were in development

and testing stages (including the heavy duty engines included in the research project).

The City also wanted to gain experience in dealing with related issues regarding compressed natural gas fueled vehicles. The project included a "fast fill" refueling station, mechanic training and certification from the state, measurement of driver satisfaction, vehicle safety and performance information, and collection of other operations and maintenance data.

RESEARCH FOCUS QUESTIONS

As illustrated in the background, project definition, and alternative fueled vehicle technology options and choice sections of this chapter, the City of Houston compressed natural gas fueled demonstration project had to deal with a wide variety of topics, concerns, and interrelated subjects. To insure that the research project addressed all the issues which needed to be addressed, at the inception of this research, a set of research focus questions were developed, which are included in Appendix A. These questions were designed to serve as parameters/guidelines for information expected to be developed during the study and provided at the conclusion of the study. In addition to the overall question previously cited, they included economic, environmental, operations, maintenance, and infrastructure questions, and were designed specifically to address Houston specific issues and information requirements.

The initial results of the compressed natural gas fueled vehicle project did not correspond to the expected results and subsequently the project scope, duration, and focus was revised to build upon the initial results. In phase two, the four critical barriers to additional

use of compressed natural gas in large vehicle fleets identified from the phase one results were assessed. These issues included standardized local, state, and industry codes and standards, limited vehicle tank storage, verifiable vehicle emissions results, and fueling infrastructure implementations and costs. Also in phase two, successful solutions or additional issues were identified relating to these barriers.

The phase two work took the information generated from the phase one results and adjusted the project to make it more useful in addressing the research questions and answering the initial question regarding fleet conversions. In addition, in phase two additional questions were raised regarding marketability and market penetration of compressed natural gas as a fleet vehicle fuel, which were also addressed in the project results.

As part of information dissemination from the project, team members participated in various workshops and conferences during the project to share on-going results with interested parties and to obtain feedback for other similar projects and CNG fueled vehicle experiences. As part of these information exchanges, a more generic set of research focus questions has been developed relating to data needed for decision making for alternatively fueled vehicles. The generic local data needs questions are also included in Appendix A, and are useful for other interested jurisdictions.

CHAPTER THREE - PROJECT CONDUCT

PROJECT ORGANIZATION AND MANAGEMENT

The City of Houston Compressed Natural Gas Fueled Vehicle Demonstration was initially designed to be an eighteen month project, with 5 Federal Test Procedure (FTP) emission tests on each of twenty CNG fueled vehicles (5 in each vehicle type) and 3 FTP tests on each of fifteen control vehicles (5 in each control type). It used multiple funding sources and partners, including the following:

- . various departments in the City of Houston,
- . the Urban Consortium Energy Task Force,
- . the Governor's Energy Office,
- . the U.S. Environmental Protection Agency,
- . the Gas Research Institute,
- . Enron Corporation (an integrated natural gas company),
- . Entex (the local gas distribution company),
- . Enfuels (a local distributor of CNG and CNG conversion kits),
- . Stewart & Stevenson (a distributor of heavy duty engines),
- . American Natural Gas Power, Inc. (a local distributor of CNG and CNG conversion kits),
- . the Houston Advanced Research Center (HARC) (in collaboration with consultants at the University of Texas School of Public Health),
- . the Southwest Research Institute, and
- . Wallace Engineering (a local EPA sanctioned FTP test facility).

Although all the partners did actively participate in the project, the initial project scope was reduced to eleven CNG conversions and OEM vehicles plus eight control vehicles due to funding limitations, as noted in Chapter One. In several instances during the project conduct, actual results did not match expected results, which caused a number of revisions in project tasks, scope and duration.

The most significant changes were incorporated in a phase two of the project, which was not originally planned. The phase two work plan assessed issues associated with compressed natural gas fueled vehicle

usage in fleets, based on the results from the Houston experience in phase one. Issues which were included in the phase two work included the addition of an OEM CNG light duty vehicle in the project, the substitution of a dual fueled heavy duty OEM CNG vehicle for a dedicated OEM CNG vehicle, testing of later generation CNG conversion kit technologies, assisting in developing local, state, and industry standards for critical CNG fueled vehicle components, researching CNG vehicle fuel storage limitations and options, an enhanced emphasis on certifiable emissions testing of CNG products, and developing a solution to CNG refueling infrastructure issues. Delays which occurred in phase one plus the revisions included in phase two lengthened the project duration from eighteen months to thirty six months.

The initial proposal for this project was submitted in June, 1989, although project work did not commence until November, 1989. Because of the complexity of the multiple funding sources and partnership arrangements, special handling of the CNG project was required from the beginning. The City Council approved the overall concept, and each of the separate funding, partnership, and contractual agreements. A special fund was established by the City Controller's Office to keep accurate account of the various funding sources and requirements.

A significant amount of staff effort was required to develop and administer the separate funding, partnership, and contractual arrangements. Agreements among the participating City departments as well as the other public partners and private participants were required to be completed. Separate agreements were made with the Urban Consortium Energy Task Force, the Governor's Energy Office, the Environmental Protection Agency (through the use of alternate settlement funding),

Enron (through the Gas Research Institute), Entex, Enfuels, Stewart and Stevenson, HARC, Southwest Research Institute, and Wallace Engineering. Between June, 1989 and November, 1989, most initial administrative and managerial details were resolved (although some were not completed until much later in the project), and the final initial scope and schedule of the project was determined as a result of these negotiations and agreements. During the second half of 1991, the project scope and schedule were significantly revised by the addition of phase two.

The CNG project was initially administered in the Fleet Management Division of the General Services Department. This division was responsible for maintaining a significant percentage of the City's nine thousand vehicle fleet. However, the pilot vehicles and the CNG refueling site were provided by the Public Utilities (and Public Works) Departments. During the project, administration was reassigned to the Energy Management Office of the Finance and Administration Department.

Enron and Entex were the private sector partners that played an active role in funding the project. They were also involved in defining the scope and focus of the project, both initially as well as in the phase two revisions. In particular, they were heavily involved in identifying the public and private barriers to the use of compressed natural gas fueled vehicles in fleets. They were also relied upon for their technical knowledge and expertise regarding natural gas throughout the project duration. Entex also leased the CNG refueling station equipment to the City at a nominal cost. Enfuels succeeded Enron and Entex in the project, once this shareholder organization was established. It also was awarded a CNG refueling contract for the City in the later part of the project.

The primary roles of the Urban Consortium Energy Task Force, the Governor's Energy office, and the Environmental Protection Agency were funding and technical expertise on specific topics. The Energy Task Force, through the Alternative Vehicle Fuels Core Program and the unit management structure, also provided peer review, technology transfer, and information dissemination.

The Houston Advanced Research Center was selected to serve as the environmental liaison. This group assisted in emission test data analyses and advice on vehicle conversion technologies, emission results and other technical matters.

Stewart and Stevenson participated in the research project by providing two heavy duty original equipment manufactured engines designed to operate on compressed natural gas. Initially these engines were to be dedicated CNG engines, but dual fueled CNG-diesel engines were used in the project due to technological delays in the readiness of the dedicated CNG engines. During phase two of the project, Stewart and Stevenson also allowed the use of the Gaseous Fuel Injected CNG conversion kit for a light duty vehicle.

American Natural Gas Power, Inc. provided technical assistance and expertise in compressed natural gas fueling and conversion technology. They also allowed the use of second and third generation light duty CNG conversion kit technologies to be tested during the project.

DATA COLLECTION PROCEDURES

In project startup, various data collection tools were developed and utilized for monitoring and collecting the types of data pertinent to the compressed natural gas project. Among data mechanisms utilized are driver/fuel usage forms (Exhibit 3-1) developed to monitor and collect

EXHIBIT 3 - 1

CITY OF HOUSTON
COMPRESSED NATURAL GAS DEMONSTRATION PROJECT
DRIVER/FIELD OPERATION SURVEY

Driver's Name.....Dept.....Div.....
(Print)

Vehicle Shop#.....Make/Model.....Date.....Milage.....

Conversion Type: CNG/Diesel [] CNG/Gasoline []

Gals. of Diesel at the beginning of the day.....

Gals. of Diesel at the end of the day.....

Gals. of Gasoline at the beginning of the day.....

Gals. of Gasoline at the end of the day.....

Pressure of Gas at the beginning of the day.....

Pressure of Gas at the end of the day.....

	GOOD	AVE	POOR	N/A
First start of the day	[]	[]	[]	[]
Acceleration at speed under 35 mph	[]	[]	[]	[]
Acceleration at speed over 35 mph	[]	[]	[]	[]
Engine performance during first 1/2 hour	[]	[]	[]	[]
Engine performance after 30 min. driving	[]	[]	[]	[]
Vehicle pickup on CNG (from start to cruise)	[]	[]	[]	[]
Vehicle performance going uphill	[]	[]	[]	[]
Vehicle performance on flat surface	[]	[]	[]	[]
Stop and Go performance using CNG	[]	[]	[]	[]
Overall performance of vehicle on				

CNG Fuel []Satisfactory []Unsatisfactory

Vehicle is used for.....
.....

Comments/Suggestions.....
.....
.....
.....
.....
.....
.....

data relevant to daily field operation of test and control vehicles. Information collected from this instrument included fuel usage, downtime for testing and downtime for unscheduled repairs, and operational personnel observations. This form also served as a daily driver perception monitor and survey mechanism. The survey instrument developed and used to determine supervisor perceptions and comments is shown in Exhibit 3-2.

PARTICIPANT ORIENTATION AND TRAINING

Operations personnel for this study were drawn from three departments in the City. Light duty vehicle operators and medium and heavy-duty vehicle operators were selected from Public Utilities and Public Works departments, respectively, while maintenance and support personnel were drawn from the fleet division which is responsible for servicing these vehicles.

A total of twenty four operations and support personnel were trained, including twelve drivers, eight mechanics, and four supervisors. The orientation and training approach included 1) sessions to diminish previously existing negative perceptions regarding the safety of operating and servicing natural gas vehicles and 2) sessions to emphasize the importance of the results of the pilot CNG vehicle conversions relating to future fleet composition, air quality issues, and future job requirements and security. A special emphasis on accurate record keeping was included.

The initial training included four hours viewing of the CNG tank stress test video prepared by the American Gas Association plus other materials addressing the safety and operation of natural gas vehicles and associated devices. It also included presentations from City

EXHIBIT 3 - 2

CITY OF HOUSTON COMPRESSED NATURAL GAS DEMONSTRATION PROJECT FLEET SUPERVISOR MONTHLY SURVEY

Project or Fleet Manager _____

Department _____ Phone _____

Circle the column that best describes the overall situation in the fleet
If opinions varied greatly among users, circle "#" and indicate the median view

Issues	Less	<<< Same >>>	More	Varied		
Complaints about vehicles	A	B	C	D	F	#
Cost of operation	A	B	C	D	F	#
Cost of repairs	A	B	C	D	F	#
Hours spent on repairs	A	B	C	D	F	#
Hours spent on training	A	B	C	D	F	#
Work accomplished by vehicles	A	B	C	D	F	#

Were the vehicles usually driven at altitudes over 7000 ft?

Yes () No ()

How many miles per day was the average for these vehicles?

Under 10 ()

10 to 50 ()

50 or more ()

How heavy was their average load?

Under 100 lbs. ()

100 to 500 lbs. ()

500 or more ()

What kind of roads were most of the miles driven on?

City streets ()

Highway ()

Mixed ()

Are these vehicles always driven by the same person or people?

Yes, one person ()

Yes, the same few people ()

No, it varied a lot ()

Comments/Suggestions.....
.....
.....
.....
.....
.....
.....
.....

and Entex operations personnel who shared their previous experiences in using compressed natural gas in vehicles. The Texas Railroad Commission rules and guidelines were also reviewed. In addition, drivers completed a hands-on demonstration of data gathering and documentation requirements, and reviewed the procedure for notifications regarding unexpected malfunctions. The mechanics underwent extensive training in conversion kit installation and related fabrications, CNG fuel tank installations, and fuel line installation, including actual conversions of City vehicles. Subsequent training on different CNG technologies (particularly the PING technology) was also completed, and Railroad Commission certification requirements were met.

In Texas, two state agencies (the Texas Railroad Commission and Texas Air Control Board) have primary regulatory enforcement responsibilities relative to safety and emission compliance, respectively, in natural gas vehicle operation as well as personnel certification. The Railroad Commission has published a comprehensive safety specification guideline (Regulations For Compressed Natural Gas) covering such issues as equipment specification, CNG storage and dispensing systems and regulations governing CNG vehicle conversions, including certification requirements for all individual and organizations involved in natural gas vehicle conversion, repair, and fueling infrastructure activities.

The Texas Railroad Commission has established six classes of operation and personnel certification licenses, as follows:

- (1) This category applies only to manufacturers of compressed natural gas (CNG) cylinders. This comprises entities which assemble, repair, test, sell, install or subframe CNG cylinders for use in Texas.
- (2) This category includes those who sell, install, service or repair CNG systems including cylinders.

- (3) This category encompasses persons who sell, store, transport for delivery, or dispense CNG for use other than as an ultimate consumer.
- (4) Category 4 covers persons or entities who engage in testing of CNG cylinders.
- (5) Licensing under this category covers both the operation of a CNG service station filling cylinders and or a cylinder exchange operation.
- (6) This category applies only to entities involved in the sale of CNG cylinders.

An initial license fee is required for any of the above categories with an additional annual renewal fee. The two channels through which qualification for a license can be achieved are through a written examination or by participating in a Texas Railroad Commission sponsored hands-on CNG conversion seminar.

Eight city employees have been trained and certified by the Texas Railroad Commission. These employees are of the fleet division of the Public Works department and specialize as follows; One (1) overall supervisor, one (1) specialist on light duty trucks, two (2) specialists on medium duty vehicles, and four (4) specialists on the heavy duty diesel trucks. In addition to fulfilling the commission certification requirement, these employees have also received hands-on training by Stewart & Stevenson on their CNG vehicle technology.

The remainder of this chapter will be divided into three major sections, with each section focusing on project conduct associated with that section. The three major sections are initial phase one research, revised phase one research, and phase two research.

INITIAL PHASE ONE RESEARCH

The initial phase one research occurred from November, 1989 to the spring of 1991. Some of the startup activities (in addition to those previously discussed) included selecting the emissions testing facilities, selecting the compressed natural gas conversion kit technology, establishing baseline data on converted vehicles, selecting the test vehicles, and defining the refueling station characteristics and location. Additional activities in the initial phase one research include conversion of the vehicle types, definition of emissions testing issues and approaches, and compilation of vehicle performance information.

BASELINE VEHICLE SELECTION AND TESTING

To assure the vehicles performed well on compressed natural gas, they were optimized to perform properly on gasoline/diesel. It was also crucial that the test vehicle perform according to the OEM emission standard set for the vehicle, since it may adversely affect the results of the FTP procedure. In an effort to achieve this pre-conversion status, the following steps were taken to ensure proper baseline performance standards for each vehicle:

- o PM maintenance; a comprehensive evaluation of the vehicle structural and engine condition.
- o A comprehensive engine tune-up program using genuine OEM parts and specifications, and adjusting engine timing to manufacturer's specifications.
- o All pertinent fluids and related filters including charcoal canisters were changed according to manufacturer's specifications.
- o Bear Machine engine diagnostic tests were conducted.
- o An engine valve adjustment to ensure adequate timing and engine performance recommended for the vehicle (medium duty diesel vehicles).
- o The structural integrity of the cab and chassis were evaluated to ensure safety adequacy for CNG fuel tank installation, particularly for the heavy and medium-duty vehicles.

- o A comprehensive system evaluation was carried out with regard to the electrical systems and other mechanical support systems.
- o All tires were brand and pressure standardized or changed as necessary to permit better grip on the dynamometer during emission testing.

This project was designed as a field demonstration study with an objective to validate experimental data on compressed natural gas applications in truck fleets. In light of this objective, it was deemed appropriate to utilize test vehicles which represented City fleet composition and operational characteristics. Vehicles selected for this study reflected important characteristics of the City's current operating fleet. The age of these vehicles range from five (5) to eight (8) years, with a mileage range from twenty three (23,000) thousand to sixty eight (68,000) miles. Vehicles with significant mileage were determined to be the most appropriate test of CNG aftermarket conversion technologies, and the most likely candidates for conversions rather than acquisition of new vehicles to be converted to CNG. Test vehicles were drawn from the Public Works and Public Utility departments responsible for comprehensive Citywide service functions with higher mileage duty cycles.

The following vehicles were originally selected as test vehicles for the demonstration study:

<u>Veh. #</u>	<u>Make & Model</u>	<u>Eng. Size</u>	<u>Fuel Type</u>	<u>Department</u>
CNG01	1986 Chevy LD Pickup Truck	305 cc	Unleaded	Pub. Utilities
CNG02	1986 Chevy LD Pickup Truck	350 cc	Unleaded	Pub. Utilities
CNG03	1986 Chevy LD Pickup Truck	350 cc	Unleaded	Pub. Utilities
CNG04	1988 Ford F700 Dump Truck	429 cc	Unleaded	Pub. Works

CNG05	1988 Ford F700 Dump Truck	429 cc	Unleaded	Pub. Works
CNG06	1987 GMC Dump Truck	8.2	Diesel	Pub. Works
CNG07	1987 GMC Dump Truck	8.2	Diesel	Pub. Works
CNG08	1983 GMC Trac. Trailer	6V92	Diesel	Pub. Works
CNG09	1983 GMC Trac. Trailer	6V92	Diesel	Pub. Works

During the revisions to phase one and in phase two, some modifications and additions to this initial list of vehicles were required, which will be detailed later in the report.

COMPRESSED NATURAL GAS CONVERSION KIT SELECTION

In the initial conversion kit selection for this study, the following three minimum selection criteria were utilized:

- 1 - A California Air Research Board (CARB) approved/certified conversion kit with proven adaptation to CNG application.
- 2 - A conversion kit with reasonable cost and minimum installation requirements.
- 3 - A US manufactured kit or a kit with strong local representation to ensure dependable parts availability.

An exhaustive search resulted in the use of the Canversion, Inc. kit (with major components manufactured by Landi-Renzo), which was also recommended by Entex, one of the funding partners for the project. Entex has had an extensive operational experience with the kit, but had not conducted any emission investigations on the kit. The Canversion kit did not meet the first criteria, but did meet the other two.

INITIAL CNG CONVERSION KITS

All vehicles utilized in this study were initially retrofitted with the Canversion conversion kit, with the conversion methodology approved by the Texas Railroad Commission. Approval was obtained from the Environmental Protection Agency for exemptions from federal anti-tampering requirements for purposes of testing the various CNG kits. Any conversion process entails two key phases - the underhood category and the chassis/ carriage category. The underhood equipment is illustrated in Exhibit 3 - 3 and consists primarily of the following equipment:

- Fuel Mixers,
- Regulators,
- Pressure Regulators,
- Pressure Gauges,
- Hose & Hose Connections, and
- Vehicle Fueling Valves.

The chassis/carriage category comprises:

- Stainless steel fuel delivery lines,
- CNG fuel storage cylinders,
- Automatic shut-off valves,
- Dual Fuel switch, and
- Fuel gauge regulator.

Texas Railroad Commission rules require that all vehicles operating on compressed natural gas be legibly marked with labels depicting such vehicles as operating on CNG. In addition, a wire cage must be installed over inter-tank fittings and connectors. A vent hole must be created at an area immediately adjacent to CNG tank nozzle to ensure adequate venting in the event of natural gas discharge.

CNG CONVERSIONS AND FUEL TANKS

The three light duty trucks initially converted for this demonstration study consist of one Chevy pickup truck with 305 cc carburetted engine and two utility body pickup trucks with 350 cc fuel injected engine.

Under hood CNG conversion in a 1986 Chevy light duty truck using Landirenzo three (3) stage regulator.

Landirenzo CNG mixer unit installed in the breather of a light duty Chevy truck.

The CNG fuel tanks used on each vehicle type are shown in Exhibit 3 - 4. For the pickup trucks, each CNG cylinder can hold up to 330 cu ft of natural gas and a total of four cylinders were installed to achieve an equivalent of twelve gallon gasoline range. For the utility body trucks, tanks with different configuration but equivalent capacity were utilized. These vehicles are primarily used for trouble shooting and the pay load bay is designed for tools and equipment storage. Both body type vehicles are (as required by Texas Railroad Commission) equipped with automatic shut valves. The steel CNG Fuel tanks are designed to withstand DOT approved pressure level of 2400 psi but in the event of an excessive overfill, the pressure valve at the tip of the tank snaps, thus allowing release of excess natural gas into the atmosphere.

The medium duty gasoline 1988 Ford F700 trucks had a gross vehicle weight of 24,500 pounds and were originally powered by a Ford 429 cubic inch (7.0 liter) V-8 engine rated at 200 brake horsepower at 3600 rpm. Both trucks had approximately 25,000 miles before baseline testing. For the Ford F700 trucks, the underhood CNG conversions are accomplished with a Canversion/Landi Renzo kit comprising a fuel mixer and No. 3 regulator. A No. 3 regulator is mounted in the engine compartment and connected to a mixer mounted over a four barrel carburetor. The CNG storage tanks used included one large (1150 cf) tank on the driver's side and two smaller (310 cf each) tanks cascaded together on the passenger side, for a total capacity approximating 13 gallons of gasoline. Exhibit 3 - 5 shows a converted F700 test truck.

The medium duty diesel trucks being utilized in this study are 1986 GMC 8.2 trucks rated at a gross vehicle weight of 25,600 pounds

CNG fuel storage tanks shown as mounted light duty truck. Each tank has a storage capacity of 330 cu ft.

Short CNG storage tanks shown in different mounting configuration on light duty (Utility body) trucks. Each tank has CNG storage capacity of 330 cu ft.

Side A: 1986 Ford F700 test truck converted to dual fuel (CNG/Gasoline) and retrofitted on this side with double CNG tanks with combined storage capacity of 660 cu ft.

Side B: Opposite view of a Ford F700 showing additional CNG fuel tank with storage capacity of 1150 cu ft. Vehicle is retrofitted with a total storage capacity of 1810 cu ft.

and were powered with a Detroit Diesel 500 cubic inch (8.2 liter) V-8 naturally aspirated engine rated at 165 brake horsepower at 2,800 rpm. Exhibit 3 - 6 illustrates one of these vehicles. The GMC trucks had approximately 42,000 miles before baseline testing. These vehicles were also retrofitted with a Canversion kit. This process is a dual fuel approach in which the vehicle starts and idles on diesel fuel at 550 rpm, then automatically kicks into Compressed Natural Gas at 1100 rpm. A DOT approved CNG steel tank is mounted on the right side frame of the vehicle. The tank being utilized has a storage capacity of 1150 cu ft. which is equivalent to 8.2 gallons of diesel. This significantly reduces the range of the truck, since the replaced tank has a capacity of 50 gallons of diesel. In order to achieve this installation, the secondary diesel tank on the right of the vehicle was removed, while the battery housing was adjusted. The size of the CNG fuel tanks on these vehicles was a significant unanticipated limitation on the usefulness of CNG technology in the duty cycle of these vehicles.

The two heavy duty diesel trucks being utilized in this study are 1983 GMC (6V92 TA) tractor trailers, as illustrated in Exhibit 3 - 7. These vehicles are operated by the Public Works department, and are utilized for various activities ranging from street repairs to hauling full loads of sand and gravel to different job sites. These vehicles are used in both off and on-road conditions.

These vehicles were originally projected to be retrofitted with mono fuel (CNG) engines to be developed by Stewart & Stevenson Power Inc., but after a twelve month wait, technological advancement in this area could only achieve a dual fuel (6V92 turbo charged) engine with an 80/20 (CNG/Diesel) mix ratio. In addition, this engine was equipped

Picture showing secondary diesel fuel tank displacement with an 1150 cu ft CNG tank on a GMC 8.2L diesel truck.

Picture of a City GMC 8.2L diesel truck converted to dual fuel CNG/Diesel

EXHIBIT 3 - 7

Pictures showing Two (2) 1973 GMC Brigadier Tractor Trailers retrofitted with 6V92 Dual Fuel (CNG/Diesel) Engines developed by Stewart & Stevenson and Detroit Diesel Corporation. The above vehicle are part of the City CNG project fleet.

with the Detroit Diesel electronic control (DDEC) system which provides a pilot charge of diesel into the combustion chamber and in turn ignites a charge of natural gas. At idle, the engine operates on 100% diesel, while in a drive cycle, the engine switches to burn primarily natural gas, using a small amount of diesel fuel for continued combustion. These engines use Pilot Ignition Natural Gas (PING) technology.

Resting on the frame behind the cabin wall is a secured arrangement of three (Model 1554) pressed steel tanks. Each of these has a capacity of 1260 cu ft of natural gas, which is equivalent to 10.2 gallons of diesel fuel. All three tanks have a combined capacity of 3780 cu ft. of useable natural gas, which gives the vehicle an estimated range of 244 miles. It should also be noted that the dual diesel tanks originally installed on the vehicle by the original vehicle manufacturer are still in-place and fully operational.

COMPRESSED NATURAL GAS REFUELING STATION

The compressor station utilized for this project, donated and constructed by Entex Gas, a primary contributing partner to the project, is illustrated in Exhibit 3 - 8. This single CNG fueling station served all test vehicles domiciled in different locations within the city. Effective fueling logistics required careful planning. The fuel station design was completed through a joint effort of Entex and City of Houston staff, and submitted to the Texas Railroad Commission (TRC) for approval. Construction of the fuel station was completed in forty five days and went into full operation in July, 1990. The cost of installation of the refueling station was approximately \$85,000, with \$58,000 in materials costs and \$27,000 in labor costs.

Side and Front View

Ingersol Rand CNG compressor station (Model 5522) constructed and donated to the City of Houston CNG project by Entex - A division of Arkla Inc. A four stage air cooled compressor powered by 20 hp electric motor with incoming pressure level of 5lb and outgoing pressure of 3600lb. This unit possesses a slow and fast filling capability. Station has CNG storage capacity of 27,000 cu ft for fast filling.

The compressor driving this CNG fueling station is an Ingersoll-Rand four stage air cooled unit, powered by an electric motor and does not require an enclosure or weather proofing. In compliance with the Railroad Commission setback requirements, the station is located forty two feet away from the closest property line. TRC regulation also require that power sources within an eighteen feet radius of the compressor station be power proofed, and that no power transmission line be located over the compressor station.

The fueling station is equipped with dual filling mechanism; the fast-fill mechanism and the slow-fill capability. The dual nozzle fast-fill mechanism which fills at a rate of two cubic feet of natural gas per minute at 2400 pounds of pressure, obtains fuel supply from a twenty seven thousand cubic feet adjoining storage cascade. The fast-fill system is used to fuel light and medium duty trucks. The slow-fill process is adapted for fueling heavy duty vehicle which are domiciled at the same facility as the fuel station. This process permits drivers to hook up the gas nozzle to their vehicle and fuel overnight. The fast-fill mechanisms permit drivers to fuel their vehicles within ten minutes. The station is equipped with a sequential control panel which can cycle compressors on and off. It also possesses a safety warning and shut down capability. During the project, the limited pressure available from the refueling station became an issue, as higher pressure (3000 and 3600 psi) kits and vehicles became commonplace in the industry.

SELECTION OF EMISSIONS TESTING FACILITIES

The fundamental driving force behind this study was determining the air quality effect. In light of this fact, the utmost attention was given

to selecting reputable and independent testing facilities to conduct emissions testing. In the selection process, key factors considered were company reputation, testing cost and proximity of test site to Houston. Requests were forwarded to the Environmental Protection Agency office in Houston for recommendation on area laboratories. In response, Wallace Environmental Testing Laboratory, Houston was recommended for emission testing on light duty truck and passenger cars while Southwest Research Institute was recommended for heavy duty vehicle testing. The EPA recommended firms were selected to provide FTP test services, with light duty FTP tests provided at the Wallace facility in Houston.

The FTP tests for medium and heavy duty vehicles were conducted in San Antonio by Southwest Research, since it is the only facility in the state with both a heavy duty chassis dynamometer and FTP emissions testing equipment. This arrangement presented both logistical and out-of-service constraints which were resolved during the project. The logistical constraints were addressed by towing the vehicles to the test facilities; the out-of-service constraints were addressed by scheduling the amount of time at the test facility.

EMISSIONS TESTING PROCEDURES

As previously indicated, air quality impacts were a major focus of the research project. Because of the importance of these factors and the timeliness of the emissions results, several separate reports and presentations were completed during the project duration providing detailed examination of the emissions testing conducted during the project and the emissions results from the various CNG kit technologies which were evaluated. These separate reports are noted in Appendix B, and are discussed later in this chapter. In the initial Phase One

activities, key decision regarding emissions testing approaches were made which impacted the entire project cost and duration, as well as the replicability of the results.

Emissions measured for all vehicles included "total" hydrocarbons, carbon monoxide, oxides of nitrogen and methane, a "non-reactive" hydrocarbon. The difference between total hydrocarbons and methane are "reactive" hydrocarbons, since they react in the atmosphere to promote ozone formation. Particulate emissions were measured for heavy duty vehicles using diesel fuel or bi-fueled diesel and CNG, and a soluble fraction of the total particulates determined, since this is the fraction generally associated with potential health effects.

The Federal Testing Procedure (FTP) is the EPA established testing methodology used to determine conformity of vehicles with emission standards set forth in the Code of Federal Regulations, and was selected as the emissions test procedure to maximize replicability of results and to minimize test-based criticism of any results. There is no Environmental Protection Agency approved federal testing procedure (FTP) designated for compressed natural gas vehicles, and thus gasoline (and diesel) vehicle test criteria were utilized.

The overall FTP test consists of prescribed sequences of fueling, parking, and operating conditions including idling, acceleration, and high speed loads as illustrated in Exhibit 3 - 9. Vehicles were all tested for both exhaust and evaporative emissions to achieve the objective of this study. The exhaust emission test is designed to determine hydrocarbon, carbon monoxide, and oxides of nitrogen mass emissions while simulating an average of 7.5 miles urban dynamometer driving schedule for both hot and cold start tests. This process is

EPA Urban Dynamometer Driving Schedule for Heavy-Duty Vehicles

subsequent to a 12 hour soak. A proportional sample of the exhaust emissions diluted with ambient air is proportionally collected for subsequent analyses. A computer report gave analyzer reading in parts per million and results in weighted grams per mile.

The evaporative emissions portion of the test is designed to determine hydrocarbon evaporative emissions as a consequence of diurnal temperature fluctuation, urban driving, and hot soaks during parking. It is associated with series of events representative of a motor vehicle operation which result in hydrocarbon losses. This test procedure is designed to measure:

1. Diurnal breathing losses resulting from daily temperature changes measured by the enclosure technique,
2. Running losses resulting from a simulated trip on a chassis dynamometer measured by carbon traps, and
3. Hot soak losses which result when a vehicle is parked and the hot engine is turned off, measured by enclosure techniques.

The analytical procedures used throughout the emission tests are those outlined by EPA for light duty, medium duty, and heavy duty chassis and engine testing. They also incorporate procedures adopted by the California Air Resources Board (CARB) for testing light, medium and heavy duty CNG fueled engines. In general, the CARB procedures call for testing spark-ignited gasoline fueled engines that have been converted to operate on CNG as if they were still gasoline engines, and for testing diesel fueled engines that have been converted to operate on CNG as if they remained diesel engines.

INITIAL EMISSION RESULTS

Emission test data on the light duty trucks were compiled and analyzed by Wallace Engineering. Emission test data on the medium duty gasoline and medium and heavy duty diesel trucks were compiled and analyzed by Southwest Research Institute. The emissions testing programs were broken down into three phases 1) to establish baseline criteria of gasoline and diesel for comparison purposes, 2) to determine initial post-CNG conversion data, and 3) to determine CNG emission data after a significant period of CNG powered vehicle use. The complete emission test results by vehicle for the complete demonstration project are illustrated in Exhibits 3 - 10 through 3 - 14 for light duty vehicles and Exhibits 3 - 15 through 3 - 20 for medium and heavy duty vehicles, and are discussed in detail later in this chapter. The specific emission results, including the baseline gasoline/diesel emission results used as benchmarks for all alternative fuel emission comparisons, are provided in Appendix B, with information about the testing procedures detailed in the referenced reports.

The vehicle conversion and emission testing phase of this study originated with three Chevy (305 cc carbureted) trucks (CNG01, CNG02, CNG03) were selected to be utilized as the light duty truck sample. CNG conversion activities was initiated on these trucks, but on completion of equipment installation, it became difficult to adjust two of the three trucks (CNG01 & CNG02) to run on compressed natural gas. Vehicles continued to stall on the process of highway testing. It should be noted that the Entex crew conducting this conversion, did recommend against using carbureted light duty trucks, citing possible poor performance in smaller non-fuel injected engines. Because of this poor

Composite Emissions-Chev. Custom Deluxe VID # 173173 (1987)

Composite Emissions-Chev. Custom Deluxe VID # 172955 (1987)

Composite Emissions-Dodge RAM 250 VID # 362911 (1991)

Not tested with gasoline

Composite Emissions-Chev. Cheyenne 350 VID # 185384 (1990)

Composite Emissions-GMC Sierra Dedicated (1992)

EXHIBIT 3 - 15

HDCC Composite Emissions and Fuel Economy Summary
for City of Houston Ford F700 Truck CNG05

EXHIBIT 3 - 16

HDCC Composite Emissions and Fuel Economy Summary
for City of Houston Ford F700 Truck CNG06

EXHIBIT 3 - 17

HDCC Composite Emissions and Fuel Economy Summary
for Dual-Fuel GMC 8.2L Diesel Truck CNG07.

EXHIBIT 3 - 18

HDCC Composite Emissions and Fuel Economy Summary
for Dual-Fuel GMC 8.2L Diesel Truck CNG08.

EXHIBIT 3 - 19

HDCC Composite Emissions and Fuel Economy Summary
for City of Houston Truck 2285

EXHIBIT 3 - 20

HDCC Composite Emissions and Fuel Economy
Summary for City of Houston Truck 2288

performance, the two problematic light duty trucks were replaced with two 1985 Chevy (350 cc FI engine) trucks. Based on this experience, the participating partners concluded carbureted engines are not suitable candidates for CNG conversions.

PHASE ONE EMISSION RESULTS AND PROJECT REVISIONS

By the spring of 1991, the light duty vehicles had been tested for emissions at Wallace Engineering and the medium duty gasoline and diesel vehicles had been tested for emissions at Southwest Research. The emissions testing procedures, problems which arose during the emissions tests, and the phase one emissions are detailed in the first interim report from Houston Advanced Research Center and the Phase I Final Report from Southwest Research Incorporated noted in Appendix B.

The results were not what was expected, based on generally accepted knowledge about CNG technology, as the emissions for the CNG vehicles in most cases were not any better than the emissions for the same vehicles on gasoline or diesel fuel. The results of the various emission tests during the project are provided in Exhibits 3 - 10 through 3 - 18, as previously noted, with the impact of unanticipated results on the project scope and duration described in the following paragraphs.

The light duty vehicles had emission results that were worse on compressed natural gas than when operated on gasoline. The non-methane hydrocarbons were substantially higher on compressed natural gas, carbon monoxide emissions were at least double on compressed natural gas, and nitrogen oxide emissions varied by vehicle, with some higher and some lower on compressed natural gas. The medium duty vehicle results varied by fuel type, with the previously gasoline fueled trucks

showing improved emissions of non-methane hydrocarbons and carbon monoxide but worse emissions of nitrogen oxide and the previously diesel fueled trucks showing improved emissions of nitrogen oxides and particulates, but worse emissions of non-methane hydrocarbons and carbon monoxide.

A number of potential explanations other than the CNG conversion kits for the unanticipated emission test results were developed and each was checked in sufficient detail to minimize the probability that it was the basis for the results. By process of elimination, it was determined that the unanticipated emission results were attributable to the specified CNG conversion kits.

Potential explanations for the unanticipated emission results which were examined and rejected as the cause of the results include:

- . testing errors, such as failure to adjust for flame ionization detector bias,
- . tampering by drivers or mechanics with the CNG conversion kits,
- . lean/rich air/fuel ratio adjustments, to insure optimum performance and emission results, and
- . composition of the compressed natural gas, to maximize methane content and minimize water and other elements.

To correct for flame ionization detector (FID) bias, the emission results were presented before and after FID bias corrections were made. City supervisory and employee records were reviewed and interviews conducted to insure that tampering did not occur on the CNG conversion kits. To address concerns regarding the air/fuel ratio, the kits were

readjusted to optimum engine and emission performance using the Entex engine analyzer and immediately thereafter tested using the FTP emissions test procedure. To respond to concerns regarding the composition of the compressed natural gas, tests were conducted at the CNG refueling station, with methane content exceeding 94 percent.

Another explanation for the unsatisfactory emission results was that the CNG conversion kits being tested were first generation kits with mechanical devices in an open loop configuration that did not make adjustments for variations in operating conditions in order to maintain a stoichiometric air/fuel ratio to the engine in real world operating conditions. The possibility of conducting expensive gas chromatography/mass spectroscopy tests to obtain a detailed breakdown of the individual components in the exhaust emissions was considered and rejected until more acceptable gross comparative emission results between the CNG fueled kits and the baseline gasoline/diesel engines were obtained, using later generation CNG conversion kits.

REVISED PHASE ONE RESEARCH

Based on the unsatisfactory nature of the initial emission results, it became clear to all the participating partners that a major adjustment of the original scope and timelines of the demonstration project was required. It was the consensus of the participants that the initial emission results did not disprove the concept of "clean burning" compressed natural gas fueled vehicles, but did warrant reconsideration of the parameters of CNG vehicle conversions.

During the period from the spring through the fall of 1991, various options were reviewed and reconsidered to refocus and redirect the Houston CNG fueled demonstration project. The state of the art in

the natural gas fueled vehicle industry was rapidly changing, with various modifications, enhancements, and improvements being developed around the country, particularly in the conversion kit portion of the industry, where multiple refinements of kits from the same manufacturer were commonplace.

The revised approach to the demonstration project agreed upon by the partners was to review again the state of CNG conversion kits across the country, particularly in light of second generation CNG kits with electronic controls and closed loop feedback systems capable of making realtime adjustments to reflect real operating conditions. The agreed upon approach also limited any further CNG after-market conversion kits and further emission testing in the Houston project to kits which had already been certified as having emission results which meet specified standards by the California Air Resources Board (CARB), the Environmental Protection Agency (EPA), or a similar state agency.

After extensive review of the natural gas vehicle industry, including review of written reports and discussions with the Natural Gas Vehicle Coalition, it was determined that the state of the industry was such that no aftermarket diesel fumigation CNG conversion kits were available in the marketplace which had proven emission results superior to the emission results available from diesel engines. Consequently, a decision was made to discontinue any further testing of aftermarket diesel CNG conversion kits.

At about the same time, it was determined that the dedicated CNG fueled heavy duty 6V92 engines from Detroit Diesel would not be available in the foreseeable future. In lieu of the dedicated CNG fueled engine, a dual fueled CNG-diesel engine was available, and it

was determined to complete field tests and do emission testing on the dual fueled CNG-diesel Detroit Diesel 6V92 engine.

The CNG aftermarket conversion kits that had been certified by CARB at this time included the Impco CNG kits, the ANGI CNG kits, and the GFI CNG kits. After review with compressed natural gas experts in the Houston region, it was determined that physical adjustment requirements on the ANGI kits limited their non-tamperability, impacted their performance versus emissions trade-offs, and limited emission results replicability. For these reasons, it was decided not to test ANGI CNG kits despite their CARB certification. American Natural Gas Power, Inc. offered the use of a CARB certified IMPCO CNG aftermarket conversion kit and Stewart and Stevenson offered the use of a CARB certified GFI CNG aftermarket conversion kit for the demonstration project. Since these kits included closed loop systems to address performance and emission trade-offs and emission replicability, and were designed to be tamperproof, these kits were subsequently installed on comparable light duty City of Houston vehicles for demonstration and testing purposes.

It was also at this time (summer, 1991) that General Motors Corporation introduced the first original equipment manufactured (OEM) dedicated compressed natural gas fueled vehicle - the 3/4 ton GMC Sierra pick-up. It was determined that emission testing of an in-use OEM-CNG vehicle would be a good benchmark for comparison purposes with the aftermarket CNG conversion kits as well as the gasoline fueled equivalent vehicles. Thus, emission testing of the OEM-CNG light duty vehicle was added to the scope of the demonstration project.

PHASE TWO RESEARCH

Based on the lessons learned during the first eighteen months of the City of Houston compressed natural gas fueled vehicle project, several issues were identified which required further research, additional funding and more time to complete than was possible in the original project scope. As a result, an expanded project scope was proposed and funded to address those issues identified as barriers to the implementation of large scale fleet natural gas vehicle utilization. The phase two research was conducted from November, 1991 through January, 1993.

The four issues which were researched in phase two of the CNG fueled vehicle demonstration project were the following:

- . changes in local, state, and industry codes and standards required to encourage the use of natural gas vehicles,
- . alternative fuel storage options and devices to insure weight/energy content (range) comparability with gasoline,
- . standard testing procedures and emission test results on CNG fueled vehicles to insure compliance with current and proposed emission requirements, and
- . approaches to achieve installation of natural gas refueling stations on a regional basis.

It was determined that appropriate responses to these four issues were critical to the determination of the market niches (fleet vehicle classes) in which compressed natural gas fueled vehicles would be able to effectively compete with gasoline, diesel, or other alternative fuels. Project conduct for each of these issues will be addressed in the following sections.

UNIFORM CNG CODES AND STANDARDS

Various local, state, and industrywide codes and standards needed to be made uniform if significant national CNG fueled vehicle market niches (fleet classes) are to be developed. The standardization of these codes and standards allows economies of scale in design, manufacture, and sales of CNG related vehicle fueling products and provides stability in the guidelines for developing and marketing this new technological application of an existing fuel resource.

Most codes and standards are either industrywide (fuel tank specifications), national (fire protection) or statewide (natural gas safety) in application, although some are local (land use restrictions). During the project conduct, it was determined that local restrictions on CNG vehicle usage and refueling locations were being addressed in Energy Task Force funded projects in Albuquerque and New York City and that those recommendations would be applied in Houston. The specific recommendations regarding local restrictions on CNG vehicle and fueling sites (e.g., land use and bridge/tunnel usage) are found in the reports referenced at the end of this report.

NATURAL GAS COMPOSITION STANDARD

One of the industrywide standards issues which was identified as a potential barrier to more widespread use of compressed natural gas as a vehicle fuel was the lack of uniformity in the composition of pipeline natural gas, specifically, significant variability in the amount of water vapor (and other corrosive agents) and methane content of natural gas from region to region, from dispenser to dispenser, and in a few cases from hour to hour. In different geographical regions,

methane content varies from seventy percent to ninety six percent; water vapor is nominally no more than seven pounds per one million cubic feet of natural gas, but this amount also varies widely, although not commonly in one location. Variability in both of these components impairs consistent engine and emission performance, requires more sophisticated (and more expensive) computerized controls on the converted CNG vehicles (or fueling stations) to adjust for the variability in fuel content, and impacts CNG fuel tank integrity and design. In fact, one of the major arguments in favor of liquified natural gas instead of compressed natural gas is that methane content can be maximized and made consistent (up to 99 percent methane), with the result of increasing the energy content per gallon equivalent. Considerable discussion has occurred in various standards and industry groups about creating a CNG vehicle fuel quality natural gas specification which would have less variability than pipeline quality natural gas similar to certification specifications for gasoline. (For example, see draft proposed revisions to SAE J1297.) Thus far, no industrywide standard has yet been developed for natural gas for vehicular applications.

In the Houston project, the methane content of the pipeline quality natural gas consistently tested at between 92 and 94 percent methane, so this was not a problem for the demonstration project vehicles. However, the water vapor content did become an issue relating to CNG fueling options and the potential need for dryers to be added to the compressors (with the resultant addition in cost).

INDUSTRYWIDE AND NATIONAL STANDARDS AND CODES

Similar industrywide issues where more progress has been made in developing standards to address consistency issues include natural gas

vehicle fuel connecting devices (e.g., nozzles) and natural gas vehicle fuel containers (e.g., fuel tanks). The American Gas Association is in the process of adopting national standards for natural gas vehicle connection devices (AGA NGV1) as well as national standards for natural gas vehicle fuel containers (AGA NGV2).

Variability in both these issues have caused barriers to market penetration of natural gas fueled vehicles. The three major different types of CNG nozzles has required public fueling stations to carry all three types of nozzles, and has limited the refueling capability of vehicles equipped with any nozzle to those fueling stations which have the same kind of nozzle connectors. AGA NGV1 is designed to address these nozzle interchangeability issues. AGA NGV2 is designed to address manufacturing issues of safety, composition, durability, and service life of CNG (and LNG) fueling tanks and associated pressure valves, plus related testing and inspection requirements.

Another national code which is being revised and modified to reflect more accurate information regarding natural gas fueled vehicles and fueling stations are the National Fire Protection Association standards, including NFPA 52,55,57, and 59 standards. The primary focus of the NFPA standards are safety.

STATE CODES, STANDARDS, AND MODEL SPECIFICATIONS

In Texas, the two agencies which regulate alternative fuel conversions are the Texas Air Control Board and the Texas Railroad Commission. The Railroad Commission focuses on safety issues, and has issued a comprehensive set of safety regulations for compressed natural gas, including CNG equipment qualifications, CNG compression, storage and dispensing systems, engine fuel systems, residential fueling faci-

lities, and registration and licensing requirements for mechanics and fueling personnel. The detailed requirements specified in these state standards are contained in the Texas Railroad Commission CNG regulation manual.

The Texas Air Control Board (TACB) regulates alternative fuel conversions relative to air pollutant emissions. Based partly on the initial emission results of this project, the TACB adopted revisions to their Regulation IV which requires aftermarket conversion equipment to be certified as meeting emission requirements by the California Air Resources Board or the U.S. Environmental Protection Agency. As of March, 1993, only eleven CNG kits had met both the TACB and the Railroad Commission requirements.

During the conduct of this research project, the General Services Commission of the State of Texas developed and revised model state specifications for conversion of gasoline engines to alternative fuels. These standard state specifications for CNG aftermarket conversion kits incorporated the requirements of the Railroad Commission and the Air Control Board plus the appropriate national codes and standards and a cost effectiveness analysis developed by the Texas GSA. A copy of the final specifications are included in Appendix C.

CNG VEHICLE FUEL TANK CONSTRAINTS

The second major issue researched during phase two of the project related to compressed natural gas vehicle fuel tank constraints. The following fuel tank issues impact the range of CNG fueled vehicles and especially impact the potential market niches for medium and heavy duty vehicles. Specifically, concerns were identified regarding the energy content of compressed natural gas at various pressures compared to

gasoline or diesel fuels plus the current composition, design and technology associated with the vehicle CNG fuel tanks which results in a weight penalty of three to four times comparable gasoline or diesel tanks. In addition, trying to find suitable spaces to retrofit the cylinders on existing vehicles is problematic. The bulk, weight, location, and storage capacity of existing onboard CNG storage cylinders is a major technical barrier to widespread use of CNG in large fleets.

Current CNG fuel cylinders are typically made of steel, aluminum, or advanced composite fiberglass wrapped metal lined cylinders. The latter cylinders typically cost three to four times more than the former, but reduce the fuel tank weight penalty in half. The cylinders are typically pressurized to 3000 to 3600 psi, although the cylinders are manufactured to specifications allowing from 2400 psi to 4350 psi. The higher the pressure, the more energy content in the compressed natural gas, and the greater the range for the same fuel tank size.

During the Houston CNG project, the pressure used for the conversion kits was 2400 psi, which caused significant range limits, particularly when coupled with fuel tank storage of approximately ten equivalent gallons per vehicle. During the project conduct, the industry standard for pressure of CNG in vehicle applications was changing, from 2400 psi to 3000 psi to 3600 psi. The 1992 GMC dedicated vehicles were designed to use 3600 psi natural gas, with a nominal range of 200 miles. Unfortunately, most CNG refueling stations are being designed with nominal pressures of 3000 psi, which reduces the range of the GMC vehicles by 15 to 20 percent. As a result of this 3000 psi refueling pressure, the City had to buy extra fuel storage tanks for all the dedicated CNG fueled vehicles it acquired during the

project, at an additional cost of \$1100 per vehicle to acquire the nominal range of 200 miles per fill-up (which is somewhat less than gasoline or diesel tank ranges).

The issue of acceptable pressure for CNG vehicle applications continues to be a major barrier to widespread fleet applications, with different approaches from the fleet users and vehicle manufacturers, who want pressures of at least 3600 psi, and the fueling industry, which supports pressures of 3000 psi because of additional infrastructure costs. Regardless of which pressure is the final choice, additional costs will be incurred, either by the fueling industry for higher pressure CNG or by the vehicle manufacturer in additional fuel tanks. All these costs will ultimately be borne by the fleet users.

The issue of tank weight and range is particularly relevant for medium and heavy duty vehicles with high operating range requirements. Transit buses nominally require a range of 300 miles, which can be obtained with 55 gallons of diesel fuel. The weight of full 55 gallon diesel tanks is 550 pounds; the weight of comparable liquified natural gas tanks is 640 pounds; the weight of comparable compressed natural gas tanks is 2500 pounds. The additional weight of the CNG cylinders affects axle load distribution, increases tire load ratings, requires modifications to steering arms and recertification of bus handling and braking systems, and may exceed bridge and road load limits. As a result of these factors, many medium and heavy duty fleets, such as Houston Metro, have determined that liquified natural gas, despite other limitations and technological concerns, is a better choice for alternative fueled medium and heavy duty applications than compressed natural gas.

The Houston project attempted to work with the NASA Technology Utilization Program to address the CNG fuel tank issues mentioned previously. Specifically, research was attempted to identify advanced materials and new processing methods to produce lighter weight, less expensive high pressure CNG cylinder storage systems and the use of other technological approaches such as advanced adsorbent materials to increase the "energy density" of compressed natural gas in the cylinders. Specific approaches to be investigated included thermoplastic liner materials with a design life of 15 years or more; low cost carbon fiber material and filament wound composites and technology; adsorption materials; and alternative materials and systems to reduce cylinder weight or increase storage capacity.

Unfortunately, the joint technology utilization project did not receive funding, and thus little progress was made through this research project on these CNG onboard fuel tank critical issues. The Gas Research Institute is conducting research on these topics, and attempting to address the energy content/tank weight/ gas pressure components of the continuing CNG fuel tank limited range issue.

PHASE TWO CNG VEHICLES

A major portion of the phase two research involved addressing the emissions related issues which had surfaced as a result of the phase one emission results. These tasks included selecting additional vehicles for CNG aftermarket conversion, obtaining original equipment manufactured dedicated CNG vehicles, selecting the CNG aftermarket conversion kits on which further emission tests were to be conducted, installing the selected CNG conversion kits, conducting the FTP emission tests, and evaluating the results of the emission tests.

As a result of the initial unsatisfactory emission tests, coupled with the advice of the aftermarket conversion retrofitters, it was determined that the additional CNG aftermarket conversion kits would not be used on the mid-level mileage vehicles previously included in the demonstration. One conclusion from the phase one test results was that retrofitting older model vehicles did not produce the desired reduction in emissions and was thus not a viable market niche for CNG conversions with current CNG conversion technology.

In order to improve the emission results, newer model light duty vehicles were used for the phase two CNG aftermarket conversion kits. Specifically a 1991 Dodge Ram 250 with low mileage (3,669 miles) was retrofitted with an Impco CNG conversion kit (shown in exhibit 3 - 21) and a 1990 Chevrolet Cheyenne 350 with low mileage (9,688 miles) was retrofitted with a Gaseous Fuel Injection (GFI) CNG conversion kit (shown in exhibit 3 - 22). Both kits were second and third generation kits and both were selected only after receipt of the CARB Board Order indicating they had been certified as meeting emission standards.

The Impco kit included closed loop feedback, and was tested with and without this feature. The Impco kit consisted of a mixer and regulator with and without an oxygen sensor. It included Autotronics computer and electronic controls. Prior to the second round of emission testing of this kit, an ALGAS metering valve was added to the kit configuration to improve feedback operation. For the medium duty gas trucks previously tested with a Canversion CNG aftermarket conversion kit, an Impco CNG conversion kit (similar to the above described kit, but specified for the medium duty Ford 7.0 liter gasoline engine) was installed and emission tested in phase two.

1991 Dodge Pickup Truck retrofitted with Impco kit. Vehicle is assigned to Public Works department.

Picture showing underhood conversion in the light duty Dodge light duty pickup truck.

1990 Chevrolet Cheyenne truck converted to CNG with a Stewart & Stevenson Gas Fuel Injected (GFI) kit and emission tested.

The GFI kit was a closed loop, solid state electronic throttle body fuel injection with computer software and controls calibrated to engine and vehicle classes. It included computer, regulator, injectors, fuel nozzle, manifold and combustion air temperature sensors, and metering valve, and was computer coded for the specific vehicle engine class and type. The GFI kit has been certified by the American Gas Association through its 1-85 CNG conversion kit standard.

The City also decided to obtain an original equipment manufactured dedicated compressed natural gas fueled pick-up and validate emission test results on one of these vehicles, for comparative purposes. The initial emission results from the CARB certification Board Order were significantly better for these vehicles than the emission results for any of the aftermarket conversion kits, and it was decided to validate this data using the same testing facilities and procedures as already used in this project for the aftermarket CNG conversion kits. The 1992 GMC Sierra obtained was a new vehicle, with a 5.7 liter V8 natural gas powered engine, as illustrated in exhibit 3 - 23. It included ECM controlled gaseous fuel injectors, with adaptive learning for variable gas composition, OEM electronics for fuel metering, and aluminum lined composite cylinders rated at 3600 psi, with a 3 year 36,000 mile warranty. During project duration, problems with the dedicated OEM CNG light duty pick ups were identified and resolved, such as fuel tank range and injector malfunctioning, but the overall performance of these vehicles was assessed as very good.

PHASE TWO EMISSION RESULTS

Emission testing was conducted at Wallace Engineering on the phase two

1993 GMC OEM Dedicated CNG Pickup Truck Emission tested and assigned to City's Public Works department.

Picture showing underhood engine arrangement in the light duty OEM CNG Dedicated light duty Sierra Pickup.

aftermarket CNG conversion kit light duty vehicles in February, 1992 and again in August, 1992, after modifications as previously noted. Emission testing was conducted on the OEM dedicated CNG vehicle in November, 1992. The August, 1992 light duty emission tests included duplicate testing at the Shell emissions testing lab in Houston, which included speciation of the hydrocarbon and aldehyde emissions, as previously recommended.

All emission test results for each vehicle are shown in Exhibits 3 - 10 through 3 - 20, as previously noted and detailed in the Final reports cited in Appendix B. The emission results for the CARB certified aftermarket CNG conversion kits were better than the previous kit results, but only marginally better than comparable gasoline emission results (and worse for some pollutants). The Impco kit had 20% lower nonmethane hydrocarbon emissions and 26 % fewer carbon monoxide emissions, but a marginal increase in nitrogen oxide emissions. The GFI kit had a 5 % increase in nonmethane hydrocarbons and a marginal increase in carbon monoxide, but a 10 % reduction in nitrogen oxide emissions.

The OEM-CNG emission test results were significantly better than the aftermarket CNG conversion kit emission results, with a 31 % reduction in nonmethane hydrocarbons compared to the gasoline emissions, a 44 % reduction in carbon monoxide emissions, and an astonishing 95 % reduction in nitrogen oxide emissions. In fact, the OEM-CNG vehicle emission results were less than ultralow emission standards for carbon monoxide and nitrogen oxides and below the 1994 federal emission standards for nonmethane hydrocarbons, although these test results did not achieve the low emission standards for nonmethane hydrocarbons.

These impressive emission results document emission improvements for the OEM CNG vehicle of four to five times better than the best aftermarket CNG conversion kit results. Based on this data, the City determined its alternative fueled vehicle strategy for light duty vehicles should be based primarily on OEM CNG vehicles. It would only use aftermarket CNG conversion kits in vehicle classes where OEM CNG vehicles are not available, where the incremental cost of OEM CNG is significantly greater than aftermarket CNG conversion kits, or if the aftermarket CNG conversion technology improves sufficiently to demonstrate FTP emission results comparable to the OEM CNG emission results previously shown.

Emission testing was conducted at Southwest Research on the medium duty Impco conversion kit in December, 1992 and on the heavy duty OEM dual fueled Detroit Diesel PING engine in March, 1992 and again in December, 1992, after significant modifications to improve emission results. These engine modifications were completed by Stewart and Stevenson (after consultation with Detroit Diesel), and included addition of an oxidizing catalyst, various engine component upgrades such as new piston rings and liquid charge cooling, and fuel control system software upgrades. Details of the emission testing procedures and issues associated with the heavy duty emission testing are detailed in the Phase II Final Report (March, 1993) cited in Appendix B.

The emission results from both the medium duty Canversion and the Impco kits were similar, with 60 % reductions in nonmethane hydrocarbons and 75 % increases in nitrogen oxides. The Canversion kit produced significantly lower carbon monoxide results, but both kits had better carbon monoxide results than gasoline.

Since both nonmethane hydrocarbons and nitrogen oxides are precursors of low level ozone formation, reducing one while increasing the other has minimal air quality benefits. Thus, it was concluded that the medium duty gasoline aftermarket CNG conversion kits did not achieve the air quality benefits expected, and were roughly comparable to gasoline from an ozone related air quality perspective.

The emission results from the heavy duty dual fueled OEM CNG 6V92 vehicles did not meet expectations, like the aftermarket conversion kit results obtained in this project. The best emission results for non-methane hydrocarbons and carbon monoxide were three times higher on dual fuel than on diesel alone, with nitrogen oxide emissions about the same as on diesel. Based on these emission results, it was determined that the anticipated air quality benefits from this OEM CNG engine technology were not demonstrated, and further technological improvements would be required to achieve air quality benefits comparable to the light duty OEM CNG vehicle emissions previously noted.

CNG FUELING INFRASTRUCTURE ISSUES

The fourth issue addressed in phase two of the project dealt with determining an effective operational and financing approach to address CNG fueling in the region. A number of joint public-private approaches were investigated to provide CNG refueling stations, but the final approach involved primarily a private sector response.

The City considered upgrading the existing project CNG refueling station as the initial public CNG fueling station. However, that facility was designed to operate on 2400 psi, using a probe nozzle.

The cost of upgrading the station to 3600 psi, and providing the multiple nozzle connectors necessary to make it a public CNG fueling station was estimated at \$ 30,000, including replacing all hoses, replacing all fill connectors, additional cascade storage, replacing tubing, and considering an upgrade of the compressor.

City staff expressed concerns regarding the potential liability of the City operating a public CNG fueling station. The City experience with gasoline and diesel fueling raised questions about whether it was cost effective for the City to provide any kind of vehicle fueling services rather than having these services provided by contractors. There were even more concerns expressed about the potential "carrying costs" which would be required in providing a City CNG fueling station until the number of CNG vehicles in the region (or even in the City fleet) was sufficient to economically support a moderate sized CNG refueling station, particularly in light of the generally unsatisfactory emission results which emerged from the project. Despite potential cost sharing benefits from various public-private CNG fueling options, the City decided not to participate actively in the CNG fueling infrastructure development because of the aforementioned concerns.

Another factor in this City decision was the existence of active private sector groups, with an interest in and funding available to proceed in the creation of a regional public CNG fueling system. For example, one approach used in response to the CNG fueling infrastructure concerns in the Houston region was the creation of a private corporation, Enfuels, designed to finance, design, construct and operate a public CNG refueling system in the Houston region. Initially, the principal private sector partners involved in the

creation of Enfuels were Enron, a major gas transmission company headquartered in Houston, Entex, the Houston area gas distribution company, and Natural Fuels, a Denver based firm specializing in CNG fuel stations. Prior to incorporation, Natural Fuels was replaced by Transco, another Houston based natural gas company, as the third corporate shareholder of Enfuels.

Enfuels developed a marketing strategy to provide six CNG fueling stations geographically dispersed through the Houston region by the end of 1992, with a much larger network to be operational by the turn of the century, with many of the initial CNG dispensers co-located with existing gasoline stations. The first public CNG fueling station in Houston was a stand alone station opened by Crown Services in July, 1991, with the first Enfuels CNG refueling station (jointly with Chevron) operational by July, 1992. By the end of 1992, four public CNG fueling stations were operational in Houston, with another five in the planning or construction stages. While the initial CNG fueling stations took some time to obtain all the necessary permits and code approvals, during 1992, the time from final contractual agreements to operation of the CNG stations was reduced to several weeks.

Based on the availability of public CNG fueling stations, the City decided to develop specifications to purchase CNG to fuel its growing CNG fueled vehicle fleet (from 12 demonstration vehicles to 31 OEM CNG vehicles in 1992, with another 25 under order and much larger quantities anticipated in subsequent budget years) at the public CNG stations, rather than invest in its own CNG fueling system. Enfuels was awarded the three year contract at a fixed price of 68 cents per equivalent gallon, with further volume discounts available.

While the aforementioned arrangement has had positive results for both the City and the private CNG fueling companies, future decisions still need to be made regarding the long term CNG fueling infrastructure in the Houston region and for the City of Houston. Options under consideration include CNG stations without cascades and liquified to compressed natural gas refueling. A number of operational and technological issues need to be resolved prior to determining the final CNG fueling system in Houston.

EVALUATIONS OF CNG VEHICLE PERFORMANCE

Survey tools utilized for operational data collection during this study were structured to serve both as field operation personnel monitoring tool as well as supervisory perception mechanism. In addition to the field operation personnel, mechanics who worked on these vehicles were also monitored. Among the factors considered were:

- Vehicle Take-off power
- Smoothness of vehicle operation
- Equipment Dependability/Downtime Safety concerns
- Fuel flammability/Explosive potential
- Fueling Time/Range Inconveniences associated with dual
- Fueling requirements

The City conducted an extended field study to obtain operational, maintenance, and performance information on each vehicle type. Generally the operation, maintenance, and performance of the converted vehicles was judged to be satisfactory by the City drivers and support personnel. Initially, driver and mechanic satisfaction with the vehicles was very high. During the course of the research project, particularly after the conversion kit revisions and modifications were required as a result of the emission results, driver and operational personnel support waned.

The overall performance and maintenance of the converted vehicles was deemed to be at least equivalent, if not better, than the gasoline or diesel vehicles, however, there was some variability in driver response depending on the vehicle type. The light duty vehicle operators reported the fewest problems and the greatest level of satisfaction with the CNG vehicles. The medium duty vehicles were highly rated for performance and added power as well as for technical support, but were assessed as only fair with respect to downtime, equipment reliability, and maintenance frequency by the mechanics and supervisors. Some of the downtime can be attributed to the age of the vehicles and is unrelated to CNG, but other parts of the downtime were directly related to the CNG demonstration. (An example was the time required to transport the vehicles to San Antonio, leave them there, and return them to obtain the FTP emission testing required by the project.) Another problem experienced primarily during the early phases of the project was repeated freezing up of the refueling nozzles in the fast fill process.

The driver acceptance of the heavy duty OEM CNG bi-fueled vehicles was initially very positive, but became less so as problems and delays occurred during the project duration. There were several incidents which identified inappropriate location of key components and circuitry (under driver's seat), resulting in water contamination of the components requiring replacement and relocation. There was also significant downtime associated with the installation of and revisions to the engine technology and emissions control components.

CNG VEHICLE SAFETY

The perception of natural gas as an explosive fuel has been one of the most significant barriers to public acceptance. As a result of low toxicity level, compressed natural gas (CNG) presents a very low health risk from direct exposure or inhalation as opposed to the impact of gasoline or diesel fuel. At the beginning of this project, various strategies were designed to calm the fears of potential CNG vehicle operators and their supervisors. Among the steps taken were: meetings with Entex staff whom have accumulated extensive experience using CNG as vehicle fuel. Open and one-on-one discussions relating to operational experiences were permitted and encouraged. Safety oriented video tapes developed by the AGA were shown to employees and their supervisors and repeated when necessary.

The safety of CNG fueled vehicles was demonstrated at various times during the project. A convincing event occurred during a light duty conversion, in which natural gas escaped from the vehicle being converted. The gas which escaped from the tank, rapidly moved upward resulting in a popping sound. The situation was immediately controlled by shutting off the release valve. Two of the medium duty vehicles were involved in separate accidents in October, 1991 and in February, 1992 (including a wreck of one vehicle), with no CNG leaks in either the tanks or the fuel lines. Similarly, one of the heavy duty dual fueled tractor trailer trucks turned over in March, 1992 without any damage or problems associated with the compressed natural gas fueling and storage components. Exhibit 3 - 24 shows one of the GMC Sierra pickups after it rolled over in the fall of 1992 without any damage to the compressed natural gas systems.

Accident experience with a light duty dedicated CNG GMC Pickup truck. Picture shows left, right and rear damage including impact on fuel storage system with no extensive damage. Vehicle was repaired and returned to service.

CHAPTER FOUR - CRITICAL CNG FUELED VEHICLE ISSUES

For compressed natural gas fueled vehicles, several critical issues have emerged from this and similar research projects and from other experiences in the fleet marketplace which require further progress if CNG vehicles are to achieve significant penetration into various fleet market niches (vehicle types). These critical issues include demonstration of positive emission results, resolution of vehicle range limitations, replication of compressed natural gas vehicle fueling infrastructure, and competitive costs of CNG vehicles, kits and fuels.

DEMONSTRATION OF POSITIVE EMISSION RESULTS

The accepted wisdom is that natural gas is a clean burning fuel, and therefore should have a marketplace advantage as an environmentally preferable fuel. It has been shown in laboratory tests that natural gas produces fewer regulated pollutants than virtually any other type of commonly used energy.

However, the emission results from this project generally do not support this accepted wisdom or marketplace advantage for compressed natural gas fueled vehicles. The results from this test program dismiss the widely held conception that simply converting a vehicle to run on natural gas will result in dramatic reductions in exhaust emissions. The general conclusion was that none of the natural gas conversion systems that were tested justified wide scale conversion to natural gas based solely on exhaust emissions performance. Of the twelve CNG vehicles in this demonstration project for which emission results were

determined (ten after-market CNG conversion kit applications and two OEM CNG vehicles), only one (the light duty OEM CNG vehicle) showed significant improvement in emissions from the baseline gasoline or diesel vehicles.

What the project did demonstrate was that current CNG vehicle technology is not appropriate for a number of vehicle types. From an emissions perspective, current CNG technology is not competitive for carbureted vehicles; for older model, moderate mileage vehicles; for diesel vehicles; for dual fueled (CNG and diesel) vehicles; and generally for aftermarket conversion kits. Only the latest second and third generation CARB certified aftermarket conversion kits showed marginal improvements in emissions from the gasoline fueled vehicles.

The project clearly indicated that CNG vehicle technology can produce significant emission improvements compared to gasoline vehicles, as demonstrated by the very low emission results for the OEM CNG light duty vehicle. However, of the vehicles tested, this result was the exception rather than the rule.

These results reflect the state of CNG vehicle technology in the early 1990s, and one of the early lessons learned from the project was that CNG vehicle technology is changing very rapidly. At times during the demonstration project, it appeared to be changing monthly, and even weekly. Significant and widespread research activity is occurring in CNG vehicle technology, and each CNG conversion iteration improves on the previous versions.

A significant component of the unsatisfactory emission results from this project can be attributed to comparing the CNG results to actual baseline gasoline and diesel emission results, which were significantly less than the current emission standards. The low baseline emission results can be directly attributed to the significant

improvements made by the automotive and oil industries in cleaning up the emissions from gasoline and diesel fuel through catalysts, sophisticated engine and fuel technologies, and other improvements.

Perhaps the unsatisfactory emission results can be attributed to the new applications (vehicles) of a proven clean burning fuel. If this is part of the explanation, then the industry needs to devote even more efforts and resources (similar to the resources devoted by the automobile and oil industries) to improve the existing CNG vehicle technologies (particularly the aftermarket CNG conversion kits), to refine catalytic converters for CNG engines, and to increase the commitment of the automobile industries to producing low emission CNG vehicles.

The most significant issue to emerge from this research project is the importance of achieving and documenting lower air pollutant emissions using compressed natural gas in vehicles instead of gasoline or diesel fuel. The TACB regulation requiring CARB or EPA certification of the air quality benefits of CNG conversion kits is the type of standard which needs industrywide support and implementation.

RESOLUTION OF VEHICLE RANGE LIMITATIONS

One barrier to widespread use of CNG fueled vehicles in fleet applications (and to the larger public market utilization) which was not successfully addressed through this research project was the vehicle range limitations. Typically CNG fueled vehicles do not have the range of comparable gasoline or diesel fueled vehicles. Additional research needs to be completed to reduce the energy content/weight penalties of compressed natural gas as a vehicle fuel, particularly if it is to compete effectively for medium and heavy duty fleet applications, over the road and similar fleet applications with high range requirements, and general public (non-fleet) vehicle applications.

Three different approaches have been identified which might successfully remedy the range limitations of CNG vehicles - development of lightweight fuel tank materials, refinement of adsorption technologies to increase the density of natural gas at various pressures, and increase the industrywide standard for compressed natural gas operating pressure in vehicles. All three approaches will increase the incremental costs for CNG as a vehicle fuel, and the first two approaches will require significant additional research and testing before they are commercially viable options.

Resolution of the industrywide compressed natural gas pressure standard issue (2400 psi, 3000 psi, 3600 psi, or a higher pressure) will significantly impact the potential market niche of CNG fueled vehicles since it will determine the comparability of CNG vehicles with gasoline vehicles with regard to range and cost, and also impact the cost of CNG fueling infrastructure . It will also influence whether medium and heavy duty fleets decide to use liquified or compressed natural gas as an alternative fuel of choice.

COMPRESSED NATURAL GAS FUELING INFRASTRUCTURE

One marketplace barrier which was successfully addressed during the Houston demonstration project was the development of a regional CNG fueling system available to the public through private suppliers. In the Houston region, various private interests had both the motivation and the funding to design, construct, and operate CNG fueling stations, generally in combination with existing gasoline fueling stations. The approach of joint ventures among interested private groups (natural gas suppliers, natural gas transmission companies, natural gas distribution companies, and gasoline distribution companies) proved to be effective in cost and risk sharing to achieve a geographically widespread CNG fueling presence in a short time.

Experience from the Houston project provided little support for individual fleet based fuel sites, due to the limited number of CNG vehicles in operation during the project and the availability of public CNG fueling sites at competitive prices. Houston Metro was the notable exception, but their decision to construct LNG stations on their property was based on the lack of any other options, on their determination to accelerate LNG vehicle and fueling technology, and on their desire to maintain control over their vehicle fueling operations.

In the Houston region, the private marketplace has provided CNG fueling infrastructure and is expanding as demand for CNG vehicles grows. It is critical that the development of the CNG fueling infrastructure be properly planned and scheduled so as to not get too far ahead or too far behind the actual utilization of CNG fleet vehicles. As an example, it was important for the CNG fuel distributors to know the approximate CNG vehicle acquisition schedule of the major fleets in order to insure adequate numbers and capacity of the fueling sites, given the lead time to permit and construct the various fueling sites.

For the natural gas fueled vehicle industry the issue regarding CNG vehicle fueling infrastructure is how to replicate the successful Houston approach elsewhere, or how to achieve similar results with another approach. As previously noted, the major unresolved issue regarding CNG refueling, like the vehicle range limitation issue, is the determination of which CNG pressure (3000 psi or 3600 psi) will become the industrywide standard for vehicular applications.

COMPETITIVE CNG VEHICLE, KITS, AND FUEL COSTS

The last critical issue for CNG fueled vehicles which emerged from the Houston research project was the competitiveness of CNG vehicles, CNG conversion kits, and CNG fuel. Obviously, the closer the cost of CNG vehicles, kits, and fuels are to the costs of gasoline vehicles and

fuels, the greater the market niche and the fleet vehicle utilization likely to be achieved by CNG vehicles.

Natural gas has historically been underpriced in comparison to petroleum on an energy content basis. Historical pricing data demonstrate a relatively constant price ratio between natural gas and petroleum over the past several decades, as shown in Exhibit 4 - 1. This historical constant price differential provides some level of confidence regarding future price relationships between these two fuels, and argues against a future increase in natural gas prices without a comparable increase in petroleum prices, particularly in light of the significantly larger amount of natural gas than petroleum reserves in the United States.

However, the cost of compressed natural gas must not only include the cost of the natural gas but also the cost of compression. The City of Houston pays 82 cents per gallon of gasoline, including state taxes but not including federal taxes. Houston also pays approximately 30 cents per gallon equivalent for uncompressed natural gas, based on a negotiated contract rate with our local gas distribution company. In addition, any CNG vehicle in Texas must pay a licensing fee to the Texas Railroad Commission, which equates 10 cents per gallon equivalent. Thus, the cost of compressing natural gas for vehicle use cannot exceed 42 cents per gallon equivalent if the price of compressed natural gas is not to exceed the price of gasoline.

If the City decided to construct its own CNG fueling sites, the cost of the equipment would need to be less than 42 cents per gallon equivalent. Since the City currently purchases CNG at a cost of 68 cents per gallon equivalent, it saves 7 cents per gallon equivalent of CNG compared to the price it would pay for gasoline and has no capital costs for the compression facilities.

NATURAL GAS VS GASOLINE COST COMPARISON 1976 - 1988

While natural gas as a fuel is less expensive than gasoline, the opposite is true regarding vehicle costs, either on an aftermarket retrofit basis or on an original equipment manufactured basis. The cost of a typical aftermarket CNG conversion kit for a light duty vehicle is approximately \$2500, with \$1000 for the CNG cylinders and \$1500 for the conversion kit. This is an additional cost of approximately 20 percent to the original cost of the vehicle.

For the OEM CNG 3/4 ton pickups obtained by the City of Houston, there was a substantial incremental cost for the CNG option, which ranged from 14 to 27 percent (\$2,000 to \$4,600 extra). The low cost was for 1992 vehicles (including extra CNG tanks at 3000 psi to approximate the range of comparable gasoline vehicles) purchased in July, 1993 with several nonmanufacturers' pricing incentives incorporated. The high cost was for 1992 vehicles purchased in July, 1992 on a state contract, which had very favorable prices, but which had to be retrofitted with extra tanks to achieve comparable range.

The incremental cost differential for the CNG option for same 3/4 ton pickup in the 1993 model year (with the extra CNG tanks required for comparability) exceeded \$7300, or an additional cost of 39 percent. The City decided not to buy any of the 1993 CNG vehicles because of the 39 percent additional cost.

To obtain an illustration of the life cycle cost of the CNG vehicle options, assume the above referenced trucks drive 15,000 miles per year and average 10 miles per gallon. Also assume there is a price differential of 20 cents per gallon equivalent between the price of CNG and gasoline, and the additional cost of the CNG vehicle is \$2500. Based on these cost assumptions, the additional CNG vehicle cost would be repaid in slightly more than eight years (or 120,000 miles), which is also slightly more than the useful life of most light duty vehicles.

This example illustrates the sensitivity of the various components of costs of CNG vehicles and fuels. It also illustrates the existing price competition in the marketplace, and indicates which incremental CNG vehicle prices can and which cannot be supported based on economic criteria. If CNG vehicles are to achieve any marketplace penetration, they must compete within the existing vehicle pricing structure, or clearly demonstrate some marketplace advantage which warrants the additional costs.

CHAPTER FIVE - LESSONS LEARNED

During the conduct of the Houston CNG fueled vehicle demonstration project, several changes were required as a result of unanticipated results or external events. This chapter will briefly discuss several of the observations and lessons learned during the project, excluding those outstanding issues associated with CNG fueled vehicles. The previous chapter detailed critical issues for CNG fueled vehicle utilization in large fleet applications which evolved from the project experience and which remain outstanding at the conclusion of the research project.

PROJECT SCHEDULE AND DURATION

As noted previously, the project was initially designed as a small scale, limited demonstration project with an expected duration of eighteen months to field test existing CNG fueled vehicle technology in various vehicle classes (light, medium, and heavy duty, plus gasoline and diesel fueled) representative of the City of Houston fleet composition. Its primary focus was on the emissions benefits of using compressed natural gas as a vehicle fuel, and projected completing 145 Federal Test Procedure emissions tests on 35 test vehicles.

Due to funding limitations, the original scope of the project was scaled back to nine CNG aftermarket conversions or OEM CNG vehicles in the four vehicle classes. Due to the unanticipated and unsatisfactory emission results noted in chapter three, the duration and scope of the project were significantly expanded in 1991 to incorporate three additional aftermarket CNG conversion kits and an additional OEM CNG light duty vehicle and to address the four barriers to CNG fueled vehicle use in fleets noted in chapter three.

The lesson learned from the project regarding the project duration and scope is that it is difficult to accurately project time lines associated with emerging technological applications, such as CNG fueled vehicles. There was an initial overassessment of the state of the art with respect to natural gas fueled vehicle technology, which resulted in a gross underestimate of the time and unresolved issues relating to CNG vehicle technology. The project also emphasized the need to be flexible and the ability to respond effectively to unanticipated results in conducting field tests of emerging technologies.

CNG FUELED VEHICLE TECHNOLOGY

There were several lessons learned from the project regarding compressed natural gas fueled vehicle technology. The first lesson was the initial overassessment of the state of the art of CNG fueled vehicle technology at the start of the project. While CNG fueled vehicles had been in operation for several years at project initiation, little, if any, documented research had been conducted regarding the emission results of CNG vehicles in operation. The project was effective in focusing attention on the importance of emissions results in CNG fueled vehicle conversions. The project was also effective in focusing attention on vehicle range (fuel tank) and fueling infrastructure issues.

Some of the early lessons from the project included the identification of what vehicle types were not suitable candidates for current CNG conversion technology. Specifically, carbureted vehicles, diesel fueled vehicles, high mileage vehicles, medium duty vehicles, and heavy duty vehicles are not recommended for CNG conversions using existing CNG technology, based on the project results. Similarly, aftermarket CNG conversion kits for light duty vehicles did not perform as well as OEM CNG vehicles in emission tests.

Another important lesson learned from the project was the rapidly changing status of compressed natural gas fueled vehicle technology. No sooner than one CNG aftermarket conversion kit demonstrated unacceptable emission results, another iteration of the kit was available to address the problem. There continues to be widespread activity in compressed natural gas fueled vehicle technology, with increasing sophistication in the design of CNG conversion kits (comparable to the sophistication in gasoline engine and catalyst technologies).

Currently natural gas conversion equipment consists of two types, mechanical and electronic, with mechanical systems typically in use, since they are first generation technology. Like the Canversion kits, they consist of several components designed to get the fuel to the fueling system (carburetor/fuel injectors) and to adjust the timing so natural gas can be ignited at the right time in the cylinder. They can be either open or closed loop systems. Open loop systems are passive devices that do not adjust to varying engine operating conditions; closed loop systems adjust fuel - air mixtures based on different sensed conditions.

The second and third generation CNG conversion kits are electronically controlled, like the Impco and GFI kits tested in the project. An electronic conversion system uses gas injectors or metering valves rather than an air mixing unit to allow more precise control. Microprocessors are used (in conjunction with the car's computer or in place of it) to drive the injectors and control the spark ignition, and modify these controls based on different sensed conditions from the closed loop sensors.

At some point in time in the project duration, there had to be a cessation of testing of "new and improved" CNG technologies and modi-

fications. For the CNG vehicle technologies tested in this project, only the OEM dedicated CNG light duty vehicle produced acceptable emission results in comparison to gasoline vehicles. However, research and development is continuing at a rapid pace at various sources to address issues in CNG vehicle technology implementation. It appears to be a prudent course of action to select the most recent iterations of CNG vehicle technology available at the time of acquisition, so that the latest improvements in this rapidly changing field are obtained.

One of the important lessons from the demonstration project is the prerequisite that purchasers of CNG fueled vehicle technologies need to insist on documented acceptable emission results from an independent source, such as CARB or EPA, prior to acquisition, as required by the CNG conversion kit model specifications developed by the Texas General Services Administration (and provided in Appendix C.) It is also important to note that CNG kits are generally approved for a specific vehicle class, and it is critical that the kit be certified for the vehicle class and type for which it is intended to be used.

For the City of Houston, the project resulted in a CNG vehicle acquisition strategy emphasizing OEM CNG light duty vehicles due to the significant demonstrated difference in emission results compared to aftermarket conversion kits. Similarly, as part of any CNG vehicle acquisition, a requirement for additional onboard fuel tanks (or some other solution to the vehicle range limitation issue) needs to be addressed, in addition to a CNG fueling infrastructure solution.

An important lesson learned from the project regarding CNG fueled vehicles is that they can achieve the clean burning status widely attributed to this technology, although improved emissions from CNG vehicle technology might not be as easily achieved as previously assumed. The project has demonstrated that compressed natural gas can

be an effective alternative fuel in light duty fleet applications, but there are ongoing issues which need to be addressed before it can increase its potential for widespread fleet use to other vehicle classes, including emission results and competitive costs of CNG vehicles and fuel.

PARTNERSHIP APPROACHES

The Houston project was effective in establishing a collaborative public-private approach in addressing the issues associated with the introduction of CNG fueled vehicles in the region. As noted in chapter two, the project involved a wide array of interested federal, state, and local government groups as well as several local private sector companies and corporations. The collaborative approach established at the beginning of the project proved to be very effective, particularly in responding to the mid-course corrections and changes in project scope and duration, and in refocusing the project on further research options. The continuing dialogue among the various partners in the project provided excellent expert review and comment, while influencing not only the City CNG fueled vehicle strategy, but also the CNG fueled vehicle strategy of the other local, state, and national public and private participants.

This approach also resulted in industrywide approaches and responses to issues raised through this research project, as previously noted. This collaborative approach can be readily transferred to other jurisdictions, although the participating groups will vary from area to area.

One area regarding partnership approaches where the project did not meet initial expectations was in the level of active commitment and risk taking by the City. Several times during the project duration, partnership approaches were explored which required significant active

participation and commitment by various City groups in collaboration with private partners, and decisions were made not to proceed with these approaches. Specifically, in the CNG fueling infrastructure options, a number of approaches for City owned sites were considered for initial public fleet CNG fueling sites (including equity participation, leasing, and City operation) and all were rejected by the relevant operating departments.

The response to the CNG project varied widely within various City fleet operating departments, ranging from avid and vocal support and participation in the Public Utilities Department to non-participation by certain fleet departments. Overall, the fleet operating departments took a limited support and exposure approach, consistent with the overall City project approach.

The limited field test approach of the project was shown to be an effective decision-making process. This approach resulted in limiting exposure (and costs) to what turned out to be unacceptable CNG vehicle options, and resulted in an acceptable citywide CNG vehicle approach to fleet conversion requirements, as further discussed in chapter six. It is recommended that other jurisdictions follow this approach as an effective way to explore and assess new technologies and innovative approaches while limiting costs and liabilities.

CHAPTER SIX - HOUSTON APPROACH

This chapter will present the conclusions drawn from this research project which relate to City of Houston choices regarding fleet alternative fuel mandates. It will generally provide the answers to the initial research focus questions detailed in Appendix A based on Houston's experience with compressed natural gas fueled vehicles through this project. It will identify the City of Houston's alternative fueled vehicle fleet strategy, based on the research results.

RESEARCH FOCUS QUESTION ANSWERS

The answer to the overall research question about what portion of the fleet should be converted to alternatively fueled vehicles depends on the reason alternatively fueled vehicles are being considered. If alternatively fueled vehicles were being considered solely on a voluntary basis in the Houston region, the research project concludes that no compressed natural gas fueled vehicles should be acquired, due to the additional costs (which are not recovered in the life cycle of a typical City vehicle) and the minimal positive impacts on air quality. There are some benefits from energy security and economic development (jobs) perspectives, but these do not outweigh the limited air quality benefits and additional vehicle costs.

However, the City of Houston is required to convert portions of its fleet to alternative fuels by two federal (clean air and energy security) and one state law, as noted in chapter two. The state law has the most extensive fleet conversion requirements, and thus has the greatest impact on the amount and numbers of vehicle alternative fuel conversions.

From an air quality perspective, the use of compressed natural gas vehicles in the City fleet will not have a significant impact on the low level ozone problem in the Houston/Galveston nonattainment area. This is because no strategy based only on fleets will result in significant air quality impacts in this region. Only fourteen percent of this region's VOCs and eighteen percent of its NOX emissions are from on road mobile sources. If all fleet vehicles (estimated at 12 - 15 % of the region's vehicles) were able to achieve zero emissions, it would only reduce VOC emissions by two percent and NOX emissions by less than three percent.

While the emissions from the OEM CNG light duty vehicle were very low in comparison to gasoline emissions, they are not zero emissions. However, these vehicles have shown emission improvements of 40 - 90 % from existing gasoline vehicles, and, if compressed natural gas vehicles were to achieve widespread general public acceptance, the air quality benefits could approach ten to twelve percent of the region's air quality problem. All air pollution control strategies may be required to achieve compliance with the national ozone standards in the Houston region.

From an energy security perspective, the impact of converting the City fleet to alternative fuels is insignificant. The City fleet uses an average of 1,000 gallons per vehicle annually, or a total of about ten million gallons of gasoline and diesel (less than 250 barrels per year). Assuming similar consumption for all fleet vehicles in the region, the total regional fleet vehicle consumption of gasoline and diesel is about 7 million barrels annually. The current national consumption of oil approximates 20 million barrels each day, with the preponderant use in vehicle fuels. If all Houston area fleet vehicles were converted to compressed natural gas, it would only reduce national

demand for oil by less than one-one hundredth of one percent ($<0.01\%$).

From a cost perspective, the additional cost of OEM CNG light duty vehicles and aftermarket CNG conversion kits are not recovered in the expected life cycle of City vehicles, based on current cost comparisons, as detailed in chapter four. The current additional costs for medium and heavy duty CNG vehicles are even less competitive than for light duty vehicles.

Despite the aforementioned comments, the City of Houston is proceeding to implement a compressed natural gas fueled fleet conversion program, in part, because the fleet conversion is mandated by state and federal laws. Additionally, success in obtaining acceptable answers to the other research focus questions has motivated the City to continue. The research project has provided satisfactory answers to infrastructure, maintenance, and operations questions regarding CNG fueled vehicles, as detailed earlier in the report.

HOUSTON ALTERNATIVE FUELED FLEET STRATEGY

The alternative fueled fleet strategy being pursued by the City of Houston to meet mandated fleet conversions is based on the lessons learned and successful experiences provided by the demonstration project. It also reflects the City's fleet composition, the current relative state of light duty CNG vehicle technology compared to medium and heavy duty CNG vehicle technology, and the lower ozone precursor emissions of diesel fuel compared to gasoline.

The City has mandated that all future light duty vehicles will be compressed natural gas fueled, with two qualifications - 1) that original equipment manufacturers (OEMs) produce CNG vehicles of the type and class being obtained, and 2) that costs are competitive with similar gasoline fueled vehicles. The City has also indicated it will

consider aftermarket CNG conversion kits for light duty vehicles under the following circumstances:

- . proven emission results comparable to OEM CNG emission results,
- . comparable costs to OEM CNG vehicles, and
- . vehicle classes in which no OEM CNG vehicles are available.

Because of the composition of the City fleet, with more than sixty percent of its fleet consisting of light duty vehicles, the City CNG fueled vehicle strategy of procuring OEM CNG light duty vehicles will meet all state and federal requirements through 2000. It will also cost significantly less, since the cost per light duty CNG vehicle is lower than medium and heavy duty CNG vehicles.

The City CNG fueled fleet strategy is also predicated on the conclusion that light duty CNG vehicle technology is significantly ahead of medium and heavy duty CNG vehicle technology at this time, particularly for the preponderance of medium and heavy duty vehicles which are diesel fueled. In addition, some air quality benefits will accrue in these classes of vehicles with the mandated use of low sulfur diesel, starting in October, 1993. The City strategy will allow medium and heavy duty vehicle CNG or LNG technology to improve so that it clearly exceeds diesel ozone precursor emission results by the time (2000) these vehicle classes will be required to be converted to alternative fuels. It is also anticipated that the cost increment for medium and heavy duty CNG engine technology will decline as the technology improves.

The City strategy for fueling its CNG vehicles relies on fueling stations provided by the private sector as a transitional approach. There is a short term contract in place to provide CNG at public fueling stations at a price below gasoline prices. This strategy was based on the availability of private sector fueling stations, the reluctance

of City operating groups to provide public fueling facilities, and the cost of constructing a CNG station compared to the relatively low volume of CNG vehicles in the City fleet in the near term. The City will explore other long term CNG fueling options as the size of its CNG fleet expands.

The City is exploring what role it will take in encouraging the use of CNG in other light duty fleets in the region. There are strong financial arguments in favor of one alternative fuel in a region, rather than multiple alternative fuels. The City is also investigating what compatible actions can be taken in support of Metro's LNG decision for their heavy duty vehicles. To the extent a fueling system can accommodate both LNG and CNG vehicles, it will have a larger vehicle base and can achieve certain economies from using the same fuel, but in different forms.

APPENDIX A

**CITY OF HOUSTON
COMPRESSED NATURAL GAS DEMONSTRATION PROJECT**

FOCUS QUESTIONS - HOUSTON

1. Overall questions

What part of the City Fleet should be converted to natural gas alternate fuel?

2. Economic questions

- What is the cost of using CNG as a vehicle fuel? in mpg?
- What is the cost of a refueling station?
- What is the cost of conversion (retrofit or new) to CNG?
- What is the cost removing CNG conversion kit?
- What is the marketability (resale value) of a converted vehicle?
- What is the life cycle cost of a CNG fueled vehicle?
- What are the comparable cost to the City for gasoline or diesel?

3. Environmental

- What are the NOx effects of CNG converted vehicles?
- What are the other vehicle emission results of CNG-converted vehicles?
- What are the environmental effects of "flexible fuels" (CNG or gasoline) conversions?
- What are the environmental effects of "mixed fuels" (CNG and diesel) conversions?
- What highway safety and safety certification problems result from the use CNG as vehicle fuel?

4. Operations

- What are the effects on payload loss from tanks located in payload bay - space and weight impact?
- What are the effects of CNG on vehicle performance?
- What is the level of driver acceptance of CNG?
- What are the effects of limited range on CNG vehicle usage?
- What extra safety precaution are necessary as a result of high pressure CNG fuel storage condition?
- What is the down time for tank and system testing?

- What is the effect of slow fill time in refueling - even using cascades?
- What are the impact of double fueling required in diesel applications?
- What are the impacts on engine performance (and emissions) of fuel switching?
- How do you handle emergencies such as fuel loss?

Maintenance

- What are the cost of repairs?
- What training/skills are required to repair CNG vehicles?
- What training/skills are required to convert CNG vehicles?
- What routine service is required?
- What special tools are required?
- What engine adjustments are required for fuel switching?
- What is the availability and cost of replacement parts?
- What is the reliability and dependability of the CNG equipment?
- What are the maintenance costs of refueling stations?

Infrastructure

- What is the local support of the conversion apparatus, tanks, etc.?
- Who owns and operates the refueling stations?
- What is the CNG supply reliability and long-term CNG supply security?
- What costs and other operating issues occur regarding centralized Vs decentralized refueling?

**CITY OF HOUSTON
COMPRESSED NATURAL GAS DEMONSTRATION PROJECT**

Research focus Questions - General

1. What are your purpose and proposed schedule for acquiring alternatively fueled vehicles?
 - Is it to meet federal or state mandates (required)?
 - Is it for environmental concerns (air quality)?
 - Is it for economic concerns (cost savings)?
 - Is it for national security concerns (domestic fuel availability)?
 - What are the planned timeliness for acquisition?

2. What are your existing vehicle fleet characteristics and requirements?
 - What are the types of vehicle (light, Medium, Heavy duty)?
 - What are the purposes of vehicle use (duty cycle; daily fixed or variable routes; range; short or long haul; load passenger or material; daily return to base or not; vehicle primarily idling, under load or over load)?
 - What are the number of each type of vehicle?
 - What are the current fuel type (gasoline, diesel, other)?
 - What are the current fueling arrangements (central, multiple, or public fueling facilities)?
 - What is the current vehicle replacement cycle?

3. What are vehicle fleet characteristics and requirements for other entities (public and private) in your region which are considering alternatively fueled vehicles?
 - Same as above

4.
 - What are the advantages and disadvantages of each fuel (Electric, Ethanol/MTBE, Hydrogen, Methanol, Natural Gas Propane, Reformulated diesel/gasoline)?
 - In what stage of development is each vehicle fuel technology (concept, research, testing, technological improvements, demonstration, commercialized)?
 - What is the availability of original equipment manufactured vehicles or aftermarket conversion kits (sources, quantity, warranty, repairs, resale)?
 - What is the availability of alternative fuel (supply, source, distribution/transmission system, fueling stations)?

5. What is the Economic information needed to compare alternative fueled vehicles?

- What are the life cycle cost of each alternative fueled vehicle?
- What are the fuel costs?
- What are the vehicle costs (new or retrofit)?
- What are the fueling station cost (new or modified)?
- What are the repair/maintenance costs for each alternative?
- What are the costs associated with repair/maintenance facility modification to accommodate each alternative?
- What is the resale/salvage value of each alternative fueled vehicle?
- How are the costs changing (from technological changes, order quantities, etc.)?
- Are there ways in which costs can be shared?

6. What is the Environmental information needed to compare alternative fueled vehicles?

- Which pollutants are critical factors in air quality problems in your region? (non-reactive hydrocarbons, nitrogen oxides, carbon monoxide, nitrogen oxide, non-soluble particulate, carcinogen, green house gases)?
- What are the emission levels in vehicle operation for each alternate fuel for your crucial air quality pollutants?
- How can you ensure the accuracy of the emission results (FTP procedure)?

7. What operational and maintenance information is needed to compare alternative fueled vehicles?

- What is the vehicle performance (range, weight of tanks, acceleration, driveability, payload, cold start, downtime for fueling or repair/parts, reliability) on each alternative fuel?
- what is the impact on vehicle maintenance and repair operations (training/certification requirements, parts availability, frequency of maintenance, time of completion, special tools required) for each alternative fuel?
- What are the impacts of refueling operations (duration, frequency, special handling, locations, capacity) for each alternative fuel?
- What are the health and safety issues for alternative fuel vehicle type (flammability, containment, extinguishment, risk assessment toxicity, cleanup requirements, storage constraints)?

8. What infrastructure information is required to compare alternatively fueled vehicles?

- What and where is the source of each alternative vehicle fuel? What is it's supply dependability?
- What capacity is available in your region for each alternative fuel source? What is the cost and time required for additional source capacity?
- What distribution/transmission capacity is available in your region for each fuel source? What is the cost and time for additional distribution capacity.
- What fueling capabilities exist in your region for each alternate fuel type? What is the cost and time required for additional fueling facilities?
- What modifications are necessary for existing repair and maintenance facilities for each fuel type, and at what cost?
- Are there vehicle storage requirements for each alternative fuel type?

9. What is the current and prospective market in your region for each alternative fueled vehicle type?

- Who are the groups providing each type of fuel, vehicles, warranties, maintenance and parts in your region?
- What local, state or federal regulations affect the use of each alternative fueled vehicle in your region (safety, fire, environmental, developmental)?
- What are the competing fuels (and Interest groups) in your region, and on what basis are they primarily competing?
- Who are other potential partners that may face the same constraints or opportunities regarding alternative fueled vehicle choices that you have to make?

APPENDIX B
EMISSION RESULTS

The following pages provide the detailed Federal Test Procedure emission test results for the vehicles and associated aftermarket CNG conversion kits (or OEM CNG vehicles) which were conducted during this project. For additional detailed information on the emissions testing procedures and issues as well as more detailed emission results, see the following documents:

Fritz, Steven G. and Egbuonu, Ralph I., Emissions from Heavy Duty Trucks Converted to CNG, ASME Paper #92-ICE-10, presented January 26-30, 1992, at Houston, Texas.

Fritz, Steven G. and Egbuonu, Ralph I., Emissions from Heavy Duty Trucks Converted to Compressed Natural Gas, SAE Paper presented November 1-4, 1993, at Detroit, Michigan.

Fritz, Steven G., Emissions from Heavy Duty Trucks Converted to Compressed Natural Gas, Phase I Final Report, Southwest Research Institute, July, 1991.

Fritz, Steven G., Emissions from Heavy duty Trucks Converted to Compressed Natural Gas, Phase II Final Report, Southwest Research Institute, March, 1993.

Hitchcock, David, CNG Fueled Vehicle Comparison Program, Environmental Liaison Report, Houston Advanced Research Center, December, 1992.

Morandi, Maria T. and Stock, Thomas H., City of Houston Alternative Fuel Comparison Project Pre- and Post-Conversion Exhaust Emission Comparison, Interim Report, School of Public Health, University of Texas Health Science Center at Houston, August 26, 1991.

Morandi, Maria T. and Stock, Thomas H., Performance Evaluation of the Impco and Stewart and Stevenson CNG Conversion Kits, Second Interim Report, May 15, 1992 and supplementary letter July 7, 1992.

Morandi, Maria T. and Stock, Thomas H., Performance Evaluation of the Second Testing of the Impco and Stewart and Stevenson CNG Conversion Kits, Final Interim Report, December 23, 1992.

EMISSIONS and FUEL ECONOMY

1987 CHEVY CUSTOM DELUXE

VEHICLE # 173173

	THC	NMHC	CO	NOx	MPG
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	
BASELINE GASOLINE	0.346	N/A	4.73	0.441	11.4
CNG LANDI-RENZO	3.486	0.818	21.523	1.243	12.2

EMISSIONS and FUEL ECONOMY

1987 CHEVY CUSTOM DELUXE

VEHICLE # 172955

	THC	NMHC	CO	NOx	MPG
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	
BASELINE GASOLINE	4.06	N/A	5.157	0.495	11.3
CNG LANDI-RENZO TEST #1 (01/11/91)	13.937	2.531	9.789	0.707	13.4
CNG LANDI-RENZO TEST #2 (03/05/91)	13.091	2.936	11.298	0.770	13.4

EMISSIONS and FUEL ECONOMY

1990 CHEVY CHEYENNE 350 cc

VEHICLE # 185384

	THC	NMHC	CO	NOx	MPG
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	
BASELINE GASOLINE	2.169	0.347	5.423	1.299	12.0
CNG GFI TEST DATE (08/25/92)	3.703	0.411	4.026	1.18	13.6

EMISSIONS and FUEL ECONOMY

1991 DODGE RAM 250

VEHICLE # 362911

	THC	NMHC	CO	NOx	MPG
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	
BASELINE GASOLINE	0.434	N/A	3.316	1.337	16.1
CNG IMPCO TEST #1 (02/07/92)	2.882	0.501	0.276	3.821	18.7
TEST #2 (08/25/92)	1.486	0.316	2.917	1.356	15.9
SHELL LAB TEST (08/14/92)	1.605	0.1483	4.616	1.773	N/A

EMISSIONS DATA COMPARISONS

ACTUAL VS STANDARDS
1992 GMC LIGHT DUTY TRUCK
VEHICLE # 555898

	THC	NMHC	CO	NOx	MPG
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	
1994 FEDERAL STANDARD	N/A	0.32	4.4	0.7	N/A
LOW EMISSION STANDARD	N/A	0.10	4.4	0.4	N/A
ULTRA LOW EMISSION STANDARD	N/A	0.050	4.4	0.4	N/A
CARB CERTIFIED RESULTS		0.14	3.8	0.2	
HOUSTON FTP RESULTS TEST DATE (11/05/92)		0.273	2.186	0.056	17.2

**Emissions and Fuel Economy Summary for City of Houston
1988 Model Year Ford F700 Truck CNG05**

	THC	NMHC	CO	NO _x	Fuel ^{b,c} Economy
	g/mi	g/mi	g/mi	g/mi	(mi/gal)
Baseline, Gasoline-Only					
Cold HDCC	17.0	16.1	78.6	9.9	4.4
Hot HDCC 1	6.0	6.0	34.9	10.2	5.1
Hot HDCC 2	8.7	8.6	37.0	12.1	5.3
Composite ^a	8.7	8.6	42.1	11.0	5.1
Conversion CNG Conversion					
Cold HDCC	15.3	3.8	29.4	17.8	5.2
Hot HDCC 1	12.8	3.3	4.5	18.4	6.0
Hot HDCC 2	19.2	4.5	4.6	18.1	5.9
Composite ^a	15.9	3.9	8.1	18.2	5.8
IMPCO CNG Conversion					
Cold HDCC	4.0	1.1	36.6	17.8	5.1
Hot HDCC 1	3.5	1.0	25.4	18.9	5.6
Hot HDCC 2	11.9	5.7	40.9	19.5	5.4
Hot HDCC 3	10.4	4.7	39.5	21.0	5.5
Composite ^a	7.9	3.4	35.5	19.5	5.4
Note: a - Composite computed using 1/7 (Cold HDCC) + 6/7 (Hot Start Average) b - MPG-equivalent computed using energy content of gasoline = 114,000 BTU/gallon c - Fuel consumption computed using carbon balance					

**Emissions and Fuel Economy Summary for City of Houston
1988 Model Year Ford F700 Truck CNG06**

	THC	NMHC	CO	NO _x	Fuel ^{b,c} Economy
	g/mi	g/mi	g/mi	g/mi	(mi/gal)
Baseline, Gasoline-Only					
Cold HDCC ^d	16.7	15.7	91.7	17.4	4.7
Hot HDCC 1 ^d	3.5	3.4	44.8	16.6	5.6
Hot HDCC 2 ^d	3.6	3.5	42.4	18.5	5.7
Composite ^{a,d}	6.2	6.0	50.5	17.6	5.5
Conversion CNG Conversion					
Cold HDCC	10.1	9.7	48.5	15.4	4.7
Hot HDCC 1	5.5	0.9	21.7	17.8	5.4
Hot HDCC 2	7.4	2.1	18.4	19.2	5.4
Composite ^a	7.0	2.7	24.1	18.0	5.3
Note: a - Composite computed using 1/7 (Cold HDCC) + 6/7 (Hot Start Average) b - MPG-equivalent computed using energy content of gasoline = 114,000 BTU/gallon c - Fuel consumption computed using carbon balance d - Malfunctioning ERG valve					

**Emissions and Fuel Economy Summary for City of Houston
1986 Model Year GMC Truck CNG07**

	THC	NMHC	CO	NO _x	Total Particulate	Particulate SOF	Fuel ^{b,c} Economy
	(g/ml)	(g/ml)	(g/ml)	(g/ml)	(g/ml)	(g/ml)	(ml/gal)
Baseline Diesel-Only							
Cold HDCC	1.3	1.3	6.8	14.1	1.51	0.21	7.3
Hot HDCC 1	1.0	1.0	5.6	13.4	1.34	0.17	8.1
Hot HDCC 2	1.1	1.1	5.0	13.3	1.31	0.20	8.6
Composite ^a	1.1	1.1	5.5	13.5	1.35	0.19	8.2
Dual-Fuel Testing							
Cold HDCC	48.7	5.2	26.5	11.0	0.74	0.10	5.7
Hot HDCC 1	51.9	7.3	22.6	10.4	0.54	0.09	6.3
Hot HDCC 2	50.9	8.4	23.6	10.6	0.81	0.09	6.2
Composite ^a	51.0	7.5	23.6	10.6	0.68	0.09	6.2
Note: a - Composite computed using $1/7(\text{Cold HDCC}) + 6/7((\text{Hot HDCC 1} + \text{Hot HDCC2})/2)$ b - MPG-equivalent computed using energy content of diesel fuel = 129,000 BTU/gallon c - Fuel consumption computed using carbon balance							

**Emissions and Fuel Economy Summary for City of Houston
1986 Model Year GMC Truck CNG08**

	THC	NMHC	CO	NO _x	Total Particulate	Particulate SOF	Fuel ^{b,c} Economy
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mi/gal)
Baseline Diesel-Only							
Cold HDCC	1.3	1.3	7.7	16.2	1.82	0.45	6.9
Hot HDCC 1	1.2	1.2	6.1	15.2	1.51	0.28	7.7
Hot HDCC 2	1.3	1.3	5.7	15.1	1.54	0.30	7.8
Composite ^a	1.2	1.2	6.1	15.3	1.57	0.31	7.6
Dual-Fuel Testing							
Cold HDCC	35.2	10.4	20.8	10.4	1.05	0.41	5.9
Hot HDCC 1	34.3	10.4	17.2	11.2	0.93	0.34	6.2
Hot HDCC 2	33.3	10.1	16.5	11.1	0.87	0.36	5.2
Composite ^a	34.0	10.3	17.4	11.1	0.92	0.36	5.7
Note: a - Composite computed using $1/7(\text{Cold HDCC}) + 6/7((\text{Hot HDCC 1} + \text{Hot HDCC2})/2)$ b - MPG-equivalent computed using energy content of diesel fuel = 129,000 BTU/gallon c - Fuel consumption computed using carbon balance							

**Emissions and Fuel Economy Summary for City of Houston
1983 Model Year GMC Brigadier Truck 2285**

	THC	NMHC	CO	NO _x	Total Particulate	Particulate SOF	Fuel ^{b,c} Economy
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mi/gal)
Baseline Diesel-Only							
Cold HDCC	2.8	2.8	8.7	20.5	1.08	0.35	4.5
Hot HDCC 1	2.4	2.4	5.6	18.5	1.05	0.45	4.8
Hot HDCC 2	2.5	2.5	5.3	18.8	1.00	0.38	4.9
Composite ^a	2.5	2.5	5.9	18.9	1.03	0.41	4.8
Interim Dual-Fuel Testing							
Cold HDCC	25.1	7.6	23.5	23.7	0.63	0.38	3.5
Hot HDCC 1	34.3	10.5	26.6	20.7	0.60	0.40	3.8
Hot HDCC 2	37.1	11.2	30.6	21.6	0.61	0.43	3.8
Composite ^a	34.2	10.4	27.8	21.5	0.61	0.41	3.8
Final Dual-Fuel Testing With Catalyst							
Cold HDCC	21.3	4.4	20.0	20.8	1.25	0.14	3.4
Hot HDCC 1	30.7	8.0	14.3	18.3	0.48	0.15	3.9
Hot HDCC 2	34.4	9.2	15.7	18.0	0.40	0.18	4.0
Composite ^a	30.9	8.0	15.7	18.5	0.56	0.16	3.9
Note: a - Composite computed using $1/7(\text{Cold HDCC}) + 6/7((\text{Hot HDCC 1} + \text{Hot HDCC2})/2)$ b - MPG-equivalent computed using energy content of diesel fuel = 129,000 BTU/gallon c - Fuel consumption computed using carbon balance.							

**Emissions and Fuel Economy Summary for City of Houston
1983 Model Year GMC Brigadier Truck 2288**

	THC	NMHC	CO	NO _x	Total Particulate	Particulate SOF	Fuel ^{b,c} Economy
	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mi/gal)
Baseline Diesel-Only							
Cold HDCC	2.5	2.5	11.7	20.6	1.22	0.57	4.4
Hot HDCC 1	2.1	2.1	7.0	18.3	0.99	0.45	4.7
Hot HDCC 2	2.2	2.2	6.6	21.1	0.94	0.48	4.9
Composite ^a	2.2	2.2	7.5	18.8	1.00	0.48	4.7
Interim Dual-Fuel Testing							
Cold HDCC	20.5	6.1	24.5	21.8	0.79	0.37	3.3
Hot HDCC 1	30.7	8.9	29.2	19.3	0.59	0.37	3.7
Hot HDCC 2	31.2	9.1	30.8	21.5	0.56	0.35	3.8
Composite ^a	29.5	8.6	29.2	20.6	0.61	0.36	3.7
Note: a - Composite computed using $1/7(\text{Cold HDCC}) + 6/7((\text{Hot HDCC 1} + \text{Hot HDCC2})/2)$ b - MPG-equivalent computed using energy content of diesel fuel = 129,000 BTU/gallon c - Fuel consumption computed using carbon balance							

APPENDIX C

DATE: May 29, 1992

TEXAS SPECIFICATION
No. 055-20-01

SPECIFICATION

for

GASOLINE-TO-COMPRESSED NATURAL GAS CONVERSION SYSTEMS

1. **SCOPE** - This specification establishes requirements for the purchase and aftermarket installation of fuel conversion systems to convert vehicular gasoline engines to operate on compressed natural gas. (See Texas Specification No. 055-20-02 for the conversion of vehicular gasoline engines to liquefied petroleum gas.)
2. **APPLICABLE SPECIFICATIONS AND STANDARDS** - Reference to specifications, standards, test methods, and other documents shall be to the issues in effect on the date of the Invitation for Bids. Copies of the referenced documents may be obtained from the issuing organizations at the addresses shown. In the event requirements in this specification are in conflict with rules and/or regulations of the Federal government, the rules and/or regulations of the Texas Air Control Board, or the Railroad Commission of Texas, shall take precedence in that order. The following publications form a part of this specification to the extent specified herein:
 - 2.1. **CALIFORNIA AIR RESOURCES BOARD**, 9528 Telstar Ave., El Monte, California 91731-2900:
 - 2.1.1. **Approved LPG and CNG Conversion Systems**, February 6, 1992 (or current edition).
 - 2.2. **NATIONAL FIRE PROTECTION ASSOCIATION**, 1 Batterymarch Park, Quincy, Massachusetts 02269-9101:
 - 2.2.1. **NFPA 52 - COMPRESSED NATURAL GAS (CNG) VEHICULAR FUEL SYSTEMS**.
 - 2.3. **STATE OF TEXAS** -
 - 2.3.1. **DEPARTMENT OF PUBLIC SAFETY**, P.O. Box 4087, Austin, Texas 78773-0001:
 - 2.3.1.1. **Administrative Rules, Chapter 23 - Vehicle Inspection**.
 - 2.3.2. **GENERAL SERVICES COMMISSION**, Specifications/Inspections Section, P.O. Box 13047, Austin, Texas 78711:
 - 2.3.2.1. **The Cost Effectiveness of Alternative Fuels Using Life Cycle Cost Benefit Analysis**, 2nd. Printing, Sept., 1991.
 - 2.3.2.2. **Specification for Automobiles and Trucks**, No. 070-AT-XX (current edition)
 - 2.3.2.3. **Specification for School Buses**, No. 070-SB-XX (current edition)
 - 2.3.3. **RAILROAD COMMISSION OF TEXAS**, 1701 N. Congress Ave., Austin, Texas 78711:
 - 2.3.3.1. **Regulations for Compressed Natural Gas**.
 - 2.3.4. **TEXAS AIR CONTROL BOARD**, 12124 Park 35 Circle, Austin, Texas 78753:
 - 2.3.4.1. **Control of Air Pollution from Motor Vehicles, Regulation IV.**, Revised, August 30, 1991.

2.3.5. **TEXAS MOTOR VEHICLE COMMISSION**, P.O. Box 2293, Austin, Texas 78768:

2.3.5.1. **Texas Motor Vehicle Code, V.C.S. Art. 4413 (36)**

2.4. **SUPERINTENDENT OF DOCUMENTS**, U.S. Government Printing Office, Washington, D.C. 20402:

2.4.1. **CFR, Title 40, Part 85 - Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines**, Environmental Protection Agency.

3. **CLASSIFICATION** - Gasoline-to-compressed natural gas conversion systems shall be classified by original equipment manufacturer and engine size as follows (in cubic inch displacement unless followed by an "L" suffix indicating displacement in liters). (Ordering entity must specify whether the engine is carbureted or electronic fuel injected):

3.1. **CHEVROLET/GMC -**

3.1.1. 97-I4
3.1.2. 133-I4
3.1.3. 151-I4
3.1.4. 191-V6
3.1.5. 262-V6
3.1.6. 305-V8
3.1.7. 307-V8
3.1.8. 350-V8
3.1.9. 366-V8
3.1.10. 454-V8
3.1.11. 427-V8
3.1.12. Other 4-cylinder
3.1.13. Other 6-cylinder
3.1.14. Other 8-cylinder

3.2. **CHRYSLER:**

3.2.1. 135-I4
3.2.2. 146-I4
3.2.3. 153-I4
3.2.4. 181-V6
3.2.5. 201-V6
3.2.6. 203-V6
3.2.7. 205-V6
3.2.8. 239-V6
3.2.9. 242-I6
3.2.10. 318-V8
3.2.11. 360-V8
3.2.12. Other 4-cylinder
3.2.13. Other 6-cylinder
3.2.14. Other 8-cylinder

3.3. **FORD -**

3.3.1. 1.9L I-4
3.3.2. 2.3L I-4
3.3.3. 3.0L V-6
3.3.4. 3.8L V-6
3.3.5. 4.0L V-6
3.3.6. 4.6L V-8
3.3.7. 4.9L I-6
3.3.8. 5.0L V-8
3.3.9. 5.8L V-8
3.3.10. 7.0L V-8
3.3.11. 7.5L V-8
3.3.12. Other 4-cylinder
3.3.13. Other 6-cylinder
3.3.14. Other 8-cylinder

3.4. **OTHERS -**

3.4.1. **Manufacturer - Engine Sizes**

4. **DEFINITIONS** - Terminology used in this specification is intended to be generic in nature and consistent with meanings that have been defined through general use and/or accepted trade practices. Where variant meanings may exist, the applicable interpretation shall be determined by the Specification Section of the General Services Commission.
- 4.1 **ALTERNATIVE FUELS** - Fuels used to propel vehicular engines including natural gas, electricity, liquefied petroleum gas, methanol and others as defined by the Texas Air Control Board.
 - 4.2 **ASME** - American Society of Mechanical Engineers.
 - 4.3 **BI-FUELED ENGINE** - An engine capable of operating either on a conventional fuel or an alternative fuel, but not simultaneously.
 - 4.4 **CARB** - California Air Resources Board.
 - 4.5 **CNG** - Compressed Natural Gas.
 - 4.6 **COMMISSION** - General Services Commission.
 - 4.7 **CONVERSION FACILITY** - The firm performing the conversion of an engine to operate on an alternative fuel.
 - 4.8 **DEDICATED FUELED ENGINE** - An engine, originally designed to operate on a conventional fuel, which has been converted to use an alternative fuel only; or an engine designed to operate on a single fuel only.
 - 4.9 **DOT** - United States Department of Transportation.
 - 4.10 **DUAL-FUELED ENGINE** - An engine capable of simultaneous operation on a mixture of a conventional fuel and an alternative fuel. (See **FUMIGATED ENGINE**.)
 - 4.11 **EQUIVALENT GALLON** - The amount of natural gas at standard conditions containing the same energy content (114,000 Btus) as one gallon of unleaded gasoline (approximately 114 cubic feet).
 - 4.12 **FUEL CONVERSION SYSTEM** - A device or series of components that, when properly installed and adjusted, will permit an engine, originally designed to operate on a conventional fuel, to operate on natural gas, liquefied petroleum gas, or other alternative fuel, or a mixture of diesel fuel and either CNG, LPG, or other alternative fuel.
 - 4.13 **FUMIGATED ENGINE** - A diesel engine capable of operation on a mixture of diesel and either natural gas or liquefied petroleum gas.
 - 4.14 **GSC** - General Services Commission.
 - 4.15 **LCCBA** - Life Cycle Cost Benefit Analysis.
 - 4.16 **LNG** - Liquefied Natural Gas.
 - 4.17 **LPG** - Liquefied Petroleum Gas, also known as "propane."
 - 4.18 **METHANOL** - A non-petroleum, clear liquid fuel, made primarily from either natural gas, renewable agricultural waste, organic garbage, wood or coal.
 - 4.19 **NATURAL GAS** - A gaseous fuel consisting principally of methane.
 - 4.20 **OEM** - Original Equipment Manufacturer.
 - 4.21 **PIPELINE QUALITY NATURAL GAS** - Natural gas conforming to the specifications as defined in NFPA 52.
 - 4.22 **PROPANE** - A fuel that is composed predominately of hydrocarbons or mixture of hydrocarbons.

- 4.23. **STANDARD CONDITIONS** - A standard pressure and temperature at which compressed natural gas is measured which is a pressure of 14.7 lbs per sq in (psia) and a temperature of 70°F.
- 4.24. **VENDOR** - The business entity having a contract with the user to provide and/or install fuel conversion systems or to provide services for the conversion of engines to alternative fuels. The vendor may or may not be the conversion facility.
- 4.25. **VIN** - Vehicle Identification Number.
5. **REQUIREMENTS** - Products furnished under this specification shall meet or exceed the following requirements:
- 5.1 **GENERAL REQUIREMENTS** -
- 5.1.1. All conversion systems and accessories shall be new, unused, and currently a standard product of an established manufacturer except for such deviations as may be required by this specification. These conversion systems shall not be a rebuilt, repaired, reconditioned, display model, prototype, or a used model.
- 5.1.2. The conversion system shall be the latest model in current production and shall have been tested by a reputable federal test procedure laboratory. Specific design configurations and test results for any acceptable conversion system must be approved by the CARB Aftermarket Parts Section, by any other state air quality regulatory authority, sanctioned by the EPA (for systems applicable to low altitudes), or recognized, in writing, by the EPA as satisfying applicable anti-tampering policies included in Memorandum 1A (1974). Conversion systems and/or components not certified by one of the above means will not be considered. All conversion systems must be maintained in their approved configuration without substitution or modifications. Any system bid must demonstrate compliance with one of the three procedures listed in the second sentence in this paragraph. The burden of proof for system compliance shall rest with the bidder.
- 5.1.3. All applicable components of the fuel conversion system shall meet or exceed applicable rules of the Railroad Commission of Texas in effect on the date of the Invitation for Bids. In addition, all conversion facilities must be licensed according to the rules of the Railroad Commission of Texas and the Texas Motor Vehicle Commission.
- 5.1.4. The conversion system shall be designed to operate on pipeline quality natural gas which has approximately 1,000 Btus per cubic foot and 114,000 Btus per equivalent gallon of unleaded gasoline (see Par. 4.11.).
- 5.1.5. Details not specified herein shall be in accordance with **standard commercial practices** for products of this type.
- 5.1.6. The alternative fuel system fuel tank(s) must be filled to capacity upon delivery to the ordering agency.
- 5.1.7. Safety plaques or decals shall be furnished and shall be affixed at any hazardous area. The plaques or decals shall include necessary warnings and precautions. Permanent plaques are preferred to decals.
- 5.2. **DESIGN REQUIREMENTS** - Each conversion system furnished to this specification shall include, but not be limited to the following. All other parts or components which are required or normally included to provide a complete, working fuel conversion system, shall be furnished.

5.2.1. **Fuel Tank(s)** - Fuel tank(s) shall be manufactured to ASME or DOT standards and shall have combination of separate shut-off/relief valves. They shall have a rated capacity of not less than 3000 psi. They shall be installed in such a manner to allow for easy viewing of serial numbers, where accessible. Exterior surfaces shall be corrosion-resistant or shall be treated to resist corrosion (primed and painted, etc.).

5.2.1.1. **Material** - The vehicular fuel tank(s) shall be any one of the following, unless otherwise specified in the Invitation for Bids:

- 5.2.1.1.1. Steel
- 5.2.1.1.2. Aluminum
- 5.2.1.1.3. Composite Steel
- 5.2.1.1.4. Composite Aluminum

NOTE: A stone shield shall be provided on vehicular fuel tanks furnished with composite material where the tanks are in direct proximity to the road surface.

5.2.1.2. **Size** - CNG fuel tanks shall be provided in sufficient numbers and sizes (capacities) to provide a range (in miles) as specified in the Invitation for Bids. The range shall be determined by operation on 100% CNG, not conventional fuels. The fuel range shall be calculated by multiplying the EPA city fuel economy rating less 5% of the gasoline equivalent volume of the CNG tanks.

5.2.2. **Fuel Cylinder Cages** - Each CNG fuel cylinder installed on any school bus shall be enclosed by a steel cage similar to those used on medium-duty gasoline bus chassis. These cages shall be designed to permit removal of the cylinders for testing purposes.

NOTE: These cages are not required if the CNG cylinder(s) are furnished with internal automatic shut-off valves, or if the tanks are mounted between the frame rails of a full-frame school bus chassis.

5.2.3. **Fuel Filter and Vacuum Fuel Lock** - A fuel filter and vacuum fuel lock (or similar device) shall be provided, as required, to prevent the flow of fuel to the engine when the engine is not in operation but the ignition key is on. The device shall be UL-listed and shall be either vacuum-operated or operated electrically.

5.2.4. **Pressure Regulator** - The pressure regulator shall be adjusted, adjustable, and tested by the factory. The regulator shall be water-heated and shall be capable of accepting pressures up to the working pressure of the vehicle's fuel cylinder(s) and shall deliver CNG at a pressure acceptable for the mixing devices. The regulator shall be furnished with brass fittings and coolant shut-off valves for the engine water coolant inlet and outlet connections.

Pressure regulators shall be designed for each specific engine so that stoichiometric power settings can be maintained.

For electronic fuel injection systems which have sonic metering, the functions of fuel filtration, fuel lock-off, pressure regulation, pressure relief and fuel pressure sensing shall be combined. The regulator, and its components must be listed by EPA, CARB, or other entities, and approved by the Railroad Commission of Texas.

- 5.2.5. **Carburetor/Fuel Injection Systems** - The existing OEM carburetor or injection system may be used. However, the fuel conversion system shall be tested and approved by the CARB and listed on their Approved LPG and CNG Conversion Systems prior to the bid opening date, or otherwise approved and/or recognized by the EPA (see Par. 5.1.2.).
- 5.2.6. **Gas/Air Mixer** - The gas/air mixer shall be specifically designed for efficient mixing CNG and air at the correct flow rate for the engine in which it is installed.
- 5.2.7. **Control Panel** - Unless Option 5.7.8. is specified on the Invitation for Bids, a single pole, 2-position (for fuel injection systems) or 3-position (for carbureted systems) electrical fuel selection switch shall be provided on the instrument panel or in a location convenient to the vehicle operator. This switch shall allow the operator to select gasoline operation or CNG operation and shall be so marked. The operator shall not have to operate any other controls in switching from one fuel to the other.
- 5.2.8. **Fittings and Plumbing Materials** - CNG fuel lines and/or tubing shall be stainless steel and approved by the Railroad Commission of Texas. All hoses and tubing shall be rated for 4000 psi or greater working pressure with burst strength safety factor of 3 to 5 times. Fittings shall be SAE fittings; NPT pipe fittings are not acceptable. Fuel lines shall be secured to the body or frame in a manner to avoid pinching or chafing and shall have fastenings (supports) at not more than 2-foot intervals. Fuel lines shall be protected by placing between the frame rails, if at all possible; otherwise, these lines shall be placed no closer than 8" from any exhaust component and shielded from damage due to rocks, debris, etc. from the road. The CNG fuel line shall not be placed adjacent to an exhaust system component without being shielded. No plumbing or fitting material shall be placed in the interior passenger compartment of a school bus. If this is not possible, the ordering agency shall be advised and shall provide written acceptance of the location. All fuel system valves and plumbing located in the cargo area shall be protected with shields.
- 5.2.9. **Refueling Receptacle** - The vehicle refueling receptacle shall be a quick-disconnect type receptacle requiring no tools to use in refueling. It shall be a Sherex SR 1040, Sherex SR 1020 or other Federally approved standard. The receptacle shall be protected with a dust cap, permanently attached to the vehicle by means of a metal chain or cable. The vehicle refueling probe shall be installed in one of the following locations on the vehicle, unless otherwise specified in the Invitation for Bids:
- 5.2.9.1. Gasoline filler location. (The gasoline filler shall remain operable.)
 - 5.2.9.2. Front Grille.
 - 5.2.9.3. Engine compartment.
- NOTE:** In no case shall the refueling receptacle be mounted in a vehicle crush area. This area is defined as areas within 18" of the vehicle bumper surface, front or rear.
- 5.2.10. **Manual Shut-Off Valve** - A manual, quarter-turn shut-off valve to isolate the fuel cylinder(s) from the rest of the CNG system shall be as required by the Railroad Commission of Texas.
- 5.2.11. **Fuel Pressure Gauge** - A mechanically operated non-electric fuel pressure gauge shall be installed under the hood and at the refueling location except at the gasoline filler location. A second gauge is not required if the refueling location is under the hood. This gauge shall be a dial type with shatter-proof glass providing readings from 0 to 4000 psi maximum.

- 5.2.12. **Fuel Gauge** - The OEM analogue fuel gauge shall be utilized to provide accurate available fuel readings for both gasoline and CNG selectively with the fuel in use. If the instrumentation is digital, a separate fuel gauge for CNG shall be furnished and mounted so that it can be easily observed by the seated driver.
- 5.3. **INSTALLATION AND OPERATION** - The installation of the CNG fuel system and the operation of the vehicle after conversion shall be in accordance with the following:
- 5.3.1. **Installation** - The installed conversion system shall present a neat, well-finished appearance and shall be free of all imperfections and/or defects which might affect appearance, normal life, or serviceability. The systems shall be installed so as not to interfere with normal maintenance tasks such as tune ups, checking of fluid levels, etc. The installed conversion system shall not restrict or prevent normal tune-up activities, such as replacement of spark plugs, distributor caps and rotors, or drive belts nor render inoperative the functions of the air filter air connection, or any component of the emission control system of the vehicle unless approved under EPA guidelines. Fuel tanks mounted in the cargo area of passenger vehicles shall be boxed and covered in upholstery that color-coordinates with the vehicle interior. All electrical wiring shall be insulated and enclosed in a fibrous loom, plastic loom, or flexible conduit for protection from external damage and short circuits. Wiring shall be securely fastened at sufficient intervals to prevent sagging and insure clearance of mechanical parts. Routing of the wiring through the subframe, body, etc., shall be in such a manner so as not to interfere with the normal operation and use or present a safety hazard. A sealed splice-free modular wiring harness is acceptable. Rubber grommets shall be used wherever wires or harness pass through metal. Workmanship shall be comparable to that of the OEM. The systems shall be installed in conformance with the system manufacturer's instructions and recommendations.
- 5.3.2. **Conversion Site** - Unless otherwise specified in the Invitation for Bids, it shall be the responsibility of the vendor to arrange for pick up and delivery of the vehicle(s) which are to be converted, at no expense to the ordering state agency or school district.
- 5.3.2. **Connections** - All hose connectors shall be from the same manufacturer; fittings, etc. from different manufacturers **SHALL NOT BE USED** on the same vehicle. Hose connections shall be tubing fittings. All electrical connections to the vehicle OEM wiring shall be accomplished with brass or copper connectors. **Aluminum connectors are not acceptable.**
- 5.3.3. **Engine Tune-up** - Each conversion system installation shall be made only after the engine has been tuned to the OEM's specifications by the vendor.
- 5.3.4. **Pre-conversion Dynamometer Test** - When so specified in the Invitation for Bids (see Par. 5.7.6.), the conversion system installation shall be made only after the vehicle has been operated on gasoline using a dynamometer to measure the brake horsepower output at the rear or driving wheels and the pollution levels checked and recorded.
- 5.3.5. **Post-conversion Dynamometer Test** - When so specified in the Invitation for Bids (see Par. 5.7.6.), the conversion system shall be checked on a dynamometer. The engine, when operating on CNG, shall be adjusted to provide at least 85% of the power measured in all speed ranges as specified in Par. 5.3.4. The engine shall not lose any power when operated on gasoline. The installing conversion facility will adjust the engine for maximum performance on both gasoline and CNG.

- 5.3.6. **Dynamometer Test Reports** - Copies of all dynamometer tests shall be provided to the owner. This test report shall identify the vehicle(s) by VIN number. If dynamometer testing is specified on the Invitation for Bids, payment will not be made until dynamometer testing documentation is provided.
- 5.3.7. **Engine Operating Characteristics** - The engine, after conversion, shall operate on CNG without hesitation, stalling, power loss of more than 15%, or surging. The OEM's recommended maximum operating temperature, horsepower, engine speed, etc. shall not be compromised or surpassed.
- 5.3.8. **Safety and Emissions** - The engine, after conversion, shall meet all Federal and state safety rules and regulations, all applicable EPA emission standards, Department of Public Safety Vehicle Inspection Rules, and Texas Air Control Board Regulation IV when operated on gasoline. The vendor shall perform a minimum of three emissions tests on each vehicle using a Four-Gas Analyzer. Data shall be taken at idle and at 2,500 RPM, no load. One test shall be performed prior to conversion, with the vehicle operating on gasoline. A second test shall be performed after conversion, with the vehicle operating on CNG. A third test shall be performed after the conversion with the vehicle operating on gasoline. The methods and parameters for all tests shall be identical, with the exception of fuel used. This test will verify that the converted vehicle has been converted in compliance with all applicable emissions requirements. The results of the tests shall be provided to the school district of ordering state agency upon completion of each vehicle conversion. Payment procedure will not be initiated until this documentation is provided.
- 5.3.9. **OEM Engine Speed Governor** - Any OEM engine speed governor shall not be made inoperable during conversion to CNG. It shall remain operable when the vehicle is operating on CNG as well as on gasoline.
- 5.3.10. **OEM Fuel Injection System** - The fuel injection system of gasoline engines, if used, shall be made inoperable by means which will not damage the injectors and associated components, while the engine is operating on CNG and shall not be damaged by short or long term use of CNG.
- 5.3.11. **Radio (2-way) Frequency (RF) Interference** - All electronic conversion components shall be designed to prevent electromagnetic interference with 2-way radio equipment.
- 5.3.12. **Engine Electronics** - All electronics required to properly interface with the original vehicle electronics, and necessary in order to meet vehicle performance and emission objective, shall be included in the conversion.
- 5.3.13. **Installation Time** - The installing dealer shall have a period of time not to exceed 5 working days in which to install, adjust, and test each fuel conversion system.
- 5.4. **WARRANTY** -
- 5.4.1. **Standard Warranty** - All conversion systems shall carry the manufacturer's standard warranty and shall be guaranteed against defects in materials, workmanship, and performance for a minimum of one year.

The warranty shall begin on the date of acceptance of the unit by the school district or state agency. During this warranty period, the vendor shall repair or replace defective components/units at no cost to the State of Texas or the school district.

- 5.4.2. **Warranty Responsibility** - In case of warranty work on an engine converted to use CNG, if there is a question of whether it is the responsibility of the OEM or the vendor, it shall automatically become the vendor's responsibility. If the question is not resolved within one week from the date of notification to the vendor by the owner, the vendor will arrange, with the permission of the owner, for the vehicle to be repaired by a duly licensed carburetion technician, at an OEM or other facility chosen by the owner, at no cost to the owner. The vendor may then negotiate with the OEM if the repair is covered by the OEM warranty or pay for the repairs if it is not, unless it can be determined that the damage to the engine was due to improper operation such as low oil, low water, etc. A copy of the conversion equipment manufacturer's warranty and the vendor's supplemental warranty shall be provided to the state agency or school district at the time of vehicle delivery. Payment for the vehicle(s) cannot be processed until these documents are provided.

When major warranty repairs are required, the state agency or school district will notify a representative of the vendor's Texas dealer by telephone as designated by the bidder. Major repairs are defined as those repairs other than minor adjustments, replacement of hoses, etc. Major warranty repair work means major repair to the engine due to operation of the engine on CNG. All conversion components shall be covered. Diagnosis of the actual repairs required will be the responsibility of the vendor. The vehicle(s) will be made available at the location designated by the owner. The repair work may be performed by the vendor or his authorized representative. At the vendor's option, the unit may be taken by the vendor to a commercial repair facility. The vendor shall be responsible for the cost of the round trip transportation of the vehicle(s).

- 5.4.3. **General Engine Warranty** - The vendor shall warrant converted engines for 6 months or 6,000 miles, whichever occurs LATER against damages due to the operation of the engine on CNG. This warranty shall be equal to or better than the OEM's original warranty on the engine and shall be limited to damages caused by the alternative fuel used.
- 5.4.4. **Personal Injury/Property Damage Liability** - Proof of product liability, as required by the Railroad Commission of Texas, shall be provided with the Invitation for Bids.
- 5.5. **LIST OF REFERENCES** - It is the intent of this specification to provide for installation of fuel conversion systems by licensed, skilled and experienced installers ONLY, who are capable of providing not only safe installations, but conversion systems that perform as required. Before an award will be considered, the apparent low bidder shall supply GSC with a list of at least 5 different entities for which the conversion facility has successfully converted gasoline vehicles to CNG use within the last 3 years. In addition, the bidder shall provide proof of the conversion entity or company being in the CNG fuel conversion business for a period of not less than 6 months. This list shall include the name of the school district, state agency, or business, complete address, name and phone number of a contact person familiar with the installation, and number of vehicles converted for each reference. If two or more of the references indicate unacceptable performance as determined by the Purchasing Division, General Services Commission, the bidder will not be considered for an award.
- 5.6. **IDENTIFICATION OF EQUIPMENT** - The apparent low bidder will be required to furnish, prior to award, a list of the equipment being utilized for the conversion, the brand name, and the name and address of the manufacturer of the equipment.

- 5.7.11. **Extended Warranty** - The conversion system and related components shall be warranted against all defects in material and workmanship for a period of not less than thirty-six months or 50,000 miles, whichever occurs first, and shall cover 100% parts and labor for the converted unit. If the manufacturer's standard warranty exceeds thirty-six months/50,000 miles, the standard warranty shall be in effect.
- 5.7.12. **Other TxDOT (or ordering entity) Warranty Option** - (When ordering this option, the ordering entity shall specify in detail, the warranty required on the Invitation for Bids.)
6. **TESTING** - Testing shall be done by, or at the direction of, the General Services Commission and/or the receiving school district or state agency. Tests shall be performed on products from shipments to ordering agencies. In the event products tested fail to meet or exceed all conditions and requirements of this specification, the cost of the samples used and the cost of testing shall be borne by the supplier.
7. **SAMPLES** - Unless otherwise specified in the Invitation for Bids, no prepurchase samples shall be required. Samples tested shall be obtained from products supplied on regular orders.
8. **INSPECTION** - Products furnished under this specification shall be inspected by, or at the direction of the General Services Commission and/or the ordering school district or state agency (as applicable) either at the destination or place of manufacture.
9. **AVAILABILITY OF SERVICE** - Factory-authorized service shall be available within the State of Texas:
 - 9.1. **SERVICE** - When so specified in the Invitation for Bids, the bidder shall submit a current list of companies or individuals, and their addresses, who can perform service on the products furnished.
 - 9.2. **PARTS** - An adequate supply of repair parts shall be carried in stock within the State of Texas for the expected life of all products furnished under this specification.
10. **INSTRUCTION BOOKS/MANUALS** - The vendor shall furnish one copy (unless otherwise specified in the Invitation for Bids) of any required operating/maintenance/troubleshooting instructions for each conversion system installed or delivered. The instructions shall accompany the system when installed or shipped.
11. **PACKING/PACKAGING** - Packaging for shipment shall be in accordance with the manufacturer's standard practice and in a manner readily accepted by common carriers engaged in interstate commerce. Within the shipping carton, units shall be packed in a manner designed to minimize damage during shipment due to rough or improper handling.
12. **MARKING/LABELING** -
 - 12.1. **MARKING** - Each shipping container shall be clearly marked with:
 - 12.1.1. Name of contents,
 - 12.1.2. Quantity,
 - 12.1.3. Name and address of the manufacturer.
 The container or shipping documents shall include:
 - 12.1.4. Order number or contract number,
 - 12.1.5. Name and address of ordering agency,
 - 12.1.6. Agency requisition number.

- 12.2. **LABELING** - Labels shall be installed at appropriate locations on and in the converted vehicle in conformance with the rules and regulations of the Railroad Commission of Texas to indicate the vehicle is equipped for operation on CNG and for required warnings.
13. **BID LITERATURE** - All bids shall be accompanied by a complete and illustrated description of the products being offered.
14. **COMPLIANCE** - In order for consideration to be given to the bid on an item under this specification, the bidder must comply with the following conditions:
- 14.1. **EQUIPMENT IDENTIFICATION** - The make, model number, name of manufacturer, brand or trade name, etc., as applicable, of the item which the vendor proposes to furnish must be stated as part of the bid.
- NOTE: BIDS ON ANY EQUIPMENT NOT LISTED ON THE CALIFORNIA AIR RESOURCES BOARD'S LATEST LIST OF APPROVED CONVERSION SYSTEMS, OR OTHER RECOGNIZED ENTITIES AND NOT APPROVED BY THE RAILROAD COMMISSION OF TEXAS WILL NOT BE CONSIDERED.**
- 14.2. **EXCEPTIONS** - Notwithstanding the above, any exception taken by the bidder to the requirements and conditions of this specification must be stated and described in detail as a part of the bid. If no exceptions or deviations are identified in this manner, the items must be furnished exactly as described herein.
- 14.3. **PROOF** - The bidder shall bear the burden of proof of compliance with this specification.
15. **PRODUCT INFORMATION** - When considering the selection of vehicles to convert to an alternative fuel, the school district or state agency may want to consider the following.
- 15.1. **SELECTION OF VEHICLES** - As a general rule, newer vehicles should be considered first for conversion, followed by those that are somewhat older but still in good condition. Obviously, those vehicles that are near the end of their useful life and must soon be replaced, should not be candidates for conversion. Any vehicle that has several years of useful life that will be kept in the fleet, might be considered for conversion. School districts and state agencies may want to use LCCBA to ascertain if it is cost effective to convert an older vehicle to an alternative fuel. (See guidelines in the GSC's workbook (See Par. 2.3.2.1.)
- 15.2. **SELECTION OF ALTERNATIVE FUELS** - Each of the three alternative fuels have advantages and disadvantages. The one selected should be the one that is the most cost effective meeting the needs of the particular fleet under consideration.
- 15.2.1. **Safety** - The use of CNG and LPG as vehicle fuels has had an outstanding safety record and these alternative fuels are probably safer than gasoline. LPG and CNG fuel tanks normally will not rupture or leak fuel resulting in fires even in accidents in which the vehicle is totally demolished. When conversion systems are properly installed, and the vehicle is operated and maintained as recommended, this should result in a vehicle that will have a safety record at least as good as a comparable operated and maintained gasoline vehicle. However, all recommended safety precautions and suggested operating procedures should be followed meticulously.

Both CNG and LPG have very narrow limits of flammability and much higher ignition temperatures than gasoline.

15.2.2. **Selection of Vehicular Fuel Tanks** - There are basically four different types of fuel tanks approved for installation on vehicles using CNG and one for LPG (see Par. 5.2.1.1.). Aluminum tanks are much lighter in weight than steel tanks and the labor in removing and reinstalling aluminum tanks for testing is much less. Composite aluminum and steel tanks have a weight advantage over aluminum and steel tanks, respectively. Steel tanks must be removed from the vehicle and tested **every 5 years**; aluminum and all composite metal tanks must be removed from the vehicle and tested **every 3 years**. LPG tanks and tanks manufactured to ASME specifications do not have to re-tested.

16. **ORDERING DATA** - When ordering products conforming to this specification, the requisitioning school district or state agency shall specify the following:
- 16.1. **The Number of this Specification** (055-20-01).
 - 16.2. **Engine Type and Size** (Indicate whether carbureted or electronic fuel injected type, see Par. 3.).
 - 16.3. **Fuel Tank Material** (see Par. 5.2.1.1.)
 - 16.4. **Fuel Tank Size** (see Par. 5.2.1.2.)
 - 16.5. **Fuel Gauge type** (digital or analogue, see Par. 5.2.12.)
 - 16.6. **Refueling Receptacle Location** (see Par. 5.2.9.)
 - 16.7. **Pre-conversion Dynamometer Test**, if required (see Paragraphs 5.3.4. and 5.3.6.)
 - 16.8. **Post-conversion Dynamometer Test**, if required (see Paragraphs 5.3.5. and 5.3.6.)
 - 16.9. **Options** (see Par. 5.7.)
 - 16.10. **Quantity of Vehicles to be converted or Number of Systems ordered** of each engine type and size.
17. **AVAILABILITY OF SPECIFICATIONS** - Copies of this specification may be obtained from:

SPECIFICATION SECTION
General Services Commission
P.O. Box 13047
Austin, TX 78711-3047
Phone (512) 463-3411

REPORT AND INFORMATION SOURCES

Additional copies of this report, "Compressed Natural Gas Fueled Vehicles: The Houston Experience," are available from:

Publications and Distribution
Public Technology, Inc.
1301 Pennsylvania Avenue, NW
Washington, D.C. 20004

For additional information concerning the Houston CNG project, please contact:

Dewayne Huckabay
City of Houston
Office of Energy Management
Department of Finance and Administration
P.O. Box 1562
Houston, Texas 77251
(713) 658-4517

DG/90-320
10/93-150

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
90-331	Hydraulic Waste Energy Recovery: A Technical Report	15.00
90-318	A Regulatory Framework for Alternative Fuels and Transportation Management Services	15.00
90-316	Alternative Vehicle Fuels: A Demonstration Project	15.00
90-314	Energy Efficiency in Public Housing	15.00
89-330	Analysis of Programmatic Fleet Conversion to Ethanol Blends	15.00
89-325	An Alternative Fuels Evaluation System for Fleet Vehicles	15.00
89-323	Dual Fuel Conversion Demonstration and Technology Transfer Project	10.00
89-321	Summary of Low and Moderate Income Residential Energy Conservation Programs	15.00
89-315	A Case Study in the Pursuit of Urban Energy Efficiency	15.00
89-314	Communicating with the Public About Environmental Health Risks: A Case Study	13.00
89-313	Evaluation and Comparison of Selected Household Hazardous Waste Collection Facilities	15.00
89-311	Yard Waste Recycling Study: A Pilot Study	15.00
89-310	Sludge Storage Lagoon Biogas Recovery and Use, Volume 1	15.00
89-307	Proceeding: 1989 Electric Utility Franchise Conference	20.00
89-306	Reducing Electricity Demand Through Energy-Related Efficient Construction	15.00
89-304	Modernization of Lighting in Municipal Auditoriums	15.00
89-303	Wastewater Treatment Process Energy Optimization	13.00
89-301	Implementation of Alternative Technologies through the Assessment of Energy Markets	14.00
88-322	Marketing Energy Efficiency Programs to Commercial and Industrial Firms: Lighting Incentives and	15.00
88-321	Urban Energy Management Today: Ten Year Compendium of UCETF Programs	10.00
88-319	Integrating Energy Efficiency Into Municipal Purchasing Decisions: Computerizing Procurement	15.00
88-318	Household Hazardous Waste: Implementation of a Permanent Collection Facility	20.00
88-317	Hazardous Waste as an Energy Manager's Issue	15.00
88-316	Household Hazardous Waste Management Planning	15.00
88-312	Summary of Small Business Energy Conservation Programs	15.00
88-310	The Earth-Coupled Heat Pump: Utilizing Innovative Technology in Single Family Rehabilitation	15.00
88-309	Energy Planning for Economic Development	18.00
88-308	Conversion of Resource Recovery Steam to Hot and Chilled Water Systems	10.00
88-306	HVAC Equipment Replacement for Best Size and Efficiency, Transfer Report	15.00
88-305	Cogeneration and Cooling in Small Scale Applications	15.00
88-304	Energy Master Planning: Innovative Design and Energy Analysis Services for New Commercial	22.00
88-303	Energy Efficient Building Design: Guidelines for Local Government	15.00
88-302	Direct Digital Control of Air Washer Cooling System	15.00
88-301	Feasibility Study of Transportation Management Strategies in the Poplar Corridor, Memphis, Tennessee	18.00
87-327	Energy Efficient Urban Cooling Technologies: 1st National Conf.	20.00
87-324	Memphis Area Rideshare	15.00
87-317	Joint City Government/Utility Partnerships to Reduce Business Costs	15.00
87-314	The Impact of Budgetary Incentives on Energy Management	15.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
87-313	Computer Assisted Control for Municipal Water Systems, Phase II	20.00
87-312	Economic Development Through Energy Technology Transfer	15.00
87-311	Electric Utility Franchise Guide	20.00
87-310	Hidden Link: The Energy and Economic Development, Phase II	15.00
87-307	Municipal Underground Storage Tanks: An Energy Manager's Guide	18.00
87-306	Integrating Energy Efficiency into Mun. Purchasing Decisions	20.00
87-305	Energy Enhancement in New Residential Construction	40.00
87-302	Thermal Energy Storage: Application Guide for Local Governments	20.00
87-301	HVAC Equipment Replacement for Best Size & Efficiency	20.00
86-315	Balancing Single Pipe Steam Heating Systems	20.00
86-314	Inhibition of Respiration in Activated Sludge by High Carbon Dioxide Concentration	7.50
86-313	Water Supply System Energy Conservation Through Computer Control	18.00
86-312	Energy Cost Reduction Through Wastewater Flow Equalization	20.00
86-311	High Efficiency Gas Furnace Modification in Low Income Housing	15.00
86-310	Hidden Link: Energy and Economic Development, Phase I	15.00
86-307	Disposal Techniques with Energy Recovery for Scrapped Vehicle Tires	20.00
86-306	District Heating Marketing: Analysis of a Twelve City Survey	20.00
86-305	Technology Transfer for Residential Energy Programs in New Construction and Existing Housing	15.00
86-304	Technology Transfer for Residential Energy Efficiency	15.00
86-302	Neighborhood Energy Efficiency & Reinvestment	15.00
86-301	On-Site Municipal Fuel Cell Power Plan: Feasibility and Application Guide	15.00
85-326	Resource Recovery for Urban Yard Waste	18.00
85-323	Energy Monitoring and Controlling in Municipal Facilities	10.00
85-320	Transportation Management for Business Relocation	15.00
85-319	District Heating in Denmark	10.00
85-318	Computer-Assisted Control for Municipal Water Systems, Phase I	18.00
85-317	Financing Energy Efficient Housing as a Community Economic Development Tool	15.00
85-316	Modular District Heating Planning as a Development Tool	15.00
85-314	Alternative Techniques for Dev. of Energy Efficient Residences	15.00
85-312	Shared Savings and Low Income Homeowners	18.00
85-311	Measures and Investment Options for Community Energy Conservation	18.00
85-310	Planning for Energy Efficiency in New Commercial Buildings	15.00
85-308	Residential Space Heating with Wood	15.00
85-307	Thermal Storage Strategies for Energy Cost Reduction	18.00
84-325	Shared Savings in the Residential Market	
84-324	Methanol Use in Vehicle Fleet Operations: Barriers	20.00
84-322	Energy Management and Technology for Urban Governments	15.00
84-321	Hydrate Process for Waste Water Treatment Plant Sludge Dewatering	15.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
84-320	Development of Computerized Inventory and Maintenance System for Municipal Street Lights	15.00
84-315	Facilities Energy Monitoring System	15.00
84-314	Application of Mini-Van Technology to Vanpool Services	18.00
84-312	Implementation Methods for an Integrated Energy System	10.00
84-311	Feasibility of Water-Based District Heating and Cooling	15.00
84-310	Budgetary Incentives for Municipal Energy Management	22.00
84-309	Central Energy Systems Applications to Economic Development	20.00
84-308	On-Site Cogeneration for Office Buildings	15.00
84-306	Analysis of Municipal Bus Operations for the Advancement of Fuel Cell Technology	15.00
84-305	Computer Based Maintenance	15.00
84-304	Innovative Finance Plans for Privately Owned Waste/Vol. 2	15.00
84-303	Innovative Finance Plans for Privately Owned Waste/ Vol. 1	15.00
84-301	Coordinating Preventive Maintenance with Energy Management	15.00
83-319	The Rehabilitation and Retrofit of Older Houses to Superinsulated Standards	15.00
83-318	Developing Sources and Techniques for Alternative Financing of Energy Conservation	20.00
83-316	Hydrate Process for Dewatering Sewage Sludge	10.00
83-315	Financial Planning for District Heating: Brooklyn Navy Yard	15.00
83-314	Memphis Area Rideshare On-Line Information System	18.00
83-313	Renovation Opportunities for Steam District Heating Systems	18.00
83-312	Initial Assessment of District Heating and Cooling	20.00
83-311	Energy Conservation Through Computerized Automation	18.00
83-309	Development of an Energy Park: Issues and Implementation Options	15.00
83-308	Alternative Uses for Digester Methane Gas	25.00
83-307	Innovative Financing and Incentive Package to Reduce Energy	15.00
83-305	Multi-Jurisdictional Planning for District Heating and Cooling	10.00
83-303	Improving Energy Management and Accountability in Municipal Operations	15.00
82-320	Utilization of Felled City Trees as Supplemental Boiler Fuel	7.50
82-319	Methanol Use in Vehicle Fleet Operations: Comparisons	15.00
82-317	Microcomputer Tools for Trans. and Residential Energy Conservation	20.00
82-316	Reduction of Impediments to Alternative Energy Use	20.00
82-315	Reducing Regulatory and Financial Impediments to Energy Conservation	20.00
82-314	Integrating Energy Management with Economic Development	20.00
82-313	Energy Conservation and Economic Development	10.00
82-310	Municipal Technologies	20.00
82-307	Strategies to Improve Community Energy Use Practices	10.00
82-306	Energy Conservation In Water Treatment	
82-305	Development of an Energy Action Plan: Participating Approach	15.00
82-303	Energy Economic Development	20.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
82-302	Public Housing Energy Efficiency Through Private Financing	10.00
82-300	Developing an Energy Management Tracking System	
81-328	Matching End Use Energy Needs to Source Possibilities	20.00
81-327	Development of a Hydrogen-Fueled Mass Transit Vehicle s	15.00
81-326	Operational and Maintenance Guidelines for Reducing Energy Consumption	
81-324	Energy Management for Small Business	10.00
81-320	Energy Data Gathering, Analysis, and Review System	20.00
81-318	Fuel Management and Planning System for Local Government	25.00
81-316	Production of Ethanol from Cellulosic Fraction	
81-313	Metro-Dade County Comprehensive Energy Emergency Plan	
81-311	Developing Energy Emergency Preparedness	15.00
81-310	Simplified Methodology for Community Energy Management	20.00
81-309	Energy Management: The Public Sector	15.00
81-307	Municipal Technical Assistance-Energy Monitoring	6.00
81-306	New Technology Demonstration	10.00
81-305	Technology Transfer: Unit Report from the Energy Task Force	15.00
81-304	Development of Local Energy Management Preparedness	10.00
81-303	Municipal Energy Management	10.00
80-314	Methodology for Energy Impact Analysis of Urban Development Projects	15.00
80-313	Evaluation of Landfill Gas as an Energy Source	15.00
80-309	Decision Process for the Retrofit of Municipal Buildings	20.00
80-308	Primary Urban Energy Management Planning Methodology	7.50
80-306	Local Government Use of Thermography for Energy	15.00
79-300	Planning for and Purchasing Computer Technology	6.50

END

DATE

FILMED

2/24/94