PROGRESS REPORT TO THE DEPARTMENT OF ENERGY

Title of Project: Computer Aided Surface Representation

Grant Number: DE-FG02-87ER25041

Duration of Grant: June 1, 1988 - May 31, 1991

Period Covered by Progress Report: June 1, 1989 - May 31, 1990

Principal Investigator: Dr. Robert E. Barnhill
Department of Computer Science
Arizona State University
Tempe, Arizona 85287

Date: 19 February 1990

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Executive Summary	1
Introduction	1
Organization of this report	1
Research areas	1
Research events	2
Faculty summaries	4
R. E. Barnhill	5
G. Farin	10
T. A. Foley	16
G. M. Nielson	23
Research assistant summaries	32
B. K. Bloomquist	33
T. M. Frost	36
B. Hamann	42
D. C. Hansford	49
D. A. Lane	52
S. H. Watson	58
Research papers and theses supported by DoE grant	61
Research plans for the coming year	63
Appendix: Graduate students supported by DoE grant, 1989-90, and their topics ...	64
Enclosures: SIAM Geometric Design conference program	
Copies of papers and theses supported by DoE grant	

EXECUTIVE SUMMARY

Introduction

The central research problem of this project is the effective representation, computation, and display of surfaces interpolating to information in three or more dimensions. If the given information is located on another surface, then the problem is to construct a "surface defined on a surface". Sometimes properties of an already defined surface are desired, which is "geometry processing". Visualization of multivariate surfaces is possible by means of contouring higher dimensional surfaces. These problems and more are discussed below.

The broad sweep from constructive mathematics through computational algorithms to computer graphics illustrations is utilized in this research. The breadth and depth of this research activity makes this research project unique.

Organization of this Progress Report

An Executive Summary is followed by summaries by the four faculty members and by the research assistants supported by the DoE grant. (The amounts and times of support vary widely, of course; this is reflected in the reports.) Although this procedure of reporting introduces some redundancy, it has the virtues of demonstrating the wide scope of the project, in the exact words of the researchers. Including the research assistants' reports verbatim also indicates the training of new scientists in this subject. Selected applications of this research are included in the individual reports; these applications include combustion modelling, water pollution modelling and geographical information system research.

Research areas

Research progress was made in several areas, with the most significant areas being summarized below. Additional detail is given in the faculty and research assistant summaries which follow.

1. Surfaces Defined on Surfaces

New suites of methods have been developed by R. E. Barnhill and H. S. Ou and by T. A. Foley, D. A. Lane and G. M. Nielson. Comparisons of the methods are currently being made by Barnhill, Foley, and Lane.

2. Multivariate Visualization

A variety of methods for "seeing" higher dimensional interpolants have been developed, including Foley and Lane's "image interpolation" and Barnhill and Bloomquist's trivariate contouring.

3. Geometry Processing

Earlier research on this project on curvature analysis, surface-surface intersection and numerical integration has been consolidated and used for current topics: Barnhill and Kersey have constructed a robust surface-surface intersection algorithm combining the best features of earlier algorithms. In turn, this work is being applied to the offset surface problem by Barnhill and Frost.

Research events

Several events important for this research project occurred during the past year. Some of the most important are listed below.

1. SIAM Geometric Design conference

In November 1989 we hosted the Society for Industrial and Applied Mathematics conference on Geometric Design in Tempe, Arizona. We have marked the enclosed Final Program on the talks supported by the DoE grant. There are also higher level significances to this meeting: The Geometric Design conference was a very significant meeting, seeking to further establish this scientific discipline. This DoE project, being fundamental to the CAGD Group's presence at Arizona State University, was instrumental in the conference's existence. Our Summary of the conference is enclosed in the Appendix. The choice of emphases in the conference was influenced by this DoE project, for example, the emphasis on computer graphics and CAGD. In addition, there were several sessions on multidimensional problems, as well as many sessions on surfaces. During the conference we gave tours of the CAGD Lab to many attendees, evoking interest in the topics of the DoE project. Also during the conference, we announced the formation of a SIAM Geometric Design Special Interest Group, with Barnhill as Chair and Foley as Secretary. Finally, there will be publications of refereed selections from the conference, edited by Farin, Barnhill, and others.

2. Silicon Graphics equipment donation

Silicon Graphics has just donated fifteen IRIS workstations for instructional use in CAGD and computer graphics. This donation makes these instructional labs among the finest in the country. SGI's reason for the donation is their desire to collaborate with the CAGD Group here. The reported value of this donation is $15 \times \$50,000 = \$750,000$. The importance for this project is that students in classes will be trained on nearly current research equipment and thus will be more effective research assistants.

3. Ardent contest

Foley, Lane, and Nielson were co-winners in the Ardent contest with their multivariate visualization entry illustrating their surface on surface method. The corresponding videotape was shown at SIGGRAPH, a well attended conference. The prize was a sixteen megabyte memory board for our Ardent Titan.

4. CAGD prominence at Arizona State University

Many local, national, and international visitors tour the CAGD Lab and see demonstrations of DoE funded research on the computer graphics equipment. The CAGD Lab is included on many of Arizona State University's high level tours. Computer Aided Geometric Design is the most prominent research area in the Computer Science Department. Moreover, Computer Science is one of three research areas most emphasized in the College of Engineering Strategic Plan.

5. Research presentations

Faculty presentations at the SIAM Geometric Design meeting included Farin as an invited speaker, Foley and Barnhill led minisymposia, and Foley and Nielson led the opening, tutorial day on computer graphics. Several research assistants also made presentations at this meeting.

All four faculty participated in the "Surfaces in CAGD" meeting at the Mathematics Institute, Oberwolfach, F. R. Germany in April, 1989. The refereed proceedings will appear in the CAGD journal, published by North Holland. Farin, Foley, and Nielson presented a six hour tutorial on CAGD at SIGGRAPH '89. Farin and Foley presented talks at the RPI "Discrete Curves and Surfaces" conference in November, 1989. Barnhill was a

reporter on the subject of Geometric Design for the National Science Foundation Computer Integrated Engineering Program at the NSF Grantees' Conference in January, 1990. Additional presentations by the faculty and graduate students are listed in their individual summaries.

6. Research computing developments

During the past year we have utilized our Ardent Titan computer, which we upgraded to three processors. We also upgraded our Silicon Graphics IRIS workstation to two processors. We are currently applying parallelization, as well as vectorization, to some of our multidimensional surface codes and are obtaining significant efficiencies. (See David Lane's report.)

In order to fully utilize this computing equipment we have collaborated with Ardent and with Silicon Graphics, including training courses.

PROGRESS REPORT TO THE DEPARTMENT OF ENERGY

Faculty summaries

DoE Progress Report for 1989

Robert E. Barnhill

My principal research areas during the past year have been Surfaces defined on Surfaces and Geometry Processing, with additional research in Contours of Trivariate Surfaces and Optimal Triangulations. These topics have the dual appeal of DoE applicability and intrinsic scientific interest.

Surfaces on Surfaces

"Surfaces defined on surfaces" means the construction of interpolants to phenomena measured on a given surface, for example, temperatures on an object. During the past year we (Barnhill and Ou '90) developed a new set of surface on surface methods and compared them with earlier methods (Barnhill, Piper and Rescorla '87). Further comparisons, with additional methods, are currently being made by Barnhill, Foley, and Lane. The various methods solve different problems: surfaces with barriers, with certain symmetries, or other special geometric features.

Contours of trivariate surfaces

Trivariate surfaces can only be displayed indirectly. The best display method is to look at contours, which are themselves three-dimensional surfaces. This has proved to be a difficult problem, in part because of the lack of robust smooth trivariate interpolants. In a long term collaboration with A. J. Worsey begun at The University of Utah, we have developed a solution to this problem. This research will be described in B. Bloomquist's forthcoming thesis. (See his summary for more details.) This is an example of the value of this long term project, because known trivariate interpolants were inappropriate for contouring, for a variety of technical reasons, and the trivariate Clough-Tocher interpolant developed by Worsey and Farin beginning at Utah and continuing at Arizona State/North Carolina is just now showing its true usefulness.

Geometry Processing

"Geometry Processing" means the calculation of geometric attributes of already constructed curves, surfaces, or volumes. The principal topics addressed this year in Geometry Processing are surface-surface intersections and offset surfaces. In addition, we completed work on numerical multiple integration and have initiated new research on data dependent triangulations.

Surface-surface Intersections

Surface-surface intersections are important for the display of networks of patches and in applications such as geometric modellers for trimming surfaces. Earlier we had developed a robust surface-surface intersection algorithm for general rectangular patches and then extended it to triangular patches. This extension is important because triangular patches are the more important for applications with arbitrarily located data. We have combined our original marching algorithm (Barnhill et al. '87) with a geometric subdivision algorithm (Houghton et al. '85). We reported on this progress at the SIAM Geometric Design meeting and it will appear in (Barnhill and Kersey '90). The curvature analysis research reported in the preceding DoE Progress Report is used to help detect regions where numerical care is required.

The most often occurring case of surface-surface intersections is a planar section of an object. This figure illustrates several planar sections of a parametric patch. The intersection paths in the domains correspond by color to the surfaces.

The surface on surface method of Barnhill and Ou is applied to aeronautical data in this figure. The trivariate interpolant is rendered by color contours.

Offset Surfaces

Offset surfaces describe the growth of physical and biological phenomena, as well as being important in numerically controlled milling and, more generally, collision avoidance. Most offset surface algorithms avoid the principal difficulties of offset surfaces, which are self-intersections and discontinuous derivatives. We use our surface-surface intersection algorithm to detect both of these classes of difficulties. A description of our offset surface algorithm is given in Todd Frost's section of this Progress Report. See also (Barnhill, '89).

Numerical Multiple Integration

The computation of surface and volume integrals occurs in many applications, such as computational fluid dynamics and aeronautical design. Barnhill and Watson ('89, '90) completed robust adaptive cubature algorithms, for bivariate and for trivariate integrands, which also formed Watson's Masters thesis. This research built on much earlier work by Barnhill and Little ('84). See Watson's report for more information.

Optimal Triangulations

Triangulations are important to define the domains of interpolants both for planar domains and for higher dimensional domains. Triangulations also have direct application to computer graphics lighting models and other graphics applications. For numerical and geometric stability, one wants the triangles as equilateral as possible, i.e., "optimal". A recent idea is to develop "data dependent" optimal triangulations. Chris House's Masters thesis implements ideas due to Dyn and to Schumaker and Quak in which measures of first or second derivatives, respectively, are minimized. "Data dependent" means that the triangulation of the domain is influenced by the values to be interpolated, for example, a cliff-like function would have triangles aligned along the cliff as nearly as possible. Dianne Hansford, Andrew Worsey, and I are considering trivariate data dependent triangulations, which will lead to important new classes of methods for trivariate and, eventually, multivariate interpolation.

Applications

An interesting application of interpolation to arbitrarily located data was the Michigan water pollution project. Given a few measurements at common locations but at different times, the problem is to represent the pollution through time. We made a videotape illustrating our results. See the reports by Farin, Foley and Lane for additional information.

In the water pollution problem there were few data sites. In Geographical Information Systems there are many (for example, one million) data sites. We used bivariate Clough-Tocher interpolants, with some specially tailored properties, to address this problem. See Farin's and Hansford's reports for more information.

Most important external research activities

Chair, SIAM Geometric Design conference, Tempe, AZ, November, 1989

Editor-in-Chief, Computer Aided Geometric Design research journal.

Reporter on Geometric Design, NSF Grantees conference, Tempe, AZ, January, 1990

Member of organizing committees, "Surfaces in CAGD", F. R. Germany, April, 1989 and Italy, May, 1990.

Invited speaker:

NASA Computational Fluid Dynamics workshop on Surface Modelling and Grid Generation, NASA Ames, December, 1989.

Mathematics of Surfaces III conference, Institute of Mathematics & Applications, Oxford, England, September, 1989.

Approximation Theory conference, Mathematics Institute, Oberwolfach F. R. Germany, August, 1989.

Approximation Theory VI, Texas A. and M. University, January, 1989.

Computational Geometry session, American Math. Society, Boulder, CO, August, 1989.

Leader of tours/speaker on CAGD for many audiences at Arizona State University.

References

- R. E. Barnhill, Computer Aided Geometric Design, in Approximation Theory VI, volume 1, C. K. Chui et al. (eds.), Academic Press, 1989.
- R. E. Barnhill, G. Farin, M. Jordan, and B. R. Piper, Surface-surface intersection, Computer Aided Geometric Design, 4, 3-16, 1987.
- R. E. Barnhill and S. N. Kersey, A Marching Method for Surface-surface intersections, Computer Aided Geometric Design, 7, 1990.
- R. E. Barnhill and F. F. Little, Adaptive Triangular Cubatures, Rocky Mountain Journal of Mathematics, 14, 53-76, 1984.
- R. E. Barnhill and S. Ou, Surfaces Defined on Surfaces, Computer Aided Geometric Design, 7, 1990.
- R. E. Barnhill, B. R. Piper, and K. L. Rescorla, Interpolation to Arbitrary Data on a Surface, in Geometric Modeling, G. Farin (ed.), SIAM, Philadelphia, 1987, 281-289.
- R. E. Barnhill and S. H. Watson, Geometry Processing: Numerical Surface and Volume Integration, in Approximation Theory VI, volume 1, C. K. Chui et al. (eds.), Academic Press, 1989.
- R. E. Barnhill and S. H. Watson, Geometry Processing: Numerical Multiple Integration, in Mathematics of Surfaces III, D. C. Handscomb (ed.), Oxford, 1990.
- N. Dyn, D. Levin, and S. Rippa, Data Dependent Triangulations for Piecewise Linear Interpolation, 1988, submitted for publication.
- E. G. Houghton, R. F. Emmett, J. D. Factor, and C. L. Sabharwal, Implementation of a divide-and-conquer method for intersection of parametric surfaces, in Surfaces in Computer Aided Geometric Design '84, R. E. Barnhill and W. Boehm (eds.), North Holland, 1985.
- C. House, Optimal Triangulations, Masters thesis, Computer Science Department, Arizona State University, Tempe, 1989.
- L. L. Schumaker, Triangulation Methods, in Topics in Multivariate Approximation, C. K. Chui, L. L. Schumaker, and F. I. Utreras (eds.), Academic Press, 1987, 219-232. (More recent developments by Schumaker and Quak on data dependent triangulations were given in Schumaker's lecture at the Approximation Theory VI conference in January, 1989.)

Progress Report for DOE grant
G. Farin

My research during 1989 focused on generalizations of rational Bézier and B-spline schemes. These are of interest for the DOE since they offer a unified framework for all curve and surface schemes presently employed by DOE labs, in addition to being able to solve several concrete problems.

1 Publications

The following are publications that are of relevance to the DOE grant.

- A major effort was put into the investigation of an interpolation scheme due to R. Sibson [10], [9], the result being a generalization to C^1 surfaces which can be used for scattered data interpolation as well as for the design of surfaces [5]. The method is local, works for any number of dimensions, and may thus be used for multivariate problems. We have successfully applied this method to ground water pollution data as described in D. Lane's writeup.
- Another project was the completion of the second edition of the text [2]. This second edition (estimated publication date: May 1990) will include C code for some 30 applications as well as more details on Coons patches and rational B-spline schemes. Publication is scheduled for April 1990. The book (sales: 5,000 by end 1989) acknowledges DOE support.
- Work was finished on the project involving contouring piecewise quadratic surfaces in a robust yet efficient manner: the contours are represented as rational quadratic splines [11].

2 Conference Participation

I was invited to give presentations at the following conferences and seminars:

- AMS summer meeting, Boulder, CO
- SIAM conference on Geometric Design, Tempe, AZ
- Oberwolfach CAGD meeting, FRG

- Discrete Curves and Surfaces meeting, Albany, NY
- General Motors Research labs, Warren, MI
- Boeing Research labs, Seattle, WA
- University of Washington, Seattle, WA
- MIT, Cambridge, MA

Each talk contained substantial amounts of material related to the DOE grant.

3 Applications of this Research

The following are applications of the research described above as well as research funded by the DOE in past years.

- The surface generation schemes from [5] have been applied to data obtained from Michigan ground water pollution measurements. They appear to produce a faithful fit to the data. Figure 1 shows a C^1 surface that is defined over a Dirichlet tessellation. Figures 2 and 3 show, respectively, the basis function for Sibson's C^0 interpolant and for the new C^1 interpolant.
- DOE funded research carried out in 1985 (see [3]) was used to produce results in the area of Geographical Information Systems. The given data were terrain elevation measurements (up to 1,000,000 per data set), and the problem was to fit a piecewise polynomial surface to it, using only local information. We devised a quick C^0 preview method and a more sophisticated one for final output that is based on [3]. The data were supplied by the Californian company Environmental Systems Research Institute.

The following bibliography contains all 1989 Farin papers that acknowledge DOE support.

References

- [1] G. Farin. Curvature continuity and offsets for piecewise conics. *ACM Transactions on Graphics*, 8(2):89–99, 1989.

- [2] G. Farin. *Curves and Surfaces for Computer Aided Geometric Design*. Academic Press, 1988.
- [3] G. Farin. A modified Clough-Tocher interpolant. *Computer Aided Geometric Design*, 2(1-3):19-27, 1985.
- [4] G. Farin. Rational curves and surfaces. In T. Lyche and L. Schumaker, editors, *Mathematical Aspects in CAGD*, pages 215-238, Academic Press, 1989.
- [5] G. Farin. Surfaces over Dirichlet tessellations. *Computer Aided Geometric Design*, 7, 1990.
- [6] G. Farin. Trends in curve and surface design. *Computer Aided Design*, 21(5):293-296, 1989.
- [7] G. Farin and N. Sapidis. Curvature and the fairness of curves and surfaces. *IEEE Computer Graphics and Applications*, 9(2):52-57, 1989.
- [8] G. Farin and A. Worsey. Reparametrization and degree elevation of rational Bézier curves. 1989. submitted for publication.
- [9] R. Sibson. *A brief description of the natural neighbour interpolant*. Technical Report, Math department, Univ. of Bath, 1980.
- [10] R. Sibson. A vector identity for the Dirichlet tessellation. *Math Proc of the Cambridge Philosophical Society*, 87:151-155, 1980.
- [11] A. Worsey and G. Farin. Contouring quadratic surfaces. *Computer Aided Geometric Design*, 7, 1990.

Figure 1: A C^1 surface that is defined over a Dirichlet tessellation (colored).

Figure 2: A basis function for Sibson's C^0 interpolant. Note sharp corner at top.

Figure 3: A basis function for the new C^1 interpolant. Note overall smoothness.

DoE Progress Report for 1989

Thomas A. Foley

1. Research

My research in 1989 focused on "surface on surface" interpolation and approximation, shape preserving interpolation and the visualization of multivariate functions. Much of my work has been joint research with G. Nielson, R. Barnhill and D. Lane. My research has been presented at conferences, several papers were published, others have been submitted, and research is in progress on all of these topics. Together with D. Lane and G. Nielson, we were co-winners of a software contest run by Ardent. Specific applications to real data are noted in the following summary of my research.

1.1 Surfaces on Surfaces

Given N arbitrary points p_i on a closed surface D and associated real values f_i , we address the problem of constructing a function $F(p)$ defined over all of D which satisfies $F(p_i) = f_i$, for $i = 1, \dots, N$. Applications include representing functions which estimate temperature, pressure, rainfall or ozone over all of the surface D , based on the given samples. Another application of this problem is discussed in the multivariate visualization section.

Researchers: Foley, Nielson, Lane

- Foley, Lane and Nielson of ASU, in collaboration with R. Franke (Naval Postgraduate School, Monterey, CA), and H. Hagen (Univ. of Kaiserslautern, Kaiserslautern, West Germany), obtained a solution to the surface on surface problem on general nonconvex domains. The general technique conceptually involves mapping the domain D to a unit sphere, solving a corresponding interpolation problem on the spherical domain, and finally mapping the results back to the surface domain D . This research has been accepted for publication in [Foley, Lane, Nielson, Franke & Hagen '90] and I presented this in April at the CAGD Conference in Oberwolfach. This method was applied to NASA data to represent pressure on a wing. Figure 1 illustrates this technique by interpolating data on a nonconvex domain.
- Figure 1 was generated using a program on the Ardent Titan developed by Foley, Lane & Nielson. This program was entered in an Ardent contest and we were co-winners. We received a \$17,000 memory board for our efforts, and that extra memory enabled us test our methods on larger data sets. Figures of the demo program are given in D. Lane's section. The programs have been also implemented on the Silicon Graphics IRIS 4D/220 workstation.
- The computer graphics research involved with the rendering of surfaces on surfaces was recently published in [Foley, Lane, Nielson & Ramaraj '90]. Figure 1 involves an extension of these graphical techniques and most of the figures in the IRIS Universe magazine (pages 26-33) used these techniques.

(Surfaces on Surfaces)

- Foley and Lane developed another approach for interpolation and approximation of data on a sphere using a compact support basis similar to B-splines. This technique allows for the approximation of noisy data sampled at a large number of locations on a sphere. In addition, the method can be used to model closed surfaces with local spherical precision. We plan to complete this work and submit it for publication. This work was presented in November at the SIAM Conference in Tempe.

Researchers: Barnhill, Foley, Lane

- Barnhill, Foley and Lane are near completion of a critical comparison of several surface on surface methods tested on many different data sets. These results will be reported at a conference in May, and a paper on this will be submitted. The survey paper describing several surface on surface techniques was submitted for publication [Barnhill and Foley '90].
- For the simpler case of constructing a bivariate interpolant over a planar domain, we have implemented several existing methods and applied them to water pollution data. In Michigan, chloride and conductance measurements were sampled at several wells over several years. By viewing the interpolants over time, one can observe the movement of the contaminants. Figure 2 illustrates an interpolant to one set of chloride data.

Researchers: Foley

- For the case where the domain D is a sphere, a C^2 interpolant based on geodesic distance was published in [Foley '89]. This work was done in 1988 and reported last year.
- I recently developed an interpolant on a spherical domain that consists of a weighted average of two interpolants to data defined on a planar domain. With D. Lane's programming help, this technique appears to be one of the most effective of all those implemented so far. Theoretical details and extensions will be completed and a paper will be submitted.
- Together with R.E. Carlson of Lawrence Livermore National Laboratory, we have obtained empirical results on the optimal value for the ambiguous constant used in multiquadric interpolation. This technique was applied to water temperature data sampled off of the California coast. An initial draft of the paper has been written.

Figure 1. Surface on surface interpolant and graphical display techniques applied to functional data sampled at points on the non-convex surface in the upper right. [Foley et al. '90]

Figure 2. Interpolation to chloride measurements near a dump site in Michigan.

1.2 Shape Preserving Interpolation

A shape preserving interpolant is a function which passes through some given data and retains the intrinsic shape implied by the given data.

- Four papers related to this topic, which were noted in last year's report, were published in 1989, namely [Foley and Ely '89], [Foley, Goodman & Unsworth '89], [Foley and Nielson '89] and [Nielson and Foley '89].

Researchers: Foley, Gregory, Hamann, Lane, Neuser

- Research on curve and surface interpolation with interactive shape control parameters was published in [Foley and Neuser '89]. This method uses piecewise quintic polynomials to represent a function which optimizes a norm on the first, second and third derivatives. I presented this research in January at the Sixth Texas Symposium on Approximation Theory.
- Hamann and I have worked on an interpolation method that optimizes a measure of the function's second derivative. See B. Hamann's section for figures of this technique. A draft of the paper has been written.
- John Gregory, of Brunel University, visited our research group in April. John and I developed a convexity preserving curve interpolation method based on geometric principles, and D. Lane implemented the technique. This effective approach was presented in November at R.P.I., at which time we were surprised to learn that someone else had developed the same method in the past year, but they had not yet published it. We did obtain additional theoretical results and we are investigating how to generalize this method to surfaces.

1.3 Multivariate Visualization

Lane, Hamann, Nielson and I have developed techniques for visualizing surfaces on surfaces and 4D data (x, y, z, w) , where w is a trivariate function $w = f(x, y, z)$. Since much of this research is stated in Nielson's section, my description will be brief.

Researchers: Foley, Lane, Nielson

- As noted in my section on Surfaces on Surfaces, we have developed graphical techniques for visualizing functions defined on surfaces. The paper [Foley, Lane, Nielson & Ramaraj '90] considers the case where the domain is a sphere, while [Foley, Lane, Nielson, Franke & Hagen '90] discusses both the interpolation and visualization on general surfaces. Figure 1 and the IRIS Universe magazine illustrate these techniques.
- The ray-casting technique for viewing 4D trivariate function data is a costly method that takes approximately 40 minutes to compute a single image on our Ardent Titan. By using concepts from interpolation on a spherical domain, we were able to generate approximate ray-cast images in less than one second per image. Our implementation made use of the vectorization and parallelization capabilities on the Ardent Titan. This research has recently been submitted for publication [Foley, Lane & Nielson '90]. Figure 3a is an application of this method to CAT scan data of a skull, and Figure 3b shows the results applied to a smooth trivariate function with four regions of high density.

a)

b)

Figure 3. The upper-right images are ray-traced volumetric images that took 40 minutes to compute on the Ardent Titan. The upper-left images are approximations that took less than one second to compute. Fig. 3a) is CAT scan data and 3b) is a smooth trivariate function with four regions of high density. [Foley, Lane & Nielson '90]

1.4 Other Research

Two students who were not funded by the DoE completed their MS Theses under my direction in 1989 on work somewhat related to the DoE grant.

- [Zelov '89] worked on the problem of reconstructing a three dimensional surface from two stereo photographs. This technique was successful in generating 3D surfaces from Viking photographs of natural terrain on Mars.
- [Danielson '89] developed effective methods for generating stochastic 4D volumetric data, based on a small number of 4D input values. This technique involved stochastic perturbation and the subdivision of trivariate Bezier quadratic functions.
- Other non-funded graduate students of mine have been conducting MS research on multivariate visualization, effective parametrization of spline surfaces, shape preserving interpolation and the animation of rigid bodies (with Nielson).

2. Conference Presentations

I presented talks at the following conferences in 1989. Each presentation involved DoE funded research discussed in the previous section and the DoE support was acknowledged.

- Sixth International Symposium on Approximation Theory, Texas A & M, January, 1989.
- Conf. on Computer Aided Geometric Design, Oberwolfach, West Germany, April, 1989
- SIAM Conference on Geometric Design, Tempe, AZ, November, 1989.
- Discrete Curves and Surfaces, R.P.I. University, Troy, NY, November, 1989.

One day courses taught at conferences:

- At the ACM SIGGRAPH Conference in Boston, Farin, Nielson and I taught the course "Curve and Surface Design: From Geometry to Applications."
- At the SIAM Conf. on Geometric Design, Nielson and I co-organized and taught the course "Visualization Techniques for Geometric Design."

3. Publications for 1989-90

(All papers involving Foley acknowledge DoE support.)

Barnhill, R.E. and Foley, T.A. (1990). Methods for constructing surfaces on surfaces, submitted for publication.

Danielson, B.H. (1989). Fractal processes applied to data in volumetric space, M.S. Thesis, Computer Science Dept., Arizona State University.

Foley, T.A. (1989). Interpolation of scattered data on a spherical domain, in Algorithms for Approximation II, M. Cox and J. Mason, eds., Chapman and Hall, London.

Foley, T.A. and Ely, H.S. (1989). Surface interpolation with tension controls using cardinal bases, Computer Aided Geometric Design 6, no. 2, 97-109.

Foley, T.A., Goodman T.N. and Unsworth, K. (1989). An algorithm for shape preserving parametric interpolating curves with G^2 continuity, in Mathematical Methods in CAGD, T. Lyche and L.L. Schumaker, eds., Academic Press, San Diego, 249-259.

Foley, T.A., Lane, D.A. and Nielson, G.M. (1990). Towards animating ray-cast volume visualization, submitted for publication.

Foley, T.A., Lane, D.A., Nielson, G.M., Franke, R. and Hagen, H. (1990). Interpolation of scattered data on closed surfaces, Computer Aided Geometric Design 7, (accepted/to appear).

Foley, T.A., Lane, D.A., Nielson, G.M. and Ramaraj, R. (1990). Visualizing functions on a sphere, IEEE Computer Graphics & Applications 10, no. 1, 32-40.

Foley, T.A. and Neuser, D.A. (1989). Quintic spline interpolation with shape control parameters, in Approximation Theory VI, Vol. 1, C.K. Chui, L.L. Schumaker and J.D. Ward, eds., Academic Press, San Diego, 259-262.

Foley, T.A. and Nielson, G.M. (1989). Knot selection for parametric spline interpolation, in Mathematical Methods in CAGD, T. Lyche and L.L. Schumaker, eds., Academic Press, San Diego, 261-271.

Nielson, G.M. and Foley, T.A. (1989). A survey of applications of an affine invariant norm, in Mathematical Methods in CAGD, T. Lyche and L.L. Schumaker, eds., Academic Press, San Diego, 445-467.

Zelov, S.B. (1989). Digital terrain derivation using combined area- and feature-based stereo vision techniques, M.S. Thesis, Computer Science Dept., Arizona State University.

DOE Progress Report for 1989

by
Gregory M. Nielson

1. Research

Since the beginning of last summer, I have been involved in a variety of research projects. On most of these projects, I have collaborated with other faculty and students. Tom Foley and I have worked together on a number of projects. While we interact quite often with most of the students affiliated with the CAGD group, the students that we most often work with are Bernd Hamann, David Lane and Brett Blomquist. For the most part, the research I have done falls into the subject areas of scientific visualization, curve comparisons, surfaces on surfaces, triangulations and tessellations, and splines for computer animation.

1.1 Scientific Visualization Projects

1.1.1 Multivariate Visualization

Researchers: Tom Foley, Gerald Farin, Bernd Hamann, David Lane and Greg Nielson

Summary:

The representation of multivariate surfaces is one of the major goals of our group's research. Since visualizing multivariate data and surfaces is an important component of this research we continue to develop techniques and methods in this area. Please see the sections by Tom Foley, Bernd Hamann and David Lane for more details. The data of Figure 1 is from Marshal Long of Yale University who works with other researchers at Sandia Laboratory on combustion problems. We met him and initiated this collaboration during a visit to Sandia Labs in Livermore, CA. We were fortunate to get some exposure for this research when the cover of the Fall, 1989 issue of *IRIS universe* featured the image of Figure 1.

Another aspect of this research is the construction of surface contours of trivariate functions and data. A rather standard approach is to use a gradient operator and to determine surface facets (normally triangles) by thresholding. While this is fine for the simple display of a contour surface, it does not aid much in finding a mathematical representation of the surface. For this you need to compute the interconnection topology. We have developed a method for doing this. In Figure 2 is shown the triangulation of a surface contour which was computed using the method of Bernd Hamann. Our next step is to first reduce the number of triangles and then use a G^1 triangular patch in order to obtain a smooth surface approximation to the contour. Bernd Hamann (see [Hamann & Farin & Nielson '90]) has recently developed such a patch which shows a good deal of promise.

Figure 1. The visualization of gas concentrations from an acoustically driven forced flow. Data is courtesy of Marshall Long, Yale University.

Figure 2. A contour surface for which the interconnection topology has been computed using the method of Bernd Hamann.

1.1.2 Ardent Contest

Researches: Tom Foley, David Lane and Greg Nielson

Summary:

Based upon some software and techniques original discussed in R. Ramaraj's 1986, ASU Thesis, we have developed a very nice interactive program for demonstrating our methods for fitting and visualizing surfaces on surfaces. The software was a co-winner in a contest sponsored by Ardent. David Lane was the main programmer of the software for this project. See the report by David Lane for more details. At SIGGRAPH (with more than 25,000 attendees) this past summer images generated by our software was shown on a large, 5 monitor X 5 monitor display at the Ardent Booth (see figure below).

Figure 1. Surface on surface (teapot) demo at Ardent booth at SIGGRAPH '89.

1.1.3 Special Issue of IEEE Computer

Summary:

The August issue of **IEEE Computer** is devoted to the topic of Visualization in Scientific Computing. Two members of our research group, Tom Foley and Greg Nielson, are on the Executive Committee of the IEEE Technical Committee on Computer Graphics which sponsored this special theme issue (see [Nielson '89a]). DOE support is acknowledged in the introduction to this special issue.

1.1.4 Annotated Bibliography of Scientific Visualization

Researchers: Tom Foley, Greg Nielson and Keith Voegelé

Summary:

A bibliography of over 150 publications in the area of scientific visualization has been compiled. This is an annotated bibliography which includes comments on the content and the context of each of the entries. This is the first bibliography on this topic. It will be included in a soon-to-be-published book on scientific visualization [Nielson & Shiver '90].

1.1.5 Image Interpolation

Researchers: Tom Foley, David Lane and Greg Nielson

Summary:

A major research goal in scientific visualization is to achieve real-time volume rendering. The benefits of this accomplishment could be tremendous for many areas of science, medicine, and engineering. A number of research groups around the country are approaching this problem by developing special purpose hardware. We have taken a quite different approach which is software oriented. We do a large amount of preprocessing prior to the interactive session of viewing the data. Images are constructed by "interpolating" other images which have been precomputed. A typical screen image of our interactive program is shown in Figure 1.

We are currently able to generate a 300 X 300 volume rendered image in about .14 seconds. Ten frames a second would be considered real-time and so we are quite close. We hope to achieve real-time speeds soon. Please see the sections by Tom Foley and David Lane on this same topic.

Figure 1. Typical screen image of interactive volume rendering program.

1.2 Curve Comparison Metric

Researchers: Fred N. Fritsch and Greg Nielson

Summary:

As surprising as it may seem, there are not standard nor uniformly accepted methods for computing the distance between two curves. One would want to make quantitative statements on this type in a variety of situations. For example, in order to answer the question, "How well can a Wilson-Fowler spline be approximated by a C^2 cubic B-spline?", some type of curve metric needs to be available. Working with Fred Fritsch of Lawrence Livermore National Laboratory, we have been working on the development of curve comparison metrics. Some of our preliminary results were reported at the Fall SIAM meeting and we plan to publish the results soon (see [Fritsch & Nielson '90]).

1.3 Surfaces on Surfaces

Researchers: Tom Foley, David Lane, Hans Hagen, Dick Franke and Greg Nielson

Summary:

Since Tom Foley's section (and David Lane's) covers this subject well, I will make my comments brief. Given data values F_i at locations p_i on a closed domain D , the problem is to construct a smooth function F which is defined on all of D such that $F(p_i) = F_i$. In collaboration with R. Franke (Naval Postgraduate School) and H. Hagen (Universität Kaiserslautern), Tom Foley and David Lane, we have developed a technique which works for the general nonconvex domain case. This research is soon to be published (see [Foley & etal '90]). DOE support is acknowledged in this publication.

1.4 Spherical Tessellations and Triangulations

Researchers: Brett Bloomquist and Greg Nielson

Summary:

Triangulations and tessellations are basic to many of the techniques for representing surfaces. If the data is from a sphere (such as the earth) then it is of interest to develop algorithms for triangulating the domain based upon these points. Using the concept of geodesic distance, we have developed an algorithm for computing a tessellation of the sphere based upon the data points. The dual of this Dirichlet tessellation yields a triangulation as is shown in Figure 2. See also the material in Brett Bloomquist's section on this topic

Figure 1. A Dirichlet Tessellation of the sphere

Figure 2. The triangulation dual to the above tessellation

1.5 Computer animation using Splines and Splines on Spheres

Researchers: Chao-Chi Chen, Tom Foley, Randy Heiland and Greg Nielson

Summary:

This is continuing research on the development of new methods for the animation. Previously, we have developed some new techniques for animating orientations (see [Nielson & Heiland '90]). These techniques are based upon splines on a sphere. We are now extending these techniques to the full animation problem which requires position as well as orientation. This will allow animated sequences to be specified by several key frames. In addition to the splines on spheres, we are using weighted Nu-splines. In order to make the methods affine invariant, we are using our new affine invariant metric to develop methods for knot selection.

2. Publications

Fritsch, F. N. and G. M. Nielson (1990), On the comparison of parametric curves, SIAM Conference on Geometric Design, in preperation

Foley, T. A., D. A. Lane and G. M. Nielson (1990), Towards animating ray-cast volume visualization, in preperation

Foley, T. A., D. A. Lane, G. M. Nielson, R. Franke and H. Hagen (1990), Interpolation of scattered data on closed surfaces, to appear in Computer Aided Geometric Design 7.

Foley, T. A., D. A. Lane, G. M. Nielson and R. Ramaraj (1990), Visualizing functions on a sphere, IEEE Computer Graphics & Applications 10, No. 1, 32-40.

Foley, T. A. and G. M. Nielson (1989), Knot selection for parametric spline interpolation, in Mathematical Methods in CAGD, T. Lyche and L. L. Schumaker, eds. Academic Press, San Diego, 261-271.

Hamann, B., G. Farin and G. Nielson (1990), A parametric triangular patch for convex data based on conics, in preperation

Nielson, G. M. and T. A. Foley(1989), A survey of applications of an affine invariant norm, in Mathematical Methods in CAGD, T. Lyche and L. L. Schumaker, eds. Academic Press, San Diego, 445-467.

Nielson, G. M. (1989a), Author of Introduction and Guest Editor of special theme issue on Visualization in Scientific Computing, Computer 22, No.8.

Nielson, G. M. (1989b), Affine invariant triangulations, submitted.

Nielson, G. M. and R. W. Heiland (1990), Interpolation of Rotation Matrices using Quaternions and Splines on a 4D Sphere, ASU Technical Report #90-001.

Nielson, G. M. & B. Shriver (1990), **Scientific Visualization**, IEEE Computer Society Press, to be published in 1990.

PROGRESS REPORT TO THE DEPARTMENT OF ENERGY

Research assistant summaries

DoE Progress Report for 1989

Brett Keith Bloomquist

INTRODUCTION

Research efforts for 1989 were concentrated on developing tools for visualizing multivariate surfaces. In particular, a significant portion of the research effort has been spent toward developing an algorithm for contouring trivariate surfaces. There has also been some time spent working on an algorithm for forming the Dirichlet tessellation and the Delaunay triangulation of data points on a sphere. A more detailed account of these activities follows.

TRIVARIATE CONTOURING

Researchers: Dr. R. E. Barnhill, *Arizona State University*, Brett Bloomquist, *Arizona State University*, and Dr. Andrew Worsey, *University of North Carolina at Wilmington*.

Contouring has proven to be an effective way of visualizing a bivariate surface with a two-dimensional medium. Anyone who has used contour maps of terrain knows how valuable such information can be. There are also many real-world problems that are represented by trivariate surfaces, such as temperature readings at locations in an oven, salt concentrations in the ocean, radiation levels in space, etc. Since trivariate surfaces are four-dimensional objects, we can't view them with the human eye. Hence, we need a way to reduce the dimension of the problem. Since a sequence of contours also provides visual gradient information, contouring would be a valuable tool for analyzing trivariate surfaces. Although some work has been done in this area, there is still much to be done.

We have been working towards developing an efficient algorithm for contouring trivariate surfaces. The approach is similar to an approach taken by Chip Petersen [Petersen et al. '86]. Briefly, Chip Petersen degree reduces a polynomial trivariate surface until it is linear — the linear polynomials are easy to contour.

The degree reduction steps in Chip Petersen's algorithm are computationally intensive, since the original polynomial must be subdivided many times before a good linear approximation is obtained. The most intensive step is the degree reduction from quadratic to linear.

To eliminate some of the instabilities of so much splitting we are looking at contouring trivariate quadratics exactly, thus eliminating the degree reduction step from quadratic to linear.

In order to contour the trivariate quadratics, we first need to be able to contour bivariate quadratics. There have been some methods developed in the past for the exact contouring of bivariate quadratics (contours of a quadratic patch are conic sections). However, there are cases for each method that pose some problems. Recently, Dr. Andrew Worsey and Dr. Gerald Farin [Worsey & Farin '90] developed a very robust method for finding contour sections of quadratics. We have implemented the algorithm at ASU, and it works very well. The contour sections are represented as rational quadratic Bézier curves.

We have also looked at ways of improving the degree reduction and splitting steps. We have developed a least squares degree reduction scheme for the polynomial degree reduction. If the degree reduction isn't good enough, we need to split the simplex and start over. Since we want to reduce the number of splits used, we looked at how splitting the simplex at different places affects the quality of the next degree reduction step. In the univariate case we found that the best place to split is *always* at the midpoint of the polynomial [Bloomquist et al.]. This simplicity doesn't extend to the higher dimensions, but we found that splitting the simplex at the midpoint of the edge with the largest univariate error was often close to the best degree reduction possible.

The splitting process is one of the most time consuming steps of the algorithm. We have investigated different methods of splitting the simplices. By splitting at the centroid of the simplex we don't need to split any neighbors, but the subsimplices degenerate very rapidly. Another possibility is to split at the largest face between two neighboring tetrahedra. This works better, but we have found that we can do even better by splitting along an edge. However, this splitting method affects every neighbor that shares an edge. Because of this we wanted to develop a way of splitting the simplices uniformly. By doing this we have obtained excellent results and very rapid convergence.

This research will lead to a thesis on contouring trivariate surfaces. There will also be some papers written that will concentrate on significant accomplishments of this research.

SPHERICAL TESSELLATION/TRIANGULATION

Researchers: Brett Bloomquist, *Arizona State University*, and Greg Nielson, *Arizona State University*.

It makes sense to reduce some trivariate problems to a lower dimensional problem by defining the problem over a different domain (surface on surface problems). An efficient routine for tessellating/triangulating scattered data on a sphere would help in developing methods defined over the sphere.

We developed a robust algorithm for constructing the Dirichlet tessellation and Delaunay triangulation over the sphere (refer to Dr. Nielson's report for figures). The construction is no harder (and sometimes easier) than over the plane. The method is similar to a planar method developed by Bowyer [Bowyer '81].

REFERENCES

- Bloomquist, B.K., Barnhill, R.E., and Worsey, A.J., Optimal degree reduction, in preparation.
- Bowyer, A. (1981), Computing Dirichlet tessellations, *The Computer Journal* 24, 102-106.
- Petersen, C.S., Piper, B.R., and Worsey, A.J. (1986), Adaptive contouring of a trivariate interpolant, in: Farin, G., ed., *Geometric Modeling: Algorithms and New Trends*, SIAM, Philadelphia.
- Worsey, A.J. and Farin, G. (1990), Contouring a bivariate quadratic polynomial over a triangle, *Computer Aided Geometric Design* 7.

DoE Program Report for 1989
T. M. Frost

Parametric Offset Surfaces

Dr. Robert. E. Barnhill, Dr. Gerald. E. Farin and Dr. Thomas. A. Foley

Offset surfaces arise in a variety of applications such as generation of navigation paths for submarines and modeling growth surfaces as they typically occur in solid fuel combustion. Planar offset curves are often used to develop an understanding of offset surfaces.

Let $c(t)$ be a planar parametric curve (referred to as the progenitor curve) possessing a well defined unit normal, then an offset curve can be defined as follows (Tiller & Hanson 1984):

$$o(t) = c(t) + d \cdot n(t)$$

where n is the progenitor unit normal and d is the offset distance. Graphically,

Let $s(u,v)$ be an arbitrary parametric surface (referred to as the progenitor surface) possessing a well defined unit normal, then an offset surface can be defined as follows (Farouki 1985):

$$o(u,v) = s(u,v) + d \cdot n(u,v)$$

where n is the progenitor unit normal and d is the offset distance. Graphically,

Geometrically this corresponds to a surface defined by the center of a sphere of radius d that rolls over every point of s (Farouki 1985). Farouki developed an algorithm which generates a uniform mesh of bicubic Hermite patches that interpolate the exact offset's position, first and second partial derivatives. We have developed an adaptive version of this method. The need to generate an approximate offset surface stems from the fact that, in general, an offset surface cannot be represented within the same class of functions as its progenitor surface. More significantly the formulation of the offset surface involves a cross product and a square root. This material was presented in a mini-symposium at the SIAM Conference on Geometric Design on November 9, 1989.

Inherent in the offset problem is the problem of self-intersection and generation of possibly undesirable features such as cusps and ridges. Degeneracy of the offset occurs when the offset magnitude is comparable to the minimum concave radius of curvature (Farouki 1985). Surface self intersection methods and 'degeneracy' maps are among the tools that can be used to find degenerate regions and determine the overall goodness of the approximate. Both of these tools have been developed and research is being done to make them robust and efficient parts of an offset surface generation program. Research is also being done to establish more strict continuity conditions in the approximate offset, to develop the ability to trim undesirable regions and to develop a method of incorporating absolute error bounds within the approximation algorithm.

The illustrations on the following page show a sequence of approximate offsets to a progenitor surface. As the offset changes orientation (d changes sign) and magnitude, the offset progresses from a simple form to a more complex form possessing increasingly degenerate regions and self-intersection.

Rational bicubic Bezier progenitor

Approximate offset with negative offset distance d^-

Approximate offset with positive offset distance $d_2^+ > d_1^+$

References

- Farouki, R. T. (1985). *The approximation of non-degenerate offset surfaces*, Computer Aided Geometric Design, 15-43.
- Tiller, W. and Hanson, E. G. (1984). *Offsets of two-dimensional profiles*, I.E.E.E. Computer Graphics and Applications 4 (9), 517-524.

January 31, 1990

DoE Progress Report for 1989

Bernd Hamann
CAGD Research Group
Arizona State University, Computer Science Department

Research title : **Rendering / Visualizing multivariate data**
Researchers : Dr. Gregory M. Nielson, Bernd Hamann

Description : Techniques involve rendering of trivariate functions of the form $f=f(\mathbf{x})=f(x,y,z)$. Physical measurements or data from simulations are taken at arbitrary 3D space points thus determining a set of points $\{\mathbf{x}[i]=(x[i],y[i],z[i]) \mid i=1\dots N\}$ together with associated function values $\{f[i]=f(\mathbf{x}[i]) \mid i=1\dots N\}$.

Methods developed :

- 1.1.) Decompose function $f(\mathbf{x})$ into sets of bivariate functions $f(x,y,\text{const})$, $f(x,\text{const},z)$ $f(\text{const},y,z)$
- 1.2.) Find contour surfaces where f is constant :
 $f(\mathbf{x})=\text{const}[i]$, $i=1\dots N$, yields N contour surfaces
- 1.3.) Intersect the 3D domain of f with planes and contour f there using color contouring for f
- 1.4.) Decompose the domain into a set of cubes that do not intersect and may have gaps between them:
use color contouring for f on the faces of all cubes
- 1.5.) Use method 1.4. with additional transparency effect
- 1.6.) Use ray tracing techniques; shoot rays from viewer's position into 3D domain of f and accumulate the function values along each ray to get color

Applications :

The rendering methods described here, all find use in the visualization process for any kind of physical data in 3D space, e.g., temperature measurements, pressure measurements, radiation measurements, ... Ray tracing techniques are of special interest in medical imaging (simulating X-rays). Algorithms that generate the boundaries of some 3D object are of interest if one can obtain both a geometrical and a topological description. This enables us to use standard CAGD techniques to model those data.

See pictures : P1.1, P1.2, P1.3, P1.4, P1.5, P1.6

Research title : **Curves and Surfaces**
Researchers : Dr. Gerald E. Farin, Dr. Thomas A. Foley,
Dr. Gregory M. Nielson, Bernd Hamann

Description : C2 quartic tension spline

A C2 quartic spline based on a minimization problem has been developed. The paradigm behind this spline is to create curves/surfaces that are shape preserving and approach the given data polygon very closely ("tension").

See pictures : P2.1 and P2.2

Description : A parametric rational triangular surface patch has been developed for interpolating data points in 3D space together with unit outward normals at these points. The resulting patch will finally interpolate to both positional and normal data. The scheme is based on conics.

See pictures : P3

P1.1 : Decomposition of Trivariate Function

P1.2 : Contours of Trivariate Function

P1.3 : Contouring Trivariate Function in Planes

P1.4 : Decomposition of 3D Domain into Cubes

P1.5 : Decomposition with Transparency Effect

P1.6 : Ray Tracing - Simulating X-Rays

P2.1 : C2 Quartic Spline for Planar Data

P2.2 : C2 Quartic TP Spline for 3D Data

P3 : Parametric Rational Triangular Surface

DoE PROGRESS REPORT FOR 1989

Dianne Hansford

This report is an outline of my research accomplishments that have been supported by the DoE during 1989.

ADAPTIVE TRIANGULATIONS OF TRIMMED NURB SURFACES

Researchers: Barnhill, Farin, Hansford, House

The outcome of this project was a package for defining trimmed NURB surfaces and then representing them in an adaptively triangulated form. The primary application of this package is for enabling accelerated rendering by decreasing the number of triangles needed to represent the surface.

The information needed for this package include an explicit representation of the surface and trim curves that are defined in the domain of the surface. Our package will first define the "visible" parts of the surface by eliminating the parts of the surface cut-off by the trim curves. After this, the package triangulates the surface adaptively by determining highly curved areas in which more triangles are necessary.

Because triangular finite element representations are an integral part in surface representation (in terms of rendering), this project represents a very useful tool.

The initial work on this project took place in Fall 1988, however the final package was completed in February 1989. Part of this package grew out of previous work we have done on triangulations which was supported by the DoE in 1987.

SCATTERED DATA INTERPOLATION USING THE DIRICHLET TESSELLATION

Researchers: Farin, Hansford

We have been investigating scattered data interpolants which are based upon the Dirichlet tessellation (Voronoi diagram) of the point set. Such schemes, also called natural neighbor

schemes, are advantageous because they are local, and use a selection of local data which is in some sense "natural".

We investigated Sibson's C^0 and C^1 interpolants. I programmed these schemes and analyzed the resulting interpolants in a variety of instances. Also, we have been investigating theoretical aspects of these interpolants in order to make them more useful: calculating exact derivatives or determining the interpolant outside of the convex hull of the given data points. This work is still in progress.

Additional work on natural neighbor interpolants was done by Farin with his C^1 interpolant [1]. This scheme blends Dirichlet tessellations, Bézier methods, and Sibson's methods. His scheme represents an improvement over Sibson's interpolant due to its theoretical soundness and that it has quadratic precision (Sibson's has spherical quadratic precision). My contribution was to program this scheme for Farin and to compare it with the other natural neighbor schemes.

DATA DEPENDENT TRIANGULATIONS

Researchers: Barnhill, Hansford, Worsey

Trivariate data representation has become a common need for scientists. We are currently developing methods to represent trivariate data with tetrahedral elements such that this piecewise trilinear interpolant is a best fit to the data. That is, we want the tetrahedral elements to most accurately represent changes in the data. This type of element fitting is called data dependent triangulations. Not only does this project demand theoretical and numerical results, it also will require surface visualization techniques.

This work is currently in progress. We have implemented one method, and we are currently testing its effectiveness.

TRIANGULAR INTERPOLANTS

Researchers: Farin, Hansford, Kashyap

With the increased use of computers for designing surfaces of complex shape, triangular patches are becoming more common. We have been experimenting with the C^0 9-parameter interpolant and the modified Clough-Tocher C^1 interpolant (developed by Farin in 1982, and supported by the DoE). Our interest is focused on the application of terrain modeling. This project has the cooperation of ESRI: Environmental Systems Research Incorporated. We are not only examining how well these interpolants allow us to model the terrain data,

but also how they can be used when large amounts of data are present. Storage and time requirements are of uppermost importance. This project is currently in progress.

An extension of this project is the derivation of good derivative information from given point data. We have realized that the current methods are not always adequate. We have just begun to work on this problem.

MIN-MAX TRIANGULATIONS

Researcher: Hansford

During this year, my paper "The neutral case for the min-max triangulation" [2] was accepted for publication. The work done for this paper was supported by the DoE in 1988. I presented this paper at the SIAM conference on Geometric Design in Tempe, Arizona in November 1989.

GAMMA-SPLINE INTERPOLATION

Researchers: Farin, Hansford, Worsey

During this year, the paper "The singular cases for gamma-spline interpolation" [3] was accepted for publication. (This is not technically DoE supported research, although DoE equipment was used and the agency is in the acknowledgements.)

REFERENCES

- [1] Farin, G. (1990) Surfaces over Dirichlet tessellations. Computer Aided Geometric Design, vol 7.
- [2] Hansford, D. (1990) The neutral case for the min-max triangulation. Computer Aided Geometric Design, vol 7.
- [3] Farin, G., D. Hansford, A. Worsey (1990) Results on the singular cases for interpolating gamma-splines. Computer Aided Geometric Design, vol 7.

DoE Progress Report for 1989

David A. Lane

Image Interpolation

Researchers: Dr. T.A. Foley, Dr. G.M. Nielson, and D.A. Lane

A method which interpolates time costly ray-cast images was implemented. Several interpolation and implementation approaches were used for this method. For the implementation, several approaches were tested to seek the minimal interpolation time. During the process of testing these approaches, we gained more knowledge in vectorization and parallelization of programs on an Ardent TITAN. In a representative example, the execution time of a subroutine was improved from 2.3 seconds to 0.18 seconds after the subroutine was vectorized and parallelized. We also learned how to run programs on a Cray X-MP/14se. We used the Cray to help us generate several ray-cast images.

Recently, we were pleased to report that we can generate one approximate ray-cast image in less than one second. To generate the actual image using existing ray-cast techniques, it would take approximately 40 minutes on the TITAN and 8 minutes on the Cray. A complete description of this research can be found in [Foley, Lane & Nielson '90].

Surfaces on Surfaces

Researchers: Dr. R.E. Barnhill, Dr. T.A. Foley, Dr. G.M. Nielson, and D.A. Lane

To further demonstrate the applications of surfaces on surfaces, more domains were used. In particular, the following objects were used as domains: teapot, airplane wing, torpedo, heart, and balloon. To display the interpolation results over these domains, the rendering techniques introduced in [Foley, Lane, Nielson & Ramaraj '90] were used.

A comparison of six interpolation methods and seven test functions on three domains was performed. Some of the interpolation methods used in the comparison are described in [Barnhill & Ou '90], [Foley '89], [Foley, Lane Nielson, Franke & Hagen '90], and [Hardy & Goepfert '75]. The comparison was performed using evaluation grids with 244 points and 1252 points. Work to include more test functions and interpolation methods [Nielson & Ramaraj '87] is underway.

Approximation over Closed Surface Domains

Researchers: Dr. T.A. Foley and D.A. Lane

A method which uses B-Splines defined over the unit sphere to approximate data on a closed surface was implemented. To test the goodness of the approximation, scattered data on several domains were tested. The test results showed that the method was able to produce good approximations.

Curve Fitting using Subdivision

Researchers: Dr. T.A. Foley and D.A. Lane

A method of fitting a curve through a set of given data points was implemented. Several parameters for this method were tested. Some of these parameters include perturbation of angles at the vertices of the input polygon and insertion of artificial points to allow change of convexity in the input polygon. More testings will be performed.

Weighted Interpolants

Researchers: Dr. T.A. Foley and D.A. Lane

A new method for surfaces on surfaces was implemented. This method is based on Dr. Foley's idea. Several tests were performed to investigate this method. Specifically, several parameters associated with this method were tested. Current results indicate that this method was able to interpolate data over a closed domain with small interpolation errors.

Volumetric Data Visualization

Researchers: Dr. T.A. Foley, A. S. Alnaji, and D.A. Lane

A method of rendering volumetric data was investigated. This method is based on Dr. Foley's algorithm. The method renders volumetric data using transparent contour surfaces. Some preliminary results were obtained.

Water Pollution Data Project

Researchers: Dr. R.E. Barnhill, Dr. T.A. Foley, and D.A. Lane

During April 1989, we received a set of nitrate data from Dr. Paul Jorgensen of Research & Technology Institute (RTI). The data were measured from Michigan state's Allendale township. An interactive interpolation/rendering tool was then developed to interpolate and display this data set. Subsequently, we received another set of data on June 1989. This set of data consists of chloride and conductance measurements from Park township. Both Allendale township and Park township are part of the Ottawa county in Michigan. Several colorful prints and slides of the interpolation results were generated. In addition, a video tape narrated by Dr. Foley and taped by Wayne Woodland was made and sent to RTI. This video tape shows the interpolation and rendering of the data from Ottawa county.

Demo Contest

Researchers: Dr. T.A. Foley, Dr. G.M. Nielson, and D.A. Lane

A program which demonstrates surfaces on surfaces was developed on an Ardent TITAN. This fully interactive and menu driven program was developed by Dr. Foley, Dr. Nielson, and Lane for a contest sponsored by Ardent. We were the co-winners of the contest and Ardent awarded a sixteen-megabyte memory board to the computer science department at ASU. Many visitors to the ASU CAGD lab have seen a demonstration of this program and most of them were very impressed.

Figures

Attached are three 8x11 color prints generated from a color laser printer which is connected to an Ardent TITAN. The first two color prints show the results from the image interpolation research project. The third color print shows the main menu of the demo program that won a sixteen-megabyte memory board.

References

- Barnhill, R.E. and Ou, H.S. (1990), *Surfaces defined on surfaces*, Computer Aided Geometric Design 7, (to appear).
- Foley, T.A. (1989), *Interpolation to scattered data on a spherical domain*, in: Cox, M. and Mason, J., eds., *Algorithms for Approximation '88*, Oxford University Press.
- Foley, T.A., Lane, D.A., and Nielson, G.M. (1990), *Towards animating ray-cast volume visualization*, (submitted for publication).
- Foley, T.A., Lane, D.A., Nielson, G.M., Franke, R., and Hagen, H. (1990), *Interpolation to scattered data on closed surfaces*, Computer Aided Geometric Design 7, (to appear).
- Foley, T.A., Lane, D.A., Nielson, G.M., and Ramaraj, R. (1990), *Visualizing functions over a sphere*, Computer Graphics and Applications 10, 32-40.
- Hardy, R.L. and Goepfert, W.M. (1975), *Least squares prediction of gravity anomalies, geoidal undulations, and deflections of the vertical with multiquadric harmonic functions*, Geophys. Research Letter 2, 423-426.
- Nielson, G.M. and Ramaraj, R. (1987), *Interpolation over a sphere*, Computer Aided Geometric Design 4, 41-57.

ASU
CAGD

IMAGE
INTERPOLATION

THOMAS FOLEY
GREGORY NIELSON
DAVID LANE

<p>ASU CAGID</p>	<p>THOMAS FULLER GREGORY NELSON DAVID LANE</p>

RENDERING
OF SEPARATION
OF
FROM 1 M

D

RENDERING
OF
FROM 1 M

FIGURE 1. A 3D rendering of a surface defined by a smooth function $F(p)$ on a domain D . The surface is shown in a perspective view, with the domain D visible in the background. The surface is rendered with a smooth, shaded appearance, and the domain D is shown as a flat, rectangular area.

Given N distinct points $p(i)$ on a closed surface domain D and N real values $F(p)$, the problems we demonstrate are the CONSTRUCTION and DISPLAY of a smooth function $F(p)$ defined on all of D that satisfies $F(p(i)) = f(i)$, for $i=1, \dots, N$. Scientific applications of the construction include representing functions which estimate temperature, pressure, rainfall, ozone etc. at all points on the earth's or space shuttles' surface based only on a discrete sample of measurements. The graphics visualization techniques are useful tools for a scientist to analyze a scalar valued function defined on a closed surface domain. The opaque surface represents the domain D , for example, the earth, apple etc., mushroom, and teapot. The transparent surface represents the function $F(p)$ projected radially from the domain a distance proportional to the magnitude of $F(p)$.

DoE Progress Report for 1989

Stephen H. Watson

Title: Numerical Surface and Volume Integration

Researchers: Robert E. Barnhill and Stephen H. Watson

Description: Traditionally, the computation of surface and volume integrals has been a weak component of geometric modelling systems. We have completed the development and analysis of algorithms for the computation of integrals of scalar-valued functions defined over parametric surfaces and volumes.

Results for the integration of scalar-valued functions defined over parametrically described surfaces such as Coons patches was presented at the 6th Texas Symposium on Approximation Theory, held in January of 1989. Results were also published in the proceedings from that conference, as well as in the Proceedings from the Mathematics of Surfaces III conference held at Oxford, England.

The integration methods were then extended to handle simple triple integrals and volume integrals. We were able to successfully integrate scalar-valued functions defined over trivariate interpolants such as Bernstein-Bezier volumes. The results of both this and the double integration routines were used as the basis of Mr. Watson's Master's Thesis, completed in May of 1989.

These methods have direct application in the computation of fundamental properties of surfaces and volumes used in aeronautical and automotive design, as well as fluid dynamics and other engineering fields. In addition, the surface integration routines were found to be useful (by Mr. C. House) in the testing of various optimal triangulation schemes.

Title: Surfaces Defined on Surfaces

Researchers: Robert E. Barnhill, Suisheng Ou and Stephen H. Watson

Description: For many interpolation problems arising in aeronautics, physics, fluid dynamics, etc., the domain over which the data is located is non-planar. In addition, the data sites are irregularly located, and hence tensor product type methods are not applicable. For such problems, it is necessary to take into account the shape of the domain surface and the irregular nature of the data sites.

We continued work originated by Mr. Suisheng Ou and Dr. Robert E. Barnhill on Surfaces on Surfaces, adapting some of the routines for use on the Ardent supercomputer. Results of these methods (based on triangulations of the surface) and comparison with the Barnhill-Piper method were presented at the SIAM Conference on Geometric Design, held in November of 1989.

We are continuing research into the development of a good surface-on-surface method, and currently are investigating the likelihood of a generalized thin plate spline. The essential concept is that, just as a thin plate spline can be thought of as modeling a thin, flat sheet which is bent so as to interpolate the data, a generalized thin plate spline can be thought of as some arbitrary, although well-defined, surface which is bent to interpolate the data. For example, given a sphere with scattered data points on the surface, a generalized TPS would model a spherical shell which is deformed to fit the data sites. The solution to this problem will involve the use of the Theory of Elasticity and methods from the Calculus of Variations, and we have begun discussions with various individuals in the appropriate fields in order to derive both the proper equations to describe the problem and the methods to solve them.

References

- Barnhill, R. E., Piper, B. R. and Rescorla, K. L., Interpolation to Arbitrary Data on a Surface, in *Geometric Modelling*, G. Farin (ed.), SIAM, Philadelphia, 1987, pp. 281-289.
- Barnhill, R. E. and Ou, S., Surfaces Defined on Surfaces, *CAGD*, 7, 1990.
- Barnhill, R. E. and Watson, S. H., Geometry Processing: Numerical Surface and volume Integration, in *Approximation Theory VI, Volume 1*, C.K. Chui, *et al.* (eds.), Academic Press, 1989.
- Barnhill, R. E. and Watson, S. H., Geometry Processing: Numerical Multiple Integration, in *Mathematics of Surfaces III Proceedings*, to appear.
- Foley, T. A., Lane, D., Nielson, G. M., Franke, R. and Hagen, H., Interpolation of Scattered Data on Closed Surfaces, *CAGD*, 7, 1990.
- Franke, R., Thin Plate Splines with Tension, *CAGD*, 2, North-Holland, 1985, pp. 87-95.
- Kantorovich, L. V. and Akilov, G.P., *Functional Analysis in Normed Linear Spaces*, MacMillan Company, New York, 1964.
- Nielson, G. M., A Method for Interpolating Scattered Data Based upon a Minimum Norm Network, *CAGD*, 4, pp. 41-57.
- Pottman, H. and Eck, M., Modified Multiquadric Methods for Scattered Data Interpolation over a Sphere, preprint. Stroud, A. H., *Approximate Calculation of Multiple Integrals*, Prentice-Hall, Englewood Cliffs, New Jersey, 1971.
- Southwell, R. V., *An Introduction to the Theory of Elasticity for Engineers and Physicists*, Clarendon Press, Oxford, 1936.
- Watson, S. H., *Numerical Multiple Integration with Applications to Computer Aided Geometric Design*, Master's Thesis, Arizona State University, 1989.
- Westergaard, H. M., *Theory of Elasticity and Plasticity*, Harvard University Press, Cambridge, Massachusetts, 1952.

Research Papers and Theses Supported by DoE Grant

Barnhill, R. E., Computer Aided Geometric Design, in Approximation Theory VI volume 1, C. K. Chai et al. (eds.), Academic Press, 1989.

Barnhill, R. E., Bloomquist, B. K., and Worsey, A. J., Optimal degree reduction, in preparation.

Barnhill, R. E. and Foley, T. A., Methods for constructing surfaces on surfaces, 1990, submitted for publication.

Barnhill, R. E. and Kersey, S. N., A Marching Method for Surface-surface intersections, Computer Aided Geometric Design, 7, 1990.

Barnhill, R. E. and Ou, S., Surfaces Defined on Surfaces, Computer Aided Geometric Design, 7, 1990.

Barnhill, R. E. and Watson, S. H., Geometry Processing: Numerical Multiple Integration, in Mathematics of Surfaces III, D. C. Handscomb (ed.) Oxford, 1990.

Barnhill, R. E. and Watson, S. H., Geometry Processing: Numerical Surface and Volume Integration, in Approximation Theory VI, volume 1, C. K. Chui et al. (eds.), Academic Press 1989.

Farin, G., Curvature continuity and offsets for piecewise conics. ACM Transactions on Graphics, 8(2):89-99, 1989.

Farin, G., Rational curves and surfaces. In T. Lyche and L. Schumaker, editors, Mathematical Aspects in CAGD, pages 215-238, Academic Press, 1989.

Farin, G., Surfaces over Dirichlet tessellations. Computer Aided Geometric Design, 7, 1990.

Farin, G., Trends in curve and surface design. Computer Aided Design, 21(5):293-296, 1989.

Farin, G., Hansford, D., and Worsey, A. J., Results on the singular cases for interpolating gamma-splines, Computer Aided Geometric Design, vol. 7, 1990.

Farin, G. and Sapidis, N., Curvature and the fairness of curves and surfaces. IEEE Computer Graphics and Applications, 9(2):52-57, 1989.

Farin, G. and Worsey, A. J., Reparameterization and degree elevation of rational Bezier curves. 1989. submitted for publication.

Foley, T. A., Interpolation of scattered data on a spherical domain, in Algorithms for Approximation II, M. Cox and J. Mason, eds., Chapman and Hall, London, 1989.

Foley, T. A. and Ely, H. S., Surface interpolation with tension controls using cardinal bases, Computer Aided Geometric Design, 6, no. 2, 97-109, 1989.

Foley, T. A., Goodman, T. N., and Unsworth, K., An algorithm for shape preserving parametric interpolation curves with G2 continuity, in Mathematical Methods in CAGD, T. Lyche and L. L. Schumaker, eds., Academic Press, San Diego, 249-259, 1989.

- Foley, T. A., Lane, D. A. and Nielson, G. M., Towards animating ray-cast volume visualization, 1990, submitted for publication.
- Foley, T. A., Lane, D. A., Nielson, G. M., R. Franke and H. Hagen, Interpolation of scattered data on closed surfaces, to appear in Computer Aided Geometric Design 7, 1990.
- Foley, T. A., Lane, D. A., Nielson, G. M. and Ramaraj, R., Visualizing functions on a sphere, IEEE Computer Graphics & Applications 10, No. 1, 32-40, 1990.
- Foley, T. A. and Neuser, D. A., Quintic spline interpolation with shape control parameters, in Approximation Theory VI, Vol. 1, C. K. Chui et al. (eds.), Academic Press, San Diego, 259-262, 1989.
- Foley, T. A. and Nielson, G. M., Knot selection for parametric spline interpolation, in Mathematical Methods in CAGD, T. Lyche and L. L. Schumaker, eds. Academic Press, San Diego, 261-271, 1989.
- Fritsch, F. N. and Nielson, G. M., On the comparison of parametric curves, SIAM Conference on Geometric Design, 1990, in preparation.
- Hamann, B., Farin, G. and Nielson, G., A parametric triangular patch for convex data based on conics, 1990, in preparation.
- Hansford, D., The neutral case for the min-max triangulation, Computer Aided Geometric Design, vol. 7, 1990.
- House, C., Optimal Triangulations, Masters thesis, Computer Science Department, Arizona State University, Tempe, 1989.
- Neuser, D. A., Curve and Surface Interpolation using Quintic Weighed Tau-splines, Master thesis, Computer Science Department, Arizona State University, Tempe, 1988.
- Nielson, G. M., Author of Introduction and Guest Editor of special theme issue on Visualization in Scientific Computing, Computer 22, No. 8, 1989a.
- Nielson, G. M., Affine invariant triangulations, 1989b, submitted.
- Nielson, G. M. and Foley, T. A., A survey of applications of an affine invariant norm, in Mathematical Methods in CAGD, T. Lyche and L. L. Schumaker, eds. Academic Press, San Diego, 445-467, 1989.
- Nielson, G. M. and R. W. Heiland, Interpolation of Rotation Matrices using Quaternions and Splines on a 4D Sphere, ASU Technical Report #90-001, 1990.
- Nielson, G. M. and Shriver, B. (1990), **Scientific Visualization**, IEEE Computer Society Press, to be published in 1990.
- Watson, S. H., Numerical Multiple Integration with Applications to Computer Aided Geometric Design, Master's Thesis, Arizona State University, 1989.
- Worsey, A. J. and Farin, G., Contouring a bivariate quadratic polynomial over a triangle, Computer Aided Geometric Design 7, 1990.

Research Plans for the Coming Year

The scope and objectives of the project will continue as originally proposed.

An overall computing task will be to enhance our utilization of the parallelization and vectorization features of our equipment. Currently, the only way to access the Cray supercomputer at ASU is in "batch" mode. In the summer of 1990, we will be able to access the Cray in an interactive mode. This connection allows us to more effectively use the supercomputer capabilities at ASU.

We shall continue to solicit more data from actual physical problems, such as the gas data, pollution data, and geographical information discussed in this Progress Report

Edited books from the SIAM Geometric Design conference will appear.

Specific plans for research topics include the following.

Multidimensional interpolation

We will make a definitive comparison of surface on surface methods, including the situations of best applicability of each. The trivariate contouring algorithm will be completed. The first trivariate data dependent triangulation algorithms will be developed. The image interpolation method and volume visualization methods will be enhanced and applied to additional problems. We shall apply Farin's modification of Sibson's interpolant to multivariate data and extend Nielson's minimum norm network. The trivariate data dependent triangulations will be investigated and applied to trivariate data. We will also improve upon existing bivariate interpolation methods.

Geometry Processing

Our offset surface algorithms will be further developed in at least two ways: algorithmic ideas from the SIAM Geometric Design conference will be added and parallelization of the geometry will be investigated.

Shape Preserving Interpolation

We will develop tensor product methods that preserve the shape of the data. Shape preserving methods for bivariate scattered data will be investigated.

Multivariate Visualization

The approximate ray-traced volumetric method of Foley, Lane and Nielson will be improved and other approximate visualization techniques will be developed.

Graduate Students with Support from DoE Grant, 1989-90

<u>Name (and academic status)</u>	<u>Topic</u>
Brett Bloomquist (In CS Masters program)	Contours of trivariate surfaces
Todd Frost (In CS Masters program)	Offset surfaces
Bernd Hamann (In CS Doctoral program)	Volume visualization
Dianne Hansford (Completed CS Masters, in CS doctoral program)	Triangulations
Chris House (Completed CS Masters program)	Optimal triangulations
Scott Kersey (Completed Mechanical Engin. Masters program, in Math doctoral program at Wisconsin)	Surface-surface intersections
David Lane (In CS doctoral program)	Surfaces on surfaces
David Neuser (Completed CS Masters program)	Tau splines
Sui-sheng Ou (Completed Math Masters program, in CS Masters program)	Surfaces on surfaces
Stephen Watson (Completed CS Masters program, in CS doctoral program)	Numerical multiple integration

END

**DATE
FILMED**

2 / 12 / 92