DOE/PC/88935--T9

88PC-88935-QTR-12

Received

DEC 8 1991

INHIBITION OF RETROGRESSIVE REACTIONS IN COAL/PETROLEUM CO-PROCESSING

QUARTERLY TECHNICAL PROGRESS REPORT

Reporting Period: July 1, 1991 - September 30, 1991

Harold H. Schobert
Jasna Tomic

November 1991
Contract No. DE-FG22-88PC88935

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INHIBITION OF RETROGRESSIVE REACTIONS IN COAL/PETROLEUM CO-PROCESSING

QUARTERLY TECHNICAL PROGRESS REPORT

Reporting Period: Jul 1, 1991 - September 30, 1991

Harold H. Schobert
Jasna Tomic

November 1991
Contract No. DE-FG22-88PC88935

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

402

NOV 29 1991

TABLE OF CONTENTS

OBJECTIVE.....	1
SUMMARY.....	1
SOLVENT FRACTIONATION OF RESIDS.....	2
GAS CHROMATOGRAPHY AND GAS CHROMATOGRAPHY-MASS SPECTROMETRY ANALYSIS OF PETROLEUM RESIDS.....	3
COAL/RESID REACTIONS.....	10
CONCLUSIONS.....	19
LITERATURE CITED.....	20

OBJECTIVE

The overall objective of this project is to develop a fundamental understanding of the reactions occurring at the onset of coke formation during the co-processing of coals with petroleum residua. The specific objectives include examination of chemical components, or groups of components, in coals and petroleum feedstocks to quantify and rank the effects of these components in retarding or enhancement of coke formation. The work involves bench scale reactions in microautoclaves, supplemented by studies of the carbonaceous residues by such techniques as diffuse reflectance Fourier transform infrared spectroscopy and ^{13}C nuclear magnetic resonance spectrometry.

During this reporting period work focused on Task 4, identification of mechanisms of coke formation. The objective of this task is to identify those compounds or components which are specifically responsible for initiating coke formation. The data obtained in this task will allow for identification of coke precursors and establish a ranking system for predicting compatibility of particular coals and petroleum resids as feedstocks for coprocessing with minimal coke formation.

SUMMARY

The petroleum resids were characterized by solvent fractionation. The three vacuum resids were separated into pentane-insoluble (asphaltenes) and pentane-soluble (maltenes) fractions. The maltenes were subsequently characterized by gas chromatography (GC) and gas chromatography-mass spectrometry (GC/MS). The information from GC/MS and previous NMR spectroscopy was used to identify the type of structures present in these resids. Hondo resid exhibited a strong paraffinic character.

The information about the chemical structure of the petroleum resids was related to the coal conversion data. Petroleum resids are good reaction solvents for coal conversion at 400°C . This is attributed to the resids acting as hydrogen shuttlers, similar to pyrene. The comparison between the model compound/coal data and the petroleum resid/coal data showed that the coal conversions in coprocessing reactions with petroleum resids were similar in value to those in pyrene/coal reactions. Presence of long alkyl chains in petroleum resids tends to decrease the hydrogen shuttling capacity of the resid and decrease the degree of conversion.

Asphaltene content correlated well with coal conversion only at the lower reaction temperatures. At 450° the Blend vacuum resid, which has an intermediate asphaltene content but highest aromaticity, becomes a very poor coal solvent

SOLVENT FRACTIONATION OF PETROLEUM RESIDS

The three petroleum resids (Hondo, Blend, and West Texas) were separated into asphaltenes (toluene-soluble /pentane-insoluble) and maltenes (pentane-soluble) fractions. Approximately 10g of sample was mixed with a small amount of toluene, which was added to facilitate the subsequent mixing of toluene-solubles with n-pentane. The beaker with the sample was warmed in a water bath at 70° C. An excess amount of pentane (1000 ml) was placed in a separate beaker and vigorously stirred. The well mixed resid was slowly added to the stirred pentane and allowed to mix for 15 to 30 minutes. The large beaker was left covered for 1 hour in order to allow the precipitated asphaltenes to settle. The asphaltenes were filtered through a dried cellulose thimble and washed continually with pentane until only solids were left in the thimble. The thimbles containing the asphaltenes were dried in a vacuum oven at 60° C.

The flask with the pentane-solubles was placed in a rotavap at 50° C to remove the solvent. The flask was left under vacuum for another 30 minutes after all the pentane was out in order to remove any residual toluene. Although it is possible that some lighter hydrocarbons can be removed during this prolonged evaporation, it is important to remove the toluene from the pentane-solubles to ensure a good material balance. Residual toluene can also interfere during chromatography because a toluene peak can decrease the relative intensity of the individual constituent compound peaks in the chromatogram.

It should be noted here that some problems were encountered during the solvent fractionation. While separation of Hondo resid into fractions was fairly successful, the separation of West Texas and Blend vacuum resids were not as effective. Hondo resid flows readily at room temperature but the other two vacuum resids do not. The higher viscosity of these resids causes mixing problems. Table 1 compares the asphaltene contents of the petroleum resids as determined in this study and as provided by the suppliers.

Table 1. Asphaltene contents of petroleum resids.

Petroleum resid	Hondo	Blend (FHC571)	W.Texas (FHC470)
Asph.wt%-deter	17.9	21.44	28.2
Asph.wt%-provided	15.9	14.8	0.5

The agreement between the asphaltene content determined in this laboratory and provided by the supplier is best for Hondo resid and worst for West Texas resid. The problem was mainly that these two samples (Blend resid and West Texas) are solid at room temperature and require addition of a greater amount of toluene or better heating before adding the

suspension to excess pentane. Poor mixing between the two phases (pentane and suspension of resid with toluene) possibly resulted in incomplete removal and separation of the pentane-solubles (maltenes) from the pentane-insolubles (asphaltenes). Therefore, the fractionation of all three vacuum resids, in particular of the W. Texas and Blend vacuum resids, will be repeated in order to assess the experimental error.

GAS CHROMATOGRAPHY (GC) AND GAS CHROMATOGRAPHY-MASS SPECTROMETRY (GC/MS) ANALYSIS OF PETROLEUM RESIDS

High resolution capillary column chromatography was used to characterize the petroleum resids using a Perkin-Elmer 8500 Gas Chromatograph. A fused silica capillary column (50% phenylmethyl-50% polysiloxane, 0.25mm i.d. x 30m) was used with He as the carrier gas and flame ionization detector. The column temperature was programmed from 40°C to 280°C at a heating rate of 4°C/min. The maltene fractions were selected for analysis rather than the whole resids since the asphaltenes would not be volatile and would stay in the column. The maltene fractions (pentane-soluble) were diluted in pentane before injection.

The first sample injected was the Hondo maltenes dissolved in pentane. The amount injected was 0.5 µl. The chromatogram of the Hondo pentane-solubles is shown in Figure 1. Visual observation of the chromatogram reveals that this sample contains a series of normal alkanes, as indicated by a series of high-intensity peaks, as well as branched alkanes. The chromatogram of Blend resid indicated a greater amount of compounds in the higher molecular weight eluting much later. Also, not all of the compounds eluted in this case. This could be due to the problems mentioned during solvent fractionation which could have caused some of the pentane-insolubles to be found in the pentane-soluble fractions. A more careful separation of the original sample will be performed in the future to ensure more reliable chromatograph results.

The Hondo pentane-solubles were in addition analyzed by gas chromatography-mass spectrometry (GC/MS) on a Hewlett-Packard 5890 interfaced with a HP 5971A Mass Selective Detector. The column was heated from 40° to 280°C at a rate of 8°/min during the analysis.

Figure 2 shows the total ion chromatogram (TIC) obtained from GC/MS analysis of Hondo pentane-solubles. The most obvious observation is the characteristic n-alkane pattern. Selected specific ion chromatograms are shown in Figures 3-5. The specific ion chromatogram of m/z 71 is indicative of normal alkanes. The peaks in the specific ion chromatogram correspond well to the peaks in the TIC indicating that this sample is rich in

long chain paraffins. Normal alkanes from C₁₂ to C₃₂ were identified with the most prominent peaks for C₁₅ and C₁₆. The specific ion chromatogram of m/z 83, representative of cycloalkanes, shows that the concentration of cycloalkanes is low in this sample. The concentration of aromatic structures was estimated by observing the peaks in the specific ion chromatograms of m/z 91 (alkylbenzenes), m/z 141 and 156 (naphthalenes), and m/z 165 (fluorenes). The relative abundance of the peaks implies that the concentration of two-ring aromatics is higher than of aromatic structures whose ring size is higher than two.

Combining the information from GC/MS with the previous information gained from NMR analysis, we can estimate some groups of chemical components of Hondo resid. Proton NMR information indicated that Hondo resid has close to 92% aliphatic hydrogens which are predominantly paraffinic. ¹³C NMR data showed that the carbon aromaticity of Hondo resid is 25.4% and the atomic ratio of aromatic hydrogen and carbon is 0.54 which is assumed to indicate ring condensation. Of all the three resids, Hondo probably has the smallest concentration of conjugated aromatic structures or the number of rings in the condensed aromatics is lower than in the other two samples. Indeed, the GC/MS results of the pentane-soluble fraction of Hondo confirm: 1) the high concentration of paraffins and 2) that the aromatics in the pentane-solubles are predominantly two ring structures. Since most of the higher molecular weight components are concentrated in the asphaltene fractions, it is necessary to analyze the asphaltene fraction separately. We plan to characterize the asphaltene by NMR and perhaps pyrolysis/GC/MS in order to develop a more complete picture of the chemical structure of the whole resid. It should be noted that the GC and GC/MS results are important as a qualitative technique primarily. In terms of quantitative measurements, it is used as a relative technique comparing the concentration of chemical components in the three resid samples.

Figure 1. Capillary gas chromatogram of Hondo pentane-solubles.

File: D:\DATA\HOND5.D
Operator: JASNA
Date Acquired: 2 Nov 91 12:01 pm
Method File: JASNA.M
Sample Name: HONDO MALT 5%
Misc Info: NOV2,91
ALS vial: 1

Figure 2. GC/MS total ion chromatogram (TIC) of Hondo pentane-solubles.

File: D:\DATA\HOND5.D
Operator: JASNA
Date Acquired: 2 Nov 91 12:01 pm
Method File: JASNA.M
Sample Name: HONDO MALT 5%
Misc Info: NOV2,91
ALS vial: 1

Figure 3. Specific ion chromatogram of Hondo pentane-solubles.

File: D:\DATA\HOND5.D
Operator: JASNA
Date Acquired: 2 Nov 91 12:01 pm
Method File: JASNA.M
Sample Name: HONDO MALT 5%
Misc Info: NOV2,91
ALS vial: 1

Figure 4. Specific ion chromatograms of Hondo pentane-solubles.

File: D:\DATA\HOND5.D
Operator: JASNA
Date Acquired: 2 Nov 91 12:01 pm
Method File: JASNA.M
Sample Name: HONDO MALT 5%
Misc Info: NOV2,91
ALS vial: 1

Figure 5. Specific ion chromatogram of Hondo pentane-solubles.

COAL/RESID REACTIONS

Additional microautoclave reactions were performed with Hondo resid and the project coals thus completing the reactions at 30 minutes with all the coal/resid pairs at the three reaction temperatures (350°, 400°, and 450° C) and two atmospheres (N₂ and H₂).

Table 2. Total coal conversion results for coal/resid reactions at 30 minutes.

Resids	350°	400°	450°	350°	400°	450°
	N ₂			H ₂		
	PSOC 1488					
Hondo	17.61	28.63	6.86	5.46	27.29	9.93
Blend	17.73	28.46	3.45	17.35	31.32	-13.54
W.Texas	14.81	28.87	19.31	19.95	33.03	16.99
	PSOC 1498					
Hondo	12.41	22.53	3.21	7.88	22.79	48.68
Blend	11.41	24.83	0.17	11.56	27.93	-2.7
W.Texas	9.92	23.61	21.08	16.5	26.82	12.83
	PSOC 1501					
Hondo	14.99	29.92	13.4	13.36	28.89	12.41
Blend	12.36	29.5	-0.39	14.75	31.75	20.99
W.Texas	15.2	29.51	26.91	20.89	31	25.85
	PSOC 1504					
Hondo	19.14	36.54	16.53	17.38	31.30	16.66
Blend	13.73	31.94	2.54	16.48	33.94	-7.76
W.Texas	13.36	33.66	26.99	14.73	31.98	28.91
	PSOC 1448					
Hondo	17.33	31.87	14.37	16.45		15.26
Blend	16.24	33.85	-0.46	14.07	32.78	6.88
W.Texas	17.5	32.35	25.99	15.26	36.39	29.05

The conversions in Table 2 are calculated on basis of THF-insoluble yield.

$$\text{Yield THF-insol (\%)} = \frac{[\text{THF-insol-ash} - (\text{THF-insol/g resid} * \text{wt. resid})]}{\text{coal daf}} \times 100$$

$$\text{Conversion (\%)} = 100 - \text{Yield THF-insol}$$

Best conversions are at a reaction temperature of 400° C for all coal/resid pairs, disregarding the value 48.68 % at 450° C for Hondo resid and PSOC 1498, which is probably an experimental error and will be repeated. The conversions at the lower temperature (350°C) are in the range from 10 to 20 % depending on the coal/resid pair. At 350°C in a nitrogen atmosphere the coal conversions in reactions with Hondo resid seem to be higher (or at least equal) to coal conversions achieved with the other two resids. When hydrogen is used instead of nitrogen (the temperature remaining the same) the efficiency of Hondo as a good solvent for coal conversion decreases. A similar effect is observed when the data for reactions in nitrogen and hydrogen at 400°C are compared. Figures 6 and 7 show the change of coal conversion with different resids at three reaction temperatures and under a nitrogen and hydrogen atmosphere. For comparison, the results of the coal blank experiments are shown on the same graphs.

In the model compound studies we concluded that the coal conversion results can be related to the type of chemical structures present in the model solvent [1]. Namely, in the model compound studies we observed that coal conversions were highest when pyrene was used as a solvent. Pyrene was found to be a more effective reaction solvent for coal than the compounds containing long alkyl chains (eicosane and 1-phenyldodecane) or compounds containing short alkyl chains (1,4-diisopropylbenzene and durene). At a reaction temperature of 400°C the presence of model compounds containing alkyl chains in the system increased the conversion, compared to coal blank reactions (in the absence of a solvent) by 1-2% and in the reactions with some of the project coal the conversion decreased. In a hydrogen atmosphere (same reaction temperature) the conversions did not improve when these solvents were used. These observations indicate that a strong paraffinic character of a solvent does not promote higher degree of coal conversion.

The similarity of the results of reactions pyrene/coal and petroleum resid/coal imply that petroleum resids interact with the coal via a similar mechanism. Polyaromatic structures like pyrene are good hydrogen shuttlers. In a system deficient in donatable hydrogens, pyrene will transfer hydrogen from the solvent (or from a hydrogen rich part of the coal) to the coal radicals. In a hydrogen atmosphere the conversions will be higher because the hydrogen is transferred from the gas to the reactive radicals.

It has been reported that petroleum resids act as hydrogen shuttlers rather than hydrogen donors [2]. The aromatic compounds present in petroleum resids can act as hydrogen shuttlers therefore giving conversions on the order of those with pyrene. The aromaticity of the three petroleum resids is 25.4, 28.2, and 32.3% for Hondo, W.Texas, and Blend vacuum resid respectively, as determined by NMR spectroscopy.[3]. The degree of ring condensation was estimated by an atomic ratio of aromatic hydrogen to carbon and

increased in the same order as the aromaticity; Hondo - 0.54, W. Texas- 0.46, and Blend- 0.42. Conversions of resid/coal pairs containing W. Texas and Blend vacuum resids showed a slight increase compared to conversions involving Hondo resid at 350° and 400°C. This increase was more significant in a hydrogen atmosphere when the more aromatic resids (W. Texas and Blend) were used. This was not the case for the systems with Hondo resid. It was shown from the NMR and GC/MS analysis that this particular resid contains long chain paraffins and aromatic structures in the maltenes which are predominantly two ring. Therefore, it can be said that W. Texas and Blend vacuum resid exhibit higher hydrogen shuttler capability than Hondo resid due to their higher aromaticity and greater ring condensation.

We also reported previously that at 450° C the coal conversions were negative regardless of the coal/petroleum resid pair. Correcting the data mainly for the the amount of insolubles produced from the resid alone, it is seen that really negative conversion occurs only in several, rather than all, cases. Table 2 shows that all of the negative conversions are observed in reactions with Blend vacuum resid (FHC 571) at 450°C reaction temperature.

Correlation of the asphaltene content of the resids and coal conversion was evaluated. Figures 8 - 11 show selected graphs correlating the conversion with the asphaltene content of the petroleum resids at different temperatures and gas atmospheres. The correlation is linear, and conversion slightly increases as the asphaltene content of the resid increases (Hondo: 17.9wt%; Blend: 21.44;wt% W. Texas: 28.2wt%) for reaction temperature 350° and 400°C. This relationship does not hold when the temperature of reaction is 450°C. Figure 11 clearly shows a drop in coal conversion as the asphaltene value increases from 17.7% (Hondo) to 21.44% (Blend). Asphaltenes probably do play an important role during coprocessing reactions but a simple relationship with the asphaltene content is not obvious. Chemical components of asphaltenes rather than the asphaltenes as a whole influence coal conversion.

In light of the discussion about the pyrene-like behavior of petroleum resids, it is more likely to expect the aromatic part of asphaltenes, and in particular their structure, to have an influence on the interaction between the petroleum resid and coal. It has been reported in the literature that a minimum aromatic proton content of asphaltenes is necessary for significant coal conversion degree [4].

The most important observation is the significant difference in conversion levels depending on the resid feedstock. The range of coal conversion for reactions at 450°C has increased significantly compared to the two lower reaction temperatures.

Figure 6. Temperature dependence of coal conversion for coal PSOC 1501 with petroleum resid under a nitrogen and hydrogen atmosphere.

Figure 7. Temperature dependence of coal conversion for coal PSOC 1504 with petroleum resid under a nitrogen and hydrogen atmosphere.

Figure 8. Coal conversion vs asphaltene content of petroleum resid (350°C; H₂)

Figure 9. Coal conversion vs asphaltene content of petroleum resid (400°C; H₂)

Figure 10. Coal conversion vs asphaltene content of petroleum resid (450°C; H₂)

Figure 11. Coal conversion vs asphaltene content of petroleum resid (450°C; N₂)

CONCLUSIONS

The GC/MS results of the Hondo pentane-solubles indicate that the maltene fraction of this resid contains predominantly long chain paraffins. The aromatic portion of the Hondo maltenes appear to be mostly two ring aromatic structures.

The aromatic compounds in petroleum resids can act as hydrogen shuttlers. This is confirmed by the similar coal conversion values for the reactions with resids and reactions with pyrene, a known hydrogen shuttler. Therefore, it can be said that petroleum resids contain pyrene-like structures which promote coal conversion.

Most of the aromatics are concentrated in the asphaltene fraction. When the coal conversion data is related to the asphaltene content of the resids, an increase in degree of conversion is observed as the asphaltene content increases when the reaction temperatures is below 450°C. At this higher temperature of reaction the asphaltenes probably undergo some changes so the dependance of coal conversion on the asphaltene content is not linear. The reactions at 350° and 400°C have conversion values similar regardless of the coal/resid pair used. The reactions at 450°C are much more sensitive on the feedstock composition.

LITERATURE CITED

- [1] Schobert, H.H., J.Tomic, D. Moyer and, J. McConnie, "Inhibition of Retrogressive Reactions in Coal/Petroleum Co-processing" U.S.DO.E. Report, No. 88PC-88935-QTR-7, 1990.
- [2] Rahimi,P.M., W.H. Dawson, and J.F.Kelly, *Fuel*, Vol.70, p.95, 1991.
- [3] Schobert, H.H., J.Tomic, "Inhibition of Retrogressive Reactions in Coal/Petroleum Co-processing" U.S.DO.E. Report, No. 88PC-88935-QTR-11, 1991.
- [4] Wallace, S.,K.D.Bartle, M.P.Burke, B.Egia, S.Lunt, S.Lu, N.Taylor, T.Flynn, W.Kemp, and W. Steedman, *Fuel*, Vol.68, p.961, 1989.

END

**DATE
FILMED**

02/13/92

I