2
DOE/PC/90309--5

DE92 008181

DOE/PC/90309-5

ANION-EXCHANGE RESIN-BASED DESULFURIZATION PROCESS

Quarterly Technical Progress Report

October 1, 1991 - December 31, 1991

Prepared by:

**Atul C. Sheth
Sterling D. Strevel**

**The University of Tennessee Space Institute
Tullahoma, Tennessee 37388**

DOE Grant No. DE-FG22-90PC90309

MASTER

US/DOE Patent Clearance is not required prior to the publication
of this document.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE OF CONTENTS

	<u>Page</u>
Executive Summary	1
1.0 Introduction	2
2.0 Objectives and Project Description	2
3.0 Project Status/Progress to Date	3
3.1 Task 1.1	3
3.2 Task 1.2	3
3.3 Task 1.4	6
3.4 Task 1.5	15
4.0 Plans for Next Reporting Period	16
5.0 Summary	16
6.0 References	17

LIST OF FIGURES

1.	Milestone Schedule and Status Report	4
2.	Milestone Log	5

LIST OF TABLES

1.	IRA-68 Capacities by Batch and Fixed-bed Experiments	6
2.	Resin and Concentration Effects on Exhaustion Efficiency	7
3.	Resin and Concentration Effects on Regeneration Efficiency	8
4.	Resin and Cycle Effects on Exhaustion Efficiency	9
5.	Resin and Cycle Effects on Regeneration Efficiency	9
6.	Resin and Counter-ion Effects on Exhaustion Efficiency	10
7.	Resin and Counter-ion Effects on Regeneration Efficiency	10
8.	Resin and Seed Effect on Exhaustion Efficiency	11
9.	Resin and Seed Effect on Regeneration Efficiency	11
10.	Parameter Effects on Exhaustion and Regeneration Efficiencies	12
11.	Parameter Importance Ratings	13
12.	Calculated Resin Utilities	15

EXECUTIVE SUMMARY

Under the DOE Grant No. DE-FG22-90PC90309, the University of Tennessee Space Institute (UTSI) is contracted to further develop its anion-exchange, resin-based desulfurization concept to desulfurize alkali metal sulfates. From environmental as well as economic viewpoints, it is necessary to remove soluble sulfates from the wastes created by flue gas desulfurization systems. In order to do this economically, a low-cost desulfurization process for spent sorbents is necessary. UTSI's anion-exchange resin-based desulfurization concept is believed to satisfy these requirements.

During this reporting period, October 1, 1991 - December 31, 1991, both statistical and multiattribute analyses were performed on the results from the batch mode screening experiments. The results support our selection of IRA-68, IRA-35, and IRA-93 resins for the process variables study. The preliminary experiments necessary to develop a valid fixed-bed procedure are in progress. The results obtained so far show a marked deterioration in the equilibrium capability of the IRA-68 resin batch procured from previous studies. A fresh batch of IRA-68 resin has been ordered.

There were some unforeseen problems experienced during the shakedown experiments with the modified fixed bed unit. This has resulted in the project being about four weeks behind the schedule. However, by including help from a second graduate research assistant (GRA) during the quarter, we plan to regain the schedule during the next quarter.

3.0 PROJECT STATUS/PROGRESS TO DATE

The progress made during the period October 1, 1991 - December 31, 1991, is indicated in Figures 1 and 2. Figure 1 shows the proposed schedule and the progress to date for each task. Figure 2 lists the major milestones to be accomplished under each task and their planned and actual completion dates. Activities carried out under each task are as follows:

3.1 Task 1.1

Bench scale screening tests for the candidate resins as well as preliminary selection of the three leading resins for further process variables study were completed in the previous quarter. To support our selection of these three resins, additional statistical analyses were carried out. These analyses as well as the resulting conclusions are reported as part of the Task 1.4 activities.

3.2 Task 1.2

During the batch mode screening experiments the calculated equilibrium capacity of the IRA-68 resin was found to be less than the expected value. The possible deterioration of this IRA-68 resin batch was confirmed during the shakedown experiments with the modified fixed-bed unit. Table 1 lists the calculated equilibrium capacities for the IRA-68 resin from the batch experiments and the fixed-bed preliminary runs. The manufacturer reported equilibrium capacity for the IRA-68 resin is about 0.08 gm SO_4^{2-} /ml resin. Butler⁽¹⁾ and Modeste⁽²⁾ both were able to reach and/or exceed this value in their work. The difference in the equilibrium capacities found in the present work is possibly contributed by the channeling in the bed and/or further

Milestone Schedule and Status Report

Contract Identification		ANION - EXCHANGE RESIN - BASED DESULFURIZATION PROCESS		Reporting Period October 1, 1991 - December 31, 1991		Grant Number DE-FG22-90PC90309						
Contractor: Name, Address		THE UNIVERSITY OF TENNESSEE SPACE INSTITUTE TULLAHOMA, TENNESSEE 37388		Contract Start Date September 1, 1990		Contract Completion Date August 1993						
ID	Reporting Category - Contract Line Item or Work Breakdown Structure Element	CY 90	I	CY 91	I	CY 92	CY 93					
		O	N	D	J	F	M	A	M	J	J	A
1.0	LITERATURE SURVEY, VENDOR CONTACTS & SCREENING TESTS											
2.0	PROCESS VARIABLES STUDY & IMPROVING RESIN PERFORMANCE											
3.0	OPTIMIZATION OF RESIN REGENERATION STEP AND EVALUATION OF PERFORMANCE ENHANCERS											
4.0	DEVELOPMENT OF BEST PROCESS SCHEMATIC & RELATED ECONOMICS											
5.0	PROJECT MANAGEMENT AND REPORTING											
COMMENTS		<div> PLANNED COMPLETED RESCHEDULED </div>										
Signature of Contractor's Project Manager & Date												

MS-0038

Figure 1.

[illegible]

5

contamination of the resin. The channeling in the fixed bed may be caused by the increased superficial velocity.

Table 1. IRA-68 Capacities by Batch and Fixed-bed Experiments

<u>Solution Concentration</u> (ppm as K ₂ SO ₄)	<u>Equilibrium Capacity (gm SO₄²⁻/ml resin)</u>	
	<u>Batch</u>	<u>Fixed-Bed</u>
1000	0.002	
25000	0.035	
50000	0.050	0.019

During the shakedown experiments and procedure development work with the modified fixed bed unit, several minor problems were experienced and we believe that they have been solved successfully. Some of these problems include:

- contamination of resin resulting from brass soldering used in fabrication of the stainless steel storage tanks.
- leaking of CO₂ from flanged connections of the fixed bed units, and
- channeling in the fixed bed.

Most of these problems have been solved or will be solved as we finalize our fixed bed experimental procedure and acquire a fresh batch of the IRA-68 resin.

3.3 Task 1.4

Statistical Analysis

The analysis of variance, two-way fixed-effects model was used to determine the effects of resin type, concentration, cycles, and counter-ions on the resin's removal and regeneration efficiencies⁽³⁾. The values used in these calculations were the first

observations taken for each resin and test condition. The batch experimental procedure was developed before the first observation was made. Therefore, there was no learning curve associated with the results, which frees the data of any bias. Due to time constraints, only one observation was taken. This weakens the statistical results and combines the interaction (C-N-R) and error terms. Therefore, no interaction effect or error can be determined from the data. The test statistic is f_0 , which is the mean square resin or concentration divided by the mean square interaction. This test statistic follows the F distribution. Therefore, the ratios will be compared with values taken from a F distribution table with a 95 percent confidence level that the null hypothesis is true, when it is true. The null hypothesis is that none of the above factors affect the exhaustion or the regeneration efficiency. When the f_0 and the F distribution table values are relatively close in magnitude, the conclusion drawn from the analysis should be conditional. If the f_0 is less than the F distribution table value then there is no effect.

Table 2 details the data and calculations for the effects of solution concentration (1k, 25k, and 50k ppm K_2SO_4) and resin type on the exhaustion efficiency.

Table 2. Resin and Concentration Effects on Exhaustion Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,9,18}$ <u>$F_{0.05,2,18}$</u>	<u>Conclusion</u>
Resin Type	11.912	2.46	Yes
Solution Concentration	129.717	3.55	Yes

In Table 2 the comparison of the test statistic with the appropriate value from a F distribution table shows that the resin type and solution concentration definitely affect the removal efficiency. Based on ion exchange theory, increasing solution concentration should have an effect on the resin performance.

Table 3 deals with the effect of resin type and solution concentration on the regeneration step of the batch procedure. (The percent retained is 100 minus the regeneration efficiency.) In Table 3 the only effect on regeneration efficiency is due to the resin type. The amount of sulfate ion removed during the corresponding exhaustion step may have an effect on the regeneration efficiency. The theoretical conclusion is that there could be an effect of solution concentration on the regeneration efficiency. This uncertainty is due, at least in part, to the lack of multiple observations for each run.

Table 3. Resin and Concentration Effects on Regeneration Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,9,18}$ <u>$F_{0.05,2,18}$</u>	<u>Conclusion</u>
Resin Type	15.237	2.46	Yes
Solution Concentration	3.039	3.55	May be

Tables 4 and 5 deal with the effect of resin type and cyclic operation (4 cycles) on the exhaustion and regeneration efficiency. The solution concentration used is 25K ppm K_2SO_4 . As in Tables 2 and 3, Table 4 contains the data for each run and the fixed effects model calculations. Table 4 shows that there is definitely an effect due to resin type on exhaustion efficiency. Also in Table 4 the analysis leads to the conclusion that

4 consecutive cycles of exhaustion and regeneration do not affect the exhaustion efficiency. This is expected for commercial resins.

Table 4. Resin and Cycle Effects on Exhaustion Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,10,30}$ <u>$F_{0.05,3,30}$</u>	<u>Conclusion</u>
Resin Type	82.377	2.16	Yes
Cyclic Operation	0.244	2.92	No

Table 5 deals with the effect of resin type and cycles on the regeneration efficiency. In Table 5 the results from the fixed-effects calculations imply that both the resin type and exhaustion-regeneration cycles affect the regeneration efficiency. In some resins this means that the resin regeneration performance improves. In other cases the regeneration performance either deteriorates or does not show a conclusive effect. Theoretically the regeneration performance for four consecutive cycles should either increase or remain constant. This inconsistent behavior is probably due to the lack of multiple observations.

Table 5. Resin and Cycle Effects on Regeneration Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,10,30}$ <u>$F_{0.05,3,30}$</u>	<u>Conclusion</u>
Resin Type	7.681	2.16	Yes
Cyclic Operation	15.170	2.92	Yes

Tables 6 and 7 deal with the effects of resin type and counter-ion on the exhaustion and regeneration efficiency. The solutions used were 25k ppm K_2SO_4 and

20.4k ppm Na_2SO_4 (equimolar SO_4^{2-} solutions). These solutions contain the same molar concentration of sulfate ion. Table 6 gives the percent removal data and shows that there is definitely an effect of resin type on percent removal. The analysis also implies that there may be an effect from different counter-ions because two statistic values are close. However, we believe that based on ion-exchange chemistry no effect should exist and that more observations would support this conclusion.

Table 6. Resin and Counter-ion Effects on Exhaustion Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,4,4}$ <u>$F_{0.05,1,4}$</u>	<u>Conclusion</u>
Resin Type	255.053	6.39	Yes
Counter-ion	7.224	7.71	May be

Table 7 lists the percent retained and analysis of variance results. Here, the resin type definitely show an effect on the regeneration efficiency. The counter-ion, however, has no effect on the percent retained. Obviously this would be true because no counter-ion except ammonium ion is present in the regeneration step.

Table 7. Resin and Counter-ion Effects on Regeneration Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,4,4}$ <u>$F_{0.05,1,4}$</u>	<u>Conclusion</u>
Resin Type	40.717	6.39	Yes
Counter-ion	0.928	7.71	No

In Tables 8 and 9, the effect of a pure 50k ppm K_2SO_4 , spent seed from the MHD baghouse/ESP, and resin type on the exhaustion and regeneration efficiencies

are determined. The seed for simplicity will be considered another potassium sulfate source. Table 8 shows that there is definitely an effect due to resin type, however, there is no effect due to source of potassium sulfate.

Table 8. Resin and Seed Effect on Exhaustion Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,4,4}$ <u>$E_{0.05,1,4}$</u>	<u>Conclusion</u>
Resin Type	81.573	6.39	Yes
Potassium Sulfate Source	0.371	7.71	No

In Table 9 the analyses of variance and fixed-effects calculations were performed for the 50k ppm K_2SO_4 , spent seed solutions and resin type to determine the effect on the percent retained. Again the seed is considered as another potassium sulfate source. The resulting effect of the resin type and the seed (source of potassium sulfate) on the regeneration efficiency is shown in this table. The only parameter that affects the percent retained is the resin type. The seed has no effect.

Table 9. Resin and Seed Effect on Regeneration Efficiency

<u>Effect</u>	<u>Test Statistic, f_0</u>	$F_{0.05,4,4}$ <u>$E_{0.05,1,4}$</u>	<u>Conclusion</u>
Resin Type	12.088	6.39	Yes
Potassium Sulfate Source	1.324	7.71	No

In summary, the exhaustion and regeneration efficiencies are not affected by the same parameters. The only exception to this statement is resin type, which strongly affects both the exhaustion and regeneration efficiencies. The exhaustion

efficiency is affected by the resin type and the solution concentration. The regeneration efficiency is affected by the resin type and the cycling between the exhaustion and regeneration steps. Table 10 lists all the parameters that affect the exhaustion and regeneration efficiencies.

Table 10. Parameter Effects on Exhaustion and Regeneration Efficiencies

<u>Parameter</u>	<u>Efficiency</u>	
	<u>Exhaustion</u>	<u>Regeneration</u>
Resin Type	Yes	Yes
Solution Concentration	Yes	No
Cyclic Operations	No	Yes
Counter-ion	No	No
Spent Seed*	No	No

* Source of potassium sulfate

Multiattribute Analysis

Multiattribute analysis involves the use of an importance rating and a utility scheme to determine the best of several alternatives. For the data from the batch experiments, the scheme developed is one which considers the percent removal as the most important result. The importance of the resin's performance for each test condition has also been established. Table 11 lists the importance ratings in two columns. The first column lists the importance of each parameter. The second column lists the importance of the attributes contained within each parameter. These ratings were arbitrary chosen to provide more importance to factors such as high solution concentration and cyclic operations. The reason for such a choice is that the resin

selected finally must be able to handle the high solution concentrations and repeated use for an extended time period.

Table 11. Parameter Importance Ratings

<u>Parameter Rating</u>		<u>Attribute Rating</u>	
Concentration	0.3	Removal	0.6
Cyclic Operation	0.3	Retained	<u>0.4</u>
Counter-ion	0.2		1.0
Seed	<u>0.2</u>		
	1.0		

The data presented in Tables 2 through 9 were used in the determination of the respective importance ratings. The exhaustion and regeneration efficiencies were averaged to give a number which corresponds to the resin's ability to handle concentration changes. Likewise, the exhaustion and regeneration efficiencies were averaged to give a number which corresponds to the resin's ability to handle repeated cycles of exhaustion and regeneration. In Tables 6 and 7 the percent removal and retained were averaged to give weights for the resin's susceptibility to counter-ion interference. The values associated with the spent seed solution were used as the weights which correspond to the resin's ability to be fouled by soluble impurities.

For each of the parameters listed in Table 11, their individual utilities were calculated using the additive utility model given by(4)

$$U_P = \sum_{A=1}^n k_A U_A \quad (1)$$

Where, U_p is the utility of the parameter, and k_A is the importance rating for the attribute. U_A is the utility of the attribute. The utility of each resin is then calculated using

$$U_R = \sum_{p=1}^4 k_p U_p, \quad (2)$$

where U_R is the utility of the resin and k_p is the importance rating of the parameter.

The attribute's utility functions for the interval between 0 and 1 are

$$U_{A_{rm}} = 1 - \sqrt{1 - x^2} \quad (3)$$

and

$$U_{A_{rt}} = 1 - \sqrt{1 - (x-1)^2}, \quad (4)$$

where

$$x = \frac{X_A - X_l}{X_f - X_l}. \quad (5)$$

X_A is either the percent removed or retained, X_l is the beginning of the interval, and X_f is the end of the interval. For the percent removal X_l and X_f are 0 and 100, respectively. These values for the percent retained are reversed. These utility curves were chosen to give more importance to those values closer to 100 for percent removed and to those values closer to zero for percent retained.

The calculated resin utilities are given in Table 12. As can be seen the values are not orders of magnitude different. But there is enough of a difference to be

reasonably certain that the leading candidates are the IRA-68, IRA-35, IRA-93 resins, and the unspecified Culligan resin. Since Culligan would not provide adequate information on the resin, it was dropped from further consideration. Therefore, the three candidate resins for the process variable study are IRA-68, IRA-35, and IRA-93, as previously identified and reported by us.

Table 12. Calculated Resin Utilities

<u>Resin</u>	<u>Utility</u>
IRA-68	.26
IRA-35	.21
IRA-93	.12
IRA-94	.08
A-7	.02
A-365	.03
MWA-1	.07
LVGR-2	.10
AFP-329	.01
A-305	.10
UNKNOWN	.12

3.4 Task 1.5

The following activities were completed under this task.

- The annual technical progress report (report no. DOE/PC/90309-4) covering the performance period from August 9, 1990 - September 30, 1991 was issued on October 11, 1991.
- We received a verbal instruction (telephone call) from Dr. Soung Kim (PETC Technical Program Officer) asking for an informal halfway progress review during May 1992. Dr. Kim plans to send an official letter about this review in March 1992.

To date the project is about four (4) weeks behind schedule. The major reasons for this delay are: holiday periods, unforeseen problems during shakedown experiments, and possible contamination of the existing IRA-68 resin batch. We plan to include help from a second graduate research assistant. With the two students' efforts this slight delay will be overcome readily.

4.0 PLANS FOR THE NEXT REPORTING PERIOD

During the next reporting period the fixed-bed experimental procedure and the process variables study are planned for completion. The review of the articles obtained from the literature search will also be completed, and the preparation of the M.S. thesis will be started.

5.0 SUMMARY

The work performed during this period is summarized as follows:

- The statistical and the multiattribute analyses were completed. The results support the tentative conclusions drawn and reported in our earlier reports.
- Initial experiments were carried out on the modified fixed-bed system. The experimental procedure is being tested with results from Butler's and Modeste's work, and necessary modifications are being made to the equipment or procedure.

At the present time the project is about four weeks behind schedule but still within budget.

6.0 REFERENCES

1. Butler, W. A., "Bench Scale Evaluation of Anion-Exchange Resin-Based Seed Regeneration Concept for Coal-Fired Magnetohydrodynamics Power System," a thesis presented for M. S. degree, The University of Tennessee Space Institute, December 1986.
2. Modeste, D. C., "Evaluation of Improved Anion-Exchange Resin-Based Seed Regeneration Concept for Coal-Fired MHD Power System," a thesis presented for M. S. degree, The University of Tennessee Space Institute, December 1988.
3. Hines, William W. and Montgomery, Douglas C., Probability and Statistics in Engineering and Management Science, Wiley, New York, 1990.
4. Canada, John R. and Sullivan, William C., Economic and Multiattribute Evaluation of Advanced Manufacturing System, Prentice Hall, New Jersey, 1989.

END

**DATE
FILMED**

3 / 24 / 92