2.
DOE/PC/90098--T7

DEC 28 1992

DOE/PC/90098--T7

DE93 004938

PREDICTIVE MODELLING OF BOILER FOULING

QUARTERLY TECHNICAL PROGRESS REPORT

FOR THE PERIOD
April 1, 1992 - June 30, 1992

Prepared by:

Textron Defense Systems
2385 Revere Beach Parkway
Everett, Massachusetts 02149

Prepared for:

U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania 15236

Under Contract No. DE-AC22-90PC90098

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
jrz

1.0 PROGRAM OBJECTIVE AND SCOPE OF WORK

The primary objective of this work is the development of a comprehensive numerical model describing the time evolution of fouling under realistic heat exchanger conditions. As fouling is a complex interaction of gas flow, mineral transport and adhesion mechanisms, understanding and subsequently improved controlling of fouling achieved via appropriate manipulation of the various coupled, nonlinear processes in a complex fluid mechanics environment will undoubtedly help reduce the substantial operating costs incurred by the utilities annually, as well as afford greater flexibility in coal selection and reduce the emission of various pollutants. In a more specialized context, the numerical model to be developed as part of this activity will be used as a tool to address the interaction of the various mechanisms controlling deposit development in specific regimes or correlative relationships. These should prove of direct use to the coal burning industry.

The Statement of Work comprises a series of related and logically structured tasks described as follows:

Phase I

Task 1

Perform semi-quantitative evaluations of solution and algorithmic details of Higher Level Simulation (HLS) techniques applicable to flow in and around a tube bundle.

Task 2

Assess (quantitatively) HLS predictions for flow and turbulence characteristics of related, simpler problems.

Task 3

Reformulate the algorithm to predict flow details around a cylinder in an isothermal, but otherwise representative environment.

Task 4

Predict heat transfer characteristics for the problem in Task 3.

Task 5

Generalize the algorithm to predict flow, turbulence and heat transfer details for multi-tube configurations including in-line and staggered arrangements.

Task 6

Provide project management and financial control with the required technical and financial reports and documentation.

Phase II

Task 1

Develop an appropriate multi-phase, multi-species transport algorithm for a "frozen" gas aerothermal field.

Task 2

Develop sub-modules for surface related processes including adherence and removal.

Task 3

Provide project management and financial control with the required technical and financial reports and documentation.

Phase III

Task 1

Extend the algorithm to couple multi-species, multi-phase transport and deposition models with a comprehensive HLS of flow and heat transfer in a tube bundle for a representative case.

Task 2

Perform pertinent parameter variation studies and develop improved engineering correlations to model fouling in practical boiler configurations and operating environments.

Task 3

Provide project management and financial control with the required technical and financial reports and documentation.

2.0 SUMMARY OF PROGRESS TO DATE

In this reporting period, efforts were continued to supplement the comprehensive flowfield description obtained from the RNG-Spectral Element Simulations by incorporating, in a general framework, appropriate modules to model particle and condensable species transport to the surface. Specifically, attention was focussed on describing particle-surface interaction and related phenomena and the nature of surface topography in influencing deposition patterned for the tube banks.

Regarding the former topic, experimental measurement of the restitution coefficient is difficult, but the information is necessary for solving the equations governing the trajectories of particles rebounding from surfaces and subsequently striking the surface again. The data are generally provided as least square fits to polynomial functions of the form:

$$\frac{V_2}{V_1} = a + b\beta_1 + c\beta_1^2 + \dots \quad (1)$$

$$\frac{\beta_2}{\beta_1} = a' + b'\beta_1 + c'\beta_1^2 + \dots$$

where V_1 and β_1 are the particle incidence speed and angle and V_2 and β_2 the corresponding rebound values, β_1 and β_2 measured relative to the target to the surface at the input location, in the V_1 - V_2 plane. The numerical values of the coefficients a , b , c , etc. in Equation 1 depend on the material properties of the specific particle surface pair. Similar data for the rotation velocities of particles rebounding from surfaces apparently are unavailable.

Representative conditions regarding particle impact and rebound from target surface involve large spatial and temporal conditions in the vicinity of the target. However, such conditions are fairly difficult to control and measure, because they require the use of nonintrusive techniques, especially close to the impacted surface.

The restitution characteristics of particles rebounding from surfaces require a statistical description. For fixed incidence values β_1 and V_1 , the rebound values β_2 and

V_2 have statistical distributions resulting from (a) variations in particle shape, size and rotational velocity at the time of impact; (b) variations in the topography and properties of the surface; (c) uncontrollable phenomena, such as particle and/or surface fragmentation, particle-particle collisions, changes in properties of materials owing to sudden highly localized temperature increases; and (d) variations in near-surface fluid flow conditions which significantly affect particle trajectories if the momentum equilibration number is less than 1.

Studies of typical histograms showing statistical distribution of the velocity distribution ratio for the case of relatively hard particles striking a ductile surface reveal that shapes of the distributions for V_2/V_1 and β_2/β_1 as well as the mean values of these ratios vary strongly with β_1 . Nevertheless all attempts to date to use restitution coefficient information at boundaries for predicting particle trajectories have been limited to the use of the mean values of the distributions, with the information contained in the shape of the distribution being ignored. This practice raises serious questions about the validity of predictions of particle trajectories when particles are subjected to sequential impacts.

The distributions of V_2/V_1 and β_2/β_1 , as well as their variations with the incidence angle β_1 are highly dependent on the physical properties of the impacting particle/impacted material surface pair. The highly specific dependence of the restitution coefficient of the materials evolved and the unknown influence of transverse Magnus and Saffman forces make deriving general theoretical relations or postulating generally applicable empirical correlations for these from experimental measurements very difficult.

On the question of surface topography, as it influences substantially deposition patterns for tube banks, the role of surface roughness in mechanisms for explaining deposition cannot be ignored. Except for the isolated interesting turbulent flow studies reported in the literature, little attention however, has been paid to the synergistic effects between deposition-induced surface evolving topographies and the associated fluid motion. One particular study reported in the literature centers on large scale changes in topography of bends. However, the local influence of surface roughness on fluid and particle motions was not investigated. This topic is discussed briefly next.

The wall region of a developed turbulent flow is characterized by a large spectrum of scales of motion and vigorous unsteady dynamics. However, the average velocity component, U_f , of fluid moving parallel to the surface can be expressed as:

$$\frac{U_f}{U_\tau} = \frac{1}{\chi} \ln\left(\frac{yU_\tau}{\nu}\right) + f\left(\frac{hU_\tau}{\nu}\right) \quad (2)$$

where U_τ is the wall friction velocity defined at $U_\tau = (\tau_w/\rho)^{1/2}$, y is the normal distance from the surface, h is the "equivalent" roughness height and χ is the Von Karman constant. The wall region to which Equation (2) applies is bounded by $40\nu/U_\tau < y < 0.2\delta$ where δ is the boundary layer thickness. For values of $hU_\tau/\nu > 5$ roughness has the effect of reducing the mean fluid velocity relative to that which would develop along a smooth wall and for $hU_\tau/\nu > 70$ this effect becomes pronounced. Appropriate forms for the fraction $f(hU_\tau/\nu)$ in Equation (2) are provided in the literature.

For a pipe flow at room temperature with $Re_D = 10^5$, the magnitude of the friction velocity is $U_\tau = 0.10 \text{ ms}^{-1}$. Thus, roughness elements of height $h > 100 \mu\text{m}$ or $h > 10 \mu\text{m}$ in water significantly reduce the mean speed of fluid near a surface (relative to a smooth surface) at this value of Re_D . Photographic evidence suggests that typical values of h for surfaces roughened by particle impacts range from 1 to $1000 \mu\text{m}$. Because of viscous damping in the sublayer region of the flow, fluids with high kinematic viscosity, ν are less sensitive than fluids with low ν to the presence of protrusions on a surface. However, in both cases roughness retards the mean component of fluid motion and hence particle motion parallel to the surface.

The ultimate consequences for deposition owing to surface roughness are hard to generalize, because particle incidence speeds and angles that determine the amount and spatial distribution of surface deposition depend markedly on momentum equilibration number, λ , and local flow turbulence. Nevertheless, relative to a smooth pipe, we can reasonably expect that in an initially rough pipe, particles with $\lambda > 1$ approaching the pipe wall at shallow incidence angles on average will be deviated less from their damaging trajectories by the component of fluid motion parallel to the wall.

Even from such a crude picture, based on mean flow interpretation of a region of flow characterized by intense velocity fluctuations distributed randomly in time and over space, one concludes that roughness elements can alter both the magnitude and

topography of surface deposit by affecting the flow. Thus, such influences have to be accounted for when planning experiments and interpreting observations or when attempting to calculate particle trajectories near a surface.

3.0 TECHNICAL PROGRESS

As this study incorporates in a general framework, appropriate modules to model condensable species transport to the surface along with particles, the need for a suitable solver for the reaction component of the species equations with regard to issues of stability, stiffness, economy, etc. becomes obvious.

It is generally agreed in the literature that the major problem associated with the simultaneous integration of large sets of chemical kinetic rate equations is that of stiffness. Although stiffness does not have a simple definition, it is characterized by widely varying time constants. For example, in hydrogen-air combustion, the induction time is of the order of microseconds whereas the nitric oxide formation time is of the order of milliseconds. These widely different time constants present classical methods (such as the popular explicit Runge-Kutta method) with the following difficulty: to ensure stability of the numerical solution, these methods are restricted to using very short time steps that are determined by the smallest time constant. However, the time for all chemical species to reach near-equilibrium values is determined by the longest time constant. As a result, classical methods require excessive amounts of computer time to solve stiff systems of ordinary differential equations (ODE's).

Several approaches for the solution of stiff ODE's have been proposed. Of all these techniques, the general purpose codes EPISODE and LSODE are regarded as the best available "packaged" codes for the solution of stiff systems of ODE's. However, although these codes may be the best available for solving an arbitrary systems ODE's, it may be possible to construct superior methods for solving a particular system of ODE's governing the behavior of a specific problem. In this view, an exponentially fitted method, CREK1D, deserves a special mention and is described briefly next.

CREK1D is a computer algorithm designed for transient chemical kinetics problems and combustion kinetics problems in particular. It is based on the exponentially fitted trapezoidal method described adequately in the literature. It consists of a predictor-corrector algorithm and includes automatic step size selections. Given a prescribed error tolerance, it selects either a Newton-Jacobi or a Newton iteration for convergence. It

compares favorably with LSODE for lower accuracy requirements and costs somewhat more when higher accuracy is required.

The decision whether to solve the implicit equations using a Newton-Raphson iteration or Jacobi-Newton iteration (which does not require evaluation of the Jacobian matrix) is automated. The trade-offs involve accuracy, convergence rate and total computation time. A Newton-Raphson iteration converges quadratically, but the Jacobian and its inverse must be evaluated frequently to ensure this convergence.

In CREK1D, Jacobi-Newton iteration is used during the early part of the integration of chemical equations involving the chemical induction time and early heat release stages. During this time, when small step sizes are required for stability, this iteration minimizes the work involved. During the late heat release stages and the equilibration region, the Newton-Raphson iteration is preferred, since it has better convergence properties and large step sizes must be used. A test is performed to identify each regime based on the differences between the forward reverse reactions.

4.0 CONCLUSION AND PLANS FOR FUTURE WORK

4.1 Conclusions to Date

Good technical progress has been made. However, some of the issues that have been raised in the previous discussions regarding particle/species ~ surface interactions still remain to be described in adequate detail. Most discussions available in the literature on deposit initiation/build-up implicitly assume an ideally smooth heat exchange surface. In reality, even a new tube structure has a finite roughness scale. Localized irregular deposition drives both physical and thermal roughness. These directly affect the gas flow field. However, they also create local abrupt flow turns and recirculation patterns, substantially enhancing deposition of finer scale particulates. This is an awkward and difficult issue to address, but may have substantial impact on the rate of fouling build-up. Flow and transport models incorporating this mechanism, and deposit development models incorporating stochastic or chaotic deposit development may well prove necessary. From another perspective, this surface roughness effects may dominate transport of very fine particles, decreasing the importance of thermophoretic transport.

4.2 Plans for Next Reporting Period

Efforts will be continued to supplement the comprehensive flow field description obtained from the RNG-Spectral Element Simulations by incorporating in a general framework, appropriate sub/models to model particle and condensable species transport to the surface.

**DATE
FILMED
01/20/93**