**COAL LIQUEFACTION PROCESS STREAMS
CHARACTERIZATION AND EVALUATION**

**Quarterly Technical Progress Report
April 1 through June 30, 1991**

**G. A. Robbins, S. D. Brandes,
R. A. Winschel, F. P. Burke**

November 1991

**CONSOLIDATION COAL COMPANY
Research & Development Department
4000 Brownsville Road
Library, PA 15129**

**Prepared for the
United States Department of Energy
Under Contract No. DE-AC22-89PC89883**

**US/DOE Patent Clearance was provided by
Chicago Operations Office on Oct. 28, 1991**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DEC 20 1991

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

**COAL LIQUEFACTION PROCESS STREAMS
CHARACTERIZATION AND EVALUATION**

**Quarterly Technical Progress Report
April 1 through June 30, 1991**

**G. A. Robbins, S. D. Brandes,
R. A. Winschel, F. P. Burke**

November 1991

**CONSOLIDATION COAL COMPANY
Research & Development Department
4000 Brownsville Road
Library, PA 15129**

**Prepared for the
United States Department of Energy
Under Contract No. DE-AC22-89PC89883**

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, APRIL 1 THROUGH JUNE 30, 1991

This is the seventh Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Major topics reported are:

1. Feed coals and process oils from Wilsonville Run 260 were analyzed to provide information on process performance. Run 260 was operated in the thermal/catalytic and catalytic/thermal Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) modes with ash recycle. The supported catalyst used was Shell 324 and the subbituminous coal fed was from Black Thunder Mine (Wyodak and Anderson seams).
2. The status of the Participants Program is described.
3. A summary of the Phase I Participants Program final report from the University of Kentucky/Center for Applied Energy Research is presented.
4. A description of work in progress is included.
5. Five papers are appended. One paper was presented at the 16th Annual EPRI Fuel Science Conference in Palo Alto, California, on June 18-20, 1991. Two papers were accepted for presentation at the 202nd ACS National Meeting in New York on August 26-30, 1991. Two papers were accepted for presentation at the International Conference on Coal Science, at Newcastle-Upon-Tyne, United Kingdom, on September 16-20, 1991.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
RESULTS AND DISCUSSION	7
Wilsonville Run 260	7
Summary	7
Wilsonville Run 260 Overview	9
Plant Description	11
Abbreviated History of Wilsonville Run 260	12
Sample Descriptions	15
Analyses	16
850°F ⁺ Resid Conversion and Kinetics	17
Effect of Catalytic/Thermal vs Thermal/Catalytic	
Reactor Configurations	20
Comparisons of Run 260 with Run 258	23
Dowtherm A Contamination of 260D Samples	25
Participants Program Status	29
Summary	29
Discussion	29
Summary of University of Kentucky/Center for Applied Energy	
Research Final Report	32
General Description	32
Summary	32
Program Description	32
Participants Methodology	33
Major Findings Reported by UK/CAER	34
Consol Evaluation	34
Further Development	36
UK/CAER Summary	36
Work in Progress	40
Preheater Simulation Studies	40
O-Alkylation of Phenolic Groups	40
Wilsonville 261	41
EXPERIMENTAL	42
REFERENCES	43

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Daily Operating Conditions, Wilsonville Run 260	44
2	Operating Conditions and Yields for Material Balance Periods	45
3	Analyses of Subbituminous Feed Coal, Wilsonville Run 260	46
4	Component Distribution of V-131B Samples, Wilsonville Run 260	47

LIST OF TABLES (Continued)

<u>Table</u>		<u>Page</u>
5	Component Distribution of V-1067 Samples, Wilsonville Run 260	47
6	Component Distribution of Interstage Samples, Wilsonville Run 260	47
7	Solubility Fractionation of V-131B Samples, Wilsonville Run 260	48
8	Solubility Fractionation of V-1067 Samples, Wilsonville Run 260	48
9	Solubility Fractionation of Interstage Samples, Wilsonville Run 260	48
10	Proton Distribution of V-131B Whole Samples, Wilsonville Run 260	49
11	Proton Distribution of V-1067 Whole Samples, Wilsonville Run 260	49
12	Proton Distribution of Interstage Whole Samples, Wilsonville Run 260	49
13	Proton Distribution of V-131B Distillate Samples, Wilsonville Run 260	50
14	Proton Distribution of V-1067 Distillate Samples, Wilsonville Run 260	50
15	Proton Distribution of Interstage Distillate Samples, Wilsonville Run 260	50
16	Proton Distribution of V-131B Resid Samples, Wilsonville Run 260	51
17	Proton Distribution of V-1067 Resid Samples, Wilsonville Run 260	51
18	Proton Distribution of Interstage Resid Samples, Wilsonville Run 260	51
19	Phenolic -OH Concentration by FTIR, Wilsonville Run 260	52
20	Microautoclave Test Results, Wilsonville Run 260	53
21	Conversion of Resid Components, Wilsonville Run 260	54
22	850°F ⁺ Conversion and Kinetics, Wilsonville Run 260	55
23	Comparison of Wilsonville Runs 260 and 258, Operating Conditions	56
24	Comparison of Wilsonville Runs 260 and 258, Yield and Performance Data	57
25	Comparison of Wilsonville Runs 260 and 258, Process Oil Characteristics, Conversions and Kinetic Constants	58

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Simplified CC-ITSL Process Diagram for Wilsonville Run 260	59
2	Partial CC-ITSL Process Diagram for Wilsonville Run 260 Showing Major Distillate Streams	60
3	Component Distribution of Whole V-131B Oils From Wilsonville Run 260	61
4	Component Distribution of Whole V-1067 Oils From Wilsonville Run 260	62

LIST OF FIGURES (Continued)

<u>Figure</u>		<u>Page</u>
5	Component Distribution of Whole Interstage Oils From Wilsonville Run 260	63
6	Solubility Fractionation of V-131B THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 260	64
7	Solubility Fractionation of V-1067 THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 260	65
8	Solubility Fractionation of Interstage THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 260	66
9	Proton Distribution of V-131B Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilsonville Run 260	67
10	Proton Distribution of V-1067 Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilsonville Run 260	68
11	Proton Distribution of Interstage Distillate and THF- Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilson- ville Run 260	69
12	Phenolic -OH Concentrations of Distillate and THF- Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilson- ville Run 260	70
13	Microautoclave Solvent Quality Assays of Samples From Wilsonville Run 260	71
14	First-Stage and Total Conversions of THF-Soluble 850°F ⁺ and Coal + IOM for Wilsonville Run 260	72
15	THF-Soluble 850°F ⁺ Conversions for Wilsonville Run 260	73
16	Conversion of Oils (Hexane Solubles) in Wilsonville Run 260	74
17	Conversion of Asphaltenes in Wilsonville Run 260	75
18	Conversion of Preasphaltenes in Wilsonville Run 260	76
19	Resid and UC Conversion Activity in Wilsonville Run 260	77
20	GC/MS Chromatograms of Process Oil Distillates From 10/9/90, Wilsonville Run 260	78

APPENDICES

<u>Appendix</u>		<u>Page</u>
1	Inspection of Integrated Two-Stage Liquefaction Pro- ducts by Petroleum Assay	80
2	The Application of Advanced Analytical Techniques to Direct Coal Liquefaction	104
3	Stable Carbon Isotope Analysis of Coprocessing Materials	113
4	Coal Cleaning for Liquefaction by Selective Agglom- eration with Recycle Oils	121
5	Inspection of Integrated Two-Stage Liquefaction Pro- ducts as Petroleum Refining Feedstocks	126

Section 1

INTRODUCTION

This is the Technical Progress Report for the seventh quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period April 1, 1991, through June 30, 1991.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The R&D Department of Consolidation Coal Company (Consol R&D) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, Consol R&D will obtain samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterize them using established analytical techniques. In addition, selected samples will be characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations will be provided by a subcontracted project team.

In addition to samples from current process development programs, Consol R&D maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the Lummus, HRI and UOP coprocessing development programs. These samples,

which represent important stages in the recent development of coal liquefaction technology, also will be used in the analytical program.

CONTRACT OBJECTIVES

Consol R&D is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples will be chosen from ongoing DOE-funded liquefaction and coprocessing projects and from Consol's collection of coal liquids produced during the past ten years. Samples will be chosen based on their relevance to process development programs, and will be well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen will be sufficient to judge the applicability of the analytical methods being evaluated. These process oils will be analyzed by Consol R&D in a base characterization program using techniques established in previous Consol research. Selected samples also will be provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who will characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 10 to 15 organizations that have specialized analytical capabilities will be a major aspect of this work. Individual analytical specialists from the subcontractors will take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program will evaluate the utility of promising analytical techniques for providing useful information for coal

liquefaction process development, and will apply those results to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in process monitoring, to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This will include support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate process oils will be characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses will aid plant operations and planning. Also, these results will provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. Each topic is summarized and discussed in detail under a separate heading in Section 2, Discussion. Because each topic is summarized, when appropriate, in the corresponding section of the Discussion, no overall Summary section is provided in this report.

- A set of eighteen process oils and one feed coal sample from Wilsonville Run 260 were analyzed to provide information on process performance. Run 260 was operated with Black Thunder Mine coal (Wyoming subbituminous, Wyodak and Anderson seams) and Shell 324 supported catalyst (Ni/Mo on alumina). The plant was run in the thermal/ catalytic (high/low temperature) and catalytic/thermal (nominally low/high temperature) modes of the Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) configuration with ash recycle. Reactor volumes in use were 100% in the thermal stage and 75% in the catalytic stage. A new interstage separator was tested. This was the first subbituminous coal run with the improved distillation system and the revised recycle flow scheme. Major

objectives were to eliminate solids deposition when processing low-rank coals and to obtain an improved distillate yield and a lower boiling end-point product with subbituminous coal.

- A status report of progress made in the Participants Program during the seventh quarter is given here. One final report, one draft final report, and several status reports were received from Phase I subcontractors. The last sample data sets and processing information packages for Phase I were sent out. Preparations were begun for Phase II.
- The final report was received from the University of Kentucky/Center for Applied Energy Research, completing their subcontract under Phase I of the Participants Program. That report is summarized here, and will be issued later as a topical report.
- Ongoing work, in addition to the Participants Program, includes the analysis of samples from Wilsonville Run 261, and continuation of preheater simulation studies with selected Wilsonville process oils. Work was begun on derivatizing the phenolic groups contained in a Wilsonville recycle solvent by O-methylation. Solvent quality assays will be made with the treated and untreated solvents. The goal of the work is to assess the role of phenolic groups in donor solvent properties of the oil.
- Six papers were presented or prepared for presentation. These are itemized below.
 1. G. A. Robbins presented a paper entitled, "Agglomeration of Low-Rank Coal as a Pretreatment for Direct Coal Liquefaction" at the 201st National Meeting of the American Chemical Society in Atlanta, Georgia, in April 1991. The same presentation also was given at the Ames Laboratory in May, by invitation. The written paper was appended to an earlier report under this contract (report covering the period from October 1 through December 31, 1990).

2. R. A. Winschel presented a paper, entitled "Inspection of Integrated Two-Stage Liquefaction Products by Petroleum Assay", (co-authored by P. Zhou, Burns and Roe Services Corp.) at the 16th Annual Electric Power Research Institute Fuel Science Conference, Palo Alto, California, in June. A copy of the paper is included as Appendix 1 of this report.
3. A paper authored by S. D. Brandes, R. A. Winschel, and F. P. Burke, entitled "The Application of Advanced Analytical Techniques to Direct Coal Liquefaction", was accepted for presentation at the 202nd National Meeting of the American Chemical Society and Fourth Chemical Congress of North America, New York, New York, in August 1991. A copy of the preprint is included as Appendix 2.
4. A paper authored by M. S. Lancet, R. A. Winschel, and F. P. Burke, entitled "Stable Carbon Isotope Analysis of Coprocessing Materials", was accepted for presentation at the 202nd National Meeting of the American Chemical Society and Fourth Chemical Congress of North America, New York, New York, in August 1991. A copy of the preprint is included as Appendix 3.
5. A paper authored by F. P. Burke, R. A. Winschel, and G. A. Robbins, entitled "Coal Cleaning for Liquefaction by Selective Agglomeration with Recycle Oils", was accepted for presentation at the International Conference on Coal Science in Newcastle-Upon-Tyne, United Kingdom, in September 1991. A copy of the paper is included as Appendix 4 in this report.
6. A paper authored by R. A. Winschel, F. P. Burke, and P. Zhou (Burns and Roe Services Corp.), entitled "Inspection of Integrated Two-Stage Liquefaction Products as Petroleum Refining Feedstocks", was accepted for presentation at the International Conference on Coal Science in Newcastle-Upon-Tyne,

United Kingdom, in September 1991. A copy of the paper is included as Appendix 5 of this report.

Section 2

RESULTS AND DISCUSSION

WILSONVILLE RUN 260

SUMMARY

Consol analyzed eighteen process oils and one feed coal sample from Wilsonville Run 260, which was operated in the thermal/catalytic and catalytic/thermal Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) modes. The subbituminous feed coal was from Black Thunder Mine. Shell 324 catalyst was used. The major results from Consol's analyses are summarized below.

- The properties of oils produced during period C (thermal/catalytic, 825/790°F) were compared with those produced during period D (catalytic/thermal, 790/774°F) to examine the effect of operating configuration on oil properties. Several properties of the interstage samples changed drastically on changing from a thermal first stage (period C) to a catalytic first stage (period D). The IOM concentration increased greatly because less coal conversion took place in the catalytic first stage than in the thermal first stage. There was an increase in hydroaromatics in the interstage distillate from period C to period D. The interstage distillate showed a very large decrease of 0.9 meq/g in the phenolic -OH concentration from period C to period D. Donor solvent quality of the whole interstage oil increased from period C to D, whereas all the other distillate and whole oil samples decreased in solvent quality from period C to D. THF-soluble 850°F⁺ resids from period D contained relatively more oils (hexane solubles) and less pre-asphaltenes, than did those from period C. Except for the sample most contaminated by Dowtherm A fluid, the proton aromaticities of distillates and THF-soluble resids dropped significantly from period C to period D. Taken together, the observations seem to indicate that the resids were more hydrogenated, but less defunctionalized in period D than in period C.

- Periods H and M from Run 258 (the only prior run with Black Thunder coal) were selected for comparison with period C of Run 260. Overall, the resids produced in period 260C appeared to be more upgraded than those from the comparison periods. They were more hydrogenated and defunctionalized than their Run 258 counterparts. Lower space velocity in period 260C may have been the dominant factor affecting the residual oil characteristics. Distillate properties from period 260C were similar to those from periods 258H and 258M. They may have been influenced strongly by other conditions in addition to space velocity.
- Distillate samples from Run 260, period D were contaminated with Dowtherm A heat transfer fluid. Concentrations, determined by GC/MS, are 6 wt % in the V-131B distillate sample, at 1.2 wt % in the interstage distillate sample, and 0.5 wt % in the V-1067 distillate sample. The Dowtherm A was detected when the oil was analyzed to identify the cause of an objectionable odor reported by Conoco personnel who are performing a crude oil assay on the Wilsonville net product from 260D.
- First-stage and total 850°F⁺ resid + UC conversions, as calculated by Consol, were higher for period 260C than in the 258H and 258M periods, in agreement with Wilsonville's results. First- and second-stage rate constants for 850°F⁺ resid + UC conversion were relatively low in 260C. On a conversion activity basis, the first stage in Run 260 was intermediate between the comparison periods. The second-stage activity was low, however, relative to the Run 258 periods. This low activity may result from the low space velocity used in Run 260, or from some other inadequacy of the mathematical model of the kinetics (activation energy, first-order assumption).
- Typically, Consol measures conversions of 850°F⁺ resid + UC which are slightly lower, on average, than Wilsonville's reported 1050°F⁺ resid + UC conversions. However, during catalytic/thermal operation, Consol's calculated conversions (second stage and total) were significantly higher than those of Wilsonville. This suggests that

high second-stage conversion of 850 x 1050°F material or low second-stage conversion of 1050°F+ material (including IOM) took place in those periods of operation (D through F).

- Activities (pre-exponential factors) for 850°F+ resid + UC conversion in the first stage were consistently greater than or equivalent to those in the second stage. The first reactor provides most of the resid + UC conversion, whether it is thermal or catalytic. The conversion activity of the thermal reactor was not greatly affected by reactor order, but the conversion activity of the catalytic reactor increased significantly when it was operated as the first stage. The activity for conversion is higher in the catalytic first stage because the catalytic reactor can convert both coal and resid, whereas it primarily converts only resid when it is operated as the second stage. Overall, the catalytic stage 850°F+ resid + UC conversion activity was poor when operated in the thermal/catalytic mode, but was higher and more typical of past Wilsonville operation when operated in catalytic/thermal mode.
- The first-stage conversion of UC (coal + IOM) was much lower in catalytic/thermal operation than in thermal/catalytic operation. The catalytic second-stage (A through C) contributed almost nothing to UC conversion, whereas the thermal second-stage (D through F) contributed a substantial amount. Total UC conversion was slightly lower in periods D-F relative to periods A-C. These results indicate that the temperature effect on coal conversion is significant.

WILSONVILLE RUN 260 OVERVIEW

Consol analyzed one feed coal and 18 process oils from Wilsonville Run 260 which was operated with subbituminous coal and 1/16-inch extrudate Shell 324 (Ni/Mo on alumina) supported catalyst. Run 260 was operated from July 17 through November 13, 1990, in two configurations of Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) with ash recycle. The two configurations were thermal/catalytic (high/low temperature) and

catalytic/thermal (nominally low/high temperature -- see later discussion). The thermal and catalytic stages used 100% and 75%, respectively, of the available reactor volume. The feed coal for the entire run was from Black Thunder Mine, which is located in the Wyoming Powder River Basin and extracts subbituminous coal from the Wyodak and Anderson seams. Regardless of whether the supported catalyst was in the first or second stage, disposable Fe_2O_3 was added to the first stage at a rate of about 2 wt % of the MF coal, with di-tertiary-nonyl-polysulfide (TNPS, $\text{C}_9\text{H}_{19}\text{S}_x\text{C}_9\text{H}_{19}$) sulfiding agent in stoichiometric excess to maintain the Fe in a fully sulfided form (although the extent of sulfidation is not measured). During the entire run, a supported catalyst replacement rate of 3.0 lb cat/T MF coal was used. A new, smaller interstage separator tried in Run 260 was ineffective during periods A and B, was bypassed in period C, and was removed from service for periods D through F. The major operating variables during Run 260 were configuration (thermal/catalytic and catalytic/thermal), temperature in both reactor stages (774-840°F thermal and 774-790°F catalytic), and coal feed rate (251-352 MF lb/hr). Of course, changes in the catalytic and thermal space velocities accompanied the coal feed rate changes. Wilsonville's improvements to the T-102 distillation tower were in place for Run 260, but not for Run 258 (which was the previous run with this coal). The recycle stream also was changed to accommodate the distillation system changes.

The Run 260 objective were: 1) to eliminate solids deposition when processing low-rank coal, 2) to obtain a better-defined boiling endpoint for the distillate product, and 3) to improve the distillate yield and product quality when processing a low-rank coal.

Operating conditions¹ for those periods from which we were supplied samples appear in Table 1. Operating conditions and yields¹ for material balance periods appear in Table 2. A simplified flow scheme² of the Wilsonville plant, as configured for Run 260, appears in Figure 1. More detail on the part of the plant involving the major distillate streams is shown in Figure 2.

PLANT DESCRIPTION

During Run 260, the Wilsonville plant was operated in the CC-ITSL mode with ash recycle. Coal was slurried with a mixture of second-stage vacuum-flashed bottoms (ashy resid, V-1082 bottoms), second-stage heavy distillate (V-1074), and deashed second-stage product resid. The pasting solvent stream is called V-131B. The slurry was mixed with hydrogen and passed through the preheater and first-stage ebullated bed reactor (R-1235 or R-1236, depending on the operating period). Part of Run 260 was made with a new, smaller interstage separator (V-1258B) in place. When it was in use, the gas and light products were removed from the first-stage products prior to processing in the second stage. The liquid portion of the separator overheads was sent to the product distillation system. The separator bottoms were sent to the second stage, along with make-up hydrogen. In the absence of the interstage separator, all the first-stage products were sent to the second stage. The interstage sample consisted of the feed to the second stage. Depending on the operating period, the second-stage reactor was either R-1236 or R-1235. Gases and light oils were separated from the second-stage product in an atmospheric flash. The atmospheric flash bottoms (V-1067) were separated in a vacuum flash into distillate (V-1082 overheads) and resid (V-1082 bottoms). A portion of the V-1082 bottoms stream was recycled to the first stage as a component of the pasting solvent. The remainder of the V-1082 bottoms stream was deashed in the Kerr-McGee ROSE-SR (formerly called Critical Solvent Deashing) unit, which rejected an ash concentrate and produced a deashed resid product. The deashed resid was recycled back to V-131B as the second component of the pasting solvent. The atmospheric flash overhead liquids and the V-1082 overheads were sent to the distillation system (consisting of an atmospheric tower, followed by a vacuum tower), which produced naphtha (V-161), middle-distillate (V-182), and heavy distillate (V-1074). The heavy distillate was recycled as the third component of the pasting solvent.

During Run 260, the V-1258B interstage separator was in use during periods A and B, but was discontinued after period B. The first-stage reactor was R-1235 for periods A, B, and C, when the plant was run in the

thermal/catalytic mode and the high/low temperature sequence in the first/second stages. R-1236 was the second-stage reactor during that time. After period C, the reactor sequence was reversed: R-1236 was the first stage and R-1235 was the second stage. Periods D, E, and F were run in this configuration, which was catalytic/thermal and (nominally) low/high temperature.

ABBREVIATED HISTORY OF WILSONVILLE RUN 260

This section is paraphrased from Wilsonville technical review meeting handouts.¹ Run 260 began on July 17, 1990, in the thermal/catalytic CC-ITSL mode feeding Black Thunder subbituminous coal. The first-stage (thermal) reactor was R-1235 and the second-stage (catalytic) reactor was R-1236. The reactors were configured to use 100% and 75% of the available reactor volume, respectively, in the thermal and catalytic stages. The interstage separator (V-1258B) was in use at the beginning of the run, but was discontinued later. Disposable Fe_2O_3 catalyst was mixed with the coal slurry prior to feeding it to the first stage. TNPS sulfiding agent was added to the reactors to maintain adequate sulfidation of the disposable and supported catalysts. The second-stage reactor was charged with 280 lb (dry) Shell 324 1/16-inch (Ni/Mo) catalyst as follows: 160 lb was aged catalyst from Run 258 (Black Thunder coal, age was 664 lb MF coal/lb cat, or 1324 lb resid + CI/lb cat); and 120 lb was fresh presulfided catalyst. This mixed catalyst was loaded to shorten the time required to get to the desired equilibrium age for the run. The start-up solvent was from Run 259 with Ireland Mine (Pittsburgh seam) coal. Start-up conditions were: 350 MF lb/hr coal feed rate, 30 wt % coal in the slurry (2.33 solvent/coal ratio), 40 wt % resid and 20 wt % cresol insolubles (CI) in the recycle solvent, iron oxide addition rate of 2.0 wt % MF coal, 825/790°F reactor temperatures and inlet H_2 partial pressure of 2600 psi.

A chronological account of the run follows:

7/17: Start of Run 260

7/18-23: Several level and vent control problems, problems with coal addition, recirculating pumps. Temporarily off feed July 19 to clean out vent line and downstream separators. V-1258 overhead oil/water separator plugging. Temporarily off feed on July 23.

7/24: Could not add coal due to recirculation pump problems. Off feed several hours.

7/27: Gas not being removed effectively from liquid in V-1258B separator.

7/30: Motor control center breaker overheated. Off feed several hours.

8/2-4: Catalyst addition and withdrawal in R-1236 was started after plug was cleared.

8/7: V-1258B separator problems and adjustments continued.

Period A: August 8, 9, 10

8/11: Plant was off feed for several hours during a power failure.

Period A: August 14

8/15: Plant upset due to broken coal slurry feed pump. The first-stage temperature was increased to 840°F to study the effect on resid yield.

8/16-9/7: Up to 8 wt % naphtha found in V-1074 (normally about 2 wt %).

8/18 & 20: Upsets on 8/18 and 8/20 caused by power failures.

8/22: Reduced MF coal feed rate to 300 lb/hr.

Period B: August 25

8/26-27: Interruption of both steam and vacuum systems due to boiler problems.

Period B: August 27, 28, 29

8/23-9/7: Pressure drop in line between reactors getting higher, second reactor pressure getting progressively lower.

8/30: Gas flow from separator was all directed through bottom. Coal feed rate was lowered to 250 lb MF/hr. Decreased first-stage reactor temperature to 825°F.

Period C: September 2, 3, 4

9/3-4: Catalyst withdrawn normally, one addition attempt failed. Addition successful on following day.

Period C: September 5

9/8-25: Outage. Lines between the reactors were inspected and hydroblasted clear. Separator had no deposits. Boiler was inspected - some problems found (see August 26-27, entry). Reactors were switched - R-1236 became the first reactor.

9/26: Run 260 resumed in catalytic/thermal mode. Coal feed rate was set to 250 MF lb/hr. Reactor temperature set to 790°F in first stage. Target temperature for second stage was 825°F.

9/27: Target second-stage reactor temperature was not reached due to lack of exothermic reaction heat and due to heat losses in second reactor.

9/27-29: Boilers were down several times, vacuum upsets occurred. Low water flow due to high pressure drop in ion exchange bed.

9/29-30: Problem with Dowtherm heater. Off coal feed for several hours.

10/1-2: Attempted to adjust hydrogen flow and partial pressure in second stage.

10/4: Pressure control problem in T-102 column. Recirculation solvent not topped properly.

10/5-6: Valve repaired in vacuum flash line. Off coal feed for several hours.

Period D: October 7, 8, 9, 10 (Consol samples from period D were contaminated with Dowtherm A).

10/11: Steam tracing on line to second stage reactor was repaired. Vacuum problems at vacuum flash and problems transferring heavy distillate to T-102. Condensate line plug was repaired.

10/12: Increased coal feed rate to 300 lb MF coal/hr. Catalyst addition tube plugged and addition not possible. Dowtherm reported in distillate samples. T-105 taken off line to check for Dowtherm A leaks.

10/13: Briefly off coal feed due to slurry recirculation pump outage.

10/14-18: Outage. Ammonium salts found plugging catalyst addition tube. R-1236 ebullating pump repaired. Replaced leaking catalyst addition valves. Vacuum jets on T-102 repaired.

10/18: On coal feed at 350 lb MF coal/hr. High feed rate allowed second stage temperature to be increased.

10/23: Loss of some light ends at V-1250 (after high-pressure let down).

10/26-27: Repair of V-1250 control valve.

Period E: October 26, 27, 28, 29, 30

10/30: V-1247 carry-over into V-1249. Heavy ashy resid and ash was sent to distillate piping. Start of gas-liquid separation problem in separator.

10/31: First-stage temperature was lowered to 775°F.

11/2: Dowtherm found in V-1082 sample. Steam used in jacket after leak was detected.

11/3: Low steam pressure delayed bottoms processing. Feed rate lowered for extended time. Rough operation.

Period F: November 4, 5

11/5: Difficult and unsteady operation, due to large temperature spread in R-1236 catalyst addition/withdrawal.

Period F: November 7, 8

11/8: Feed pump stoppage. Brief loss of feed to reactors.

11/9: Raised temperature of first reactor to 805°F and lowered second reactor to 750°F. V-124 carry-over and loss of separation in V-1247 caused contamination of distillation towers with ash.

11/12: Second-stage temperature was lowered to 735°F. Operation was very difficult and unstable.

11/14: End of Run 260.

SAMPLE DESCRIPTIONS

Consol received one feed coal sample and 18 process oil samples from Run 260. The coal was from the Thunder Basin Coal Company's Black Thunder Mine in Campbell County, Wyoming (Wyodak and Anderson seams).

It was a composite sample from the Wilsonville stockpile, Wilsonville sample number 9827, sampled June 13, 1990, and received by Consol on June 20, 1990. The process oils consisted of a recycle oil (V-131B) sample, an interstage oil (R-1235, some with HP (high pressure) or OTL (outlet) suffix) sample, and a product oil (V-1067) sample from each of the six material balance periods. V-1067 is the second-stage flashed bottoms product. Although samples were labelled R-1235 for periods D through F, the first-stage reactor was R-1236 for those periods.

ANALYSES

Coal analyses (Table 3) were obtained by the following methods: LECO MAC 400 (moisture, ash); LECO CHN-600 (C, H, N); LECO SC-32 (S, Ash SO_3); Parr 1261 isoperibol calorimeter (gross heating value); and Jarrell Ash JA-61 simultaneous inductively-coupled plasma atomic emission (ash elemental).

Proton distributions were obtained by ^1H -NMR for each of the V-131B, interstage and V-1067 whole samples (Tables 10-12). All the whole samples were tested in the microautoclave at the modified equilibrium conditions (Table 20). Prior experience has shown that the microautoclave results show high variability when the samples have high solids concentrations, as was the case in Run 260. The whole samples were distilled (Tables 4-6) to 320°C pot/270°C column/5 torr (850°F/atm). Each 850°F⁺ resid was analyzed by solubility fractionation (Tables 7-9), ^1H -NMR (Tables 16-18) and FTIR for phenolic -OH content (Table 19). Each 850°F⁻ distillate was analyzed by ^1H -NMR (Tables 13-15) and FTIR (Table 19). Microautoclave tests were made at the modified equilibrium conditions with each 850°F⁻ distillate (Table 20). Details of the sample work-up and analytical procedures have been presented elsewhere.^{3,4} All samples for proton distribution by NMR were dissolved in 99.96% deuterated pyridine (whole or resid samples) or in CDCl_3 (distillate samples) and integrated electronically. Response factors used for flame ionization detection of solubility fractions were those previously used for Run 258 samples produced from Black Thunder coal. A different set of

response factors is used for each feed coal used to produce an oil sample.

850°F⁺ RESID CONVERSION AND KINETICS

Consol analyses of the process oils were used to calculate conversions (forced ash balance method) of the 850°F⁺ material and its various components in each reactor stage (Table 21). The 850°F⁺ conversions then were used to calculate conversion rate constants and conversion activities (Table 22). A deactivation rate constant was obtained from these data by a method described later. The conversion and kinetic calculations were made as described elsewhere.⁵ Briefly, the following equations are used in the calculations:

$$C = \text{Conversion} = \left(\frac{850^{\circ}\text{F}^{+} \text{ In/Ash In} - 850^{\circ}\text{F}^{+} \text{ Out/Ash Out}}{850^{\circ}\text{F}^{+} \text{ In/Ash In}} \right) \times 100\%$$

$$K = \text{Rate Constant} = \text{WHSV} \left(\frac{C}{100 - C} \right)$$

$$A = \text{Conversion Activity} = K e^{E_{\text{act}}/RT},$$

where E_{act} is assumed to be 23,500 cal/mol, as has been used in the past at Consol. The thermal stage WHSV used is the same as the catalytic stage when reactor volumes are equal. The catalytic stage WHSV is used for the thermal stage because the absolute thermal space velocities are proprietary and the only values provided are on a relative basis. In Run 260, however, a correction was applied to account for differing volumes in the catalytic and thermal reactors. The following correction was applied to the thermal space velocities.

$$\text{WHSV (thermal stage)} = \text{WHSV (catalytic stage)} \times \left(\frac{75\% \text{ volume}}{100\% \text{ volume}} \right)$$

Conversions of 850°F⁺ resid and its components calculated for each reactor stage and the total system are given in Table 21. Figure 14 shows the first stage and total 850°F⁺ and coal + IOM conversions for Run 260.

Several interesting observations can be made. First, the first-stage conversion of UC (Coal + IOM) was much lower in catalytic/thermal operation than in thermal/catalytic operation. The catalytic second-stage (periods A through C) contributed almost nothing to UC conversion, whereas the thermal second-stage (periods D through F) contributed a substantial amount. However the total UC conversion was slightly lower in periods D-F than in periods A-C. The plant personnel were unable to raise the thermal reactor temperature high enough during periods D-F to achieve higher coal conversion. These results indicate that the thermal effect on coal conversion was significant. Overall 850°F⁺ THF-soluble resid conversions were near zero throughout the run (Figure 15), the average being not (statistically) significantly different from zero. This merely indicates that there is little net make or net loss of THF-soluble resid in the process. It appears that the first-stage conversion of soluble 850°F⁺ resid was improved in periods D-F over periods A-C. The negative conversions in most periods represent net yields of 850°F⁺ soluble resid. When the catalytic stage was the second stage (periods A-C), second-stage 850°F⁺ THF-soluble resid conversion was consistently positive, ranging from 8 to 20%. Except for period F, the second-stage conversion of 850°F⁺ resid was higher than that of the first stage. The conversion of the oil fraction (hexane solubles) was small and invariant for periods B through D (Figure 16). In periods E and F, total conversion of oils was higher. First- and second-stage oil conversions calculated by Consol for period F were quite high. Perhaps some problem existed with the analyses or the samples. The conversions of asphaltenes (Figure 17) and preasphaltenes (Figure 18) showed trends which were similar to each other. Catalytic stage conversions of these components were consistently higher in thermal/catalytic periods (A through C) relative to catalytic/thermal periods (D through F). Thermal stage conversions of these components were consistently higher in catalytic/thermal periods (D through F) than in thermal/catalytic periods (A through C). Viewed another way, the conversions of these components in the second stage were consistently greater than or equivalent to their conversions in the first stage. In Table 22, the 850°F⁺ resid + UC conversions obtained by Consol are compared with those obtained by Wilsonville. The associated kinetic rate constants and conversion

activities obtained by Consol also are given. The conversions obtained by Consol are different from those obtained by Wilsonville because of a difference in laboratory distillation conditions. Consol uses an 850°F atmospheric equivalent distillation endpoint, whereas Wilsonville uses a 1050°F atmospheric equivalent endpoint. Therefore, Consol calculates conversion of 850°F⁺ material, but Wilsonville calculates conversion of 1050°F⁺ material. The effect of this difference on measured conversions has been discussed elsewhere.⁵

The average ratios of Consol conversions to Wilsonville conversions are compared below.

RATIO CONSOL/WILSONVILLE CONVERSIONS OF RESID + UC

Period	First Stage	Second Stage	Total
260C	1.01 (thermal)	0.67 (catalytic)	0.92
260D-F	0.96 $\pm$ 0.18 (catalytic)	1.79 $\pm$ 0.72 (thermal)	1.13 $\pm$ 0.10
258 Average (I, J, J omitted)	0.89 $\pm$ 0.12	0.78 $\pm$ 0.33	0.87 $\pm$ 0.11
Average Runs 250-259	0.98 $\pm$ 0.10	0.85 $\pm$ 0.16	0.94 $\pm$ 0.06

Relative to the global averages (Runs 250-259) and the Run 258 averages specifically, the 260C ratio was slightly high for the first stage, low for the second stage and about average for the total. In contrast, the ratios for 260D-F were average for the first stage, quite high for the second stage and relatively high for the total. A ratio higher than one indicates that the percentage conversion of 850 x 1050°F material is greater than the percentage conversion of 1050°F⁺ material. The ratio for the thermal reactor in 260D-F is quite high, indicating high 850 x 1050°F conversion or, alternatively, low conversion of 1050°F⁺ (including unconverted coal). Note that a thermal second stage is atypical at Wilsonville. Also note that the thermal stage temperature was quite low during periods D through F. The ratio of 1.13 $\pm$ 0.10 for the total conversion for 260 D-F is higher than the averages from the prior runs (Runs 250 to 259). Perhaps this results from thermal severity so low in 260 D-F that the 1050°F⁺ conversion (including coal conversion) was reduced below the 850 x 1050°F⁺ conversion.

The kinetic rate constants and conversion activities for each reactor stage are given in Table 22. Activities (i.e., pre-exponential factors)

for resid + UC conversion in the first and second stages are shown in Figure 19. The first stage had activities consistently greater than or equivalent to the second stage. Whereas, the resid + UC conversion activity of the thermal reactor was not greatly affected by reactor order (first-stage in periods A-C vs second stage in periods D-F), operation of the catalytic reactor as the first reactor significantly increased its resid + UC conversion activity (second-stage in periods A-C vs first-stage in periods D-F). The first reactor provides most of the resid + UC conversion, whether it be thermal or catalytic. The conversion activity of the catalytic reactor is higher in catalytic/ thermal operation because, in addition to converting resid (its usual function), it is also converting coal, a function which is not greatly demanded of it in thermal/catalytic operation. Overall, the conversion activity of the catalytic stage in periods A-C was poor (about 1×10^{-7}). Its conversion activity during periods D-F was much higher (2.5×10^{-7} to 5.0×10^{-7}) and was more typical of past catalytic stage performance in past runs at Wilsonville.⁵

EFFECT OF CATALYTIC/THERMAL VS THERMAL/CATALYTIC REACTOR CONFIGURATIONS

In periods D through F, the sequence of reactors was reversed relative to that used in periods A through C. The configuration for D through F was catalytic/thermal, and nominally low/high temperature. However, in periods D through F, the plant could not be operated to achieve the higher thermal-stage temperatures desired. In fact, in period D the thermal (second) stage was about 15°F lower than the catalytic stage. A comparison of oil properties from period C (thermal/catalytic) with those from period D (catalytic/thermal) shows the effects of reactor configuration, although the comparison is partly confounded by the difference in temperatures (825/790°F in period C, 790/774°F in period D).

Wilsonville personnel found that product yields in period D were not bad, in spite of a coal conversion of only 88.5 wt % MAF, down from 94.2 wt % MAF in period C. Distillate (C_4+) and resid yields were 54.1 and 7.5 wt % in period C, respectively, and were 59.8 and 0.3 wt % in period D. The yield of C_4+ naphtha was 11.6 wt % in period D, but only 4.4 wt % in

period C. The yield of C_1 - C_3 gas was 11.2 wt % in period C, but only 5.6 wt % in period D. So, in addition to a slightly higher distillate yield in period D, the yield structure favored increased production of naphtha and lowered gas production. Thermal reactor temperature was increased by increasing the coal feed rate (to increase the heat input from the exothermic hydrogenation reaction); however, the distillate yield decreased in response. The period D results sparked an interest in the catalytic/thermal configuration, with the hope that in a future run the thermal reactor can be run at higher temperature for increased coal conversion and distillate yield.

Before proceeding further with a discussion of oil properties, it deserves mention here that the oil samples from period 260D were found to be contaminated with Dowtherm A heat transfer fluid. The amount of contamination was found to be up to about 1.7 wt %, with contaminant concentration decreasing in the order V-131B > interstage > V-1067. More detail on the Dowtherm A contamination can be found in a separate section of this report.

Relative to period C, the whole samples from period D contained more IOM and less ash (Tables 4 through 6 and Figures 3 through 5). This reflects the lower coal conversion obtained in period D and later. Figure 6 shows the large increase in IOM in the interstage sample from period C to D, resulting from much lower first-stage coal conversion with the catalytic first stage in 260D. The V-131B and interstage whole samples in period D also showed somewhat higher concentrations of 850°F distillate and lower concentrations of the resid than in period C. This resulted in part from the use of a lower resid concentration in Wilsonville's recycle solvent blend in period D (Table 2), and contamination by Dowtherm A, which would be included in the distillate.

THF-soluble resids (Tables 7 through 9, Figures 6 through 8) from period D contained relatively more oils (hexane solubles) and less preasphaltenes, than did those from period C (especially the V-131B and V-1067 samples). With one exception, the proton aromaticity (Figures 9 through 11) of distillates (Tables 13 through 15) and THF-soluble resids

(Tables 16 through 18) dropped significantly from period C to period D. The exception was the V-131B distillate, which contained the most Dowtherm A (period D) and showed no aromaticity change from period C to D. Relatively high uncondensed aromatic hydrogen and total aromatic hydrogen contents for the V-131B distillate from period D (Table 13 and Figure 9), in the absence of other identifiable factors, indicate that the Dowtherm A contamination is responsible for this exceptional sample. Dowtherm A fluid is a mixture of diphenyl ether and biphenyl and all of its hydrogen is classified as uncondensed aromatic. In the distillate samples, an increase in paraffinic hydrogen content accompanied the aromaticity decrease from period C to period D (Figures 9-11). Also evident is a corresponding increase in hydroaromatic protons in the interstage and V-1067 distillates (Figures 10 and 11). This is most prominent in the interstage distillate and results from changing from a thermal first stage to a catalytic first stage. The catalytic first stage will produce hydroaromatics, whereas the thermal first stage will deplete them. Thus, a rather large increase is seen here.

The interstage distillate also shows a very large (~0.9 meq/g sample) decrease in phenolic -OH concentrations from period C to period D, as would be (qualitatively) expected (Figure 12, Table 19). A small decrease in the phenolic -OH concentration of the interstage resid also occurred. Curiously, the V-131B and V-1067 resids show a small increase in phenolic -OH concentration from period C to period D. This is consistent with the increased preasphaltene and decreased oil concentrations in the resids. However, the resid aromaticity in these samples decreased from period C to period D. It should be noted that the phenolic -OH, preasphaltene and oil concentrations are on a wt % sample basis, whereas the aromaticity units are % of protons. The hydrogen content of the samples must be accounted for in quantitation on a weight basis. Wilsonville data for several samples indicate that they had a higher hydrogen content in period D than in period C, consistent with Consol's usual interpretation that lower aromaticity indicates more hydrogenation. If we assume that the preasphaltene and phenolic -OH concentration in the resid samples represent functional groups in some general sense, then it is reasonable to conclude that the resids were

more hydrogenated, but less defunctionalized in period D than in period C.

Distillate donor solvent quality, as determined by microautoclave assay, decreased by several percent in each sample type from period C to period D (Table 20 and Figure 13). Whole-sample donor solvent qualities of V-131B and V-1067 oils also decreased considerably from periods C and D. The interstage whole sample increased in solvent quality from period C to period D. It is interesting that the corresponding distillate decreased in solvent quality from C to D, instead of increasing.

COMPARISON OF RUN 260 WITH RUN 258

Differences in numerous run conditions preclude a good comparison of performance during Run 260 with that of prior Wilsonville runs. In spite of the differences, it is instructive to perform such an exercise, for two important reasons. First, it is likely that something useful can be learned from such a comparison. Second, it links the past with the future by referencing historical data. In some instances, it provides a yardstick by which progress can be measured.

Two periods from Run 258 were selected for comparison with period C of Run 260 (Table 23). Run 258 (periods H through M) was the only prior run in which Black Thunder coal was the feedstock. Period 258H had the same coal feed rate as in 260C and it had the lowest first-stage temperature of any from periods 258H to 258M. Period 258M had the same equilibrium catalyst age as in 260C, but higher first-stage temperature and coal feed rate than in 260C. Other major differences in reactor volumes, interstage separation and distillation operation existed between Runs 260 and 258. However, the same supported catalyst, Shell 324, was used in both runs.

Selected yield and performance data reported by Wilsonville for periods 260C, 258H and 258M are shown in Table 24. Yields of water and C_1 - C_3 gas were higher in 260C, but the other heterogases were lower in 260C, relative to 258H and M. Distillate yield in 260C was similar to that in

the other two periods, but the distillate produced in 258H and 258M was much lighter, containing more naphtha and mid-distillate than that from 260C. Resid yield was higher, but ROSE-SR bottoms yield was lower in 260C relative to the other periods. Coal conversion and resid conversions were higher in 260C than in the comparison periods.

Table 25 gives process oil characteristics, 850°F⁺ conversions, and kinetic constants for the comparison periods. Properties for V-131B and V-1067 samples are grouped together as feed and product samples, because they are very similar. Calculated solvent quality indices (SQIs) from 260C distillate oils were similar to those from the Run 258 periods. The feed and product distillate SQI values of the Run 260C samples were, however, at the low end of the range of the Run 258 periods. This may result, in part, from the relatively high paraffinicity of the 260C distillates (all samples). The feed and product distillates from 260C were intermediate in hydrogen aromaticity relative to the comparison Run 258 distillates, but the interstage distillate and all the resids from 260C were lower in aromaticity than the comparison samples. The low aromaticity and high paraffinicity of those samples indicates that they are better hydrogenated than their Run 258 counterparts. The distillate samples from 260C were similar to Run 258 samples in phenolic -OH concentration: the feed and product distillate values from 260C were intermediate between the Run 258 values; and the interstage distillate values from 260C were slightly higher than the Run 258 values. Feed, product, and interstage resid samples from 260C were all significantly lower in phenolic -OH than corresponding Run 258 samples. The resids produced in period 260C were lower in preasphaltenes and higher in oils than the 258H and 258M resids. Asphaltenes in the period 260C resids ranged from low (feed and product samples) to intermediate (interstage sample), relative to the Run 258 periods. Overall, the resids produced in period 260C were evidently more upgraded than those from the comparison periods. The period 260C resids were more extensively hydrogenated and defunctionalized relative to resids from periods 258H and 258M. In a product quality sense, the 260C resids were higher in quality than those from the periods in Run 258. A simple explanation is the significantly lower space velocity and higher hydrogen consumption

in 260C relative to the Run 258 periods. The impact of other run conditions on resid properties is not known, however. The distillate samples from 260C were generally similar or had properties intermediate to those from 258H and 258M. Therefore, the distillates and resids behave differently in the comparison of Run 260C with Runs 258H and 258M. It is possible that other run conditions in addition to space velocity had more effect in determining the distillate properties.

Consol's calculated first-stage and total 850°F⁺ resid + UC conversions were higher in 260C than in 258H and 258M. These results are in good agreement with those of Wilsonville, where 1050°F⁺ conversion is measured. Consol obtained a second-stage 850°F⁺ conversion for 260C which was slightly lower than in 258H and 258M, whereas Wilsonville reported it to be slightly higher for 260C relative to the other two periods. The thermal reactor space velocity was particularly low in 260C relative to 258H and 258M, because of the reactor volume in use. The relative thermal/catalytic space velocities also were different in Run 260, because different reactor volumes were used in the thermal and catalytic stages. The kinetic rate constants for first- and second-stage 850°F⁺ conversion were lower in 260C than in the comparison periods. The first-stage activity for 850°F⁺ conversion in 260C was intermediate relative to the 258 periods, but the second-stage 850°F⁺ conversion activity was relatively low in 260C. It is not clear which run conditions might account for these observations. However, kinetic rate constants are directly dependent on space velocity, which was much lower in 260C than in 258H and 258M. It is probable that the kinetic model used here and at Wilsonville is not accurate. Thus, the calculated conversion activities and rate constants may be low because the activation energy is inappropriate, the assumption of first-order kinetics is incorrect, or result from other mathematical artifacts or inadequacies.

DOWTHERM A CONTAMINATION OF 260D SAMPLES

The net product from Wilsonville period 260D was reported to contain an unusual odor by Conoco personnel, who were subjecting it to crude oil inspection tests. On examining the process oils from 260D in our

laboratory, we detected the odor of diphenyl ether (one component of Dowtherm A heat transfer fluid). From our experience, we believe that substantial quantities of diphenyl ether in coal liquefaction process oils arise only through contamination from a foreign (non-coal) source; usually Dowtherm A. The presence of diphenyl ether and biphenyl, the components of Dowtherm A fluid, was detected in substantial quantities in the V-131B, V-1067 and interstage samples by gas chromatography/mass spectrometry (GC/MS) analysis of the 850°F distillate portions of those samples.

The samples Consol analyzed were from October 9, 1990. Wilsonville personnel reported⁷ that they suspected a Dowtherm A leak October 12, 1990, during period D, in the T-105 re-boiler. T-105 was inspected, but no leak was detected. Wilsonville personnel also reported⁷ that a Dowtherm A leak was detected in the transfer line between V-1082 and V-130 on November 2, 1990. After the replacement of the Dowtherm A with steam in the jacket and a later re-build of the line, no additional problem with Dowtherm A contamination was reported.

The total ion chromatograms of the three 850°F distillate samples examined by Consol (Run 260D, 10/9/90) are shown in Figure 20. The analyses were performed with a Hewlett Packard 5970B instrument equipped with a 30 m x 0.25 mm DB-5 column. The injection port was at 300°C. He carrier gas at 20 psi was used. The temperature program was as follows: 35°C for 5 min, 35°C/min to 100°C, 4°C/min to 320°C, hold for 20 min. The m/e scan was made over the range 45 to 300. The Dowtherm A components (biphenyl and diphenyl ether, peaks 4 and 5 in Figure 20) are the largest peaks in the V-131B distillate chromatogram. Those compounds decrease in prominence in the R-1235 and V-1067 distillates, but they remain significant. The Dowtherm A components were quantified by generating standard curves for both diphenyl ether and biphenyl, followed by analysis of the three distillate samples. Quantitation was based on selected ion monitoring of m/e = 153 and 154 for biphenyl and of m/e = 141, 143 and 170 for diphenyl ether. Results are shown below.

**DETERMINATION OF DOWTHERM A IN PROCESS STREAMS
FROM 10/9/90, MATERIAL BALANCE PERIOD D
Wilsonville Run 260**

Stream	wt % of Diphenyl Ether (DPE) in 850°F Distillate	wt % of Biphenyl (BP) in 850°F Distillate	DPE as % of (DPE + BP)	wt % of Dowtherm A in 850°F Distillate	wt % of Dowtherm A in Whole Oil
V-131B	4.4	1.6	73.3	6.0	1.7
R-1235	0.9	0.4	69.2	1.2	0.4
V-1067	0.4	0.2	66.7	0.5	0.2

Note that the Dowtherm A components are well resolved from all other peaks in the chromatogram of the V-131B sample (Figure 20). In the V-131B case, the diphenyl ether comprises 73.3% of the sum of the two components, as shown in the table above. The Material Safety Data Sheet (No. 000412) for Dow Chemical's Dowtherm A (effective June 18, 1990) shows Dowtherm A to be composed of 73% diphenyl ether and 27% biphenyl. Clearly, the peaks 4 and 5 in the V-131B distillate chromatogram represent Dowtherm A. Small amounts of coal-derived components elute at about the same time as the Dowtherm A components in the chromatograms of the R-1235 and V-1067 distillates (Figure 20) and, as shown above, diphenyl ether comprises less than 70% of the two components for those two samples. Either coal-derived biphenyl is contributing to the biphenyl peaks for the two latter samples, or the diphenyl ether was selectively converted to other products. As noted above, we have never detected diphenyl ether in coal liquefaction products that we knew were not contaminated. Therefore, the diphenyl ether acts as a good marker for Dowtherm A. In order to quantify the Dowtherm A in the R-1235 and V-1067 samples, we use diphenyl ether as the indicator such that

$$\text{Dowtherm A} = \text{diphenyl ether} \times \frac{1}{0.73}$$

Dowtherm A concentrations are listed in the table above. The concentrations listed for the whole oils (i.e., non-distilled oils) are simply the concentration in the distillates multiplied by the fraction

of distillate in the whole oil (Tables 4, 5 and 6). The quantities of Dowtherm A so obtained do not account for any additional hydrogenated or hydrocracked products of Dowtherm A.

As shown in the table above, the level of Dowtherm A contaminations in the three process oil streams decreases in the order V-131B > R-1235 > V-1067. Contamination is highest in the V-131B stream. It decreases in the R-1235 sample because of dilution from the feed coal products. Other contributing factors may be losses from conversion of the two components in the first-stage reactor and possibly discrimination against low-boiling components (Dowtherm A included) in the interstage sampling system. The level of contamination again decreases in the V-1067 sample, probably because of the removal of overheads (including Dowtherm A components) in the upstream separators. Also contributing to the decrease may be conversion of the two components in the second-stage reactor (future experiments are planned to examine this). These observations suggest that the contamination entered the system downstream of the second-stage reactor but upstream of V-131B (recycle slurry oil tank).

The boiling points of biphenyl (256°C) and diphenyl ether (259°C) and the decrease in their concentrations between the R-1235 and V-1067 samples indicate that the net products of the plant produced on 10/9/90 (period D) must also be contaminated with Dowtherm A. The net product of period D is undergoing petroleum inspection tests at Conoco Inc. The contaminants are expected to be concentrated in the jet fuel fraction (193 x 266°C), although the diesel fuel fraction (266 x 343°C) also may be contaminated.

PARTICIPANTS PROGRAM STATUS

SUMMARY

The following items were accomplished in the seventh quarter of this contract.

- The Analytical Needs Assessment Topical Report was issued.
- Conoco Inc., Petroleum Products Research Division, began the crude oil inspection testing of the net products from Wilsonville Run 260D. This is the second and final planned set of inspection tests.
- The final report was received from the University of Kentucky Center for Applied Energy Research, completing that subcontract.
- A draft final report was received from Western Research Institute (WRI). Additional samples were sent to expand on the reported work.
- Sample data sets and processing information packages were sent to Advanced Fuel Research, National Institute for Petroleum and Energy Research, and SRI International.
- Two bi-monthly status reports from Virginia Polytechnic Institute were reviewed. Status reports for March and April were received from Advanced Fuel Research. April and May status reports were received from SRI International.
- Preparations were begun for Phase II of the Participants Program.

DISCUSSION

The Analytical Needs Assessment was issued as a Topical Report. Copies of the report were sent to approximately thirty interested parties. Portions of the report are being included for reference in our Phase II solicitation.

Conoco Inc., Petroleum Products Research Division, began the second crude oil assay on April 2, 1991. The sample is the net product of Wilsonville Run 260D. Two distillations (9L and 6-7L charges) were required to produce enough of the jet fuel fraction for the planned tests. At the request of Burns and Roe Services Corp. (BRSC), the test plan was expanded to include bromine number (naphtha), naphthalenes content (jet fuel) and flash point (diesel fuel). We also agreed to caustic-wash each of the three fractions and to analyze the extracts by GC/MS. The crude oil was reported by Conoco to have a strong odor. Our analyses of recycle and other process oils from the same period, by GC/MS, indicate that the sample must be contaminated with Dowtherm A (a mixture of biphenyl and diphenyl ether used as a heat-transfer medium at Wilsonville). An expanded discussion of these findings can be found elsewhere in this report. Simulated distillations were substituted for ASTM D-86 distillations because of the strong odor of the samples. A final report is expected for this sample next quarter.

The final report in finished form was received from the University of Kentucky/Center for Applied Energy Research, thus completing their subcontract. The full document will be issued as a Topical Report. A brief introduction and the Executive Summary excerpted from the report can be found elsewhere in this report.

We reviewed Western Research Institute's draft final report and provided our comments. With available information, it was not possible for WRI to complete an aromatic carbon balance or hydrogen accounting on the Wilsonville plant. We sent two additional samples and a change order to WRI to allow them to complete the subcontract objectives.

Sample data sets and processing information packages have now been completed and sent to all subcontractors in Phase I of the program. We received a considerable amount of positive feed-back from the subcontractors who have found this information to be useful in assessing their analytical data. Subcontracts with The Pennsylvania State University, National Institute for Petroleum and Energy Research, SRI International, and Advanced Fuel Research are proceeding as scheduled. Status reports

were received from SRI International for April and May, and from Advanced Fuel Research for March and April.

Virginia Polytechnic Institute (VPI) issued two bi-monthly status reports. VPI reports low extraction efficiencies with the CO₂ and modified CO₂ supercritical extraction techniques chosen for use on the THF-soluble resids. Alternative extraction conditions are being explored by VPI to improve the efficiency of separation.

Preparations were begun for Phase II of the Participants Program. A tentative schedule for this phase of the program was roughed out. A letter was drafted to solicit brief technical proposals from members of the research community who may have the potential to enhance our current program. Suggestions for possible participants were obtained from a number of people including Malvina Farcasiu (DOE/PETC), Paul Scott (DOE/HQ), Herb Retcofsky (U.S. editor, FUEL), Tom Squires (Assoc. Western Universities), and Gerry Huffman (CFFLS). We received expressions of interest from Leon Stock (University of Chicago), Mohindar Seehra (West Virginia University), John Larsen (Lehigh University), Sanford Asher (University of Pittsburgh), and John Vander Sande (MIT). Phase II proposals were received from Hydrocarbon Research, Inc., Dr. Larsen, Dr. Vander Sande, Dr. Huffman, and Dr. Seehra (WVU). Dr. Seehra based his proposal on a preliminary study of six samples which we sent to him at his request. The samples were whole (850°F⁺) resids, and THF-soluble and insoluble portions of the resid. One set of samples was from Wilsonville Run 259, and the other from HRI Run CC-5.

SUMMARY OF UNIVERSITY OF KENTUCKY/CENTER FOR APPLIED ENERGY RESEARCH FINAL REPORT

GENERAL DESCRIPTION

This section consists of two main parts. The first is Consol's summary of the program and the results. The second consists of the Executive Summary supplied by the subcontractor.

SUMMARY

This study demonstrated the feasibility of using fluorescence and reflectance microscopy techniques for the examination of distillation resid materials derived from direct coal liquefaction. Resid, as defined here, is the 850°F+ portion of the process stream, and includes soluble organics, insoluble organics and ash. The technique can be used to determine the degree of hydrogenation and the presence of multiple phases occurring within a resid sample. It can also be used to infer resid reactivity. The technique is rapid, requiring less than one hour for sample preparation and examination, and thus has apparent usefulness for process monitoring. Additionally, the technique can distinguish differences in samples produced under various process conditions. It can, therefore, be considered a potentially useful technique for the process developer. Further development and application of this analytical method as a process development tool is justified based on these results.

PROGRAM DESCRIPTION

This report describes the work performed at the University of Kentucky/Center for Applied Energy Research (UK/CAER) under a subcontract to Consolidation Coal Co., Research and Development. Consol's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of

participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction, and those which have not been fully demonstrated in this application. Consol is providing well-documented samples from different direct coal liquefaction production facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed then is evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

UK/CAER used fluorescence and reflectance microscopy to analyze distillation residues (850°F⁺). These are solids at room temperature, and contain THF-soluble and -insoluble organics and mineral matter. The samples were produced at two different continuous liquefaction facilities: the 6TPD Wilsonville Advanced Coal Liquefaction R&D Facility and the 30-50 lb/day Hydrocarbon Research Inc. (HRI) bench unit. Two major processing parameters were varied among the Wilsonville runs. These were feed coal and reactor configuration (thermal/catalytic vs. catalytic/catalytic). Samples from Wilsonville were taken from two locations: between the reactors and after the second-stage reactor. These samples are expected to represent different extents of coal liquefaction. The Wilsonville samples were composites of samples taken over long periods of single runs. Samples from HRI were chosen to represent production of material as the catalyst aged during one liquefaction run.

Major Findings Reported by UK/CAER

The following principal observations for the application of fluorescence and reflectance microscopy to coal liquefaction materials were reported by UK/CAER. An expanded discussion can be found in the report, pages 15-33. Fluorescence and reflectance spectra of distillation resids were measured through the use of a microscope photometer system. Wilsonville samples taken at different sampling locations in the plant were found to exhibit distinct variations in fluorescence intensities and spectral distribution. The degree of upgrading the process stream undergoes in the production facility could be evaluated from this information. Relative resid reactivity also could be inferred by direct comparison of the spectral intensities and wavelengths of the fluorescence spectra, and the reflectance spectra, of different samples within a single production run and of samples from different runs. The inferred reactivities are consistent with complementary information such as volatile matter contents, aromaticities and phenolic -OH infrared peak positions, as well as with fundamental factors affecting fluorescence and reflectance. With homogeneous samples, such as the HRI samples, the repeatability of the technique is well within inter-sample variability.

Consol Evaluation

The fluorescence microscopic technique was shown to be potentially useful for the analysis of solid direct coal liquefaction resid samples. A specific and unique advantage of this technique for the analysis of resids is that the whole resid samples can be examined without alteration. This results in a particularly important feature of the technique which is the ability to detect and quantify inhomogeneous components of solid resid samples including unreacted macerals, mineral matter, and multiple resid phases. In addition to qualitative observations, the technique can provide quantitative data. The measured fluorescence intensities provide a relative scale to determine the degree of aromatic condensation found in different samples. The interpretation of these values in the context of coal liquefaction and resid reactivity could indicate which resids are more refractory to upgrading. The determina-

tion of red/green quotients (Q), obtained from the fluorescence spectra, is a rapid method to assess the degree of fluorescence heterogeneity of the resids. The fluorescence spectrum apparently is responsive to process trends. The degree of liquefaction or upgrading of coal liquids is discernable among different samples taken at different points in the continuous liquefaction process. In addition, the relative degree of resid hydrogenation can be determined in samples taken consecutively during a liquefaction run in which the major process change is catalyst age.

It is difficult to assess the precision of the technique due to the inherent variabilities of the samples examined here. However, when homogeneous samples, or the portion of heterogeneous samples displaying only one fluorescence population, are examined, repeatability is good. Long-term reproducibility of fluorescence results can be poor and misleading if spectral changes in the mercury arc lamp emissions, as the lamp ages, are not considered. Inter-laboratory comparisons of data generated outside the scope of this program show that while relative results are consistent, absolute values are not reproducible. An expanded discussion on these points can be found in the report, pages 34-39.

The repeatability of the method and its ability to discern differences and similarities among samples were tested through the use of two "blind" samples. The UK researchers correctly identified that blind sample No. 13 was very similar to sample No. 12 (a homogeneous sample; the pressure filter liquid resid from HRI Run I-27, period 25). In fact, sample Nos. 12 and 13 are aliquots of the same sample. The UK researchers indicated that blind sample No. 14 was most similar to sample No. 1 (the interstage resid from Wilsonville Run 251-II). Actually, sample No. 14 was a separate aliquot of sample No. 2 (the recycle resid from Wilsonville Run 251-II). The Wilsonville Run 251-II samples were highly heterogeneous. Therefore, the UK researchers correctly identified the one homogeneous blind sample and correctly identified the processing run (but not the sampling location) of the one heterogeneous blind sample. Considering the high degree of heterogeneity found in the one

blind sample, the fluorescence method proved to be useful for identification of the two unknowns. See page 32 of the report for detailed discussion.

The technique is relatively rapid, requiring about one-half hour for sample preparation and only a few minutes for sample examination. The initial capital investment, including the cost of the microscope, computer, lenses, and ancillary equipment, is approximately \$85,000. The labor costs are relatively low. Once the initial system is set up, the sample preparation and examination can be done by a laboratory technician. Data interpretation is minimal for samples taken within a single process in which variables, such as catalyst age, are changed systematically. Data can be quantified and interpreted based on an established calibration.

Further Development

There are a number of avenues for further development of this technique for coal liquefaction materials. Additional chemical information may be obtainable from a more sophisticated analysis of the fluorescence spectra. Quantification of the qualitative observations may be possible through the use of a calibration that is based on well-controlled liquefaction experiments in which process variables are systematically changed. Sample preparation times can be substantially reduced if faster setting epoxy resins can be found which do not interfere with the microscopic analysis. The automation of the technique may lead to an at-site, or near-line, method for process monitoring.

UK/CAER SUMMARY

Under U.S. Department of Energy contract No. DE-AC22-89PC89883, it is the intent of Consolidation Coal Company, Pittsburgh, Pennsylvania, to investigate and develop existing analytical techniques which could potentially lead to more effective liquefaction process control. In this context, it is the goal of this subcontract to evaluate the usefulness of a fluorescence microscopy methodology for the analysis of coal-derived resids and interpret the data in light of liquefaction processing

conditions, process response, the inferred resid reactivity, and in relation to results of other analytical data. The fluorescence technique utilized in this study has been widely applied to coal and kerogen characterization, albeit with some modifications, but is novel in its application to the characterization of coal liquids.

Fluorescence spectra (ultraviolet-violet light), and reflectances (white light) of non-distillable (850°F⁺, or 454°C⁺) coal liquids (resid) were measured by a microscope spectrophotometer system. The fluorescence emission, from 470 to 700 nm, was taken from a polished resid sample surface by scanning at least five resid particles per sample, with the spectrum for each particle representing the average of 20 scans. The proportion of white light reflected off a polished resid surface (% reflectance), in air immersion, was measured for 25 resid particles per sample, and reported as a mean value. Volatile matter yield also was obtained for each sample, as an approximate indicator of resid reactivity.

Well-documented resid samples from the Wilsonville CC-ITSL pilot plant and HRI CTSL ebullated bed bench unit were provided by Consolidation Coal Company. Fluorescence, reflectance, and chemical data for Wilsonville Runs 250, 251-II, 257, and 259 were interpreted in relation to reactor modes (catalytic/catalytic vs thermal/catalytic), sample location (interstage vs recycle), and coal feedstock, although other processing parameters were varied over the course of these runs. Pressure filter liquid resids from HRI Run I-27 were instantaneous samples, produced under more stable operating conditions, with monotonic changes in catalyst age, reactor temperatures, solvent cut-point, and the solvent/coal ratio as the run progressed. Two unidentified resid samples were provided for experimental control.

It was concluded from an evaluation of the fluorescence microscopical technique that experimental precision was difficult to assess for the Wilsonville resids because of the inherent sample fluorescence variability. The interstage and recycle resids from Run 257 (Illinois No. 6 coal, C/C) exhibited distinct, usually inter-particle, variations

in fluorescence intensities and spectral distributions. The Run 251-II (Wyodak coal, T/C) recycle resid contained an intensely yellow fluorescing component whose fluorescence properties were distinctly different to the majority of the resid. Although the origin of this material is problematical, its presence may indicate that the resid contains two or more incompatible phases, and illustrates a distinct advantage of the fluorescence microscopy technique; the ability to resolve inhomogeneities within resid samples. The analytical precision of the technique was evaluated with more homogeneous resid samples, such as the Wilsonville Run 250 (Illinois No. 6 coal, T/C) resids and, particularly, the pressure filter liquids from HRI Run I-27, which revealed that spectral intensities are repeatable within 3 to 4 nm.

Within the precision limits of the microscopical techniques, it was concluded that resids from Wilsonville Runs 251-II (Wyodak coal, T/C), 250 (Illinois No. 6 coal, T/C), and 257 (Illinois No. 6 coal, C/C) had been upgraded to less condensed, lower molecular weight products in the second stage when compared to the interstage resids. This is based on a shift of the average fluorescence spectra to shorter wavelengths, concomitant with an intensity increase and reflectance decrease, from the interstage to recycle resid samples. Fluorescence spectra for Run 259 (Pittsburgh seam coal, C/C) interstage and recycle resids were nearly identical, suggesting that the second catalytic stage provided only minor additional hydrogenation.

Interpretations of fluorescence in the context of resid reactivity were founded on the supposition that resids comprised of more highly condensed aromatics are relatively refractory to upgrading and would exhibit relatively higher reflectance values, low fluorescence intensities, and maximum fluorescence intensities shifted to longer wavelengths. It was, therefore, concluded that the Run 257 resids (Illinois No. 6 coal, C/C) were probably the most reactive, as evidenced by lower reflectances, high volatile matter yields, and shorter fluorescence spectral peak wavelengths than the other Wilsonville resids investigated, followed by resids from Run 250 (Illinois No. 6 coal, T/C) and 251-II (Wyodak coal, T/C). Resids produced in Run 259 (Pittsburgh seam coal, C/C) probably

would be the least reactive, based on relatively high reflectances, low volatile matter yields, and fluorescence spectra shifted to longer wavelengths than the other Wilsonville resids studied.

Fluorescence and reflectance data suggest that during HRI Run I-27 (Illinois No. 6 coal, C/C), there was progressively less hydrogenation of the resid with increasing catalyst age, reactor temperature, and solvent cut-point, and a decrease in the solvent/coal ratio. This was supported by proton NMR data and phenol peak location shifts, which indicated an increased condensation of aromatic structures during the run. A decrease in the volatile matter yield of resids from run day 2 to day 25 suggests that a decrease in resid reactivity occurred over the course of HRI Run I-27.

It is concluded that quantitative fluorescence microscopy is potentially a rapid, inexpensive technique, which can provide new insight into the structure and composition of coal-derived resid. Consequently, an automated fluorescence microscopical technique, as an integral component of a liquefaction process monitoring scheme, could lead to more effective process control. Perhaps the greatest strength of quantitative fluorescence microscopy lies in its ability to resolve inhomogeneities within coal-derived resid samples, including, but not limited to, minerals, unreacted macerals, and multiple resid phases (as determined by reflectance and fluorescence properties). This capability is not possible with most other analytical techniques which typically require dissolution of the resid in a solvent prior to analysis. Whereas these analytical techniques provide chemical and structural information on a homogenized resid sample, and only on the solvent-soluble portion, inherent variability within the coal liquids can be identified and measured with fluorescence microscopical methods.

WORK IN PROGRESS

PREHEATER SIMULATION STUDIES

Preheater studies using the feed coal for Wilsonville Run 261 (Illinois 6 seam, Burning Star 2 Mine) and a V-131B (recycle) oil from Run 261 period B were continued this quarter. Preliminary results show that the four-hour soak at 370°F of the coal/recycle-solvent mixture prior to a rapid rise in temperature, corresponding to the conditions which the coal slurry undergoes in the Wilsonville preheaters, improves coal conversion over that which is obtained without the low-temperature four-hour soak. The quality of the converted material is under investigation.

O-ALKYLATION OF PHENOLIC GROUPS

A large batch of tetrahydrofuran (THF) -soluble recycle solvent from Wilsonville Run 261 period B was prepared for use in alkylation studies. The alkylation reaction was carried out by Liotta's method. The alkylated material was analyzed by FTIR. The phenolic -OH content of the THF-soluble starting material was 0.41 meq/g, the O-alkylated material had 0.09 meq/g -OH. Microautoclave assays were run, using modified equilibrium conditions, on the THF-soluble starting material and the O-alkylated material. The conversion of Old Ben No. 1 Mine coal with the THF-soluble oil was 81.7 wt %, comparable to the result previously obtained with the whole oil (80.8 wt %). The O-alkylated sample gave a coal conversion of only 67.7 wt %. This value was considered suspect; therefore, a second batch of O-alkylated THF-soluble recycle oil (V-131B) from Wilsonville Run 261B was prepared. The material was examined by FTIR and found to contain 0.20 meq/g phenolic -OH. In comparison, the starting material had 0.41 meq/g -OH. A microautoclave assay on the sample gave coal conversion of 68.9 wt %, comparable to the first batch of O-alkylated material (67.7 wt %), but much lower than the starting THF-soluble oil (81.7 wt %). A blank run was made to determine if the O-alkylation or the experimental procedures are lowering the yields. The sample was handled using the same procedure employed for the alkylated material; however, no CH_3I or TnPAH was added to the reaction vessel.

This material after handling had a phenolic -OH content of 0.37 meq/g. A microautoclave assay with this control sample gave 77.8% coal conversion, only slightly lower than the 81.7% found for the starting THF-soluble oil, and considerably better than the 68.3% (average) found for the O-alkylated oil. This indicates that the O-alkylation is lowering the solvent quality of the oil. These findings are under further investigation.

WILSONVILLE 261

All samples were received from Wilsonville Run 26i periods A through G, with the exception of the feed (recycle) solvent from period G. During this period, the resid injection system was tested, so the feed solvent sample must be blended from three different component samples (the heavy distillate, ashy resid and deashed resid). Sample workup and analysis is complete through period E (except for the solvent fractionation procedure to be done when all the resid samples are available). Work-up of samples from period F are in progress.

Section 3

EXPERIMENTAL

Experimental details are described, where appropriate, in the Discussion section of this report. Details of the other analytical techniques used in this work were reported previously.^{3,4}

Section 4

REFERENCES

1. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handouts from Technical Meeting No. 106 (Sept. 19-20, 1990), No. 107 (November 14-15, 1990), and No. 108 (January 17, 1991).
2. Adapted from various handouts from Wilsonville Technical Review Meetings.
3. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization Final Report - October 1980 through March 1985", DOE/PC 30027-61, March 1985.
4. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1985", DOE/PC 70018-13, December 1985.
5. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Coal Liquefaction Process Solvent Characterization and Evaluation - Final Report", DOE/PC 70018-70, September 1989.
6. Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Technical Progress Report, October 1 through December 31, 1989", DOE/PC 89883-10, October 1990.
7. Davies, O. L., letter to E. B. Klunder (U.S. Department of Energy), June 14, 1991.

TABLE 1
DAILY OPERATING CONDITIONS
Wilsonville Run 260

Date, 1990	Opera- tion Day	Balance Period (c)	Thermal Stage (a) Conditions		Catalytic Stage (b) Conditions						
			Avg. Temp., °F	Thermal Space Rate lb MF Coal/ hr ft ² C (d,e)	Avg. Temp., °F	Space Velocity			lb (feedd + Cl)/lb Cat. (f)	lb MF Coal/ lb Cat.	lb MF Coal/ ft ² Cat. (g)
						lb Feed/ lb Cat-hr (f)	lb MF Coal/ hr-ft ² Cat. (f)	lb Feed/ hr-ft ² Cat. (g)			
8/10	23	A*	825	43.2	790	3.95	-	63.3	1320	680	3.56
8/25	38	B*	840	37.4	790	3.36	-	54.8	1375	672	3.63
8/26	39	(B*)	840	37.5	789	-	-	54.9	1325	648	3.50
9/5	49	C	825	31.0	790	3.10	45.30	45.3	-	651	3.52
10/9	63	D	774	31.0	791	2.83	31.00	45.4	1439	658	3.55
10/29	79	E	796	42.5	789	3.98	42.50	62.2	1503	655	3.53
11/5	86	F	802	42.5	771	4.01	42.50	62.3	1457	629	3.40

(a) Thermal stage (reactor R-1235) was first stage for periods A, B and C, and second stage for periods D, E and F.

(b) Catalytic stage (reactor R-1236) was second stage for periods A, B and C, and first stage for periods D, E and F.

(c) Periods marked with an asterisk were unstable.

(d) C is a constant.

(e) Wilsonville Phase 2 data.

(f) Wilsonville Phase 3 data (used in material balances).

NOTE: Other conditions are listed in Table 2.

/ls

TABLE 2
OPERATING CONDITIONS AND YIELDS FOR MATERIAL BALANCE PERIODS

Operating Period	260A (Unstable)	260B (Unstable)	260C	260D	260E	260F
Date, 1990	8/8-10,14	8/25,27-29	9/2-5	10/7-10	10/26-30	11/4-8
Operation Days	21-23, 27	39-42	46-49	61-64	76-80	85-89
<u>Coal</u>						
Feed rate, MF lb/hr	352.2	302.9	251.0	253.0	348.3	346.6
Ash, wt % MF	6.1	6.1	6.2	6.2	6.3	6.4
Conc. in slurry, wt % MF	30.1	30.2	30.4	30.2	30.2	30.0
<u>Process Solvent, wt %</u>						
Resid	40.1	39.9	40.4	38.6	38.8	38.7
Ol	20.1	20.0	20.7	20.0	20.0	19.7
<u>First Stage</u>						
Reaction temp., °F (avg)	825	840	825	790	789	774
Inlet H ₂ partial pressure, psia	2622±60	2680±4	2760±20	2713±6	2677±11	2703±26
Space vel., lb feed/hr/lb cat				2.8	4.0	4.0
Space vel., lb MF coal/hr/ft ³ cat				45.6	62.7	62.4
Catalyst type (supported)	None	None	None	S324	S324	S324
Catalyst age, lb (res+Ol)/lb cat				1415±20	1416±31	1497±31
lb MF coal/lb cat				648±11	638±15	645±15
Coal space rate, lb MF coal/hr/ft ³ (thermal) (*C° is a constant)	43.3C	37.2C	30.8C			
Cat add'n rate, lb/ton MF coal				3.0	3.0	3.0
Fe ₂ O ₃ addition rate, wt % MF coal	2.0	2.0	2.0	2.0	2.0	2.0
<u>Second Stage</u>						
Reaction temp., °F (avg)	790	790	790	774	797	804
Inlet H ₂ partial pressure, psia	2473±21*	2404±14*	2107±34**	2240±10**	2174±**	2149±19**
Space vel., lb feed/hr/lb cat	3.9	3.3	3.1			
Space vel., lb MF coal/hr/ft ³ cat	63.4	54.5	45.5			
Catalyst type (supported)	S324	S324	S324	None	None	None
Catalyst age, lb (res+Ol)/lb cat	1330±31	1362±25	1368±20			
lb MF coal/lb cat	665±15	666±10	661±12			
Coal space rate, lb MF coal/hr/ft ³ (thermal) (*C° is a constant)				31.1C	42.8C	42.6C
Cat add'n rate, lb/ton MF coal	3.0	3.0	3.0			
ROSE-SR SM DAS type	2614	2544	2504	2414	2454	2454
<u>Yield, wt % MAF coal</u>						
H ₂	-6.3±0.2	-6.5±0.2	-6.3±0.2	-6.2±0.3	-5.6±0.3	-5.4±0.2
Water	16.3±1.1	15.9±0.6	18.8±0.6	18.6±0.4	17.2±1.2	16.3±1.4
H ₂ S, CO, CO ₂ , NH ₃	6.7±1.5	10.3±0.7	4.1±0.6	3.4±0.1	4.3±0.9	4.0±0.2
C ₁ -C ₃ gas	7.8±1.1	14.2±0.5	11.2±0.1	5.6±0.2	6.2±0.9	5.2±0.3
C ₄ + distillate	55.0±2.4	54.7±2.5	54.1±3.8	59.8±3.3	52.2±2.2	48.1±3.0
C ₄ + naphtha	17.6±3.0	9.7±1.2	4.4±0.9	11.6±0.8	13.3±3.4	11.0±0.7
Middle distillate	9.1±1.1	5.7±1.8	4.0±0.9	6.7±0.4	7.4±1.6	7.1±0.4
Distillate solvent	28.4±3.0	39.2±2.0	45.7±2.7	41.5±3.6	31.5±6.0	31.1±3.1
Resid (a)	8.5±3.0	2.0±2.3	7.5±3.1	0.3±2.4	5.6±3.1	8.7±4.7
ROSE-SR SM Bottoms Product	11.9±0.3	9.4±0.6	10.7±0.5	18.5±0.9	20.1±0.9	23.0±2.5
<u>H₂ efficiency (x 100)</u>						
lb C ₄ + dist/lb H ₂ consumed	8.7±0.2	8.5±0.4	8.5±0.3	9.6±0.7	9.2±0.3	9.0±0.6
<u>C₁-C₃ selectivity (x 100)</u>						
to C ₄ + distillate	14.2±2.1	26.1±1.7	20.7±1.3	9.5±0.6	12.0±1.9	11.0±0.7
<u>Coal conversion, wt % MAF</u>						
1st stage	92.2±0.9	93.4±2.3	92.9±1.4	73.5±3.9	72.1±1.0	70.7±2.8
1st and 2nd stages	95.1±0.2	96.2±0.1	95.0±0.5	91.1±0.7	89.4±0.8	88.4±0.9
Overall TSL	93.7±0.3	95.4±0.6	94.2±0.6	88.5±1.2	87.0±1.0	85.8±1.8
<u>Resid + UC conversion (b), wt % feed</u>						
1st stage	29.1±1.1	33.2±3.2	33.3±0.8	29.1±1.8	27.0±1.4	24.8±0.8
2nd stage	12.4±2.8	11.9±4.2	16.7±2.6	10.5±3.3	9.0±1.1	7.1±1.2

(a) Includes UC accumulation; (b) phase 2 data

* not adjusted for H from separator; **estimated

/lb

TABLE 3
ANALYSES OF SUBBITUMINOUS FEED COAL
Wilsonville Run 260

	Black Thunder 6-13-90 Composite
Wilsonville Sample No.	9827
Moisture, wt % as determined	25.38
<u>Proximate, wt % dry basis</u>	
Volatile Matter	45.01
Fixed Carbon	48.64
Ash	6.35
<u>Ultimate, wt % MAF Basis</u>	
Carbon	75.30
Hydrogen	5.37
Nitrogen	1.06
Oxygen (diff.)	17.91
Sulfur, Total	0.51
Pyrite	0.09
Sulfate	0.03
Organic (diff.)	0.39
Chlorine	0.078
HHV, Btu/lb MAF Basis	12904
<u>Elemental, wt % of Ash</u>	
Na ₂ O	1.00
K ₂ O	0.33
CaO	20.52
MgO	4.43
Fe ₂ O ₃	4.53
TiO ₂	1.19
P ₂ O ₅	0.91
SiO ₂	32.39
Al ₂ O ₃	15.56
SO ₃	18.50
Unaccounted	0.64

/ls

TABLE 4

**COMPONENT DISTRIBUTION OF V-131B SAMPLES
Wilsonville Run 260**

Sample				wt % of Sample			
Date, 1990	Time	No.	Period	850°F Dist.	THF- Soluble Resid	IOM	Ash
8/10	0930	11079	A	25.2	51.5	11.5	11.3
8/28	0635	11925	B	24.4	54.1	7.1	13.0
9/5	0015	14176	C	21.4	56.3	6.5	13.4
10/9	1530	14878	D	27.8	51.1	10.2	9.9
10/29	1740	15639	E	23.7	54.8	11.5	9.2
11/5	2355	15977	F	19.4	60.0	11.4	8.0

TABLE 5

**COMPONENT DISTRIBUTION OF V-1067 SAMPLES
Wilsonville Run 260**

Sample				wt % of Sample			
Date, 1990	Time	No.	Period	850°F Dist.	THF- Soluble Resid	IOM	Ash
8/10	1500	11093	A	26.2	49.7	9.6	13.8
8/25	1500	11902	B	26.3	50.9	7.4	14.6
9/5	DC	14154	C	27.6	49.8	7.2	15.0
10/9	DC	14850	D	28.4	47.2	11.8	11.6
10/29	DC	15614	E	24.1	50.1	13.1	11.8
11/5	DC	15954	F	18.0	56.2	14.4	10.6

TABLE 6

**COMPONENT DISTRIBUTION OF INTERSTAGE SAMPLES
Wilsonville Run 260**

Sample				wt % of Sample			
Date, 1990	Time	No.	Period	850°F Dist.	THF- Soluble Resid	IOM	Ash
8/10	0500	11071	A	19.1	61.0	6.0	13.6
8/25	1700	11915	B	23.8	52.9	8.2	13.9
9/5	0500	14136	C	24.6	52.2	7.8	14.0
10/9	0500	14837	D	29.8	42.1	17.3	10.0
10/29	1700	15611	E	25.9	43.0	20.1	9.0
11/5	1800	15966	F	25.0	43.4	21.6	8.8

/ls

TABLE 7

**SOLUBILITY FRACTIONATION OF V-131B SAMPLES
Wilsonville Run 260**

Date, 1990	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
8/10	60.6	26.1	13.4
8/26	65.8	24.1	10.1
9/5	69.0	22.8	8.2
10/9	60.4	24.8	14.8
10/29	59.3	23.2	17.5
11/5	58.8	23.6	17.6

TABLE 8

**SOLUBILITY FRACTIONATION OF V-1067 SAMPLES
Wilsonville Run 260**

Date, 1990	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
8/10	58.4	24.9	16.7
8/25	64.1	23.0	12.9
9/5	68.3	21.5	10.2
10/9	57.8	24.5	17.7
10/29	54.7	24.5	20.8
11/5	54.6	24.2	21.2

TABLE 9

**SOLUBILITY FRACTIONATION OF INTERSTAGE SAMPLES
Wilsonville Run 260**

Date, 1990	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
8/10	54.4	25.5	20.1
8/25	60.7	24.0	15.3
9/5	61.3	25.3	13.4
10/9	59.2	23.8	17.0
10/29	54.9	24.2	20.9
11/5	48.2	25.6	26.1

/ls

TABLE 10
PROTON DISTRIBUTION OF V-131B WHOLE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	24.0	2.9	17.6	8.3	13.9	22.9	10.3
8/26	27.1	3.4	18.9	8.2	14.5	18.3	9.7
9/5	25.6	4.0	18.2	8.8	14.5	19.4	9.5
10/9	19.6	4.7	16.0	8.8	15.1	23.6	12.1
10/29	20.2	3.1	17.4	8.6	15.2	23.9	11.6
11/5	20.3	3.2	18.2	8.8	15.3	23.9	10.4

TABLE 11
PROTON DISTRIBUTION OF V-1067 WHOLE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	22.8	4.6	17.3	9.2	14.0	20.6	11.6
8/25	26.8	3.4	19.6	8.9	14.7	17.9	8.6
9/5	23.7	5.1	17.2	9.2	14.3	19.4	11.0
10/9	17.3	4.4	16.9	8.8	16.2	24.0	12.4
10/29	17.9	3.5	17.4	9.0	15.7	23.7	12.8
11/5	19.6	3.9	17.2	8.9	15.3	22.9	12.2

TABLE 12
PROTON DISTRIBUTION OF INTERSTAGE WHOLE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	24.3	4.8	16.5	9.5	12.2	21.4	11.3
8/25	27.1	5.8	17.2	9.5	12.0	19.1	9.3
9/5	25.9	4.6	18.4	9.5	13.3	18.9	9.4
10/9	15.7	4.2	16.2	8.9	16.7	24.9	13.4
10/29	16.1	3.6	16.5	8.8	15.7	26.5	12.8
11/5	15.8	4.2	15.4	8.9	15.5	25.6	14.6

/1s

TABLE 13
PROTON DISTRIBUTION OF V-131B DISTILLATE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	13.9	4.4	13.9	7.1	13.9	32.0	13.8
8/26	14.8	5.1	14.1	8.1	13.2	29.8	15.0
9/5	14.3	5.1	14.9	8.4	14.1	30.6	12.6
10/9	12.9	6.1	12.6	7.0	14.1	33.1	14.1
10/29	10.9	3.6	11.8	7.0	13.5	37.6	15.6
11/5	11.2	3.4	13.0	7.1	14.9	37.2	13.1

TABLE 14
PROTON DISTRIBUTION OF V-1067 DISTILLATE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	13.8	4.9	15.4	9.0	15.3	28.5	13.2
8/25	14.1	6.1	14.4	9.2	15.0	28.1	13.2
9/5	13.6	6.0	14.7	9.2	15.9	27.7	12.8
10/9	10.0	4.9	13.7	8.1	17.3	31.2	14.8
10/29	10.6	4.5	13.8	7.8	16.1	33.2	14.0
11/5	10.7	4.3	14.1	8.3	16.2	32.7	13.6

TABLE 15
PROTON DISTRIBUTION OF INTERSTAGE DISTILLATE SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	13.0	6.1	13.1	9.9	12.9	30.9	14.1
8/25	15.0	7.3	14.1	10.6	12.4	28.8	11.8
9/5	14.1	6.8	15.1	10.0	13.8	28.0	12.3
10/9	9.0	4.5	12.9	10.9	17.7	30.9	14.1
10/29	8.9	4.3	12.6	8.3	16.1	34.2	15.5
11/5	8.3	4.4	12.1	8.2	15.9	35.2	15.9

/1s

TABLE 16
PROTON DISTRIBUTION OF V-131B RESID SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	24.8	4.7	17.9	8.7	14.5	15.5	13.9
8/26	34.1	4.4	20.3	8.7	12.9	12.6	7.0
9/5	32.8	3.1	21.3	8.5	13.9	13.7	6.8
10/9	24.0	3.9	19.1	8.5	15.0	20.0	9.6
10/29	23.5	4.2	20.0	8.8	15.3	18.3	9.8
11/5	23.9	2.7	19.1	8.7	15.3	21.1	9.2

TABLE 17
PROTON DISTRIBUTION OF V-1067 RESID SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	30.3	4.4	19.3	8.7	12.8	14.7	9.9
8/25	35.0	3.6	21.6	8.6	13.1	11.8	6.4
9/5	32.3	3.8	21.1	8.8	13.8	13.4	6.8
10/9	24.2	3.3	20.9	8.8	15.4	19.0	8.5
10/29	24.0	4.0	19.7	9.0	14.4	18.5	10.4
11/5	25.0	3.8	19.3	8.6	14.1	20.1	9.2

TABLE 18
PROTON DISTRIBUTION OF INTERSTAGE RESID SAMPLES
Wilsonville Run 260

Date, 1990	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
8/10	32.4	3.0	20.6	9.0	12.0	15.8	7.2
8/25	36.7	4.2	20.3	9.0	11.5	11.5	6.6
9/5	33.4	5.0	20.5	8.9	12.3	13.0	6.9
10/9	23.6	2.6	21.2	8.9	16.5	19.1	8.2
10/29	23.0	3.8	19.2	9.0	14.5	20.5	9.9
11/5	22.6	3.6	19.4	8.8	14.6	20.8	10.1

/ls

TABLE 19
PHENOLIC -OH CONCENTRATION BY FTIR
Wilsonville Run 260

	Date, 1990	Phenolic -OH Concentrations, meq/g			
		Dist.	ν , cm^{-1}	Resid	ν , cm^{-1}
<u>V-131B</u>					
A	8/10	0.35	3307	0.80	3297
B	8/26	0.40	3307	0.67	3294
C	9/5	0.42	3307	0.65	3295
D	10/9	0.31	3308	0.81	3299
E	10/29	0.33	3306	0.86	3298
F	11/5	0.36	3307	0.86	3298
<u>V-1067</u>					
A	8/10	0.39	3309	0.81	3296
B	8/25	0.41	3308	0.68	3294
C	9/5	0.45	3309	0.67	3296
D	10/9	0.42	3311	0.88	3298
E	10/29	0.46	3309	0.93	3297
F	11/5	0.53	3309	0.94	3297
<u>Interstage</u>					
A	8/10	1.06	3309	1.01	3295
B	8/25	1.26	3308	0.93	3294
C	9/5	1.20	3309	0.94	3293
D	10/9	0.34	3313	0.82	3299
E	10/29	0.41	3312	0.89	3298
F	11/5	0.52	3311	0.92	3298

/ls

TABLE 20
MICROAUTOCLAVE TEST RESULTS
Wilsonville Run 260

Date, 1990	Coal Conversion, wt % MAF					
	V-131B		V-1067		Interstage	
	Dist.	Whole	Dist.	Whole	Dist.	Whole
8/10	77.6	68.7	81.7	65.8	68.2	52.0
8/26	80.3	60.9	82.9*	54.0*	70.2*	56.2*
9/5	77.8	59.0	84.5	70.1	74.5	60.0
10/9	70.7	36.5	73.5	50.3	71.7	80.5
10/29	63.3	59.8	66.6	47.6	65.7	51.9
11/5	59.5	62.7	62.7	60.5	65.6	69.4

*8/25 samples.

Conditions: MOD-EQ, Old Ben Mine No. 1 Coal

/ls

TABLE 21
CONVERSION OF RESID COMPONENTS
Wilsonville Run 260

Period	Conversion, %					
	850°F ⁺ (a)	Oils	Asphal- tenes	Preasphal- tenes	Coal + IOM	THF-Soluble Resid
First Stage						
A*	33.7	-8.9	-18.5	-81.9	88.2	-21.3
B*	32.5	-1.5	-9.6	-66.7	80.7	-10.0
C	33.5	5.2	-18.4	-74.3	81.1	-6.7
D	26.6	-1.6	0.5	-19.1	57.1	-3.7
E	21.7	3.7	-8.5	-24.2	48.8	-4.0
F	28.8	27.2	4.2	-30.9	48.8	11.7
All Periods: Avg ±S.D.	29.5 ±4.7	4.0 ±12.4	-8.4 ±9.4	-49.5 ±27.8	67.5 ±17.8	-5.7 ±10.7
Periods A-C: Avg ±S.D.	33.2 ±0.6	-1.7 ±7.1	-15.5 ±5.1	-74.3 ±7.6	83.3 ±4.2	-12.7 ±7.7
Periods D-F: Avg ±S.D.	25.7 ±3.6	9.8 ±15.3	-1.2 ±6.5	-24.7 ±6.0	51.6 ±4.8	1.4 ±9.0
Second Stage						
A*	12.8	13.8	21.6	33.3	-57.7	19.7
B*	9.2	3.3	12.2	22.8	14.1	8.4
C	11.3	0.8	24.3	32.2	13.8	11.0
D	14.4	5.6	0.5	-0.6	41.2	3.3
E	23.6	11.5	10.0	11.6	50.3	11.1
F	9.8	-21.8	-1.6	12.7	44.7	-7.5
All Periods: Avg ±S.D.	13.5 ±5.3	2.2 ±12.7	11.2 ±10.6	18.6 ±13.2	17.7 ±40.1	7.7 ±9.1
Periods A-C: Avg ±S.D.	11.1 ±1.8	6.0 ±6.9	19.4 ±6.4	29.4 ±5.8	-9.9 ±41.4	13.0 ±5.9
Periods D-F: Avg ±S.D.	15.9 ±7.0	-1.6 ±17.7	3.0 ±6.2	7.9 ±7.4	45.4 ±4.6	2.3 ±9.4
Total						
A*	42.1	6.1	7.1	-21.4	81.3	2.6
B*	38.7	1.8	3.8	-26.7	83.4	-0.8
C	41.0	6.0	10.4	-18.2	83.7	5.0
D	37.2	4.1	1.0	-19.8	74.8	-0.2
E	40.2	14.8	2.4	-9.8	74.6	7.6
F	35.8	11.4	2.7	-14.3	71.7	5.1
All Periods: Avg ±S.D.	39.2 ±2.4	7.4 ±4.8	4.6 ±3.5	-18.7 ±6.4	78.2 ±5.2	3.2 ±3.3
Periods A-C: Avg ±S.D.	40.6 ±1.8	4.6 ±2.4	7.1 ±3.3	-22.8 ±5.4	82.8 ±1.3	2.3 ±2.9
Periods D-F: Avg ±S.D.	37.7 ±2.2	10.1 ±5.4	2.0 ±0.9	-14.7 ±5.0	73.7 ±1.7	4.2 ±4.0

*Unstable

(a) Includes THF-soluble resid and IOM.

/ls

TABLE 22

850°F⁺ CONVERSION AND KINETICS
Wilsonville Run 260

Period	First Stage							
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	A, 10 ⁷ (a)
				Consol (d)	W'ville (e)	Ratio C/W (f)		
A*	825	2.9	-	33.7	29.10	1.158	1.49	2.34
B*	840	2.5	-	32.5	33.20	0.979	1.19	1.55
C	825	2.3	-	33.5	33.30	1.008	1.17	1.84
D	790	2.8	1415	26.6	29.10	0.914	1.01	2.54
E	789	4.0	1461	21.7	27.00	0.804	1.11	2.81
F	774	4.0	1497	28.8	24.80	1.161	1.62	5.05
Averages for Stage 1:								
Average Periods A-C				33.23	31.87	1.05	1.28	1.91
± Std. Dev.				0.64	2.40	0.10	0.18	0.40
Average Periods D-F				25.70	26.97	0.96	1.25	3.47
± Std. Dev.				3.63	2.15	0.18	0.32	1.38
Average All Periods				26.47	29.42	1.00	1.27	2.69
± Std. Dev.				4.74	3.37	0.14	0.23	1.24
Average All Periods (A, B Omitted)				27.65	28.55	0.97	1.23	3.06
± Std. Dev.				4.90	3.62	0.15	0.27	1.39

Period	Second Stage								Total Conversion		
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	A, 10 ⁷ (a)	Consol (d)	W'ville (e)	Ratio C/W (f)
				Consol (d)	W'ville (e)	Ratio C/W (f)					
A*	790	3.9	1330	12.8	12.40	1.032	1.43	1.43	42.2	37.9	1.113
B*	790	3.3	1362	9.2	11.90	0.773	0.84	0.84	38.7	41.1	0.941
C	790	3.1	1368	11.3	16.70	0.677	0.99	0.99	41.0	44.4	0.923
D	774	2.1	-	14.4	10.50	1.371	1.10	1.10	37.2	36.5	1.017
E	797	3.0	-	23.6	9.00	2.622	2.11	2.11	40.2	33.6	1.197
F	804	3.0	-	9.8	7.10	1.380	0.68	0.68	35.8	30.1	1.187
Averages for Stage 2 and Total:											
Average Periods A-C				11.10	13.67	0.83	0.43	1.09	40.64	41.16	0.99
± Std. Dev.				1.81	2.64	0.18	0.12	0.31	1.77	3.27	0.11
Average Periods D-F				15.93	8.87	1.79	0.54	1.30	37.71	33.42	1.13
± Std. Dev.				7.03	1.70	0.72	0.34	0.74	2.25	3.21	0.10
Average All Periods				13.52	11.27	1.31	0.48	1.19	39.17	37.29	1.06
± Std. Dev.				5.30	3.30	0.71	0.24	0.52	2.42	5.14	0.12
Average All Periods (A, B Omitted)				14.78	10.83	1.51	0.50	1.22	38.54	36.17	1.08
± Std. Dev.				6.19	4.16	0.81	0.29	0.62	2.47	6.10	0.13

*Unstable

- (a) Basis was lb total feed/hr/lb catalyst. K and A were calculated from Consol conversion data. See text for discussion of thermal stage WHSV.
 (b) lb coal + resid + UC/lb catalyst
 (c) First stage and total conversion: wt % resid + MAF coal + UC fed to first stage
 Second stage conversion: wt % resid + UC fed to second stage
 (d) 850°F distillation end point, atm equivalent
 (e) 1050°F distillation end point, atm equivalent
 (f) Ratio of Consol conversion to Wilsonville conversion
 /lb

TABLE 23
COMPARISON OF WILSONVILLE RUNS 260 AND 258
OPERATING CONDITIONS

Period	260C	258H	258M
Source (Reference)	This Report	6	6
<u>Conditions</u>			
% Volume Takeoff, Reactor 1	100	50	50
% Volume Takeoff, Reactor 2	75	50	50
T ₁ , °F	825	841	852
T ₂ , °F	790	790	788
Therm. Space Velocity, Reactor 1	31C	65C	77C
WHSV, lb (feed)/hr-lb cat	3.1	4.5	5.4
Interstage Separator	Small*	Large	Large
Cat. Age, lb (resid+CI)/lb-cat	~1368	~2572	~1314
Distillation System	New	Old**	Old**
Cat. Repl. Rate, lb/T MF coal	3.0	1.5	3.0
Coal Feed Rate, MF lb coal/hr	251	247	291
Coal Ash, wt % MF	6.2	7.3	7.3

*Note that vapor-liquid separation was not occurring

**T-102 not working

/ls

TABLE 24
COMPARISON OF WILSONVILLE RUNS 260 AND 258
YIELD AND PERFORMANCE DATA

Source	260C	258H	258M
<u>Yields and Performance, wt % MAF Coal</u>			
H ₂	-6.3 ±0.2	-5.4 ±0.2	-5.3 ±0.1
Water	18.8 ±0.6	13.7 ±0.6	12.9 ±0.4
H ₂ S, CO, CO ₂ , NH ₃	4.1 ±0.6	8.4 ±0.5	8.0 ±0.4
C ₁ -C ₃ Gas	11.2 ±0.1	9.2 ±0.3	8.8 ±1.4
C ₄ + Distillate	54.1 ±3.8	55.4 ±1.6	51.5 ±2.4
C ₄ + Naphtha	4.4 ±0.9	16.3 ±0.4	16.6 ±0.8
Middle Distillate	4.0 ±0.9	9.9 ±0.4	10.5 ±0.8
Distillate Solvent	45.7 ±2.7	29.2 ±1.6	24.4 ±3.1
Resid	7.5 ±3.1	4.9 ±1.4	3.8 ±1.5
ROSE-SR Bottoms	10.7 ±0.5	13.8 ±1.1	20.3 ±0.8
TSL Coal Conversion	94.2 ±0.6	93.1 ±0.7	89.1 ±0.5
Resid + UC Conv./1st, wt % feed	33.3 ±0.8	27.4	22.0
Resid + UC Conv./2nd, wt % feed	16.7 ±2.6	14.6	15.0

/ls

TABLE 25
COMPARISON OF WILSONVILLE RUNS 260 AND 258
PROCESS OIL CHARACTERISTICS, CONVERSIONS AND KINETIC CONSTANTS

Period	260C	258H	258M
Source (Reference)	This Report	6	6
<u>SQI (a)</u>			
Feed & Product Distillate	74.8-77.1	78.0-79.6	80.8-81.3
Interstage Distillate	74.9	70.8	74.4
<u>Hydrogen Aromaticity, % of Protons (b)</u>			
Feed & Product Distillate	19.4-19.6	17.4-19.9	19.9-21.0
Interstage Distillate	20.9	23.0	26.1
Feed & Product Resid	35.9-36.1	37.1-40.8	40.1
Interstage Resid	38.4	40.3	44.9
<u>Paraffinic Hydrogen, % of Protons (c)</u>			
Feed & Product Distillate	40.5-43.2	38.2-42.6	36.2-37.2
Interstage Distillate	40.3	40.7	35.3
<u>Phenolic -OH Concentration, meq OH/g Sample</u>			
Feed & Product Distillate	0.42-0.45	0.57	0.35-0.39
Interstage Distillate	1.20	1.13	1.00
Feed & Product Resid	0.65-0.67	0.93-0.98	0.78-0.80
Interstage Resid	0.94	1.18	1.11
<u>Feed & Product Resid Components, wt %</u>			
Oils	68.3-69.0	59.5-60.2	56.3-58.0
Asphaltenes	21.5-22.8	22.6-23.9	26.1-26.7
Preasphaltenes	8.2-10.2	15.9-17.9	15.9-17.0
<u>Interstage Resid Components, wt %</u>			
Oils	61.3	55.6	55.8
Asphaltenes	25.3	22.8	26.9
Preasphaltenes	13.4	21.5	17.3
<u>850°F⁺ Conversion, %</u>			
First Stage	33.5	27.9	20.6
Second Stage	11.3	15.3	13.5
Total	41.0	38.9	31.3
<u>Kinetic Rate Constants for 850°F⁺</u>			
<u>Conversion (d)</u>			
First Stage	1.17	1.74	1.40
Second Stage	0.39	0.81	0.84
<u>Activities for 850°F⁺ Conversion,</u>			
<u>10⁷ (d)</u>			
First Stage	1.84	2.23	1.57
Second Stage	0.99	2.03	2.16

- (a) SQI = Solvent Quality Index, predicted microautoclave donor solvent quality based on proton distribution of each distillate sample.
(b) Sum of condensed and uncondensed aromatic protons.
(c) Sum of alkyl beta and gamma (aliphatic) protons.
(d) lb total feed/hr/lb catalyst.

/ls

Figure 1. Simplified CC-ITSL Process Diagram for Wilsonville Run 260. Dotted lines represent operation with interstage separator in Periods A and B. Bold line represents operation without interstage separator (periods C, D, E, F).

Figure 3. Component Distribution of Whole V-131B Oils
From Wilsonville Run 260.

Figure 4. Component Distribution of Whole V-1067 Oils
From Wilsonville Run 260.

Figure 5. Component Distribution of Whole Interstage Oils From Wilsonville Run 260.

Figure 6. Solubility Fractionation of V-131B THF-Soluble 850°F⁺ Resid Samples From Wilsonville Run 260.

Figure 7. Solubility Fractionation of V-1067 THF-Soluble 850°F⁺ Resid Samples From Wilsonville Run 260.

Figure 8. Solubility Fractionation of Interstage THF-Soluble 850°F+ Resid Samples From Wilsonville Run 260.

Figure 9. Proton Distribution of V-131B Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 260.

Figure 10. Proton Distribution of V-1067 Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 260.

Figure 11. Proton Distribution of Interstage Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 260.

Figure 12. Phenolic -OH Concentrations of Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 260.

Figure 13. Microautoclave Solvent Quality Assays of Samples From Wilsonville Run 260.

Figure 14. First-Stage and Total Conversions of THF-Soluble 850°F⁺ Resid and Coal + IOM for Wilsonville Run 260.

Figure 15. THF-Soluble 850°F+ Conversions for Wilsonville Run 260.

Figure 16. Conversion of Oils (Hexane Solubles) in Wilsonville Run 260.

Figure 17. Conversion of Asphaltenes in Wilsonville Run 260.

Figure 18. Conversion of Preasphaltenes in Wilsonville Run 260.

Figure 19. Resid and UC Conversion Activity in Wilsonville Run 260.

Figure 20. GC/MS Chromatograms of Process Oil Distillates From 10/9/90, Wilsonville Run 260. (Key to peak numbers follows.)

KEY TO FIGURE 20

Peak No.	Identification	Peak No.	Identification
1	Tetralin	16	n-Hexacosane
2	Methyltetralin	17	Alkyl pyrene?
3	Cyclohexybenzene	18	n-Heptacosane
4	Biphenyl	19	Methyl chrysene
5	Diphenyl ether	20	n-Octacosane
6	C ₂ -Biphenyl	21	C ₂ -Chrysene
7	Hexahydropyrene	22	n-Nonacosane
8	Hexahydropyrene	23	n-Triacontane
9	Dihydropyrene	24	n-Hentriacontane
10	Pyrene	25	n-Dotriacontane
11	Methylpyrene	26	n-Tritriacontane
12	n-Tetracosane	27	n-Tetratriacontane
13	C ₂ -Pyrene	28	n-Pentatriacontane
14	C ₂ -Pyrene	29	n-Hexatriacontane
15	n-Pentacosane		

Identifications based on Wiley/NBS library of mass spectra and on retention times.

/ls

5 confs
cycled separately.
ds

END

**DATE
FILMED**

4 / 01 / 92

11/11/11

11/11/11

1

(