NIPER-555
Distribution Category UC-122

MODELING OF HEAVY ORGANIC DEPOSITION NIPER--555
DE92 001016

By
Frank T. H. Chung

January 1992

Work Performed Under Cooperative Agreement No. FC22-83FE60149

Prepared for
U.S. Department of Energy
Assistant Secretary for Fossil Energy

Jerry Casteel, Project Manager
Bartlesville Project Office
P. O. Box 1398
Bartlesville, OK 74005

Prepared by
IIT Research Institute
National Institute for Petroleum and Energy Research
P. O. Box 2128
Bartlesville, OK 74005

MASTER

TABLE OF CONTENTS

	Page
Abstract.....	1
Introduction.....	1
PART I: MODELING.....	3
Approach-1.....	3
Approach-2.....	15
PART II: EXPERIMENTAL.....	21
Conclusions.....	24
Acknowledgments.....	24
Nomenclature.....	24
References.....	26

TABLE

1. Experimental Conditions and Results To Test Mechanisms of Asphaltene Deposition .. 22

ILLUSTRATIONS

1. Modeling approach for organic deposition (Method 3) 12
2. Composition of the extracted oil from New London oil by CO₂ at 125° F and
1,500 psig..... 22
3. Change of asphaltene content in the recovered oil during CO₂ displacement 24

MODELING OF HEAVY ORGANIC DEPOSITION

by Frank T-H. Chung

ABSTRACT

Organic deposition is often a major problem in petroleum production and processing. This problem is manifested by current activities in gas flooding and heavy oil production. The need for understanding the nature of asphaltenes and asphaltics and developing solutions to the deposition problem is well recognized. Prediction technique is crucial to solution development. In the past 5 years, some progress in modeling organic deposition has been made. A state-of-the-art review of methods for modeling organic deposition is presented in this report.

Two new models were developed in this work; one based on a thermodynamic equilibrium principle and the other on the colloidal stability theory. These two models are more general and realistic than others previously reported. Because experimental results on the characteristics of asphaltene are inconclusive, it is still not well known whether the asphaltenes in crude oil exist as a true solution or as a colloidal suspension. Further laboratory work which is designed to study the solubility properties of asphaltenes and to provide additional information for model development is proposed.

Some experimental tests have been conducted to study the mechanisms of CO₂-induced asphaltene precipitation. Coreflooding experiments show that asphaltene precipitation occurs after gas breakthrough. The mechanism of CO₂-induced asphaltene precipitation is believed to occur by hydrocarbon extraction which causes change in oil composition. Oil swelling due to CO₂ solubilization does not induce asphaltene precipitation.

INTRODUCTION

Organic deposition is a serious problem in oil production and processing. The products of organic deposition are complicated and may contain asphaltenes, asphaltic resins, wax, and solid fines. Deposition may occur in reservoir formations, wellbores, production tubing, submersible pumps, and surface equipment. Asphaltenes that are flocculated can adsorb on rock surfaces. Clay minerals in reservoir formations can strongly adsorb asphaltic resins of crude oils.¹ Adsorption of asphaltic material on reservoir rock has been shown to alter wettability to a more oil-wet condition.²⁻⁴ Also, deposition of asphaltic materials near the wellbore may cause pore plugging and thus block the flow of oil. In CO₂ flooding, organic deposition often occurs in the wellbore region after CO₂ breakthrough. Laboratory studies have indicated that carbon dioxide can cause precipitation of organic materials from crude oils.⁵⁻⁷ Several instances of problems in field operations of CO₂ miscible floods have also been reported.⁸ The nature of organic deposition

during CO₂ flooding depends on a complex interaction between oil, mineral, and CO₂. It is important to know how CO₂ induces organic deposition and where the deposition occurs. Organic deposition in tubing and production facilities will cause operational difficulties. This problem is particularly serious in offshore oil fields, especially in the North Sea.⁹ Heavy organic deposition also causes many problems in oil transportation and processing. It has been shown that asphaltene precipitation and subsequent carbonization is the major mechanism in crude oil heat exchanger fouling.¹⁰

The organic deposition problem has confronted the petroleum industry for many decades. Recently, this problem has attracted more attention because (1) operating costs have become more critical to the profit of oil production, (2) oil sources are limited, and (3) the problem occurs in gas flooding EOR. It is important to producers that any potential organic deposition problems can be predicted and the impact on the economics of the project can be evaluated before the development of a field. Early prediction for the potential of deposition problems can help producers design a production strategy to prevent, if possible, or mitigate this problem. With the recent technology development in statistical thermodynamics, it is now possible to model the phase behavior for extremely complicated systems such as polymer solutions, electrolyte solutions, and multicomponent crude oil systems. These new developments in thermodynamic and colloidal science rekindled research in the modeling of asphaltene and wax precipitation. Some significant progress in model development has been made during the past 5 years, especially for well defined wax deposition.¹¹⁻¹⁴ This report gives the state-of-the-art review of all the published modeling work.

Organic deposition is a complicated problem, especially for asphaltenes. Because of the limitation of analytical instruments, the nature of asphaltene in crude oils is not understood. The application of light scattering is difficult in the case of asphaltene solution because of the presence of an intense fluorescence signal and optical absorption.¹⁵ Gel permeation chromatography (GPC), small angle X-ray scattering, and small angle neutron scattering are often-used techniques for asphaltene characterization. There is still no conclusive answer to the structure of asphaltene. Published data for the molecular weight of petroleum asphaltenes range from approximately 1,000 to 500,000, depending on the analytical method.¹⁶ Whether the asphaltene-crude solution is a true solution or a colloidal suspension solution is still debatable. Experimental results are mixed. Therefore, the developed models for asphaltene deposition are still diverse. Some models were developed based on the assumption that asphaltenes are molecules dissolved in crude oil. Others were developed based on the assumption that asphaltenes are colloidal particles suspended in crude oil. So far, there is no unique theory to interpret all the experimental results. Further studies of the solution properties of asphaltenes are needed. Systematic experiments starting from simple binary

systems, instead of the complicated crude oil systems, can be more helpful for the understanding of asphaltene solution properties.

PART I: MODELING

There are two different approaches for asphaltene precipitation modeling. One (Approach-1) is based on the assumption that asphaltenes are dissolved in oil in a true liquid state and may precipitate as a result of changing thermodynamic conditions such as temperature, pressure, and composition. Thus, asphaltene precipitation is considered to be thermodynamically reversible. It only takes a longer time for asphaltene dissolution into oil than precipitation. The complete dissolution of some asphaltenes in some organic solvents such as toluene and benzene supports this assumption. The other approach (Approach-2) is based on the assumption that asphaltenes are solid particles colloidally suspended in crude oil which are stabilized by the adsorbed resin molecules. When the adsorbed resin molecules are dissolved into solution, the asphaltene particles may aggregate mechanically or by electrostatic attraction. This concept is based mainly on titration experiments which demonstrate that once the adsorption equilibrium of resins between solid (asphaltene) and liquid phases is disturbed by adding paraffinic solvents, the asphaltene particles flocculate irreversibly. A review of each of these approaches is given in the following sections.

Approach-1

The reversibility assumption implies that thermodynamic models can be used to describe asphaltic phase behavior. A simple thermodynamic model (Method 1) was proposed by Hirschberg, et al.¹⁷ This model describes the precipitation mechanism by polymer solution theory. The asphaltene molecules are considered to be similar in structure and behavior to polymer molecules. In this approach, a vapor-liquid equilibrium calculation using an equation of state is conducted to determine the composition of the liquid phase, and then the Flory-Huggins model is used to calculate the amount of asphaltene precipitated from the liquid phase, assuming that this precipitation does not affect the vapor-liquid equilibrium. A simplified expression for the maximum volume fraction of asphaltene soluble in crude oil was derived from a modified Flory-Huggins theory.¹⁸ In this model, all asphaltene molecules are treated as the same, and the crude oil is viewed as a solvent phase in which the asphaltenes are dissolved. Thus, asphaltenes were considered as a component in the crude oil. The conditions for phase equilibrium between the solid (asphaltene) phase (S) and a liquid (crude oil) phase (L) for the asphaltene component, a , is

$$\mu_a^L = \mu_a^S \tag{1}$$

Following the modified Flory-Huggins theory, the chemical potential μ_a of asphaltene in solvent is given by¹⁸

$$\frac{\mu_a - \mu_a^0}{RT} = \ln(\phi_a) + 1 - \frac{v_a}{v_m} + \frac{v_a}{RT}(\delta_m - \delta_a)^2 \quad (2)$$

where μ_a^0 is the chemical potential at the reference state of pure asphaltene, and δ_a and v_a are the solubility parameter and the molar volume of asphaltene, respectively. T is the absolute temperature and R is the universal gas constant. The volume fraction of asphaltene in solution, ϕ_a , is defined as

$$\phi_a = \frac{x_a v_a}{v_m} \quad (3)$$

The molar volume, v_m , and the solubility parameter, δ_m , of the mixture are calculated using Hildebrand's approximation,

$$v_m = \sum_i x_i v_i \quad (4)$$

$$\delta_m = \sum_i \phi_i \delta_i \quad (5)$$

where x_i is the mole fraction of component- i .

For the solid phase, it was assumed that the precipitated phase is pure asphaltene. Therefore, we have $v_m = v_a$, $\delta_m = \delta_a$ and $\mu_a^S = \mu_a^0$. Combination of Eqs. 1 and 2 yields

$$\phi_a^L = \exp \left\{ \frac{v_a^L}{v_m^L} \left[1 - \frac{v_m^L}{v_a^L} - \frac{v_m^L}{RT} (\delta_a^L - \delta_m^L)^2 \right] \right\} \quad (6)$$

where the superscript L denotes the properties of the liquid phase obtained from the calculated vapor/liquid split of the crude (or crude/solvent mixture) at the conditions of pressure and temperature considered. In Eq. 6, the solubility parameter, δ_a , and the molar volume, v_a , of asphaltene are unknown parameters, which are usually determined by matching the results of titration experiments. The values obtained by Hirschberg, et al.¹⁷ are $v_a = 4 \text{ m}^3/\text{kmol}$, and

$(\delta_a)_{T=25^\circ\text{C}} = 19.5 \text{ MPa}^{0.5}$. It was found that the solubility parameter of asphaltene is close to the solubility parameter of aromatics such as naphthalene.

Eq. 6 gives a simplified expression for the maximum volume fraction, ϕ_a^L , of asphaltene soluble in the crude oil. From Eq. 6, we can see that any condition which increases the deviation in $(\delta_a^L - \delta_m^L)$ enhances precipitation. For example, the light hydrocarbons possess low solubility parameters, and if sufficient quantities are added to the crude oil, the solubility parameters of the liquid phase δ_m are lowered and this leads to asphaltene precipitation. This model can therefore be useful to interpret the precipitation of asphaltenes in a n-alkane titration. The effects of temperature and pressure on asphaltene precipitation are through change of δ_m and v_m . Above the bubble point of the crude oil, there is no change in composition of the oil with an increase in pressure. The increase in solubility is caused by the increase of δ_m and the decrease of v_m . Below the bubble point, the crude oil, which is undersaturated with respect to gas, also has a higher dissolving power (since they have a higher solubility parameter) than the same crude at its bubble point. Thus the solubility of asphaltene in crude oil has a minimum value at the bubble point.

Although this simplified model has been employed by many researchers¹⁹⁻²¹ to interpret experimental results, it conflicts with the experimental evidence that the asphaltene is not a homogeneous component. The molecular weight of precipitated asphaltene is distributed in the range from 1,000 to 500,000 and depends on solvent type and how the molecular weight is determined. To accommodate this experimental evidence, we have made the following modifications,

(1) The heavy fractions of crude oil with a molecular weight greater than 500 were considered as asphaltenes (this may include some resins), and the other components of the crude oil were lumped into a solvent. The C_{7+} fraction of crude oil was represented with a continuous distribution function. A method was used to discretize the continuous C_{7+} fraction molar distribution.

(2) The mole fractions of solvent(h) and asphaltene(a) were computed by

$$x_h = \sum_{i=1}^{NC-Na} x_i \quad (7)$$

$$x_a = \sum_{i=(NC-Na+1)}^{NC} x_i \quad (8)$$

where NC = total number of components in the liquid-phase

Na = number of components having a molecular weight of 500 or larger.

The molar volume of asphaltene and solvent are $v_a^L = x_a v^L$, $v_b^L = v^L - v_a^L$, respectively.

(3) The Flory-Huggins polymer theory, instead of Eq. 2, for the chemical potential of asphaltene (a) in solvent (b) was used.

$$\frac{\mu_a - \mu_a^0}{RT} = \ln(\phi_a) + \left(1 - \frac{v_a}{v_b}\right) \phi_b + \frac{(\delta_a - \delta_b)^2}{RT} v_a (\phi_b)^2 \quad (9)$$

The corresponding expression for the maximum volume fraction of asphaltene soluble in the crude is

$$\phi_a^L = \exp \left[\left(\frac{v_a^L}{v_b^L} - 1 \right) \phi_b^L - \frac{(\delta_a - \delta_b)^2}{RT} v_a^L (\phi_b^L)^2 \right] \quad (10)$$

The solubility parameters for solvent (b) and asphaltene (a) in Eq. 10 were computed by

$$\delta_b = \sum_{i=1}^{NC-Na} \phi_i^L \delta_i^L \quad (11)$$

$$\delta_a = \sum_{i=(NC-Na+1)}^{NC} \phi_i^L \delta_i^L \quad (12)$$

where

$$\phi_i^L = \frac{x_i v_i^L}{\sum_{i=1}^{NC} x_i v_i^L} \quad (13)$$

In this approach, asphaltene was treated as a lumped pseudocomponent component for all components of crude oil with molecular weight of 500 or larger. Thus, there is no assumption that all asphaltenes are of the same molecular weight. The asphaltene properties (v_a^L , δ_a^L) are the average of the values for each discretized component, which can be estimated from equations of state and correlations. The details of the computation and results were presented in the previous report to DOE.¹⁴

As mentioned by Hirschberg, et al.,¹⁷ some improvements might be achieved if more appropriate polymer solution theories are used. Some experimental results show that the precipitated asphaltene is a mixture with virtually continuous distribution of molecular weights.³¹ To formulate a continuous mixture model for asphaltene, Mansoori et al. have proposed a continuous thermodynamic model²²⁻²⁴ (Method 2) by applying the Scott and Magat heterogeneous polymer theory.^{25,26} Assuming that the asphaltene behaves as a heterogeneous polymer, the Scott and Magat theory can be used to calculate the chemical potential, μ_{ai} , of the i -th fraction of asphaltene in a mixture of asphaltene (a) and a solvent (b) as

$$\frac{\mu_{ai} - \mu_{ai}^o}{RT} = \ln(\phi_{ai}) + 1 - \frac{m_{ai}}{\langle m_a \rangle} (1 - \phi_b) - m_{ai} \phi_b + f m_{ai} \phi_b^2 \quad (14)$$

Subscript ai refers to the i -th fraction of asphaltene. The volume fraction, ϕ_i , is defined by the volume, V_i , of i -th component divided by the total volume, V_m , of the mixture. Thus,

$$\phi_{ai} = \frac{V_{ai}}{V_m}, \quad \phi_b = \frac{V_b}{V_m}, \quad \text{and} \quad (\sum \phi_{ai}) + \phi_b = 1 \quad (15)$$

In Eq. 14, m_{ai} is the segment number of the i -th fraction of asphaltene. Each segment is considered to be same size as a molecule of solvent so that m_{ai} is the ratio of molar volume, v_{ai} , of the i -th fraction of asphaltene and the molar volume, v_b , of the solvent,

$$m_{ai} = v_{ai}/v_b = M_{ai}/(\rho_{ai}^{mass} v_b) \quad (16)$$

where M_{ai} and ρ_{ai} are the molecular weight and mass density of the i -th fraction of asphaltene, respectively. The average segment number, $\langle m_{ai} \rangle$, of asphaltene was defined by

$$\langle m_{ai} \rangle = \sum x_{ai} m_{ai} \quad (17)$$

where x_{ai} is the mole fraction of the i -th fraction of asphaltene with respect to the total asphaltene; i.e., $\sum x_{ai} = 1$. In Eq. 14, the parameter f is defined by

$$f = \frac{1}{r} + \frac{v_b}{RT} [(\delta_a - \delta_b)^2 + 2k_{ab} \delta_a \delta_b] \quad (18)$$

where r is the "coordination number," i.e., the number of neighbor segments around each segment (r has a value between 3 and 4), k_{ab} is the interaction parameter between asphaltene and solvent

(asphaltene-free crude oil) and was assumed as a linear function of the average molecular weight of asphaltene-free oil, $\langle m_b \rangle$, δ_a is the average solubility parameter of the asphaltene, and δ_b is the average solubility parameter of asphaltene-free crude.

By using the above equations and the principle of phase equilibria, an expression for calculating the solubility of asphaltene in solution can be derived. Provided Eq.1 is valid for every fraction of asphaltene in the liquid and solid phases, an expression for the volume fraction, ϕ_{ai} , of the i-th fraction of asphaltene can be written as

$$\phi_{ai}^L / \phi_{ai}^S = \exp(m_{ai} \theta) \quad (19)$$

where

$$\theta = \left(\frac{1}{\langle m_a^L \rangle} - \frac{1}{\langle m_a^S \rangle} \right) + \left(1 - \frac{1}{\langle m_a^L \rangle} \right) \phi_b^L - f^L (\phi_b^L)^2 \quad (20)$$

It was assumed that the molar volume and the segment number of the i-th fraction of asphaltene in both phases are identical, and the solid phase is free of the solvent. To apply this theory, we need to use a molecular weight distribution function to characterize the continuous asphaltene components. The molecular weight distribution function of asphaltene can be defined as

$$F(M_{ai}) = \frac{1}{N_a} \left(\frac{dn_{ai}}{dM_{ai}} \right) \quad (21)$$

where $F(M_{ai})$ is a normalized distribution function. dn_{ai} is the differential of the number of moles of the i-th fraction of asphaltene whose molecular weight is in the range of M_{ai} to $M_{ai} + dM_{ai}$, and N_a is the total number of moles of asphaltene.

After the introduction of a miscible solvent into the crude oil (C), there will be two phases (one liquid (L) and one solid (S)) formed. The mass balance for the i-th fraction of asphaltene can be written as

$$dn_{ai}^C = dn_{ai}^L + dn_{ai}^S \quad (22)$$

and

$$F^C(M_{ai})N_a^C = F^L(M_{ai})N_a^L + F^S(M_{ai})N_a^S \quad (23)$$

The relationship between the mole number and the volume fraction is given for each phase as

$$dn_{ai}^C = \frac{V^C d\phi_{ai}^C}{V_{ai}}, \quad dn_{ai}^S = \frac{V^S d\phi_{ai}^S}{V_{ai}}, \quad dn_{ai}^L = \frac{V^L d\phi_{ai}^L}{V_{ai}} \quad (24)$$

where V^C , V^S , and V^L are the total volumes of the crude oil, solid phase, and the liquid phase, respectively. Also, it was assumed that $V^C = V^S + V^L$.

By combining the phase equilibrium equation, Eq. 19, and the mass balance equations for continuous asphaltene components, Eqs. 21 to 23, the following relationships for the molecular weight distribution functions can be derived,

$$F^L(M_{ai}) = [V^L / \{V^L + V^S \exp(-m_{ai}\theta)\}] (N_a^C / N_a^L) F^C(M_{ai}) \quad (25)$$

$$F^S(M_{ai}) = [V^S / \{V^S + V^L \exp(-m_{ai}\theta)\}] (N_a^C / N_a^S) F^C(M_{ai}) \quad (26)$$

The total volume fraction of asphaltene in the liquid phase, ϕ_a^L , in equilibrium with the solid phase was given in the following form:

$$\phi_a^L = \int d\phi_{ai}^L = \int_0^\infty [(M_{ai} \bar{M}_a) V_a^C / \{V^L + V^S \exp(-m_{ai}\theta)\}] F^C(M_{ai}) dM_{ai} \quad (27)$$

where $\bar{M}_a$ is the average molecular weight of asphaltene, V_a^C is the total volume of asphaltene in the crude oil ($V_a^C = V^C - \phi_b^C V^C$), and θ is given by Eq. 20. The average segment number, $\langle m_a \rangle$, of asphaltene, in Eq. 20, can be defined by using the continuous distribution function of asphaltene as,

$$\langle m_a^L \rangle = \int_0^\infty m_{ai} F^L(M_{ai}) dM_{ai} \quad (28)$$

$$\langle m_a^S \rangle = \int_0^\infty m_{ai} F^S(M_{ai}) dM_{ai} \quad (29)$$

Knowing the total volume fraction of asphaltene in the liquid phase, ϕ_a^L , from Eq. 27, the amount of asphaltene in the liquid phase in equilibrium with the solid phase will be equal to $\rho_a \phi_a^L V^L$. Therefore, the amount of asphaltene precipitated is given by

$$(W_a)_{\text{pre.}} = (W_a)_{\text{Total}} - \rho_a \phi_a^L V^L \quad (30)$$

The total amount of asphaltene, $(W_a)_{\text{Total}}$, in the crude oil can be obtained from a titration experiment or calculated by knowing the asphaltene composition of the liquid phase at the onset of asphaltene flocculation,

$$(W_a)_{\text{Total}} = \rho_a (\phi_a^L V^L)_{\text{onset}} \quad (31)$$

This model can give information on the molar concentration distribution of asphaltene in different phases at equilibrium resulting from the addition of an amount of miscible solvents. However, it needs to input the molecular weight distribution, $FC(M_{ai})$, for the asphaltene in crude oil, which is usually unknown. Therefore, experimental titration data of asphaltene precipitation are needed to determine the parameters of the assumed distribution function by minimizing the differences between the experimental titration data of n-alkanes and the model. This is the major shortcoming of this model. Although this model is more sophisticated than the model of Hirschberg, et al. (Method 1), it also contains some assumptions for simplification. When the complicated crude oil (asphaltene-free) is treated as a solvent, the definitions of solubility parameter and molar volume for the solvent are ambiguous. The values of these two properties will change during solvent titration. By definition, the segment number of the i -th fraction of asphaltene, m_{ai} , will also change with the change of solvent molar volume, v_b . The whole computation is complicated and requires trial-and-error methods to determine these unknown parameters. For example, to calculate $FL(M_{ai})$, $FS(M_{ai})$, and ϕ_a^L from Eqs. 25, 26, and 27, respectively, one needs to compute the average segment numbers, $\langle m_a \rangle$, of asphaltene in the equilibrium liquid and solid phases, which require the information of $FL(M_{ai})$, and $FS(M_{ai})$ as shown in Eqs. 28 and 29. Therefore, the calculation is not straight forward and trial-and-error is needed. The details of derivations for this model were given in references 23 and 24. However, the calculation procedure was not clearly presented.

In both the homogeneous and heterogeneous models, the precipitation of asphaltene resulted from changes of the solubility parameter, δ_b , and the molar volume, v_b , of solvent. These models (Methods 1 and 2) still cannot account for some of the solution properties of asphaltene such as the dissolution of solid asphaltene in some organic solvents. For example, n-heptane can dissolve part

of a n-pentane precipitated asphaltene, and toluene can dissolve essentially all asphaltenes. A good model should be able to predict the solubility properties of asphaltenes for such simple binary or ternary systems as well as the more complicated systems.

In this work, a new model (Method 3) is developed based on the thermodynamics of solid-liquid equilibria^{11,18} as shown in Fig. 1. This model is general for all organic deposition and dissolution including wax, resins, and asphaltenes. It also gives the molar distribution of the precipitated solid phase. Following the same assumption as the previous two methods that the formation of a solid phase does not affect the vapor-liquid equilibrium (VLE), a VLE calculation for the crude oil is performed to obtain the composition of liquid oil. With the known liquid oil composition, a liquid-solid equilibrium (LSE) calculation is then performed to obtain the composition of solid phase. The method is illustrated in Fig. 1. Distribution functions can be used to characterize the liquid oil and solid phase compositions.

Assuming that the solid hydrocarbon mixture is in a solution form, at solid-liquid equilibrium, the fugacity of component i in the solid phase, f_i^S , must be equal to the fugacity of the same component i in the liquid phase, f_i^L .

$$f_i^S = f_i^L \quad (32)$$

where the fugacities of the i -th component in solid and liquid phases are defined by:

$$f_i^S = \gamma_i^S x_i^S f_i^{\circ S} \exp\left[\int_0^P \frac{v_i^S dP}{RT}\right] \quad (33)$$

$$f_i^L = \gamma_i^L x_i^L f_i^{\circ L} \exp\left[\int_0^P \frac{v_i^L dP}{RT}\right] \quad (34)$$

where γ_i , x_i , and f_i° are the activity coefficient, mole fraction, and standard state fugacity of component, i , the superscript, S, stands for the solid phase, and L for the liquid state.

The solid-liquid equilibrium coefficient, K_i^{SL} , is then derived by combining Eqs. 32, 33, and 34,

FIGURE 1. - Modeling approach for organic deposition (Method 3).

$$K_i^{SL} = \frac{x_i^S}{x_i^L} = \left(\frac{\gamma_i^L}{\gamma_i^S} \right) \left(\frac{f_i^{oL}}{f_i^{oS}} \right) \exp \int_0^P \frac{\Delta v_i dP}{RT} \quad (35)$$

where $\Delta v_i = v_i^L - v_i^S$. The first term in this equation represents the effect of composition in both phases on K_i^{SL} , the second term stands for the temperature effect, and the last term is the pressure effect. Thus, Eq. 35 is a general representation for a solid-liquid equilibrium constant.

The relation between the standard state fugacity of component i in the solid phase, f_i^{oS} , and that in the liquid phase, f_i^{oL} , can be derived by calculating the Gibbs energy change of pure component i from solid to liquid:^{11,18}

$$\ln \left(\frac{f_i^{oL}}{f_i^{oS}} \right) = \frac{\Delta h^f}{RT} \left(1 - \frac{T}{T^f} \right) + \frac{\Delta C_P}{R} \left[1 - \frac{T}{T^f} + \ln \frac{T^f}{T} \right] \quad (36)$$

where Δh^f is the latent heat of fusion, T^f is the fusion temperature, and ΔC_P is the difference of heat capacity between the two phases. The second term is usually very small and can be neglected, and the fusion temperature, T^f , for high molecular-weight asphaltenes is high enough that the term of T/T^f can be neglected except at high temperature. Won¹¹ has developed correlations for the fusion temperature and the heat of fusion as functions of molecular weight from C₁₀ to C₇₀. His correlations will be extended to higher molecular weight components.

In Eq. 35 the activity coefficient, γ_i^S , of component-i in the solid phase is assumed to be equal to unity. A thermodynamic model for the liquid phase activity coefficient, γ_i^L , was proposed in the previous work of this project,¹⁴ i.e.,

$$\ln \gamma_i^L = \frac{v_i}{RT} (\delta_m - \delta_i)^2 + \ln \frac{\phi_i}{x_i} + 1 - \phi_i - \sum_{k \neq i}^N \frac{v_i}{v_k} \phi_k \quad (37)$$

where the solubility parameter, δ_i , and the volume fraction, ϕ_i , for each component i in the liquid phase are defined as,

$$\delta_i = \left(\frac{\Delta H_v - RT}{v} \right)_i^{1/2} \quad (38)$$

$$\phi_i = \frac{x_i v_i}{\sum_j x_j v_j} \quad (39)$$

and the average solubility parameter, δ_m , is

$$\delta_m = \sum \phi_i \delta_i \quad (40)$$

Under no significant pressure changes, combining Eqs. 35, 36, and 37, gives

$$K_i^{SL} = \exp \left[\frac{\Delta h_i^f}{RT} (1 - T/T_i^f) + \frac{v_i^L}{RT} (\delta_m^L - \delta_i^L)^2 + \ln \frac{\phi_i^L}{x_i^L} + 1 - \phi_i^L - \sum_{k \neq i}^{NC} \frac{v_i^L}{v_k^L} \phi_k^L \right] \quad (41)$$

The liquid-solid equilibrium calculation is then performed by solving the following mass balance equations with Eq. 41 simultaneously,

$$F^{SL} = \sum x_i^S - \sum x_i^L = \sum \frac{z_i (K_i^{SL} - 1)}{[1 + \frac{S}{F} (K_i^{SL} - 1)]} = 0 \quad (42)$$

$$x_i^L = z_i \left[1 + \frac{S}{F} (K_i^{SL} - 1) \right] \quad (43)$$

$$x_i^S = z_i K_i^{SL} \left[1 + \frac{S}{F} (K_i^{SL} - 1) \right] \quad (44)$$

where z_i , x_i^L , and x_i^S are the compositions of the crude oil (before precipitation), the equilibrium liquid oil (after precipitation) phase, and the precipitated solid phase, respectively. S/F is the mole fraction of solid (precipitated phase) to feed (crude oil). The onset of asphaltene flocculation is the point at which the solid fraction (S/F) approaches zero. This model has been demonstrated to be accurate for wax formation prediction. The computing procedure and results were reported in a DOE Report.¹⁴ For asphaltene precipitation prediction, the computing procedure is the same. The only difficulty is in the characterization of asphaltenes. A more detailed compositional analysis for the crude oil, which gives the actual asphaltene composition and molar distribution in the crude oil, is required. Two techniques: the pseudocomponent method and the continuous thermodynamic method can be used to represent the C₇₊ fraction of the crude oil. In order to get the molar distribution of asphaltenes in the solid and liquid phases, the continuous thermodynamic technique has to be employed.²⁷ A thorough test of this model will be conducted in the next project year as the required data of oil analysis becomes available.

Approach-2

Another approach to model asphaltene precipitation is based on the assumption that asphaltenes exist in crude oil as solid particles in a colloidal suspension, stabilized by the repulsion of the adsorbed resin molecules. Resins are a class of highly polycyclic molecules that exist in the oil in true solution; they are easily adsorbed on common adsorbents like clay or silica gel, and insoluble in ethylacetate but soluble in n-heptane, toluene, and benzene. The molecular weight of resins fall in the range of 250 to 1,000. There are several points of structural similarity between asphaltenes and resins. It is considered that aromatization is more advanced in asphaltenes than in resins. Dickie and Yen¹⁶ postulated that petroleum resins provide a transition between the polar (asphaltene) and the relatively nonpolar (oil) fraction in petroleum, and thus, prevent the assembly of polar aggregates that would be nondispersible in oil. When resin molecules are insufficient to complex the entire asphaltene particles, asphaltene particles may aggregate due to the neutralization of their weak repulsive forces by mechanical (agitation) or electrical (opposing streaming potential) means. A thermodynamic-colloidal model (Method 4) which takes into account the factors that affect the repulsive forces which are responsible for the stability of the asphaltene colloidal suspension was proposed by Leontaritis and Mansoori.²⁸ Their model contains two parts: a static model to calculate the chemical potential of the resin, and a dynamic model to predict the streaming potential for the asphaltene to precipitate.

The static model is to predict the conditions at which flocculation is possible. The concept is that at the onset of asphaltene flocculation the colloidal particles are just covered with a monolayer of resin molecules. The point at which the concentration of resins in the liquid is just high enough to keep the colloidal asphaltene particles completely complexed with resins is called the critical point and the concentration of the resins in the liquid phase is called the critical resin concentration, $(C_r)_{crit}$. At this concentration, we can calculate the critical chemical potential, $(\mu_r)_{crit}$ of resins in the liquid mixture. According to thermodynamics, a necessary condition for resins (r) at chemical equilibrium between two phases is

$$\mu_r^{\text{solid phase}} = \mu_r^{\text{oil phase}} \quad (45)$$

By assuming that resins are homogeneous in molecular weight and size, the Flory-Huggins theory, Eq. 2, can be employed to calculate the chemical potential of resins in the liquid,

$$\frac{\Delta\mu_r}{RT} = \frac{\mu_r - \mu_r^0}{RT} = \ln(\phi_r) + 1 - \frac{v_r}{v_m} + \frac{v_r}{RT}(\delta_m - \delta_r)^2 \quad (46)$$

where: ϕ_r = volume fraction of resin in the liquid

v_r, v_m = molar volume of resin and liquid mixture, respectively

δ_r, δ_m = solubility parameters of resin and liquid mixture, respectively

From Eq. 45, the resin chemical potential in the solid phase, $(\mu_r)^{\text{solid}}$, which is difficult to estimate from chemical adsorption data, can be calculated from the equilibrium liquid phase composition. At the critical point that the asphaltene particles are just completely covered with resin molecules, the resin chemical potential in the solid phase (i.e., asphaltene phase) is a constant regardless of what the composition of the liquid phase is. In other words, the critical chemical potential, $(\mu_r)_{\text{crit}}$, of the resin in the solid phase (asphaltene) is only a function of the chemical nature of the asphaltene-resin aggregation and the temperature. If the critical chemical potential is known at one liquid composition (calculated from the liquid phase chemical potential of resin at the onset of asphaltene flocculation), then it is the same for all other compositions provided that the temperature remains the same and the pressure stays above the bubble point of the mixture. The calculation algorithm at the onset of asphaltene flocculation was given as follows,²⁹

1. Do an experiment with any solvent to get the onset of asphaltene flocculation of stock tank oil at reservoir temperature,
2. Calculate the molar volume and the solubility parameter of resin and oil at reservoir temperature and $P=1$ atm.,
3. Using Eq. 46 calculate $(\Delta\mu/RT)_{\text{crit}}$ of this oil at reservoir temperature,
4. Perform the vapor-liquid equilibrium (VLE) calculation for the reservoir oil at reservoir temperature and a different pressure to obtain the liquid phase composition,
5. Calculate the molar volume and solubility parameter of the resin and of the liquid mixture, then use Eq. 46 to calculate $(\Delta\mu/RT)_{\text{actual}}$ at the reservoir T and P conditions used in the VLE calculation,
6. Compare the two chemical potentials,
 - i. if $(\Delta\mu/RT)_{\text{actual}} > (\Delta\mu/RT)_{\text{crit}}$, no asphaltene flocculation is possible.
 - ii. if $(\Delta\mu/RT)_{\text{actual}} = (\Delta\mu/RT)_{\text{crit}}$, the liquid mixture is at the onset point of asphaltene flocculation.
 - iii. if $(\Delta\mu/RT)_{\text{actual}} < (\Delta\mu/RT)_{\text{crit}}$, asphaltene flocculation is possible by mechanical or electrical means.

As can be seen, this method only tells us the static conditions (temperature, pressure, and composition) at which asphaltene flocculation is possible. In this model the definitions of resin

properties such as the molar volume and the solubility parameter are not clear. It is also not clear how the resin concentration in the liquid phase is determined.

The second step is to apply colloid theory to predict the dynamic conditions (fluid flow conditions) at which asphaltene will deposit. Leontaritis and Mansoori²⁸ have developed the following streaming potential equations,

$$E = \rho_c u_{avg} L / k \quad \text{for laminar flow} \quad (47)$$

$$E = 4.95 \times 10^{-3} \{ \rho_c L (d\rho/\eta)^{0.75} / k \} u_{avg} \quad \text{for turbulent flow} \quad (48)$$

where ρ_c = charge density (total charge/unit volume of oil)

u_{avg} = average flow velocity

L = the length of the flow channel

d = the diameter of the conduit

k = the overall electrical conductivity of oil and pipe wall

η = oil viscosity

ρ = oil density

The charge density, ρ_c , was expressed in terms of some measurable quantities,

$$\rho_c = q_p \rho (6W_a/W_p) \quad (49)$$

where q_p is the mean charge on the colloidal asphaltene particles, W_a is the weight percent of asphaltenes in oil, and W_p is the mean weight of the colloidal asphaltene particles. The overall electrical conductivity, k , is given by,

$$k = k_{oil} + k_{wall} (d_o/d_i - 1) \quad (50)$$

where k_{oil} and k_{wall} are the electrical conductivity of the oil and the pipe wall, respectively. d_o and d_i are the external and internal pipe diameter, respectively.

From these equations, we can calculate the generated minimum streaming potential, E , during asphaltene deposition. When the actual resin chemical potential, $(\Delta\mu/RT)_{actual}$, is less than the critical chemical potential, $(\Delta\mu/RT)_{crit}$, electrokinetic effects will play a key role in the asphaltene deposition process.

This thermodynamic-colloidal model can only predict the conditions for asphaltene deposition. It cannot provide information about the quantity and composition of the asphaltene deposits. In order to account properly for the phenomenon of asphaltene and resin deposition, a new model (Method 5) is proposed in this work. This model has incorporated the following features: (1) the role of resin concentration in the asphaltene precipitation mechanism and its effect on the asphaltene aggregation process, and (2) utilization of the population balance equation to account properly for the irreversible aggregation kinetic and size distributions of clusters of asphaltene particles. This model assumes that asphaltenes are solid particles (spherical) peptized by resin molecules in crude oil.

A general dynamic equation describing the behavior of a polydispersed emulsion in which Brownian flocculation, sedimentation-flocculation, and creaming occur is given as³⁰

$$\begin{aligned} \frac{\partial n(v,y,t)}{\partial t} &= -U(v) \frac{\partial n(v,y,t)}{\partial y} + \frac{1}{2} \int_{v_m}^{v-v_m} [B(v',v-v') + G(v',v-v')] n(v',y,t) n(v-v',y,t) dv' \\ &\quad - \int_{v_m}^{v_M} [B(v,v') + G(v,v')] n(v,y,t) n(v',y,t) dv' \end{aligned} \quad (51)$$

(Accumulation) (Gain by creaming) (Gain by Brownian and sedimentation flocculation)

(Loss by Brownian and sedimentation flocculation)

Where

$n(v,y,t)dv$ = concentration of particles with volume between v and $v+dv$ at distance y and time t ,

$B(v,v')$ = Brownian collision frequency function.

$G(v,v')$ = gravitational collision frequency function,

$U(v)$ = creaming velocity of particles with volume, v ,

v_m, v_M = volume of the smallest and the largest particle, respectively.

In asphaltene precipitation, we can neglect the sedimentation-flocculation and creaming terms. Using the sectionalization technique, Eq. 51 can be rewritten as³⁰

$$\begin{aligned} \frac{\partial N_k(t)}{\partial t} &= \frac{1}{2} \sum_{i=1}^{k-1} \sum_{j=1}^{k-1} \beta_1 N_i(t) N_j(t) - N_k(t) \sum_{i=1}^{k-1} \beta_2 N_i(t) \\ &\quad - \frac{1}{2} \beta_3 N_k(t) - N_k(t) \sum_{i=k+1}^n \beta_4 N_i(t), \quad k = 1, 2, 3, \dots, n. \end{aligned} \quad (52)$$

where

$$N_k(t) = \int_{r_{k-1}}^{r_k} n(r,t) dr \quad (53)$$

The net rate of addition of particles into the section of k (particle radius between r_{k-1} and r_k) is the result of all flocculations between particles in sections lower than section k . Particles of a given size can only be formed by the coalescence of smaller particles since breakage is absent. These coagulations are represented by the first term on the right-hand side (RHS) of Eq. 52. The other three terms on RHS are the loss of section k particles due to the coalescence of particles in section k with smaller particles, with the same size particles, and with larger size particles, respectively. Eq. 52 is the same as the Smoluchowski's coagulation equation, which was employed by Park and Mansoori³¹ in their model.

The flocculation coefficients, β_1 , β_2 , β_3 , and β_4 , which affect the net rate of addition or removal of particles from section k , are defined as:³⁰

$$\beta_1 = \int_{r_{i-1}}^{r_i} \int_{r_{j-1}}^{r_j} \frac{\theta(r_{k-1}^3 < r'^3 + r^3 < r_k^3) B(r', r)}{(r_i - r_{i-1})(r_j - r_{j-1})} dr' dr \quad (54)$$

$$\beta_2 = \int_{r_{i-1}}^{r_i} \int_{r_{k-1}}^{r_k} \frac{\theta(r'^3 + r^3 > r_k^3) B(r', r)}{(r_i - r_{i-1})(r_k - r_{k-1})} dr' dr \quad (55)$$

$$\beta_3 = \int_{r_{k-1}}^{r_k} \int_{r_{k-1}}^{r_k} \frac{2\theta(r'^3 + r^3 > r_k^3) B(r', r)}{(r_k - r_{k-1})^2} dr' dr \quad (56)$$

$$\beta_4 = \int_{r_{i-1}}^{r_i} \int_{r_{k-1}}^{r_k} \frac{B(r', r)}{(r_i - r_{i-1})(r_k - r_{k-1})} dr' dr \quad (57)$$

The discontinuous functions θ determine whether a collision between particles of radius r and radius r' will result in the addition or removal of particles from section k . In general the function θ takes the following values:

θ (condition)

= 1, if the condition is satisfied

= 0, if the condition is not satisfied

The Brownian collision frequency function $B(r',r)$ is given by the Stokes-Einstein relation³²

$$B(r',r) = \frac{2k_bT}{3\eta Q} \left(\frac{1}{r'} + \frac{1}{r} \right) (r' + r) \quad (58)$$

where k_b is the Boltzmann constant, T the temperature ($^{\circ}\text{K}$), η the viscosity of the continuous medium, and Q the stability factor which is a function of electrostatic properties, temperature, and the size of the particles. For the interaction of two colloidal particles with radii r' and r , Q is given by the expression:³³

$$Q(r',r) = 2 \int_0^{\infty} Z(r',r) \text{EXP}[\psi(r',r)/k_bT] \frac{du}{(u+2)^2} \quad (59)$$

where:

- $Z(r',r)$ = hydrodynamic correction factor for particles of radii r' and r ,
- $\psi(r',r)$ = the total interaction potential between particles of radii r' and r ,
- $u = 2H/(r'+r)$, where H is the shortest interparticle distance.

For colloidal particles, the total interaction potential is given by the DLVO (Derjaguin, Landau, Verwey, Overbeek) theory,³⁰ but, for asphaltene particles in crude oil the interaction potential is affected by the resin molecules adsorbed on the asphaltene particles. Thus, the stability factor, Q , is a function of resin concentration on the solid phase. The development of the Q -function for asphaltene particles will be the major task for future research in this project. Resin concentration on the solid phase can be calculated from the principles of thermodynamics of multicomponent mixtures and phase equilibria. We can consider resins as a pseudocomponent (Method 1) or as a polydispersed system³⁴ with a continuous molecular weight distribution (Method 3).

The total resin molecules adsorbed on the asphaltene particles, $C_{r,d}$ is

$$C_{r,d} = C_{r,T} - \rho_r \phi_r^L V^L \quad (60)$$

where $C_{r,T}$ is the total resin content in the crude oil, which can be determined by experiment, ρ_r is the molar density of resins in crude oil, V^L is the total volume of crude oil, and ϕ_r^L is the total volume fraction of resins in the liquid phase. By applying the proposed model in Approach-1 (Method 1 or Method 3) for resins, we can calculate the total volume fraction of resins in the liquid

phase. To apply this model, we need to know the size distribution of asphaltene particles in the crude oil.

PART II: EXPERIMENTAL

A series of experiments was performed to investigate the mechanisms of asphaltene deposition during CO₂ displacement. The experiments were performed using New London (AR) oil (containing 4.0 wt % of n-pentane insoluble asphaltene) in a 100-mL cell at 1,500 psig pressure and 125° F. The experimental conditions and results are shown in Table 1. In the first experiment, designed to test the effect of supercritical extraction of hydrocarbon on asphaltene deposition, CO₂ was bubbled through 50 mL of oil in the cell. The resulting hydrocarbon enriched gas was bled through the backpressure regulator, and the extracted oil in the effluent was collected and analyzed. Approximately 2 mL of oil was extracted; the compositional analysis is shown in Fig. 2. After the oil extraction, the cell was opened, and an asphaltic deposit (about 4.57 gm) was found at the bottom of the cell. The deposited asphaltic mass contains about 1.5 gm of asphaltene, which corresponds to 3.77 wt % of the sample oil. In a second experiment, also testing the supercritical extraction effect, CO₂ was introduced into the cell and pressured to 1,500 psig. The system was kept at the same condition as the first experiment overnight to let the gas equilibrate with the oil. The equilibrated oil was subsequently removed and filtered to determine the quantity of asphaltic material deposited. About 3.96 gm of asphaltic mass was deposited at the bottom of the cell. A total of 1.59 gm of asphaltenes (corresponding to 3.57 wt% of oil) was separated from the asphaltic mass. In a third experiment, more oil (75 mL) was put into the cell to leave no room for a vapor phase. All of the injected CO₂ was dissolved in the oil, and the oil was swelled to 100 mL. No hydrocarbon was extracted, and the oil composition was unchanged. This experiment was performed to investigate the solvation effect on asphaltene precipitation. No significant amount of asphaltic material deposited inside the cell. The first experiment was repeated with an injection of nitrogen, instead of CO₂. In this test, only a trace amount of oil was stripped by N₂, and no significant deposition was observed inside the cell. From these experiments, we can draw the conclusion that asphaltene deposition was caused by hydrocarbon extraction which caused a change in oil composition, not by a solvation effect.

Another series of experiments was designed to study the role of resins in the deposition of asphaltenes. Resins are defined as that fraction of crude oil not soluble in ethylacetate but soluble in n-heptane, toluene, and benzene at room temperature. The sample oil (12.1 mL) was titrated with ethylacetate (1: 10 ratio). About 0.438 gm of precipitate was obtained, which corresponds to 4.23 wt % of the oil. The precipitate was then titrated with 100 mL of n-heptane, and about 17.06 wt % of the solid was dissolved. The remaining insoluble part (asphaltene) was 0.363 g,

TABLE 1. - EXPERIMENTAL CONDITIONS AND RESULTS TO TEST MECHANISMS OF ASPHALTENE DEPOSITION

Test No.	Experimental conditions	Weight of deposited asphaltic material, g	Weight of deposited asphaltene, g
1	Bubbling CO ₂ , and bled effluent through backpressure regulator	4.57	1.5 (3.77% of oil)
2	Equilibrate with CO ₂ , allow to reach vapor-liquid equilibrium	3.96	1.59 (3.57% of oil)
3	Saturate with CO ₂ , no vapor phase	0	0
4	Bubble N ₂	0	0

FIGURE 2. - Composition of the extracted oil from New London oil by CO₂ at 125° F and 1,500 psig.

which corresponds to 3.51 wt % of the oil. The resin content determined from this experiment was 0.075 g (0.72 wt % of the oil). The asphaltene (n-heptane insoluble) content of the sample oil was 3.567 wt %. Since asphaltenes are also insoluble in ethylacetate, the precipitation of resins by ethylacetate titration will also cause the precipitation of asphaltenes. The resin-free asphaltene can dissolve in toluene, and again precipitated by n-alkane (nC₅ - nC₁₀) titration. However, not

all the asphaltenes can be recovered from the asphaltene-toluene solution. In the previous work, a test of remixing the asphaltene-toluene solution with the original oil (asphaltene-free) was performed. It was found that about 50 wt % of the asphaltene was dissolved in the oil. Further experiments with these simple systems will help us to understand the solubility properties of asphaltenes in crude oils and the role of resins in asphaltene precipitation. Also, these simple systems can be used to test the developed models.

A CO₂ coreflooding experiment was conducted to determine the change of asphaltene content in oil (New London oil) during CO₂ flooding. A Berea core 2 ft long and 2 in. in diameter (porosity = 18.6% PV, water permeability=160 mD, and PV=207.6 mL) was first saturated with brine (2% NaCl) and then flooded with the sample oil until the remaining brine saturation was down to 37.02% PV (oil saturation = 62.98% PV). The asphaltene content for the oil flowing out of the core was determined. The result showed that the asphaltene content of the oil did not change after flowing through the 2-ft-long Berea core. Continuous CO₂ injection was then conducted to displace the oil. During the CO₂ displacement, the produced oil was analyzed to determine the asphaltene content. Oil production and the asphaltene content of the produced oil are shown in Fig. 3. Asphaltene contents for the produced oil before gas breakthrough are the same as that of the original oil, whereas the oil produced after breakthrough contains less asphaltene because the oil was produced mostly by hydrocarbon extraction. The CO₂ displacement was conducted under immiscible conditions (T=122° F, P=1,500 psig). The ultimate oil recovery after about 2.5 PV

FIGURE 3. - Change of asphaltene content in the produced oil during CO₂ flooding.

CO₂-injection was 79.5% OIP, and the cumulative asphaltene production was about 50 wt % of the total original asphaltenes in the oil. There was about 50 wt % of the total asphaltene left with the 20% oil inside the core. A heavy black deposit was observed inside the backpressure regulator after the end of the flooding experiment. A significant reduction of permeability in the core was observed.

CONCLUSIONS

1. Resins are not essential for the dissolution of asphaltenes in organic solvents. The solubility of asphaltenes in organic solvents depends on the solubility power of solvents.
2. The major mechanism for CO₂-induced asphaltene precipitation in crude oil is the change of oil composition caused by CO₂ supercritical extraction. Hydrocarbons extracted by CO₂ at the experimental condition (125° F, 1,500 psig) contain mostly C₈ to C₁₂ constituents.
3. Two different types of models have been presented in the literature, one was based on the assumption that asphaltene-crude oil is a true solution and asphaltene precipitation is thermodynamically reversible; the other was based on the assumption that asphaltenes are colloidal particles suspended in crude oil and stabilized by adsorbed resin molecules. Each of the two approaches has some experimental supporting evidence. The nature of asphaltenes in crude oils and the real mechanisms of asphaltene precipitation are still not well known.
4. A more general model has been developed in this work for the prediction of heavy organic deposition. This model is based on thermodynamic principles for solid-liquid equilibria. It has been tested with reasonable accuracy for the prediction of wax formation and will be tested with asphaltene and resin precipitation cases.

ACKNOWLEDGMENTS

The author acknowledges the financial support of this work provided by the U.S. Department of Energy under Cooperative Agreement DE-FC2283FE-60149. The author would like to thank Ray Jones and Partha Sarathi for their help in completing work on this project. The author also would like to thank Arden Strycker for his assistance in this work.

NOMENCLATURE

- C = total molecules
C_p = heat capacity at constant pressure
d = conduit diameter
E = streaming potential
f = fugacity
 Δ_h^f = latent heat of fusion
 Δ_H^v = enthalpy change of vaporization

k = the overall electrical conductivity
 k_{ab} = binary interaction parameter between asphaltene and solvent
 k_b = Boltzmann constant
 K^{sL} = solid-liquid equilibrium coefficient
 L = the length of flow channel
 m = segment number of asphaltene
 $\langle m \rangle$ = average segment number
 M = molecular weight
 $\bar{M}$ = average molecular weight
 n = mole number or colloidal particle number
 N = total mole number or total colloidal particle number
 N_a = number of components of asphaltics
 N_C = total number of components in the oil
 P = pressure
 q_p = the mean change of colloidal asphaltene particles
 Q = stability factor
 r = coordination number, or particle radius
 R = universal gas constant
 T = absolute temperature
 T_f = temperature of fusion
 u = flow velocity
 v = molar volume
 W = total mass
 W_a = weight percent of asphaltenes in oil
 W_p = the mean weight of colloidal asphaltene particles
 x = mole fraction
 z = mole fraction of feed

Greek Letters

δ = solubility parameter
 Δ = difference
 η = oil/viscosity
 γ = activity coefficient
 ρ = mass density
 ρ_c = charge density
 ϕ = volume fraction

μ = chemical potential

Superscripts

o = reference state

L = liquid state

S = solid state

C = crude oil

Subscripts

a = asphaltenes

ai = i-th fraction of asphaltene

avg = average

b = solvent

i = component, i

m = solution mixture

r = resins

REFERENCES

1. Collins, S.H. and J.C. Melrose. Adsorption of Asphaltenes and Water on Reservoir Rock Minerals. Pres. at SPE Oilfield and Geothermal Chemistry Int'l Symp., Denver, CO, June 1983. SPE paper 11800.
2. Crocker, M.E. and L.M. Marchin. Wettability and Adsorption Characteristics of Crude-Oil Asphaltene and Polar Fractions. J. Pet. Tech., April 1988, pp. 470-474.
3. Dubey, S.T. and M.H. Waxman. Asphaltene Adsorption and Desorption from Mineral Surfaces. Pres. at SPE Int'l Symp. on Oilfield Chemistry, Houston, TX., Feb. 8-10, 1989. SPE paper 18462.
4. Kim, S.T., M-E. Boudh-Hir, and G.A. Mansoori. The Role of Asphaltene in Wettability Reversal. Pres. at SPE Annual Tech. Conf. and Exhib., New Orleans, LA, Sept. 23-26, 1990. SPE paper 20700.
5. Monger, T.G. and J.C. Fu. The Nature of CO₂-Induced Organic Deposition. Pres. at SPE Annual Tech. Conf. and Exhib., Dallas, TX., Sept. 27-30, 1987. SPE paper 16713.
6. Wolcott, J.M., T.G. Monger, R. Sassen, and E.W. Chinn. The Effects of CO₂ Flooding on Reservoir Mineral Properties. Pres. at SPE Int'l Symp. on Oilfield Chemistry, Houston, TX., Feb. 8-10, 1989. SPE paper 18467.
7. Danesh, A., D. Krinis, G.D. Henderson, and J.M. Peden. Asphaltene Deposition in Miscible Gas Flooding of Oil Reservoirs. Chem. Eng. Res. Des., v.66, July 1988, pp. 339-344.
8. Hansen, P.W.. A CO₂ Tertiary Recovery Pilot - Little Creek Field, Mississippi. Pres. at the SPE Annual Fall Tech. Conf. and Exhib., Denver, CO., Oct.9-12, 1977. SPE paper 6747.

9. Thaver, R. and D.C. Nicoll. Asphaltene Deposition in Production Facilities. Pres. at SPE Int'l Symp. on Oilfield Chemistry, Houston, TX., Feb. 8-10, 1989. SPE paper 18473.
10. Dickkian, G. and S. Seay. Asphaltene Precipitation Primary Crude Exchanger Fouling Mechanism. Oil&Gas J., Technology, Mar. 7, 1988, pp. 47-50.
11. Won, K.W. Continuous Thermodynamics for Solid-Liquid Equilibria: Wax Formation from Heavy Hydrocarbon Mixtures. Pres. at AIChE Spring National Meeting, Session 1A, Mar. 24-28, 1986, Houston, TX.
12. Won, K.W. Thermodynamics for Solid Solution-Liquid-Vapor Equilibria: Wax Phase Formation from Heavy Hydrocarbon Mixtures. Fluid Phase Equil., v.30, 1986, pp. 265-279.
13. Hansen, J.H., A. Fredenslund, K.S. Pedersen, and H.P. Ronningsen. A Thermodynamic Model for Predicting Wax Formation in Crude Oils. AIChE J., v.34, No. 12, December 1988, pp. 1937-1942.
14. Chung, T-H. F., P. Sarathi, and R.Jones. *Modeling of Asphaltene and Wax Precipitation*. DOE Report NIPER-498, 1991.
15. Ravey, J.C., G. Ducouret, and D. Espinat. Asphaltene Macrostructure by Small Angle Neutron Scattering. Fuel, V.67, November 1988, pp. 1560-1567.
16. Dickie, J.P. and T.F. Yen. Macrostructures of the Asphaltic Fractions by Various Instrumental Methods. Anal. Chem. 39(14), December 1967, p. 1847.
17. Hirschberg, A, L.N.J. deJong, B.A. Schipper, and J.G. Meijer. Influence of Temperature and Pressure on Asphaltene Flocculation. Soc. Pet. Eng. J., June 1984, pp. 283-293.
18. Prausnitz, J.M. *Molecular Thermodynamics of Fluid-Phase Equilibria*. Prentice-Hall Inc., Englewood Cliffs, NJ, 1969.
19. Burke, N.E., R.D. Hobbs, and S.F. Kashou. Measurement and Modeling of Asphaltene Precipitation from Live Reservoir Fluid Systems. Pres. at SPE Annual Tech. Conf. and Exhib., Houston, TX, Oct. 2-5, 1988. SPE paper 18273.
20. Novosad, Z. and T.G. Costain. Experimental and Modeling Studies of Asphaltene Equilibria for a Reservoir Under CO₂ Injection. Pres. at SPE Annual Conf. and Exhib., New Orleans, LA, Sept. 23-26, 1990. SPE paper 20530.
21. Kokal, S., J. Najman, S.G. Sayegh, and A. George. Asphaltene Precipitation during Enhanced Recovery of Heavy Oils by Gas Injection. Pres. at CIM/AOSTRA Tech. Conf., Banff, Canada, Apr. 21-24, 1991. CIM/AOSTRA paper 91-10.
22. Mansoori, G.A. and T.S. Jiang. Asphaltene Deposition and Its Role in Enhanced Oil Recovery Miscible Gas Flooding. Pres. at the 3rd European Conf. on EOR, Rome, Italy, April 1985.
23. Kawanaka, S., S.J. Park, and G.A. Mansoori. The Role of Asphaltene Deposition in EOR Gas Flooding: A Predictive Technique. Pres. at the SPE/DOE Sym. on EOR, Tulsa, OK, Apr. 17-20, 1988. SPE/DOE paper 17363.

24. Mansoori, G.A., T.S. Jiang, and S. Kawanaka. Asphaltene Deposition and Its Role in Petroleum Production and Processing. *Arabian J. for Science and Eng.*, 13(1), January 1988, pp. 17-34.
25. Scott, R.L. and M. Magat. The Thermodynamics of High-Polymer Solutions: I. The Free Energy of Mixing of Solvents and Polymers of Heterogeneous Distribution. *J. Chem. Phys.*, 13(5), May 1945, pp. 172-177.
26. Scott, R.L.. The Thermodynamics of High-Polymer Solutions: II. The Solubility and Fractionation of a Polymer of Heterogeneous Distribution. *J. Chem. Phys.*, 13(5), May 1945, pp. 178-187.
27. Halpin, T.P.J. and N. Quirke. A New Method of Continuous Thermodynamics Applied in an Equation of State. *Soc. Pet. Eng. Reservoir Engineering*, November 1990, pp. 617-622.
28. Leontaritis, K.J. and G.A. Mansoori. Asphaltene Flocculation During Oil Production and Processing: A Thermodynamic Colloidal Model. Pres. at SPE International Sym. on Oilfield Chem., San Antonio, TX, Feb. 4-6, 1987. SPE paper 16258.
29. Leontaritis, K.J. Asphaltene Deposition: A Thermodynamic-Colloidal Model. Ph.D. Dissertation, Univ. of Illinois at Chicago, Ill., 1988.
30. Reddy, S.R., D.H. Melik, and H.S. Fogler. Emulsion Stability-Theoretical Studies on Simultaneous Flocculation and Creaming. *J. Colloid and Interface Sci.*, v. 82, No.1, July 1981, pp. 117-127.
31. Park, S.J. and G.A. Mansoori. Aggregation and Deposition of Heavy Organics in Petroleum Crudes. *Energy Sources*, v. 10, 1988, pp. 109-125.
32. Friedlander, S.K.. *Smoke, Dust and Haze. Fundamentals of Aerosol Behavior*. Wiley, New York, 1977.
33. Verwey, E.J.W. and J.Th.G. Overbeek. *Theory of the Stability of Lyophobic Colloids*. Elsevier, Amsterdam, 1948.
34. Leontaritis, K.J. and G.A. Mansoori. Fast Crude-Oil Heavy-component Characterization Using Combination of ASTM, HPLC, and GPC Methods. *J. Pet. Sci. and Eng.*, v. 2, 1988, pp. 1-12.

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
1	Period	BE5	BE5B	BE11A	BE11B	B41044	Jury	Leave	Personal		Vac/Sick	MLOA	a. SGP37		ROE	
2	ending	GMiscible	GMiscible	Lit Oil	Hvy Oil	B000	Duty/Death	W/Out	Leave		I* Flex	5 consec.	B06837 B001	Other		
3	11/1/91	B06090	B06090	B06090	B06090	B45044	in	Pav	(Pre-90)	Regular	Time	days	b. SGP37	Groups	41,42,43	
4		B007	B008	B010	B011	B000	Family		Carryover	HOLIDAY	Off	illness	B06837	Projects	ETC.	TOTAL
5	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
6	Strycker, A.	1	2	1	2	9					8		17			40
7	Chung, F.	40												8		40
8	Jones, R.	32											12			40
9	Kerr, A.		1		14	11								20	2	40
10	Tham, Min			2											18	40
11	Mahmood, S.			36							4					40
12	Olsen, D.								40							40
13	Raible, C.		10										40	30		40
14	Ramzel, B.															40
15	Sarathi, P.				40											40
16	Schatzinger, V												6	34		40
17	Llave, S.								8					30	2	40
18	Pautz, J.													37	3	40
19	Hatcher, E.													27	13	40
20	Crocker, M.													4	28	32
21	Turney, D.			4										10	26	40
22	Johnson, B.												38	2		40
23	Burchfield, T.													3	37	40
24	Ridley, D.													3	36	40
25	Linville, B.	2			3								4	31		40
26	Taylor, G.														40	40
27	Kendall, R.				2									22	16	40
28																
29	TOTALS	75	13	43	61	20	0	1	48	0	12	0	117	261	221	872
30	Grand Total															872
31																
32	[] = (minus) removal of time to correct time sheet.															
33	[] = (plus) addition of time to correct time sheet.															
34	Totals at the bottom reflect the changes.															
35					*	B06837	A.Strycker		4 hours	and	13 hrs	B06837	B003			
36	copy: AS, TB, DO, FC, CR, PS				*	B06837	W.I.Johnson		37 hours	and	1 hr	B06837	B003			

END

**DATE
FILMED**

2 / 18 / 92