DOE/PC/91040--T4

DOE/PC/91040--T4

DE93 007478

**ADVANCED DIRECT LIQUEFACTION CONCEPTS
for PETC GENERIC UNITS**

**Quarterly Technical Progress Report
for Period July 1992 through September 1992**

by

**University of Kentucky
Center for Applied Energy Research**

Sandia National Laboratories

Consolidation Coal Company

LDP Associates

November 1992

Prepared for

The U. S. Department of Energy

Under Contract No.

DE-AC22-91PC91040

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INDEX

INDEX	ii
SUMMARY	1
WORK PERFORMED	7
TASK 1.1 LABORATORY SUPPORT (UK/CAER)	7
Metals Concentration in WCS	7
Hydrogen Consumption	9
H ₂ Consumption by WCS	9
H ₂ Consumption by Coal in Tetralin	9
H ₂ Consumption by Coal in WCS	12
Effect of Fe ₂ O ₃ on Reactivity at Wilsonville	14
Effect of WCS Reactivity on Catalyst Evaluation	15
TASK 1.2 LABORATORY SUPPORT (Consol)	17
TASK 1.3 LABORATORY SUPPORT - (Sandia)	21
TASK 2.1.1 CO PRETREATMENT (UK/CAER)	26
Experimental	27
Coal Liquefaction	27
Optical Microscopy	27
Yield of CO Pretreated Product from Wyodak Coal	28
CO Pretreated Product from Black Thunder Coal	30
Liquefaction of Raw and Pretreated Coal	31
Hydrogen Consumption during Liquefaction	34
Optical Microscopy H ₂ O-insol Residues	34
N ₂ (800 psig), 300°C, 6 ml. 0.33 M NaOH	34
CO (400 psi), 300°C, 4 ml H ₂ O, NaOH	35
CO (800 psig), 300°C, 6 ml H ₂ O, NaOH	36
Liquefaction Residues (THF-Insolubles)	37
400°C tetralin 15 min untreat v. pretre	37
400°C tetralin 60 min raw v. pretreat	38
TASK 2.1.2.1 PRETREATMENT / DEWAXING (Consol)	38
TASK 2.1.2.2 PRETREATMENT / AGGLOMERATION (Consol)	50
SUBTASK 2.1.3 SOLVENT PRETREATMENT (Sandia)	54
Background	54
Experimental	54

Nickel Molybdenum Thin-Film HTO Catalyst Testing	55
Platinum Catalyst Testing	56
Testing with V1074 Feed	58
SUBTASK 2.2.3 MODIFIED REACTOR CONCEPTS (Sandia)	58
TASK 2.3.1 IRON BASED DISPERSED CATALYSTS (UK/CAER)	58
Catalytic Activity of Superfine Iron Oxide	61
Impact of React Variables with SFIO	61
Predicted versus Model Values	63
Relative Conversion of Different Iron Oxides	72
SUBTASK 2.3.3 CATALYST STUDIES (Sandia)	74
Nickel Molybdenum Catalyst Tests	74
Platinum Catalyst Tests	74
Task 2.6.1 FLUIDIZED COKING (UK/CAER)	75
Experimental Apparatus	77
Project Status	79
TASK 3.4 PRELIMINARY TECHNICAL ASSESSMENT (LDP Assoc)	81
Baseline Economic Assessment	81
Dewaxing the Process Solvent Distillate	81
Fluid Coking	82
HRI Two Stage Process	82
REFERENCES	84

SUMMARY

TASK 1 LABORATORY SUPPORT

UK/CAER - Based upon the concentrations of molybdenum and iron in the Wilsonville Composite Solvent (WCS), the 7.8% concentration of Fe_2O_3 in the 30 wt% coal slurries that were used in liquefaction studies to which 2 wt% Fe_2O_3 was added, breaks down into its component parts as follows: 2.0% of which is freshly added iron oxide, 4.2% as recycled added iron oxide, 0.3% as freshly added iron oxide in the coal ash, and 1.3% as iron oxide in the recycled coal ash. The corresponding distribution of molybdenum in these runs, to which no fresh molybdenum was added, was 350 ppm of recycled added molybdenum and 1 ppm Mo in the fresh and recycled coal ash.

Along with the exceptionally high conversion of the IOM in the WCS and the observed transformation of PA+A, significant amounts of hydrogen are consumed by solvent. Hydrogen consumption values for the run without any added fresh catalyst and in the absence of coal was 10.3 mg/gram of WCS, which is equivalent to consumption of 18.8% of the total amount of hydrogen present at the start of the run. The addition of fresh catalysts to the reaction mixture increased the hydrogen consumption to a high of 15.8 mg/g solvent. Comparatively, coal in tetralin had a gaseous hydrogen consumption level of 8.7 mg/g maf total feed. Therefore, the magnitude of the consumption by solvent is as great as the total consumption by the coal present in a 30 wt% slurry.

Consol - The distillate and resid samples from Wilsonville Run 262 that CONSOL prepared and distributed to the program participants for experimental studies were analyzed for proton distributions and phenolic -OH concentrations. The elemental compositions, including the molybdenum content, of these samples

and the Black Thunder coal were also determined.

Sandia - Coal liquefaction tests using V1074, Wilsonville Composite Solvent, Wyodak coal and a hydroaromatic donor have demonstrated solvent quality improvements at reduced pressures. These tests indicate that solvent improvements are very effective in reducing Insoluble Organic Matter in coal liquefaction.

TASK 2 COAL PRETREATMENT AND CATALYST WORK

CO-Pretreatment UK/CAER

CO pretreatment of coal has potential beneficial impact on a number of areas, namely, (1) major reconstruction and hydrogenation of the coal structure leading to the enhancement in reactivity of the coal (2) partial rejection of the oxygen in the coal structure and possible arrest of retrogressive reactions which led to a better hydrogen consumption efficiency during the liquefaction process. A brief discussion on the material and elemental balance is presented to provide an insight into the efficiency of the pretreatment process at laboratory scale. A preliminary material balance was performed for the Black Thunder coal.

The physical and structural changes occurring during CO pretreatment was evaluated by an optical microscopy technique which was applied to both the raw coal and the pretreated products. This technique has also been applied to residues generated from subsequent liquefaction experiments of both the raw and pretreated coal. These results are presented in conjunction with the available conversion data. Preliminary results have indicated that Black Thunder subbituminous coal responded to the pretreatment in a similar manner as Wyodak coal. A discussion on some of the main and interactive effects of various variables (temperature, catalyst loading, type of catalyst and CO partial pressure) in the reaction system is

presented.

Catalyst Work

UK/CAER - The liquefaction activity of a sample of superfine iron oxide (SFIO) which is comprised of nanometer size particles with very high BET surface area of 318 m²/g. was evaluated. A full 2^k factorial experimental design was followed to determine the main effects and interactions of reaction temperature, catalyst concentration, and sulfur concentration separately for THF conversion, hydrogen consumption, CO+CO₂, hydrocarbon gas, oil and PA+A yields. A linear model having terms for each of the main effects and each interaction was developed for each dependent variable. An analysis of variance is used to determine the value of these coefficients and the statistical significance of each coefficient. The high-low values of the factors were: reaction temperatures of 390 and 440°C, centered at 415°C; iron oxide concentrations ranging from 1 to 4 wt% Fe on as-fed coal; sulfur selected to explore a wide range of S/Fe atomic ratios with the centerpoint at 2:1. The R² value plus the probabilities indicate a good fit of the model to the observed values. Temperature has by far the biggest effect on each of the dependent variables except for THF conversion where temperature and catalyst concentration appear to be about equal. The catalyst sensitivity values reflect known catalysis of iron in promoting coal dissolution but not being overly beneficial for converting PA+A to oils. The negative effect of sulfur on THF conversion and on the oil yield was unexpected.

The predicted data at the midpoint are in good agreement with the experimentally observed values. The biggest differences were in the THF conversion, i.e., 107 predicted versus 110 wt% observed. Use of the model to predict dependent variables at the center-edge departed significantly from experimentally determined values under these conditions. However, experimental results show that

the addition of SFIO, at a loading of 1.1 wt% iron on maf coal, which is 2 wt% added iron on dried coal, produced 8.5 wt% more oils than in the thermal case while THF conversion was essentially the same or differed only slightly. Added WIO gave 5 wt% more oil than in the thermal case, which agrees closely with the results observed at Wilsonville. SFIO at the 1 wt% added iron oxide level, which fell outside the range used in developing the model, had a dramatically increased oil yield of 61.2 wt%, which is an advantage of almost 13 wt% over the thermal case. At the same time, THF conversion, HC gases yield and CO+CO₂ were unchanged over the 2 wt% SFIO addition level.

Pretreatment / Dewaxing

CONSOL - Preliminary dewaxing tests to determine suitable conditions for producing dewaxed oil for Sandia to use in hydrogenation experiments were completed. A 1.3 kg sample of -35°C dewaxed oil and a 1.8 kg sample of -5°C dewaxed oil were prepared. Dewaxing significantly improved liquefaction solvent quality. Samples (approximately 1 L each) of these dewaxed oils were shipped to Sandia for solvent hydrogenation tests.

Pretreatment / Agglomeration

CONSOL - Fifteen agglomeration runs were made with No. 6 fuel oil to explore conditions appropriate for ash rejection from Black Thunder subbituminous coal. Ash rejection was limited to about 15% unless the pH was lowered below 5.6, and ash rejection reached about 40% when the pH was 2.5 or lower. The additional ash rejected below pH 5.6 was dissolved, rather than suspended, in the water. Organic recovery was over 99 wt % in these experiments.

Solvent Hydrogenation

Sandia - Catalyst testing for solvent pretreatment continued using Hydrous Titanium Oxide catalysts. The catalysts were

tested for the combined water-gas shift/solvent hydrogenation reaction using a synthetic solvent (9.5% polynuclear aromatics in hexadecane).

A nickel/molybdenum thin-film HTO catalyst coated on alumina extrudate showed catalyst activity equivalent to a commercial NiMo on alumina catalyst. The thin-film catalyst had a molybdenum content of 7.2% compared to 12.4% for the commercial catalyst. A platinum HTO catalyst showed very high activity for solvent hydrogenation and water-gas shift. Experiments at 315°C showed catalyst sulfur tolerance during a one-day catalyst deactivation test.

Coking

UK/CAER - Fluid coking of the vacuum bottoms to remove ash and unconverted coal from the liquefaction system is being investigated because the capital costs for installing such a system are estimated to be much lower than a critical solvent de-ashing system. In this scheme the coker overhead stream would be recycled back to the liquefaction process. An existing 3 inch fluidized retort is being modified to conduct the studies.

TASK 3 PRELIMINARY TECHNICAL ASSESSMENT

LDF Associates - A baseline economic assessment, based on Wilsonville Run #263J, is being prepared which will serve as the reference against which the results of this program will be compared. Calculation of the material and energy balances for the conceptual commercial plant were completed and estimation of the investment for the main process units was begun. CONSOL's Dewaxing test results were analyzed and used to help develop a simple Dewaxing separation model which was used to predict steady-state commercial unit performance. Two options were examined. In one a large portion of the entire distillate process stream can be treated at mild conditions to separate the

net wax produced in the process, while alternatively, a much smaller portion of the distillate stream can be treated at more severe conditions. Hydrotreating of the hard wax is likely to be required in order to meet strict odor and color specifications. Texaco, one of the leading licensors of solvent dewaxing technology, was contacted. They were very cooperative in providing technical information and a preliminary investment for a solvent dewaxing unit. Based on Texaco's information and the information developed by the wax separation model the economics indicates that the cost of the Dewaxing Unit and the reduction in the main product (gasoline) rate can almost be offset by the value of the wax which is separated and purified.

TASK 1.1 LABORATORY SUPPORT (UK/CAER)

Metals Concentration in WCS

The concentrations of molybdenum and iron in each of the three fractions of the Wilsonville Composite Solvent (WCS) and the concentration of iron and molybdenum in the Black Thunder coal were determined by Consol and are included in this report. From these data the amounts of iron and molybdenum in the reactants used in the catalytic screening runs in this program were more accurately calculated than reported previously.

In Wilsonville Run 262, Black Thunder coal was fed as a 30 wt% slurry in Wilsonville composite solvent to which was added 2 wt% iron oxide, or 1.4 wt% iron, and 100 ppm molybdenum on dried coal. The total amount of iron in the system was a sum of (1) "added iron" from the freshly added catalyst, (2) "recycled added iron" contained in the ashy resid, that came originally from the addition of iron oxide catalyst precursor, (3) iron contained in the freshly added coal ash, and (4) iron in recycled coal ash contained primarily in the ashy resid.

	Fe ₂ O ₃ wt% mf coal	Fe, wt% mf coal
Freshly Added Iron	2.0	1.4
Recycled Added Iron	4.2	2.9
Fresh Coal Ash Iron	0.3	.2
Recycled Coal Ash Iron	1.3	0.9
Total Iron	7.8	5.4

Of the total amount of iron in the system, only 20% was

introduced in the Black Thunder coal ash. The overwhelming majority was originally introduced as iron oxide with the coal slurry. Of that 80% added iron, one-third was freshly added while the remainder was recycled. Clearly the iron appears to report exclusively to the ash phase with little of it appearing to be either molecularly dispersed or suspended as very small particles in the liquid phase. At present we have no data on the relative activities of the freshly generated iron catalyst versus the catalytic iron species contained in the recycle stream.

Similar treatment of the available molybdenum data provides relative concentrations of freshly added metal versus that contained in the recycle stream. Unlike the iron species, there was a sizable Mo content reported in the deashed resid fraction, i.e., 53 ppm., and negligible concentration in the original coal ash.

	Mo x 10 ⁴ , wt% mf coal
Freshly Added Mo	100
Recycle Added Mo	350
Mo in Fresh & Recycled Coal Ash	1
Total Mo	451

At an addition rate of 100 ppm molybdenum on dried coal in Run 262, the recycle of ashy and deashed resid resulted in an increase of 350 ppm Mo in the feed for a total of 450 ppm added Mo on dried coal. As with the iron case, at present no information is available regarding the activity of the recycled molybdenum species. We will be evaluating, in the near future, the relative activity of adding 100 ppm Mo to the system.

Hydrogen Consumption

H₂ Consumption by WCS - Since the last reporting period hydrogen consumption data on runs reported in the 3rd Quarterly Report have become available. The exceptionally high conversion of the IOM in the WCS and the observed transformation of PA+A suggest that the solvent may be consuming significant amounts of hydrogen. Hydrogen consumption values for runs made in composite solvent in the absence of coal are reported in Table 1 both in the presence and absence of added catalysts. These data were reported previously without the hydrogen consumption values.¹

For the run without any added fresh catalyst the hydrogen consumption was 10.3 mg/gram of WCS which is equivalent to consumption of 18.8% of the total amount of hydrogen at the start of the run. The addition of fresh catalysts to the reaction mixture, except for the Wilsonville Iron Oxide (WIO), increased the hydrogen consumption to a high of 15.8 mg/g solvent.

Although a blank run comparison with distillate alone was not performed we would anticipate that hydrogen consumption by these highly hydrogenated liquids under strictly thermal conditions would be minimal.

H₂ Consumption by Coal in Tetralin - Generally, dissolution in tetralin or allied solvents provide some indication of the level of hydrogen consumption by a coal with some, though not a significantly large amount, of the hydrogen going into the solvent. The level of hydrogen consumption for Black Thunder coal in tetralin at the same overall conditions as run in the blank WCS runs above is shown in Table 2. These data show only gross gaseous hydrogen consumption and do not show the level of hydrogen transfer from the solvent to the coal.

Table 1. H₂ Consumption During Thermal Conversion of WCS
415°C; 60 minutes; 1000 psig H₂ (cold); 50 ml. reactor volume

		None	WIO	SFIO	MoNA	S-324
Fresh Cat/Solv Feed, wt% (af)		-	1.0	1.0	1.0	5.4
Fresh Fe/Solv, wt% (af)		-	0.69	0.62	-	-
Added Fe, wt% af [†]		1.7	2.4	2.3	1.7	1.7
Added S/Fresh Added Fe		-	2.3	2.3	-	-
Product from Solvent						
HC Gases, wt% af		0.3	0.4	0.6	0.4	0.4
CO+CO ₂ , wt% af		0.1	0.1	0.1	0.1	0.1
Oils wt% af	67.2*	69.7	75.7	75.7	78.8	79.9
PA wt% af	20.8*	21.8	16.4	17.5	13.7	11.6
IOM, wt% af	12.1*	8.1	7.4	6.0	7.0	8.1
mg H ₂ /g Solvent		10.3	9.3	14.0	14.8	15.1
H ₂ consumed, wt%		18.8	15.8	23.9	25.3	27.6
Conversion, wt%						
IOM (af)		33	39	50	42	37
PA + A		-5	21	16	34	47
(IOM + PA + A)		9	28	28	37	43
Run Number		140-1	142-1	156-2	149-1	126-2
* Weight percent in feed. † Excludes iron contained in coal ash. ash. ash						

Table 2. Liquefaction of Black Thunder Coal in Tetralin*

	Time, min		
Yields, wt% maf coal	15	30	60
HC Gases	0.4	0.6	1.0
CO+CO ₂	4.2	4.5	4.9
Total Gases	4.6	5.1	5.9
Oils	20.7	28.0	43.4
PA + A	40.9	43.6	35.8
IOM	33.7	23.3	14.9
THF Conversion, wt%	66.3	76.7	85.1
H₂ Consumption			
mg/g maf coal	30.0	28.0	36.2
mg/g maf feed	6.9	6.4	8.7
Fraction H ₂ consumed	18.3	17.0	23.2
Run Number	154-2	154-1	160-2
* See Table 21 in Reference 1 for previously reported data on this run. Conditions: 415°C, 1000 psig H ₂ , 2.3 wt tetralin/wt dried coal.			

The level of hydrogen consumption, calculated on a total feed basis for the 60 minute tetralin Run 160-2, was on the same order as for the WCS without coal in Run 140-1 in Table 1. Coal in tetralin showed a gaseous hydrogen consumption level of 8.7 mg/g maf feed while in WCS in the absence of coal the corresponding value was 10.3 mg/g maf feed. This level of hydrogen incorporation corresponds to consumption of about one-quarter of the gaseous hydrogen charged to the reactor.

H₂ Consumption by Coal in WCS - Liquefaction of Black Thunder coal in WCS at the same concentration as in tetralin above is shown below in Table 3. In Run 167-1, under the same conditions as in tetralin for a 60 minute reaction period, the gaseous hydrogen consumption based upon coal was 52.4 mg/gram maf coal which is significantly higher than the 36.2 mg/g maf coal in tetralin in Run 160-2. This higher value could be the result of either higher conversion of the coal, catalyzed by the significant amount of iron and molybdenum already present in the ashy resid component of the WCS, or the result of significant hydrogenation of the various fractions of the WCS, again being catalyzed by the iron and molybdenum. Coupling these results with those observed in Table 1 in WCS in the absence of coal strongly suggests that solvent hydrogenation may be a major recipient of hydrogen being transferred to the product from the gaseous phase.

The question arises as to which component(s) in the solvent is consuming the hydrogen. Although liquefaction of coal in distillate only would conclusively demonstrate its behavior, it is highly unlikely that it would significantly hydrogenate because of its already highly hydrogenated state. Based upon previous results, distillate solvent was found to exhibit little reactivity under these conditions and would not likely complicate the analysis of coal reactivity or affect the level of hydrogen consumption.² Therefore, we wouldn't expect it to behave much differently regarding hydrogenation during liquefaction than tetralin. Although at present we have no data on liquefaction of Black Thunder coal in distillate solvent alone, there are data available on liquefaction of this coal in the presence of added iron oxide.

The level of hydrogen consumption during liquefaction of Black Thunder coal in the presence of 2 wt% freshly added Fe₂O₃ in

Table 3. Black Thunder Liquefaction

	WCS	WCS + Fe ₂ O ₃	Distillate + Fe ₂ O ₃
Solvent/coal w/w ratio	1.8	1.8	1.8
Distillate	0.77	0.77	1.8
Residual	1.04	1.04	0
Fresh Fe ₂ O ₃ Added (wt% mf coal)	none	2.0	2.0
Yields, wt% maf coal			
HC Gases	1.9	2.1	2.2
CO + CO ₂	5.0	4.8	5.1
Oils	48.5	53.8	35.8
PA + A	52.2	45.3	51.9
IOM	-7.6	-6.0	5.0
THF Conv wt%	107.6	106.0	95.0
H ₂ Consumption			
mg/g maf coal	52.4	53.4	35.3
mg/g maf feed	16.3	16.6	10.2
Run Numbers	139-1/ 167-1	142-2/ 189-1	169-2
* Conditions: 415°C, 1000 psig H ₂ cold, 60 minutes, 2.4 S atoms/Fe atom			

distillate only (Run 169-2 in Table 3) was 35.3 mg/gram maf coal. This value is quite close though slightly higher than observed for liquefaction in tetralin which gave a value for hydrogen consumption of 36.2 mg/gram maf coal. These data show that even in the presence of a catalyst, though obviously a weak one, the hydrogen consumption levels in Wilsonville distillate is not significantly different from tetralin. This, of course, does not address the alternative that the iron and molybdenum present in the ashy resid fraction of the WCS could catalyze the hydrogenation of the distillate solvent. We suspect that hydrogenation would be reasonably small because of the already highly hydrogenated state of the solvent. This then suggests that most of the hydrogen consumption by WCS goes into the residual fractions or the IOM.

Liquefaction of Black Thunder coal in WCS results in a significantly higher level of hydrogenation than occurs in the absence of coal. The levels of hydrogenation during liquefaction in WCS in the absence and presence of freshly added Fe_2O_3 at a level of 2 wt% of coal were 45.9 and 53.5 mg/g maf coal, respectively, which are well above the values observed in the absence of the residual fractions. The corresponding values based upon hydrogen consumption by total feed are 16.3 and 16.6 mg/g total maf feed, respectively, which are in excess of the observed hydrogenation for WCS shown in Table 1, specifically Runs 140-1 and 142-1, which were 10.3 and 9.3 mg/gram maf total feed, respectively.

Effect of Fe_2O_3 on Reactivity at Wilsonville

An increase in oil make and hydrogen consumption in the presence of added WIO was observed in Run 142-1/189-1 in Table 3. Correspondingly, the addition of the WIO to WCS without coal results in a slight, though possibly not statistically

significant, drop in hydrogen consumption (9.3 versus 10.3 mg/g maf feed) and a significant increase in oils conversion (75.7 v 69.7) as shown in Table 1. Small, though readily recognizable changes, were observed in the Wilsonville pilot plant operation when running with 2 wt% added iron oxide. Specifically, results reported from Wilsonville upon adding iron oxide in Run 249 showed an increase in coal conversion (wt% maf coal) of 4 wt%.³ They also reported in Run 246⁴ that adding DMDS to Wyodak coal containing 2 wt% iron oxide resulted in an increased exotherm in the reactor of from 30 - 40°F (See Figure 35 in Reference 4). This presumably occurs because of the formation of the active pyrrhotite phase. How much the hydrogenation of the DMDS contributed to the exotherm that was observed wasn't discussed probably because they believed the magnitude of the exotherm would be quite small.

Effect of WCS Reactivity on Catalyst Evaluation

Certainly the evaluation of coal liquefaction catalysts is complicated by the use of a solvent that is highly reactive, especially from the standpoint of consuming significant quantities of gaseous hydrogen. Any evaluation of the activity of a catalyst that would be added to such a reaction system has to be based upon an incremental change that would be observed over a base conversion level that would itself reflect the catalytic effect of metals already contained in the ashy resid. This approach seems viable if the catalytic effect of the freshly added catalyst were simply additive, however at the outset there is no way of knowing whether any interactive or synergistic effects will be observed. The challenge will be to recognize their existence, if indeed they are present.

It would be, of course, desirable to have additional data on the reactivity of the various solvent constituents in the reaction system. The above data show that the distillate, at least in the

presence of added Fe_2O_3 , is largely unreactive under these conditions. It would be of interest to further expand this data base to determine:

1. The reactivity of the coal in distillate alone without any catalyst and in the presence of the iron and molybdenum that is present in the WCS.
2. The reactivity of the deashed resid added to the distillate in the presence of coal. This could be examined, in part, by examining the reaction in the absence of the ashy resid component.
3. Determine the catalytic effect of fresh catalysts or their precursors on the individual combinations.
4. Determine the effect of adding back separately the IOM, coal ash, and the iron and molybdenum contained in the ashy resid in order to determine their effect on the reactivity of both the residual fraction and the coal.

This IOM reactivity could be related to previous work done on Kerr McGee ash concentrate and filter cake materials. In the earlier work significant conversion of solvent IOM was observed in liquefaction reactions in which the solvent contained ash concentrate taken from the Wilsonville ROSE-SR unit.^{5,6} A specific difference in the feed used in that study and the composite solvent used in this study is that the ash-IOM component, which is contained in the ashy resid in the composite solvent, had not passed through the ROSE-SR unit. Only a very small portion of the composite solvent, namely the deashed resid, which made up 6.7% of the composite solvent, came from the ROSE-SR unit. The earlier work showed that the high reactivity of the solvent components, of which the IOM was the most reactive, was not

related to the accumulation of catalytic metals in the ash concentrate, since those samples were taken when the plant was running in a non-catalytic thermal mode. Although this reactivity was originally thought to be related to changes produced in the ROSE-SR unit, the observations made in this study suggest that the ROSE-SR unit has little to do with the solvent reactivity.

Exploring these questions would enhance our understanding of this particular system. However, this information is not absolutely needed in order to meet the objective of this task which is to identify more active and selective catalysts for converting coal. However, as time permits, we will attempt to evaluate the WCS while basically pursuing the overall objective of finding more active catalysts. We are investigating whether we might be able to find another WCS feedstock without the molybdenum for evaluating catalysts. Also, additional work is being done using distillate solvent in the evaluations in order to increase our confidence in the catalyst comparisons. These alternative approaches will be pursued carefully in order to insure that the limited resources being applied to this program are being efficiently applied.

TASK 1.2 LABORATORY SUPPORT (CONSOL)

The elemental compositions of aliquots of the distillate and resid samples from Wilsonville Run 262 that CONSOL prepared and shipped to Sandia and UK/CAER were determined. The results of these analyses, together with those of the Black Thunder feed coal to Run 262, are shown in Table 4.

Comparison of the ash elemental compositions of the Black Thunder coal and the V-1082 ashy resid, Table 4, shows a much higher Fe_2O_3 content in the ashy resid. This is due to the iron catalyst

added during the run. A calculation of the iron addition from the ash and Fe_2O_3 contents of the coal and resid indicates that 2.1 wt % Fe_2O_3 was added to the dry coal during the period of Run 262 from which these samples were obtained. This agrees with the 2 wt % iron oxide addition reported for this part of Run 262.⁷

The molybdenum contents of the distillate, resid and Black Thunder coal samples from Wilsonville Run 262 also were determined. During the period of Run 262 from which these samples were derived (September 16, 1991, between balance periods D and E) 100 mg/kg Mo (on an MF feed coal basis) was added in the form of Molyvan L catalyst precursor. The molybdenum contents of these materials are given in Table 4, together with the elemental analyses. These values are substantially lower than those previously reported (see Ref 1). These results appear to be generally consistent with Wilsonville's operating conditions at the time the samples were taken. For example, the molybdenum-to-ash feed ratio in Run 262E was 1520 mg/kg. CONSOL's analysis of the ashy resid (Table 4) gives a Mo/ash ratio of 1470 mg/kg. The agreement in these two values indicates that the molybdenum tends to track the coal ash. The molybdenum/ash ratio of the deashed resid is greater (7300 mg/kg) indicating that some molybdenum is retained with the deashed product. The V-1074 distillate is low in molybdenum (2 ppm). CONSOL's results also are generally consistent with our earlier analyses of samples and fractions from Wilsonville Run 262A and B (under DOE Contract No. DE-AC22-89PC89883) in which almost all of the Mo reported to the THF insoluble fraction of various process stream samples.⁸

^1H -NMR analysis and phenolic -OH determinations for the distillate and resid samples were completed. The experimental procedures used to obtain the ^1H -NMR and phenolic -OH data appear elsewhere.^{9,10} The ^1H -NMR spectra were obtained in $\text{C}_5\text{D}_5\text{N}$ solution

Table 4

**ANALYSIS OF MATERIALS FROM WILSONVILLE RUN 262
(September 16, 1991)**

	<u>Black Thunder Coal</u>	<u>V-1082 Ashy Resid</u>	<u>V-130 Deashed Resid</u>	<u>V-1074 Distillate</u>
<u>Moisture, wt% as received</u>	22.40			
<u>Ultimate, wt% dry</u>				
Carbon	70.32	72.59	89.79	88.86
Hydrogen	4.68	5.40	7.26	9.91
Nitrogen	1.04	0.88	0.86	0.44
Sulfur	0.50	1.93	0.03	<0.03
Chlorine	0.035	N.D.	N.D.	N.D.
Ash	6.69	20.28	0.73	N.D.
SO ₃ -free basis	5.54	16.04	N.D.	N.D.
Oxygen, by diff	16.74	-1.08	1.33	0.79
SO ₃ -free basis	17.89	3.15	N.D.	N.D.
<u>Molybdenum, mg/kg as det</u>	20	298	53	2
<u>Sulfur forms, wt% dry</u>				
Pyritic	0.08			
Sulfate	0.08			
Organic	0.34			
<u>Major Ash Elementals, wt% of ash</u>				
Na ₂ O	0.48	0.47		
K ₂ O	0.49	0.29		
CaO	21.34	16.13		
MgO	4.30	3.49		
Fe ₂ O ₃	5.48	23.19		
TiO ₂	1.14	0.89		
P ₂ O ₅	0.96	1.14		
SiO ₂	31.48	22.82		
Al ₂ O ₃	15.76	10.71		
SO ₃	17.26	20.92		
Total	98.69	100.05		

*Note: N.D. - not determined

(resid) or CDCl₃ solution (distillates). The phenolic -OH determinations were made on the tetrahydrofuran (THF) soluble portion of each sample. THF solubilities and ash contents of these materials are shown below.

The results of the ¹H-NMR and phenolic -OH determinations are given in Table 5. As expected, the soluble portions of the ashy resid and the deashed resid have similar characteristics. The distillate is considerably less aromatic and correspondingly more aliphatic than the resid samples. The phenolic -OH contents of the resid samples are about double that of the distillate.

Table 5
¹H-NMR AND PHENOLIC -OH DATA, THF-SOLUBLE BASIS
Wilsonville Run 262 Materials

<u>Sample</u>	<u>Proton Distribution, %</u>							<u>Phenolic -OH</u>	
	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>	<u>Conc, meq/g</u>	<u>v, cm⁻¹</u>
V-130	22.7	4.9	19.3	9.3	14.7	19.3	9.7	0.80	3298
V-1074	11.3	3.6	14.7	7.6	15.8	34.6	12.3	0.44	3306
V-1082	24.6	4.0	20.2	9.5	14.9	18.1	8.7	0.86	3296

TASK 1.3 LABORATORY SUPPORT (Sandia)

In support of the solvent pretreatment work, the hydrogen donating ability of the Wilsonville Run 262E (V1074) Heavy Distillate was evaluated using the modified equilibrium test described by CONSOL.¹¹ The reaction conditions were 400°C, 30 minutes with no added gas pressure. Two coal liquefaction experiments were performed with Wyodak subbituminous coal, one using straight V1074 as solvent, and the other using V1074 with an added hydrogen donor (hexahdropyrene= H_6Py).

In addition, two coal liquefaction runs were made using the Wilsonville Composite Solvent consisting of heavy distillate (V1074), ashy resid (V1082), and deashed resid (V130) from Wilsonville Run 262. These tests used Wyodak coal and the Wilsonville composite solvent both with and without added hexahdropyrene. Since refluxing was noted during the liquefaction runs using V1074, the composite solvent tests were pressurized with 100 psig of nitrogen prior to reaction. This gave an added benefit during post run analysis, since a nominal positive pressure on the reactor aids in gas subsampling.

Data from direct coal liquefaction tests at CAER showed that yield and conversion calculations for liquefaction experiments using the Wilsonville composite solvent must take into account solvent reactivity. Since the composite solvent contains oil, insoluble organic matter (IOM), ash, preasphaltenes and asphaltenes (PA&A), the calculations should be done on a forced ash balance accounting for initial solvent makeup. The Advanced Concepts Quarterly Report for April-June 1992 contains a full description of the of the forced ash calculation method including the composition of the Wilsonville composite solvent. The assumption for these tests is that the solvent solubility classes are additive. Results from batch microautoclave tests are shown in Tables 6 and 7.

Table 6. Forced Ash Balance (400°C, 30 min, 100 psi N₂ cold, Wyodak Coal)

Reactant, grams				
Coal	2.4565	2.4718	2.5039	2.5064
Ashy Resid	0	0	1.8994	1.5235
Deashed Resid	0	0	0.2537	0.2094
Distillate	3.7548	3.0056	1.6756	1.2857
H ₆ Py	0	0.7519	0	0.7547
Total	6.2113	6.2293	6.3326	6.2797
Reactant Solvent, g				
Ash in Solvent	0.0098	0.0078	0.3858	0.3094
Wt Oils(+H ₆ Py)	3.6012	3.6346	2.3338	2.5745
PA + A (af)	0.0278	0.0222	0.7009	0.5636
IOM (af)	0.1160	0.0928	0.4083	0.3258
Moisture in Coal	0.6903	0.6946	0.7036	0.7042
Coal, maf	1.5203	1.5300	1.5499	1.5516
Coal Ash	0.2459	0.2472	0.2504	0.2506
Total	6.2113	6.2293	6.3326	6.2797
Product, g				
Coal Gas	0.0555	0.0503	0.0107	0.0155
PA + A	0.4921	0.4109	1.2800	1.0884
THF Insol	0.9353	0.8105	1.8333	1.2662
Water	0.6903	0.6946	0.7036	0.7042
Oil (diff)	4.0381	4.2630	2.5050	3.2054
Run Number	073001	073002	081901	081902

Table 7 Product Yield for Microautoclave Tests (Forced Ash Balance)

Solvent	V1074	V1074+H ₆ Py	Composite	Composite + H ₆ Py
Gases	3.6	3.3	0.7	1.0
Wt Oils	28.7	41.1	11.0	40.7
Wt PA+A	30.5	25.4	37.4	33.8
Wt IOM	37.1	30.2	50.9	24.5
Coal Conv	62.9	69.8	49.1	75.4
Run Number	073001	073002	081901	081902
Coal conversion is equal to (100-IOM Yield). All numbers given in % Yield on a daf coal basis. (Wyodak Coal, 400°C, Autogenic-100 psi N ₂ , 30 minutes, No catalyst).				

Results from experiments with added hexahdropyrene show a dramatic increase in coal conversions, especially in the Wilsonville composite solvent (compare exp. 081901 and 081902). Addition of a hydrogen donor was particularly effective in reducing IOM and increasing oil yield. Solvent dewaxing (subtask 2.1.2.1) and solvent from the coking studies (subtask 2.6.1) should provide even more opportunity to increase donor capacity by generating a more aromatic feed for our solvent pretreatment studies.

An attempt was made to dewax a small quantity of Wilsonville Run 262E (V1074) Heavy Distillate, using the ketone dewaxing procedure described by CONSOL.¹² These tests were exploratory and preliminary to receiving samples from CONSOL. High resolution gas chromatograms and elemental analyses of the wax and dewaxed products are shown in Figures 1 and 2.

FIGURE 1: Dewaxed V1074 Heavy Distillate

Carbon Hydrogen
 88.9% 9.0%
 H/C Ratio = 1.21

FIGURE 2: Wax from V1074 Heavy Distillate

Carbon 85.4%
 Hydrogen 14.1%
 H/C Ratio = 1.98

Solvent samples dewaxed at -5°C and -35°C were received from Consol in September.

TASK 2.1.1 CO PRETREATMENT (UK/CAER)

In the last reporting period, we have shown that CO pretreatment on Wyodak coal has potential beneficial impact on a number of areas, namely, (1) major reconstruction and hydrogenation of the coal structure leading to the enhancement in reactivity of the coal (2) partial rejection of the oxygen in the coal structure and possible arrest of retrogressive reactions which led to a better hydrogen consumption efficiency during the liquefaction process.

In this report, a brief discussion on the material and elemental balance is presented to provide an insight into the efficiency of the pretreatment process at laboratory scale. Similar material balance exercise will be performed for the Black Thunder coal as data becomes available.

In order to examine the physical and structural changes occurring during the CO pretreatment process, an optical microscopy technique has been applied to the raw coal and the pretreated products. This technique has also been applied to residues generated from subsequent liquefaction experiments of both the raw and pretreated coal. These results are presented in conjunction with the available conversion data.

Preliminary results have indicated that Black Thunder subbituminous coal responded to the pretreatment in a similar manner as Wyodak coal. A discussion on some of the main and interactive effects of various variables (temperature, catalyst loading, type of catalyst and CO partial pressure) in the reaction system is presented.

Experimental

Coal Liquefaction - Liquefaction experiments were performed using 2.0 g raw or pretreated coal (Wyodak, 800 psig CO, 6 ml. 0.33 M NaOH, 300°C, 1 hour). Tetralin (2:1 tetralin : coal ratio) was charged into a 25 ml. microautoclave and the reactor was leaked tested and pressurized to 800 psig with H₂. The reaction was carried out at 400 °C from 15 to 60 min. . The reactor was cooled rapidly in a bucket of water and the gaseous products were collected for analysis. The solid/liquid products were scrapped out of the reactor with THF and the detailed work-up procedure has been previously described (4th quarterly report). The insoluble organic matter(IOM) defines the total coal conversion, Preasphaltenes and asphaltenes (PA+A) are the product components soluble in THF but insoluble in pentane , and oil is defined as the THF and pentane soluble fraction.

Optical Microscopy - Samples of coal, pretreated coal, and liquefaction residues were prepared for microscopical examination by mixing with epoxy resin, placing the mixture into a small cylindrical mold, and allowing the epoxy to harden. A sample surface was then ground and polished on a rotating lap using a series of SiC grits and alumina polishing compounds.

Microscopical observations were conducted using a Leitz MPV Compact polarizing microscope-photometer. As a qualitative measure of the acidic oxygen functional groups in the feedstock and pretreated coal, a freshly polished surface of the coal-epoxy pellet was immersed in a solution of KOH and water (pH = 13), rinsed, then immersed into a solution of water and cationic dye (Safranin-O). This procedure has been used as a petrographic method for detecting weathering in coals (Gray et al., 1976; Marchioni, 1983), the results of which are presumably a function of the number of carboxyl and phenolic groups in the coal; the greater the proportion of acidic oxygen functional groups, the more intense the staining of the polished coal surface.

Yield of CO Pretreated Product from Wyodak Coal

Elemental analysis of the humic acid fractions, THF insolubles and PA+A fractions was provided in several of the cases in the previous report. In other cases elemental analysis of the total water insoluble product was provided. Using this data the recoveries of the individual elements in the water insoluble products was calculated based upon the proximate and ultimate analysis of the original Wyodak coal. These data are shown in Table 8.

As pointed out previously, workup of the 800 psig CO products was less complicated than the lower pressure runs where humic and fulvic acid fractions were formed. In the higher pressure runs the total recovered masses were between 89 and 99 wt%, suggesting some error in these measurements. Since replicates were not made, no estimate of error in these data can be provided. However, the magnitude of these recoveries suggest that only a small amount of the total feed is lost. For all of these runs it appears that mass recoveries on the order of 90% is consistent with carbon recoveries in the high 90s. In run 45 made at 800 psig 97% carbon recovery was observed. The numbers in run 49 were extraordinarily large compared to run 45. Whether these are significant is unknown at present, however they need to be evaluated to determine if water concentrations has such an effect on recovery.

Hydrogen recoveries indicate that more hydrogen is incorporated into the product at the higher CO pressures. Hydrogen recoveries for the higher pressure runs at significantly greater than 100% while the run at 200 psig is only 84%. The intermediate pressure run at 400 psig CO gives an intermediate value. Whether this is related to higher concentrations of the CO-H₂ intermediate or the overall higher hydrogen partial pressure isn't known at this stage. As discussed below, these data suggest that the more

Table 8. Water Insoluble Product from CO Pretreatment

2.4 grams Wyodak coal, 4.4 wt% NaOH on maf coal, 25 ml reactor

Water, ml	2	6	4	2	6	6
CO psig, initial cold	200	200	400	800	800	800 N ₂
Products, wt% maf coal						
PA+A	2.2	5.5	17.2	17.6	18.0	0.0
IOM	78.6	69.2	72.8	81.6	71.7	80.0
Humic Acids	5.1	5.5	2.7			7.0
Total Recovered	85.9	80.2	93.2	99.2	88.8	87.0
Recovery wt%						
C	93.3		101.1	109.2	97.2	97.0
H	84.1		99.3	111.2	106.9	81.4
N	79.3		119.9	106.8	90.8	114.9
S	62.5		59.6	74.2	96.9	50.9
O	63.7		66.1	64.4	58.9	55.8
Removal, wt%						
C	4.8		-0.8	-6.5	2.0	2.1
H	0.8		0.0	-0.5	-0.3	0.9
N	0.3		-0.3	-0.1	0.1	-0.2
S	0.4		0.4	0.3	0.0	0.5
O	7.9		7.4	7.7	8.9	9.6
H ₂ to remov O, mg/g maf coal	9.8		9.2	9.7	11.1	12.0
H ₂ cons, mg/g maf coal			13.0	21.7	25.7	
Run No.	52	48	46	49	45	69

important factor is the concentration of the intermediate in the reaction media since reactions in hydrogen under these conditions fail to have the impact that CO-H₂O has on the reaction.

Oxygen recoveries appear quite uniform across the range of conditions that were evaluated falling around 60% for all the runs. This recognizes that since the oxygen was determined by difference, all the error associated with this measurement resides in this value. Assuming that hydrogen consumption is involved in the removal of oxygen as water, the required amount of consumption is around 9-11 mg/g maf coal, which is a major amount of the total hydrogen consumed in the reaction. This amount varies from about 50% at 800 psig to about 70% at 400 psig. This latter value reflects the lower overall amount of CO in the reaction media at the lower pressure. Whether this reflects a higher efficiency for oxygen removal isn't known at this time.

A corresponding run in water in the absence of CO gave mass, carbon, and oxygen recoveries that are very similar to the CO runs as shown in Run 69. Hydrogen in the product, however, is significantly lower than for the CO runs. Making the assumption that all the oxygen removed from the coal is removed as water, the hydrogen demand would be 12.0 mg/g maf coal. The decrease in hydrogen in the non-CO run was equivalent to 9 mg/g maf coal, which is 75% of the total required to comply with the constraints of this assumption. This provides support that one of the major reaction pathways for H₂ gas consumption is its involvement in the removal of oxygen from the coal, possibly through radical termination as the oxygen moiety is severed from the coal framework.

CO Pretreated Product from Black Thunder Coal

The results from treatment of Black Thunder coal in 300 and 800

psig CO at 300°C in the presence of sodium hydroxide for one hour are presented in Table 9. The recovery of water insoluble product in these two runs was between 94 and 96% with essentially complete carbon recovery. As with the Wyodak coal, the hydrogen in the product was higher at the higher CO pressure, namely, 98.2 versus 84.6 wt%. There was some difference in oxygen in the product in this case as compared to Wyodak where the oxygen removals were nearly constant. This difference impacts on the hypothetical hydrogen demand on removing the oxygen as water. This demand of 8.1 mg/g maf coal is actually greater than the hydrogen actually consumed in the reaction which may be partially responsible for the significantly greater loss of hydrogen from the total water insoluble product than at the higher pressure.

Liquefaction of Raw and Pretreated Coal

Results for the liquefaction of CO pretreated (800 psi CO, 6 ml. 0.33 M NaOH, 300 °C, 1 hr.) and raw coal with hydrogen and tetralin at 400 °C for 15, 30 and 60 min. are presented in Figure 3. The results showed that CO pretreatment consistently gave higher THF conversions than the raw coal. The conversion increased from 62 wt.%(maf) at 15 min. to 84 wt.% at 60 min. for the pretreated coal. The raw coal gave THF conversions of 55 wt.% at 15 min. and this increased to 73 wt.% at 60 min. It was noted that the improvement in reactivity in the 15 and 30 min. reactions for the pretreated coal reported mainly to the preasphaltene and asphaltene fractions. However, at longer reaction time (60 min) almost all of the improvement in conversion reported to the oil fraction. Although the pretreatment is successful in generating a more reactive material, the results suggests that the hydrogenation of the coal fragments and enhancement in oil production during liquefaction may be better accomplished with an added catalyst eg. molybdenum or iron.

Table 9. Recovery of Material from Black Thunder Coal

	300°C	
	2.4 grams Black Thunder Coal	
	6 ml water	
	4.4 wt% NaOH on maf coal	
CO psig	800	300
Products, wt% maf coal		
PA+A, wt% maf	27.0	17.6
IOM, wt% maf coal	69.0	76.5
Total Recovered	96.0	94.1
Recovery, wt %		
C	99.7	100.7
H	98.2	84.6
N	100.6	102.8
S	57.5	51.0
O	78.4	65.9
Removal, wt %		
C	0.2	-0.5
H	0.1	0.8
N	-	-
S	0.3	0.3
O	4.1	6.5
H ₂ to remove O, mg/g maf coal	5.1	8.1
H ₂ consumption, mg/g maf coal	19.0	
Run No.	J110	J111

Fig. 3 Hydrogenation of raw and pretreated coal at 400 °C

Fig. 4 Total hydrogen consumption from the reaction of raw and pretreated coal

Hydrogen Consumption during Liquefaction

The hydrogen consumption data from the liquefaction of the raw and pretreated coal is presented in Figure 4. The total hydrogen consumption is defined as the hydrogen consumed from both the gaseous phase and from the solvent (tetralin) in mg/g maf coal basis. It is interesting that the amount of hydrogen consumed by the pretreated coal is essentially constant through 15 min. to 60 min. reaction time (ca. 25 mg/g maf coal) even though there is ca. 22 wt% increase in conversion during this period. In contrast, the raw coal consumed ca. 20 mg/g maf coal at 15 min. and this increased to ca. 32 mg/g after 60 min. This observation is consistent with the coal conversion trend. In light of the chemical and physical data available to date, some of which we will be discussing in the following section, we concluded that the hydrogenation and reconstruction of the coal structure during the pretreatment process led to the enhancement in coal reactivity. In addition it is possible that some of the retrogressive reactions competing for hydrogen during liquefaction had been quenched in the pretreatment leading to a more effective utilization of the hydrogen source.

Optical Microscopy on Pretreated Coals (water-insoluble residues)
N₂ (800 psig), 300°C, 6 ml. 0.33 M NaOH - Treatment of the Wyodak coal with aqueous NaOH and N₂ at 300°C resulted in a partial disintegration/digestion of the vitrinite, particularly the particles in which the vitrinite was admixed with other macerals and minerals, which caused some of the coal particles to take-on a ragged, granular appearance. However, the microstructure of the large vitrinite particles (presumably formed from large woody tissues) remained essentially intact, and did not appear to have been severely affected by this treatment. In general, the pretreated sample adsorbed only a small amount of the cationic dye onto the polished surface, although this varied within the sample; whereas the larger vitrinite particles adsorbed very

little of the dye, the more disintegrated particles stained to a higher degree. This is in contrast to the vitrinite in the untreated coal, which adsorbed the dye to a much higher degree, suggesting that a substantial number of acidic oxygen functional groups, including carboxyl and some hydroxyl, have been removed from the coal during pretreatment. This is consistent with the elemental analysis data which showed ca. 35 %wt decrease in oxygen content upon pretreatment under this conditions.

The reflectance of the altered vitrinite increased from that of the feed, from 0.39% to 0.67%. Although it is unwise to present an interpretation based on these reflectance values alone, we have some recent evidence, which is discussed in the following section, which suggests that this increase in reflectance may be attributed in part to oxygen removal during alkali treatment at 300°C. In addition, under a non-hydrogen or hydrogen deficient atmosphere, regressive reactions such as re-polymerization and condensation becomes more prominent and has been cited as possible factors leading to an increase in the reflectance of a subbituminous rank vitrinite after liquefaction (Derbyshire et al., 1986; Davis et al., 1991). In addition to the oxygen loss stated earlier, the elemental analysis of this sample also showed much lower H/C ratio after pretreatment of the Wyodak coal (H/C=0.72 v. 0.85 for the untreated coal).

CO (400 psi), 300°C, 4 ml H₂O, NaOH - Replacing N₂ with 400 psi of CO to the pretreatment step resulted in extensive melting of the vitrinite, forming colloidal to spherical bodies of "vitroplast" (Mitchell et al., 1977) that in some places have agglomerated. Large pores, formed by the evolution of volatiles within the plastic vitrinite (at 300°C), occur throughout the sample. The cationic dye was adsorbed only to a small degree on the sample surface (visually almost undetectable), which suggests a pronounced removal of acidic oxygen groups from the coal, and is

in partial agreement with the chemical data, which show ca. 25% decrease in oxygen content. Reflectance of the altered vitrinite (%Ro = 0.58) is higher than that of the untreated coal, but lower than the nitrogen-treated coal. This variation in the vitrinite reflectance may be a function of the competing processes; the removal of oxygen and regressive reactions, both of which can cause an increase in reflectance and, hydrogenation reactions which may possibly lead to a lowering of the reflectance. Although physical factors such as increased porosity have been noted to lower the reflectance value, we observed that increasing the hydrogenation reactions by increasing the CO partial pressure in the pretreatment process (from 0-800 psig, see also next section) has progressively led to a lower reflectance value in the samples, given that the oxygen removal is similar in all cases. This variation in reflectance will be examined further in view of how the process conditions can affect the chemical and optical properties of the product generated.

CO (800 psig), 300°C, 6 ml H₂O, NaOH - When the CO partial pressure was increased to 800 psig, the coal structure completely melted/digested, and had apparently agglomerated to form large, coherent masses. Within these masses are abundant pores, ranging from submicron to tens of microns in size, that are often filled with a solid, dark-gray to black (under reflected incident white light), homogeneous bitumen-like material that was fluorescent under ultraviolet illumination. The data suggest that this "bitumen" is a more hydrogen-rich product than the surrounding altered vitrinite, which has a higher reflectance and no visible fluorescence under uv illumination. A similar material was also observed on the edges of some of the altered coal particles. The origin of the "bitumen", in the context of a specific maceral source, is unknown at this time. In contrast to the Wyodak feed the microstructure of the 800 psi CO-pretreated coal was not severely

affected when the polished surface was immersed in the KOH solution, and adsorbed the cationic dye to a much smaller degree.

The reflectance of the dominant material, which is presumed to be altered vitrinite, is 0.43%, a value only slightly higher than that of the feedstock (0.39%), and lower than the other pretreated samples. It is likely that the reflectance of this sample has been affected (lowered), in part, by its high porosity relative to the other pretreated samples; a higher porosity was observed microscopically and measured by mercury porosimetry technique. The reflectance of a relatively homogeneous area of the altered vitrinite, with few discernible pores, was approximately 0.50%, a value still lower than that of the other pretreated samples but higher than the parent coal. As with the other pretreated coals, the microscopical data are consistent with chemical analyses; the 800 psig CO pretreated coal exhibited a higher H/C ratio than the other two pretreated coals and the feedstock, and a significantly lower oxygen content than the feedstock.

LIQUEFACTION RESIDUES (THF-INSOLUBLES)

400°C, tetralin, 15 min., untreated v. pretreated coal - The THF-insoluble material from the hydrogenation of the untreated coal revealed a substantial amount of fine granular material and "ragged" coal particles, indicative of partial dissolution, although numerous large vitrinite particles are still present, with evidence of partial melting (e.g. slightly rounded edges on some particles) and total melting (i.e. spherical "vitroplast"). According to Derbyshire et al. (1986), the development of plasticity during liquefaction is indicative of dominant thermal reactions. In contrast, pretreatment of the coal with 800 psi CO, 6 ml H₂O, and NaOH at 300°C followed by liquefaction resulted in a higher degree of coal dissolution and, presumably, hydrogenation as evidenced by a much larger proportion of "ragged" coal particles and micron to sub-micron size granular

material. In addition, fewer large vitrinite particles remain in the pretreated liquefaction residue. In both samples, inertinite macerals were present and appeared to be unaffected by the processing conditions, whereas the liptinite macerals were much more difficult to identify and were visibly altered by the treatment.

400°C, tetralin, 60 min., raw v. pretreated coal - The microscopic features of the THF- insoluble material generated after 60 min. reaction time is similar to their 15 min. equivalents, although the effects were more severe. The residue from the untreated coal reaction comprised a large amount of granular material, in addition to vitrinite particles that have undergone various stages of melting, although many particles retained somewhat angular edges. As with the 15 min. sample, partial melting was observed and may suggest that thermal reactions were important. In contrast, CO pretreatment in combination with liquefaction produced a THF-insoluble material that comprised almost entirely granular residue with few recognizable altered vitrinite particles, suggesting a higher degree of coal dissolution/hydrogenation.

The microscopic observations of the 15 min. and 60 min. liquefaction residues are consistent with the coal conversion data discussed earlier, i.e., for each of the liquefaction conditions, CO pretreatment resulted in a higher degree of THF conversion compared to liquefaction of non-pretreated coal.

TASK 2.1.2.1 PRETREATMENT / DEWAXING - (CONSOL)

A series of ketone (acetone) dewaxing tests was carried out at temperatures from 0°C to -35°C. The results of these tests, Table 10, indicated that maximum solvent quality, defined as the microautoclave conversion to THF solubles of an Indiana V Old Ben

#1 mine coal (750°F, 30 min, 1.5 solvent/coal ratio) could be attained by dewaxing the Wilsonville V-1074 distillate at -5°C and below. Although oil dewaxed at -5°C was essentially free of n-paraffins, dewaxing at -35°C resulted in a product with a significantly higher content of aromatic protons than the -5°C product (23.5% vs 22.0%). This increased aromaticity, however, came at the expense of dewaxed product yield (55 % v 80%). Based on the results of these preliminary trials, it was decided to produce two batches of dewaxed oil for Sandia to use in their hydrogenation experiments. The first batch was dewaxed at -35°C and the second batch was dewaxed at -5°C.

The V-1074 distillate was dewaxed according to the following procedure. V-1074 oil (150 g) was mixed with 450 mL of HPLC grade acetone in a beaker. The mixture was gradually cooled, with stirring, to the desired temperature in a bath of dry ice and acetone. At the desired temperature, the precipitated wax was suction-filtered and washed with cold acetone. The filter cake was then dissolved and washed through the filter into a separate container with THF which was at room temperature or higher (warmed on a hot plate). The wax and dewaxed oil fractions were recovered by rotary evaporation, followed by drying overnight in a vacuum oven at about 90°C. Yields of each fraction and the total recovered material were calculated from the weights of feed oil and recovered fractions, Tables 11 and 12. For Runs 1 through 6 of the -35°C dewaxing tests, two dewaxing experiments were made simultaneously. The dewaxed products from the two runs were combined during filtration, and yields were calculated on the combined material, Table 11. Part of the wax product was accidentally lost during the first -35°C run; therefore, it was not possible to calculate an overall material balance. However, in runs 2 through 7, product recovery was 99.9 wt%.

TABLE 10
RESULTS OF ACETONE DEWAXING EXPERIMENTS

<u>Temp, °C</u>	<u>Oil Yield, wt %</u>	<u>Aromatics^a, %</u>	<u>Paraffinics^b, %</u>	<u>Solvent Quality^c, %</u>
Feed	---	14.9	46.9	62.4
0	90.5	17.3	41.0	71.2
-5	80.4	20.3	34.8	81.4
-10	79.1	20.1	34.0	82.9
-20	70.9	23.0	28.9	84.1
-35	55.7	26.3	26.6	84.7

a - Condensed aromatic protons + uncondensed aromatic protons

b - Alkyl beta + gamma protons

c - % MAF conversion of Indiana V coal to THF solubles at 750°F, 30 min, 1.5 solvent/coal ratio.

The lower dewaxed product yield and correspondingly higher wax yield in Run 7, Table 11, resulted from the use of a smaller, more easily chilled filtration funnel. Apparently, the dewaxed samples were re-warmed during filtration in the larger funnel, resulting in partial dissolution of the precipitated wax. This is also reflected in the proton distributions of the dewaxed products from the individual runs, Table 13. The dewaxed oil from Run 7 contained a slightly higher proportion of aromatic protons, 24.1% vs 23.3% than the other six runs. Similarly, the wax from Run 7 was more aromatic than the wax separated in the other runs, reflecting a higher content of trapped oil. The yields, proton distributions and phenolic -OH contents of the V-1074 feed and the composite -35°C dewaxed product oil and wax are given in Table 14. The composition of the composite product is very similar to the average composition calculated from the individual runs in Table 13. The solvent quality of the

TABLE 11
YIELDS FROM -35°C DEWAXING PRODUCTION RUNS

Run No.	Wt, g			Yield, Wt%		Recovery ^a , %
	Feed	Dewaxed Oil	Wax	Dewaxed Oil	Wax	
1	304.1	204.8	10.4 ^b	67.3	3.4 ^b	--- ^b
2	301.2	199.0	101.1	66.1	33.6	99.6
3	301.0	199.8	101.8	66.4	33.8	100.2
4	301.3	193.1	107.7	64.1	35.8	99.8
5	303.3	199.0	104.6	65.6	34.5	100.1
6	300.6	200.6	99.6	66.7	33.1	98.9
7	150.2	87.0	62.8	57.9	41.8	99.7
Total	1961.8	1283.2	--- ^b	65.4	--- ^b	--- ^b
Without Run 1	1657.6	1078.5	577.5	65.1	34.8	99.9

a = Recovery does not include insolubles which were not determined in these runs.

b = Wax from Run 1 was not weighed prior to blending wax fractions.

TABLE 12
YIELDS FROM -5°C DEWAXING PRODUCTION RUNS

Run No.	wt, g				Yield, wt %		Recovery, %
	<u>Feed</u>	<u>Dewaxed Oil</u>	<u>Wax</u>	<u>Insols.</u>	<u>Dewaxed Oil</u>	<u>Wax</u>	
1	304.16	235.80	67.75	0.24	77.53	22.27	99.88
2	300.54	224.61	74.81	0.25	74.74	24.89	99.71
3	301.74	227.49	73.52	0.20	75.39	24.37	99.82
4	302.66	227.31	74.60	0.19	75.10	24.65	99.82
5	304.09	233.72	69.46	0.26	76.86	22.84	99.79
6	303.95	226.89	76.29	0.24	74.65	25.10	99.83
7	303.28	216.99	85.37	0.20	71.55	28.15	99.76
8	301.51	224.72	75.87	0.16	74.53	25.16	99.75
Total	2421.93	1817.53	597.67	1.74	75.04	24.68	99.79

composite dewaxed oil was 84.7% vs 62.4% for the V-1074 distillate feed, Table 14.

Approximately 2400 g of V-1074 heavy distillate from Wilsonville Run 262 was dewaxed at -5°C according to the same procedure used for the -5°C dewaxing experiments described above. The yields from the eight individual dewaxing runs are given in Table 12. The overall recovery of dewaxed oil and wax from these experiments was 99.8 wt %. The overall yield of dewaxed oil at -5°C was ~75 wt % compared with ~65 wt % at -35°C. Over 1800 g of -5°C dewaxed oil was produced in these tests.

Proton distributions in the dewaxed oil and wax fractions produced during the eight -5°C dewaxing runs are shown in Table 15. The proton distributions and phenolic -OH contents of the composited dewaxed oil and wax samples are given in Table 16. The dewaxed oil produced at -5°C contains a lower concentration of aromatic protons (combined condensed and uncondensed aromatic protons) and a correspondingly higher concentration of paraffinic protons (alkyl beta + gamma protons) than the oil dewaxed at -35°C. The -5°C wax was less aromatic and had a higher paraffinic proton content than the -35°C wax. The solvent quality of the -5°C dewaxed oil, 81.4%, was slightly lower than that of the -35°C dewaxed oil, 84.7% but significantly higher than that of the V-1074 feed oil, 62.4%. The yields of dewaxed oil in both the -5°C and the -35°C production dewaxings (75 wt % and 65 wt %, respectively) were significantly different than anticipated from the preliminary trials (80 wt % and 56 wt %, respectively), Table 10. The higher oil yield at -35°C is attributable to the difficulty in cooling the larger filtration funnel used in the -35°C production runs discussed earlier. The same equipment was used in both the preliminary and production -5°C dewaxings and so there is no obvious reason for the observed 5% lower dewaxed oil yield in the production runs. The observed trend of lower

TABLE 13

¹H-NMR ANALYSES OF PRODUCTS FROM -35°C DEMAXING PRODUCTION RUNS
WITH WILSONVILLE RUN 262 V-1074 OIL

Run No.	Proton Distribution of De-Waxed Product, %						
	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>
1	16.8	5.0	20.2	10.1	17.8	19.2	10.9
2	17.7	5.8	19.8	10.2	17.2	17.8	11.4
3	17.7	6.4	19.9	10.1	16.7	17.6	11.6
4	17.4	5.7	20.2	10.3	17.7	18.1	10.7
5	17.4	5.8	19.7	10.1	17.0	18.2	11.7
6	17.2	7.1	18.6	10.5	16.8	18.1	11.6
7	<u>18.1</u>	<u>6.3</u>	<u>19.7</u>	<u>10.5</u>	<u>16.4</u>	<u>17.0</u>	<u>12.0</u>
Avg.	17.5	6.0	19.7	10.3	17.1	18.0	11.4

Run No.	Proton Distribution of Waxes, %						
	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>
1	2.1	1.3	3.2	3.0	13.9	55.0	21.4
2	2.5	1.2	4.5	3.6	13.1	55.8	19.4
3	2.5	1.7	6.8	4.7	15.4	52.9	16.1
4	3.1	1.3	7.0	4.7	15.9	53.0	15.1
5	2.5	1.9	6.3	4.4	13.3	54.1	17.5
6	2.7	1.5	6.6	4.9	15.4	54.2	14.7
7	<u>4.4</u>	<u>1.8</u>	<u>7.0</u>	<u>5.1</u>	<u>14.8</u>	<u>51.0</u>	<u>16.0</u>
Avg.	2.8	1.5	5.9	4.3	14.5	53.7	17.2

TABLE 14
FEED AND COMPOSITED PRODUCT ANALYSES FROM -35°C DEWAXING RUNS
WITH WILSONVILLE RUN 262 V-1074 OIL

	<u>Feed</u>	<u>Dewaxed Oil</u>	<u>Max</u>
<u>¹H-NMR, %</u>			
Condensed Aromatics	11.3	17.3	2.3
Uncondensed Aromatics	3.6	6.2	1.1
Cyclic Alpha	14.7	20.0	4.6
Alkyl Alpha	7.6	10.3	3.8
Cyclic Beta	15.8	17.1	13.3
Alkyl Beta	34.6	17.9	55.7
Gamma	12.3	11.2	19.1
<u>Phenolic -OH</u>			
Concentration, meq/g	0.44	0.61	<0.10
ν , cm^{-1}	3306	3304	3325
Solvent Quality ^a , %	62.4	84.7	-

a = % MAF conversion of Indiana V coal to THF solubles at 750°F, 30 min, 1.5 solvent/coal ratio.

TABLE 15

¹H-NMR ANALYSES OF PRODUCTS FROM -5°C DEWAXING PRODUCTION RUNS
WITH WILSONVILLE RUN 262 V-1074 OIL

Proton Distribution of De-Waxed Product, %							
<u>Run No.</u>	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>
1	14.8	5.2	18.3	9.3	16.7	22.7	13.1
2	16.1	4.6	19.9	9.8	18.3	20.1	11.2
3	16.1	5.3	19.0	9.5	17.3	20.3	12.5
4	14.9	6.8	16.6	9.7	16.4	21.6	14.1
5	14.4	6.3	16.3	9.7	16.2	21.9	15.2
6	15.6	6.6	17.7	9.8	17.3	20.1	12.8
7	15.1	7.2	16.1	9.7	16.7	20.5	14.7
8	<u>16.3</u>	<u>5.5</u>	<u>18.5</u>	<u>9.4</u>	<u>17.8</u>	<u>19.8</u>	<u>12.6</u>
Avg.	15.4	5.9	17.8	9.6	17.1	20.9	13.3

Proton Distribution of Waxes, %							
<u>Run No.</u>	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>
1	1.0	0.6	4.2	3.8	15.4	58.8	16.2
2	1.3	1.2	5.4	4.2	15.2	57.1	15.7
3	1.3	0.6	4.1	3.5	13.4	60.4	16.6
4	1.3	1.0	2.4	2.8	12.5	60.4	19.6
5	1.3	1.0	1.6	2.6	10.6	63.5	19.5
6	1.4	1.4	6.0	4.7	17.1	54.1	15.3
7	2.0	0.7	2.9	2.6	11.0	61.6	19.2
8	<u>1.3</u>	<u>0.7</u>	<u>2.7</u>	<u>3.3</u>	<u>11.6</u>	<u>62.8</u>	<u>17.5</u>
Avg.	1.4	0.9	3.7	3.4	13.4	59.8	17.5

TABLE 16
FEED AND COMPOSITED PRODUCT ANALYSES FROM -5°C DEWAXING RUNS
WITH WILSONVILLE RUN 262 V-1074 OIL

	<u>Feed</u>	<u>Dewaxed Oil</u>	<u>Max</u>
<u>¹H-NMR %</u>			
Condensed Aromatics	11.3	14.3	1.2
Uncondensed Aromatics	3.6	7.7	0.6
Cyclic Alpha	14.7	15.9	3.1
Alkyl Alpha	7.6	10.2	3.3
Cyclic Beta	15.8	16.3	12.6
Alkyl Beta	34.6	21.7	61.1
Gamma	12.3	14.0	18.2
<u>Phenolic -OH</u>			
Concentration meq/g	0.44	0.56	<0.10
ν cm ⁻¹	3306	3304	3339
Solvent Quality ^a , %	62.4	81.4	---

a = % MAF conversion of Indiana V coal to THF solubles at 750°F, 30 min, 1.5 solvent/coal ratio.

dewaxed oil yield resulting in less pure wax is consistent with that found in the parametric study of the effects of dewaxing temperature on dewaxed oil and wax.

Preliminary assessment by LDP Associates suggests that potential sales of a refined wax by-product may pay for the cost of dewaxing recycle solvent in a liquefaction plant. Therefore, experiments were initiated to clean-up the slack wax produced during dewaxing and to determine the properties of the cleaned wax.

Attempts were made to clean the wax produced during dewaxing by repeating the solvent dewaxing step with the wax produced in the initial dewaxing step as feed. Although the wax produced in this second dewaxing step contained a significantly lower concentration of aromatic protons, it retained its grey color and turned dark brown upon melting in air.

Relatively clean, nearly colorless wax was obtained by dissolving the slack wax in n-hexane and passing the solution through an activated alumina column. The results of these wax clean-up experiments are shown in Table 17. The cleaned -35°C wax still contains measurable aromatic protons, has a slightly yellow tinge and retains a slight odor. The cleaned -5°C wax is nearly colorless and odorless and contains no measurable aromatic protons. As shown in Table 17, the proton distribution of the -5°C wax is similar to that of the commercial canning and candle wax, Paraseal. The residual oils removed from both the -35°C and -5°C slack waxes on the alumina column had compositions that were similar to the dewaxed oils produced at each temperature, Table 17.

Even though wax clean-up via alumina contacting may not be commercially interesting, these encouraging results suggest that

TABLE 17

**PROTON DISTRIBUTIONS OF PRODUCTS FROM DEWAXING WILSONVILLE V-1074
HEAVY DISTILLATE AT 35°C AND AT -5°C**

<u>Material</u>	<u>Proton Distribution of Waxes %</u>						
	<u>Cond Arom</u>	<u>Uncond Arom</u>	<u>Cyclic Alpha</u>	<u>Alkyl Alpha</u>	<u>Cyclic Beta</u>	<u>Alkyl Beta</u>	<u>Gamma</u>
V-1074 Oil	11.3	3.6	14.7	7.6	15.8	34.6	12.3
<u>-35°C</u>							
Dewaxed Oil	17.3	6.2	20.0	10.3	17.1	17.9	11.2
Slack Wax	2.3	1.1	4.6	3.8	13.3	55.7	19.1
Clean Wax	1.4	1.7	5.0	4.6	15.8	53.7	17.8
Residual Oil	16.8	5.6	18.8	9.8	15.1	22.5	11.3
<u>-5°C</u>							
Dewaxed Oil	14.3	7.7	15.9	10.2	16.3	21.7	14.0
Slack Wax	1.2	0.6	3.1	3.3	12.6	61.1	18.2
Clean Wax	0.0	0.0	1.3	2.8	12.3	66.9	16.6
Residual Oil	13.2	3.4	18.7	8.8	18.6	27.5	9.8
Paraseal™	0.0	0.0	0.8	0.7	5.8	79.0	13.7

a salable coal-derived product wax product should be attainable. Further exploration of wax clean-up methods, including dewaxing/de-oiling and procedures used in commercial petroleum dewaxing, is planned.

TASK 2.1.2.2 - PRETREATMENT / AGGLOMERATION - (CONSOL)

Fifteen agglomeration runs were made with Black Thunder coal and -10 to 25 wt % (MF coal basis) No. 6 fuel oil. Organic recoveries (oil + coal) were 99.2% or better. The results are given in Table 18.

Four runs made in deionized water at ambient pH gave ash rejections of 9 to 13% and ash balances of 90 to 96%. Run conditions were: 1) moderate oil dosage (ca. 25 wt %), 2) low oil dosage (ca. 15 wt %), 3) low oil dosage plus cresylic acid promoter, and 4) low oil dosage at 90 to 95°C (without promoter).

Lowering the pH resulted in significantly higher ash rejections. Two runs were made at pH 2, one using HCl, the other using H₂SO₄, (both unpromoted). These runs yielded ash rejections of 36 and 41 wt %, 61 and 66 wt % ash balances (reject water not included), and high organic recoveries (~99.8%). There was no additional improvement in ash rejection at pH 1. Additional runs were made at pHs of 3 and 4 to better characterize the behavior of the low pH system. Between pH 2 and pH 5.6, ash rejection is linear with pH (Figure 5). The ash balance is linear with pH from pH 1 to pH 8 (Figure 5). Much of the increased ash rejection observed at low pH appears to be due to dissolution of mineral matter. This is reflected in the lower ash balances seen for the low pH runs.

Agglomeration at pHs above natural (i.e., pH 5.6) resulted in the creation of very fine, suspended particulate matter. However, ash rejection at the higher pHs was about the same as in

TABLE 18
AGGLOMERATION CONDITIONS AND RESULTS
No. 6 Fuel Oil and Black Thunder Coal

<u>Run</u>	<u>Oil Dosage, wt % MF Coal</u>	<u>Temp., °C</u>	<u>pH</u>	<u>pH Agent</u>	<u>Other Additive</u>	<u>Organic Recovery</u>	<u>Ash Rejection</u>	<u>Ash Balance</u>
A1	25.6	54	5.6*	None	None	99.9	11.7	95.9
A2	13.1	54	5.6*	None	None	99.9	9.4	93.4
A3	14.1**	54	5.6*	None	CA	99.5	12.8	92.2
A4	14.4	54	2.0	HCl	None	99.8	38.3	65.8
A5	17.6	95	5.6*	None	None	99.9	13.3	89.8
A6	14.6	54	2.0	H ₂ SO ₄	None	99.9	41.2	61.0
A7	14.4	54	4.0	H ₂ SO ₄	None	99.8	21.8	80.8
A8	14.1	54	3.0	H ₂ SO ₄	None	99.7	31.6	71.2
A9	14.6	54	1.0	H ₂ SO ₄	None	99.9	39.8	61.8
A10	14.4	54	1.0	H ₂ SO ₄	None	99.9	40.2	61.6
A11	51.5***	54	10.0	NaOH	CA	No Agglomeration		
A12	12.9	54	2.5	H ₂ SO ₄	None	99.2	42.2	62.2
A13	14.2	54	8.0	NaOH	None	99.3	14.3	100.2
A14	13.0	54	7.0	NaOH	None	99.6	14.4	94.1
A15	14.4	54	6.0	NaOH	None	99.9	15.7	89.3

CA = Cresylic Acid

*Natural slurry pH of about 5.6 was not measured in every run.

**1.7g cresylic acid added prior to oil.

***4mL cresylic acid added after oil.

deionized water, 14 to 16 wt %. The run at pH 10 failed to result in agglomeration despite the addition of a considerable amount of oil (>50 wt % MF coal).

A 300 mL Parr autoclave is being adapted to perform agglomeration experiments at elevated temperatures (up to 250°C) and elevated pressure. Equipment scale-up calculations were made to select equipment dimensions, stirring speed, and reactor charge, within reactor safety constraints.

Oil agglomeration experiments with Black Thunder coal will be resumed. Coal liquids will be used to verify the performance achieved with No. 6 fuel oil.

CO pretreated coal and dispersed catalyst will be needed next quarter for timely completion of this task.

OIL AGGLOMERATION EXPERIMENTS

FUEL OIL NO. 6, BLACK THUNDER COAL

Figure 5 Agglomeration Results with No. 6 Fuel Oil and Black Thunder Coal.

SUBTASK 2.1.3 SOLVENT PRETREATMENT (Sandia)

Background

Pretreatment work at Sandia consists of solvent hydrogenation using the water-gas shift reaction. The aim of the work is to reduce reaction temperature and pressure for donor solvent hydrogenation and to remove the requirement for purified hydrogen. The use of water and CO mixtures involves two classes of coupled catalytic reactions:

Water-gas shift:

Hydrogenation of donor species, for example:

Hydrogenation of the donor solvent species is illustrated here by the hydrogenation of pyrene, a donor solvent precursor.

Equilibrium concentrations of hydrogen and $H_2\text{Py}$ are greatly increased at lower temperatures due to the greater K_p for each of the above reactions. The ability to lower the coupled reaction temperature allows the total system pressure to be reduced and still achieve adequate solvent hydrogenation. Catalyst testing at Sandia involves hydrogenation of a synthetic solvent containing 9.5 wt% aromatic compounds (phenanthrene, fluoranthene, pyrene) in hexadecane at temperatures near 300°C.

Experimental

The microflow reactor used in these tests consists of a fixed bed tubular reactor supported inside of a thermostatically controlled oven. Nickel molybdenum catalysts were presulfided in situ

before use and the platinum hydrous titanium oxide (HTO) catalyst was first air calcined and then prereduced in situ with hydrogen. After pretreatment the synthesis gas and steam were fed in equimolar amounts ($\text{CO}:\text{H}_2:\text{H}_2\text{O} = 1:1:1$) followed by feeding the solvent at various space velocities concurrently with the gas. All reactants were fed downward over the catalyst bed, and periodic liquid and gas samples were taken during the reaction. In all cases the system pressure was maintained at 1000 psig.

Nickel Molybdenum Thin-Film HTO Catalyst Testing

Previous tests with thin-film HTO catalysts have shown high solvent hydrogenation activity on an active metals basis. The thin-film catalyst (described in the Quarterly Report for April to June 1992) was supported on a large-pore silica bead. This quarter we have coated the thin-film HTO on 1/32" alumina extrudates to achieve more favorable reactor packing densities. The catalyst was used as extrudate and mixed with a low surface area alpha alumina as a diluent in the 0.5" O.D. reactor tube. The catalyst bed was then sulfided at 390°C for two hours with a 9% H_2S in hydrogen mixture. Weight Hourly Space Velocity (WHSV) effects were measured at 0.87 hr^{-1} and 0.43 hr^{-1} on an aromatic feed basis. Comparative results from this catalyst and previous NiMo catalysts are shown in Table 19.

This catalyst showed high activity for both the water-gas shift reaction and the solvent hydrogenation reaction. In addition this catalyst has 7.2% molybdenum compared to 12.4% molybdenum for the Shell 324 catalyst. The improved activity on an active metal basis is most likely due to increased metal dispersion using the thin-film coating technology. Thin-film coating technology allows for increased flexibility in catalyst metal loading and dispersion.

Table 19

Catalyst	Temp (°C)	WHSV hr ⁻¹	% CO conv	% Hydrogenated		
				PHEN	FLUOR	PYRENE
Thin-film on Alumina	275	0.43	93	44	96	62
	275	0.87	97	22	81	43
Thin-film on silica	275	0.44	95	43	85	55
	275	0.89	95	25	65	36
NiMo/alumina (Shell 324)	275	0.44	93	48	96	68
	275	0.89	95	27	84	54
. Data from May 1992 monthly report. System pressure= 1000 psig						

The alumina supported NiMo HTO is a candidate for testing with dewaxed solvents and coker overhead. Longer term tests with these solvents will be undertaken in the next quarter.

Platinum Catalyst Testing

Previous tests with a platinum HTO catalyst showed catalyst deactivation at 275°C. Small amounts of sulfur in the synthetic solvent were implicated in the deactivation. For this reason, a catalyst stability test was performed at 315°C to test for deactivation due to sulfur at a higher temperature. The catalyst was first calcined at 500°C in air, pelletized and fractionated into -30+40 mesh particle size. The catalyst was then packed in the 0.25" O.D. reactor tube and reduced at 200°C with hydrogen. Weight Hourly Space Velocity (WHSV) was maintained at 0.85 hr⁻¹ on an aromatic feed basis for over six hours. Results from the "one-day" catalyst stability test are shown in Table 20.

Table 20

Elapsed Time (min)	Temp (°C)	% CO Conv	% Hydrogenated		
			PHEN	FLUOR	PYRENE
104	315	NA	63	93	74
200	315	95	61	92	71
287	315	95	61	93	72
366	315	96	60	93	71
Reactor system pressure = 1000 psig					

This catalyst showed high activity for both the water-gas shift reaction and the solvent hydrogenation reaction. The extent of solvent hydrogenation for all three aromatic compounds was higher than the most active nickel molybdenum catalyst at a similar WHSV, yet different temperature (Shell 324M, Temperature=300°C, WHSV=0.89 hr⁻¹, % hydrogenated: PHEN=45, FLUOR=82, PYRENE=49). In addition, the catalyst did not show any measurable deactivation, indicating that sulfur poisoning at these conditions is not problematic. The platinum catalyst also removed much of the sulfur in the feed. The feed had over 250 ppm of sulfur and the product had less than 30 ppm of sulfur. An odor of H₂S was present throughout the experiment, indicating that the sulfur was at least partially removed by hydrodesulfurization. Sulfur adsorption onto the catalyst will be measured at different bed depths using a sulfur selective test.

This catalyst too, is a candidate for longer term tests with coal liquid solvents.

Testing with V1074 Feed

The previous (NiMo thin-film HTO and Pt HTO) experiments used a mixture of three aromatic compounds in hexadecane as a synthetic solvent. Tests in late September used heavy distillate (V1074) solvent in the microflow reactor. This set of tests was performed with Shell 324M as the catalyst to evaluate the baseline response of heavy distillate to low severity hydrogenation using the water-gas shift reaction.

The catalyst was used as extrudate and packed in the 0.5" O.D. reactor tube without diluent. The catalyst bed was then sulfided at 390°C for four hours with a 9% H₂S in hydrogen mixture. Again equimolar amounts of gaseous reactants (steam:CO:H₂ = 1:1:1) were fed with concurrently flowing solvent (V1074). Weight Hourly Space Velocity (WHSV) effects were tested from 0.3 hr⁻¹ to 0.9 hr⁻¹. The reactor system pressure was kept at 1000 psig and temperature was varied between 300°C and 325°C. Since the V1074 solvent is a semisolid at room temperature it was necessary to heat the feed reservoir and to heat-trace feed lines to keep the waxy V1074 from freezing and stopping flow. Several modifications were made to the reactor to ensure smooth operations. Analysis of the product from these runs is underway.

SUBTASK 2.2.3 MODIFIED REACTOR CONCEPTS (Sandia)

Work on this subtask involved coal liquefaction experiments conducted at autogenic pressures and are summarized in Table 6.

TASK 2.3.1 IRON BASED DISPERSED CATALYSTS (UK/CAER)

Catalytic Activity of Superfine Iron Oxide

Sulfided iron oxide particles in the size range 50-80 nm, that were prepared by high temperature thermal oxidation, have been

reported to show high activity for coal liquefaction.¹³ The catalytic effect has been attributed to the high surface area and small particle size of the pyrrhotite formed upon sulfiding in the presence of coal where the pyrrhotite particles retain the small particle size of the oxide precursor.¹⁴ In this program extensive work has been conducted on a sample of superfine iron oxide (SFIO) was obtained from Mach I, Inc., King of Prussia, Pennsylvania. That material is comprised of nanometer size particles and has a very low packing density and a very high BET surface area of 318 m²/g. which is consistent with nanometer size particles. Unlike the results of the French group (See Reference 7), current data suggest that SFIO may under sulfiding conditions give rise to larger particles providing reduced surface area liquefaction catalysts under reaction conditions.¹⁵ In the handling of these materials samples were stored under nitrogen in order to protect against the adsorption of moisture which promote particle growth,

An experimental approach was adopted that would maximize the amount of information gathered in a given series of experiments and provide a data set from which to draw valid comparisons. A full 2^k factorial experimental design was developed following the method described by Box, Hunter, and Hunter.¹⁶ The main effects and interactions of reaction temperature, catalyst concentration, and sulfur concentration were determined separately for THF conversion, hydrogen consumption, CO+CO₂, hydrocarbon gas, oil and PA+A yields.

In the experimental design each independent variable is tested at both a high and a low value. The main objective of this design is to screen a large number of factors to determine which have significant impact on the dependent variables to warrant further study. From a total of 2^k experiments, used to test k factors, all main effects plus both two-way and three-way interactions of

the independent variables, can be determined. The data can be used to generate a simple linear model without any estimate of curvature. A series of mid-point data, which are independent of the model coefficient calculations, are used to provide a measure of experimental error and test the model for curvature. Failure to provide a good estimate of the centerpoint indicates that there is significant curvature and additional experimental work is required to quantify this curvature. The experimental design used to evaluate the SFIO involved 2^3 experiments and 3 replicated centerpoint experiments for a total of 11 runs.

Because of the replication of the differences in the low-high experimental values and in the absence of any two-way interactions, the coefficients are known with the precision of a four-fold replicated difference, which lends credibility to the coefficients that are predicted. This technique is particularly applicable to complex reaction systems, such as coal liquefaction.

The output of this method for a three factor design is an equation of the form:

$$Z = \beta_0 + \beta_a(A) + \beta_b(B) + \beta_c(C) + \beta_{ab}(A*B) + \beta_{ac}(A*C) + \beta_{bc}(B*C) + \beta_{abc}(A*B*C)$$

where the first coefficient, β_0 , is the intercept, the second three coefficients ($\beta_a, \beta_b, \beta_c$) are main effects, the next three ($\beta_{ab}, \beta_{ac}, \beta_{bc}$) are two-way interactions, and β_{abc} is the three-way interaction. Z represents one of the five dependent variables under consideration.

An analysis of variance is used to determine the value of these coefficients, and further statistical analysis shows which coefficients are likely to be insignificant, and therefore can be

deleted from the linear model. If all coefficients are retained, the model is unique for the data set in which all variation is accounted. However, it is more useful to discard the least significant coefficient and to use the resulting equation to gain insight into the influence of the principal factors.

This streamlining of the model allows two important types of coefficients to be calculated. The first is a correlation coefficient for the linear model, R squared, which indicates how much of the variation in the effects has been accounted for by the coefficients selected for the model. The second is a Student's t parameter for the selected coefficients. This allows a quantitative test of the probability that the coefficient is not equal to zero.

The run conditions chosen for the study and the results from these runs are shown in Table 21 for the three independent variables. Because of the high concentration of metals in the composite solvent, iron oxide concentrations were selected which could have a clearly discernible effect on coal liquefaction, ranging from 1 to 4 wt% Fe on as-fed coal. Added sulfur was selected to explore a wide range of S/Fe atomic ratios, with the centerpoint at 2:1. The reaction temperatures were 390 and 440°C, centered at 415°C.

Impact of Reaction Variables on Liquefaction with SFIO - The R squared values for each dependent variable that was selected indicate the degree of fit by the linear model coefficients as shown in Table 22. Values for the coefficients for the simple linear model is summarized in Table 23. The significance of each coefficient, as a probability of that coefficient not being equal to zero, is shown in parentheses.

Table 21. Results from 2³ Factorial Evaluation of Superfine Iron Oxide (SFIO)^a

Temperature, °C	390	390	390	390	390	415	415	415	440	440	440	440
Added Fe, wt%	4	1	1	1	4	2.5	2.5	2.5	4	4	1	1
coal												
Added S, wt% Coal	1.4	1.4	4.3	4.3	4.3	2.9	2.9	2.9	1.4	4.3	1.4	4.3
S/Added Fe m/m	0.6	2.5	7.5	1.9	2.0	2.1	2.1	2.1	0.7	1.9	2.7	7.6
Products, wt% MAF												
coal												
HC Gases	1.3	1.1	2.0	2.1	2.8	2.8	2.8	2.8	5.8	5.5	4.6	5.6
CO + CO ₂	4.4	4.2	4.1	4.2	4.7	4.7	4.9	4.9	6.5	5.4	5.9	5.7
Oils	52.7	42.2	40.0	44.0	53.0	56.4	67.9	79.4	79.4	54.4	82.8	73.3
PA + A	54.2	49.7	52.1	53.1	46.7	47.5	35.8	25.4	25.4	47.5	16.3	23.7
IOM	-12.6	2.8	1.8	-3.4	-7.2	-11.4	-11.4	-11.4	-17.1	-12.8	-9.6	-8.3
THF Conv	112.6	97.2	98.2	103.4	107.2	111.4	111.4	111.4	117.1	112.8	109.6	108.3
mg H ₂ /g coal	52.1	49.1	50.8	52.5	61.5	61.0	57.4	74.5	74.5	72.5	62.4	68.1
Run Number	175-2	175-1	190-2	175-3	174-2	190-1	190-3	196-1	192-1	192-1	174-3	174-1

a. 60 minute reaction time, 3 g. Black Thunder coal, 5.4 g. Wilsonville composite solvent, 1000 psig H₂ cold.

Table 22. Dependent Variables Evaluated

<u>Effect</u>	<u>Units</u>	<u>R Squared</u>
THF Conv	THF conversion, wt% maf coal	0.926
mg H ₂	H ₂ consumption, mg/g maf coal	0.973
HC Gas	Hydrocarbon gas yield, wt% maf coal	0.969
CO+CO ₂	CO and CO ₂ gas yield, wt% maf coal	0.944
TGas	Total gas yield, wt% maf coal	0.961
Oils	wt% maf coal	0.880
PA+A	wt% maf coal	0.922

Predicted versus Model Values - The calculated or predicted values from the model coefficients as shown in Table 23 were determined for each of the dependent values. Predicted versus observed THF conversion values are shown in Table 24. The R² value in Table 22 plus the probabilities shown in Table 23 indicate a good fit of the model to the observed values. From the coefficients in Table 23, temperature and catalyst concentration appear to equally affect THF conversion while sulfur has a slight negative effect. The catalyst sensitivity is a reflection of the known catalysis of iron in promoting coal dissolution. The negative effect of sulfur on THF conversion, and on the oil yield that will be discussed below, was unexpected based upon the results of Das Gupta, et al.,¹⁷ on the liquefaction of an iron deficient Indian coal. They found, through a non-linear parameter estimation procedure, that adding sulfur up to a S/Fe atomic ratio of 8 improved conversion. In the experiments reported here adding sulfur at a S/Fe atomic ratio between 0.6 to 7.4 was detrimental. This effect could be related to adverse side reactions caused by the presence of excess sulfur.

Table 23. Summary of Estimated Coefficients^a

	Inter- cept	T ^b Coeff (prob)	X ^b Coeff	S ^b Coeff	TxX ^b Coeff	TxS ^b Coeff	XxS ^b Coeff
THF Conv	107.40	4.54 (99.7)	4.08 (99.5)	-1.72 (90.3)			-1.62 (88.7)
mg H ₂	60.28	9.12 (99.9)	2.66 (98.6)		1.48 (90.3)		-1.13 (81.9)
HC Gas	3.50	1.86 (99.9)		0.29 (93.9)			
CO+CO ₂	5.06	0.84 (99.9)		-0.20 (95.4)			
TGas	8.57	2.71 (99.9)					
Oils	58.61	13.87 (99.9)		-5.67 (94.6)	-4.60 (90.0)		
PA+A	40.23	-12.03 (99.5)	4.80 (91.5)	3.85 (85.9)	3.42 (82.1)	3.52 (83.1)	
<p>a. All three way interaction coefficients (TxXxS) are small and set equal to zero. Coefficient estimates are for coded variables (-1,0,+1).</p> <p>b. T = temperature; X = wt% Fe in SFIO on coal; S = wt% sulfur in DMDS on coal; TxX = two-way interaction of temperature with wt% Fe in SFIO on coal; TxS = two-way interaction of temperature with wt% sulfur in DMDS on coal; XxS = two-way interaction of wt% Fe in SFIO</p>							

The observed midpoint value for THF conversion indicates an approximate 3% difference from the predicted value, namely 107,

and the observed value, 110 wt%, possibly indicating some curvature in conversion in the mid-range. Unlike the other dependent variables that will be discussed below, conversion within the experimental range that was evaluated is not overwhelmingly dominated by temperature.

Table 24. Predicted vs Observed THF Conversion

Run No.	°C	Added Fe, wt% coal	Added Sulfur wt% coal	THF CONV	
				Observed	Predicted
				Observed	Predicted
175-2	390	4	1.4	113	110
175-1	390	1	1.4	97	99
190-2	390	1	4.3	98	99
175-3	390	4	4.3	103	104
196-1	440	4	1.4	117	119
192-1	440	4	4.3	113	113
174-3	440	1	1.4	110	108
174-1	440	1	4.3	108	108
Midpoint	415	2.5	1.45	110	107

The predicted versus observed values for PA+A are given in Table 25. In the reaction sequence, coal dissolution will initially give rise to PA+A product which will build up to a maximum value before diminishing as oils formation progresses.¹⁸ The temperature coefficient, which is by far the largest of the various interactions driving the conversion of PA+A to oils, indicates buildup at the lower temperatures with a corresponding net disappearance at the higher temperature. This is reflected in the temperature coefficient of the oils which is slightly

Table 25. Predicted v Observed PA+A and Oils Conversion

Run No.	°C	Added Fe, wt% coal	Added S, wt% coal	PA+A		Oils	
				Observed	Predicted	Observed	Predicted
						Observ.	Predicted
175-2	390	4	1.4	54.2	49.8	52.7	55.0
175-1	390	1	1.4	49.7	47.0	42.2	45.8
190-2	390	1	4.3	52.1	54.7	40.0	34.5
175-3	390	4	4.3	53.1	57.5	44.0	43.7
196-1	440	4	1.4	25.4	32.6	79.4	73.6
192-1	440	4	4.3	47.5	40.3	54.4	62.2
174-3	440	1	1.4	16.3	16.1	82.8	82.8
174-1	440	1	4.3	23.7	23.8	73.3	71.4
Mid-point	415	2.5	1.45	43.3	40.2	59.1	58.6

smaller in magnitude in the PA+A model but having an opposite sign. The catalyst sensitivity, sulfur sensitivity and the TxX and TxS sensitivities are of lower but significant magnitude. The magnitude of the catalyst coefficient for the PA+A model (4.80 v. 4.08 for THF conversion) suggests that catalytic IOM dissolution reports mainly to the PA+A fraction. The negative interaction between temperature and catalyst concentration for oil yield indicates that thermal effects begin to dominate catalytic effects at the higher temperature. Note that the confidence levels are also somewhat lower for these latter values than the corresponding value for temperature. The midpoint experimental versus predicted values for the oil conversions

were 59.1 versus 58.6 wt%, respectively, while the corresponding values for PA+A were 43.3 and 40.2 wt%, respectively.

The predicted versus observed values for gases formation broken down into hydrocarbon gases and CO+CO₂ are given in Table 26. Over the temperature range, CO+CO₂ varies least of any of the dependent variables while, percentage wise, hydrocarbon gases varies the most. Between 390 and 440°C the CO+CO₂ yield varied only between 4.1 and 6.5 wt%, while the corresponding hydrocarbon gas yield varies over a much broader range between 1.1 and 5.8 wt%. Both show a small sensitivity to sulfur with HC gases showing a small positive sensitivity while CO+CO₂ with a small

Table 26. Predicted v Observed CO+CO₂ and HC Gas Formation

Run No.	°C	Added Fe, wt% coal	Added S, wt% coal	CO+CO ₂		HC Gases	
				Obs	Calc	Obs	Calc
						Obs.	Pred.
175-2	390	4	1.4	4.4	4.4	1.3	1.4
175-1	390	1	1.4	4.2	4.4	1.1	1.4
190-2	390	1	4.3	4.1	4.0	2.0	1.9
175-3	390	4	4.3	4.2	4.0	2.1	1.9
196-1	440	4	1.4	6.5	6.1	5.8	5.1
192-1	440	4	4.3	5.4	5.7	5.5	5.7
174-3	440	1	1.4	5.9	6.1	4.6	5.1
174-1	440	1	4.3	5.7	5.7	5.6	5.7
M i d - point	415	2.5	1.45	4.7	5.1	2.8	3.5

negative sensitivity. The observed versus calculated midpoint values vary only slightly for both.

Both observed and calculated hydrogen consumption values are shown in Table 27 in units of mg H₂/gram maf coal, which translates to weight percent hydrogen consumption when divided by 10. Since these runs were all made in WCS the level of hydrogen consumption at the higher severities were quite high (see discussion above). As with the other dependent variables, temperature again had a very large impact on the amount of

Table 27. Predicted versus Observed H₂ Consumption, mg/g maf coal

Run No.	°C	Added Fe, wt% coal	Added S, wt% coal	H ₂ Consumption		Percent Gaseous H ₂ Reacted*
				Obs	Calc	
				Observ	Predict	
175-2	390	4	1.4	52.1	53.5	35.5
175-1	390	1	1.4	49.1	48.9	37.6
190-2	390	1	4.3	50.8	51.1	39.2
175-3	390	4	4.3	51.2	51.2	40.2
196-1	440	4	1.4	74.5	74.7	57.3
192-1	440	4	4.3	72.5	72.4	54.8
174-3	440	1	1.4	62.4	64.1	47.8
174-1	440	1	4.3	68.1	66.4	52.1
Mid-point	415	2.5	1.45	60.1	60.2	48.6 obs.

* Represents percent of gaseous H₂ charge that was consumed.

negative sensitivity. The observed versus calculated midpoint values vary only slightly for both.

Overall the predicted versus observed data at the midpoint are in good agreement as shown by the midpoint data compiled in Table 28. The biggest differences in the predicted versus observed values are in THF conversion, i.e., 107 versus 110 wt%, respectively, and PA+A yield, i.e., 40.2 versus 43.3 wt%, respectively. The same magnitude of these two differences reflect a less than predicted conversion of IOM into the PA+A fraction indicating the non-linearity for these two dependent variables around the center point. We are not able at present to determine whether the higher actual conversion is related in any way to the apparent "zero time" conversion of IOM in the ashy resid fraction of the solvent. We know from the reactions of the ashy resid in the absence of coal that the IOM in the ashy resid exhibits two levels of reactivity. One fraction reacts very rapidly while the other is far more refractory. Overall, the IOM in the ashy resid appears to be far more reactive than the freshly derived IOM that forms from the coal that remains after completion of the reaction. The highly reactive IOM in the ashy resid may unduly shift the conversion to a higher value which the model is unable to adjust making the predicted value lower than observed.

SFIO was also evaluated under the same conditions as used for WIO in Table 3, namely at 2 wt% added iron oxide. The experimentally observed values were then compared with product distributions generated from the model. The specific conditions are near the edge of the reaction space where temperature is at the midpoint (415°C) and catalyst concentration and sulfur addition are near the lower end. Observed and predicted values under these conditions are shown in Table 29. The difference between the observed and predicted THF conversion at the

Table 28. Predicted versus Observed Liquefaction with SFIO[†] at the Midpoint

	Observed	Predicted	Δ
Iron, wt % coal	-----2.5-----		
Sulfur, wt % coal	-----2.8-----		
Yields, wt% maf coal			
HC Gases	2.8	3.5	+0.7
CO+CO2	4.7	5.1	+0.4
Oils	59.1	58.6	-0.5
PA+A	43.3	40.2	-3.1
IOM	-9.9	-7.4	2.5
THF Conversion	110	107	
H ₂ Consumption mg/g maf coal	60.1	60.3	+0.2
Run Number	174-2/190- 1/190-3		
‡ 415°C, 1 hour, 1000 psig hydrogen cold, 5.4 grams WCS solvent, 3.0 grams coal.			

edgepoint is even greater than for the midpoint data presented in Table 28, namely 4.4 wt% for the edgepoint versus 2.5 wt% for the midpoint. Unlike the midpoint data, big differences were observed between most of the other experimental and predicted values. The model significantly over predicted the HC gases and oil yield. For example, the observed hydrocarbon gas yield was less than half the predicted yield, namely 1.2 wt% versus a predicted value of 3.2 wt%. The oil yield was 6.6 wt% less than the predicted value, i.e., 57.0 versus 63.6 wt%. The biggest

difference was in the PA+A value for which the predicted value was 31.8 wt% versus an observed value of 45.0 wt%, a difference of 13.2 wt%. This corresponded to a conversion far in excess of what was observed. Overall, the lack of agreement between predicted and observed data at the edgepoint depart significantly from the corresponding values around the midpoint.

Table 29. Predicted versus Observed Liquefaction with SFIO at the Center Edgepoint[‡]

	Observed	Predicted*	Δ
Iron, wt % coal	-----1.1-----		
Sulfur, wt % coal	-----1.5-----		
Yields, wt% maf coal			
HC Gases	1.2	3.2	2.0
CO+CO ₂	5.0	5.2	0.2
Oils	57.0	63.6	6.6
PA+A	45.0	31.8	-13.2
IOM	-8.2	-3.8	4.4
THF Conversion	108.2	103.8	
H ₂ Consumption, mg/g maf coal	54.8	56.8	2.0
Run Number	272-1		
[‡] 415°C, 1 hour, 1000 psig hydrogen cold, 5.4 grams WCS solvent, 3.0 grams coal. * For these conditions model coefficients were as follows: $\beta_a = 0$; $B_b = -0.94$; $\beta_c = -0.96$; $\beta_{ab} = \beta_{ac} = 0$; $\beta_{bc} = 0.90$.			

The accuracy of the model diminishes dramatically as the reaction conditions move away from the midpoint. In order to determine the parameters that would best define the reaction space around the center edge of the reaction space will require more experimental data. In summary, the model provides an understanding of the product distribution under a range of temperature conditions at high concentrations of catalyst and sulfur. Temperature consistently has a strong overall effect while catalyst concentration produces a significant effect for THF conversion with a somewhat more moderate relative effect on hydrogen consumption and PA+A yield. In this reaction regime this catalyst has a surprising negative effect on oil yield through interaction with temperature and a corresponding positive effect on PA+A. This supports previously disclosed conclusion that iron promotes dissolution of coal but does not promote further conversion of the PA+A to oils.

Relative Conversion of Different Iron Oxides - The experimental data provide a comparison of the conversion of both WIO and SFIO with runs made in the absence of added iron at concentrations similar to the iron oxide runs made at Wilsonville, namely at 2 wt% added iron oxide on dried coal. The addition of SFIO, at a loading of 1.1 wt% iron on maf coal, which is 2 wt% added iron on dried coal, produced 8.5 wt% more oils than in the thermal case as shown in Table 30 while THF conversion was essentially the same or differed only slightly. The yield of hydrocarbon gases from SFIO was also significantly less than for either the thermal or WIO case. The added WIO gave 5 wt% more oil than in the thermal case, which agrees closely with the results observed at Wilsonville upon addition of the same amount of fresh iron oxide.²⁴ WIO also gave a hydrocarbon gas yield similar to the thermal, non-catalyzed case, and a slightly lower THF coal conversion.

Table 30. Comparison of SFIO with WIO for Liquefaction*

	Thermal	WIO	SFIO	SFIO
Added Iron,				
As Fe, wt% coal	None	1.1	1.1	0.5
As Fe ₂ O ₃ , wt% dried coal	None	2.0	2.0	1.0
Sulfur, wt % coal	None	1.5	1.5	0.7
Yields, wt% maf coal				
HC Gases	1.9	2.1	1.2	1.1
CO+CO ₂	5.0	4.8	5.0	4.8
Oils	48.5	53.8	57.0	61.2
PA+A	52.2	45.3	45.0	41.2
IOM	-7.6	-6.0	-8.2	-8.3
THF Conversion	107.6	106.0	108.2	108.3
H ₂ Consumption, mg/g maf coal	52.4	53.4	54.8	57.7
Run Number	139-1/167-1	142-2/189-1	272-1	272-2
* 415°C, 1 hour, 1000 psig hydrogen cold, 5.4 grams WCS solvent, 3.0 grams coal, 2.4 atom sulfur/atom added iron.				

Addition of SFIO at the 1 wt% added iron oxide level had a definite positive affect on the reaction as shown in Table 30. At this level of catalyst addition, that fell outside the range used in developing the model, the oil yield increased dramatically up to 61.2 wt%, which is an advantage of almost 13 wt% over the thermal case. At the same time, THF conversion, HC gases yield and CO+CO₂ were unchanged over the 2 wt% SFIO

addition level. The results at this lower iron concentration approaches the predicted value at the center edgepoint in Table 29. The oil yield in this run was only 2.4 wt% below the predicted value at the same conversion value observed at the higher SFIO level in Run 272-1. It would be interesting to know whether this same catalyst response would be observed in systems where there is not such a high level of recycled iron and molybdenum in the composite solvent.

SUBTASK 2.3.3 CATALYST STUDIES (Sandia)

Nickel Molybdenum Catalyst Tests

A hydrous titanium oxide (HTO) thin-film catalyst was prepared on an alumina substrate (Shell 324 blanks) by first coating the extrudate with a thin film of the hydrous titanate. The molybdenum is next loaded by ion exchange and finally the nickel is added by incipient wetness. Previous studies with a nickel molybdenum (NiMo) thin-film catalyst on large pore silica beads (see Table 19) showed good activity at 275°C. The 1/32" alumina substrate was chosen since its packing density is twice that of the silica spheres used in May. This catalyst has a nickel content of 2.4% and a molybdenum content of 7.2%.

Platinum Catalyst Tests

A hydrous titanium oxide (HTO) catalyst was prepared with platinum as the active metal. Platinum ammonium nitrate is used in the bulk HTO preparation. A 500°C calcining step activates the catalyst and drives off troublesome nitrogen compounds before the catalyst is reduced in the reactor with flowing hydrogen. Previous studies with this catalyst (see February 1992 report) showed that it deactivated at 275°C, ostensibly, because of sulfur in the feed. Platinum catalysts are known to desorb

sulfur at higher temperatures;¹⁹ for this reason we raised the reaction temperature to 315°C (from 275-300°C) for the combined water-gas shift/solvent hydrogenation reaction.

Task 2.6.1 FLUIDIZED COKING

Researchers at the CAER are currently investigating the integration of fluid coking (FC) into the advanced concepts liquefaction process scheme. The purpose of fluid coking in the current process scheme is to remove ash and unconverted coal from the liquefaction system. The capital costs for installing a FC system are estimated to be much lower than that of critical solvent de-ashing. Another economic advantage of the FC system is the utilization of the coker overhead stream, which can be recycled back to the liquefaction process.

To gain a better understanding of the production of coker overhead products, a background literature search was conducted by the CAER staff. The earliest comprehensive liquefaction FC study was conducted by Exxon Research and Engineering and funded by DoE in the late 1970s. The objective of the Exxon study was to evaluate the applicability of FC technology to processing of coal liquefaction residues. They obtained preliminary coking results using batch pyrolysis tests of vacuum bottoms resid. Exxon later developed the Continuous Stirred Coking Unit (CSCU) to simulate FC on a commercial scale. A simplified schematic of the CSCU is shown in Figure 6.

Tabular alumina particles (350 - 750 μm diameter) were used as a seed material for the coking reactions. The relatively high minimum fluidization velocity of this particle size range was not compatible with the residence time requirements of the test program, therefore the CSCU was mechanically stirred to simulate the fluidizing environment of a commercial scale fluid coker.

The resid feedstock was melted and subsequently sprayed into the alumina bed of the CSCU reactor. Coking reactions occurred on the surface of the alumina particles. Fresh alumina was continuously added to the CSCU while coked particles were removed from the system.

Figure 6. Schematic of the Continuous Stirred Coking Unit (CSCU)
(Adapted from Exxon Research and Engineering, 1978)

Steam and coker product gases exited the reactor through a vapor space above the alumina bed and proceeded to the recovery section. The first stage of the recovery section consisted of an air cooled heat exchanger; this was to cool the reactor gases to approximately 500°F and condense the higher molecular weight coker tars. In the second stage, a water cooled condenser was used to condense the steam and the lighter oils. The quantity and concentration of non-condensable product gases were measured by a wet test flow meter and a gas chromatograph, respectively.

With this reactor configuration, they assessed the effect of the major operational variables such as coking temperature (1000 - 1200°F) and steam-to-resid ratio (0.15 to 0.30). In general, coke yield decreased with increasing temperature. The liquid yield was found to remain relatively constant over the range of temperatures tested. As expected, the gas yield increased with increasing temperature. The steam-to-resid ratio had no effect on the product yield distribution.

In a more recent DoE program, Lummus-Crest Inc. conducted CSCU tests to process vacuum bottoms resid and established the hydrogen donor properties of the resulting coker distillate liquids. In general, the coker product liquids were found to be poor hydrogen donors and had low solvent quality index (SQI) values. With increasing coking temperature, the SQI of the liquids decreased. Some of the liquids produced at the higher temperature (i.e., those with the lowest SQI) were hydrotreated by CONSOL. In a micro-autoclave reactor, the calculated SQI of the coker liquids produced from an Ohio #6 feedstock increased from 51.7 to 85.9 with hydrotreating. Similarly, hydrotreatment of an Illinois #6 coker liquid, using a stirred autoclave reactor, increased the SQI from 51.0 to 97.7. Although the number of data points from the CONSOL tests were relatively few, there seems to be promise for upgrading the coker liquids for recycle liquids in the advanced liquefaction process based upon these results.

Experimental Apparatus

To produce the quantities of coker overhead liquids required for subsequent testing and analysis in the current test program, the CAER has opted to modify an existing 3 inch fluidized retort. With the larger scale reactor, external agitation of the alumina bed will not be needed as in the case of the CSCU, since the velocity of the steam will be adequate for fluidization.

The current pilot-scale reactor scheme is shown in Figure 7. The ashy resid feedstock will be ground in the presence of liquid nitrogen (this is to prevent melting) to a mean particle size of less than 120 μm . The resid will be mixed with an alumina seed material of similar particle size range. The optimal resid-to-alumina ratio will be determined in the shake-down phase of the test program. The alumina/resid mixture shall be metered into an eductor device via a calibrated screw feeder. Nitrogen gas will be used to transport this mixture from the eductor to the reactor fluidized bed zone. Once the resid particles enter the fluid

Figure 7. Schematic of the CAER 3-inch Fluidized Bed Coker Unit

bed, they will begin to melt and subsequently coke onto the alumina particles. The height of the fluidized bed zone will be controlled by varying the length of an overflow tube in the center of the reactor. Coked particles shall be continuously withdrawn from the bottom of this tube to maintain the reactor material balance.

A mixture of steam and nitrogen shall be used as the fluidizing gas. These gases will be heated in the pre-heater furnace to a specified temperature upstream of the fluidized bed. Heat trace lines surrounding the reactor will be utilized to maintain constant fluid bed and freeboard temperatures. A two-stage recovery section, similar to that of the Exxon CSCU, will be used to trap the coker tars and light oils.

The range of design feed rates for the pilot-scale reactor are shown in Table 31a (0.3 m/s) and Table 31b (0.17 m/s). The reactor heating system was designed to control the fluidized bed and freeboard temperatures in the range of 900 to 1200°F. Operating conditions and reactor specifications of previous liquefaction coking experiments are currently under review. This information and the published physical properties of vacuum bottoms resid will be taken into consideration for the design of the initial test matrix.

Project Status

The major modifications to the 3-inch reactor will be completed by November 6. The resid screw feeder has been ordered and is expected to be shipped in late November. Until that time, all other systems of the reactor will be tested (for example, the steam generator, flow instrumentation, steam and liquid recovery system, etc.).

**Center for Applied Energy Research
Bench Scale Fluid Coker Reactor
Parameter Ranges**

Table 31a. Fluidizing Velocity= 0.3 M/s @550°C

Resid Feed Rate (gram/min)	Steam Rate (gram/min)	Steam/Resid Ratio
5	22.6	4.5
10	22.6	2.3
15	22.6	1.5
20	22.6	1.1
45	22.6	.5

Table 31b. Fluidizing Velocity= 0.17 M/s @550°C

Resid Feed Rate (gram/min)	Steam Rate (gram/min)	Steam/Resid Ratio
5	12.5	2.5
10	12.5	1.25
15	12.5	0.83
20	12.5	0.63
45	12.5	0.28

TASK 3.4 PRELIMINARY TECHNICAL ASSESSMENT

Baseline Economic Assessment

Preparation of the baseline economic assessment, based on Wilsonville Run #263J, continued. This baseline study will serve as the reference against which the results of this program will be compared. During the quarter calculation of the material and energy balances for the conceptual commercial plant were completed and estimation of the investment for the main process units was begun (Wyoming plant site basis). A presentation on the technical results of the baseline study was prepared and delivered at the Quarterly Project Review Meeting in Pittsburgh.

Dewaxing the Process Solvent Distillate

The main purpose of Dewaxing the distillate portion of the process solvent is to improve process solvent quality and thereby improve liquefaction system economics.

Consol conducted several Dewaxing tests and reported their results in June. CONSOL's Dewaxing test results were analyzed and used to help develop a simple Dewaxing separation model which was then used to predict steady-state commercial unit performance. Assumptions about the net make of wax and its composition had to be made as this information could not be determined from the available Wilsonville plant operating data. The results of the model indicate that there are two options for conducting the Dewaxing operation. A large portion of the entire distillate process stream can be treated at mild conditions to separate the net wax produced in the process. Alternatively, a much smaller portion of the distillate stream can be treated at more severe conditions. In either case, a wax fractionation stage is also required to produce a "hard" wax. Hydrotreating of the hard wax is likely to be required in order to meet strict odor and color specifications.

Texaco, one of the leading licensors of solvent dewaxing technology, was contacted to gain a better overall perspective of this process and its costs. Texaco representatives were very cooperative in providing technical information and a preliminary investment for a solvent dewaxing unit based on a feedrate of approximately 30,000 BPSD (low feedrate - high severity operation). Based on Texaco's information and the information developed by the wax separation model a quick look was taken at the economics of partially dewaxing the distillate portion of the process solvent. Out of necessity numerous assumptions had to be made in order to carry out this evaluation. The evaluation indicates that the cost of the Dewaxing Unit and the reduction in the main product (gasoline) rate can almost be offset by the value of the wax which is separated and purified. However, this preliminary conclusion is based on several key assumptions including the quality and quantity of the wax produced and its selling price. A presentation on this preliminary assessment was prepared and delivered at the Quarterly Project Review Meeting in Pittsburgh. A list of recommended future activities was also made.

Fluid Coking

Information on fluid coking technology and its application to coal liquids was researched. A 1989 MITRE working paper on the impact of liquefaction bottoms fluid coking indicates a favorable result. However, this result is based on many assumptions, some of which seem to be quite optimistic. Further analysis is required once the Baseline Economic Assessment has been completed.

HRI Two Stage Process

A brief review of HRI's work in Two Stage Liquefaction with Wyoming sub-bituminous coals was conducted. HRI's standard approach for their CTSL process is to utilize supported catalyst in both reaction stages, a low-high reactor temperature sequence and a solids-free recycle process solvent stream. All of the preceding techniques differ from those used at Wilsonville and in our

Baseline Assessment. Based on a 1988 HRI technoeconomic study of a conceptual commercial plant processing Wyoming coal, it appears that the CTSL configuration would require significantly more reactor volume than is required in our Baseline Assessment. However, reactor volume is only one of many factors in evaluating the economics of a liquefaction process. No further work is planned since a more detailed comparison of the two processes is beyond the scope of our program.

REFERENCES

1. Advanced Direct Liquefaction Concepts for PETC Generic Units, Quarterly Technical Progress Report, August 1992, p 59-61.
2. Anderson, R. R. and Bockrath, B. C., Fuel 1984, 63, 329.
3. Southern Electric International, Inc., Technical Progress Report, "Integrated Two-Stage Liquefaction of Subbituminous Coal", DOE Contract No. DE-AC22-82PC50041 and EPRI RP1234-1-2, EPRI AP-5221, Final Report, June 1987; p 3-7.
4. Southern Electric International, Inc., DOE Contract No. DE-AC22-82PC50041 and EPRI RP1234-1-2, Technical Progress Report Run 246 with Wyodak Coal, DOE/PC/50041-57, August 1985.
5. Skinner, R. W. and Givens, E. N., ACS Div Fuel Chemistry Preprints, 1982, 27(3-4), p 37.
6. Skinner, R. W., "Effects of Accumulated Solids and Solvent Initial Boiling Point on Dissolver Performance," DOE/OR/03054-29, Sept 1983.
7. Southern Clean Fuels, handouts from Technical Meeting No. 113 (November 13-14, 1991) Wilsonville Advanced Coal R&O Facility.
8. Robbins, G. A.; Brandes, S. D; Winschel, R. A.; Burke, F. P. Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, January 1 through March 31, 1992", DOE Report No. DOE/PC 89883-50, August 1992.
9. Burke, F. P.; Winschel, R. A.; Robbins, G. A., Recycle Slurry Oil Characterization Final Report, October 1983 - March 1984, DOE Report No. DOE/PC 30027-61, March 1985.
10. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Second Annual Report, January 1 - December 31, 1986", DOE Report No. DOE/PC 70018-37, June 1987.
11. R.A. Winschel, G.A. Robbins, F.P. Burke. Fuel 1986, Vol 65, 526-532.
12. R.A. Winschel, G.A. Robbins, F.P. Burke. Fuel 1987, Vol 66, 654-660.
13. Andres M, Charcosset H, Chiche P, Davignon L, Djega-Mariadassou G, Joly J-P, Pregermain S, 1983, Fuel; 62; 69-72

14. Djega-Mariadassou, G., Besson, M., Brodzki, D., Charcosset, H., Huu, T. V. and Varloud, J., Fuel Processing Tech. 1986, 12, 143-145.
15. R. Srinivasan, R. A. Keogh and B. A. Davis, "Structural Characterization of Sulfided Iron Oxide Catalyst", in press.
16. Box, G. E. P., Hunter, W. G. and Hunter, J. S., Statistics for Experimenters, John Wiley and Sons, New York (1978).
17. Das Gupta, R., Mitra, J. R., Dutta, B. K., Sharma, U. N., Sinha, A. K. and Mukherjee, D. K., Fuel Proc Tech, 1991, 27, 35.
18. R. A. Keogh, K. Tsai, L. Xu, B. H. Davis, Energy Fuels 1991, 5, p625.
19. J. Barbier, E. Lamy-Pitara, P. Marecot, J. Boitiaux, J. Cosyns, F. Verna. Advances in Catalysis. Academic Press; 1990. V. 37: 279-318.

END

**DATE
FILMED**

3 / 17 / 93