Acquisition and Reduction of Data Obtained from Tank 101-SY In-Situ Ball Rheometer

C. L. Shepard
M. A. Chieda
L. J. Kiriara
J. R. Phillips
A. Shekariz
G. Terrones
J. Abbott¹
C. Unal¹
K. O. Pasamehmetoglu¹
A. Graham¹
T. I. Stokes²

December 1994

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

¹Los Alamos National Laboratory
Los Alamos, New Mexico 87545

²Westinghouse Hanford Company
Richland, Washington 99352

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ja

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Summary

Development of the ball rheometer to measure rheological properties and density of the waste in Hanford Tank 241-SY-101 will be completed around September 1994. This instrument is expected to provide the first-of-its-kind in-situ measurements of the fluid properties, such as viscosity, of the waste contained within this tank that have been desired for years. Since the ball rheometer project began, a mixer pump has been installed in this tank, and by all accounts this pump has been very successful at mitigating the flammable gas problem associated with Tank 101-SY. Present plans now call for the use of mixer pumps in several other tanks.

The ball rheometer will serve as a diagnostic tool for judging the effectiveness of mixing in Tank 101-SY and others and will be one of few in-situ probes available for diagnostic measurements. The data requirements and basis of choice for the ball rheometer and the theory of the operation of the ball rheometer have been covered in previous reports (Pasamehmetoglu et al. 1993, Shepard 1994, Shepard et al. 1994). The in-situ data collection strategy and the methods of data analysis and reduction are presented in this final report concerning this instrument. Based on experiments performed at Los Alamos National Laboratory and Pacific Northwest Laboratory, it is believed that a generalized Bingham fluid model (Herschel-Bulkley fluid model) may be useful for describing at least some of the waste contained in Tank 101-SY, and data obtained in the tank will initially be reduced using this fluid model. The single largest uncertainty in the determination of the drag force on the ball is the drag force which will be experienced by the cable attached to the ball. This drag can be a substantial fraction of the total drag when the ball is deep within the tank. Careful accounting of the cable drag will be important in the reduction of the data.

It is expected that the fluid properties may be history dependent, thus rheological properties of the undisturbed fluid may be different from the same properties after the fluid has been disturbed by passage of the ball. The data collection strategy allows the determination of the waste fluid rheology both in the undisturbed state and after it has been disturbed by the ball. Fluid density will be measured at regular intervals. Unlike the rheological parameters, measurement of density requires no model for its interpretation; however, the effects of yield stress may need to be accounted for. This measurement can be made with fairly good accuracy and may provide the most useful data in determination of mixer pump effectiveness.

Contents

Summary	iii
Contents	v
1.0 Introduction	1
2.0 Results from Laboratory Investigations	3
2.1 Experiments Performed at PNL	3
2.2 Experiments Performed at LANL	6
3.0 Data Acquisition Strategy	8
3.1 Measurements in the Riser Pipe and Dome Space	8
3.2 Measurements in the Waste	9
4.0 Reduction of Data	13
5.0 Expected Accuracies	17
6.0 Conclusions	18
7.0 References	18
Appendix A: Experiments Performed at Pacific Northwest Laboratory and Los Alamos National Laboratory	20

1.0 Introduction

Since mid-1993 a team made up of staff from Westinghouse Hanford Company (WHC), Pacific Northwest Laboratory (PNL), and Los Alamos National Laboratory (LANL) has been developing a measurement instrument for determination of some of the fluid properties of the wastes contained in Tank 241-101-SY (hereafter abbreviated as 101-SY) on the Hanford Reservation. The ball rheometer was chosen for its simplicity, its ease of deployment, and its capabilities for providing data from which fluid density, yield stress, and apparent viscosity can be determined. The basis for its choice and the identified data requirements are outlined in an earlier report (Shepard 1994), while the underlying theory and practical application of the ball rheometer are given in other reports (Shepard et al. 1994; Pasamehmetoglu et al. 1993). The ball rheometer consists of a ball attached to a cable which is wound onto a spool. The system will be installed on a riser pipe through which entry into Tank 101-SY is obtained. The ball can be lowered into the waste or retrieved from the waste by rotation of the spool, which is mechanically connected to electric drive motors. The present ball is comprised of a tungsten alloy and is 9.1 cm in diameter and weighs about 16 lb (7.3 kg). It is likely that other balls of similar size but lower density, such as a steel ball, will also be employed. The cable is stranded stainless steel of diameter 0.32 cm (0.125 inches) and has a polyethylene coating. A diagram of the ball rheometer is shown in the following figure. The ball is deployed into the waste and retrieved by rotation of the take up spool. Typically the ball will be deployed at a constant velocity, which is adjustable over the velocity range from 0.1 cm/s to 100 cm/s. The cable passes over a pulley to which a load cell is attached. The tension in the cable, or actually twice the tension in the cable is measured by this load cell. We will measure the tension in the cable as the ball is being moved through the waste at different velocities. From these measurements, the drag on the ball due to movement through the waste can be determined. The amount of drag depends on the rheology (roughly the yield stress and the viscosity) of the waste fluid, and we are interested in determining the rheology of the fluid. Static force measurements obtained while the ball is at rest in the fluid will allow a determination of the fluid density. We intend to characterize the fluid at all depths within the tank.

This report is largely concerned with the testing strategy when the ball rheometer is installed on Tank 101-SY. The strategy is based partially on the results of laboratory investigations conducted at LANL and PNL. The methods to be used for reduction of the data to obtain fluid properties is also a topic of interest here. Finally, some estimates of the accuracy we can expect in the derived fluid properties will be given.

In Section 2.0 of this report, we review the results obtained from laboratory investigations using chemical simulants of the waste. Experiments were performed at both LANL (primarily falling ball experiments) and PNL (primarily drag force measurements). These results are important for forming the tank testing strategy, which are presented in Section 3.0. The methods for reduction of the data to obtain fluid rheological parameters and fluid density are discussed in Section 4.0. Reduction of the data presently requires a fluid model, and we will initially assume that the fluid behaves as a generalized Bingham (Herschel-Bulkley) fluid and reduce the data to obtain parameters for the model. It should be noted that a time independent generalized Bingham fluid model may not adequately describe all or parts of the real waste. We can fully address the problem of data reduction only after we have acquired actual in-situ data. The actual tank waste may behave differently from the simulant tested in the laboratory. In Section 5.0 we present an estimate of the accuracies for the derived fluid

Diagram of the Ball Rheometer System Showing the Ball, Cable, Take-up Spool, Pulley, and Load Cell. The instrument fastens to a riser pipe through which entry into the waste tank is obtained.

rheological parameters and the fluid density. Conclusions and a summary are given in Section 6.0. An Appendix contains detailed information about the experiments performed at both laboratories, as opposed to the cursory review presented in the main body of this report.

2.0 Results from Laboratory Investigations

Experiments were performed at both PNL and LANL in support of the ball rheometer project. Experiments at PNL used an experimental setup which closely resembles the actual hardware being constructed by WHC. The primary purpose of these tests was to examine unresolved issues concerning the expected performance of the in-tank ball rheometer. Experiments at LANL were concerned with determination of the fluid properties of a chemical simulant of the 101-SY waste which is expected to behave similarly to the actual waste fluid. These experiments were aimed at determining the applicability of fluid models to describe the behavior of the simulant and at examining the fluid behavior of the simulant. The experiments will be described separately below.

2.1 Experiments Performed at PNL

The force measured by the load cell will not simply be the drag force on the ball. Other forces also contribute to the measurement. In the reduction of the force data to obtain the rheology of the fluid, the drag force on the ball is of primary importance. In the measurement of density, the buoyancy force on the ball must be determined. It is necessary to determine all of the forces at work in these measurements and then determine which part of the total force is due to drag on the ball. As a result, the actual measured force will have to be corrected to account for quantities such as the weight of the ball, the weight of the deployed cable, the weight of the pulley, the friction in the pulley, and the buoyancy forces on both the cable and ball. Finally, the drag force on the cable has to be determined. Some of these forces can be obtained by laboratory measurements prior to deployment of the ball. For instance, the weights of all components and pulley friction should be well known ahead of time. Buoyancy can be reliably calculated from static measurements made in the tank. It turns out that only one force, the drag force on the cable, will present difficulties for measurement or calculation. This conclusion was reached independently at both laboratories.

A theoretical analysis was performed to identify the various forces measured with the load cell. Then, experiments were performed with simulants to estimate the contribution to the total force due to buoyancy and drag on the cable. In addition, constant velocity drag force experiments were performed using several ball sizes and simulants to determine how the drag forces on the ball varied with ball size and velocity for these fluids. These experiments simulate the manner in which data will be collected in actual work with the in-tank ball rheometer. Finally, we investigated the effects due to fluid boundaries (such as the air-fluid interface) and also transients that arise when motion of the ball is started and stopped. Experiments were performed with three different fluids: a chemical simulant of the waste, carbopol (a semi-clear polymer fluid containing no particles), and Bentonite clay (a mixture of clay and water having a high yield stress and viscosity) in order to span a reasonable range of Reynolds and Bingham numbers. We have attempted to parameterize the expected transient responses in terms of the fluid properties. Samples of the fluids were also characterized independently using a Bohlin rheometer, which consists of a pair of concentric cylinders

with the sample contained in the gap between the cylinders. The results obtained with this instrument were then compared with results obtained by reducing the drag force data using theoretical relationships.

The equations giving the drag force on the ball in the case of a falling and rising ball are given respectively by (see Appendix),

$$D_b = B_b - C(z-z_o) - \int_{z_o}^z [A(z') - B(z')] dz' - \frac{\eta - \Delta R_f}{2} \quad \text{falling ball} \quad (1)$$

and,

$$D_b = -B_b + C(z-z_o) - \int_{z_o}^z [A(z') + B(z')] dz' - \frac{\eta + \Delta R_r}{2} \quad \text{rising ball} \quad (2)$$

where

- D_b = drag force on ball
- B_b = buoyancy force on ball
- z_o = reference position of ball
- z = ball position
- A = drag coefficient for cable
- B = cable buoyancy coefficient
- C = weight per unit length of cable
- η = pulley friction coefficient
- ΔR = $R(z) - R_o$
- R_o = load cell reading at reference location z_o .

The above equations assume a reference measurement (R_o) of the cable tension. This measurement should be made just above the surface of the waste (at z_o) and includes the weight of the ball, pulley, and the deployed cable. In the experiments, ΔR will be a measured quantity. Some of the other quantities given in Eq. 1 and 2 will be well known but will not be directly measurable during experiments. The weight of the cable per unit length can be determined with prior measurements. Pulley friction as a function of load and speed can also be measured beforehand. Both the buoyancy on the cable and the drag on the cable may not be linear functions of the deployed cable length, since they depend on the fluid properties. If the density is known as a function of depth, then the cable buoyancy can be calculated as an integral over the cable length. For density measurements the drag forces and the pulley friction become zero and the density is calculated from

$$B_b = - \int_{z_o}^z B(z') dz' + C(z-z_o) - \frac{\Delta R}{2} \quad (3)$$

and the relation

$$\frac{\pi d^3}{6} \cdot \rho \cdot g = B_b \quad (4)$$

where ρ is the fluid density, d is the ball diameter, and g is gravitational acceleration. If the fluid density is measured at regularly spaced intervals, then the integral over the depth can be performed to obtain the total buoyancy of the cable. Thus, static measurements allow a direct determination of the buoyancy forces and therefore the fluid density. Errors in the estimation of fluid density may result if the fluid has a significant yield stress and the ball is partially supported by this force, which is unaccounted for in Eq. 3. Laboratory experiments with a well mixed simulant have shown that the effect is negligible. The same may not necessarily be true in the actual tank waste, and this subject will be revisited when actual data are obtained. In examining Eq. 1 and 2 and in consideration of the above comments, it is seen that all terms in these equations can be accounted for except the cable drag coefficient (A).

The drag on the cable depends on the rheological properties of the fluid, which may be a function of depth within the fluid. This drag will also depend upon the length of cable immersed in the fluid. If the ball is deep enough into the waste, the drag on the cable may be a substantial fraction of the drag on the ball. At immersion depths greater than about 3 meters, the surface area of the cable in contact with the waste exceeds the surface area of the ball. We need to know the drag on the ball alone in order to determine the fluid rheology. This means that we need to correct measurements for the drag on the cable, but we can make this correction only if we know the fluid rheology. We presently have no theory with which to calculate the cable drag even if we can estimate the fluid rheology. Laboratory investigations are continuing in order to obtain some knowledge of how to account for cable drag. In the general case it does not appear possible to experimentally determine both drag forces independently in in-situ tests. However, this possibility will be explored. An iterative approach may provide a possible solution of this problem. Knowledge of the cable drag force as a function of position in the waste will allow the calculation of the integral for the total cable drag at any depth into the waste. We will discuss this problem in more detail in the Section 4.0, which deals with data reduction.

Experiments were performed to verify that the buoyancy of the ball is given by Archimedes Principle even when the ball is in motion through non-Newtonian fluids. These experiments verified that Archimedes Principle is applicable for these fluids and the measurement of fluid density will be possible in experiments conducted in the tank. Again however, if the fluid has a significant yield stress the accuracy of density determinations may suffer.

Experiments were conducted where only the drag forces acting on cables were measured. As with all of our experiments, the range of Reynolds number and Bingham number was limited. For experiments involving just the cables, the Reynolds number was always less than 0.1 while the Bingham numbers ranged from about 1 to 10. The results indicate that while the drag force per unit length of cable is small, the total force acting over a long cable may in some cases be comparable to the drag force on the ball. The drag force is dependent on the types of fluids tested, but appears weakly dependent on cable velocity. This result suggests that the drag is dominated by forces needed to yield the fluid, rather than by viscous drag. However, no clear trends are apparent from the data. The drag force does not seem to correlate with the fluid yield stress, Bingham number, or Reynolds

number. These experiments will be repeated in further attempts to understand the correlation between cable drag and fluid rheology.

There was concern that, for rising ball tests, the passage of cable through a region of fluid prior to the passage of the ball through the same fluid may affect the drag force on the ball due to the prior disturbance of the fluid. Experiments with the chemical simulant (well mixed), the bentonite clay, and the carbopol have shown that the effect is negligibly small. These experiments were mostly performed at Reynolds numbers less than 1.0.

In any experiment there will be a transition region where the ball accelerates to a constant velocity and steady state fluid flow is established about the ball. Available theory with which we will reduce the drag force data is based on steady state fluid flow. Experiments were conducted to examine the pull distance required before steady state drag is observed. The distance depends somewhat on the fluid rheology, but is typically of the order of one ball diameter, at least in our tests where the Reynolds number typically less than unity. The range of Reynolds numbers expected in actual testing in the tank may be substantially higher than 1, perhaps as high as $Re = 50$. In use of the ball rheometer in the waste tank, a pull distance of greater than one ball diameter will probably be required, and we plan initially to use at least three diameters. The required pull distance can be determined in actual in-situ testing, and adjustments will be made as necessary.

The effects of interfaces were also investigated in our experiments. For the fluids tested, a boundary (such as the fluid-air interface) begins to affect the measured drag forces when the ball approaches to within about one ball diameter of the interface. For experiments within the tank then, experiments should begin well away from known boundaries, such as the surface and the tank bottom. Interfaces within the fluid where the character of the fluid changes dramatically will be observed over a distance of several ball diameters over which it will be difficult to obtain reliable steady state data.

2.2 Experiments Performed at LANL

Primarily free-falling ball experiments were conducted in these tests. In addition, a significant effort was put forth to produce a large quantity of a chemical simulant. The primary focus of the experiments was to determine the applicability of continuum fluid mechanics in the analysis and reduction of ball rheometer data and to determine an appropriate fluid model with which to describe the fluid. Data were obtained with two simulants; an "aged" simulant which has been resident at LANL for years and a new simulant just recently prepared and chemically very similar to the older simulant. Tests show that the two simulants are not the same, but do not differ greatly. A generalized Bingham fluid model appears to be applicable for both of these fluids. The effect of cable drag was also investigated analytically. Calculations based on the assumption of a Newtonian fluid indicate that cable drag can be a substantial fraction of the drag on the ball, in agreement with the experimental findings at PNL. Both laboratories have independently identified cable drag as a major factor in the reduction of the actual in-situ data. In addition, experiments were conducted with a settled simulant in order to observe how the particulates in the fluid settle and how the fluid rheology changes as a result of the settling. Results from this testing have contributed to the testing strategy which will be discussed below. For instance, based on these laboratory tests we will conduct experiments to probe the dependence of fluid properties on the shearing history of the fluid. It was observed in these experiments that the behavior of the fluid depends on this past history. Also, these tests showed that

the undisturbed fluid can only be tested in falling-ball experiments, rather than with retrieving-ball experiments. Details of the laboratory investigations performed at LANL are given in the Appendix.

Experimental work at LANL required a considerable amount of simulant. Some existing waste simulant was available, but not nearly enough. Thirty gallons of new simulant was prepared following a procedure developed at LANL. The chemical composition of the new simulant is similar to other formulations used at PNL and is based on the chemical composition of the real waste as determined from sampling. Of course, radioactive components are omitted. While chemically very similar to existing PNL and LANL waste simulants, there was no assurance that all simulants would have exactly similar rheological properties. In order to assure that results obtained at PNL can be compared to those obtained at LANL, about 10 gallons of the new simulant was shipped to PNL for laboratory experiments. Future testing at PNL will be performed with this simulant.

Testing with the simulants was performed using free-falling ball rheometry. In addition, a Couette viscometer was used for an independent characterization of the simulant. Couette viscometry is based upon dissipative resistance in a fluid between two concentric cylinders with at least one of them rotating. Falling-ball tests utilized a variety of balls of different sizes and densities. The balls fell through a 5-cm diameter and 50-cm length column of waste simulant and the flight path of the balls through the column was recorded using x-ray radiography and a video recording system. The ball velocities were determined from the video images. Experiments were performed with well-mixed and settled simulants.

Experiments with a well-mixed homogeneous simulant showed very good reproducibility in the terminal velocities of similar balls dropped through the simulant in repeated tests. The conclusion drawn from these experiments was that the well-mixed fluid behaved as a continuum and was therefore amenable to theoretical treatment as a single phase fluid. In addition, the rheology for the well mixed simulants could be determined from these data. Both simulants ("old" and "new") appeared to behave as generalized Bingham fluids. However the new simulant had a much higher yield stress.

Results from Couette viscometer tests with the same well-mixed simulants showed qualitatively similar results, but the viscosities were consistently lower by about a factor of two than viscosities determined by the falling-ball method. In addition, there were differences in the power law indices, with the indices being less using the Couette viscometer. The most likely cause for the discrepancy is that the simulant is not exactly described with the simple power law model. Small samples taken from a large volume of simulant were used for these tests, and non uniform sampling may also be a cause for the discrepancies.

Data obtained from falling-ball tests with a settled simulant suggest that the simulant is a history dependent non Newtonian fluid. The fluid apparently thins after being subjected to shear. In repeated falling ball tests through a simulant in which particles had been allowed to settle under gravity, the first ball through a region always dropped slower than subsequent balls dropped through the same region. A fluid model could not be determined for the settled simulant due to the variability of ball velocities in repeat tests. The experiments show that steps should be taken in actual experiments with the tank to determine the history dependence of the fluid rheological properties. As described below, these measurements will be obtained.

The additional complication introduced by the presence of a cable attached to the ball was addressed analytically. Both theoretical calculations and numerical calculations which include appropriate end effects indicate that drag on the cable when the ball is near the tank bottom may be a substantial fraction of the total measured drag. The calculations were based on a Newtonian model for the fluid, and improvements could be made by using non-Newtonian fluid models. However, these studies along with the experimental measurements obtained at PNL establish that cable drag will have to be accurately accounted for in the reduction of the actual in-tank data.

3.0 Data Acquisition Strategy

We desire to obtain a complete profile of the fluid properties from the top of the waste to the bottom. Measurements will be taken proceeding downwards, primarily with a falling ball operated at constant velocity. Once a complete test has been performed, we may desire to perform measurements from bottom to top in order to obtain repeat supplemental data. It should be noted that initially we will have incomplete knowledge the actual waste rheological character and the manner in which the rheology changes as a function of depth in the waste. The goal of the testing is to obtain this information and to establish as completely as possible the nature of the waste held within the tank, at least along one vertical dimension. Our testing strategy will reflect this goal. We begin this testing description by assuming that the ball rheometer system is in place on the selected tank riser and ready for deployment.

3.1 Measurements in the Riser Pipe and Dome Space

With the ball fully retracted in the "home position," the ball position should be verified to be at distance zero, our reference position. After opening the gate valve which seals the instrument from the tank riser pipe, lower the ball at 1 cm/s for 1 cm and obtain a force measurement after the ball is stopped. The static density mode should be used for this measurement. This measurement determines the weight of the ball and the reading can be checked with the expected result. A reading which deviates from the expected value indicates that either an incorrect load cell has been installed (if there is a gross difference between measured value and expected value) or perhaps the calibration has shifted. The measurement is obtained near the home position so that immediate changes can be made if the measurement indicates a problem. It is fully expected that the measurement will be within tolerances, and the primary purpose of this measurement will be to detect long-term drifts in the apparent weight of the ball which could be due to instrument drift or waste buildup on the ball. Laboratory tests with a chemical simulant performed at PNL have shown that buildup of crystals and other material on the ball and cable occurs very slowly, and for durations of less than about a month buildup should not be a problem. However, our data analysis procedures will identify and quantify these effects.

The ball should then be lowered very slowly through the riser pipe (1 cm/s) while the load cell is monitored to observe reductions in the apparent weight of the ball. Such an observation would be an indicator that the ball is being impeded by the riser pipe or material within the riser pipe. No data are collected in this procedure. However, if the ball becomes stuck or begins to show signs that it is becoming stuck, the ball should be stopped and steps taken to understand the difficulty. Visual

verification that the ball has passed through the riser pipe and into the dome space should be obtained utilizing the DACS camera. By the same means, it should also be verified that the cable is not in contact with the riser pipe after the ball has passed through the pipe.

After the ball has passed through the riser, it should be lowered by another 50 cm and brought to rest. A static measurement should then be obtained. Then four constant velocity measurements should be obtained: (1) lower the ball at 1 cm/s for 100 cm, (2) raise the ball at 1 cm/s for 100 cm, (3) lower the ball at 10 cm/s for 100 cm, (4) raise the ball at 10 cm/s for 100 cm. These tests are designed to check for pulley friction and the results should be compared to expected results based on previous laboratory testing. Long-term deviations may indicate a changing pulley friction. A static measurement should follow the final test.

The ball should then be lowered at 1 cm/s to very near the surface of the waste and another static measurement should be obtained. No data need be collected or recorded while the ball is falling. Approach to the surface can be verified by the DACS camera or by prior knowledge of the location of the surface and consideration of the amount of cable which has been released from the cable spool, and the measurement should be performed within several inches of the actual fluid surface. Exact position is not critical, but the ball should not be in contact with the waste. This measurement forms the reference measurement against which all other measurements will be compared. In Eqs. (1) and (2), this measurement provides R_0 . At this point we are ready for measurements in the waste fluid.

3.2 Measurements in the Waste

The first task is to remove a large enough volume of crust from the area immediately beneath the ball so that we can perform tests in the waste. There are several alternative methods for removing the crust. The first attempt will be to see if the ball itself can either push through or past the crust. If this fails, then water lancing will probably be the next option. In any event, the crust must be removed so that it does not interfere with the measurements.

Lower the ball at constant velocity (1 cm/s) for 20 cm while recording data. We should observe that the apparent weight of the ball changes by about 12 N as the ball travels from the dome space completely into the fluid. The spatial midpoint of this gradual change in cable tension marks the level of the fluid, and that level should be recorded on a data sheet. If the change is much larger than 12 N, then possibly the ball is either partially or totally supported by a crust layer. The DACS camera should be used to verify the condition. Steps should be taken to position the ball past the crust layer. Possible tactics include repeated high velocity (1 m/s) impacts of the ball with the crust or perhaps water lancing of the crust. It is essential that the ball travel into the liquid region beyond the crust. Lower the ball at 1 cm/s until the ball is 30 cm below the bottom of the crust layer. As the ball is falling, observe and record the drag force data. If there is a substantial drag, it may be due to friction between the cable and a portion of the crust. As much as possible utilize the DACS camera to help in making a determination. If the crust is impeding the cable, take steps to eliminate the problem. There is little point in continuing unless the cable is free from any influence due to the crust.

Perform a static density measurement. Now a series of repeated measurements will be obtained from this location throughout the entire depth of the tank. We will perform measurements at four

velocities: 0.1, 1.0, 3.0, and 10.0 cm/s. These velocities are chosen to span as wide a velocity range as is reasonable practical, thereby providing data over a similarly broad range of strain rate. A minimum of three velocities are required in order to reduce the data in terms of a three-parameter model. A complete set of experiments will require 120 cm of distance in the fluid (30 cm for each velocity). An implicit assumption in the reduction of the data will be that the fluid can be characterized by the same model parameters over the entire 120-cm distance spanned by a set of measurements. This assumption may not necessarily hold true for the entire depth of the waste. One means of observing changes which occur over a smaller distance scale is to group contiguous sets of data obtained at four (or three) velocities and perform essentially a running average over 120 cm (or 90 cm) every 30 cm.

Starting with the ball at about 30 cm beneath the bottom of the crust, lower the ball at 0.1 cm/s for 1 cm and at the highest data rate (100 samples/s). This step is taken to obtain the initial transient force spike which occurs during the initiation of ball movement and provides an independent estimate of the fluid yield stress. This step will be repeated at the beginning of each drop into undisturbed fluid. Now lower the ball at 0.1 cm/s for 30 cm and at standard data collection rates (15 samples/s). Retrieve the ball at the same speed. Repeat these measurements. From the graphic display, determine if there is any measurable change in the drag force between the two experiments. If a change is observed, repeat the experiment a third time and a fourth time if necessary. When these measurements are done, the ball should be back at its original location, about 30 cm beneath the crust surface. Increase the velocity to 1.0 cm/s and repeat the experiment twice. Repeat the procedure (i.e., two complete runs) at 3.0 and 10.0 cm/s velocities. The point of these measurements is to observe if the fluid changes character as a result of the shearing caused by the ball. Changes can be attributed possibly to mixing or to history dependent behavior (such as thixotropy). Also, by obtaining data at four velocities, some average character for the fluid in the 30-cm section should be obtainable. Lower at 1 cm/s for 30 cm and obtain a static density measurement. We are now at the lower point of the first set of experiments (the fluid immediately beneath the ball has yet to be probed) and are ready to repeat measurements with a different initial velocity. We first perform the drop test at 0.1 cm/s for 1 cm. We then repeat all measurements but start at 1 cm/s velocity (we perform up to four experiments at this velocity) and then proceed to 5.0, 10.0, and 0.1 cm/s. We then lower the ball 30 cm and perform another static density measurement. We are now ready to perform experiments at the third velocity, 3.0 cm/s. After the initial drop test at 0.1 cm/s for 1 cm, the exact same procedure is followed, with an initial velocity of 3.0 cm/s followed by 10.0-, 0.1-, and 1.0-cm/s velocity experiments. After lowering the ball and obtaining another static density measurement, the same procedure is followed with the velocity sequence of 10.0, 0.1, 1.0, and 3.0 cm/s. We then lower the ball 30 cm and obtain another density measurement. At this point a complete sequence has been obtained and we are ready to repeat the entire process again for the next 120 cm of waste. In such a fashion we should work our way downward through the entire tank.

It may happen that the drag force on the ball will increase as we proceed deeper into the waste such that it is no longer possible to obtain high velocities such as 10 cm/s with only gravity acting in the downward direction on the ball. If this event occurs, it becomes necessary to reduce our velocity range. From the data we should be able to determine a reasonable estimate of the free-fall terminal velocity and then set a new upper limit which is somewhat less than this velocity. In such a case, the similarity between the upwards travelling experiments and the downwards travelling experiments will be broken. Only the velocities of the falling experiments need be adjusted and we will maintain the same velocity range for the retrieval measurements. If the free-fall terminal velocity falls below 1 cm/s, then it will be difficult to obtain sufficient data over a wide enough range of strain rate to

adequately produce a rheological curve for the fluid, at least for the falling ball case. When this condition is reached, it is probably best to terminate the falling-ball experiments as described above. Choosing the constant force mode of operation and setting the force as low as possible, we will simply record the free-fall velocity for the falling ball case. Retrieval experiments will be conducted as before, however, so we will still be able to obtain a rheological curve from these data. Density measurements will be obtained at 30 cm intervals just as above.

It is planned that all experiments will be conducted over the same distances, namely 30 cm, and an implicit assumption is that this distance will be sufficient for obtaining a steady state condition. Laboratory experiments suggest that this distance will be sufficient, but these tests were not complete and the tank waste may not behave like the chemical simulants used in laboratory testing. For instance, no tests were performed at a ball velocity of 10 cm/s, nor were any balls greater than 5 cm in diameter used. If in the field we observe in any test that 30 cm is not a sufficient pull distance to achieve steady state then we will increase the distance to perhaps 60- or 90-cm. It may be that conditions are such that we never achieve steady state, in which case we will have to deal with reducing transient data, which will probably be a formidable task.

If the condition occurs where the ball simply will no longer fall through the waste at any velocity, then we will terminate the downwards travelling phase of the experiments and proceed with the retrieval phase of the measurements. Upon completion of the retrieval experiments, a decision will be made as to the viability of water lancing in order to obtain data from deeper in the tank.

A complete set of data obtained over 120 cm will require from about 30 minutes to 60 minutes to obtain, depending on the exact velocity sequence which is followed. If we assume an average time of 45 minutes per set, it will require about 6 hours to perform a complete profile of the tank from top to bottom. Retrieval experiments will require about the same time. For planning purposes, 16 hours of operation time should be allowed for a complete set of experiments and personnel should be so advised.

From the experiments above, we should have a very good notion of the ball weight which the fluid will support. If the apparent weight of the tungsten alloy ball never falls below about 80 N (measured), then a steel ball of the same diameter will also fall through the waste. Subsequent experiments conducted at later dates should then be performed using a steel ball rather than the tungsten alloy ball. Use of the steel ball allows for use of a more sensitive load cell, such as the 15- or 25-lb full-scale load cell. The advantage gained from this configuration will be most evident in the determination of the fluid density, which can then be reliably determined to within 1%. Determination of model parameters may or may not be improved, but measurement capabilities towards lower viscosities and yield stresses should result. If the steel ball will sink under gravity through most of the tank, we can conclude that the fluid viscosity and yield stress are lower than the upper limits determined to date. An experimental procedure similar to the one described above should be followed.

The above experiments are conducted with the ball generally progressing in the downwards direction, although experiments with the ball in retrieval are performed along with the falling ball tests. A similar set of experiments will be performed with the ball generally heading in the upwards direction. These experiments can commence at any time after the falling-ball experiments are concluded. Experiments with the ball in retrieval will provide essentially the same information as the falling-ball experiments. The time-dependent behavior of the fluid can be probed by a comparison of results

obtained for both sets of experiments. For example, if the fluid recovers its original characteristics within several hours after the initial passage of the ball through the waste, we should be able to observe this behavior in the retrieval experiments. In addition, a comparison of results may allow some insight into determination of cable drag in the waste. In retrieval the cable leads the ball and is pulled through relatively undisturbed fluid; while in the falling-ball experiments, the cable is always travelling in fluid which has been sheared by the ball. Except for this difference, the experiments will provide basically the same information and, at a minimum, provide a repeat of the falling ball experiments.

The experiments begin by first retrieving the ball 30 cm from its original position, which will be either at the tank bottom or the position of deepest travel in the falling ball runs. Obtain density information using the dynamic density mode. Raise the ball at 0.1 cm/s for 30 cm. Lower the ball at the same speed. Repeat these measurements. From the graphic display determine if there is any measurable change in the drag force between the two experiments. If a change is observed, repeat the experiment a third time and a fourth time if necessary. When these measurements are done, the ball should be back at its original location, about 30 cm above its deepest position. Increase the velocity to 1.0 cm/s and repeat the experiment twice. Repeat the procedure (i.e., two complete runs) at 3.0 and 10.0 cm/s velocities. The point of these measurements is to observe if the fluid changes character as a result of the shearing caused by the ball. Changes can be attributed possibly to mixing or to shear-dependent behavior (such as thixotropy). Also, by obtaining data at four velocities, some average character for the fluid in the 30-cm section should be obtainable. Raise the ball at 1 cm/s for 30 cm and obtain a density measurement. We are now at the upper point of the first set of experiments (the fluid immediately above the ball has yet to be probed) and are ready to repeat measurements with a different initial velocity. We repeat all measurements but start at 1 cm/s velocity (we perform up to four experiments at this velocity) and then proceed to 5.0, 10.0, and 0.1 cm/s. We then raise the ball 30 cm at 1 cm/s and perform another density measurement. We are now ready to perform experiments at the third velocity, 3.0 cm/s. The exact same procedure is followed, with an initial velocity of 3.0 cm/s followed by 10.0-, 0.1-, and 1.0-cm/s velocity experiments. After raising the ball and obtaining another density measurement, the same procedure is followed with the velocity sequence of 10.0, 0.1, 1.0, and 3.0 cm/s. We then raise the ball 30 cm at 1 cm/s and obtain another density measurement. At this point a complete sequence has been obtained and we are ready to repeat the entire process again for the next 120 cm of waste. In such a fashion we should work our way upwards through the entire tank.

After completion of the retrieval experiments another short set of experiments should be performed. These experiments are done in order to obtain some information about cable drag. Starting at 1 cm/s velocity, lower and raise the ball through the entire depth of the tank four separate times. Repeat the procedure at 3- and 10-cm/s ball velocities. If there are regions over which the drag force varies linearly with pull or fall distance we can perhaps obtain an estimate of the contribution due to drag on the cable.

It should be clear that the rising ball experiments are exactly the same as the falling-ball experiments, except performed in the opposite direction. The same contingencies will apply in case the ball will not drop at the desired speeds. Experiments will terminate when we have reached a position within 30 cm of the bottom of the crust. The time required to perform a complete set of experiments will be very similar to the time taken to perform the falling-ball tests, estimated to be about 6 hours. If experiments are concluded and there is no desire to obtain more data, the ball should be retrieved back into the ball rheometer container. In retrieval through the dome space, the position of the fluid

surface should be determined and the apparent weight of the ball should be measured at the reference position just above the fluid surface. If differences are noted these may indicate material buildup on the ball or cable or instrumental drift. In addition to rechecking these values, pulley friction should again be measured. The procedures for accomplishing these measurements are identical to those described earlier except that the waste surface location is determined with the ball going from fluid into the dome space. There is no need to repeat the initial measurement of the ball weight with the cable almost fully retracted. Rather, the ball should simply be returned to the home position. Extreme care should be taken as the ball approaches the riser pipe from below and full use of the DACS camera should be taken.

In the event that more data are desired later on, the ball should be stored in the rheometer enclosure unless retrieval data are needed, in which case the ball should be left as near to the bottom of the tank as possible.

4.0 Reduction of Data

Experimental work with chemical simulants along with rheological data obtained previously with core samples from tank 101-SY have allowed the conclusion that the waste fluid can be modeled approximately as a history dependent generalized Bingham plastic fluid. In reality, many fluids are very complex in their fluid properties and cannot be exactly described by any of the standard fluid models. Fluid models have as their primary advantage a mathematical simplicity and, by virtue of parameters contained within these models, allow a description of the fluid in terms of these parameters. For instance, in the generalized Bingham fluid model, the parameters are termed the consistency index, the power law index, and the yield stress. These parameters only have meaning within the context of the model, and their relationship to fundamental physical parameters is not well established. It is not particularly important for the fluid model to describe the fluid except in a general sense. In our reduction of the data obtained with the ball rheometer, we will initially attempt to describe the fluid in terms of a generalized Bingham fluid, at least for regions where some mixing of the waste has occurred. Such a choice allows the great convenience of a fluid description with a very small number of parameters (three), and a more general reduction is probably not possible or advisable. A model which included all of the correct physics would better characterize the waste but inclusion of this type of model into other codes would be very difficult. For very general fluids, notions such as viscosity and yield stress begin to lose their meaning, and we then have to invent other terms with which to describe the fluid. A clearer picture of the fluid behavior would not likely result from such an endeavor, and informing data users (who want to hear terms such as viscosity) of the fluid properties could become quite confusing. However, it should be remembered that our description of the fluid will always be somewhat approximate.

The data reduction strategy outlined here represents our best present ideas of how to go about analysis of the drag force data. In fact the methods and models used to reduce the actual data may not be completely determined until these data are collected. Perhaps a generalized Bingham model will simply not be appropriate to adequately describe all of the waste. We are presently unsure of the best manner in which to account for drag on the cable, and laboratory investigations are continuing on this problem. Methods for reducing the data will evolve once data are collected in the field.

For a generalized Bingham fluid, the shear stress (τ) is related to the shear rate ($\dot{\gamma}$) by the following equation (Chhabra 1993):

$$\begin{aligned}\tau &= \tau_o + m \dot{\gamma}^n \text{ for } \tau > \tau_o \\ \dot{\gamma} &= 0 \text{ for } \tau \leq \tau_o\end{aligned}\quad (5)$$

Thus, there are three parameters in the model: the yield stress (τ_o), the consistency index (m), and the power law index (n). If $n=1$ then m is the viscosity and the fluid is a Bingham fluid. If $\tau_o = 0$ and $n=1$, then the fluid is Newtonian; while if $\tau_o = 0$ and $n < 1$, the fluid is a power law fluid. It is seen that the generalized Bingham fluid model contains as subsets three other fluid models. The relationship between the drag coefficient (C_d) and the drag force experienced by a ball of diameter (d) traversing the fluid at velocity (V) is given by, in the case of Newtonian fluids,

$$F_d = \frac{1}{2} \rho C_d V^2 \left(\frac{\pi}{4} d^2 \right) \quad (6)$$

where, in the limit of small Reynolds number, the drag coefficient is given by

$$C_d = \frac{24}{Re} \quad (7)$$

For non-Newtonian fluids, the typical approach has been to utilize Eq. 6 using a modified drag coefficient which depends on dimensionless model parameters such as the Reynolds number or the Bingham number. We will adopt the results of Attapattu (Chhabra 1993), who gives the Reynolds number as

$$Re = \frac{\rho V^{2-n} d^n}{m} \quad (8)$$

and the Bingham number as

$$Bi = \frac{\tau_o}{m \left(\frac{V}{d} \right)^n} \quad (9)$$

Attapattu relates the drag coefficient to a dynamic parameter by

$$C = \frac{24}{Q} \quad (10)$$

where

$$Q = \frac{Re}{1 + KBi} \quad (11)$$

Attapattu states that the correlation is valid over 8 orders of magnitude in the dynamic parameter. The parameter K is chosen so that, for any particular set of measurements, Eq. 10 is valid (i.e., the coefficient remains 24). This parameter probably depends on fluid rheology and is not a constant; however, Attapattu gives a value of very nearly one. If we assume that the power law coefficient is very nearly unity and further assume that the lowest viscosity of interest will be about 10 poise and that the lowest yield stress will be about 100 dynes/cm², we can estimate the range of the Reynolds number and the dynamic parameter for our in-tank experiments. Reynolds numbers range from about 0.1 (lowest velocity) to 10 (highest velocity) while the dynamic parameter ranges from 0.004 to about 2, if we estimate that K=1 in Eq. 11. The dynamic parameter is within the applicable correlation range given by Attapattu. Substituting for all quantities, we find that the drag force on the ball is given by

$$F_d = 3\pi m d^{2-n} V^n \left(1 + K \frac{\tau_o d^n}{m V^n} \right) \quad (12)$$

There are three unknowns in Eq. 12; thus, if we obtain drag force data at three or more different velocities, we can solve for all three parameters. Eq. 12 will be the basic theoretical equation by which we relate measured drag force on the ball to the fluid properties. For $n = 1$ and $Bi = 0$ (i.e., $\tau_o = 0$), the above expression reduces to the well-known result for Newtonian fluids in the limit of small Reynolds numbers.

Eq. 12 can be rewritten as

$$F_d = 3\pi d^2 \left(m \left(\frac{V}{d} \right)^n + K \tau_o \right) \quad (13)$$

or

$$F_d = M \left(\frac{V}{D} \right)^n + B, \quad (14)$$

where M is a constant and B is nearly constant if K does not vary significantly over the range of shear rates spanned by the data. One method for determining the parameters M and B is to plot the drag force data against $(V/d)^n$ and then perform a least squares best fit of the drag force to a straight line where n is varied. The best fit gives n, and the resulting slope and intercept give M and B, from which m and τ_o are determined.

Note that the method outlined for data acquisition allows some choices for the reduction of the data. We are obtaining data at four velocities rather than three; so if data from all four velocities are considered in the determination of the three model parameters, we will have four equations with three unknowns and the parameters are then overdetermined. A statistical analysis can then be performed

to determine the parameter values which best fit each set of data obtained at four velocities. Alternatively, we can take any set of three measurements and determine the model parameters. It may make sense to fit the data to the model for the lowest three velocities (0.1, 1.0, and 3.0 cm/s) and then the highest three velocities (1.0, 3.0, and 10.0 cm/s) and compare results for the parameters. There should be reasonable agreement if the model is fairly representative of the fluid. The best average representation should be obtained by full consideration of all four data sets, however.

We can obtain a characterization of the fluid for each 30-cm increment, since multiple measurements at different velocities will be obtained for each increment. These characterizations will describe the fluid after it has been well sheared by the ball. Only the data obtained as the ball first traverses any 30-cm increment is representative of the undisturbed fluid. Clearly, we will have data at only one velocity for this case.

For the undisturbed fluid, drag force data obtained at four velocities over a distance of 120 cm will be reduced to obtain the average fluid properties over that distance. Since the ball velocities will be chosen sequentially, we can reduce any contiguous set of four separate measurements (or, for that matter, any set of three measurements). Thus, while the results represent data obtained over 120 cm, we can update the results every 30 cm.

There appears to be no satisfactory method to determine drag force on the cable other than by calculation. Given that the fluid properties are known, the drag on the cable can be calculated. For each 30 cm distance in the fluid, the drag on the cable will always be much smaller than the drag on the ball. One means of calculating the cable drag is to first reduce the data, assuming there is no drag, and arrive at the fluid description. Then we correct the apparent drag on the ball to account for the drag on the cable and recalculate the fluid properties (actually, the model parameters). In order to use this method we need to understand the relationship between fluid rheology and the drag on the cable. We do not presently have this knowledge, but laboratory studies are continuing towards a solution to this problem. Assuming that we can account for cable drag, continued iteration will produce a consistent set of model parameters; and since the contribution of cable drag is incrementally small, convergence should occur very quickly. When the ball is subsequently lowered, we need to include the integrated cable drag calculated in all previous steps as a part of the correction. In this manner we can determine the cable drag just as we determine the model parameters, 30 cm at a time. We cannot, for each 30-cm increment, determine the cumulative drag on the cable from the single measurement. This method will only work if the data are reduced in a particular order, from the top of the fluid to the bottom.

Reduction of static measurement data to obtain fluid density is straightforward. Again, however, the data must be reduced in order, from the top of the fluid to the bottom, in order to perform the integral for the contribution to the buoyancy force due to the cable. The contribution due to the cable will be a small correction. Density measurements in regions of the fluid with a high-yield stress may be difficult, owing to residual stresses in the fluid which will contribute to the apparent weight of the ball. For this reason we will obtain density measurements in regions of the fluid which have already been well sheared by the ball.

5.0 Expected Accuracies

The accuracies we can expect to obtain in the determination of model parameters has been discussed in a previous report (Shepard et al. 1994), where it was assumed that a Bingham model for the fluid would be appropriate. The only difference between the model used in that report and the one used here is the addition of a power law index. This extra degree of freedom and the expected error in measuring the drag force on the ball will allow substantial errors in the calculated quantities, possibly making it difficult to differentiate the power law index from one. Experiments with well-mixed simulants have shown that the power law index is fairly close to 1.0, which is the Bingham fluid value. Given the restricted range of strain rates which will be experimentally available, it will be difficult to determine a power law index different from 1 unless it is much different from 1. Precise determination of this index is made especially difficult due to the expected large uncertainty in the effective viscosity. Therefore the analysis presented in the earlier report gives a realistic picture of the accuracies we can expect if we adopt a generalized Bingham fluid model. The drag on the ball is expected to be due primarily to yielding of the fluid with a small contribution due to viscous drag. As a result, it is expected that the fluid yield stress will be determined to good precision but there will be considerable uncertainty in the viscosity (perhaps as much as 50 to 100%).

The effect of cable drag as a source of uncertainty was not discussed in detail in the earlier report. It has since been recognized that this factor represents the most important and least accessible correction to the drag force data. The current plan is to attempt to calculate the correction. We will also perform in-situ experiments aimed at estimating cable drag. While the error in our calculation or measurement of cable drag may be incrementally small, the cumulative errors may be substantial, especially if we consistently overestimate or underestimate the cable drag contribution. For low Reynolds numbers (less than about 1) the total error in the cable drag force will affect the determination of the yield stress, but will introduce no significant error into the viscosity. It will appear as a systematic velocity-independent error in the reduction of any group of four data sets. Since the determination of viscosity relies on the velocity dependent part of the drag force, it will not be affected by the constant offset due to miscalculation of the cable drag. The yield stress is determined from the velocity independent part of the drag force and, therefore, the yield stress will reflect the error in the cable drag term. The error is estimated to be less than about 25%, based on the total expected cable drag as compared to drag on the ball. For higher Reynolds numbers the picture becomes more complicated because the drag on the ball due to yield stress may not be constant. We can probably expect Reynolds numbers of around 10 in actual experiments. In this case increased uncertainty in the calculated viscosities will probably result.

Errors in the determination of the density will depend primarily on the load cell used for the measurements. The load cells have a nominal rated accuracy of 0.1% of full-scale reading. If we use a 100 lb (450 N) range load cell, then the resolution is about 0.45 N. The fluid density is expected to range between about 1.4 and 1.6 g/cm³ (a rather limited dynamic range), so that the expected buoyancy force will be around 5.9 N. The pulley arrangement results in a doubling of this force, so we expect that we can measure density to within about 4% of true value with this load cell. As can be seen above, the expected total change in density will be about 13% of the mean value, and so resolution of 4% will produce relatively coarse results. Resolution on the order of 1% would be highly desirable, especially in view of the fact that the density data may provide the most reliable and interpretable information concerning the action of the mixer pump. It would be advantageous to use a

more sensitive load cell (15- or 25-lb full-scale) which would allow for the desired accuracy. If the initial experiments demonstrate that drag forces are sufficiently small to allow use of more sensitive load cells, measurements will be repeated using such load cells and perhaps a lower density (steel) ball.

6.0 Conclusions

We have presented a plan for the collection of in-situ data with the ball rheometer and the subsequent reduction of these data. This plan is fairly detailed and, if followed, should allow the extraction of meaningful information about the waste fluid contained in Tank 101-SY. The plan implicitly assumes that we simply wish to determine fluid rheology and density from the top of the waste to the bottom, and is presented to accomplish this goal. Contingencies have been described to account for as many possibilities as could be imagined. It should be remembered that this plan is by no means complete or all inclusive. Only time and careful planning will determine the breadth of measurements we wish to make with this instrument. It is expected that it will be called upon to provide extended service as a diagnostic tool, since the availability of in-situ measurement instruments for the tanks is quite limited. It should be remembered that the ball rheometer can only directly measure fluid rheology and density, nothing more. The interpretation of what these quantities suggest, especially in judgment of mixer pump performance, will depend on other factors involving the use of the mixer pump.

We will reduce the drag force data to obtain fluid rheological parameters by assuming that the fluid can be adequately described with the generalized Bingham fluid model. It is expected that this model should be applicable, based on experimental results with chemical simulants of the waste. If actual data obtained from the tank indicates that this model is quite inappropriate, then the fluid model question will be revisited. Data will be obtained at four ball velocities so that determination of the three model parameters can be performed. Both the undisturbed fluid and the "well-mixed" or "highly sheared" fluid will be characterized.

We do not expect to obtain highly accurate rheological values, with expected errors of perhaps 50% for the viscosity and 25% for the yield stress. Viscosities below about 10 to 100 poise will be difficult to measure, as discussed in previous reports. Data users have consistently reported that such accuracies are sufficient. Unless residual stresses due to the yield stress of the fluid present difficulties, we expect to be able to make fairly accurate measurements of density, within 1% error if a low-range load cell can be used.

7.0 References

Chhabra, R. P. 1993. *Bubbles, Drops, and Particles in Non-Newtonian Fluids*, (CRC Press, Boca Raton, FL).

Pasamehmetoglu, K. O., C. Unal, and J. Edwards. December 1993. *The Evaluation of Methods for Rheology Measurements of the Waste Contained in Hanford Tank 241-SY-101*. Los Alamos National Laboratory Report LA-UR-93-4300.

Shepard, C. L. 1994. *Report on Data Requirements and Hardware Selection for In-Situ Ball Rheometer*, PNL-10171. Pacific Northwest Laboratory, Richland, Washington.

Shepard, C. L., J. B. Colson, K. O. Pasamehmetoglu, C. Unal, J. H. Edwards, and J. Abbott. 1994. *Theory of Operation for The Ball Rheometer*, PNL-10240. Pacific Northwest Laboratory, Richland, Washington.

Appendix A

Experiments Performed at Pacific Northwest Laboratory and Los Alamos National Laboratory

Figures

1. Diagram of the Ball Rheometer System Showing the Ball, Cable, Take-up Spool, Pulley, and Load Cell.	A.2
2. Forces Acting on a Ball in Motion in a Fluid	A.3
3. Forces Acting at the Load Cell	A.4
4. Plot of ball drag force measured with chemical simulant with the 1 inch ball first falling and then rising at 0.5 cm/s	A.8
5. Plot of ball drag force measured with chemical simulant with the 2 inch ball first falling and then rising at 0.5 cm/s	A.9
6. Plot of ball drag force measured with carbopol with the 0.5 inch ball first falling and then rising at 0.2 cm/s	A.9
7. Plot of the ball drag force measured with carbopol with the 1 inch ball first falling and then rising at 0.2 cm/s	A.10
8. Plot of the ball drag force measured with carbopol with the 2 inch ball first falling and then rising at 0.2 cm/s	A.10
9. Plot of the ball drag force measured with bentonite clay with the 2 inch tungsten ball falling at 0.2 cm/s	A.11
10. Plot of the ball drag force measured with bentonite clay with the 2 inch tungsten ball rising at 0.2 cm/s	A.11
11. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the chemical simulant at 0.5 cm/s	A.12
12. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the carbopol fluid at 0.5 cm/s	A.13
13. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the bentonite clay at 0.5 cm/s	A.13
14. Plot of the ball drag force measured with the chemical simulant with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s	A.16
15. Plot of the ball drag force measured with carbopol with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s	A.16
16. Plot of the ball drag force measured with bentonite clay with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s	A.17
17. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through the chemical simulant at 0.5 cm/s	A.18
18. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through carbopol at 0.5 cm/s	A.18
19. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through bentonite clay at 0.5 cm/s	A.19
20. Rheogram for carbopol as measured with the Bohlin rheometer	A.23
21. Rheogram for bentonite clay as measured with the Bohlin rheometer	A.23
22. Rheogram for chemical simulant as measured with the Bohlin rheometer	A.24

Tables

Table 1. Drag Force per Unit Length on Cable	A.14
Table 2. Drag Forces on Ball	A.15
Table 3. Drag Force on Ball with Different Cables	A.20
Table 4. Pull Distances to Steady-State Flow	A.21
Table 5. Interface-Effects Distance	A.22
Table 6. Comparison of Experimental Results Obtained with Ball Rheometer and Laboratory Rheometer for Three Simulants	A.25

Results of Laboratory Experiments in Support of the Ball Rheometer Project

**Chester L. Shepard, Leslie J. Kiriara, M. Andrew Chieda,
Alireza Shekarriz, Guillermo Terrones, Jon Phillips**

Pacific Northwest Laboratory

1.0 Introduction

The ball rheometer is being developed in order to perform in-situ measurements of tank waste rheological properties, initially in Tank 101-SY. Previous reports have described the need for these data (Shepard 1994), rheological measurements of tank wastes (Pasamehmetoglu et al. 1993), and the theory of operation of the ball rheometer (Shepard et al. 1994). In this report we will concentrate on the reduction of the expected load cell data to obtain drag force on the ball and the methods we will employ to determine the waste's rheological properties from the drag force data. The ball rheometer consists of a ball attached to a cable which is wound onto a spool. The system will be installed on a riser pipe through which entry into Tank 101-SY is obtained. The ball can be lowered into the waste or retrieved from the waste by rotation of the spool, which is mechanically connected to electric drive motors. The present ball is comprised of a tungsten alloy and is 9.1 cm in diameter and weighs about 16 lb (7.3 kg). It is likely that other balls of similar size but lower density, such as a steel ball, will also be employed. The cable is stranded stainless steel of diameter 0.32 cm (0.125 inches) and has a polyethylene coating. A diagram of the ball rheometer is shown in Figure 1. The ball is deployed into the waste and retrieved by rotation of the take up spool. Typically the ball will be deployed at a constant velocity, which is adjustable over the velocity range from 0.1 cm/s to 100 cm/s. The cable passes over a pulley to which a load cell is attached. The tension in the cable, or actually twice the tension in the cable is measured by this load cell. We will measure the tension in the cable as the ball is being moved through the waste at different velocities. From these measurements, the drag on the ball due to movement through the waste can be determined. The amount of drag depends on the rheology (roughly the yield stress and the viscosity) of the waste fluid, and we are interested in determining the rheology of the fluid. Static force measurements obtained while the ball is at rest in the fluid will allow a determination of the fluid density. We intend to characterize the fluid at all depths within the tank.

The report is organized as follows. In Section 2 we examine the forces involved in measurements with the load cells. The goal is to identify the drag force contribution to the total force measured with the load cell. Not all of these forces will be measurable in the tank, and accurate estimates from laboratory measurements will have to suffice. We will present the results of laboratory tests to determine some of the forces involved in Section 3.

Figure 1. Diagram of the Ball Rheometer System Showing the Ball, Cable, Take-up Spool, Pulley, and Load Cell. The instrument fastens to a riser pipe through which entry into the waste tank is obtained.

2.0 Determination of Drag Forces on the Ball

The load cell measures the total tension in the cable to which the ball is tethered plus frictional forces in the pulley plus the weight of the pulley assembly. Only part of the total force is due to viscous drag on the ball. It is imperative that we be able to account for all of the forces involved and separate out the drag force contribution, since this force can be related to the rheological properties of the fluid. We will begin with a theoretical description of the ball rheometer system.

2.1 Theory

We desire to understand and identify the forces which play a part in the Ball Rheometer. First consider the forces acting on the ball in the fluid and let upward forces be positive while downward acting forces are negative. Assume that the ball is falling at some constant velocity. The forces are shown in Figure 2.

Figure 2. Forces Acting on a Ball in Motion in a Fluid

where

- T = tension in the cable at the ball
- D_b = drag force on the ball due to the liquid
- B_b = buoyancy force on the ball due to the liquid
- W_b = weight of the ball in air

The equilibrium condition is

$$T + D_b + B_b - W_b = 0 \quad (1)$$

Now consider the forces acting at the load cell, as shown in Figure 3.

Figure 3. Forces Acting at the Load Cell

where

- T' = tension in cable at pulley
- η = friction in pulley
- W_p = weight of pulley and other components
- F_c = counterbalance force
- R = force with which the load cell pushes back. This is the load cell reading.

The equilibrium condition is

$$R + F_c = 2T' - \eta + W_p \quad (2)$$

In general the tension at the pulley does not equal the tension at the ball.

$$T' = T + W_c - D_c - B_c \quad (3)$$

where

- W_c = weight of deployed cable
- D_c = total drag force on cable

B_c = buoyancy force on cable

Using Eq. (3) and substituting for T' in Eq. (2) gives

$$R + F_c = 2[T + W_c - D_c - B_c] - \eta + W_p \quad (4)$$

Using Eq. (1) and substituting for T in Eq. (4) gives

$$R + F_c = 2[W_b - D_b - B_b - D_c - B_c + W_c] - \eta + W_p \quad (5)$$

or, upon rearrangement

$$R = 2\left[\left(W_b - \frac{F_c}{2}\right) - (D_b + B_b) - (D_c + B_c - W_c)\right] - \eta + W_p \quad (6)$$

Eq. (6) shows that the counterbalance force can be viewed as equivalent to using a lighter ball of weight $(W_b - F_c/2)$. The cable-related force terms, D_c , B_c , and W_c , are not constant but will depend linearly on the amount of cable deployed in the waste.

Let z_o be the distance at which the ball is just above the surface of the waste. At this location,

$$R_o = 2\left[\left(W_b - \frac{F_c}{2}\right) + W_c(z_o)\right] + W_p$$

At some distance $z > z_o$, we have

$$R = R_o - 2[(D_b + B_b) + (D_c + B_c - W_c(z))] - \eta$$

If we assume

$$D_c = \int_{z_o}^z A(z') dz'$$

$$B_c = \int_{z_o}^z B(z') dz'$$

$$W_c = C(z - z_o)$$

where C is a constant and A and B depend on position in the waste, then we can write

$$\Delta R_f = R - R_o = -2 \left[(D_b + B_b) + \int_{z_o}^z (A(z') + B(z')) dz' - C(z - z_o) \right] - \eta \quad (7)$$

If we obtain the load cell measurement at z_o and concern ourselves with load cell measurement differences $(R - R_o)$, then the situation is simplified somewhat. Solving Eq. (7) for D_b gives

$$D_b = - \left[B_b + \int_{z_o}^z (A(z') + B(z')) dz' - C(z - z_o) + \frac{\eta + \Delta R_f}{2} \right] \quad (8)$$

Thus, in order to determine the actual drag force on the ball, several parameters must be determined independently. These include:

- the buoyancy of the ball, which may depend on waste type
- the buoyancy on the cable
- the drag on the cable
- the weight of the cable
- the friction in the pulley, which may depend on velocity and load.

Eq. (7) and (8) hold for a falling ball. For a rising ball, the drag forces on the ball and cable as well as the pulley frictional force reverse in direction. Eq. (6) becomes

$$R = 2 \left[\left(W_b - \frac{F_c}{2} \right) + (D_b - B_b) + (D_c - B_c + W_c) \right] + \eta - W_p \quad (9)$$

Following the same procedure as before, Eqs. (7) and (8) become, for a rising ball, respectively,

$$\Delta R_f = R - R_o = 2D_b - 2B_b + 2 \int_{z_o}^z (A(z') - B(z')) dz' + 2C(z - z_o) + \eta \quad (10)$$

$$D_b = B_b + \frac{\Delta R_f - \eta}{2} - \int_{z_o}^z (A(z') - B(z')) dz' - C(z - z_o) \quad (11)$$

Equations (8) and (11) relate the drag force on the ball to other quantities. We will use Eq (7) and (10) in some of the analysis of data which follows. With the load cell we will measure ΔR . Pulley friction can be determined from laboratory measurements, as can the cable weight per unit length.

Therefore only the buoyancy forces and the drag on the cable are not well known prior to deployment of the ball rheometer. Values for these forces may depend on the fluid properties and therefore cannot be determined ahead of time. We have performed laboratory experiments with several fluids in order to determine representative values for these forces, but their actual determination will have to be made in the tank if possible.

3.0 Results of Laboratory Investigations

Experiments were performed with several fluids to determine the ranges of parameters which we might expect in tests which will be performed in the tanks. Quantities such as the buoyancy forces and drag forces were measured with simulants which included a chemical simulant, Bentonite clay, and carbopol. The experimental arrangement was our standard configuration. The fluids were held in a 5 gallon bucket so that total fluid depth was about 30 cm and the bucket diameter was also about 30 cm. In most tests a steel ball was suspended over a pulley with a thin stainless steel braided cable normally used and marketed for fishing applications. The pulley and ball were supported by a load cell which measured total tension in the cable. These results are presented in this Section.

3.1 Buoyancy Force on the Ball

For static measurements in a material with a yield stress the buoyancy force on the ball may not necessarily be given by the change in the apparent weight of the ball, since the ball can be partially supported by the yield stress. In dynamic measurements it is not clear if the buoyancy is simply the weight of the displaced fluid, although it appears difficult to describe it otherwise. Due to this uncertainty, we performed experiments to determine the dynamic buoyancy of the fluids. The buoyancy force on the ball is most easily determined from total force measurements obtained while the ball is rising and while the ball is falling. For these tests we used a very thin wire for a cable, so that the drag, weight, and buoyancy of the cable could be neglected. Adding Eqs. (7) and (10) with the cable related terms set to zero we obtain

$$B_b = \frac{-(\Delta R_f + \Delta R_r)}{4} \quad (12)$$

Some of the relevant data are shown in Figures 4 through 8 for 0.5-, 1.0-, and 2.0- inch balls and for the chemical simulant and carbopol. All of the data show buoyancies, from Eq. (12), which are consistent with results obtained using Archimedes Principle. The measured densities of the chemical simulant and carbopol are 1.55 g/cm³ and 0.96 g/cm³ respectively. From Archimedes Principle we therefore expect buoyancies of 13.3 g and 106 g for the 1- and 2-inch balls in the chemical simulant and buoyancies of 1.0 g, 8.2 g, and 66.0 g for 0.5-, 1- and 2- inch balls submersed in carbopol. The data shown in these figures indicate buoyancies in close agreement. For the chemical simulant we determine buoyancies of 12.5 g and 103 g for the 1- and 2-inch balls while for the carbopol we determine buoyancies of 1.0 g, 8.5 g, and 67.5 g. We can conclude that the dynamic buoyancy force in these fluids is given by the weight of the displaced fluid.

Figure 4. Plot of ball drag force measured with chemical simulant with the 1 inch ball first falling and then rising at 0.5 cm/s

In the data presented in Figures 4-8, the ball is initially in air and is then lowered into the fluid until the bottom of the container is approached. The ball is then retrieved at the same velocity. In order to apply Eq. (12) a reference value is needed (R_0). This value is the apparent weight of the ball prior to entering the fluid. For example in Figure 4, this value is 70 g in one case and 72 g in another.

Similar high quality data are not available for the Bentonite clay mixture because this fluid would not allow the free sinking of any of the test balls. This fluid had a very high yield stress, and its density was 1.05 g/cm³. The data which are available, shown in Figures 9 and 10, are consistent with the notion that the buoyancy is given by Archimedes Principle. Some comment is necessary to describe how these data were collected. Since the ball, which was formed from tungsten powder and had a diameter of 1.925 inches, would not freely sink, weights were attached to it using a platform and a thin hollow rod. One end of the rod rested on the ball while the other end held the weights on a platform which was well above the surface of the clay mixture. The ball was then lowered into the waste at 0.2 cm/s. The reference weight shown in Figure 9 was about 2200 g. Before retrieving the ball, the platform, weights, and rod were removed. Then the clay was moved to fill in the hole left behind while the ball was falling. The thin rod has little effect on the total drag while the ball is falling because of the large hole which the ball leaves in its wake. Very little material comes in contact with the rod. Therefore, in Figure 10, the weight of the platform and other weights (2044 g) should be added to the drag curve to compensate for their removal and to allow its use with Figure 9. As the plots show there is a large uncertainty in the buoyancy obtained from these data, since stable drag forces were not obtained. Using reasonable values from the plots we obtain a buoyancy of 64 g for the ball, while the expected value is 66 g. The uncertainty in the value obtained from the plots is about 15 g. Based on the results of measurements with all three fluids and especially the chemical simulant and carbopol, which also have a yield stress, we conclude that the buoyancy is given by the weight of the displaced fluid.

Figure 5. Plot of ball drag force measured with chemical simulant with the 2 inch ball first falling and then rising at 0.5 cm/s

Figure 6. Plot of ball drag force measured with carbopol with the 0.5 inch ball first falling and then rising at 0.2 cm/s

Figure 7. Plot of the ball drag force measured with carbopol with the 1 inch ball first falling and then rising at 0.2 cm/s

Figure 8. Plot of the ball drag force measured with carbopol with the 2 inch ball first falling and then rising at 0.2 cm/s

Figure 9. Plot of the ball drag force measured with bentonite clay with the 2 inch tungsten ball falling at 0.2 cm/s

Figure 10. Plot of the ball drag force measured with bentonite clay with the 2 inch tungsten ball rising at 0.2 cm/s

The verification that the buoyancy force is given by the weight of the displaced fluid regardless of fluid type allows the calculation of both B and $B(z')$ in Eqs. (8) and (11), since the fluid density will be measured as a function of ball position.

3.2 Drag Forces on the Cable

Drag force on the cable was measured in a relatively simple manner. A length of cable was placed vertically in the fluid and extended downwards to the bottom of the container. Three cable diameters were used, 0.013-, 0.125-, and 0.250-inches. Weighted stainless steel tubing was used for the larger sizes while a stiff stainless steel wire cable was used for the small size. The cables were then withdrawn at constant velocity while the drag force was monitored. The slope of the drag force as a function of distance or time (divided by two to account for the experimental arrangement) could then be used to obtain the drag force per unit length of the cable. In the cases of the 0.125- and 0.250-inch cables which have substantial weights, corrections were applied to the data to account for the increase in cable tension due to the withdrawal of the cable from the fluid and into the air, where there is no buoyancy. Representative data are shown in Figures 11 through 13, which show the drag on a 0.125 inch diameter cable at 0.5 cm/s velocity for the three different fluids. The results obtained from all of the data are summarized in Table 1.

For the chemical simulant the drag force on the cable does not seem to depend on the cable diameter or the cable retrieval speed. For the carbopol and Bentonite clay, both diameter and speed are important, but there is no apparent simple correlation. A more thorough discussion of these results

Figure 11. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the chemical simulant at 0.5 cm/s

Figure 12. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the carbopol fluid at 0.5 cm/s

Figure 13. Plot of the drag force on a 0.125 inch diameter cable being withdrawn from the bentonite clay at 0.5 cm/s

Table 1. Drag Force per Unit Length on Cable

Cable Diameter, (inches)	Cable Velocity (cm/sec)		
	0.1	0.5	1.0
	Drag Force (gm/cm)		
	Chemical Simulant		
0.013	0.05	0.04	0.04
0.125	0.09	0.09	0.10
0.250	0.10	0.10	0.09
	Carbopol		
0.013	0.10	0.11	0.12
0.125	0.29	0.52	0.65
0.250	0.98	1.15	1.89
	Bentonite Clay		
0.013	0.52	0.52	0.53
0.125	1.91	4.17	4.03
0.250	3.27	5.71	6.18

will be presented after we discuss results obtained for the fluid rheological parameters. In actual practice in the tank, it is important to establish the drag force on the cable from in-situ measurements.

3.3 Drag Force on Ball

The drag force on balls of diameters 0.5-, 1.0-, and 2.0- inches at velocities of 0.1-, 0.5-, and 1.0- cm/s were measured for all three fluids. Results for the 1 inch ball at 0.5 cm/s velocity are shown in Figures 14 through 16. The results for all of the data are summarized in Table 2. For all fluids the velocity dependence of the drag force is very weak. The dependence on ball size is strong, scaling roughly as the square of the diameter. Both of these factors suggest that the drag force is dominated by the yield stress of the material. It is from data such as these that the model describing the behavior of the fluid must be obtained. The reduction of these data will be described below in the discussion of results obtained with the Bohlin rheometer.

Table 2. Drag Forces on Ball

Ball Diameter, (inches)	Ball Velocity (cm/sec)		
	0.1	0.5	1.0
	Drag Force (grams)		
	Chemical Simulant		
0.5	--	--	--
1.0	1.7	1.8	2.2
2.0	6.4	6.8	7.6
	Carbopol		
	0.5	4.5	6.0
1.0	16	19	22
2.0	75	92	97
	Bentonite Clay		
	0.5	44	48
1.0	138	150	155
2.0	562	600	655

3.4 Cable-Ball Interaction

There has been some concern that operation of the ball in the retrieval mode may lead to measurement errors due to the disturbance of the waste by the cable prior to the passage of the ball through the same waste. Clearly as the cable diameter approaches the ball diameter the drag on the ball will be diminished since the fluid would no longer have significant contact with the ball. However, in the case where the cable diameter is small compared to the ball diameter, which should always be the case, the effect should be very small unless the cable somehow changes the character of the fluid through which the ball will pass. We tested this concern experimentally. If the cable causes very little change in the character of the waste in the retrieval mode, then we should observe that the drag force on the ball plus cable system should equal the drag force on the cable plus the drag force on the ball measured independently. The results for the drag force on the cable and drag force on the ball have been presented above. In the measurements of the drag force on the ball, shown in Table 2, a thin stainless steel cable was used. The drag on this wire is negligible compared to the drag on the ball and so the results shown for drag force on the ball can be taken as due to the ball only. We

Figure 14. Plot of the ball drag force measured with the chemical simulant with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s

Figure 15. Plot of the ball drag force measured with carbopol with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s

Figure 16. Plot of the ball drag force measured with bentonite clay with the 1 inch ball being withdrawn completely from the fluid at 0.5 cm/s

performed experiments where cables of diameter 0.125 and 0.250 inches were attached to 1.0- and 2.0-inch-diameter balls, and drag force measurements were made as these systems were pulled through the fluids at constant velocities. After accounting for the drag force on the cable, the drag forces on the balls were compared to the same drag forces measured with the thin wire. Within experimental error there appears to be no differences. These results suggest that the interaction between cable and ball is negligible and can be neglected.

Results for the 1-inch ball with the 0.125-inch-diameter cable are shown in Figures 17 through 19 for all three fluids and a velocity of 0.5 cm/s. These plots have been corrected to account for the weight and buoyancy of the cable and the manner in which these change as the cable is being withdrawn from the fluid. The drag on the cable accounts for the apparent slope in the curves, and this drag decreases as the cable and ball are withdrawn from the fluid. The drag near the end of the pull where the cable is nearly completely withdrawn from the fluid represents the contribution of the ball to the total drag. It is this drag force which should be compared to the drag force measured when the ball was retrieved with the thin cable. The determination of drag forces from these plots is not simple, due to the fact that experimentally it is advantageous to allow for a flexible zero offset and this advantage was used to the fullest extent here. The results for all of the measurements are shown in Table 3. In nearly all cases the drag forces listed in this table are in close agreement with the corresponding drag forces shown in Table 2. There is no clear trend in the comparison of the data in these two tables. It is seen from Table 3, however, that, on average, the drag force measured with the 0.250 inch cable attached to the ball is somewhat less than the corresponding drag forces measured with the 0.125 inch cable. This would lend some support to the notion that a cable-ball interaction exists. It is clear that the effect, if any, is rather small. The conclusion from these data is that the cable has little influence on the drag force on the ball. For the case of the actual planned in-situ ball rheome-

Figure 17. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through the chemical simulant at 0.5 cm/s

Figure 18. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through carbopol at 0.5 cm/s

Figure 19. Plot of the combined drag force due to 0.125 inch diameter cable and 1 inch ball being pulled through bentonite clay at 0.5 cm/s

ter, where the cable diameter will be 0.125 inches and the ball diameter will be 3.6 inches, any effect should be entirely negligible.

3.5 Effects of Interfaces and Distances Required for Steady-State Flow

The drag force data can be related to expectations based on fluid flow models if the flow is a steady state flow. It requires some distance from the start of ball motion before steady state flow conditions are reached. This distance could conceivably depend on the fluid rheological properties as well as ball diameter and velocity. It is important to know these distances so that the distance over which a ball must be pulled or dropped at a constant velocity before steady state is achieved can be estimated. The planning of experiments is aided with this information. In addition, the distance required for steady state flow to develop may be useful for the estimation of fluid properties, although this possibility has yet to be explored to any degree greater than simple speculation. In actual practice, the steady state pull distance will be determined empirically. It may provide some qualitative information about the nature of the fluid which is independent of the drag force measurements. However, fluid properties must still be determined from the steady state drag force data.

The presence of interfaces in the fluid, such as an air-fluid boundary or a sludge-liquid boundary or the boundary between the bottom of the tank and the fluid can result in differences between the drag forces measured near the interfaces and those measured far away from the interfaces. We have two natural interfaces within our experiments, the fluid container bottom and the free surface of the fluid. In the natural course of experimentation both the steady state pull distances and the effects of interfaces have been investigated. We will first consider the pull distance necessary to reach a steady

Table 3. Drag Force on Ball with Different Cables

Cable Diameter, (inches)	Ball Velocity (cm/sec)		
	0.1	0.5	1.0
	Drag Force on Ball (grams)		
	Chemical Simulant/Ball Diameter = 1 inch		
0.125	1.5	1.5	2.0
0.250	1.4	1.5	2.1
	Chemical Simulant/Ball Diameter = 2 inches		
	0.125	6.0	6.5
0.250	6.5	6.5	6.5
	Carbopol/Ball Diameter = 1 inch		
	0.125	17	21
0.250	18	19	19
	Carbopol/Ball Diameter = 2 inches		
	0.125	80	87
0.250	76	84	101
	Bentonite Clay/Ball Diameter = 1 inch		
	0.125	140	150
0.250	130	135	150
	Bentonite Clay/Ball Diameter = 2 inches		
	0.126	600	625
0.250	575	625	625

state flow condition. Results obtained from plots such as are shown in the figures presented here are given in Table 4. The pull distance to steady state is greatest for carbopol (most of the time), which has almost no yield stress and a viscosity between those of the chemical simulant and bentonite clay. The pull distance is least for the chemical simulant, which has the lowest viscosity. Except for one case with the bentonite clay, the pull distance does not depend strongly on velocity. Most of the data suggest that it scales with ball size, but not linearly. Examination of the results in Table 4 show no

Table 4. Pull Distances to Steady-State Flow

Ball Diameter, (inches)	Ball Velocity (cm/sec)		
	0.1	0.5	1.0
	Pull Distance (cm)		
	Chemical Simulant		
1.0	0.5	0.5	1.5
2.0	0.5	0.5	1.5
	Carbopol		
	1.0	4.0	5.0
2.0	7.0	7.0	7.0
	Bentonite Clay		
	1.0	2.0	7.0
2.0	4.0	4.0	5.0

correlation with the fluid Bingham numbers or the Reynolds numbers.

The distance at which interfaces begin to affect the drag forces was also obtained from data plots. The results are shown in Table 5. This distance does not seem to depend on ball velocity. Both the carbopol and the chemical simulant give similar results and the results are similar for both ball sizes. The distance is largest for the Bentonite clay, for which case ball size seems to be important. Bentonite clay has a much larger yield stress than either the chemical simulant or the carbopol, and it would seem that yield stress may be the important factor in determining how close the ball can approach an interface before the drag force is affected. Again however, we have found no correlation with either the fluid Bingham numbers or the Reynolds numbers.

3.6 Fluid Rheograms

Samples were obtained for each fluid and rheograms were obtained with a laboratory Bohlin VOR rheometer. Results of such testing are shown in a separate report by Jon Phillips. Rheograms for the three fluids are shown in Figures 20 through 22. We will glean some of these results and compare them to the results determined from the ball rheometer as given in Table 2.

Table 5. Interface-Effects Distance

Ball Diameter, (inches)	Ball Velocity (cm/sec)		
	0.1	0.5	1.0
	Interface-Effect Distance (cm)		
	Chemical Simulant		
1.0	2.0	2.0	2.0
2.0	2.0	2.0	2.0
	Carbopol		
	1.0	2.0	2.0
2.0	2.0	2.0	3.0
	Bentonite Clay		
	1.0	3.0	3.0
2.0	7.0	8.0	8.0

The data in Table 2 show that the drag force on the ball scales roughly as the square of the ball diameter and is a weak function of the ball velocity. These observations suggest that a Bingham or generalized Bingham fluid model may be useful in describing the fluids. A simple form for the equation relating drag force on the ball to viscosity and yield stress for a Bingham fluid is given by Bhavaraju et al. (1978) as

$$F_d = 3\pi\mu_o dV \left(1 + 1.6 \frac{\tau_o d}{\mu_o v} \right) \quad (13)$$

where,

- F_d = drag force on ball
- μ_o = zero shear rate viscosity
- d = ball diameter
- V = ball velocity
- τ_o = yield stress

Simplifying Eq. 13 we find that it contains a term which depends on viscosity and velocity (the usual Stokes term) and another which depends on the yield stress and the square of the ball diameter.

Viscometry of 0.2% (wt) Carbopol 980
(040794.8&9.visc.data)

Figure 20. Rheogram for carbopol as measured with the Bohlin rheometer

Bentonite Clay - 13.5% (ball rheom) tests #2-4
T = 25°C, files = 042294.2-4.visc.data

Figure 21. Rheogram for bentonite clay as measured with the Bohlin rheometer

Figure 22. Rheogram for chemical simulant as measured with the Bohlin rheometer

$$F_d = 3\pi\mu_o dV + 4.8\pi\tau_o d^2 \quad (14)$$

If we assume the applicability of this description of the fluid we can reduce the data contained in Table 2 and determine values for the yield stress and the viscosity. These values can be compared to results obtained with the laboratory viscometer. The comparison is shown in Table 6, where ranges of measured values are reported. Results with the Bohlin rheometer show that in all cases the viscosity is shear rate dependent. The shear rates obtained in the ball rheometer studies (ball speed/ball diameter) range from less than 0.1/s to less than 1/s, and in order to facilitate comparison, we chose the region of the flow curves between shear rates of 0.1/s and 1.0/s in order to obtain results from the Bohlin rheometer. The table shows that for the chemical simulant and the bentonite clay, both instruments provide comparable numbers for the yield stress but the viscosities determined with the ball rheometer are generally somewhat lower than those found with the Bohlin rheometer. In the case of carbopol, the yield stress given by the ball rheometer is much greater than the actual yield stress as measured with the Bohlin rheometer. Carbopol is known to be undescrivable in terms of a simple Bingham fluid, and the disagreement here is not surprising. The disagreement in measured viscosities may be due to failure to include a power law term in the reduction of the ball rheometer data. The data obtained with the Bohlin rheometer indicate that the fluids are describable in terms of a power law model. Continued research at our laboratory has shown that both the bentonite clay and the chemical simulant can be described with a generalized Bingham fluid model. The carbopol cannot be so described. This study has yet to be completed, however all indications are that reduction of the actual in-situ data obtained from the tank should begin using a generalized Bingham fluid model.

Table 6. Comparison of Experimental Results Obtained with Ball Rheometer and Laboratory Rheometer for Three Simulants

	Ball Velocity (cm/sec)	
	Yield Stress (Pascals)	Viscosity (Pascal-sec)
	Chemical Simulant	
Ball rheometer	1.5 - 1.6	2.2 - 2.8
Bohlin rheometer	< 1.0	2 - 10
	Bentonite Clay	
Ball rheometer	135 - 170	60 - 200
Bohlin rheometer	130	200 - 1000
	Carbopol	
Ball rheometer	15 - 19	11 - 19
Bohlin rheometer	~2.0	20 - 30

4.0 References

Bhavaraju, S. M., R. A. Mashelkar, and H. W. Blanch. 1978. "Bubble Motion and Mass Transfer in Non-Newtonian Fluids," *AICHE Journal* 24 (6), 1063.

Pasamehmetoglu, K. O., C. Unal, and J. Edwards. December 1993. *The Evaluation of Methods for Rheology Measurements of the Waste Contained in Hanford Tank 241-SY-101*. Los Alamos National Laboratory Report LA-UR-93-4300.

Shepard, C. L. 1994. *Report on Data Requirements and Hardware Selection for In-Situ Ball Rheometer*, PNL-10171. Pacific Northwest Laboratory, Richland, Washington.

Shepard, C. L., J. B. Colson, K. O. Pasamehmetoglu, C. Unal, J. H. Edwards, and J. Abbott. 1994. *Theory of Operation for The Ball Rheometer*, PNL-10240. Pacific Northwest Laboratory, Richland, Washington.

Distribution

No. of
Copies

No. of
Copies

OFFSITE

ONSITE

12 DOE Office of Scientific and Technical
Information

4 DOE Richland Operations Office

Billy C. Hudson
202 Northridge Ct.
Lindsborg, KS 67456

R. F. Christensen	S7-54
R. E. Gerton	S7-54
J. M. Gray	S7-54
G. W. Rosenwald	S7-54

J. L. Kovach
Nuclear Consulting Services, Inc.
P.O. Box 29151
Columbus, OH 43229-0151

24 Westinghouse Hanford Company

Thomas E. Larson
Los Alamos National Laboratory
MS-P915, DX-DO
P.O. Box 1663
Los Alamos, NM 87545

W. T. Alumkal	S7-85
H. Babad	S7-30
R. E. Bauer	L6-37
G. T. Bear	R1-51
T. R. Benegas	N1-27
L. E. Efferding	H0-33
R. L. Fritz	B4-08
C. E. Hanson	H5-09
G. D. Johnson	S7-15
N. W. Kirch	R2-11
L. S. Krogsrud	R3-08
D. C. Larsen	R1-51
J. W. Lentsch (5)	S7-15
R. M. Marusich	H4-65
N. G. McDuffie	S7-15
M. A. Payne	S7-14
D. A. Reynolds	R2-11
C. P. Shaw	L5-07
T. I. Stokes	H5-09
J. E. Van Beek	R3-27

5 Los Alamos National Laboratory
P.O. Box 1663
Los Alamos, NM 87545
Attn: J. Abbott, K555
A. Graham, K555
K. Pasamehmetoglu, K555
C. Unal, K555
J. R. White, K555

D. Pepson
U.S. Department of Energy
Trevion II Building, EM-35
Washington, D.C. 20585-0002

Dana Powers
Sandia National Laboratory
Dept. 6404/MS-0744
P.O. Box 5800
Albuquerque, NM 87815-0744

No of
Copies

36 Pacific Northwest Laboratory

J. M. Alzheimer	K5-22
W. J. Apley	S7-71
Z. I. Antoniak	K7-15
R. M. Bean	P8-08
S. Q. Bennett	K7-90
M. A. Chieda	K5-25
J. B. Colson	K5-10
E. J. Eschbach	K7-15
J. D. Hudson	K7-15
B. M. Johnson	K1-78
L. J. Kiriara	K5-25
F. E. Panisko (5)	P8-34
J. R. Phillips	K7-15
K. P. Recknagle	K7-15
H. C. Reid	K7-15
P. A. Scott	P7-43
A. Shekarriz	K7-15
C. L. Shepard	K5-25
C. W. Stewart (5)	K7-15
T. I. Stokes	H5-09
G. Terrones	K7-15
D. S. Trent	K7-15
Publishing Coordination	
Technical Report Files (5)	