The Impact Of Electric Vehicles on CO₂ Emissions

Final Report

By

**Jeffrey M. Bentley
Peter Teagan
David Walls
Eric Balles
Thomas Parish**

Published May 1992

**Arthur D. Little
Cambridge, MA 02140**

**Prepared for EG&G Idaho, Inc.
Under Subcontract C91-103441
and for the
Idaho National Engineering Laboratory
U.S. Department of Energy
Assistant Secretary for Conservation and Renewable Energy (CE)
Under DOE Contract No. DE-AC07-76ID01570**

MASTER

Acknowledgement

This program was administered by Andrew Burke of INEL. His technical guidance and advice is greatly appreciated. The authors would also like to acknowledge the advice and guidance of Dr. Kenneth Heitner of the DOE office of Hybrid and Electric Vehicles.

Table of Contents

Executive Summary	ES-1
1.0 Introduction	1-1
2.0 Study Overview	2-1
2.1 Overview	2-1
2.2 Study Ground rules and Methodology	2-1
2.3 Areas of Focus	2-3
3.0 Vehicular Fuel Consumption	3-1
3.1 Vehicle Characteristics	3-1
3.2 Road Load Calculation	3-7
3.3 ICEV Powertrain Efficiency and Emissions	3-8
3.4 Engine Accessories and HVAC	3-14
3.5 EV Driveline and Battery Efficiencies	3-15
3.6 Fuel Cell Vehicle Efficiencies	3-18
3.7 Summary of Vehicle Energy Requirements	3-19
4.0 Fuel Conversion Efficiency and Fuel Chain Emissions	4-1
4.1 Fuel Chain Efficiencies	4-2
5.0 Electric Power Generation	5-1
5.1 Introduction	5-1
5.2 1992 Average Daily National Power Generation Mix and CO ₂ Production	5-5
5.3 National Power Generation Mix Projections, 2000-2020	5-6
5.4 Natural Gas Power Generation Projections	5-9
5.5 CO ₂ Emissions Based on a Marginal Power Generation Mix Analysis	5-9
5.6 Effects of Daily Variations in Power Generation on CO ₂ Production	5-11
6.0 Electric Vehicle Fleet and Vehicle Miles Traveled Projections	6-1
7.0 Findings	7-1
7.1 Summary of Scenarios ..	7-1
7.2 Resource Utilization Summary and Comparison of Primary Energy Efficiency	7-4
7.3 Carbon Dioxide Production/km	7-8
7.4 Aggregate CO ₂ Emissions	7-13
Appendix A - EV CO₂/Energy Model Description	A-1

Table of Figures

Figure ES-1:	Overview of Energy Chain and Nomenclature	ES-2
Figure ES-2:	Natural Gas Fuel Chain	ES-3
Figure ES-3:	Fuel Cell Vehicle Hydrogen Infrastructure Options	ES-4
Figure ES-4:	Effective Driveline Efficiency - LEV/ULEV Emissions for Commuter	ES-6
Figure ES-5:	Electrical Vehicle Power System Losses	ES-7
Figure ES-6:	Fuel Cell VEHICLE Power System Losses	ES-8
Figure ES-7:	CO ₂ Production Rates and Efficiencies for Various Power Generation Scenarios	ES-9
Figure ES-8:	Primary Energy Consumption Comparison for Alternate Fuels - Minivan	ES-11
Figure ES-9:	Primary Energy Consumption for Power Generation Scenarios - Minivan	ES-11
Figure ES-10:	The Effect of Thermal Losses from High Temperature Batteries on Minivan Primary Energy Consumption	ES-12
Figure ES-11:	The Effect of Thermal Losses from High Temperature Batteries on Commuter Primary Energy Consumption	ES-13
Figure ES-12:	Primary Energy Consumption for Natural Gas Scenarios, Including Fuel Cells - Family Car	ES-14
Figure ES-13:	Carbon Dioxide Production Comparison of EVs and ICEVs - Minivan	ES-15
Figure ES-14:	CO ₂ Production for Power Generation Scenarios - Minivan	ES-16
Figure ES-15:	The Effect of Thermal Losses from High Temperature Batteries on CO ₂ Emissions - Minivan	ES-17
Figure ES-16:	CO ₂ Estimates for Natural Gas Scenarios, Including Fuel Cells - Family	ES-18
Figure 2-1:	Overview of Energy Chain and Nomenclature	2-3
Figure 3-1:	Effective Driveline Efficiency - Tier 1 Emissions, Commuter Vehicle	3-13
Figure 3-2:	Effective Driveline Efficiency - LEV/ULEV Emissions, Commuter Vehicle	3-14
Figure 3-3:	Electric Vehicle Power System Losses	3-15
Figure 3-4:	Vehicle Energy Available for Regeneration - Urban Cycle, Small Commuter EV	3-16
Figure 3-6:	Fuel Cell vehicle Power System Losses	3-19
Figure 3-7:	Energy Consumption From the Tank (or Plug) - Small Commuter, Urban Cycle, LEV/ULEV	3-21
Figure 3-8:	Energy Consumption from the Tank (or Plug) - Minivan, Composite Cycle	3-21
Figure 3-9:	Energy Consumption from the Tank (or Plug)- Family Car. Composite Cycle	3-22
Figure 4-1:	Natural Gas Fuel Chain	4-1
Figure 4-2a:	Calculation of Actual Process Efficiencies	4-3

Table of Figures (Continued)

Figure 4-2b:	Calculation of Simplified Process Efficiencies	4-3
Figure 4-3a:	Calculation of Efficiency for Corn to Ethanol (from Turhollow Reference 4-4)	4-7
Figure 4-3b:	Calculation of Efficiency for Wood to Ethanol (from Deluchi Reference 4-11)	4-7
Figure 4-4:	Fuel Cell Vehicle Hydrogen Infrastructure Options	4-7
Figure 5-1:	Distribution of Power Generation by Technology for 1992	5-5
Figure 5-2:	Power Generation for National Mix Scenario	5-7
Figure 5-3:	CO ₂ Production Rates for Various Power Generation Scenarios	5-8
Figure 5-4:	CO ₂ Production Rates of EPRI Analysis and Selected Regions	5-10
Figure 6-1:	Projected Size of Fleet Subject to ZEV Regulations - Base Case	6-3
Figure 6-2:	Total EV Fleet for Three Scenarios	6-4
Figure 6-3:	Forecast Vehicle Mix for All Scenarios	6-5
Figure 6-4:	Annual Vehicle Kilometers Traveled for Various Scenarios	6-7
Figure 7-1:	Primary Energy Consumption Comparison for Alternate Fuels - Minivan	7-5
Figure 7-2:	Primary Energy Consumption for Power Generation Scenarios - Minivan	7-6
Figure 7-3:	The Effect of Thermal Losses from High Temperature Batteries on Minivan Primary Energy Consumption	7-6
Figure 7-4:	The Effect of Thermal Losses from High Temperature Batteries on Commuter Primary Energy Consumption	7-7
Figure 7-5:	Primary Energy Consumption for Natural Gas Scenarios, Including Fuel Cells - Family Car	7-9
Figure 7-6:	Carbon Dioxide Production Comparison of EV's and ICEV's - Minivan	7-10
Figure 7-7:	CO ₂ Production for Power Generation Scenarios - Minivan	7-10
Figure 7-8:	The Effect of Thermal Losses from High Temperature Batteries on CO ₂ Emission	7-11
Figure 7-9:	CO ₂ Estimates for Natural Gas Scenarios, Including Fuel Cells - Family	7-12
Figure 7-10:	Sources of CO ₂ in 2010 - Minivan Configuration	7-12

Table of Tables

Table ES-1:	Fuel Chain Efficiency and CO ₂ Emissions	ES-3
Table ES-2:	Vehicle Technology Evolution - Family Car	ES-5
Table ES-3:	Summary of Projected IC Engine/Driveline Efficiency Improvements	ES-6
Table ES-4:	Thermal Losses from High Temperature Batteries Comparative Calculations	ES-7
Table ES-5:	Primary Energy Consumption of Vehicle Classes (kWh/km)	ES-10
Table ES-6:	CO ₂ Production of Vehicle Classes (gCO ₂ /km)	ES-15
Table 2-1:	Primary Energy Sources and Transportation Fuels Studies	2-1
Table 2-2:	Approximate Efficiencies for a 1992 EV	2-3
Table 3-1:	1992 Gasoline Vehicles Selected for Baseline	3-2
Table 3-2:	Vehicle Technology Evolution - Small Car	3-3
Table 3-3:	Vehicle Technology Evolution - Family Car	3-4
Table 3-4:	Vehicle Technology Evolution - Van	3-5
Table 3-5a:	Calculated EPA Composite Road Load for Gasoline, Methanol and Ethanol Powered Vehicles [ICEV's] (kWh/km)	3-7
Table 3-5b:	Calculated EPA Composite Road Load for EV's and FCV's (kWh/km)	3-8
Table 3-6:	Calculated Effective Driveline Efficiency for 1992 Gasoline ICEV Vehicles - EPA Composite Cycle	3-9
Table 3-7:	Tallpipe Emissions Regulations (g/mile)	3-9
Table 3-8:	Summary of Projected IC Engine/Driveline Efficiency Improvements - Federal Tier 1 Emissions	3-10
Table 3-9:	Summary of Projected IC Engine/Driveline Efficiency Improvements - LEV/ULEV Emissions	3-11
Table 3-10:	High Temperature Battery Thermal Loss Comparison Calculations	3-18
Table 3-11:	Summary of Composite Cycle Fuel Economy Estimates - Gasoline ICEV's	3-20
Table 4-1:	Transportation Fuel Data	4-3
Table 4-2:	Fuel Chain Efficiency (Percent) and CO ₂ Emissions	4-4
Table 4-3:	CNG Process Efficiency Scenarios	4-5
Table 4-4:	Comparison of Impact of CH ₄ Emissions to CO ₂ Emissions	4-10
Table 5-1:	Power Generation Fuel Chain, CO ₂ Emissions in Grams/kWh	5-2
Table 5-2:	Average Power Generation Efficiencies by Technology (HHV) ..	5-4
Table 5-3:	New Plant Generation Efficiency	5-4
Table 5-4:	Power Generation Mix - National Mix Scenario	5-6
Table 5-5:	Power Generation CO ₂ Production (Grams/kWh Delivered) - National Mix Scenario	5-6
Table 5-6:	CO ₂ Production and Efficiency Scenarios	5-9
Table 6-1:	Implementattion Rates for Conventional Vehicles, TLEV's, LEV's, ULEV's, and ZEV's used to Calculate Fleet Average Standards for Passenger Cars	6-1

Table of Tables (Continued)

Table 6-2:	New Light Vehicle Registrations by State	6-2
Table 6-3:	Forecast Vehicle Sales Growth Rates (Source: Arthur D. Little)	6-3
Table 6-4:	Vehicle Classification for 101 Cities Scenario	6-5
Table 6-5:	Transportation to Work by Mode, 1985	6-6
Table 6-6:	Household Travel by Type of Vehicle - 1988	6-7
Table 7-1:	Vehicle Technology Evolution - Minivan	7-2
Table 7-2:	Fuel Chain Efficiency and Fuel Chain CO ₂ Emissions	7-2
Table 7-3:	Power Generation CO ₂ Production and Efficiency Scenarios	7-3
Table 7-4:	Yearly Fleet Travel for Market Penetration Scenarios (Millions of km/yr)	7-3
Table 7-5:	Primary Energy Consumption of Vehicle Classes (kWh/km)	7-4
Table 7-6:	CO ₂ Production of Vehicle Classes (gCO ₂ /km)	7-9
Table 7-7:	CO ₂ Emissions by Vehicle Type - Base Case Market Penetration	7-14
Table 7-8:	Net CO ₂ Reduction (10 ⁶ tons/yr) of EV's Over Gasoline ICEV's for Market Scenarios	7-14

Executive Summary

The energy consumption and resultant contribution of potential greenhouse gases by the transportation sector has been the subject of increasing interest among researchers and policy analysts over the last several years. The transportation sector consumes over 25% of the total energy consumption in the United States. Since nearly all of the energy for transportation is derived from fossil sources, the resulting release of carbon dioxide (CO₂) accounts for over 30% of total U.S. CO₂ emissions. Therefore, CO₂ emissions are now a consideration in regional and federal transportation technology planning along with more traditional considerations such as economics, energy security and regulated pollution. Although EVs have traditionally been viewed as a means of reducing tailpipe emissions (such as carbon monoxide and hydrocarbons), the analyses presented in this report demonstrate that EVs can also provide substantial reductions in primary energy consumption and CO₂ emissions.

Transportation planners face a difficult challenge in determining which technologies to support as an alternative to the gasoline internal combustion engine vehicle (ICEV) for light duty applications. No current electric vehicle (EV), fuel cell vehicle (FCV), or alternative fuel ICEV can match the overall performance or ease of operation of a gasoline vehicle, and each potential alternative represents differing characteristics regarding performance, tailpipe, and point source emission of regulated pollutants and greenhouse gases. Natural gas (particularly compressed natural gas (CNG)) is receiving renewed attention as a transportation energy source, because it addresses greenhouse, tailpipe emissions, and energy security issues to some extent. However, natural gas can be a primary energy source for CNG, liquefied natural gas (LNG), methanol, electric and fuel cell vehicles with each usage having differing emissions, performance, and efficiency characteristics.

A number of recent studies have examined the greenhouse gas emissions of various light duty vehicle alternatives in some detail. These studies have highlighted the extreme range of predicted net greenhouse gas emissions depending on scenarios for fuel types, vehicle and power generation efficiencies, the relative greenhouse contributions of emitted gases and a number of uncertainties in fuel chain efficiencies. Despite the potential range of results, most studies have confirmed that electric vehicles generally have significant potential for reducing greenhouse gas emissions relative to gasoline and most alternative fuels under consideration.

This report summarizes the results of a study which builds on previous efforts with a particular emphasis on:

1. A detailed analysis of ICEV, FCV, and EV vehicle technology and electric power generation technology. Most previous transportation greenhouse studies have focused on characterization of fuel chains that have relatively high efficiency (65-85%) when compared with power generation (30-40%) and vehicle driveline (13-16%) efficiencies.

2. A direct comparison of EVs, FCVs with gasoline and dedicated alternative fuel, ICEVs using equivalent vehicle technology assumptions with careful attention to likely technology improvements in both types of vehicles.
3. Consideration of fuel cell vehicles and associated hydrogen infrastructure.
4. Extension of analyses for several decades to assess the prospects for EVs with a longer term prospective.

Figure ES-1 shows the energy chains evaluated and the associated nomenclature used in this study.

Figure ES-1: Overview of Energy Chain and Nomenclature

Summary of Technical Analyses

In order to estimate the energy efficiency and CO₂ emissions of future vehicles a number of detailed analyses were conducted to establish likely vehicle configurations, driveline and component efficiencies, fuel chain efficiencies, and power generation efficiencies. The results of these analyses are summarized below:

Fuel Conversion Efficiency and Fuel Chain Emissions

For ICEV fuels the energy requirements for each step in the fuel chain from resource extraction to fuel delivery and the related CO₂ emissions for each step have been estimated on the basis of a kWh-(HHV) of energy delivered to the vehicle fuel tank. Figure ES-2 illustrates, for example, the major steps in the energy chain for CNG along with the efficiency for each step. CO₂ emissions consider not only the energy consumed in each step but also the carbon content of the fuel used and CO₂ allocations to other

byproducts. Since methane is a significant greenhouse gas in its own right, emissions of methane were analyzed for appropriate steps and found to make a relatively small contribution (less than 6%) to global warming relative to CO₂ for the vehicles considered.

Figure ES-2: Natural Gas Fuel Chain

Fuel Chain Efficiencies

The efficiency and CO₂ estimates developed for this study are shown in Table ES-1, with baseline estimates shown in bold typeface. This data was compiled from independent analyses as well as previous studies.

Table ES-1: Fuel Chain Efficiency and CO₂ Emissions

	Gasoline From Crude	Methanol From Natural Gas	CNG From Domestic Natural Gas	CNG From Imported LNG	H ₂ From NG Natural Gas	Ethanol From Corn	Ethanol from Wood
Net Delivery Efficiency (%)	85	56-62	77- 85	67-74	71	31	37
CO ₂ (g/kWh) (HHV)	46	93-124	31-53	62-87	73	244	Not determined

The two alternative fuel paths analyzed for the supply hydrogen for a fuel cell vehicle are shown in Figure ES-3. For the 2001 FCV configurations, on-board storage and reformation of methanol is the assumed hydrogen source (as shown on the top leg of Figure ES-3). In later years (2010 and 2020), hydrogen is assumed to be reformed from natural gas at fixed sites and stored in hydride form on-board the vehicle.

Figure ES-3: Fuel Cell Vehicle Hydrogen Infrastructure Options

Fuel Chain CO₂ Emissions

Calculated CO₂ emissions expressed as grams of CO₂ per kWh (HHV) of fuel delivered to the tank for each fuel chain are also shown in Table ES-2. CO₂ emissions for the CNG paths are based on combustion of all of the fuel associated with fuel chain losses. For gasoline and ethanol net fuel chain CO₂ emissions are allocated to the fuel as well as other process byproducts. For methanol some CO₂ is consumed by the conversion process. While the fuel chain CO₂ emissions for the ethanol from corn process are high, the overall CO₂ emissions are relatively low since the CO₂ emitted during vehicular use is recycled by future crops. The Ethanol from wood process would likely show greater benefits but was not studied extensively in this work.

Vehicle Characteristics

The current (1992) characteristics of representative models for three classes of light duty vehicles (commuter, family vehicle and minivan) were used as a baseline to estimate future year (2001,2010,2020) vehicle characteristics. The technology assumptions used for vehicles in future time periods were derived from relatively aggressive technology assumptions and characteristics of prototypes (such as the GM Impact) currently exhibited by vehicle manufacturers. Equivalent assumptions regarding aerodynamic coefficients, rolling resistance and weight reduction were applied to EVs, ICEVs and FEVs within each vehicle class. As an example of this analysis, details of the technology assumptions for the family vehicle are shown in Table ES-2.

Table ES-2: Vehicle Technology Evolution - Family Car

	1992 (Ford Taurus Sedan)	2001	2010	2020
Base Vehicle Characteristics				
Glider Weight (Kg)	1115	1015	835	780
C _d	.32	.29	.22	.20
Tire Coefficient C(O)	.009	.007	.006	.005
IC Engine/Driveline				
Engine Power (kW)	110	100	85	80
Electric Vehicle				
Battery Energy Density (wh/Kg)	55	100	175	200
Battery Energy (kWh)	30	52	73	77
Fuel Cell Vehicle				
Fuel Cell Nominal Power (kW)	–	25	22	20
Battery Weight (Kg)	–	200	150	120
Total Weights				
Liquid Fuel Vehicle Weight (Kg)	1565	1440	1210	1125
Natural Gas Vehicle Weight (Kg)	1610	1485	1255	1170
Electric Vehicle Weight (Kg)	1950	1820	1500	1390
Fuel Cell Vehicle Weight (Kg)	–	1745	1410	1272

Vehicle Efficiencies

To our knowledge, there are no data sources documenting the cycle average driveline efficiency of present generation gasoline or alternative fuel engines. Therefore, the ICEV average cycle efficiency was derived from EPA mileage ratings which represent empirical data for 1992 gasoline ICEVs. The effective driveline efficiency is defined by this study as the efficiency at which energy from the tank is converted into useful energy at the wheels:

$$\eta_{\text{effective}} = \frac{\text{"Useful" Energy}}{\text{Total Energy}} = \frac{\text{Integrated Road Load}}{\text{LHV/MPG*}}$$

The effective driveline efficiency for the 1992 gasoline commuter was determined to be 13.7% based on EPA fuel consumption data and calculated road loads (using a computer simulation) for the baseline gasoline vehicle. Average cycle efficiencies for other fuels and for future timeframes were determined from the 1992 baseline by evaluating the expected efficiency impact of specific driveline technologies as shown in Table ES-3.

As shown in Figure ES-4, the effective driveline efficiency for 1992 ICEVs is between 13.7% and 15.8%. By 2020 the efficiency improvements shown in Table ES-4 would increase driveline effective efficiency to 15.9%-18.6% while meeting ULEV emission standards.

The estimates of losses associated with delivering power from the plug to the road for an EV for present and future time periods are shown schematically in Figure ES-5.

Table ES-3: Summary of Projected IC Engine/Driveline Efficiency Improvements - LEV/ULEV Emissions

	1992		2001 (LEV)		2010 (LEV/ULEV)		2020 (ULEV)
Gasoline	1.0 Base ↓	→	1.10 (+10%) • Reduced Friction • Advanced EGR Control • Variable Valve Timing	→	1.15 (+5%) • Indiv Cyl Control • 5-Speed or CVT	→	1.15 (no change) • Advanced 3-way catalyst formulation
Natural Gas	1.05 (+5%) • 10.5:1 Compression	→	1.21 (+15%) • Same as Gasoline • Lean Burn • Lean NO _x Catalyst	→	1.27 (+5%) • Same as Gasoline	→	1.33 (+5%) • Unthrottled • Advanced Lean NO _x Catalyst • Compression Ign 2-Stroke

Figure ES-4: Effective Driveline Efficiency - LEV/ULEV Emissions for Commuter

Table ES-4: Thermal Losses from High Temperature Batteries Comparative Calculations

Configuration	Yearly Travel (km)	Battery Thermal Loss Factor (W/kWh)	Vehicle Thermal Loss (kWh/km)	Increase in Energy "From Plug" Due to H.T. Battery	Notes
Small commuter: • 2010 configuration • 45 kWh battery	11,000	3.2	0.98	63%	Baseline for this analysis
	11,000	2	.055	35%	Equivalent to 38% lower loss than USABC or 28 kWh battery
	11,000	12	.417	170%	Thermal loss of current NaS batteries
	26,600	3.2	.030	19%	Commercial or fleet yearly travel
Family: • 2010 configuration • 73 kWh battery	16,600	3.2	.100	49%	Baseline for this analysis
Van: • 2010 configuration • 73 kWh battery	26,600	3.2	.051	23%	Baseline for this analysis
	26,600	2.0	.023	11%	Equivalent to 38% lower thermal loss than USABC or 46 kWh battery
	26,600	12	.262	120%	Thermal loss of current NaS batteries
	11,000	3.2	.160	73%	Commuter travel

Figure ES-5: Electric Vehicle Power System Losses

The thermal loss for high temperature batteries is a continuous loss that must be offset (in order to maintain battery temperature) by the heat generated during charge/discharge or from energy from the plug or battery. The United States Advanced Battery Consortium (USABC) thermal loss goal is 3.2 W/kWh, while the reported loss for a current 60 kW sodium sulfur battery is 12 W/kWh. Average vehicle travel distance is an important consideration in calculating the effect of thermal losses on EV energy consumption. For identical vehicles, the thermal loss measured on a per km basis is lower for vehicles traveling more km per day because of the increased distance over which the fixed loss can be spread and due to the greater charge/discharge loss resulting from the increased energy consumption from the battery. Table ES-4 shows the increase in vehicle energy requirements for several alternative loss factors and travel distances to illustrate the importance of achieving the USABC thermal loss goal and the importance of battery size.

Figure ES-6 shows the losses associated with the fuel cell vehicle configurations described previously. In 2001, the estimated conversion efficiency of the fuel cell/methanol reformer is 40% (HHV) based on estimates made by Arthur D. Little. By 2020, a near atmospheric pressure fuel cell and higher operating temperature are estimated to increase fuel cell efficiency to about 55% (HHV).

Figure ES-6: Fuel Cell Vehicle Power System Losses

Power Generation Efficiency and CO₂ Emissions

The plant efficiency and CO₂ emissions associated with electric power generation and delivery for three power generation scenarios are shown in Figure ES-7. The "National Mix" scenario is derived from the U.S. National Energy Strategy (NES) and relies on coal for 50% of the total power generated. It likely represents an upper bound on the amount of coal that will be used in future U.S. generation mixes. The other scenarios

illustrate how natural gas generation technologies affect efficiency and CO₂ production. The Advanced Gas scenario includes higher efficiency natural gas technologies (such as gas turbine combined cycle and fuel cells) using the average efficiency for all plants of this type which are online at a given time. The New Gas scenario is a marginal efficiency scenario representing the most efficient natural gas generating capacity for any time period.

Figure ES-7: CO₂ Production Rates and Efficiencies for Various Power Generation Scenarios

Resource Utilization Summary and Comparison of Primary Energy Efficiency

The results of the previously discussed analyses of vehicular energy consumption, fuel chain efficiency, and power generation were combined in a resource utilization analysis which estimate the primary energy requirements to provide a km of distance traveled over defined driving cycles (urban or combined). Then, end-to-end CO₂ emissions were estimated on a per kilometer basis.

Differences Between Vehicle Classes

Table ES-5 compares the primary energy requirements (kWh/km) for the composite driving cycle for gasoline ICEVs with EVs (advanced gas generation, low-temperature battery). Gasoline ICEVs in all vehicle classes require significantly more primary energy in 1992 (31% to 50%) than EVs and the margin grows in future time periods. (The difference in primary energy requirements between EVs and ICEVs is greatest for minivans.) These estimates indicate that in 1992 gasoline powered commuter cars will

require as much primary energy as the EV minivan (although the EV has one-third the range). The estimated gasoline minivan ICEV primary energy requirement in 2020 is twice that of the EV.

Table ES-5: Primary Energy Consumption of Vehicle Classes (kWh/km)

	1992	2001	2010	2020
Small Commuter - EV	.73	.50	.35	.29
Small Commuter - Gasoline	.90	.65	.55	.49
Family - EV	.81	.66	.45	.32
Family - Gasoline	1.11	.87	.65	.58
Minivan - EV	.90	.71	.50	.36
Minivan - Gasoline	1.35	1.06	.81	.73

The decline in primary energy estimates for all vehicles is noteworthy. By 2020, the estimated gasoline ICEV primary energy consumption is over 45% lower than in 1992. Two-thirds of this decrease is due to vehicle road load reductions and one-third is due to increased driveline efficiency. For EVs, the 2020 primary energy estimate is 60% lower than in 1992. Approximately 60% of this reduction is due to the decrease in road load, 27% is due to EV driveline improvements, and 13% is due to power generation efficiency improvements.

Differences Between ICEV Fuels

Figure ES-8 shows how the various ICEV fuels compare with an EV (advanced gas, low-temperature battery) for the minivan class. Only the CNG minivan has a lower primary energy requirement than the gasoline vehicle. In 1992, the CNG ICEV requires 50% more primary energy than the EV, methanol requires twice as much, and ethanol from corn requires over 3-1/2 times as much primary energy as the EV. Ethanol from biomass would require slightly less primary energy (mostly consisting of biomass derived process energy).

Differences Between Power Generation Mixes

Figure ES-9 compares EV (low temperature) primary energy estimates for the three power generation scenarios with the estimated CNG (ULEV) minivan primary energy requirement. Under all of the power generation scenarios for all time periods, the EV requires less energy than the minivan fueled by CNG, the most efficient ICEV. In 1992, the CNG ICEV is estimated to require 18% more energy than the EV recharged from the National Mix and 50% more than the EV recharged from advanced technology power plants. In 2020, the CNG minivan will use a little less than twice as much primary energy/km as an EV charged from the advanced gas base.

Figure ES-8: Primary Energy Consumption Comparison for Alternative Fuels - Minivan

Figure ES-9: Primary Energy Consumption for Power Generation Scenarios - Minivan

The Influence of Battery Thermal Losses

Figure ES-10 compares the estimated primary energy consumption of a minivan with various EV battery configurations. Figure ES-11 shows the same comparison for the commuter configuration.

Figure ES-10: The Effect of Thermal Losses from High Temperature Batteries on Minivan Primary Energy Consumption

For both figures, 3.2 W/kWh represents the baseline battery thermal loss (USABC criteria); 2.0 W/kWh models the effect of significant insulation system improvements or a 40% reduction in battery capacity and 12 W/kWh represents the performance of current NaS batteries.

Since the minivan has a relatively high yearly travel, it is less influenced by thermal battery losses. In the hypothetical 1992 minivan, a high-temperature battery meeting USABC criteria would not require additional energy to meet thermal losses since battery charge/discharge losses are great enough to produce the necessary internal heating. In 2020, due to the assumption of a larger battery capacity and lower charge/discharge loss, the loss for a 3.2 W/kWh battery increases total primary energy consumption by 45% over the low-temperature EV. A loss factor of 12 W/kWh nearly triples the minivan EV energy consumption in 2020.

Figure ES-11: The Effect of Thermal Losses from High Temperature Batteries on Commuter Primary Energy Consumption

For the commuter, the influence of high-temperature batteries is more dramatic. Due to the relatively short average daily travel of the commuter, the primary energy required for the nominal case (3.2 kWh) equals the CNG primary energy requirement in 2001 and exceeds it by over 90% in 2020. Even the optimistic 2.0 W/kWh case just equals the primary energy required by the CNG commuter.

These estimates show that the primary energy advantage of EVs over CNG or gasoline ICEVs can be negated by high-temperature battery thermal loss. High-temperature battery EVs will only provide energy consumption advantages over ICEVs only if the USABC thermal loss goal is achieved and even then only if they are used in heavy mileage vehicles or if the battery size (and thus the range) in low mileage vehicles is significantly limited.

The Influence of Natural Gas Fuel Paths:

Figure ES-12 compares natural gas alternatives for the family car class including the CNG ICEV baseline, a CNG vehicle using imported LNG derived natural gas fuel and a fuel cell vehicle. The FCV fuel chain originates with natural gas, although the 2001 configuration uses methanol as an intermediary. The FCV-methanol configuration (2001) requires more primary energy than the low-temperature EV (although the FCV has greater range). The FCV energy efficiency in future years is essentially the same as

the low-temperature EV and much better than the CNG ICEV. Thus, the FCV offers an attractive alternative to EVs if high-temperature battery heat losses are of concern or long range or low refueling time are strong considerations.

Figure ES-12: Primary Energy Consumption for Natural Gas Scenarios, Including Fuel Cells - Family Car

Figure ES-12 also shows how the use of imported LNG increases the primary energy requirement for CNG vehicles. For all years, the LNG derived CNG requires 27% more energy than the CNG vehicle using domestic gas. This is due entirely to the less efficient energy chain for LNG. Consideration of LNG as a source of natural gas for power generation would result in a similar increase for all natural gas derived EV power.

Carbon Dioxide Production/km

In general, the primary energy comparisons drawn previously between EV scenarios based on natural gas power generation, CNG and CNG/LNG vehicles, relate directly to gCO_2/km since the assumed fuel form is natural gas in all cases. For other primary energy sources (such as petroleum), where fuel forms are changed (such as natural gas to methanol) or where carbon recycling is assumed (ethanol), the CO_2 emissions do not directly scale with the primary energy consumption.

Table ES-6 compares the total fuel chain power plant and vehicular CO₂ emissions (gCO₂/km). The CO₂ emissions advantage of the low-temperature EV over the gasoline ICEV is more pronounced than the primary energy comparison due to the lower carbon content of the natural gas used in power generation. 1992 gasoline ICEVs emit 60% to 100% more CO₂/km than their EV counterparts. In 2020, the CO₂ advantage is 2.2 to 2.6 times in favor of EVs.

Table ES-6: CO₂ Production of Vehicle Classes (gCO₂/km)

	1992	2001	2010	2020
Small Commuter - EV	137	94	67	54
Small Commuter - Gasoline	222	160	135	120
Family - EV	154	126	87	60
Family - Gasoline	273	213	161	142
Minivan - EV	169	135	94	69
Minivan - Gasoline	333	260	198	180

Figure ES-13 compares the estimated CO₂ production of ICEV minivans with a minivan EV. Ethanol and CNG are nearly equal in CO₂ emissions and are the best ICEV fuels from this standpoint, producing only 50% more net CO₂ (in the 1992 configuration) than the low-temperature advanced gas EV. Biomass derived ethanol could show even better CO₂ reduction benefits.

Figure ES-13: Carbon Dioxide Production Comparison of EVs and ICEVs - Minivan

By 2020, the ethanol emissions are 80% higher than the EV. Methanol, even though it is derived from natural gas, is the worst ICEV fuel with an estimated emission rate more than double that of the EV in 1992 and 2.8 times worse in 2020.

In Figure ES-14 the estimated CO₂ emissions for minivan EVs under different power generation scenarios are compared with a CNG minivan. The CNG and the "National Mix" EV have essentially the same CO₂ emissions for all time periods. By 2020, either the CNG ICEV or the National Mix EV emits twice as much CO₂ as an EV charged by the newest gas plants in the "New Gas" scenario. These estimates point to the CO₂ emissions benefits which can be gained by using natural gas to generate power for EVs instead of in dedicated CNG vehicles.

Figure ES-14: CO₂ Production for Power Generation Scenarios - Minivan

The Effect of Thermal Losses from High Temperature Batteries

CO₂ emission estimates for different values of high-temperature thermal battery losses are shown in Figure ES-15. The minivan configuration shown is less sensitive to these losses and both the 3.2 W/kWh (USABC goal) and the 2.0 W/kWh (smaller battery or better insulation system) emit less CO₂ than the CNG ICEV. The 12 W/kWh (1989 design thermal loss) high-temperature battery is estimated to produce twice as much CO₂ as the EV with a 3.2 W/kWh battery and nearly three times as much as the low-temperature EV. The estimated CO₂ emissions for all commuters based on high temperature batteries, regardless of thermal battery loss factor exceed those of the CNG ICEV.

Figure ES-15: The Effect of Thermal Losses from High Temperature Batteries on CO₂ Emissions - Minivan

The Influence of Natural Gas Fuel Paths

Figure ES-16 compares the estimated CO₂ production for natural gas alternatives EVs, FCVs, and CNG powered ICEVs. In 2020, FCVs and EVs charged from the advanced gas power generation group have nearly identical emissions. However, in 2001, the FCV CO₂ emissions are higher than even the CNG baseline due to the CO₂ emissions occurring during the methanol conversion process.

Figure ES-16: CO₂ Estimates for Natural Gas Scenarios, Including Fuel Cells - Family

Conclusions

The results of this study indicate that current and future electric vehicles and fuel cell vehicles can provide significant primary energy and CO₂ emissions benefits when compared with any gasoline or alternative fuel powered internal combustion vehicle. The key conclusions include:

- EVs powered by any generation mix considered (including one with 50% coal) are more efficient on a primary energy basis and emit less CO₂ than any ICEV. It is particularly relevant to compare the energy efficiency of EVs powered from a natural gas generation base with CNG vehicles. In 1992 the CNG ICEV requires 50% more primary energy than an EV. By 2020, a CNG ICEV is estimated to require 2.3 times as much natural gas primary energy as an EV powered by the most efficient natural gas generation plants coming on line.
- A 1992 gasoline commuter car will consume as much primary energy per kilometer (and emit 30% more CO₂) as a near-term configuration EV minivan. By 2020, the gasoline commuter is estimated to consume one-third more primary energy (and emit 70% more CO₂) than the EV minivan.
- Thermal battery losses can strongly influence the projected efficiency of EVs. If Battery energy density improvements are used to increase maximum vehicle range, a vehicle that uses a relatively small amount of its battery capacity per day (such as the commuter modeled in this study) will lose its energy efficiency advantage over

CNG and gasoline ICEVs. Even the minivan configuration with high yearly travel suffers at least a 45% increase in energy consumption when high temperature batteries are considered. These results underscore the importance of achieving the USABC thermal loss goals.

- Fuel cell vehicles with on-board storage of hydrogen provide nearly the same energy efficiency and CO₂ emissions benefit as EVs powered from an advanced natural gas generation base. FCVs using methanol as an intermediate fuel (2001 configuration) are less efficient than EVs but still just as efficient as CNG ICEVs. Although the advanced FCV would have nearly the same energy efficiency and CO₂ emissions as the best EV studied, it also can provide unlimited range (quick refueling) and is not subject to the potential negative performance impact of high temperature batteries.

1.0 Introduction

The energy consumption and resultant contribution of potential greenhouse gases by the transportation sector has been the subject of increasing interest among researchers and policy analysts over the last several years. The transportation sector consumes over 25% of the nation's total energy. Since nearly all of the energy for transportation is derived from fossil sources, the resulting release of carbon dioxide (CO₂) accounts for over 30% of total U.S. CO₂ emissions. CO₂ along with atmospheric water vapor and trace gases (methane, oxides of nitrogen, and CFC's) are now thought to play a major role in long-term atmospheric thermal balance. Therefore, greenhouse gas emissions and particularly CO₂ are now a consideration in regional and federal transportation technology planning along with more traditional considerations such as economics, energy security and regulated pollution.

Transportation planners face a difficult challenge in determining which technologies to support as an alternative to the gasoline internal combustion engine vehicle (ICEV). No current electric vehicle (EV), fuel cell vehicle (FCV), or alternative fuel ICEV can match the overall performance or ease of operation of a gasoline vehicle, and each potential alternative represents differing characteristics regarding performance, tailpipe, and point source emission of regulated pollutants and greenhouse gases. Moreover, national energy security considerations imply that consideration be given to fuels and energy sources which contribute to independence from or at least diversity among foreign energy sources.

As an example, natural gas is receiving renewed attention as a transportation energy source, because it addresses greenhouse, tailpipe emissions, and energy security issues to some extent. However, natural gas can be a primary energy source for compressed natural gas (CNG), liquefied natural gas (LNG), methanol, electric and fuel cell vehicles with each usage having differing emissions, performance, and efficiency characteristics. Given predictions of increasing demand for available natural gas supplies in the coming decade, it is important for transportation planners to understand the efficiency and emissions profiles of alternative energy chains for natural gas as well as other primary energy sources.

A number of recent studies^{1-12,3,4,5} have examined the greenhouse gas emissions of various transportation alternatives in some detail. These studies have highlighted the extreme range of predicted net greenhouse gas emissions depending on scenarios for fuel types, vehicle and power generation efficiencies, the relative greenhouse contributions of emitted gases and a number of uncertainties in fuel chain analyses. In addition, assumptions regarding timing of technology introduction and policy changes further complicates the analysis of alternatives. Depending on the assumptions and input data used, nearly any conclusion can be reached regarding the relative greenhouse contribution of ICEV's, EV's and FCV's.

Despite the potential range of results, most studies have confirmed that electric vehicles generally have significant potential for reducing greenhouse gas emissions relative to gasoline and most alternative fuels under consideration. The advantage of EV's over ICEV's is particularly strong in city driving and other situations with limited range requirements and intermittent tractive power demands

The purpose of this study is to build on previous efforts with a particular emphasis on:

1. Comparison of EV's and FCV's with alternative fuel ICEV's in EV markets.
2. A comparison of EV's, FCV's, and ICEV's using equivalent vehicle technology assumptions with careful attention to possible technology improvements for each type of vehicles. Most previous assessments have focused on fuel chain effects and near-term vehicle configurations. Evolving component, engine, and vehicle technologies could dramatically improve the efficiency of EV's and ICEV's and could have a much more significant impact on total greenhouse gas emissions than fuel chain effects.
3. Consideration of fuel cell vehicles and associated hydrogen infrastructure.
4. A thorough review of the likely efficiency and mix of power generation sources through 2020. Power generation efficiency improvements and fuel mix changes will significantly influence the primary energy requirements and greenhouse gas emissions for EV's. Again, changes in power generation will have a much greater impact than fuel chain efficiencies.
5. Incorporation of evolving standards and new technical information, including:
 - United States Advance Battery Consortium (USABC) battery performance goals and other recent battery and EV data;
 - Recently announced regional actions regarding ZEV/LEV's such as the recent decision by the Northeast States for Coordinated Air Use Management (NESCAUM) to adopt the California timetable for cleaner vehicles;
 - EV and alternative fuel vehicle implementation scenarios developed by the Interagency Commission on Alternative Motor Fuels; and
 - Consideration of the influence of climate control, engine accessory loads, and battery thermal losses on EV energy consumption.
6. Development of a simple transparent model (spreadsheet computer tool) of the energy flows and resulting emissions with flexibility for updating as new information becomes available.

As with any study dealing with the forecast of technology trends, there are significant uncertainties associated with future year estimates of performance, energy consumption and emissions. The level of technology achieved in future years is subject to a number of factors not considered in this analysis, including government policy, energy pricing, cost, and the actual performance of specific technologies.

References

- 1-1 Deluchi, M. A., "Emissions of Greenhouse Gases From the Use of Transportation Fuels and Electricity", Center for Transportation Research, Energy Systems Division, Argonne National Laboratory Report ANL/ESD/TM-22, November 1991.
- 1-2 Ho, S. P. and T. A. Renner, "Global Warming Impact of Gasoline vs. Alternative Transportation Fuels", SAE, Paper No. 901489, Future Transportation Technology Conference and Exposition, San Diego, California, August 13-16, 1990.
- 1-3 Unnasch, Stefan, Carl B. Moyer, Douglas D. Lowell, Michael D. Jackson, "Comparing the Impact of Different Transportation Fuels on the Greenhouse Effect", Acurex Corporation, Mountain View, CA, prepared for California Energy Commission, March, 1989.
- 1-4 Fisher, Diane C., "Reducing Greenhouse Gas Emissions With Alternative Transportation Fuels", Environmental Defense Fund, Oakland, CA, April, 1991.
- 1-5 Finizza, Anthony, "Utilization of Alternative Fuels, Economic and Energy Consequences", ARCO, Los Angeles, CA, June 1991.

2.0 Study Overview

2.1 Overview

The period of the estimates made in this study is from 1992 to 2020. The four major parts of this study are addressed in separate sections. Section 3.0 provides a comprehensive analysis of EV, FCV, and ICEV technology leading to the determination of the energy required from the tank or plug to travel a kilometer (kWh/km) over a defined driving cycle for three vehicle classes. Section 4.0 analyzes the efficiency and CO₂ emissions (g CO₂/kWh) associated with extracting, processing, and delivering a kWh of fuel to the tank. Section 5.0 analyzes current and future power generation technology to determine the efficiency and CO₂ emissions (g CO₂/kWh) to generate and deliver a kWh to the plug. Section 6.0 develops two market penetration scenarios for EV's. Section 7.0 combines the results of these analyses to estimate the overall primary energy efficiency and CO₂/km and aggregate CO₂ emissions for each vehicle class and market scenario. A spreadsheet model described in Appendix A was developed in conjunction with this study. The results presented in Section 7.0 are derived from the model using the technical inputs developed in Sections 3.0, 4.0, 5.0, and 6.0.

2.2 Study Ground rules and Methodology

The energy sources and transportation fuels studied are shown in Table 2-1. Alternative fuels considered include methanol, ethanol, and CNG fuels derived from primary energy sources such as coal, natural gas, and corn.

Table 2-1: Primary Energy Sources and Transportation Fuels Studied

Primary Energy Source	Transportation Fuel					
	Gasoline	Methanol	Ethanol	Natural Gas	Electricity	Hydrogen
Petroleum	X				X	
Coal					X	
Natural Gas		X		X	X	X
Nuclear					X	
Hydro/Solar/Geo (Renewables)					X	
Corn			X			

Electricity generated from coal, natural gas, nuclear, and renewables was analyzed for efficiency and emissions based on several generation technology scenarios ranging from coal-dominated to all natural gas.

Vehicular fuels and primary energy sources which were not analyzed include:

- LNG (as a vehicular fuel) which is likely to be a viable fuel only for buses and other heavy duty applications. However, this study considers the use of imported LNG as a source of pipeline natural gas for CNG vehicles.
- LPG which is likely to be too limited a resource for widespread use.
- Methanol from coal because the greenhouse penalty has already been clearly demonstrated^{1-1,2}.
- Synthetic fuels, ethanol, methanol, and hydrogen from biomass or other renewables since the technology for these processes is still under development. Ethanol derived from cellulosic biomass is receiving a significant amount of funding focused on improved conversion economics. Likewise, photovoltaics are not considered in this study even though they are a source for electricity or hydrogen. Successful development of cost competitive biomass derived fuel sources could largely eliminate the global warming contribution from the transportation sector while also contributing to air quality and energy security.
- Flex fuel and dual fuel vehicles since performance compromises and infrastructure complications will likely limit market penetration except during periods of transition from traditional fuels.
- Diesel fuel since battery powered light-duty EV's are unlikely to compete with or replace significant amounts of diesel fuel.

There is a significant and growing interest in hybrid vehicles incorporating combinations of prime movers (IC engines, turbines, etc.), generation devices (fuel cells), and storage devices (batteries or ultra capacitors). These vehicles show potential for improved performance compared to dedicated EV's and should be studied in a manner similar to this analysis.

Figure 2-1 shows the energy chains considered in this analysis and the associated nomenclature. The flow of energy is from primary energy sources to the vehicle (left to right). However, the calculation of CO₂ and primary energy requirements (per km travelled) necessarily proceeds from right to left starting with a determination of vehicular road load. CO₂ production is allocated to power plant, fuel chain, and vehicular sources. The market scenarios for EV utilization (km/yr) and penetration (number of vehicles on the road) are used to determine aggregate primary energy utilization and CO₂ production. The imbedded energy and CO₂ emissions resulting from infrastructure construction and vehicle manufacture are not considered in this study. This process is conducted for four time periods starting in 1992 and ending in 2020.

Figure 2-1: Overview of Energy Chain and Nomenclature

2.3 Areas of Focus

Previously, much analysis regarding transportation greenhouse effects^{1-1.2.3} has been directed at establishing the energy efficiency and CO₂ emissions associated with the ICEV fuel chain.

Because of the relatively long timeframe for this study, it is worthwhile to identify and focus on those factors which will have the greatest influence on aggregate energy consumption and CO₂ emissions now and in the next several decades. The total primary energy requirements for each energy chain shown in Figure 2-1 can be calculated by multiplying the road load by the efficiencies in each of the boxes in the chain. CO₂ emissions are approximately proportional to the total primary energy consumption.

For an EV with today's technology charged from an advanced gas technology generation base, Table 2-2 shows approximate energy chain efficiencies leading to an overall primary energy to road load conversion of 15%.

Table 2-2: Approximate Efficiencies for a 1992 EV

Fuel Production	.88
Electric Power Generation	.43
Electric Power Transmission	.92
Charger	.85
Battery	.75
Motor/Controller	.69
Approximate Overall Energy Chain Efficiency	.15

Because these efficiencies are multiplicative, higher efficiency elements must change more than those of lower efficiency in order to have the same overall influence. For instance, a 5 percentage point change in the generation efficiency has about twice the influence of a 5 percentage point change in fuel production efficiency. Additionally, the higher efficiency elements are typically harder to influence precisely because of their already high efficiency.

Following this reasoning, the elements of each energy chain with the most influence on overall energy efficiency are:

- For EV's
 - Generation efficiency.
 - Battery charge/discharge loss including thermal losses.
 - Motor/transmission/controller efficiency.
- For ICEV's
 - Engine/driveline efficiency.
- For FCV's
 - Fuel cell/reformer efficiency.
 - Motor/transmission/controller efficiency.

In addition to those listed above, other factors which will influence total energy consumption and CO₂ emissions include:

- The actual road load, which will vary significantly between vehicle types and in future years.
- The number of vehicles (market size).
- The annual travel for each vehicle.

These are the elements and factors which are the focus of the analyses presented in Sections 3.0 through 6.0.

3.0 Vehicular Fuel Consumption

This section describes the analyses of current and future vehicle characteristics which were conducted in order to provide a common set of vehicle technology assumptions for all ICEV's, FCV's, and EV's leading to the calculation of energy consumption of each vehicle type for current and future vehicles. The vehicle configurations assembled for each future time (2001, 2010, 2020) are based on estimates of the best available technology which would be ready for commercialization at that time. The actual energy consumption performance of new ICEV's for these time periods may not be as good as that predicted here depending on the response of manufacturers to regulatory, cost, and marketing influences. In terms of efficiency, the fleet average efficiency at any point in time would be lower than these point estimates, and the performance of prototype vehicles would generally be higher. The 1992 gasoline vehicles are based on actual models, while the 1992 alternative fuel and EV configurations represent the performance which could be achieved if the best available technology were utilized.

In this analysis, vehicular energy consumption is defined as the energy (kWh/km) required from the fuel tank (for ICEV's and FCV's) or from the power plug (for EV's) to travel a kilometer under a defined vehicle driving cycle. This analysis uses the EPA city/highway driving cycle³⁻¹ unless otherwise noted. ICEV energy consumption is affected by powertrain efficiency (engine and driveline) and vehicle road load (which consists of aerodynamic, inertial, and rolling resistance components). EV efficiency is affected by road load and the net efficiencies of the charger, battery, controller and motor. Dedicated FCV efficiency is affected by road load and the efficiencies of the reformer, fuel cell, controller and motor. Accessory loads (electric, power equipment, HVAC, etc.) and parasitics (such as the thermal loss from high-temperature batteries) contribute significantly to fuel consumption for all vehicle types and are discussed separately.

The analysis of vehicular road load is shown below followed by an analysis of ICEV, FCV, and EV vehicular energy consumption. Most previous studies have typically relied on percentage adjustments of gasoline ICEV miles per gallon (MPG) to account for alternative fuel combustion characteristics and a mix of presumed changes in driveline efficiency and road load reduction over time. This study evaluates the separate influences of driveline conversion efficiency, emissions, road load reduction, and accessories on vehicular energy consumption. Since the ICEV, FCV, and EV powertrain is treated as another step in the energy chain, this is consistent with the logic used to construct the fuel chain and power plant efficiency analyses and allows calculation of an end-to-end (resource to wheel) fuel chain efficiency.

3.1 Vehicle Characteristics

Three vehicle classes--small commuter car, family car, and minivan--were selected for analysis. To provide a realistic baseline, a specific 1992 gasoline powered make and model corresponding to a popular domestic vehicle with relatively current technology

was selected for each category. Table 3-1 shows characteristics of the baseline vehicles. The Escort and Taurus lines both represent popular vehicles with recently reworked configurations and relatively modern engines. The Voyager is the top selling minivan and also has a newly introduced engine. Both the Voyager and the Escort have current EV derivatives indicating the adaptability of these vehicle designs to EV requirements. Also shown in Table 3-1 is the EPA sticker mileage for the selected vehicles. This is the adjusted mileage (10% lower for city, 22% lower for highway) from vehicle dynamometer tests^{3,2}.

Table 3-1: 1992 Gasoline Vehicles Selected for Baseline

Vehicle Class	Badge (typ)	Drag Coefficient (C_d)	Frontal Area ¹ (m^2)	Curb Weight (Kg)	Cycle	EPA Mileage	EPA Combined Mileage ²
Small Commuter	Escort Sedan	.35	1.81	1075	City	25	29.5
	1.9 liter 4-speed auto				Highway	35	
Family	Taurus Sedan	.32	1.99	1425	City	20	24.1
	3.0 liter 4-speed auto				Highway	29	
Minivan	Voyager	.37	2.50	1425	City	17	19.7
	3.3 liter 4-speed auto				Highway	23	

1. 80% of overall height x width per SAE J1263.

2. 55% city, 45% highway per SAE 840496^{3,2}.

The vehicle characteristics which most strongly influence road load (at the wheel) energy consumption (kWh/km) are:

- Total vehicle inertial weight,
- Frontal area and aerodynamic drag coefficient (C_dA), and
- Rolling resistance.

Tables 3-2, 3-3, and 3-4 show the baseline values for these parameters and their expected evolution over time for the three vehicle classes. FCV characterization was conducted only for the family vehicle. In keeping with the study goals of applying equal technology to all vehicles (ICEV's, EV's, and FCV's) in the same class and time period, all vehicles in a class use common frontal area, drag coefficient, and rolling resistance values. In general, future year configurations were established using available analyses, data from vehicle prototypes, and Arthur D. Little estimates. This analysis assumes that the utility of each vehicle class will remain constant over time (the same interior volume, and acceleration.

To establish FCV, EV, and ICEV weights using a common technical baseline, a 1992 glider weight was estimated for each vehicle class by subtracting estimated fuel system and driveline weights from the base vehicle weight. The 2010 glider weight was determined as a percentage of the 1992 glider baseline vehicle weight based on the technology scenario outlined in Reference 3-3 prepared for the Office of Technology Assessment (OTA) using the Level II risk technology. This is a level of technology implementation with differing opinions regarding benefits and feasibility and is generally more aggressive than the estimates of vehicle manufacturers relative to the benefits and timing of new technology. Glider weight for 2020 assumes further weight savings resulting from improved packaging as described in Reference 3-3.

Table 3-2: Vehicle Technology Evolution - Small Car

	1992 Ford Escort	2001	2010	2020
Base Vehicle Characteristics				
Glider Weight (Kg)	860	780	705	690
C _d	.35	.26	.23	.20
Tire Coefficient C(O)	.009	.007	.006	.005
Cargo Weight (Kg)	140	140	140	140
IC Engine/Driveline				
Engine Power (kW)	68	60	56	55
Driveline Specific Weight (Kg/kW)	2.4	2.2	2.1	1.9
Driveline Weight (Kg)	165	135	120	105
Gasoline/Methanol Fuel System Weight (Kg)	50	46	42	40
Added Natural Gas Weight (Kg)	35	35	35	35
Electric Vehicle				
Battery Energy Density (wh/Kg)	55	100	175	200
Battery Energy (kWh)	26	32	45	50
Battery Weight (Kg)	480	320	260	250
Motor Power (kW)	80	69	58	52
Motor/Controller/Transm Wt. (Kg)	128	110	85	67
Total Weights				
Liquid Fuel Vehicle Weight (Kg)	1215	1100	1005	975
Natural Gas Vehicle Weight (Kg)	1250	1135	1040	1010
Electric Vehicle Weight (Kg)	1610	1350	1190	1150

Future year drag coefficients were based on OTA analyses for 2010 and the Impact for 2020 for the small car and family car. GM's HX-3 hybrid prototype³⁻⁵ was used for 2020 van characteristics. Frontal area was held constant for all vehicles and years in line with assumptions of constant interior volume. Current rolling resistance values

Table 3-3: Vehicle Technology Evolution - Family Car

	1992 (Ford Taurus Sedan)	2001	2010	2020
Base Vehicle Characteristics				
Glider Weight (Kg)	1115	1015	835	780
C _d	.32	.29	.22	.20
Tire Coefficient C(O)	.009	.007	.006	.005
Cargo Weight (Kg)	145	145	145	145
IC Engine/Driveline				
Engine Power (kW)	110	100	85	80
Driveline Specific Weight (Kg/kW)	2.3	2.1	2.0	1.8
Driveline Weight (Kg)	235	215	170	145
Gasoline/Methanol Fuel System Weight (Kg)	70	65	60	55
Added Natural Gas Weight (Kg)	47	47	47	47
Electric Vehicle				
Battery Energy Density (wh/Kg)	55	100	175	200
Battery Energy (kWh)	30	52	73	77
Battery Weight (Kg)	540	520	415	385
Motor Power (kW)	95	80	74	64
Motor/Controller/Transm Wt. (Kg)	152	138	107	83
Fuel Cell Vehicle				
Fuel Cell Nominal Power (kW)	--	25	22	20
Fuel Cell System Weight (Kg)	--	100	50	25
Fuel Processor/Supply Weight (Kg)	--	147	100	61
Battery Weight (Kg)	--	200	150	120
Total Weights				
Liquid Fuel Vehicle Weight (Kg)	1565	1440	1210	1125
Natural Gas Vehicle Weight (Kg)	1610	1485	1255	1170
Electric Vehicle Weight (Kg)	1950	1820	1500	1390
Fuel Cell Vehicle Weight (Kg)	--	1745	1410	1272

were based on data supplied by INEL³⁻⁶ and future values from OTA³⁻³ and Impact data³⁻⁴. These values again are more aggressive than those estimates typically provided by industry sources.

ICEV weight for future years was established by adding estimated weights for the driveline and fuel system to the glider weight. The driveline weight was estimated by first determining the required driveline power to hold vehicle acceleration performance constant. For the commuter car, this value is .055 kW/Kg which results in a 0-60 mph acceleration of 9.1 seconds and for the family car and van it is .070 kW/Kg. The 0-60 mph time for the 1992 Taurus is 10.4 seconds and for the T-Van is 12.6 seconds.

Table 3-4: Vehicle Technology Evolution - Van

	1992 (Chrysler T-Van)	2001	2010	2020
Base Vehicle Characteristics				
Glider Weight (Kg)	1115	1015	835	780
C _d - Van	.37	.33	.26	.25
Tire Coefficient C(O)	.009	.007	.006	.005
Cargo Weight (Kg)	145	145	145	145
IC Engine/Driveline				
Engine Power (kW)	110	100	85	80
Driveline Specific Weight (Kg/kW)	2.3	2.1	2.0	1.8
Driveline Weight (Kg)	235	215	170	145
Gasoline/Methanol Fuel System Weight (Kg)	70	65	60	55
Added Natural Gas Weight (Kg)	47	47	47	47
Electric Vehicle				
Battery Energy Density (wh/Kg)	55	100	175	200
Battery Energy (kWh)	29	52	73	76
Battery Weight (Kg)	530	515	415	380
Motor Power (kW)	100	90	75	68
Motor/Controller/Transm Wt. (Kg)	155	140	105	85
Total Weights				
Liquid Fuel Vehicle Weight (Kg)	1565	1440	1210	1125
Natural Gas Vehicle Weight (Kg)	1610	1485	1255	1170
Electric Vehicle Weight (Kg)	1945	1815	1500	1390

Driveline weight was estimated using a transmission power density of 0.9 Kg/kW for the small car and 0.8 Kg/kW for the family car and van. Engine power density was assumed to improve (from 1.5 Kg/kW in 1992 to 1.0 Kg/kW in 2020) as a result of the technology evolution discussed in Section 3.6.

Gasoline fuel system weight includes estimates for the fuel, plumbing, bracketry and vapor control system. In future years, with more efficient vehicles, gasoline fuel system weight was decreased to maintain constant range. For methanol and ethanol vehicles, the fuel system weight for all years was assumed to be equal to the gasoline system leading to lower range for these vehicles compared to the gasoline vehicle. For CNG vehicles, the available tank volume was assumed to be twice that of the corresponding gasoline vehicle, leading to a bulkier, heavier fuel system with less stored energy than gasoline. The overall weight of the ICEV commuter car decreases by 17% from 1992 to 2010 and the family car and van weights decrease by 23%. This is a slightly less aggressive overall weight reduction than that outlined in Reference 3-2.

EV weights were established by adding battery, controller and electric driveline weights to the glider weight. A 0-60 mph acceleration time of approximately 10 seconds was used for all vehicles and all time periods. As with ICEV's, the necessary EV driveline power required to hold acceleration constant was determined for each vehicle class and time period based on vehicle weight. Electric driveline weight was determined using the power density figures taken from Modular Electric Vehicle Program (MEVP) data. EV battery energy density for 1992 assumes a nickel-alkaline battery or an advanced bipolar lead acid battery. Battery energy density for 2001 is taken from the USABC mid-term technical criteria and 2020 energy density reflects the USABC advanced criteria.

Battery sizes for EV's were determined based on the assumption that improved energy density would be used principally to increase range. An alternative battery sizing scenario would be to hold EV range constant (at, say, 150 km) and reduce battery weight in correspondence to increased energy density. This "range limited" EV would require only about 10% less energy/km (due to lower inertial weight) and thus not dramatically change the conclusions of this study. In addition, a 2020 EV with a battery sized to 150 km range would have only about 70% of the power (based upon the USABC "advanced" criteria of 400 W/Kg) required to maintain equal acceleration performance.

FCV weight estimates assume a vehicle with performance and range approximately equal to the corresponding ICEV. Since this is an advanced technology, no 1992 FCV configuration was specified. For future years, the Proton Exchange Membrane (PEM) fuel cell is the assumed technology because this technology holds the most promise for traction applications in terms of efficiency, start-up, and power density.

For 2001, the fuel cell was sized at 25 kW to provide good gradability at nominal power (constant 88 km/h on a 3% grade). Peak power demand (an additional 80 kW) was assumed to be provided by a 200 kg battery (400 w/kg). For 2020, the fuel cell nominal power requirement was 20 kW available at start-up using on-board hydrogen. No warm-up is assumed, and the fuel cell is assumed to load follow-up to 60 kW so that only a 20 kW battery was assumed.

The FCV motor/controller weights are assumed to be the same as for EV's of the same year. The fuel cell stack and fuel processor weights are derived from Arthur D. Little estimates of fuel cell power density. For 2001, this is based on near-term prototypes with a cell current density of approximately 500 amps/square foot (Asf) yielding a stack power density of 2.2 Kg/kW. The total fuel cell system including the cathode air pressurization system is assumed to weight 4.0 Kg/kW. For 2020, a current density of 2000 Asf is assumed along with substantial reductions in cell thickness and increases in active area for an estimated stack power density of .44 Kg/kW (1.0 Kg/kW for the system). For the 2001 configuration, methanol and an on-board reformer are the fuel source for the fuel cell (2.0 Kg/kW). For 2020, a hydride bed with a storage density of .045 Kg H₂/Kg is assumed based on magnesium hydrides or surface activated carbons³⁻⁸.

In summary, all of the hypothetical vehicles were assumed to maintain the same acceleration performance over time. Because a common glider weight was used for all vehicles within a class, because of the aggressive technology assumptions for all technologies and because battery technology was assumed to increase range (rather than reduce EV weight), the resulting decrease in ICEV weight (28% in 2020 for family car) is very similar to the decrease in EV weight (29%). Range estimates for all vehicles are shown at the end of this section.

3.2 Road Load Calculation

The vehicle parameters given in the previous section were used to calculate the road load (power at the wheels) over the EPA City and Highway driving cycles using SIMPLEV, an electric vehicle simulator³⁻⁸. SIMPLEV was used to determine the road load for ICEV's as well as EV's and FCV's since the vehicle road load equations depend only on the vehicle characteristics and driving cycle velocity profiles and not on the source of motive power.

The average energy delivered to the wheels (kWh/km) over each driving cycle was determined by integrating the tractive power load at the wheels over the cycle and dividing by the cycle distance. The composite city/highway road load was calculated using the EPA consumption weighting of 55% city and 45% highway. Table 3-5 shows the calculated composite road loads for each vehicle class for liquid fueled ICEV's and for the heavier EV/FCV's.

The calculated EPA composite road load for CNG powered vehicles is 2% to 4% greater than that shown for gasoline, methanol, and ethanol powered vehicles due to tank weight. Although the FCV weighs slightly less than the equivalent EV family configuration for each time period, this analysis assumes the same road load for both configurations. The estimated decline in road load for ICEV's is 36-40% over the 28-year period. The decline in EV/FCV road load is 42% to 46% over the same period.

Section 3.9 describes how these road load calculations are combined with driveline efficiency estimates (discussed in the following section) to estimate the energy from the tank for ICEV's.

Table 3-5a: Calculated EPA Composite Road Load for Gasoline, Methanol and Ethanol Powered Vehicles [ICEV's] (kWh/km)

Vehicle	1992	2001	2010	2020
Small	0.097	0.077	0.069	0.061
Family	0.115	0.099	0.079	0.069
Van	0.131	0.113	0.090	0.082

Table 3-5b: Calculated EPA Composite Road Load for EV's and FCV's (kWh/km)

Vehicle	1992	2001	2010	2020
Small	.118	.096	.087	.084
Family	.134	.134	.118	.095
Van	.149	.144	.129	.111

3.3 ICEV Powertrain Efficiency and Emissions

This section describes the methodology for calculating emissions and efficiency of gasoline and alternative fueled internal combustion engine vehicles for 1992 and future years. The object of this analysis is to determine the actual effective efficiency of the ICEV driveline (engine and transmission) in converting fuel energy from the tank to power at the wheels under the specified driving cycles. Future improvements in powertrain conversion efficiency are then tied to specific technical developments. All ICEV efficiencies are based on the lower heating value (LHV) of the fuel in keeping with accepted convention. In the summary analyses, these are converted to HHV to be compatible with HHV efficiencies derived for electricity generation and fuel processing.

To our knowledge, there are no data sources documenting the average driveline efficiency of present generation gasoline or alternative fuel engines. Although engine performance maps are sometimes available (fuel consumption as a function of speed and torque), these maps must be combined with a vehicle description (transmission efficiency, shift schedule, etc.) and driving cycle (speed vs. time) in order to determine average cycle driveline efficiencies. Complete engine performance maps for dedicated alternative fuel engines are not generally available. Therefore, the ICEV average cycle efficiency was derived from EPA mileage ratings which represent empirical data for 1992 gasoline ICEV's. Average cycle efficiencies for other fuels and for future timeframes were determined from this baseline in the manner described below. The effective driveline efficiency for the 1992 gasoline vehicles was determined based on EPA fuel consumption data (see Table 3.1) and road loads for the baseline gasoline vehicle calculated using SIMPLEV. The effective driveline efficiency is defined by this study as the efficiency at which energy from the tank is converted into useful energy at the wheels under conditions which approximate actual usage:

$$\eta_{\text{effective}} = \frac{\text{"Useful" Energy}}{\text{Total Energy}} = \frac{\text{Integrated Road Load}}{\text{LHV/MPG}^*}$$

*Driving Cycle Distance

where LHV is the lower heating value of the fuel kWh/gal and MPG is the EPA adjusted composite mileage (converted to km/gal). The adjusted city EPA mileage is 10% lower than the fuel economy measured on the city dynamometer test specified in Reference 3-1, while the adjusted highway fuel economy is 22% lower. The composite fuel economy adjustment of about 15% is meant to approximate in-use fuel economy. Some observers (Reference 3-3) have argued that because of increased urban congestion

and higher average highway speeds typical of current driving patterns, this adjustment understates the in-use fuel economy. The analyses presented here are based only on the EPA adjustments.

Table 3-6 shows the 1992 city and highway effective driveline efficiency for gasoline engines. The composite driveline efficiency is low when compared with the maximum engine efficiency. For a given engine, efficiency is a function of both speed and torque. Brake thermal efficiency can range from zero (at idle) to approximately 28% (peak efficiency) for typical automobile gasoline engines. Typical transmission efficiency is 90% but is also low at light loads. During normal driving, a significant amount of time is spent at idle, braking, or low load conditions leading to relatively low effective driveline efficiency.

Table 3-6: Calculated Effective Driveline Efficiency for 1992 Gasoline ICEV Vehicles - EPA Composite Cycle

Vehicle Class	EPA Composite MPG	Composite Road Load kWh/km	Effective Driveline Efficiency
Small	29.5	0.097	0.136
Family	24.1	0.115	0.132
Van	19.7	0.130	0.122

Effective driveline efficiency for 1992 alternative fuel ICEV and for future year ICEV's was derived from the 1992 gasoline baseline. Estimates of the percentage change in driveline efficiency were based on consideration of fuel characteristics, specific engine design changes and transmission changes.

Assumptions regarding allowable tailpipe emissions significantly influence the timing and applicability of technology. Table 3-7 shows the Federal Tier 1 Emissions standards and the California Low Emissions Vehicle Program 50,000 Mile Standards for Passenger Cars. Table 3-8 shows the analysis of the engine and transmission driveline changes which will affect the effective driveline efficiency for ICEV's assuming Federal Tier 1 Standards, while Table 3-9 shows the same analysis assuming LEV/ULEV standards. These efficiency improvements are all derived from estimates made by Arthur D. Little as described below.

Table 3-7: Tailpipe Emissions Regulations (g/mile)

Category	NMOG	CO	NO _x
Federal Tier 1	.250	3.4	0.4
LEV	.075	3.4	0.2
ULEV	.040	1.7	0.2
ZEV	0.000	0.0	0.0

Table 3-8: Summary of Projected IC Engine/Driveline Efficiency Improvements - Federal Tier 1 Emissions

	1992		2001		2010		2020
Gasoline	1.0 Base	→	1.10 (+10%)	→	1.15 (+5%)	→	1.27 (+10%)
	↓		<ul style="list-style-type: none"> • Reduced Friction • Variable Valve Timing 		<ul style="list-style-type: none"> • Indiv Cyl Control • 5-Speed or CVT 		<ul style="list-style-type: none"> • Advanced Engine (2-stroke, S.I., Lean Burn)
Methanol/ Ethanol	1.15 (+15%)	→	1.29* (+12%)	→	1.42 (+10%)	→	1.62 (+15%)
	<ul style="list-style-type: none"> • 12:1 Compression • Fuel Effects 		<ul style="list-style-type: none"> • Same as Gasoline • 14:1 Compression 		<ul style="list-style-type: none"> • Same as Gasoline • Lean Burn 		<ul style="list-style-type: none"> • Unthrottled • Compression Ign 2-Stroke
Natural Gas	1.05 (+5%)	→	1.21* (+15%)	→	1.28 (+5%)	→	1.45 (+15%)
	<ul style="list-style-type: none"> • 10.5:1 Compression 		<ul style="list-style-type: none"> • Same as Gasoline • Lean Burn 		<ul style="list-style-type: none"> • Same as Gasoline 		<ul style="list-style-type: none"> • Unthrottled • Compression Ign 2-Stroke

*Technology would likely meet Federal Tier 1 but not LEV standards.

Federal Tier 1 Driveline Efficiency Improvements

For conventional gasoline engines under Federal emissions standards, it is estimated there will be approximately a 10% increase in efficiency (new vehicle average) in the next 8 to 10 years. Efficiency improvements are expected to come from several technical innovations which are now under development. It is expected that the main efficiency improvements will come from friction reduction methods and variable valve timing. Friction reduction methods include modified lubricants and low friction mechanical designs such as roller cams. Any reduction in friction power can be translated directly to shaft power. Advanced valve control (variable valve timing) allows an engine to be "tuned" for a wider operating range yielding higher efficiency over most of the driving cycle.

In the 2010 time period, an additional 5% increase in efficiency is expected for gasoline engines as a result of transmission advancements and advanced electronic engine control individual cylinder control. In a multi-cylinder engine, there is a certain degree of cylinder to cylinder variation. These cylinder variations require the manufacturer to tune an engine based on the worst cylinder. For example, today spark timing for the whole engine is set so that no cylinder will experience knock. By controlling spark timing, fuel/air ratio, and other parameters on a cylinder by cylinder basis, each cylinder can operate more efficiently. Additional driveline efficiency improvements may come

Table 3-9: Summary of Projected IC Engine/Driveline Efficiency Improvements - LEV/ULEV Emissions

	1992		2001 (LEV)		2010 (LEV/ULEV)		2020 (ULEV)
Gasoline	1.0 Base ↓	→	1.10 (+10%) • Reduced Friction • Advanced EGR Control • Variable Valve Timing	→	1.15 (+5%) • Indiv Cyl Control • 5-Speed or CVT	→	1.15 (no change) • Advanced 3-way catalyst formulation
Methanol/ Ethanol	1.15 (+15%) • 12:1 Compression • Fuel Effects	→	1.29 (+12%) • Same as Gasoline • 14:1 Compression	→	1.35 (+5%) • Same as Gasoline	→	1.35 (no change) • Same as gasoline
Natural Gas	1.05 (+5%) • 10.5:1 Compression	→	1.21 (+15%) • Same as Gasoline • Lean Burn • Lean NO _x Catalyst	→	1.27 (+5%) • Same as Gasoline	→	1.33 (+5%) • Unthrottled • Advanced Lean NO _x Catalyst • Compression Ign 2-Stroke

from 5 or 6 speed automatic transmissions or continuously variable transmissions (CVT). These transmission improvements will allow the engine to operate more of the time in the higher efficiency speed-load range.

In the 2020 timeframe, a 10% efficiency improvement is estimated to come from a major technical innovation such as a two-stroke, spark-ignited, lean burn gasoline engine. Lean burn offers efficiency improvement through a favorable change in the working fluid properties (increase in the ratio of specified heats) and a reduction in throttling losses. Two-stroke engines have higher power density than their four-stroke counterparts--a factor which is also incorporated into the vehicle weight estimates presented earlier.

Alcohol and natural gas fueled engines are expected to benefit from the same advances that increase the efficiency of gasoline fueled engines. However, these fuels offer additional advantages from an engine efficiency perspective.

If dedicated methanol vehicles were produced today (there are no commercially produced dedicated alcohol or natural gas passenger vehicles due to a number of reasons including the lack of a refueling infrastructure), it is estimated that these engines would have approximately 15% higher efficiency than conventional gasoline engines due primarily to fuel effects and increased compression ratio. Methanol has a high octane number which allows the engine designer to increase the compression ratio significantly (from approximately 8.5:1 to 12:1) resulting in higher thermal efficiency.

In the 2001 timeframe, it is expected that alcohol fueled engine efficiency will increase an additional 12%. Most of this increase is due to the same improvements as in gasoline engines (friction reduction, variable valve timing). A small additional increase (approximately 2%) can be expected if engine designers raise the compression ratio closer to maximum allowable for the fuel which is estimated between 13:1 and 15:1.

In the 2010 timeframe, a 10% efficiency increase from the 2001 scenario is estimated. Half of the increase is due to gasoline engine improvements (individual cylinder control, continuously variable transmission). It is also expected that lean burn technology can be applied resulting in an additional 5% efficiency increase. In 2020, it is expected that a major technical innovation such as an unthrottled two-stroke compression ignition, methanol engine (similar to today's diesel engine) for automotive applications will result in a 15% increase in efficiency over the 2010 scenario.

If dedicated natural gas vehicles were produced today, it is estimated that the engines would be about 5% more efficient than the gasoline equivalent. Natural gas also has a higher octane number than gasoline which would allow boosting the compression ratio to approximately 10.5:1. This compression ratio is common for current production stationary engines such as gen-set applications.

The 2000 to 2020 scenarios for natural gas are similar to the methanol scenario described above. The major differences being that compression ratio increase would not be as dramatic (limited to approximately 10.5:1) and lean burn technology would be applied 10 years earlier (there are numerous examples today of automotive size lean burn natural gas engines in stationary applications). Figure 3-1 compares the estimated driveline efficiency for the commuter vehicle using these Tier 1 estimates.

LEV/ULEV IC/Driveline Efficiency Improvements

LEV and ULEV emissions standards are likely to apply to the markets where ICEV's compete with EV's. Meeting these LEV and ULEV standards will have a significant impact on the implementation of technologies which affect efficiency. Based on the California Clean Vehicle Implementation Schedule (see Section 6.0), it is assumed that LEV standards will apply to new cars in the year 2000 and ULEV standards will apply in 2020, resulting in lower efficiency improvements than predicted than under the Federal Tier 1 scenario. The estimated driveline efficiency changes under these standards are shown in Table 3-9.

Figure 3-1: Effective Driveline Efficiency - Tier 1 Emissions, Commuter Vehicle

Gasoline engines are still expected to see improvements from friction reduction, variable valve timing, individual cylinder control of spark timing and fuel injection, and advanced transmissions. However, it is expected that they will require new emission control strategies such as heated catalysts (for lower HC) and advanced EGR (lower NO_x) to meet LEV standards. In addition, it is far less likely that a major innovation such as a lean burn two-stroke engine can meet ULEV standards. Instead, it is more likely that stoichiometric spark ignited four-stroke engines with sophisticated electronic control and new catalyst formulations will be the norm.

The same reasoning applies to alcohol engine efficiency predictions. Lean burn and/or unthrottled compression ignition strategies are judged to be too risky (i.e., low probability of meeting ULEV standards). Natural gas engines, however, do have a reasonable chance of meeting LEV and ULEV standards using lean burn and/or unthrottled compression ignition technology. This is due mainly to the low reactivity of natural gas exhaust hydrocarbons making it more likely they can meet the non-methane organic gases (NMOG) standard.

Figure 3-2 shows the estimated effective driveline efficiency change for LEV/ULEV emissions standards.

Projected efficiencies would be lower for dual fuel alternative fuel vehicles owing to the combustion and engine design compromises inherent in multi-fuel engines. Although the vehicular fuel scenario proposed by the Multi-Agency Task Force on Alternative Fuels³⁻⁹ involves a significant number of dual fuel vehicles, the results of this study are based on dedicated alternative fuel engines which illustrate the full efficiency potential of alternative fuels.

Figure 3-2: Effective Driveline Efficiency - LEV/ULEV Emissions, Commuter Vehicle

3.4 Engine Accessories and HVAC

The composite EPA mileage used to calculate the effective driveline efficiency for ICEV's implicitly includes some recognition of parasitic accessory loads (power steering, power brakes, alternator etc.) since these accessories are present on the vehicle but not operating under load during the EPA mileage test. No recent data was found on accessory loads, but the EPA test protocol³⁻¹⁰ does not capture the actual engine loads such as those caused by alternator demands (headlights, battery charging, etc.) or the active loads from other belt powered equipment such as power steering. While the analyses presented earlier estimate a composite road load reduction of approximately 40% over the next 28 years, it is very likely that engine accessory loads will increase over this time. Some of the increased accessory power demand may be feature-driven (such as active suspension or windshield deice), while some may result from regulatory action (for instance, electrically heated catalysts). As a result, it is likely that accessory loads for ICEV's will require a greater portion of total engine load over time. This factor is not recognized by this analysis due to the lack of actual data regarding current or future engine accessory data.

The baseline EPA mileage for the selected 1992 vehicles also includes a simulated load for air conditioning since all vehicles selected have an air conditioning accessory market penetration of over 33%. Current belt-driven ICEV air conditioning systems require 3 kW or more during operation under nominal conditions³⁻¹¹. The test procedure for measuring EPA mileage for light duty vehicles and trucks specifies an increase of 10% in the dynamometer power absorber (DPA) setting. The DPA setting simulates the power required at 50 mph (80 km/h) to overcome loads produced by aerodynamic drag and rolling resistance for the set of wheels which are not loaded by the dynamometer.

For the 1992 Taurus, the 10% DPA adjustment was 0.53 hp (.40 kW) according to the EPA³⁻¹². The power actually absorbed by the dynamometer as a result of the DPA adjustment varies as the cube of the velocity so this adjustment roughly corresponds to a 0.05 kW addition at 40 km/h (the approximate average speed during the urban cycle) and no load at zero speed. Therefore, the EPA adjustment simulates a very modest air conditioning utilization of around 1.7% (.05/3) on the city cycle.

Based on the preceding discussion, it is likely that the current EPA test procedure significantly underestimates the power requirement for auxiliary loads and air conditioning. Since all ICEV efficiencies were derived from the 1992 baseline, the estimated energy consumption attributed to these losses declines in future years in proportion to the decline in calculated road load and the increase in engine efficiency. In actuality, these loads are likely to hold steady or grow so their significance will increase as reductions in road load reduce propulsion energy requirements. However, no compensating adjustment has been made to the ICEV energy requirement estimates in this study.

3.5 EV Driveline and Battery Efficiencies

Figure 3-3 shows in schematic form the losses in an EV from the plug to the road and the estimates of those losses made in this study. Charger efficiency of 85% is typical of current chargers³⁻¹³. Solectria claims to already have a 90% efficient charger³⁻¹⁴. For 2020, it is assumed that additional increases in charger efficiency may be gained by reducing switching or I²R losses. Consideration is currently being given to an inductive coupling between the EV and the charger for safety and ease of use. The coupling losses could be between 1% and 5% and are not included in this analysis.

Figure 3-3: Electric Vehicle Power System Losses

The battery charge/discharge efficiency of 75% shown for 1992 and 2001 is typical of lead acid and some near term batteries.^{3-15,16} However, the charge/discharge efficiency can range from 50% to 90%³⁻¹⁷ depending on the battery depth of discharge and the charging power profile. It is assumed that the charge/discharge efficiency of advanced batteries including sodium sulfur will increase to 85% to 90%.

The 1992 controller and driveline motor efficiencies are estimates of the likely composite driving cycle averages derived from constant speed efficiency measurements of a current EV³⁻¹⁷. The 2020 values are representative of the peak efficiency now achieved in controllers and drivelines.

The regeneration fraction represents the amount of battery energy actually supplied by regeneration. All values are based on composite drive cycle simulation data. The maximum theoretical regeneration energy available at the wheels with 100% component efficiency is approximately equal to the inertial fraction of the total driving cycle energy. Figure 3-4 shows that the inertial fraction of total road load over the city cycle actually increases over time as a result of the vehicle technology assumptions made in this analysis. Aerodynamic and rolling resistance reduce the available regeneration energy which can be captured. In addition, motor, controls and battery charge/discharge losses dissipate additional amounts of regenerative energy.

Figure 3-4: Vehicle Energy Available for Regeneration - Urban Cycle, Small Commuter EV

The net battery thermal loss was estimated for high temperature batteries (2001 and later) using the USABC criteria of 3.2 W/kWh as a baseline. This is a continuous loss which must be supplied from the wall plug, the battery itself or by the heat generated during charge/discharge. Vehicle mileage is an important consideration in calculating the effect of net thermal losses on EV energy consumption. For identical vehicles, the thermal loss measured on a per km basis is lower for vehicles traveling more km per day because of the increased distance over which the fixed loss can be spread and due to the greater charge/discharge loss (which is assumed in this analysis to result entirely in useful battery heating thereby reducing net thermal loss) resulting from the increased energy consumption from the battery.

For sodium sulfur batteries, the charging process is endothermic, and part of the charging loss is used to provide the necessary heat of reaction to prevent battery temperature decreases. The discharge process is exothermic so that this heat release associated with discharge coupled with I^2R heating may lead to a requirement to dissipate heat outside the battery system during periods of heavy discharge such as hill climbing to avoid battery overheating.

The reported thermal loss for a current 60 kWh prototype sodium-sulfur battery is 700 watts or 12 W/kWh³⁻¹⁸ or about four times the USABC criteria. This loss factor is used in several alternative analyses to illustrate the importance of achieving the USABC thermal loss goal.

The assumptions relative to thermal losses used for the baseline analysis include:

- A thermal loss factor of 3.2 W/kWh based on the USABC criteria.
- All battery charge/discharge losses result in useful heat energy which offsets battery thermal loss. This may only be partially correct if discharge thermal losses require active battery cooling.
- Significantly increasing battery capacity in future time periods as discussed earlier in this section. The effect of reduced battery sizes is discussed below.
- Mileage for different vehicle types was taken from Section 6.0.

Table 3-10 shows the calculated thermal loss for the baseline analysis and several alternative sets of assumptions. These calculations indicate that high temperature batteries will significantly compromise EV efficiency unless:

1. High-temperature battery thermal loss factors are reduced below the USABC of 3.2 W/kWh, or
2. EV configurations with high-temperature batteries are designed so that a significant fraction of the battery capacity is used in average daily travel.

The impact of high-temperature batteries on primary energy consumption and CO₂ emissions is discussed in detail in Section 7.0.

Table 3-10: High Temperature Battery Thermal Loss Comparison Calculations

Configuration	Yearly Travel (km)	Battery Thermal Loss Factor (W/kWh)	Vehicle Thermal Loss (kWh/km)	Increase in Energy "From Plug" Due to H.T. Battery	Notes
Small commuter: • 2010 configuration • 45 kWh battery	11,000	3.2	.098	63%	Baseline for this analysis
	11,000	2	.055	35%	Equivalent to 38% lower loss than USABC or 28 kWh battery
	11,000	12	.417	270%	Thermal loss of current NaS batteries
	26,600	3.2	.030	19%	Commercial or fleet yearly travel
Family: • 2010 configuration • 73 kWh battery	16,600	3.2	.100	49%	Baseline for this analysis
Van: • 73 kWh battery	26,600	3.2	.051	27%	Baseline for this analysis
	26,600	12	.262	120%	Thermal loss of current NaS batteries
	11,000	3.2	.160	73%	Commuter travel

Accessory loads for vehicle electrical systems and electrically driven pumps for steering and brakes were assumed to total about 400 watts or approximately .01 kWh/km over a composite drive cycle. EV heating and deicing was assumed to be supplied from motor/controller battery waste heat. EV air conditioning was assumed to require 1000 watts³⁻¹⁹ and operate 40% of the year adding another .01 kWh/km. The .02 kWh/km added for EV parasitics equals 0.8 kW at 40 km/h and is a minimal representation of likely actual parasitic loads corresponding to the very modest parasitic loads assumed in the ICEV analysis.

3.6 Fuel Cell Vehicle Efficiencies

Figure 3-6 shows in schematic form the estimated losses for a FCV from the fuel tank to the road. As described in Section 3.1, the 2001 FCV configuration is based on methanol stored and reformed on-board while for 2010 and 2020 hydrogen is stored on-board.

For the on-board reformer/PEM fuel cell, the combined conversion efficiency is estimated to be 40% (gross stack electrical output/methanol HHV) based on estimates made by Arthur D. Little. This efficiency assumes a 50% efficient stack, 85% hydrogen utilization (with the balance consumed by the reformer) and a 5% compression energy requirement for cathode air. By 2020, major advances in PEM technology are assumed including operation at near atmospheric pressure (which reduces compression energy requirements) and higher temperature operation (over 100°C). The estimated fuel cell stack efficiency for this configuration is 55% (HHV).

Because the fuel cell is not likely to be able to respond to transient power requirement (particularly when operated with a reformer), a battery or other storage device is required. Depending on instantaneous demand, power produced by the fuel cell is split between the electric driveline and the storage device, which in this analysis is assumed to be a battery. The fraction of energy which is stored before use depends on the driving

Figure 3-6: Fuel Cell Vehicle Power System Losses

	η_{hydride}	$\eta_{\text{fuel cell (HHV)}}$	η_{storage}	$\eta_{\text{regeneration}}$	η_{motor}	Regeneration Fraction of Gross Stack Output	Accessory and A/C Load (kWh/km)
2001	N/A	.40	.94	.94	.80	.08	.02
2010	.97	.47	.96	.94	.85	.10	.02
2020	.97	.55	.99	.96	.88	.12	.02

cycle demand, the output of the fuel cell and the vehicle operating strategy. The configuration options for series hybrids such as this are now receiving significant attention through several DOE programs at INEL and General Motors, but much further analysis and development is required to determine optimum component sizes and control strategies. The storage efficiency shown in Figure 3-6 indicates the effect of the storage system losses on the overall delivery efficiency. Based on hybrid vehicle simulation results using the FCV characteristics from this analysis (Reference 3-6) only about 40% of the fuel cell output will go directly to the driveline, while 60% will be first stored by the battery. The battery charge/discharge efficiency is assumed to improve over time from 90% in 2001 to 98% in 2020, thereby improving the storage system efficiency.

3.7 Summary of Vehicle Energy Requirements

Figures 3-7, 3-8, and 3-9 show the energy consumption (Wh/km) from the tank (or plug) in various years for the small commuter vehicle over the urban driving cycle and the minivan and family configurations over the composite driving cycle. Although this is the energy consumption which is most apparent to the user, it should be remembered that the most significant efficiency penalty for EV's occurs during power generation further up the energy chain. However, the most significant efficiency penalties for ICEV's and FCV's occur on the vehicle and are reflected in the energy "from the tank" figures. The energy requirements for the ICEV's (ULEV emissions scenario) are between 2.5 and 4 times larger than the EV's, and all ICEV's and low-temperature EV's show a decrease of about 40% in energy requirements over the time period of this study. Approximately two-thirds of the decrease in the EV and gasoline ICEV energy consumptions are due to decreased road load with engine or conversion efficiency responsible for the other one-third. For alternative fuel ICEV's, road load reduction and

engine efficiency contribute approximately half each to the decrease. EV energy requirements for the urban cycle are about 10% to 20% higher than for the composite driving cycle and show the same trends. The miles per gallon equivalent for the gasoline ICEV is also shown for the gasoline ICEV's to further illustrate the significant increase in estimated overall efficiency.

Table 3-11 summarizes the gasoline ICEV composite cycle fuel economy estimates which results from the relatively aggressive vehicle and driveline technology assumptions presented in this chapter. As this report was in final preparation, a report by the National Academy of Sciences (NAS) was issued (3-20) assessing the "technically achievable" CAFE levels through 2006. The estimates shown in Table 3-11 are slightly higher than the estimates of achievable CAFE levels from the NAS study. The NAS report considers not only technical achievability but also economic and industrial competitiveness. The intent of this analysis was to demonstrate how EV's would compare with ICEV's if both were the subject of the same technology implementation. Any lower gasoline ICEV performance, such as the lower CAFE levels recommended by NAS, will increase the energy consumption and CO₂ advantages of EV's discussed in Section 7.

Table 3-11: Summary of Composite Cycle Fuel Economy Estimates - Gasoline ICEV's

	1992	2001	2010	2020
Small Commuter	30	41	48	54
Family	24	31	41	44
Minivan	20	25	33	37

Figure 3-7: Energy Consumption From the Tank (or Plug) - Small Commuter, Urban Cycle, LEV/ULEV

Figure 3-8: Energy Consumption From the Tank (or Plug) - Minivan, Composite Cycle

Figure 3-9: Energy Consumption From the Tank (or Plug) - Family Car, Composite Cycle

References

- 3-1 Federal Register, CFR 40-600.11, EPA.
- 3-2 Hellman, Karl H. And J. Dillard Murrell, "Development of Adjustment Factors for the EPA City and Highway MPG Values", SAE Paper No. 840496, Presented at the International Congress & Exposition, Detroit, Michigan, February 27-March 2, 1984.
- 3-3 U.S. Congress, Office of Technology Assessment, "Improving Automobile Fuel Economy: New Standards, New Approaches", OTA-E-504, Washington, D.C.: U.S. Government Printing Office, October 1991.
- 3-4 GM Impact Electric Vehicle, Technical Highlights, GM Technical Center, Warren, Michigan, Technical Information Release, January 3, 1990.
- 3-5 HX³ Hybrid Concepts, GM Technical Center, Warren, Michigan, Technical Information Release, January 9, 1991.
- 3-6 A. Burke, DOE/EG&G, Idaho Falls, Idaho, personal communication.
- 3-7 Noh, J. S., R. K. Agarwal and J. A. Schwarz, "Hydrogen Storage Systems Using Activated Carbon", *J. Hydrogen Energy*, Vol. 12, No. 10, pp. 693-700, 1987.
- 3-8 Cole, G. H., "SIMPLEV: A Simple Electric Vehicle Simulation Program - Version 1", EG&G Report DOE/ID-10293, June, 1991.
- 3-9 Second Interim Report of the Interagency Commission on Alternative Motor Fuels, September, 1991.
- 3-10 40 CFR 86.127-80 and 40, 1/9/92.
- 3-11 Personal communication with Bob Bendeen, Sanden Corporation, Dallas, Texas, January 9, 1992.
- 3-12 Personal communication with Tom Ball, U.S. EPA, Ann Arbor, Michigan, February 27, 1992.
- 3-13 Hardin, J.E. And Martin, M.E., Laboratory Testing of the Sonnenschein Charger EG&G report EP-9015, September 1990.
- 3-14 Technical Data Sheet, Solectria Electronics Division, Arlington, MA, November, 1991.
- 3-15 Electric Vehicles: Performance, Life-Cycle Costs, Emissions and Recharging Requirement. Transportation Research Volume 23A, Pergamon Press, 1989.

- 3-16 Buoncrota, A and P. Menga, "Application of a Mathematical Model of the Lead Acid Battery in the Design and Operation of Electric Vehicles", 10th International Electric Vehicle Symposium, December, 1990.
- 3-17 Burke, A. Ford, McDowell, R.D., Performance Testing of the Eaton Dual Shaft Electric Propulsion (DSEP) System, DOE/ID-10-366, June, 1991.
- 3-18 EG&G Report, EP-9688, December 1991, Prepared for The U.S. Department of Energy, A. F. Burke, 1/92, 7th Annual Battery Conference.
- 3-19 EG&G Report EP-9831, "Study of Long-Term Options for Electric Vehicle Air Conditioning", Prepared by Arthur D. Little, July, 1991.
- 3-20 National Research Council, "Automotive Fuel Economy, How Far Should We Go?" National Academy Press, 1992.

4.0 Fuel Conversion Efficiency and Fuel Chain Emissions

This section estimates the fuel conversion efficiency and the emissions of CO₂ resulting from producing and delivering fuels used in heat engines. The energy requirements for each step in the fuel chain from resource extraction to fuel delivery and the related CO₂ emissions for each step have been estimated on the basis of a kWh-(HHV) of energy delivered to the vehicle fuel tank. Figure 4-1 illustrates, for example, the major steps in the energy chain for CNG along with the efficiency for each step. CO₂ emissions consider not only the energy consumed in each step but also the carbon content of the fuel used and CO₂ allocations to other byproducts. Emissions of methane were analyzed for appropriate steps and aggregated and discussed separately. Because this analysis shows that methane emissions make a relatively small contribution (less than 5%) to global warming relative to CO₂, methane emissions are not included in the aggregated emission results presented in Section 7.0.

Fuel chain efficiencies are used in the overall analysis of the efficiency of converting primary fuel to road load. In addition, the fuel chain analysis provides useful insights for alternative fuel policy planning since the overall conversion efficiency of alternative fuels utilizing the same resource base (i.e., methanol and CNG are both derived from natural gas) can be compared as a way of measuring the efficiency of energy resource utilization.

Figure 4-1: Natural Gas Fuel Chain

4.1 Fuel Chain Efficiencies

The efficiency and CO₂ estimates used in this study were compiled from independent analyses as well as from several fuel chain studies^{4-1,2,3} which have been previously published. In areas where existing analyses agree or where the impact of any variations were judged to be small, no new data have been added. For instance, all fuel transport and delivery efficiencies except CNG were taken from the literature⁴⁻². Additional analyses and data from other sources have been added to areas of more significant impact for the methanol, ethanol, and natural gas fuel chains, including natural gas compression, methanol reformation, ethanol conversion, and fuel cell fuels.

Figure 4-2a shows the energy flow for a typical process step where the input stream I, the process stream P, and the output stream O may all be of different energy forms or derive from different primary energy sources. For simplicity in dealing with the calculation of primary energy requirements (but not CO₂) for fuels derived from fossil sources in this analysis, a simplified process is assumed in which the process energy is assumed to be derived from the entering energy stream. For example, all methanol and natural gas fuel chain steps assume that natural gas (the primary energy source) is used for all process requirements. Where the process energy is an electrical requirement, a 35% conversion efficiency is assumed.

In Figure 4-2b, the efficiency is defined in terms of the energy output by the process since this analysis will compare alternative energy paths on the basis of equivalent end-use impact (i.e., a kWh of fuel delivered to the tank or a km of distance traveled by the vehicle).

The CO₂ emissions for each fuel chain step depend on the chemical content of the process fuel, the efficiency of that step, and the overall fuel chain efficiency (since this determines how many units of primary fuel energy must be extracted and processed to deliver a unit of energy to the fuel tank).

In addition, the utilization of CO₂ in fuel conversion steps (for instance, in methanol conversion) and the allocation of CO₂ to other process byproducts (as is the case for gasoline and ethanol) must be considered.

Carbon content and other physical properties, including the lower heating value (LHV) and higher heating value (HHV) for transportation fuels, are shown in Table 4-1 (generating fuels are discussed in Section 5.0). The CO₂ emissions are based on the complete combustion of the fuel in air based on the HHV.

Figure 4-2a: Calculation of Actual Process Efficiencies

$$\eta = \frac{O}{P + I}$$

Figure 4-2b: Calculation of Simplified Process Efficiencies

$$\eta = \frac{O}{T} = \frac{O}{O + P}$$

Table 4-1: Transportation Fuel Data

Fuel	Formula	Density	% Carbon	LHV (kWh/Kg)	HHV (kWh/Kg)	Emissions g CO ₂ /kWh (HHV)
Gasoline	C _n H _{1.87n}	0.737	86.6	12.15	13.05	243.7
Methanol	CH ₃ OH	0.790	37.5	5.56	6.20	222.5
Ethanol	C ₂ H ₅ OH	0.787	52.2	7.43	8.27	231.0
CNG	CH ₄	0.163	75.0	13.89	15.44	178.1

In order to accurately reflect the CO₂ contribution from conversion processes (i.e., natural gas to methanol), both carbon and energy balances were considered for each step based on data from Acurex⁴⁻³ and DOE⁴⁻⁴.

Fuel Chain Efficiencies

Conversion efficiencies and CO₂ production for each fuel chain are summarized in Table 4-2. The net delivery efficiency is the multiplicative sum of four fuel chain elements. The values used in the baseline analysis are shown in bold type. Data sources and other issues for efficiencies and CO₂ production are discussed separately below.

Table 4-2: Fuel Chain Efficiency (Percent) and CO₂ Emissions

	Gasoline From Crude	Methanol From Natural Gas	CNG From Domestic NG	CNG From Imported LNG	H ₂ From NG	Ethanol From Corn	Ethanol From Wood ²
Feedstock Extraction/ Farming/ Transport	96	94	94	94	94	71	39
Processing and other Losses	90	67-73	97	97	97	47	100 ³
Delivery	--	96	97	85	97	95	95
Local Distribution and Fueling	98	94	87-96	87-96	80	98	98
Net Delivery Efficiency	85	56-62	77-85	67-74	71	31	36
CO ₂ g/kWh (HHV)	46	93-124	31-53	62-87	250	244	Note 4

¹ From Marland and Turhollow (Ref. 4-4).

² From Deluchi (Ref. 4-11).

³ Processing energy is included in 39% efficiency above

⁴ The CO₂ emissions from the wood to ethanol process depend on the amount of total process energy derived from biomass. If renewable derived energy is used for all preparation, conversion and delivery, the net CO₂ emissions would be negligible

Discussion of Fuel Chain Efficiencies

Gasoline. As shown in Table 4-2, the fuel chain efficiency for gasoline, which was derived completely from Reference 4-2, is the most efficient of all fuel chains (on a refinery slate-weighted basis). This reflects the efficiency benefit from the highly developed, integrated production infrastructure, the efficient utilization of refinery byproducts and gasoline's high volumetric and weight specific energy density. This analysis does not consider the increased use of oxygenates in gasoline which may result from Clean Air Act requirements.

Methanol. The overall natural gas to methanol conversion efficiency depends most significantly on the assumed reformation process which is shown in the processing row. These efficiencies reflect limited actual operating experience since fuel grade methanol plants have not been built and higher quality chemical grade methanol is currently produced in smaller quantities than vehicular usage would require. The lower conversion efficiency is typical of proposed large-scale plants using relatively proven technology⁴⁻³. The higher efficiency is the calculated efficiency of the proposed Brookhaven circulating catalyst process⁴⁻⁴. The baseline scenario (shown in bold) for this analysis assumes the lower conversion efficiency.

CNG. The domestic CNG fuel chain is relatively efficient except for the process step required to compress the fuel. Current vehicular CNG systems operate at a maximum storage pressure of 2400 to 3000 psi. The compression energy required is accounted for in the distribution step and does not appear in the vehicle efficiency estimates. The CNG compression energy requirements depend on the following variables:

- Tank charge before filling (half full, etc.)
- Inlet pressure to compressor
- Compressor efficiency
- Vehicle tank storage pressure
- Rate of filling (slow fill vs. quick fill)

Three scenarios were evaluated for CNG refueling as shown in Table 4-3. The resulting process efficiency (accounting for electric power conversion efficiency) depends heavily on the fuel supply pressure. Scenarios 1 and 2 are typical of current CNG installations which typically have access only to low pressure inlet gas and are representative of the efficiency assumed by previous studies^{4,1,2}. Scenario 3 is the most efficient for natural gas compression and also involves lower capital costs for compressors. The significant reduction in compressor train cost and pumping power associated with higher inlet pressures will likely provide incentive for CNG service stations to be located with access to high pressure natural gas lines. Therefore, this analysis uses Scenario 3 as a baseline.

Table 4-3: CNG Process Efficiency Scenarios

Scenario	Vehicle Storage Pressure (psi)	Inlet Pressure (psi)	Pump Flow Rate (scfm)	Pumping Power (kW)	Process Efficiency ¹ (% of HHV)
1. Home/small fleet: low inlet pressure, slow fill	3,000	7"	1.8	1.6 ²	86
2. Service station: low inlet pressure, quick fill	3,000	10	50	30 ³	90
3. Service station: high pressure inlet, quick fill	3,000	500	50	9.7 ⁴	97%

¹Pumping power based on 35% conversion efficiency from primary energy to electric power; process efficiency = 1 - Pumping Power/Inlet Fuel HHV.

²Reference 4-5.

³Reference 4-6.

⁴ADL estimate.

CNG From LNG. Table 4-2 also shows the fuel chain efficiency for CNG derived from imported LNG. The AGA estimates^{4,7} that up to 5% of domestic natural gas requirements will be met by LNG in 2001. This LNG (imported into several terminals along the Eastern and Gulf Coasts) is liquefied with a significant energy/CO₂ penalty (at least 12% of the thermal value of the liquefied fuel) at the point of origin. When revaporized for domestic distribution, the same distribution and compression losses as for domestic gas apply. Therefore, if incremental CNG vehicle demand is assumed to be supplied by imported LNG, the resulting CO₂ penalty is significant. The baseline analysis for this study assumes CNG is provided by domestic natural gas sources.

Ethanol From Corn. Data on the corn-ethanol conversion process as shown in Figure 4-3a was taken from Reference 4-4 which indicates that 0.87 units of process energy (26 MJ/Kg ethanol) embodied in agriculture, fertilizer, and conversion processes) are required to produce 1 unit of ethanol (29.7 MJ/Kg) energy (HHV). In addition, the fuel value of the corn input, 3.5 kg at 17.6 Btu/kg^(4,8), represents another 2.1 units of energy (since the corn feedstock could have been combusted in some alternative process to derive useful energy) for an overall process efficiency of 33.4%. This energy was partitioned between crop raising and process using data from Ref 1-2. There has been significant discussion and widely varying estimates in the literature regarding the efficiency and byproduct credits for ethanol from corn. The efficiency estimates presented here are at the high end of the range of estimates.

Ethanol From Biomass. DOE and others are sponsoring a number of programs^{4,9} in support of producing alcohol fuels from cellulosic biomass such as short rotation wood crops. Reference 4-10 projects an overall process efficiency of 500% (ethanol energy output is 5 times process energy inputs) but does not include the fuel value of the feedstock as a primary energy source.

A recently published report^{4,11} provides an extensive analysis of biomass energy requirements, including a review of a large number of data sources for process and conversion energy. Data from Reference 4-11 (shown in Figure 4-3b) indicate that about 2.3 units of wood energy and 0.2 units of agricultural energy are required to produce a unit of ethanol energy from short rotation wood crops. Part of the wood input is used for process heat so no additional process energy is required. While the overall economics and efficiency of a biomass-to-ethanol process must eventually be measured against alternative processes (such as generating electricity by burning the biomass), the potential benefits of a biomass based energy source are significant. These benefits include improved energy security and the potential for sequestering and recycling atmospheric CO₂. Further analysis of biomass fuel sources was not undertaken in this study.

Figure 4-3a: Calculation of Efficiency for Corn to Ethanol (from Turhollow Reference 4-4)

$$\text{Process Efficiency} = \frac{29.7}{63 + 8.4 + 17.6} = 33.4\%$$

Figure 4-3b: Calculation of Efficiency for Wood to Ethanol (from Deluchi Reference 4-11)

$$\text{Process Efficiency} = \frac{1}{2.35 + 0.2} = 39\%$$

Hydrogen. Two alternative fuel paths to supply hydrogen for the fuel cell vehicle configurations described in Section 3.0 are shown in Figure 4-4. For the 2001 FCV configuration, on-board storage and reformation of methanol is the assumed hydrogen source (as shown on the top leg of Figure 4-4). In later years (2010 and 2020), hydrogen is assumed to be reformed from natural gas at fixed sites and stored in hydride form on-board the vehicle.

Figure 4-4: Fuel Cell Vehicle Hydrogen Infrastructure Options

The fuel conversion efficiency for supplying methanol derived from natural gas to a FCV with an on-board reformer is the same as the methanol fuel chain previously described because the fuel dispensed to the vehicle is the same. The efficiency associated with reformation of the methanol to hydrogen on-board the vehicle and fuel cell efficiencies are discussed in the FCV analysis in Section 3.0.

The natural gas to hydrogen fuel chain (shown schematically in the lower leg of Figure 4-4) assumes that natural gas is supplied to a reformer located at the filling station. Therefore, the efficiencies of the extraction, processing, and fuel delivery steps shown in Table 4-3 are all derived from the domestic CNG analysis. The local distribution and fueling step consists of natural gas reformation (at 80% efficiency) and pressurization to 10 atmospheres for transfer to a fixed site hydride storage bed. Reformer waste heat was assumed to be utilized to desorb H_2 for transfer to the vehicle hydride storage bed.

CO₂ Emissions

Calculated CO₂ emissions expressed as grams of CO₂ per kWh (HHV) of fuel delivered to the tank for each fuel chain are also shown in Table 4-1. The sources and methods used to derive these values are as follows:

Gasoline: Data from Renner & Ho⁴² was used. These calculations allocate a share of CO₂ to gasoline on a refinery slate-weighted basis.

Methanol: The CO₂ emissions from the conversion process depend on the specifics of the process layout since the carbon deficit in the steam-methane syngas reaction can be balanced by oxidizing fuel gas to make CO₂, capturing CO₂ from process combustors or utilizing CO₂ emitted from other co-located processes. Reference 4-3 evaluated six alternative processes and determined the net CO₂ from processing and conversion ranged from 93 to 125 g CO₂/kWh. Another 26 g/kWh has been added to account for the consumption of diesel fuel for methanol transport and distribution.

Natural Gas (domestic and imported LNG): Natural gas is the assumed source for all process energy. Therefore, the calculated CO₂ emissions are based on the fuel consumed to deliver one unit of energy (an 85% efficient fuel chain requires 18 units of energy to deliver 100 units "to the tank") and the natural gas fuel chemistry shown in Table 4-2.

Ethanol: CO₂ emissions for corn-ethanol crop raising and conversion were calculated in the DOE report⁴⁴ based on the mix of coal, oil, and natural gas used in agricultural and conversion process. Eleven per cent of the CO₂ has been allocated to byproducts using the displacement method outlined therein. It is not known if these byproduct markets would be stable in the face of large increases in ethanol production. An additional 17 gCO₂/kWh associated with fuel delivery and transport was added based on the consumption of diesel fuel. Distribution of ethanol involves less CO₂ emissions than methanol due to the higher gravimetric energy density of ethanol. There is no CO₂ associated with the vehicular use of ethanol from corn or biomass since the carbon not associated with fuel production is assumed to be fixed (recycled) by subsequent corn or biomass crops.

Reference 4-11 contains estimates from several sources for process energy requirements for wood to ethanol processes. In the limit, all farming, conversion and delivery energy could be derived from biomass, resulting in zero CO₂ emissions from production and consumption. Achievement of this level of biomass utilization will depend on technical success as well as economic factors.

Hydrogen: Fuel chain CO₂ emissions per kWh delivered to the tank for methanol reformat are the same as for methanol ICEV fuel (93-124 g/kWh). Vehicular CO₂ emissions from the on-board reformer assume all of the carbon in the methanol is converted to CO₂ ($\text{CH}_3\text{OH} + \text{H}_2\text{O} \rightarrow \text{CO}_2 + 3\text{H}_2$) resulting in 218 g CO₂/kWh [HHV]). CO₂ emissions for fixed site natural gas reformation assume natural gas as the primary energy source and are calculated based on the fuel chain efficiency (71%) and the carbon content of natural gas shown in Table 4-2 (178 g/kWh).

Methane Leakage and GHG Contribution

Although atmospheric methane concentrations have varied substantially over the last 100,000 years⁴⁻¹², the amount of methane in the atmosphere has risen at an average rate of 1.1% per year since 1951⁴⁻¹³. However, considerable uncertainty exists with regard to the sources of atmospheric methane and the contribution of methane to global warming. The global warming contribution of methane depends on its influence on atmospheric radiation characteristics and the longevity of individual methane molecules. Recent calculations by Lashoff⁴⁻¹⁴ have established a global warming index (GWI) of 10 for methane indicating that a gram of CH₄ released to the environment has the same effect on global warming over a long period of time as 10 grams of CO₂. The GWI for various non-CO₂ emissions including methane depends on the timeframe of the analysis since each compound has a unique attrition rate in the atmosphere. The selected GWI for methane is at the low end of the range of GWI's used in most previous fuel chain studies, but it is consistent with the view that global warming is a long-term problem and results in a lower GHG contribution from methane in the context of transportation fuels.

Table 4-4 shows the potential sources of methane emissions at various steps in the fuel chains studied in this analysis and the vehicles affected. For instance, methane is emitted during the mining of coal which ultimately is used to generate power for EV's. The CH₄ emissions (as calculated in the references at the end of this section) are shown as a percentage of the total primary energy processed and on a mass basis. For example, Reference 4-1 estimated .0005 gigatons of CH₄ is emitted per quad (10¹⁵ Btu) of coal. On a thermal basis, this methane is equal to 2.2% of the coal heating value. On a mass basis, it is equal to 1.7 gCH₄ per kWh of coal. The emission factor of .85 gCH₄/kWh is based on the "National Mix" power generation scenario which consists of 50% coal. Vehicular primary energy estimates from Section 7.0 are used along with the GWI of 10 to convert methane emissions to a gCO₂ equivalent/km. The calculated global warming impact of methane emissions can be compared with the overall CO₂ emissions estimates shown in the last column.

Table 4-4: Comparison of Impact of CH₄ Emissions to CO₂ Emissions

Methane Source	Vehicle Affected	CH ₄ Emissions		Vehicular Primary Energy kWh/km	CO ₂ Equivalent From CH ₄ g/km	CO ₂ Baseline (Fuel and Vehicle) g/km
		% of Primary Fuel kWh/kWh	gCH ₄ /kWh			
Coal mining	EV - Nat'l Mix	2 ¹	.85	0.72	6.1	137
Venting during resource extraction	Gasoline	0.2 ¹	.14	0.90	1.3	222
	Natural Gas	0.5 ²	.36	0.90	3.2	160
	Methanol	0.5 ²	.36	1.2	4.3	239
	EV - Adv Gas	.5 ²		.72	2.5	148
Distribution leaks	Natural Gas	1.0 ³	.66	0.90	5.9	149

¹(4-1).

²(4-2).

³This is at the upper end of a number of estimates including those in references noted above.

The last 2 columns in Table 4-4 illustrate that the estimated methane contribution to global warming is less than 4.5% of the CO₂ emissions for each vehicle type. This finding is consistent with other analyses⁴⁻¹² when consideration is made for a GWI of 10 for methane.

Another potential source of CH₄ emissions is the tailpipe emissions from CNG and perhaps other ICEV's. The methane emissions from dedicated CNG vehicles are expected to be on the order of 1.0 g/km⁴⁻¹⁶ which, with a GWI of 10, would be equivalent to about 5% of the baseline CO₂ emissions of a CNG ICEV. Because this comparison indicates that the contribution of methane to overall GHG emissions is relatively small compared to CO₂ emissions, the summary analysis focuses on CO₂ only.

References

- 4-1 Deluchi, M. A., Robert A. Johnston and Daniel Sperling, "Transportation Fuels and the Greenhouse Effect", Transportation Research Record 1175.
- 4-2 Ho, S. P. and T. A. Renner, "Global Warming Impact of Gasoline vs. Alternative Transportation Fuels", SAE Paper No. 901489, Future Transportation Technology Conference and Exposition, San Diego, California, August 13-16, 1990.
- 4-3 Unnasch, Stefan, Carl B. Moyer, Douglas D. Lowell and Michael D. Jackson, "Comparing the Impact of Different Transportation Fuels on the Greenhouse Effect", Acurex Corporation, Mountain View, CA, prepared for California Energy Commission, March, 1989.
- 4-4 Marland, G., A. F. Turhollow, "CO₂ Emissions From the Production and Combustion of Fuel Ethanol From Corn", Oak Ridge National Laboratory, Oak Ridge, TN, February 12, 1991.
- 4-5 Personal communication with Ralph Racum, Fuelmaker Corporation, October 23, 1991.
- 4-6 Personal communication with Jason Smitherman, Oklahoma Alternative Fuels Office, October 14, 1991; David Moniz, The Providence Gas Company, October 23, 1991; Verl Elms, Northern Indiana Public Service, May 29, 1990.
- 4-7 Gas Energy Review, American Gas Association, Gas Supply Committee, Vol. 18, No. 1, January, 1990.
- 4-8 Hall, Carl W., "Biomass as an Alternative Fuel", Government Institutes, Inc., Rockville, MD, 1981.
- 4-9 Texeira, R. H. and B. J. Goodman, Ethanol Annual Report, Solar Energy Research Institute, Golden, CO, January, 1991.
- 4-10 Lynd, L., J. Cushman, R. Nichols, and C. Wyman, "Fuel Ethanol From Cellulosic Biomass", *Science*, Volume 251, March 15, 1991.
- 4-11 Deluchi, M.A., "Emissions of Greenhouse Gases From the Use of Transportation Fuels and Electricity," Argonne National Laboratory, Report ANL/ESD/TM-22 Volume 2, November 1991.
- 4-12 Stone, R. H., "Forecast Cloudy, The Limits of Global Warming Models", *Technology Review*, February/March, 1992.
- 4-13 "Impact of Energy Production", *Energy Digest*, August, 1990.
- 4-14 Lashoff, D. A., "Relative Contributions of Greenhouse Gas Emissions to Global Warming", *Nature*, Volume 34, 1990.

- 4-15 O'Hare, T. E., R. S. Sapienza, D. Mahajan, and G. T. Skgrerdas, "Liquefaction of Natural Gas to Methanol for Shipping and Storage, 1989 International Gas Research Conference, Toronto, Canada.
- 4-16 Weaver, C., Sierra Technologies, Personal Communication.

5.0 Electric Power Generation

5.1 Introduction

Electric vehicles do not emit air pollutants such as CO₂, SO₂ and NO_x directly. The pollutants associated with electric vehicles are emitted at the power generation source. Therefore, in order to assess the emissions from electric vehicles it is necessary to analyze the emissions from power generation sources. Due to the complexity involved in evaluating these emissions, it is necessary to simplify the total power generation capacity in the U.S. In evaluating the emission of CO₂, the primary contributors are those power plants burning fossil fuels, that is, either coal, oil, or natural gas. Nuclear power and renewable sources, such as hydroelectric, wind, solar, geothermal, and municipal solid waste, are assumed not to contribute to the CO₂ production associated with power generation in this analysis. This analysis does not attempt to estimate the built-in or embedded energy or CO₂ associated with power plant infrastructure construction or nuclear fuel processing. Similarly, the energy associated with waste disposal, clean-up and plant decommissioning is not estimated.

For each of the fossil fuels used in power generation, the amount of CO₂ is directly related to the amount of carbon in the fuel. All heating values and efficiencies shown for power generation are HHV. For each of these fuels, there are variations in carbon content as well as their heating values which will lead to variations in emissions dependent on the specific characteristics of the fuel being burned. An eastern bituminous Pittsburgh seam coal, for example, has a gross heating value of 8.42 kWh/Kg (kilowatt hour thermal/kilogram) and is 71.3% carbon by weight, while a south-central Texas lignite has a gross heating value of 4.39 kWh/Kg and is 40.6% carbon by weight. In order to simplify this analysis, a value of 325 grams CO₂/kWh of fuel is used as an estimate of the average CO₂ production for the national mix of coal types. This is the CO₂ associated with the complete combustion of coal, regardless of the technology used. Similar simplifying assumptions have been used to provide the estimates of CO₂ production associated with the combustion of fuel oil and natural gas which are summarized in Table 5-1. For each fuel, there is also CO₂ produced during the extraction, processing, and delivery of the fuel as discussed for transportation fuels in Section 4.0. These fuel chain emissions have been added to the CO₂ from combustion in order to obtain a value for the total CO₂ production associated with burning the fuel for the generation of power. Again, the assumption is made that each fuel can be represented by an average value; however, there are large variations associated with these figures. Fuel and fuel chain data used in this analysis are summarized in Table 5-1. The total CO₂ production for coal is 336 grams per kWh of fuel, and for oil it is 300 grams/kWh of fuel. The total CO₂ emission for natural gas, including CO₂ emissions from fuel chain consumption as derived in Section 4.0, is 190 g/kWh. Note that the CO₂ production associated with natural gas is 50% that of coal. This gives natural gas a distinct advantage over other fuels with respect to CO₂ production.

Table 5-1: Power Generation Fuel Chain, CO₂ Emissions in Grams/kWh

Fuel	Combustion (HHV)	Extraction	Proc.	Deliv.	Total
Coal	325.2	3.9	0.0	6.5	335.6
Oil	262.9	10.5	21.0	5.3	299.8
Natural Gas	178.1	9.8	4.9	4.9	191.7

To determine the amount of CO₂ produced per kilowatt hour electrical (kWh_e), it is necessary to evaluate the efficiency of the power generation technologies used to convert the thermal energy of the fuel into electrical energy. For a given power generation technology, the CO₂ production is calculated as:

$$\text{CO}_2(\text{grams/kWh}) = \text{Fuel CO}_2(\text{grams/kWh}_t) / (\text{Efficiency (kWh}_e/\text{kWh}_t))$$
where kWh_e represents electrical energy and kWh represents thermal energy

To simplify the analysis, the power generation technologies have been categorized by fuel type. The technologies are then further grouped in a manner based on the major types of existing capacity and new capacity which will be added in the future. Existing capacity is that which is already on line and is used in the evaluation of 1992 emissions. Generating efficiencies for the existing capacity remain constant in the scenarios for future generation projections. New capacity is that which will come on-line in the upcoming decades under the various scenarios evaluated. The efficiencies associated with new capacity change in this analysis as a function of available technology when the additions are made.

The following is a description of the categories used to represent the various power generation technologies in the U.S. for this analysis.

Coal Technologies: In 1992, it is assumed that the existing capacity will consist of mostly coal-fired steam plants which make up the majority of the U.S. power generation base. For new capacity introduced after 1992, it has been assumed it will be made up of advanced coal burning technologies. These include such technologies as: Integrated Gasification Combined Cycle (IGCC), Circulating Fluidized Bed Combustion (CFBC), Pressurized Fluidized Bed Combustion (PFBC), and supercritical and ultracritical pulverized coal steam units. Estimates for future projections of new power generation capacity include combinations of these technologies.

Oil Steam Generation: These are oil-fired steam plants, most of which run on #6 residual fuel oil and have been in service for several years. These are included as existing capacity. It is assumed that only a small amount of this type of new capacity will be added in the future.

Gas Steam Generation: These are natural gas-fired steam plants included in the existing capacity mix. It is assumed that only a small amount of this type of new capacity will be added in the future.

Advanced Natural Gas Technologies: In the assumptions for the model of generating mixes, the existing capacity is initially made up of Gas Turbine Combined Cycle (GTCC) plants. In assumptions for future generation mixes, an increasing amount of fuel cell capacity is used along with new GTCC capacity. For purposes of this evaluation, the actual technology assumed is less important than the efficiency used. Both GTCC and fuel cells are similar in efficiency and therefore emissions of CO₂. Various projections about the specific types and mixes of these new technologies exist, and the actual implementation may vary significantly from these projections. The important characteristic is the change in efficiency in future years as new capacity is introduced which burns natural gas as a fuel.

Gas or Combustion Turbines: These are simple cycle gas turbines which have been traditionally used for peaking to satisfy short-term demand requirements. Therefore, the existing capacity and fuel use are small. A small amount of future capacity additions are assumed.

Nuclear: Total nuclear capacity is as large as it is projected to be for the next 20-30 years unless there is a change in policy and renewed interest in development of second generation nuclear plants. This evaluation has assumed that the contribution to total emissions from nuclear power plants is zero.

Renewables: This includes hydroelectric, geothermal, solar, wind, wood, wood waste, municipal solid waste, and other biomass sources. As of 1989, hydroelectric accounted for 83% of this and approximately 10% consisted of municipal solid waste and biomass. It is projected that non-hydro sources will account for the majority of new capacity in this sector. This evaluation has assumed that the contribution to total CO₂ emissions from renewable sources is zero. The power generation data used for this analysis includes all utility generation and non-utility generation purchased by utilities and imports of electricity such as Canadian hydro.

The average efficiencies for each power generation technology, on a national basis are presented in Table 5-2. The efficiencies for 1992 represent the total installed capacity for plants on line at that time. This is the existing power generation capacity. The efficiencies listed for future years represent the average efficiency for each category considering existing capacity which remains on line and new capacity which has come on line in the preceding decade. All of these efficiencies represent the net station heat rates or efficiencies expected to be realized in operation for each type of plant. The efficiencies shown in Table 5-2 are used in the composite national mix scenario. The efficiency for Advanced Gas Technologies is used for the "Advanced Gas" scenario.

Table 5-3 shows the estimated efficiency for the Advanced Gas Technology group on a marginal efficiency (the efficiency of the most recently commissioned plant) for the same time periods. These efficiencies are used in the scenario for "New Gas." Even higher efficiencies could be achieved if advanced cycles (such as high temperature solid oxide fuel cells combined with gas turbines and steam bottoming cycles) are deployed during this time period.

Table 5-2: Average Power Generation Efficiencies by Technology (HHV)

	1992	2000	2010	2020
Coal Technologies	33%	36%	38%	40%
Oil Steam	33%	34%	34%	34%
Gas Steam	33%	34%	34%	34%
Advanced Gas Technologies	43%	47%	51%	53%
Gas Turbine	26%	32%	34%	36%
Nuclear	32%	32%	34%	34%
Renewable Sources	N.A.	N.A.	N.A.	N.A.

Table 5-3: New Plant Generation Efficiency

	1992	2000	2010	2020
New Gas Plants	43%	52%	55%	57%

To calculate the power delivered to the point of use (the plug), the total power generated is reduced by 8% to account for transmission and distribution losses. This is typical for U.S. utilities and is reflected in the 1991 Annual Energy Outlook⁵⁻¹ as the difference between total sales by utilities and the total energy load. For each technology, the CO₂ produced is calculated on the basis of a kWh delivered to the point of use (the plug).

The "National Mix" power generation scenario used for this analysis is a daily average generation mix for the entire country. This scenario does not distinguish between power requirements such that a kilowatt of EV demand is assumed to be supplied by a kilowatt made up of an average of the power generation mix available. The "Advanced Gas" scenario assumes that the EV load is supplied from capacity with the average efficiency for all plants on line in the Advanced Gas Technology group. The "New Gas" scenario is a limiting case which assumes that the EV demand is supplied entirely from natural gas plants using the newest, most efficient technology at that point in time.

Alternate methods of analysis may be used such as a marginal generation approach which assumes that charging an electric vehicle will require marginal generation capacity in order to meet its needs. This analysis, which was used by EPRI⁵⁻² in their evaluation of emissions from utilities associated with EV's, assumes that emissions associated with charging EV's are attributable to the marginal capacity which comes on line to meet this need, no matter how large the increase in demand. In the EPRI analysis, power generation capacity is dispatched using utility economic dispatch methodology. In general, the marginal capacity will consist of a mix of fossil fired capacity. A comparison with these results will be presented in Section 5.5. Other scenarios based on environmental dispatch of capacity or assumptions about capacity additions required to meet new emissions regulation may provide more variations in results; however, these other alternatives have not been addressed at this time.

The current generation mix and CO₂ production will be discussed first in Section 5.2, and then a projection of power demand in the coming decades will be analyzed in Section 5.3. Section 5.4 discusses the implications of some alternative power generation projections such as the National Energy Strategies (NES)⁵⁻³ scenario. Section 5.5 discusses results of the marginal dispatch scenario performed by EPRI in comparison to the average daily generation mix. In Section 5.6, the effects of time of day are reviewed with the conclusion that in spite of changes in generation mix the average emissions change only very slightly from peak to nighttime base load.

5.2 1992 Average Daily National Power Generation Mix and CO₂ Production

The 1992 average daily national power generation mix used for this analysis is essentially unchanged from the U.S. generation mix presented in the 1991 Annual Energy Outlook⁵⁻¹. Total capacity and generation have been increased over 1990 data to account for planned expansion and increased demand estimates as published in this report. The 1992 distribution of power generation by technology is presented in Figure 5-1 and Table 5-4. In 1992, coal is the predominate fuel making up approximately 54% of the total power generated. This total includes all utility generation and non-utility generation purchased by utilities. This capacity is virtually all coal steam technology which came on line over the last 30 or more years. Nuclear power makes up about 19% of the generation, and oil and natural gas-fired steam plants generate 12%. Renewable sources, which are made up of hydro, geothermal, wood, municipal solid waste, solar, and wind, account for 12%. The remaining 3% is made up of combustion turbines and combined cycle systems running primarily on natural gas.

Figure 5-1: Distribution of Power Generation by Technology for 1992

Table 5-4: Power Generation Mix - National Mix Scenario

	1992	2001	2010	2020
Coal Technologies	54%	50%	51%	52%
Oil Steam	4%	3%	3%	2%
Gas Steam	8%	7%	6%	5%
Advanced Gas Technologies	2%	6%	11%	16%
Gas Turbine	1%	2%	2%	2%
Nuclear	19%	18%	15%	13%
Renewable Sources	11%	13%	12%	11%

The 1992 CO₂ produced in grams per kWh delivered based on the fuel carbon content and estimated generation mix for each technology is presented in the first column of Table 5-5. Since nuclear and renewable technologies make up 30% of the power generation mix and there is no CO₂ production associated with them, the average amount of CO₂ produced (696 grams/kWh) is less than that associated with coal or oil generation alone. The predominate technology currently being used is coal steam which produces 1088 grams/kWh based on an average generation efficiency of 33%.

Table 5-5: Power Generation CO₂ Production (Grams/kWh Delivered) - National Mix Scenario

	1992	2001	2010	2020
Coal Technologies	1088	1080	1048	1011
Oil Steam	972	972	972	972
Gas Steam	622	622	621	621
Advanced Gas Technologies	482	459	428	411
Gas Turbine	796	752	726	0
Nuclear	0	0	0	0
Renewable Sources	0	0	0	0
Weighted Average	696	662	663	653

5.3 National Power Generation Mix Projections, 2000-2020

For purposes of predicting the electricity demand growth rate and the generation mix for the national mix scenario, an intermediate annual growth rate of 2% was selected based on an assessment of demand by the Energy Information Administration⁵⁻¹. Domestic electric power sales grew 3.3% per year during the period 1985 to 1989. This high rate was boosted by favorable economic conditions and weather extremes. The projection for the coming decades assumes a more conservative growth rate resulting from future economic uncertainties and demand side management programs.

The mix of power generation technologies assumed for the National Mix scenario is shown in Table 5-4 and graphically in Figure 5-2. Coal as a fuel is predicted to decrease as a percent of the total generation, down to 50% in the year 2000 and then increase slightly over the next two decades. This drop is due partially to our assumptions on retirements of old technology coal steam plants and also to an assumption of increased

emphasis on natural gas for new capacity in the next decade. New GTCC plants are estimated to make up the majority of this new capacity, increasing the percentage of gas technology plants from 2% in 1992 to 6% of the total capacity in the year 2001. These new GTCC plants are predicted to have operating efficiencies of 46% to 53% on a higher heating value basis. The EIA projection calls for an increase in renewable capacity also. The combined effect of all of these changes results in a 5% decrease in CO₂ production in grams/kWhe delivered by the year 2001 as shown in Table 5-5.

Figure 5-2: Power Generation for National Mix Scenario

From 2010 to 2020, the CO₂ production per kWhe rises very slightly and then falls 1.5%. The small improvements over this time period for this projection are due to three different effects:

- Nuclear power capacity is predicted to decrease as a percent of the total because no new plants are currently being planned for this timeframe. Because nuclear power does not contribute to CO₂ production from power generation, the reduction in nuclear capacity increases the total CO₂ per kWhe.
- The EIA projection does not predict substantial amounts of new renewable technology generation capacity to be added in these decades which causes it to become a smaller percentage of the total generation.

- Coal technology plants increase in their percentage share of the total; and even with retirements of older, less efficient plants, the newer more efficient coal technologies emit more CO₂ per kWh than average due to the higher carbon content of coal as a fuel.

These three effects offset the improvements in efficiency and the increased use of natural gas which would have otherwise lowered the average significantly.

The National Energy Strategy (NES)⁵⁻³ contains two alternative projections of power generation demand and mixes of generation technologies. The higher prediction for both generation demand and CO₂ production is based on what the NES defines as the "current policy". The lower prediction is based on the NES scenario which would result if the suggested policies are implemented. Figure 5-3 also shows the CO₂ production rates for these two projections.

Figure 5-3: CO₂ Production Rates for Various Power Generation Scenarios

The National Mix scenario defined here is intended to represent a mid-level case which is conservative in predictions of generation growth rates, changes in technology mix, retirements of old capacity, and additions of new more efficient technology. It also

represents a likely upper bound on the percentage of coal used in the generation mix. The Advanced Gas and New Gas scenarios illustrate how natural gas generation technologies affect efficiency and CO₂ production.

5.4 Natural Gas Power Generation Projections

The National Mix scenario defined in Section 5.3 represents one possible projection of power generation demand growth and one possible mix of technologies and fuels for meeting that growth in the coming decades. Two additional scenarios were developed to illustrate the effect of strategies encouraging the use of natural gas for power generation. An advanced gas case is derived from the Advanced Gas Technology scenario plotted in Figure 5-2. This is representative of the aggregate efficiency of the new technology natural gas generation capacity described in Section 5.1. In this scenario, these plants supply just 2% of the total national mix in 1992, increasing to 16% in 2020. This growth exceeds the demand from EV's under any feasible market penetration scenario.

A third "New Gas" scenario also shown in Figure 5-3 is based on the efficiency of the newest gas technology plant for each time period and represents a best case for evaluating the potential of natural gas power generation to improve efficiency and reduce CO₂ emissions. The generating efficiency and CO₂ (per kWh delivered to the plug) for all three scenarios are shown in Table 5-6. The generation efficiency is based on HHV (net from the plant). For the National Mix scenario, this efficiency is representative of the weighted average of fossil fuel plants only since this efficiency is used principally to calculate the primary energy efficiency of alternatives for fossil fuel utilization.

Table 5-6: CO₂ Production and Efficiency Scenarios

Scenario	1992	2001	2010	2020
National Mix:				
• gCO ₂ /kWh	696	662	663	653
• Efficiency	33%	34%	36%	38%
Advanced Gas:				
• gCO ₂ /kWh	482	461	432	415
• Efficiency	43%	45%	48%	50%
New Gas:				
• gCO ₂ /kWh	482	401	379	365
• Efficiency	43%	52%	55%	57%

1. gCO₂ is based on a kWh delivered to the plug.
2. Efficiency is plant level (net of "own use").
3. National Mix Efficiency is average of fossil plants.

5.5 CO₂ Emissions Based on a Marginal Power Generation Mix Analysis

An alternative method for determining the daily generation mix which is utilized in the draft version of a forthcoming study by EPRI^{5,2} is based on the emissions from the marginal power generation capacity in the utility system at a given time. This method uses a generation dispatch model similar to actual utility economic dispatch

methodology. In order to meet the hourly variations in demand, the loads are dispatched by using the equal incremental fuel cost method in which the next increment of load is picked up by the unit with lowest incremental fuel cost. The marginal generation units in this type of analysis are typically fossil fueled and vary regionally based on generation capacity mix and fuel costs.

This analysis conducted by EPRI results in CO₂ emissions data which is, in general, slightly higher than that obtained from the National Mix Scenario analysis. This is due to the marginal capacity being primarily made up of fossil fired generation. In Figure 5-4, the EPRI data for the Northeast and West are included for comparison to other scenarios. The resulting 720 grams/kWh is less than 10% higher than the National Mix scenarios. In its draft form the EPRI study does not consider changes in generation mix or improvements in efficiency beyond the year 2000.

Figure 5-4 also shows the current and 2001 projected CO₂ emissions from the average generation mix for several regions of interest. The CO₂ emissions for the "National Mix" and "Advanced Gas" scenarios represent upper and lower bounds on the emissions for these regions.

Figure 5-4: CO₂ Production Rates of EPRI Analysis and Selected Regions

Various other scenarios based on dispatch could be evaluated in further studies. Changes in fuel price will change the economics of dispatch, and the fuel mix or the possibility of environmental dispatch could provide wide variations in outcome. For this reason, it is important to evaluate these other alternative scenarios in relation to the

average generation mix. In general, these alternative scenarios will not vary significantly from the average unless they become biased with all one type of fuel such as natural gas.

5.6 Effects of Daily Variations in Power Generation on CO₂ Production

Power generation load over a 24-hour period typically varies from a daytime maximum to a nighttime minimum. The peak load may be two or more times the minimum nighttime load with a very different generation mix or more depending on the region of the country, the time of year, and the specific utility. To evaluate how nighttime CO₂ emissions compare with the scenarios selected for this analysis, it was assumed that the baseload capacity in the U.S. is primarily made up of coal, nuclear, and hydro capacity and that natural gas and oil are typically used more for intermediate or peak loads. This means that during periods of low demand the primary fuels being used will be coal, nuclear, and hydro. During periods of higher demand, fuel oil and natural gas will increase in use. Using the National Mix power generation scenario as discussed in Section 5.3, variations in CO₂ production associated with changes in generation mix which might occur from minimum load to maximum were evaluated.

The minimum load case, which would be the equivalent of nighttime generation, consisted of using just the coal, nuclear, and renewable capacity as modeled in 1992. In the future years, the capacity of gas-based generation was increased slightly based on the assumption that there will be increased use of combined cycle plants for base loading. The result is a 1% increase in the CO₂ production rates relative to the National Mix scenario. Even though the nuclear and renewable technologies are a larger percentage of the total, this is offset by the increased share of coal.

For the evaluation of maximum or peak load CO₂ production, the oil and gas steam capacities and the combined cycle and gas turbine capacities were increased as a percentage of the total generation. The resulting power generation was approximately two times that of the minimum. The result was only a 1-2% increase in CO₂ production. Even though a larger percentage of power is generated with fossil fuels, in this case the average does not change significantly due to the increased use of natural gas and oil. Oil has a CO₂ production rate which is greater than the average, and natural gas has a rate which is lower than the average resulting in an insignificant overall effect.

The conclusion here is that time of day does not have a big effect on CO₂ production relative to the national mix scenario. Clearly, utilities will seek to avoid adding new capacity for incremental EV loads by encouraging offpeak charging through time-of-day pricing, demand reduction or other strategies.

References

- 5-1 Energy Information Administration, 1991 Annual Energy Outlook, DOE EIA 0383 (91) U.S. Dept. of Energy, Washington, D.C.
- 5-2 Yau, T. S., Electric Power Research Institute, Utility Emissions Associated With EHV Charging, Draft Report, December 9, 1991.
- 5-3 DOE National Energy Strategy Technical Annex 2 1991/1992.

6.0 Electric Vehicle Fleet and Vehicle Miles Traveled Projections

Among the many factors that influence the impact of the introduction of Electric Vehicles on CO₂ production, there are three that are among the most fundamental:

- The number of EV's that will be introduced into the vehicle fleet,
- The types (size and capacity) of EV's that will be used, and
- The number of mile those EV's are driven.

This section of the report describes the methodology and assumptions used in developing forecasts of these factors. In order to make the results of this work as directly comparable as possible to the work of other researcher's, assumptions from earlier work have been used wherever possible.

Electric Vehicle Fleet Calculation

In order to address the wide range of possible outcomes in the number of Electric Vehicles that will be introduced into the U.S. fleet, two scenarios for the introduction of EV's were developed.

1) *Base Case Scenario - California Regulations*

Much of the recent interest in EV's has been a result of California's introduction of regulations requiring Zero Emission Vehicles (ZEV's) starting in 1998 (Table 6-1). Electric Vehicles are the most likely approach to meet the ZEV requirements. This analysis assumes a constant percentage of ZEV sales (10%) beyond 2003.

Table 6-1: Implementation Rates for Conventional Vehicles, TLEV's, LEV's, ULEV's, and ZEV's Used to Calculate Fleet Average Standards for Passenger Cars

Model Year	0.39*	0.25*	TLEV 0.125*	LEV 0.075*	ULEV 0.040*	ZEV 0.00*	Fleet Average Standard
1994	10%	80%	10%				0.250
1995		85%	15%				0.231
1996		80%	20%				0.225
1997		73%		25%	2%		0.202
1998		48%		48%	2%	2%	0.157
1999		23%		73%	2%	2%	0.113
2000				96%	2%	2%	0.073
2001				90%	5%	5%	0.070
2002				85%	10%	5%	0.068
2003				75%	15%	10%	0.062

*Allowed HC emission levels.

With passage of the Clean Air Act Amendment, which allowed states to adopt either the Federal or California vehicle emission standards, a number of other states have indicated that they intend to adopt the California regulations - including the ZEV requirement.

As a Base Case Scenario for Electric Vehicle fleet size, it has been assumed that the following states will adopt the California regulations:

- California*
- Massachusetts*
- Maine
- New Hampshire
- Vermont
- Rhode Island
- Connecticut
- New York*
- Pennsylvania
- New Jersey
- District of Columbia
- Maryland
- Delaware

***Regulations already adopted.**

The included states are those that were considered most likely to adopt the California regulations at the time the model was developed. However, the adoption process is subject to the vagaries of the political process and is therefore clearly subject to change. In addition, Colorado is now among those states that are considering adoption.

Since the California regulations are stated in terms of a percent of light vehicle (passenger car and light truck) sales in a particular year, to arrive at a total level of annual sales of EV's, it was necessary to develop an estimate of the total light vehicle sales in each state. Each state's share of total national light vehicle sales was assumed to be constant at the average of that state's share of national sales in 1989 and 1990 (Table 6-2).

Table 6-2: New Light Vehicle Registrations by State

	1989 Volume (000's)	1990 Volume (000's)	1989 Share (%)	1990 Share (%)	1989/1990 Average (%)
California	1,736	1,599	11.6	11.5	11.5
D.C.	24	22	0.2	0.2	0.2
Delaware	74	61	0.5	0.4	0.5
Massachusetts	380	307	2.5	2.2	2.4
Maryland	398	364	2.7	2.6	2.6
Maine	81	60	0.5	0.4	0.5
New Hampshire	91	74	0.6	0.5	0.6
New Jersey	546	484	3.7	3.5	3.6
New York	867	786	5.8	5.6	5.7
Pennsylvania	683	627	4.6	4.5	4.5
Virginia	394	358	2.6	2.6	2.6
Rhode Island	56	45	0.4	0.3	0.3
Connecticut	224	187	1.5	1.3	1.4
Total of States With EV Requirement	5,553	4,975	37.1	35.6	36.4
U.S. Total	14,953	13,965			

The forecast of total national sales was developed by applying Arthur D. Little's forecast growth rate for passenger car and light truck sales to the actual 1990 sales level (Table 6-3). The resulting forecasts of total national light vehicle sales, and sales in those states with Electric Vehicle sales requirements is shown in Figure 6-1.

Table 6-3: Forecast Vehicle Sales Growth Rates (Source: Arthur D. Little)

Vehicle Type	Growth Rate
Passenger Cars	0.8%/Year
Light Trucks	1.3%/Year

Figure 6-1: Projected Size of Fleet Subject to ZEV Regulations - Base Case

Having determined the level of Electric Vehicle sales, the final step is to determine the total Electric Vehicle fleet. This was calculated by "vintaging" the EV sales, i.e., estimating the rate at which Electric Vehicles would drop out of the fleet, either as a result of accidents or old age. EV's are assumed to drop out of fleet at same rate as conventional vehicles. Data on conventional vehicle survival was taken from R.L. Polk registration data as reported in Ward's Auto Yearbook (various years).

The resulting forecast of total Electric Vehicle fleet is shown in Figure 6-2. For Scenario 1 (Base Case), which is based on a fixed percentage of new vehicle sales, the steady state EV population growth rate (beyond about 2014) is equal to the total fleet growth (Table 6-3).

Figure 6-2: Total EV Fleet for Three Scenarios

2) Scenario 2: Bernard's 101 City Scenario

A second EV sales and fleet scenario was developed using expected EV sales and fleet levels developed in Bernard⁶⁻¹. Of the three scenarios developed by Bernard, the 101 Cities scenario was selected as the most optimistic. The values for EV sales and total fleet were taken from Bernard's Table A-1. The resulting EV fleet forecast is also shown in Figure 6-2. The new vehicle sales percentage in this scenario continues to grow robustly through the time periods considered as opposed to the fixed percentage assumed beyond 2003 for Scenario 1.

Electric Vehicle Fleet By Vehicle Type

Having arrived at estimates of the total EV sales and fleet levels, the second issue is the type of vehicle that are represented in those sales scenarios. In order to arrive at comparable results, we have used the projections of vehicle types developed in Bernard's work.

In his work, Bernard defined annual sales for three vehicle types; van, truck and car. In the present analysis, three slightly different EV types have been used: minivan, commuter car, and family car.

The most significant change is the categorization of cars. This analysis assumes that commuter cars will dominate the passenger car mix during the early years. Beyond 2007, when technology improvements result in greater EV range, family cars are assumed to dominate.

The correspondence of Bernard's vehicle classifications to those used for the sales projections of this analysis is shown in Table 6-4. The resulting forecast of the percentage share of total EV sales represented by each vehicle type is shown in Figure 6-3. These share forecasts were used for all three EV fleet scenarios.

Table 6-4: Vehicle Classification for 101 Cities Scenario

	Bernard Classification	Classification for This Analysis
All Years	Van	Van
All Years	Truck	Van
1992-2004	Car	Commuter Car
2005	Car	85% Commuter, 15% Family
2006	Car	70% Commuter, 30% Family
2007	Car	50% Commuter, 50% Family
2008	Car	30% Commuter, 70% Family
2009 and Beyond	Car	25% Commuter, 75% Family

Figure 6-3: Forecast Vehicle Mix for All Scenarios

Annual Vehicle Miles Traveled By Vehicle Type

The final element in calculating the total annual usage of electric vehicles, is an estimate of the number of kilometers that each of the three types of electric vehicles will be driven each year.

- Vans** - Vans are assumed to be used as commercial fleet vehicles only. The fleet average daily use of trucks and vans is taken from Table 2.3 of Reference 6-3.

It was assumed that an average commercial van would be used 250 days per year, resulting in an annual travel of 26,500 km

Annual Van VKT	=	Average Daily Use	x	Days
	=	106 km	x	250 Days
	=	26,500 km per year		

- b) **Commuter Car** - The commuter car was assumed to be used only as a commuter car, with limited weekend use. The 1985 average commute distance traveled to work by car, truck, or van (Table 6.5) was used as to calculate total commuting miles traveled. Total annual mileage is the total commute distance (18.28 kilometers x 2) multiplied by working days (250) plus one day of use on the weekend, which is assumed to be the same as the commute distance (18.28 x 2).

Commuter Car KMT	=	Commute Usage	+	Weekend Usage
	=	(18.28 km x 2 x 250) + 106 km	+	(18.28 km x 2 x 52)
	=	11,040 km		

Table 6-5: Transportation to Work by Mode, 1985

Mode	Average One-Way Distance Traveled (Miles)	Average One-Way Commute Time (Minutes)
Car, Truck, or Van	11.36 (18.3 km)	19.01
Bus or Streetcar	8.68	38.27
Subway or Elevated Rail	6.70	27.62
Railroad	24.82	64.33
Taxicab	2.92	12.66
Motorcycle	9.62	16.45
Bicycle	2.06	37.76
Other Vehicle	6.25	23.23
Walked Only	0.19	8.33
Total	10.73	19.66

Source: U.S. Department of Energy, *Transportation Energy Data Book*. Edition 11, 1991.⁶⁴

- c) **Family Car** - The family car was assumed to be used exactly as a present typical family car. Annual vehicle kilometers traveled, therefore, is assumed to be 16,689 km which was the 1988 average household use of passenger cars as shown in Table 6-6.

The above assumptions on annual kilometers traveled by vehicle type were held constant for all of the fleet size scenarios. The resulting forecasts of annual vehicle kilometers traveled are shown in Figure 6-4.

Table 6-6: Household Travel by Type of Vehicle--1988

Vehicle Type	Number of Vehicles (Million)	Annual Vehicle Miles (Billion)	Average Miles Traveled (per Vehicle)	Fuel Consumption (Billion Gallons)	Fuel Expenditures (Billion)
Passenger Car	109.3	1,134	10,372	57.5	\$57.1
Jeep-like Vehicle	4.8	57	11,843	3.7	\$3.6
Minivan	2.2	28	12,650	1.4	\$1.4
Large Van	4.7	46	9,774	3.5	\$3.3
Pickup Truck	25.9	244	9,433	15.9	\$15.3

Source: U.S. Department of Energy, Energy Information Administration, *Household Vehicles Energy Consumption*, 1988.

Figure 6-4: Annual Vehicle Kilometers Traveled for Various Scenarios

References

- 6-1 Bernard, M. J., et al, "Three Scenarios for Electric and Hybrid Vehicle Commercialization", ANL/ESD/TM-13.
- 6-2 Second Interim Report of the Interagency Commission on Alternative Motor Fuels, Chapter 3, September, 1991.
- 6-3 Hamilton, William, "Electric and Hybrid Vehicles: Technical and Background Report for the DOE Flexible and Alternative Fuels Study", DOE/ID-10252.
- 6-4 U.S. Department of Energy, *U. S. Transport Energy Data Book: Edition 11*, 1991.
- 6-5 U.S. Department of Energy, Energy Information Administration, *Household Vehicles Energy Consumption*, 1988.

7.0 Findings

The technical and market estimates presented in Sections 3 through 6 allow conclusions to be drawn in several major areas:

1. The relative energy efficiencies of complete fuel/vehicle chains for various alternative transportation fuels provide insight into strategies for optimizing the use of scarce or preferred energy resources.
2. The relative differences in production of greenhouse gases (particularly CO₂) among transportation alternatives lead to the possibility of global warming mitigation strategies which can be directed toward enhancing the use of preferred fuels in the most favorable transportation applications.
3. An understanding of the markets, technologies, and component areas with the highest leverage for improving energy efficiency and reducing CO₂ emissions provides guidance for research and development planning.

In this section, the results of analyses of vehicular energy consumption, fuel chain efficiency, and power generation are first combined in a resource utilization analysis which estimates the primary energy requirements to provide a km of distance traveled over defined driving cycles (urban or combined). Then, end-to-end CO₂ emissions are estimated on a per kilometer and fleet aggregate basis. Conclusions are drawn from the data regarding technologies and strategies which are likely to be most constructive for decreasing CO₂ emissions. As discussed in previous sections, the uncertainties associated with future year estimates are significant. The estimates presented here could be influenced by regulatory, technical or economic developments which differ from the baseline assumptions.

7.1 Summary of Scenarios

The scenarios and other data developed in previous sections are briefly summarized below. In Section 3.0, ICEV, EV, and FCV configurations were developed for three vehicle classes over four time periods. As an example, key characteristics for ICEV and EV minivans are shown in Table 7-1. All vehicle characteristics were selected based on the best technology which was estimated to be available at each time period.

An additional vehicle efficiency consideration discussed in Section 3.0 is the thermal loss associated with high-temperature batteries which (depending on battery size, thermal loss factors, and vehicle usage characteristics) consume about 30% of total

Table 7-1: Vehicle Technology Evolution - Minivan

	1992 (Chrysler Voyager)	2001	2010	2020
Base Vehicle Characteristics				
C_d	.37	.33	.26	.25
Tire Coefficient C(O)	.009	.007	.006	.005
IC Engine/Driveline				
Engine Power (kW)	110	100	85	80
Driveline Efficiency (LEV)	2.3	2.1	2.0	1.8
Driveline Weight (Kg)	235	215	170	145
Gasoline/Methanol Fuel System Weight (Kg)	70	65	60	55
Added Natural Gas Weight (Kg)	47	47	47	47
Electric Vehicle				
Battery Energy Density (wh/Kg)	55	100	175	200
Battery Weight (Kg)	530	515	415	380
Battery Efficiency (%)	75	75	85	90
Controller/Driveline Efficiency (%)	69	71	80	85
Motor/Controller/Transm Wt. (Kg)	155	140	105	85
Total Weights				
Liquid Fuel Vehicle Weight (Kg)	1585	1440	1210	1125
Natural Gas Vehicle Weight (Kg)	1610	1485	1255	1170
Electric Vehicle Weight (Kg)	1945	1815	1500	1390

energy from the plug for the minivan and up to 50% for the commuter. Additionally, ICEV "from the tank" consumption derived from EPA test data does not capture the full parasitic loss attributable to the alternator, air conditioning, and other devices.

Table 7-2 shows the fuel chain process efficiency and CO₂ production estimates developed in Section 4.0. The numbers shown in bold are used in the baseline analyses of this section.

Table 7-2: Fuel Chain Efficiency and Fuel Chain CO₂ Emissions

	Gasoline From Crude	Methanol From Natural Gas	CNG From Domestic NG	CNG From Imported LNG	H ₂ From NG	Ethanol From Corn	Ethanol from Biomass
Net Delivery Efficiency (%)	85	56-62	77-85	67-74	71	31	36
CO ₂ g/kWh (HHV)	46	93-124	31-53	62-87	73	244	Note 1

1. The CO₂ emissions from the wood to ethanol process depend on the amount of total process energy derived from biomass. If renewable derived energy is used for all preparation, conversion and delivery, the net CO₂ emissions would be negligible.

The plant efficiency and CO₂ emissions associated with electric power generation and delivery for three power generation scenarios are shown in Table 7-3. The National Mix is derived from the National Energy Strategy and relies on coal for 50% of the total power generated. The Advanced Gas scenario includes higher efficiency natural gas technologies (such as Gas Turbine Combined Cycle and Fuel Cells) using the average efficiency for all plants of this type. The New Gas scenario is a marginal efficiency scenario representing the most efficient natural gas generating capacity for any time period.

Table 7-3: Power Generation CO₂ Production and Efficiency Scenarios

Scenario	1992	2001	2010	2020
National Mix:				
• gCO ₂ /kWh	696	662	663	653
• Efficiency	33%	34%	36%	38%
Advanced Gas:				
• gCO ₂ /kWh	482	461	432	415
• Efficiency	43%	45%	48%	50%
New Gas:				
• gCO ₂ /kWh	482	401	379	365
• Efficiency	43%	52%	55%	57%

1. gCO₂ is based on a kWh delivered to the plug.
2. Efficiency is plant level (net of "own use").
3. National Mix Efficiency is average of fossil plants.

Two market penetration scenarios were defined in Section 6.0. The most conservative scenario, which was used as the baseline, assumes ZEV regulations (following the schedule and maximum penetration established by California) will affect 36% of the vehicle population. The 101 Cities scenario was developed based on a previous DOE study and models a strategy intended to maximize the displacement of gasoline ICEVs by EVs in the 101 metropolitan areas of the U.S. that are nonattainment areas for ozone.

The minivan application is modeled as a commercial vehicle traveling 26,500 km/yr, while the commuter vehicle is assumed to be a private vehicle traveling only 11,040 km/yr. This mileage determination has a considerable impact on fleet aggregate CO₂ emissions and thermal battery losses. The total yearly fleet travel for each scenario is shown in Table 7-4, below:

Table 7-4: Yearly Fleet Travel for Market Penetration Scenarios (Millions of km/yr)

Scenario	2001	2010	2020
Base Case	13,663	86,195	116,532
101 Cities	16,164	89,887	258,573

7.2 Resource Utilization Summary and Comparison of Primary Energy Efficiency

Differences Between Vehicle Classes:

Table 7-5 compares the primary energy requirements (kWh/km) for the composite driving cycle for gasoline ICEV's (ULEV emissions) with EV's (advanced gas generation, low-temperature battery). Gasoline ICEV's in all vehicle classes require significantly more primary energy in 1992 (31% to 50%) than EV's and the margin grows in future time periods.

The difference in primary energy requirements between EV's and ICEV's is greatest for minivans. These estimates indicate that in 1992 gasoline powered commuter cars will require as much primary energy as the EV minivan (although the EV has one-third the range). The estimated gasoline minivan ICEV primary energy requirement in 2020 is twice that of the EV.

The decline in primary energy estimates for all vehicles is noteworthy. By 2020, the estimated gasoline ICEV primary energy consumption is over 45% lower than in 1992. Two-thirds of this decrease is due to vehicle road load reductions and one-third is due to increased driveline efficiency. For EV's, the 2020 primary energy estimate is 60% lower than in 1992. Approximately 60% of this reduction is due to the decrease in road load, 27% is due to EV driveline improvements, and 13% is due to power generation efficiency improvements.

Table 7-5: Primary Energy Consumption of Vehicle Classes (kWh/km)

	1992	2001	2010	2020
Small Commuter - EV	.73	.50	.35	.29
Small Commuter - Gasoline	.90	.65	.55	.49
Family - EV	.81	.66	.45	.32
Family - Gasoline	1.11	.87	.65	.58
Minivan - EV	.90	.71	.50	.36
Minivan - Gasoline	1.35	1.06	.81	.73

Differences Between ICEV Fuels:

Figure 7-1 shows how the various ICEV fuels (ULEV emissions) compare with an EV (advanced gas, low-temperature battery) for the minivan class. Only the CNG minivan has a lower primary energy requirement than the gasoline vehicle. In 1992, the CNG ICEV requires 50% more primary energy than the EV, methanol requires twice as much, and ethanol from corn requires over 3-1/2 times as much primary energy as the EV. Ethanol from wood requires only three times as much energy. As described in Section 4.0, the heating value of the corn and wood feedstock is included in the ethanol primary energy.

Figure 7-1: Primary Energy Consumption Comparison for Alternative Fuels - Minivan

Differences Between Power Generation Mixes:

Figure 7-2 compares EV (low temperature) primary energy estimates for the three power generation scenarios with the estimated CNG (ULEV) minivan primary energy requirement. Under all of the power generation scenarios for all time periods, the minivan EV requires less energy than the minivan fueled by CNG, the most efficient ICEV fuel. In 1992, the CNG ICEV is estimated to require 18% more energy than the EV recharged from the National Mix and 50% more than the EV recharged from advanced technology power plants. In 2020, the CNG minivan will use a little less than twice as much primary energy/km as an EV charged from the advanced gas base, and more than twice as much as an EV charged from the newest ("New Gas") natural gas power plant.

The Influence of Battery Thermal Losses:

Figure 7-3 compares the estimated primary energy consumption of a minivan with various EV battery configurations. Figure 7-4 shows the same comparison for the commuter configuration.

For both figures, 3.2 W/kWh represents the baseline battery thermal loss (USABC criteria); 2.0 W/kWh models the effect of significant insulation system improvements or a 40% reduction in battery capacity; 12 W/kWh represents the performance of current NaS batteries tested at INEL.

Figure 7-2: Primary Energy Consumption for Power Generation Scenarios - Minivan

Figure 7-3: The Effect of Thermal Losses from High Temperature Batteries on Minivan Primary Energy Consumption

Figure 7-4: The Effect of Thermal Losses from High Temperature Batteries on Commuter Primary Energy Consumption

Since the minivan has a relatively high yearly travel, it is less influenced by thermal losses from high temperature battery losses. In the hypothetical 1992 minivan, a high-temperature battery meeting USABC criteria would not require additional energy to meet thermal losses since battery charge/discharge losses are great enough to produce the necessary internal heating. In 2020, due to the assumption of a larger battery capacity and lower charge/discharge loss, the loss for a 3.2 W/kWh battery increases total primary energy consumption by 45% over the low-temperature EV. A loss factor of 12 W/kWh nearly triples the minivan EV energy consumption in 2020. Only the 12 W/kWh EV exceeds the primary energy consumption of the CNG ICEV minivan.

For the commuter, the influence of high-temperature batteries is more dramatic. Due to the relatively short average daily travel of the commuter, the primary energy required for the nominal case (3.2 kWh) equals the CNG primary energy requirement in 2001 and exceeds it by over 90% in 2020. Even the optimistic 2.0 W/kWh case just equals the primary energy required by the CNG commuter.

These estimates show that the primary energy advantage of EV's over CNG or gasoline ICEV's can be negated by high-temperature battery thermal loss. High-temperature battery EV's will only provide energy consumption advantages over ICEV's when only if the USABC thermal loss goal is achieved and even then only if they are used in heavy mileage vehicles or if the battery size (and thus the range) in low mileage vehicles is significantly limited.

The Influence of Natural Gas Fuel Paths:

Figure 7-5 compares natural gas alternatives for the family car class including the CNG ICEV baseline, a CNG vehicle using imported LNG derived natural gas fuel and a fuel cell vehicle. As described in Section 4.0, the FCV fuel chain originates with natural gas, although the 2001 configuration uses methanol as an intermediary. The FCV-methanol configuration (2001) requires more primary energy than the low-temperature EV (although the FCV has greater range). The FCV energy efficiency in future years is essentially the same as the low-temperature EV and much better than the CNG ICEV. Thus, the FCV offers an attractive alternative to EV's if high-temperature battery heat losses are of concern or long range or low refueling time are strong considerations.

Figure 7-5 also shows how the use of imported LNG increases the primary energy requirement for CNG vehicles. For all years, the LNG derived CNG requires 27% more energy than the CNG vehicle using domestic gas. This is due entirely to the less efficiency energy chain for LNG. Consideration of LNG as a source of natural gas for power generation would result in a similar increase for all natural gas derived EV power.

Figure 7-5: Primary Energy Consumption for Natural Gas Scenarios, Including Fuel Cells - Family Car

7.3 Carbon Dioxide Production/km

This section compares the estimated production of CO₂ for a kilometer traveled under various scenarios. In general, the primary energy comparisons drawn previously

between EV scenarios based on natural gas power generation, CNG and CNG/LNG vehicles, relate directly to gCO₂/km since the assumed fuel form is natural gas in all cases. For other primary energy sources (such as petroleum), where fuel forms are changed (such as natural gas to methanol) or where carbon recycling is assumed (ethanol), the CO₂ emissions do not directly scale with the primary energy consumption.

Table 7-6 compares the total fuel chain power plant and vehicular CO₂ emissions (gCO₂/km) in an analogous manner to the primary energy consumption comparison of Table 7-5. The CO₂ emissions advantage of the low-temperature EV over the gasoline ICEV is more pronounced than the primary energy comparison due to the lower carbon content of the natural gas used in power generation. 1992 gasoline ICEV's emit 60% to 100% more CO₂/km than their EV counterparts. In 2020, the CO₂ advantage is 2.2 to 2.6 times in favor of EV's.

Figure 7-6 compares the estimated CO₂ production of ICEV minivans (ULEV emissions) with a minivan EV (advanced gas). Ethanol from corn and CNG are nearly equal in CO₂ emissions and are the best ICEV fuels from this standpoint, producing only 50% more net CO₂ (in the 1992 configuration) than the low-temperature advanced gas EV. As previously discussed, biomass derived ethanol has the potential for zero CO₂ emissions.

Table 7-6: CO₂ Production of Vehicle Classes (gCO₂/km)

	1992	2001	2010	2020
Small Commuter - EV	137	94	67	54
Small Commuter - Gasoline	222	160	135	120
Family - EV	154	126	87	60
Family - Gasoline	273	213	161	142
Minivan - EV	169	135	94	69
Minivan - Gasoline	333	260	198	180

By 2020, the ethanol from corn CO₂ emissions are 80% higher than the EV. Methanol, even though it is derived from natural gas, is the worst ICEV fuel with an estimated emission rate more than double that of the EV in 1992 and 2.8 times worse in 2020.

In Figure 7-7, the estimated CO₂ emissions for minivan EV's under different power generation scenarios are compared with a CNG minivan. The CNG and the "National Mix" EV have essentially the same CO₂ emissions for all time periods. By 2020, either the CNG ICEV or the National Mix EV emits approximately twice as much CO₂ as an EV charged by the newest gas plants in the "New Gas" scenario. These estimates point to the CO₂ emissions benefits which can be gained by using natural gas to generate power for EV's instead of in dedicated CNG vehicles.

Figure 7-6: Carbon Dioxide Production Comparison of EV's and ICEV's - Minivan

Figure 7-7: CO₂ Production for Power Generation Scenarios - Minivan

The Effect of Thermal Losses from High Temperature Batteries:

CO₂ emission estimates for different values of thermal losses from high temperature batteries are shown in Figure 7-8. The minivan configuration shown is less sensitive to these losses and both the 3.2 W/kWh (USABC goal) and the 2.0 W/kWh (smaller battery or better insulation system) emit less CO₂ than the CNG ICEV. The 12 W/kWh (1989 design thermal loss) high-temperature battery is estimated to produce twice as much CO₂ as the EV with a 3.2 W/kWh battery and nearly three times as much as the low-temperature EV. The estimated CO₂ emissions for all commuters based on high temperature batteries, regardless of thermal battery loss factor exceed those of the CNG ICEV.

Figure 7-8: The Effect of Thermal Losses from High Temperature Batteries on CO₂ Emissions - Minivan

The Influence of Natural Gas Fuel Paths:

Figure 7-9 compares the estimated CO₂ production for natural gas alternatives EV's, FCV's, and CNG powered ICEV's. The ranking of these alternatives by CO₂ emissions is similar to the primary energy ranking shown in Figure 7-5. In 2020, FCV's and EV's charged from the advanced gas power generation group have nearly identical emissions. However, in 2001, the FCV CO₂ emissions are higher than even the CNG baseline due to the CO₂ emissions occurring during the methanol conversion process.

Sources of CO₂ Emissions:

Figure 7-10 shows the sources of CO₂ emissions in 2010 for several of the minivan configurations discussed previously. The ICEV estimates are for the ULEV emissions scenario. Fuel chain emissions are shown separately only for ICEV's. The EV-Adv is assumed to be charged from the advanced gas generation group. EV-Nat is charged

Figure 7-9: CO₂ Estimates for Natural Gas Scenarios, Including Fuel Cells - Family

Figure 7-10: Sources of CO₂ in 2010 - Minivan Configuration

from the national mix and EV-HT is a high-temperature battery configuration charged from an advanced gas generation base. This segmentation shows the significance of fuel chain CO₂ emissions for methanol. This points to the need for a more efficient conversion processes or perhaps methods for producing methanol from biomass in order to make this fuel more competitive on a CO₂ emissions basis.

Comparison of the three minivan EV configurations in Figure 7-10 shows that the generation scenario has a greater influence on CO₂ emissions than the high-temperature battery. A lower duty-cycle vehicle or a higher loss battery results in a greater influence of thermal losses from high temperature batteries as was demonstrated in Figure 7-4 for the commuter configuration.

For 2010 and 2020, the CO₂ emissions for a commuter EV with a high-temperature battery charged from the advanced gas generation base exceed the emissions of an EV with low-temperature battery charged from the coal dominated "National Mix".

7.4 Aggregate CO₂ Emissions

This section combines the estimates of vehicle CO₂ emissions per kilometer with the estimates of market size and yearly travel presented in Section 6.0. This comparison assumes that within each vehicle class (i.e., commuter) that all vehicles (ICEV, FCV, and EV) have the same population and same yearly travel.

Since there are very few EV's in operation today, this analysis begins in 2001. Because the estimates in Section 7.3 found that methanol ICEV's emit more CO₂ than gasoline ICEV's, they are not considered further here.

Comparison of Gasoline ICEV's:

Table 7-7 compares the aggregate tons of CO₂ emitted by EV's (advanced power) and gasoline ICEV's for each class of vehicle for the "Base Case" Market scenario which assumes adoption of California ZEV timetable for approximately 36% of the national fleet.

Table 7-7 shows that the net CO₂ emissions reduction from small commuter cars under this scenario is relatively small owing to the relatively low yearly travel, the smaller energy consumption (kWh/km), and the modest market penetration.

Minivans initially provide the most emissions reduction, but their contribution declines in 2020 as the minivan EV population declines. By 2020, family vehicles contribute over 60% of the net CO₂ emissions reductions under this scenario.

Table 7-8 summarizes the net CO₂ reduction of EV's over gasoline ICEV's for the two market scenarios described in Section 6.0.

Table 7-7: CO₂ Emissions by Vehicle Type - Base Case Market Penetration

	2001	2010	2020
Small Commuter			
Vehicles in operation (000):	146	1,790	1,795
• Fleet yearly travel (10 ⁶ km)	1,603	19,684	19,744
• Gasoline CO ₂ (10 ⁶ tons/yr)	.26	2.7	2.4
• EV CO ₂ (10 ⁶ tons/yr)	.15	1.3	1.1
Net CO ₂ Reduction (10 ⁶ tons/yr)	.11	1.4	1.3
Family			
Vehicles in operation (000):	0	1,611	4,581
• Fleet yearly travel (10 ⁶ km)	0	26,892	76,449
• Gasoline CO ₂ (10 ⁶ tons/yr)	0	4.3	10.8
• EV CO ₂ (10 ⁶ tons/yr)	0	2.3	4.6
Net CO ₂ Reduction (10 ⁶ tons/yr)	0	2.0	6.2
Minivan			
Vehicles in operation(000):	451	1,471	741
• Fleet yearly travel (10 ⁶ km)	11,984	39,137	19,687
• Gasoline CO ₂ (10 ⁶ tons/yr)	3.1	7.8	3.5
• EV CO ₂ (10 ⁶ tons/yr)	1.6	3.7	1.3
Net CO ₂ Reduction (10 ⁶ tons/yr)	1.5	4.1	2.2

Table 7-8: Net CO₂ Reduction (10⁶ tons/yr) of EV's Over Gasoline ICEV's for Market Scenarios

	2001	2010	2020
Small Commuter			
• Base	.11	1.4	1.3
• 101 Cities	.16	1.8	3.8
Family			
• Base	0	2.0	6.2
• 101 Cities	0	2.0	16.2
Minivan			
• Base	1.5	4.1	2.2
• 101 Cities	1.7	1.5	0
Total Fleet			
• Base	1.6	7.6	9.7
• 101 Cities	1.9	5.3	20.0

In both scenarios, the minivan provides the bulk of the emissions reduction for 2001, and the family vehicle is the dominant contributor in 2020. The yearly CO₂ emissions reduction is nearly flat after 2010 in the base case due to the assumption that EV's will be regulated as a constant percentage of total fleet sales.

Appendix A: EV CO₂/Energy Model Description

The EV CO₂/Energy Model is a spreadsheet tool written for Quattro-Pro. The program consists of 12 linked modules which calculate energy consumption and CO₂ emissions for electric and alternative fuel vehicles. The derivation of input data and calculation methodologies is described in the report entitled *The Impact of Electric Vehicles on CO₂ Emissions*.

Figure A-1 shows the modules in the program and their interlinking. In the real world, energy flows from primary resources through conversion processes (power generation, engines, etc.) and eventually is applied to the "useful" work of overcoming vehicular road load.

The calculation routine used to estimate primary energy and CO₂ emissions however necessarily starts with a defined road load and calculates all of the upstream losses and efficiencies.

Each module in the program is briefly described below, starting with calculation of road load:

- **EVTOTEN** calculates the total energy required from the battery for EV's based on user input of road load for Urban (col. F) and Highway (col. J) driving cycles. The composite road load is based on the EPA consumption weighting of 55% urban/45% highway. The efficiency of EV driveline elements and accessories pictured in Figure 3-3 are input in the table at the top of the module and are used to convert road load into energy from the battery.
- **THERMAL** calculates the thermal loss from high-temperature batteries based on the battery thermal loss factor, capacity, and other factors discussed in Section 3.0. User input includes loss factor, vehicle yearly travel, and battery capacity.
- **BATTERY** converts EV energy "from the battery" into energy "from the plug" using efficiencies for the battery and charger. Fuel cell and reformer efficiencies are also used in this module to calculate fuel cell energy "from the tank" for the family car only.
- **FUELUSE** converts energy "from the plug" to the primary energy and CO₂ emissions based on a user specified power plant efficiency/CO₂ generation scenario. Three such scenarios are provided based on data presented in Section 5.0.
- **EFF** calculates ICEV driveline efficiencies (LHV) for each time period, fuel type, and vehicle based on user specified percentage increases over the baseline 1992 gasoline driveline. Estimates are provided for ULEV and Federal Tier 1 emissions (see Section 3.0).

- SIMDAT takes the user specified urban and highway road loads (for instance from SIMPLEV or other vehicle simulation program) and driveline efficiency (LHV) for ICEV vehicles and calculates composite cycle energy from the tank for the composite EPA cycle (55% urban, 45% highway on a consumption basis).
- ENGINE calculates the CO₂ emissions associated with ICEV combustion. Ethanol emissions from full combustion have been set to zero because all ethanol related CO₂ emissions are accounted for in the fuel chain analyses (see Section 4.0).
- CHAIN is a matrix of user specified efficiencies and CO₂ emissions for each ICEV fuel chain. (See Table 4.3 and associated discussion for assumptions and details of derivation.)
- PRIMARY converts ICEV vehicular energy to a HHV basis and adds fuel chain energy requirements to calculate total primary energy requirements for ICEV's. EV primary energy requirements (from FUELE) are also displayed.
- MARKET allows the user to specify scenarios for market penetration by year for each vehicle type. The data is entered in the top matrix in the form of millions of kilometers traveled per year for each class and time period. Three scenarios developed in Section 6.0 are shown for reference.
- SUMMARY summarizes all CO₂ emissions from power plant, fuel chain, and ICEV combustion. Section II summarizes vehicular CO₂ emissions (g/km) from ENGINE. Section III summarizes fuel chain CO₂ (g/km) emissions using vehicular consumption from ENGINE, fuel properties from FUELE and energy chain efficiencies from CHAIN. Section IV summarizes all CO₂ emissions in g/km and fleet totals (millions of tons/yr). Annual travel for each vehicle category and year (from MARKET) is used to calculate the tons of CO₂ emitted by all vehicles in each class for each fuel type and time period.

Opening the SUMMARY module and linked modules will activate all modules listed above.

Figure A-1: Flow Chart for the Spreadsheet Tool

END

**DATE
FILMED**

1 / 27 / 93