ANL--92007030

ANL--92007030

DE92 007030

ARGONNE NATIONAL LABORATORY
Laboratory Directed Research and Development
FY 1991 PROGRAM ACTIVITIES

SUMMARY REPORT

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

By

Strategic Planning Group
Office of the Director
November 15, 1991

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

	<u>Page</u>
1.0 INTRODUCTION	iv
2.0 PROJECT AND TECHNICAL EMPHASES	v
3.0 PROJECT SUMMARIES	
3.01 New Advanced Research Techniques for High Brightness Synchrotron Studies	1
3.02 SSC Physics and Data Handling Conceptualization.....	3
3.03 Production and Study of Coherent Radiation Using the APS Linac.....	6
3.04 Development of Coherent X-Ray Optics and Coherence-Based Techniques	9
3.05 Corrosion and Spherical Mirror Analyzer - Display Type	11
3.06 Advanced Techniques for Synchrotron Radiation Research	16
3.07 Anomalous X-Ray Scattering.....	18
3.08 Time Domain Synchrotron Research	20
3.09 Catalysis and Coal.....	25
3.10 Atomic Physics Using Synchrotron Radiation.....	29
3.11 X-Ray Techniques for Biomedical Research.....	32
3.12 Process Development for Recovery of Oxide-Reduction Salts	34
3.13 Pyrochemical Actinide Extraction	36
3.14 Numerical Modeling of Anisotropic Turbulence	39
3.15 Advanced Reactor Studies for 600 MWe LMR	43
3.16 Laser Aided Materials Processing Research	48
3.17 Fabrication and Testing of 1-kJ High-Temperature Superconducting Magnetic Energy Storage Device	49
3.18 Effects of Interfacial Bond Strength on Toughness of Ceramic Fiber-Reinforced Ceramic Matrix Composites	51
3.19 Characterization of Elastomers	56
3.20 Theoretical Developments in Superconductivity	59
3.21 Low Temperature Scanning Tunneling Microscope	60
3.22 Advanced Superconducting Magnet Design Study	62
3.23 "Buckeyball" Tribology	69
3.24 Advanced Computing Methods for Genome Sequencing	71
3.25 Logic-Based Systems for Automated X-Ray Crystallography	73

- Contents - continued...

3.26	Scalability and Performance Issues in the Molecular Sciences	75
3.27	Vortex Structures in Superconductors	77
3.28	Application of Automated Reasoning to Equality-Oriented Reasoning, Program Verification, and Circuit Design	78
3.29	Computational Simulation of Protein Interaction	79
3.30	Human Genome Sequencing by Hybridization	81
3.31	Inosine 5-Monophosphate Dehydrogenase Growth Control	83
3.32	Gene Fusion Technology	86
3.33	Modeling and Remote Sensing of Global Terrestrial Ecosystems	89
3.34	Cancer Risk Assessment Bases	93
3.35	Remote Sensing and Global Change	95
3.36	Degradation of Hazardous Chemicals Using Thermal and Biological Treatment	97
	<u>Part I:</u> Rate Study of Thermal Destruction of Selected Hazardous Chemical Surrogates Utilizing FTIR Analysis	
	<u>Part II:</u> Biodegradation of Hazardous Wastes Using the White Rot Fungus Phanerochaete Chrysosporium and its Lignin Peroxidase	
3.37	Mixed Hazardous Waste Stabilization Techniques	102
3.38	Assessment of Risk Associated with Exposure to Molten Cadmium	104
3.39	Argonne Experimental Initiative on Maglev	110
3.40	Picosecond Optical Switching with Molecular Electronic Devices	114

1.0 INTRODUCTION

The purposes of Argonne's Laboratory Directed Research and Development (LDRD) Program are to encourage the development of novel concepts, enhance the Laboratory's R&D capabilities, and further the development of its strategic initiatives. Among the aims of the projects supported by the Program are establishment of engineering "proof-of-principle"; development of an instrumental prototype, method, or system; or discovery in fundamental science.

Several of these projects are closely associated with major strategic thrusts of the Laboratory as described in Argonne's Five Year Institutional Plan, although the scientific implications of the achieved results extend well beyond Laboratory plans and objectives. The projects supported by the Program are distributed across the major programmatic areas at Argonne as indicated in the laboratory's LDRD Plan for FY 1991. Table I displays the area of principal emphasis (indicated by an "X") as well as additional area(s) to which a contribution was made (indicated by an "o") for each project. Individual reports summarizing the purpose, approach, results and accomplishments of projects funded under Argonne's LDRD Program for FY 1991 then follow.

2.0 FISCAL YEAR 1991

LABORATORY DIRECTED RESEARCH AND DEVELOPMENT FUNDS

	<u>Project Title</u>	<u>COST</u> \$ Thousands
3.01	New Advanced Research Techniques for High Brightness..... Synchrotron Studies	502.5
3.02	SSC Physics and Data Handling Conceptualization	81.7
3.03	Production and Study of Coherent Radiation Using the APS Linac	175.4
3.04	Development of Coherent X-Ray Optics and Coherence- Based Techniques	514.1
3.05	Corrosion and Spherical Mirror Analyzer - Display Type	101.0
3.06	Advanced Techniques for Synchrotron Radiation Research	211.2
3.07	Anomalous X-Ray Scattering	80.2
3.08	Time Domain Synchrotron Research	295.5
3.09	Catalysis and Coal	102.6
3.10	Atomic Physics Using Synchrotron Radiation	187.5
3.11	X-Ray Techniques for Biomedical Research	796.8
3.12	Process Development for Recovery of Oxide-Reduction Salts	247.2
3.13	Pyrochemical Actinide Extraction	224.5
3.14	Numerical Modeling of Anisotropic Turbulence	166.2
3.15	Advanced Reactor Studies for 600 MWe LMR	306.0
3.16	Laser Aided Materials Processing Research	247.5
3.17	Fabrication and Testing of 10-kJ High-Temperature Superconducting Magnetic Energy Storage Device	260.5
3.18	Effects of Interfacial Bond Strength on Toughness of Ceramic Fiber-Reinforced Ceramic Matrix Composites	220.0
3.19	Characterization of Elastomers	105.2
3.20	Theoretical Developments in Superconductivity	84.7
3.21	Low Temperature Scanning Tunneling Microscope	88.9
3.22	Advanced Superconducting Magnet Design Study	69.3
3.23	"Buckeyball" Tribology	28.6
3.24	Advanced Computing Methods for Genome Sequencing	81.3
3.25	Logic-Based Systems for Automated X-Ray Crystallography	31.6
3.26	Scalability and Performance Issues in the Molecular Sciences	32.1
3.27	Vortex Structures in Superconductors	37.0

- 2.0 Fiscal Year 1991 - continued...

3.28	Application of Automated Reasoning to Equality- Oriented Reasoning, Program Verification, and Circuit Design	53.9
3.29	Computational Simulation of Protein Interaction	21.2
3.30	Human Genome Sequencing by Hybridization	300.1
3.31	Inosine 5-Monophosphate Dehydrogenase Growth Control	44.9
3.32	Gene Fusion Technology	49.1
3.33	Modeling and Remote Sensing of Global Terrestrial Ecosystems	313.0
3.34	Cancer Risk Assessment Bases	40.9
3.35	Remote Sensing and Global Change	9.9
3.36	Degradation of Hazardous Chemicals Using Thermal and Biological Treatment <u>Part I:</u> Rate Study of Thermal Destruction of Selected Hazardous Chemical Surrogates Utilizing FTIR Analysis <u>Part II:</u> Biodegradation of Hazardous Wastes Using the White Rot Fungus Phanerochaete Chrysosporium and ITS Lignin Peroxidase	300.3
3.37	Mixed Hazardous Waste Stabilization Techniques	214.7
3.38	Assessment of Risk Associated with Exposure to Molten Cadmium	21.0
3.39	Argonne Experimental Initiative on Maglev	256.1
3.40	Picosecond Optical Switching with Molecular Electronic Devices	108.5
TOTAL ALLOCATIONS:		7,012.7

TABLE I

	Advanced Accelerator and Detector Technology	X-Ray Techniques for Research in the Biological and Physical Sciences	Advanced Reactor Technology	Materials Science and Technology	Computational Science and Technology	Biological Sciences	Environmental Science	Environmental Control and Waste Management Technology	Novel Concepts in Other Areas
3.01	X	o							
3.02	X								
3.03	X								
3.04	X			o					
3.05	o	X		o					
3.06		X		o					
3.07		X							
3.08		X							
3.09		X							o
3.10		X							
3.11		X							
3.12			X	o					o
3.13			X	o					
3.14			X		o				
3.15			X						
3.16				X					
3.17				X					
3.18				X					
3.19			o	X					
3.20				X					
3.21				X					
3.22				X					o
3.23				X					
3.24					X	o			
3.25					X	o			
3.26					X				o
3.27				o	X				
3.28					X				
3.29					X	o			
3.30						X			
3.31						X			
3.32						X	o	o	
3.33					o		X		
3.34							X		
3.35					o		X		
3.36						o		X	
3.37			o					X	
3.38							o	X	
3.39				o	o				X
3.40				o	o				X

(3.01) NEW ADVANCED RESEARCH TECHNIQUES FOR HIGH BRIGHTNESS SYNCHROTRON STUDIES

Associate Laboratory Director Area: Physical Research

Principal Investigators: P.A.Montano, G.S.Knapp, Materials Science

Funding History:	FY 1989	\$0K
	FY 1990	\$*
	FY 1991	\$502.5K

Purpose: Our research is directed towards the preconceptual design of the beam lines for the Basic Energy Sciences Synchrotron Radiation Center(BESSRC) at the APS.

Approach: One of our principal tasks is to evaluate the technical characteristics of insertion devices used for the generation of circularly polarized radiation. This type of radiation will be applied to the study of magnetic properties of materials. Development of software and computer interfaces to be used in our beam lines at APS. Development of optical components for the BESSRC beam lines.

Technical Progress and Results: We made a comparative study of the new insertion devices that have been introduced to deliver tunable circularly polarized radiation. Among the various conceptually different devices proposed and built are: (i) helical undulators; (ii) the crossed planar undulator; (iii) asymmetric wigglers; and (iv) the elliptical multipole wiggler. We require an insertion device that can produce circularly polarized light over the 1-100 keV energy range. Only the asymmetric wiggler and the elliptical multipole wiggler can fulfill these requirements since the first two are relatively low energy devices. The simplest way to understand these two types of wigglers is to first consider the physics of bending magnet radiation. In the plane of the orbit there is linear polarization and above and below there is circularly polarized light with opposite polarizations. A standard wiggler can be thought of as a series of back to back bending magnets so the polarization from each half cancels the other. The asymmetric wiggler works by making the fields strong on one half cycle and weak on the other so the radiation comes primarily from the strong region and therefore has polarization properties much like a series of bending magnets. The elliptical wiggler is a combination of a strong vertical wiggler and a weak horizontal wiggler. The phases of the magnets are adjusted so that the electrons follow a highly elliptical path so that on one half cycle the electrons are slightly above the center plane and on the other half slightly below. The circularly polarized radiation from each half now has the same direction on axis. It is now clear that the elliptical wiggler will be much more efficient than the asymmetric wiggler since it does not require the weak field regions which produce little radiation. It is also much more flexible and is capable of operating as a helical undulator with a first harmonic in the 1-2 keV range. This great brilliance and flexibility will make this type of device ideal for our varied needs in the studies of magnetic materials.

We continued with our tests of new optical components for our projected beam lines at APS. We are constructing a new beam line (X-6A) at the NSLS for time resolved measurements. The beam line will be completed during 1992. We hired a temporary staff scientist to assist in the construction and assembly of the beam line (Dr. Guy Jennings). This beam line will be our testing ground for proposed time resolved experiments at the APS. We plan this beam line to be the first operational energy dispersive x-ray facility in the USA. Our research program in this direction is moving on schedule.

A technical staff member specializing in computer interfacing was hired to do work related to our beam lines. This person has many years of experience at NSLS in the design and development of software and hardware for synchrotron radiation beam lines (Mark Engbretson). He is working at our beam lines at NSLS, doing development work on x-ray scattering programs. He is also involved in the design and development of the computer programs that will represent the core of our computational capabilities at the BESSRC beam lines.

We have been successful during the past year in the development of new technical components for research at our beam lines, for example, sagittal focusing for our beam lines and new detectors design.

Specific Accomplishments: We investigated in detail the type of insertion device needed for generation of circularly polarized light. We decided that the elliptical multipole wiggler is the most appropriated device. A new beam line for time resolved measurements at NSLS was designed. New computer software for interfacing x-ray equipment to our beam lines at NSLS were developed, as well as prototypes for our beam lines at APS.

* This project was one of four subtasks of a FY 1990 LDRD project funded at \$785.6K.

(3.02) SSC PHYSICS AND DATA HANDLING CONCEPTUALIZATION

Associate Laboratory Director Area: Physical Research

Principal Investigator: T. B. W. Kirk, High Energy Physics

Funding History:	FY 1989	\$111.5K
	FY 1990	\$294.5K
	FY1991	\$81.7K

Purpose: The general purpose experimental detectors for the 40-TeV Superconducting Super Collider (SSC) will require conceptual as well as technological advances to meet the scientific goals of the program. The LDRD program funded here contributed helpful concepts to the Solenoidal Detector Collaboration (SDC) for the evolving SDC detector concept, for its technological realization and for data handling and analysis of the resulting anticipated data stream from this detector. Success in this phase of the SDC work has improved the collaboration's technical position for preparation of its formal proposal to the SSC Laboratory (the proposal is due April 1, 1992) as well as solidified the ANL group as principal leaders in the very large (600 members, 100 institutions) SDC.

Approach: Argonne high energy physicists have played key roles in a string of collider physics collaborations (HRS, CDF, ZEUS) stretching back to the early collider experiments and detectors in HEP. The current intense activity in the field to define and develop detectors for the coming SSC era posed a challenge to Argonne physicists that they have gladly taken up. Not only has the energy scale been raised by a factor of 22 over the CDF program at Fermilab, but the raw interaction rates at the SSC will be more than two orders of magnitude higher. These daunting parameters must be coped with in order to reach the compelling SSC goal of studying the Higgs particle (or mechanism), hence uncovering a key part of the riddle surrounding the nature of mass in particle physics.

The scope of the present investigation is the attempt to conceptualize and characterize an optimum general purpose detector for SSC that meets its key physics requirements in a cost-effective manner. The means of organizing, handling, and processing the huge amounts of raw data generated by this detector as well as the information characterizing the detector itself were also included as part of the scope.

The method of meeting the goals of this investigation included analysis by individual investigators, group discussions, and meetings to refine ideas, calculations, and simulations to compare alternative concepts and comparisons with existing detectors, technologies, and data handling methods. No laboratory work per-se was carried out directly in this study, but concepts were identified that were, or will be, explored by ANL and other groups under separate sponsorship.

Technical Progress and Results: During FY1990, the first phase of the work was completed. This consisted of the completion of a computer-based system for information handling jointly developed by physicists and engineers at the SSC Laboratory in Dallas, Texas and at Argonne National Laboratory. The system is based on Sun Computers linked through the Bitnet electronic network among the key institutions in the Solenoidal Detector Collaboration. The the end of FY90, the SDC collaboration and the SSC Laboratory agreed to adopt the developed prototype system as the official SDC information handling system. At the start of FY91, SSCL took over responsibility for developing and managing the system. It is now in use under SSCL management and Argonne is a principal user along with other institutions collaborating in SDC.

In FY91, attention turned to the functional and technological conceptualization of the SDC detector. Technical requirements were developed for the SDC detector to meet the physics goals of the collaboration. Argonne's role in this work was focussed on design of the central calorimeter, the key subsystem of the entire experiment. The functional requirements for energy resolution and segmentation (transverse and longitudinal) were decided and a technology based on scintillating plastic tiles embedded in a steel and lead mechanical matrix were identified. The resulting tile/fiber calorimeter concept has recently been adopted by the SDC as its baseline design after spirited competition against alternative designs advocated by other SDC institutions.

A number of benchmark physics processes that are accessible to the SSC were used to evaluate the projected performance of the tile/fiber calorimeter design and the parameters refined to optimize performance. The detection of the Higgs particle in the mass interval from 80 GeV to 150 GeV through its two-photon decay was a key benchmark. Jet-jet decays of the Z boson were also used to optimize calorimeter parameters. The use of both analytical and simulation methods allowed this work to be completed.

In FY92, the calorimeter preliminary engineering design will be completed and its cost estimated. The official design report and proposal of the SDC will be submitted to SSCL. This work will be supported by programmatic funds from the SSC and no support from LDRD is expected in FY92. The tile/fiber calorimeter concept developed under the FY91 LDRD will be the basis of the central calorimeter for SDC.

Specific Accomplishments: The tile/fiber calorimeter concept and the associated physics requirements developed under this LDRD project were documented in a number of SDC notes and reports. We list these here:

1. "Letter of Intent by the Solenoidal Detector Collaboration", SDC-90-00151, November 30, 1990.
2. "Estimation of Hadronic and EM Resolution for Scintillator Plate Calorimeter Configurations", P. K. Job and J. Proudfoot, SDC-91-00013, March, 1991.
3. "Central Calorimeter Configuration - A Study Report to the SDC Technical Board", T. Kirk, B. Wicklund, SDC-91-00018, April 11, 1991.

4. "The Effect of Passive Material on the Detection of Hadrons in Calorimeter Configurations for the SDC Detector", T. B. W. Kirk, and H. J. Trost, SDC-91-00050, July, 1991.
5. "b-Jet Tagging Using Electrons at SDC", A. B. Wicklund, SDC-91-00051, July 25, 1991.
6. "Fiber-Tile Optical Studies at Argonne", D. G. Underwood, SDC-91-00052, August, 1991.
7. "SDC Calorimeter Design Requirements", edited by J. Siegrist, August 5, 1991.
8. "Conversion Electrons in SDC", B. Wicklund, SDC-91-00059, August, 1991.
9. "Calorimeter Conceptual Design - Tile/Fiber Scintillator Option", SDC Tile/Fiber Calorimeter Group, September 5, 1991.

(3.03) PRODUCTION AND STUDY OF COHERENT RADIATION USING THE APS LINAC

Associate Laboratory Director Area: Advanced Photon Source

Principal Investigators: G. Mavrogenes, M. Borland, Accelerator Systems,
P. J. Viccaro, E. Gluskin, Experimental Facilities, APS

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$175.4K

Purpose: A test stand providing a low-emittance electron beam of the proper-energy offers the capability to readily assess the performance of novel insertion device (ID) designs. Such R&D serves to efficiently determine the most productive direction for future ID research and design.

Approach: There are several promising avenues for the enhancement of the spatial coherence of ID radiation. One of these involves the use of multi-section devices, such as a double-undulator system, where the two undulator sections are separated by an achromatic bend section. For this type of multi-sectioned device, a low emittance particle beam is essential, as is the preservation of that low emittance in a storage ring containing such an insertion device. Under favorable conditions, the radiation coherent phase-space area is expected to be at least a few orders of magnitude greater than that produced by a single planar undulator.

Another type of multi-undulator device has the potential to substantially improve the temporal coherence of X-ray radiation while simultaneously preserving the total power. This system is based on a set of identical undulators with dispersion sections between them, and produces a set of sharp X-ray lines inside the width of the undulator harmonic. The multi-undulator system selects one of these lines and, given a low-emittance electron beam, can provide extremely high coherent radiation power.

While other systems are possible, the two proposed systems are representative of the types of new geometries that need to be investigated for the enhancement of coherent flux. Similar devices have also been proposed for the enhancement of polarization properties, and these could be of potential interest to the program. These devices are of multi-section design and result in complex perturbation of the particle beam.

Another area of potential interest is the production of 1 to 100 micron radiation using short electron bursts from an RF linac coupled with an undulator installed within resonant mirrors. The Advanced Photon Source (APS) will have a 650 MeV electron linac as part of the injector facilities, capable of accelerating up to 50 nC of charge in a 30 ns pulse. However, the emittance of this beam is too large to make it suitable for the applications proposed here.

The only available way of improving the beam emittance is to use a high-brightness, RF-gun-based system in place of the existing thermionic triode gun with its associated prebuncher. Use of a thermionic RF gun is a cost-effective way to provide an electron beam with emittance reduced by a factor of 15. Space is available for such a gun and its associated transport system in the region of the first section of the APS linac, with injection into the second linac section. Space is available to extract this beam into the infield region of the APS and for the construction of required experimental facilities.

Technical Progress and Results: A new RF gun design was completed, starting from the successful SSRL design. The APS design has about a three-fold reduction in beam emittance relative to the SSRL design, implying an order of magnitude greater brightness. In the absence of space-charge effects, the predicted emittance is about 0.25 π -mm-mrad for a momentum spread of $\pm 5\%$. Preliminary studies of space-charge effects in the APS design indicate that, as in the SSRL design, space-charge effects should no more than double the emittance at high current (i.e., 0.5 nC per bunch or 50 nC per 30 ns pulse).

The ratio of peak surface field to cathode field is 0.48 in the APS design, compared to 0.30 in the SSRL design, resulting in more rapid initial acceleration, and hence greater suppression of space-charge effects. In spite of this difference in field distribution, the SSRL and APS designs can be installed on the same magnetic compression system, with anticipated bunch lengths in the sub-picosecond range.

Significant effort has been devoted to understanding how an emittance-preserving transfer line can be made without an alpha-magnet while still obtaining the sub-picosecond bunch lengths possible from an alpha-magnet-based system.

A preliminary design of an undulator test beamline has been done. The beamline can operate in one of two imaging modes for each transverse plane. One mode allows detection of a two microradian deflection error, while the other allows detection of a two micrometer trajectory error.

Specific Accomplishments: A technical specification (Document No. 21-00006) was produced for two prototype guns, one of SSRL design and one of the APS design. The contract was awarded to AET Associates, and both guns have been delivered.

Internal notes produced:

"Wavelength Ranges of Coherent Undulator Radiation from the APS Linac and a RF Gun", Borland, M., APS/LINAC/91-1, April 23, 1991.

"Preliminary Cavity Design for the APS RF Gun", Borland, M., July 8, 1991.

PROTOTYPE RF GUNS

(3.04) DEVELOPMENT OF COHERENT X-RAY OPTICS AND COHERENCE-BASED TECHNIQUES

Associate Laboratory Director Area: Advanced Photon Source

Principle Investigators: Wenbing Yun, P. James Viccaro, Dennis Mills,
Experimental Facilities, Advanced Photon Source

Funding History:

FY 1989	\$0K
FY 1990	\$389.6K
FY 1991	\$514.1K

Purpose: The feasibility of development of coherent x-ray optics and coherence-based techniques in the x-ray spectral region (1- 30 keV) is being explored. Coherence-based x-ray techniques, for example, diffraction-limited microfocusing, holography, interferometry, phase contrast and signal enhancement scattering, and wave front manipulation, offer substantial advantages over non-coherence-based x-ray techniques, which include most x-ray techniques currently in use. The development of the coherence-based techniques will be facilitated by the high coherence flux of the third generation synchrotron sources under construction worldwide (e.g., APS), and other coherent x-ray sources (e.g., x-ray laser). This project includes three integral parts: (1) a study of the feasibility of extending various coherence-based techniques developed in the visible spectral region to the x-ray spectral region, (2) development of coherent x-ray optics, and (3) preliminary experimental demonstration of the underlying principles.

Approach: The coherent flux of x-rays that is available today (or in the near future) and the feasibility of fabricating coherent x-ray optics are two important aspects for the development of coherence-based techniques. Several methods to be used for improving the coherence property of an x-ray beam were investigated. Fabrication of Fresnel phase zone plates for applications in diffraction-limited microfocusing and wave-front manipulation were studied theoretically. A plan for fabricating diffraction-limited microfocusing phase zone plates for focusing 1-20 keV x-rays was established that is based on an analysis of the capabilities and limitations of the two techniques currently in use. Several prototype Fresnel zone plates optimized for x-rays of energy greater than 7 keV were fabricated in collaboration with Dr. R. M. Bionta of Lawrence Livermore National Laboratory. Extensive experimental measurements were done to investigate the focusing properties of the zone plates. Analysis of the experimental results was made to derive zone plate parameters relevant to its focusing properties. For focusing x-rays of energy less than 7 keV, zone plates are currently being fabricated in collaboration with Dr. F. Cerrina of University of Wisconsin. In addition, in collaboration with Dr. G Fenske of Argonne National Laboratory, an existing deposition system is being modified for x-ray optics fabrication.

Technical Progress and Results: Fiscal year 1990 was devoted mainly to the theoretical study of the feasibility of extending various coherence-based techniques from visible light region to the x-ray region and to the establishment of collaborations in the fabrication of diffraction-limited

microfocusing optics. In fiscal year 1991, we carried out extensive characterization of several prototype Fresnel zone plates and preliminary demonstration of microfocusing-based techniques, such as microimaging, microanalysis, and microspectroscopy.

Several prototype Fresnel zone plates of focal lengths 30 and 40 cm for 8 keV x-rays were designed and made. Characterization of the zone plates using synchrotron x-rays was done. A focal spot less than 2 microns was obtained. The focusing efficiency of a 40-cm focal length zone plate was measured as a function of x-ray energy between 5-17 keV. A maximum focusing efficiency of 20% was obtained for 8.7 keV x-rays. Preliminary experiments using this zone plate in microimaging, microanalysis, and microspectroscopy were carried out.

In addition to Fresnel zone plates, other types of diffraction-limited focusing elements were investigated, and their fabrication tolerances were analyzed. Fabrication of Bragg-Fresnel optics was carried out in collaboration with Dr. Troy Barbee of LLNL. A linear-patterned multilayer Bragg-Fresnel optic was fabricated. This type of optics will be used for real-time x-ray reflectivity measurement. Such a measurement will enable one to study kinematical and dynamical process at surfaces and interfaces.

Specific Accomplishments:

Publications:

1. W. Yun, P. J. Viccaro, J. Chrzas, and B. Lai, "Coherent Hard X-Ray Focusing Optics and Applications," Rev. Sci. Instrum., in press.
2. T. M. Mooney, E. E. Alp, W. Yun, "Mossbauer-Fresnel Zone Plate", submitted to Applied Physics Lett.
3. B. Lai, J. Chrzas, W. Yun, D. Legnini, and P. J. Viccaro, "Experimental Characterization of Fresnel Zone Plate for Hard X-Ray Applications," paper presented at SPIE's International Symposium on Optical Applied Science and Engineering, San Diego, 21-26 July 1991.
4. J. Chrzas, W. Yun, B. Lai, and D. Legnini, "Material Considerations for Hard X-ray Zone Plates," to be presented at the 7th National Conference on Synchrotron Radiation and Instrumentation, 28-31 October 1991.
5. B. Lai, W. Yun, J. Chrzas, D. Legnini, and P. J. Viccaro, "Applications of Zone Plate Based Hard X-ray Focusing Optics," to be presented at the 7th National Conference on Synchrotron Radiation and Instrumentation, 28-31 October 1991.
6. D. Legnini, W. Yun, B. Lai, and J. Chrzas, "Phase Zone Plate Based Scanning X-ray Microscope," to be presented at the 7th National Conference on Synchrotron Radiation and Instrumentation, 28-31 October 1991.

(3.05) CORROSION AND SPHERICAL MIRROR ANALYZER - DISPLAY TYPE

Associate Laboratory Director Area: Physical Research

Principal Investigator: D. M. Gruen, Chemistry/Materials Science

Funding History:	FY 1989	\$0K
	FY 1990	\$* (Subtask II only)
	FY 1991	\$101K (Subtasks I and II)

Spherical Mirror Analyzer - Display Type (Subtask I)

Purpose: A spherical mirror analyzer: display-type (SMADT) apparatus is being developed in our laboratory for applications that probe the structure and dynamical behavior of surfaces at a very detailed level. It is now realized that angular distributions of photoelectrons can be exploited to provide structural information about the near-surface region by direct inversion through the techniques of "holographic crystallography." The correctness of the forward scattering interpretation of angular distributions of ejected electrons has become clear during the past year, and there seem to be good prospects for routinely achieving the direct three-dimensional determination of surface structures that are several layers deep. This could become a valuable resource on the Argonne APS synchrotron, with applications to many pure and applied areas of research. Catalysis and corrosion studies are examples of applied areas in which structural information is essential to mechanistic insight.

Approach: This proposal is intended to take advantage of recent developments in particle-optics technology in order to implement a new type of angle-resolved analyzer to be developed as an x-ray photoelectron spectroscopy facility on the Advanced Photon Source. The proposed device will map electrons emitted from a sample onto a spatially resolved detector that will also have high-speed counting capability with low background, allowing maximum dynamic range. The intrinsic lack of any moving parts in the basic electron-spectroscopy "camera" will facilitate reliable operation. The resulting apparatus can rapidly generate complete angular maps of x-ray-induced photoelectrons emitted within a narrow energy window. The brilliant APS photon beams can be exploited in order to scan the surface region of samples with high spatial resolution. Variations of the technique include the differencing of scans taken above and below core levels of specific elements, and operation in modes that emphasize sensitivity to species residing near the surface of a sample.

Our instrument design adopts an innovative suggestion of H. Daimon who has pointed out that the desired angular mapping can be achieved through the use of only two concentric spherical surfaces. Furthermore, the transmitted particles lie in a narrow, intrinsically *differential* energy window. The first demonstration of the technique produced dramatically clear LEED patterns, as demonstrated on a Si(111) 7x7 surface. This aspect is very useful for *in situ* characterization of the sample surface condition. Subsequently, improvements enhancing the energy resolution of the device were introduced, and application to two additional types of experiment was

demonstrated: (1) x-ray photoelectron spectroscopy (XPS), and (2) angle-resolved electron stimulated desorption of ions (ESDIAD)]. For analysis, electron- and photon-stimulated desorption can be employed as a very sensitive diagnostic of the top surface layer. In our version of the angular distribution camera, we will also be able to utilize laser ionization of neutrals to supplement the ion-channel information regarding photodesorbed species. Operation at the APS facility will allow these investigations at deep-core levels.

Technical Progress and Results: This project was first formally proposed in a memo (D. M. Gruen to P. A. Montano) dated August 24, 1990 and was not funded prior to FY 1991. Co-investigator, C. E. Young, has investigated a number of modifications to the original 180° hemispherical SMADT design involving the use of a truncated sector (e.g., 120°) for the purpose of increasing the access of diagnostic beams (x-ray photons, electrons, laser beams) to the sample surface. Some effort also went into considerations for allowing the use of interchangeable detector systems optimized for different possible experiments. Also, a commercial supplier has been found for the critical spherical grid system (requirements: large diameters, fine mesh, minimal distortion). A configuration for sturdy mechanical and electrical construction on a single flange has been chosen. These improvements are expected to contribute significantly to the applicability of the SMADT instrument to a variety of experiments.

Specific Accomplishments: In FY1991 we have concentrated on the design of components for the SMADT apparatus that will allow for a program of laboratory tests. LDRD funding for this interval was 4.5 months effort. The layout for a dedicated vacuum chamber has been produced which will allow for (1) a multiple-sample carousel with heating and cryogenic cooling capability, and (2) capability for detector-system flexibility, allowing for the interchangeable use of optimal detector types (wedge/strip anode for temporal and spatial data; phosphor/CCD technology for high-data-rate spatial data alone). A number of alternatives for the layout of the chamber were explored and good design was reached within the capabilities of standard UHV commercial production. Dr. L.-J. Wang (Department of Physics and Astronomy, University of Tennessee, Chattanooga) has collaborated with our group as a faculty research participant (May-July 1991), carrying the design of the sample carousel and the vacuum chamber support frame through to the level of machine-shop drawings. All drafting and design work has been performed on a high-level computer CAD program, ensuring compatibility in a complex spatial layout and allowing for convenient drawing updates. Plans for the near future include the following steps: (1) obtain bids on a suitable vacuum test chamber for the instrument, (2) complete detailed machine drawings for the spherical mirror components, and (3) begin construction work on both the vacuum housing and SMADT instrument.

Corrosion: Device for X-ray Studies of Electrode/Electrolyte Interfaces (Subtask II)

Purpose: The purpose of this LDRD project (funded in FY 1990 and FY 1991) has been to design, construct, and test the performance of a device for in situ x-ray reflectivity studies of electrode/electrolyte interfaces in a transmission-type geometry. This device represents a state-of-the-art development in the methodology available for probing the microstructure of immersed interfaces where the interface is maintained under precise electrochemical control (with current

flow, if desired) while the x-ray reflectivity measurement is being performed. The successful completion of this project in FY 1991 enhances the Laboratory's capabilities for conducting advanced synchrotron experimentation on electrochemical systems and represents a unique tool that has both technical and commercial value for a variety of applications.

Approach: The interfacial region between a bulk solid and a liquid in contact with it has unique characteristics, quite different from those of either bulk phase. Adsorbed layers and surface films at such interfaces can range in thickness from less than a monolayer to many hundreds of monolayers. In recent years, there has been extensive research done on the development of methods to interrogate such interfaces. The most promising methods for determining structural properties are ones based on the use of x-rays because of the ideal match of x-ray wavelengths to the dimensional information needed and the ability of x-rays to penetrate to interfaces that are buried within condensed phases.

Interfacial chemistry and physics are particularly important to electrochemical and corrosion science. A variety of spectroscopic, electrochemical, and theoretical techniques has been developed for studies of the molecular, kinetic, and electronic properties of corroding interfaces. To complete the interpretation of the information derived using these techniques, there is a strong need for complementary data on elemental density profiles and ordering behavior (1) within and between the interfacial corrosion layers that form on metal surfaces and (2) in the double-layer region adjacent to the metal surface. In particular, it is important to understand the role played by dissolved solution species, pH, and the solvent (water) molecules during the formation of passive films and the restructuring of the double layer.

After examining the options for studying immersed interfaces under conditions of uniform electrochemical potential and reasonable x-ray transmission, we chose to design and construct an x-ray/ electrochemical cell having the narrow, elongated geometry illustrated in Fig. 1.

Fig. 1 - Cross-section view of the x-ray/electrochemical cell developed as part of the LDRD program.

Because of the cell's narrow width, the absorption of x-rays by the electrolyte is minimized relative to the intensity of the incident x-ray beam, thus maximizing the relative intensity of the reflected x-rays. Also, since there is no constraint on the depth of the liquid phase above the working surface being studied, the counter electrode can be positioned in a manner conducive to having a uniform electric field across the working surface. Positioning of the reference electrode, the changing or continuous circulation of electrolyte, and movement of the entire cell assembly to effect changes of incidence geometry between the x-ray beam and the electrode/electrolyte interface are also facilitated by this design.

Technical Progress and Results: Following completion of its construction (in FY 1990) several successful experimental campaigns, using the x-ray/electrochemical cell, were carried out at the National Synchrotron Light Source (NSLS) in FY 1990 and FY 1991. The angular dependence of the reflectivity from a bi-layered interface structure was measured under dry nitrogen and in aqueous electrolyte to test the general performance and interface resolution capability of the cell. The bi-layered film structure, consisting of nickel (1000 Å) and chromium (50 Å) on polished borosilicate glass, showed the expected bimodal modulation in reflectivity in both the presence and absence of electrolyte. The decrease in reflected x-ray intensity, when electrolyte was added to the cell, was (as expected) a strong function of x-ray energy. (At 8.4 keV, this decrease was less than a factor of twenty with the narrow geometry cell.)

Combined in situ x-ray and electrochemical measurements were made on thin films of copper and silver supported on polished single-crystal substrates to study the changes in film thickness and roughness accompanying sequential oxidation-reduction-oxidation cycles. An example of the type of result obtained in these studies, taken from an investigation of a thin film of copper (250 Å) on silicon (100), is shown in Fig. 2. The reflectivity is plotted as a function of the scattering vector [$Q = (4\pi/\lambda)\sin\phi$], and the data are evaluated using the Fresnel Laws of classical optics. The recovery of the copper film interference pattern after reduction evidences an abrupt change in scattering density at the copper/electrolyte interface, which is consistent with the anticipated densification of copper that should accompany complete restoration of the metallic surface. These results represent first-of-a-kind x-ray reflectivity measurements of immersed, electrochemically controlled metal films.

An x-ray reflectivity study was also made on a Pt(111) electrode in cesium fluoride solution after oxidation at various anodic potentials and reduction

Fig. 2 - Reflectivity of Cu-on-Si electrode at various potentials on borate buffer solution (pH 8.4). Solid lines represent calculated curves, while symbols correspond to experimental data.

of the oxide film. It was found that the initially flat surface completely recovered its original morphology after a reduction of the oxide film formed at potentials up to 500 mV (vs. Ag/AgCl, 3 M KCl) but irreversibly roughened after oxidation at potentials exceeding 500 mV. Charge calculation from voltammetric measurements indicated that the critical oxygen coverage necessary to induce surface disorder is approximately one monolayer.

Preliminary results were obtained from an investigation aimed at determining the width and concentration distribution of the electrochemical double layer formed at the Pt(111) interface in cesium fluoride electrolyte. The intensity of reflected x-rays at a fixed momentum transfer was found to depend on the applied potential. This observation has been attributed to alteration of the concentration profile of cesium ions in the interfacial region as the electrode is polarized negative from the potential of zero charge.

Specific Accomplishments: The novel, narrow-pass, transmission geometry x-ray/electrochemical cell developed under this LDRD has proven to be well suited for controlled potential studies of immersed interfaces. Many of the expected advantages of this approach to x-ray reflectivity studies have been realized in the work summarized above. We will continue to exploit this unique research tool in our basic materials science program and have submitted a patent application covering the inventive design features. A series of publications and presentations has resulted from this work. Some of these are listed below.

Cell Design for In Situ X-ray Scattering Study of Electrodes in Transmission Geometry,
Z. Nagy, H. You, R. M. Yonco, C. A. Melendres, W. Yun, and V. A. Maroni,
Electrochim. Acta **36**, 209 (1991).

Specular X-ray Reflection for the "In Situ" Study of Electrode Surfaces,
C. A. Melendres, H. You, V. A. Maroni, Z. Nagy, and W. Yun,
J. Electroanal. Chem. Interfacial Electrochem. **297**, 549 (1991).

X-ray Reflectivity Study of the Copper/Water Interface in a Transmission Geometry under In Situ Electrochemical Control,
H. You, C. A. Melendres, Z. Nagy, V. A. Maroni, W. Yun, and R. M. Yonco,
to be published.

* This project was one of four subtasks of a FY 1990 LDRD project funded at \$785.6K

(3.06) ADVANCED TECHNIQUES FOR SYNCHROTRON RADIATION RESEARCH.

Associate Laboratory Director Area: Physical Research

Principal Investigators: M. Bedzyk, K. Huang, P.A.Montano, Materials Science

Funding History:	FY 1989	\$
	FY 1990	\$*
	FY 1991	\$211.2K

Purpose: We intend to develop a strong scientific program on surface scattering from interfaces using X-Ray Standing Waves (XSW) and glancing incidence x-ray fluorescence.

Approach: We hired two new scientists in order to develop this new scientific program. Dr. K. Huang and Prof. M. Bedzyk (50% ANL/50% Northwestern University) were hired as staff scientists. K. Huang has considerable experience in x-ray scattering from surfaces and is in charge of our x-ray scattering beam line at NSLS (X-6B). Dr. Bedzyk is a well-known authority in the use of synchrotron radiation techniques, specifically in the application of XSW to study of surfaces. Both scientists have active collaboration with other members of the synchrotron radiation group.

Technical Progress and Results: We have already performed a series of successful studies of interfaces using beam line X-6B. We measured anomalous x-ray reflectivity from a Ni/Fe alloy (0.8 Ni/0.2 Fe) which was sputtered on SiO₂ glass substrate. The x-ray energies were chosen to be 7.0 Kev (below the Fe edge), 7.5 Kev (above the Fe edge but below the Ni edge) and 9.0 Kev (above the Ni edge). The anomalous reflectivity measurements allow the solution of the phase problem and permit accurate determination of the composition profile and roughness of the thin film. We are currently analyzing the experimental data.

Glancing Angle Surface-sensitive X-ray fluorescence is a powerful nondestructive technique for surface characterization. In this study we have measured the angular dependence of X-ray fluorescence from both Ni and W atoms in the Ni/W multilayers as well as the reflectivity at grazing incidence angle. The X-ray energy was set to 11.0 Kev which is high enough to excite both Ni and W fluorescence. The double-layer-thickness of the samples are 22, 75, 120 and 300 Å and the Ni and W have the same thicknesses within each double layer. These samples show very strong elastic anomalies that we think are related to the interface structure. We have finished with the measurements and are starting with the analysis of the data. This work was carried out in collaboration with Prof. I.K.Schuller's group at the University of California San Diego.

We have also studied the interface structure of epitaxially grown Si/CoSi₂/Si(001) using x-ray reflectivity and near glancing angle fluorescence. CoSi₂ can be grown epitaxially on the low index surfaces of silicon (small lattice mismatch of 1.2%). This system is a promising

candidate for applications in electronic devices because of the high efficiency of the electron transmission across the interface. We have completed systematic measurements of the x-reflectivity and near glancing angle fluorescence in order to investigate the structural properties of this system. A detail analysis of the data is in progress.

We have completed construction of all the components for the XSW experiments . We are in the process of installing the equipment at our beam line at NSLS. We expect that in the coming months our experimental capabilities will be fully operational. It is our objective to make this scientific activity one of the leading research programs in the synchrotron radiation field for studies of metal/semiconductor and liquid solid interfaces.

Specific Accomplishments: We completed the design of the experimental set up for X-ray Standing Waves measurements. We carried the first systematic use of anomalous x-ray reflectivity to study the structure of Ni/Fe thin films. We completed experiments on superlattices of Ni/W using glancing x-ray fluorescence. We completed a structural study using the same techniques of the technologically important system Si/CoSi₂/Si(001).

* This project was one of four subtasks of a FY 1990 LDRD project funded at \$785.6K.

(3.07) ANOMALOUS X-RAY SCATTERING

Associate Laboratory Director Area: Physical Research

Principal Investigators: Marie-Louise Saboungi, David L. Price, Materials Science; John E. Enderby, Argonne Fellow 1989-91; Milton Blander, Materials and Components Technology.

Funding History:	FY 1989	\$0
	FY 1990	\$*
	FY 1991	\$80.2K

Purpose: Anomalous x-ray scattering can, in principle, provide detailed information about the structure of a disordered condensed system at the partial structure factor level. The successful implementation of this technique would greatly expand our ability to determine the bulk and surface structure of a large number of scientifically important materials, including liquids, glasses, amorphous thin films, and biological materials.

Many attempts to apply this technique to disordered materials have been inconclusive because of low signal-to-noise ratios and systematic errors inherent in the methods used. We propose to develop a new method which will significantly enhance the statistical and systematic accuracy of the technique and the quality of the scientific results obtained. The ultimate goal is the provision of a dedicated instrument at the APS based on this method.

Approach: The present project involves the design and development activities necessary to arrive at this goal, including the fabrication and testing of components and proof-of-principle experiments. The activities include development of optimized containment cells, test measurements of first-order difference measurements on a variety of materials at existing sources, testing key elements of the x-ray optics, and computer simulations of different experimental configurations.

Technical Progress and Results: The initial measurements have given valuable experience relating to sample cell and window design, statistics of the first-order difference method, different methods of discriminating against inelastic scattering processes (resonant Raman and Compton scattering), and procedures for determining anomalous scattering factors, a key factor in deriving accurate structural information from the data. These measurements have involved the principal investigators and a post-doctoral appointee, P. Jemian, hired from Northwestern University in January 1991. In addition, important computer simulations of the inverse problem, calculating experimental diffraction patterns from a given structure and experimental configuration, have been carried out by J. E. Enderby with a summer student supported by the Division of Educational Programs.

The plans for the coming year involve continuation of the NSLS measurements on bulk liquids, including aqueous solutions and molten salts. New sample cells will be fabricated for both types

of measurements based on our experience to date. We will make a detailed comparison of different methods for inelastic discrimination (crystal analyzer, energy-dispersive detector, etc.) and for determination of anomalous scattering factors (Bragg reflection from crystals, surface reflectivity, transmission measurements). In addition, two new activities will be started, one on anomalous scattering from glasses, in collaboration with T. Egami, Pennsylvania, and one on liquid metal surfaces with P. Pershan, Harvard. Both scientists attended our symposium of "Frontiers of Liquid and Amorphous States" and expressed a strong interest in collaboration.

Specific Accomplishments: Starting in January 1991, significant progress towards these goals has been achieved. Three exploratory experiments at NSLS have been carried out, one on aqueous solutions at X-14 (in collaboration with P. Zschach, ORNL), and two on molten salts at X-22 (in collaboration with S. K. Sinha, Exxon, and M. Sanyal, BNL).

* This project was one of four subtasks of a FY 1990 LDRD project funded at \$785.6K.

(3.08) TIME DOMAIN SYNCHROTRON RESEARCH

Associate Laboratory Director Area: Physical Research

Principal Investigator: J. R. Norris, L. Chen, Chemistry

Funding History:	FY 1989	\$0K
	FY 1990	\$566.7K
	FY 1991	\$295.5K

Purpose: We intend to establish the feasibility of determining molecular structures as a function of time using x-ray radiation provided by synchrotrons, particularly the ANL APS. In particular, we wish to measure structural changes that occur in certain short-lived, photo-induced excited states using extended x-ray absorption fine structure spectroscopy (EXAFS).

Approach: A major unresolved question in several fields is whether structural changes in photoexcited molecules can be mapped as a function of time using x-rays. Since intense pulsed X-rays from synchrotrons may allow the direct measurement of excited-state molecular structures and dynamics, we have initiated work to determine molecular structures with a time resolution of approximately 50 ps. During the past year, our research activities on time-domain X-ray spectroscopy have been focused on X-ray shutter development and steady-state EXAFS of photoexcited model compounds. Eventually, we intend to explore picosecond time-domain structure determination with X-ray absorption spectroscopies (i.e., EXAFS and XANES) and picosecond time-resolved X-ray diffraction (e.g., single crystal, powder, or membrane).

Our first goal is to establish the feasibility of time-domain X-ray spectroscopy. In this phase of our work we have established two major problems.

1) *Regulation of the repetition rate of X-ray bunches:* Third generation synchrotrons provide five to six million pulses per second. However, the optimum time-domain experiment typically requires 100 X-ray pulses per second with the further restraint that these X-ray pulses must be slaved to a visible-light pulse sequence provided by a laser. Thus, one chief obstacle of this investigation entails the development of a suitable X-ray shutter slaved to a pulsed laser.

2. *Understand the experimental requirements for excited state EXAFS:* The main complication in these experiments is to reduce the mismatch of the optical experimental conditions for the EXAFS and the photoexcitation. A thick, concentrated sample is highly desirable for EXAFS which makes homogeneous excitation by visible light quite difficult. The means for producing high yields of excited states in concentrated solid solution of the samples while maintaining approximately constant temperature must be established.

Technical Progress and Results (1): We now discuss a solution to the first problem. The structural changes are to be mapped by setting different time delays between the laser "pump" and the synchrotron "probe", a standard technique of time-domain spectroscopy. The time resolution of this "pump-probe" experiment is independent of the detection device, depending only on the pulse width of the radiation source, about 50 ps for APS. Typically, at each time

delay, repetitive measurements are averaged over many pulses to provide a good signal-to-noise ratio. An ideal system for study undergoes reversible changes with relaxation times less than the interpulse interval of the X-ray radiation. The photosynthetic bacterial reaction center provides an excellent example. Although the first laser pulse to strike a reaction center induces an electron transfer in 2.8 ps, relaxation back to the ground state requires approximately 15 ns for the main reaction of the singlet manifold and about 100 μ s for the accompanying secondary photochemistry of the triplet manifold. In this case, the X-ray bunches must be at least 100 μ sec apart to permit the system to relax completely to the ground state. Because no synchrotron facility provides the means to control the time interval between single radiation bunches, very few reactions can directly utilize the pulsed feature of synchrotron radiation to monitor the structural changes. Obviously, controlling the repetition rate of the X-ray pulses from synchrotrons is the key to successfully monitoring structural changes of excited molecules.

Precision pulse control has not been accomplished because of extreme difficulties in selecting a single X-ray bunch from the continuous pulse train of a synchrotron. In last year's Survey of Research in the Chemistry Division, we presented an X-ray "shutter" designed for the third generation APS of ANL. In the 20-bunch mode of APS, an X-ray pulse will occur every 177 ns, which would require each edge of a conventional two-blade "shutter" to travel at least 0.25 mm in $\sim$ 177 ns in order to select an X-ray pulse with beam diameter of 0.5 mm. The blades would have to move approximately four-times faster than the speed of sound. This approach appears mechanically unrealistic. Instead, we advocated a rotating mirror with its rotational period slaved to a multiple of the synchrotron interpulse period. The synchrotron X-ray bunches will be reflected a distance of 2 m to a 0.5-mm slit in front of the sample. The time that the reflected synchrotron bunch spends traveling across the slit is given by $d/4\pi r f$, where d is the slit width, r is the radius from the center of the mirror to the slit, and f is the rotation frequency of the mirror. A mirror rotating at a low (7,500) rpm (125 Hz) is sufficient to select a single synchrotron pulse. The effective speed of the reflected pulse at the slit is eight times the speed of sound even though the rotating mirror travels significantly slower than sound. In principle, this technique solves the speed requirement for the "shutter".

Specific Accomplishments: During the past year, we have proven the feasibility of our X-ray shutter. Mr. Dvorscak of the Office of Intellectual Property Counsel of DOE is in the final stages of applying for a patent on our synchrotron shutter. An appropriate rotating mirror is commercially available for infrared-light reflection. This commercial product has all the mechanical requirements demanded by our mirror-shutter design. In particular, the phase and frequency stability of the commercial rotor has been demonstrated by the manufacturer to be satisfactory for our application. Some details in converting this device to an X-ray shutter have been pursued and discussed with the manufacturer. The final decision to employ this device awaits the appropriate funding and the availability of a future X-ray beam-line facility on the APS at ANL. In addition we have a manuscript accepted for publication explaining our shutter concept ("A Shutter Design for Time Domain Studies Using Synchrotron Radiation at the Advanced Photon Source", J. R. Norris, M. K. Bowman, L. Chen, J. Tang, M. C. Thurnauer, G. S. Knapp and P. A. Montano, Proc. of 4th International Conference on Synchrotron Radiation Instrumentation (SRI), Chester, UK, July 15-19, 1991.).

Technical Progress and Results (2): We now discuss the second problem listed above. Our first attempts at steady-state EXAFS have involved the photoexcited triplet of metalloporphyrins in solid state solutions. The selection of ZnTPP (zinc tetraphenylporphyrin) for the first experiment is based on its relatively long triplet-state lifetime (e.g., 15-20 ms at 77K) and high quantum yield for formation. Our MMX calculations (quantum chemistry geometry optimization program reported in the last Survey) and a magnetic resonance investigation (J. van der Waals, Leiden) suggest that zinc-to-ligand bond-length changes of 0.01 Å to 0.02 Å occur in ZnTPP when going from the ground state to the triplet state. Simulated EXAFS spectra with the predicted bond-length changes show a detectable difference between the ground state and the excited state assuming a fifty percent, steady-state triplet yield.

Our previous EXAFS experiments on photo-illuminated ZnTPP at the National Synchrotron Light Source (in collaboration with P. Montano) failed. Although incomplete photoexcitation, unsatisfactory EXAFS signal-to-noise ratio, distortion of the data by conventional Fourier analysis and/or insufficient bond-length changes are possible sources of this failure, low concentration of the triplet state is by far the most important stumbling block preventing these EXAFS studies. Therefore, we have explored in detail the triplet yield of Zn tetraphenylporphyrin as a function of light intensity, sample thickness and concentration. With the previous EXAFS experimental setup, only approximately one percent triplet yield was created, preventing any possibility of triplet-state observation by EXAFS. For generating a high steady-state triplet yield, a thin ZnTPP sample is required. We have recently observed triplet yields of 40% with light fluxes lower than that used in the previous EXAFS experiments at NSLS. A calculation shown in Figure 1 models the triplet yield as a function of sample concentration and thickness. With the higher light power to be used in future experiments, a triplet yield of 60% or higher should be created.

Although we now can prepare high-triplet yields in concentrated, thin, solid solutions, a major problem still remains. Because EXAFS is a relatively insensitive technique, a much thicker sample is required for EXAFS than for visible light excitation of the sample. As a result, in such a concentrated, thick, solid solution, visible-light only enters the upper layer of molecules while the X-rays examine the entire sample. Thus, in these thick samples the X-rays examine primarily the ground state, not the excited state accounting for our previous failure at NSLS. In order to resolve the dilemma presented by the requirement of a thick sample for EXAFS versus a thin sample for optical excitation, we have designed a new sample geometry that aligns a concentrated but thin film of the sample nearly parallel to the X-ray propagation direction while the light path is perpendicular to X-ray propagation direction. This configuration results in a large sample for X-rays and a thin sample for the excitation light. Based on this sample configuration, a calculation for the X-ray fluorescence signal-to-noise ratio as a function of the angle between the thin sample plane and X-ray propagating direction shown in Figure 2. Combined with the results in Figure 1, we have established the requirements for steady-state time domain EXAFS experiments on metastable triplet states.

Figure 1

Figure 2

(3.09) CATALYSIS AND COAL

Associate Laboratory Director Area: Physical Research

Principal Investigators: K. Carrado, K. Chatterjee, L. Soderholm, L. M. Stock, J. Sullivan, P. Thiyagarajan, and R. Winans, Chemistry

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$102.6K

Purpose: The goals of the work have been to develop expertise in the area of X-ray spectroscopy data collection, analysis, and interpretation, and to begin several programs that use these methods in the Chemistry Division.

Approach: Preliminary investigations of XANES, EXAFS, SAXS, ASAXS techniques for the study of chemical problems in coals, catalysts, and heavy elements were undertaken.

Specific Accomplishments: Coal Sulfur (L. M. Stock, K. Chatterjee) Preliminary experiments in several laboratories suggested that progress could be made in the definition of the organic sulfur-containing compounds in solid coals by X-ray work. A collection of dimineralized, depyritized and selectively desulfurized coals were prepared and submitted to several different synchrotron radiation science research teams. The collaborative effort between the ANL scientists, who had very special capabilities to produce chemically unique coal samples, and the group led by Martin Gorbaty of Exxon Research at NSLS provided remarkable results that, for the first time, defined the amounts of sulfidic sulfur compounds and aromatic sulfur compounds in a key Argonne Premium coal sample.

This contribution has demonstrated to the coal science community that X-Ray absorption spectroscopy can be very profitably coupled with selective chemical strategies to aid in the speciation of the organic sulfur compounds in coal, a vital problem for future practical coal desulfurization.

Layer Clays (K. A. Carrado and R. E. Winans) Elucidation of the molecular structure of active sites in heterogeneous catalysts is important in the determination of catalytic activity. X-ray absorption fine structure of clays containing copper(II) and iron(III) ions were acquired. Preparations of clays containing organometallic species were compared with analogous ion-exchanged natural clays. Other pure compounds including water-soluble copper(II) compounds and copper metalloporphyrins were studied at NSLS X23A2. Because the amount of copper present in the exchanged clays was quite small (<20% of the total absorption), fluorescence detection was necessary.

Preliminary analyses of the raw data have yielded promising information. Routine normalization and background subtraction of the raw data was done by using an analysis package provided by scientists at the University of Washington. These programs are now available on the Chemistry Division's VAX. Inspection shows, for example, that the particular Cu(II) metalloporphyrins do not demetallate when intercalated into the clays. In addition, the signatures of a Cu(II)-exchanged clay before and after exchange with a porphyrin are clearly different. These observations are supported by X-ray diffraction and UV-visible absorption studies which also imply that a free base porphyrin will metallate on the surface of a Cu(II)-exchanged clay.

This synthetic work is essentially on target. We have already demonstrated that catalytically active metalloporphyrins can be incorporated into synthetic clays via the silicate synthesis gel method. The fate of the metal ions is extremely important, and it is expected that future synchrotron work at NSLS will be indispensable in determining the coordination environment of the metal ions.

EXAFS on Brannerite (L. Soderholm) Brannerite is a naturally occurring mineral with the formula UTi_2O_6 . It is one of the common forms of U that is commercially mined and refined. The mineral itself is metamict (amorphous to X-ray diffraction), however heating to about 1000°C transforms it into a crystalline material, on which single crystal x-ray diffraction has been used to discern the crystal structure. The methods used to refine and separate U from the natural ore are based in part on this crystal structure (i.e. through the speciation of U in the ore). We initially chose to examine the natural ore of brannerite, in its metamict form, for use as a standard for EXAFS analysis of some U-containing glasses. For completeness, we also examined a heat-treated crystalline form. The experiments were done at X23A2 at NSLS. It was surprising to see that the metamict and heat treated forms have very different coordination about the U. While the heat treated form is 8-coordinate about U, there is no uranyl group ($O=U=O$) present in the structure.

EXAFS on Uranium Glasses (L. Soderholm) Interest in this project stems from the use of glasses as a solid storage media for radioactive waste. Of particular importance and current interest is the effect of an aqueous leaching environment on the radioactive isotopes' migration and speciation within the glass environment. SEM measurements on a series of glasses that had known leaching histories provide evidence that there are changes in the depth profiles of uranium concentrations with prolonged leaching, however the data were not sufficient to determine whether changes in speciation had occurred. Glancing incident EXAFS could, in principle, provide a powerful means of analysis. Since glancing incident EXAFS is an important tool for understanding a variety of problems of chemical interest involving surfaces, including electrochemical and catalytic processes, this project provided an opportunity to gain experience with this experimental procedure. Experiments were performed at NSLS on beamlines X11 and X23A2. Initial analyses showed significant changes between some samples, indicating that glancing incidence EXAFS can be applied successfully.

EXAFS on Uranium-Carbonate Solutions (L. Soderholm, J. Sullivan) A detailed knowledge of speciation of solutions containing dioxatine(VI)-ions is essential if adequate modeling of radioactive wastes is to become a reality. This is a particularly urgent problem for Pu(VI) solutions. We have begun to study this problem by obtaining EXAFS on a matrix of U-perchlorate solutions in which the pH and U-concentration have been systematically varied. Predictions from current modelling of U-solutions are used as a guide for data interpretation. Of most significant concern is the presence of U-dimers, trimers or polymers in solution. To obtain meaningful results from the EXAFS experiments, it is necessary to have data that are interpretable at distances of about 5 Å. This should be possible with U since it is such a large ion. Initial data obtained on X19A, show evidence of a peak in the neighbourhood of 4-4.5Å, but the statistics were not sufficient to unequivocally determine the number of ions associated with this peak and further work will be necessary.

Ruthenium XANES (L. Soderholm) To begin work on this project, we chose to examine Ru compounds: (1) Ru has available a wide range of formal oxidation states and (2) Mossbauer measurements have been performed on a variety of Ru compounds. The Mossbauer isomer shift provides an independent measure of the electron density at the nucleus, and therefore a valence that can be compared with XANES data. With these compounds as a starting point, we have obtained two sets of data; one series of L-edge spectra from X19A, and a series of K-edge spectra from X23A2. Preliminary data analyses have been carried out, but more results are needed before any well determined correlations can be ascertained.

Anomalous Scattering (P. Thiyagarajan) The aim of this project is to elucidate the solution structures encountered in the transuranic extraction (TRUEX) process used for the clean up of both high level and low level nuclear wastes by using SAXS (Small Angle X-ray Scattering) and ASAXS (Anomalous Small Angle X-ray Scattering) techniques. The key ingredient in the TRUEX process is the extractant CMPO [octyl(phenyl) -N,N-diisobutylcarbamoylmethylphosphine oxide] which forms aggregate with metal ions especially at low extractant/metal ratios. The nature of aggregation depends on a variety of factors including the concentration of the extractant, extractant/metal ratio, nature of the organic solvent, the presence of other modifiers, etc. Furthermore, a second organic phase is formed upon high metal loading conditions in long chain hydrocarbon solvents.

SANS (Small Angle Neutron Scattering) techniques were applied to investigate the morphology of the particles formed under a variety of conditions. However, information relating to the metal-to-metal distances and their distribution in the particle could not be derived from SANS. It is likely that the distribution of metal ions is quite different in the aggregates formed at high and low acid conditions as well as in the second organic phase and it will be of interest to learn about the solution structures and the disposition of metal ions in those species. The distance between the metal ions in the complexes will be larger than 5 Å, and hence EXAFS techniques cannot be applied for their determination. One of the ways to obtain the distance between the metal ions and their disposition in the particles is to use the ASAXS by carrying out studies on the Lanthanide-CMPO complexes. ASAXS is an extremely weak effect, but it yields information on the distance between the metal ions and their distribution in the whole particle which cannot

be obtained by any other technique. This technique demands very high flux sources which can be tunable and hence is feasible only at a wiggler or undulator source at the synchrotron facilities. Hence SAXS and ASAXS experiments were done on CMPO- lanthanide systems in organic solvents under a variety of conditions at SSRL. The data are being analysed and we are optimistic about obtaining the information on the solution structures in terms of metal-to-metal distances in various species. Additional beamtime will be assigned by SSRL for experiments in FY1992.

Publications.

"The Sulfidic and Thiophenic Sulfur Content of An Illinois No. 6 Coal through XANES."
K. Chatterjee, L. M. Stock, M. L. Gorbaty, G. N. George, and S. R. Kileran, Energy and Fuels, 5, 771-773 (1991).

(3.10) ATOMIC PHYSICS USING SYNCHROTRON RADIATION

Associate Laboratory Director Area: Physical Research

Principal Investigators: Yoshiro Azuma, Nora Berrah Mansour, Physics

Funding History:	FY 1989	\$0K
	FY 1990	\$156.3K
	FY 1991	\$187.5K

Purpose: The Atomic Physics group in the Physics Division is working towards an active research program utilizing synchrotron radiation, with a view towards measurements at the Argonne Advanced Photon Source (APS) when it comes on line in 1995-96.

Approach: Our principal approach has been to pursue research at an existing source. The research of this year has covered five main areas of measurements, most of which took place at the National Synchrotron Light Source (NSLS) at Brookhaven. Four extended in-beam runs were made by us at the NSLS: October 1990 - 2 weeks, January/February 1991 - 2 weeks, July/-August 1991 - 3 weeks, September 1991 - 10 days.

Technical Progress and Results:

1) Double photo-ionization of helium

We have measured the ratio of double-to-single photoionization of helium far above threshold at a photon energy of 2.8 keV. This is the first measurement to test the expected asymptotic value of the ratio at high energy. This is a collaboration with the Oak Ridge/University of Tennessee group of Levin and Sellin, with experiments taking place at the NSLS, Brookhaven. Our results disagreed with the most accurate available many-body calculations, but showed some agreement with previous approximate theories. The experiment and results are described in a recent Physical Review Letter.

New more detailed calculations are now being made by several groups. Many-body calculations of Ishihara *et al.* show agreement with our measurement, but disagree with low-energy results. We have begun measurements at both higher and lower photon energies to test the approach to the asymptotic limit.

2) Photoion-photoion coincidence (PIPICO) studies

Following a series of molecular X-ray emission studies, we have initiated the PIPICO method to study the dissociation of CF_3Cl and H_2S at photon energies near the K-threshold regions. An initial study of SO_2 was also performed.

The apparatus is a time-of-flight ion analyzer, with a channelplate and resistive anode detector. The single detector provides both start and stop inputs to a time-to-amplitude converter. An example spectrum is shown below.

Figure: H_2S PIPICO spectrum at 2472.1 eV

3) Photoion-Auger electron coincidence studies

The charge state distributions of photoions near threshold for inner-shell electrons show great variations across the resonances. Because of the many energy pathways allowed during such photo-processes, we have found that it is essential to make coincidence measurements to allow meaningful interpretation of these distributions. The work has been done in collaboration with the Oak Ridge/Tennessee group, Levin and Sellin and with Lindle of NIST.

Measurements have been made over the K-shell threshold in argon with coincidence measurements between various auger electrons and the argon ion charge states. The ions are detected in a time-of-flight detector in coincidence with electrons detected in energy-resolved by a cylindrical mirror analyzer. Work continues with the Oak Ridge group on the design, building and testing of a new electron analyzer to provide energy and angle resolution.

4) Stored multi-charged ions

Experiments have been completed using the white-light X-26C NSLS beam-line to study photoionization of doubly-charged, trapped argon ions. This collaboration was led by the Texas A&M group, Kravis and Church, with support from Johnson at BNL and the Argonne group.

We studied K-shell photoionization of Ar^{2+} by synchrotron light with energy between 3 and 15 keV. This feasibility experiment showed the difficulty of measuring such photoionization cross-sections, even in such a well-controlled trap geometry. The results are described in a recent Physical Review Letter.

5) Inner-shell double photo-excitation

Analysis of data obtained in an April 1990 run at the Stanford Synchrotron Radiation Lab SPEAR storage ring was completed during this year. The search for single-photon absorption, two-electron excitations in krypton (1s_{nl} edges) was partially successful. This study was a collaboration of Crasemann at the University of Oregon, Kodre at the University of Ljubljana and Azuma of the Argonne group. The goal is the observation of relativistic and QED corrections to the fine structure of these inner-shell electrons.

Further measurements are planned for the NSLS X-24A beamline.

Specific Accomplishments: In addition to this experimental work, we have completed and published the Proceedings of the previous year's workshop on *Atomic Physics at the Advanced Photon Source*, published as ANL/APS/TM-8. An atomic physics CAT proposal for the BESSRC was prepared and submitted in early spring 1991. Together with Ivan Sellin of the University of Tennessee, Knoxville, we have submitted a proposal to the National Science Foundation for support for a meeting on Atomic Physics using hard x-ray synchrotron radiation, to be held in Hawaii in November 1992, as part of the NSF Japanese/American programs. Yoshiro Azuma is also part of the organizing committee for a workshop in Japan (March 1992) on atomic physics using synchrotron radiation. Professor Awaya of Riken, and leader of the atomic physics efforts using SPring8 is the primary organizer.

Follow-up work on the conceptual design report for the BESSRC has continued. We have also worked on developing a proposal for future synchrotron-based atomic physics work, to be submitted to the DOE Division of Chemical Sciences, Fundamental Interactions Branch.

Publications:

"Measurement of the ratio of double-to-single photoionization of helium at 2.8 keV using synchrotron radiation," J.C. Levin, D.W. Lindle, N. Keller, R.D. Miller, Y. Azuma, N. Berrah-Mansour, H.G. Berry, and I.A. Sellin, *Physical Review Letters* **67**, 968 (1991)

"Sequential photoionization of ions using synchrotron radiation and a Penning ion trap," S.D. Kravis, D.A. Church, B.M. Johnson, Y. Azuma, J. Levin, I.A. Sellin, M. Meron, K.W. Jones, M. Druetta, N. Mansour, H.G. Berry and R.T. Short, *Nucl. Instr. Meths* **B56/57**, 396 (1991)

"Electron transfer collision studies on stored ions produced by synchrotron radiation," D.A. Church, S.D. Kravis, B.M. Johnson, Y. Azuma, J. Levin, I.A. Sellin, M. Meron, K.W. Jones, M. Druetta, N. Mansour, H.G. Berry and R.T. Short, *Nucl. Instr. Meths* **B56/57**, 417 (1991)

"Inner-Shell Photoionization of Stored Positive Ions Using Synchrotron Radiation," S.D. Kravis, D.A. Church, B.M. Johnson, M. Meron, K.W. Jones, J. Levin, I.A. Sellin, Y. Azuma, N. Berrah-Mansour, H.G. Berry and M. Druetta, *Phys. Rev. Letters*, **66**, 2956-59 (1991)

(3.11) X-RAY TECHNIQUES FOR BIOMEDICAL RESEARCH

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigator: Edwin Westbrook, Biological and BIM Division

Funding History:	FY 1989	\$178.2K
	FY 1990	\$335.6K
	FY 1991	\$796.8K

Purpose: The purpose of this program is to explore concepts in X-ray optics that will be needed for two-dimensional medical imaging with synchrotron radiation sources and to establish a Laue diffraction station on the X26C beamline at the National Synchrotron Light Source (NSLS).

Approach: The approach taken in the program was to concentrate the activities on the X8C and X26C beamlines at NSLS in order to make them available for research projects. This would enable the researchers to do preliminary optics studies that would be useful in the design of X-ray optics for the APS beamlines and to perform Laue diffraction studies that would provide some experience in synchrotron experimentation that would be applicable to the APS.

Technical Progress and Results: In FY1990, funds were spent on developing and testing of prototype beamline components and detector systems. In FY1991, effort was devoted to the establishment of requirements for medical imaging equipment for APS and the development of prototype equipment for NSLS.

On the NSLS X8C facility, several data sets were run to demonstrate that the beamline is operational. Detectors were installed and characterized. A complete test of the properties of the detectors was conducted. They were calibrated for spatial resolution, dynamic range, speed, etc. Designs have been completed for the X8C hutch equipment and control hardware, and the goniostat and monochromator controls software.

The NSLS X26C beamline was made operational for Laue diffraction studies. Laue diffraction images have been taken and two crystal structures have been solved. The beamline is still undergoing further shakedown procedures before it is to be considered fully operational.

Specific Accomplishments: On the X8C beamline, data was collected on PyrX, an enzyme of pyrimidine metabolism, and on HIV protease. The latter was conducted for a crystallographic group at the Upjohn Company. On the X26C beamline, crystals of the metastable catalytic intermediate p-guanidinobenzoyl-trypsin (GBT) were subjected to X-ray diffraction analysis using white beam ("Laue") synchrotron radiation. Diffraction data were obtained over the range 5.0 to 1.8 Å using the Laue method. Orthorhombic crystals belonging to space group $P2_12_12_1$ had with unit cell dimensions $a = 63.74$, $b = 63.54$, $c = 68.93$ Å. White beam, or "Laue", diffraction data were collected from a single crystal mounted in a flow cell using Kodak DEF film; typical exposure times were 1 second. Data were collected with the crystal equilibrated against pH 5.5

buffer. At this pH, the GBT is quite stable, with a lifetime of several days. The pH of the buffer flowing through the flow cell was raised to 8.9, and additional data sets were collected after 3 and 80 minutes. In preliminary kinetic experiments, the lifetime of GBT was measured to be ~1 hr. under equivalent conditions.

In preliminary crystallographic studies, it was shown that such a pH jump had no effect on the structure of benzamidine-inhibited trypsin, with the exception of various polar side chains located on the surface of the protein molecule. Most notable was the Ser195 side chain in the pH 8.9 structure, which is swiveled away from His57, resulting in the loss of the H-bond between O and NE2 of the histidine.

While the models have not been refined to fit the present data, difference Fourier maps between the time zero (pH 5.5) and the first pH 8.9 (i.e. 3 min. timepoint) data sets clearly show movement of atoms near the active site of the enzyme. The most striking is the ~2 Å shift of a water molecule previously identified by this group as important in the stability of GBT. Furthermore, densities in the difference map suggest that backbone atoms may also be moving in and around the active site, in direct contrast to the results obtained in the previous study of the effect of such a pH jump on benzamidine-inhibited trypsin.

(3.12) **PROCESS DEVELOPMENT FOR RECOVERY OF
OXIDE-REDUCTION SALTS**

Associate Laboratory Director Area: Engineering Research

Principal Investigators: J. E. Battles, R. D. Pierce, Chemical Technology

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$247.2K

Purpose: An initial step in proposed pyrochemical processes for recycling LWR actinides to an IFR employ calcium to reduce the oxide fuel. The CaO reduction product dissolves in a CaCl_2 -20 mol % CaF_2 cover salt. When the cover salt nears saturation (about 17 mol % CaO at 800°C), the salt becomes ineffective for the reductions. The resultant salt-CaO would be a major waste stream if the salt were not recycled. The CaO must be removed from the salt if the salt is to be recycled. This project was an attempt to develop an electrochemical process to recover the salt and calcium for recycle by converting the CaO back to calcium metal.

Approach: The approach taken in this project was the electrolysis of CaO in molten CaCl_2 - CaF_2 at 800°C using a liquid metal cathode and consumable carbon anode. In the electrolysis, the cathode reaction generates calcium in solution in the liquid cathode, and the anode reactions yield CO and CO_2 gas. Thus, the oxygen from oxide fuel is removed as gas, which can be scrubbed and released. The salt and calcium can be recycled; hence, waste is minimized. The use of a consumable carbon anode enhances the electrolysis because of the free energy of formation of the oxides of carbon. A magnesium-copper cathode is employed for a flowsheet that uses a Mg-Cu-Ca alloy as reductant, and zinc is used for a flowsheet that uses a Zn-Ca reductant. For flowsheets requiring pure calcium, a zinc cathode is used, and calcium is recovered by distilling off the zinc.

Technical Progress and Results: Twenty-four small-scale feasibility experiments on the process were performed. The cell was operated either in a constant current or constant voltage mode at 800°C for the electrolysis experiments. The cell potential was generally limited to less than 2.7 V, the reversible decomposition potential for CaCl_2 with a zinc cathode.

The experimental results demonstrated that the specially designed cell system can recover reduction salt and calcium metal in either a zinc or magnesium-copper liquid metal cathode. The process is reproducible under the established conditions. Current efficiencies of 80% were demonstrated with the zinc cathode and 60% with the magnesium-copper cathode. Initial current densities of 250 mA/cm^2 were obtained with the zinc cathode and 170 mA/cm^2 with the magnesium-copper cathode. Both CO and CO_2 were released at the carbon anode. However, no chlorine was detected in samples of effluent gas from the anode, which indicates that no CaCl_2 was decomposed even when the cell voltage was deliberately increased to 3.4 V.

A major problem encountered in the early experiments was carbon contamination of the molten salt electrolyte. Carbon particles are dislodged from the anode surface during the electrolysis. Also, carbonates, which can form by reaction of CO_2 from the anode with CaO in the salt, can be reduced chemically or electrochemically in the vicinity of the cathode to produce carbon or carbides. The accumulation of carbon dust in the electrolyte may cause shorting and voltage oscillation. Most importantly, carbon or carbides in the salt makes it unsuitable for recycling without filtering. Therefore, a porous anode shroud was developed to prevent contamination of the bulk salt. The pore size of the porous anode shroud was sufficiently small to prevent carbon particles from moving through the pores yet sufficiently large to allow transfer of salt and ionic reactants. At the conclusion of electrolysis, the anode shroud was raised above the molten salt, and the salt drained out through the pores. The carbon particles were retained in the shroud and subsequently were removed by oxidation. Experimental results demonstrated that the incorporation of the anode shroud into the electrolysis cell effectively prevented carbon dust from contaminating the bulk salt. The shroud also appears to have kept any carbonates that may have formed away from the cathode where carbon and carbides could form.

Specific Accomplishments: A patent application was made based on part of the results obtained in this project: "Calcium Electrowinning Process with Electrode Compartment to Avoid Carbon Powder Contamination of Electrolyte," (ANL-IN-90-58, DOE Case No. 73112), David S. Poa, R. Dean Pierce, Thomas P. Mulcahey, and Gerald K. Johnson.

Publications Include: "Electrochemical Recovery of Pyrochemical Reduction Salt," D. S. Poa, G. K. Johnson, T. P. Mulcahey, and R. D. Pierce, Extended Abstracts, 180th Electrochem. Soc. Meeting, Phoenix, AZ, Oct. 13-17, 1991.

(3.13) PYROCHEMICAL ACTINIDE EXTRACTION

Associate Laboratory Director Area: Engineering Research

Principal Investigators: T. R. Johnson, L. S. Chow, R. A. Leonard, Chemical Technology

Funding History:	FY 1989	\$101.7K
	FY 1990	\$338.1K
	FY 1991	\$224.5K

Purpose: The purpose of this activity was to develop a high-temperature centrifugal contactor (pyrocontactor) for countercurrent processing of liquid salts and metals up to 500°C. Experiments were conducted to determine the performance and extraction efficiency of the contactor. The ultimate goal is to develop a multistage, countercurrent, continuous, liquid metal-salt extraction process using pyrocontactors to separate transuranic (TRU) elements from the waste salts.

Approach: The approach used in this work was to first design and build a test facility to process metals and salts at 500°C. This facility includes (1) a single stage pyrocontactor, (2) a metal feed tank to feed liquid metal to the contactor, (3) a salt feed tank to feed liquid salts to the contactor, (4) a metal raffinate tank to receive metal raffinates from the contactor, (5) a salt raffinate tank to receive salt raffinates from the contactor, (6) a metal treatment tank to purify the metal prior to an experiment, (7) a salt treatment tank to purify the salts prior to an experiment, (8) transfer lines to transport molten liquids between the processing apparatus either by gravity or by pressurized gas, (9) heaters and furnaces, (10) a data acquisition system, (11) instrumentation and control, and (12) an argon-filled glovebox to house the above apparatus. Tests will be conducted in this facility to demonstrate the operation of the pyrocontactor with cadmium metal and chloride salts and to determine the stage efficiency of the contactor with uranium and a rare earth at 500°C.

Special features of the centrifugal contactors used in aqueous solvent extraction such as having a compact size, an annular mixing region for mixing and extracting two immiscible liquids and a centrifugal separating zone for separating the liquid-liquid dispersion into two phases were adopted in designing the pyrocontactor. Strings of pyrocontactors can be used for countercurrent, continuous pyrochemical processing. The pyrocontactors can be used in (1) separating transuranic (TRU) elements from rare earths in the IFR fuel cycle, (2) recovering TRU elements from the LWR spent fuel and used as LMR fuel in a combined LWR/LMR fuel cycle, (3) purifying plutonium from intractable scraps and residues accumulated at the Department of Energy production sites, and (4) separating americium and other minor actinides from plutonium.

Technical Progress and Results: The design and fabrication work for the pyrocontactor is completed. The design of the feed tanks is about 90% completed. The design, fabrication, and installation work for the raffinate and treatment tanks is completed. Pretests of these tanks are continuing.

Tests were completed with the transfer line test apparatus that includes a transfer line, two process vessels, a high temperature control valve, and compression fittings. These tests successfully demonstrated the transfer of molten chloride salts at a temperature of 500°C and a gas pressure of about 20 psia.

A data acquisition system, which includes a Macintosh computer and related software, was purchased, installed, and successfully tested.

Installation work for process control instruments such as thermocouples, liquid level probes, induction probes, and reference electrodes is about 85% completed. Facility control systems such as pressure control subsystem, emergency control system, gas cooling system for the main purification system, and temperature control for the furnaces are about 85% completed.

The design work to modify the existing glovebox, which is 5.5' high, 4.5' wide, and 13.5' long, is completed. Modification work to the glovebox including floor wells for the raffinate and treatment tanks, electrical and mechanical feed throughs, and ducts and pipe connections to the main purification system of the box is about 90% completed.

A document, "Procedures for Transfer Line Test Apparatus", document No. CMT-30-0438, was issued on November 1, 1990. This document describes the detailed set up of the transfer line test apparatus and outlines the procedures to be followed during the testing of the apparatus. The objective of the work is to demonstrate the operation of the transfer lines, valves, and compression fittings at a temperature of about 500°C and a gas pressure of 20 psia.

A meeting to review the design drawings and calculations for the feed tanks and raffinate and treatment tanks was held on November 12, 1990 and answers to the comments and discussions raised in the meeting were issued on December 12, 1990. A closeout review meeting for the feed tanks was held on December 18, 1990.

A document, "Work Plan for the Design, Procurement, and Installation of the Pyrocontactor Test Facility, Room J-134, Building 205," document No. CMT30-439 was issued on March 15, 1991. This work plan describes the pyrocontactor test facility, project scope, quality assurance, project organization, project responsibility, and project schedule.

A document, "Test Plan for Pretests of the Raffinate and Treatment Tanks in the Pyrocontactor Test Facility," ANL-CMTI-10,321 was issued on May 16, 1991. This plan describes tests to be made to each of the raffinate and treatment tanks before the glovebox is closed and filled with inert gas. The test plan includes procedures for testing leaks for wells, liners, and tanks, agitator, level probes, leak detection probes, and furnace and calibrating tank volumes and thermocouples.

A document, "Preliminary Safety Review Description for the Pyrocontactor Test Facility, Room J-134, Building 205," document No. CMT30-0441, dated July 10, 1991 was issued. This document describes the safety aspects of the pyrocontactor test facility, the experiments to be performed, the chemicals used, the potential hazards involved, and the planned measures to alleviate these hazards.

Specific Accomplishments: A patent application has been filed for the "New Contactor for Pyrochemical Process," (Invention Report ANL-IN-91-07) on Jul-12-91.

Publication:

"Development of a Pyrochemical Actinide Extraction Apparatus," L. S. Chow, R. A. Leonard, and T. R. Johnson, submitted for presentation at the 11th Annual Pyrochemical Workshop, Oak Brook, IL, Nov. 11-14, 1991.

(3.14) NUMERICAL MODELING OF ANISOTROPIC TURBULENCE

Associate Laboratory Director Area: Engineering Research

Principal Investigators: M. Bottoni, F. C. Chang, Materials and Components Technology

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$166.2K

Purpose: This work was to develop an anisotropic turbulence model capable of predicting, more accurately than the k - ϵ model, the effects of thermal stratification on natural convection flows in pool-type nuclear reactors. The newly developed model has to be integrated into the general-purpose three-dimensional, transient, single-phase flow version of the COMMIX-1C¹ computer code. Applications have been foreseen in the frame of safety analysis of pool-type liquid metal reactors, such as the Integral Fast Reactor (IFR).

Approach: Physical modeling and numerical work on turbulence have been pioneered in the past years by the French Commissariat à l'Energie Atomique de Grenoble (CENG) by the Electricite de France (EdF) at Chatou, Paris, and by the United Kingdom Atomic Energy Authority (UKAEA) at Harwell, among others. Based on the experience gained by these groups, with which one of the above investigators (M. Bottoni) had close working contacts, an anisotropic turbulence model has been devised, based on the transport equations for the turbulent scalar fluxes ($\overline{u_i \phi}$, where u_i = fluctuation of velocity component, ϕ = temperature fluctuation) and on a transport equation for the variance of temperature fluctuations ($\overline{\phi^2}$). These equations add to the k and ϵ equations written in an implemented form with respect to the original formulation used in the COMMIX-1C code. All above transport equations are solved rigorously, without simplifying approximations.

Technical Progress and Results: All transport equations mentioned above have been treated analytically and transformed into Poisson-like differential equations which have been discretized into algebraic systems of linearized equations. Following the analytical work, the resulting linearized equations have been coded and solved numerically with direct solvers. Rigorous, noniterative, numerical solutions are compulsory to obtain required precision. The new package written for the numerical solution of the transport equations, consisting of about 25 new subroutines, has been linked to the already operational code version COMMIX-1C. As a first check of the new code, test cases have been rerun, in which the impact of buoyancy upon turbulence is expected to be negligible (for instance, heated pipe flow at high Reynolds number). For these cases the anisotropic model has reproduced, as expected, the same results as the k - ϵ model. Work is now in progress to test the performances of the anisotropic model in case of unstably stratified flows, where the impact of buoyancy upon turbulence is expected to be relevant.

Prototypical experimental data have been published² for the shear flow of hot and cold water, with different velocities ($U_{\text{cold}} = 2 \cdot U_{\text{hot}}$), between two parallel plates. In case of unstable stratification (hot water entering the system at the bottom), a temperature inversion is expected to take place. The attached Fig. 1 shows velocity distributions computed with the $k-\epsilon$ and with the six-equation anisotropic models; the six-equation model predicts stronger mixing between the flows, as expected. Figure 2 shows temperature distributions at the location $x/h = 20$. The experimentally measured temperature profile at the same location is almost vertical. Therefore, it is evident that the performance of the anisotropic model is much better than that of the standard $k-\epsilon$ model, though not yet satisfactory.

It is the investigators' opinion that the still existing discrepancies are due to the isotropic formulation of the Reynolds stresses $\overline{u_i u_j}$, which does not match the anisotropic model now used. This topic is going to be investigated in FY 92, in case financial support for this (initially prepared as) two-year project is granted.

Specific Accomplishments: A detailed ANL report is being written with all modeling and numerical treatment of the transport equations involved in the six-equation model and will be issued by the end of 1991.

The investigators are planning to present a contribution to the Eurotherm-Ercoftac Workshop to be held at Delft, The Netherlands, in March 1992, on the topic *Benchmark Computation and Experiment for Turbulent Natural Convection in a Square Cavity*. At this workshop, contributions with the $k-\epsilon$ model, as well as with more advanced models are encouraged. The investigators plan to present a final report on this work to the NURETH-5 session on *Liquid Metal Cooled Reactor Thermal Hydraulics* to be held in Salt Lake City, Utah, in September 1992.

1. H. M. Domanus et. al., *COMMLX-1C: A Three-Dimensional, Transient, Single-Phase Computer Program for Thermal Hydraulic Analysis of Single- and Multicomponent Engineering Systems, Volume I: Equations and Numerics; Volume II: User's Guide and Manual*, NUREG/CR-5649, ANL-90/33 (Sept. 1990).
2. *Modele de Turbulence au Deuxieme Ordre: Ecoulements Complexes ou Straifies*, These de L'Ecole Centrale de Lyon, par Mohamed Kanniche (5 Jan. 1990).

Fig. 1 - Axial Velocity (m/s)

Fig 2 - Temperature Distribution (C)

(3.15) ADVANCED REACTOR STUDIES FOR 600 MWe LMR

Associate Laboratory Director Area: Engineering Research

Principal Investigators: R. W. Seidensticker, D. R. Pedersen, Reactor Engineering

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$306K

Purpose: The EBR-II nuclear reactor facility has operated very successfully for over 27 years, producing not only electrical power (for which the laboratory receives about \$2000K per year in sales), but also serving as a test reactor for many concurrent in-core experiments. The main purpose of this study is to identify those key design and operational features of the EBR-II facility which are believed to be the most instrumental in achieving this successful record and to see if these desirable characteristics can be incorporated into a modern LMR plant of much larger power level (600 MWe versus 20 MWe for EBR-II). In addition, it is the goal of this study to incorporate modern codes and standards in the larger plant, provide very high levels of protection against accident initiators (such as the use of a low sodium void worth core), and to consider relevant features of foreign LMR plants. Figure 1 illustrates the interaction effects of all of these elements of our goals.

Approach: Fortunately for the Laboratory, many of the original design engineers and project managers for the initial EBR-II plant are still employed by Argonne, either as permanent staff or as special term appointees or consultants. The basic approach to creating a first cut at even the most rudimentary speculative designs has been to assemble these individuals on a fairly regular basis to critique preliminary designs presented by various members of the design team. The nature of these working meetings run the gamut from reviewing global speculative design layouts to extensive discussions on a particular system or feature being proposed as a key EBR-II characteristic. Supplementing this smaller design core group are a number of other engineers and physicists who make substantial contributions to the design study effort and who benefit from intense interactions with the original plant designers. We are indeed fortunate to have two senior project management staff from the original EBR-II project: Mr. Leonard J. Koch, Project Director for the design, construction and initial operation of EBR-II, and Mr. Wallace R. Simmons, Project Manager for the EBR-II Power Plant, Sodium Boiler Plant and the Steam Generator System. In addition, Dr. Walter B. Loewenstein, formerly a director of the EBR-II division and former director of safety/physics for EPRI, has participated extensively during the past year.

Technical Progress and Results: Activities in FY-1991 focused on identifying key features of EBR-II, decisions as to what approaches should be made to display draft speculative layouts and designs, selection of areas felt to require engineering trade-off studies and to reach preliminary decisions on how best to proceed with this study, particularly in view of the need to meet current modern codes and standards and to compare favorably with latest foreign LMR concepts.

Seven major features (attributes) of EBR-II were selected as representing those things which the Study Team feels contributed most to the success of EBR-II. The areas/feature chosen were:

1. constant low-temperature, low-pressure pool and boundary,
2. large volume low-temperature sodium in pool,
3. in-vessel fuel storage that is accessible during reactor operation,
4. simple direct pull fuel handling system,
5. separation of hot primary tank from cold deck support structure,
6. natural convection cooling of reactor during shutdown,
7. unique controlled response to "loss of flow without scram", and
8. double walled tube steam generators.

Somewhat cursory studies, though in detail in certain aspects, were carried out for many of the seven features listed above.

To assist in carrying out any significant assessment or study, one must have a rough idea of the physical layout of the systems and some idea of the problems and constraints involved in carrying out studies of any one of the areas/features discussed above. To do this, three somewhat different preliminary-concepts were "developed":

1. A top suspended primary LMR pool system with single "hot" deck and an internal reactor core vessel with a top cover (same as EBR-II). This layout requires close coupling of the primary sodium outlet pipe to the intermediate heat exchanger (IHX) to avoid tortuous long piping runs to get sufficient flexibility.
2. A bottom-supported LMR pool system quite similar (otherwise) to the top-supported system just described.
3. A top-supported (suspended) primary LMR pool system similar to #1 above except the top cover on the small internal core reactor vessel is replaced with a high cylinder (redan) which eliminates the need for the expensive cover used in #1 (and #2 above).

Figure 2 shows concept #1 (above), identifying relevant features of EBR-II and other design goals.

In developing these three layouts, every effort was made to estimate realistic sizes of key internal equipment such as the IHXs, primary sodium pumps, fuel handling system. Note that in-vessel fuel storage has become almost an essential, though this will be studied in greater depth.

A thorough study has been made which shows that the EBR-II double-walled steam generators probably can be made in large unit sizes which results in a scaled-up version of the EBR-II which looks "reasonable" (much work remains).

To gather, organize and make easily available all study data -- reports; drawings; studies; specifications; etc. -- this study group has developed first: a Project Master Function Chart, not too unlike a Work Breakdown Structure, but one felt more useful to this project. The other is a Project Notebook Binder which is organized to follow the format of the Task Building area chart just described, and which serves to keep all members informed and up-to-date on all aspects of this study.

Specific Accomplishments: Accomplishments include the preparation of three distinct speculative design approaches to a 600 MWe LMR based on EBR-II Technology and the preparation of study reports showing feasibility of scaling up EBR-II double-wall steam generator concept to the 600 MWe plant. Preliminary draft memos have been prepared on design choices for decay-heat-removal systems, variations on "pancake" reactor-core geometry; alternate refueling schemes and strategies. No formal publications have been prepared. Presentations have been made to senior ANL management.

ANL 600 MWe LMR PLANT STUDY

600HWEB2.VGF

Figure 1

E00344--1

600 MWe IFR CONCEPT BASED ON EBR II EXPERIENCE

Figure 2

IFR Concepts Design Meeting

(3.16) LASER AIDED MATERIALS PROCESSING RESEARCH

Associate Laboratory Director Area: Engineering Research

Principal Investigators: K.H. Leong, S. K. Bhattacharyya, Engineering Physics

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$247.5K

Purpose: Lasers as applied in materials processing have emerged as high technology tools that can impact on the competitiveness of the manufacturing industry. The objective of this work is to establish the technical capability to conduct research and development in laser aided materials processing with state-of-the-art lasers, beam delivery systems and diagnostic equipment.

Approach: Lasers are efficient materials processing tools that are superior in many respects to conventional tools. The precision and quality that can be achieved in cutting, welding, drilling, heat treatment and marking of materials are frequently impossible with other machine tools. Small heat affected zones, high quality finish and minimal waste are characteristic of laser machining. However, the lack of diagnostics, process control and scientific understanding of the laser-material interaction process has hampered the widespread acceptance of this technological tool. (The recognition of the importance of laser processing technology to the competitiveness of the manufacturing industry has led the state of Illinois to award an equipment grant to Argonne National Laboratory and the University of Illinois at Urbana-Champaign in FY1991.)

The focus of this work is to assess the problems and deficiencies in current laser processing technology as applied in industry and develop the necessary diagnostic tools and process control techniques using state-of-the-art equipment such as that acquired from the state of Illinois grant. This is being accomplished through interaction and collaboration with the University of Illinois and several major manufacturing companies that include Caterpillar, Deere & Co., and General Motors. A significant outcome of this interaction will be direct technology transfer to industry of the improvements in laser processing technology.

Technical Progress and Results: An assessment was carried out with industrial input to determine the appropriate equipment needed to carry out the goals of the research. Effort was expended in the acquisition, installation and testing of a 6 kW CO₂ and a 1.6 kW YAG laser system and associated controls and diagnostics.

A state-of-the-art 6 kW CO₂ rf laser system has been interfaced with a computer numerical control with a 5-axis workstation, beam delivery, and on-line beam diagnostics. A 2-D plasma diagnostic system using fiberoptics, spectrograph and a CCD detector has been assembled. An on-line melt pool monitoring system has also been designed.

A second year of support will permit completion of the interfacing of the YAG laser to the computer-controlled workstation and the development of process control methods.

(3.17) **FABRICATION AND TESTING OF 10-kJ HIGH-TEMPERATURE SUPERCONDUCTING MAGNETIC ENERGY STORAGE DEVICE**

Associate Laboratory Director Area: Engineering Research

Principal Investigators: J. R. Hull, R. B. Poeppel; Materials and Components Technology

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$260.5K

Purpose: The feasibility of fabricating a "hatbox-sized" solenoid magnet coil, made from high-temperature superconductors, (HTSs) is being explored. The fabrication will require state-of-the-art techniques to produce high current densities in very long lengths of wires and forming these wires into a solenoid magnet coil. It is envisioned that the coil will be approximately 30 cm in diameter, 30 cm high, generate a magnetic field of 1 T, and store 10 kJ of energy. It is anticipated that if such a coil can be fabricated successfully with relatively high current density, it can then be operated as a miniature superconducting magnetic energy storage (SMES) device. Such HTS coils can also be used for motors and other applications.

Approach: Plastic extrusion is a promising method for producing the required long lengths of HTS and forming it into the shape of multilayer solenoid coils. A crucial phase of the extrusion method is removal of organic constituents. Incomplete removal can leave residual carbon at grain boundaries, which can adversely affect the superconducting properties, whereas excessively rapid removal of the organics can cause the extruded superconductor to disintegrate completely. The effect of process parameters (such as temperature, pressure, oxygen flow rate, and heating rate) are of paramount importance during heat treatment of the extruded YBCO coils and are being investigated so that maximum current density can be achieved for a given coil.

A separate issue is the quantitative determination of the amount of magnetic energy stored in a superconducting coil as a function of size and current density. The energy stored in a superconducting coil is being calculated using analytic (approximation) and numerical (finite-element) methods as well as other available methods (working formula and tables). The energy stored is calculated for coils with and without inserts to determine the gain in stored energy when an insert is used.

Additional participants in this work include Drs. S. E. Dorris and Y. S. Cha of the Materials and Components Technology Division.

Technical Progress and Results: Firing coils at reduced pressure was found to greatly minimize, if not eliminate, decomposition of YBCO for two possible reasons: (a) CO_2 and H_2O are not allowed to accumulate in the atmosphere because the furnace operates under a dynamic vacuum, thus minimizing the reaction between YBCO and CO_2 and H_2O , (b) the reduced pressure limits the supply of oxygen to the decomposing binder, thereby moderating the binder

decomposition reaction and preventing thermal runaway. It was also shown that uneven cooling of the coil can result if oxygen is allowed to flow unimpeded into the furnace. Disrupting the flow of oxygen by placing a porous material at the entrance to the furnace helps to alleviate this problem.

Heat conduction into the coil interior is controlled by the thermal diffusivity of the organic phase. Because this thermal diffusivity is very low (10^{-7} – 10^{-8} m²/s), large steady-state temperature gradients (approx. 50°C) might be expected across moderately thick coils (2 cm) that are heated at rates of 0.01°C/s. This can lead to nonuniform removal of organics from the coil and result in large stresses in the weak green coil. Calculations and experiments show that this problem is avoided when coils are heated at a rate of 0.001°C/s. Finally, it was shown that the diffusion of volatile components is much slower than heat conduction, so the entire coil may be above the saturation temperature while most of the volatile components are still trapped in the interior. This results in bubble formation and can be prevented by the use of very slow heating rates.

The energy stored in a coil with a diameter of 30 cm and a length of 30 cm is calculated by using the three methods described previously. It is found that the current density required to store 10 kJ of energy in a coil with insert must be at least 4,000 A/cm². When the insert is removed, the current density requirement is increased by a factor of 2.5.

Specific Accomplishments: YBCO/Ag wires with diameters between 0.1 and 3.0 mm and lengths up to 20 m have been extruded. Coils typically consist of six to twelve layers of 2 mm diameter wire, have an inside diameter of 2.5 cm and an outside diameter of 5–8 cm, are fired at 900–920°C and annealed at 450°C. The critical current density at zero applied field and 77 K ranged from 120–225 A/cm².

Publications include:

"The Effect of Processing Parameters During Heat Treatment of Bulk High-T_c Superconductors," Cha, Y. S., Dorris, S. E., Hull, J. R., and Poeppel, R. B., Paper to be presented at the 1991 ASME Winter Annual Meeting, Atlanta, GA, December 1–6, 1991

"Analysis of Magnetic Energy Stored in Superconducting Coils with and without Insert," Cha, Y. S., internal report to be issued.

(3.18) **EFFECTS OF INTERFACIAL BOND STRENGTH ON TOUGHNESS OF
CERAMIC FIBER-REINFORCED CERAMIC MATRIX COMPOSITES**

Associate Laboratory Director Area: Engineering Research

Principal Investigators: J. P. Singh, D. Singh, D. S. Kupperman, S. Majumdar,
Materials and Components Technology

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$220K

Purpose: Demands of high technology increasingly require new materials to be used in elevated temperature applications. An important example of such application is the use of engineering ceramics and composites for energy related heat engine applications. The major problem obstructing the use of ceramics and composites in structural applications is the brittleness and low fracture toughness of these materials. To enhance overall fracture toughness of ceramics, a new class of fiber-reinforced ceramic composite materials are being developed. Fracture toughness of ceramic composites are greatly influenced by the characteristics of the fiber-matrix interface which controls the extent of fiber pullout from the matrix. Increasing amount of fiber pullout increases the energy absorbed through interfacial shear between fiber and matrix and hence improves fracture toughness. The extent of fiber pullout depends on the strength of the fiber/matrix interface. Therefore, fracture toughness which is proportional to the amount of energy/absorbed, can be increased by appropriately controlling the strength of interfacial bond between fiber and matrix. The interfacial bond strength depends upon the nature of fiber surface which can be controlled by coating the fibers with different coatings. Other parameters controlling the bond strength include the nature of interfacial chemical reaction and the internal stresses resulting from the mismatch between thermal expansion coefficients of the matrix and fiber. Therefore, the purpose of this research is to understand the effects of these parameters (nature of fiber surface, chemical reaction, and thermal expansion mismatch between matrix and fiber) on the interfacial bond strength between fiber and matrix for developing composites with improved toughness.

Approach: Initial inhouse efforts were spent on fabricating ceramic fiber reinforced ceramic matrix composites. Fibers with different surface conditions (with and without surface coatings) were used for composite fabrication in order to obtain composites with different interfacial bond strengths. In parallel, interactions were established with appropriate research laboratories and industrial partner(s) who could also provide the necessary composite specimens with appropriate interfacial bond characteristics between fiber and matrix. After fabrication and/or acquisition of composite specimens, their mechanical and microstructural (specifically interfacial) characterizations were completed. In parallel, the interfacial stresses at the matrix/fiber interface were evaluated using both neutron diffraction measurements and analytical modeling. The results of interfacial characterization and internal stress evaluations are being correlated with the mechanical properties to provide recommendations for improved composite design.

Technical Progress and Results: Initial effort was spent on establishing contacts with industry and other research institutions to discuss the important and relevant fabrication parameters controlling the interfacial bond strength and the resulting toughness in continuous fiber-reinforced ceramic matrix composites. Specimens with controlled interfaces were obtained from NASA, Dow Corning, and Oak Ridge National Laboratory. A limited effort was also spent on in-house composite fabrication. Because silicon carbide (SiC) fiber-reinforced reaction bonded silicon nitride (RBSN) matrix composites received from NASA included a complete set of specimens with systematically varying fiber contents, fiber surface conditions, and fabrication procedures, research effort was concentrated on these specimens. (These specimens had been submitted for neutron diffraction analysis by NASA under a Work for Others agreement, the data from which can be compared to results of the work reported here.)

During fiscal year 1991, effort was directed towards the development of a fiber pushout test facility to evaluate the fiber/matrix interfacial strengths. Pushout test system was designed and built in which individual fibers can be located under a flat tip indenter using a micrometer driven X-Y stage, and subsequently, pushed out from the matrix. Fiber pushout test system was used on a universal testing system (Instron Corp.) and the accuracy of locating the fibers is within two microns. Also, advantage of using this system is that the load versus indenter displacement behavior for the entire pushout process can be continuously monitored. Continuous recording of the load-displacement behavior (figure 1) enables in distinguishing between the various interfacial fracture processes related to interfacial strength such as interfacial debonding and frictional sliding.

Figure 1. Typical Load-Displacement Curve for a Fiber Pushout Test

Table 1 summarizes the initial results obtained for the different types of SiC/RBSN composites with varying processing parameters. Interfacial bond strengths were evaluated for composites based on a simple linear relationship between interfacial strength and embedded fiber length in the matrix. It is interesting to find that both debonding stress and sliding friction stress substantially reduce with increase in the fiber volume content indicating interaction of the residual stresses associated with neighboring fibers and matrix. SiC/RBSN composites with uncoated fibers showed significantly higher interfacial debonding and sliding friction stresses as compared to composites with carbon coated fibers. Higher debonding stress indicates formation of a strong chemical bond between fiber and matrix for uncoated fibers and the difference in the sliding friction stress indicates the difference in the fiber surface structure in the two cases. Hot isostatically pressed SiC/RBSN composites with comparable fiber volume fraction showed higher interfacial strength which probably is due to the higher processing temperature for hot-pressed composites resulting in chemical bonding. Currently, investigation is being conducted to quantitatively establish the nature of the interfacial bond and location of interfacial debonding and sliding in different composite types.

Table 1. Summary of the Results Obtained for SiC/RBSN Composites Using Fiber Pushout Tests

COMPOSITE TYPE	Debonding Stress, MPa	Sliding Friction Stress, MPa
C-Coated SiC (12.57 vol %)/RBSN	13.61	17.03
C-Coated SiC (23.34 vol %)/RBSN	3.45	4.32
Uncoated SiC (24.44 vol %)/RBSN	92.59	58.17
C-Coated SiC (28.92 vol %)/RBSN	15.22	13.81

In a parallel effort, strength and microstructures of SiC fiber reinforced SiC matrix composites (processed by chemical vapor infiltration) were characterized. Microstructural evaluations of these composites indicated a substantial fiber pullout suggesting fiber pullout as the major toughening mechanism due to the absence of interfacial reaction between fibers and matrix.

As part of a separate Work-for-Others project using the Neutron Stress Monitor technique (which had been developed under LDRD in FY 1987 and 1988), neutron diffraction data on SiC/RBSN composite specimens for residual stress measurement in the composite constituents

as a function of processing parameters were available. Strain values in the fibers decreased with increasing fiber content which is qualitatively in agreement with the predictions of theoretical models developed considering linear elastic behavior of the constituents. On the other hand, strain variations in the matrix are not consistent with model predictions. The reasons for these observations are currently under investigation.

In the area of analytical modeling, a two-dimensional model has been developed to account for the effects of fiber slippage on the residual thermal stresses developed in fiber-reinforced composites. Predictions made based on this model for the variations of the radial and shear stresses in fiber and matrix, along the fiber axis, are in excellent agreement with results of finite element analysis for a SiC-Al₂O₃ composite system. Results for SiC/RBSN composites based on this analysis will be further compared with the experimental observations.

The results of interfacial bond strength and internal stress measurements are being correlated with measured mechanical properties through analytical modeling to provide information for composite design with improved microstructure and properties. A proposal has been submitted for further LDRD funding for FY 1992. If funded, the results of this study will be used for development and fabrication of ceramic fiber-reinforced ceramic matrix composites with tailored microstructures and improved properties for elevated temperature applications.

Specific accomplishments:

Publications:

J.P. Singh, D.S. Kupperman, and S. Majumdar, Strengthening of Composites by Internal Stresses: Determination by Neutron Diffraction, Proceedings of the First International Symposium on the Science of Engineering Ceramics, Koda, Aichi-Preecture, Japan, October 21-23, 1991.

D.S. Kupperman, S. Majumdar, J.P. Singh and A. Siagal, Application of Neutron Diffraction Time-of Flight Measurements to the Study of Strain in Composites, Proceedings of the NATO Advanced Research Workshop on "Measurement of Residual Stress and Applied Stress Using Neutron Diffraction", Oxford, England, March 18-22, 1991.

S. Majumdar, Effects of Fiber Slippage on Stresses in Composites, internal report, MCT Division, Argonne National Laboratory, October, 1991.

S. Majumdar, Modeling of Fiber Pullout and Pushout Tests, internal report, MCT Division, Argonne National Laboratory, October, 1991.

D. Singh and J.P. Singh, The Effect of Processing on Nicalon Fibers in Nicalon Fiber-SiC Matrix Composites, to appear in the Proceedings of the 16th Annual Conference on Composites and Advanced Ceramics, Cocoa Beach, Florida, January 7-10, 1992.

A. Saigal and D.S. Kupperman, Application of Neutron Diffraction in Measuring Residual Strains in High-Temperature Composites, to appear in the Proceedings of the Sixth Japan-US Conference on Composite Materials, Orlando, Florida, June 22-25, 1992.

Proposals Submitted:

J.P. Singh, W.A. Ellingson, and D.S. Kupperman, contribution to a proposal submitted by Dow Corning to DOE Composite Initiative entitled, Research and Development of Materials/Processing Methods for the Continuous-Fiber-Ceramic Composite (CFCC) Program.

J.P. Singh, D.S. Kupperman, and S. Majumdar, The Role of Internal Stresses in Toughening of Continuous-Fiber-Reinforced Ceramic Matrix Composites, submitted to DOE CFCC Program.

Oral Presentations:

D. Singh, J.P. Singh, and M.J. Wheeler, Evaluation of Fiber/Matrix Interfacial Bond Strength in SiC-Fiber-Reinforced Reaction-Bonded Silicon Nitride Composites, at Amoco/University Poster Session, at Amoco Research Center, Naperville, IL, October 4, 1991.

J.P. Singh, D.S. Kupperman, and S. Majumdar, Strengthening of Composites by Internal Stresses: Determination by Neutron Diffraction, Invited paper presented at the First International Symposium on the Science of Engineering Ceramics, Koda, Aichi-Prefecture, Japan, October 21-23, 1991.

J.P. Singh, D.S. Kupperman and S. Majumdar, Role of Internal Stresses in Improvement of Mechanical Properties of Ceramic Composites, Invited paper at the 44th Pacific Coast Regional Meeting of the American Ceramic Society, San Diego, California, October 31-November 2, 1991.

D. Singh and J.P. Singh, The Effect of Processing on Nicalon Fibers in Nicalon Fiber-SiC Matrix Composites, to be presented at the 16th Annual Conference on Composites and Advanced Ceramics, Cocoa Beach, Florida, January 7-10, 1992.

D. Singh and J.P. Singh, Evaluation of Fiber/Matrix Interfacial Bond Strength in SiC-Fiber-Reinforced Reaction-Bonded Silicon Nitride Composites and its Correlation to the Composite Mechanical Properties, to be presented at the 94th Annual Meeting and Exposition of the American Ceramic Society, Minneapolis, Minnesota, April 12-16, 1992.

(3.19) CHARACTERIZATION OF ELASTOMERS

Associate Laboratory Director Area: Engineering Research

Principal Investigator: R. F. Kulak, T. H. Hughes, Reactor Engineering

Funding History:	FY 1989	\$0K
	FY 1990	\$197.7K
	FY 1991	\$105.2K

Purpose: The capability to determine the mechanical properties of elastomeric materials for use in seismic isolators is being developed. The variation of these properties with strain level, state of stress, frequency and temperature will be determined from this study. The elastomer response to combined compression (gravity) and shear (earthquake) loadings has been identified as an important research area. Constitutive models for the elastomer can be developed and verified. These constitutive models will then be used in three-dimensional finite element models of the complete laminated elastomer isolation bearing. Follow-on research support for activities related to nuclear reactor applications is expected from the same governmental and industry sources that currently fund our reactor programs. This capability should help to establish ANL as a center for seismic isolation elastomer testing.

Approach: Optimization of the design of elastomeric seismic isolators requires computer simulations that use realistic constitutive models of the elastomers. These models contain parameters that must be determined from combined loading experiments on small samples of the elastomers. The licensing of base isolated nuclear power plants will require a data base of material response and validated computer constitute models of the elastomers. However, the methodology and capability to obtain the parameters and validate the material models did not exist. Bearing manufacturers and bearing testing centers understood the need for such data; neither group is equipped to develop the methodology and carry out the tests.

A set of tests were identified that will generate a database for use in characterizing elastomer compounds for the seismic base isolation application. These tests include simple shear, relaxation, biaxial (shear plus compression/tension), and complex wave forms.

An elastomer testing configuration has been designed and assembled to perform high precision dynamic testing of small coupon specimens. The configuration consists of two 8500 series Instron universal testing machines, a 386DX computer, a biaxial reactor frame with loading hardware and instrumentation and a temperature cabinet (-100F to 400F). Special purpose software was developed for test control. In addition, vendor supplied software (FLAPS PLUS) was acquired.

Technical Progress and Results: Fiscal year 1990 was devoted to acquiring and learning how to use the Instron testing machine. A control and data collection program, RSHEAR, was written in QuickBasic. Some preliminary elastomer testing was performed.

During FY-1991, simple shear and relaxation tests were successfully performed at room temperature on a high damping natural rubber compound (#259-62) provided by Oil States Industries of Arlington, Texas. Figures 1 and 2 show the variation of stiffness and damping, respectively, with frequency. Because of these variations with frequency, it appears that the current bearing acceptance tests will have to be revised to reflect the fact that the manufacture's testing frequency (0.005 Hz) is usually much lower than the design frequency (0.5 Hz).

A biaxial reaction frame was designed and manufactured. A hydraulic actuator, servovalve and load cell were acquired for use with the reaction frame for performing biaxial tests.

Recently, Instron has introduced new and more general control software for performing dynamic and static tests. We have purchased this software (FLAPS PLUS) and are in the process of installing and learning to use it for our test needs.

Our findings have shown the inadequacy of the current bearing acceptance tests and has provided data to improve them. Our test results are forming a data base for future use by elastomer researchers and seismic isolation bearing designers.

Specific Accomplishments: Inquiries from researchers at the Army Materials Testing Laboratory and at Bristol Polytechnic (England) indicated an interest in our capabilities and in potential future collaboration.

Internal Report:

"Experimental Determination of the Mechanical Properties of Elastomeric Materials Used in Seismic Isolators," Hughes, T. H. and Kulak, R. F., letter report to D. R. Pedersen, RE, September 27, 1991.

Publications:

"Mechanical Characterization of Seismic Base Isolation Elastomers," Kulak, R. F. and Hughes, T. H., SMiRT II transactions, Vol. K (August 1991) 163-168.

"Mechanical Tests for Validation of Seismic Isolation Elastomer Constitutive Models," Kulak, R. F., and Hughes, T. H. (in preparation).

Presentations:

"Seismic Base Isolation: Elastomer Characterization, Bearing Modelling, and System Response," Kulak, R. F., Wang, C. Y., and Hughes, T. H., SMiRT II Post-Conference Seminar No. 1: Seismic Isolation of Nuclear and Non-Nuclear Structures (August 26-27, 1991) Nara-shi, Japan.

Fig. 1. Variation in stiffness with frequency and strain level.

Fig. 2. Variation in damping with frequency and strain level.

(3.20) THEORETICAL DEVELOPMENTS IN SUPERCONDUCTIVITY

Associate Laboratory Director Area: Physical Research

Principal Investigator: V. Vinokur, Materials Science

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$84.7K

Purpose: While a number of theoretical studies exist for high-temperature superconductors which address the fundamental nature of the interactions which give rise to superconductivity, there is a strong need for the development of more phenomenological theories which will provide guidance to experimentalists. Such developments are the purpose of this project.

Approach: Phenomenological theories which are useful for the new materials must take account of their special features, which include extreme anisotropy of the properties, the presence of layered, two-dimensional superconductors, and the very short superconducting coherence length of the materials. Such effects can be included in previous, highly successful theories, such as the Ginsburg-Landau theory, which has been applied very widely, and the Lawrence-Doniach theory which was specifically pertinent to thin-film superconductors.

Technical Progress and Results: Theoretical developments have been carried out by a visiting Russian theorist, Dr. Valerii Vinokur. Vinokur and his colleagues have developed a theory of the temperature dependence of the critical current in high temperature superconductors using the concepts of collective pinning. This is the first description of critical current incorporating the pinning potential of point, cylindrical, and planar defects, and the thermal fluctuations of vortex lines in the same framework. His theory correctly describes the observed temperature dependence of critical currents in several superconductors of current interest.

Specific Accomplishments: Several publications have appeared, including Phy. Rev. Letters 66, 3297 (1991). Dr. Vinokur's work will be presented as an invited talk at the March meeting of the American Physical Society, to be held next March in Indianapolis.

(3.21) LOW TEMPERATURE SCANNING TUNNELING MICROSCOPE

Associate Laboratory Director Area: Physical Research

Principal Investigator: G. W. Crabtree, Materials Science

Funding History:	FY 1989	\$0K
	FY 1990	\$83K
	FY 1991	\$88.9K

Purpose: A scanning tunneling microscope is being developed which will operate at liquid helium temperatures. At present, no suitable commercial devices operating are available. However, the implications for exploratory research on a large number of systems is high. In particular, studies of the nature of the magnetic flux lattice in high-temperature superconductors is critical for understanding the critical current capacity of those materials, and the scanning tunneling microscope will provide unique microscopic imaging, as well as information on the electronic structure of various parts of the material. It will be possible to directly observe vortex motion and the interaction of vortices with pinning sites, leading to new and fundamental characterizations of pinning mechanisms. This will ultimately lead to improved methods for increasing the critical currents in these compounds.

Approach: A workable STM requires several components: a scanning head which detects the tunneling current, an electronic feedback system which maintains the tunneling tip at a constant height above the sample while scanning, computer software for control of the scanning parameters as well as data acquisition, and adequate vibration isolation. Several personnel are involved in this project: one postdoc, Kurt Vandervoort, and one graduate student, Roberta Bennett, are devoted full time while two staff members are involved part time.

Technical Progress and Results: To date, a workable STM at room temperature has been developed which is being used to optimize the various parameters in the electronic circuit and control software. The next step is to modify the scanning head so that it may be used in the available cryostat and magnet system.

Specific Accomplishments: Included is an image (figure 1) from of a gold diffraction grating both from forward and reverse scans, taking with the room temperature STM. Displaying the images for data acquired in both directions demonstrates their validity, as the real features of the surface topography must show up as mirror images of one another. Features have been imaged on the scale of 10,000 Å as well as features as small as ~ 20 Å. The resolutions required for the imaging of vortices has therefore been achieved.

Forward and Reverse Scans of an Au Covered (300 Å)
Diffraction Grating

(3.22) ADVANCED SUPERCONDUCTING MAGNET DESIGN STUDY

Associate Laboratory Director Area: Energy Environmental and Biological Research

Principal Investigators: J. X. Bouillard, G. E. Marsh, M. Petrick,
A. Wolsky, Energy Systems
R. Poeppel, Materials Components and Technology

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$69.3K

Purpose: The analytical and experimental feasibility of novel low specific weight and high-performance superconducting magnet design concepts that could promote the use of high temperature superconductors is being explored. This project is an attempt to study the technical viability of force-reduced magnet concepts to produce high field strength magnets (> 8 Teslas) of low specific weight of $2\text{--}4 \text{ ton/m}^3$ of warm bore which could show enhanced reliability and simplicity of construction and operation. This study may trigger the development of innovative approaches to magnet design and foster the development of a laboratory capability to pursue the development of advanced superconducting magnet systems. If successful, potential technical and economic impacts are foreseen for many civilian and defense applications which include medical/biological applications (e.g. magnetic resonance imaging (MRI)), MHD (Magnetohydrodynamic) power generation, fusion, propulsion, Maglev, SMES (Superconducting Magnetic Energy Storage) and other applications.

Approach: The present state-of-the-art of the superconducting magnet technology is reflected by the major constructions of 8 Tesla D coil fusion toroidal magnets and large high energy physics and MHD magnets. To advance further the status of this technology, higher field strength (> 8 Teslas) and lower specific weight ($2\text{--}4 \text{ tons/m}^3$ of warm bore) magnets need to be developed. The inevitable large magnetic pressure exerted at high field strength on the magnet coils, which results from the Lorentz forces, make its containment difficult with present technology and calls for innovative coil arrangements and possibly for the use of classes of ultra-high strength materials (nanophase, composite, etc.)

In an effort to mitigate this problem, past developments of force-free magnetic field solutions [1-7], where the current lines are parallel to the field lines [i.e. $\vec{j}=\alpha\vec{H}$] - thus eliminating the Lorentz forces- have led to examples of innovative and truly force-free coils surrounded by a force bearing coil [6]. In these configurations, internal forces of varying peak magnitudes are transformed into outward pressures spread over a larger region. By such reduction of internal stresses on the conductors, new avenues to utilize high temperature superconductors, inherently brittle, open. Furthermore, because of their high operating temperatures, the thermo-mechanical contraction of the magnet structure during cool-down is considerably reduced, thus vastly simplifying the final design of the magnet.

Our study has mainly focussed on the three following tasks:

- 1) the definition of a novel force-reduced toroidal coil winding for MHD ship propulsion application (shown in Figure 1).
- 2) the preliminary estimation of the reduction of forces for this type of coil in comparison to a conventional racetrack toroidal magnet configuration (shown in Figure 2) and,
- 3) the preliminary investigation of a non-constant α force-free toroidal field solution for MHD propulsion or fusion application.

To compute the magnetostatics for such intricate coil windings, the TOSCA computer code from Vector Fields Inc. was used. Analytical cylindrical force-free solutions developed by G. Marsh [8] were also used to help investigate the potential structure reduction in the central portion of toroidal magnets.

An additional participant in this work is Professor J. Schwartz of the University of Illinois, Urbana-Champaign who studied the non-constant alpha force-free field solution.

Technical Progress and Results: During the fiscal year 1989 and 1990, no work was undertaken; the project started only in April 1991.

The first and second part of this study dealt with the definition of a toroidal torsatron winding shown in Figure 1, where the internal to external cylinder radius ratio is 9/10 with an annulus gap to inner cylinder radius ratio of 1/9 and with a cylinder height to outer cylinder radius ratio of 10/10, was studied using the TOSCA computer code. A force reduction of about 20 times on the inner and outer coils supported by the surfaces of the cylinders was found, when compared to the racetrack configuration (shown in Figure 2) operated at similar electrical loadings. Moreover, for these conditions, a force reduction of about 5 times on the conductors that cross the annulus gap was found. These findings may be of considerable importance if they can be applied to the design of high performance ship propulsion MHD thrusters. These results reinforce Moon's observation [9] that significant weight reduction of present magnets could be possible.

The third part of this study consisted in the investigation of a non-constant α force-free toroidal field solution in cylindrical coordinates. Figure 3 indicates that a large and relatively uniform force-free poloidal magnetic field exists at the center of the toroid. In the region of the first non-trivial zero of the α function ($r=a$, $z=0$ Figure 3.a), the field is toroidal and the current density minimal.

This result has considerable importance since it indicates that essentially coil-free and force-free field regions may coexist. This illustrates the peculiar properties of non-constant α solutions.

An immediate application of this result would be the construction of force-reduced toroidal magnets which could offer great structural reduction of their central bucking posts.

For both the toroidal torsatron and the force-free toroidal windings, a more conclusive technical assessment of the potential benefits of such coil configurations remains to be undertaken.

Specific Accomplishments: Search for funding to continue and expand this work has been pursued with DARPA, agency presently funding the ANL sea-water MHD propulsion program.

Internal Reports Include:

A.M. Wolsky, "Notes on Toroidal Magnets for Sea-Water Thrusters and SMES and New Ways to Balance Their Magnetic Forces" in preparation, Sept. 23, 1991.

J.X. Bouillard, M. Petrick, and J. Schwartz, "Preliminary Investigation of Possible Force-Reduced (Low Specific Weight) Superconducting Magnet Configurations for Advanced Technology Applications" in preparation, Oct. 23, 1991.

Fig. 1. Torsatron Coil Winding Configuration for Novel Toroidal Magnet Concept

Fig. 2. Racetrack Toroid Magnet Configuration

(a)

$H(R,Z)$

(b)

Fig. 3 a) Non-constant α Poloidal Field Distribution
b) Radial Variations of Poloidal, Toroidal Field Components and of α in Dimensionless Units

REFERENCES

1. S. Lundquist, Arkiv-För Fysik, 2, 361 (1951)
2. R. Lüst and A. Schlüter, Z. Astrophys. 34, 263 (1954).
3. S. Chandrasekhar, Proc. Nat. Acad. Sci (USA) 42, 1 (1956)
4. H.P. Furth, et al., Rev. Sci. Instr. 28, 949 (1957).
5. E.N. Parker, Phys. Rev. 109, 1440 (1958).
6. D.R. Wells and R.G. Mills, Proceedings of the International Conference on High Magnetic Fields, November 1-4, 1961, Edited by H. Kolm, et al. (The MIT Press and John Wiley and Sons, Inc., 1962).
7. K.E. Wakefield, "Design of Force-Free Toroidal Magnets," Plasma Physics Lab., Princeton Univ., NJ (March 1964), Report No. MATT-208.
8. G.E. Marsh, J. Appl. Phys. 68, 3818 (1990)
9. F.C. Moon, "The Virial Theorem and Scaling Laws for Superconducting Magnet Systems," J.Appl. Phys 53 (12), 9112 (1982).

(3.23) "BUCKEYBALL" TRIBOLOGY

Associate Laboratory Director Area: Engineering Research

Principal Investigator: G. R. Fenske, Materials and Components Technology

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$28.6K

Purpose: The objective of this research is to determine whether or not newly discovered molecular forms of carbon, C_{60} and C_{70} , that have been termed Fullerenes or "buckyballs", have any potential for improving tribological (friction and wear) properties of advanced engineering materials.

Approach: New molecular forms of carbon were recently discovered. These molecules consist 60-, 70-, (and more) carbon atoms arranged 3-dimensionally in a form of a soccer ball. They have been nicknamed "buckyballs" after **Buckminster** Fuller who pioneered geodesic-shaped structures that look similar to soccer balls. Predictions indicate that buckyball molecules (which are approximately 0.7 -0.8 nm in diameter) can be compressed to a small fraction of their original volume and bounce back to their original volume/structure when the pressure is released. The theoretical predictions indicate that when C_{60} is compressed to one-third of its original height, it is still capable of rolling, thus making it the ideal molecular lubricant.

Conventional liquid-lubricants consist of strings or chains of carbon atoms that break-up under high shear stresses. In contrast, buckyballs appear to remain spherical (or in a deformed spherical shape - i.e. a rugby ball) under high stresses and thus might act as extremely small molecular bearings.

Although buckyballs are predicted to have excellent tribological properties, no experimental research has been performed to prove this hypothesis.

Our approach to this problem is to perform laboratory-scale, pin-on-disc tests to measure the friction and wear of surfaces that have been coated with buckyballs. The research investigates the effects of temperature, applied stress, and time on the friction and wear coefficients of metallic and ceramic components that have been treated with buckyballs.

Technical Progress and Results: The effort on this program during FY-1991 was expended on assessing environmental, safety, and health considerations of performing tribological tests on fullerene substances, designing/procuring environmental chambers to enclose the pin-on-disc apparatus that will be used to test fullerene-coated substrates, modifying a pin-on-disc apparatus for remote operation in a glovebox enclosure, procurement of fullerene compounds for coating substrates, and procurement of pins and discs for tribological tests.

A report documenting safety aspects/concerns of the experimental program was prepared. This report will serve as the basis for a safety review that is currently in progress.

The effort that was initiated this year establishes a sophisticated capability to evaluate the tribological properties of fullerene compounds as a new class of lubricants. Laboratory testing, using the facilities established during FY-1991, will be carried out.

Specific Accomplishments: Because fullerenes are a new class of compounds, their impact on the health and safety of personnel handling them is relatively unknown. Although material safety data sheets (MSDS) recommend treating fullerenes in a manner comparable to carbon black, there is a concern that fullerenes may be harmful if taken internally. Therefore, different environmental enclosures were examined to minimize exposure of personnel to fullerene compounds during the tribological tests. An uncontaminated sealed glovebox was located and is currently being relocated and modified for use in this program.

The pin-on-disc tribometer that will be placed inside of the glovebox is being modified for low-load applications and a heating stage is under construction to permit testing at temperatures up to 600°C.

Sources of fullerene compounds were also identified. Based on costs and effort, it was decided to purchase fullerene compounds from an outside firm specializing in fullerenes rather than obtaining these compounds on-site.

Metallic and ceramic pins and discs were also specified and procured for the tribological tests.

(3.24) ADVANCED COMPUTING METHODS FOR GENOME SEQUENCING

Associate Laboratory Director Area: Energy, Environmental and Biological Research

Principal Investigator: R. Overbeek, Mathematics and Computer Science Division

Funding History:

FY 1989	\$136.8K*
FY 1990	\$29K and 179.8K**
FY 1991	\$81.3K

Purpose: The purpose of this project is to apply logic programming techniques and to exploit parallel processing to help gather, interpret, and manipulate genetic maps and sequence data. The acquisition of massive amounts of data presents a significant challenge. Moreover, analyzing such data requires flexible tools, in particular graphical tools, that make it easy to integrate and display data.

Approach: The logic programming language Prolog was used to explore different approaches to designing tools for large-scale sequencing and for graphical representation of genetic maps. We also explored the feasibility of using parallel processing for the computation of large phylogenetic trees.

Additional participants in this work include Ray Hagstrom of Argonne's High Energy Physics Division and H. Matsuda of Japan.

Technical Progress and Results: We designed and constructed a prototype robot to allow the acquisition of massive amounts of hybridization data. The robot was used to simulate the spreading of spots caused by energy diffusion. We also simulated certain heuristic sequence-reconstructing algorithms. Considerable progress was made toward formulating a rigorous theory of oligo-hybridization.

Our efforts on general-purpose tools for graphical representation led to the development of GenoGraphics and PC GenoGraphics, together with a Prolog-based natural language query mechanism and database. The GenoGraphics codes were demonstrated in conferences at London and San Diego and are currently being used in approximately 40 laboratories.

We continue to interact at various levels with biologists, including W. Gilbert (Harvard), C. Woese (U. of Illinois), and F. Blattner (U. of Wisconsin).

We continued work with C. Woese and G. Olsen at the University of Illinois at Urbana on techniques to implement their database of sequence data. In particular, we developed logic programming tools that aid in extracting and manipulating data. The database is accessible electronically.

Other areas of research included: (1) demonstration of the feasibility of using parallel computing technology for the computation of large phylogenetic trees, (2) investigation of the secondary structure of the AIDS virus, and (3) study of covariance analysis of alignment sequences.

Specific Accomplishments: Much of this work is being prepared as preprints for eventual publication in the open literature.

We also attended or participated several meetings, including (1) Human Genome Program Workshop, Albuquerque, N.M., February 17-21, 1991; (2) Human Chromosome 21 Meeting, Denver, Colorado, May 10-11, 1991; and (3) as a panel participant, Human Genome Meeting 11, London, England, August 18-22, 1991.

* In FY 1989, the funded project was titled "Fifth Generation Technology in Molecular Biology."

** In FY 1990, two projects were funded, titled "Application of Fifth Generation Technology" and "Molecular Biology and Genome."

(3.25) **LOGIC-BASED SYSTEMS FOR AUTOMATED X-RAY
CRYSTALLOGRAPHY**

Associate Laboratory Director Area: Physical Research

Principal Investigator: R. Stevens, Mathematics and Computer Science
 F. Stevens, Biological and Medical Research

Funding History: FY 1989 \$0K
 FY 1990 \$0K
 FY 1991 \$31.6K

Purpose: Our objective was to explore the feasibility of using logic based systems (i.e., automated reasoning and logic programming) to automate the process of x-ray crystallographic structure refinement of biomolecules.

Approach: Many computational problems in molecular biology require modeling and reasoning about constrained systems. A particularly interesting case occurs in the reconstruction of biomolecular structures from x-ray crystallographic data--a highly labor-intensive process requiring many iterations from a probable guess to numerical simulation to comparison with experimental data and subsequent refinement of the predicted structure. The refinement process is currently one of the most severe bottlenecks preventing a major increase number of protein structure solved. With the advent of bright X-ray sources like the APS this problem will only grow worse.

Our approach involves combining automated reasoning methods and parallel simulation to address the problem of deducing a probable structure subject to certain restraints and constraints. Our intention is to offer the crystallographer a set of tools that will significantly reduce the time currently needed for the reconstruction of biomolecular structures from crystallographic data.

Our approach combines numerical simulation with symbolic computation. Parallel versions of molecular dynamics (MD) models such as AMBER will be used as components in a larger system, a system that will use MD when needed and will also apply to the unknown structure rules of bond angles, conserved structures, and similarities to known structures. The use of a symbolic or reasoning program to setup and run parallel numerical simulations and then apply or disregard the results to the refinement of the unknown structure is a novel feature of our approach.

Technical Progress and Results: This effort has just gotten started; however, to date, we have identified three program components needed for an integrated system: a parallel molecular

dynamics system, a parallel macromolecular interaction simulation, and a logic-based intelligent refinement program.

That these various programs need to be parallel is evident from the difficulty of applying MD or nonlinear optimization methods to large molecules on sequential computers. We wish each of these methods to be used in concert--under the control of the logic program--to refine a single structure in as short a time as possible. Each program component is being addressed simultaneously as funding permits.

We have begun a parallel implementation of protein-protein interactions kinetics on the Touchstone DELTA. We have identified the initial numerical components of the combined numerical/symbolic Automated Refinement System (ARS). PROLSQ and AMBER are the nonlinear optimization program and molecular dynamics programs chosen, respectively.

A graduated set of test cases to evaluate our method has been determined.

We have begun development of initial visualization tools for small to medium chains of light immunoglobulin.

Progress has been made on the development of initial test strategy for applying automated reasoning techniques to the refinement problem. Our initial approach is to develop automated capability for the manipulation and composition of Hendrickson's stereochemical restraint functions and the application of these composite functions to control the numerical refinement program PROLSQ

(3.26) **SCALABILITY AND PERFORMANCE ISSUES IN THE MOLECULAR SCIENCES**

Associate Laboratory Director Area: Physical Research

Principal Investigator: R. Stevens, Mathematics and Computer Science
 A. Wagner, Chemistry

Funding History: FY 1989 \$0K
 FY 1990 \$0K
 FY 1991 \$32.1K

Purpose: This project involves investigation of the parallel scalability of *ab initio* quantum chemistry methods, including direct self consistent field (SCF), Hartree-Fock, configuration interaction (CI), and multireference configuration interaction (MRCI) methods on large-scale massively parallel processors (MPP). Performance models will be developed and used to evaluate the architectural suitability of each method. Our primary goal is to understand and to make predictions about which parallel computational chemistry algorithms are appropriate for various MPP systems. In addition, selected methods will be implemented using portable parallel programming techniques to provide a testbed for benchmark computations.

Approach: This project is exploring innovative scalability analysis techniques for handling dynamic load balancing. New fine-grain parallel decomposition strategies will be examined, and the communications requirements determined. Insights gained from this work will be used to devise prototype implementations for the Touchstone DELTA and other parallel computers and may be used to study dissociation pathways of halogenated aromatics (a difficult set of grand-challenge problems) and thus used to verify the correctness of performance predictions on a number of parallel computers.

The initial focus will be on SCF Hartree-Fock methods and will be extended to CI, MRCI, and multipole methods; but where these methods scale poorly, we shall investigate alternative techniques. For each method, we shall explore parallel data decompositions and determine which can best be used on parallel architectures, including MIMD, and heterogeneous machines. This effort will include identification of the main computational kernels, development of analytical performance models, implementation and validation of the parallel kernels on diverse architectures, and proof of effectiveness on problems involving halogenated aromatics.

A fundamental objective of the DOE High Performance Computing and Communications program is to enable the use of teraflop architectures for the solution of Grand Challenge-class problems, including computational chemistry within the next few years. Our proposal is intended to help determine which architecture(s) can be most effectively exploited for computational chemistry applications and to develop the computational techniques necessary to exploit those architectures.

Technical Progress and Results: This work, under way since August 1991, has identified four areas of effort:

- (1) Development of a comprehensive set of performance models for important quantum chemistry methods and to demonstrate which methods have the best parallel scaling properties. In each case we examine a multitude of alternative data decompositions, each allowing us to vary the granularity of the parallel algorithm. From these models (which are in terms of the chemistry problems input and the machine parameters) we can determine the likelihood of obtaining good parallel program efficiency.
- (2) Determination that, in many parallel algorithms, a number of recurring parallel program structures can be found. These recurring structures are called "templates" or "motifs". Often one can describe the complete computation as a composition of these high-level motifs. When this is the case, building the performance models can be simplified by using models of these pre-defined motifs.
- (3) Construction of several existing coarse-grained parallel implementations of these methods have been constructed using a set of tools known as TCGMSG. Part of this LDRD effort is to port these implementations to the more widely available and broader based toolset P4 (both TCGMSG and P4 are derived from the Argonne MONMACS package of tools developed in 1986). This conversion will allow direct testing of the models developed in part one of this work.
- (4) Testing of the specific predictions made with the performance models. A set of benchmark calculations will be assembled and run with a variety of methods.

Work has started on a complete performance model of a fine-grain parallel implementation of direct-SCF Hartree-Fock. In this performance model we assume the Fock-matrix is completely distributed across the machine (i.e., with no replication). All exiting parallel SCF methods replicate the Fock-matrix and thus are limited to basis sets of approximately 400 on machines like the Touchstone DELTA. The distributed Fock-matrix approach should allow up to 1000 basis functions which would significantly improve the range of problems open to direct-SCF methods while maintaining high (85%-97%) parallel efficiency.

A preliminary implementation of a "template"-based SCF test program has been completed. This code will be used to evaluate the technique of using "templates" for parallel code development.

(3.27) VORTEX STRUCTURES IN SUPERCONDUCTORS

Associate Laboratory Director Area: Physical Research

Principal Investigators: H. G. Kaper, Mathematics and Computer Science
D. Malon, Computing and Telecommunications
V. Vinokur, Materials Science

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$37K

Purpose: The purpose of this project is to explore, develop, and implement computational methods for the study of vortex lattice structures and their dynamics in high-Tc superconductors.

Approach: With the discovery of high Tc superconductors, the structure and dynamics of vortex (flux) lines in type II superconductors has become a central issue. Although experimental investigations are well established, theoretical investigations are still in the early stages. We are investigating the structure and dynamics of irregular and regular vortices using mathematical analysis, modeling, large-scale computational algorithms, and parallel programming tools.

Additional participants include M. K. Kwong, G. K. Leaf, and D. Levine of the Mathematics and Computer Science Division and R. Benedek and K. Strandburg of the Materials Science Division.

Technical Progress and Results: Our study of vortex dynamics began with the development of a model of an isolated vortex in the presence of impurities and subject to thermal excitation. The thermal activity was modeled as white noise, and the impurity effects were modeled through the use of Gaussian potentials. The model was implemented on a serial machine; consistency, accuracy, and efficiency tests and modifications were made on this algorithms. This serial algorithm is now being used in a preliminary study of the correlations between temperature and pinning of an isolated vortex in the presence of impurities.

We have also developed a parallel algorithm describing this model, which will be tested on a distributed-memory architecture. We expect to use this experience in parallelization in our development of a parallel multidimensional algorithm describing the dynamics and interactions of multiple vortices.

(3.28) **APPLICATION OF AUTOMATED REASONING TO EQUALITY-ORIENTED REASONING, PROGRAM VERIFICATION, AND CIRCUIT DESIGN**

Associate Laboratory Director Area: Physical Research

Principal Investigator: L. Wos, Mathematics and Computer Science

Funding History:	FY 1989	\$0K
	FY 1990	\$68.2K*
	FY 1991	\$53.9K

Purpose: The purpose of this proposed research is to develop--within the class of linked inference rules--effective automated, equality-oriented reasoning capabilities to capture and generalize the type of argument found in mathematics; formulate strategies to control and markedly enhance the power of linked inference rules; blend the equality-oriented aspects of linked inference with those aspects in which equality plays little or no role, in order to provide a full treatment for set-theoretic reasoning; and develop an extended version of OTTER that will offer scientists the capacity to apply equality-oriented reasoning effectively, especially in the context of circuit design.

Approach: Linked inference rules in which equality plays a small role produce a marked increase in efficiency over reasoning programs using traditional inference rules. Our study has focused on that aspect of reasoning in which equality plays the dominant role. We demonstrated the utility of using our reasoning program OTTER in the context of circuit design.

A major participant in this work was Prof. R. Veroff of the University of New Mexico. Computational Logic Inc. provided sample circuits for testing our approach to circuit design.

Technical Progress and Results: We studied the use of our automated reasoning program OTTER for circuit design. One of the features of OTTER compares proofs with the intention of finding the shortest. Using this feature, OTTER successfully designed various circuits to meet specifications. Further, within the same computer run, OTTER was able to produce improved circuits that involved a minimal number of components.

In the area of linked inference, we produced almost the entire formalism needed for linked inference rules in which equality plays the dominant role. Moreover, we virtually completed the formalism for linked inference that combines the cases in which equality is emphasized and in which equality is irrelevant.

With respect to implementation, we now have available a new linked inference rule called linked hyperresolution.

* In FY 1990, the project title was Application of Automated Reasoning to Set-Theoretic Reasoning and Program Verification. This project comprised the initial development of linked inference and briefly explored its use for set-theoretic reasoning.

(3.29) COMPUTATIONAL SIMULATION OF PROTEIN INTERACTION

Associate Laboratory Director Area: Energy, Environmental and Biological Research

Principal Investigator: F.J. Stevens, Biological and Medical Research

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$21.2K

Purpose: A key technology for the systematic redesign of proteins and polypeptides is the development of computational algorithms capable of quantitatively predicting the affinity and kinetics of protein-protein and protein-small molecule interactions. An essential step in the development of this technological capability is the identification and development of new protein model systems suitable for extended systematic experimental and theoretical study. We have proposed that antibody light chains represent such a model system. The purpose of this project is to establish the computational algorithms required to analyze size-exclusion chromatography data obtained from dynamically polymerizing antibody light chains for the purpose of experimentally determining the affinity and kinetics of their interactions.

Approach: Protein-protein interactions result from complementarity of three-dimensional shapes and favorable juxtaposition of chemical groups provided by amino acid side chains of both molecules involved in the interaction. The total thermodynamic free energy change that occurs when two protein molecules come together determines the affinity of interaction, and is a function of both the structures of the molecules and the composition of the solvent. The kinetics of interaction are also determined by structure and solvent.

Therefore, quantitative analysis of protein-protein interaction is a means of studying details of protein structure, i.e. by providing an experimental test system for computationally obtained predictions of protein affinity and kinetics. Antibody light chains are capable of monomer-monomer interactions to form dimers, and dimer-dimer interactions to form polymers. These interactions are chemically independent but functionally linked, i.e. polymer formation is dependent upon dimer formation, and dimers are likely stabilized by the formation of polymers.

The size-distribution of molecular aggregates in a sample of a protein capable of one or more interactions is determined by the affinity constants and the concentration of protein. Size-exclusion chromatography separates macromolecules on the basis of size; thus, the elution profile obtained from a sample of antibody light chains is determined by the initial protein concentration and the four kinetic rate constants which determine the two independent interactions. Therefore, we are developing computer simulation algorithms to model the concentration dependence of protein chromatography elution profiles as a means to obtain values of the kinetic parameters.

Technical Progress and Results: The dynamic simulation of the multiple concentration dependent interactions occurring during the chromatography of antibody light chains is an extremely computationally intensive challenge. A simplified version of an algorithm developed by extension of previous work required several hours of computer time -- on a MicroVax system capable of approximately 1,000,000 calculations per second. Therefore, our first goal is to adopt this simulation for execution on massively parallel supercomputers, such as the Intel Touchstone Delta to which we have access provided by Argonne's participation in the Concurrent Supercomputing Consortium.

Specific Accomplishments: As indicated above, we have developed a preliminary algorithm that has demonstrated qualitative agreement with experimentally observed elution patterns of interacting antibody light chains. Significant effort was directed to breaking the original multi-page fortran program into small independent functional modules, providing a library of "tools" that are called from what is now a much simpler, and conceptually clearer, master program. By this means development, validation, and documentation of this program and future programs will be facilitated. In addition, the program will be more accessible to collaborators and other users. In collaboration with Rick Stevens of the Mathematics and Computer Science Division, we are now progressing with the implementation of a parallel version of this program. We anticipate initial testing of this algorithm on the 30 billion calculation per second Touchstone Delta supercomputer during the week of 11/4/91.

Publications include:

Results of this simulation development will be included in "Polymerization of immunoglobulin domains: a model system for the development of facilitated macromolecular assembly," by F.J. Stevens, to be published in the journal, Nanotechnology. This publication will follow presentation at the Second Foresight Conference on Molecular Nanotechnology, Palo Alto, CA (Nov 6-9,1991).

(3.30) HUMAN GENOME SEQUENCING BY HYBRIDIZATION

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigators: R. Drmanac, R. Crkvenjakov, Biological and Medical Research

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$300.1K

Purpose: The purpose of this proposal is to aid the establishment at Argonne National Laboratory of the sequencing-by-hybridization (SBH) project of the Human Genome initiative by providing funds for the methodological development of sequencing-by-hybridization technology. The effort at miniaturization of SBH will principally explore the original approach to binding nucleic acids to matrixes, using micro beads as obligatory intermediates.

Approach: The Department of Energy's DNA sequencing effort is proceeding through both the evolution of conventional techniques and the development of novel methods. The former are based on the classical techniques of Sanger and of Maxam and Gilbert, which are rate-limited by a lengthy fractionation step and the labor-intensive process of sequencing longer DNA fragments. In contrast, novel methods promise to provide sequence data at much higher rates.

A novel method pioneered by the co-PIs is the sequencing-by-hybridization strategy. This is the only new method that has successfully passed a proof-of-concept test. This method does not have a fractionation step; rather, the sequence data is accessed within recombinant DNA clones by hybridization with short DNA oligomers. The current success depends fundamentally on algorithms for the assembly of extended DNA sequences from the oligomer content of the clones and in methods for efficiently acquiring the oligomer data. Much of the further development in SBH will involve automating the biochemistry, mechanical processing, and data capture.

This has the benefit of supporting Drmanac's new concept of partial SBH, in which valuable data on many clones could be obtained more rapidly and with lower cost and effort. Partial SBH is analogous to sieving, in which nuggets of genome sequence data will be obtained early while the complete sequence will come later as complete SBH accesses the finer levels of information.

Future development of this technique includes plans for extensive miniaturization with data readout by fluorescence microscopy from matrix-bound oligomers able to capture fragmented DNA from a clone. It offers the advantage of simultaneous reactions of synthesis or binding of nucleic acids to physically or chemically different beads, potentially allowing economical production of matrices of significantly higher complexity. This capture at a matrix position of a known oligomer will confirm the presence of a corresponding sequence in the clone, providing all the oligomer information on a single clone simultaneously. Arrays with longer oligomers will allow interrogation of larger clones, with a concomitant decrease in the size of the libraries that must be prepared.

Satisfactory discrimination so far has not been obtained with oligonucleotides attached to a support. Besides excluding the possibility of the negative influence of steric factors on hybrid formation, there is a chance to improve discrimination with bound oligonucleotides if a longer wash at low temperature is performed, just as in the case of bound DNA fragments or by using probes containing polyinosine tails. Technologically, the bound-oligonucleotide approach becomes more important if longer oligonucleotides are used.

Technical Progress and Results: Fiscal year 1991 was devoted to bringing the SBH research group to Argonne National Laboratory and establishing a productive laboratory. This was accomplished in less than eight months. The newly painted laboratories and offices were furnished with necessary equipment, including the two major instruments and personal computer network.

Smooth integration is evident from the results we have obtained that demonstrate (1) the power of oligomer hybridization on blind sequencing of unknown DNA and (2) the advantages of a new algorithmic principle that similar sequences help each other in sequence reconstruction. The limits of reproducibility and efficiency of SBH have been extended in the process. These results provide a base from which the investigation of oligomer preparation and hybridization on beads can be profitably explored in FY 1992.

Specific Accomplishments: Complementary funding for the other components of the SBH project have been obtained from DOE for FY 1992.

Publications include:

"Partial Sequencing by Oligohybridization: Concept and Application in Genome Analysis," Drmanac, R., Lennon, G., Labat, I., Drmanac, S., Crkvenjakov, R., and Lehrach, H., in Proceedings of the First International Conference of Electrophoresis, Supercomputing and the Human Genome, ed. by Cantor, C. R. and Lim, H. A. (World Scientific Publishing Co., Singapore) 1991.

"Sequencing by Oligonucleotide Hybridization: A Promising Framework in Decoding of the Genome Program?", Drmanac, R., Labat, I., Strezoska, Z., Paunesku, T., Radosavljevic, D., Drmanac, S., and Crkvenjakov, R., in Proceedings of the First International Conference on Electrophoresis, Supercomputing and the Human Genome, ed. by Cantor, C. R. and Lim, H. A. (World Scientific Publishing Co., Singapore) 1991.

"An Algorithm for the DNA Sequence Generation from K-tuple Word Contents of the Minimal Number of Random Fragments," Drmanac, R., Labat, I., and Crkvenjakov, R., *Journal of Biomolecular Structure and Dynamics*, 5:1085, 1991.

"DNA Sequencing by Hybridization: 100 Bases Read by a Non Gel-based Method," Strezoska Z., Paunesku, T., Labat, I., Radosavljevic, D., Drmanac, R., and Crkvenjakov, R., *Proceedings of the National Academy of Science USA*, in press.

(3.31) INOSINE 5-MONOPHOSPHATE DEHYDROGENASE GROWTH CONTROL

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigator: E. Huberman, Biological and Medical Research

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$44.9K

Purpose: An understanding of the distribution and expression of genes involved in the control of cell growth is essential in defining the mechanisms involved in normal cell growth and in identifying the changes in these processes that are responsible for malignant growth or other disease states. We have developed specific monoclonal antibodies and cDNA probes for inosine 5'-monophosphate dehydrogenase (IMPDH), an enzyme involved in the control of cell growth. To investigate if increased expression of IMPDH has a role in the development of malignancy in humans, we examined the levels of IMPDH mRNA and the cellular enzyme in samples of normal and malignant brain tissue using the specific cDNA and monoclonal antibody probes.

Approach: Enzymes involved in the regulation of cell growth may mediate some aspects of the development of malignancy. During tumor development, preneoplastic cells acquire a malignant phenotype and with it, a clonal growth advantage over normal cells. An increase in the activity of enzymes which are associated with enhanced cell growth may be a mechanism by which this growth advantage is achieved.

Inosine 5'-monophosphate dehydrogenase (IMPDH), an enzyme that regulates guanine nucleotide biosynthesis, is involved in the control of cell growth. The essential role of this enzyme in providing precursors for RNA and DNA biosynthesis is indicated by the abrupt cessation of DNA synthesis when cells are treated with inhibitors of this enzyme. The involvement of IMPDH in the regulation of cell growth is derived from the observation that normal tissues that exhibit increased cell proliferation also exhibit increased IMPDH activity. A similar relationship between increased proliferation and elevated enzyme activity has also been found in rat hepatomas having varied growth rates, suggesting that in both normal and malignant cells, the activity is positively correlated with cellular growth rate. However, the rat hepatomas manifested IMPDH activities that were disproportionately higher than those of normal tissue, suggesting that increased IMPDH activity may be associated not only with growth control, but also with malignant transformation or tumor progression.

The level of IMPDH mRNA and cellular enzyme was determined in tissue samples from brain tumors relative to their normal counterparts. Total RNA was extracted from normal brain and tumor tissue. Using Northern blot analysis and a specific cDNA probe, the level of IMPDH

mRNA expression in the tumor tissue was determined relative to that of normal brain. Small pieces of the tumor tissue were placed in tissue culture medium to promote attachment and growth of the tumor cells. These explant cultures were used in cytochemical staining to determine the cellular levels of IMPDH. The cytochemical staining procedure used the monoclonal antibody specific for IMPDH. Immunofluorescent microscopy was used to visualize the specific localization of the antibody. The explant tumor cultures not used in the cytochemical studies are being maintained in the tissue culture facility in an attempt to establish cell lines. Additional tumor tissue not used for these procedures was stored at -70°C for DNA isolation or future oncogene studies.

This project was conducted in collaboration with Dr. Bernard Mirkin of the Children's Memorial Institute for Education and Research, who supervised acquisition of the brain tumor samples. Additional participants included Dr. Frank Collart of ANL, who conducted the Northern blot analysis of IMPDH mRNA expression, and Cynthia Chubb, who performed the immunofluorescence staining.

Technical Progress and Results: We have analyzed 6 tumor samples which have been coded as CM-1 through CM-6. Several of the samples were of sufficient size to allow preparation of the RNA, freezing of a sample for future DNA extraction, and culturing of tissue pieces in an attempt to establish a tumor cell line. The amount of sample CM-3 was estimated at 0.1 g and was used solely for tissue culture procedures. The tumors obtained for this study included neuroblastomas, astrocytomas, and a Ewing's sarcoma.

Northern blot analysis of the total RNA obtained from the tumor samples indicated increased IMPDH mRNA expression in all the tumor samples in comparison to the normal brain tissue samples. These results suggest that the increased activity of IMPDH observed in tumors is a consequence of increased IMPDH mRNA expression. The level of IMPDH mRNA was similar in all of the brain tumors except the CM-6 sample, in which the IMPDH mRNA level was approximately 8-fold higher. DNA is being extracted from CM-6 tumor tissue to determine if the increased IMPDH expression is a consequence of DNA amplification.

To determine if the increase expression of IMPDH mRNA results in increased levels of cellular enzyme, we used the monoclonal antibody to examine cellular levels of IMPDH in cultured cells obtained from the tumor explants. In some cases, these samples represented tumor cell clones, while other samples contained mixtures of tumor cells and normal brain fibroblasts. Immunofluorescent studies of the amount of cellular IMPDH using the specific monoclonal antibody show increased fluorescence of the tumor cells relative to normal brain fibroblasts. This is consistent with the increased mRNA expression which was observed in the tumor samples relative to normal brain, suggesting the level of IMPDH mRNA is an indicator of the amount of cellular enzyme. Several of the tissue explants are still growing in culture and will be used for future cytochemical staining and RNA analysis.

Specific Accomplishments: We have characterized the increased IMPDH mRNA expression in several tumor tissue samples relative to normal brain tissue and used a specific monoclonal antibody to determine the cellular level of IMPDH. These results support the notion of a role for IMPDH in malignant cell growth.

Publications:

"Increased Expression of IMP Dehydrogenase in Tumor Cells," Collart, F. R., Chubb, C. B., Mirkin, B., and Huberman, E. Biochem. Biophys. Res. Comm., in preparation.

(3.32) GENE FUSION TECHNOLOGY

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigator: T. A. Kokjohn, M. Hansen, C. Bebrich, B. Lesht,
Environmental Research

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$49.1K

Purpose: This study initiated an investigation of the potential of gene fusions to act as rapid indicators of environmental contaminants. Gene fusions responding to the presence of a contaminant by emitting visible light were constructed by recombinant DNA (transposition) methodology. The ability of gene fusions to act as sensitive and contamination-specific analytical tools in detecting contamination was assessed.

Approach: At present, the remediation of environmental contamination requires the extensive use of laborious, time-consuming, and expensive chemical analyses. A substantial portion of remediation costs is associated with site characterization involving laboratory analysis. Development of rapid analysis methods that can be used in the field would accelerate remediation and environmental monitoring projects and would significantly reduce costs.

Recent developments in molecular biology have led to a detailed understanding of the control of gene expression. It is now clear that many organisms precisely control the expression of certain genes, leaving them inactive until they are needed. For example, bacterial cells will activate the genes needed to transport and metabolize lactose only when lactose is present in the environment. Widely varying species of bacteria have been shown to possess genes that are inducible by environmental contaminants. The induced genes may allow a cell to detoxify a compound or, in some cases, to actually metabolize it.

Continued exploration of the basis for control of gene expression in both prokaryotes and eukaryotes has driven the development of new molecular tools for analysis. One of the most powerful tools available today for expression studies is gene fusion. The use of recombinant DNA procedures or laboratory-engineered transposable elements allows the formation of chimeric structures in which elements from two genes are fused. Thus, the portion of a gene that responds to the presence of a contaminant can be combined with another gene whose product is easily detected (the reporter). The fusion structure will then report induction in response to the presence of the contaminant by production of the readily assayable gene product. For example, fusing the toluene-inducible gene(s) of the TOL plasmid with the beta-galactosidase gene will cause beta-galactosidase to be produced whenever toluene is present. The production of beta-galactosidase is easily detectable because under the proper conditions the cells turn blue.

The use of gene fusions as environmental indicators of contaminants has not been extensively

pursued because technical difficulties arise in detecting the reporter gene products. The development of the *lux* fusion indicator system has provided a simple detection scheme that might be useful for site characterization applications in the field. When they are fused to a contaminant-inducible gene, the *lux* genes produce visible light in response to the presence of that contaminant. Application of this technology to environmental assessment and monitoring is feasible and could substantially save costs and time.

The overall goals of this effort were to develop new methods and techniques for genetic fusion construction by using the *lux* reporter and to apply the new technology to real environmental problems. By conducting experiments with the fusions under realistic conditions, we hoped to rigorously establish whether such technology is useful for environmental characterization.

Technical Progress and Results: This is a new project with work conducted only in FY 1991. Experiments began in May 1991.

Development of fusion construction protocols. To develop fusion construction protocols, we obtained the *lux* transposon delivery system, Tn4431, developed by Dr. C. Kado of the University of California. This system consists of the transposable element Tn4431 in a broad-host-range plasmid. We have found that this delivery system is reliable only in *Escherichia coli*, severely limiting its usefulness. Attempts to transfer the *lux* delivery system into new host species of bacteria to construct novel fusions were unsuccessful. Transfer of the delivery plasmid into *Pseudomonas aeruginosa*, *P. putida*, and *P. cepacia* occurred at very low levels, below the limit of detection of one event per 10^9 donor cells. The failure of transfer is probably not due to restriction effects. Attempts to use restrictionless strains of *P. aeruginosa* and to perform matings under environmental conditions in which the DNA restriction system is inactive also were unsuccessful.

Because of the limitations of the delivery system, we constructed a fusion of the *lux* transposon to another broad-host-range plasmid, pKT240. This plasmid is mobilizable and readily transferable to *Pseudomonas*. The new plasmid is designated pANL1. In addition, another construction, designated pANL2, was isolated, representing Tn4431 resident on plasmid pRK2013. Although this is not a broad-host-range plasmid, it has been widely useful as a "suicide" transposon delivery system in which the plasmid is mobilized into the target host but is unable to replicate. Delivery of the transposable element in this case is effected by transposition. The ability of these new constructs to deliver Tn4431 is under investigation.

Construction of gene fusions inducible by mercury contamination. By using the transposon delivery system in *E. coli*, we were able to construct fusions of the *lux* genes to the mercury detoxification genes of the transposable element Tn501. Cells of *E. coli* HB101 containing these constructions produce visible light in the presence of mercuric chloride. The actual site of fusion of the *lux* genes in the *mer* operon has not yet been mapped.

The precise sensitivity of mercury detection by the fusion constructions is currently unknown. The fusion strains do produce light when they grow in the presence of 20 parts per million (ppm)

mercuric chloride and no light with concentrations of 2.5 ppm or lower. The fusions will be moved into other strains of *E. coli* known to be better producers of light from the *lux* genes to determine if the lower limit of detection may be extended. In addition, because Tn501 transposes in the presence of mercury, cells containing fusions and incubated in low levels of mercuric chloride may increase their light production over time, enhancing the sensitivity of detection. This possibility is under investigation.

Evaluation of the potential of DNA-damage-inducible fusions to indicate environmental contaminants. Existing gene fusions to *E. coli* SOS genes were evaluated for their potential to act as indirect indicators of contaminants capable of causing DNA damage. We tested the ability of 2,4,6-trinitrotoluene (TNT), 2,4-diaminotoluene, and 2,6-diaminotoluene to induce activity of *sfiA::lacZ* and *mucA::lacZ* (DNA-damage-inducible) fusions. Our experiments indicate that these compounds are weak inducers of DNA damage genes at best. Therefore, as they are presently constructed, DNA-damage-inducible fusions are of little use for environmental screening of TNT and related compounds. However, other genes that may be useful for this task will be tested in future work. In addition, preliminary experiments suggest that toluene-dioxygenase-expressing plasmids and DNA-damage-inducible fusions together may serve as a bioindicator system for trichloroethylene.

Implications of this project. This project has developed significant new capabilities for research at Argonne with implications and applications far beyond environmental detection and monitoring of contaminants. Controlling and accelerating bioremediation, whether the activities are performed *in situ* or in a bioreactor, presents major technical challenges. The development of gene fusion indicators will allow quantitation of target analytes; will provide novel, rapid methods to determine cell activity at a glance, to rigorously assess the precise nutrient requirements of remediative microbial populations even in complex environments such as soil; and will provide an important predictive capability of the relative difficulty and time requirements for specific bioremediation projects. This combination of the tools of molecular biology and microbial ecology offers a powerful, integrated approach to the challenges of bioremediation.

We will apply these and other gene fusions to the operation of remediative bioreactors and the design of future experiments. The feasibility of modifying the responses of gene fusions to inducing compounds in order to extend their utility, e.g., creating a TNT detection system, will be examined. The ability of fusions to indicate the availability of nutrients in soil slurry bioreactors will also be tested.

Specific Accomplishments: This effort has produced several new fusion constructions. (1) A fusion of the *lux* genes to the broad-host-range plasmid pKT240 (designated pANL1) may provide a new vector to easily extend the *lux* system to a wider variety of bacterial species. This construction will also be useful in examining the ability of cells in bioreactors to express constitutive genes and in gauging the relative levels of stress of the cells present in bioreactors. (2) A new fusion to the plasmid pRK2013 (pANL2) will provide an alternative *lux* delivery system. (3) A mercury-responsive gene fusion derived from transposon Tn501 has been constructed (pANL3).

(3.33) **MODELING AND REMOTE SENSING OF GLOBAL TERRESTRIAL ECOSYSTEMS**

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigators: M. L. Wesely, Environmental Research; A.P. Campbell,
Environmental Assessment and Information Sciences

Funding History: FY 1989 \$*
 FY 1990 \$0K
 FY 1991 \$313K

Purpose: This work is designed to develop methods for the modeling and remote sensing of global terrestrial ecosystems to evaluate the effects of potential climate change on biota and the consequential feedbacks to the earth's climate system. In Environmental Research (ER), research concentrates on simulating physiological and biophysical processes of vegetation to allow the quantitative description of biosphere-atmosphere interactions and on incorporating the simulations into atmospheric General Circulation Models (GCMs). In Environmental Assessment and Information Sciences (EID), research focuses on the use of hyperspectral imagery for the detection and monitoring of global change, particularly at the scale of major earth ecosystems. Hyperspectral imagery provides a much richer data set for analysis than existing satellite imagery and thus allows detection of more subtle changes in ecosystems. Techniques established to detect and measure the effects of climate change may ultimately be used in conjunction with the effort to model global terrestrial ecosystems to provide data for planning and gauging international responses to changes that might occur.

Approach: The modeling of global terrestrial ecosystems is being carried out by gathering extensive ecological information and incorporating it into a framework that can be used by an existing GCM or other large-scale numerical models. The process of scaling up from small to large spatial areas involves several steps and is quite complicated. Land cover types, each with separate responses to environmental conditions and with various types and rates of atmosphere-biosphere exchanges of mass and energy, must be aggregated into forms that can be used in biogeochemical models for specific biomes to describe both exchange and ecological processes. An existing biophysical model provides the connecting point between biogeochemical models and large-scale climate models, which require extensive parameterization of variables involving atmosphere-biosphere exchange. The overall numerical modeling effort must provide for efficient transfer of environmental and air-surface exchange data among all levels of simulation. Our approach will include an extensive effort to develop the overall modeling framework, but the work's most crucial aspect is the ecological modeling itself. That is, satisfactory descriptions

* In FY 1989 a progenitor LDRD project (funded at \$98.1K) entitled "Greenhouse Effect" is related to the general topic of the current work but not with respect to the specific remote sensing algorithms presently under study.

must be developed for ecological responses in terms of the surface accumulation of carbon, the exchange of greenhouse gases, evapotranspiration, and the basic functioning that affects the viability of competing plant species. Furthermore, the descriptions must be efficiently parameterized so that long-term simulations can be accomplished. Because of the difficulty of this modeling, an established ecologist (Dr. Craig Loehle) was hired late in FY 1991, after an extensive national search, to lead the ecological modeling effort.

The second portion of this work focuses on developing techniques for using advanced remote sensing data to monitor changes in global terrestrial ecosystems. The use of satellite imagery to monitor earth systems has been relatively successful in the fields of meteorology, oceanography, geology, and agriculture, but many uncertainties remain when these existing techniques are applied to ecosystem changes. Hyperspectral imagery, which currently consists of 210 narrow spectral bands (10 nm) between the long ultraviolet (400 nm) and middle infrared (2500 nm), is used in this study because it provides much more information than existing satellite imagery, which is available in only four or five bands, each of considerable width. Acquisition of hyperspectral imagery from satellites is expected within the next ten years. Recently the Jet Propulsion Laboratory (JPL) developed and flew on aircraft a set of instruments that collect hyperspectral image data. In addition, JPL and the U.S. Engineering Terrain Laboratory (ETL) have used mostly laboratory determinations to compile a database of over 1000 surface spectra, including reflected and emitted energy spectra for a wide variety of natural and man-made surfaces. To be useful, this information must be related to features that occur naturally at the surface of the earth. Because image pixels observed from aircraft and satellite platforms often include returns from surfaces with various proportions of coverage by different types and conditions of vegetation, the spectral responses for a pixel usually do not accurately match the spectra in the database. Our approach to this problem has been first to develop tools to allow automatic handling of the huge amounts of data collected and then to use the tools to manipulate the data in various ways and examine relationships between measured surface spectra and those compiled in the database.

Technical Progress and Results: This work began in FY 1991. A preliminary scheme for computation of terrestrial biogeochemical trace gases in the context of a GCM was developed by Dr. Norman Miller. The components are a GCM that provides a medium-resolution (e.g., one degree latitude by one degree longitude) simulation of atmospheric circulation; a procedure for identifying regions of defined homogeneity of surface type within GCM grid cells; a set of surface process models to be run within each homogeneous region, including a biophysical model (the Biospheric Atmospheric Transfer Model or BATS) and a biogeochemical model; an interpolation-integration system that transfers information between the GCM and surface process models with finer resolution; and a interactive data array based on a geographic information system (GIS). Ecological modeling began in late FY 1991 after Dr. Craig Loehle joined Argonne. Unresolved issues about methods for dealing with spatial heterogeneity were addressed, and planning began on a scheme to develop new parameterizations involving the interfacing of terrestrial processes with climate processes.

With the aid of a consultant, Mr. David H. Slade, a plan has been developed to widen Argonne's contacts with the global modeling community, coordinate activities within Argonne on global climate change, and develop strong collaborative proposals on global change research.

Progress on remote sensing included (1) acquisition from ETL of an energy spectra database and its installation on a machine-readable database at Argonne; (2) design of an easy-to-use data access system that allows manipulation of the data, including matching new field data to spectra in the database with a neural-network-based pattern matcher; and (3) construction of a working prototype data analysis system that allows the database to be used in support of the investigations of surface response signals by comparison with the base data. The prototype system allows various strategies to be employed in matching field data with the database and in building composite spectra, which is done automatically because manual manipulation of the data is not practical. The work that remains to be accomplished includes the following: (1) developing several more sophisticated algorithms for combining the test spectra in the database into synthetic spectra; (2) training the neural network to recognize general elements, e.g., a "stressed environment"; and (3) developing synthetic spectra that might correspond to various changes in the signals from ecosystems of interest. After several test cases have been produced and analyzed, they will be used to demonstrate the system's capabilities to potential sponsors of further research.

Specific Accomplishments:

Manuscripts for publication:

"Landscape Habitat Diversity: An Index," C. S. Loehle and G. Wein, work mostly done elsewhere but with final analysis at ANL, to Ecology.

"Rescaled Box-Counting for the Topological Analysis of Spatial Data," C. S. Loehle, manuscript undergoing internal review.

"Extrapolation of Transect Data to Two Dimensions: Necessary and Sufficient Conditions." C. S. Loehle, manuscript undergoing internal review.

"Hierarchical Framework for Coupling a Biogeochemical Trace Gas Model to a General Circulation Model," N. L. Miller and I. T. Foster, manuscript undergoing internal review, to be submitted to Chemosphere in Nov. 1991.

Presentations:

"Framework for a Global Biogeochemical Trace Gas Model Coupled to a GCM," N. L. Miller Atmospheric Chemistry Division Seminar, Boulder, CO, 19 Sept. 1991.

"Framework for a Global Biogeochemical Trace Gas Model Coupled to a General Circulation Model," N. L. Miller, abstract and presentation scheduled for the NATO Advanced Research Workshop on the Atmospheric Methane Cycle: Sources, Sinks, Distributions, and Role in Global Climate Change, Mt. Hood, OR, 6-11 Oct. 1991.

(3.34) CANCER RISK ASSESSMENT BASES

Associate Laboratory Director Area: Energy, Environmental and Biological Research

Principal Investigator: D. Streets, Environmental Assessment and Information Systems

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$40.9K

Purpose: The objective of this program is to critically examine the procedures currently used to identify and characterize carcinogens and the approach to using this information in exposure assessments to establish standards or other criteria for their control. This examination of current methods will be used as the basis for demonstrating the value of initiating a research and development program to develop new techniques that reduce the present uncertainties.

Approach: Overall, the approach is to evaluate the regulatory process for key substances encountered in the DOE environmental restoration program and then to generalize the results and proposed research and development program for potentially wider application. As a first step in this approach three substances, benzene, PCBs and asbestos were selected as the focus of the evaluation effort. The experimental and analytic techniques used to characterize the carcinogenic potential of these substances were reviewed. Uncertainties due to the nature of the techniques or their specific application were evaluated and techniques identified that offer potential improvement in the information base for regulatory decisions. Techniques for estimating exposures to carcinogens were also evaluated and methods of estimating the value of decreasing uncertainties in the regulatory process were reviewed.

Technical Progress and Results: A preliminary draft report on the review findings has been prepared and circulated internally for comments. Completion of this report has been hindered by the departure of two of the principal contributors to the effort.

Specific Accomplishments: The thinking and team development resulting from this program has contributed to development of several research projects.

Development of an exposure pathway model that includes both radiological and chemical hazards. The model is to be used in evaluating risk from contaminated DOE facilities. Funding is being provided by DOE/EH.

Estimation of cancer risk from DOE facilities before and after cleanup actions. The evaluations are underway for three major DOE facilities, and discussions are being conducted regarding evaluation of two additional facilities. Funding provided by DOE/EM.

Development of risk assessment strategy and related data base for asbestos management at DoD facilities. Preliminary planning funding provided by U.S. Army C.O.E.

In addition, one of the program leaders participated in two DOE committees on development of risk-based standards. Sponsored by DOE/EH and DOE/EM.

(3.35) REMOTE SENSING AND GLOBAL CHANGE

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigators: D. Streets, J. Krummel, Environmental Assessment and Information Sciences

Funding History:

FY 1989	\$0K
FY 1990	\$0K
FY 1991	\$9.9K

Purpose: The purpose of this project is to identify, evaluate, and test methods of quantifying global environmental changes in order to develop a capability to utilize remote sensing data for research on global change and global warming. The project will demonstrate that the usage of advanced technology (remote sensing by satellite platforms), new spatial pattern algorithms applied to ecosystem data bases, and geographic information systems (GIS) can enhance fundamental understanding of how humans alter regional, continental, and global land cover (e.g., vegetation) patterns.

Approach: To determine the effects of large-scale human alteration of vegetation patterns requires an understanding of the rate at which these changes are occurring and a methodology to quantify the pattern of heterogeneous ecosystem processes over large geographic areas. Central to this problem is the application of pattern recognition algorithms to remote sensing data bases which have been collected at the same location over several decades.

The Environmental Assessment and Information Sciences Division (EID) presently has the computer hardware and software and staff capability to process and analyze these very large data bases. A raster GIS can manipulate the spatial attributes and reflectance categories of remote sensing data bases. The GIS, combined with statistical analysis software and pattern recognition algorithms that operate on ANL mainframe and high performance computers, provides the necessary tools to quantify vegetation change and spatial patterns over large geographic areas. EID staff have gained considerable experience in the development and application of these tools to ecological modeling, environmental restoration, and data base development for environmental mitigation. However, to date, all studies have focused on relatively small landscapes (<10,000 hectares). EID staff have a window of opportunity to apply this knowledge and expertise to regional, continental, and global land cover and vegetation data bases in order to become a contributor in the emerging research area of global change and global warming.

Technical Progress and Results: Fiscal year 1991 work addressed data availability and quality of the multi-spectral scanning (MSS) information acquired from the EOSAT Landsat remote sensing satellites. While MSS data has been acquired continuously from 1973 through the present, most of the scenes (area covered by a single satellite image) have not been processed by EOSAT. In addition, scene quality (e.g., the spectral reflectance) and cloud cover must be

examined for the available processed data to determine if the data can be used in a land cover change detection study.

To determine rates of change in global land cover conditions, study regions were chosen as representative samples of world biomes. The study regions included Mexico City and the surrounding region, the state of Rondonia in Brazil which incorporates portions of the upper Amazon River Valley, a series of scenes from Chad that comprise a transect from the Sahara through the Sahel, the lower Mississippi River Valley in Mississippi and Louisiana, the "golden triangle" of Northern Thailand and the Nile River delta in Egypt. For each study region, a computer printout of all available MSS scenes from 1973 through the present was obtained from EOSAT. The listing included information on the specific path and row number of the scenes, scene quality and percent of the scene obscured by clouds. Based on the processed information, satellite photographic data, which included scenes with the same path and row number, but covering a time series from 1973 through the present, were ordered from EOSAT.

The photographic information was analyzed to determine if each scene contained the appropriate land cover data (e.g., forest conversion to agricultural production) and the location of the cloud cover. Based on this screening of the Landsat remote sensing data, Rondonia, Northern Thailand, the southern Mississippi River Valley and Chad were considered for further analysis. The initial screening also indicated that the rate of forest loss due to agricultural conversion in southern Mississippi flood plain forests is similar to that occurring in the developing areas of the world.

Specific Accomplishments: The work conducted under this LDRD proposal has been linked to a study conducted by ANL, the East-West Center in Hawaii, and Chaing Mai University, Thailand, that is being funded by the U.S. Man and the Biosphere Program.

(3.36) **DEGRADATION OF HAZARDOUS CHEMICALS USING THERMAL AND BIOLOGICAL TREATMENT**

PART I: RATE STUDY OF THERMAL DESTRUCTION OF SELECTED HAZARDOUS CHEMICAL SURROGATES UTILIZING FTIR ANALYSIS

PART II: BIODEGRADATION OF HAZARDOUS WASTES USING THE WHITE ROT FUNGUS PHANEROCHAETE CHRYSOSPORIUM AND ITS LIGNIN PEROXIDASE

Associate Laboratory Director Area: Energy, Environmental and Biological Research

Principal Investigators: Part I: M.J. McIntosh, Energy Systems
 J.C. Demirgian, Analytical Chemistry

 Part II: S.P. Tsai, R. Venkatadri, Energy Systems
 S.N. Kakar, R. D. Coleman, Environmental Research

Funding History: FY 1989 \$0K
 FY 1990 \$274.6K
 FY 1991 \$300.3K

Part I:

Purpose: Fourier Transform Infrared Spectroscopy (FTIR) has the potential to analytically resolve and quantify multiple chemical components in a gaseous mixture. Incinerator emissions can contain many hazardous or obnoxious products of incomplete combustion (PICs). Demonstration of FTIR's ability to resolve PICs from incinerator emissions and to use this to characterize incinerator operating conditions is the purpose of this project.

Approach: Incineration is a preferred treatment technology in the management of both hazardous and non-hazardous wastes. However, there is concern about the safety of incinerator air emissions, since the emissions can contain unburned hazardous materials and toxic PICs, and there is no on-stream method which can detect them.

This study uses FTIR to monitor emissions from a small laboratory incinerator. The feasibility of FTIR as an emissions monitor for incinerators is evaluated and potential problems for on-site monitoring are explored.

A laboratory-scale hazardous waste incinerator is coupled directly, via heated sampling lines, to a heated long-path cell combined with an FTIR analyzer. Toluene and chlorobenzene are selected as hazardous surrogates to be incinerated in a methane-air flame. Methane, toluene, benzene, chlorobenzene, hydrogen chloride, and carbon monoxide in the flue gas are simultaneously analyzed. The incinerator is operated at various conditions to simulate both normal and abnormal conditions in industrial incinerators to test the ability of the system to detect concentration changes in the emissions.

Technical Progress and Results: Fiscal year 1990 was devoted to the purchase of Fourier transform infrared spectrometer, long-path cell and computer system, and to the design and fabrication of a laboratory scale incinerator. In addition, a comprehensive library was prepared for use on analysis of toluene and chlorobenzene and their products of incomplete combustion.

In fiscal year 1991, Dr. Z. Mao, associate investigator, was hired; and the incinerator system was tested and integrated to a heated, long-path cell (LPC) via heated sampling lines. Linearity, precision, and detection level of the system for selected target analytes were determined. Operating conditions for complete combustion of methane in the laboratory incinerator were identified with FTIR/LPC as an emissions monitor. Both toluene and chlorobenzene were incinerated in the methane-air flame.

Two types of experiments, steady and unsteady, were conducted. In the steady experiments, the incinerator was maintained at various stable conditions and the effects of steady state chlorobenzene were studied. In the unsteady experiments, the incinerator was first set at a condition, under which toluene or chlorobenzene was completely destroyed. Then the incinerator temperature was continuously decreased and progressive conditions of incomplete destruction were observed. The results from the unsteady were compared to those of the steady experiments and found to be consistent. This result demonstrated FTIR/LPC, as a continuous emissions monitor, can effectively detect failures in incinerator operations and can greatly contribute to the safety of incinerator. Table 1 shows some representative data from the steady experiments.

Interestingly, benzene, as a product of incomplete combustion of toluene and chlorobenzene, was always found in emissions when the incineration was incomplete, even when toluene and chlorobenzene were not detected. This suggests that benzene is an important target compound in continuous monitoring of incineration of toluene and chlorobenzene and possibly other organic aromatics, including hazardous wastes containing chlorinated aromatics.

Future work for development of monitor for on-site use has been identified, such as the reduction of water and carbon dioxide interference, improvement of FTIR/LPC sensitivity, selection of target compounds to be monitored, test of cell materials, and development of computer software for data processing and automation.

Specific Accomplishments: DOE programmatic funding for continuing development of on-line emissions monitor for industrial incinerators is pending. The continuation of the project is expected to begin November 1991.

Publications Include:

"Determination of On-Stream Destruction Removal Efficiency Using Fourier Transform Infrared Spectroscopy," J.C. Demirgian, Z. Mao, M.J. McIntosh, and C.A. Wentz, Proceedings of the 1991 Incineration Conference (Knoxville, Tennessee, May 14-17, 1991) pp. 563-570.

"On-line Monitoring of Chlorobenzene Incineration Using Fourier Transform Infrared Spectroscopy," Z. Mao, M.J. McIntosh, and J.C. Demirgian, submitted to 1992 Incineration Conference.

Part II:

Purpose: The white rot fungus *Phanerochaete chrysosporium* and its extracellular enzyme lignin peroxidase are both known to transform or degrade several hazardous compounds and are, therefore, promising candidates for application in the treatment of hazardous wastes. The treatment application of *P. chrysosporium* and lignin peroxidase is hampered by the lack of processes which yield rapid growth of the organism, high levels of lignin peroxidase, and rapid rates of degradation of hazardous compounds. The objective of this study was to develop an efficient process at the bench scale level for the biodegradation of hazardous wastes and the production of lignin peroxidase using *P. chrysosporium*.

Approach: Two concurrent approaches, bioreactor design and testing, and fungal strain development, were employed. In bioreactor development, two bioreactor systems, a hollow fiber reactor and a silicone tubing bioreactor, were evaluated. Batch experiments were conducted to optimize the production of lignin peroxidase by *P. chrysosporium* in the silicone tubing reactor, which used silicone membrane tubing for the attached growth of *P. chrysosporium* as a biofilm and for oxygenation. Pentachlorophenol (PCP), a priority pollutant, was chosen as a surrogate hazardous waste and its biodegradation was studied in the silicone tubing reactor.

In fungal strain development, classical genetic techniques were used to generate and isolate mutant strains that are hyperproducers, super secretors, or nitrogen-deregulated, with the initial emphasis being on the nitrogen-deregulated mutants.

Technical Progress and Results: In Fiscal year 1990, the hollow fiber bioreactor and the silicone tubing bioreactor were designed, constructed, and tested. The silicone tubing bioreactor was found to be more promising and chosen for further development. Also, the protocols for fungal strain development, such as mutation conditions and isolation procedures in plate cultures, were developed.

In Fiscal year 1991, the silicone tubing reactor was further studied for lignin peroxidase production by *P. chrysosporium*. Consistent growth of the organism as a biofilm followed by production of high levels of lignin peroxidase were obtained. Surface area of the silicone tubing and biomass concentrations were studied to maximize lignin peroxidase production. A 1.7-fold increase in the surface area of the silicone tubing resulted in a 1.5-fold increase in the maximum lignin peroxidase activity obtained. The optimal biomass concentration was determined, which yielded a maximum lignin peroxidase activity of 195 units per liter (U/L). These optimal conditions were then used to study PCP degradation. The disappearance of PCP, introduced at 20 mg/L to the reactor during the enzyme production phase, was complete in less than 46 hours. The mechanism of PCP degradation seems to be a combination of: (1) oxidation by extracellular lignin peroxidase and (2) adsorption followed by transformation by surface-bound enzymes or transport across the cell membrane followed by transformation by intracellular enzymes.

Conidia were treated with ultraviolet light or gamma rays under conditions that yielded survival rates of 0.2-2.0%, which resulted in good mutant yields. Several million conidia were irradiated and thousands of colonies were screened for deregulated mutants on high-nitrogen media plates. Over two hundred colonies of putative deregulated mutants were further screened. About six colonies have consistently shown ligninolytic activity under high nitrogen conditions. These mutants have been purified to homogeneity through serial cultures for 8-10 generations and through conidiation. One of the mutants being studied further has shown, under high nitrogen growth conditions, desirable characteristics, such as early production of lignin peroxidase, high enzyme activity, and improved enzyme stability. The highest activity obtained has been up to 280 U/L and production up to day 17 has been observed with this mutant.

Specific Accomplishments: Negotiations for program funding with Inland Steel Industries for continuation of this work is in progress.

Publications Include:

Venkatadri, R. and Tsai, S.P., "Application of the White Rot Fungus *Phanerochaete chrysosporium* for Hazardous Waste Treatment." Informal internal report, October, 1990.

Venkatadri, R. and Tsai, S.P., "Production of Lignin Peroxidase and Degradation of Pentachlorophenol by *Phanerochaete chrysosporium* using a Fixed Film Bioreactor," Presented at the AIChE Summer Meeting, Pittsburgh, Pennsylvania, August 19-21, 1991.

Venkatadri, R. and Tsai, S.P., "Production of Lignin Peroxidase and Degradation of Pentachlorophenol by *Phanerochaete chrysosporium* using a Fixed Film Bioreactor," manuscript in preparation.

Table 1 Data for Destruction of Chlorobenzene at Various Conditions

T (°C)	11-1	11-2	11-3	10-1	10-2	9-1	9-2	8-1	8-2
Feeds:									
Primary air (cm ³ /min)	1200	1200	1200	1200	1200	1200	1200	1200	1200
Secondary air (cm ³ /min)	6324	5162	2600	6324	5162	6324	5162	6324	5162
Auxiliary O ₂ (cm ³ /min)	0	1249	718	0	1249	0	1249	0	1249
Methane (cm ³ /min)	436	436	436	436	436	436	436	436	436
Chlorobenzene (g/min)	0.0631	0.0692	0.074	0.068	0.0708	0.0659	0.0723	0.0669	0.068
Excess O ₂ ratio	1.64	2.65	1.54	1.62	2.64	1.63	2.64	1.63	2.66
Residence time (sec)	1.06	1.05	1.70	1.14	1.24	1.24	1.23	1.36	1.34
Inlet Concentration:									
O ₂ (%)	19.8	32.1	30.5	19.8	32.1	19.8	32.1	19.8	32.1
CH ₄ (ppm)	5.47E4	5.41E4	8.77E4	5.41E4	5.41E4	5.41E4	5.41E4	5.41E4	5.41E4
C ₆ H ₅ Cl (ppm)	1.689E3	1.833E3	3.18E3	1.821E3	1.875E3	1.764E3	1.915E3	1.792E3	1.801E3
Outlet Concentration:									
CH ₄ (ppm)	0	0	0	ND	0	3.00±0.73	0	1.94±0.61	0
Toluene (ppm)	0	0	0	0	0	0	0	0	0
Benzene (ppm)	10.2±3.2	7.36±3.0	11.2±4.4	68.7±4.2	7.99±3.0	159±11	7.21±2.87	54.7±6.2	19.6±4.0
Chlorobenzene (ppm)	0	0	0	5.77±2.32	0	262±12	0	163±8	39.3±3.1
CO (ppm)	86.8±8.0	0	0	265±11	0	463±18	38.9±6.9	492±18	285±12
HCl (ppm)	715±19	726±19	976±32	727±20	607±16	680±22	658±17	693±22	787±23
Soot observed	yes	no	little	yes	yes	yes	yes	yes	yes
DRE of Chlorobenzene	>99.95%	>99.95%	>99.97%	99.7%	>99.95%	85.1%	>99.95%	90.9%	97.8%

(3.37) MIXED HAZARDOUS WASTE STABILIZATION TECHNIQUES

Associate Laboratory Director Area: Engineering Research

Principal Investigator: R.W. Benedict, Fuel Cycle

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$214.7K

Purpose:

Stabilization of the hazardous component of mixed hazardous waste was investigated as a potential method to meet the criteria of the Environmental Protection Agency's (EPA) Land Disposal Restrictions (LDR). The management of mixed hazardous waste is a growing area of concern for all parts of the nuclear industry. By developing methods to sample and chemically analyze mixed waste, different stabilization techniques may be developed and tested to eliminate the hazardous constituent below regulatory concern. If a successful stabilization technique can be developed, the management of the waste stream is simplified and can meet all the regulatory requirements.

Approach:

The initial approach was to survey the different types of wastes that are produced throughout the nuclear industry and are affected by the land disposal restrictions. The ordinary radioactive and hazardous contaminated trash that is produced during normal operations is a waste that has many different waste management problems. This material, such as HEPA filters, broken equipment and miscellaneous maintenance produced waste, pose an especially difficult sampling problem.

Since the performance and applicability of stabilization techniques require valid analytical techniques, a study was made of possible methods to sample and analyze various mixed waste streams. Many of the standard solid waste measurements that have been developed are not easily applied to mixed waste. Since the waste characterization is required, neutron activation analysis was identified as a possible method that may be applicable. Calculations on different types of waste showed that this method could provide values for seven of the eight metals of regulatory concern.

To further investigate the potential of this method, different neutron sources were evaluated for their applicability. Preliminary evaluation of the Neutron Radiography Reactor (NRAD) at the Hot Fuel Examination Facility identified that minor modifications would be required. These modifications would allow for the analysis of samples or actual waste that are twelve inches in diameter and twelve inches long. Detail design and fabrication of equipment would be required before this method could be tested. An approach utilizing an accelerator based neutron generator was also identified.

Initial work for the stabilization techniques investigated the applicability of the approach and the data requirements that would be required to successfully demonstrate a technology. An approach and acceptance criteria were established for evaluating different potential technologies. Necessary laboratory procedures and several stabilization techniques were identified that would possibly meet the requirements of the EPA regulations. An experimental plan was developed to test these potential candidates.

Technical Progress and Results:

Fiscal year 1991 was devoted to the development of a detailed approach and identification of applicable potential stabilization techniques. The application of neutron activation analysis was identified as an area that would increase Argonne's capability to characterize mixed hazardous waste. The necessary modifications to the NRAD facility at Argonne West were investigated so that these analyses could be performed on actual waste streams produced throughout the DOE complex. The design of these modifications is continuing so that funding can be pursued to allow the development of this waste characterization capability. Additionally, the use of a neutron generator is being further investigated.

The applicability of the stabilization approach to mixed waste management was established. This approach is being incorporated into specific programs such as the waste form development for the Integral Fast Reactor and Actinide Recycle Programs. Also, this approach is being proposed as part of the Environmental Restoration and Waste Management Five Year plan for ANL-W waste that is presently regulated by the Land Disposal Restrictions. If additional funding can be obtained, specific testing of different stabilization techniques would be done for mixed wastes that are produced in the nuclear industry. Also, fundamental studies of the mechanisms that make stabilization techniques work, would be conducted.

Specific Accomplishments:

Preparation of internal report and experimental plan "Mixed Waste Management", S. Slater, R. Benedict, B. Westphal, November 1991.

(3.38) ASSESSMENT OF RISK ASSOCIATED WITH EXPOSURE TO MOLTEN CADMIUM

Associate Laboratory Director Area: Energy, Environmental and Biological Research

Principal Investigators: M. H. Bhattacharyya, N. A. Sacco-Gibson, Biological and Medical Research

Funding History:	FY 1989	\$0K
	FY 1990	\$0K
	FY 1991	\$21K

Purpose: The Occupational Safety and Health Administration (OSHA) is proposing to decrease the present permissible exposure levels (PELs) for cadmium (Cd) by 95-99% (1). Such proposals are pertinent to Argonne National Laboratory (ANL) -East and -West since the Integral Fast Reactor (IFR) pyrochemical process involves potential exposure to Cd during recovery of nuclear fuels. The purpose of this study is to evaluate what health risks are reported to be associated with Cd exposure, what exposure levels are associated with these health risks, what biological and environmental monitoring are or should be done to insure worker safety, and ultimately, what assessments should be implemented for evaluating potential exposure of IFR workers. The pathway of Cd exposure is different from the nonvolatile radioactive compounds. Cd is part of an electrode recovering and separating plutonium and uranium and is also found in waste salts produced during extraction of actinides. Although the processes are done in a containment area, a vapor is produced which plates Cd onto the inside surfaces of the glove box and the circulating argon atmosphere contains Cd aerosols (2). Demonstrating that ANL-IFR conditions can meet proposed criteria for safe handling of Cd strengthens commitment to worker safety as well as impacts in favor of further commercial development of this nuclear energy processing initiative.

Approach: Due to a petition by the International Chemical Workers Union and the Public Citizens Health Research Group, OSHA has placed Cd on an expedited rulemaking track (1,3,4). The PEL of Cd fume is $100 \mu\text{g}/\text{m}^3$ with a ceiling of $300 \mu\text{g}/\text{m}^3$; for Cd dust the PEL is $200 \mu\text{g}/\text{m}^3$ with a ceiling of $600 \mu\text{g}/\text{m}^3$. OSHA is proposing to change regulations to one of two possible alternatives: 1) PEL of $1.0 \mu\text{g}/\text{m}^3$; short-term 15 min excursion limit (EL) of $5.0 \mu\text{g}/\text{m}^3$; action limit (AL) of $0.5 \mu\text{g}/\text{m}^3$; or 2) PEL of $5.0 \mu\text{g}/\text{m}^3$; EL of $25 \mu\text{g}/\text{m}^3$; AL of $2.5 \mu\text{g}/\text{m}^3$ (1,3,4). OSHA has until February 1992 to lower the exposure limit (5) and has been involved in hearings, including rebuttals from the Department of Commerce, the International Lead and Zinc Research Organization and the Society of Glass and Ceramic Decorators, questioning the technological feasibility of controlling exposure to Cd in numerous industries at the proposed levels (4-9). The National Institute for Occupational Safety and Health (NIOSH) supports the OSHA proposal (1,3,4). A brief synopsis of studies pertaining to the OSHA and NIOSH proposals, as well as some studies that have complicated the health hazard evaluations, are presented in this report. Risk assessments should be based on both animal and human data, but since assessment results are similar only human data are referenced. Biological monitoring and health hazard effects of

Cd on the respiratory, circulatory, renal, skeletal, reproductive and nervous systems are assessed in relation to the IFR workers. A number of major reviews (10-22) provide more detailed information on studies related to Cd production, occupational exposure, biological metabolism, and health hazards.

Biological monitoring (blood and urine) for occupational exposure to Cd, resulting in chronic poisoning, has been difficult due to the lack of accurate reliable methods for analyzing low levels (10,14,20,23) and problems in recognizing early signs of subclinical poisoning, which are often confused with and attributed to other etiological factors (17). Monitoring blood Cd levels addresses total body burden to some extent, but is primarily related to more recent exposure of the previous several months. Monitoring urinary Cd excretion reflects total body burden over a long period of time since the kidneys accumulate Cd. A blood Cd concentration higher than 1.0 $\mu\text{g}/100\text{ g}$ has been suggested as an index of significant Cd exposure (20,23,24). NIOSH has no recommendations for blood Cd limits in industry (3). On the other hand, NIOSH suggests that urinary Cd should be less than 10 $\mu\text{g}/\text{g}$ creatinine (3); OSHA proposes an AL at 5 $\mu\text{g}/\text{g}$ creatinine (1,24). Cd excretion in exposed workers has ranged from 0-1.0 mg/dy (14,25-36) and more often than not levels correlated with years of employment and occupational exposure. Cd-induced renal dysfunction in workers has resulted in glucosuria and proteinuria, including increased excretion of retinol binding protein, albumin, B₂-microglobulin and N-acetyl-B-D-glucosaminidase, formation of renal calculi, and elevated urinary metallothionein concentrations (14,32-45). While there is agreement that Cd-induced renal damage is irreversible, even when workers are removed from exposure, it is still unclear which biological marker is best for assessing early renal effects that might precede the onset of damage from long-term low-level Cd exposure (45-49). Recently, blood pH has been used to monitor progression of renal tubular dysfunction (50). These studies of occupational exposure to Cd related to renal function are most important considering that 30% of the body Cd can be found in the kidney and that Cd is retained for 10-30 yrs. The critical threshold level for Cd burden in the kidney is reported as 200 $\mu\text{g}/\text{g}$ wet weight of cortex (33,48,49). These levels have been observed in workers having been exposed for 10-20 yrs and being approximately 50 yrs old. This is pertinent considering the mean age of IFR workers at ANL-East (48 ± 4), many with a work history of potential exposure to Cd (personal communications with IFR workers, July 1991). Possibly related to renal effects of Cd exposure (48,51), osteomalacia has been reported in Ni-Cd battery plant workers exposed for 8-16 yr (44,52-55), and Cd has been linked to Itai-Itai bone disease (56-58).

Cd exposure has also been linked to acute pulmonary toxicity, including emphysema, pneumonitis, and fibrosing alveolitis (13-15,31,59-64). NIOSH endorses respiratory protection for workers exposed to Cd since it has been shown to be a potential carcinogen in some cases (65-69), although not always (70-72). A major occupational hazard is Cd oxide fumes, which are rapidly absorbed by as much as 10-50%. Particle size is also a major factor in pulmonary absorption of Cd (11-14,73). Cigarette smoke has played a role in a number of exposure studies and has been linked to elevated pulmonary, blood and urinary Cd concentrations (21,36,74-79). However, the lungs are not the only target organ prone to cancer or other possible mutagenic effects as a result of occupational exposure to Cd. Prostatic cancer and impaired testicular function have also been reported (80-82). The new OSHA proposal (PEL 1.0 $\mu\text{g}/\text{m}^3$) is estimated

to result in a total cancer risk of 2.1 excess deaths/1000 (1,19); NIOSH acknowledges that this will reduce the present risk factor, but with more than 300,000 workers exposed to Cd (excluding agriculture and mining) excess deaths could exceed 600 (1,3,4).

Other clinical problems which may be associated with low-level long term Cd exposure include: hypertension, anemia, granulocytosis, lymphocytopenia, peripheral nerve disturbance and cognitive impairment such as decreased attention span, memory loss and poor psychomotor speed (83-82). These effects did not always correlate with blood or urinary Cd concentrations presently used as indices of Cd exposure, nor did they occur in all exposed workers.

Technical Progress and Results: The literature review has provided necessary information for planning, designing and implementing a study to: 1) assess potential Cd exposure in ANL-IFR workers; 2) validate use of a new assay method capable of detecting extremely low Cd concentrations in blood and urine (89); and 3) evaluate the technological possibility of the IFR process to meet the proposed OSHA changes for Cd exposure in the occupational setting.

Specific Accomplishments: A study design, following the National Institutes of Health and the Center for Disease Control regulations for human volunteers has been presented to the ANL Human Use Committee. Biological (blood, urine) and environmental (air, skin) monitoring will be used to evaluate Cd exposure during a time when workers are actively involved in the IFR pyrochemical process. Previous work history will be assessed. Pertinent issues relating to Cd exposure (i.e., cigarette smoking) will be addressed in a health/lifestyle questionnaire (90,91). Blood Cd concentrations obtained by the new assay method (89) will be presented at the 1992 Society of Toxicologists Meeting in Seattle, Washington. An internal report summarizing data and conclusions will be provided to directors associated with the IFR project with possible expansion of the study to Argonne-West.

References

1. NIOSH: Comments of the National Institute for Occupational Safety and Health on the Occupational Safety and Health Administration's Proposed Rule on Occupational Exposure to Cadmium. May 7, 1990. (29 CFR Part 1910)
2. Argonne National Laboratory. Chemical Technology Division Annual Technical Report. 1988 (May 1989), pp. 76-84.
3. NIOSH: Testimony of the National Institute for Occupational Safety and Health on the Occupational Safety and Health Administration's Proposed Rule on Occupational Exposure to Cadmium. July 17, 1990. (29 CFR Part 1910)
4. NIOSH: Posthearing comments of the National Institute for Occupational Safety and Health on the Occupational Safety and Health Administration's Proposed Rule on Occupational Exposure to Cadmium. September 18, 1990. (29 CFR Part 1910)
5. Abrahamson P. Amer. Metal Mrkt. 98:2, 1990.
6. Worden E. Amer. Metal Mrkt. 96:7, 1988.
7. Monks R. Plastics Technol. 36:113, 1990.

8. _____ "Lead, cadmium focus of FDA fall canvassing." (Food and Drug Administration; lead and cadmium content in glassware and ceramics). *Ceramic Indust.* 135:10, 1990.
9. Worden E. *Amer. Metal Mrkt.* 98:2, 1990.
10. Carson BL et al. *Toxicology and Biological Monitoring of Metals in Humans*. Lewis Publishers, Michigan. 1987.
11. Fleischer M. et al. Environmental Impact of Cadmium: A Review by the Panel on Hazard Trace Substances. *Environ. Health Perspect.*, May 1974, pp. 253-323.
12. Fassett D. W. Cadmium as an environmental contaminant. In: Contaminants and Human Health. DHK Lee (ed), Academic Press, New York, 1972.
13. Friberg L et al. *Cadmium in the Environment*. Chemical Rubber Press, Cleveland, 1971.
14. Friberg L, C G Elinder, T Kjellstrom, G F Nordberg (ed) *Cadmium and health: A Toxicological and Epidemiological Appraisal*. Vols. I and II, CRC Press, Boca Raton. I) Exposure, Dose, Metabolism (1985); II) Effects and Response (1986).
15. Kazantzis G. Cadmium. In: Genotoxic and Carcinogenic Metals: Environmental and Occupational Occurrence and Exposure. L. Fishbein, A. First, M. A. Mehlman (ed). Princeton Scientific Publishing Co., Inc., New Jersey, 1988, pp. 127-142.
16. Nilsson R. Aspects on the toxicity of cadmium and its compounds. *Ecological Research Committee Bull. No. 7*, Swedish National Science Research Council, Stockholm, 1970.
17. Nriagu J O (ed) *Changing Metal Cycles and Human Health*. Report of the Dahlem Workshop 1983. Springer-Verlag, Berlin, 1984.
18. Tsuchiya K (ed) *Cadmium Studies in Japan: a review*. Amsterdam, Elsevier/North Holland Biomedical Press, 1978.
19. U.S. Depart. of Labor: Protective Measures for Controlling Exposure to Cadmium. OSHA Instruct. Pub. 8-1.4A Directorate of Technical Support, 1988.
20. Vahter M. Assessment of Human Exposure to Lead and Cadmium through Biological Monitoring. National Swedish Institute of Environmental Medicine and Department of Environmental Hygiene Karolinska Institute, Stockholm, 1982.
21. Vercruysse A (ed) *Hazardous Metals in Human Toxicology (Part B)*. Elsevier Press, New York, 1984.
22. Vouk V. General Chemistry of Metals. In: Handbook on the Toxicology of Metals. Vol. I. L. Friberg, G. F. Nordberg, V. B. Vouk (eds). Elsevier/North-Holland Press. Amsterdam, 1986, pp. 15-35.
23. O'Laughlin J W et al. Analytical Methodology for Cadmium in Biological Matter - A Critical Review. ILZRO, Inc., New York, 1976.
24. WHO Technical Report 647. Geneva, World Health Organization. 1980.
25. Lehnert G et al. *Brit. J. Ind. Med.* 26:156, 1969.
26. Tsuchiya K. *Arch. Environ. Health* 14:875, 1967.
27. Suzuki S et al. *Ind. Health* 3:73, 1965.
28. Smith J C et al. *Brit. J. Ind. Med.* 14:240, 1957.
29. Adams R G et al. *Quart. J. Med.* 38:425, 1969.
30. Kazantzis G et al. *Quart. J. Med.* 32:165, 1963.
31. Bonnell J A. *Brit. J. Ind. Med.* 12:181, 1955.
32. Kawada T et al. *Int. Arch. Occup. Environ. Health* 62:95, 1990.
33. Bernard A and Lauwerys R. *Toxicol. Lett.* 46:293, 1989.

34. Chia K S et al. Brit. J. Indust. Med. 46:165, 1989.
35. Kawada T et al. Brit. J. Ind. Med. 46:52, 1989.
36. Hassler E et al. Brit. J. Ind. Med. 40:420, 1983.
37. Ahlmark A et al. Further investigations into kidney function and proteinuria in chronic cadmium poisoning. Proc. 13th Internatl. Congr. Occup. Health, 1961, pp. 201-203.
38. Kjellstrom T and Piscator M. Phadedoc. Diagnostic Commun. 1:1, 1977.
39. Smith J C et al. Brit. J. Ind. Med. 18:70, 1961.
40. Nogawa K et al. Environ. Health Perspectives 28:161, 1979.
41. Piscator M. Arch. Environ. Health 12:335, 1966.
42. Friberg L et al. Cadmium in the Environment. CRC Press, Cleveland, 1974, p. 24.
43. Roels H et al. Intl. Symposium Recent Adv. in Assessment of Health Effects of Environmental Pollution (Paris) 1974:64A.
44. Roels H A et al. Brit. J. Indust. Med. 46:755, 1989.
45. Friberg L. Arch Ind. Health 16:30, 1957.
46. Bonnell J A et al. Brit. J. Ind. Med. 16:135, 1956.
47. Shaikh Z A. Environ. Health Perspect. 54:171, 1984.
48. Kjellstrom T. Renal effects. In: L. Friberg, C. Elinder, T. Kjellstrom, G. Nordberg (ed) Cadmium and Health: A Toxicological and Epidemiological Appraisal, Vol. 2, Boca Raton, CRC Press, 1986.
49. Piscator M and Pettersson B. Clinical Chemistry and Chemical Toxicology of Metals. S. S. Brown (ed) Elsevier/North Holland Biomedical Press, Amsterdam, 1977, pp. 143-155.
50. Kido T et al. Arch. Environ. Health 45:35, 1990.
51. Kjellstrom T. Effects on bone, on vitamin D, on calcium metabolism. In: L. Friberg, C. Elinder, T. Kjellstrom, G. Nordberg (ed) Cadmium and Health: A Toxicological and Epidemiological Appraisal, Vol. 2, Boca Raton, CRC Press, 1986.
52. Nicaud P et al. Arch. Mel. Prof. Med. Trav. Secur. Soc. 4:192, 1942 (French)
53. Gervais J and Delpech P. Arch. Mal. Prof. 24:803, 1963 (French).
54. Kazantzis G. Environ. Health Perspect. 28:155, 1979.
55. Thun M J et al. Brit. J. Indust. Med. 46:689, 1989.
56. Nogawa K. Itai-Itai disease and follow-up studies. In: Cadmium in the Environment. J. O. Nriagu (ed) John Wiley and Sons, New York, 1981, pp. 1-37 (II).
57. Nogawa K and Ishizaki A. Environ. Res. 18:410, 1979.
58. Nogawa K et al. Environ. Res. 15:185, 1978.
59. Yates D H and Goldman K P. Brit. J. Ind. Med. 47:429, 1990.
60. Edling et al. Brit. J. Indust. Med. 43:657, 1986.
61. Davison A G et al. Lancet i:663, 1988.
62. Bernard A and Lauwerys R. Effects of cadmium exposure in humans. In: Cadmium. Handbook of Experimental Pharmacology, Vol. 80, E. C. Foulkes (ed), Springer Verlag. Berlin, 1986, pp. 135-177.
63. Nemery B. Eur. Respir. J. 3:202, 1990.
64. Hygienic Guides Committee. Cadmium. Am. Ind. Hyg. Assoc. J. 23:518, 1962.
65. Takenaka S et al. JNCI 70:367, 1983.
66. Kazantzis G et al. Scand. J. Work Environ. Health 14:220, 1988.

67. Elinder et al. *Am. J. Ind. Med.* 8:553, 1985.
68. Elinder C G et al. *Brit. J. Ind. Med.* 42:651, 1985.
69. Thun M J et al. *JNCI* 74:325, 1985.
70. Oberdörster G. *Scand. J. Work Environ. Health* 12:523, 1986.
71. Ades A E and Kazantzis G. *Brit. J. Ind. Med.* 45:435, 1988.
72. Sorahan T. *Brit. J. Ind. Med.* 44:803, 1987.
73. McLellan J S et al. *J. Toxicol. Environ. Health* 1:131, 1978.
74. Pääkkö P et al. *Environ. Res.* 49:197, 1989.
75. Franklin D M et al. In vivo neutron activation analysis of organ cadmium burdens. Referent levels in liver and kidney and the impact of smoking. In: Biological Trace Element Research. G. N. Schrauzer (ed) Humana Press, 1990, pp. 401-406.
76. Morgan W D et al. In vivo measurements of cadmium and lead in occupationally-exposed workers and an urban population. In: Biological Trace Element Research. G. N. Schrauzer (ed) Humana Press, 1990, pp. 407-414.
77. Louekari K et al. *Science of the Total Environ.* 84:1, 1984.
78. Lewis G P et al. *J. Chronic Dis.* 25:717, 1972.
79. Adamska-Dyniewska H and Trojanowska B. 19th Intl. Congress on Occupational Health Dibrovnik, September 1978.
80. Le Marchand L et al. *Am. J. Epidemiol.* 133:103, 1991.
81. Elghany N A et al. *Epidemiology* 1:107, 1990.
82. Mason H J. *Human and Exper. Toxicol.* 9:91, 1990.
83. Hart R P et al. *J. Clin. Exper. Neuropsychology* 11:933, 1989.
84. Babitch J A. Cadmium neurotoxicity. In: Metal Neurotoxicity. S. C. Bondy, K. N. Prasad (ed), CRC Press, Boca Raton, 1988, pp. 141-166.
85. Feldman R G. *Arch Neurologica Scand.* 66:143, 1982.
86. Marlowe M et al. *Am. J. Mental Deficiency* 87:477, 1983.
87. Pihl R O and Parkes M. *Science* 198:204, 1977.
88. Thatcher R W et al. *Arch Environ. Health* 37:159, 1982.
89. Peterson D et al. *Analyt. Biochem.* 192:434, 1991.
90. Van Gelderen CEM et al. *Fd. Chem. Toxic.* 28:775, 1990.
91. Gochfeld M. *Occup. Med.* 5:25, 1990.

(3.39) ARGONNE EXPERIMENTAL INITIATIVE ON MAGLEV

Associate Laboratory Director Area: Energy, Environmental, and Biological Research

Principal Investigators: D.M. Rote, H. T. Coffey, Energy Systems; J. R. Hull, Materials and Components Technology

Funding History:

FY 1989	\$0K
FY 1990	\$170.2K
FY 1991	\$256.1K

Purpose: To develop a research, development, and evaluation capability for magnetically-levitated (maglev) vehicle technology at Argonne. Specifically, to develop the capability to conduct laboratory experiments and conduct supporting computer-aided computational studies focused on concepts for magnetically levitating, guiding, and propelling vehicles. Further, to develop the capability to evaluate maglev concepts invented in house or by government contractors participating in the National Maglev Initiative.

Approach: A team of scientists, and engineers from the ES and MCT Divisions, a technician, several students at the undergraduate and graduate levels, a visiting professor from Northern Illinois University, and a post doctoral fellow was assembled. The initial focus in early 1990 was on designing, fabricating, and installing experimental apparatus including rotating aluminum disks and the 1.2 m diameter rotating wheel. These devices were used to conduct basic experiments with magnets moving relative to continuous-sheet guideways of effectively infinite width. Results were compared with computations of magnetic field distributions and magnetic lift and drag forces. In FY91 additional experimental equipment was designed and fabricated and the data acquisition equipment was refined and automated. New experiments were conducted to examine "edge-effects" associated with finite-width guideways and to study discrete shorted-turn and null-flux coil guideways. Measurements of lift, drag, and lateral guidance forces were conducted and comparisons were made with computer code calculations. In mid FY91 the experimental program was expanded to include the design and fabrication of a 5m long laboratory demonstration maglev model capable of demonstrating propulsion as well as lift and guidance forces using three-phase-excited guideway mounted coils.

Technical Progress and Results: Several types of experimental apparatus were designed, built, and used to explore basic-physics phenomena associated with magnetic levitation, guidance, and propulsion. These include a 1.2m diameter rotating wheel installed in a safety pit, several rotating aluminum disks that were used to investigate lift and drag forces and to study the effects of discontinuities in continuous sheet guideways caused by thermal expansion joints, rotating plastic drum facilities used to investigate lift, drag, and guidance forces associated with discrete, shorted-turn and null-flux coil guideway conductors, an aluminum drum setup for studying parallel vs. antiparallel magnet configurations, and a special apparatus for investigating the ANL-invented "alternating-gradient" magnetic suspension concept. Components for the 5m long laboratory demonstration maglev model were built and assembly was nearly completed by the

end of FY91. Some preliminary tests of the levitation, guidance, and propulsion systems were conducted, and some initial force measurements indicated good agreement with design calculations.

Several new computer codes were written at ANL and tested using the data acquired from the experiments. Very good agreement was found between measurements of forces exerted on moving "null-flux" figure 8 coils by stationary magnets and calculations performed with a new computer code developed at ANL that is based on dynamic circuit theory. In addition, a special version of the widely-used, vendor-supplied computer code "PE2D" that treats moving conductors and eddy currents in two dimensions was supplied to us by Vector Fields, Inc., and validated using data obtained from experiments mentioned above. A new vendor-supplied computer code "ELEKTRA", that is supposed to be capable of treating eddy-current problems in 3-dimensions with moving conductors is currently being tested at ANL through a special arrangement with Vector Fields, Inc..

Specific Accomplishments: An analysis of magnetic force transients associated with discontinuities in continuous-sheet guideway conductors was completed in FY90 and an invention report of a thermal expansion joint that minimizes the force transients was prepared (see entry #1 in Table 1 and the paper listed as item 1 in Table 2).

Developed the capability to conduct experimental investigations of concepts for magnetic suspension, guidance, and propulsion using laboratory apparatus built especially for this purpose. The apparatus included a 1.2 m diameter rotating wheel facility, a 4.5 m-long linear guideway, and several smaller rotating devices.

Two new designs for magnetic suspension, guidance, and propulsion systems were developed, analyzed, and invention reports were prepared in FY91 (see entries #2 & 3 in Table 1).

A new maglev concept utilizing 20K high-temperature superconductors was investigated and reported in a paper presented at a conference in Boston in FY91 (see entry #3 in Table 2).

A new computational method for calculating magnetic forces based on Dynamic Circuit Theory was developed and reported in a paper presented at a conference in Langley, VA in FY91 (see entry #4 in Table 2).

A database was developed for validating eddy-current computer codes capable of computing eddy currents, magnetic flux densities, and magnetic forces in 2-dimensions. This database was constructed from measurements made on the 1.2-m diameter rotating wheel facility set up in FY90.

A database was developed in FY91 for validating eddy-current computer codes capable of computing eddy currents, magnetic-flux densities, and magnetic forces in 3-dimensions. In particular, this database was designed especially to describe "edge-effects" associated with narrow continuous-strip guideways.

A set of preliminary experiments were conducted in FY91 using various arrays of discrete, shorted-turn and figure-8 null-flux guideway conductors (instead of continuous-sheet guideway conductors). A limited database for validation of the computer code based on dynamic circuit theory was developed.

A set of preliminary experiments to demonstrate the concept of alternating gradient suspension and guidance (see item #5 in Table 1) were carried out. These experiments showed that while the concept was technically feasible, the ability to experimentally-demonstrate it on a small laboratory-scale device was doubtful.

Designed and fabricated a 4.5-m long experimental/demonstration device for simultaneously suspending, guiding, and propelling a 6.5 kg "vehicle" with magnetic forces.

Table 1 ANL Maglev Invention Disclosures

1. *Expansion Joint for Maglev Guideway*, ANL-IN-91-12, Thomas D. Rossing, 12-12-90
2. *A New Configuration of Magnetic Suspension and Propulsion for Vehicles*, ANL-IN-91-67, Jianliang He, Donald M. Rote, and Howard T. Coffey, 3/28/91
3. *Integrated Null-Flux Suspension & Multiphase Propulsion System for Magnetically-Levitated Vehicles*, ANL-IN-91-13, Donald M. Rote, Jianliang He, Larry Johnson, 12/28/90
4. *Possible Magnetic Levitation Scheme, Incorporating Levitation, Guidance and Linear Synchronous Motor*, ANL-IN-90-57, Howard Coffey, June 12, 1990
5. *Alternating-gradient Attractive Magnetic Levitation for High-Speed Ground Transport*, John Hull, May 27, 1988*
6. *Propulsion and Stabilization System for Magnetically-Levitated Vehicles*, Howard T. Coffey, August 29, 1989*

Table 2 Papers Reporting on AXIOM Accomplishments

1. *Effect of Guideway Discontinuities on Magnetic Levitation Force*, T.D. Rossing, R. Korte, and J.R. Hull, presented at the 5th Joint MMM-Intermag Conference, Pittsburgh, June 18-21, 1991. Accepted for publication in the Journal of Applied Physics.
2. *Effect of Size and Geometry on Levitation Force Measurements Between Permanent Magnets and High Temperature Superconductors*, W.S. Cha, J.R. Hull, T.M. Mulcahy, and T.D. Rossing, presented at the 5th Joint MMM-Intermag Conference, Pittsburgh, June 18-21, 1991. Accepted for publication in the Journal of Applied Physics.
3. *Maglev System Concept Using 20-k High-Temperature Superconductors and Hyperconductors*, J.R. Hull and J.L. He. Presented at Intersociety Energy Conversion Engineering Conference, Boston, MA, August 4-9, 1991.
4. *Computation of Magnetic Suspension and Propulsion of Maglev Systems Using Dynamic Circuit Theory*, J.L. He, D.M. Rote, and H.T. Coffey, presented at the International Symposium on Magnetic Suspension Technology, NASA Langley Research Center, Hampton, VA, Aug 19-23, 1991 will be published in the conference proceedings.

*Prepared prior to AXIOM program.

(3.40) **PICOSECOND OPTICAL SWITCHING WITH MOLECULAR ELECTRONIC DEVICES**

Associate Laboratory Director Area: Physical Research

Principal Investigator: M. R. Wasielewski, Chemistry

Funding History:	FY 1989	\$0K
	FY 1990	\$123.4K
	FY 1991	\$108.5K

Purpose: This project will develop prototype molecular electronic devices based on complex organic molecules that will act as opto-electronic switching components on a picosecond time scale. This project will also investigate the techniques necessary to interface these molecular electronic components to macroscopic electronic components. The development of energy-efficient, state-of-the-art electronic devices depends increasingly on the ability to produce ever-higher densities of circuit elements within integrated circuits. The ability to use circuit elements the size of molecules would result in a several order of magnitude increase in circuit density. The availability of such components and the methods to interconnect them would make it possible to produce molecular switches, gates, and wires. These components would have application in logic circuits, memories, and novel micro-sensors for chemical analysis.

Approach: Chemical synthesis will yield the complex organic molecules needed to implement several types of molecular switch: initially two types of AND gate, and one molecular memory. The switching properties of these molecules will be examined with multi-wavelength picosecond laser techniques.

Technical Progress and Results: We have completed the synthesis of two new classes of molecular switching molecules. Both molecules are designed to switch electronic states on a picosecond time scale using two different colors of light. The first molecule contains two photoactive components. Electron transfer is initiated by light of color 1 to form an ion-pair, i.e. the system is switched on. The optical properties of this ion-pair are used to detect its formation. At a time several picoseconds later, a second light pulse of color 2 is used to catalyze the recombination of the two charges in the ion-pair. Thus, the system is switched off. We have observed this effect at times as short as 30 ps, and are working toward observing it at 10 ps.

The second molecule is also designed to use laser pulses of two different colors to initiate switching. In this case a light pulse of color 1 initiates the formation of ion-pair A. Ion-pair A absorbs light from a probe pulse at color A. During the lifetime of ion-pair A a second laser pulse of color 2 initiates a second electron transfer. The second electron transfer results in ion-pair B, which absorbs light at color B. Color B is different from color A, and thus can be used to distinguish between the formation of ion-pairs A and B. Therefore, the presence or absence of the second initiator light pulse at color 2 can result in rapid modulation of light

beams at both colors A and B. Thus, information in a laser beam at one frequency can be transferred to a beam at two other frequencies using the molecular switch. Arrays of these switches can be used to route information in molecular logic devices.

We have also developed a new femtosecond laser system that delivers the light pulses that will form our basic test bed for developing molecular switches. This laser system uses new solid state technology based on a titanium-doped sapphire lasing medium.

Specific Accomplishments: We have prepared two new molecules that are being tested for molecular switching capability. We have also completed about 90% of a new femtosecond laser system designed to investigate molecular switching in the molecular systems that we are preparing. We submitted a proposal to the Advanced Energy Projects Division of the Office of Basic Energy Sciences at DOE. This proposal was favorably reviewed and was funded for a three year period beginning November, 1991. The monies from this proposal will be used to extend the work initiated with this LDRD project. Two papers on switching phenomena already observed in molecular systems are being prepared.

**DATE
FILMED**
3 / 12 / 92