10/3-18-97 JSC

MARTIN MARIETTA

ORNL/CSD/TM-285

The Network Observer A User's Manual and Programmer's Guide for the xb Code

Malcolm R. Patterson
Dan O. Harton

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

THE NETWORK OBSERVER

A USER'S MANUAL AND PROGRAMMER'S GUIDE FOR THE xb CODE

Malcolm R. Patterson and Dan O. Harton
Computing and Telecommunications Division
Oak Ridge National Laboratory
Post Office Box 2008
Oak Ridge, Tennessee 37831

Date Published - March 1992

MARTIN MARIETTA ENERGY SYSTEMS, INC.
managing the
Oak Ridge National Laboratory Oak Ridge Y-12 Plant
Oak Ridge K-25 Site Paducah Gaseous Diffusion Plant
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MAR. 92

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

LIST OF FIGURES	iv
ACKNOWLEDGMENTS	v
ABSTRACT	vii
1. INTRODUCTION	1
2. EQUIPMENT REQUIRED	2
3. USER'S MANUAL	3
3.1 OPERATION OF XB	3
4. PROGRAMMER'S GUIDE: ORGANIZATION OF THE PROGRAM	5
4.1 STRUCTURE OF PROGRAM XB	5
4.2 STRUCTURE OF PROGRAM XNAT.C	6
4.3 PRECURSOR ROUTINES FOR INITIALIZATION	6
4.4 REAL TIME LOOP	8
4.5 DESCRIPTION OF THE FILES	8
5. SUMMARY	11
6. REFERENCES	12

LIST OF FIGURES

Fig. 1. Directory <u>xmx/xmxdan</u> should be copied to the user's directory <u>xbprog</u>	3
Fig. 2. Cluster of plots of network traffic for K-25.	4
Fig. 3. Schematic of Program <u>xb</u>	5
Fig. 4. Call structure of xnat.c.	7

ACKNOWLEDGMENTS

The authors express their great appreciation to Thomas H. Dunigan, Jr., for his help with the xtraffic.c code, the present modification of which is called xnat.c in this report. In addition, the assistance of Judy A. Green in getting the xmx code to run is gratefully acknowledged. Fred Harris and Jeff W. Frederick were helpful in many matters relating to the SUN computer. This project was conceived and directed by Ronald M. Rutledge under the guidance of D. Michael Turpin. Both authors thank Mona L. Harmadi for typing this report and making effective displays. The report has benefitted from the work of Cathy H. Shappert as editor.

ABSTRACT

A computer program that will yield graphic displays of a variety of statistics simultaneously for 13 emeters has been created. It runs on the SUN computer and uses Dunigan's xtraffic.c code¹ and the mx code written at Brown University² to multiplex these graphs to users at remote sites. By operating in this manner the remote user gets the information without having to query the emeter directly. The emeter is then not overloaded by requests for information, and the operation of the network is more efficient.

Current versions of this code operate on the SUN computer and can be extended to other platforms.

1. INTRODUCTION

At the request of the Telecommunications Department of the Computing and Telecommunications Division (C&TD), a program to monitor the communications network has been systematized from several programs. These programs generally include (1) a program called xnat.c, originating at the Massachusetts Institute of Technology (MIT) as xperfmon.c and rewritten extensively at the Oak Ridge National Laboratory (ORNL) by Thomas H. Donigan, Jr.;¹ (2) a program called xmx written at Brown University in Providence, Rhode Island;² and (3) numerous C-shell script codes to mediate and control the first two. Each of the first two programs existed before the current work, and the xnat.c code was modified somewhat to suit the present purpose. The C-shell script programs allow both to function and not lose the emeter input. A framework was conceived that permits the monitoring of the emeters to interfere as little as possible with the business of the networks.

The purpose of the program is to summarize in screen graphics form the traffic volume for several types of packets. Eleven plots for each emeter are presented in a window in a contiguous manner, sharing labels and a time axis, as shown in Fig. 1. Approximately 15 of these windows of 11 plots can be shown on the screen of a SUN computer at one time. Using the xmx program from Brown University, an individual group of 11 plots can be multiplexed to other workstations who may have an interest in only one of the emeters.

According to the xmx copyright, this program can be used, copied, or modified for any purpose other than its incorporation into a commercial product, providing that the copyright notice appears on all copies and distribution is only within the organization represented by the person receiving the software from Brown.

2. EQUIPMENT REQUIRED

The measuring devices in the network are emeters. These emeters are queried by SUN computers having pickup devices that can interrogate the emeters. Other computers, such as IBM RISC 6000's or DEC workstations, could be used equally as well for these purposes, but our firsthand experience is with SUNs. In order for the multiplexor program to work such that the base SUN can transmit a set of graphs from the base SUN to the satellite SUN, the SUNs that are to be connected must be nearly identical. At the least the sender and the recipient must both have color videos, or both must have black and white videos. Further, they must be equipped with and operating in the "openwin" (windows) mode to run an X-window display server such that several windows can be active at one time.

3. USER'S MANUAL

3.1 OPERATION OF XB

In spite of the complexity of the results obtained with xb, the operation of the code is relatively straightforward. In the following paragraphs the user's response at the console is underlined. Having logged onto the workstation, the user must open the "windows" mode of operation with the instruction

```
/prompt> openwin
```

With the windows mode open, the user must choose a window in which to operate by using the mouse, clicking on the desired window, and moving it to the desired location. All the foreign screens that will be connected to the host platform (i.e., lansun) must execute the instruction

```
/prompt> xhost lansun
```

before the run begins. Note again that this instruction must be given on each of the computers connecting to lansun. Then the user can change to the directory that contains the xb programs and routines (c.g., xbprog) by using the cd instruction. The user should have copied into xbprog all the routines listed in Fig. 1 from the author's directory xmx/xmxdan.

Fig. 1. Directory xmx/xmxdan should be copied to the user's directory xbprog.

```
/prompt> cd xbprog
```

All that the user has to do at this point is to type xb:

```
/prompt> :b
```

All the 13 emeters that are initiated in the xb program should begin to operate within a short time (i.e., 1 or 2 min). The fact that they are operating will be indicated on the screen by a cluster of eleven plots for each operational meter, such as shown in Fig. 2.

Should any emeter plot cluster fail to display on the screen, the user can restart that program by typing x.i, where i is the number of the desired emeter. For example, if emeter_10 fails to come up when the other meters are started with xb, then it can be started separately by typing

```
/prompt> x.10
```

The x.10 program will then attempt to start emeter_10 again. Occasionally an emeter will not be operational, and under those conditions neither program will be able to start it.

The actions described for emeter_10 should be repeated for any other meters that are missing. Finally, one should have a display of 13 windows, each containing an 11-graph cluster. These windows will represent emeter_3 through emeter_15 in the current application. Each window can be moved around on the screen and will automatically refresh itself when the time signal reaches the right-hand side of the graph.

A single emeter can be displayed on the screen. At the current polling rate, its window size can be increased to show a time period up to about 30 min on the screen. This larger size cannot be used when all 13 emeters are shown on the screen simultaneously.

Fig. 2 Cluster of plots of network traffic for K-25.

4. PROGRAMMER'S GUIDE: ORGANIZATION OF THE PROGRAM

4.1 STRUCTURE OF PROGRAM XB

The program xb, shown schematically in Fig. 3, is the initiator of all the jobs. First it removes the file called stopper that is used to curtail execution of the remaining programs. Then it deletes all files in this directory that start with "ee". These files are the storage files (logs) for data on each of the emeters and summarize the traffic up to the time of the last recorded observation. In turn xb calls a set of programs, one directed at each of the emeter monitors, by starting the vector of programs x.3 through x.15. Each individual program x.i has the purpose of starting a certain emeter (say emeter_i), restarting emeter_i if it fails, and checking whether shutdown of the program has been initiated by the operator. The latter condition is detected by examining the existence of the file stopper. If stopper does exist, emeter_i is not restarted and an exit is initiated.

Program xb is at the top of the structure of programs that relate to the current work. It is initiated simply by typing "xb" at the beginning of a run, after the SUN computer has been put in the "openwin" (windows) mode. The operation of this code is described earlier in the "Operations" section. Program xb automatically calls the scripts x.3.....x.15. Each of these scripts in turn starts the corresponding scripts x3.....x15.

The x3 script, typical of the remaining x.i scripts, gets the current computer (e.g., lansun) entered in the list of host computers. Then x3 sets the environmental variable DISPLAY to use channel 3 on lansun. Next the program xmx is started on channel 3 with an option to list the receptor computers in the file f.3. The xmx program is invoked with an "&" at the end, meaning that the program will execute in an independent mode until halted by an explicit command to stop.

An xnat program is pointed at each emeter within each x.i script. For example, x.3 calls x3, which in turn calls the xnat program targeted at emeter_3. These actions are carried out by the programs without any further

Fig. 3. Schematic of Program xb.

action required by the user. The computer must be in the "Open Windows" mode of operation in order for the routines to start properly.

4.2 STRUCTURE OF PROGRAM XNAT.C

T. H. Dunnigan's version of MIT's xperfmom.c is called xtraffic.c within Energy Systems. This code was used at ORNL with success and was chosen to incorporate in xb. Because it was modified somewhat, its name was changed to xnat.c for use in xb. As a C-program the changes could be made at a relatively high level, with little disturbance to the original code.

The multiprocessing capability of the Sun computer is being used to display 15 or so graphs of the network loads in 15 windows on the screen of the Sun workstation. Because each graph can consist of as many as 11 quantities plotted as a function of time, a large amount of information is available to the user at any particular instant. The original code xnat.c tended to lose contact with some emeters at random times. When this loss of contact occurred, that xnat program died. A restart capability was built into peripheral programs that now guide the basic xnat code and direct it to restart when the signal is lost. These peripheral programs are the C-script nodes x3,.....,x15, which give the programs the ability to run for much longer periods of time, as much as 4 to 8 hours, before contact with an emeter is lost.

In addition to adding the ability to run the programs in parallel and introducing the restart capability, the query interval was changed from 1 to 5 seconds, and the time scale on the plots was changed correspondingly. Ordinate scales for all of the plots were adjusted to meet new requirements. Identification of the emeters on the screen plots was changed to a system that allows a short but descriptive name. The ordinate "total output" was changed from kilobytes/second (Kbts) to megabits/second (Mbs). Other short routines allow for the accumulation of the statistical output of xnat at the end of a run.

The essential programs reside on the lansun computer in the directory home/landsun/mrp/xnatdan, and the group of programs is initiated within the resident directory by typing xb. An individual job can be killed by clicking on its plot and typing q, in the original xnat.c manner, or all the xnat jobs can be killed by running killnat. Statistics generated by each job are accumulated by the log program and can simply be listed on screen or sent to the printer.

4.3 PRECURSOR ROUTINES FOR INITIALIZATION

A schematic of the flow of control in xnat is shown in Fig. 4. This diagram shows the main structure of the xnat.c code. The main code has the two conventional arguments (argc,argv) through which one can pass the on-line arguments to the code at execution time. These arguments are processed by the routine called process_cmdline(argc,argv). The code proceeds with sys_setup which calls init_stat to initialize the statistics. The routine signal(SIGINT,edstop) is called to set up the interval for sending and receiving signals. Next, edstart() is called to connect to the emeter and set the time delay.

Fig. 4. Call structure of xnat.c.

Graph_setup(num_stats,LINES_PER_LABEL) next sets up the number of statistics (graphs) that are to be presented. **Init_graph_list**(...) sets up the order of the plots that will be presented. Then **win_setup**(argc,argv) sets up the window and readies the plots to proceed.

4.4 REAL TIME LOOP

With the necessary preliminaries out of the way, the **main_event_loop**() routine takes control and implements the basic loop structure of xnat. The complexity of the code prevents discussion of all the routines shown in Fig. 4, but the main points about the loop will be brought out. The principal routines called in the loop include the following:

calloc(num_stats,sizeof(int)) handles allocation of memory resources.

exit() is self explanatory and stops execution of the program.

check_win_events(&ch) monitors the window events since the last loop to determine whether update action is required on the screen.

handle_key(ch) traps the latest keyboard entry and determines what character has just been entered.

The following routines in the loop are only executed as needed:

XFD_ZERO(&display_fd_set) initializes keyboard display/entry.

select(display_fd+1,&display_fd_set,0,0,timeout) tests for keyboard entry.

update_stats() updates the statistics that are kept on each of the emeters. At the end of the run for each emeter, these statistics are stored in the file eei, where i is 03 through 15. The eei files are gathered together in the log file and can be printed for a record of network activity at all of the emeters.

graph_values plots the updated data in each window containing an xnat run.

free(values) releases space that is not needed after the end of the run.

The above routines call a myriad of other functions in order to accomplish the task that each has been assigned. These other routines are displayed in part in Fig. 4 for reference. Many of these routines are concerned with displaying the data within the X-windows context. Some explicitly draw the graphics on the screen of the work station.

4.5 DESCRIPTION OF THE FILES

All the routines required to operate this program are presently included on the "lansun" computer located in the MAXIMA building. They are stored in directory /usr1/mrp/xmx/xmxdan/, and a schematic list of this directory is given in Fig. 1. These contents

are discussed below alphabetically.

The numerous files — the names of which start with "e" or with "ee" — contain data and error messages generated during the run, along with summaries of the types of messages that were received while a given emeter was running. The files that begin with "f." contain the network address that is to receive the plots. For example, f.10 contains the address of the SUNs to which information on emeter_10 should be sent.

The program idenmeter is a short C code to identify the name attached with a certain emeter number. The program is activated by typing "idenmeter" after the prompt. The computer responds with

type emeter id =

and the user responds with the identity of the emeter (e.g., emeter9).

Then the code responds with

emeter9 is equivalent to 4500N
(4500N is the name of a meter that is located in 4500N at ORNL).

Four programs follow that have "kill" as the first four letters of their names. Their functions are to stop certain types of programs from running and/or delete them from the list of active programs:

killiw stops jobs in a wait state,
killnat stops all xnat jobs,
killxmx stops all xmx jobs, and
killxnn stops stops a certain job number.

The files f.3 through f.15 contain the names of the recipient screens that will receive the signals sent out by xmx for the respective emeter (e.g., file f.3 might contain entries landev and fzhsun as the SUN receptors of the xnat plots for emeter_3).

The file log accumulates the statistics from all the e-files and thus from all the 13 emeters. The stopper file exists to stop the running of the emeter codes xnat. The script programs tstf and testtstf are incomplete programs to add other users to the xmx network.

The C-script program xb starts all 13 xnat emeter monitors simultaneously by calling programs x.3 through x.15.

xkill is a program generated by an awk program to kill a job number that represents either a certain emeter number or a certain xmx job number.

xmx is the program² used to multiplex a window from the host screen and send it to connecting screens. This program was written at Brown University for classroom use to connect several identical platforms during one lecture.

The xnat program is the heart of the system that is described here. It initiates the calls to an emeter, monitors the response, analyzes the data, and presents the statistics as graphs in a window on the SUN. The collected batch of 11 plots for each emeter is then propagated by the xmx program to other platforms.

These brief summaries of the files that make up the current version of the network monitor should be sufficient to guide the interested observer in the use and modification of the xb code.

5. SUMMARY

A computer program has been created that will give graphic displays of a variety of statistics simultaneously for 13 emeters. The program runs on the SUN computer and uses Dunigan's xtraffic.c code¹ and the xmx code written at Brown University² to multiplex these graphs to users at remote sites. By operating in this manner the remote user gets the information without having to query the emeter directly. The emeter is then not overloaded by requests for information, and the operation of the network is more efficient.

Current versions of this code operate on the SUN computer and can be extended to other platforms.

6. REFERENCES

1. The xtraffic.c code can be requested from Dr. Thomas H. Dunigan, Jr., Oak Ridge National Laboratory, Building 6012, MS 6367, P.O. Box 2008, Oak Ridge, Tennessee 37831.
2. The xmx code was copyrighted by Brown University of Providence, Rhode Island, in 1988, 1989, and 1990. This code can be requested from the Computer Science Department at Brown University.

INTERNAL DISTRIBUTION

1. J. B. Bradshaw	21. R. M. Rutledge
2. J. L. Duncan	22-24. C. H. Shappert
3. T. H. Dunigan, Jr.	25. J. E. Thomas
4. R. H. Fowler	26. D. M. Turpin
5. J. W. Frederick	27. G. E. Whitesides
6. J. A. Green	28. Central Research Library
7-11. D. O. Harton	29. ORNL Y-12 Research Library
12. J. T. Holdeman	Document Reference Section
13. K. G. Leihkauff	30. Laboratory Records Department
14. M. R. Marshall	31. Laboratory Records ORNL (RC)
15. P. D. Morris	32. ORNL Patent Office
16-20. M. R. Patterson	

EXTERNAL DISTRIBUTION

- 33. Office of Assistant Manager for Energy Research and Development, U.S. Department of Energy Field Office, Oak Ridge (DOE-OR), P.O. Box 2001, Oak Ridge, TN 37831
- 34. Fred T. Harris, Computer Sciences Department, University of Tennessee, Knoxville, TN 37996
- 35. John Bazik, Brown University, Computer Sciences Department, Box 1910, Providence, RI 01912
- 36-45. Office of Scientific and Technical Information, P.O.Box 62, Oak Ridge, TN 37831

END

DATE
FILMED
4/8/92

2