1 of 1

A REVIEW OF SENSITIVITY ANALYSIS TECHNIQUES (U)

by
David M. Hamby
Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

LIBRARY
FEB 28 1994
OSTI

A document prepared for:
Technometrics

DOE Contract No. DE-AC09-89SR18035

This paper was prepared in connection with work done under the above contract number with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

WSRC-MS-93-576

A REVIEW OF SENSITIVITY ANALYSIS TECHNIQUES (U)

D. M. Hamby

Westinghouse Savannah River Company

Savannah River Technology Center

Aiken, SC 29808

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P. O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161

ABSTRACT

Mathematical models are utilized to approximate various highly complex engineering, physical, environmental, social, and economic phenomena. Model parameters exerting the most influence on model results are identified through a "sensitivity analysis". A comprehensive review is presented of more than a dozen sensitivity analysis methods. The most fundamental of sensitivity techniques utilizes partial differentiation whereas the simplest approach requires varying parameter values one-at-a-time. Correlation analysis is used to determine relationships between independent and dependent variables. Regression analysis provides the most comprehensive sensitivity measure and is commonly utilized to build response surfaces that approximate complex models.

KEY WORDS

computer models; uncertainty analysis; error analysis; environmental modeling

INTRODUCTION

Mathematical models are utilized to approximate various highly complex engineering, physical, environmental, social, and economic phenomena. Model development consists of several logical steps, one of which is the determination of parameters which are most influential on model results. A "sensitivity analysis" of these parameters is not only critical to model validation but also serves to guide future research efforts.

Modelers may conduct sensitivity analyses for a number of reasons including the need to determine: 1) which parameters require additional research for strengthening the knowledge base, thereby reducing output uncertainty; 2) which parameters are insignificant and can be eliminated from the final model; 3) which inputs contribute most to output variability; 4) which parameters are most highly correlated with the output; and 5) once the model is in production use, what consequence results from changing a given input parameter. There are many different ways of conducting sensitivity analyses and answering these questions, however, the various analyses may not produce identical results (Iman and Helton 1988).

Generally, sensitivity analyses are conducted by: 1) defining the model and its independent and dependent variables, 2) assigning probability density functions to each input parameter, 3) generating an input matrix through an appropriate random sampling method, 4) calculating an output vector, and 5) assessing the influences and relative importance of each input/output relationship (Iman et al. 1981a; Iman et al. 1981b; Helton and Iman 1982; Helton et al. 1985; Helton et al. 1986).

The literature contains details on the types of sensitivity analyses utilized for various modeling situations. More than a dozen methods have been reviewed (Cukier et al. 1973; Morisawa and Inoue 1974; Krieger et al. 1977; Oblow 1978; Conover 1980; Gardner et al. 1980; Demiralp and Rabitz 1981; Gardner et al. 1981; Iman et al. 1981b; Hoffman and Gardner 1983; Downing et al. 1985; Helton et al. 1985; Crick et al. 1987; IAEA 1989; Iman and Helton 1991; Hamby 1993). This paper is a comprehensive assessment of several of the more practical methods for conducting parameter sensitivity studies, ranging from "local" sensitivity measures to standardized regression coefficients to statistical tests based on partitioning of empirical input distributions. Generally, method practicality is determined based on the calculational ease and the usefulness of results. Conceptual descriptions of methods are given so that investigators conducting sensitivity analyses can judge the relative merits weighted against the expense, resource drain, and usefulness of each technique. Discussions of the following sensitivity analysis techniques are included: differential analysis, one-at-a-time design, the derivation of sensitivity and importance indices, subjective analysis, construction of scatter plots, the relative deviation method, relative deviation ratios, correlation coefficients, rank transformation, rank correlation coefficients, partial correlation coefficients, regression techniques, standardized regression techniques, the Smirnov test statistic, the Cramer-von Mises test, Mann-Whitney test, and the squared ranks test.

A few of the sensitivity analysis techniques currently in the literature are intended for highly complex or very large models and are discussed below only briefly. These include methods using adjoint equations (Oblow 1978), Fourier analysis (Cukier et al. 1973; Helton et al. 1991), and Green's functions (Demiralp and Rabitz 1981). The adjoint method has been demonstrated by several investigators in the fields of climatological modeling, reactor thermal hydraulics, and reactor safety (Koda et al. 1979; Cacuci et al. 1980; Cacuci et al. 1983; Hall et al. 1982). In this approach, 'exact' (Downing et al. 1985)

sensitivities are calculated as defined by partial derivatives. The Fourier amplitude sensitivity test (FAST) (Cukier et al. 1973; Cukier et al. 1978) has been used to solve coupled nonlinear rate equations by Schaibly and Shuler (1973) and Cukier et al. (1975). FAST also has been used by Dickinson and Gelinas (1976) to study sensitivities of parameters used to model atmospheric chemical kinetics, by Koda et al. (1979) to study atmospheric diffusion, and several others (Leipmann and Stephanopoulos 1985; Kim et al. 1988). Theoretical aspects of a method using Green's functions are presented by Demiralp and Rabitz (1981). In this method, Green's functions are used to avoid solving the differential equations for each model parameter each time the base-case parameter values are changed (Hall et al. 1982). Iman and Helton (1985) briefly discuss and apply all three methods.

SENSITIVITY ANALYSIS METHODS

Many authors, when referring to the degree to which an input parameter affects the model output, use "sensitive", "important", "most influential", "major contributor", "effective", or "correlated" interchangeably (Krieger et al. 1977; Downing et al. 1985; Iman 1987; Iman and Helton 1988; Marguiles et al. 1991). Crick et al. (1987) have referred to "important" parameters as those whose uncertainty contributes substantially to the uncertainty in assessment results, and "sensitive" parameters as those which have a significant influence on assessment results. The consensus among authors is that models are sensitive to input parameters in two distinct ways: 1) the variability, or uncertainty, associated with a sensitive input parameter is propagated through the model resulting in a large contribution to the overall output variability, and 2) model results can be highly correlated with an input parameter so that small changes in the input value result in significant changes in the output.

The necessary distinction between important and sensitive parameters is in the type of analysis being conducted: uncertainty analysis (parameter importance) or sensitivity analysis (parameter sensitivity). An important parameter is always sensitive because parameter variability will not appear in the output unless the model is sensitive to the input. However, a sensitive parameter is not necessarily important because the sensitive parameter may be known precisely, thereby having little variability to add to the output.

At the completion of an analysis on parameter sensitivity the analyst holds a list, or "sensitivity ranking", of the input parameters sorted by the amount of influence each has on the model output. More than a dozen sensitivity techniques are described, each of which would result in a slightly different sensitivity ranking. The actual ranking is not as important as is the specification of which parameters consistently appear near the top of the list. Disagreement among rankings by the various methods for variables of lesser importance is not of practical concern since these variables have little or no affect on model output.

Throughout this paper a generalized model is utilized that contains several independent variables, $X = (X_1, \dots, X_n)$, and one dependent variable Y , where $Y = f(X)$. These methods also can be applied to models with several dependent variables. Sensitivity methods will be addressed in three groups: 1) those that operate on one variable at a time, 2) those that rely on the generation of an input matrix and an associated output vector, and 3) those that require a partitioning of a particular input vector based on the resulting output vector.

Differential Sensitivity Analysis. Differential analysis, also referred to as the direct method, is discussed first since it is the backbone of nearly all other sensitivity analysis techniques. Methods in the literature range from solving simple partial derivatives to spatial and temporal sensitivity analyses (Morisawa and Inoue 1974; Atherton et al. 1975; Dickinson and Gelinas 1976; Koda et al. 1979; Nguyen 1980; Dunker 1981; Gardner et al. 1981; Scavia et al. 1981; Summers and McKellar 1981; Koda 1982; Helton et al. 1985; Iman and Helton 1985; Helton et al. 1986; Iman and Helton 1988; Helton et al. 1991; Zimmerman et al. 1991).

A sensitivity coefficient is basically the ratio of the change in output to the change in input while all other parameters remain constant (Krieger et al. 1977). The model result while all parameters are held constant is defined as the "base case". Differential techniques are structured on the behavior of the model given a specific set of parameter values, e.g., assuming the base-case scenario is with all parameter values set to their mean. Morisawa and Inoue (1974) use the differential method as a means of selecting desirable conditions for underground waste disposal sites in Japan. They note, however, that, with the direct method, the magnitude of variable sensitivity is dependent on the base-case scenario. A major drawback is that this localized behavior may not be applicable for realms far from the base case.

Differential analysis of parameter sensitivity is based on partial differentiation of the model in aggregated form. It can be thought of as the propagation of uncertainties (Cunningham et al. 1980). A first-order Taylor series approximation is applied to the dependent variable, Y , as a function of the independent variables $X = (X_1, \dots, X_n)$. The variance of Y , $V(Y)$, is calculated using the general error propagation formula, i.e.,

$$V(Y) = \sum_{i=1}^n \left(\frac{\partial Y}{\partial X_i} \right)^2 V(X_i).$$

The variance in Y is utilized as a measure of uncertainty in model predictions while the variance in X_i , weighted by the first-order partial of Y with respect to X_i , provides a measure of model sensitivity to X_i (Helton et al. 1985). This method is a linearized theory and is valid only for small parameter uncertainties (Koda et al. 1979). A statistical sensitivity analysis consists of computing the variance and the expected value of each model output and ranking the contributions to the variance (Atherton et al. 1975). Iman (1987) uses a matrix-based approach to solving the partial derivatives since matrix notation is efficient and because it allows for the analysis of large problems. Several recent investigations have utilized the GRESS (Gradient Enhanced Software System) computer code, developed at Oak Ridge National Laboratory (Worley and Horwedel 1986; Horwedel et al. 1988), to calculate sensitivity coefficients using the direct method (Helton et al. 1991; Yu et al. 1991; Zimmerman et al. 1991).

Sensitivity analyses using partial differentiation techniques are computationally efficient (Helton et al. 1985), however, the effort required in solving these equations can be quite intensive. Derivatives of simple functions may be generated by less rigorous analytical or differencing schemes, but more complicated models often require complex numerical procedures (Iman and Helton 1988). When an explicit algebraic equation describes the relationship between the independent variables and the dependent variable, the sensitivity analysis is easy to perform (Atherton et al. 1975). In this case, the sensitivity coefficient, ϕ_i , for a particular independent variable can be calculated from the partial derivative of the dependent variable with respect to the independent variable, i.e.,

$$\phi_i = \frac{\partial Y}{\partial X_i} \left(\frac{X_i}{Y} \right)$$

where the quotient, X_i/Y , is introduced to normalize the coefficient by removing the affects of units. Inherent to this calculation are the assumptions that the higher ordered partials are negligible and there is no correlation between input parameters (Atherton et al. 1975; Gardner et al. 1981). For large sets of equations, the partial derivative can be approximated as a finite difference and output values calculated for small changes in the input parameter (Downing et al. 1985). Thus, if non-linearities are neglected (Nguyen 1980), the partial derivative can be approximated as,

$$\phi_i = \frac{\% \Delta Y}{\% \Delta X_i}$$

Gardner et al. (1981) report that the partial derivative approach to sensitivity analysis may become so complex that implementation is impractical. Also, since this approach is only valid for small changes in parameter values, when parameter variability is allowed to take on "realistic" values, the direct approach is seriously violated (Gardner et al. 1981). The differential analysis is typically much more demanding to implement than other sensitivity methods and yet provides comparable results.

Measure of "Local" Sensitivity. Conceptually, the simplest method to sensitivity analysis is to repeatedly vary one parameter at a time while holding the others fixed (Gardner et al. 1980; O'Neill et al. 1980; Merkhofer 1981; Downing et al. 1985; Bandrowski et al. 1986; Breshears 1987; Crick et al. 1987; Bandrowski 1988; Bandrowski 1989; Yu et al. 1991). A sensitivity ranking can be obtained quickly by increasing each parameter by a given percentage while leaving all others constant, and quantifying the change in model output. This type of analysis has been referred to as a

"local" sensitivity analysis (Crick et al. 1987) since it only addresses sensitivity relative to the point estimates chosen for the parameters held constant. The RESRAD code, developed at Argonne National Laboratory for the Department of Energy, calculates dose (or risk) to man from residual soil contamination (Gilbert et al. 1989; Yu et al. 1991). The package contains a routine that uses the local sensitivity method by varying user-specified parameter values and printing a graphical representation of parameter sensitivity over time.

A more powerful test of local sensitivity examines the change in output as each parameter is individually increased by a factor of its standard deviation. This sensitivity measure takes into account the parameter's variability and the associated influence on model output. Downing et al. (1985) call this method a "one-at-a-time" design and typically evaluate parameters at their mean value and then vary them by ± 4 standard deviations to measure the effect on the output.

The Sensitivity Index. Another of the simple methods of determining parameter sensitivity is to calculate the output percent difference when varying one input parameter from its minimum value to its maximum value (Hoffman and Gardner 1983; Simon 1987; Bauer and Hamby 1991). Hoffman and Gardner (1983) advocate utilizing each parameter's entire range of possible values in order to assess true parameter sensitivities. The "sensitivity index" (SI) is calculated using,

$$SI = \frac{D_{\max} - D_{\min}}{D_{\max}}$$

where $D_{\min}$ and $D_{\max}$ represent the minimum and maximum output values, respectively, resulting from varying the input over its entire range (Hoffman and Gardner 1983). This figure-of-merit provides a good indication of parameter and model variability.

Subjective Sensitivity Analysis. The final sensitivity method based on analysis of individual parameters is the subjective method (Downing et al. 1985). The method is rather simple and only qualitative since it relies on the opinions of experienced investigators to determine, *a priori*, which parameters can be discarded due to lack of influence on model results. One advantage is that, for large models, where most other methods are impractical, the subjective method can be used as a first cut to reduce the number of input parameters to a manageable size.

Parameter Sensitivity Analysis Utilizing Random Sampling Methods

To this point, sensitivity has been assessed on parameters one-at-a-time without regard to the combined variability resulting from considering all input parameters simultaneously. Random sampling (e.g., simple random sampling, Monte Carlo, Latin hypercube, etc.) of input parameters generates input and output distributions useful in assessing model and parameter uncertainties in a "global" sense (McKay et al. 1979; Iman and Conover 1980; Iman et al. 1981a; Scavia et al. 1981; Helton and Iman 1982; Iman and Conover 1982; Iman and Shortencarier 1984; Reed et al. 1984; Downing et al. 1985; Kim et al. 1985; Iman 1987; Helton et al. 1991). Gardner et al. (1980) refer to parameter sensitivity studies of this type as "parameter error analysis".

A large array of randomly selected input parameter values and calculated output values provides a means for determining parameter sensitivity through a variety of procedures. The influence of other input parameters is meaningful to consider in uncertainty and sensitivity analyses since overall model performance is of importance. Distribution effects are meaningful because parameter sensitivity depends, not only on the range and distribution of an individual input parameter, but also on those of other parameters to

which the model is sensitive (Iman et al. 1981a). Parameter sensitivity is dependent on the interactions and influences of all parameters.

Scatter Plots. Parameter sensitivity can be determined qualitatively by plots of input vs output values, or quantitatively by calculations of correlation coefficients or regression analysis. Scatter plots of input vs output are useful for quick determinations of the degree of correlation and the linearity of the input/output relationship (Helton et al. 1986; Crick et al. 1987; Iman and Helton 1988; Helton et al. 1991; Helton et al. 1993). They may also reveal unexpected relationships between input and output variables that can provide insight as to how other investigations (e.g., regression analysis) might be performed.

The Importance Index. Hoffman and Gardner (1983) have also introduced an "importance index", I_i , which is equal to the variance of the parameter value, $s_{X_i}^2$, divided by the variance of the dependent values, s_Y^2 , i.e.,

$$I_i = \frac{s_{X_i}^2}{s_Y^2}$$

where s refers to the variance of the raw data for additive models and to the variance of the log-transformed values for multiplicative models. This measure of importance is based on the parameter's fractional contribution to total variability, or uncertainty. Variable importance is estimated by Cunningham et al. (1980) through the use of a combination of the fractional contribution to output variability and the resulting change in output given individual change in input.

Importance Factors. Downing et al. (1985) have introduced three importance factors. Their measures are calculated from data collected after a five-point one-at-a-time analysis; model output is recorded for each parameter at its mean value, ± 2 standard

deviations, and ± 4 standard deviations. The first importance factor is defined as parameter uncertainty (defined as two standard deviations of the input) multiplied by parameter sensitivity (defined as the change in output divided by change in input). The second is the positive difference in the maximum output value and the minimum output value. And, third, they estimate importance utilizing the output sample variance.

The "Relative Deviation" Method. One sensitivity ranking method utilizes random sampling techniques and measures the amount of variability introduced into the model output while varying one-at-a-time each input parameter according to its probability density function. This method is similar to the local sensitivity method with the exception that a much larger sampling is made of the input distribution. The sensitivity figure-of-merit is the "relative deviation" (RD), the ratio of the standard deviation to the mean of the output's density function (Hamby 1993), and is similar to the coefficient of variation (standard deviation $\times$ 100 / mean). This test provides an indication of each parameter's contribution to the variability present in the model output and, to a degree, the extent of correlation that exists between the input and output variable.

The "Relative Deviation Ratio". Given two input distributions, one narrow and one wide, producing identical output distributions, the model is more sensitive to the input parameter of the narrow distribution. This test statistic will, therefore, be the ratio of the output distribution's relative deviation to the input distribution's relative deviation and is similar to the importance index proposed by Hoffman and Gardner (1983). A large value of this "relative deviation ratio" (RDR) indicates that either the output distribution varies widely or that the input distribution is relatively narrow. Additionally, information on the amount of variability added to the total output variability by the model itself is gained from this statistic. A value greater than unity indicates that uncertainty propagated through the model is being increased due to the model's structure and its high sensitivity

to that particular variable. An RDR of 1 indicates that all input uncertainty is passed through the model and appears as output uncertainty, while a value less than unity indicates that the model is less sensitive to the parameter, thereby contributing to output uncertainty to a lesser degree.

Pearson's r . A quantitative estimate of linear correlation can be determined by calculating a simple correlation coefficient on the parameter values of input and output. Gardner et al. (1981) recommend using simple correlation coefficients, derived from Monte Carlo simulations, as a reasonable way to rank model parameters according to their contribution to prediction uncertainty. Pearson's product moment correlation coefficient is denoted by r and is defined as,

$$r = \frac{\sum_{j=1}^n (X_{ij} - \bar{X}_i) (Y_j - \bar{Y})}{\left[\sum_{j=1}^n (X_{ij} - \bar{X}_i)^2 \sum_{j=1}^n (Y_j - \bar{Y})^2 \right]^{1/2}}$$

for the correlation between X_i and Y (Conover 1980). The larger the absolute value of r the stronger the degree of linear relationship between the input and output values (IAEA 1989). A negative value of r indicates the output is inversely related to the input. A linear regression on the data can be used to determine the correlation coefficient from the square root of the coefficient of determination, R^2 .

Major drawbacks of utilizing the correlation coefficient for sensitivity ranking include the inherent assumption that the input/output relationship is linear and the possibility that input parameters strongly correlated to one another may result in apparent input/output

correlations (Hoffman and Gardner 1983; Crick et al. 1987; IAEA 1989). In addition, a large number of trials may prohibit hand calculations of the correlation coefficient.

The Rank Transformation. One of the problems encountered in calculating test statistics, e.g., correlation coefficients, from raw data is that the data are not necessarily linear. A method of reducing the effects of nonlinear data is to use the rank transformation (Iman and Conover 1979). The transformation of raw data into ranks has been shown to work quite well if the dependent variable is a monotonic function of the independent variables (Iman and Conover 1979). Rank transformation linearizes monotonic nonlinear relationships between variables and reduce the effects of extreme values (Helton and Iman 1982). This transformation converts the sensitivity measure from one of linearity to one of monotonicity.

Spearman's ρ . If the input/output associations are monotonic then rank transformations of the input and output values (i.e., replacing the values with their ranks) will result in linear relationships and the rank correlation coefficient will indicate the degree of monotonicity between the input and output sample values (IAEA 1989). The rank correlation coefficient, or Spearman's ρ , can be calculated using the equation for Pearson's r with the exception of operating on the rank transformed data (Iman and Conover 1979).

The Partial Correlation Coefficient. Strong correlations between input parameters may influence input/output correlations. Partial correlation coefficients (PCC) are calculated to account for correlations among other input variables (Gardner et al. 1980; Gardner et al. 1981; Iman et al. 1981a; Iman and Conover 1982; Otis 1983; Downing et al. 1985; Iman and Helton 1985; Breshears 1987; Whicker and Kirchner 1987; Iman and Helton 1988; IAEA 1989; Whicker et al. 1990; Iman and Helton 1991; Helton et al. 1993).

Given random variables X_1 and X_2 as input and the output variable Y , a partial correlation coefficient is a measure of the correlation between X_1 and Y , for example, while eliminating indirect correlations due to relationships that may exist between X_1 and X_2 or X_2 and Y . The PCC is defined as (Conover 1980),

$$r_{X_1 Y | X_2} = \frac{r_{X_1 Y} - r_{X_1 X_2} r_{X_2 Y}}{\sqrt{(1 - r_{X_1 X_2}^2)(1 - r_{X_2 Y}^2)}}$$

where the notation $r_{X_1 Y | X_2}$ represents the partial correlation coefficient for X_1 and Y while accounting for the affects of X_2 . The parameters of the generic model considered in this report are assumed to be independent and no correlations have been assigned, i.e., $r_{X_1 X_2} = 0$. Therefore, $r_{X_1 Y | X_2}$ reduces to,

$$r_{X_1 Y | X_2} = \frac{r_{X_1 Y}}{\sqrt{1 - r_{X_2 Y}^2}}$$

where, again, X_1 and X_2 represent any two input variables and Y represents the output variable. The square of the partial correlation coefficient is useful in determining the percentage of variability in Y accounted for by variability in X_i (Gardner et al. 1981). Sensitivity rankings based on the relative values of the partial correlation coefficients will not change from the rankings determined based on the simple correlation coefficients. Therefore, with no correlations existing between input parameters, there is no need for calculating partials to determine sensitivity rankings.

The rank transformation also can be applied to partial correlation as a test of monotonicity between input and output variables while accounting for relationships between input parameters. The partial rank correlation coefficient (PRCC) is widely utilized for sensitivity studies (Iman et al. 1981a; Iman et al. 1981b; Crick et al. 1987; Iman and Helton 1988; IAEA 1989; Iman and Helton 1991). Downing et al. (1985)

compared sensitivity rank orders determined using partial rank correlation with orders from their three importance rankings (see above section on Importance Index). They report the PRCC to be more powerful at indicating the sensitivity of a parameter that is strongly monotonic yet highly nonlinear.

Regression Techniques. Regression methods are often used to replace a highly complex model with a simplified "response surface" (Cox 1977; Iman et al. 1978; Nguyen 1980; Iman et al. 1981a; Iman et al. 1981b; Helton and Iman 1982; Downing et al. 1985; Kim et al. 1985; Iman and Helton 1988; Helton et al. 1991). The response surface is simply a regression equation that approximates model output using only the most sensitive model input parameters. Stepwise regression procedures are utilized to ensure that the final regression model provides for the best fit of raw data (Iman et al. 1978; Iman and Conover 1980; Iman et al. 1981b; Iman and Conover 1982; Helton and Iman 1982; Reed et al. 1984; Helton et al. 1985; Helton et al. 1986; IAEA 1989; Iman and Helton 1991; Zimmerman et al. 1991; Helton et al. 1991; Helton et al. 1993). The stepwise regression may involve higher ordered equations, quadratic terms, and parameters as functions of other parameters.

Regression coefficients provide a means of applying sensitivity rankings to input parameters and have been used for such in several investigations (Iman and Conover 1980; Iman et al. 1981b; Helton et al. 1985; Kim et al. 1985; Helton et al. 1986; Whicker and Kirchner 1987; Whicker et al. 1990; Margulies et al. 1991; Zimmerman et al. 1991; Helton et al. 1993; Helton et al. 1993). A model with many sensitive parameters may result in a complex regression equation. Matrix techniques have been utilized in such cases to calculate the regression coefficients (Krieger et al. 1977).

The generalized form of a simple regression equation is,

$$\hat{Y} = b_0 + \sum_k b_k Z_k$$

where each Z_k is a predictor variable and a function of $(X_1, \dots, X_n)$ and each b_k is a regression coefficient (Helton et al. 1985; Helton et al. 1986). The use of the regression technique allows the sensitivity ranking to be determined based on the relative magnitude of the regression coefficient. This value is indicative of the amount of influence the parameter has on the whole model. Because of units and the relative magnitudes of parameters, a standardization process is sometimes warranted.

Standardized Regression Techniques. Standardization takes place in the form of a transformation by ranks or by the ratio of the parameter's standard deviation to its mean. The effect of the standardization is to remove the influence of units and place all parameters on an equal level. Standardized regression analyses are performed by Iman and Helton (Helton et al. 1985; Iman and Helton 1988; Iman and Helton 1991).

The calculation of a standardized rank regression coefficient (SRRC), i.e., standardization by the rank transformation, is a simple procedure requiring less computation. Utilizing means and standard deviations of input and output data sets (the standardized regression coefficient, SRC), however, is slightly more rigorous and is achieved by,

$$\frac{(\hat{Y} - \bar{Y})}{s} = \sum_k \left[\frac{b_k s_k}{s} \right] \frac{(Z_k - \bar{Z}_k)}{s_k}$$

where each Z_k is a function of $(X_1, \dots, X_n)$, s is the standard deviation of the output, and s_k is the standard deviation of the input (Helton et al. 1985; Helton et al. 1986). If each

Z_k is a function of only one parameter in X , then the value of $\frac{b_k s_k}{s}$ is the standardized regression coefficient for parameter X_k , where $k = 1$ to n .

The PRCC estimated in the section above and the standardized regression coefficient are essentially the same when using ranks; the numerical values may be different but both exhibit the same pattern of sensitivity ranking (Iman and Helton 1988).

Sensitivity Tests Involving Segmented Input Distributions

These statistical tests involve dividing or segmenting input parameter distributions into two or more empirical distributions based on an associated partitioning of the output (Crick et al. 1987). The tests are utilized to compare the characteristics of the input distributions created by the segmentation. For example, if a dose distribution is calculated and the median value of the distribution is chosen as the dividing point, all input values for the parameter in question associated with the calculation of a dose value below the median are said to belong to one random sample while the input values associated with dose estimates above the median belong to a second random sample. Means, medians, variances, and other characteristics of the independent random samples are statistically compared to determine whether the samples originated from the same population. Division of the output distribution can occur at any value or percentile, but should be based on the statistical question to be answered, e.g., "is the model more sensitive to the parameter when determining the mean value or when estimating maximum values." If the input distributions generated by this process are statistically identical then the model is not sensitive to that parameter. However, if the distributions are different then the output distribution is indeed influenced by the input and the absolute value of the test statistic can be used to perform the sensitivity ranking.

Standard parametric tests are not reasonable on input data sets generated by random sampling methods because of our limited knowledge of the input variables and their associated distributions (Iman et al. 1981b). Nonparametric statistical tests, therefore, are used where the data are considered to be distribution-free (Conover 1980). The four nonparametric statistical tests that follow (Smirnov, Cramer-von Mises, Mann-Whitney, and Squared Ranks) are used to determine whether the null hypothesis can be accepted. The Smirnov and Cramer-von Mises tests compare empirical distributions with a null hypothesis of "the distributions originate from the same population." The Mann-Whitney test and the Squared Ranks test compare means and variances, respectively, of the empirical distributions. These test statistics are calculated, however, for the purpose of sensitivity ranking and not for accepting or rejecting null hypotheses.

The convention stated earlier, that Y is a function of X ($Y = f\{X_1, \dots, X_n\}$), is no longer appropriate; a new notation is used and specified for each test. The following tests operate on ranks of the raw data. Tied values are assumed not to exist because the input and output values can be determined to several significant figures (although this feature does not reflect a high degree of precision). By excluding the possibility of ties, equations for calculating the test statistics are greatly simplified (Conover 1980).

The Smirnov Test. The Smirnov test operates on the two empirical distributions, $S_1(x)$ and $S_2(x)$, generated as a result of partitioning the input parameter values. The degree of similarity between distributions, measured by the test statistic, is used to indicate the degree of correlation, i.e. sensitivity, between the input and output values.

The Smirnov test statistic can be measured directly as the greatest vertical distance between the two distribution functions plotted on the same graph (see Fig. 1), or the test statistic can be calculated using,

$$T_1 = \sup |S_1(x) - S_2(x)|$$

where "sup" is the abbreviation for supremum and the equation represents the greatest absolute difference between $S_1(x)$ and $S_2(x)$ (Conover 1980). In the example of Fig. 1, a plot of two empirical distributions of input values resulting in an output less than the median and input values resulting in an output greater than the median. The value of Smirnov statistic can be taken from the plot or its accuracy can be increased by calculating T_1 from the two empirical distributions.

The Cramer-von Mises Test. The Cramer-von Mises test is very similar to the Smirnov test in that its purpose is to determine whether two empirical distributions are statistically identical. The computation of the test statistic is slightly more complicated, yet there is little difference in the test's power compared to the Smirnov statistic (Conover 1980). The Cramer-von Mises statistic is the sum of all squared vertical distances between the two empirical distributions,

$$T_2 = \frac{mn}{(m+n)^2} \sum [S_1(x) - S_2(x)]^2$$

where the values of n and m are the number of samples utilized to estimate the distributions. It is expected that the parameter rankings based on the Smirnov and Cramer-von Mises tests will be very similar since the two tests show little difference in their statistical power.

Recall that a large Smirnov or Cramer-von Mises statistic is indicative of a larger difference in the two empirical distributions generated by the division of input data based

on some output criteria. This large difference indicates a greater correlation between the independent and dependent variables.

The Mann-Whitney Test. The Mann-Whitney test, also known as the Wilcoxon test, is utilized to compare the means of two independent samples (Conover 1980). Two distribution functions, X and Y, are ordered as a single sample and ranks are assigned based on the ordering; ties are assumed not to exist. The test statistic, T, is the sum of the resulting ranks of the data from distribution X,

$$T = \sum_{i=1}^n R(X_i)$$

where $R(X_i)$ refers to the rank of X_i . In theory, if one sum of the single-sample ranks is much larger than the other, the two sample means are different (Conover 1980), i.e., the test statistic is either very small or very large. The use of ranks in the Mann-Whitney test is preferred over the use of raw data since probability theory doesn't depend on distribution-type when operating on ranks (Conover 1980).

For hypothesis testing, a range is calculated in order to accept or reject the null hypothesis that the two distributions have the same mean value. A calculated test statistic larger than the midpoint indicates that the mean value of the first empirical distribution is larger than the mean value of the second. Since the Mann-Whitney test is two-tailed, sensitivity ranks are based on an adjusted value of T. The adjusted statistic is either the value of the test statistic itself, if it is less than the midpoint of the comparison range, or the test statistic minus twice the difference between T and the midpoint, if it is greater than the midpoint. For example, if the midpoint of the comparison range is 500 and a value of 400 is calculated for T, the adjusted value of T remains 400. If, however, the calculated T is 550, the adjusted value becomes 450. Then, smaller values of T indicate

the more sensitive parameters since the means of the distributions show a greater difference based on the partitioning of input data.

The Squared Ranks Test. The variances of two independent samples, X and Y , can be compared using the squared ranks test. Ranks are not based on the raw data, rather on the absolute difference between the random sample (e.g., X_i) and the sample mean (e.g., μ_x). There are assumed to be no ties and the ranks are assigned to a single sample of the two distributions based on this transform. The ranks then are squared, to provide more statistical power (Conover 1980), and summed in a fashion similar to the Mann-Whitney test. The test statistic, T , is equal to

$$T = \sum_{i=1}^n [R(U_i)]^2$$

where

$$U_i = |X_i - \mu_x|.$$

For parameter ranking purposes, the normalization procedure executed on the Mann-Whitney statistic also is necessary with the squared ranks statistic.

Based on numerical comparisons to other sensitivity tests, the squared ranks test does not appear to be of much value for parameter sensitivity rankings. Uncertainty analyses may benefit, however, in that the amount of variability in the output distribution may be shown to be influenced by input values that result in either high or low output values.

SUMMARY AND DISCUSSION

A number of sensitivity analysis techniques have been presented. The majority of investigators utilize only a few of the methods including partial differentiation, partial correlation, and regression techniques. Investigators report on sensitivity theory and techniques related to environmental transport, reactor safety, chemical kinetic models, radiation dosimetry, multi-compartment ecological models, and general mathematical and statistical theory.

The simplest approach to sensitivity analysis is the one-at-a-time method where sensitivity measures are determined by varying each parameter while all others are held constant. Standardized regression analysis using a stepwise regression procedure appears to be the most comprehensive technique and is relatively easy to perform with commercially available computer software. If possible, complex models should be carried through an aggregating process in the screening stage to simplify the model's structure and reduce the number of input parameters.

The most fundamental of sensitivity techniques is the direct method. Direct sensitivity analysis involves calculating partial derivatives of the model with respect to each input parameter. The technique is only valid for small variability in parameter values and the partials must be recalculated for each change in the base-case scenario (e.g., all parameters set to their mean value). As stated above, "local" sensitivity methods, or one-at-a-time analyses, are conceptually the simplest methods. These too are valid only for the base-case. When working with complex models a subjective analysis, whereby experienced modelers discard unimportant variables, may be necessary as a screening tool to reduce the number of parameters to a manageable size.

"Global" sensitivity analyses examine parameter influence based on output variation while simultaneously changing input parameters. These methods are easily performed by utilizing a random sampling technique to build an input matrix and then calculating an output vector. Correlation, rank correlation, and partial rank correlation coefficients can be calculated to determine relationships between the independent and dependent variables. Rank transformations are often utilized to eliminate the forced assumption of linear correlations among the raw data. Correlation and regression methods are generally performed on rank transformed data. Investigators typically calculate partial correlations to eliminate influences of correlations between two or more input parameters. Regression analysis is commonly utilized to build response surfaces that approximate complex models and to investigate parameter sensitivity. Standardized regression coefficients are used as sensitivity measures since the standardization process removes the effect of units and places all parameters on a comparable level.

Crick et al. (1987) propose statistically analyzing selected input vectors by segmenting input values based on their relationship to some critical output value (e.g., the mean, median, or 90th percentile of the output distribution). This type of analysis provides detailed information on parameter sensitivity based on the calculated output. Non-parametric statistical tests are used to determine whether the inputs contributing to an output less than the critical value are any different than the inputs contributing to an output greater than the critical value. For example, the analysis may show that a model is much more sensitive to a particular input when the output is greater than its mean value. The non-parametric tests on partitioned data sets are labor intensive and are not necessarily beneficial unless a particular question is to be answered regarding the sensitivity of a parameter with respect to the range of the model output.

Generally, the purpose of a sensitivity analyses is to determine which input parameters exert the most influence on model results. This information, in turn, allows for unimportant parameters to be eliminated and provides direction for further research in order to reduce parameter uncertainties and increase model accuracy. Strict adherence to sensitivity rankings, therefore, is not as important as is the determination of the top several parameters to which the model is most sensitive. While some sensitivity methods are mathematically elegant and comprehensive, their use is inefficient and their results, in many cases, are comparable to those obtained from simpler techniques. Since few studies exist that indicate the superiority of one approach over another, a study is underway to compare the methods numerically and provide recommendations on their use.

Acknowledgement. The author would like to thank Drs. L.R. Bauer, W.H. Carlton, and R.C. Tuckfield for their critical reviews of this manuscript. This work was supported by the U.S. Department of Energy under Contract No. DE-AC09-89SR18035 with the Westinghouse Savannah River Company.

CAPTIONS

Figure 1. Example of the graphical determination of the Smirnov statistic. The value of T_1 is a measure of the disparity of the two empirical distributions.

REFERENCES

Atherton, R.W.; Schainker, R.B.; Ducot, E.R. 1975. On the statistical sensitivity analysis of models for chemical kinetics. *AIChE*. 21:441-448.

Bandrowski, M.S. 1988. Sensitivity analysis of EPA's codes used to assess health impact from LLW disposal alternatives. In: Proceedings of the ninth annual DOE low-level waste management forum. Denver, CO: U.S. Department of Energy, Report No. CONF-870859; 12-26.

Bandrowski, M.S. 1989. Scenario sensitivity analyses performed on the PRESTO-EPA LLW risk assessment models. In: Proceedings of the tenth annual DOE low-level waste management conference. Denver, CO: U.S. Department of Energy, Report No. CONF-880839; 84-98.

Bandrowski, M.S.; Hung, C-Y.; Meyer, G.L. 1986. Sensitivity analysis of EPA's codes for assessing potential health risks from disposal of low-level wastes. In: Proceedings of the seventh annual participants' information meeting DOE low-level waste management program. Las Vegas, NV: U.S. Department of Energy; Report No. CONF-8509121; 757-774.

Bauer, L.R.; Hamby, D.M. 1991. Relative sensitivities of existing and novel model parameters in atmospheric tritium dose estimate. *Radiation Protection Dosimetry*. 37:253-260.

Breshears, D.D. 1987. Uncertainty and sensitivity analyses of simulated concentrations of radionuclides in milk. Fort Collins, CO: Colorado State University; MS Thesis; 1-69.

Cacuci, D.G.; Weber, C.F.; Oblow, E.M.; Marable, J.H. 1980. Sensitivity theory for general systems of nonlinear equations. *Nuclear Science and Engineering*. 75:88-110.

Cacuci, D.G.; Maudlin, P.J.; Parks, C.V. 1983. Adjoint sensitivity analysis of extremum-type responses in reactor safety. *Nuclear Science and Engineering*. 83:112-135.

Conover, W.J. 1980. Practical nonparametric statistics. 2nd Edition. John Wiley & Sons, New York.

Cox, N.D. 1977. Comparison of two uncertainty analysis methods. *Nuclear Science and Engineering*. 64:258-265.

Crick, M.J.; Hill, M.D.; Charles, D. 1987. The role of sensitivity analysis in assessing uncertainty. In: Proceedings of an NEA workshop on uncertainty analysis for performance assessments of radioactive waste disposal systems. Paris: OECD; 1-258.

Cukier, R.I.; Fortuin, C.M.; Shuler, K.E.; Petschek, A.G.; Schaibly, J.H. 1973. Study of the sensitivity of coupled reaction systems to uncertainties in rate coefficients. I. Theory. *Journal of Chemical Physics*. 59:3873-3878.

Cukier, R.I.; Levine, H.B.; Schuler, K.E. 1978. Nonlinear sensitivity analysis of multiparameter model systems. *Journal of Computational Physics*. 26:1-42.

Cukier, R.I.; Schaibly, J.H.; Shuler, K.E. 1975. Study of the sensitivity of coupled reaction systems to uncertainties in rate coefficients. III. Analysis of the approximations. *Journal of Chemical Physics*. 63:1140-1149.

Cunningham, M.E.; Hann, C.R.; Olsen, A.R. 1980. Uncertainty analysis and thermal stored energy calculations in nuclear fuel rods. *Nuclear Technology*. 47:457-467.

Demiralp, M.; Rabitz, H. 1981. Chemical kinetic functional sensitivity analysis: elementary sensitivities. *Journal of Chemical Physics*. 74:3362-3375.

Dickinson R.P.; Gelinas, R.J. 1976. Sensitivity analysis of ordinary differential equation systems - a direct method. *Journal of Computational Physics*. 21:123-143.

Downing, D.J.; Gardner, R.H.; Hoffman, F.O. 1985. An examination of response-surface methodologies for uncertainty analysis in assessment models. *Technometrics*. 27:151-163.

Dunker, A.M. 1981. Efficient calculation of sensitivity coefficients for complex atmospheric models. *Atmospheric Environment*. 15:1155-1161.

Gardner, R.H.; Huff, D.D.; O'Neill, R.V.; Mankin, J.B.; Carney, J.; Jones, J. 1980. Application of error analysis to a marsh hydrology model. *Water Resources Research*. 16:659-664.

Gardner, R.H.; O'Neill, R.V.; Mankin, J.B.; Carney, J.H. 1981. A comparison of sensitivity analysis and error analysis based on a stream ecosystem model. *Ecological Modelling*. 12:173-190.

Gilbert, T.L. et al. 1989. A manual for implementing residual radioactive material guidelines. Argonne, IL: Argonne National Laboratory; Report No. DOE/CH/8901.

Hall, M.C.G.; Cacuci, D.G.; Schlesinger, M.E. 1982. Sensitivity analysis of a radiative-convective model by the adjoint method. *Journal of the Atmospheric Sciences*. 39:2038-2050.

Hamby, D.M. 1993. A probabilistic estimation of atmospheric tritium dose. *Health Physics*. 65:33-40.

Helton, J.C.; Garner, J.W.; Marietta, M.G.; Rechar, R.P.; Rudeen, D.K.; Swift, P.N. 1993. Uncertainty and sensitivity analysis results obtained in a preliminary performance assessment for the Waste Isolation Pilot Plant. *Nuclear Science and Engineering*. 114:286-331.

Helton, J.C.; Garner, J.W.; McCurley, R.D.; Rudeen, D.K. 1991. Sensitivity analysis techniques and results for performance assessment at the waste isolation pilot plant. Albuquerque, NM: Sandia National Laboratory; Report No. SAND90-7103.

Helton, J.C.; Iman, R.L. 1982. Sensitivity analysis of a model for the environmental movement of radionuclides. *Health Physics*. 42:565-584.

Helton, J.C.; Iman, R.L.; Brown, J.B. 1985. Sensitivity analysis of the asymptotic behavior of a model for the environmental movement of radionuclides. *Ecological Modelling*. 28:243-278.

Helton, J.C.; Iman, R.L.; Johnson, J.D.; Leigh, C.D. 1986. Uncertainty and sensitivity analysis of a model for multicomponent aerosol dynamics. *Nuclear Technology*. 73:320-342.

Hoffman, F.O.; Gardner, R.H. 1983. Evaluation of uncertainties in environmental radiological assessment models. In: Till, J.E.; Meyer, H.R. eds. *Radiological assessments: a textbook on environmental dose assessment*. Washington, DC: U.S. Nuclear Regulatory Commission; Report No. NUREG/CR-3332.

Horwedel, J.E.; Worley, B.A.; Oblow, E.M.; Pin, F.G.; Wright, R.Q. 1988. GRESS version 0.0 user's manual. Oak Ridge, TN: Oak Ridge National Laboratory; Report No. ORNL/TM-10835.

Iman, R.L. 1987. A matrix-based approach to uncertainty and sensitivity analysis for fault trees. *Risk Analysis*. 7:21-33.

Iman, R.L.; Conover, W.J. 1979. The use of the rank transform in regression. *Technometrics*. 21:499-509.

Iman, R.L.; Conover, W.J. 1980. Small sample sensitivity analysis techniques for computer models, with an application to risk assessment. *Communications in Statistics - Theory and Methods*. A9:1749-1842.

Iman, R.L.; Conover, W.J. 1982. Sensitivity-analysis techniques: self-teaching curriculum. Albuquerque, NM: Sandia National Laboratories; Report No. NUREG/CR-2350.

Iman, R.L.; Helton, J.C. 1985. A comparison of uncertainty and sensitivity analysis techniques for computer models. Albuquerque, NM: Sandia National Laboratory; Report No. NUREG/CR-3904.

Iman, R.L.; Helton, J.C. 1988. An investigation of uncertainty and sensitivity analysis techniques for computer models. *Risk Analysis*. 8:71-90.

Iman, R.L.; Helton, J.C. 1991. The repeatability of uncertainty and sensitivity analyses for complex probabilistic risk assessments. *Risk Analysis*. 11:591-606.

Iman, R.L.; Helton, J.C.; Campbell, J.E. 1978. Risk methodology for geologic disposal of radioactive waste: sensitivity analysis techniques. Albuquerque, NM: Sandia National Laboratories; Report No. NUREG/CR-0390.

Iman, R.L.; Helton, J.C.; Campbell, J.E. 1981a. An approach to sensitivity analysis of computer models: Part I - Introduction, input variable selection and preliminary assessment. *Journal of Quality Technology*. 13:174-183.

Iman, R.L.; Helton, J.C.; Campbell, J.E. 1981b. An approach to sensitivity analysis of computer models: Part II - Ranking of input variables, response surface validation, distribution effect and technique synopsis. *Journal of Quality Technology*. 13:232-240.

Iman, R.L.; Shortencarier, M.J. 1984. A FORTRAN 77 program and user's guide for the generation of Latin hypercube and random samples for use with computer models. Albuquerque, NM: Sandia National Laboratory; Report No. NUREG/CR-3624.

International Atomic Energy Agency (IAEA). 1989. Evaluating the reliability of predictions made using environmental transfer models. Vienna: Safety Series No. 100. Report No. STI/PUB/835; 1-106.

Kim, T.W.; Chang, S.H.; Lee, B.H. 1988. Uncertainty and sensitivity analyses in evaluating risk of high level waste repository. *Radioactive Waste Management and the Nuclear Fuel Cycle*. 10:321-356.

Koda, M.; Dogru, A.H.; Seinfeld, J.H. 1979. Sensitivity analysis of partial differential equations with application to reaction and diffusion processes. *Journal of Computational Physics*. 30:259-282.

Koda, M. 1982. Sensitivity analysis of the atmospheric diffusion equation. *Atmospheric Environment*. 16:2595-2601.

Krieger, T.J.; Durston, C.; Albright, D.C. 1977. Statistical determination of effective variables in sensitivity analysis. *Transactions of the American Nuclear Society*. 28:515-516.

Liepmann, D.; Stephanopoulos, G. 1985. Development and global sensitivity analysis of a closed ecosystem model. *Ecological Modelling*. 30:13-47.

Margulies, T.; Lancaster, L.; Kornasiewicz, R.A. 1991. Uncertainty and sensitivity analysis of environmental transport models for risk assessment. In: *Engineering applications of risk analysis*. Atlanta, GA: ASME; 11-19.

McKay, M.D.; Beckman, R.J.; Conover, W.J. 1979. A comparison of three methods for selecting values of input variables in the analysis of output from a computer code.

Technometrics. 21:239-245.

Merkhofer, M.W. 1981. Risk assessment: quantifying uncertainty in health effects. The Environmental Professional. 3:249-264.

Morisawa, S.; Inoue, Y. 1974. On the selection of a ground disposal site by sensitivity analysis. Health Physics. 26:251-261.

Nguyen, D.H. 1980. The uncertainty in accident consequences calculated by large codes due to uncertainties in input. Nuclear Technology. 49:80-91.

Oblow, E.M. 1978. Sensitivity theory for general nonlinear algebraic equations with constraints. Nuclear Science and Engineering. 65:187-191.

O'Neill, R.V.; Gardner, R.H.; Mankin, J.B. 1980. Analysis of parameter error in a nonlinear model. Ecological Modelling. 8:297-311.

Otis, M.D. 1983. Sensitivity and uncertainty analysis of the PATHWAY radionuclide transport model. Fort Collins, CO: Colorado State University; PhD Dissertation; 1-86.

Reed, K.L.; Rose, K.A.; Whitmore, R.C. 1984. Latin hypercube analysis of parameter sensitivity in a large model of outdoor recreation demand. Ecological Modelling. 24:159-169.

Scavia, D.; Powers, W.F.; Canale, R.P.; Moody, J.L. 1981. Comparison of first-order error analysis and Monte Carlo simulation in time-dependent lake eutrophication models. *Water Resources Research*. 17:1051-1059.

Schaibly, J.H.; Shuler, K.E. 1973. Study of the sensitivity of coupled reaction systems to uncertainties in rate coefficients. II. Applications. *Journal of Chemical Physics*. 59:3879-3888.

Simon, S.L. 1987. Uncertainty analysis and model validation for a retrospective assessment of thyroid dose resulting from atomic weapons' test fallout. In: *Proceedings of a Workshop on Methods for Assessing the Reliability of Environmental Transfer Model Predictions*. Athens, Greece: October 5-9.

Summers, J.K.; McKellar, H.N. 1981. A sensitivity analysis of an ecosystem model of estuarine carbon flow. *Ecological Modelling*. 13:283-301.

Whicker, F.W.; Kirchner, T.B. 1987. PATHWAY: A dynamic food-chain model to predict radionuclide ingestion after fallout deposition. *Health Physics*. 52:717-737.

Whicker, F.W.; Kirchner, T.B.; Breshears, D.D.; Otis, M.D. 1990. Estimation of radionuclide ingestion: the "Pathway" model. *Health Physics*. 59:645-657.

Worley, B.A.; Horwedel, J.E. 1986. A waste package performance assessment code with automated sensitivity-calculation capability. Oak Ridge, TN: Oak Ridge National Laboratory; Report No. ORNL/TM-9976.

Yu, C.; Cheng, J-J.; Zielen, A-J. 1991. Sensitivity analysis of the RESRAD, a dose assessment code. Transactions of the American Nuclear Society. 64:73-74.

Zimmerman, D.A.; Hanson, R.T.; Davis, P.A. 1991. A comparison of parameter estimation and sensitivity analysis techniques and their impact on the uncertainty in ground water flow model predictions. Albuquerque, NM: Sandia National Laboratory; Report No. NUREG/CR-5522.

DATE

FILMED

3 / 24 / 94

END