Rec'd 4-10-91

Nitrogen Oxide Abatement by Distributed Fuel Addition

Contract DE-AC22-87PC79850

DOE/PC/79850--13

DE92 005215

Quarterly Report No. 13

for Period

August 1, 1990 through October 31, 1990

Prepared by

J. O. L. Wendt and J. B. Mereb
Department of Chemical Engineering
University of Arizona
Tucson, Arizona 85721

Submitted to

Diane Revay Madden, Project Officer
Environmental Control Technology Division
Pittsburgh Energy Technology Center
Department of Energy

January 2, 1991

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

SUMMARY

This report consists of three sections:

1. **Experimental Results: Effect of Primary Flame Mode**

This section presents results of reburning experiments in which the effect of the primary flame mode is examined. The application of reburning downstream of an axial diffusion primary flame without swirl is compared to reburning results in which the primary flame is premixed. The comparison is qualitative and is intended to examine reburning under more realistic conditions of utility boilers, where premixed flames are not common.

2. **Experimental Results: Reburning Zone Profiles**

Experimental results of reburning tests using nitrogen containing reburning fuels (ammonia doped natural gas and coal) are presented. The effect of reburning fuel type and nitrogen content on nitrogenous species profiles in the reburn zone are discussed.

3. **Applications of the Kinetic Model**

This section is concerned with the applications of the kinetic model to predict overall reburning effectiveness from the primary NO level and to identify configurations for low total fixed nitrogen concentration. The effects of mixing in the early stage of reburning are examined and appropriate corrections are incorporated with the kinetic model to allow the prediction of nitrogenous species concentrations in the region where mixing effects are important. An empirical correlation is used to estimate the conversion of the total fixed nitrogen in the reburn zone to NO in the final stage of reburning. The kinetic model is also applied to the testing of hypothetical fuel rich configurations to identify kinetic limits that would prevent further reductions in nitrogenous species.

EXPERIMENTAL RESULTS: EFFECT OF PRIMARY FLAME MODE

The experimental studies described in previous reports were conducted on a laboratory pulverized coal combustor that was operated in a premixed plug flow mode. The premixed burner that was used allowed thorough mixing of the air stream transporting the coal particles with the preheated combustion air stream. Other experiments were performed in a turbulent diffusion flame mode in which another burner was used to produce a long axial flame with no swirl (type A.) The construction of both types of burners is described in Figure 1. In this section, the results of reburning experiments involving a turbulent diffusion primary flame are presented and the effects of primary flame mode are discussed. The interpretation of the results is qualitative and serves only to demonstrate the outcome of reburning and its limitations when applied under more practical conditions.

Premixed Primary Flame

Premixed flames are not common in practical pulverized coal combustors, since they produce more NO_x in post flame flue gases. Premixing enhances the contact of fuel nitrogen with oxygen in the early stage of combustion, resulting in increased oxidation of fuel nitrogen to NO. Nevertheless, a premixed plug flow mode can provide valuable information on residence time, temperature and local environment since these properties depend only on axial position and can be well defined. Furthermore, a premixed environment is useful in the study of kinetics and the determination of kinetic limits that govern the fate of nitrogenous species in post flame flue gases. In pulverized coal combustion, results from premixed flames are applicable in practical units since fuel nitrogen oxidation kinetics occur in a diffusion flame environment, even when the coal particles are premixed with air (Wendt, 1980).

Effect of Reburning Fuel Jet Momentum

Mixing is a key variable in reburning and is expected to affect the overall reduction in NO and the location of the optimum reburn zone stoichiometry. In addition, poor mixing in the reburn zone creates local variations in reburn zone stoichiometry which would prevent complete optimization

of the reburning process. A well mixed reburn zone is necessary to validate the assumption of one dimensional plug flow behavior throughout the combustor. Consequently, the reburning fuel injection mode was modified to produce adequate mixing within 0.18 seconds, by injecting nitrogen gas with the reburning fuel.

An experiment was conducted to examine the effect of improved mixing in the reburn zone on reburning effectiveness. In all the tests, the total flow of reburning fuel and transport N_2 was held constant at 15.6 slm (0.55 scfm) and introduced through port 4. The results are presented in Figure 2 as the variation of reburning effectiveness with reburn zone stoichiometry. The trend is similar to that observed in previous experiments in which no transport gas was injected with the reburning fuel. However, the optimum reburn zone stoichiometry is closer to 0.9, corresponding to NO reduction of 75%, as compared to an optimum reburn zone stoichiometry of 0.8 that was identified in previous experiments. Comparing the results of this experiment at optimum conditions to those of Figure 3, in which no N_2 was injected with the reburning fuel, shows an improvement of about 5% in reburning effectiveness, although both experiments are not entirely comparable due to minor differences in primary NO levels, residence times and temperatures.

In short, poor mixing reduces overall reburning effectiveness, results in broader dependence on reburn zone stoichiometry and creates a shift in the optimum reburn zone stoichiometry to the richer side. This is consistent with the results of previous studies (Chen et al., 1986; Kolb et al., 1988).

Conversions of Nitrogenous Species

Figure 4 shows the results of a reburning experiment in which detailed measurements of nitrogenous species were made at the exit of the fuel rich reburn zone at various stoichiometries in addition to exhaust NO measurements after final air addition. This allowed the examination of nitrogenous species inter-conversion in the reburn zone, the burnout zone and the overall effect of reburning on NO concentrations. The results of this experiment are typical and clearly demonstrate the tradeoff which determines an optimum reburn zone stoichiometry. As the stoichiometry

decreases, HCN and NH_3 concentrations increase, whereas, NO concentration decreases in the reburn zone. Thus, stoichiometry determines the distribution of nitrogenous species leaving the reburn zone and subsequently, the conversion of the total fixed nitrogen to NO in the final stage of reburning. This conversion is very sensitive to reburn zone stoichiometry and approaches 100% as the stoichiometry approaches the fuel lean side, corresponding to HCN and NH_3 levels approaching zero, as seen in Figure 4. Similar trends, under various conditions were examined by Greene et al. (1985).

In this experiment, an optimum reburn zone stoichiometry was identified at 0.84, corresponding to an overall destruction of about 80% of the primary NO.

Diffusion Primary Flame

In a turbulent diffusion flame mode, pulverized coal particles are transported by primary air and are injected into the furnace where they are contacted by a secondary air stream. At the injection point, fuel nitrogen evolves in an oxygen deficient environment, which favors its conversion to N_2 . The delayed contact of nitrogenous species with oxygen reduces the conversion of fuel nitrogen to NO. Thus, in a diffusion flame mode, there is less oxidation of fuel N to NO than is a premixed flame mode.

Experiments were conducted in which the premixed burner was replaced by a burner that produced a long axial flame with no swirl (type A.) The results in this case are more complex to interpret than in a premixed mode, but relate more closely to flames that exist in industrial applications. Typically, axial pulverized coal flames without swirl are difficult to stabilize if the heat due to the combination of wall radiation and convection of hot combustion gases is not sufficient to ignite the fuel. No problem with flame stability was experienced in these experiments, possibly due to the properties of the silicon carbide refractory that constituted the inside wall of the combustor.

Two reburning experiments were performed in which the primary flame was a bituminous coal axial diffusion (type A) flame and natural gas transported by N_2 gas was the reburning fuel.

In one experiment, time resolved nitrogenous species profiles in the reburn zone are compared to those in which the primary flame was premixed. The results of the second experiment show the variation of reburning effectiveness with reburn zone stoichiometry.

Nitrogenous Species Profiles in the Reburn Zone

Figure 5 shows nitrogenous species profiles in the reburn zone for two types of primary flames, a premixed flame and a type A axial diffusion flame. The overall stoichiometry in the primary zone (1.10) and the reburn zone (0.86) and temperature profiles were similar in both cases. As expected, a premixed primary flame produced a primary NO concentration of 1200 ppm, compared to 700 ppm (dry, 0% O₂) when the primary flame was of the diffusion type. The difference in the primary NO levels is due to difference in the level of contact between fuel nitrogen in the volatile fraction and oxygen in the primary zone which affects the formation of NO from coal nitrogen. In the reburn zone, HCN and NH₃ levels were higher for the primary diffusion flame and the decay of all nitrogenous species proceeded at a slower rate. That is partly due to the lower concentration of the primary NO and partly due to the nature of the diffusion flame in the primary zone which can create local variations in stoichiometries in the primary zone and the reburn zone. On the other hand, significant destruction of NO was observed in both cases, with NO decaying to about the same low level of 270 ppm (dry, 0% O₂). Therefore, it may be possible that reburning can produce low levels of NO emissions regardless of the type of primary flame, even though the overall reduction in NO is affected. In other words, the reburning effectiveness may be higher if the primary flame is premixed, rather than the diffusion type, but the final NO emissions may not necessarily be lower.

Overall Reburning Effectiveness

An experiment was performed with a bituminous coal primary diffusion flame and using natural gas transported by N₂ gas as reburning fuel. Figure 6 shows the variation of reburning effectiveness with reburn zone stoichiometry. NO reductions as high as 65% were obtained and no optimum reburn zone stoichiometry was identified in the range that was covered. Similar results

were obtained by Lanier et al. (1986) in their study of natural gas reburning in a pilot scale package boiler simulator. It is expected that an optimum reburn zone stoichiometry would exist at stoichiometry richer than 0.8 due to poor mixing conditions that are associated with diffusion flames. Comparison of Figures 6 and 2 shows that the reburning effectiveness in a premixed flame mode is higher than that in a diffusion primary flame mode. However exhaust NO emission levels are comparable in both cases, reaching levels below 325 ppm (dry, 0% O₂) at reburn zone stoichiometries below 0.9.

In short, the application of reburning downstream of a coal diffusion primary flame is effective in reducing NO emissions. Lower reburning effectiveness would be expected in the case of a diffusion primary flame than in the case of a premixed primary flame, but the final NO emissions might be comparable.

EXPERIMENTAL RESULTS: REBURNING ZONE PROFILES

Ammonia Doped Natural Gas Reburning

Experiments were conducted to examine the effect of nitrogen content in the reburning fuel on the distribution of nitrogenous species in the reburn zone. An increase in nitrogen content in the reburning fuel is expected to produce higher levels of nitrogenous species due to the introduction of additional fuel nitrogen into the reburn zone. Figure 7 shows fixed nitrogenous species profiles in the reburn zone for two natural gas reburning tests at similar temperature profiles and a stoichiometry of 0.85 in the reburn zone. For one test, the reburning fuel was natural gas and for the other, the reburning fuel was natural gas doped with NH_3 to a nitrogen content of about 1.1% nitrogen.

Nitrogenous species profiles for the two tests show that at residence times greater than 0.4 seconds, the levels of nitrogenous species were about the same in both cases. However, at the first measurement downstream of the reburning fuel injection point, the presence of nitrogen in the reburning fuel produced significantly higher levels of HCN and NH_3 . The high concentration of HCN at this point is due to enhanced formation of HCN from $\text{CH}_3 + \text{N}$ reaction, originally proposed by Haynes (1977). Furthermore, NO decay rate was more rapid in the early stage of the reburn zone when NH_3 was injected with the reburning fuel, possibly due to enhanced NO destruction by NH_i radicals.

These results demonstrate that the effect of fuel nitrogen in the volatile form in the reburning fuel is strongly dependent on the residence time that is allowed in the reburn zone. The introduction of additional nitrogen with the reburning fuel into the reburn zone can significantly increase HCN and NH_3 concentrations for residence times less than 0.4 seconds. This corresponds to higher concentrations of total fixed nitrogen, although NO decay may be enhanced in the presence of higher concentrations of NH_3 . For residence times greater than 0.4 seconds in the reburn zone, the overall effect of the additional nitrogen in the reburn zone is of minor significance as the nitrogenous species decay to lower levels that are comparable to those observed in natural gas

reburning.

Coal Reburning

The use of coal as a reburning fuel is attractive in the application of reburning in a commercial coal fired boiler. Literature data on the use of coal as reburning fuel downstream of a coal primary flame are scarce. Most studies of coal reburning involved a gas primary flame doped with nitrogenous species to simulate coal combustion flue gases in the primary zone. In this study, the use of coal as a reburning fuel was examined and involved coal primary flames. Utah bituminous coal was used as the primary fuel and as the reburning fuel. As in the case of natural gas reburning, N_2 gas was used to transport the reburning fuel. However, for coal reburning experiments, a different injector tip was used consisting of four holes, each 0.64 cm in diameter. A secondary coal feeder was used to introduce the coal reburning fuel at the desired feed rate.

Figure 8 shows nitrogenous species profiles in the reburn zone for a natural gas reburning test and a coal reburning test at a reburn zone stoichiometry of 0.80. The introduction of coal into the reburn zone resulted to rapid formation of HCN and NH_3 within 0.14 seconds, with HCN concentrations exceeding 600 ppm and NH_3 concentrations exceeding 90 ppm (dry, 0% O_2). At longer residence times, HCN and NH_3 decayed to lower levels that were comparable to those observed in natural gas reburning. On the other hand, in coal reburning, NO levels were significantly higher throughout the reburn zone and lower NO decay rates were observed, compared to those of natural gas reburning. The reduced NO decay rates when coal was used as a reburning fuel was due to the production of low levels of hydrocarbons from the coal where measured methane concentrations were less than 0.07% in the reburn zone. Consequently, NO destruction by hydrocarbon radicals was of minor significance and NO reactions with NH_3 species dominated the destruction of NO. These results are consistent with coal reburning results of Knill and Morgan (1989), who used a model based only on $NO + NH_3$ reactions to describe NO decay in the reburn zone.

The results of the coal reburning test suggest that the effect of nitrogen in the coal reburning fuel on the distribution of nitrogenous species in the reburn zone is strongly dependent

on residence time in the reburn zone. As in the case of NH_3 doped natural gas reburning, the effect of nitrogen in the reburning fuel is limited to short residence times in the vicinity of the reburning fuel flame. This effect is of minor significance for residence times greater than 0.4 seconds in the reburn zone as nitrogenous species decay to lower levels.

Effect of Reburning Fuel Type and Nitrogen Content

Figure 9 shows nitrogenous species profiles for three reburning tests corresponding to three different reburning fuel types, namely, natural gas, natural gas doped with NH_3 to a nitrogen content of 1.4% and bituminous coal containing 1.3% nitrogen. Primary NO levels and temperature profiles in the reburn zone were similar in all three cases corresponding to a reburn zone stoichiometry of 0.9. HCN and NH_3 concentrations were less than 100 ppm throughout the reburn zone. A comparison of NO profiles shows minor differences when gaseous reburning fuel were used, regardless of the nitrogen content. However, NO decayed at a slower rate in coal reburning and corresponded to low methane concentrations of less than 0.02%. These observations are similar to those discussed earlier for NH_3 doped natural gas and coal reburning tests at different stoichiometries in the reburn zone. Similar observations were reported by Greene et al. (1985) in their study of coal reburning fuels and gaseous reburning fuels doped with NH_3 to the same nitrogen content. Lower NO decay rates were obtained with coal reburning, but HCN and NH_3 yields were the same for coal and gaseous reburning fuel over a wide range of stoichiometries at a residence time of 0.4 seconds in the reburn zone.

The effect of nitrogen content in the reburning fuel is less obvious at leaner stoichiometries in the reburn zone, possibly due to mixing inhomogeneities and oxygen availability in the vicinity of the reburning fuel flame, corresponding to short residence time. The presence of oxygen in the early stage of the reburn zone enhances the decay of HCN and NH_3 that are formed from the nitrogen in the reburning fuel. For coal reburning, HCN decayed to levels lower than 20 ppm within 0.6 seconds, as seen in Figure 9. These low levels are due to the dominance of HCN destruction reactions in the reburn zone since HCN formation from hydrocarbon reactions is minor

in the presence of low hydrocarbon concentrations of less than 0.02%. These results further support the hypothesis that HCN formation in long time scales is mostly due to reactions involving hydrocarbon radicals and the slow release of nitrogen from the coal residue is a minor contributor to HCN formation.

To summarize, the effect of nitrogen content in the reburning fuel is strongly dependent on residence time and reburn zone stoichiometry. This effect is limited to short residence times, typically less than 0.4 seconds during which significant amounts of HCN and NH_3 are formed from the nitrogen in the reburning fuel. At longer residence times in the reburn zone, HCN and NH_3 decay to lower levels depending on conditions in the reburn zone, such as temperature and local hydrocarbon concentrations. Coal reburning fuels are less effective than gaseous fuels in destroying NO, since coal produces lower levels of hydrocarbons than gaseous reburning fuels. Consequently, in coal reburning, $\text{NO} + \text{NH}_i$ reactions dominate the destruction of NO. There is no evidence to indicate that the introduction of coal nitrogen into the reburn zone significantly contributes to the reduction in NO decay rates, due to the formation of additional NO from coal nitrogen. The lower NO decay rates in coal reburning are mostly due to significantly lower NO destruction by hydrocarbon radicals, which is the driving force behind the reburning process.

APPLICATIONS OF THE KINETIC MODEL

The inter-conversion of nitrogenous species in the fuel rich stage of reburning were explored and a simple mechanism was proposed based on homogeneous gas phase kinetics, known kinetic parameters and partial equilibrium assumptions. This simple mechanism was successful in predicting nitrogenous species profiles in the fuel rich zone under reburning and air staging configurations. This section is concerned with the applications of the kinetic model as a predictive tool. The objectives are to expand the model to predict the overall destruction of NO in a reburning configuration and to examine hypothetical configurations that would allow further reductions in NO emissions.

In the previous analysis, the use of the kinetic model was limited to the prediction of nitrogenous species profiles in the region of the reburn zone where mixing effects were not important. Furthermore, the model required known initial concentrations of the three fixed nitrogenous species. In order to apply the model to the prediction of the overall reburning effectiveness, it is necessary to expand the analysis to allow the prediction of nitrogenous species in the reburn zone from the primary NO level and then to estimate the conversion of the total fixed nitrogen to NO after final air addition. Empirical correlations, both derived and taken from the literature are used for this purpose.

In another application of the kinetic model, hypothetical configurations are examined to identify kinetic limits in achieving low levels of total fixed nitrogen under fuel rich conditions. The two variables that are manipulated in this examination are temperature and residence time.

Predictions of Reburn Zone Nitrogenous Species

It is desired to predict the values of nitrogenous species in the reburn zone from the primary NO values and ultimately from known process parameters such as temperature, desired residence time in the reburn zone and stoichiometries. The kinetic model can be used for this purpose, provided an initial value for OH radical concentration is known and if the effect of mixing in the vicinity of the reburning fuel injection point is accounted for.

Corrections for Mixing Effects in the Reburn Zone

Mixing can limit NO destruction by hydrocarbon radicals due to limited contact between the primary NO and the reburning fuel. Furthermore, oxygen carryover into the reburn zone can create variations in the local stoichiometry which affect the distribution of nitrogenous species. In the region of the reburn zone where mixing effects are important, the presence of oxygen results in the destruction of a fraction of the hydrocarbon radicals to form neutral products, such as CO and CO₂. Thus, mixing affects NO destruction by hydrocarbon radicals partly due to limited contact between the primary NO and the reburning fuel and partly due to the presence of oxygen rich pockets which can reduce the availability of CH₃ radicals.

In the vicinity of the reburning fuel flame, mixing can also limit HCN formation from hydrocarbon reactions. HCN formation is partially inhibited due to reduced NO destruction by hydrocarbon radicals, in addition to the destruction of HCN in the presence of oxygen carryover from the primary zone. Thus, in the region of the reburn zone where mixing effects are important, a fraction of the HCN that is formed is oxidized to form other nitrogenous species and N₂. An examination of the fixed nitrogenous species profiles in Figure 10 for a reburning test in which the reburn zone was operated fuel lean at a stoichiometry of 1.03 supports this hypothesis. In this experiment, the introduction of the reburning fuel corresponded to destruction of over 400 ppm NO, mostly within 0.18 seconds, but HCN levels were less than 5 ppm throughout the reburn zone. Clearly, a significant amount of NO can be destroyed in the reburn zone without a significant increase in HCN levels, depending on the extent of mixing and oxygen availability.

The development of a theoretical model to account for mixing at the reburning fuel injection point is beyond the scope of this investigation. Instead, a simple mixing model is presented in which methane concentration rises linearly from zero at the entrance to the reburn zone to an average measured value in the region of the reburn zone with no mixing complications. This simple model accounts for the effect of mixing on NO and hydrocarbon interaction in the vicinity of the reburning fuel flame. To account for reduced HCN formation from hydrocarbon radicals in this

region, a correction factor of 0.3 is used. These simple modifications are applied only to the region between the entrance to the reburn zone and the first measured point downstream of the injection point, corresponding to a residence time of about 0.18 seconds, beyond which the kinetic model is used as before. The initial OH concentration was estimated by extrapolation of OH values calculated in the reburn zone and correlation of these values as a function of temperature at the entrance to the reburn zone. Adjustment of this expression was necessary to obtain predictions for all three nitrogenous species in the reburn zone from the primary NO level. The following correlation for initial OH values was used: $OH = 35 \times \exp(-24100/T)$.

To summarize, some modifications were necessary to apply the kinetic model to the prediction of nitrogenous species values in the reburn zone for residence times less than 0.18 seconds, where mixing effects were important. An empirical correlation was used for the initial OH, combined with a model in which methane concentration rose linearly from zero to an average value and only 30% of NO destruction by hydrocarbon radicals produced HCN. These empirical modifications were designed to account for the effects of mixing on the inter-conversion of nitrogenous species in the early stage of the reburn zone. The choice of the parameters was mostly based on trial and error and examination of the predictions of the kinetic model. It should be emphasized that these modifications are empirical and would be valid only for the experimental configuration and the injection scheme that are used in this study. The objective of this analysis is to demonstrate that with proper modifications to account for mixing effects in the early stage of reburning, the kinetic model can be applied to predict nitrogenous species values in the reburn zone from known NO concentrations in the primary zone.

Predictions of the Extended Model

The extended model is used to predict initial concentrations of all three nitrogenous species in the region of the reburn zone with no mixing complications where the kinetic model could be used to predict all nitrogenous species profiles with no limitations. Figure 11 shows a comparison between model predictions and measurements for the initial concentrations of the three fixed

nitrogenous species in the reburn zone, corresponding to residence times less than 0.18 seconds. The predictions are based on the kinetic model combined with the empirical modifications described earlier to account for mixing effects that exist in these short time scales. In all these tests, the primary fuel was bituminous coal and the reburning fuel was natural gas. Reasonable predictions are obtained for all nitrogenous species. These points can be used as initial values in the region of the reburn zone with no mixing complications. Consequently, the kinetic model can be applied to predict values for the nitrogenous species in the remainder of the reburn zone.

The effect of the choice of a methane concentration at the entrance to the reburn zone on the predictions of NO is shown in Figure 12. NO decay based on the initial diluted value for methane, assuming instantaneous perfect mixing, is far too rapid. A similar trend is observed for NO decay based on an initial value for methane equal to that at the first measurement downstream of the reburning fuel injection point which assumes instantaneous oxidation of the reburning fuel. Much better predictions are obtained by assuming that methane concentration rises linearly from zero to the measured value below the reburning fuel injection point. This demonstrates the sensitivity of the choice of an initial value for methane concentration on NO predictions in the reburn zone and the limitations imposed by mixing on NO reduction by hydrocarbon reactions.

Figure 13 shows a comparison between measured and predicted nitrogenous species profiles in the reburn zone starting from the primary NO values. The predictions are based on the extended model as described earlier. Again, it is emphasized that for residence times greater than 0.18 seconds, the kinetic model is used with no modifications. The empirical corrections are used only for short residence times to account for mixing effects. Comparison of the lines to the data shows good agreement between measurements and predictions for NO, HCN and NH_3 concentrations throughout the reburn zone and under various conditions of primary NO levels and stoichiometries in the reburn zone.

To summarize, for natural gas reburning in a practical coal combustor, the inter-conversion of nitrogenous species occurs in two sequential regions in the reburn zone. The first region is

limited to the vicinity of the reburning fuel flame and involves short time scales of about 0.18 seconds. In this region, mixing effects are important and can limit both NO destruction by hydrocarbon reactions and the formation of HCN. The second region follows downstream, covers the remainder of the reburn zone and involves no mixing complications. In the second region of reburning, nitrogenous species inter-conversion reactions can be described by a kinetic model based on homogeneous gas phase kinetics. The kinetic model was combined with empirical corrections in the first region of the reburn zone to account for mixing effects. The extended model was successful in predicting nitrogenous species profiles in the reburn zone from the primary NO values.

Prediction of Exhaust NO in the Burnout Zone

In the final stage of reburning, air is added and the oxidizable nitrogenous species (HCN and NH_3) leaving the reburn zone are converted to NO and N_2 . In this stage, there is no validated detailed mechanism to predict the formation of NO. An empirical correlation was developed by Chen et al. (1986) to estimate the conversion of the total fixed nitrogen leaving the reburn zone to the NO in the final burnout zone. This correlation is used in this study to predict final NO emissions for natural gas reburning, based on reburn zone values. The correlation is later combined with the extended predictive model to allow the prediction of NO exhaust emissions from primary NO values. The following correlation is used:

$$NO_{ex} = 0.81 * SR_2 * NO + \left[\frac{0.36 (HCN + NH_3)}{1 + 0.0024 (HCN + NH_3)} \right] + 53$$

with all concentrations in ppm on a dry basis and corrected to 0% O_2 . This is the same correlation used by Chen et al. (1986) and no adjustments are made.

Figure 14 shows a comparison between measured and predicted NO exhaust values for different reburning fuel types. There is good agreement between measurements and predictions under various conditions.

Prediction of Configurations for Low NO Emissions

The validity of the kinetic model in describing the inter-conversion of nitrogenous species

under fuel rich conditions was demonstrated in the previous report. The model was shown to be relatively insensitive to the overall configuration and could be applied in reburning and air staging configurations. Under practical combustion conditions, final NO emissions have little dependence on final stage parameters and are mostly determined by the levels and the distribution of nitrogenous species leaving the fuel rich stage. In this section, the kinetic model is used to examine hypothetical configurations under reducing conditions that would ultimately produce low levels of final NO emissions after final air addition. The objectives are to identify fuel rich configurations for low total fixed nitrogen concentrations and to determine kinetic limits that would prevent further destruction of nitrogenous species.

In this examination, initial conditions are specified and residence time and temperature in the fuel rich zone are allowed to vary downstream of the initial point. The focus is on the change in the values of the nitrogenous species. The values of the major species are assumed to be independent of residence time and temperature. Four cases are examined, corresponding to the fuel rich zones of two reburning tests and two air staging tests, under various conditions. The initial concentration of OH is assumed at equilibrium.

Under fuel rich conditions, the mutual destruction of NO and NH_3 species is favored at low temperatures. On the other hand, high temperatures at early residence times enhance the formation of NH_3 . Therefore, it is expected that temperature quench rate would be an important variable in determining the distribution of nitrogenous species in the fuel rich zone. Figure 15 and 16 show the effect of temperature quench rate on predicted nitrogenous species after a residence time of 3 seconds. Figure 15 examines two fuel rich reburn zones at different initial temperatures and Figure 16 examines the fuel rich combustion of a bituminous coal and a lignite coal. In all four cases, an optimum temperature quench rate is identified corresponding to a minimum in the total fixed nitrogen concentration.

An increase in temperature quench rate corresponds to an increase in HCN concentration and decrease in NO and NH_3 concentration until an optimum quench rate is approached. The

increase in HCN concentration is expected since its destruction at lower temperatures is less favorable. The decrease in NO and NH_3 concentration is due to their mutual destruction that is favored at lower temperatures. However, as NH_3 values approach zero, NO decay rate is reduced and further reduction in the total fixed nitrogen concentration may not be possible. If temperature quench rate is too rapid, NH_3 formation is retarded in the early stage of the fuel rich zone and approaches zero at a faster rate. Consequently, the enhanced destruction of NO and NH_3 species at short residence times due to reduced temperatures is offset by reduced NO decay rates at longer residence times as NH_3 concentration drop to low levels. Furthermore, lower temperatures are accompanied by higher HCN concentrations. On the other hand, if temperature quench rate is too slow, NO + NH_3 reactions are less favorable at the higher temperatures in the fuel rich zone. NO destruction by CH_3 radicals has little sensitivity to changes in temperature and is not addressed in this analysis.

Figures 17 and 18 show time resolved predicted nitrogenous species profiles for the four cases discussed earlier at their optimum temperature quench rates. The trends show decay in NO concentration and little change in HCN with residence time. On the other hand, NH_3 profiles show an increase in NH_3 concentrations within residence times of about 1 second, followed by decay to low levels approaching zero within three seconds. The profiles suggest that there are two limitations that would prevent further reduction in the total fixed nitrogen concentration. First, minor or no reduction in HCN levels could be obtained by allowing longer residence times in the fuel rich zone and these levels seem to depend mostly on conditions in the early stage of the fuel rich zone. Second, the mutual destruction of NO and NH_3 can be enhanced by manipulation of the time temperature history in the fuel rich zone, but is also limited since NH_3 concentrations decay to very low levels in about three seconds, beyond which only little reduction in total fixed nitrogen can be further achieved.

To summarize, temperature quench rate is an important parameter in determining the distribution and levels of all nitrogenous species. There is an optimum temperature quench rate that

corresponds to a minimum concentration of the total fixed nitrogen, mainly due to the effect of temperature on $\text{NO} + \text{NH}_i$ reactions. The value of this optimum seems to depend on the properties of the fuel rich zone. Long residence times of about 3 seconds are effective in reducing NO and NH_3 concentrations, until NH_3 concentration approaches zero. The presence of high levels of HCN in the fuel rich zone is an important limitation in achieving low levels of total fixed nitrogen. Increasing the residence time in the fuel rich zone seems to have a minor effect on HCN concentrations. This suggests that final HCN levels leaving the fuel rich zone are mostly dependent on conditions at or near the entrance of the fuel rich zone, such as temperature and local concentrations.

REFERENCES

- Chen, S. L., J. M. McCarthy, W. D. Clark, M. P. Heap, W. R. Seeker and D. W. Pershing, "Bench and Pilot Scale Process Evaluation of Reburning for In-Furnace NO_x Reduction," Twenty-first Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pennsylvania, 1159 (1986).
- Greene, S. B., S. L. Chen, W. D. Clark, M. P. Heap, D. W. Pershing and W. R. Seeker, "Bench-Scale Process Evaluation of Reburning and Sorbent Injection for In-Furnace NO_x/SO_x Reduction," U.S. EPA Report EPA-600/7-85-012, March 1985.
- Haynes, B. S., "The Oxidation of the Hydrogen Cyanide in Fuel Rich Flames," Combustion and Flame, 28, 113 (1977).
- Knill, K. J. and M. E. Morgan, "The Effect of Process Variables on NO_x and Nitrogen Species Reduction in Coal Fuel Staging," Paper presented at the 1989 Joint Symposium on Stationary Combustion NO_x Control, San Francisco, CA, March, 1989.
- Kolb, T., P. Jansohn and W. Leuckel, "Reduction of NO_x Emission in Turbulent Combustion by Fuel-Staging / Effects of Mixing and Stoichiometry in the Reduction Zone," Twenty-second Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pennsylvania, 1193 (1988).
- Lanier, W. S., J. A. Mulholland and J. T. Beard, "Reburning Thermal and Chemical Processes in a Two-Dimensional Pilot-Scale System," Twenty-first Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pennsylvania, 1171 (1986).
- Wendt, J. O. L., "Fundamental Coal Combustion Mechanisms and Pollutant Formation in Furnaces," Progress in Energy and Combustion Science, 6 (2), 201 (1980).

Figure 1 . Premixed and Diffusion Burners.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Primary SR = 1.23, $\text{NO}_p \sim 1070$ ppm (dry, 0% O_2)

Reburn Zone: Time = 0.4-0.5 s, Temp = 1500-1600 K

Figure 2 . Variation of Reburning Effectiveness with Reburn Zone Stoichiometry - Premixed Primary Flame Mode - N_2 Gas Injection with the Reburning Fuel.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Reburn Zone: Time = 0.33-0.43 s, Temp = 1550-1600 K

$\text{NO}_p \sim 900$ ppm (dry, 0% O_2)

Figure 3. Variation of Reburning Effectiveness with Reburn Zone Stoichiometry - Premixed Primary Flame Mode.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Primary Zone: $SR = 1.18$, $NO_p = 1030$ ppm (dry, 0% O_2)

Reburn Zone: Time ~ 0.7 s, Temp ~ 1570 K

Figure 4 . Nitrogenous Species Conversions at Various Stages of Reburning.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Figure 5 . Fixed Nitrogenous Species Profiles in the Reburn Zone - Comparison of Premixed and Diffusion Primary Flame Modes.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Primary SR = 1.18, $\text{NO}_p \sim 700$ ppm (dry, 0% O_2)

Reburn Zone: Time = 0.43-0.52 s, Temp = 1550-1600 K

Figure 6 . Variation of Reburning Effectiveness with Reburn Zone Stoichiometry - Axial Diffusion Primary Flame Mode with no Swirl - N_2 Gas Injection with the Reburning Fuel.

BITUMINOUS COAL PRIMARY FLAME, FUEL RICH SR = 0.85

Figure 7 . Fixed Nitrogenous Species Profiles in the Reburn Zone - Effect of Reburning Fuel Nitrogen Content.

BITUMINOUS COAL PRIMARY FLAME, FUEL RICH SR = 0.80

Figure 8 . Fixed Nitrogenous Species Profiles in the Reburn Zone - Effect of Reburning Fuel Type.

Figure 9 . Fixed Nitrogenous Species Profiles in the Reburn Zone - Effect of Reburning Fuel Type and Nitrogen Content.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Figure 10. Fixed Nitrogenous Species Profiles in the Reburn Zone - Effect of Reburn Zone Stoichiometry.

Figure \\. Comparison between Model Predictions and Measurements for Reburn Zone Residence Times Less than 0.2 Seconds - Bituminous Coal Primary Flame - Natural Gas Reburning.

Figure 12. Effect of Methane Concentration at the Reburning Fuel Injection Point on NO Predictions in the Reburn Zone.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING

Figure 13. Comparison of Measured and Predicted Nitrogenous Species Profiles in the Reburn Zone - Predictions from Primary NO Concentrations.

Figure 14. Comparison between Measured and Predicted NO Exhaust Emissions (Dry, 0% O₂) in the Final Stage of Reburning.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING
FUEL RICH SR = 0.86, RESIDENCE TIME = 3 seconds

Figure 15. Effect of Temperature Quench Rate on Predicted Nitrogenous Species Concentrations in the Reburn Zone.

FUEL RICH SR = 0.6, RESIDENCE TIME = 3 seconds

Figure 16. Effect of Temperature Quench Rate on Predicted Nitrogenous Species Concentrations in the Fuel Rich Combustion of Coal.

BITUMINOUS COAL PRIMARY FLAME, NATURAL GAS REBURNING
FUEL RICH SR = 0.86

Figure 17. Predicted Nitrogenous Species Profiles in the Reburn Zone at Optimum Temperature Quench Rate.

Figure 18. Predicted Nitrogenous Species Profiles in the Fuel Rich Combustion of Coal at Optimum Temperature Quench Rate.

END

**DATE
FILMED**

3 / 20 / 92