**DOE/PC/89870-T1
(DE92008748)**

DESIGN OF SLURRY REACTOR FOR INDIRECT LIQUEFACTION APPLICATIONS
Final Report

By
Anand Prakash
Prakash G. Bendale

Work Performed Under Contract No. AC22-89PC89870

For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By
Viking Systems International
Pittsburgh, Pennsylvania

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

FINAL REPORT

DOE/PC/89870--T1

DE92 008748

**DESIGN OF SLURRY REACTOR
FOR
INDIRECT LIQUEFACTION
APPLICATIONS**

DOE Contract No. DE-AC22-89PC89870

Anand Prakash

Prakash G. Bendale

Viking Systems International

2070 William Pitt Way

Pittsburgh, PA 15238

CONTENTS

	<u>Page</u>
1.0 INTRODUCTION	1
2.0 Slurry Reactor Model	3
2.1 Assumptions for Methanol synthesis	3
2.2 Assumptions for FT synthesis	5
2.3 Model Equations	7
2.4 Determination of model parameters	9
2.5 Vapor-Liquid Equilibrium Calculations in Fischer - Tropsch Synthesis	35
3.0 Development of Computer Codes	41
3.1 Test and Validation of Reactor Models	42
4.0 Recommendations for future work	69
5.0 Conceptual Commercial size Reactor Design	71
5.1 Cost Comparison with Fixed Bed Reactor	74
Nomenclature	82
References	88
Appendix A - System requirements and operating instructions for personal computers	
Appendix B - Sample INPUT and OUTPUT files for methanol synthesis model	
Appendix C - Sample INPUT and OUTPUT files for FT Synthesis model	

1.0 INTRODUCTION

Coal can be converted into liquid fuels by direct or indirect liquefaction processes. The chemical composition of the liquid products from the two processes, however, are very different. The products of direct liquefaction are highly aromatic such as high octane gasoline and excellent feedstock for aromatic chemicals. On the other hand, the indirect liquefaction provides saturated hydrocarbon liquids such as high quality diesel fuel and intermediates for olefin production. Indirect liquefaction is considered as being more flexible than direct liquefaction as regards to the types of coal that can be used and the end products that can be produced.

Fischer-Tropsch synthesis represents an important route for indirect coal liquefaction. It is essentially hydrogenation of carbon monoxide which yield saturated and unsaturated compounds of the homologous series. It permits the synthesis of hydrocarbons ranging from methane to high melting paraffins depending on the catalyst, temperature and type of process employed. A small quantity of byproducts such as alcohols, aldehydes, ketones etc. are also formed. A variant of the FT synthesis is the production of methanol in high yields. Methanol is suitable for direct use as a turbine and transport fuel, although its energy content on a volume basis is only half that of gasoline (Derbyshire and Gray, 1985). It can also be used as a feedstock to produce high octane gasoline by employing the MOBIL Methanol-to-gasoline (MTG) process which uses a highly shape selective zeolite ZSM-5 catalysts (Kuo, 1982).

Several reactor configurations have been developed to produce liquid products by Fischer-Tropsch synthesis. The reactor systems used are: fixed bed reactor (ARGE), entrained bed reactor, fixed

fluidized-bed reactor and slurry bubble column reactor. The fixed-bed reactor must operate with H_2/CO ratio in excess of unity, due to the possibility of plugging as a consequence of wax and/or carbon buildup (Kolbel and Ralek, 1980). The fluidized bed reactors are useful for producing gasoline, but cannot be operated under reaction conditions that lead to high molecular weight lubes and waxes due to agglomeration of catalyst particles. Three-phase slurry bubble column reactors provide an attractive alternative to the vapor-phase fixed and fluidized beds since they can be operated with low H_2/CO ratio (<0.6) synthesis gas in either a wax or gasoline producing mode. In addition these reactors also offer the advantages of high heat transfer rate, isothermal conditions of operation, reduced rate of catalyst deactivation due to washing effect of the liquid and on-line catalyst addition and withdrawal.

The objective of this project is to design and model a conceptual slurry reactor for two indirect liquefaction applications; 1) production of methanol and 2) production of hydrocarbon fuels via Fischer-Tropsch route. A slurry reactor is defined here as a three-phase bubble column reactor using a fine catalyst particle suspension in a high molecular weight liquid. The feed gas is introduced through spargers. It then bubbles through the column providing the agitation necessary for catalyst suspension and mass transfer. The reactor models for the two processes have been formulated using computer simulation. Process data, kinetic and thermodynamic data, heat and mass transfer data and hydrodynamic data have been used in the mathematical models to describe the slurry reactor for each of the two processes. Available data from process development units and demonstration units were used to test and validate the models. Commercial size slurry reactors for methanol and Fischer-Tropsch synthesis were sized using reactor models developed in this report.

2.0 Slurry Reactor Model:

The development of a reactor model starts with writing the differential mass and energy balance equations. The resulting differential equations can then be solved using suitable boundary conditions. The reactor design configuration, its operating conditions and process type also allow for some simplifying assumptions to be made. Since both methanol and FT synthesis reactors use fine catalyst particles suspended in liquid and operate at high pressures, some of the assumptions related to operating conditions are common to both reactor models. The kinetics and stoichiometry of the two processes are, however, very different. The products and stoichiometry of methanol synthesis process are well defined and leave the reactor in vapor phase. During FT synthesis, however, a large number of products are formed which makes it impractical to attempt individual component balance. For design purposes, however, some products can be grouped together without significant loss of accuracy. The following assumptions were made for the development of methanol synthesis and Fischer-Tropsch synthesis slurry reactor models.

2.1 Assumptions for Methanol Synthesis:

- i) The total pressure within the reactor does not vary with axial position, i.e. the influence of hydrostatic head on gas expansion is neglected. This assumption is reasonable in view of the relatively high pressures used in the process.
- ii) The effectiveness factors for the catalyst particles are taken as unity. Due to the relatively small particle sizes used in the reactors, diffusional limitations should be negligible.

- iii) Again, as a consequence of the small particle size, mass and heat transfer resistances between the catalyst and liquid are assumed to be negligible.
- iv) The gas and slurry phases are modeled using the axial dispersion model, the most appropriate model for bubble column reactors (Deckwer et al., 1983).
- v) The catalyst is not uniformly distributed in the reactor and the sedimentation-dispersion model (Cova, 1966; Kato et al., 1972, Smith et.al, 1985) is used for modeling the catalyst concentration.
- vi) The hydrodynamic parameters, namely gas holdup, interfacial area, heat and mass transfer coefficients and dispersion coefficients are assumed to be spatially independent.
- vii) A heat balance will be made only on the slurry phase, since the heat capacity of the gas phase is much lower than that of the slurry.
- viii) The temperature dependence of the total gas phase concentration $C_G = P/RT$ can be neglected since

$$d(1/T)/dz = -1/T^2(dT/dz) \sim 0$$

This approximation is justified since the temperature gradient is usually small due to liquid-phase back-mixing.

- ix) Heat and mass dispersion in the slurry phase are equal and related by Lewis analogy, i.e.

$$D_L = (k_{eff}/C_p)_L$$

- x) Steady-state conditions prevail.

2.2 Assumptions for FT reactor model:

- 1) The synthesis products obey Schulz-Flory distribution. This assumption has been found to be valid over the entire range of products of an iron catalyst (Satterfield and Huff, 1982).

$$p_n = \alpha p_{n-1} = \alpha^{n-1} p_1 \quad (1)$$

Here, p_n refers to the product distribution as formed on the catalyst.

- 2) The hydrocarbon products consist of n-alkanes and n-alkenes only. These are in fact the main products of catalysts and little design error is introduced by lumping the methyl branched isomers with n-alkenes and n-alkanes.
- 3) The gas phase component balance is made only for i) CO, ii) H₂, iii) CO₂, iv) H₂O and v) C₁ to C₃ hydrocarbons. The contribution of hydrocarbons heavier than C₃ in the gas phase is estimated to be less than 4% of the gas flow rate in the reactor.
- 4) The effectiveness factors for the catalyst particles are taken as unity. Due to the relatively

small particle sizes ($< 50 \mu\text{m}$) used in the reactors, diffusional limitations should be negligible.

- 5) Again, as a consequence of the small particle size, mass and heat transfer resistances between the catalyst and liquid are assumed to be negligible.
- 6) The gas and slurry phases are modeled using the axial dispersion model, the most appropriate model for bubble column reactors (Deckwer et al., 1983).
- 7) The catalyst is not uniformly distributed in the reactor and the sedimentation-dispersion model (Cova, 1966; Kato et al., 1972, Smith et.al, 1985) is used for modeling the catalyst concentration.
- 8) The hydrodynamic parameters, namely gas holdup, interfacial area, heat and mass transfer coefficients and dispersion coefficients are assumed to be spatially independent.
- 9) The temperature dependence of the gas phase concentration $C_G = P/RT$ can be neglected since

$$d(1/T)dz = -1/T^2(dT/dz) \sim 0$$

- 10) Steady-state conditions prevail.
- 11) The vapor and liquid product streams leaving the reactor are in phase equilibrium.

2.3 Model Equations:

Based on the above assumptions, mass and energy balance were developed for the reactor model.

Gas Phase Mass Balance:

The gas phase mass balance with axial dispersion for component i can be written as:

$$\frac{1}{Pe_G} \frac{d^2 y_i}{dz^2} - \frac{d(vy_i)}{dz} - (St_{G,i})(y_i - x_i) = 0 \quad (2)$$

subject to the following boundary conditions:

$$vy_i - \frac{1}{Pe_G} \frac{dy_i}{dz} = y_{i,o} \quad \text{at } z=0 \quad (3)$$

$$\frac{dy_i}{dz} = 0 \quad \text{at } z=1 \quad (4)$$

The molar flow rate of gas will vary along the column due to reaction. The effect of change in molar flow rate on the superficial gas velocity can be determined by writing an overall mass balance. Thus

$$-\frac{dv}{dz} - \sum St_{G,i}(y_i - x_i) = 0 \quad (5)$$

The above equation is subject to the boundary condition

$$v = 1 \quad \text{at } z = 0 \quad (6)$$

The volumetric flow rate of the gas will also vary along the column due to change in hydrostatic

head. The local pressure along the column is given as

$$P(z) = P_T [1 + h_o(1-z)] \quad (7)$$

where

$$h_o = \rho_{sl} g (1 - \epsilon_g) L / P_T \quad (8)$$

Liquid Phase Mass Balance:

The liquid phase mass balance for component i can be written as:

$$\frac{1}{Pe_L} \frac{d^2 x_i}{dz^2} - \frac{dx_i}{dz} + St_{L,i}(y_i - x_i) + \sum \theta_{i,k} (1 - \epsilon_g) C_{cat} r_k (H_i L / P U_L) = 0 \quad (9)$$

subject to the following boundary conditions:

$$-\frac{1}{Pe_L} \frac{dx_i}{dz} + x_i = x_{i,o} \quad \text{at } z=0 \quad (10)$$

$$dx_i/dz = 0 \quad \text{at } z = 1 \quad (11)$$

Solid Phase Mass Balance:

The axial distribution of catalyst is governed by gravitational settling and axial dispersion due to agitation of the catalyst slurry by the gas flow. From assumption (8) the volume fraction of the liquid is constant along the column length and hence the mass balance on catalyst can be written

as:

$$\frac{1}{Pe_s} \frac{d^2w}{dz^2} + \frac{dw}{dz} = 0 \quad (12)$$

with boundary conditions:

$$w - 1/Pe_s(dw/dz) = 0 \quad (13)$$

$$\int_0^1 w dz = 1 \quad (14)$$

An analytical solution to the above equation is possible and is given below:

$$w = \frac{Pe_s \exp(-Pe_s z)}{[1 - \exp(-Pe_s)]} \quad (15)$$

2.4 Determination of Model Parameters

An extensive literature search was undertaken to estimate various parameters in the above model equations. Justifications for selecting various correlations are summarized in the following paragraphs.

Gas Holdup

The gas holdup in slurry bubble columns is affected by a number of factors which include: physical properties and coalescing behavior of liquid, gas and liquid velocities, column diameter, gas distributor design, solids concentration, size and density. The gas holdup also depends on the operating flow regime in the column. The development of a general correlation which takes

into account the effect of all these variables is indeed a difficult task. The work done by various researchers is summarized below:

There seems to be general agreement among researchers that the gas holdup and volumetric mass transfer coefficient decrease with increasing solids concentration for particle size larger than 10 micron (Kato et al., 1973; Kara et al., 1982; Koide et al., 1984). For particles smaller than 10 micron, the gas holdup can be higher than the solid free bubble column (Kara et al., 1982; Sada et al., 1986). The effect of suspended particles was generally found to diminish when the superficial gas velocity was higher than 0.1 m/s. Kato et al. (1973) found the gas holdups to decrease with increasing particle size over the size range used for their study (i.e. 60-175 micron). These results suggest that a correlation for gas holdup in slurry bubble columns should account for the effects of particle size as well as slurry concentration. While most of the literature work for hydrodynamic studies in slurry bubble columns has been carried out in aqueous solutions, Bukur et al. (1989) used Fischer-Tropsch waxes for their study. The data of Bukur et al. (1989,1990) is, therefore more relevant for our purposes. Experiments were conducted in both batch bubble column mode and continuous bubble column mode to investigate the effects of solids concentration (0 to 30 wt.%), solid particles type and size (iron oxide and silica particles; 0-5 μ m and 22-44 μ m). Two types of liquids, namely hydrotreated reactor wax (FT-300) and SASOL reactor wax were used. The operating conditions were generally selected to closely simulate slurry bubble column reactors for Fischer-Tropsch synthesis applications. It may be pointed out that Bukur et al. (1990) conducted their experiments at atmospheric pressure, using one gas only, therefore the effect of operating pressure (or gas density) was not studied.

Moreover, Bukur et al. (1990) data is limited to slurry concentration of upto 30 wt. %. The gas holdup data from PDU operation, however, indicate that for fine particle suspensions, the influence of slurry concentration becomes more significant at concentrations higher than 35 wt%.

Recent studies show that gas holdup in bubble columns generally increases with increasing operating pressure, hence gas density (Idogawa et al., 1987; Clark, 1990; Kojima et al., 1991). The influence of pressure has been found to depend on pressure level, distributor type, gas velocity and solids concentration. These results show that a correlation for gas holdup should account for the effect of operating pressure (or gas density). Most of the literature correlations, however, are based on data obtained at atmospheric pressure and usually for one gas, as a result these equations do not account for any influence of gas density. In solid-free bubble columns, a few gas holdup equations have been developed based on high pressure operation (Idogawa et al., 1985 and 1987) or experiments using various gases (Reilly et al., 1986; Hammer et al., 1984). There is, however, a lack of systematic research to investigate the influence of pressure on gas holdup in slurry bubble columns. The limited gas holdup values that have been reported in the literature for slurry bubble columns operating under high pressure are generally relatively high (Brown, 1984; Tarmy et al., 1984; Clark, 1990). The gas holdup data from Air Products and Chemicals PDU operation also demonstrates the influence of gas density on gas holdup. For similar operating conditions, higher gas holdups were obtained with CO-rich gases compared to H₂-rich gases.

Selection of Gas Holdup Correlation

Correlations for gas holdup in slurry bubble columns have been proposed by a number of researchers including Deckwer et al. (1980), Koide et al. (1984), Sada et al. (1986), Sauer and Hempel (1987) and Bukur et al. (1990). The hydrodynamics of solid-free bubble column have been investigated more extensively. Some of the well known correlations for solid-free bubble columns (i.e. Hughmark, 1967; Akita and Yoshida, 1973; Hikita et al., 1980) may prove useful for slurry bubble columns under certain operating conditions. Smith and Ruether (1985) modified the correlation of Hughmark (1967) for slurry bubble columns. It was observed that when liquid density was replaced by slurry density in the correlation of Hughmark (1967) the residual error was reduced for their slurry bubble column data. The modified correlation of Hughmark was, therefore, selected for further testing.

Relevant experimental data to test various literature correlations was available from Process Development Unit operation by Air Products and Chemicals for the development of slurry reactor technology for methanol synthesis. The experimental holdups for the PDU operation were obtained using the available information from different reports and the data provided by APCL engineers. Various literature correlations for the estimation of gas holdup (Table 1) were tested against this experimental gas holdup data. Table 2 gives average relative error, average absolute relative error and minimum and maximum errors for different correlations. It can be seen that correlations Hughmark (1967) and Hikita et al. (1980) predict gas holdup for the given system with average absolute error of 12% or less. Correlation of Hughmark (1967) can account

for the effect of slurry concentration but does not account for the effect of gas density. While Hikita et al. (1980) correlation can account for the effect of gas density it fails to account for the effects of slurry concentration. In the slurry reactor model we decided to include correlations of Hughmark (1967) and Hikita et al. (1980). For a given run, either of these correlations can be selected for testing. Correlation of Hughmark (1967) is recommended for CO-rich gases and slurry concentration higher than 34 wt. % but lower than 38 wt%. Hikita et al. (1980) correlation is recommended for slurry concentrations below 35 wt. %.

All the literature correlations for gas holdup are based on a constant gas velocity along the column height. Gas velocity would, however, decrease significantly along the reactor height for both methanol synthesis and Fischer-Tropsch synthesis due to decrease in moles of products. The effect of decreasing gas velocity on gas holdup and other hydrodynamic parameters need to be investigated.

Table 1. Literature correlations for gas holdup

Hughmark (1967) as modified by Smith and Ruether (1985)

$$e_G = [2 + (0.35/U_G)(\rho_{SL}\sigma/72)^{1/3}]^{-1}$$

Akita and Yoshida (1973)

$$\frac{e_G}{(1-e_G)^4} = 0.2 \left(\frac{g D_c^2 \rho_L}{\sigma_L} \right)^{1/8} \left(\frac{g D_c}{v_L^2} \right)^{1/12} \frac{U_G}{(g D_c)^{0.5}}$$

Hikita et al. (1980)

$$e_G = 0.672 \left(\frac{U_G \mu_L}{\sigma_L} \right)^{0.578} \left(\frac{\mu_L^4}{\rho_L \sigma_L^3} \right)^{-0.131} \left(\frac{\rho_G}{\rho_L} \right)^{0.062} \left(\frac{\mu_G}{\mu_L} \right)^{0.107}$$

Deckwer et al. (1980)

$$e_s = 0.053 U_g^{1.1}$$

Koide et al. (1984)

$$\frac{e_G}{(1-e_G)^4} = \frac{0.227 \left(\frac{U_G \mu_L}{\sigma_L} \right)^{0.918} \left(\frac{g \mu_L^4}{\rho_L \sigma_L^3} \right)^{-0.253}}{1 + 4.35 \left(\frac{e_{s,max}}{\rho_s} \right)^{0.748} \left(\frac{\rho_s - \rho_L}{\rho_L} \right)^{0.881} \left(\frac{D_c U_G \rho_L}{\mu_L} \right)^{-0.168}}$$

Table 1. Cont'd

Sada et al. (1986)

$$\left[\frac{\epsilon_G}{(1-\epsilon_G)^3}\right]_{III} = 0.41 U_t^{1/16} \epsilon_{s, \text{max}}^{-(.125 U_t^{-0.18})} \left[\frac{\epsilon_G}{(1-\epsilon_G)^4}\right]_{II}$$

here

$$U_t = \frac{g(\rho_P - \rho_L)d_P^2}{18\mu_L}$$

units of U_t and U_G are in cm

Sauer Hempel (1987)

$$\frac{\epsilon_G}{1-\epsilon_G} = 0.0277 [U_G / (v_{s, \text{max}} g U_G)^{25}]^{.844} [v_{s, \text{max}} / v_{\text{eff, rad}}]^{-0.136} [C_{\text{cat, avg}} / C_{\text{cat, b}}]^{0.0392}$$

$$v_{s, \text{max}} = v_L [1 + 2.5\epsilon_s + 10.05\epsilon_s^2 + 2.73 \times 10^{-3} \exp(16.6\epsilon_s)]$$

$$v_{\text{eff, rad}} = 0.011 D_c [g D_c]^{0.5} [U_G^3 / (v_{s, \text{max}} g)]^{1/8}$$

Bukur et al. (1990)

$$\epsilon_G = 0.24 Fr_G^{0.28} Bo^{0.14}$$

Table 2. Comparison of various literature correlations

Correlation by	Avg. Abs. Relative Error	Avg. Relative Error (Min & Max)
	(%)	(%)
Hughmark (1967)	12.	-4.0 (-18.0,38.)
Akita and Yoshida (1973)	34.	-34. (-45.,-8.7)
Hikita et al. (1980)	11.0	0.3 (-17.0,40.0)
Deckwer et al. (1980)	165.0	165.0 (28.0,286.0)
Koide et al. (1984)	36.0	-36.0 (-46.0, -8.4)
Sada et al. (1986)	16.0	-10.0 (-49.0,17.5)
Sauer and Hempel (1987)	17.5	-15.0 (-28.0,23.0)
Bukur et al. (1990)	20.0	-18.0 (-32.0,17.0)

Volumetric Mass Transfer Coefficient:

The estimation procedure for volumetric mass transfer coefficient in slurry bubble column reactors was analyzed critically in view of available correlations and mass transfer theory.

Volumetric mass transfer coefficient in a slurry bubble column is affected by a number of variables which include gas velocity, diffusivity, physical properties of liquid, properties of solid particles, concentration of solids, coalescing behavior of the system and gas distributor. Volumetric mass transfer coefficient also depends on operating flow regime in the column i.e. bubbly flow, churn turbulent regime. Bubbly flow regime is characterized by bubbles of narrow size distribution, high gas holdup and mass transfer rate. Bubbly flow regime is obtained at low gas velocities (< 0.05 m/s) with fine gas distributors. As the gas velocity is increased, the flow regime moves to churn turbulent regime via an intermediate flow regime. In the churn turbulent regime ($U_G > 0.08$ m/s) the effect of gas distributor is negligible. Industrial slurry reactor are operated at high gas velocities (> 0.14 m/s) to achieve high throughput, therefore, these reactors operate in churn turbulent regime.

Several correlations are available in the literature for the estimation of volumetric mass transfer coefficient in slurry bubble columns (i.e. Koide et al., 1984; Nguyen-tien et al., 1985; Sauer and Hempel, 1987; Schumpe et al., 1987). There is no relevant data, however, to test the validity of these correlations for our purposes. The correlations of Koide et al. (1984) and Sauer and Hempel (1987) are based on limited set of data over narrow operating conditions. Although the correlation of Schumpe et al. (1987) is based on a large set of data, it requires the

knowledge of fluid consistency index and flow behavior index for the slurry. This information may be difficult to obtain at reactor conditions. The correlation of Nguyen-tien et al. (1985) is based on a comprehensive study of gas-liquid mass transfer in three-phase contactors.

Nguyen-tien et al. (1985)

$$k_{La} = 0.39(1 - e_f/0.58)U_G^{0.67} \quad (16)$$

Nigam and Schumpe (1987) observed that for a batch operated slurry bubble column (no external recirculation of slurry) the mean solid fraction (e_f) should be replaced by solid fraction at the reactor bottom (e_{so}). Although, this correlation accounts for the effects of solids concentration and gas velocity, it is based on data obtained for oxygen mass transfer in aqueous solutions. For other systems, this correlation needs to be corrected for the effects of diffusivities, physical properties of liquid and coalescing behavior of the system.

Correction for Diffusivity:

Correlations for volumetric mass transfer coefficient in bubble columns (Akita and Yoshida, 1973; Ozturk et al., 1987) show that:

$$k_{La} \propto D_l^{0.5} \quad (17)$$

This shows that, gas-liquid mass transfer in bubble column is governed by Higbie's penetration theory.

Correction for Physical Properties of Liquid and Slurry:

Volumetric mass transfer coefficient in bubble columns has been found to be affected by the viscosity, surface tension and density of the liquid medium (Akita and Yoshida, 1973; Hikita et al., 1981; Ozturk et al., 1987). Akita and Yoshida (1973) and Hikita et al. (1980) studied gas-liquid mass transfer in aqueous solutions, while Ozturk et al. (1987) used organic liquids for their study. The effects of changes in surface tension can be enhanced in aqueous solutions of oxygenated compounds (i.e alcohols) due to a simultaneous change in coalescing behavior of the liquid. The correlation of Ozturk et al. (1987) was, therefore, used to apply corrections for physical properties of liquid. It gives:

$$k_{La} \propto \sigma_L^{-.33} \mu_L^{-.08} \rho_L^{.37} \quad (18)$$

The correlation of Ozturk et al. (1987) is based on data obtained in solid-free bubble column. The surface tension effects are not expected to change due to presence of solids. The effect of slurry viscosity on mass transfer coefficient is accounted for by the term in brackets in the correlation of Nguyen-tien et al. (1985). For density correction in slurry bubble columns, the liquid density can be replaced by slurry density, since fine particles in slurry reactor form a homogeneous slurry phase. The correlation of Nguyen-tien et al. (1985) can, therefore, be corrected as below to estimate volumetric mass transfer coefficients in other systems;

$$(k_{La})_l = (k_{La})_w (D_l/D_{o,w})^{0.5} (\sigma_L/\sigma_w)^{-0.33} (\mu_L/\mu_w)^{-0.08} (\rho_{SL}/\rho_w)^{-0.37} \quad (19)$$

The above correlation is applicable to coalescing media, for noncoalescing media (and other high gas holdup conditions) it would give conservative estimates of volumetric mass transfer coefficient.

A number of correlations have also been proposed for volumetric mass transfer coefficient in solid-free bubble columns. These correlation generally do not account for the effects of solid particles on gas-liquid mass transfer rate. The correlation proposed by Akita and Yoshida (1973), however, includes a gas holdup term which would indirectly account for the effects of solids. The proposed correlation also accounts for physical properties of liquid and is based on a large set of experimental data. This correlation may overpredict the effect of reactor diameter for large diameter reactors (> 0.15 m). Literature data, however, indicate little effect of column diameter on volumetric mass transfer coefficient for diameters larger than 0.15 m. Therefore, the effect of column diameter has been restricted to 0.15 m for this correlation. The modified correlation of Akita and Yoshida (1973) also has been included in the slurry reactor model and can be selected from the input data file.

Liquid Phase Dispersion Coefficient

While liquid phase dispersion in solid-free bubble columns has been investigated extensively, very little work has been done to measure liquid backmixing in slurry bubble columns.

However, in the suspension of fine catalyst particles used in Fischer-Tropsch synthesis reactors, there is expected to be little effect of the presence of solids on liquid mixing. The various correlations available in the literature for liquid phase dispersion in bubble column were compared by Wendt et al. (1984). The correlation proposed by Deckwer et al. (1974) provides a good estimate of the liquid phase dispersion coefficient. This correlation was, therefore, selected to predict liquid phase dispersion coefficient in slurry reactor.

Deckwer et al. (1974)

$$D_L = 0.68 D_C^{1.4} U_G^{0.3} \quad (20)$$

Gas Phase Dispersion Coefficient:

Only a few studies have investigated gas phase dispersion in bubble columns (Towell and Ackerman, 1972; Field and Davidson, 1980; Kawagoe et al., 1989). Kawagoe et al. (1989) observed that the correlation of Towell and Ackerman (1972) provided a good estimate of the overall gas phase dispersion coefficient in bubble columns. A recent report from Air Products and Chemicals (Topical Report: Tracer Studies in the LaPorte LPMEOH PDU, 1990), however, showed that literature correlations (Towell and Ackerman, 1972; Field and Davidson, 1980) over-predicted gas phase mixing by a factor of about three in their large diameter slurry bubble column reactor. A new correlation was then recommended based on the best fit of their data.

Towell and Ackerman (1972)

$$D_G = 20.0 D_C^2 U_G \quad (21)$$

Air Products and Chemicals (1990)

$$D_G = 21.7 D_C^{1.5} U_G^{1.8} \quad (22)$$

Both the above correlations have been included in the slurry reactor model, however, correlation of Air Products and Chemicals (1990) is recommended for commercial size reactors.

Axial Solids Distribution:

Although several groups of researchers have investigated distribution of solids in slurry bubble columns, the work of Bukur et al. (1989), using Fischer-Tropsch waxes, is more relevant for our purposes. Bukur et al. (1989) observed that the axial distribution for the 0-5 μm and 20-44 μm iron oxide and silica particles were uniform for all runs in the continuous mode of operation. For batch mode of operation, the 0-5 μm particles showed only a slight gradient with high concentration towards the bottom of the column. However, with 20-44 μm particles significant gradients in axial solids distribution profiles were observed in the batch mode of operation. Bukur et al. (1989) also noted that the correlation of Smith and Ruether (1985) provided a good prediction of solids dispersion coefficient in slurry bubble columns.

Smith and Ruether (1985)

$$Pe_p = 9.6(Fr_G^6/Re_G)^{0.114} + 0.019Re_p^{1.1} \quad (23)$$

$$Re_p = Ar/18 \quad \text{if } Re_p < 0.05 \quad (24)$$

$$Re_p = (Ar/13.9)^{0.7} \quad \text{if } Re_p > 0.5 \quad (25)$$

Smith and Ruether (1985) have suggested the following equation for hindered settling velocity in particle swarm.

$$U_s = 1.1 U_G^{0.026} U_t^{0.8} e_L^{3.5} \quad (26)$$

Physical, Thermodynamic and Transport Properties:

Various literature correlations and models were reviewed to select suitable methods for estimation of physical, thermodynamic and transport properties. Whenever possible, available experimental data were used to develop suitable correlations.

Properties of Liquid:

For its liquid phase methanol process development program, Air Product selected Drakeol 10

as the solvent. Drakeol 10 from Penreco was selected based on plant trials, when Witco announced discontinuation of Freeze-100. Drakeol 10 is 65% paraffinic and 35% naphthenic and with average carbon number of 25. The liquid phase in Fischer-Tropsch reactor was approximated by paraffinic liquid with average carbon number of 38. The equations for density, viscosity and specific heats for the liquid phase were developed as a function of temperature.

Diffusivities:

Akgerman measured the diffusion coefficients for synthesis gas in high molecular weight liquids (n-C₂₀ and n-C₂₈) and FT waxes for a DOE contract DE-AC22-84PC 70032 at temperatures ranging from 373 to 534°K. The following correlation was proposed to estimate diffusion coefficients.

$$\frac{10^9 D_i}{T^{0.5}} = \frac{94.5(V_s - c_i V_{so})}{M_i^{0.239} M_s^{0.781} (\xi_i / \xi_s)^{1.134}} \quad (27)$$

Here

$$c_i V_{so} = \frac{c_i N \xi_s^3}{\sqrt{2}} \quad (28)$$

$$c_i = 1.206 + 0.0632(\xi_i / \xi_s) \quad (29)$$

Henry Law Constants:

Chao and Lin (1987) investigated the solubilities of synthesis gas in high molecular weight solvents (n-C₂₀, n-C₂₈ and n-C₃₆) and Fischer-Tropsch waxes for a DOE contract No. DE-AC22-84PC 70024. Solubilities of hydrogen, carbon monoxide, carbon dioxide, methane, ethane and ethylene were measured at temperatures in the range of 100-300°C and pressure 10-50 atm. Lee (1986) studied phase equilibria for syngas in Witco-40 and Freezene-100 oils. Graff et al. (1988) measured solubility of syngas in the temperature range of 210 to 260°C in another high molecular weight solvent (squalene). These authors observed that the Henry's coefficients could be well approximated by an equation of the form:

$$H_i = A_i \exp(B_i/T) \quad (30)$$

Following equations were obtained for Henry's constants from regression analysis of the data from Chao and Lin (C₄₃ wax, temperature range 200 to 300°C).

$$H_{H_2} = 83.35 \exp(604.7/T) \quad (31)$$

$$H_{CO} = 151.0 \exp(136.0/T) \quad (32)$$

$$H_{CO_2} = 297.0 \exp(-582.4/T) \quad (33)$$

$$H_{CH_4} = 204.4 \exp(-264.2/T) \quad (34)$$

$$H_{C_2H_6} = 558.36 \exp(-1118.87/T) \quad (35)$$

Kinetic Models for Methanol Synthesis:

In the synthesis of methanol, the following chemical reactions are primarily discussed:

Several researchers have investigated the kinetic rate for methanol synthesis, using Cu/ZnO/Al₂O₃ catalyst. The proposed models can be divided into power law rate expressions and mechanistic models.

Power law models for methanol synthesis in three-phase slurry reactors have been proposed by Berty et al. (1983), Wedel et al. (1988) and Lee(1990). The proposed models are shown below:

Berty et al. (1983)

$$r_{MeOH} = k_1 (C_{H_2} - \frac{C_{MeOH}}{K_{eq,1} C_{H_2} C_{CO}}) \quad (39)$$

$$r_{WGS} = k_2(C_{H_2} - \frac{C_{CO}C_{H_2O}}{K_{eq,2}C_{CO_2}}) \quad (40)$$

Here $K_{eq,1}$ and $K_{eq,2}$ are equilibrium constants for reactions 1 and 2 respectively. This model does not account for partial pressure of carbon dioxide.

Lee (1990)

$$r_{MeOH} = A \exp(-E/RT)(C_{H_2} - C_{H_2,eq}) \quad (41)$$

Here

$$A = 3380 \text{ m}^3/\text{kg.s} \quad E = 18,800 \text{ kcal/kmol}$$

This model does not account for partial pressure of carbon monoxide and carbon dioxide.

Wedel et al. (1988) developed a power law rate expression based on a review of various literature models.

$$r_{MeOH} = 1.98 \times 10^7 \exp(-56343/RT) P_{H_2}^{0.4} P_{CO}^{0.18} - 2.15 \times 10^{10} \exp(-85930/RT) P_{CH_3OH}^{0.13} \quad (42)$$

Since the power law rate expressions are empirical in nature, their applicability is limited to the narrow range of experimental conditions used for the study. Moreover, none of the proposed power law expressions account for the effect of CO_2 concentration on methanol production rate, while the results from Air Products and Chemicals clearly show the importance of CO_2

concentration on methanol production rate.

Graff et al. (1988) developed a mechanistic model for the kinetics of three-phase methanol synthesis based on extensive set of experiments. The proposed model is given below:

$$r_{MeOH,1} = \frac{k_{ps,1} K_{CO} (C_{CO} C_{H_2}^{3/2} - C_{CH_3OH} / (C_{H_2}^{1/2} K_{C1}))}{1 + K_{CO} C_{CO} + K_{CO_2} C_{CO_2} (C_{H_2}^{1/2} + K_{H_2O} / K_{H_2}^{1/2}) C_{H_2O}} \quad (43)$$

$$r_{WGS} = \frac{k_{ps,2} K_{CO_2} (C_{CO_2} C_{H_2} - C_{H_2O} C_{CO} / K_{C2})}{(1 + K_{CO} C_{CO} + K_{CO_2} C_{CO_2}) (C_{H_2}^{1/2} + (K_{H_2O} / K_{H_2}^{1/2}) C_{H_2O})} \quad (44)$$

$$r_{MeOH,2} = \frac{k_{ps,3} K_{CO_2} (C_{CO_2} C_{H_2}^{3/2} - C_{CH_3OH} C_{H_2O} / (C_{H_2}^{3/2} K_{C3}))}{1 + K_{CO} C_{CO} + K_{CO_2} C_{CO_2} (C_{H_2}^{1/2} + (K_{H_2O} / K_{H_2}^{1/2}) C_{H_2O})} \quad (45)$$

$$K_{C1} = 1.7210^{-16} \exp(126011/RT) \quad (46)$$

$$K_{C2} = 5.8110 \exp(-33760/RT) \quad (47)$$

$$K_{C3} = K_{C1} K_{C2} \quad (48)$$

The kinetic and adsorption constants are given in Graff et al. (1988).

The Graff et al. (1988) model is based on proper analysis of reaction mechanism for the reaction system. It also accounts for the effects of CO_2 concentration on methanol production rate. This kinetic model is, therefore expected to provide better predictions of the reaction rates over a wide range of operating conditions.

Stoichiometry of Fischer-Tropsch synthesis:

The products of Fischer-Tropsch synthesis range from methane to high molecular weight paraffins. FT synthesis products are known to obey Schulz-Flory distribution. The general stoichiometry of Fischer-Tropsch reaction can be given as:

Water formed as primary product is converted to carbon dioxide by the water gas shift reaction in presence of iron catalyst.

As shown by Stern et al. (1985), the stoichiometric coefficients (γ_i) and average number of carbon (n) and hydrogen (m) atoms in the hydrocarbon products can be expressed in terms of the probability of chain growth (α) and the fraction of paraffinic hydrocarbons (λ) variables.

$$\gamma_{\text{CO}} = \frac{1}{D} \quad (51)$$

$$\gamma_{H_2} = \frac{2 + (1-\alpha)^2 + \lambda \alpha (1-\alpha)}{D} \quad (52)$$

$$\gamma_{HC} = \frac{(1-\alpha)}{D} \quad (53)$$

$$\gamma_{H_2O} = \frac{1}{D} \quad (54)$$

$$D = 3 + (1-\alpha)^2 + \lambda \alpha (1-\alpha) \quad (55)$$

$$n = (1-\alpha)^{-1} \quad (56)$$

$$m = 2[(1-\alpha)^{-1} + (1-\alpha) + \lambda \alpha] \quad (57)$$

The value of chain growth probability factor (α) and fraction of paraffins in the product (λ) are a function of the catalyst and operating conditions. For the production of high molecular weight products, value of α has been found to be in the range of 0.85-0.95.

Two Chain Growth Probabilities in Fischer-Tropsch Synthesis:

There is also some evidence for two chain growth probabilities in Fischer-Tropsch synthesis (Huff et al., 1984; Bukur et al., 1989). Huff et al. (1984) observed a marked break on a Flory plot at carbon number of ten. At higher carbon numbers, hydrocarbons are produced with a much higher probability of chain growth than for lower carbon numbers. The carbon number distribution is interpreted in terms of a dual site mechanism that can be described by an extended Flory equation which accounts for the fraction of product formed on each type of site.

$$m_n = \beta(1-\alpha_1)\alpha_1^{n-1} + (1-\beta)(1-\alpha_2)\alpha_2^{n-1} \quad (58)$$

where m_n is the mole fraction of products containing n carbon atoms, β is the fraction of type I sites on the catalyst and α_1 and α_2 are the chain growth probabilities associated with the type I and type II sites respectively.

A more general approach for the stoichiometry of FT synthesis should account for the two chain growth probabilities. The values of γ_i , x and y are now expressed in terms of the following variables.

α_1, α_2	two chain growth probabilities
λ	the fraction of paraffinic hydrocarbons
β	fraction of type I sites on the catalyst

$$\gamma_{CO} = -\frac{\frac{\beta}{1-\alpha_1} + \frac{1-\beta}{1-\alpha_2}}{D} \quad (59)$$

$$\gamma_{H_2} = -\frac{2\left(\frac{\beta}{1-\alpha_1} + \frac{1-\beta}{1-\alpha_2}\right) + \lambda[\beta\alpha_1 + (1-\beta)\alpha_2] + [\beta(1-\alpha_1) + (1-\beta)(1-\alpha_2)]}{D} \quad (60)$$

$$\gamma_{H_2O} = \frac{\frac{\beta}{1-\alpha_1} + \frac{1-\beta}{1-\alpha_2}}{D} \quad (61)$$

$$D=3\left(\frac{\beta}{1-\alpha_1}+\frac{1-\beta}{1-\alpha_2}\right)+\lambda[\beta\alpha_1+(1-\beta)\alpha_2]+[\beta(1-\alpha_1)+(1-\beta)(1-\alpha_2)] \quad (62)$$

$$x=\frac{\beta}{1-\alpha_1}+\frac{1-\beta}{1-\alpha_2} \quad (63)$$

$$y=2\left[\left(\frac{\beta}{1-\alpha_1}+\frac{1-\beta}{1-\alpha_2}\right)+\lambda(\beta\alpha_1+(1-\beta)\alpha_2)+(\beta(1-\alpha_1)+(1-\beta)(1-\alpha_2))\right] \quad (64)$$

Kinetics of Fischer-Tropsch Synthesis:

The reaction kinetics of Fischer-Tropsch synthesis over iron catalyst have been investigated by a number of researchers. The various kinetic expressions have been reviewed by Huff and Satterfield (1984) and Zimmerman and Bukur (1990). The rate expression proposed by Anderson (1956) was found to be particularly useful.

$$r_{FT}=\frac{k_o P_{CO} P_{H_2}}{P_{CO}+a_1 P_{H_2O}} \quad (65)$$

This equation includes water inhibition effect. At synthesis gas conversion below about 60 % Equation (65) reduces to

$$r_{FT} = k_1 P_{H_2} \quad (66)$$

Huff and Satterfield (1984) derived an alternate form of expression based on the observed hydrogen dependance for a fused-magnetite catalyst.

$$r_{FT} = \frac{k_2 P_{CO} P_{H_2}^2}{P_{CO} P_{H_2} + b_1 P_{H_2O}} \quad (67)$$

Equations (65) and (67) have the same form if the constant 'a₁' in Equation (65) depends on the H₂ partial pressure i.e. a₁ = b₁/H₂.

For precipitated iron catalyst (100Fe/0.3Cu/0.2K), Zimmerman and Bukur (1990) observed that Equation (65) gave a better fit to their data compared to Equation (67). Similar observations were made by Nettelhoff et al. (1985) using a precipitated, unpromoted iron catalyst. Based on these observations, kinetic expression given by Equation (65) was selected for precipitated iron catalyst in the FT reactor model. The rate constants and adsorption constants were obtained from experimental data of Zimmerman and Bukur (1990).

Water gas shift reaction:

The water gas shift reaction occurs readily over potassium promoted iron catalyst. The shift reaction enables CO rich feeds to be utilized efficiently without the need for external shift. Both

Equations (49) and (50) for the FT and WGS reaction must be considered to accurately predict both $H_2 + CO$ conversions and H_2/CO usage ratio which requires knowledge of WGS kinetics. The following rate expression for water gas shift reaction has been selected based on literature information (Kuo, 1983; Zimmerman and Bukur, 1990).

$$r_{WGS} = k_{wo} \frac{(P_{CO}P_{H_2O} - P_{CO_2}P_{H_2}/K_P)}{P_{CO} + a_1 P_{H_2O}} \quad (68)$$

It may be pointed out here that literature kinetic expressions for FT synthesis are based on partial pressures in the gas phase while in a slurry reactor the rate depends on the liquid phase concentrations.

Cobalt Catalyst:

Fischer-Tropsch synthesis on a cobalt catalyst has been investigated by a number of researchers (Sarup and Wojciechowski, 1988, 1989; Yates and Satterfield, 1991). Specific activity of cobalt catalyst is high for FT synthesis (Withers et al., 1990). The FT synthesis over cobalt catalysts produce mostly n-alkanes and 1-alkenes. However, in contrast to most iron-based FT catalysts, cobalt is not very active for the water gas shift reaction. Yates and Satterfield (1991) reviewed and tested various literature rate expressions for FT synthesis over cobalt catalyst. The following kinetic equation was recommended based on their study.

$$r_{FT} = \frac{k_c P_{CO} P_{H_2}}{(1 + c P_{CO})^2} \quad (69)$$

2.5 Vapor-Liquid Equilibrium Calculations in Fischer-Tropsch Synthesis:

The major constituents of the products from Fischer-Tropsch synthesis are the hydrocarbons ranging from methane to high melting paraffins with relatively small quantities of olefinic compounds. For iron catalyst, carbon dioxide is one of the major products formed with relatively small amounts of product water. In the case of cobalt catalyst, however, due to its poor activity for water gas shift reaction, water will be the major byproduct with relatively small amount of carbon dioxide. Small quantities of other byproducts such as alcohols, aldehydes, ketones etc. are also formed. Straight-chain paraffins along with some 2-methylated branched paraffins predominate among the saturated hydrocarbons; major olefins are terminal olefins.

The products and the unreacted synthesis gas leaving the top of the slurry reactor will be assumed to be in equilibrium with the liquid phase in the reactor. A computer program has been developed to study the phase equilibria of the vapor and the liquid streams leaving the slurry reactor. Such information will be helpful in determining the relative flow rates and the composition of vapor and liquid streams which can be further used in the process design of the downstream units in the Fischer-Tropsch Plant. The conversion and the production yields from the slurry reactor model will be used to determine the overall composition for the phase

equilibrium calculations. The problem presented here is identical with that of determining vapor and liquid compositions in a multi-component flash separation. Following assumptions will be made regarding the products formed during the reaction. The hydrocarbon products consists of n-alkanes and n-alkenes only. These are, in fact, the main products for many of the FT catalyst and little design error will be introduced by lumping the methyl-branched isomers with n-alkanes and n-alkenes. In the lower oxygenates, ketones and primary alcohols are formed in relatively small amounts as compared to water and hence these compounds will be lumped with water. The light hydrocarbons (C_5 to C_{11}) will be lumped together; heavy hydrocarbons (C_{12} to C_{15}) will be lumped together and hydrocarbons C_{16} and heavier will be considered as the slurry reactor wax with an average composition of C_{40} paraffin. The olefin to paraffin split of the hydrocarbon products can be obtained from the literature. For example, unreacted synthesis gas and reaction products from the Mobil's pilot plant for Fischer-Tropsch synthesis may be characterized into following fourteen components:

<u>Component No.</u>	<u>Component(s)</u>
1	Carbon Dioxide
2	Water + Ketones & Primary Alcohols (Acetone & 1-Propanol)
3	Hydrogen
4	Carbon Monoxide
5	Methane
6	Ethylene
7	Ethane

8	Propylene
9	n-Propane
10	Butylene
11	n-Butane
12	C ₅ to C ₁₁ Light Hydrocarbons Lumped as n-Octane
13	C ₁₂ to C ₁₅ Heavy Hydrocarbons as n-Tridecane
14	C ₁₆ and Heavier as Slurry Reactor Wax (C ₄₀ Paraffin)

Phase Equilibrium Calculations for Multicomponent Vapor-Liquid Phase Equilibria:

A technique has been presented by Bendale, 1991, to predict multicomponent vapor-liquid equilibria from the optimized binary interaction parameters obtained from the Peng-Robinson equation of state, which is given as:

$$P = \frac{RT}{(V - b_{\text{mix}})} - \frac{a_{\text{mix}}}{V(V + b_{\text{mix}}) + b_{\text{mix}}(V - b_{\text{mix}})} \quad (70)$$

For a multicomponent mixture, the parameters a_{mix} and b_{mix} are given by the following expressions:

$$a_{mix} = \sum_i \sum_j x_i x_j \sqrt{a_i a_j} (1 - \delta_{ij}) \quad (71)$$

$$b_{mix} = \sum_i x_i b_i \quad (72)$$

In the above equation, δ_{ij} is defined as an interaction parameter that describes the deviation of parameter a_{mix} from the geometric mean of the pure component parameters a_i and a_j and is assumed to be constant. The pure component parameters a_i and b_i are given as:

$$a_i = a(T_c) \alpha(T_r, \omega) \quad (73)$$

$$a(T_c) = 0.45724 (R^2 T_c^2 / P_c) \quad (74)$$

$$\alpha(T_r, \omega) = [1 + \kappa (1 - \sqrt{T_r})]^2 \quad (75)$$

$$\kappa = C_a (0.37464 + 1.54226 \omega - 0.26992 \omega^2) \quad (76)$$

If ω is greater than 0.5, then

$$\kappa = C_a (0.379642 + 1.48503 \omega - 0.164423 \omega^2 + 0.016666 \omega^3) \quad (77)$$

$$b_i = C_b [0.0778 (RT_c / P_c)] \quad (78)$$

The optimized values of correction factors C_a and C_b for pure components are evaluated which minimize the sum of absolute relative errors of calculated and experimental saturated vapor pressure and saturated liquid density. The values of these correction factors approach unity for small molecules and non-polar gases which the Peng-Robinson equation of state is known to model accurately. If these values are not available, then the default values are assigned as unity.

The expression for the fugacity coefficient obtained from the evaluation of the following equation,

$$RT \ln \Phi_i = \int_V \left[\left(\frac{\partial P}{\partial n_i} \right) - \frac{RT}{V} \right] dV - RT \ln Z \quad (79)$$

is given as:

$$\ln \Phi_i = \frac{b_i}{b_{mix}} (Z - 1) - \ln (Z - B) + \left[\frac{\sum_k x_k (a_{ik} + a_{kl})}{a_{mix}} - \frac{b_i}{b_{mix}} \right] \times \frac{a_{mix}}{2.414 b RT} \ln \left[\frac{Z - 0.414 B}{Z + 2.414 B} \right] \quad (80)$$

$$B = \frac{b_{mix} P}{RT} \quad (81)$$

Phase equilibrium calculations are performed at constant temperature and pressure and known overall composition to determine the flow rates and compositions of vapor and liquid streams. The governing equations include overall and component material balances, mole fraction constraints, and thermodynamic equilibrium criterion of equal fugacities of each component in each phase. For an N component system at constant temperature and pressure, there will be 2N independent expressions for these components equilibrated in two phases, with 2N unknowns, L, V, x_i 's and y_i 's, respectively.

On the basis of one mole of mixture F (unreacted reactants and products formed), an overall material balance and a component balance for each component can be represented as follows:

$$L + V = F = 1 \quad (82)$$

$$Lx_i + Vy_i = Fz_i = z_i, \quad i = 1 \text{ to } N \quad (83)$$

with the following constraints:

$$\sum_i z_i = \sum_i x_i = \sum_i y_i = 1, \quad i = 1 \text{ to } N \quad (84)$$

and thermodynamic criteria,

$$f_i^V = f_i^L \quad \text{or} \quad \phi_i^V y_i P = \phi_i^L x_i P \quad \text{or} \quad \phi_i^V y_i = \phi_i^L x_i, \quad i = 1 \text{ to } N \quad (85)$$

To perform Flash calculations, temperature T and pressure P are considered as the known variables, which are used to calculate the unknown mole fractions x_i 's and y_i 's of the liquid and vapor phases, respectively. In addition to system temperature and pressure, the input data required consists of critical temperature, critical pressure and acentric factor of each component as well as the optimized binary interaction parameters, δ_{ij} as applied to the Peng-Robinson equation of state. The liquid and vapor phase fugacity coefficients for each component can be readily calculated from the expression 80. The set of equations 82, 83, 84 and 85 are solved simultaneously to determine the flow rates and mole fractions of liquid and vapor streams.

3.0 Development of Computer Codes:

The model equations for the Fischer-Tropsch synthesis reactor constitute a set of coupled second-order non-linear differential equations. These equations are not amenable to an analytical solution and therefore, a numerical method was selected for solution. Orthogonal collocation techniques are particularly suitable for the solution of boundary value problems and the software package, COLSYS, developed by Ascher et al. (1981) was selected for the numerical solution of the model equations. This method is based on spline collocation at Gaussian points using a B-spline basis. Approximate solutions are computed on a sequence of automatically selected meshes until a user-specified set of tolerances is satisfied.

Computer codes for the reactor model have been developed with a modular approach to computer programming, to ensure easy modifications by the user. Standard FORTRAN 77 has been used for writing the codes since this will ensure transfer to other compatible systems. The codes have been tested on VAX/VMS operating system and personal computers. Appendix-A gives the system requirements and operating instructions for personal computers. Computer codes for the slurry reactor model have been developed for the following cases:

With external recirculation of slurry

- o Gas plug flow; Liquid axial dispersion
- o Gas axial dispersion; Liquid axial dispersion

No external recirculation of slurry

- o Gas plug flow; Liquid axial dispersion
- o Gas axial dispersion; Liquid axial dispersion

3.1 Test and Validation of Reactor Models:

Both methanol synthesis and Fischer-Tropsch synthesis models were tested against available experimental data from demonstration and process development units.

Methanol Synthesis

For methanol synthesis, Air products and Chemicals conducted process development unit runs in a slurry reactor to investigate the influence of different operating conditions on methanol production rates. The range of operating variables investigated are summarized in Table 3.

Table 3. Operating conditions and reactor dimensions for process development unit for methanol synthesis

Diameter	0.57 m
Length	5.85 m
Temperature	235-285°C
Pressure	35-62 atm
Gas Velocity	0.04-0.194 m/sec

Table 3. Cont'd

Slurry Conc. 28.0-42.0 wt. %

H₂/CO ratio 0.5-2.6

CO₂ Conc. 0.9-12 %

Air Products PDU reactor for methanol synthesis was simulated using our reactor model. The kinetic expressions of Berty et al. (1983), Wedel et al. (1988) and Graff et al. (1988) were tested in the model. None of these kinetic expressions could predict the high production rates achieved for PDU runs. The predicted rates were lowest for Berty et al. (1983) model followed by Graff et al. (1988) and Wedel et al. (1988) models. These kinetic expressions were again tested in the reactor model by adjusting the rate constants to match the experimental production rate for a run where mass transfer effects were expected to be negligible (i.e. high gas velocity and low slurry concentration). The kinetic expressions of Berty et al. (1983) and Graff et al. (1988) could not predict the effects of temperature, hydrogen concentration and carbon dioxide concentrations. The Wedel et al. (1988) power law expression could well predict the effect of temperature and hydrogen concentration. The influence of carbon dioxide concentration was not accounted for, since the reported expression is based on data obtained with more than optimum carbon dioxide concentration. Suitable correction factors for the effect of lower carbon dioxide concentrations were, therefore incorporated into the model based on literature information. It was observed that for slurry concentration lower than 35 wt. % and gas velocities higher than 0.1 m/s, the predicted rates were generally within 6% of the experimental rates. Figure 1 is a parity plot of production rates for 22 such runs. The predicted rates were, however, high for gas velocities below 0.05

m/s for all slurry concentrations. The predicted rates were always higher for slurry concentrations higher than 35 wt%. As shown in Figure 2, for a given gas velocity, the relative error increased with increasing slurry concentration. Also for a given slurry concentration relative error decreased with increasing gas velocity. The low production rates observed at high slurry concentrations and low gas velocities could be the result of reduced gas-liquid mass transfer rate due to poor gas-liquid contact in some parts of the reactor (mainly distributor region). The available literature correlations could not, however, predict the large decreases in volumetric mass transfer coefficient required to predict the experimental reactor performances. Further work is needed to investigate the changes in mixing patterns and gas-liquid contacting with increasing slurry concentrations in large diameter columns.

Figure 1. Predicted vs experimental production rates for PDU

Figure 2. Effects of slurry concentration on relative error between predicted and experimental rates

Effect of Operating Variables

The reactor model for methanol synthesis was also used to investigate the effect of operating variables. For the results of this section, the slurry reactor was modeled assuming there was no external recirculation of slurry and both gas and liquid phases were axially dispersed. Table 4 gives the range of operating variables studied.

Table 4. Range of input data used to simulate slurry Fischer-Tropsch reactor

Diameter	4.8 m
Length	14.5 m
Temperature	232-265 °C
Pressure	50-70 atm
Gas Velocity	0.10-0.16 m/s
Slurry Conc.	30-35 wt. %
Syngas in Feed	90.0%
H ₂ /CO ratio	0.5-2.0
Particle size	0.000025-0.00005 m

Figure 3 shows that methanol production rate increases with increasing reactor temperature, up to a temperature of about 240°C. Production rate, however, decreased sharply at higher temperatures due to increasing rate of backward reaction. Figure 4 shows that methanol production rate increased linearly with reactor pressure while syngas conversion increased only

slightly with increasing reactor pressure. Figure 5 shows that while the production rate increased linearly with space velocity, the syngas conversion decreased with increasing space velocity. Methanol production rate increased linearly with increasing hydrogen to carbon monoxide ratio upto a ratio of about one (Figure 6). The rate of increase dropped for higher hydrogen to carbon monoxide ratios.

Figure 3. Effect of temperature on methanol production rate

Figure 4. Effect of pressure on methanol production rate and hydrogen conversion

Figure 5. Effect of space velocity on methanol production rate and syn gas conversion.

Figure 6. Effect of hydrogen to carbon monoxide ratio on methanol production rate.

Parameter Sensitive Analysis

Computer simulation models allow the user to perform parameter sensitivity analysis and calculate estimated errors. For example it is possible to quantify error in predicted reactor productivity due to an estimated error in gas holdup. Parameter sensitive analysis was carried out to investigate the effects of non-adjustable variables such as gas holdup, volumetric mass transfer coefficient and gas phase dispersion coefficient.

Figure 7 shows that both production rate and syngas conversion decreased with increasing gas holdup. It can also be observed that a 14 % error in gas holdup estimate could result in about 3 % error in estimated production rate for a commercial size reactor. Figure 8 shows that production rate increases with increasing mass transfer coefficient, the rate of increase, however, slows down when volumetric mass transfer coefficient increases above 0.45 s^{-1} . In this region the overall rate is no longer limited by mass transfer. The volumetric mass transfer coefficient estimated by the selected correlation in the model is also shown on Figure 8. The reactor production rate decreased with increasing gas phase dispersion coefficient (Figure 9). As the dispersion coefficient increases the reactor approaches the behavior of a single CSTR. For a commercial size slurry reactor, a 100% error in estimated dispersion coefficient would result in about 2 % error in production rate.

Figure 7. Effect of gas holdup on methanol production rate and hydrogen conversion

Figure 8. Effect of volumetric mass transfer coefficient on methanol production rate

Figure 9. Effect of gas phase dispersion on methanol production rate

Fischer Tropsch Synthesis

Simulation of Demonstration Unit:

The slurry reactor model for Fischer-Tropsch synthesis was tested using the demonstration unit at Rheinpreussen. Table 5 gives the reactor dimensions and operating conditions used at Rheinpreussen and Table 6 presents simulation results. It can be seen that although, the predicted syngas conversion was 12 % higher the predicted yield of C_3^+ products was within 4%. The higher syngas conversion could be attributed to higher shift activity of the catalyst used at Rheinpreussen.

Table 5. Operating conditions and reactor dimensions for Rheinpreussen
Demonstration Unit

Diameter	1.29 m
Length	7.7 m
Temperature	268°C
Pressure	11.84 atm
Gas velocity	0.095 m/s
Slurry Conc.	18 wt %

Table 6. Simulation Results for Rheinpreussen unit

	Reported	Predicted
Syngas conversion	89%	77%
STY of C ₃ ⁺ Products (kg/hr-m ³)	38.75	37.8

Simulation with Bechtel Design Data:

Bechtel presented a design for a commercial size slurry reactor for Fischer-Tropsch synthesis (Fox and Degen, 1990). The slurry reactor model developed in this report was used to predict the reactor performance using Bechtel design data. Table 8 compares the reactor performance given by Bechtel study with the performance predicted by the Fischer-Tropsch reactor model developed in this report. The predicted syngas conversion is within 1% of the reported value. However, predicted production rate and space time yield are higher.

Table 7. Bechtel Design Data

Diameter	4.8 m
Length	12.0 m
Net xsect of reactor	15.16 m ²
Reactor volume	211.0 m ³
Temperature	257°C
Pressure	28.3 atm
Slurry Conc.	35 wt%
Gas velocity	0.14 m/s

Table 8. Simulation Results with Bechtel Design data

	Bechtel Design	Model Prediction
Syngas conversion	80%	79%
-CH ₂ - Production (MTD)	403.4	405.0
Space Time Yield (kg-CH ₂ -/hr-m ³)	80.	87.4

The Fischer-Tropsch reactor model was also used to investigate the effect of operating variables on reactor performance. Parameter sensitive analysis was carried out to investigate the influence of non-adjustable variables such as gas holdup, volumetric mass transfer coefficient and gas phase dispersion coefficient.

For the results of this section, the slurry reactor for Fischer-Tropsch synthesis was modeled assuming there was no external recirculation of slurry and both gas and liquid phases were axially dispersed. Table 9 gives the range of operating variables studied.

Table 9. Range of input data used to simulate slurry Fischer-Tropsch reactor

Diameter	4.5 m
Length	12.0 m
Temperature	230-270 °C
Pressure	15-20 atm
Gas Velocity	0.10-0.16 m/s
Slurry Conc.	30-35 wt. %
Syngas in Feed	90.0%
H ₂ /CO ratio	0.5-1.5
Particle size	0.00003-0.00005 m

Figure 10 shows that syngas conversion increased with increasing reactor temperature. Figure 11 shows that space time yield increases linearly with pressure while syngas conversion does not change significantly. Space time yield also increases almost linearly with increasing space velocity while syngas conversion decreases linearly (Figure 12). Figure 13 shows the effect of H_2/CO ratio in the feed gas on space time yield and syngas conversion. It can be seen that both pass through a maximum at a H_2/CO ratio of about 0.6 (stoichiometric).

Parameter sensitivity analysis for the reactor model was investigated for gas holdup, volumetric mass transfer coefficient and gas dispersion coefficient. Figure 14 shows that space time yield and syngas conversion decreased with increasing gas holdup. This analysis showed that a 15% error in gas holdup estimates could result in 2.0-2.5% error in the estimation of space time yields. Figure 15 shows the significance of proper estimation of volumetric mass transfer coefficient in the model. It can be seen that space time yield would be significantly reduced for low gas-liquid mass transfer rates ($k_L a < 0.4 \text{ s}^{-1}$). The effect, however, becomes less significant for higher values of mass transfer coefficients. Figure 15 also shows the estimated values of volumetric mass transfer coefficients using the selected correlations. Figure 16 shows that, as expected, the space time yields and syngas conversions decrease with increasing gas phase dispersion coefficient. The gas dispersion coefficient estimated by the selected correlation in the model is also shown on the Figure. About 50% error in the estimated value of gas dispersion coefficient would result in less than 1% error in predictions for syngas conversion.

Figure 10. Effect of temperature on syngas conversion

Figure 11. Effect of pressure on space time yield and syngas conversion

Figure 12. Effect of space velocity on space time yield and syn gas conversion

Figure 13. Effect of Hydrogen to Carbon Monoxide ratio on Syn Gas conversion

Figure 14. Effect of gas holdup on space time yield and syn gas conversion

Figure 15. Effect of volumetric mass transfer coeff. on space time yield

Figure 16. Effect of gas phase dispersion on space time yield and syn gas conversion

4.0 Recommendations for Future Work:

Hydrodynamics of slurry bubble columns need further investigations especially the effects of high solids concentrations (>30.0 wt%) and high pressure on gas holdup need to be investigated. At increasing solids concentrations in a slurry reactor, there is a possibility of poor gas-liquid contact especially in the distributor region. This problem was pointed out during our analysis of Air Products PDU data for methanol synthesis. Therefore, new studies for hydrodynamics in slurry bubble columns should also investigate the effects of solid concentration and gas velocity on mixing patterns and gas-slurry contact. This brings us to the problem of gas-liquid mass transfer in slurry bubble columns. Poor gas-liquid contact would result in low gas-liquid mass transfer and could lower the reactor productivity. Gas holdup and volumetric mass transfer coefficient are interrelated via the interfacial area. It would be, therefore, prudent to conduct hydrodynamic and mass transfer studies simultaneously.

Future hydrodynamic studies in slurry bubble columns should also include the effects of decreasing gas velocity and presence of internals. Superficial gas velocity in a Fischer-Tropsch reactor reduces to about half its initial value from bottom to the reactor top. Moreover, internal heat exchanger in a Fischer-Tropsch reactor could occupy up to 15% of reactor cross-sectional area. Little work has been done so far to investigate the effect of decreasing gas velocity and presence of internals on hydrodynamic parameters such as gas holdup, gas and slurry phase mixing and axial solids distribution. These studies should be carried out in large diameter

reactors (> 0.2 m) and should also include regime mapping and investigate heterogeneities in slurry bubble columns.

Future studies for hydrodynamics and gas-liquid mass transfer in slurry bubble columns should be conducted using high molecular weight Fischer-Tropsch waxes (C_{30} - C_{50}) or other high molecular weight hydrocarbon solvents with similar properties. As pointed out in this report, gas-liquid mass transfer studies in slurry bubble columns, so far, have been conducted using aqueous solutions at ambient temperatures.

The scope of reactor models developed in this study could be further improved when more information for hydrodynamics and mass transfer become available.

In our reactor model we used Henry's law to determine gas solubilities at reactor conditions. Gas solubilities could be more accurately determined by using a suitable equation of state (i.e Peng Robinson). Reactor model can be modified to include such calculations.

Rate constants in a kinetic expression vary with catalyst activity. Catalyst activity in turn varies widely depending on the procedures used for catalyst preparation and activation. Mechanistic kinetic models are expected to provide better predictions of reaction rates over wide range of operating conditions. Our analysis of kinetic models for methanol synthesis showed that reliable mechanistic model for methanol synthesis still needs to be developed.

The FT synthesis reactor model can be further tested and refined as more data become available from demonstration units.

The reactor models developed in this study can be easily integrated with a process simulator to improve overall process design and optimization.

5.0 Conceptual Commercial size Reactor Design:

Using the computer models developed in this study, commercial size slurry reactors for methanol synthesis and Fischer-Tropsch synthesis can be sized rather quickly. Appendix-B and C contain sample input and output files for Methanol synthesis and Fischer-Tropsch synthesis models respectively. The reactor models can also be used to obtain optimum reactor size for a required rate of production. For this report, we sized a methanol synthesis reactor for a production rate of 1000 metric ton per day and a Fischer-Tropsch synthesis reactor for production rate of 400 metric tons per day of C_3^+ products. For commercial size slurry reactors, Bechtel has recommended an upper limit of 4.8 m for reactor diameter (Fox and Degen, 1990). The operating conditions for commercial size reactors were selected based on literature review and our analysis of process development units data. Table 9 and 10 summarize the dimensions and model outputs for methanol synthesis and Fischer-Tropsch synthesis reactors respectively.

Table 9. Commercial size reactor for Methanol Synthesis

Diameter	4.8 m
Length	12.5 m
Temperature	240°C
Pressure	55.0 atm
Slurry Conc.	34 wt%
Gas velocity	0.155 m/s
H₂/CO ratio	0.64
Catalyst size	0.000025 m
Tube OD	0.038 m
Tube ID	0.034 m
Tube Length	12.0 m
Total Cooling Surface	1134.0 m²
No. of tubes	800
Methanol Production	1000.0 MTD
STY	188.0 kg methanol/hr.m³
Productivity	0.745 kg methanol/hr-kgcat
Space Velocity	1340.0 Nm³/hr-m³
Gas Holdup	0.30

Table 10. Commercial size reactor for Fischer-Tropsch synthesis

Diameter	4.8 m
Length	11.5 m
Temperature	255°C
Pressure	28.0 atm
Slurry Conc.	34 wt%
Gas velocity	0.155 m/s
H ₂ /CO ratio	0.64
Catalyst size	0.000025 m
Tube OD	0.038 m
Tube ID	0.034 m
Tube Length	11.0 m
Total Cooling Surface	3400 m ²
No. of tubes	2600
C ₃ ⁺ Production	411.0 MTD
STY	100.0 kg HC/hr.m ³
Productivity	0.385 kg HC/hr-kgcat
Space Velocity	640.0 Nm ³ /hr-m ³
Gas Holdup	0.272

5.1 Cost Comparison with Fixed Bed Reactor:

Design information for fixed-bed reactors was mainly obtained from literature although some quick checks were made using the heterogeneous reactor model for fixed-bed reactor. Fixed bed reactor design for methanol synthesis is well established. The commonly used fixed-bed reactors for methanol synthesis are ICI quench type reactor and Lurgi shell and tube type reactor. The Lurgi reactor design offers advantages over ICI design. The overall dimensions of a commercial size Lurgi fixed-bed reactor for a production rate of 1480 MTD are provided in the Bechtel report (Fox and Degen, 1990). The conventional fixed bed reactors for methanol synthesis use stoichiometric synthesis gas. In order to make a one-for-one comparison of reactor design, a slurry reactor for methanol synthesis was sized using stoichiometric synthesis gas (see Table 11). Figure 17 and 18 show the dimensions of fixed bed and slurry reactors respectively for methanol synthesis. The length of slurry reactor required for similar production rate is about twice that of the fixed-bed reactor. This difference is mainly due to significantly higher catalyst loading possible in a fixed bed reactor. The conventional fixed bed reactor, however, is not suitable to process syngas from with low hydrogen to carbon monoxide ratio due to higher rate of deactivation and possibility of plugging from coke formation. The operating cost of a fixed bed reactor is expected to be higher due to frequent shut down for catalyst regeneration.

For Fischer-Tropsch synthesis tubular fixed-bed ARGE reactors have been used at Sasol, South Africa. Bechtel used the design basis for ARGE reactors (information given in Encyclopedia of Chemical Technology, 2nd Edition, Vol. 4) to size a larger tubular fixed bed reactor for a

production capacity of 400 MTD. Again for cost comparisons, slurry reactor for Fischer-Tropsch synthesis was sized for similar production rate, using our reactor model (Table 12). The dimensions of slurry and fixed-bed reactors are shown in Figures 19 and 20 respectively.

In order to obtain realistic cost estimates, several well known manufacturers of large size high pressure equipments were contacted. Most of them, however, expressed their inability to fabricate vessels of these sizes. We are presently in touch with one company willing to provide the cost estimates for these reactors.

Table 11. Slurry reactor design for methanol synthesis for cost comparison

Diameter	4.8 m
Length	13.5 m
Temperature	240°C
Pressure	55.0 atm
Slurry Conc.	34 wt%
Gas velocity	0.155 m/s
$(H_2-CO_2)/(CO+CO_2)$	2.05
Catalyst size	0.000025 m
Tube OD	0.038 m
Tube ID	0.031 m
Tube Length	13.0 m
Total Cooling Surface	2100.0 m ²
No. of tubes	1500
Methanol Production	1480.0 MTD
STY	266.0 kg methanol/hr.m ³
Productivity	1.0 kg methanol/hr-kgcat
Space Velocity	1170.0 Nm ³ /hr-m ³
Gas Holdup	0.30

Table 12. Slurry reactor design for FT synthesis for cost comparison

Diameter	4.8 m
Length	11.5 m
Temperature	255°C
Pressure	28.0 atm
Slurry Conc.	34 wt%
Gas velocity	0.155 m/s
H ₂ /CO ratio	0.64
Catalyst size	0.000025 m
Tube OD	0.038 m
Tube ID	0.034 m
Tube Length	11.0 m
Total Cooling Surface	3300 m ²
No. of tubes	2500
C ₃ ⁺ Production	411.0 MTD
STY	100.0 kg HC/hr.m ³
Productivity	0.385 kg HC/hr-kgcat
Space Velocity	640.0 Nm ³ /hr-m ³
Gas Holdup	0.27

Figure 1/

Fixed BED Methanol Reactor
(Lurgi Design)

Design Conditions - Tube Side 875 PSIG 550F; Shell Side 650 PSIG 550F

Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized

Figure 18
Slurry Reactor for Methanol Synthesis

Design Conditions - Tube Side 580 PSIG 550F; Shell Side 875 PSIG 550F

Metallurgy: Shell - SA516 GR70 with SS304 Cladding Tubes SS304

Figure 19
Slurry Reactor Fischer - Tropsch Synthesis

Design Conditions - Tube Side-580 PSIG 550F; Shell Side 460 PSIG 550F
Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized

Figure 20
Fixed Bed Fischer - Tropsch Reactor
(Bechtel Design)

Design Conditions - Tube Side: 460 PSIG 550F; Shell Side: 580 PSIG 550F
Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized

NOMENCLATURE

a_i	water adsorption coefficient FT synthesis, Equations (65), (68)
a_{mix}	Peng-Robinson attractive parameter for mixture [$\text{atm cm}^6 / \text{gmole}^2$]
a_i, a_j	Peng-Robinson attractive parameter for component i and j [$\text{atm cm}^6 / \text{gmole}^2$]
A_i, B_i	coefficient and exponent for equation of Henry's constant
b_i	water adsorption coefficient FT synthesis, Equation (67), atm
b_{mix}	Peng-Robinson repulsive parameter for mixture [$\text{cm}^3 / \text{gmole}$]
b_i	Peng-Robinson repulsive parameter for component i [$\text{cm}^3 / \text{gmole}$]
c_i	coefficient in Equation 27, a function of molecular size of solute and solvent
C_a, C_b	correction factors in the Peng-Robinson EOS
C_{cat}	catalyst concentration, kg/m^3 slurry
$C_{cat,avg}$	average catalyst concentration, kg/m^3 slurry
$C_{cat,b}$	catalyst concentration at reactor bottom, kg/m^3
$C_{G,i}$	gas-phase concentration of component i, kmol/m^3
$C_{L,i}$	liquid-phase concentration of component i, kmol/m^3
C_G	total gas-phase concentration, kmol/m^3
C_P	heat capacity, kJ/kg.K
d_p	particle diameter, m
D_C	column diameter, m
D_G	gas-phase dispersion coefficient, m^2/s
D_i	diffusivity of component i in liquid phase, m^2/s
D_L	liquid-phase dispersion coefficient, m^2/s

$D_{o,w}$	diffusivity of oxygen in water, m^2/s
D_s	solid-phase dispersion coefficient, m^2/s
F	moles in feed in flash calculations
f_i^v	fugacity of component i in vapor phase [atm]
f_i^L	fugacity of component i in liquid phase [atm]
h_o	ratio of hydrostatic head to the head pressure
H_i	Henry's constant for component i , $atm \cdot m^3/kmol$
k_o	rate constant for FT synthesis rate by Equation (65), $kmol/kg-cat.s.atm$
k_1, k_2	reaction rate constants (units depend on kinetic model)
k_c	rate constant for FT synthesis on cobalt catalyst $kmol/kg-cat.s.atm$
$k_{L,i}$	liquid-side mass transfer coefficient for component i , (m/s)
$k_{ps,1}, k_{ps,2}, k_{ps,3}$	pseudo reaction rate constants, equations (43) to (45)
k_{wo}	rate constant for water gas shift reaction by Equation (68), $kmol/kg-cat.s.atm$
K_{c1}, K_{c2}, K_{c3}	chemical equilibrium constants based on concentration
K_p	chemical equilibrium constants based on partial pressure
L	reactor length, m in reactor model or moles of liquid phase in flash calculations
m	average number of hydrogen atoms in the hydrocarbon products
M_i	molecular weight of diffusing component i (kg/kgmol)
M_s	molecular weight of solvent (kg/kgmol)
n	average number of carbon atoms in the hydrocarbon products
N	Avogadro number
P_n	mole fraction of hydrocarbon products with carbon number n

P	reaction Pressure [atm]
P_c	critical pressure [atm]
P_i	partial pressure of component i, atm ($i = \text{CO}, \text{H}_2, \text{CO}_2, \text{H}_2\text{O}$)
P_{ri}	reduced pressure of component i
P_T	pressure at reactor top, atm
R	universal gas constant, $0.082 \text{ m}^3\text{-atm/kmole/K}$
r_{MeOH}	reaction rate for MT synthesis, kmol/kg-cat.s
r_{FT}	reaction rate for FT synthesis, kmol/kg-cat.s
r_k	reaction rate for kth reaction, kmol/kg-cat.s
r_{WGS}	reaction rate for water gas shift, kmol/kg-cat.s
T	reaction temperature [K]
T_c	critical temperature [K]
T_{ri}	reduced temperature of component i
T_w	reactor wall temperature, K
U_G	gas superficial velocity, m/s
U_{G0}	inlet gas superficial velocity, m/s
U_L	liquid superficial velocity, m/s
U_s	settling velocity of catalyst particles in swarm, m/s
U_t	terminal settling velocity of a single particle, m/s
v	dimensionless gas-phase superficial velocity (U_G/U_{G0})
V	specific volume of gas in equation of state or moles of vapor in flash calculations
V_i	solvent molar volume (m^3/kmol)

V_{so}	theoretical close-packed volume for solvent spheres($10^{-6}\text{m}^3/\text{mol}$)
w	dimensionless catalyst concentration ($C_{cat}/C_{cat,avg}$)
x_i	dimensionless liquid-phase concentration of component i ($C_{L,i}H_i/P$) in slurry reactor model or mole fraction of component i in liquid phase in flash calculations
y_i	mole fraction of component i in the vapor (or gas) phase
z	dimensionless axial distance (x/L)
z_i	overall Mole fraction of component i in feed in flash calculations
Z	compressibility factor of the liquid or vapor phase

Dimensionless Numbers

Ar	: Archimedes number [$\rho_L(\rho_{cat}-\rho_L)d_p^3/\mu_L^2$]
Bo	: Bond number ($D_c^2\rho_{SL}g/\sigma_L$)
Fr_G	: Froude number for gas (U_G^2/gD_G)
Pe_G	: gas-phase Peclet number ($U_{Go}L/D_G\epsilon_G$)
Pe_L	: liquid-phase Peclet number ($U_L L/D_L\epsilon_L$)
Pe_p	: particle peclet number ($U_G D_c/D_p$)
Pe_s	: solid-phase Peclet number [$(U_s - U_L/\epsilon_L)(L/D_s)$]
Re_G	: gas Reynolds number ($U_G D_G \rho_L/\mu_L$)
Re_p	: particle Reynolds number ($U_t d_p \rho_L/\mu_L$)
St_G	: gas-phase Stanton number ($K_{L,i} a L/U_{Go}$)
$St_{L,i}$	: liquid-phase Stanton number for component i ($K_{L,i} a L/U_L$)

Greek Letters

δ_{ij}	binary interaction parameter in Peng-Robinson EOS with one-parameter mixing rule
ϕ_i^v	fugacity coefficient of component i in vapor phase [atm]
ϕ_i^L	fugacity coefficient of component i in liquid phase [atm]
ω	acentric factor
θ_{ik}	stoichiometric coefficient of component i in reaction k
ϵ_G	gas holdup
ϵ_L	liquid holdup
ϵ_s	solids holdup
$\epsilon_{s,0}$	volume fraction of solids at reactor bottom
$\epsilon_{s,sus}$	average volume fraction of solids in slurry
ρ	density, kg/m ³
ρ_{SL}	density of slurry, kg/m ³
ρ_w	density of water, kg/m ³
σ_L	surface tension of the hydrocarbon solvent, N/m
σ_w	surface tension of water, N/m
α	probability of chain growth
β	fraction of type I site on FT catalyst
μ	viscosity, Pa.s

μ_w	viscosity of water, Pa.s
ν	kinematic viscosity, m ² /s
γ_i	stoichiometric coefficient for component i in FT synthesis reaction, (i = CO, H ₂ , H ₂ O, HC)
λ	fraction of paraffinic hydrocarbons
ξ_i	molecular diameter of component i (A)
ξ_s	molecular diameter of solvent molecules (A)

Subscripts

L	liquid phase
G	gas phase
i	component i
k	kth reaction
o	inlet condition
S	solid phase

REFERENCES

- Air Products and Chemicals, Final Report, "Liquid Phase Methanol Process Development Unit: Installation, Operation and Support Studies", Under DOE contract No. DE-AC22-81PC30019 Aug. (1987).
- Air Products and Chemicals, "Tracer Studies in the LaPorte LPMEOH PDU", Topical Report to DOE for contract No. DE-AC22-87PC 90005 (1990).
- Akgerman, A., "Diffusivities of Synthesis Gas and Fischer-Tropsch Products in Slurry Media", Final Report DOE contract No. DE-AC22-84PC 70032.
- Akita, K., and Yoshida, F., "Gas Holdup and Volumetric Mass Transfer Coefficient in Bubble Columns", Ind. Eng. Chem. Proc. Des. Dev., Vol. 12, p. 76 (1973).
- Anderson, R.B. In "Catalysis", Emmett, P.H., Ed.; Rheinhold: New York, Vol. IV (1956).
- Ascher, U., Christiansen, J., and Russel, R.D., "Algorithm 569 COLSYS: Collocation Software for Boundary-Value ODEs", ACM Trans. Math. Softw., 7, 223 (1981).
- Bendale, P.G., "Experimental Measurements and Thermodynamic Modeling of Supercritical Fluid-Liquid Phase Equilibria for Binary and Ternary Systems", Ph.D. Dissertation, University of Pittsburgh, PA, April (1991).
- Berty, J.M., Lee, S., Parekh, V., Gandhi, R., and Sivagnanam, K., "Diffusional Kinetics of Low Pressure Methanol Synthesis", Proceedings of PACHEC 83, Vol., 11, p.191 (1983).
- Brown, D.M., "Modeling of Methanol Synthesis in the Liquid Phase", Inst. Chem. Eng. Symp. Ser., Vol. 87, p. 699-708 (1984).
- Bukur, D.B., Patel, S.A., Daly, J.G., "Hydrodynamic Studies with Fischer-Tropsch Waxes in Three-Phase Bubble Columns", Indirect Liquefaction Proceedings, DOE Contractors Review Meeting, p. 329, Nov. 13-15 (1989).
- Bukur, D.B., J.G.Daly and S.A.Patel, "Hydrodynamics of Three-Phase Slurry Fischer-Tropsch Bubble Column Reactors", Final Report to the Department of Energy for contract No. DE-AC22-86PC90012 (1990).
- Chao, K.C. and Lin, H.M., "Synthesis Gas Solubility in Fischer-Tropsch Slurry", Final Report to DOE contract No. DE-AC22-84PC70024 (1987).
- Clark, K.N. "The Effect of High Pressure and Temperature on Phase Distributions in a Bubble Column", Chem. Eng. Sci., Vol. 45, No. 8, p. 2301-2307 (1990).

Cova, D.R., Ind. Chem. Proc. Des. Dev. 5, 21 (1966).

Deckwer, W.D., Burckhart, R., and Zoll, G., "Mixing and Mass Transfer in Tall Bubble Columns", Chem. Eng. Sci., Vol. 29, p. 2177 (1974).

Deckwer, W.D., Louisi, Y., Zaidi, A., Ralek, M., Ind. Eng. Chem. Process Des. Dev., Vol. 19, p. 699 (1980).

Deckwer, W.D., Nguyen-tien, K., Kelkar, B.G., and Shah, Y.T., "Applicability of Axial Dispersion Model to Analyze Mass Transfer Measurements in Bubble Columns", AIChE J., Vol. 29, p. 915 (1983).

Derbyshire, F. and D.Gray, "Coal Liquefaction Ullman's Encyclopedia of Industrial Chemistry, vol. A7, p. 197-243, Fifth Ed. (1985).

Field, R.W. and Davidson, J.F., Trans. Instn. Chem. Engrs., Vol. 58, p. 228 (1980).

Fox, J.M. and Degen, B.D., "Topical Report Slurry Reactor Design Studies", DOE contract No. DE-AC22-89PC 89867 (1990).

Graff, G.H., Winkelman, J.G.M., Stamhuis, E.J. and Beenackers, A.A.C.M., "Kinetics of the Three-Phase Methanol Synthesis", Chem. Eng. Sci., Vol. 43, No. 8, p. 2161-68 (1988).

Hammer, H., H. Schrag, K. Hektor, K. Schonau, W. Kusters, A. Soemarno, U. Sahabi and W. Napp, "New Sub functions on Hydrodynamics, Heat and Mass Transfer for Gas/Liquid and Gas/Liquid/Solid Chemical and Biochemical Reactors", Front. Chem. Reac. Eng., p. 464-74 (1984).

Hikita, H., Asai, S., Tanigawa, K., Segawa, K., Kitao, M., "The Volumetric Liquid Phase Mass Transfer Coefficient in Bubble Columns", Chem. Eng. J., p. 61 (1980).

Hikita, H., S.Asai, K.Tanigawa, K.Segawa and M.Kitao, "The Volumetric Liquid-Phase Mass Transfer Coefficient in Bubble Columns", The Chemical Eng. J., Vol. 22, p. 61-69 (1981).

Hughmark, G.A., "Holdup and Mass Transfer in Bubble Columns", Ind. Engng. Chem. Proc. Des. Dev., Vol. 6, p. 218 (1967).

Huff, G.A. Jr., and C.N. Satterfield., "Evidence for Two Chain Growth Probabilities on Iron Catalysts in the Fischer-Tropsch Synthesis", J. Catal., Vol. 85, p. 370-79 (1984).

Idogawa, K., K. Ikeda, T. Fukuda, S. Morooka, "Behavior of Bubbles of the Air-Water System in a Column Under High Pressure", Int. Chem. Eng., Vol. 26, No. 3, p. 468-74 (1986).

Idogawa, K., K. Ikeda, T. Fukuda, and S. Morooka, "Effect of Gas and Liquid Properties on

the Behavior of Bubbles in a Column Under High Pressure", *Int. Chem. Eng.*, Vol. 27, No. 1, p. 93-99 (1987).

Kara, S., Kelkar, B.G., Shah, Y.T., Carr, N.L., "Hydrodynamics and Axial Mixing in Three-Phase Bubble Column", *Ind. Eng. Chem. Process Des. Dev.*, Vol. 21, p. 584 (1982).

Kato, Y., Nishiwaki, A., Fukuda, T., and Tanaka, S., "The Behavior of Suspended Solid Particles and Liquid in Bubble Column", *J. Chem. Eng. Jpn.*, Vol. 5, p. 112 (1972).

Kato, Y., Nishiwaki, A., Kago, T., Fukuda, T., Tanaka, S., "Gas Holdup and Overall Volumetric Absorption Coefficient in Bubble Columns with Suspended Solid Particles: Absorption Rate of Oxygen by an Aqueous Solution of Sodium Sulfite", *Int. Chem. Eng.*, Vol. 13, p. 562 (1973).

Kawagoe, M., Otake, T., and Robinson, C.W., "Gas Phase Mixing in Bubble Columns", *J. Chem. Eng. Jpn.*, Vol. 22, p.136 (1989).

Koide, K., Takazawa, A., Komura, M., Matsunaga, H., "Gas Holdup and Volumetric Liquid Phase Mass Transfer Coefficient in Solid-Suspended Bubble Columns", *J. Chem. Eng. Jpn.*, Vol. 1, p. 459 (1984).

Kojima, H., B. Okumura, and A. Nakamura, "Effect of Pressure on Gas Holdup in a Bubble Column and a Slurry Bubble Column", *J. Chem. Eng. Japan*, Vol. 24, No. 1, p.115-17 (1991).

Kolbel, H. and M.Ralek, "The Fischer-Tropsch Synthesis in Liquid Phase", *Catal. Rev. Sci. Eng.*, Vol. 21, p. 225-74 (1980).

Kuo, J.C.W., "Two stage Slurry Fischer-Tropsch/ZSM-5 Process of Converting Syngas to High Octane Gasoline, Proc. DOE Contractor's Conference on Indirect Liquefaction, p. 10.1-10.36, Sept. 8-9 (1982).

Kuo, J.C.W., "Slurry Fischer-Tropsch/Mobil Two Stage Process of Converting Syngas to High Octane Gasoline", Final Report DOE Contract No. DE-AC22-80PC30022. Mobil Research and Development Corp., Paulsboro, N.J. (1983).

Lee, S., "Methanol Synthesis Technology", CRC Press Inc. (1990).

Lee, S., "Research to Support Development of the Liquid-Phase Methanol Synthesis Process", EPRI AP-4429 (1986).

Nettelhoff, H., R. Kokuun, S. Ledakowicz, W.D. Deckwer, "Studies on the Kinetics of Fischer-Tropsch Synthesis in Slurry Phase", *Ger. Chem. Eng.*, Vol. 8, p. 177-85 (1985).

Nguyen-Tien, K., Patwari, R.N., Schumpe, A., Deckwer, W.D., "Gas-Liquid Mass Transfer

in Fluidized Particle Beds", *AIChE J.*, Vol. 31, p. 194 (1985).

Nigam, K.D.P. and A. Schumpe, "Gas-Liquid Mass Transfer in a Bubble Column with Suspended Solids", *AIChE J.*, Vol. 33, No. 2, p. 328-30 (1987).

Nishikawa, M., H. Kato and K. Hashimoto, "Heat Transfer in Aerated Tower Filled with Non-Newtonian Liquid", *Ind. Engng. Chem. Process Des. Dev.*, Vol. 16, p. 133-37 (1977).

Ozturk, S.S., Schumpe, A., Deckwer, W.D., "Organic Liquids in a Bubble Column: Holdups and Mass Transfer Coefficients", *AIChE J.*, Vol. 33, p. 1473 (1987).

Reilly, I.G., D.S. Scott, D.T. Bruijn, A. Jain and J. Diskorz, "Correlation for Gas Holdup in Turbulent Coalescing Bubble Columns", *Can. J. Chem. Eng.*, Vol. 64, p. 705-17 (1986).

Sada, E., Kumazawa, H., Lee, C., Iguchi, T., "Gas Holdup and Mass Transfer Characteristics in Three-Phase Bubble Column", *Ind. Eng. Chem. Proc. Des. Dev.*, Vol. 25, p. 472 (1986).

Sarup, B., B.W. Wojciechowski, "Studies of the Fischer-Tropsch Synthesis on a Cobalt Catalyst 1. Evaluation of Product Distribution Parameters from Experimental Data", *Can. J. Chem. Eng.*, Vol. 66, p. 831-42 (1988).

Sarup, B., B.W. Wojciechowski, "Studies of the Fischer-Tropsch Synthesis on a Cobalt catalyst. II. Kinetics of Carbon Monoxide Conversion to Methane and Higher Hydrocarbons", *Can. J. Chem. Eng.*, Vol. 67, p. 62-74 (1989).

Satterfield, C.N., and Huff, G.A. Jr., *J. Catalyst*, Vol. 73, p. 187 (1982).

Sauer, T., and Hempel, D.C., "Fluid Dynamics and Mass Transfer in a Bubble Column with Suspended Particles", *Chem. Eng. Technol.*, Vol. 10, p. 180 (1987).

Saxena, S.C., "Heat Transfer Investigations in a Slurry Bubble Column", *Indirect Liquefaction Proceedings, DOE Contractors Review Meeting*, p. 369, Nov. 13-15 (1989).

Saxena, S.C., N.S. Rao, and A.C. Saxena, "Heat Transfer from a Cylindrical Probe Immersed in a Three-Phase Slurry Bubble Column", *The Chem. Eng. J.*, Vol. 44, p. 141-56 (1990).

Sauer, T., Hempel, D.C., "Fluid Dynamics and Mass Transfer in a Bubble Column with Suspended particles", *Chem. Eng. Technol.*, Vol. 10, p. 180 (1987).

Schumpe, A., A.K. Saxena and L.K. Fang, "Gas-Liquid Mass Transfer in a Slurry Bubble Column", *Chem. Eng. Sci.*, Vol. 42, No. 7, p. 1787-96 (1987).

Smith, D.N., Dowd W., Reuther, J.A., Stiegel G.J. and Shah, Y.T., "Slurry F-T Reactor Hydrodynamics and Scale-up" *Proc. 4th Indirect Liquefaction Contractors Conference*, Pittsburgh, PA, (1985).

Stern, D., A.T. Bell, and H. Heinemann, "A Theoretical Model for the Performance of Bubble Column Reactors Used for Fischer-Tropsch Synthesis", Chem. Eng. Sci., Vol. 40, No. 9, p. 1665-77 (1985).

Tarmy, B.L., Chang, C.A. Coualoglou and P.R. Ponzi, "The Three-Phase Hydrodynamic Characteristics of the EDS Coal Liquefaction Reactors: Their Development and Use in Reactor Scale up", Inst. Chem. Eng. Symp. Ser., Vol. 87, p.303-17 (1984).

Towell, G.D., and Ackerman, G.H., "Axial Mixing of Liquid and Gas in Large Bubble Reactors", Proc. of Fifth European/Second Int. Symp. on Reaction Engng., B-1, Amsterdam. (1972).

Wedel, W.V., Ledakowicz, S., and Deckwer, W.D., "Kinetics of Methanol Synthesis in the Slurry Phase", Chem. Eng. Sci., Vol. 43, No. 8, p. 2169-74 (1988).

Wendt, R., Steiff, A., Weinspach, P.M., "Liquid Phase Dispersion in Bubble Columns", Ger. Chem. Eng., Vol. 7, p. 267 (1984).

Wimmers, O.J., J.M.H. Fortuin, "The use of Adhesion of Catalyst Particles to Gas Bubbles to Achieve Enhancement of Gas Absorption in Slurry Reactors-II. Determination of the Enhancement in a Bubble-Containing Slurry Reactor", Chem. Eng. Sci., Vol. 43, p. 313-19 (1988).

Withers, H.P., K.F. Eliezer and J.W. Mitchell, Ind. Eng. Chem. Res., Vol. 29, p. 1807 (1990).

Yates, I.C., C.N. Satterfield, "Intrinsic Kinetics of the Fischer-Tropsch Synthesis on a Cobalt Catalyst", Energy & Fuels, Vol. 5, p. 168-73 (1991).

Zheng, C., B. Yao, and Y. Feng, "Flow Regime Identification and Gas Holdup of Three-Phase Fluidized Systems", Chem. Eng. Sci., Vol. 43, p. 2195 (1988).

Zimmerman, W., D.B. Bukur, "Reaction Kinetics over Iron Catalysts used for the Fischer-Tropsch Synthesis", Cand. J. of Chem. Eng., Vol. 68, p. 292-301 (1990).

Appendix A

System Requirements and Operating Instructions for Personal Computers

System Requirements:

Computer

- Intel 80386-33 Mhz processor with 256K cache
- 80387-33 Math Coprocessor
- Hard disk with 4MB available space
- DOS 5.0 (or DOS 4.0 with minimum 610 K free memory)
- 1.44 Mbyte 3.5" floppy drive

Computer programs for the slurry reactor model have been developed in FORTRAN 77 using Microsoft Fortran compiler and Linker. The slurry reactor programs must be copied onto hard disk. Please follow these steps:

- 1) Create a new directory on your hard disk (say SLR)
Type: MD SLR
Type: CD SLR
- 2) Insert the program diskette, SLRD, into drive B.
- 3) Type: COPY B:*. * C:\SLR*. *

Executing Slurry Reactor Program for Methanol Synthesis:

- 1) Select input conditions by editing the input data file MTIN.
- 2) To run the methanol synthesis program
Type: MTR
- 3) At the end of the run print file MTR.OUT to look at input and output summary. A sample of MTR.OUT file is enclosed.

Type: PRINT MTR.OUT

Executing Slurry Reactor Program for Fischer-Tropsch Synthesis:

- 1) Select input conditions by editing the input data file FTIN
- 2) To run the Fischer Tropsch Synthesis program

Type: FTR

- 3) At the end of the run print file FTR.OUT to look at input and output summary. A sample of FTR.OUT file is enclosed.

Type: PRINT FTR.OUT

For any inquiry, please contact:

Anand Prakash or Prakash G. Bendale
Viking Systems International
2070 William Pitt Way
Pittsburgh, PA 15238
Phone No. (412) 826-3355
Fax No. (412) 826-3353

Appendix B

Sample INPUT and OUTPUT Files for Methanol Synthesis Model

***** Input Data File for Methanol Synthesis Slurry Reactor *****

*

*

*** Enter 1 for Gas Plug Flow; 2 for Gas Dispersion

*

2

*

*** Reactor Dimensions:

*

4.8 Diameter, m

12.5 Length, m

*

*** Operating Data:

*

513. Reactor Temp., K

414. Feed Gas Temp., K

423. Slurry Inlet Temp., K

55. Reactor Pressure, Atm

55.7 Feed Gas Pressure, Atm

0.155 Supf. Gas Velocity, m/s

0.00 Slurry Flow Rate, m**3/s

*

*** Feed Gas Composition; CO,CO2,H2,CH3OH,H2O

*

0.54 CO Mole Fraction

0.115 CO2 Mole Fraction

0.345 H2 Mole Fraction

0.000 CH3OH Mole Fraction

0.00 H2O Mole Fraction

0.00 N2 Mole Fraction

0.0 CH4 Mole Fraction

*

*** Liquid Phase Conc.; CO,CO2,H2,CH3OH,H2O

*

0.0,0.0,0.0,0.0,0.0,0.,0.

*

*** Catalyst Data:

*

0.34 Weight fraction of catalyst

5730. Catalyst density, kg/m**3

0.000025 Particle diameter, m

0.49 Catalyst heat capacity

*

*** Selection of Kinetic Model for Methanol Synthesis:

*

*** Enter 1 for Graff et al. (1988); 2 for Wedel et al. (1988)

*

2

*

*** Selection of Gas Holdup Correlation:

*

*** Enter 1 for correlation by Hughmark (1967); 2 for correlation by

*** Hikita et al. (1980); 3 for correlation by Bukur et al. (1991);

*** 4 for experimental gas holdup

*

1

*

*** Enter experimental gas holdup; else 0.0

*

0.0

```

*
*** Selection of Correlation for Vol. Mass Transfer Coeff.:
*
*** Enter 1 for correlation by Nguentien et al. (1985); 2 for
*** correlation by Akita and Yoshida (1972).
*
1
*
*** Selection of Correlation for Gas Dispersion:
*
*** Enter 1 for correlation by Towell and Ackerman (1972);
*** 2 for correlation from Air Products PDU data
*
2
*
*** Heat Exchanger Data:
*
*** Enter 1 for internal heat exchanger; 2 for external heat exchanger
*
1
*
*** Heat Exchanger Tubes Data:
*
.031           Inside diameter of tubes, m
.038           Outside diameter of tubes, m
12.           Tube length, m
.0187         Thermal conductivity of tube material
*
*** Temp. of saturated steam generated
*
488.
*
*** Fraction of head volume assumed effective (distributor region)
*
0.2
*

```

*****
 ISOTHERMAL BUBBLE-COLUMN SLURRY REACTOR SIMULATION
 FOR METHANOL SYNTHESIS
 *****

SUMMARY OF THE INPUT DATA

***** REACTOR CHARACTERISTICS *****

DIAMETER = 4.80000 m
 LENGTH = 12.50000 m

***** FEED CHARACTERISTICS *****

REACTOR TEMPERATURE = 513.00000 K
 PRESSURE = 55.00000 ATM
 GAS FLOW RATE = 82.15426 Nm**3/s
 SLURRY FLOW RATE = .00000 m**3/s
 SUPERFICIAL GAS VELOCITY = .15500 m/s
 SUPERFICIAL LIQUID VELOCITY = .00000 m/s
 FLOW RATE RATIO (slurry/gas) = .00000

***** FEED COMPOSITIONS *****

COMPONENT	GAS MOLE FRAC.	SLURRY MOLE FRAC.
*****	*****	*****
CO	.54000E+00	.00000E+00
CO2	.11500E+00	.00000E+00
H2	.34500E+00	.00000E+00
CH3OH	.10000E-04	.00000E+00
H2O	.00000E+00	.00000E+00

***** CATALYST CHARACTERISTICS*****

CATALYST LOADING = 34.00000 % Weight
 CATALYST DENSITY = 5730.00000 kg/m**3
 PARTICLE DIAMETER = .25000E-04 m

OUTPUT SUMMARY

% HYDROGEN CONVERSION = .57286E+02
 % CO CONVERSION = .18242E+02
 % OVERALL CONVERSION = .33463E+02
 RATIO OF H2 CONSM/CO CONSM = .20063E+01
 SPACE VELOCITY = .13369E+04 Nm**3/hr-m**3
 GAS HOURLY SPACE VELOCITY = .52889E+01 Nm**3/hr-kgcat
 SPACE TIME YIELD I = .48248E+04 Nm**3 Syn Gas/hr-m**3
 SPACE TIME YIELD II = .18838E+03 kg Methanol/hr-m**3
 PRODUCTIVITY = .74523E+00 kg/hr-kgcat
 PRODUCTION RATE = .10001E+04 MTD
 HEAT TRANSFER AREA = .11333E+04 m**2
 GAS HOLDUP = .30097E+00

LENGTH		GAS PHASE MOLE FRACTIONS				
ZZZ	XXX(M)	CO	CO2	H2	CH3OH	H2O
*****						
.00	.00	.54580E+00	.13397E+00	.23335E+00	.86687E-01	.19929E-01
.10	1.28	.54638E+00	.13571E+00	.22328E+00	.94422E-01	.21627E-01
.20	2.56	.54697E+00	.13722E+00	.21484E+00	.10075E+00	.22875E-01
.30	3.85	.54757E+00	.13854E+00	.20762E+00	.10605E+00	.23797E-01
.40	5.13	.54815E+00	.13968E+00	.20141E+00	.11052E+00	.24477E-01
.50	6.41	.54869E+00	.14067E+00	.19613E+00	.11427E+00	.24973E-01
.60	7.69	.54916E+00	.14149E+00	.19175E+00	.11736E+00	.25329E-01
.70	8.97	.54955E+00	.14215E+00	.18827E+00	.11978E+00	.25576E-01
.80	10.26	.54985E+00	.14263E+00	.18573E+00	.12155E+00	.25737E-01
.90	11.54	.55003E+00	.14293E+00	.18415E+00	.12264E+00	.25830E-01
1.00	12.82	.55010E+00	.14303E+00	.18361E+00	.12301E+00	.25860E-01

LENGTH		LIQUID PHASE CONCENTRATIONS (kmol/m**3)				
ZZZ	XXX(M)	CO	CO2	H2	CH3OH	H2O
*****						
.00	.00	.21504E+00	.63799E-01	.80023E-01	.74722E-01	.18865E-01
.10	1.28	.21511E+00	.63920E-01	.79280E-01	.75448E-01	.18979E-01
.20	2.56	.21528E+00	.64200E-01	.77684E-01	.77081E-01	.19188E-01
.30	3.85	.21552E+00	.64551E-01	.75813E-01	.79078E-01	.19387E-01
.40	5.13	.21578E+00	.64920E-01	.73958E-01	.81123E-01	.19545E-01
.50	6.41	.21605E+00	.65272E-01	.72265E-01	.83033E-01	.19655E-01
.60	7.69	.21629E+00	.65583E-01	.70813E-01	.84699E-01	.19727E-01
.70	8.97	.21650E+00	.65839E-01	.69645E-01	.86052E-01	.19770E-01
.80	10.26	.21665E+00	.66029E-01	.68791E-01	.87048E-01	.19793E-01
.90	11.54	.21675E+00	.66146E-01	.68270E-01	.87658E-01	.19804E-01
1.00	12.82	.21678E+00	.66186E-01	.68094E-01	.87863E-01	.19807E-01

LENGTH		CATALYST CONCENTRATION	
ZZZ	XXX(M)	DIM-LESS	ACTUAL(% WT)
*****			
.00	.00	1.00595	34.20234
.10	1.28	1.00476	34.16173
.20	2.56	1.00356	34.12118
.30	3.85	1.00237	34.08067
.40	5.13	1.00118	34.04021
.50	6.41	.99999	33.99980
.60	7.69	.99881	33.95944
.70	8.97	.99762	33.91912
.80	10.26	.99644	33.87885
.90	11.54	.99525	33.83863
1.00	12.82	.99407	33.79846

LENGTH		VELOCITY PROFILE	
ZZZ	XXX(M)	UG/UGO	ACTUAL (M/SEC)
*****			
.00	.00	1.000000	.15500E+00
.10	1.28	.981076	.15207E+00
.20	2.56	.961974	.14911E+00
.30	3.85	.942430	.14608E+00

.40	5.13	.922540	.14299E+00
.50	6.41	.902473	.13988E+00
.60	7.69	.882367	.13677E+00
.70	8.97	.862308	.13366E+00
.80	10.26	.842329	.13056E+00
.90	11.54	.822427	.12748E+00
1.00	12.82	.802571	.12440E+00

Appendix C

Sample INPUT and OUTPUT Files for FT Synthesis Model

***** Input Data for Fischer Tropsch Synthesis Slurry Reactor *****

*

*

*** Enter 1 for Gas Plug Flow; 2 for Gas Dispersion

*

2

*

*** Reactor Dimensions:

*

4.8 Diameter, m

11.5 Length, m

*

*** Operating Data:

*

528.0 Reactor Temp., K

420.0 Feed Gas Temp., K

423. Slurry Inlet Temp., K

28. Reactor Pressure, Atm

28.5 Feed Gas Pressure, Atm

0.155 Supf. Gas Velocity, m/s

0.000 Slurry Flow Rate, m**3/s

*

*** Feed Gas Composition; CO,CO2,H2,N2+CH4,H2O

*

0.55 CO Mole Fraction

0.04 CO2 Mole Fraction

0.35 H2 Mole Fraction

0.06 CH4+N2 Mole Fraction

0.0 H2O Mole Fraction

*

*** Liquid Phase Conc.; CO,CO2,H2,N2,H2O

*

0.0,0.0,0.0,0.0,0.0

*

*** Catalyst Data:

*

0.34 Weight fraction of catalyst

3011. Catalyst density, kg/m**3

0.000025 Particle diameter, m

0.49 Catalyst heat capacity

*

*** Product Distribution:

*

0.85,0.85 Alpha1,Alpha2

1. Fraction of type-1 site on catalyst

0.75 Fraction of paraffinic products

*

*** If Experimental Hydrogen to Carbon Ratio For Products is

*** Available Enter 2 ; otherwise enter 1

*

1

6. Avg. carbon chain length of product molecules

2.2 Ratio of the average number of hydrocarbon

atoms to avg. carbon chain length of products

*

*** Selection of Kinetic Model:

*

*** Enter 1 for precipitated iron catalyst; 2 for cobalt catalyst

*

1

```

*
*** Selection of Gas Holdup Correlation:
*
*** Enter 1 for correlation by Hughmark (1967); 2 for correlation by
*** Hikita et al. (1980); 3 for correlation by Bukur et al. (1991);
*** 4 for experimental gas holdup
*
1
*
*** Enter experimental gas holdup; else 0.0
*
0.
*
*** Selection of Correlation for Vol. Mass Transfer Coeff.:
*** Enter 1 for correlation by Nguentien et al. (1985); 2 for
*** correlation by Akita and Yoshida (1972).
*
1
*
*** Selection of Correlation for Gas Dispersion:
*** Enter 1 for correlation by Towell and Ackerman (1972);
*** 2 for correlation from Air Products PDU data
*
2
*
*** Heat Exchanger Data:
*** Enter 1 for internal heat exchanger; 2 for external heat exchanger
*
1
*
*** Heat Exchanger Tubes Data:
*
.031      Inside diameter of tubes, m
.038      Outside diameter of tubes, m
11.       Tube length, m
.0187     Thermal conductivity of tube material
*
*** Temp. of saturated steam generated
*
503.
*
*** Fraction of head volume assumed effective (distributor region)
*
0.2
*

```

*****
 ISOTHERMAL BUBBLE-COLUMN SLURRY REACTOR SIMULATION
 FISCHER TROPSCH SYNTHESIS
 *****

SUMMARY OF THE INPUT DATA

***** REACTOR CHARACTERISTICS *****

DIAMETER = 4.80000 M
 LENGTH = 11.50000 M

***** FEED CHARACTERISTICS *****

INLET TEMPERATURE = 420.00000 K
 REACTOR TEMPERATURE = 528.00000 K
 PRESSURE = 28.00000 ATM
 GAS FLOW RATE = 32.41972 NM**3/SEC
 SLURRY FLOW RATE = .00000 M**3/SEC
 SUPERFICIAL GAS VELOCITY = .15500 M/SEC
 SUPERFICIAL LIQUID VELOCITY = .00000 M/SEC
 FLOW RATE RATIO (slurry/gas) = .00000

***** FEED COMPOSITIONS *****

COMPONENT	GAS MOLE FRAC.	SLURRY MOLE FRAC.
*****	*****	*****
CO	.55000E+00	.00000E+00
CO2	.40000E-01	.00000E+00
H2	.35000E+00	.00000E+00
CH4	.60000E-01	.00000E+00
H2O	.00000E+00	.00000E+00

***** CATALYST CHARACTERISTICS*****

CATALYST LOADING = 34.00000 % WEIGHT
 CATALYST DENSITY = 3011.00000 KG/M**3
 PARTICLE DIAMETER = .25000E-04 M

***** OUTPUT SUMMARY *****

% HYDROGEN CONVERSION = .71303E+02
 % CO CONVERSION = .74615E+02
 % OVERALL CONVERSION = .73327E+02
 RATIO OF H2 CONSM/CO CONSM = .60812E+00
 SPACE VELOCITY = .64336E+03 Nm**3/hr-m**3
 GAS HOURLY SPACE VELOCITY = .24697E+01 Nm**3/hr-kg
 SPACE TIME YIELD I = .42458E+03 Nm**3 Syn Gas conv./hr-m**3
 SPACE TIME YIELD II = .10044E+03 kg HC/hr-m**3
 PRODUCTIVITY = .38557E+00 kg HC/hr-kg cat
 PROD. RATE TOTAL HC = .43729E+03 MTD
 PROD. RATE C3+ HC = .41198E+03 MTD
 HEAT TRANSFER AREA = .34190E+04 m**2
 GAS HOLDUP = .27259E+00

PREDICTION OF MULTICOMPONENT PHASE EQUILIBRIA USING
 PENG-ROBINSON EQUATION OF STATE FOR BOTH VAPOR AND LIQUID PHASES...

VAPOR-LIQUID EQUILIBRIA FOR FISCHER-TROPSCH SYNTHESIS

REACTOR TEMPERATURE = 528.00 K
 REACTOR PRESSURE = 28.000 ATMS.

TOTAL FLOW RATE = .78520E+00 KMOLS/SEC, .25495E+02 KG/SEC.
 GAS FLOW RATE = .78044E+00 KMOLS/SEC, .23303E+02 KG/SEC
 LIQUID FLOW RATE = .47620E-02 KMOLS/SEC, .21921E+01 KG/SEC

FEED COMPOSITION IS AS FOLLOWS...

MOLE FRACTION	WEIGHT FRACTION
Z(1)= .378714	AWZF(1)= .513310
Z(2)= .010803	AWZF(2)= .005994
Z(3)= .184977	AWZF(3)= .011485
Z(4)= .257128	AWZF(4)= .221809
Z(5)= .119183	AWZF(5)= .058887
Z(6)= .001845	AWZF(6)= .001594
Z(7)= .005535	AWZF(7)= .005125
Z(8)= .001568	AWZF(8)= .002032
Z(9)= .004704	AWZF(9)= .006389
Z(10)= .001333	AWZF(10)= .002303
Z(11)= .003999	AWZF(11)= .007158
Z(12)= .020527	AWZF(12)= .054480
Z(13)= .004630	AWZF(13)= .026287
Z(14)= .005056	AWZF(14)= .083147

LIQUID PHASE MOLE FRACTIONS.....

MOLE FRACTION	WEIGHT FRACTION
XC(1)= .042100	AWXC(1)= .004025
XC(2)= .001352	AWXC(2)= .000053
XC(3)= .011412	AWXC(3)= .000050
XC(4)= .017013	AWXC(4)= .001035
XC(5)= .011086	AWXC(5)= .000386
XC(6)= .000279	AWXC(6)= .000017
XC(7)= .000963	AWXC(7)= .000063
XC(8)= .000397	AWXC(8)= .000036
XC(9)= .001270	AWXC(9)= .000122
XC(10)= .000540	AWXC(10)= .000066
XC(11)= .001734	AWXC(11)= .000219
XC(12)= .020345	AWXC(12)= .003809
XC(13)= .058008	AWXC(13)= .023233
XC(14)= .833501	AWXC(14)= .966886

VAPOR PHASE MOLE FRACTIONS.....

MOLE FRACTION	WEIGHT FRACTION
YC(1)= .380768	AWYC(1)= .561217
YC(2)= .010861	AWYC(2)= .006553
YC(3)= .186036	AWYC(3)= .012560
YC(4)= .258593	AWYC(4)= .242577
YC(5)= .119842	AWYC(5)= .064390
YC(6)= .001854	AWYC(6)= .001742
YC(7)= .005562	AWYC(7)= .005602
YC(8)= .001575	AWYC(8)= .002220
YC(9)= .004725	AWYC(9)= .006978

YC(10)= .001338	AWYC(10)= .002514
YC(11)= .004013	AWYC(11)= .007811
YC(12)= .020528	AWYC(12)= .059246
YC(13)= .004304	AWYC(13)= .026574
YC(14)= .000001	AWYC(14)= .000016

LENGTH		GAS PHASE MOLE FRACTIONS				
ZZZ	XXX(M)	CO	CO2	H2	CH4	H2O
*****						
.00	.00	.39247E+00	.24559E+00	.26124E+00	.91961E-01	.87393E-
.10	1.20	.36946E+00	.27566E+00	.24839E+00	.96742E-01	.97513E-
.20	2.41	.34961E+00	.30159E+00	.23747E+00	.10102E+00	.10314E-
.30	3.61	.33224E+00	.32421E+00	.22802E+00	.10486E+00	.10666E-
.40	4.81	.31707E+00	.34392E+00	.21983E+00	.10827E+00	.10910E-
.50	6.01	.30400E+00	.36086E+00	.21281E+00	.11125E+00	.11090E-
.60	7.22	.29305E+00	.37501E+00	.20696E+00	.11376E+00	.11225E-
.70	8.42	.28430E+00	.38629E+00	.20231E+00	.11578E+00	.11325E-
.80	9.62	.27787E+00	.39457E+00	.19889E+00	.11727E+00	.11395E-
.90	10.83	.27391E+00	.39968E+00	.19679E+00	.11819E+00	.11437E-
1.00	12.03	.27255E+00	.40142E+00	.19607E+00	.11851E+00	.11451E-

LENGTH		LIQUID PHASE CONCENTRATIONS (kmol/m**3)				
ZZZ	XXX(M)	CO	CO2	H2	CH4	H2O
*****						
.00	.00	.36351E-01	.92822E-01	.20247E-01	.22995E-01	.15428E-
.10	1.20	.35913E-01	.94023E-01	.20036E-01	.23169E-01	.15569E-
.20	2.41	.34927E-01	.96798E-01	.19590E-01	.23573E-01	.15832E-
.30	3.61	.33726E-01	.10028E+00	.19072E-01	.24082E-01	.16105E-
.40	4.81	.32498E-01	.10392E+00	.18557E-01	.24618E-01	.16351E-
.50	6.01	.31351E-01	.10739E+00	.18084E-01	.25131E-01	.16560E-
.60	7.22	.30351E-01	.11045E+00	.17674E-01	.25588E-01	.16730E-
.70	8.42	.29538E-01	.11297E+00	.17343E-01	.25964E-01	.16862E-
.80	9.62	.28939E-01	.11484E+00	.17098E-01	.26245E-01	.16956E-
.90	10.83	.28573E-01	.11599E+00	.16948E-01	.26418E-01	.17013E-
1.00	12.03	.28449E-01	.11637E+00	.16898E-01	.26476E-01	.17032E-

LENGTH		CATALYST CONCENTRATION	
ZZZ	XXX(M)	DIM-LESS	ACTUAL(% WT)
*****			
.00	.00	1.00189	34.06423
.10	1.20	1.00151	34.05137
.20	2.41	1.00113	34.03852
.30	3.61	1.00075	34.02567
.40	4.81	1.00038	34.01282
.50	6.01	1.00000	33.99998
.60	7.22	.99962	33.98714
.70	8.42	.99924	33.97431
.80	9.62	.99887	33.96149
.90	10.83	.99849	33.94867
1.00	12.03	.99811	33.93585

LENGTH		VELOCITY PROFILE	
ZZZ	XXX(M)	UG/UGO	ACTUAL (M/SEC)

*****

.00	.00	1.000000	.15500E+00
.10	1.20	.970320	.15040E+00
.20	2.41	.929025	.14400E+00
.30	3.61	.881493	.13663E+00
.40	4.81	.830719	.12876E+00
.50	6.01	.778370	.12065E+00
.60	7.22	.725348	.11243E+00
.70	8.42	.672102	.10418E+00
.80	9.62	.618818	.95917E-01
.90	10.83	.565541	.87659E-01
1.00	12.03	.512260	.79400E-01

END

**DATE
FILMED**

6 / 5 / 92