COLLIDER PHYSICS

DOE/ER/40621--2

Progress Report 1992

DE93 005116

TITLE: Collider Physics: SDC/SSC Liquified Fiber Calorimetry

Grant No.: DE-FG-05-91ER40621

Principal Investigators: James T. White
F. Russ Huson

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DEC 31 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

1 Introduction	1
2 Personnel.....	2
3 D-Zero Experiment.....	3
3.1 Physics.....	2
3.1.1 Wino-Zino Physics.....	4
3.1.2 Squark Physics.....	7
3.2 D-Zero Data Acquisition System Efforts	9
3.3 Level-1 and Level-2 Trigger.....	12
4. SDC Experiment/ Forward Calorimetry	16
4.1 Attenuation Length Measurement	17
4.1.1 Measurement Technique	17
4.1.1 Results	18

4.2 Radiation Damage Studies.....	20
4.2.1 Irradiation of Samples.....	21
4.2.2 Results	21
4.3 GEANT Simulations	23
4.4 Summary	23
5. Summary	25

Picture removed.

1. Introduction

This past year has been extremely exciting and rewarding for our group. We have participated both in the D-Zero experiment at Fermilab (our main effort) and the SDC experiment at the SSC. In both endeavors, we have enjoyed great success and have excellent progress to report.

With the turn-on of the Tevatron at Fermilab in May, the D-Zero experiment began its first data run. The detectors were brought up more smoothly than even the most optimistic people expected! By the end of November, the experiment expects to have over 3 pb^{-1} of high quality physics data. The collaboration presented more than ten preliminary results at the DPF meeting in November, thus demonstrating the physics of the experiment. Our group initiated and is leading the analysis effort of some of the most exciting physics being pursued by the collaboration. This work, as well as our other activities on D-Zero are discussed in section 3.

Our SDC work was also very successful. Our group was the original proposer of one of the primary technologies being considered for use in the forward calorimetry for both the SDC and GEM experiments (also LHC). This technology consists of using liquid scintillator-filled tubes as scintillating fibers for a "spaghetti" style calorimeter. The main idea was to take advantage of the speed and circulability of the liquid scintillator to make a fast, radiation resistant device. The key issues were to demonstrate that the liquid fibers were indeed sufficiently rad-hard and equally importantly, to demonstrate that fibers with sufficiently long attenuation length could be found to satisfy the resolution requirements. Our research revealed that both these constraints could be satisfied! This work is described in section 4.

2. Personnel

The members of our group include Professor Russ Huson, Assistant Professor James White, Post Doctorial Research Associates Jay Wightman, Amber Boehnlein and Mei Gui, and graduate students Kedarnath Kotha and Terry Brown. Graduate student Greg Dudgeon completed the work for a master's degree in August.

We have tried to maximize our presence at Fermilab to participate as strongly as possible in the commissioning of the detector. Boehnlein and Wightman are based at Fermilab, and White spent the summer at Fermilab and traveled frequently during the academic months. Dudgeon was stationed at Fermilab through August. The other students are stationed at the Texas A&M University campus. Mei Gui is currently funded through the Texas National Research Commission for SSC work and is also based in Texas.

3. D-Zero Experiment

The collider run began in May 1992, and the experiment now has recorded approximately 3 pb^{-1} of data. The D-Zero collaboration has been extremely busy both collecting and certifying the data and tuning analysis software. In the following sections we describe the main activities of our group this past year. In the first section, our current physics analysis efforts are discussed, in the second section our primary hardware responsibility is summarized and in the third, our trigger related work is discussed. Jay Wightman has been the key person responsible for the data acquisition system work (sect. 3.2), and Amber Boehnlein is carrying the major responsibility for our trigger related activities (sect. 3.3).

3.1 Physics

One of the most exciting possible discoveries in particle physics is to observe a new layer of matter. Although this occurs rather rarely, we are fortunate enough to be at a place and time where this possibility is not so far fetched. A new type of symmetry was discovered about twenty-one years ago which was found to be a spacetime symmetry on a footing similar to the foundation Poincare group which includes translations, rotations and Lorentz boosts.

This new symmetry, although a spacetime symmetry, transforms fermions into bosons and vice versa. When applied to a class of grand unification theories (GUT), this symmetry was found to solve a large number of nagging theoretical problems involving infinities and even the breaking of $SU(2) \times U(1)$. Equally astounding, starting with recent precision measurements from LEP, the simplest, minimal models incorporating this symmetry were found to cause the running coupling constants of electromagnetism, weak interactions and strong interactions to meet at a point at a high enough energy to be consistent with proton decay and all other experimental limits. This is in contrast to the standard $SU(5)$

GUT theory, which failed miserably unless new particles were cooked up with no deeper theoretical basis.

The symmetry is called SuperSYmmetry (SUSY) and it predicts that for each particle degree of freedom, there is a "supersymmetric partner" - i.e. it almost doubles the expected number of observable particles. Further, all indications are that this new layer, if it exists, must lie somewhere between our current reach and about one TeV. Until recently, the general theoretical bias was the belief that SUSY would likely have to wait for the SSC. However, recent theoretical studies (Arnowitt and Nath, Baer and Tata, Nanopoulos, Lopez et al.) (triggered largely by our group), indicate that a significant portion of the allowed phase space for SUSY may be excludable or observable by the Tevatron! Or, at least, the Tevatron will be able to scoop a large chunk of phase space once thought to be reserved by LEP200.

3.1.1 Wino-Zino Physics

Based on a 1987 paper by Arnowitt and Nath (Arnowitt et. al., Mod. Phys. Let., A2(1987)p331), our group began studies concerning the detectability of the SUSY partners of the W and Z bosons. These objects, known as the zino ($\widetilde{Z}$) and the wino ($\widetilde{W}$) are produced through the Drell-Yan mechanism via a virtual W boson. The possible decay combinations include

- (a) $\widetilde{W}^{\pm} \rightarrow q\bar{q}\widetilde{Z}^{\pm} ; \widetilde{Z}^{\pm} \rightarrow q\bar{q}\widetilde{Z}^{\pm}.$
- (b) $\widetilde{W}^{\pm} \rightarrow l\bar{\nu}\widetilde{Z}^{\pm} ; \widetilde{Z}^{\pm} \rightarrow q\bar{q}\widetilde{Z}^{\pm} .$
- (c) $\widetilde{W}^{\pm} \rightarrow q\bar{q}\widetilde{Z}^{\pm} ; \widetilde{Z}^{\pm} \rightarrow l\bar{l}\widetilde{Z}^{\pm},$
- (d) $\widetilde{W}^{\pm} \rightarrow l\bar{\nu}\widetilde{Z}^{\pm} ; \widetilde{Z}^{\pm} \rightarrow l\bar{l}\widetilde{Z}^{\pm}$

The event signatures for the four categories are (a) four jets plus missing Pt, (b) two

jets, one lepton and missing Pt, (c) two jets, two leptons and missing Pt, and (d) three leptons plus missing Pt. Just as the dilepton signature for the top quark is considered "golden", here the trilepton channel plays this role. Although studies are not yet complete, backgrounds for the trilepton channel are thought to be extremely rare. The price one pays is, however, a relatively small branching fraction for three leptons as compared to the other channels where backgrounds are known to exist.

At our request, the theoretical group of Baer and Tata added this reaction to a Monte Carlo program (ISASUSY) designed to produce realistic SUSY signals for use by experimenters. To the surprise of many, the rates for the trilepton signal in combination with other modes should be high enough to either discover SUSY or exclude a significant amount of allowed phase space. As stated, this has triggered a burst of theoretical activity by several groups and an equally large surge of interest in SUSY in both the D-Zero and CDF experiments.

In the minimal SUSY models, the masses of the particles are highly correlated. Figure 1 shows the mass of the zino as a function of the mass of the wino for several values of the free SUSY parameters. (Although there are a large number of parameters (5 to 7 depending on how one counts), some can be tightly confined from limits on proton decay lifetime, dark matter density and current experimental limits.) The plot shows that to a good approximation, the mass of the wino is equal to the mass of the zino. Figure 2 shows the mass of the lightest SUSY particle (LSP or $\tilde{Z}_1$) as a function of the wino. This shows that the LSP is roughly half as massive as the wino and zino. The wino mass is also related to the gluino ($\tilde{g}$) mass as shown in Fig. 3. Here the correlation is not as tight, but one can extract the rule that if a parameter called μ is positive, $M_{wino} \approx \frac{1}{4} M_{gluino}$, and if negative, $M_{wino} \approx \frac{1}{3} M_{gluino}$. Therefore, even though gluino production is via the strong interaction (order α_3^2) and wino-zino production is order α_2^2 , the $mass^{-2}$ factors in the cross sections cancel the effect of the smaller coupling constant. That is, $(\alpha_3/\alpha_2)^2 \rightarrow (.118/.033)^2 \approx 10$, but $(mass_{wino}/mass_{gluino})^2 \approx (1/3)^2 \rightarrow (1/4)^2 \approx 10^{-1}$, so the cross sections for a given point in SUSY space are about equal. The wino-zino production cross section is shown in

Fig. 4 for a spread of SUSY parameters. In fact, limits on wino-zino production can place much higher indirect limits on gluino masses than the direct search at the Tevatron!

Up to now, all Tevatron effort regarding SUSY has been on the gluino and squark search. As mentioned, our group proposed and lead the first search for wino-zino pairs in the trilepton channel using a limited set (3 electrons only) of the first pb^{-1} of data from D-Zero. No events were observed with this small amount of data, and no new limits were obtainable, but our analysis showed that the backgrounds were indeed small, and now this analysis is one of the main efforts of the D-Zero new phenomena group.

Figures 5-6 show what a tri-electron event will look like in D-Zero (Monte Carlo) when the wino and zino have masses of about 50 GeV. Figure 5 is a side view of the calorimeter and central tracking chambers. The energy in the end caps is entirely from the beam jets. The three electrons are seen in the central barrel and appear as globbs in the electromagnetic part of the calorimeter. (Unfortunately- the tracking was not enabled for this Monte Carlo event, so the tracks do not appear.) Figure 6 shows an end view of the calorimeter and the electrons are seen as narrow spikes in the projective towers. One can read off from this figure that the electrons have Pt's of about 14, 8, and 5 GeV, and are balanced by a missing Pt (thin strip pointing down) of 14 GeV. Note the maximum Pt cell is 14 GeV and extends to the outer ring in the figure. The other cells are estimable by comparing their lengths to the maximum. The signature, then, is three leptons in combination with missing transverse momentum and almost no hadronic activity.

Possible backgrounds include B-quark events (BBbar, BBcc, BBBB, etc.) with semileptonic decays. We are studying this background very carefully, but preliminary indications are that there is always hadronic activity near the leptons if one requires the leptons to have at least 5 GeV Pt each. The most serious candidate event in D-Zero's first pb^{-1} is shown in Figs. 7-8. Again the side view (Fig. 7) shows three apparent electromagnetic clusters. However, they are not quite as narrow as the Monte Carlo event. Also, two of the clusters had more than one track within the standard "road". The end view (Fig. 8) shows clearly, that the clusters are not as narrow as the electrons in the MC

event. Also, D-Zero uses a likelihood method to compare the cluster shapes with electrons from test beam runs, and at least two of the clusters fail the chi-squared cuts. Hence, even though the event looks like a candidate by eye, it is easily eliminated by more detailed analysis. We think this event falls into a class of three jet events where most of the energy is electromagnetic (π^0 's). These can easily be eliminated also by a missing Pt cut.

In summary, the wino-zino analysis is extremely exciting and is well underway. We are also looking at the decay channels other than the trilepton signature to see if the topologies allow cuts to eliminate backgrounds.

3.1.2 Squark Physics

As stated, the standard Tevatron analyses for super symmetry have been limited to searching for squarks and gluinos using the missing Pt plus jets signal. Although it is well known that leptons can appear in these events, this corner of physics has been largely ignored up to now because of the large backgrounds from sources such as W plus jets and Z to tau,tau to leptons plus jets. However, a recent "interesting" event reported by CDF, and a similar event from D-Zero (not yet reported), have inspired us to look at the possible SUSY scenerios for such events.

The first thought, of course, is that these interesting events may come from the long sought top quark. However, for both events there are real problems with this interpretation. A major flaw in both events (both e, μ , jet, jet events) is that the leading particle is a jet with Pt near 100 GeV. (The leading lepton is (unofficially), close to 60 GeV Pt in both cases.) The standard top should have such a topology only rarely as can be seen in Figs 9-10. Figure 9 shows a scatter plot of the Pt of the two leptons and a scatter plot of the Pt of the two jets for the case where the top quark has a mass of 100 GeV. (It also shows jet1(2) vs lepton1(2) and jet1(2) vs lepton2(1).) Figure 10, shows histograms of the lepton, jet and missing Pt distributions. Clearly, the likelihood of 100 GeV jets is extremely low for a 100 GeV top. Figures 11 and 12 are the same distributions for a 140

GeV top. Even here, the probability of seeing a 100 GeV jet is about 2%. Since the total number of $e\mu$ events for this mass is about 0.1 for the amount of data accumulated, this makes a standard top hard to accommodate. The topology is also unfavorable for expected backgrounds.

As a possible SUSY decay involving both jets and leptons, the most natural object to consider is the squark. One of the squark decay modes is to emit a standard quark (jet) and a wino, with the wino decaying leptonically. This is identical to the top to b quark + W decay, except that the wino can be considerably lighter than the W (as low as 45 GeV vs 81 GeV). If the wino is light, then the quark jet can carry away a much larger share of the kinetic energy, so the jet can have a relatively higher Pt. An example of this is shown in Figs. 13 and 14, which show the jet and lepton Pt's for a 140 GeV squark, decaying into a jet plus 50 GeV wino. For this decay, the jet is now quite likely to be over 100 GeV Pt, but since the wino decay involves a $\widetilde{Z}_1$, plus the lepton and neutrino, the lepton has a much lower Pt spectrum than that of the standard top. Considering this alone, the squark decay seems as unfavorable as the standard top.

However after looking at the various allowed SUSY parameters, we have found a class of parameters where the topology is closer to what we need. Figure 15 and 16 show the distributions for the case of a 180 GeV squark. The key to get a large enough cross section in combination with a high enough Pt spectrum is to have a reasonably light gluino, which yields a proportionally light wino, and further to have a light enough slepton to force a large branching fraction for wino to leptons. If this turns out to be the case, the Tevatron may be able to see the wino, zino and perhaps even slepton directly!

This line of analysis will also be hotly pursued in the coming months in both D-Zero and CDF. Again, a surprisingly large volume of SUSY parameter space can be excluded (or discovered!) by this method. A key is that squarks can be produced with a much higher cross section than the top quark in some parameter space because new production mechanisms come into play.

3.2 D-Zero Data Acquisition System Efforts

The first project we undertook upon joining the D-Zero collaboration was to develop a package of routines for testing the data acquisition (DAQ) system hardware. At the start of this project, the DAQ hardware was almost non-existent. Since then, we have seen the DAQ system, both hardware and software, undergo major installation and upgrade to its present, hopefully stable, configuration. Throughout these changing times, our program has been maintaining pace with the installation and upgrades. We currently have a stand-alone program that is menu-driven and very user-friendly. It incorporates 3 major test packages which we call `DOWNLOAD_TEST`, `IN_SITU_TEST`, and `VBD_TEST`.

In `DOWNLOAD_TEST` we download one of five different test patterns into the output buffer of the Flash ADC's (FADC's) of the Central Tracker or the ADC's of the Calorimeter. The five test patterns which are interactively specified by the user are: `CONSTANT`, a single bit pattern is used; `ALTERNATING`, in which the user specifies 2 bit patterns along with the number of iterations of each before the total pattern is repeated; `INCREMENTING`, where an initial pattern is specified for some number of iterations and an increment to be applied after each set of iterations; `SHIFTING`, which is similar to `INCREMENTING` only now a cyclic bit shift is applied; and `MONTE CARLO`, the user specifies a file of Monte Carlo events and one is downloaded. In all cases, the data are held in the front-end buffers and constantly triggered for readout. We have at our disposal the complete complement of D-Zero trigger sources of which we usually use one of the pulsers, although we also have available the cosmic ray veto scintillator to provide a random trigger. We have been unable to include the Muon system in this test due to the radically different readout vis-a-vis the other two major detector systems; the Muon DAQ group has been unable to structure a test configuration for their electronics suitable for this test. In addition to the download part of this test, we also emulate the D-Zero official data taking interface, `TAKER`. We communicate the configuration, Level-1 trigger, and Level-2 filter information to `COOR`, the overall Coordinating process, and can start and stop data runs, change pre-scales for the run, and `PAUSE/CONTINUE` the run exactly

like `TAKER`. Since we emulate `TAKER`, we read out the data over the normal DAQ path, thus giving us a means for testing and exercising the DAQ path.

In `IN_SITU_TEST` we download the same variety of test patterns as `DOWNLOAD_TEST` with the exception of the `MONTE CARLO` event. We read out the download over the Controls DAQ (CDAQ) path rather than the normal DAQ path. The CDAQ path is used for downloading in all cases. There are two major differences between `IN_SITU_TEST` and `DOWNLOAD_TEST` besides the path over which the data are read out for examination on the Host Computer. First, we can download to and read out from any register on any of the electronics boards accessible from the VME backplane of the crate. This is in comparison with `DOWNLOAD_TEST` in which we can only read out from the output buffers of the FADC/ADC without having any access to any other registers during the readout. Second, since we do not use the DAQ path for readout, we do not require the Level-2 nodes to be operational nor the DAQ processes to be running. Our only requirement is that the CDAQ path be operational which includes the Host computer being operational.

The final test is `VBD_TEST` in which we download our patterns directly to the buffer of the VBD and trigger readout from there over the DAQ path. The advantage of this test over `DOWNLOAD_TEST` is that we bypass downloading the FADC/ADC buffers. This test was originally conceived to provide the most straightforward means of measuring the bit-dropping rate of the data cables since we download to the buffer at the beginning of the data cable and look at what we have at the Level-2 nodes, the terminus of the data cable. Unfortunately, software upgrades in the Supervisor/Sequencer which exercise hardware control over the DAQ system have rendered this test inoperative. We anxiously await the restoration of the software capability in the Supervisor/Sequencer code to reinstate this test.

While tuning up our `DOWNLOAD_TEST` code we were able to find and isolate several problems with some of the boards in the front-end crates of the DAQ system. Once we certified that the test procedure was working, our first usage was to measure the DAQ

system deadtime for an early configuration of the hardware. This proved the efficacy of our routines and was used to provide a benchmark for the simulation studies of the DAQ system that were being started. The acid test of the IN_SITU_TEST procedure was to trouble shoot a problem in the CDAQ path. We noticed that when a sufficiently long string of 32-bit words with all bits asserted was passed along the CDAQ path there was a failure mode in which multiple bits were dropped. This same behavior was confirmed by some of the detector people who had attributed the problem to the Vertical Interconnect which interfaces the VME backplane to the Token Ring. We called in the Fermilab group that was responsible for building and maintaining the Vertical Interconnects and were able to isolate the source of the problem, not the Vertical Interconnect but the gateway between the Token Ring and the Ethernet of the Host Computer cluster. What happened was that the Token Ring interface board in the gateway microVAX had a problem with power usage on the board. Under normal circumstances, the board functioned properly, but stressing the board with our test pattern with all bits asserted caused just enough additional power drain to cause the board to fail. The latest request for our test procedure is to try to reproduce parity errors seen on one of the data cables. These parity errors occur in about 1% of the events seen on this cable (about 2 orders of magnitude larger than any of the other 7 cables). This has just begun and has not yielded any positive results, yet. We have been unable to force parity errors to occur with the few bit patterns that we have tried.

As mentioned above, we have used the early DAQ system deadtime measurements as a benchmark for our modeling efforts. The original modeling was done in 1986 to answer questions regarding the number of front-end buffers as well as the target VME backplane bandwidth. With our deadtime measurements we have resumed the modeling to answer questions regarding the Level-2 filter code processing times and the effect of including the Level-1.5 trigger in the DAQ system. We have developed a Monte Carlo simulation model using a modeling package from IBM along with an analytical solution of the model to provide a touchstone. The success of our modeling efforts led to contributions to the 1991 Nuclear Science Symposium and Medical Imaging Conference in Santa Fe, NM [1,2], the Workshop on DAQ/Trigger System Simulations for High Energy Physics in Dallas, TX

[3,4], and as an invited lecturer at the 5th International School–Seminar on Computing and Automation in Nuclear Physics and Astrophysics in Sochi, Russia [5]. A copy of the paper that accompanied the lecture in Sochi is included in Appendix A. With the resounding success of our modeling of the present DAQ system, we are extending our model to the D-Zero upgrade, specifically the silicon tracker, to answer questions regarding readout times.

References – DAQWork

1. “Computer Modeling of the D-Zero Data Acquisition System,” R. Angstadt, M. Johnson, I. Manning, and J. Wightman, *1991 Nuclear Science Symposium and Medical Imaging Conference*, Santa Fe, NM, November 2–9, 1992.
2. “Modeling of the D-Zero Data Acquisition System,” R. Angstadt, M. Johnson, I.L. Manning, and J.A. Wightman, *IEEE Transactions on Nuclear Science* **39**, 904 (1992).
3. “The D-Zero Data Acquisition System: Model and Measurements,” J.A. Wightman, R. Angstadt, M.E. Johnson, and I.L. Manning, *Workshop on DAQ/Trigger System Simulations for High Energy Physics*, Dallas, TX, April 23–25, 1992.
4. “Simulating the D-Zero Intermediate Hardware Trigger,” M.E. Johnson, R. Angstadt, I.L. Manning, and J.A. Wightman, *Workshop on DAQ/Trigger System Simulations for High Energy Physics*, Dallas, TX, April 23–25, 1992.
5. “The D-Zero Data Acquisition System,” J.A. Wightman, for the D-Zero Collaboration, *5th International School–Seminar on Computing and Automation in Nuclear Physics and Astrophysics*, Sochi, Russia, October 16–23, 1992.

3.3 Level-1 and Level-2 Trigger

The luminosity was expected to be in the range from 5×10^{30} to $1 \times 10^{31} \text{ cm}^{-2} \text{ sec}^{-1}$ once the Tevatron became fully tuned. It is currently approaching the 5×10^{30} mark which

yields approximately 250 kHz of inelastic interactions. Out of these, the trigger must be able to select about 2 Hz of events to be recorded. Because such a large rejection ratio is required, the process of defining triggers which keep the events of interest and minimize background must be done with great care. Our group has played a major role in this process and hold major responsibilities in the monitoring and further development of the system. We have worked on all aspects of both the Level-1 and Level-2 trigger including determination of rates, thresholds, efficiencies, configurations, certification and realtime monitoring. This work is described below.

The D-Zero trigger takes place in three and one-half stages. The zeroth stage, Level-0, is a coincidence between scintillator counters on the inner surface of the two end caps. From timing, it serves to provide a measure of the position of the interaction along the beam direction for the next stage. The next stage, Level-1, makes use of calorimeter and muon chamber information. The calorimeter portion includes fast measures of total scalar Et, total electromagnetic Et, missing Pt, and counts of both electromagnetic and jet (em + hadronic) energy towers above specified thresholds. The muon portion includes counts of possible tracks from a line finding algorithm. This stage is followed by Level-1.5, which includes a measure of the Pt of the muon line candidates and information from the TRD chamber. There are currently thirty-two possible Level-1 triggers, of which approximately thirty are used. The final stage is Level-2, which takes place in an array of micro-VAXes. This level is extremely flexible and can vary in complexity from adding corrections to Level-1 signals to finding and counting jets with nearly offline precision. Current Level-2 decisions are based on number and Pt of jets, electrons, muons, photons, missing Pt and combinations of these quantities. This is done in Fortran programs that reside on the nodes and do a specific calculation as quickly as possible. There are currently about thirty nodes, and the number will increase to fifty in the near future.

One of our responsibilities has been to maintain a set of up-to-date rate curves for the various trigger quantities as determined from Monte Carlo simulation. Four such quantities from the calorimeter (jet towers, em towers, missing Pt, and scalar Et) are

shown in Figs. 17-20. These curves are needed for several purposes such as to aid in the optimization of triggers (bandwidth versus threshold considerations), and to compare with measured rates to certify that the hardware is working properly. At this stage of the experiment, the curves have to be updated often as changes occur in electronics, coverage, luminosity (multiple interactions) and simulation software. We also participate in studies regarding changes in the hardware and any problems as they arise.

We have participated equally or even more heavily in the Level-2 system. Here, we have played a major role in the development of software to study rates and efficiencies and to certify the various algorithms. We were also mainly responsible for developing the missing Et algorithm and the tau tagging algorithm. Figures 21-23 show representative Level-2 rate curves for jets, electrons and missing Et as a function of threshold.

Our group developed and maintains the real-time monitoring program that histograms trigger related quantities as data is being collected. The D-Zero data collection shifts currently require approximately ten people. Each person is responsible for monitoring part of the detector (muon system, calorimeter, tracking chambers/TRD, electronics and a global quantities). The "global" monitor is responsible for making sure the detector is working as a system and one of his tasks is to monitor trigger rates and distributions. A representative set of quantities being monitored is shown in Fig. 24. (Incidentally, two of us (White and Boehnlein) are members of the global monitor crew, and Jay is one of the "Global/DAQ Experts" who are trained to be able to handle a much more extensive range of problems.)

We have also carried out detailed comparisons between the Monte Carlo predictions and actual data rates for both Level-1 and Level-2 quantities. Figure 25 shows a comparison between Monte Carlo and measured jet tower rates from Level-1 as a function of threshold. The agreement is fairly good for this stage of the experiment, and differences are believed to be understood. Figure 26 shows a comparison between the Level-2 and offline missing Pt spectrum. Here the agreement is excellent, showing the fast algorithm used for Level-2 is giving an accurate answer.

Another important trigger related job is to optimize and determine trigger efficiencies for the many physics processes of interest. In addition to studying the triggers for the wino-zino and squark physics discussed above, we also participate heavily in other topics. For example, Figure 27 shows the efficiency as a function of Level-2 missing Pt threshold for 150 GeV gluinos, when the Level-1 threshold is set at 25 GeV. Figures 28 and 29 are from a study of $W \rightarrow \tau\nu, \tau \rightarrow \text{hadrons}$. Figure 28 shows the efficiency as a function of missing Pt after requiring a jet tower above the given threshold, and Fig. 29 shows the QCD background rates for the same conditions. Having expertise in the trigger simulation software, our group participates in a large number of such studies.

4. SDC Experiment at the SSC

The liquid scintillating fiber technology is one of the remaining options being considered for the forward calorimeter for both SDC and GEM. This past year, our group has made excellent progress in establishing that the technology can meet all the requirements including speed, safety, radiation resistance, resolution and cost. One year ago, it was still not proven whether or not the technology was really sufficiently rad-hard or whether or not liquid fibers with long enough attenuation lengths could be found. We have now established that both these requirements are met, and hence, that the liquid fiber option is every bit as attractive as anticipated. The most important or critical findings can be summarized as follows:

- Liquid-glass combinations have been found with attenuation lengths exceeding four meters. This is well beyond the required minimum length of approximately three meters.
- Radiation-induced discoloration or damage of the cladding (glass tubing or pyrex) has no detrimental effect on the attenuation lengths. This was studied for doses exceeding 100 Mrads, and attenuation lengths were observed to either remain the same or in some cases increase slightly!
- No coatings or other interaction between the glass and liquid were observed for any of several liquid samples tested. This, along with the second item, means that the performance of the detector can be kept constant by simply circulating the liquid as originally planned!
- No long term activation of either glass or liquid were observed. Hence, the active

material will not produce a hazardous waste problem.

- The liquids tested were found to be reasonably radiation resistant as tested, but preliminary findings indicate that the primary damage may largely be due to oxygen dissolved in the liquid. We are now doing tests with the oxygen removed. We have also found that it may be possible to simply filter out the damaged of the liquid and greatly extend its life!

We have also made considerable progress in other areas including the construction and testing of two em prototypes, light guide development and GEANT simulation to optimize parameters. This work is described in the following sections.

4.1 Attenuation Length Measurement

The fiber attenuation length is one of the most important quantities to determine at this stage of the project. We are in the process of determining the minimum attenuation length required in order to achieve the desired resolution. This is being studied as a function of tube diameter, spacing and angle by carrying out simulations using GEANT. Preliminary results indicate that three meters is more than sufficient to meet the SDC resolution requirements as discussed in the section on simulations.

4.1.1 Measurement Technique

The fiber attenuation length is determined by measuring the light output as a function of distance using a test stand as illustrated in Fig. 30(a). The liquid fiber is placed in a machined groove with one end approximately one inch from the face of a photo multiplier tube (EMI 9839b). The fiber is inserted through a small hole in a shield in front of the photo tube. The shield is to eliminate light not coming directly from the core of the fiber. A slot is provided just in front of the photo tube to allow placement of optical filters for

wavelength dependence studies. Once the fiber is in place, a 50 millicurie Sr^{90} source is driven along the length by a PC controlled stepper motor and the photo tube current is read out every two inches or as selected. The current is read out through a Keithley 485 picoammeter. The dark current is 1-3 nA and the signal ranges from 50 nA to 1 μ A depending on sample and optical filter. The groove containing the fiber is aligned relative to the source to within 0.005 inches.

The samples are filled by drawing the liquid into the glass tubes using a syringe which is coupled to the glass with a flexible (Tygon) tube. The liquid is allowed to touch only the glass to assure minimal contamination. A silica optical fiber (3-M Power Core), with a 1 mm OD and 5 cm length is inserted in one end and glued with 5-minute epoxy as illustrated in Fig. 30(b). The optical fiber has a 600 micron silica core with a silicate cladding and Tefzel (3-M) jacket. These materials were tested for chemical compatibility with the liquids and appear to be non-destructive. The other end is sealed with a drop of 5-minute epoxy. An air gap prevents the epoxy from touching the liquid on this end while contact on the fiber end is minimized by inserting the fiber approximately 1/2 inch into the tube and wicking away the excess liquid before gluing. This method allows the coupling to be made without an air bubble between the liquid and the silica fiber. After the glue is dry, the fiber end of the tube is painted with a graphite paint (Aquadac). The paint covers approximately 5 cm including part of the silica fiber and is necessary to eliminate light trapped in the air-glass interface.

4.1.2 Results

Measurements were made for an assortment of fibers containing different liquids and employing tubes with different diameters. For reference, a set of rectangular Pyrex tubes and a set of quartz tubes were also tested.

A primary consideration is the repeatability of the measurements. To test this, several samples of each species were measured. Figure 31 shows several samples using 2 mm OD, 1mm ID Pyrex tubes with a Bicorn liquid (BC-599-13) and no optical filter. The photo

tube sits approximately 5 inches to the left of the first data point. The main quantity of interest is the slopes of the curves and no attempt was made to control the absolute light output. Here the slopes are seen to be quite similar and the attenuation lengths were determined from a fit to an exponential function including all data points to be 1.58, 1.58, 1.57, 1.57 and 1.52 meters for the curves from top to bottom respectively. If only the furthest points (distances greater than 17 inches) are fit, the attenuation lengths are found to be 1.85, 1.69, 1.83, 1.88 and 1.97 meters respectively. The attenuation lengths are clearly increasing as is found with plastic fibers, but the small bumps and wiggles which are due to tube diameter fluctuations limit an accurate determination over such short distances. (We are in the process of obtaining much longer tubes to study this further.)

The variation in light output is caused mainly from variation in tube diameter and roughness of the coupling fibers. The silica fibers were simply scratched and broken but not polished. The tubes were off-the-shelf pyrex with specifications of 2.0 ± 0.15 mm OD and 0.5 ± 0.1 mm wall thickness which could, alone, lead to a light production variation in the 20% range. We will study the effect of polishing and the correlation between diameter and light output in the future.

Another major task is to find a liquid with a long enough attenuation length to satisfy the resolution requirements of the calorimeter. Since our program has been to concentrate on relatively high index cladding (Pyrex and quartz have refractive indices from 1.47 to 1.5), we have studied only high index liquids with indices in the 1.57 range. Figure 32 shows the light versus distance curves for four of the "best" samples with no optical filter. Two are from Bicron (BC-599-13 and BC-599-12) which are based on isopropyl biphenyl and two are from National Diagnostics (ND-XII-135-1 and ND-XII-135-2) which are based on Pseudocumene and Decalin. Several other samples were investigated, but relative to the best samples, either the attenuation length was shorter or the light output was too low to measure with our test setup.

The attenuation length varies with the wavelength of the emitted light in the same way as observed in plastic scintillating fibers. Figure 33 shows the light versus distance

curves for a sample of BC-599-13 as a function of optical filter. The filters were high pass filters that pass all light with longer wavelengths than the number shown and block the shorter wavelengths. The attenuation length is seen to increase at longer wavelengths at the expense of lower light output. These curves were measured by keeping the fiber position fixed while changing filters, so the relative light output seen by the photo tube as a function of filter is correct.

The attenuation lengths as a function of optical filter for the four samples shown are given in Table 1. The numbers given are the mean and estimated error based on several samples (3-7) of each type. The major result illustrated in this table is that several of the values exceed three meters in attenuation length, which is approximately the minimum length needed to achieve the desired resolution. Another important point to notice is that these results were obtained without having to mirror one end of the tube as is routinely done for plastic fibers. This is fortunate since it is not known whether or not a workable mirroring scheme could be devised.

In summary, it is clear that a set of liquids have been found that, in combination with common Pyrex tubing, can be used to make liquid scintillating fibers with sufficiently long attenuation lengths to meet the detector requirements. Similar results are obtained with the much more expensive quartz tubes.

4.2 Radiation Damage Studies

The forward calorimeter will be required to withstand extreme doses of radiation. As shown in Fig. 34, the SDC forward calorimeter could receive up to 10 GRads over a 10 year period at a luminosity of $10^{34} \text{ cm}^{-2} \text{ s}^{-1}$. The radiation is due to the beam jets, but the largest dose is due to the electromagnetic component of the jets and is therefore fairly localized.

The most obvious types of damage that can affect the active components (liquid fibers) of a liquid fiber calorimeter include:

- 1) Damage to the liquid : shortened attenuation length and/or loss of light output.
- 2) Damage to the cladding : discoloration or structural.
- 3) Damage to the liquid-cladding interface : radiation induced deposits or other interactions.

These possible effects were investigated by irradiating a large array of samples of liquids, glass tubes and liquid-glass combinations. The irradiation and results are discussed in the following subsections.

More subtle possible problems include the effect of activation of the absorber or fiber components, the production of gas bubbles in the liquid and damage to the light guides or electronics. These issues are being investigated in the next round of studies.

4.2.1 Irradiation of Samples

The samples were irradiated at a nuclear reactor at Texas A&M University. The core of the reactor is roughly cubic with 17 inch sides as illustrated in Fig. 35. It sits near the bottom of a tank of water 30 feet in depth and has a peak output power of one megawatt. Three of the horizontal sides include graphite shields which reduce the neutron flux in those directions.

The samples were held in a long aluminum tube that could be lowered to the core and placed in position on a side containing the graphite shielding. Perpendicular to the center of the core, the rate was measured by an ionization chamber to be approximately 5 MRads/hour.

4.2.2 Results

Pyrex and quartz tubes were irradiated up to doses exceeding 100 MRads in both air and liquid. After irradiation, the tubes irradiated in air were filled with fresh liquid and measured for attenuation length and light output. Those irradiated in liquid were rinsed with isopropyl alcohol before being filled with fresh liquid. The radiation causes the tubes to turn a dark brown color.

Figure 36 shows the attenuation lengths for both sets of tubes (those irradiated in air, and those irradiated with liquid inside) overlayed with a non-irradiated samples. Several samples of each set were done, and the conclusion is that there is absolutely no degrading effect either due to the discoloration of the glass or due to any possible interaction between the liquid and the glass! The tubes irradiated with liquid were also inspected under an electron microscope, and again, there was no evidence of deposits or damage. Structural damage to Pyrex and quartz is negligible at these doses, so we can conclude that damage to the cladding is not a factor.

Liquids were also irradiated to doses of 10, 50 and 100 MRads. Figure 37 shows the effect on the attenuation length as a function of dose for one of the samples. Notice that the curves for 50 and 100 MRads overlap. This seems to imply a saturation effect. The liquids turn a yellowish color during irradiation, and chemists suggest that this is likely due to oxidation from oxygen dissolved in the liquids. This would explain the saturation if the amount of oxygen is limited. We are now repeating the experiment for samples where the oxygen has been removed by bubbling dry nitrogen through the liquid. We have also found that a simple filter (silica) removes much of the yellow component, so it may be possible to simply clean the liquid as it becomes damaged!

Figure 38 shows the 10 MRad sample as a function of optical filter. For the 515 nm filter, the attenuation length is still 2.6 meters which is plenty long for the sections closest to the beam pipe where the dose rate is highest. The 10 MRad level is the expected dose in a month of running at the nominal luminosity for the portion of the detector only a few cm from the beam pipe. This is an extremely small volume. We conclude that the liquid, as is, is sufficiently rad-hard to allow circulation at an acceptable rate. And, we have 8-10

years to find a better one!

4.3 GEANT Simulations

In order to determine the required depth, tube diameter and spacing, and minimum attenuation length, we are conducting detailed simulation studies using GEANT. This work is done with Dan Suson of Texas A&I University, who is working with our group through the Prairie View A&M Detector Center project.

Examples of the types of results we get are shown in figures 39 and 40. Figure 39 shows the energy spectrum for 25, 50, 75 and 125 GeV pions. The width and means of these curves can be extracted and plotted in the form shown in figure 40. Here, the plots are for a fiber with infinite attenuation length. Figure 41 shows the same curves for attenuation lengths of 2 and 3 meters, showing that the resolution does indeed get worse. For infinite attenuation length the constant term is about 1.5% and the stochastic term is 55 %. For the 3 meter attenuation length , the constant term jumps to 6% and the stochastic term becomes 70%. These results are obtained for a large matrix of conditions including entry angle of the incident particle, tube diameter, spacing and attenuation length, and for both electrons and pions.

4.4 Summary

We have achieved our goal of demonstrating that the liquid fiber technology is a workable solution to the problem of finding a fast, rad-hard detector for the forward calorimetry. With our remaining funds, we are constructing an em prototype with a realistic plumbing system and light collection system for a beam test. Our earlier prototypes were successful, but did not demonstrate that the liquid could be circulated, and did not have a properly designed light guide. We have now constructed a test stand to aid in the construction of a fiber optics light guide with a perfectly flat response as a function of position.

After completing this work, our participation in forward calorimetry R&D will likely be ending since its further development has been assigned to Canada as a foreign contribution to the SSC. We have, however, requested funds from TNRLC to participate in the building of a full scale prototype with the GEM group.

5. Summary

As this report demonstrates, we have been very active in both D-Zero and the SSC. We are leading some of the most exciting physics analysis at the Tevatron. Jay Wightman will be leaving our group as of December 31 due to lack of funding for his support. He has done an excellent job, but it is time for him to move up in position. Amber Boehnlein is a central figure in the D-Zero software crew and is an extremely valuable asset to our group. Mei Gui has done excellent work on the SSC research, and is a valuable new member of our group. We feel it is time for her to be allowed to participate in our D-Zero activities since it is absolutely necessary to be involved in physics to continue a career in our field.

Figure 1. Mass of the zino as a function of mass of the wino for several values of the free SUSY parameters.

Figure 2. Mass of the lightest SUSY particle (LSP or $\tilde{Z}_1$) as a function of the wino

Figure 3. Wino mass as a function of gluino mass.

Figure 4. The wino-zino production cross section as a function of wino mass for a spread of SUSY parameters.

Figure 5. Monte Carlo simulation of the side view of a wino-zino to trilepton event in the D-Zero calorimeter and central tracking chambers.

Figure 6. Monte Carlo simulation of the end view of a wino-zino to trilepton event in D-Zero calorimeter and central tracking chambers.

Figure 7. Side view of a real event with three apparent electromagnetic clusters in D-Zero's first pb^{-1} . This is a trilepton "candidate", but detailed analysis shows it is probably just a QCD three jet event.

CAL+TKS END VIEW 30-OCT-1992 12:31

Run

52668 Event

1007

23-SEP-1992 03:32

Max ET = 9.6 GeV

MISS ET = 6.0 GeV

ETA(MIN=-13-MAX=13)

Figure 8. End view of the trilepton "candidate".

Figure 9. Scatter plots of the Pt of two leptons, two jets, jet1(2) vs lepton1(2) and jet1(2) vs lepton2(1), assuming top quark has a mass of 100 GeV.

Figure 10. Histograms of the lepton, jet and missing Pt distributions, for a 100 GeV top quark.

Figure 11. Scatter plots of the Pt of two leptons, two jets, jet1(2) vs lepton1(2) and jet1(2) vs lepton2(1), assuming top quark has a mass of 140 GeV.

Figure 12. Histograms of the lepton, jet and missing Pt distributions, for a 140 GeV top quark.

Figure 13. Scatter plots of the Pt of two leptons, two jets, jet1(2) vs lepton1(2) and jet1(2) vs lepton2(1) for a 140 GeV squark decaying into a 50 GeV wino (decays to a lepton, neutrino and LSP) and a quark.

SQUARK

M-STOP=140, GLUINO=150, WINO=50 GEV

Figure 14. Histograms of the lepton, jet and missing Pt distributions, for a 140 GeV squark.

SQUARK

M-STOP=180, GLUINO=350, WINO=93, SLEPTON=120 GEV

Figure 15. Scatter plots of the Pt of two leptons, two jets, jet1(2) vs lepton1(2) and jet1(2) vs lepton2(1) for a 180 GeV squark decaying into a 93 GeV wino (decays to a lepton, neutrino and LSP) and a quark.

SQUARK

M-STOP=180, GLUINO=350, WINO=93, SLEPTON=120 GEV

Figure 16. Histograms of the lepton, jet and missing Pt distributions, for a 180 GeV squark.

Figure 17. Jet tower Level-1 trigger rates from Monte Carlo QCD two-jet events.

Figure 18. EM tower Level-1 trigger rates from Monte Carlo QCD two-jet events.

Figure 19. Missing Pt Level-1 trigger rate from Monte Carlo QCD two-jet events.

Figure 20. Total scalar E_T Level-1 trigger rate from Monte Carlo QCD two-jet events.

Figure 21. Jet tower rates from Level-2 (VMS Filter).

Figure 22. EM tower rates from Level-2 (VMS Filter).

Figure 23. Missing Pt rate from Level-2 (VMS Filter).

Figure 24. Assortment of plots from real-time trigger monitoring program.

D0 Preliminary
MC vs DATA

Figure 25. Comparison between Monte Carlo and measured jet tower rates.

D0 Preliminary
Run 51709, mark and pass $\cancel{E}_T$

Figure 26. Comparison between Monte Carlo and measured Level-2 missing P_t spectra.

Monte Carlo Trigger Studies for MSSM

Figure 27. Monte Carlo study of efficiency as a function of Level-2 missing Pt threshold for a 150 GeV gluino.

$W \rightarrow \tau \nu_\tau$, τ decays through hadronic channels

Figure 28. Monte Carlo prediction for efficiency as a function of missing Pt threshold for a W to tau to hadrons topology.

L1 SIM $\cancel{E}_T$ Rate vs. Threshold QCD Dijet events

Figure 29. Predicted QCD background rates for the same cuts in Fig. 28.

Figure 30. (a) Test stand for measuring attenuation lengths; (b) Light coupling of liquid fiber to photo multiplier tube using a silica core optical fiber.

Figure 31. Light versus distance curves for five fibers made of BC599-13 scintillator.

Figure 32. Light versus distance curves for four of the "best" samples with no optical filter.

Figure 33. Light versus distance curves for a sample made of BC599-13 scintillator as a function of optical filter.

Figure 34. Expected radiation level of the SDC forward calorimeter at a luminosity of $10^{34} s^{-1} cm^{-2}$. (Adopted from the SDC Technical Design Report.)

Figure 35. Layout of sample placement in the nuclear reactor tank.

Figure 36. Light output versus distance. (a) Open symbols represent data for the samples of non-irradiated tubes and solid symbols represent data for the samples of irradiated tubes (air). (b) Open symbols represent data for the samples of tubes irradiated with liquid and solid symbols represent data for the samples of tubes irradiated in air.

Figure 37. Light output versus distance curves for the samples made of irradiated BC599-13 liquid scintillator.

Figure 38. Light output versus distance curves for the sample made of BC599-13 irradiated at 10 Mrads as a function of optical filters.

ENERGY P 2mm - attn ln = infinite

Figure 39. Energy spectra for 25, 50, 75 and 125 GeV points. The attenuation length of the fibers are infinite.

Figure 40. Width and means of figure 39 spectra.

41. Width and means of energy spectra for 25, 50 75 and 125 GeV points with fiber attenuation lengths of 2 and 3 meters.

END

**DATE
FILMED**

2 / 9 / 93