DOE/PC/79743--T5

MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS FROM COAL FLAMES

DOE/PC/79743--T5

DE92 013606

Quarterly Technical Progress Report No. 6
Reporting Period: January 1, 1989 - March 31, 1989

Prepared for:

U. S. Department of Energy
Pittsburgh Energy Technology Center

Under:

Contract No. DE-AC22-87PC79743

Prepared by:

G. H. Newton
C. Schieber
R. G. Socha
W. D. Clark
J. C. Kramlich

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718-2798

May, 1989

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Section	Page
ABSTRACT.	iii
1.0 INTRODUCTION.	1
2.0 EXPERIMENTAL PROGRAM.	3
3.0 ENGINEERING ANALYSIS.	7
4.0 FUTURE WORK	23
APPENDIX	

ABSTRACT

The principal activities during this quarter involved the global experiments. Ash was sampled from 13 coals (of varying rank) as a function of oxygen concentration. The coals have been submitted for analysis.

Pending the receipt of these analyses, preliminary analyses of the data were performed using the breakup model and analyses from other sources. The higher rank coals were found by the breakup model to require fewer ash particles per coal particle than the lower ranked coals, although there were some notable exceptions. Also, the deviation of the measured size distribution from the simple breakup model was examined at the small end of the size distribution. This is the region where mechanisms of second order importance might strongly influence the yield of fine respirable particulate matter. The next step will be an attempt to correlate these deviations with properties of the specific coals involved.

During the next quarter the global experiments will be completed and the mechanistic experiments begun. Engineering analysis of the data will be conducted when the analyses have been received.

1.0 INTRODUCTION

The overall objective of this project are to provide a basic understanding of the principal processes that govern fine particulate formation in pulverized coal flames. This understanding is to be used to develop a model (or models) which will predict the yield and size distribution of fine particulate matter as a function of coal type, coal processing, and combustion conditions. The goal of the model is to provide an engineering tool that will enable the practitioner to estimate the consequences of design decisions and fuel selection on the fine particulate yield. The practitioner can then make rational decisions regarding the required technology and costs associated with effluent cleanup while still in the design phase.

Long term work is presently supported by PETC that will develop detailed models of the entire mineral transformation process. The present work is directed toward global models of behavior which will become available on a shorter time frame, and will be immediately usable in engineering activities.

Another goal of the work is to extend the capabilities for the characterization of fine particulate. Present technology for characterizing size distributions usually involves manual impactor techniques for sizes down to $0.2\ \mu\text{m}$. The EAA analyzer is used for aerosols. Although the impactor covers the size range of interest, it is a very time consuming procedure. Another difficulty is that the impactor and the EAA overlap only over a small size band. The results of the comparison of the two techniques are not always consistent within the region of overlap. The goal is a single instrument that will characterize the fine particulate size band rapidly and accurately.

Particles in the $0.5\text{-}10.0\ \mu\text{m}$ size band are of interest for several reasons. First, a considerable portion of the fly ash generated in pulverized coal combustion falls within this size range. Particulate control devices, in particular electrostatic precipitators, are at their least efficient in this size band. Also, particles in this size range are most efficiently collected within the alveolar passages of the human lung. In coal combustion, a considerable

portion of the heavy, toxic metals are vaporized within the flame. As the furnace gases cool, these metals will condense on the available surface area. Since most of the surface area is present on the smaller particles, they will become enriched in these toxic metals. Thus, those particles that are deposited in the alveoli may be coated with toxic compounds and create a health hazard that is well beyond the toxic material proportion in the original mineral matter.

Finally, the mechanism by which this fine flyash is formed is not yet clear. Obviously, predicting the yield will require some definition of the dominant mechanisms. Also, the manner in which these mechanisms respond to differing coal types and combustion conditions will have to be understood to make predictions. The project objective is being accomplished through a combination of literature research, experimentation, and model development activities. The program tasks include:

Task 1. Literature review and program plan.

Task 2. Engineering analysis.

Task 3. Experimental program.

Task 4. Reporting.

This report describes work performed during the period from January 1, 1989 through April 1, 1989. The principal activity during this period involved the isothermal experimental system. Ash from thirteen coals were sampled as a function of oxygen concentration and analyzed for particle size. A preliminary analysis of the data was performed based on data obtained from other sources. A more detailed analysis will be included in the next quarterly when test results on the specific coals used in this study are returned from the analytical laboratory.

2.0 EXPERIMENTAL PROGRAM

The experimental portion of this project consists of a study of the fundamental mechanisms at laboratory scale, followed by a process simulation study conducted at the bench-scale. The fundamental mechanisms study consists of three subtasks:

- Modification of the laser diffraction particle sizer to allow it to measure down to the 0.5 μm size range. This task has been completed and reported in a previous quarterly progress report.
- Global experiments which are designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter. This task is almost complete.
- Mechanistic experiments which focus on providing a quantitative evaluating the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter.

Testing is performed in the Isothermal Reactor (ITR) which is illustrated in Figure 2-1. The ITR consists of a 10 cm diameter ceramic tube mounted in a three-zone electric furnace. The high temperature gas flow is supplied by a gas flame fired in the side chamber at the top of the reactor. The furnace is capable of operating to 1500°C.

2.1 Results

Testing during this reporting period concentrated on sampling ash from a number of coals. The coals tested to date are listed on Table 2-1 along with the conditions they were tested at. The measured particle size distributions for these coals and the resultant ashes are attached in the Appendix. Although analyses are available on many of these coals from other sources or from old analyses, they have all been sent out for proximate analysis to ensure against

Table 2-1. Coals tested to date.

Coal	Coal Type	Temperature	% Oxygen
Utah	Bituminous	1200°C 1350°C	10, 20, 25.5, 30 20
62% Illinois/ 38% Kentucky ²	Bituminous/ Bituminous	1200°C	10, 20, 30
Eagle Butte ¹	Subbituminous	1200°C	20, 30
Beulah ¹	Lignite	1200°C	20, 30
Illinois No. 6 ¹	Bituminous	1200°C	20, 30
Illinois ²	Bituminous	1200°C	10, 20, 30
Smokey Clean	Bituminous	1200°C	20, 30
PM/Fence Lake	Bituminous	1200°C	20, 30
Wyodak, Colorado	Subbituminous	1200°C	20, 30
Wards	Bituminous	1200°C	20, 30
Stratford	Bituminous	1200°C	20, 30
Big Brown	Subbituminous	1200°C	20, 30
Indo		1200°C	20, 30

1 - PSI Coals

2 - Clean Coal Technology Coals

Figure 2-1. The Isothermal Reactor.

variations in the coal batch properties or that aging has not altered their properties.

3.0 ENGINEERING ANALYSIS

Pending the receipt of these analyses, only a preliminary analysis of the data can be performed for those coals which have proximate analyses available. The ash content of these coals were used as inputs for the breakup model with the results of these calculations shown in Figures 3-1 through 3-13 for an assumed breakup number of one ash particle from each coal particle. The breakup numbers required to fit the data are also given in Table 3-2. The breakup number was found by adjusting the number of ash particles per coal particle until the predicted cumulative curve intersected the cumulative ash particle size curve at the ash mean diameter. In general, the particle size distribution of ashes from the bituminous coals could be fit with low breakup numbers of from 1 to 6. The lower rank coals, however, tended to require higher breakup numbers of 8 to 12.

A comparison of the shapes of the cumulative ash particle size distribution curve and those predicted by the breakup model reveals that different coals can be better fit by the breakup model than others. The cumulative size curves for the Utah, Illinois No. 6, Kentucky, and Big Brown coals parallel the model prediction curves. The others, however, do not. If the number of particles formed from each coal particle is adjusted so that the ash and model curves intersect at the ash mean diameter, then the fraction of ash particles smaller than the mean is less than predicted. This is illustrated in Figure 3-13 for the Beulah coal ash. This type of behavior could result from:

- The number of ash particles produced from a coal particle may vary with coal particle size. This trend could be predicted if the smaller coal particles broke into fewer ash particles than the larger coal particles. Or,
- The ash content may vary with particle size. The above trend could be predicted if the smaller coal particles had a lower ash content than the larger particles. This would result in the smaller coal particles

Table 3-1. Number of ash particles per coal particle required to fit the data.

Coal	Coal Type	Temperature	% Oxygen	Breakup Number
Utah	Bituminous	1200°C	10	3.6*
			20	2.3
			25.5	1
			30	4.2
		1350°C	20	1
			30	3.7
Illinois No. 6 ¹	Bituminous	1200°C	20	1
			30	1
Illinois ²	Bituminous	1200°C	20	2.4
			30	1
Wards	Bituminous	1200°C	20	1
			30	1
Stratford	Bituminous	1200°C	20	1
			30	1
62% Illinois/ 38% Kentucky ²	Bituminous/ Bituminous	1200°C	10	1*
			20	6
			30	6
Eagle Butte ¹	Subbituminous	1200°C	20	8
			30	8
Big Brown	Subbituminous	1200°C	20	9
			30	11
Beulah ¹	Lignite	1200°C	20	17
			30	12

* - Incomplete Burn

1 - PSI Coals

2 - Clean Coal Technology Coals

Figure 3-1. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-2. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-3 Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-4. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-5. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-6. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-7. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-8. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-9. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-10. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-11. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-12. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

Figure 3-13. Comparison of ash particle size distributions and the distribution predicted by the breakup model with a breakup number of one.

producing larger ash particles than predicted and the larger coal particles producing smaller ash particles than predicted.

These issues will be examined in the mechanistic studies portion of the program.

4.0 FUTURE WORK

The global experiments, which are almost complete, will be concluded. The experimental work will then focus on the mechanistic studies. This will involve measuring the particle size of ashes from coals which have been cleaned and sized in order to gain an understanding of the fundamental mechanisms which are occurring. Once the proximate analyses have been received on the coals tested under the Global Experiments, engineering analysis of the data will be performed.

APPENDIX

Measured Particle Size of Coals and Ashes

A-40

END

**DATE
FILMED**

8 / 12 / 92