**A Study of the Effects of Enhanced Oil
Recovery Agents on the Quality of Strategic
Petroleum Reserves Crude Oil**

DOE/PC/90283--T1

DE93 013175

Final Technical Report

October, 1992

by

Vinayak N. Kabadi

Chemical Engineering Department

North Carolina A&T State University

Greensboro, NC 27411

Prepared for

United States Department of Energy

Pittsburgh Energy Technology Center

Pittsburgh, Pennsylvania 15236

Under Grant Number: DE-FG22-90PC90283

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report was prepared with the support of U.S. Department of Energy, Grant Number DE-FG22-90PC90283. However, any opinions, findings, conclusions, or recommendations expressed herein are those of the author and do not necessarily reflect the views of DOE.

The work on the project was performed by the principal investigator with assistance from three chemical engineering undergraduate students, Ms. Angelia Charles, Ms. Kimberley Rollins and Mr. Gorav Sangal.

ABSTRACT

The project was initiated on September 1, 1990. The objective of the project was to carry out a literature search to estimate the types and extents of long time interactions of enhanced oil recovery (EOR) agents, such as surfactants, caustics and polymers, with crude oil. This information is necessary to make recommendations about mixing EOR crude oil with crude oils from primary and secondary recovery processes in the Strategic Petroleum Reserve (SPR). Data were sought on both adverse and beneficial effects of EOR agents that would impact handling, transportation and refining of crude oil.

An extensive literature search has been completed, and the following information has been compiled:

- (1) a listing of existing EOR test and field projects
 - (2) a listing of currently used EOR agents and
 - (3) evidence of short and long term physical and chemical interactions of these EOR agents with hydrocarbons, and their effects on the quality of crude oil at long times.
- This information is presented in this report. Finally some conclusions are derived and recommendations are made. Although the conclusions are based mostly on extrapolations because of lack of specific data, it is recommended that the enhancement of the rates of biodegradation of oil catalyzed by the EOR agents needs to be further studied. There is no evidence of substantial long term effects on crude oil because of other interactions. Some recommendations are also made regarding the types of studies that would be necessary to determine the effect of certain EOR agents on the rates of biodegradation of crude oil.

TABLE OF CONTENTS

	Page
ABSTRACT	
TECHNICAL HIGHLIGHTS AND MILESTONES	1
INTRODUCTION	1
CHEMICAL ENHANCED OIL RECOVERY	3
Polymer Flooding	3
Foam Flooding	4
MP Flooding	5
High-pH Flooding	6
INTERACTIONS of EOR AGENTS WITH OIL	7
Physical and Chemical Interactions	8
Biodegradation	10
CONCLUSIONS AND RECOMMENDATIONS	12
REFERENCES	13
APPENDIX A-	15
SUMMARY OF SOME EOR PILOT AND FIELD PROJECTS	

TECHNICAL HIGHLIGHTS AND MILESTONES

INTRODUCTION

Oil is the lifeblood of America's economy. Each day an average of 16 million barrels of petroleum are used in the United States. Crude oil accounts for nearly 40% of the energy consumed.

The need for a national oil storage reserve has been recognized for at least four decades. The need was dramatically emphasized by the 1973-74 oil embargo. In the aftermath of the oil crisis, America established the Strategic Petroleum Reserve (SPR).

Throughout its history, the SPR has acquired crude oil either from purchases on the international market, long-term (1 year or longer) contracts with both foreign and domestic suppliers, or special sales arrangements for oil from government-owned oil fields. As of September, 1988, the United States was the source of only approximately 7 percent of the oil in the SPR. Mexico and the United Kingdom were supplying about 66 percent, and the remaining 27 percent of the SPR oil was being supplied by 16 countries.

The SPR is an emergency supply of crude oil stored in huge underground caverns along the coastline of the Gulf of Mexico. The storage caverns are essentially huge oil cavities created within salt domes. The reserves act as one of the nation's great energy achievements. It has become the nation's first line of defense against future shortfalls in energy supplies. The very existence of the reserves and the intent to use it early serve as powerful deterrents to the possibility that the free flow of crude oil could be used again as a political weapon against the U.S.

Enhanced oil recovery is a term applied to methods used for recovering oil from a petroleum reservoir beyond that recoverable by primary and secondary methods. Primary oil recovery depends upon natural reservoir energy to drive the oil through the complex pore network to producing wells. The driving energy may be derived from liquid expansion and evolution of dissolved gas from the oil as reservoir pressure is lowered during production, expansion of free gas or a gas cap, influx of natural water, gravity, or combinations of these effects. When the natural drive energy is dissipated, we move to the second stage of production. Secondary oil recovery involves the injection of energy into a reservoir by injecting gas or water under pressure. The injected fluids maintain pressure or repressure the reservoir after primary depletion. Waterflooding is the principal secondary recovery method. Thus, enhanced oil recovery is often synonymous with tertiary recovery, although sometimes EOR methods can be used earlier in the sequence. We note that in the past, waterflooding was considered an enhanced oil recovery method, but now EOR is thought to follow waterflooding.

Three groups of methods--thermal recovery, gas miscible recovery, and chemi-

cal flooding are well established and a fourth, microbial flooding is under developmental study.

Thermal recovery processes add heat to the reservoir to reduce oil viscosity and/or to vaporize the oil. In both instances, the oil is made more mobile so that it can be more effectively driven to producing wells. In addition to adding heat, these processes provide a driving force (pressure) to move oil to producing wells. There are two principal thermal recovery methods: steam injection and in situ combustion.

Gas miscible recovery are processes in which oil may be extracted from a reservoir by mixing it with another fluid that changes the characteristics of the oil and makes it flow easily. The mechanisms of gas injection and oil recovery involved with miscible gas flooding are basically of three kinds: i) the first-contact miscible gas drive, ii) the condensing or enriched gas drive, and iii) the vaporizing or high pressure gas drive. The first and second processes are based on the injection of hydrocarbons such as methane, ethane, propane, and butane, that are soluble in the residual oil, while the third process involves injection of high density gas. Carbon dioxide is most often used in miscible flooding.

Chemical flooding recovery are processes in which chemicals are added to water floods to scour or free droplets of oil from the rock surfaces to which they cling and to sweep the reservoir more thoroughly and speedily. Polymer flooding is the most frequently used chemical process but surfactant flooding is the most effective.

Microbial flooding are processes that use microbial cultures that can survive and grow at the temperatures and salinities found in petroleum reservoirs to help increase oil recovery by forming surfactants, gas pressure and emulsions.

Over the past 120 years, about 460 billion barrels of oil have been discovered in the United States. And most of it remains in the ground today. Some numerical figures would be that of the 460 billion barrels discovered, only about 140 billion barrels have and can be extracted by primary and secondary methods. Having more than 300 billion barrels discovered oil unproduced, a method of recovering this oil is needed. The method is the tertiary method, or enhanced oil recovery.

CHEMICAL ENHANCED OIL RECOVERY

Chemical enhanced oil recovery includes processes in which chemicals are injected to increase oil recovery. Chemical recovery can be broken down further in terms of four methods [12,13]. Polymer flooding involves a small amount of polymer added to thicken brine. Foam flooding is a technique whereby low mobilities are attained by injecting a stabilized dispersion of gas in water. MP (Micellar/polymer) flooding processes are those in which surfactant is injected into the formation. High-pH or alkaline methods refer to processes where alkali is injected to increase pH and to produce surfactants in situ. In what follows we give a brief discussion of each of these processes.

Polymer Flooding

Polymer flooding is classified as a mobility control process, as it attempts to reduce the mobility of the displacing agent. In the procedure, a small amount of polymer is added to thicken brine. Polymer flooding has been used in three ways: 1) as near-well treatments to improve performance of water injectors or high-water-cut producers by blocking off high-conductivity zones, 2) as agents that may be cross-linked in situ to plug high-conductivity zones at depth in the reservoir, and 3) as agents to control the mobility of the water flood. Most polymer products use the third mode. A typical polymer flood injection sequence contains the following: pre-flush (with low-salinity) brine; an oil bank; polymer solution; freshwater buffer to protect the polymer solution from backside dilution; and, chase or drive water. Polymer floods are always performed through separate sets of injection and production wells. Mobility is lowered by injecting water that contains a high-molecular weight, water-soluble polymer.

Polysaccharides and partially hydrolyzed polyacrylamides (HPAM) are currently being used in field flooding. Polysaccharides are formed through polymerization of saccharide molecules. Biologically produced, these polymers are susceptible to bacterial attack after being introduced into the reservoir. They benefit by having higher temperature stability and are less sensitive to brine salinity and hardness. Unfortunately, they also cost more in addition to being susceptible to bacterial attack after being introduced into reservoir.

Polyacrylamides are polymers whose monomeric unit is the acrylamide molecule. In flooding, these polymers undergo partial hydrolysis (HPAM). The HPAM show a large sensitivity to salinity and hardness, are relatively resistant to bacterial attack, and exhibit good permeability reduction. They are less expensive and are easier to manufacture.

The following is a list of several polymers considered for polymer flooding. Of the polymers, only the first three have actually been field tested. The rest are potentially suitable.

Polymer Types:

1. Xanthan gum
2. Hydrolyzed polyacrylamide (HPAM)
3. Copolymers of acrylic acid and acrylamide
4. Copolymers of acrylamide and 2-acrylamide-2-methyl propane sulfonate (AM/AMPS)
5. Hydroxyethylcellulose (HEC)
6. Carboxymethylhydroxyethylcellulose (CMHEC)
7. Polyacrylamide (PAM)
8. Polyacrylic acid
9. Glucan
10. Dextran polyethyleneoxide (PEO)
11. Polyvinyl alcohol (PA)

Foam Flooding

Foams, dispersions of gas bubbles in liquids, offer an alternative to polymers for providing mobility control in chemical floods. Low mobilities are attained by injecting a stabilized dispersion of gas in water. Surfactants, added to normally unstable gas/liquid dispersions, greatly improve the stability of the foam. Foams are characterized by quality (% of total bulk foam volume that is gas volume), texture, and bubble size range. The mobility of the foam decreases with increasing quality until the films between the gas bubbles begin to break and the foam collapses. The low foam mobilities in permeable media flow are postulated to be caused by at least two different mechanisms: 1) formation of or increase in a trapped residual gas phase saturation and 2) blocking of pore throats caused by the gas films.

Surfactants are classified into four groups based on their polar portions (1). Anionics are uncharged with an inorganic metal cation (usually Na^+) with the monomer. Anionics are the most commonly used in EOR because they are good surfactants, relatively resistant to retention, stable, and relatively inexpensive. Another type of surfactant, the cationic, contains a cationic hydrophile and an inorganic anion to balance charge. These have little use because they are absorbed highly by the anionic surfaces of interstitial clays. Nonionic surfactants do not form ionic bonds, but when dissolved in aqueous solution, exhibit surfactant properties by electronegativity contrasts between their constituents. These surfactants are much less sensitive to high salinities. Amphoteric contains aspects of two or more of the previous classes. These have not been used in EOR.

The following lists examples of surfactants in each classification:

Surfactant Types:

1. **Anionics**
Sulfonates

- Sulfates
- Carboxylates
- Phosphated
- 2. **Cationics**
 - Quaternary ammonium
 - Pyridium
 - Imidazolinium
 - Piperidinium
 - Sulfonium
 - Compounds
- 3. **Amphoterics**
 - Aminocarboxylic acids
- 4. **Nonionics**
 - Alkyl-
 - Alkyl-aryl
 - Acyl
 - Acylamindo-
 - Acylaminepolyglycol ethers
 - Polyol ethers
 - Alkanolamides

MP Flooding

MP (Micellar/Polymer) flooding, a process that injects surfactants, has a tendency for surfactants to form micelles in aqueous solution. The complete process consists of the following: 1) Preflush - volume of brine whose purpose is to change the salinity and hardness of the resident brine so that mixing with surfactants will not cause loss of interfacial activity; 2) MP Slug - this volume contains main oil-recovering agent; 3) Mobility Buffer - dilute solution of water-soluble polymer whose purpose is to drive the MP slug and banked-up fluids to the production wells; 4) Freshwater Buffer - volume of brine containing a concentration of polymer grading between that of the mobility buffer at the front end and zero at the back; 5) Chase Water - reduces the expense of continually injecting polymer.

There are three techniques for generating optimal conditions in MP displacement. First, the MP system's optimal salinity can be raised to that of the resident brine salinity in the candidate reservoir. This procedure is the most satisfying and usually the most difficult. Another way to make optimal salinity of MP formation equal to the resident brine salinity is to add cosurfactant. Secondly, resident salinity of a candidate reservoir can be lowered to match the MP slug's optimal salinity. Finally, the salinity gradient design attempts to dynamically lower the resident salinity to an optimum during the displacement by sandwiching the MP slug between the overoptimal resident brine and an underoptimal mobility-buffer.

The MP flooding process uses the same type of surfactants used in foam flood-

ing. To achieve efficient oil recovery, three things must occur: 1) the MP surfactant slug must be propagated in an interfacially active mode, 2) enough surfactant must be injected so that some of it is unretained by the permeable media surfaces, and 3) the MP displacement must be designed so that the active surfactant sweeps a large portion of the reservoir without excessive dissipation (because of dispersion) or channeling.

High-pH Flooding

The final chemical flooding process is high-pH flooding, also known as alkaline flooding. There is usually a brine preflush to precondition the reservoir, a finite volume of the oil-displacing chemical, a graded mobility buffer driving agent, and the entire process is driven by chase water. The oil-displacing chemical is a surfactant, generated in situ. The generated surfactant aggregates at oil/water interfaces, which can lower IFT (interfacial tension). Increasing the water wetness increases ultimate oil recovery, where the wettability is defined as decreasing the water/oil contact angle measured on polished synthetic surfaces. High-pH chemicals can also cause improved oil recovery through the formation of emulsions through at least two ways: 1) through mobility ratio lowering, and 2) through solubilization and entrainment of oil in a flowing aqueous stream.

Many chemicals are used to generate high pH. High-pH chemicals are less costly but produce lower oil recoveries than MP flooding. Most field projects have used sodium hydroxide. Sodium orthosilicate is used because it forms very insoluble products with divalent ions such as calcium and magnesium. These divalent ions reduce the degree to which IFT is lowered. The following is a list of the most commonly used chemicals to generate high pH.

High-pH Chemicals:

1. Sodium hydroxide (caustic NaOH)
2. Sodium orthosilicate
3. Sodium carbonate
4. Ammonium hydroxide
5. Ammonium carbonate

INTERACTIONS OF EOR AGENTS WITH OIL

Polymers, alkalis, and surfactants all have different effects on produced crude oils. Volumes of literature are available on physical interactions of EOR agents with crude oil and optimization of conditions for maximum oil recovery using various EOR agents in various types of oil fields. Our interest here, however, is to investigate the interactions of the EOR agents on oil components, that will affect the long term quality of the oil. We therefore, screened the literature for data that will help our investigations. Considering the small concentrations of chemicals in the oil upon recovery, based on available data there is no evidence of any short term detectable damaging or beneficial effects on the oil. Although no data are available on any long term effects we have chosen to extrapolate such effects from known short term phenomena. As a basis for the extrapolations we have used accepted theories for natural formation and evolution of fossil fuel deposits [3,6,11].

It is now very widely accepted that crude oil has both biogenic and thermal origin [3,7,15]. The presence of optically active compounds in oils (especially the multiringed cycloalkanes) provides strong support for the biological hypothesis. Oils also contain so-called "chemical fossils" or "biological markers" which are compounds with characteristic structures that can be related to those in living systems. The compounds include isoprenoids, porphyrins, steranes, hopanes and many others. The relative abundance of members of homologous series are often similar to those in living systems with the strong odd preference in the long chain normal alkanes ($> C_{23}$) being particularly well documented [5]. Yet, most crude oils are composed of 20-50% alkanes in the range C_2 to C_{10} , and organisms and recent sediments are almost devoid of such hydrocarbons. Other compounds that are not synthesized by organisms also occur in crude oils. It is apparent that these compounds must have been formed from the available organic matter by reaction in the subsurface. The organic matter originally incorporated into sediments is buried and subjected to increasing temperature and pressure as time goes by. Continued heating of the organic matter in a reducing environment leads ultimately to final products of methane and graphite, i.e., it involves a redistribution of hydrogen to produce one hydrogen-rich and one hydrogen-poor product. At the low temperatures typical of sedimentary rocks, the organic matter progresses along this path and produces a high molecular weight, solvent-soluble material called "kerogen", that becomes more aromatic and carbon-rich as it evolves towards graphite. In contrast, the solvent extractable, lower molecular weight organics, called "bitumens" (or simply "extractables") become more hydrogen-rich and eventually progress through compositions typical of crude oils to those of gas [2].

Natural formation and evolution of crude oil deposits is therefore characterized by a numerous processes that occur over thousands and millions of years. The processes may be generally classified into (1) physical interactions between constituents resulting in such phenomena as phase separations and precipitation (2) Non-biogenic chemical reactions which would normally form lower molecular weight hydrocarbons (with differing H/C ratios) from higher molecular weight ones. And (3)

biochemical reactions and biodegradation of crude oil which need to be further classified into processes that occur in recent sediments that result in formation of crude oil and activity of micro-organisms in crude oil deposits, which may be termed biodegradation of oil. The former plays an important role in the formation of "Kerogen" the parent material from which oil is formed. the latter, however, results mostly in consumption of n-alkanes from the oil and formation of compounds such as isoprenoids, perphyrins etc. which reduce the fuel quality of the oil. The bio-activity during crude oil evolution is, therefore, mostly undesirable.

In this work, we wish to estimate the effect of enhanced oil recovery agents on the above processes. In general, enhanced oil recovery oil would be expected to contain traces of chemicals such as surfactants, polymers, alkaline agents and increased amount of water than normal crude oil. In particular, we focus our studies to petroleum sulfonate surfactants, sodium hydroxide as the alkaline agent, polysaccharide and polyacrylamide polymers and increased moisture content. From the summary of EOR field projects reported in Appendix A, it is clear that, these chemicals have been used extensively in most of the EOR field and pilot projects either completed or currently in operation. It is our objective to estimate whether these chemicals will enhance the physical, chemical and biochemical activity within the crude oil resulting in either beneficial or detrimental effects over a relatively short period of time (100-200 years) as compared to thousands or millions of years that these processes take to occur in nature. The effect to EOR agents may involve direct interactions with the fuel components or these chemicals may serve as catalysts or nutrients for enhanced chemical or biochemical activity.

Physical and Chemical interactions

It is generally accepted that the interaction of alkaline agents with components of the crude oil produce surface-active materials. The oil components responsible have been identified primarily as carboxylic acids and to a lesser extent as asphaltene fractions. Reactions noted between oil and alkali are i) films with crystalline structures were observed with several oil fraction systems, ii) interfacial films that prevent water/oil emulsion coalescence were formed, and iii) considerable swelling of the oil phase when contacted with alkaline water. It is also worth noting that excess quantities of alkali tend to form emulsions, while the same substance in small quantities helps resolve them.

Frequently, the surfactants used in EOR processes are not single substances but are instead complex mixtures of two or more principal surfactants and other additives; the composition of the mixture being constructed so as to achieve some particularly desirable property as required by the reservoir being treated or the process being used. Many studies have been done on the effects of these chemicals on produced crude oil. The most noted effect is that of emulsification. The forming of emulsions by surfactants has been both beneficial and detrimental to oil, depending on the situation.

An emulsion, by definition is a liquid in which droplets of one liquid are suspended in another liquid which would not usually mix. Industrial emulsions frequently contain a solid as a third ingredient. The liquid in an emulsion that is broken into droplets is known as the dispersed or internal phase, whereas the liquid surrounding the droplets is called the continuous or external phase. Natural petroleum emulsions are predominantly water-in-oil emulsions as continuous phase. Rarely is the reverse type emulsion, oil-in-water, encountered in natural petroleum.

The type of emulsion most favorable is governed by minimum in interfacial tension. This in turn is ascertained by controlling brine concentration in the reservoir [13,16].

The stability of natural petroleum emulsions varies considerably. The water separates from certain emulsions upon standing, as the water is "free" and in relatively large globules that separate readily; other emulsions have decidedly permanent characteristics and show no tendency to separate. It is only through coalescence that the minute particles of water become large enough to settle out of the oil. Crude oil emulsions therefore are classified as being "loose" (unstable) or "tight" (stable), depending on the rapidity with which the water coalesces and settles or upon the tendency of the mixture to remain fixed.

In conformity with the general theory of emulsions, the stability of petroleum emulsions depends upon the presence of a third substance called the emulsifying agent, which is soluble, dispersable, or wettable in or by the oil or the water. In general, the emulsifying material is considered to be present in the continuous phase of the emulsion. The type of emulsion, therefore, depends on the properties of the emulsifying agent. If the agent is soluble more easily in or by the oil than in or by the water, then oil will be the external phase and water the dispersed phase. If, on the other hand, the agent is more soluble in or by water, the opposite emulsion-type will be formed.

The substance acting as the emulsifying agent is absorbed at the interfaces separating the two liquids and forms coherent films, thereby preventing coalescence of the particles of the dispersed phase. If no emulsifying agent is present, a stable emulsion will not form. Virtually all crude oils and associated brines contain substances that possess emulsifying properties.

EOR surfactants could be classified as emulsifying agents on one hand, and as emulsion breakers on the other [14]. Lignosulfates, for example, tend to possess emulsion stabilizing properties. Lignosulfates are water soluble, anionic surface active derivatives of lignin and their properties can be adjusted with respect to sulfonate content and surface activity. Their use is desirable due to their being at least 4 times cheaper than petroleum sulfonates and available in large quantities.

Organic sulfonates, some of which are used as EOR surfactants, can act as demulsifying or emulsion breaking agents. Akyl Aryl Sulfonates fall into this class.

These substances tend to nullify the effect of the emulsifying agent that is responsible for the permanence of the emulsion. This action is largely based on surface tension.

Introduction of miscible flood agents to petroleum crude oil can produce alterations to fluid characteristics and behavior. Asphaltene deposition is a direct result of miscible flooding. Asphaltenes are dark brown to black, friable solids that have no definite melting point. They are obtained from petroleum by addition of a nonpolar solvent. They are insoluble in liquefied gases. The word "asphaltene" was coined by the French in the mid 1800's. The alcohol insoluble, essence of turpentine soluble solid obtained from the distillation residue was named due to its resemblance of the original asphalt. In modern times, asphaltene is conceptually defined as the normal-pentane-insoluble and benzene soluble fraction whether it is derived from coal or from petroleum. The generalized concept has been extended to fractions derived from other carbonaceous sources, such as coal and oil shale.

The effect of asphaltene deposition could be positive (like prevention of viscous fingering) or negative (complete plugging of the porous media) depending on whether it could be controlled and predicted before it occurs. The parameters that govern precipitation of asphaltene appear to be composition of both crude and flood agents. In heavy highly aromatic oil the asphaltenes are colloidal dispersed; but in the presence of an excess of petroleum ether, they are coagulated and precipitated. Also, precipitation of asphaltene is generally followed with flocculation of the resulting precipitate, which produces an insoluble material in the produced oil.

All the above processes would be quite possible and significant if the EOR oil contained appreciable amount of unbroken emulsions and hence large concentrations of surfactants and moisture. However, with recent advances in mechanical and chemical methods of de-emulsification, surfactant and moisture content of product EOR oil can be reduced to a minimum at relatively low costs [4,17]. There is no data in literature that indicates that there could be appreciable changes in the quality of crude oil because of direct chemical reactions of EOR agents with crude oil components over a time period of 100-200 years. Again, over the same time period chances of asphaltene formation and other phenomena related to phase separations are minimal, considering that these processes take thousands and millions of years to occur in natural reservoirs.

Biodegradation

It has been known for almost 90 years that some microbes have the ability to metabolize hydrocarbons [7,8,15]. Many hydrocarbons-utilizing bacteria are identified as belonging to the genus *Pseudomonas*. Another organism, *Aspergillus fumigatus* can operate at relatively elevated temperatures [9]. The two organisms are quite dissimilar in their overall metabolism. The effect of conditions and exact nature of biodegradation are subjects of a numerous research studies at the present time. When conditions are favorable, bacterial degradation can occur producing major

changes in crude oil compositions. The bacteria that degrade oils in the reservoir are predominantly aerobic and preferentially consume normal alkanes so that the first indication of incipient biodegradation is a reduced paraffins content. With progressive degradation, all the paraffins are removed, whereas multi-branched compounds, such as the isoprenoids, remain. Ultimately even they are consumed. This sequence of events can be duplicated exactly in laboratory studies [10].

The bacteria that consume oil need free oxygen, water and nutrients for survival. For EOR oil stored in strategic petroleum reserve reservoirs, atmospheric oxygen would be easily available. Also, for oils with appreciable moisture, polysaccharide polymer and petroleum sulfonates surfactant, the bacteria have additional nutrients. Most of the bacteria that consume oil produce their own surfactants to solubilize oil. However, the presence of petroleum sulfonate surfactants and polysaccharide and water as nutrients is likely to enhance the bacterial degradation of oil. Whether the bacterial activity would be enough to cause appreciable changes in the oil quality over 100-200 years time period is unknown and needs further extensive study. A solution to this problem is the addition of biocides to the EOR oil, in which case, the type of biocide to be used and its long term effect on the oil quality would have to be determined.

CONCLUSIONS AND RECOMMENDATIONS

After reviewing the available literature, we conclude that there is no evidence that supports the possibility that the quality of the EOR oil could change appreciably by direct physical and chemical interactions of the oil components with the EOR agents over the time period of storage of this oil in strategic petroleum reserves reservoirs. We also conclude that the bacterial degradation of the EOR oil would be accelerated because of the presence of increased moisture, petroleum sulfonates and polysaccharides in the oil. Over the period of time of interest, whether there could be significant changes in the quality of the oil should be a subject of further investigation. We recommend the following two studies to quantitatively determine the effect of biodegradation on the EOR oil.

- (1) Carry out a thorough literature search on bacterial degradation of oil. Obtain available information on rates of biodegradation as a function of moisture content of oil, salinity and concentration of surfactants (petroleum sulfonates) and polysaccharides in the oil.
- (2) Where information is not available carry out laboratory tests on rates of biodegradation as a function of composition of EOR agents in oil. Based on all of this information derive conclusions on the significance of the effect of biodegradation on EOR oil.

REFERENCES

1. Akstinat, M.H., "Surfactants for EOR Process in High-Salinity Systems: Product Selection and Evaluation", in "Enhanced Oil Recovery", F.J. Fayers, editor, Elsevier, New York, 1981.
2. Barker, C., "Organic Geochemistry in Petroleum Exploration", Am. Assoc. Pet. Geol., Contin. Educ. Course Note Ser., 10, 159, 1979.
3. Barker, C., Chapter 2 - Origin, Composition and Properties of Petroleum, in "Enhanced Oil Recovery, I Fundamentals and Analysis", Donaldson, E.C., Chilingarian, G.V. and Yen, T.F., editors, Elsevier, 1985.
4. Bragg, J.R., Gale, W.W. and McElhannon, W.A., "Loudon Surfactant Flood Pilot Test", in SPE Reprint Series No. 23 - EOR Field Case Histories, Page 196, 1987.
5. Bray, E.E. and Evans, E.D., "Distribution of n-Paraffins as a clue to Recognition of Source Beds", Geochim. Cosmochim. Acta, 22, 2, 1961.
6. Curiale, J.A., "Origin of Solid Bitumens, with Emphasis on Biological Marker Results", Org. Geochem., 10, 559, 1986.
7. Curiale, J.A., Cameron, D. and Davis, D.V., "Biological Marker Distribution and Significance in Oils and Rocks of the Monterey Formation, California", Geochim. Cosmochim. Acta, 49, 271, 1985.
8. Hill, E.C., "Microorganisms-Numbers, Types, Significance, Detection", in "Monitoring and Maintenance of Aqueous Metalworking Fluids", K.W.A. Charter and E.C. Hill, eds., John Wiley and Sons, 1983.
9. Hill, E.C., Chapter 15 - Biodegradation of Petroleum Products, in "Petroleum Microbiology", R.M. Atlas, editor, Macmillan Publishing Company, 1984.
10. Jobson, A., Cook, F.D. and Westlake, D.W.S., "Microbial Utilization of Crude Oil", Appl. Microbiol., 23, 1082, 1972.
11. Khalinov, E.M., Klimushin, I.M., Ferdman, L.I. and Goldberg, I.S., "Geological Problems of Natural Bitumen", in Proc. Eleventh World Petr. Congr., Vol. 2, pp 57-70, Wiley, Chichester.
12. Lake, L.W., Chapter 47 - Chemical Flooding, in "Petroleum Engineering Handbook", H.B. Bradley editor, Society of Petroleum Engineers, 1987.

13. Lake, L.W. "Enhanced Oil Recovery", Prentice - Hall, New Jersey, 1989.
14. Nordli, K.G., Sjoblom, J., Kizling, J. and Stenius, P., "Water-in-Crude Oil Emulsions from the Norwegian Continental shelf 4. Monolayer Properties of the Interfacially Active Crude Oil Fraction", Colloids and Surfaces, 57, 83, 1991.
15. Seifert, W.K. and Moldowan, J.M., "Paleoreconstruction by Biological Markers", Geochim. Cosmochim. Acta, 45, 783, 1981.
16. Tham, M.K. and Lorenz, P.B., "The Role of Crude-oil Components in Surfactant Interaction", U.S. Department of Energy Rep. No. DOE/BETC/R1-83/8 , September, 1983.
17. Widmyer, R.H. and Williams, D.B. , "Performance Evaluation of the Salem Unit Surfactant/Polymer Pilot", in SPE Reprint Series No. 23-EOR Field Case Histories, Page 172, 1987.

APPENDIX A

SUMMARY OF SOME EOR PILOT AND FIELD PROJECTS

Project: El Dorado Field (1976-1985)

Location: Butler County, Kansas

Operator: Cities Service Oil Company

Test type: MP flooding

Materials &

Volume: High Concentration Uniflood (Hegberg pattern)

Pre-flush size	= 0.16 V_p
Micellar slug size	= 0.04 V_p
Surfactant mass Concentration	= 0.04
Polymer Concentration in MB (Mobility buffer)	= 1600 ppm
MB size	= 0.6 V_p
Oil Production Rate	= 5-50 BPD

Low Concentration Shell (Chesney Pattern)

Pre-flush size	= 0.41 V_p
Micellar slug size	= 0.113
Surfactant Concentration	= 0.026
Polymer concentration in MB	= 2000 ppm
MB size	= 0.66 V_p
Oil production rate	= 5-50 BPD

Description: This project compared performance of a high-concentration Uniflood type system with a low concentration Shell system. The overall goal was to compare performance of these two systems under similar reservoir conditions. The Uniflood system gave the same oil productivity as the low concentration system while using only 10% as much water.

Reference: "Enhanced Oil Recovery Field Reports", Society of Petroleum Engineers, 1975-1985.

Project: Bell Creek Unit A (1979-1982)

Location: Carter and Powder River Counties, Montana

Operator: Gary Engineering Corporation

Test type: MP flooding

Materials &

Volume: Pre-flush: 16.4% V_p Slug of alkaline sodium silicate solution
Micellar slug: 3.5% V_p of soluble oil and micellar water containing petroleum sulfonate blend
Polymer slug: 100% V_p of Viscosity graded polyacrylamide polymer solution
Oil Production rate: 100-150 BPD

Description: This project was developed to determine economic feasibility of a surfactant flood after an extremely successful waterflood. A high oil content MP slug preceded by a preflush that contained sodium silicate was used. One of the purposes was to evaluate the sensitivity to reservoir heterogeneities.

Reference: "Enhanced Oil Recovery Field Reports", Society of Petroleum Engineers, (1979-1982)
L.W. Holm, "Design, Performance and Evaluation of the Uniflood Micellar-Polymer Process - Bell Creek Field" in SPE Report series No. 23 - EOR Field Case Histories, page 137, 1987.

Project: Lawry (1977-1979)

Location: Pennsylvania

Operator: Pennzoil

Test type: MP flooding

Materials &

Volume: High concentration Maraflood-type system was used. Preflush size was about 10% V_p and micellar slug size was 9.4% V_p with a surfactant concentration of about 9%.

Description: This project was designed to determine the performance of a surfactant/polymer system in a low-permeability Bradford sand reservoir of Pennsylvania. A high-concentration Maraflood type system was used in this test. The project recovered only a small amount of oil and was not successful. Apparently, surfactant systems are not capable of mobilizing and producing significant amounts of oil in reservoirs with low permeability.

References: G.L. Langnes et al "Waterflooding" chapter 8 in E.C. Donaldson, G.V. Chilingarian and T.F. Yen (editors) "Enhanced Oil Recovery, I Fundamentals and Analysis", Elsevier, 1985.

W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint Series No. 24 Surfactant/Polymer Chemical Flooding -1, page 7, 1988.

Project: North Burbank field (1976-1983)

Location: Osage County, Oklahoma

Operator: Phillips

Test type: MP flooding

Materials &
Volume:

Pre-flush: 30% V_p fresh water and 20% V_p brine.

Micellar slug: 6% petroleum sulfonate, 3% isobutyl alcohol in 0.9% sodium chloride brine.

Mobility buffer: 160 to 2300 ppm polyacrylamide

Oil Recovery: About 50% of residual oil.

Description: This project tested surfactant flooding performance in an oil-wet reservoir. This project used a system containing about 5% active surfactant. It recovered about half the oil anticipated before the test started.

Reference: P.B. Lorenz, J.C. Trantham, D.R. Zornes and C.G. Dodd, "A post-flood Evaluation Test of the North Burbank Surfactant/Polymer Pilot", in SPE Reprint Series No. 23 - EOR Field Case Histories, page 253, 1987.

Project: Wilmington

Location: Long Beach, California

Operator: City of Long Beach, CA

Test type: MP flooding

Materials &
Volume:

High Concentration Maraflood type system was used with surfactant

slug size of about 7% V_p and MB slug size of about 93% V_p .

Description: This project used a Maraflood type high-concentration surfactant system. The objective was to evaluate surfactant flooding performance in an unconsolidated reservoir containing a high-viscosity aromatic crude. The project has been deemed a success and recovered 43% of the oil remaining in place after waterflooding. The temperature of the reservoir was 145°F and the viscosity of the crude was about 35 cp in place. These temperature and viscosity conditions are the highest of any successful MP flood in the US.

Reference: G.L. Langnes et al "Waterflooding" chapter 8 in E.C. Donaldson, G.V. Chilingarian and T.F. Yen (editors) "Enhanced Oil Recovery, I Fundamentals and Analysis", Elsevier, 1985.
W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint Series No. 24 Surfactant/Polymer Chemical Flooding -1, page 7, 1988.

Project: M-1 (initiated 1977)

Location: Robinson, Illinois

Operator: Marathon Oil Company

Test type: MP flooding

Materials & Volume: High Concentrations Maraflood type system was used with surfactant slug size of about 10% V_p and MB slug size of about 105% V_p .

Description: This project, the largest surfactant flooding project in the world, was designed to compare performance on a commercial scale of identical surfactant systems in the same reservoir with different pattern spacing. A Maraflood high-concentration surfactant system was used in this project. Although data on oil recovery was not available, reports indicate successful operation.

Reference: P.B. Lorenz, J.C. Trantham, D.R. Zornes and C.G. Dodd, "A post-flood Evaluations Test of the North Burbank Surfactant/Polymer Pilot", in SPE Reprint Series No. 23 - EOR Field Case Histories, page 253, 1987.

Reference: "Enhanced Oil Recovery Field Reports", Society of Petroleum Engineers (1983-1986)

Project: Coalinga Nose Field

Location: Brea, California

Operator: Union Oil Company of California

Test type: MP flooding

Materials &
Volumes:

Preflush: 50% V_p of Na_4SiO_4 and NaCl in the produced water
Micellar Slug: 4.3% V_p containing 8 wt% of active petroleum sulfonate and cosolvent
MB Slug: A graded bank of polyacrylamide polymer in produced water, with average polymer concentration of 640 ppm.

Description: The test was successful and gave high oil recoveries in initial phases. However, a number of problems were encountered during polymer flood injection. Progress was hampered because of the injectors and producers getting plugged up. This project illustrated the difficulties inherent in applying a slug-type displacement process in a thick formation. The project was terminated in 1986.

Reference: "Enhanced Oil Recovery Field Reports", Society of Petroleum Engineers, (1983-1986).

Project: Salem Unit (1981-1985)

Location: Marian County, Illinois

Operator: Texaco

Test type: MP flooding

Materials &
Volume:

Pre-flush: 19.9% V_p fresh water
101.5 % V_p brine
Surfactant: Witco and Texaco brine tolerant surfactants

Polymer: (sulfonate) 50,000 ppm in 17.9% V_p brine.
 Kelco polysaccharide 250 to 1500 ppm in 80% V_p water.

Oil Recovery: Oil recovery efficiencies ranged from 50% to 75%

Description: The objective was to test a surfactant flood using a brine tolerant formulation to mobilize waterflood residual oil. The test was successful and was able to reduce the oil saturation to below 15% in most cases. As expected, emulsions of varying compositions were produced with the tertiary oil. Through experimentation chemical costs of separation of oil from water were minimized and later nearly eliminated with the introduction of mechanical separation means.

Reference: R.H. Widmyer and D.B. Williams, "Performance Evaluations of the Salem Unit Surfactant/Polymer Pilot", in SPE Reprint Series No. 23- EOR Field Case Histories, page 172, 1987.

Project: Loudon Pilot (1980-1981)

Location: Fayette County, Illinois

Operator: Exxon Company

Test type: MP flooding

Materials & Volume: 0.4 V_p microemulsion containing about 2.3% of a surfactant manufactured by Exxon and some biopolymer, xanthan gum made by Pfizer.
 0.8 V_p polymer drive containing xanthan biopolymer dissolved in brine having lower salinity than that of formation brine. Other chemicals were added to control pH near 5.0.
 Oil recovery of about 60% fo residual oil was achieved.

Description: The high salinity microemulsion system was successful in recovering about 60% of residual oil. Bacterial degradation of xanthan biopolymer caused loss of viscosity in the polymer drive bank.

Reference: J.R. Bragg, W.W. Gale, W.A. McElhannon Jr., O.W. Davenport and M.D. Petrichuk, "Loudon Surfactant Flood Pilot Test", in SPE Reprint Series No. 23, EOR Field Case Histories, page 196, 1987.

Project: 219-R (1975-1976)

Location: Robinson, Crawford County, IL

Operator: Marathon Oil Company

Test type: MP Flooding

Materials &
Volumes:

Fresh water 35% V_p
Micellar slug about 10.3% V_p containing 10% active sulfonate,
75% water 1.5% amyl and butyl alcohol blend and 13.5% unreacted oil.
Polymer slug about 105% V_p , Dow Chemical Company's Pusher-
700, which is partially hydrolyzed polyacrylamide in concentration
from 50-1200 ppm.

Oil recovery: Production increased from 40 BPD to a maximum
of 536 BPD. Final recovery was about 30% of the past waterflood oil
in place.

Description: The project objective was to continue testing the capability of the
micellar-polymer process for recovering oil from a previously water-
flooded reservoir. The project was completed successfully.

Reference: J.C. Howell, R.W. McAtee, W.O. Snyder and K.L. Tonso, "Large-
Scale Field Application of Micellar-Polymer Flooding", in SPE Reprint
Series No. 23, EOR Field Case Histories, page 266, 1987.

Project: North Stanley

Location: Oklahoma

Operator: Gulf Oil Corporation

Test type: Polymer flooding

Materials: Partially Hydrolyzed polyacrylamide

Description: This project used partially hydrolyzed polyacrylamides for the poly-
mer. It was conducted in a sandstone reservoir and has been com-
pleted. The project was reported technically successful, but the
economics were poor.

Reference: W.B. Gogarty, "Enhanced Oil Recovery Through the Use of Chemi-
cals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer
Chemical Flooding - 1, page 7, 1988.

Project: Storms Pool
Location: White County, Illinois
Operator: Energy Resources Co. Inc.
Test type: Polymer flooding
Materials: 23.4% V_p of Pfizer polysaccharide polymer solution
Description: This project used polysaccharides for the polymer. It was conducted in a sandstone reservoir and terminated in June, 1982 because of poor oil recovery. Apparently bacteria destroyed the polymer. The decision to terminate the project was based solely on economic considerations.
Reference: Enhanced Oil Recovery Field Reports. Society of Petroleum Engineers, (1982-83)

Project: Northeast Hallsville Crane Unit
Location: Texas
Operator: Hunt Oil
Test type: Polymer flood
Materials: Partially Hydrolyzed Polyacrylamide
Description: This project used partially hydrolyzed polyacrylamides for the polymer. When completed, the project was reported to have recovered an additional 40% oil above that expected from waterflooding.
Reference: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project: Old Lisbon
Location: Louisiana

Operator: Tenneco

Test type: Polymer flood

Materials: Partially Hydrolyzed polyacrylamide

Description: This project used partially hydrolyzed polyacrylamide for the polymer. This field, one of the largest, is using the near-welbore gel-forming technique. This project is still in its early stages.

References: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project: Mabee

Location: Texas

Operator: Texaco

Test type: Polymer flooding

Materials: Partially Hydrolyzed polyacrylamide

Description: This project used partially hydrolyzed polyacrylamide for the polymer. Texaco appears to be using both gel treatments and a large-PV polymer flood. This project is still in operation.

References: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project: Slaughter

Location: Texas

Operator: Texaco

Test type: Polymer flooding

Materials: Partially hydrolyzed polyacrylamide

Description: This project used partially hydrolyzed polyacrylamide for the polymer. This project is still in operation.

References: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project: Eliasville Caddo

Location: Stephene County, Texas

Operator: Sun E&P Company

Test Type: Polymer Flooding

Materials: Emulsion and flake polyacrylamide polymers

Description: This test was carried out to study the effect of polymer solution viscosity and types of polyacrylamide polymers on oil recovery. The problems encountered in polymer handling were also investigated. The project resulted in a wealth of information.

Reference: W.W. Weiss and R.W. Baldwin, "Planning and Implementing a Large-Scale Polymer Flood", in SPE Reprint Series No. 23, EOR Field Case Histories, page 242, 1987.

Project: Whittier

Location: California

Operator: Chevron Oil Company

Test type: High-pH flooding

Materials: 0.2 Weight % NaOH Solution. 20% V_p slug.

Description: Project was successful, in that significant increase in oil recovery was achieved.

Reference: D.J. Graue and C.E. Johnson, Jr. "Field Trial of Caustic Flooding Process", in SPE Reprint Series Nol 23, EOR Field Case Histories, Society of Petroleum Engineers, 1987.

Project; Wilmington
Location: California
Operator: THUMS
Test type: High-pH flooding
Materials: Na_4SiO_4 0.4 weight %. Slug size 60% V_p .
Description: This test is still in progress.
Reference: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project; Huntington Beach
Location: California
Operator: Aminoil
Test type: High-pH flooding
Materials: Na_4SiO_4 1.0 weight %. Slug size 40% V_p .
Description: This test is still in progress.
Reference: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

Project; Bison basic
Location: Wyoming
Operator: Gulf Oil
Test type; High-pH flooding

Materials: NaOH 0.5 weight %. Slug size 50% Vp.

Description: This test is still in progress.

Reference: W.B. Gogarty, " Enhanced Oil Recovery Through the Use of Chemicals. Part 1." in SPE Reprint series No. 24 Surfactant/Polymer Chemical Flooding - 1, page 7, 1988.

END

**DATE
FILMED**

6 / 1 / 93