DOE/PC/79743-T6

MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS FROM COAL FLAMES

DOE/PC/79743--T6

DE92 013607

Quarterly Technical Progress Report No. 7
Reporting Period: April 1, 1989 - June 31, 1989

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacture, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Prepared for:

U. S. Department of Energy
Pittsburgh Energy Technology Center

Under:

Contract No. DE-AC22-87PC79743

Prepared by:

G. H. Newton
C. Schieber
R. G. Socha
W. D. Clark
J. C. Kramlich

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718-2798

August, 1989

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Section	Page
ABSTRACT.	iii
1.0 INTRODUCTION.	1
2.0 EXPERIMENTAL PROGRAM.	3
3.0 ENGINEERING ANALYSIS.	10
4.0 FUTURE WORK	19
APPENDICES	

ABSTRACT

The principal activities during this quarter involved the global experiments. Ash was sampled from a number of coals (of varying rank) as a function of oxygen concentration. Proximate analyses of the coals were performed.

Analyses of the data were performed using the breakup model. When fitting the data with the breakup model, higher rank coals were found to require fewer ash particles per coal particle than the lower ranked coals. Deviations of the measured size distribution from the simple breakup model were examined.

During this quarter preparation for the mechanistic experiments was begun. This work involves cleaning and sizing three coals and measuring the particle size distribution of ashes from these various cuts of coals. This work will continue during the next reporting quarter.

1.0 INTRODUCTION

The overall objectives of this project are to provide a basic understanding of the principal processes that govern fine particulate formation in pulverized coal flames. This understanding is to be used to develop a model (or models) which will predict the yield and size distribution of fine particulate matter as a function of coal type, coal processing, and combustion conditions. The goal of the model is to provide an engineering tool that will enable the practitioner to estimate the consequences of design decisions and fuel selection on the fine particulate yield. The practitioner can then make rational decisions regarding the required technology and costs associated with effluent cleanup while still in the design phase.

Long term work is presently supported by PETC that will develop detailed models of the entire mineral transformation process. The present work is directed toward global models of behavior which will become available on a shorter time frame and will be immediately usable in engineering activities.

Particles in the 0.5-10.0 μm size band are of interest for several reasons. First, a considerable portion of the fly ash generated in pulverized coal combustion falls within this size range. Particulate control devices, in particular electrostatic precipitators, are at their least efficient in this size band. Also, particles in this size range are most efficiently collected within the alveolar passages of the human lung. In coal combustion, a considerable portion of the heavy, toxic metals are vaporized within the flame. As the furnace gases cool, these metals will condense on the available surface area. Since most of the surface area is present on the smaller particles, they will become enriched in these toxic metals. Thus, those particles that are deposited in the alveoli may be coated with toxic compounds and create a health hazard that is well beyond the toxic material proportion in the original mineral matter.

Finally, the mechanism by which this fine fly ash is formed is not yet clear. Obviously, predicting the yield will require some definition of the dominant mechanisms. Also, the manner in which these mechanisms respond to

differing coal types and combustion conditions will have to be understood to make predictions. The project objective is being accomplished through a combination of literature research, experimentation, and model development activities. The program tasks include:

Task 1. Literature review and program plan.

Task 2. Engineering analysis.

Task 3. Experimental program.

Task 4. Reporting.

Task 1 has been completed. This report describes work performed under Tasks 1 and 2 during the period from April 1, 1989 through June 1, 1989. The principal activity during this period involved the isothermal experimental system. Ash from a number of coals were sampled as a function of oxygen concentration and analyzed for particle size. The resultant data was analyzed with the breakup model and the breakup number correlated against coal type and coal makeup.

2.0 EXPERIMENTAL PROGRAM

The experimental portion of this project consists of a study of the fundamental mechanisms at laboratory scale, followed by a process simulation study conducted at the bench-scale. The experimental program was divided into two phases:

- Global experiments which are designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter. This task is complete.
- Mechanistic experiments which focus on providing a quantitative evaluation of the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter.

Testing is performed in the Isothermal Reactor (ITR) which is illustrated in Figure 2-1. The ITR consists of a 10 cm diameter ceramic tube mounted in a three-zone electric furnace. The high temperature gas flow is supplied by a gas flame fired in the side chamber at the top of the reactor. The furnace is capable of operating at temperatures up to 1500°C.

Particle size distributions for particles greater than approximately 2 μm were analyzed on a Malvern 2600 HSD laser diffraction particle size analyzer. Coal size distributions were measured by pneumatically spraying the coal in front of the instrument Fourier transform lens. Analysis of the ash samples were performed by suspending the ash in a surfactant solution within a glass sample cell. The ash concentration could be adjusted to obtain the optimum signal. The sample cell was then placed in front of the instrument Fourier transform lens and the ash particle size distribution measured.

2.1 Results

Testing during this reporting period concentrated on sampling ash from a large number of coals. The coals tested to date are listed on Table 2-1 along

with the conditions they were tested at. The measured particle size distributions for these coals and the resultant ashes are attached in Appendix A. Proximate analyses of these coals, given in Table 2-2, were performed by Hazen Research of Boulder, Colorado.

In addition to the above, work has begun in preparation of the mechanistic experiments. The Utah and Beulah coals were sent to Hazen which performed a froth flotation process which involves a succession of separation steps. The procedure is illustrated in Figure 2-2. The results of this process are given in Table 2-3. The Utah Coal was successfully cleaned with an 80% cut of the coal produced which had an 2.6% ash content (2nd cleaner concentrate). In general, the cleaned cuts of Utah coal had lower ash contents while the "dirtier" cuts had larger particle sizes. The particles size distributions of these cuts are given in Appendix B. The Beulah Coal, however, could not be separated by this process. All cleaner cuts had approximately the same ash content. This may indicate that its mineral matter is uniformly distributed throughout the coal matrix.

Table 2-1. Coals tested to date.

Coal	Coal Type	Temperature	% Oxygen
Utah	Bituminous	1100°C 1200°C 1350°C	10 10, 20, 25.5, 30 20
Illinois No. 6 ¹	Bituminous	1200°C	20, 30
Illinois ²	Bituminous	1200°C	10, 20, 30
Australian Bit. #1	Bituminous	1200°C	20, 30
Australian Bit. #2	Bituminous	1200°C	20, 30
Australian Bit. #3	Bituminous	1200°C 1350°C	20, 30 20, 30
Australian Bit. #4	Bituminous	1200°C 1350°C	20, 30 20, 30
Canadian Bit. (Cleaned)	Bituminous	1200°C	20, 30
U.S. Bit. (Low S)	Bituminous	1200°C	20, 30
Indonesian Bit.	Bituminous	1200°C	20, 30
62% Illinois/ 38% Kentucky ²	Bituminous/ Bituminous	1200°C	10, 20, 30
Eagle Butte ¹	Subbituminous	1200°C	20, 30
Big Brown	Subbituminous	1200°C	20, 30
Beulah ¹	Lignite	1200°C 1350°C	20, 30 30

1 - PSI Coals

2 - Clean Coal Technology Coals

Table 2-2. Properties of Coals Tested

Coal	Coal Type	% Ash ³	% H ₂ O ³	% Vol ³	BTU/lb (dry)
Utah	Bit.	6.27	3.91	40.1	13,202
Illinois No. 6 ¹	Bit.	8.73	11.98	33.5	12,312
Illinois ²	Bit.	11.77	4.13	34.5	12,217
Australian Bit. #1	Bit.	16.28	1.41	31.4	12,536
Australian Bit. #2	Bit.	16.66	1.67	26.8	12,533
Australian Bit. #3	Bit.	11.96	2.70	22.0	13,032
Australian Bit. #4	Bit.	13.53	3.63	25.7	12,412
Canadian Bit. (Cleaned)	Bit.	6.92	0.74	16.8	13,804
U.S. Bit. (Low S)	Bit.	12.61	8.12	36.8	12,834
Indonesian Bit.	Bit.	1.61	3.54	40.0	12,384
62% Illinois/ 38% Kentucky ²	Bit./ Bit.	8.67	9.31	35.2	11,762
Eagle Butte ¹	Subbit.	5.03	24.11	32.9	11,735
Big Brown	Subbit.	14.52	10.38	39.6	10,728
Beulah ¹	Lignite	10.50	28.26	29.5	10,169

* - Incomplete Burn

1 - PSI Coals

2 - Clean Coal Technology Coals

3 - As Received

● Utah Bituminous Coal

Figure 2-2. Process for cleaning Utah coal.

Table 2-3. Results from Coal Cleaning.

	% Wt. (AR)	% Ash Content (Dry Basis)	MMD (μ m)
<u>Utah Coal</u>			
First Process:			
Rougher Tail	5.41	47.66	
1 st Cleaner Tail	14.87	13.26	100
2 nd Cleaner Conc.	78.53	2.59	30
2 nd Cleaner Tail	1.38	11.36	65
Second Process:			
Rougher Tail	32.45	12.66	85
1 st Cleaner Tail	5.81	9.11	45
2 nd Cleaner Conc.	60.64	2.41	30
2 nd Cleaner Tail	1.13	6.24	100
<u>Beulah Coal</u>			
First Process:			
Rougher Concentrate	49.23	13.40	45
Rougher Tailing	50.77	14.94	70
Second Process:			
Rougher Tail	73.19	14.94	65
1 st Cleaner Tail	17.42	13.44	80
2 nd Cleaner Conc.	5.84	11.49	25
2 nd Cleaner Tail	3.55	13.58	50

3.0 ENGINEERING ANALYSIS

Analysis of the data was performed with the breakup model. According to the breakup model, the ash size distribution is related to the coal size distribution by:

$$f_a(d) = R_c(d) \cdot f_c(d)$$

where $R_c(d)$ is the ratio of the diameter of the ash particle to the diameter of the parent coal particle. If $R_c(d)$ is assumed to be constant as a function of coal particle size, it is given by:

$$R_c = \left[\frac{x_a/\rho_a n}{x_m/\rho_m + x_w/\rho_w + (1 - x_m - x_w)/\rho_o} \right]^{1/3}$$

where: x = mass fraction in coal;
 ρ = density;
 n = number of ash particles resulting from a single coal particle;

and the subscripts refer to:

a = ash;
 m = mineral matter in coal;
 w = water; and
 o = organic phase in coal.

The procedure for finding the breakup number, n , is illustrated in Figure 3-1 for the Utah bituminous coal. The line labeled breakup number 1 is the distribution which would be expected if one ash particle was produced by one coal particle. This breakup number, however, produces a distribution which is larger than the measured distribution of this ash. The breakup number was then adjusted until the predicted mass mean diameter matched the measured mass mean diameter (approximately 80 μm) which yielded a breakup number of five. This was done for

Figure 3-1. Size distributions for raw Utah coal and ash, and breakup model predictions for two breakup numbers.

all of the coals tested under the global experiments (see Appendix C). The breakup numbers required to fit the data are given in Table 3-1.

Correlations between the breakup number and various coal properties are shown in Figure 3-2. The lower rank coals generally had a higher breakup number while the higher rank coals had lower breakup numbers. (Although the breakup number increased with moisture content, this is not significant since moisture content is generally a function of coal rank.) This dependence of breakup number on rank has been correlated with the structural behavior of coal during devolatilization. The higher rank coals tend to form more plastic masses during devolatilization and therefore have little macroporosity development during char combustion. The lower rank coals, however, tend to develop a very high surface area structure during char combustion that leads to extensive pore development. A highly porous char tends to break into several daughter particles as the pores coalesce. Each daughter char particle will carry its associated mineral matter away with it, and after each daughter particle has burned out, its included mineral matter will coalesce into a single molten ash droplet.

Three types of deviations from the breakup model's predictions were observed. In Figure 3-3 the model predictions for ash from the Australian Bituminous #2 were made with the minimum breakup number allowed, 1. At particle sizes larger than the mass mean diameter (approximately 10 μm) the ash sampled at 30% oxygen and especially the ash sampled at 20% oxygen had measured particle size distributions larger than could be predicted. The ash smaller than the mass mean diameter fit the data fairly well. This type of deviation could result from incomplete combustion of the larger particles. To determine if this was true, the ash samples were sieved with a 25 μm screen and analyzed for carbon content. The results given in Table 3-2 show that ash larger than 25 μm sampled at 20% oxygen had a substantially greater carbon content than did the smaller particles.

The second type of deviation occurred for the Smokey River (Figure 3-4) coal. The predicted ash size distributions shown in Figure 3-4, which were performed with the minimum breakup number, 1, were substantially smaller than the measured ash particle size distributions. This could also result from in-

Table 3-1. Number of Ash Particles per Coal Particle
Required to Fit the Data.

Coal	Coal Type	Temp.	%O ₂	Breakup Number
Utah	Bit.	1200°C	10	3.1
			20	1.8
			26	1
			30	4.6
		1350°C	20	1
			30	2.1
Illinois No. 6	Bit.	1200°C	20	1
			30	1
Illinois (Hennepin)	Bit.	1200°C	10	2.7
			20	3.5
			30	2.2
Australian Bit. #1	Bit.	1200°C	20	2.9
			30	5
Australian Bit. #2	Bit.	1200°C	20	1
			30	1
Australian Bit. #3	Bit.	1200°C	20	1
			30	1
Australian Bit. #4	Bit.	1200°C	20	5
			30	5
Canadian Bit. (Cleaned)	Bit.	1200°C	20	1
			30	1
62% Illinois/ 38% Kentucky	Bit./ Bit.	1200°C	10	1
			20	6
			30	6
Eagle Butte	Subbit.	1200°C	20	5
			30	6
Big Brown	Subbit.	1200°C	20	7
			30	8
Beulah	Lignite	1200°C	20	11
			30	16

Figure 3-2. Correlation of breakup number with various coal properties.

Figure 3-3. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

Figure 3-4. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

complete combustion of the coal. As with the Australian Bituminous #2, however, only the larger ash particles would be larger than predicted as the smaller coal particles would be expected to burn completely. When this coal was fed to the ITR there were problems with the coal sticking together and plugging the feed lines. If agglomerates were formed when the coal was fed to the reactor, then ash from each coal particle in the agglomerate may have coalesced with ash from other coal particles in the agglomerate and ash particles larger than those predicted by the breakup model would form.

The third type of deviation of the model from the measured ash size distributions is illustrated in Figure 3-5. This type of deviation occurred for a number of the coals tested. The model predictions fit the ash size distributions fairly well except at the smaller size fractions where it over predicts the amount of ash. It is believed that this results from an inability to disperse ash particles under 2 μm in the surfactant solution when preparing the ash for particle size analysis.

Table 3-2. Carbon Content of Australian Bit. #2 Ash

% O ₂	Size (μm)	%C
20	>25	14.3
20	<25	2.7
30	>25	3.9
30	<25	1.5

Figure 3-5. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

4.0 FUTURE WORK

During the next reporting period the mechanistic experiments will begin. These will involve cleaning three coals (Utah, Illinois, and Beulah) into varying degrees of cleaned cuts, separating the cleaned cuts into a number of size fractions, burning the various cuts in the ITR, and then measuring the resultant ash size distributions. This will allow the source of the fine particulate matter to be determined as a function of mineral matter content and particle size of the coal.

APPENDIX A

Measured Particle Size Distributions of Coals and Ashes

APPENDIX B

Predicted Particle Size Distributions of Cleaned Coals

Measured coal size distribution of first cleaner tail, first process.

Measured coal size distribution of second cleaner concentrate, first process.

Measured coal size distribution of second cleaner tail, first process.

Measured coal size distribution of rougher tail, second process.

Measured coal size distribution of first cleaner tail, second process.

Measured coal size distribution of second cleaner concentrate, second process.

Measured coal size distribution of second cleaner tail, second process.

Measured coal size distribution of rougher tailing, first process.

Measured coal size distribution of rougher tail, second process.

Measured coal size distribution of first cleaner tail, second process.

Measured coal size distribution of second cleaner concentrate, second process.

Measured coal size distribution of second cleaner tail, second process.

APPENDIX C

Predicted Particle Size Distributions of Ashes

END

**DATE
FILMED**

8 / 19 / 92