APR 26 1993

Room E40-451, 77 Massachusetts Ave.
Cambridge, MA 02139-4307
Tel.: (617) 253-3433
Fax: (617) 253-8013
April 15, 1993

Energy Laboratory
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139-4307

DOE/PC/89773--12

DE93 013062

Dr. Philip M. Goldberg
Project Manager
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, Pennsylvania 15236

Re: DOE/PETC-MIT Grant No. DE-FG22-89PC89773, "Coal Plasticity at High Heating Rates and Temperatures," MIT PI's Professor J.B. Howard and Dr. W.A. Peters

Dear Phil:

Enclosed please find three (3) copies of the twelfth technical progress report for the above Grant.

With best regards,

Sincerely,

William A. Peters, Ph.D.
Principal Research Engineer;
Associate Director for Fuels
and Environmental Research

WAP/alc

cc: J. Augustine, PETC (1)
S. Gerjarusak (1)
J.B. Howard (1)
M. Keene, PETC (1)
Office of Technology Transfer, PETC (1)

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

(FE-MIT-89773-12)

Coal Plasticity at High Heating Rates and Temperatures

Twelfth Technical Progress Report

First Quarter: January 1 1993-March 31 1993

Sarakorn Gerjarusak, William A. Peters, and Jack B. Howard

**Energy Laboratory and Department of Chemical Engineering
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Submitted to the United States Department of Energy
Pittsburgh Energy Technology Center
Attention: Dr. Phillip M. Goldberg**

**PREPARED FOR THE UNITED STATES DEPARTMENT OF ENERGY
Under Contract No. DE-FG22-89PC-89773
Date Submitted: April 1993**

"US/DOE Patent Clearance is not required prior to the publication of this document."

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

The results of the multiple independent parallel reaction (MIPR) kinetics model are reported and discussed. The MIPR model's results agree well with the data. The effects of holding temperature, heating rate, and coal type on plasticity are displayed by the model. However, the model does not address the secondary reactions forming higher molecular weight liquid initial, hypothesized to be responsible for the initial rise in viscosity during solidification. The average standard error of estimates for the plastic period and maximum plasticity are 0.13 s and 317 Pa•s, respectively. These values are comparable to the measurement resolution of the plastometer (0.1 s and ± 200 Pa•s).

Introduction

From the suspension modeling results, a two phase model will be used to determine metaplast concentration from apparent viscosity of different coals (Gerjarusak et al., 1992). In analyzing the plasticity kinetics of coal, a concentrated suspension model (Frankel and Acrivos, 1967) has been chosen to relate the viscosity of molten coal to the metaplast concentration:

$$\mu/\mu^* = (9/8)/[(\frac{1-M}{1-M_c})^{-1/3} - 1] \quad 1)$$

where μ^* is the viscosity of the solids-free liquid and M is the intraparticle inventory of softened material (metaplast), having the critical value M_c , at which μ goes to ∞ . At this critical value, the liquid fraction is insufficient to separate the solid particles. The number ranges from .36 to 0.25 for close packing spheres and 0.20 to 0.10 for close packing rods. The solid elements in the coal sample are expected to be more like thin slabs (lamellae) than spheres (Fong et al., 1985). Therefore, to be representative of these ranges, the number for M_c was chosen arbitrarily to be 0.20. In addition, it is seen from Fong's pyridine extractable data that coal only starts to soften when $M > 0.20$ (Fong, 1986). From this equation, one can calculate the transient metaplast inventory, $M(T,t)$, from the plasticity data, $\mu(T,t)$, or vice versa.

The multiple independent parallel reaction model is then used to describe the metaplast generation and depletion steps. In the generation step, physical melting of coal is also incorporated. Using a nonlinear least squares regression routine (DUNLSF by IMSL),

the activation energy and its variance for each step are fitted to the experimental data. The modeling results are then compared to the experimental results.

Multiple Independent Parallel Reaction Kinetics

With the need for a model which describes the plasticity and metaplast kinetics more realistically, the multiple independent parallel reaction (MIPR) kinetics model will be used in the proposed studies. The MIPR model has been used widely by previous students in combustion at MIT to describe kinetics of weight loss and of tar production during coal pyrolysis (Anthony, 1975, Ko, 1988, and Griffin, 1989). The model is described in detail elsewhere (Anthony, 1975 and Howard, 1981). For the proposed studies, all the reactions involved in the plasticity kinetics and metaplast generation and destruction will be modeled using MIPR. For an irreversible, first-order reaction:

the rate equation and its solution are:

$$dA/dt = -k_A A \quad 3)$$

$$A = \exp\left(-\int_0^t k_A dt\right) \quad 4)$$

where A is the amount of A at time t and k_A is the rate constant. Using the MIPR model:

$$A = A_1 + A_2 + A_3 + \dots + A_n = \sum_{i=1}^n A_i \quad 5)$$

$$dA_i/dt = -k_{A_i} A_i, \quad i = 1, 2, 3, \dots, n \quad 6)$$

$$A_i = \exp\left(-\int_0^t k_{Ai} dt\right) \quad 7)$$

$$k_{Ai} = k_{0Ai} \exp(-E_i/RT) \quad 8)$$

where i denotes a particular reaction i , k_{0Ai} and E_i are respectively the preexponential factor and activation energy for reaction i . Assuming that all the reactions have the same preexponential factor ($k_{0Ai}=k_{0A}$) and that the number of reactions are large enough to permit the activation energies to be expressed as a normal distribution, $F(E)$:

$$A = \int_0^\infty \exp\left\{-k_{0A} \cdot \int_0^t \exp(-E/RT) dt\right\} \cdot F(E) dE \quad 9)$$

Following Anthony et. al. (1975) one would choose $F(E)$ to be a Gaussian such that:

$$F(E) = (2\pi\sigma_E^2)^{-1/2} \cdot \exp\left\{-(E_0 - E)^2/2\sigma_E^2\right\} \quad 10)$$

where E_0 and σ_E^2 are respectively the mean activation energy and its variance.

The rate constant expression at any time t is:

$$\frac{k}{k_{0A}} = \frac{\int_0^\infty \exp\left\{(-k_{0A}) \cdot \int_0^t \exp(-E/RT) dt - (E_0 - E)^2/2\sigma_E^2 - E/RT\right\} dE}{\int_0^\infty \exp\left\{(-k_{0A}) \cdot \int_0^t \exp(-E/RT) dt - (E_0 - E)^2/2\sigma_E^2\right\} dE} \quad 11a)$$

or when the temperature-time history is linear (constant heating rate = m_h), at any temperature T (Howard et al., 1986):

$$\frac{k}{k_{0A}} = \frac{\int_0^{\infty} \exp\{(-k_{0A}/m_h) \cdot \int_0^T \exp(-E/RT) dT - (E_0 - E)^2/2\sigma_E^2 - E/RT\} dE}{\int_0^{\infty} \exp\{(-k_{0A}/m_h) \cdot \int_0^T \exp(-E/RT) dT - (E_0 - E)^2/2\sigma_E^2\} dE} \quad 11b)$$

When the temperature is constant:

$$\frac{k}{k_{0A}} = \frac{\int_0^{\infty} \exp\{-k_{0A}t \cdot \exp(-E/RT) - (E_0 - E)^2/2\sigma_E^2 - E/RT\} dE}{\int_0^{\infty} \exp\{-k_{0A}t \cdot \exp(-E/RT) - (E_0 - E)^2/2\sigma_E^2\} dE} \quad 12)$$

Only four parameters ($A(t=0)$, E_0 , σ_E^2 , k_{0A}) are required to correlate the MIPR model to kinetics data for a reaction contributing to plasticity and/or metaplast generation and depletion data.

In addition, the values E_0 and σ_E^2 also light on interesting features of the reaction set of interest including its "chemical diversity" as expressed by the range of activation energies for which reactions make significant contributions to the rate process of interest. The variance of $F(E)$ determines the spread around the mean activation energy. A big spread implies that the overall reaction consists of a large number of independent reactions in parallel. A small spread means that the number of independent reactions is few. Further,

one can compare the mean activation energy value of the reaction of interest to activation energy values found in other studies of coal devolatilization to gain insights on the possible types of reactions occurring, e.g. cracking.

Description of Metaplast Reaction Kinetics

The following sequence of kinetic steps are used to determine the intraparticle metaplast inventory, $M(T,t)$:

$$M^* = C_r(t) + M_m(t) + M(t) + P(t) \quad 14)$$

where M^* is the maximum amount of metaplast that can be formed, $C_r(t)$ and $M_m(t)$ are the remaining amount of coal that can react and melt to form metaplast, respectively. $P(t)$ is the product from the pyrolysis (i.e. light gases, tar, and coke).

$$dM/dt = -(dC_r/dt + dM_m/dt + dP/dt) \quad 15a)$$

$$dM/dt = r_m + r_g + r_d \quad 15b)$$

where r_m is the rate of physical melting, r_g is the rate of metaplast generation, and r_d is the rate of metaplast depletion.

For a Gaussian distribution of melting points, the rate of physical melting, r_m , is given to a very good approximation by:

$$-dM_m/dt = r_m = \{ M_{m0}m_h/(2\pi\sigma_m^2)^{1/2} \} \cdot \exp\{ - (T_m-T)^2/2\sigma_m^2 \} \quad 16)$$

M_{m0} is the amount of meltable components (e.g. pyridine extractables) in the parent coal, m_h is the heating rate, and T_m the mean melting temperature of coal. The quantity r_m is thus described as the product of M_{m0} , m_h , and the melting point distribution. Since coal is assumed to melt over a narrow range of temperature, the melting point distribution is estimated to be normal, with a mean $T_m = 600$ K and the variance $\sigma_m^2 = (30K)^2$ (Fong et. al., 1985c). The quantity M_m is easily found by integrating $-r_m$ over time, knowing the $T(t)$ profile.

Defining M_r as the amount of metaplast formed by the pyrolysis of C_r , the metaplast generation step, r_g , (excluding melting) is given by:

$$-dC_r/dt = r_g = dM_r/dt \quad 17)$$

Defining M_{ri} as the amount of M_r formed by an independent reaction i , assuming the rate constant (k_g) is the same for all reactions:

$$dM_{ri}/dt = k_g(M_{ri}^* - M_{ri}) \quad 18)$$

$$\frac{M_{ri}^* - M_{ri}}{M_{ri}^*} = \exp\left\{ \int_0^t -k_{gi} dt \right\} \quad 19)$$

$$\frac{M_r^* - M_r}{M_r^*} = \int_0^\infty \exp\left\{ \int_0^t -k_{gi} dt \right\} \cdot F(E_g) dE_g \quad 20)$$

$$F(E_g) = (2\pi\sigma_{Eg}^2)^{-1/2} \cdot \exp\{ - (E_{g0} - E_g)^2/2\sigma_{Eg}^2 \} \quad 21)$$

$M_r^* = M^* - M_{mo}$, the maximum amount of metaplast produced by chemical reaction of the parent coal. Using the low temperature (< 900 K) transient viscosity data to find $M(t)$, $M_r(t) = M(t) - M_m$, in which M_m is calculated from integrating $-r_m$ over time. The generation rate constant (k_g) is found by fitting the parameters M_r^* , the mean activation energy (E_{go}) and its variance (σ_{Eg}^2) to data on $M_r(t)$ for various temperature-time histories. The preexponential factor of k_g is fixed at 10^{13} s^{-1} to generate a single set of kinetics parameter. Several sets of best-fitted parameters can be found with markedly different values of k_{go} , each set being a local minimum of the M_r vs. ($k_{go}, E_{go}, \sigma_g, M_r^*$) parameter space.

Defining P_i as the amount of P formed by an independent reaction i, assuming the rate constant (k_d) is the same for all reactions, the metaplast depletion step is given by:

$$dP_i/dt = -k_d(P_i^* - P_i) \quad 22)$$

$$\frac{P_i^* - P_i}{P_i^*} = \exp \left\{ \int_0^t -k_{di} dt \right\} \quad 23)$$

$$\frac{P^* - P}{P^*} = \int_0^\infty \exp \left\{ \int_0^t -k_{di} dt \right\} \cdot F(E_d) dE_d \quad 24)$$

$$F(E_d) = (2\pi\sigma_{Ed}^2)^{-1/2} \cdot \exp \{ - (E_{do} - E_d)^2 / 2\sigma_{Ed}^2 \} \quad 25)$$

P^* is the maximum amount of products that can be produced, $P^* = M^* = M_r^* + M_{mo}$. High temperature (>1000 K) transient viscosity data is used to calculate $M(t)$ and thus $P(t) = M^* - M$, assuming that the generation step has completed. The depletion rate constant (k_d) is found by fitting the mean activation energy (E_{do}) and its variance (σ_{Ed}^2)

Table 1: MIPR BEST-FITTED KINETICS PARAMETER VALUES^c

COAL	(dmmf)		(Kcal/mole)			
	Mmelt	M*	Eg	σ_g	Ed	σ_d
IL hvb	.28 ^a	.41	42.7	0.4	59.0	8.0
PT hvb	.30 ^a	.48	43.0	0.4	60.1	7.6
WV hvb	.30 ^b	.45	42.8	0.3	60.0	7.5
UF mvb	.07 ^a	.35	37.7	0.3	63.2	5.5
PO lvb	.01 ^a	.29	38.1	0.3	59.2	4.4

a: data from Snape and Bartle, 1989

b: no data available, estimated to be approximately equal to that of Pittsburgh No. 8 coal.

c: Best-fitted as described in text, beginning with data at 400 K/s and different holding temperatures.

Then, if needed, further refine the fit using the data at 200 K/s and 800 K/s.

$$k_{go} = k_{do} = 10^{13} \text{ s}^{-1}$$

Coal Plasticity at Different Holding Temperatures Illinois No. 6 hvb Coal

Figure 1a: Smooth lines: Apparent viscosity of Illinois No.6 hvb coal at different holding temperatures predicted from MIPR model described in text; Heating rate = 400 K/s; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Holding Temperatures Pittsburgh No. 8 hvb Coal

Figure 1b: Smooth lines: Apparent viscosity of Pittsburgh No.8 hvb coal at different holding temperatures predicted from MIPR model described in text; Heating rate = 400 K/s; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Holding Temperatures Lewis-Stockton hvb Coal

Figure 1c: Smooth lines: Apparent viscosity of Lewis-Stockton hvb coal at different holding temperatures predicted from MIPR model described in text; Heating rate = 400 K/s; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Holding Temperatures Upper Freeport mvb Coal

Figure 1d: Smooth lines: Apparent viscosity of Upper Freeport mvb coal at different holding temperatures predicted from MIPR model described in text; Heating rate = 400 K/s; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Holding Temperatures

Pocahontas No. 3 lvb Coal

Figure 1e: Smooth lines: Apparent viscosity of Pocahontas No.3 lvb coal at different holding temperatures predicted from MIPR model described in text; Heating rate = 400 K/s; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Heating Rates Illinois No. 6 hvb Coal

Figure 2a: Smooth lines: Apparent viscosity of Illinois No.6 hvb coal at different heating rates predicted from MIPR model described in text; Holding temperature = 1098 K; Pressure = 1 atm helium. Symbols: Experimental data.

Figure 2b: Smooth lines: Apparent viscosity of Pittsburgh No.8 hvb coal at different heating rates predicted from MIPR model described in text; Holding temperature = 1098 K; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Heat Rates Lewis-Stockton hvb Coal

Figure 2c: Smooth lines: Apparent viscosity of Lewis-Stockton hvb coal at different heating rates predicted from MIPR model described in text; Holding temperature = 1098 K; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Heating Rates Upper Freeport mvb Coal

Figure 2d: Smooth lines: Apparent viscosity of Upper Freeport mvb coal at different heating rates predicted from MIPR model described in text; Holding temperature = 1098 K; Pressure = 1 atm helium. Symbols: Experimental data.

Coal Plasticity at Different Heating Rates Pocahontas No. 3 lvb Coal

Figure 2e: Smooth lines: Apparent viscosity of Pocahontas No.3 lvb coal at different heating rates predicted from MIPR model described in text; Holding temperature = 1098 K; Pressure = 1 atm helium. Symbols: Experimental data.

to high temperature data on $P(t)$ for different holding temperatures. The preexponential factor of k_d is fixed at 10^{13} s^{-1} , again to generate only one set of kinetics parameter.

With each component of the metaplast reaction kinetics defined, metaplast concentration, $M(t)$, is found by:

$$M(t) = M_r + M_m - P \quad 26)$$

The best fitted parameters (M_r^* , E_{go} , σ_g , E_{do} , and σ_d) are shown on Table 1. The calculated apparent viscosity of different coals is shown in Figures 1 a-e for constant heating rate runs and in Figures 2 a-e for different heating rate runs.

Discussion Kinetics Modeling Results

The calculated apparent viscosity of different plastic coals agrees well with the experimental data. The standard error of estimate (SEE) is calculated for plastic period and minimum apparent viscosity for all runs of each coal:

$$SEE = \sum_{j=1}^n \left\{ \frac{(\text{experimental value}_j - \text{predicted value}_j)^2}{n-k} \right\}^{1/2} \quad 27)$$

where n is the number of data points and k the number of best fitted parameters used in the model. The average standard error of estimate (ASEE), either for the plastic period or the minimum apparent viscosity, is found by averaging the SEE's for all five coals. Previously, the SEE is calculated for the tar yield corresponding to a specific temperature-time history (Ko, 1988). For each temperature-time history in this work, however, a set of many viscosity data points is obtained. For each temperature time

history, the pertinent results are the minimum apparent viscosity and the plastic period. Therefore, the SEE for all data points of each run is not calculated. Only the SEE's for the minimum apparent viscosity and plastic period are calculated for each specific temperature-time history. The SEE's and ASEE's are listed in Table 2. The ASEE's for the plastic period and the minimum apparent viscosity are 0.13 s and 317 Pa•s, respectively. These values are comparable to the measurement resolution of the plastometer (0.1 s and ± 200 Pa•s).

In general, the model data fit the experimental results well, except for predicting that lower heating rate (200 and 400 K/s) apparent viscosity begins to increase at a later time than that observed. At lower heating rates, the experimentally observed viscosity during resolidification increases slowly at approximately 1000 K, then increases very rapidly when the holding temperature of 1098 K. This earlier rise in viscosity is hypothesized to be caused by secondary reactions, which the model does not address, degrading the plasticizing power of the metaplast by forming higher molecular weight liquid.

The activation energy values of the generation step for hvb are higher than those for mvb and lvb coals. There are two processes for forming metaplast: physical melting and chemical reaction. While metaplast generation for mvb and lvb coals is mostly due to kinetics, for hvb coals it is mostly due to melting. If two coals have comparable plastic behaviors, the one with a lower metaplast formation from physical melting maintains a comparable metaplast inventory by having a higher metaplast formation from chemical reaction. Lower activation energy values (i.e. higher chemical reaction rates) for mvb and lvb coals compensate for lower meltable component (i.e. lower rate of melting). The standard deviation values of E_g are very small, again supporting the interpretation that chemical generation of metaplast occurs by a small number of or even one pathway. Thus the sometimes observed phenomenon of higher product yield at higher heating rate

Table 2: Standard Error of Estimate for MIPR Kinetics Model^a

<u>Coal</u>	<u>SSE(Plastic Period). s</u>	<u>SSE(Min Viscosity). Pa•s</u>
Illinois No. 6 hvb	0.14	203
Pittsburgh No. 8 hvb	0.14	279
Lewiston-Stockton hvb	0.07	395
Upper Freeport mvb	0.21	424
Pocahontas No. 3 lvb	0.07	283
Average	0.13	317

a: see equation 27 in text.

from pathways with high activation energies is expected to be of little importance here. By modeling the metaplast generation kinetics as a single reaction, the modeling results are essentially the same. However, the SEE's and ASEE's improve by 18%, since the number of fitted parameters (k) decreases from 5 to 4, with the removal of σ_g from the parameter space.

The activation energy values of the generation step for all coals are about the same except for the mvb coal which is slightly higher. Since Upper Freeport mvb coal solidifies at much later time than other coals, its depletion step's activation energy is higher (implying a lower rate of depletion kinetics). The standard deviation of E_d decreases with increasing rank, ranging from 4.4 kcal/mole for Pocahontas No. 3 lvb coal to 8.0 kcal/mole for Illinois No. 6 hvb coal (Table 1). The greater graphitization of parent coal structures with increasing rank is supported by the σ_d results. Higher rank coals have a more uniform molecular structure, and therefore their liquid metaplast should be made up of similar molecules. These similar molecules react by more similar pathways, thus the lower σ_d , indicating that there are fewer independent reactions contributing to metaplast depletion. Hvb coals have higher σ_d values, implying that the depletion reactions involve a large number of different reactions.

Future Work

The background, experimental techniques, experimental results, and modeling results of this work are being put together as Sarakorn Gerjarusak's Ph.D. thesis. The Ph.D. defense is expected to take place in May of 1993.

Literature Reference

- Anthony, D. B., Howard, J. B., Hottel, H. C., and Meissner, H. P., "Rapid Devolatilization of Pulverized Coal," Fifteenth Symposium (International) on Combustion, pp. 1303-1317, The Combustion Institute, Pittsburgh, (1975).
- Fong, W. S., "Plasticity and Agglomeration in Coal Pyrolysis," Sc.D. Thesis, Department of Chemical Engineering, MIT, Cambridge, MA, 1986.
- Frankel, N. A. and Acrivos, A., "On the viscosity of A Concentrated Suspension of Solid Spheres," Chemical Engineering Science, Vol. 22, pp. 847-853, 1967.
- Gerjarusak, S., W. A. Peters, and J. B. Howard, "Coal Plasticity at High Heating Rates and Temperatures: Ninth Technical Report to the U.S. Department of Energy," US DOE Pittsburgh Energy Technology Center, Contract No. DE-FG22-89PC-89733 (September 1992).
- Griffin, T. P., "Intraparticle Secondary Reactions of Tar During Bituminous Coal Pyrolysis," Ph.D. Thesis, Dept. of Chemical Engineering, MIT, Cambridge, MA, 1989.
- Howard, J. B., "Fundamentals of Coal Pyrolysis and Hydropyrolysis" Chapter 8 in Chemistry of Coal Utilization, Second Suppl. Vol., edited by M.A. Elliott, Wiley, New York, 1981.

Howard, J. B., W. S. Fong, and W. A. Peters, "Kinetics of Devolatilization," NATO Advanced Research Workshop on "Fundamentals of the Physical-Chemistry of Pulverized Coal Combustion," Les Arcs, France, 1986.

Ko, G. H., D. M. Sanchez, W. A. Peters, and J. B. Howard, "Correlations for Effects of Coal Type and Pressure on Tar Yields from Rapid Devolatilization," Twenty-Second Symposium (International) on Combustion, pp. 115-124, the Combustion Institute, Pittsburgh, PA 1989.

Ko, G. H., "Pyrolysis of Different Coal Types," Ph.D Thesis, Department of Chemical Engineering, MIT, Cambridge, MA, 1988.

Snape, C. E. and Bartle K. D., "Concluding Remarks" from "Molecular Structure of Coals: A Debate," Fuel, 68, p. 1091, 1989.

END

**DATE
FILMED**

6 / 7 / 93