PPPL - 2876
December 1992

**The Use of Iron Shims to Reduce the
Toroidal Field Ripple in Tokamaks.**

George V. Sheffield

Plasma Physics Laboratory, Princeton University

ABSTRACT

A study was performed to investigate the use of laminated ferromagnetic material, iron shims, to reduce the toroidal field, TF, ripple in Tokamaks.

Fixed geometry shims can reduce the TF ripple and will behave linearly for Low Field Tokamaks with central fields under 2 Tesla. For High Field Tokamaks with central fields under 6 Tesla, fixed geometry shims can reduce the TF ripple but will have some non-linear behavior.

Variable geometry shims can reduce the field ripple significantly with complete linearity for High Field Tokamaks.

MASTER

ef

1.0 INTRODUCTION

In most of the large Tokamaks currently operating, the toroidal field ripple has been designed to be less than 1% at the outer edge of the standard plasma cross section. However, these machines can run other plasma geometries which cover regions where the field ripple can exceed 5%. As an example, Figure 1 shows ripple contour plots for TFTR superimposed on one such plasma cross section. It would enhance the operating regimes of these devices if the toroidal field ripple in these outer regions could be reduced to under 1 %.

At this laboratory, in the past, ferromagnetic material has been used to reduce the confining field ripple in linear devices whose operating fields were below 2 Tesla. A cross section of one of these linear devices is shown in Figure 2 along with a ripple plot with and without the iron rings under each confining field coil. The iron effect was made linear over the whole range of operating field levels by laminating the iron with non-magnetic material such as aluminium¹ which acts like distributed air gaps. These laminated iron rings were call "iron shims."

2.0 GENERAL BEHAVIOR OF IRON SHIMS IN A TOROIDAL FIELD COIL SET

Since the ripple in a set of discrete toroidal field, TF, coils is only significant on the outboard side of the bore, the iron shims only need to be discrete annuli, in the shadow of the TF coils, on the outboard side of the bore. Figure 3 shows an initial shim geometry for the TFTR TF coils. The lamination of the iron and air gaps is characterised by the fraction of iron in the shim, f , which is defined as:

$$f = i / (g + i). \quad [2.1]$$

The behavior of the iron can be approximated by assuming that it is uniformly magnetized and, therefore, can be represented by surface currents equal to its magnetization². For the geometry shown in Figure 3, the field at the center of the iron as a function of its magnetization, M , can be approximated by plus and minus infinite current sheets of finite width³ as follows:

$$B = 2 \mu_0 M \tan^{-1} (w / t) / \pi \quad [2.2]$$

which, with $w=0.35$ meters and $t=0.1$ meters, equals:

$$B = 0.823 \mu_0 M \quad [2.3]$$

The effect of the lamination is to reduce the surface that the current can flow on so equation [2.3] becomes:

$$B = 0.823 f \mu_0 M \quad [2.4]$$

For TFTR, the magnetic intensity, H , at the center of the iron, R_{iron} , from the toroidal field set in terms of the TF field, B_{tf} , at the standard plasma center, R_{tf} , is :

$$\mu_0 H = B_{\text{tf}} R_{\text{tf}} / R_{\text{iron}} \quad [2.5]$$

The field intensity evaluated for $R_{\text{tf}} = 2.48$ meters and $R_{\text{iron}} = 3.95$ meters is:

$$\mu_0 H = 0.6278 B_{\text{tf}} \quad [2.6]$$

The field at the center of the iron, B^* , from the vacuum field intensity and its own magnetization would then be:

$$B^* = 0.6278 B_{\text{tf}} + 0.823 f \mu_0 M \quad [2.7]$$

The ferromagnetic material is characterised by its B vs. H curve which using the relationship:

$$B = \mu_0 H + \mu_0 M \quad [2.8]$$

can be recouched as $\mu_0 M$ vs. B . The $\mu_0 M$ vs. B curve for hot rolled, low carbon steel is given in Figure 4.1 .

The operating point for the iron is determined when $B = B^*$. Once this operating point is determined, the effectiveness of the iron can be estimated by knowing its relative permeability, μ_r , which is given in Figure 4.2 as a function of B for hot rolled, low carbon steel. An

equivalent relative permeability, μ_{eqr} , for the lamination with air gaps can be determined by finding an equivalent reluctance, R .

$$R = \sum_j L_j / \mu_j A_j \quad [2.9]$$

Therefore, the equivalent reluctance for the laminate in terms of an equivalent permeability, μ_{eq} , is :

$$L / \mu_{eq} A = L f / \mu A + L (1-f) / \mu_0 A \quad [2.10]$$

This equation can be rearranged in terms of relative permeabilities, $\mu_r = \mu / \mu_0$, to become:

$$\mu_{eqr} = \mu_r / (f + \mu_r + f \mu_r) \quad [2.11]$$

The shim basically acts like an isolated volume of iron in an external field similar to the classic case of a sphere immersed in a uniform field ⁴. For such a case, the effectiveness, Eff , of the iron is quantified by:

$$Eff = (\mu_{eqr} - 1) / (\mu_{eqr} + 2) \quad [2.12]$$

Taking the material property of Figure 4.2 and operating on it with equation [2.12], the effectiveness of the iron can be plotted as a function of B for various values of lamination, f . Figure 4.3 shows this relationship. It is apparent that completely linear behavior only exists for values of field under 1.5 Tesla. For the hot rolled, low carbon steel, this corresponds to a value of $\mu_0 M$ equal to 1.5248 Tesla. Substituting these values of B and $\mu_0 M$ into equation [2.7] gives the maximum TFTR TF field allowed for linear iron shim behavior as a function of iron fraction.

$$1.5 = 0.6278 B_{ff} + (0.823)(1.5248) f \quad [2.13]$$

or

$$B_{ff} = 2.389 - 1.999 f \quad [2.14]$$

Evaluating equation [2.14] gives the following relation between iron fraction and maximum TF field:

f=	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8
B_{ff} =	2.19	1.99	1.79	1.59	1.39	1.19	0.99	0.79

It is obvious that, for TFTR with its maximum TF field of 5.2 Tesla, iron shims can not be completely linear over the TF field range.

However, it may be possible to use the iron shims for fields above 2 Tesla by relaxing the requirement of complete linearity and by taking advantage of the general shape of the effectiveness vs. B_{ff} curves for the various values of iron fraction.

Using the following solution procedure:

- (1) select B_{ff} and f.
- (2) find the intersection of equation [2.7] and the curve $\mu_0 M$ vs. B given in Figure 4.1.
- (3) Use the value of B to find the value of μ_r from Figure 4.2.
- (4) substitute μ_r into equation [2.12] to give μ_{eqr} .
- (5) substitute μ_{eqr} into equation [2.13] to give Eff.

the shape of the Eff vs. B_{ff} curves for various values of f can be generated and these curves are shown in Figure 4.4.

Examination of the $f = 0.375$ curve of Eff vs. B_{ff} in Figure 4.4 seems to indicate that there may be solutions that can give acceptable variation of effectiveness of the iron shims over the full operating range of TF field for TFTR.

3.0 DETAILED SIMULATION OF FIXED GEOMETRY IRON SHIMS

A three dimensional iron simulation code was used to model the shim geometry of Figures 3 and 4 in the TFTR discrete TF coils set. The TF

ripple calculated is defined as :

$$\text{Ripple} = 200(B_{\text{max}} - B_{\text{min}}) / (B_{\text{max}} + B_{\text{min}}) \quad [3.1]$$

at a radius of 3.6 meters and on the device midplane. The simulation was run over the range of B_{tf} to generate the ripple vs. B_{tf} curves for various values of iron fraction, f . The resulting curves are shown in Figure 5.

The shape of the curves from the detailed simulation qualitatively match the shape of the curves generated in the simpler analysis which are shown in Figure 4.4. However, the curves in Figure 5 show the value of the TF ripple including the value of the ripple with no iron present, $f=0.0$. The value of vacuum field ripple shown, 4%, is consistent with the ripple contour curves of Figure 1 for the radius of 3.6 meters. An enlargement of the simulation curves is given in Figure 6. Note that the $f = 0.375$ curve is relatively flat. This led to the decision to try holding $f=0.375$ and to increase the shim thickness to try to reduce the ripple further with minimal variation with field level.

The results of increasing the shim thickness, while holding the iron fraction fixed at 0.375, are shown in Figure 7. At a thickness of 0.28 meters, the ripple has been reduced to $\pm 1.3\%$ from the vacuum value of +4%. However, at this thickness, the shim would probably exceed the available space between the vacuum vessel and the TF coil case. Figure 8 shows the cross section of the iron shim at $t=0.28$ meters.

4.0 DETAILED SIMULATION OF VARIABLE GEOMETRY IRON SHIMS

Since the space available between the vacuum vessel and the TF coil does not seem sufficient for a fixed geometry iron shim, a variable geometry shim was tried. The cross section of this iron shim is shown in Figure 9. In its fully extended mode it covers an annulus of $\pm \alpha$ while in its fully contracted mode it covers ± 30 degrees. Figure 10 (a) shows a three dimensional view of the variable geometry iron shim. As the top and bottom pieces move in or out of the center piece, different regions of the annulus have different values of iron fraction, f . This variation of f is shown schematically in Figures 10 (b) through 10 (f).

A three dimensional simulation was run for the variable geometry shim. At each value of α , a scan in B_{tf} was made to find the intersection of the ripple vs. B_{tf} curve with the zero ripple axis. A summary of these

runs is shown in Figure 11. From this data, a curve of α vs. B_{tf} can be generated, Figure 12, which would force the ripple at 3.6 meters to be zero in TFTR. Therefore, when the device was going to run at a particular B_{tf} , the proper value of α could be read off of Figure 12 and a remote actuator could deploy the pieces of the variable geometry iron shim to give no field ripple in the outer region of the TFTR vacuum vessel.

5.0 SUMMARY AND CONCLUSIONS

The study described in this report looked at the possible use of laminated ferromagnetic material, iron shims, in Tokamaks to reduce the toroidal field ripple. TFTR was used as an example. The conclusions reached follow.

First, for Low Field Tokamaks with central toroidal fields less than 2 Tesla, fixed geometry iron shims can be designed to reduce the field ripple and to have linear behavior over the whole TF operating range.

For High Field Tokamaks with central toroidal fields up to 6 Tesla, fixed geometry iron shims can be designed to reduce the field ripple but the resulting lower ripple will have some non-linear behavior over the TF operating range. Also, the fixed geometry iron shim, at these high fields, requires significant radial space between the outboard side of the vacuum vessel and the inner surface of the outer leg of the TF coil.

The use of a variable geometry iron shim will allow reduction of the TF ripple to near zero and linear behavior over the TF operating range for High Field Tokamaks. Additionally, these shims require less radial space than the fixed geometry shims.

ACKNOWLEDGEMENTS

This work was supported by the U.S. Department of Energy under contract no. DE-AC02-76-CHO-3073.

REFERENCES

- [1] Christensen, U.R., "Improving the Homogeneity of Axially Symmetric Magnetic Fields", Princeton Plasma Physics Laboratory Report MATT-Q-21 (April 1964) 371.
- [2] Reitz, J.R. and Milford, F.J., "Foundations of Electromagnetic Theory", Addison-Wesley Publishing Company, Reading, Massachusetts, (1960) 186.
- [3] Thome, R.J. and Tarrh, J.M., "MHD and Fusion Magnets", John Wiley and Sons, New York, New York (1982) 308.
- [4] Reitz, J.R. and Milford, F.J., "Foundations of Electromagnetic Theory", Addison-Wesley Publishing Company, Reading, Massachusetts, (1960) 212.

FIGURES

- Fig. 1.0 Toroidal field ripple contours for TFTR.
- Fig. 2.0 Cross section of Q-1 linear device with plots of confining field ripple with and without the laminated iron rings.
- Fig. 3.0 Cross section of iron shim in the bore of the TFTR TF coil with shim parameters of $t=0.1$, $h/2=0.6$, and $w/2=0.175$ meters.
- Fig. 4.0 Isometric view of a quarter of the iron shim and the equation defining the fraction of iron, f , in the shim.
- Fig. 4.1 $\mu_0 M$ vs. B curve for hot rolled, low carbon steel.
- Fig. 4.2 Relative permeability vs. B curve for hot rolled, low carbon steel.
- Fig. 4.3 Effectiveness vs. B curve for various values of iron fraction, f , for hot rolled, low carbon steel.
- Fig. 4.4 Effectiveness vs. B curve for various values of iron fraction, f , for an iron shim made of hot rolled, low carbon steel with the parameters $t=0.1$, $h/2=0.6$, and $w/2=0.175$ meters.
- Fig. 5.0 Ripple at 3.6 meters vs. B_{ff} for various values of iron fraction, f , for an iron shim made of hot rolled, low carbon steel with the parameters $t=0.1$, $h/2=0.6$, and $w/2=0.175$ meters.
- Fig. 6.0 Enlarged view of ripple at 3.6 meters vs. B_{ff} for various values of iron fraction, f , for an iron shim made of hot rolled, low carbon steel with the parameters $t=0.1$, $h/2=0.6$, and $w/2=0.175$ meters.
- Fig. 7.0 Ripple at 3.6 meters vs. B_{ff} for various values of shim thickness, t , for an iron shim made of hot rolled, low carbon steel with the parameters $t=0.1$, $f=0.375$, $h/2=0.6$, and $w/2=0.175$ meters.
- Fig. 8.0 Cross section of iron shim in the bore of the TFTR TF coil with shim parameters of $t=0.28$, $f=0.375$, $h/2=0.6$, and $w/2=0.175$ meters.

Fig. 9.0 Cross section of variable geometry iron shim in the bore of the TFTR TF coil with the parameters $t=0.135$ and $w/2=0.175$ meters.

Fig. 10.0 (a) Three dimensional view of the variable geometry iron shim.

Fig. 10.0 (b) Cross section of the variable geometry iron shim in the bore of the TFTR TF coil for $\alpha = 30$ degrees with the indications of the value of the iron fraction over the annulus.

Fig. 10.0 (c) Cross section of the variable geometry iron shim in the bore of the TFTR TF coil for $\alpha = 36$ degrees with the indications of the value of the iron fraction over the annulus.

Fig. 10.0 (d) Cross section of the variable geometry iron shim in the bore of the TFTR TF coil for $\alpha = 42$ degrees with the indications of the value of the iron fraction over the annulus.

Fig. 10.0 (e) Cross section of the variable geometry iron shim in the bore of the TFTR TF coil for $\alpha = 48$ degrees with the indications of the value of the iron fraction over the annulus.

Fig. 10.0 (f) Cross section of the variable geometry iron shim in the bore of the TFTR TF coil for $\alpha = 54$ degrees with the indications of the value of the iron fraction over the annulus.

Fig. 11.0 Ripple at 3.6 meters vs. B_{ff} for various values of α for a variable geometry iron shim made of hot rolled, low carbon steel with the parameters $t=0.135$ and $w/2=0.175$ meters.

Fig. 12.0 α vs. B_{ff} to give zero ripple at 3.6 meters for a variable geometry iron shim made of hot rolled, low carbon steel with the parameters $t=0.135$ and $w/2=0.175$ meters.

Figure 1

Field on axis of Q-1 machine.

Figure 2

$t = 0.1$
 $h/2 = 0.6$
 $w/2 = 0.175$

Figure 3

$$f = i / (g+i)$$

Figure 4

Figure 4.1

Figure 4.2

Figure 4.3

Btf at 2.48 meters

Figure 4.4

Figure 5

Figure 6

Figure 7

$t = 0.28$
 $h/2 = 0.6$
 $f = 0.375$
 $w/2 = 0.175$

Figure 8

$t = 0.135$
 $w/2 = 0.175$
 $\alpha = \text{variable}$
 $f = \text{variable}$

Figure 9

Figure 10

Figure 11

Figure 12

EXTERNAL DISTRIBUTION IN ADDITION TO UC-420

Dr. F. Paoloni, Univ. of Wollongong, AUSTRALIA
 Prof. M.H. Brennan, Univ. of Sydney, AUSTRALIA
 Plasma Research Lab., Australian Nat. Univ., AUSTRALIA
 Prof. I.R. Jones, Flinders Univ, AUSTRALIA
 Prof. F. Cap, Inst. for Theoretical Physics, AUSTRIA
 Prof. M. Heindler, Institut für Theoretische Physik, AUSTRIA
 Prof. M. Goossens, Astronomisch Instituut, BELGIUM
 Ecole Royale Militaire, Lab. de Phy. Plasmas, BELGIUM
 Commission-Europeen, DG. XII-Fusion Prog., BELGIUM
 Prof. R. Bouciqué, Rijksuniversiteit Gent, BELGIUM
 Dr. P.H. Salanaka, Instituto Fisica, BRAZIL
 Instituto Nacional De Pesquisas Especiais-INPE, BRAZIL
 Documents Office, Atomic Energy of Canada Ltd., CANADA
 Dr. M.P. Bachynski, MPB Technologies, Inc., CANADA
 Dr. H.M. Skarsgard, Univ. of Saskatchewan, CANADA
 Prof. J. Teichmann, Univ. of Montreal, CANADA
 Prof. S.R. Greenivasan, Univ. of Calgary, CANADA
 Prof. T.W. Johnston, INRS-Energie, CANADA
 Dr. R. Bolton, Centre canadien de fusion magnétique, CANADA
 Dr. C.R. James, Univ. of Alberta, CANADA
 Dr. P. Lukáč, Komenského Univerzita, CZECHO-SLOVAKIA
 The Librarian, Culham Laboratory, ENGLAND
 Library, R61, Rutherford Appleton Laboratory, ENGLAND
 Mrs. S.A. Hutchinson, JET Library, ENGLAND
 Dr. S.C. Sharma, Univ. of South Pacific, FIJI ISLANDS
 P. Mähönen, Univ. of Helsinki, FINLAND
 Prof. M.N. Bussac, Ecole Polytechnique, FRANCE
 C. Mouttet, Lab. de Physique des Milieux Ionisés, FRANCE
 J. Radet, CEN/CADARACHE - Bat 506, FRANCE
 Prof. E. Economou, Univ. of Crete, GREECE
 Ms. C. Rinni, Univ. of Ioannina, GREECE
 Dr. T. Mui, Academy Bibliographic Ser., HONG KONG
 Preprint Library, Hungarian Academy of Sci., HUNGARY
 Dr. B. DasGupta, Saha Inst. of Nuclear Physics, INDIA
 Dr. P. Kaw, Inst. for Plasma Research, INDIA
 Dr. P. Rosenau, Israel Inst. of Technology, ISRAEL
 Librarian, International Center for Theo Physics, ITALY
 Miss C. De Palo, Associazione EURATOM ENEA, ITALY
 Dr. G. Grosso, Istituto di Fisica del Plasma, ITALY
 Prof. G. Rostangni, Istituto Gas Ionizzati Del Cnr, ITALY
 Dr. H. Yamato, Toshiba Res & Devel Center, JAPAN
 Prof. I. Kawakami, Hiroshima Univ., JAPAN
 Prof. K. Nishikawa, Hiroshima Univ., JAPAN
 Director, Japan Atomic Energy Research Inst., JAPAN
 Prof. S. Itoh, Kyushu Univ., JAPAN
 Research Info. Ctr., National Inst. for Fusion Science, JAPAN
 Prof. S. Tanaka, Kyoto Univ., JAPAN
 Library, Kyoto Univ., JAPAN
 Prof. N. Inoue, Univ. of Tokyo, JAPAN
 Secretary, Plasma Section, Electrotechnical Lab., JAPAN
 S. Mori, Technical Advisor, JAERI, JAPAN
 Dr. O. Mitarai, Kumamoto Inst. of Technology, JAPAN
 J. Hyeon-Sook, Korea Atomic Energy Research Inst., KOREA
 D.I. Choi, The Korea Adv. Inst. of Sci. & Tech., KOREA
 Prof. B.S. Liley, Univ. of Waikato, NEW ZEALAND
 Inst of Physics, Chinese Acad Sci PEOPLE'S REP. OF CHINA
 Library, Inst. of Plasma Physics, PEOPLE'S REP. OF CHINA
 Tsinghua Univ. Library, PEOPLE'S REPUBLIC OF CHINA
 Z. Li, S.W. Inst Physics, PEOPLE'S REPUBLIC OF CHINA
 Prof. J.A.C. Cabral, Instituto Superior Tecnico, PORTUGAL
 Dr. O. Petrus, A.I. CUZA Univ., ROMANIA
 Dr. J. de Villiers, Fusion Studies, AEC, S. AFRICA
 Prof. M.A. Hellberg, Univ. of Natal, S. AFRICA
 Prof. D.E. Kim, Pohang Inst. of Sci. & Tech., SO. KOREA
 Prof. C.I.E.M.A.T, Fusion Division Library, SPAIN
 Dr. L. Stenflo, Univ. of UMEA, SWEDEN
 Library, Royal Inst. of Technology, SWEDEN
 Prof. H. Wilhelmson, Chalmers Univ. of Tech., SWEDEN
 Centre Phys. Des Plasmas, Ecole Polytech, SWITZERLAND
 Bibliotheek, Inst. Voor Plasma-Fysica, THE NETHERLANDS
 Asst Prof. Dr. S. Cakir, Middle East Tech. Univ., TURKEY
 Dr. V.A. Glukhikh, Sci. Res. Inst. Electrophys. Apparatus, USSR
 Dr. D.D. Ryutov, Siberian Branch of Academy of Sci., USSR
 Dr. G.A. Eliseev, I.V. Kurchatov Inst., USSR
 Librarian, The Ukr.SSR Academy of Sciences, USSR
 Dr. L.M. Kovrizhnykh, Inst. of General Physics, USSR
 Kernforschungsanlage GmbH, Zentralbibliothek, W. GERMANY
 Bibliothek, Inst. Für Plasmaforschung, W. GERMANY
 Prof. K. Schindler, Ruhr-Universität Bochum, W. GERMANY
 Dr. F. Wagner, (ASDEX), Max-Planck-Institut, W. GERMANY
 Librarian, Max-Planck-Institut, W. GERMANY
 Prof. R.K. Janev, Inst. of Physics, YUGOSLAVIA

END

DATE
FILMED

5/04/93