Technical Progress Report

Title: Oceanic CO₂ Measurements for the WOCE Hydrographic Survey in the Pacific Ocean, 1990-1991: Shore Based Analyses During Legs 1-3

Principal Investigator: Charles D. Keeling

Period of Report: 1 December, 1990 to 28 January, 1992

Award No.: DEFG0390ER60982

DOE/ER/60982--2

Address: Scripps Institution of Oceanography
University of California, San Diego
La Jolla, California 92093-0220

DE92 013064

Summary of Progress

Activities During the winter and spring of 1991 we made preparations for sampling on three legs of the U.S. World Ocean Circulation Experiment in the Pacific Ocean. These transects, postponed from an original start date early in 1991, took place between May 31 to October 1. In advance we prepared 1400 0.5 liter Pyrex sampling bottles for the collection of sea water, obtained from the Corning and Schott glass companies. Because in our previous studies we had always used 1.0 liter bottles, all 1400 bottles had to be purchased and prepared for use from the factory product. Approximately half of the bottles were of a basic design used by us previously, except that the closures were hollow glass plugs without hold-downs, whereas our previous bottles had solid plugs and metal clamps. Each hollow plug closure had to be reground (hand lapped) in order to provide an adequate seal after applying stopcock grease. The other half of the bottles were equipped with solid standard-taper stoppers, also to be greased, and were held down with threaded plastic "Rodavis" collars. The stoppers of these bottles proved to seal sufficiently well that they did not require relapping. All bottles were washed and reannealed to insure that they were without strain and were free of any organic carbon films. Bottle preparation was a major task that was assisted by student help hired for the purpose, but also required considerable time of two of our chemists, Mr. Guenther and Mr. Lueker.

A second major pre-expedition task was the construction of a dual titration cell system of new design, as described in the original proposal and our previous semi-annual report. This work was carried out mainly by our engineer, Mr. Moss, assisted by Mr. Guenther and Mr. Lueker. Concurrent with construction of this system, a computer program was devised to drive the two titrators by computer

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

and to calculate the results. This latter task turned out to require more time than anticipated. Mrs. Stewart, a programmer whom we had hired temporarily in 1990 to assist us in preparing code for data entry and management, was retained to carry out the details of this task under Mr. Moss' supervision. The titration system, including software, was completed in late July; it was tested in August until the date that it was shipped to Papeete, Tahiti for use on Leg 3.

Although the employment of this system at sea was in accordance with a separate Grant from DOE (FG03-91ER61116), the device itself was built to be used mainly on shore after Leg 3. Thus, Grant ER60982 provided for the cost of construction and testing.

The construction project and bottle preparation, described above, left only nominal time for personnel to prepare the shore laboratory for the return of samples from Legs 1 and 2. In particular, we were unable to devote significant time to the completion of the new manometric system for measuring dissolved inorganic carbon (DIC) in sea water. As a consequence, we have been obliged to continue the use of our previously existing quartz spiral manometer, in use since 1983 and no longer in optimum working order. We were also obliged to defer completion of the programming for data entry and management. Our existing procedures had been adequate for our former studies of DIC and alkalinity, involving about 400 samples per year, but were found to be too cumbersome to handle efficiently the large data stream expected from the WOCE program.

To improve data management we have continued to employ Mrs. Stewart. Pending completion of this work we have been obliged to defer the hiring of an additional chemist to assist in the routine analyzing of sea water samples. This has reduced our ability to analyze DIC samples by 50%, but has not limited our alkalinity analyses.

Throughout 1991 we have assisted Dr. Andrew Dickson who, under a separate DOE Grant, has been preparing standard reference sea water (SRM's) for general use in the WOCE program. We have analyzed on demand, samples of his new standards for both alkalinity and DIC.

Sea water samples from Leg 1 arrived on July 31. Their analysis for DIC and alkalinity began on August 5. During the rest of August, Mr. Emanuele, hired at the beginning of the proposal to work full time on DIC measurements, worked on the analysis of these samples for DIC. Mr. Lueker, however, spent nearly full time assisting Mr. Moss in preparing the titrator system for Leg 3 shipboard use,

deferring routine measurements of alkalinity.

During the latter half of August and most of September, Peter Guenther was absent from the laboratory, first on annual leave and then while carrying out shipboard measurements of alkalinity on leg 3. Upon his return, he began measurements of DIC using our mercury manometer, the primary method for analyzing DIC at high accuracy and precision.

From September till the present both Mr. Emanuele and Mr. Lueker have worked almost continuously on analyzing samples. They have also carried out a preliminary work up of the data. In addition, Mr. Guenther has carried out numerous extra mercury manometric analyses to assure that our results have high precision and accuracy during the early stage of the field program, in which comparisons with field data are especially crucial. Mr. Moss has divided his time between completion of the new quartz spiral manometric system and in supervising development of the new data management system.

As can be determined from a summary of samples analyzed, shown in Table 1, we have, as of this date, analyzed 209 WOCE samples of which 196 are from Legs 1 to 3, while 13 were from an expedition in the Atlantic Ocean in which Brookhaven National Laboratory participated. We have also analyzed all of these samples for alkalinity. Of 786 samples collected on Legs 1 to 3, 590 thus remain to be analyzed. We have also analyzed, for DIC, 29 standards for Dr. Dickson and 12 samples collected at Bermuda as controls, and for alkalinity 19 laboratory working standards, each several times for a total of 68 runs.

Results. We obtain a reliable measure of our imprecision of analysis in DIC and alkalinity by analyzing pairs of samples from each Niskin bottle (the source of sea water from a hydrographic cast). From the differences between analyses of each sample pair, our imprecision in measuring DIC using our mercury manometer, as can be seen from Table 2, is about 0.8 to 1.0 $\mu\text{m}/\text{kg}$, i.e., about 15 to 40% greater than the 0.70 $\mu\text{M}/\text{kg}$ that we have maintained over a ten year period prior to participating in the WOCE program. The samples from Leg 3 were collected by Peter Guenther who had collected samples satisfactorily at sea for our program several times before and has carried out all of the mercury manometric analyses for our program for over twenty years, making unlikely that changed sampling procedures is the main cause of the poorer precision.

The only difference in procedures that we can so far identify is the change in type of sample bottles. Up to now we can not see any significant difference between Rodavis equipped and hollow-plug bottles. Thus we tentatively attribute the higher imprecision to circumstances related to the bottles being smaller. A possible explanation is that it is more difficult to prevent significant exchange of CO₂ gas between the water and ambient air with smaller bottles. This exchange could occur either during sampling at sea or during extraction in the laboratory. In either case, the loss of precision is not under our control, since we cannot expect to be able to collect more water in the WOCE program.

The alkalinity of sea water is not affected by small amounts of CO₂ gas exchange. Thus the use of smaller bottles should not affect the alkalinity, unless chemical reactions with the glass take place. Leaching of the glass, for example, would probably be worse in small bottles, because of the larger surface to volume ratio. Our imprecision for alkalinity so far (see Table 3) is close to that obtained previously (about 1.5 μ Eq/kg). This result is in spite of our switching to use of the new volumetric apparatus where formerly we controlled the amount of water very precisely by weighing it. Extensive testing of the reproducibility of the syringes that dispense the water for titration indicate that we should be able to achieve almost as precise measurements of water amount as we can do gravimetrically. Our results tend to substantiate that we have.

Table 2 lists the DIC data obtained at sea during each leg of WOCE for water drawn from the same Niskin bottles as our samples were drawn. On Leg 1 the imprecision of the difference between our results and the shipboard results indicates that the measurements at sea had an imprecision of about 3.7 μ M/kg. On average their measured values are almost identically to ours, however. On Leg 2 the shipboard imprecision was considerably improved (about 2.0 μ M/kg) but the results on average were lower than ours by about 2.0 μ M/kg. For both legs, however, not enough samples have been run yet with the mercury manometer to achieve a definitive comparison. On Leg 3, the imprecision on board ship was evidently still lower. Again the average, now based on a significant number of samples, was lower by 1.3 μ M/kg.

Our early results using the quartz spiral manometer for DIC and our gravimetric procedures for alkalinity titration were reported at the DOE Workshop in Washington, D. C. in November, 1991. These data were not as precise for either constituent as we had obtained routinely before. Indeed, they were not satisfactory enough to justify a detailed comparison with shipboard samples as a

basis of quality assurance at sea. After the meeting, we determined that there was no obvious cause for this poorer precision. Rather it appears to reflect a reduction in caution during routine work. Beginning in July, 1991 somewhat fewer standards were run, and samples were sometimes hurried in and out of the quartz spiral manometer instead of waiting until complete temperature control was assured. On some days, evidence of poor results for standards run in the quartz spiral manometer did not cause measurements to be halted. Similarly, the glass electrodes in the titration apparatus did not always give consistent results with standards, and again this did not cause work to be halted. In summary, the problem with higher imprecision evidently mainly reflects a conscientious effort to maintain a production schedule at too high a priority.

We have increased our precision since November mainly by taking more care, and in the case of the titrations, by replacing electrodes frequently even though this requires more standardizations. We conclude that for our measurements of DIC and alkalinity to be satisfactory, we cannot treat them as a routine procedure with time pressure applied to reach a certain goal of samples per week. By slowing down the pace of analysis, we have again obtained satisfactory results, similar to those reported in our original proposal.

Sample Collection. As noted above, our original proposal called for the collection of 1400 samples. Because of a shortage of chemical personnel at sea, it was infeasible to collect so many. In total, about 750 were collected. To increase sampling on Leg 3, we were prepared to engage another chemist, paid for by our other DOE grant, but we were unable to secure a berth, because the ship was too small. (This was the result of a delay in refurbishing the R.V. Knorr, necessitating the use of a smaller ship.) Similar restrictions in sampling occurred on Legs 1 and 2. On these first two legs, the bottles returned to us were, in general, not prepared as carefully as desirable. Especially on Leg 2 many bottles appear to have been improperly greased and showed signs of possible leakage. We may not be able to analyze successfully more than 50 to 75% of the samples collected on Legs 1 and 2.

In retrospect, it is evident that a third person for the carbon system work at sea is needed to carry out all of the assigned tasks satisfactorily. This person should be trained in advance in the collection of water samples, in a manner similar to the training we always give to persons who take samples of air for us at remote field stations in our study of atmospheric CO₂.

Personnel

The original proposal calls for Messrs. Guenther, Moss, and Lueker to participate in the program 25%, 20%, and 50%, respectively. During the reporting period their actual times spent on the project were approximately twice the budgeted times. Since this was also the case the previous year, it is obvious that this project was significantly supported by the National Science Foundation (NSF) that provided the additional funding of their salaries. Mr. Emanuele, hired specifically for the WOCE program with DOE funds, has worked full time, while Mrs. Stewart, hired as a programmer in place of an additional Staff Research Associate to assist in chemical analyses, has worked 80% time. Last year we sought a supplement from DOE to pay for Mrs. Stewart but were unsuccessful in obtaining it. As explained above, we chose to retain Mrs. Stewart and not hire the proposed second Staff Research Associate. The funds from the National Science Foundation that paid for the additional time of three other staff members, however, exceed the budgeted cost of the proposed second Staff Research Associate.

Summary of Future Plans

It is evident that we were unable to prepare for the first year of the WOCE program at the cost and in the time frame originally proposed. We are still not able to analyze samples optimally, pending completion of a new quartz spiral manometer and data management software. The NSF funding used to supplement the program was originally intended to pay costs of analysis of samples of sea water collected at time-series stations at Bermuda and Hawaii, and near the coast of California. Much of that analysis work has had to be postponed.

For this report we have assessed our present ability to analyze samples. If no obstacles appear in the procedures, Mr. Emanuele, without undue time pressure, can carry out four extractions for DIC in one day. We plan that he extracts samples for three days each week. On the remaining two days he will operate the quartz spiral manometer. Mr. Lueker will titrate 16 samples for alkalinity in two days and will extract four samples for DIC on a third day. Since Mr. Lueker will also spend time in data entry and management, he will again work longer than the budgeted 50% time provided by the grant.

In this way we expect to analyze about 270 samples in the remaining 17 weeks before the scheduled completion of analysis on 1 June, 1992. Since we must maintain standardization and will probably require additional control runs, we

expect to have completed approximately 230 to 250 more WOCE samples, making for a total of about 450 samples for the year. Since a considerable number of the original 780 samples cannot be analyzed because of leakage, and bottle breakage, we will have approximately 200 samples still remaining to be run, or approximately three additional months work.

Mr. Moss expects to complete the new quartz spiral manometer in February. Mrs. Stewart will probably require several more months to complete the data management scheme, but it should be completed in time for us to carry out demobilization on schedule, beginning on June 1.

Table 1. Sea Water Samples Analyzed from
1 July, 1991 to - 28 January, 1992

	For DIC		For
	Mercury Manometer	Both Manometers	Alkalinity
Leg 1	14	110	110
Leg 2	14	14	14
Leg 3	36	72	72
WOCE A9	00	13	13
Bermuda Controls	12	12	8
Dickson SRM's	15	29	54
Working Standards			
Bottles			19
Runs			68
Total	91	250	306

Table 2. Imprecision in DIC of samples analyzed at shore with the mercury manometer since 1 December, 1991^a

	No. of samples analyzed	Imprecision ($\mu\text{M}/\text{kg}$)	Shore results minus shipboard results ($\mu\text{M}/\text{kg}$)	Imprecision of differences between ship and shore ($\mu\text{M}/\text{kg}$)
WOCE-Leg 1	12	0.89	0.29	3.69
WOCE-Leg 2	10	0.81	2.17	1.98
WOCE-Leg 3	26	0.85	1.29	1.30
Bermuda controls	12	0.55		
SRM 6	7	1.80		
SRM 7	2	0.06		
SRM 10	3	0.33		
SRM 11	3	0.47		

^a Results are shown only for pairs that were both successfully analyzed and can be compared to results obtained at sea. For Leg 2, two pairs showing disagreement, of 4.0 and 4.3 $\mu\text{M}/\text{kg}$, are omitted from consideration, likewise for Leg 3, one pair that disagreed to 4.7 $\mu\text{M}/\text{kg}$ is omitted.

Table 3. Imprecision in alkalinity of samples analyzed at shore with the volumetric titration system since 7 Jan 1992^{a,b}

	No of Imprecision Samples analyzed	(μ equiv/kg)
WOCE-Leg 1	10	1.39
WOCE-Leg 2	10	1.09
WOCE-Leg 3	32	1.72
Bermuda controls	6	1.54

^a Results are shown only for pairs that were both successfully analyzed. For Leg 1, two pairs showing disagreement of 13.45 and 7.62 μ equiv/kg are omitted from consideration; likewise for Leg 2, two pairs showing disagreement of 6.17 and 6.80 μ equiv/Kg are omitted; for Leg 3, one pair showing disagreement of 9.42 μ equiv/kg is omitted; and for Bermuda one pair showing disagreement of 8.56 μ equiv/kg is omitted.

^b Overall imprecision for 52 WOCE samples is 1.56 μ equiv. At-sea imprecision obtained for bicarbonate reference standards was 1.52 μ equiv/kg.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

**DATE
FILMED**

6/15/92