Cost- Effectiveness of Compact Fluorescent Lighting

***Retrofits for Residential
Consumers in the Pacific
Northwest***

By

Jonathan A. Lesser, Ph.D.
Richard Byers

Washington State Energy Office
809 Legion Way SE
Olympia, WA 98504
WAOENG-91-06

March 1991

Copies

Additional copies of this publication
are available by contacting:

WAOENG--91-06

DE92 011825

Washington State Energy Office
Energy Library
809 Legion Way SE
Olympia, WA 98504-1211
(206) 956-2015
SCAN 494-2015

This document is one of a series
of investigations into energy policy
and planning issues.

*Changes in Gasoline Consumption in
Washington State due to the 65 m.p.h.
Speed Limit: Energy Policy and Planning
Research Series*
WAOENG-89-03/1
January 1989

*Canadian-U.S. Power Production and the
Columbia River Treaty—Implications
For Northwest Electricity Supply:
Energy Policy and Planning Research Series*
WAOENG-89-03/2
March 1989

*Global Warming:
Implications for
Energy Policy:
Energy Policy and Planning Research Series*
WAOENG-89-03/3
July 1989

*Cost-Effectiveness of
Compact Fluorescent Lighting:
Retrofits for Residential Consumers
in the Pacific Northwest*
WAOENG-91-06
March 1991

Disclaimer

The United States, the Bonneville Power Administration, the State of Washington, the Washington State Energy Office, nor any of their employees, their contractors, subcontractors, nor their employees, make any warranty, expressed or implied, or assume any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed within this document.

MASTER

Abstract

Compact fluorescent technologies have been steadily improving. There has been increased interest in utilizing compact fluorescents to provide cost-effective energy savings for electric utilities in the residential sector. Several utilities in the United States have already distributed compact fluorescents to consumers free of charge. This study assesses the cost-effectiveness of compact fluorescents from the perspectives of consumers and utilities in the Pacific Northwest, where electricity rates are, on average, the lowest in the United States. The study also assesses cost-effectiveness from a societal perspective. Secondary heating impacts and the value of reduced emissions of pollutants are incorporated into the analysis. Results indicate that compact fluorescents are more likely to be cost-effective as the perspective upon which they are assessed is broadened. Thus, they are least likely to be viewed as cost-effective by consumers, more likely to be considered cost-effective from a utility perspective, and almost always cost-effective from a societal perspective. Given these differences, it is suggested that policies be developed to capture the societal benefits of compact fluorescent retrofits through alternative regulatory or market mechanisms.

I. Introduction

Replacing incandescent light bulbs with compact fluorescents may have a significant energy savings potential (Fickett, Gellings, and Lovins 1990). Several studies (Krause, et al. 1988; Krause, Vine, and Gandhi 1989; Gadgil and Jannuzzi 1989) have examined the efficacy of lighting retrofits nationally and internationally using alternative methodologies. Kraus, Vine, and Gandhi (1989), for example, identified 12 utilities that have instituted residential lighting programs and assessed the effectiveness of these programs.

In the Pacific Northwest, where the average price of electricity is lower than all other regions of the United States (EEI 1989), the cost-effectiveness of residential lighting retrofits is still being debated. Several authors (Hinman 1990, Byers 1990) have done preliminary work to assess the cost-effectiveness of compact fluorescents in the region. The results of these analyses have been mixed.

Hinman (1990), for example, generally concluded that compact fluorescents were cost-effective for Pacific Northwest ratepayers. However, he also raised issues raised several issues, including bulb lifetimes, secondary heating impacts, temperature considerations, and the aesthetic properties of compact fluorescent bulbs that could affect the overall acceptability of the bulbs. Krause, Vine, and Gandhi (1989) argued that the costs of a program to a utility could be significant due to the presence of free-riders.

The majority of previous studies have appeared to base their conclusions on calculations of avoided (marginal) costs. Krause, Vine, and Gandhi (1989), for example, estimated avoided costs for the bulbs between 1 - 6 cents/kWh, depending on utilization. These avoided costs were then compared to the reported avoided costs for the utilities using alternative generating resources. If the avoided cost of the compact fluorescent was less than the utility's reported avoided cost, then the bulb would be considered cost-effective. Gadgil and Jannuzzi (1989) used this same approach, but also determined the overall net present value (NPV) of the bulbs.

Hinman (1990) and Byers (1990) also calculated maximum bulb prices that would still yield a positive NPV. Neither of these studies, nor the others mentioned, adequately included secondary heating impacts. And, none of the studies accounted for the potential value from reduced emissions of Clean Air Act¹ criteria pollutants and carbon dioxide.²

The avoided cost approach has the advantage of providing a straightforward ordering of compact fluorescent retrofits relative to other potential efficiency measures or generating resource measures. Essentially, avoided cost determinations allow a supply curve to be constructed. Presumably, utilities would invest in the resources along the supply curve in order of their increasing cost. However, avoided costs are quite sensitive to the assumptions that underlie their calculation. They can be calculated based on the lifetime of the particular resource, a fixed timeframe coinciding with a utility's time horizon, or the lifetimes of alternative measures. Different time frames can yield widely different avoided costs. Furthermore, different time frames affect the utility avoided cost upon which comparisons are based.

The choice of time frame is arbitrary. As a result, alternative avoided costs calculated for different time frames may lead to significantly different recommended policy actions. Nor do avoided cost comparisons by themselves provide a measure of overall net benefits. A measure

¹42 U.S.C.A. § 7401 et seq.

²The Byers study did estimate the magnitude of CO₂ savings. These may be somewhat high, however, due to the exclusion of the secondary heating impacts.

with a lower avoided cost, for example, may realize fewer net benefits than a higher cost measure because of its smaller size.

Rather than taking an avoided cost approach, this report determines the cost-effectiveness of compact fluorescent lighting retrofits through NPV analysis. In particular, this study differs from past analyses by determining cost-effectiveness separately for consumer, utility, and societal perspectives. Secondary heating impacts for homes with either electric or natural gas space heating are included in the analysis. Environmental benefits associated with retrofits (due to reduced emissions of criteria pollutants) are also accounted for from the utility and societal perspectives. By examining the three different perspectives, alternative conclusions over the cost-effectiveness of compact fluorescents can be better understood. As a result, the development of more cogent energy policies may be pursued in the Pacific Northwest. Lastly, because of its relatively low electricity prices, an analysis of the cost-effectiveness of compact fluorescent retrofits in that region may be able to provide a benchmark for other regions. Section II presents the data assumptions used in the report. Section III presents the results of the analysis. Section IV concludes with some suggestions about applicable policies with regards to compact fluorescent retrofits for residential consumers and discusses issues that remain unresolved.

II. Data Assumptions

As with several previous analyses, the current analysis focuses on replacement of an average 75 watt incandescent bulb with an 18 watt compact fluorescent bulb. The time frame chosen for the analysis was 10 years, equal to the assumed lifetime for a compact fluorescent bulb in use an average of 1,000 hours per year.³ The purchase cost of a compact fluorescent bulb was assumed to be \$15.00 in 1989 dollars. This figure was based on an evaluation of several competitive bidding solicitations (SESCO 1989) and the current wholesale price of this type of bulb (Byers 1990.) As with the Hinman (1990) analysis, the purchase cost of the incandescent bulb was estimated to be \$0.50 in 1989 dollars, though actual prices can vary depending on place of purchase and brand. The real (inflation adjusted) prices of both bulbs were assumed to remain constant over the analysis.⁴

In 1988, average electric rates for all residential customers in the Pacific Northwest equaled 4.4 cents/kWh (EEI 1989). (For the purposes of this study, the Pacific Northwest was taken to be the states of Washington, Oregon, and Idaho. This definition does not precisely coincide with the definition in the Pacific Northwest Regional Power Planning and Conservation Act of 1980, which also includes the portion of Montana west of the Continental Divide.⁵ However, precise data on average electricity rates for western Montana were not available.) For investor owned utility customers, the average residential rate in the region equaled 5.07 cents/kWh (EEI 1989). For publicly owned utility customers, it equaled 3.86 cents/kWh (BPA 1989).⁶

The avoided (marginal) cost of electricity faced by utilities will depend on the resource opportunities available. The range of avoided costs can be quite variable, depending on the type

³This time is also somewhat arbitrary. It was chosen since it is not uncommon for planning, siting, licensing, and construction of a major new generating facility to take an equivalent amount of time. If a long term comparison of resources is made, therefore, it is reasonable to use a time period that is relevant to the alternative (generating) resource.

⁴Byers (1990) reports that, in fact, the wholesale price of compact fluorescents is expected to decrease over time. As a conservatism, however, no such decline was incorporated into the current analysis.

⁵P.L. 96-501, 94 Stat 2697, 16 U.S.C. § 839 (1980).

⁶These rates were escalated to 1989 dollars for analysis.

of resource that is considered "marginal" over the time frame that is considered. In the very short run, for example, a utility might argue that spot market purchases best reflect its marginal cost (Puget Power 1989). Over a 10-year planning horizon, however, the marginal resource could be a major generating facility such as a coal plant or combined cycle combustion turbine (CT). A range of nominal levelized avoided costs, between 5.0 cents/kWh and 11.0 cents/kWh, was assumed for this study. This range reflects estimates developed by the Northwest Power Planning Council (NPPC 1990) and avoided cost schedules submitted by utilities to state regulatory commissions (PSPL 1989, Folsom 1990).

In evaluating long-term resource options, utilities will have to account for emissions of criteria pollutants in order to meet Clean Air Act requirements. Utilities may also have to reduce CO₂ emissions to combat global warming impacts.⁷ Emission levels of CO₂, sulfur dioxide (SO₂), and oxides of nitrogen (NO_x) from typical generating plants are summarized in NPPC (1990) and Chernick and Caverhill (1989). The value of enhanced environmental quality through reductions in air pollution emissions can, of course, be debated. However, the value of emissions reductions can be indirectly approximated via their control costs (Ottinger, et al. 1990; Chernick and Caverhill 1989). For the purposes of this study, control cost values were assumed to equal \$8.41/kG for SO₂ reductions, \$3.30/kG for NO_x reductions, and \$0.024/kG for CO₂ reductions (Chernick and Caverhill 1989).

These values were then translated into per kWh values for reductions in electric power production and per million Btu (MBtu) values for direct combustion. The final values depend on the marginal resource assumed. Using the estimates from Chernick and Caverhill (1989), for example, SO₂ reductions from new coal plants may be valued at 0.56 cents/kWh, NO_x reductions may be valued at 0.97 cents/kWh, and CO₂ reductions may be valued at 2.45 cents/kWh. The Chernick and Caverhill (1989) values, along with alternative estimates, are summarized in Koomey (1990).

Overall pollutant reductions depend on the type of marginal resource assumed and whether the residence is heating with either electricity or natural gas, the two most common space heating sources in the Pacific Northwest (NPPC 1989). Emissions of CO₂ and SO₂ from a combined cycle gas turbine, for example, will be lower than from a fluidized bed coal plant.

Reduced usage of incandescent lighting was assumed to increase aggregate electric space heating requirements. These secondary space heating requirements were assumed to be 47 percent in electrically heated homes (Palmiter and Kennedy 1986.) Thus, 100 kWh of energy savings from compact fluorescent installation would result in a net savings of $(1 - 0.47) * 100 = 53$ kWh of electricity. For homes heated by natural gas, the total efficiency of the space heating system was assumed to be 55 percent. Thus, the additional natural gas requirements for a 100 kWh savings in lighting requirements would equal $[47 \text{ kWh} / (0.55)] * 3,412 \text{ Btu/kWh} = 0.29 \text{ MBtu}$. From an emissions standpoint, homes heated with natural gas would save more electric related pollutant emissions, but produce greater emissions as a result of increased direct combustion of natural gas.

The price of natural gas for residential consumers in the Pacific Northwest was assumed to average \$5.00 per million Btus (MBtu).⁸ Unlike electricity, residential natural gas consumers in the Pacific Northwest do not face increasing block rate tariffs. Therefore, average rates were

⁷A comprehensive strategy for reduced greenhouse gas emissions is contained in the National Energy Policy Act of 1990 (U.S. Senate 1990).

⁸Residential rates in the Pacific Northwest differ significantly by state depending on the allocation of costs to the individual sectors. Rates can also be volatile. The figure used represents an approximate average rate over the four states.

used in the analysis. The real escalation rate was assumed to be 2.8 percent annually (USDOE 1990). Of course, this escalation rate could be affected by the choice of marginal electric resource. Electric utility reliance on natural gas fired CTs would, all other things equal, tend to increase the price of natural gas to residential consumers. However, an integrated analysis of this type is beyond the scope of the present study.

III. Results of the Analysis

The results of the analysis are presented in Tables 1-12. Results for each of the perspectives—consumer, utility, and societal—depend critically on the assumed values for key factors. Formulae used to compute net present values are contained in the Appendix.

Consumer Perspective

From the consumer standpoint, the key factors are the current and future prices of electricity and the implicit discount rate placed on future energy savings. In practice, consumers will almost certainly be affected by the purchase price of compact fluorescents. Consumers, used to paying 50 cents for an incandescent bulb, may be unable or unwilling to pay \$15 for a compact fluorescent. The analysis further assumes that bulk purchase arrangements would make it possible for consumers to purchase the bulbs for the same price as would cost a utility purchasing bulbs at a wholesale rate. Lastly, consumers were assumed to place no value on improved air quality due to reductions in air pollutants.

The study determined consumer cost-effectiveness under several scenarios. Overall, two consumer scenarios were considered. In the first, consumers were assumed to have electric resistance space heat. In the second, they were assumed to heat with natural gas. Real escalation rates for retail electricity were allowed to range from 0 to 3 percent annually. Usage intensities of the compact fluorescent retrofits ranged from 500 to 8,000 hours per year. Additionally, the analysis was performed for both investor owned utility and public utility customers, using their respective average residential rates.

The nominal rate of discount chosen for the base case was 18 percent, representing a typical finance rate for consumer credit card purchases. It was believed that this rate would reflect observed consumer willingness to finance small purchases at a relatively high rate. Not surprisingly, there is much disagreement over the actual discount rates. Hausman (1979), for example, estimated discount rates for the purchase of room air conditioners that ranged from 5.1 to 89 percent, with the estimated rates inversely related to income class. On the other hand, consumers are observed to make long-term capital investments in the form of houses and vehicles. Financing rates for these tend to be around 10 to 15 percent, providing a reasonable lower bound. The rate chosen was believed to be a reasonable compromise.

Table 1 shows the NPV of the 18 watt compact fluorescent for an electrically heated home from the consumer's perspective, assuming an investor owned utility electric rate of 5.3 cents/kWh. Overall NPVs ranged from -\$6.59 to \$35.75. (For the 500-hour utilization case, the NPV was calculated somewhat differently. At this utilization, a compact fluorescent would have a lifetime of 20 years. In order to account for the full savings potential of the bulb, the NPVs calculated for this case are all based on a 20-year time frame.) As the table shows, the compact fluorescent would be cost-effective only if used at least 2000 hours per year.

For consumers who use natural gas for space heating purposes, the cost-effectiveness thresholds are somewhat improved, as shown in Table 2. NPVs ranged from -\$5.32 to \$63.35. As with the electric space heat case, the net present value of the retrofit is positive if the lamp is used at least 2000 hours per year. Tables 3 and 4 show the results of the same analysis with the 4.1 cent/kWh rate for publicly owned utilities. As the tables show, cost-effectiveness is improved, especially at higher real escalation rates.

From a consumer perspective, therefore, the results are not overly encouraging. Utilization rates would have to be over 5 hours per day to yield positive net benefits. Consumer uncertainty over the performance of these bulbs, relatively high implicit discount rates, and capital constraints make individual consumer purchase of the bulbs unlikely. Indeed, as Kraus, Vine, and Gandhi (1989) observed, penetration rates for compact fluorescents have been quite small, even in areas with electric rates much higher than in the Pacific Northwest.

Utility Perspective

From the utility perspective, the key factors examined included the avoided cost of electricity and the long-term utility cost of capital. Utilities were also assumed to value reductions in emissions levels of pollutants covered by the Clean Air Act. Reductions in emissions in CO₂ were also included, since it is becoming more commonplace for regulators to require utilities to account for the environmental cost associated with global warming.⁹ The utility would also be concerned about the administrative costs of the program. Krause, Vine, and Gandhi (1989) estimate these administrative costs to be between 0.1 - 0.8 cents/kWh. Our analysis used a mid-range value of 0.5 cents/kWh.¹⁰

There may also be specific regulatory issues, such as whether a utility sponsored retrofit program could be capitalized to earn a rate of return or would be expensed by the utility. Free rider problems, for example, which can reduce the cost-effectiveness to the utility but that have little effect from a societal standpoint, are probably minimal for compact fluorescents (Krause, Vine, and Gandhi 1989). These institutional issues are briefly discussed in Section IV. No attempt was made in this analysis to account for impacts on short-term utility revenues, since those impacts will be utility specific.¹¹

The utility analysis assumed that the utility purchases the compact fluorescent for the consumer. For simplicity, it was assumed that this cost includes installation by the utility. The utility was assumed to value reductions in air pollutant emissions, including CO₂. A weighted utility cost of capital of 9.30 percent was assumed to represent the utility's nominal discount rate.¹²

Results of the analysis from a utility perspective are presented in Tables 5 - 8. Tables 5 and 6 present the analysis assuming the marginal resource is a coal plant, for consumers with electric and natural gas heat, respectively. Tables 7 and 8 assume a combined cycle CT as the marginal resource, again for both types of heating systems. Choice of the marginal resource affects total

⁹See, for example, Bernow and Marron (1990).

¹⁰Administrative costs could be expected to decline on a per kWh basis, however, as utilization rates increased. The costs of distributing a bulb to a consumer should be the same, irrespective of utilization. Thus, a better estimate might be an administrative cost equal to a fraction of the capital cost. The Bonneville Power Administration (1990), for example, estimates administrative costs at 20 percent of total capital cost. An 18 watt compact fluorescent designed to replace a 75 watt incandescent bulb would save 570 kWh over its lifetime. At a price of \$15, therefore, the associated administrative cost would be 0.53 cents/kWh.

¹¹There may also be capacity benefits from installation of compact fluorescents, since the load factor associated with lighting is almost certainly less than 100 percent. Due to the variability of potential capacity benefits, the current analysis assumed no capacity benefits. This reinforces the conservative nature of the estimated net benefits.

¹²This weighted after-tax cost of capital is currently used by one Washington state investor-owned electric utility in its rate filings with the Washington Utilities and Transportation Commission (Folsom 1990). Other Washington utilities use similar rates.

pollutant emissions and thereby overall cost-effectiveness. The environmental cost associated with increased use of natural gas space heat is not included, since the electric utility is assumed not to factor that cost into its decision framework. Neither does the electric utility incorporate the costs of incandescent light bulbs.

In the majority of the cases analyzed, the results show that utility purchase of the compact fluorescent is cost-effective, even if the nominal levelized cost of the marginal resource is as low of 5 cents/kWh.¹³ The only exception is shown in Table 7, where consumers were assumed to have electric space heat and the marginal resource is assumed to be a CT. In that case, at a 5.0 cent/kWh nominal levelized avoided cost, the compact fluorescent is never cost-effective. In fact, as utilization increases, NPV becomes more negative.

Societal Perspective

Analysis of cost-effectiveness from a societal perspective includes the savings from reduced purchases of incandescent bulbs and reductions in emissions of pollutants. A real discount rate of 3 percent was used to reflect the social rate of time preference. This value is consistent with estimates of the consumption rate of interest, which has been used as a proxy for the social rate of time preference (Lind 1982). Coupled with the assumed 5 percent inflation rate, the nominal discount rate used was 8.15 percent. For the analysis with natural gas space heat, the cost of the additional natural gas requirements was included in the NPV calculations, as were the additional pollutant emissions from increased combustion of natural gas.

Results of the analysis from this third perspective are presented in Tables 9 - 12. The results indicate that compact fluorescents are cost-effective, even at usage levels of just 500 hours per year. The marginal cost of new generation from a societal perspective is further likely to be much higher than for any individual utility in the Pacific Northwest, since most utilities do not have access to low cost hydropower on a non-firm basis. Thus, instead of an avoided cost of about 5.5 cents/kWh (the 10-year avoided cost of PP&L), society's avoided cost could easily be 9 - 10 cents/kWh, as estimated by the Northwest power Planning Council (NPPC 1990).¹⁴

IV. Policy Implications

The results of this analysis show clear differences in cost-effectiveness, depending on the perspective taken. From a consumer standpoint, compact fluorescents may not be cost-effective, except in situations where they are expected to be utilized a significant amount of time. In addition, consumers may be unable or unwilling to provide the up front investment required to purchase the bulbs, nor may the bulbs be readily available on a retail basis. Consumers may also be risk averse and be concerned about reliability, ease of use, and substitutability. Lastly, consumers will not, in general, incorporate external environmental costs into their purchase decisions. All of these factors contribute to the observed small penetration rates for compact fluorescents.

From the utility perspective, the bulbs appear to be cost-effective in most situations, based on the assumptions about the long-term avoided costs of new generating resources and the value of reduced air pollution emissions. Utilities, however, may be concerned that implementation of compact fluorescent retrofits will result in loss of earnings. They may also wish to compare program costs with short-term marginal costs, such as buying non-firm power on the spot market. These costs may be quite low in comparison to the long-run marginal utility resource

¹³In practice, the nominal dollar levelized costs of coal plants and CTs tends to be about 9 - 12 cents/kWh (NPPC 1990).

¹⁴Again, no capacity benefits are included.

costs, reducing the likelihood of utility investments. Unfortunately, foregoing long-term investments in efficiency, such as compact fluorescents, may result in lost opportunities and higher long-term costs.

As an example, consider a utility with a low short-term avoided cost in the range of 15 mills/kWh (PSPL 1989). This power may represent secondary energy that is available for purchase on the spot market. Next consider a consumer who wishes to install a compact fluorescent and operate it continuously. Not surprisingly, as Table 1 demonstrates, compact fluorescents are increasingly cost-effective the more they are used. Over the first year, a consumer faced with a 5.5 cent/kWh marginal rate for electricity would realize savings of about \$28 worth of electricity, less secondary space heat losses and not including savings on incandescent bulbs.

A continuously operating bulb would last slightly more than one year. A utility claiming a 15 mill/kWh avoided cost would likely balk at paying for this compact fluorescent, since the value of the electricity over the first year (not including environmental costs) would only be about \$7.50, half of the bulb's assumed cost. The utility might also argue that lost revenues and profits from installation of the bulb would damage its financial position, making the bulb even less favorable from its perspective. Under this scenario, the utility could conceivably offer to pay consumers to not use such bulbs, or at least only to use them sporadically. This regulatory complication is counter intuitive and may limit cost-effective (from society's standpoint) investments in efficiency improvements, increasing the overall costs of supplying electricity to consumers in the long run.

A utility cost-effectiveness determination based on avoided cost streams that include short-run non-firm sources of power may be inappropriate, however, unless that power is expected to be available over the long-run. Efficiency investments such as lighting retrofits are meant to delay or eliminate the need for new firm power generating facilities. Krause, Vine, and Gandhi (1989) report that lighting retrofits could, in fact, achieve such a delay. Comparing a long-term investment in an efficiency measure with a short-run resource that may or may not be available will delay investments in efficiency, since the short-term power is given the greatest present value weight by its very nature.

The societal perspective showed that the bulbs were almost always cost-effective, unless the marginal cost of electricity to society is less than 6.0 cents/kWh and utilization rates are less than 1000 hours per year. The dichotomy between societal, consumer, and utility cost-effectiveness thresholds points to the need to adopt regulatory mechanisms that will encourage consumers and utilities to use compact fluorescents. This could be accomplished in several ways, though the most probable method would be through enhanced utility conservation programs, such as those described by Kraus, Vine, and Gandhi (1989).

There have been alternative proposals for utility mechanisms to decouple sales and profits, not all of which agree (Cavanagh 1988, Moscovitz 1989).¹⁵ These mechanisms may provide the necessary encouragement for utilities to develop marketing programs. Alternatively, there may be other mechanisms that can by-pass the utility regulatory arena and provide consumers with direct incentives to purchase and install compact fluorescents. Such mechanisms might include federal tax credits for installation of the bulbs. Irrespective of the mechanisms used, however, as the market for compact fluorescents is expanded, it is likely that production economies will reduce bulb prices and enhance their cost-effectiveness. Based on the results of this analysis, the least cost-effective action therefore appears to be inaction.

¹⁵A complete discussion of these mechanisms is beyond the scope of this paper. The interested reader is referred to the two articles cited, and references therein.

References

- Bernow, S., and D. Marron. 1990. *Valuation of Environmental Externalities for Energy Planning and Operations*, Tellus Institute, Boston, MA.
- Byers, R. 1990. *Cost-Effectiveness of Compact Fluorescent Light Bulbs*, Washington State Energy Office, Memorandum to Tom Trulove, Olympia, WA.
- Cavanagh, R. 1988. *Responsible Power Marketing in an Increasingly Competitive Era*, Yale Journal on Regulation 5:331-366.
- Chernick, P., and E. Caverhill. 1989. *The Valuation of Externalities from Energy Production, Delivery, and Use*, Report to the Boston Gas Company, Boston, MA.
- Edison Electric Institute (EEI). 1990. Edison Electric Yearbook 1989, New York, NY.
- Fickett, A., C. Gellings, and A. Lovins. 1990. *Efficient Use of Electricity*, Scientific American 263(3):56-74.
- Folsom, B. 1990. *Personal communication*, Washington Utilities and Transportation Commission, Olympia, WA.
- Gadgil, A., and G. Jannuzzi. 1989. *Conservation Potential of Compact Fluorescent Lamps in India and Brazil*, Lawrence Berkeley Laboratory, LBL-27210, Berkeley, CA.
- Hausman, J. 1979. *Individual Discount Rates and the Purchase and Utilization of Energy-Using Durables*, Bell Journal of Economics (1):33-54.
- Hinman, G. 1990. *Possibilities for Energy Efficient Residential Lighting in the Pacific Northwest—A Preliminary Evaluation*, Washington State University, Office of Applied Energy Studies, Pullman, WA.
- Koomey, J. 1990. *Comparative Analysis of Monetary Estimates of External Environmental Costs Associated with Combustion of Fossil Fuels*, Lawrence Berkeley Laboratory, LBL-28313, Berkeley, CA.
- Krause, F., E. Vine, and S. Gandhi. 1989. *Program Experience and Its Regulatory Implications: A Case Study of Utility Lighting Efficiency Programs*, Lawrence Berkeley Laboratory, LBL-28268, Berkeley, CA.
- _____, et al. 1987. *Analysis of Michigan's Demand Side Electricity Resources in the Residential Sector*, Lawrence Berkeley Laboratory, LBL-23026, Berkeley, CA.
- Lind, R. 1982. *A Primer in the Major Issues Relating to the Discount Rate for Evaluating National Energy Options*, in R. Lind (ed.) Discounting for Time and Risk in Energy Policy, Resources for the Future, Washington, DC., 23-94.
- McCully, R. 1990. *Development History of More Efficient Lamp Designs*, Energy Engineering 87(1):29-45.
- Moscovitz, D. 1989. *Least-Cost Planning and Utility Earnings*, NARUC Conservation Committee White paper, Alma, ME.

Northwest Power Planning Council (NPPC). 1990. *New Resources: Supply Curves and Environmental Effects*, Issue Paper No. 90-1, Portland, OR.

Ottinger, R., et al. 1990. The Environmental Cost of Electricity, Pace University School of Law, White Plains, NY.

Palmiter, L., and Kennedy. 1986. *Annual Thermal Utility of Internal Gains*, paper presented at the 8th National Passive Solar Conference, American Solar Energy Society, Santa Fe, NM.

Puget Sound Power & Light Co. (PSPL). 1989. *Securing Future Opportunities: 1990-1991*, Appendix D, Bellevue, WA.

SESCO. 1990. *Petition to Require Nondiscriminatory Treatment of Residential Conservation in Resource Acquisition by Puget Sound Power & Light Co.*, Testimony before the Washington Utilities and Transportation Commission, Olympia, WA.

United States Dept. of Energy, Energy Information Administration (USDOE). 1989. Annual Review of Energy, Washington, DC.

United States Dept. of Energy, Bonneville Power Administration (BPA). 1989. Electricity Use in the Pacific Northwest, Portland, OR.

United States Senate. 1990. National Energy Policy Act of 1990, Report together with Additional Views. Report # 101-361, 101st Congress, 2nd Session, Washington, DC.

Appendix. Formulae Used to Determine Net Present Values

Let P_f = fluorescent bulb price
 P_i = incandescent bulb price
 L_f = fluorescent lifetime
 L_i = incandescent lifetime
 R_c = nominal consumer discount rate
 R_u = nominal utility after tax cost of capital
 R = societal real rate of time preference
 U_y = bulb utilization rate (hrs / year)
 i = inflation rate
 P_e = average residential rate for electricity
 MC_u = avoided cost of electricity from the utility perspective
 MC_s = marginal cost of electricity from the societal perspective
 e_g = real escalation rate of natural gas
 E_g = nominal escalation rate of natural gas
 e_e = real escalation rate of electricity
 E_e = nominal escalation rate of electricity
 PE_{CO2} = nominal value of CO₂ emissions reductions / kWh
 PE_{NOx} = nominal value of NO_x emissions reductions / kWh
 PE_{SO2} = nominal value of SO₂ emissions reductions / kWh
 PG_{CO2} = nominal cost of CO₂ emissions from natural gas / MBtu
 PG_{NOx} = nominal cost of NO_x emissions from natural gas / MBtu
 PG_{SO2} = nominal cost of SO₂ emissions natural gas / MBtu

The analysis assumes that an 18 watt fluorescent bulb replaces a 75 watt incandescent bulb. Thus, the savings per hour equal 57 watt-hours, or 0.057 kWh. However, two cases must always be considered: 1) the consumer heats with electricity and 2) the consumer heats with natural gas. In Case 1, net savings equal 0.057 kWh per hour of use. In Case 2, net savings equal $0.057 * 0.53 = 0.30$ kWh per hour of use.

Let $\delta = 1$ in case 1, and 0.53 in case 2.

Using the assumed efficiency of 55 percent for natural gas heating systems, the additional gas requirements per kWh of electricity saved = $(0.47 / 0.55) * 3412 = 0.0033$ MBtu / kWh.

1. Consumer Perspective

PV Fluorescent:

If $U_y \leq 1000$, $PV_{fc} = \$15.00$

If $U_y > 1,000$ $PV_{fc} = \sum_{j=1}^{\alpha} P_f * (1 / (1+R_c))^{\beta(j-1)}$,

where: $\alpha = U_y / 1000$
 $\beta = L_f / U_y$

PV Incandescents:

First, assume incandescents are purchased annually only.

If $U_y = 500$, then

$$PV_{ic} = (P_c * U_y / 1000) * [(1+R_c) / R_c] * (1 - 1 / (1+R_c)^{20}).$$

If $U_y \geq 1000$, then

$$PV_{ic} = (P_c * U_y / 1000) * [(1+R_c) / R_c] * (1 - 1 / (1+R_c)^{10}).$$

(The term in brackets is the standard formula for the present value of an annuity payment.)

PV of electricity saved:

If $U_y = 500$, then

$$PV_{ec} = 0.057 * \delta * U_y * P_e * [(1+R_c) / (R_c - E_e)] * (1 - ((1+E_e) / (1+R_c))^{20}).$$

If $U_y \geq 1000$, then

$$PV_{ec} = 0.057 * \delta * U_y * P_e * [(1+R_c) / (R_c - E_e)] * (1 - ((1+E_e) / (1+R_c))^{10}).$$

PV of natural gas used:

Case 1: $PV_{ngc} = 0$.

If $U_y = 500$, then

$$\text{Case 2: } PV_{ngc} = 0.0033 * 0.057 * U_y * P_g * [(1+R_c) / (R_c - E_g)] * (1 - ((1+E_g) / (1+R_c))^{20}).$$

If $U_y \geq 1000$, then

$$PV_{ngc} = 0.0033 * 0.057 * U_y * P_g * [(1+R_c) / (R_c - E_g)] * (1 - ((1+E_g) / (1+R_c))^{10}).$$

Thus, the net present value to the consumer of the fluorescent bulb retrofit, NPV_c , can be written:

$$NPV_c = PV_{ec} + PV_{ic} - PV_{fc} - PV_{ngc}.$$

2. Utility Perspective

PV Fluorescent:

If $U_y \leq 1000$, $PV_{fu} = \$15.00$

$$\text{If } U_y > 1000, PV_{fu} = \sum_{j=1}^{\alpha} P_f * (1 / (1 + R_u))^{\beta(j-1)},$$

PV of electricity saved:

Let $\delta = 1$ in case 1, and 0.53 in case 2.

If $U_y = 500$, then

$$PV_{eu} = 0.057 * \delta * U_y * MC_u * (1 + R_u) / R_u * [1 - 1 / (1 + R_u)^{20}].$$

If $U_y \geq 1000$, then

$$PV_{eu} = 0.057 * \delta * U_y * MC_u * (1 + R_u) / R_u * [1 - 1 / (1 + R_u)^{20}].$$

PV of emissions reductions:

If $U_y = 500$, then

$$PV_{emit-u} = (PE_{co2} + PE_{nox} + PE_{so2}) * 0.057 * U_y * \delta * [(1+i) / (R_u-i)] * (1 - ((1+i) / (1+R_u))^{20}).$$

If $U_y \geq 1000$, then

$$PV_{emit-u} = (PE_{co2} + PE_{nox} + PE_{so2}) * 0.057 * \delta * U_y * [(1+i) / (R_u-i)] * (1 - ((1+i) / (1+R_u))^{10}).$$

Thus, the net present value to the utility will be:

$$NPV_u = PV_{eu} + PV_{emit-u} - PV_{fu}.$$

3. Societal Perspective

PV Fluorescent:

If $U_y \leq 1000$, $PV_{fs} = \$15.00$

$$\text{If } U_y > 1000, PV_{fs} = \sum_{j=1}^{\alpha} P_f * (1 / (1 + R))^{j-1},$$

where: $\alpha = U_y / 1000$
 $\beta = L_f / U_y$

PV Incandescents:

First, assume incandescents are purchased annually only.

If $U_y = 500$, then

$$PV_{is} = (P_c * U_y / 1000) * [((1+R) / R) * (1 - 1 / (1+R)^{20})].$$

If $U_y \geq 1000$, then

$$PV_{is} = (P_c * U_y / 1000) * [((1+R) / R) * (1 - 1 / (1+R)^{10})],$$

PV of electricity saved:

If $U_y = 500$, then

$$PV_{es} = 0.057 * \delta * U_y * MC_s * (1+R) / R * [1 - 1 / (1+R)^{20}].$$

If $U_y \geq 1000$, then

$$PV_{es} = 0.057 * \delta * U_y * MC_s * (1+R) / R * [1 - 1 / (1+R)^{10}].$$

PV of natural gas used:

Case 1: $PV_{ngs} = 0$.

Case 2:

If $U_y = 500$, then

$$PV_{ngs} = 0.0033 * 0.057 * U_y * P_g * [(1+R) / (R-E_g) * (1 - ((1+E_g) / (1+R))^{20})].$$

If $U_y \geq 1000$, then

$$PV_{ngs} = 0.0033 * 0.057 * U_y * P_g * [(1+R) / (R-E_g) * (1 - ((1+E_g) / (1+R))^{10})].$$

PV of emissions reductions:

If $U_y = 500$, then

$$PV_{emit-s} = (PE_{co2} + PE_{nox} + PE_{so2}) * 0.057 * U_y * \delta * [(1+i) / (R-i) * (1 - ((1+i) / (1+R))^{20})] \\ - (PG_{co2} + PG_{nox} + PG_{so2}) * 0.0033 * 0.057 * U_y * [(1+i) / (R-i) * (1 - ((1+i) / (1+R))^{20})].$$

If $U_y \geq 1000$, then

$$PV_{emit-s} = (PE_{co2} + PE_{nox} + PE_{so2}) * 0.057 * \delta * U_y * [(1+i) / (R_u-i) * (1 - ((1+i) / (1+R_u))^{10})] \\ - (PG_{co2} + PG_{nox} + PG_{so2}) * 0.0033 * 0.057 * U_y * [(1+i) / (R-i) * (1 - ((1+i) / (1+R))^{10})].$$

Thus, the net present value to society will be:

$$NPV_u = PV_{es} + PV_{emit-s} + PV_{is} - PV_{fs} - PV_{ngs}.$$

Tables

TABLE 1

SL-18: 10 Year NPV Analysis
Consumer Perspective, Electric Space Heat
Investor Owned Utility

Marg. Elec. Price (per kWh)	\$0.053
Nominal Discount Rate:	18.00%
Incandescent Bulb Price:	\$15.00
Fluorescent Bulb Price:	\$0.50
Fluorescent Bulb Lifetime (hrs):	10,000
Incandescent Bulb Lifetime (hrs):	1,000

Net Present Value

hr/yr	PV Fluoro. Bulbs	PV Incand. Bulbs	k Wh/Year Savings	Electricity Price Real Escalation Rate						
				0.00%	0.50%	1.00%	1.50%	2.00%	2.50%	3.00%
500	\$15.00	\$1.82	15.11	(\$6.59)	(\$6.39)	(\$6.18)	(\$5.96)	(\$5.73)	(\$5.49)	(\$5.23)
1000	\$15.00	\$2.78	30.21	(\$2.17)	(\$1.99)	(\$1.80)	(\$1.61)	(\$1.42)	(\$1.22)	(\$1.02)
2000	\$23.37	\$5.56	60.42	\$2.29	\$2.65	\$3.02	\$3.40	\$3.79	\$4.19	\$4.60
3000	\$32.06	\$8.34	90.63	\$6.43	\$6.98	\$7.53	\$8.10	\$8.68	\$9.28	\$9.89
4000	\$40.82	\$11.13	120.84	\$10.50	\$11.22	\$11.96	\$12.72	\$13.50	\$14.29	\$15.11
5000	\$49.62	\$13.91	151.05	\$14.52	\$15.43	\$16.36	\$17.30	\$18.27	\$19.27	\$20.29
6000	\$58.44	\$16.69	181.26	\$18.54	\$19.62	\$20.73	\$21.87	\$23.04	\$24.23	\$25.45
7000	\$67.27	\$19.47	211.47	\$22.54	\$23.81	\$25.10	\$26.43	\$27.79	\$29.18	\$30.61
8000	\$76.10	\$22.25	241.68	\$26.53	\$27.98	\$29.46	\$30.98	\$32.53	\$34.13	\$35.75

**SL-18: 10 Year NPV Analysis
Consumer Perspective, Natural Gas Space Heat
Investor Owned Utility**

Z-L

TABLE 3

SL-18: 10 Year NPV Analysis
Consumer Perspective, Electric Space Heat
Publicly Owned Utility

Marg. Elec. Price (per kWh)	\$0.041
Nominal Discount Rate:	18.00%
Fluorescent Bulb Price:	\$15.00
Incandescent Bulb Price:	\$0.50
Fluorescent Bulb Lifetime (hrs):	10,000
Incandescent Bulb Lifetime (hrs):	1,000

hr/yr	Net Present Value			
	PV		Electricity Price Real Escalation Rate	
	Fluoro. Bulbs	Incand. Bulbs	kWh/Year Savings	
500	\$15.00	\$1.82	15.11	0.00% (\$8.10) 0.50% (\$7.95) 1.00% (\$7.78) 1.50% (\$7.61) 2.00% (\$7.44) 2.50% (\$7.25) 3.00% (\$7.06)
1000	\$15.00	\$2.78	30.21	0.00% (\$4.47) 0.50% (\$4.34) 1.00% (\$4.19) 1.50% (\$4.05) 2.00% (\$3.90) 2.50% (\$3.74) 3.00% (\$3.59)
2000	\$23.37	\$5.56	60.42	0.00% (\$2.32) 0.50% (\$2.04) 1.00% (\$1.75) 1.50% (\$1.46) 2.00% (\$1.16) 2.50% (\$0.85) 3.00% (\$0.54)
3000	\$32.06	\$8.34	90.63	0.00% (\$0.48) 0.50% (\$0.06) 1.00% \$0.37 1.50% \$0.81 2.00% \$1.25 2.50% \$1.71 3.00% \$2.19
4000	\$40.82	\$11.13	120.84	0.00% \$1.28 0.50% \$1.84 1.00% \$2.41 1.50% \$2.99 2.00% \$3.59 2.50% \$4.20 3.00% \$4.83
5000	\$49.62	\$13.91	151.05	0.00% \$3.00 0.50% \$3.70 1.00% \$4.41 1.50% \$5.15 2.00% \$5.89 2.50% \$6.66 3.00% \$7.44
6000	\$58.44	\$16.69	181.26	0.00% \$4.71 0.50% \$5.55 1.00% \$6.41 1.50% \$7.28 2.00% \$8.18 2.50% \$9.10 3.00% \$10.04
7000	\$67.27	\$19.47	211.47	0.00% \$6.41 0.50% \$7.39 1.00% \$8.38 1.50% \$9.41 2.00% \$10.46 2.50% \$11.53 3.00% \$12.63
8000	\$76.10	\$22.25	241.68	0.00% \$8.10 0.50% \$9.22 1.00% \$10.36 1.50% \$11.53 2.00% \$12.72 2.50% \$13.95 3.00% \$15.21

TABLE 4

SL-18: 10 Year NPV Analysis
Consumer Perspective, Natural Gas Space Heat
Publicly Owned Utility

Marginal Cost of Nat. Gas: \$5.00 per million Btu (MBtu)
Nat. Gas Real Esc. Rate: 2.80%

hr/yr	Net Present Value													
	PV Fluoro. Bulbs	PV Incand. Bulbs	kWh/Year Savings	Nat. Gas Use (MBtus)	PV Cost Nat Gas	Electricity Price Real Escalation Rate								
						0.00%	0.50%	1.00%	1.50%	2.00%	2.50%	3.00%		
500	\$15.00	\$1.82	28.50	0.094	\$4.57	(\$8.17)	(\$7.88)	(\$7.57)	(\$7.25)	(\$6.92)	(\$6.57)	(\$6.20)		
1000	\$15.00	\$2.78	57.00	0.187	\$6.48	(\$4.09)	(\$3.83)	(\$3.56)	(\$3.28)	(\$3.00)	(\$2.71)	(\$2.41)		
2000	\$23.37	\$5.56	114.00	0.375	\$12.97	(\$1.55)	(\$1.02)	(\$0.48)	\$0.07	\$0.63	\$1.21	\$1.80		
3000	\$32.06	\$8.34	171.00	0.562	\$19.45	\$0.67	\$1.46	\$2.27	\$3.10	\$3.95	\$4.81	\$5.70		
4000	\$40.82	\$11.13	228.00	0.750	\$25.93	\$2.82	\$3.87	\$4.95	\$6.05	\$7.18	\$8.34	\$9.52		
5000	\$49.62	\$13.91	285.00	0.937	\$32.41	\$4.93	\$6.24	\$7.59	\$8.97	\$10.38	\$11.82	\$13.31		
6000	\$58.44	\$16.69	342.00	1.124	\$38.90	\$7.02	\$8.60	\$10.21	\$11.87	\$13.56	\$15.30	\$17.07		
7000	\$67.27	\$19.47	399.00	1.312	\$45.38	\$9.10	\$10.94	\$12.83	\$14.76	\$16.73	\$18.76	\$20.83		
8000	\$76.10	\$22.25	456.00	1.499	\$51.86	\$11.18	\$13.28	\$15.44	\$17.64	\$19.90	\$22.21	\$24.58		

TABLE 5

SL-18 10 Year Analysis with Electric Space Heat
Includes Value of Air Pollutant Emissions Reductions
Electric Utility Perspective
Marginal Resource: Coal Plant

Fluorescent Bulb Price:	\$15.00
Weighted Cost of Capital:	9.30%
Value of CO ₂ Reductions:	0.0245 Per kWh
Value of SO ₂ Reductions:	0.0056 Per kWh
Value of NO _x Reductions:	0.0097 Per kWh

hr/yr	kWh/Year Savings	PV Bulbs	Value of SO ₂ Saved/Yr	Value of NO _x Saved/Yr	Value of CO ₂ Saved/Yr	Net Present Value						
						Levelized Avoided Cost of Electricity (cents/kWh)						
						5.00	6.00	7.00	8.00	9.00	10.00	11.00
500	15.11	\$15.00	\$0.08	\$0.15	\$0.37	(\$2.71)	(\$1.36)	(\$0.01)	\$1.34	\$2.69	\$4.04	\$5.39
1000	30.21	\$15.00	\$0.17	\$0.29	\$0.74	\$2.33	\$4.25	\$6.16	\$8.07	\$9.99	\$11.90	\$13.81
2000	60.42	\$27.27	\$0.34	\$0.59	\$1.48	\$7.39	\$11.22	\$15.05	\$18.87	\$22.70	\$26.53	\$30.35
3000	90.63	\$39.60	\$0.51	\$0.88	\$2.22	\$12.40	\$18.14	\$23.88	\$29.62	\$35.36	\$41.10	\$46.84
4000	120.84	\$51.94	\$0.68	\$1.17	\$2.96	\$17.39	\$25.04	\$32.69	\$40.35	\$48.00	\$55.66	\$63.31
5000	151.05	\$64.29	\$0.85	\$1.47	\$3.70	\$22.37	\$31.94	\$41.51	\$51.07	\$60.64	\$70.21	\$79.78
6000	181.26	\$76.64	\$1.02	\$1.76	\$4.44	\$27.36	\$38.84	\$50.32	\$61.80	\$73.28	\$84.76	\$96.24
7000	211.47	\$88.99	\$1.18	\$2.05	\$5.18	\$32.34	\$45.73	\$59.12	\$72.52	\$85.91	\$99.31	\$112.70
8000	241.68	\$101.34	\$1.35	\$2.34	\$5.92	\$37.32	\$52.62	\$67.93	\$83.24	\$98.55	\$113.85	\$129.16

TABLE 6

SL-18 10 Year Analysis with Nat. Gas Space Heat
Includes Value of Air Pollutant Emissions Reductions
Electric Utility Perspective
Marginal Resource: Coal Plant

hr/yr	kWh/Year Savings	PV Bulbs	Nat Gas Use (MBtus)	Value of SO ₂ Saved/Yr	Value of NO _x Saved/Yr	Value of CO ₂ Saved/Yr	Net Present Value							
							Levelized Avoided Cost of Electricity (cents/kWh)							
							5.00	6.00	7.00	8.00	9.00	10.00	11.00	
500	28.50	\$15.00	0.094	\$0.16	\$0.28	\$0.70	\$8.20	\$10.74	\$13.29	\$15.84	\$18.38	\$20.93	\$23.48	
1000	57.00	\$15.00	0.187	\$0.32	\$0.55	\$1.40	\$17.70	\$21.31	\$24.92	\$28.53	\$32.14	\$35.75	\$39.36	
2000	114.00	\$27.27	0.375	\$0.64	\$1.11	\$2.79	\$38.13	\$45.35	\$52.57	\$59.79	\$67.01	\$74.23	\$81.46	
3000	171.00	\$39.60	0.562	\$0.96	\$1.66	\$4.19	\$58.51	\$69.34	\$80.17	\$91.00	\$101.83	\$112.66	\$123.49	
4000	228.00	\$51.94	0.750	\$1.28	\$2.21	\$5.59	\$78.87	\$93.31	\$107.75	\$122.19	\$136.63	\$151.07	\$165.51	
5000	285.00	\$64.29	0.937	\$1.60	\$2.76	\$6.98	\$99.22	\$117.27	\$135.33	\$153.38	\$171.43	\$189.48	\$207.53	
6000	342.00	\$76.64	1.124	\$1.92	\$3.32	\$8.38	\$119.58	\$141.24	\$162.90	\$184.56	\$206.22	\$227.88	\$249.55	
7000	399.00	\$88.99	1.312	\$2.23	\$3.87	\$9.78	\$139.93	\$165.20	\$190.47	\$215.74	\$241.01	\$266.29	\$291.56	
8000	456.00	\$101.34	1.499	\$2.55	\$4.42	\$11.17	\$160.28	\$189.16	\$218.04	\$246.92	\$275.81	\$304.69	\$333.57	

TABLE 7

SL-18 10 Year Analysis with Electric Space Heat
Includes Value of Air Pollutant Emissions Reductions
Electric Utility Perspective
Marginal Resource: Combined Cycle CT

Fluorescent Bulb Price:	\$15.00
Weighted Cost of Capital:	9.30%
Value of CO ₂ Reductions:	0.0113 Per kWh
Value of SO ₂ Reductions:	0.0000 Per kWh
Value of NO _x Reductions:	0.0028 Per kWh

hr/yr	kWh/Year Savings	PV Bulbs	Value of			Net Present Value						
			SO ₂ Saved/Yr	NO _x Saved/Yr	CO ₂ Saved/Yr	Levelized Avoided Cost of Electricity (cents/kWh)						
						5.00	6.00	7.00	8.00	9.00	10.00	11.00
500	15.11	\$15.00	\$0.00	\$0.04	\$0.17	(\$6.29)	(\$4.94)	(\$3.59)	(\$2.24)	(\$0.89)	\$0.46	\$1.81
1000	30.21	\$15.00	\$0.00	\$0.08	\$0.34	(\$2.68)	(\$0.77)	\$1.14	\$3.06	\$4.97	\$6.89	\$8.80
2000	60.42	\$27.27	\$0.00	\$0.17	\$0.68	(\$2.64)	\$1.19	\$5.02	\$8.84	\$12.67	\$16.50	\$20.32
3000	90.63	\$39.60	\$0.00	\$0.25	\$1.02	(\$2.65)	\$3.09	\$8.83	\$14.57	\$20.32	\$26.06	\$31.80
4000	120.84	\$51.94	\$0.00	\$0.34	\$1.37	(\$2.67)	\$4.98	\$12.64	\$20.29	\$27.95	\$35.60	\$43.25
5000	151.05	\$64.29	\$0.00	\$0.42	\$1.71	(\$2.70)	\$6.87	\$16.44	\$26.00	\$35.57	\$45.14	\$54.71
6000	181.26	\$76.64	\$0.00	\$0.51	\$2.05	(\$2.73)	\$8.75	\$20.23	\$31.71	\$43.19	\$54.67	\$66.15
7000	211.47	\$88.99	\$0.00	\$0.59	\$2.39	(\$2.76)	\$10.63	\$24.03	\$37.42	\$50.81	\$64.21	\$77.60
8000	241.68	\$101.34	\$0.00	\$0.68	\$2.73	(\$2.80)	\$12.51	\$27.82	\$43.13	\$58.43	\$73.74	\$89.05

TABLE 8

SL-18 10 Year Analysis with Nat. Gas Space Heat
Includes Value of Air Pollutant Emissions Reductions
Electric Utility Perspective
Marginal Resource: Combined Cycle CT

hr/yr	kWh/Year Savings	PV Bulbs	Nat Gas Use (MBtus)	Value of SO ₂ Saved/Yr	Value of NO _x Saved/Yr	Value of CO ₂ Saved/Yr	Net Present Value						
							Levelized Avoided Cost of Electricity (cents/kWh)						
							5.00	6.00	7.00	8.00	9.00	10.00	11.00
500	28.50	\$15.00	0.094	\$0.00	\$0.08	\$0.32	\$1.44	\$3.99	\$6.53	\$9.08	\$11.63	\$14.18	\$16.72
1000	57.00	\$15.00	0.187	\$0.00	\$0.16	\$0.64	\$8.24	\$11.85	\$15.46	\$19.07	\$22.68	\$26.29	\$29.90
2000	114.00	\$27.27	0.375	\$0.00	\$0.32	\$1.29	\$19.21	\$26.43	\$33.65	\$40.87	\$48.09	\$55.31	\$62.53
3000	171.00	\$39.60	0.562	\$0.00	\$0.48	\$1.93	\$30.12	\$40.96	\$51.79	\$62.62	\$73.45	\$84.28	\$95.11
4000	228.00	\$51.94	0.750	\$0.00	\$0.64	\$2.58	\$41.03	\$55.47	\$69.91	\$84.35	\$98.79	\$113.23	\$127.67
5000	285.00	\$64.29	0.937	\$0.00	\$0.80	\$3.22	\$51.92	\$69.97	\$88.02	\$106.07	\$124.13	\$142.18	\$160.23
6000	342.00	\$76.64	1.124	\$0.00	\$0.96	\$3.86	\$62.81	\$84.47	\$106.14	\$127.80	\$149.46	\$171.12	\$192.78
7000	399.00	\$88.99	1.312	\$0.00	\$1.12	\$4.51	\$73.70	\$98.97	\$124.25	\$149.52	\$174.79	\$200.06	\$225.33
8000	456.00	\$101.34	1.499	\$0.00	\$1.28	\$5.15	\$84.59	\$113.47	\$142.36	\$171.24	\$200.12	\$229.00	\$257.88

TABLE 9

SL-18 10 Year Analysis with Electric Space Heat
Includes Value of Air Pollutant Emissions Reductions
Societal Perspective
Marginal Resource: Coal Plant

Fluorescent Bulb Price:	\$15.00
Incandescent Bulb Price:	\$0.50
Real Discount Rate:	3.00%
Value of CO ₂ Reductions:	0.0245 Per kWh
Value of SO ₂ Reductions:	0.0056 Per kWh
Value of NO _x Reductions:	0.0097 Per kWh

hr/yr	kWh/Year Savings	PV Fluoro. Bulbs	PV Incand. Bulbs	Value of SO ₂ Saved/Yr	Value of NO _x Saved/Yr	Value of CO ₂ Saved/Yr	Net Present Value						
							Marginal Cost of Electricity (cents/kWh)						
							5.00	6.00	7.00	8.00	9.00	10.00	11.00
500	15.11	\$15.00	\$3.72	\$0.08	\$0.15	\$0.37	(\$1.88)	(\$0.42)	\$1.05	\$2.52	\$3.98	\$5.45	\$6.92
1000	30.21	\$15.00	\$4.27	\$0.17	\$0.29	\$0.74	\$2.63	\$4.64	\$6.65	\$8.67	\$10.68	\$12.69	\$14.71
2000	60.42	\$27.94	\$8.53	\$0.34	\$0.59	\$1.48	\$11.01	\$15.04	\$19.07	\$23.09	\$27.12	\$31.15	\$35.17
3000	90.63	\$40.91	\$12.80	\$0.51	\$0.88	\$2.22	\$23.07	\$29.11	\$35.15	\$41.19	\$47.23	\$53.27	\$59.31
4000	120.84	\$53.89	\$17.06	\$0.68	\$1.17	\$2.96	\$38.82	\$46.87	\$54.92	\$62.98	\$71.03	\$79.09	\$87.14
5000	151.05	\$66.87	\$21.33	\$0.85	\$1.47	\$3.70	\$58.26	\$68.33	\$78.40	\$88.46	\$98.53	\$108.60	\$118.67
6000	181.26	\$79.85	\$25.59	\$1.02	\$1.76	\$4.44	\$81.40	\$93.49	\$105.57	\$117.65	\$129.73	\$141.81	\$153.89
7000	211.47	\$92.84	\$29.86	\$1.18	\$2.05	\$5.18	\$108.25	\$122.34	\$136.44	\$150.53	\$164.62	\$178.72	\$192.81
8000	241.68	\$105.82	\$34.12	\$1.35	\$2.34	\$5.92	\$138.79	\$154.90	\$171.01	\$187.11	\$203.22	\$219.33	\$235.44

SSL-18: 10 Year Analysis with Nat. Gas Spaceheat
Includes Value of Air Pollutant Emissions Reductions
Societal Perspective
Marginal Resource: Coal Plant

D-R2-25

TABLE 11

SL:18 10 Year Analysis with Electric Space Heat
Includes Value of Air Pollutant Emissions Reductions
Societal Perspective
Marginal Resource: Combined Cycle CT

Fluorescent Bulb Price:	\$15.00
Incandescent Bulb Price:	\$0.50
Real Discount Rate:	3.00%
Value of CO2 Reductions:	0.0113 Per kWh
Value of SO2 Reductions:	0.0000 Per kWh
Value of NOx Reductions:	0.0028 Per kWh

lir/yr	kWh/Year Savings	PV Fluoro. Bulbs	PV Incand. Bulbs	Value of SO2 Saved/Yr	Value of NOx Saved/Yr	Value of CO2 Saved/Yr	Net Present Value						
							Marginal Cost of Electricity (cents/kWh)						
							5.00	6.00	7.00	8.00	9.00	10.00	11.00
500	15.11	\$15.00	\$3.72	\$0.00	\$0.04	\$0.17	(\$3.84)	(\$2.37)	(\$0.91)	\$0.56	\$2.03	\$3.49	\$4.96
1000	30.21	\$15.00	\$4.27	\$0.00	\$0.08	\$0.34	(\$0.42)	\$1.59	\$3.61	\$5.62	\$7.63	\$9.65	\$11.66
2000	60.42	\$27.94	\$8.53	\$0.00	\$0.17	\$0.68	\$1.71	\$5.74	\$9.76	\$13.79	\$17.82	\$21.85	\$25.87
3000	90.63	\$40.91	\$12.80	\$0.00	\$0.25	\$1.02	\$4.30	\$10.34	\$16.39	\$22.43	\$28.47	\$34.51	\$40.55
4000	120.84	\$53.89	\$17.06	\$0.00	\$0.34	\$1.37	\$7.38	\$15.44	\$23.49	\$31.54	\$39.60	\$47.65	\$55.71
5000	151.05	\$66.87	\$21.33	\$0.00	\$0.42	\$1.71	\$10.95	\$21.02	\$31.09	\$41.15	\$51.22	\$61.29	\$71.35
6000	181.26	\$79.85	\$25.59	\$0.00	\$0.51	\$2.05	\$15.01	\$27.09	\$39.17	\$51.25	\$63.33	\$75.41	\$87.49
7000	211.47	\$92.84	\$29.86	\$0.00	\$0.59	\$2.39	\$19.56	\$33.65	\$47.75	\$61.84	\$75.94	\$90.03	\$104.13
8000	241.68	\$105.82	\$34.12	\$0.00	\$0.68	\$2.73	\$24.60	\$40.71	\$56.82	\$72.93	\$89.03	\$105.14	\$121.25

SL-18: 10 Year Analysis with Nar. Gas Spaceheat
Includes Value of Air Pollutant Emissions Reductions
Societal Perspective
Marginal Resource: Combined Cycle CT

T-12

END

**DATE
FILMED
6/01/92**