**DOE/PC/73743-T8
(DE92014840)**

**MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS FROM COAL
FLAMES**

Final Report

**By
G. H. Newton
C. Schleber
R. G. Socha
J. C. Kramlich**

April 1990

Work Performed Under Contract No. AC22-87PC79743

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Energy and Environmental Research Corporation
Irvine, California**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, ~~NTIS-84-000001~~.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS FROM COAL FLAMES

DOE/PC/79743--T8

DE92 014840

Final Report

Prepared for:

**Dr. Soung S. Kim
Technical Project Officer**

**U. S. Department of Energy
Pittsburgh Energy Technology Center**

Under

Contract No. DE-AC22-87PC79743

Prepared by:

**G. H. Newton
C. Schieber
R. G. Socha
J. C. Kramlich**

***Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718-2798***

April, 1990

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
TABLE OF CONTENTS	ii
LIST OF FIGURES	iv
LIST OF TABLES.	
1.0 EXECUTIVE SUMMARY.	1-1
1.1 Experimental Facilities.	1-2
1.2 Modeling	1-2
1.3 Results - Global Experiments	1-3
1.4 Results - Mechanistic Experiments	1-5
1.5 Results - Process Simulation	1-6
1.6 Conclusion	1-6
2.0 INTRODUCTION	2-1
3.0 EXPERIMENTAL APPROACH.	3-1
3.1 Isothermal Reactor	3-1
3.2 Ash Characterization Furnace	3-1
3.3 Laser Diffraction Particle Size Measurements	3-4
3.3.1 Theoretical Background	3-4
3.3.2 Theoretical Issues	3-10
3.3.3 Modification Approach.	3-13
3.4 Cascade Impactor Measurements.	3-17
3.5 Coal Preparation	3-19

4.0	THEORETICAL APPROACH	4-1
4.1	Mineral Matter in Coal	4-1
4.2	Submicron Aerosols	4-3
4.3	Residual Fly Ash	4-11
4.4	Breakup Model.	4-15
5.0	GLOBAL EXPERIMENTS	5-1
5.1	Results.	5-1
5.2	Comparison to Breakup Model.	5-1
5.3	Comparison to Modified Breakup Model	5-15
5.4	Summary.	5-27
6.0	MECHANISTIC EXPERIMENTS	6-1
6.1	Cleaned Cuts	6-1
6.2	Mechanistic Experiments - Sized Cuts	6-10
6.3	Mechanistic Experiments - Grinding	6-40
6.4	Summary.	6-43
7.0	PROCESS SIMULATION	7-1
8.0	CONCLUSIONS.	8-1
9.0	REFERENCES	9-1

APPENDICES

A.	PARTICLE SIZE DISTRIBUTIONS OF RAW COALS AND THEIR ASHES.	A-1
B	PARTICLE SIZE DISTRIBUTIONS OF CLEANED COALS.	B-1
C	PARTICLE SIZE DISTRIBUTIONS OF SIZED COALS.	C-1

LIST OF FIGURES

Figure 1-1.	Correlation of breakup number with coal rank.	1-4
Figure 1-2.	Particle size distributions of ash from raw coals	1-6
Figure 1-3	Differential size distributions of four raw coals (taken from the data plotted in Figure 1-2)	1-7
Figure 1-4.	Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and, except for the Beulah coal, the release of 2 μ m inclusions.	1-8
Figure 1-5	Cumulative size distributions for ash from whole and cleaned coal.	1-10
Figure 1-6.	Heights of 2 μ m peaks from differential size distributions of raw and cleaned Utah and Illinois coals	1-11
Figure 1-7.	Comparison of ash size distributions of coal ground to the given size and coal ground first and subsequently sieved to the given size.	1-13
Figure 2-1a	Changes in size distribution on a furnace emission caused by an ESP, and the subsequent alveolar retention size distribution .2-2	
Figure 2-1b	Precipitator efficiency curves	2-2
Figure 2-1c	Absorption of particles in the human pulmonary system. . . .	2-2
Figure 3-1	Isothermal reactor and precombustor assembly	3-2

Figure 3-2	Ash characterization furnace	.3-3
Figure 3-3	Conceptual setup for evaluating diffracted light intensity at any angle from the initial light direction	.3-6
Figure 3-4	Configuration for diffraction sizing instrument	.3-8
Figure 3-5	Scattering angle/intensity relationship	.3-11
Figure 3-6	Mie scattering comparison to Fraunhofer	.3-12
Figure 3-7	Optical configuration for sample cell between lens and detector	.3-15
Figure 3-8	Orientation of the laser diffraction system	.3-16
Figure 3-9	Schematic showing the influence of refraction at the liquid/air interface on the angle of scatter.	.3-18
Figure 4-1	Mechanisms of fine particulate formation.	.4-2
Figure 4-2	Geometry for the formation of aerosol in the coal particle boundary layer (from Senior and Flagan 1982).	.4-6
Figure 4-3	Particle mass size distribution from a lignite. Squares are 15% oxygen, circles are 40% (Neville et al., 1981)	4-10
Figure 4-4	Comparison of size distributions from model and data (Flagan, 1979)	.4-10
Figure 4-5	Comparison of number density and mass size distributions for unstaged Utah coal combustion	.4-10
Figure 4-6	Gaussian distribution used in modified breakup model.	.4-17

Figure 5-1.	Influence of oxygen concentration on ash particle size. . . .	5-4
Figure 5-2	Correlation of breakup number with various coal properties	5-6
Figure 5-3	Comparison of ash particle size distributions and the distribution predicted by the breakup model	5-8
Figure 5-4	Comparison of ash particle size distributions and the distribution predicted by the breakup model	5-9
Figure 5-5	Comparison of ash particle size distributions and the distribution predicted by the breakup model	5-11
Figure 5-6	Mineral content as a function of coal particle size	5-12
Figure 5-7	Mineral content as a function of coal particle size	5-13
Figure 5-8	Mineral content as a function of coal particle size	5-14
Figure 5-9	Ash size distributions of raw coals	5-16
Figure 5-10	Comparison of cascade impactor ash size distributions and the breakup model	5-17
Figure 5-11	Comparison of cascade impactor ash size distributions and the breakup model	5-17
Figure 5-12	Comparison of cascade impactor ash size distributions and the breakup model	5-19
Figure 5-13	Comparison of cascade impactor ash size distributions and the breakup model	5-20

Figure 5-14	Differential size distributions of four raw coals (taken from the data plotted in Figure 5-9).	5-22
Figure 5-15	Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.	5-23
Figure 5-16	Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.	5-24
Figure 5-17.	Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.	5-25
Figure 5-18.	Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism	5-26
Figure 6-1	Illustration of the application of the physical coal cleaning process to the Illinois coal.	6-3
Figure 6-2	Cumulative size distributions for ash from the firing of the various cleaning cuts. Data obtained with a cascade impactor.	6-4
Figure 6-3	Quantitative comparison of ash size distributions from the original Illinois coal, and the sum of the ash from the cuts	6-6
Figure 6-4	Cumulative size distributions for ash from whole and cleaned coal.	6-7

Figure 6-5	Ash size distributions normalized to the mineral content of the original coal for the Illinois original coal, the Rougher Cut, and the Third Cleaner Concentrate.	.6-8
Figure 6-6	Ash size distributions of ashes	.6-9
Figure 6-7	Ash size distributions of raw and cleaned coal.	.6-11
Figure 6-8	Ash size distributions of raw and cleaned coal.	.6-12
Figure 6-9	Ash size distributions of sized coal.	.6-14
Figure 6-10	Ash size distributions of cleaned and size coal	.6-15
Figure 6-11	Ash size distributions of sized coal	.6-16
Figure 6-12	Ash size distributions of sized coal.	.6-17
Figure 6-13.	Differential size distributions of four raw coals (taken from the data plotted in Figure 6-9).	.6-19
Figure 6-14.	Differential size distributions of four cleaned coals (taken from the data plotted in Figure 6-10).	.6-20
Figure 6-15.	Differential size distributions of four raw coals (taken from the data plotted in Figure 6-11).	.6-21
Figure 6-16.	Differential size distributions of four cleaned coals (taken from the data plotted in Figure 6-12).	.6-22
Figure 6-17.	Heights of 2 μ m peaks from differential size distributions in Figures 6-13 through 6-16	.6-23

Figure 6-18. Comparison of cascade impactor ash size distributions and the breakup model	.6-24
Figure 6-19. Comparison of cascade impactor ash size distributions and the breakup model	.6-25
Figure 6-20. Comparison of cascade impactor ash size distributions and the breakup model	.6-26
Figure 6-21. Comparison of cascade impactor ash size distributions and the breakup model	.6-27
Figure 6-22. Comparison of cascade impactor ash size distributions and the breakup model	.6-28
Figure 6-23. Comparison of cascade impactor ash size distributions and the breakup model	.6-29
Figure 6-24. Comparison of cascade impactor ash size distributions and the breakup model	.6-30
Figure 6-25. Comparison of cascade impactor ash size distributions and the breakup model	.6-31
Figure 6-26. Comparison of cascade impactor ash size distributions and the breakup model	.6-32
Figure 6-27. Comparison of cascade impactor ash size distributions and the breakup model	.6-33
Figure 6-28. Comparison of cascade impactor ash size distributions and the breakup model	.6-34
Figure 6-29. Comparison of cascade impactor ash size distributions and the breakup model	.6-35

Figure 6-29. Comparison of cascade impactor ash size distributions and the breakup model	.6-35
Figure 6-30. Comparison of cascade impactor ash size distributions and the breakup model	.6-36
Figure 6-31. Comparison of cascade impactor ash size distributions and the breakup model	.6-37
Figure 6-32. Comparison of cascade impactor ash size distributions and the breakup model	.6-38
Figure 6-33. Comparison of cascade impactor ash size distributions and the breakup model	.6-39
Figure 6-34. Ash size distributions of Utah coal ground to various sizes	.6-41
Figure 6-35. Differential size distributions of Utah coal ground to various sizes and a coal ground to a specified size	.6-42
Figure 6-36. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.	6-44
Figure 6-37. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.	6-45
Figure 6-38. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.	6-46
Figure 6-39. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.	6-47
Figure 7-1. Comparison of particle size distributions of ash sampled from pilot and full scale facilities	.7-2

- Figure 7-2. Comparison of particle size distributions of ash sampled from pilot and full scale facilities7-3
- Figure 7-3. Comparison of particle size distributions of ash sampled from pilot and full scale facilities7-4
- Figure 7-4. Comparison of particle size distributions of ash sampled from pilot and full scale facilities7-5
- Figure 7-5. Comparison of particle size distributions of ash sampled from pilot and full scale facilities7-6

LIST OF TABLES

Table 5-1.	Coals Tested	.5-2
Table 5-2.	Properties of Coals Tested.	.5-3
Table 5-3.	Number of Ash Particles per Coal Particle Required to Fit the Data.	.5-5
Table 5-4.	Carbon Content of Australian Bit. #2 Ash.	.5-7
Table 6-1.	Results from Coal Cleaning.	.6-2
Table 6-2.	Proximate Analysis Results (As Received).	.6-13
Table 6-3.	Mass Mean Diameters of Size Cuts.	.6-13
Table 6-4.	Breakup Numbers for Ash from Sized Coals.	.6-40
Table 7-1.	Properties of Coals Tested in Process Simulations.	.7-7

1.0 EXECUTIVE SUMMARY

The primary objective of this program was to provide a basic understanding of the principal processes that govern the formation of particulate matter in the 0.5 - 10 μm size range in pulverized coal flames. Particles in this size range are of interest for several reasons:

- A considerable portion of the ash produced by coal combustion falls in this range;
- electrostatic precipitators are least efficient in this range;
- ash in this size range are enriched in heavy, toxic metals; and
- particles in this size range are preferentially deposited in the alveoli of the human lung.

The mechanism that produces ash particles in this size range is not clear. Particle sizes smaller than the 0.5 - 10 μm size range are generally accepted to result from a vaporization/condensation mechanism while particles larger than this size result from the coalescence of ash in coal particles which may breakup as they burn. This program combined experimental and theoretical studies to understand the mechanisms which control the production of ash in the 0.5 - 10 μm size range.

The experimental program was divided into three phases:

- Global experiments which were designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter.
- Mechanistic experiments which focussed on providing a quantitative evaluation of the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter.
- Process simulation experiments which compared data taken in a pilot scale facility to data taken in a full scale boiler.

The theoretical portion of the program involves the development of a model which predicts the particle size distribution of fine particulate matter in the 0.5 - 10 μm size range. The data obtained from the global and mechanistic experiments were used to determine the validity of the various mechanisms potentially responsible for the formation of fine particulate matter. Those mechanisms which appeared promising were incorporated into a breakup model to determine whether they could be used to predict the yield of particulate matter in the 0.5 - 10 μm size range.

1.1 Experimental Facilities

Ash was sampled from two research facilities: the Isothermal Reactor (ITR); and the Ash Characterization Furnace. The ITR is an electrically heated drop tube furnace down-fired by a premixed flat-flame burner. Sampling residence times range from .1 - 1 s with isothermal operating temperatures ranging from 500 - 1500°C. The Ash Characterization furnace was designed to simulate the complete thermal history of full scale utility boilers. This facility is down-fired and contains several heat exchanger systems to allow the simulation of convective passages and match the profile of a full scale boiler.

Particle size distributions were measured in two ways: ash was collected, dispersed into a liquid phase, and the distribution measured with a "Malvern" laser diffraction particle size analyzer; and by the use of an "Anderson" cascade impactor. The Malvern was used to measure particle sizes of ash samples from 2 μm to 100 μm while the cascade impactor was used to measure ash size distributions in the 0.2 to 6.5 μm size range. Particle size distributions of coals were measured by pneumatically spraying the coal in front of the Malvern instrument.

1.2 Modeling

The particle size distributions of ashes were matched using the breakup model. The breakup model assumes if a coal particle does not break apart that all of the ash within the coal particle will coalesce into a single ash particle.

If the coal particle breaks into two or more particles than the ash within each of the smaller particles will form a single ash particle. The model was modified by allowing a single coal particle to produce a distribution (Gaussian) of different sized coal particles. Further modifications were made based on the results of the data obtained during the program.

1.3 Results - Global Experiments

This portion of the program focussed on determining the influence of global parameters on the formation of ash particle size distributions. Varying oxygen concentration and temperature had no influence on the measured ash particle size distributions.

The data was compared against the simple breakup model in order to gain an understanding of the mechanisms which control the formation of ash particles. Shown in Figure 1-1, lower rank coals required higher breakup numbers to fit the data while higher rank coals required lower breakup numbers. Three types of deviations of the breakup model from the data were observed:

- The yield of ash particles greater than 10 μm were greater than could be predicted. This was attributed to incomplete combustion at lower oxygen concentrations.
- Ash particle size distributions were larger than could be predicted by the breakup model. This occurred for one coal and was attributed to the tendency of this coal to stick together and form large agglomerates.
- The yield of ash at particle sizes under 10 μm was less than could be predicted. It was determined that this was not due to variations in the mineral content in the coal with particle size. The possibility existed that the procedure used to disperse ash particles for the measurement of ash size distribution by the Malvern laser instrument could not disperse particles under 2 μm and therefore biased the results towards larger

Figure 1-1. Correlation of breakup number with coal rank.

particles. Further modeling was therefore performed only on ash size distributions taken with the cascade impactor.

The ash particle size distributions measured with the cascade impactor showed two deviations from the breakup model. First, ash size distributions for four coals measured with the cascade impactor, plotted in Figure 1-2, showed percent fractions of ash under $0.3\ \mu\text{m}$ ranging up to 6%. The breakup model, however, typically predicts that no particles will be present in under $0.3\ \mu\text{m}$. This was attributed to the contribution of ash particles from the vaporization/condensation mechanism. Second, differential plots of the ash size distributions, plotted in Figure 1-3, showed a peak at $2\ \mu\text{m}$, a range where the breakup model predicts that the particle size distribution should be tailing off. The $2\ \mu\text{m}$ peak was attributed to included ash which was released either during grinding or during the initial stages of the combustion process and retained its original size. Two further modifications to the breakup model were made to improve its ability to match the measured data. These were:

- Assumed that particles under $0.3\ \mu\text{m}$ resulted from the vaporization/condensation mechanism; and
- Assumed that included mineral matter within a short distance of the coal's particle surface was released during grinding or during the early stages of combustion and retained its original size.

Including these modifications into the model substantially improved the match between the model and data, plotted in Figure 1-4, for the Utah, Illinois, and Eagle Butte coals. The distance used in the model within which included mineral matter was allowed to be released and retain its original size, $0.25 - 1.0\ \mu\text{m}$ for the three coals considered, is reasonable. The fit between the model and Beulah coal, which is known to not contain included mineral matter, was excellent when just the vaporization/condensation mechanism was included (also shown in Figure 1-4).

Figure 1-2. Differential size distributions of four raw coals (taken from the data plotted in Figure 1-2).

Figure 1-3 Differential size distributions of four raw coals
(taken from the data plotted in Figure 1-2)

Figure 1-4. Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and, except for the Beulah coal, the release of $2 \mu\text{m}$ inclusions.

1.4 Results - Mechanistic Experiments

This part of the program focussed on experiments designed to determine the influence of various mechanism which have the potential for contributing to the formation of fine particulate matter in the 0.5 - 10 μm size range. Three sets of experiments were performed: 1) a study to determine the influence of coal cleaning (removing extraneous mineral matter) of ash formation; 2) sizing raw and cleaned coals (which had been ground first) to determine the influence of coal particle size; and 3) grinding a coal to different sizes to determine the influence of grinding.

Comparison of ash size distributions from raw and cleaned coal, plotted in Figure 1-5, indicated that cleaning coals increased the yield of ash particles under 1 μm . The presence of the extraneous mineral matter in the raw coal appeared to reduce the yield of fine particulate matter under 1 μm . It was hypothesized that fine particulate matter released as the char particle is consumed may become attached to the relatively large extraneous mineral matter particles which were imbedded on the surface of coal particles during grinding. The addition of extraneous mineral matter to a coal which does not contain any extraneous mineral matter, reduce the yield of fine particulate matter under 0.5 μm by half.

The 2 μm peaks in the differential ash size distributions observed in the global experiments were also observed to occur in those of the sized coals. The height of the peaks, plotted in Figure 1-6, decreased as coal particle size was increased, which is consistent with the hypothesis that the 2 μm peaks resulted from included mineral matter released either during grinding or the early stages of combustion. (Smaller coal particles will have less included mineral matter near the surface than larger particles). The fit between the modified breakup model and the ash size distributions from -18 μm and +18 - 37 μm coals was excellent while the fit for the larger sized coals was good. Inconsistencies between the model and the data for the larger sized coals was attributed to either: the use of an included mineral size of 2 μm (obtained from the literature) rather

Figure 1-5. Cumulative size distributions for ash from whole and cleaned coal.

Figure 1-6. Heights of 2 μ m peaks from differential size distributions of raw and cleaned Utah and Illinois coals.

than the measured included size distributions of the individual coals; or, a greater degree of aerosol production by larger coal particles.

The grinding experiments involved grinding four batches of coal to four size ranges ($-20\text{ }\mu\text{m}$, $+20 - 40\text{ }\mu\text{m}$, $+40 - 80\text{ }\mu\text{m}$, $+80\mu\text{m}$). As with the sized experiments discussed in the previous section, a $2\text{ }\mu\text{m}$ peak could be observed in the differential particle size distributions of the smaller size cuts. This data was compared to that of the ash size distributions from the sized experiments (where a single batch of coal was prepared by first grinding and then sieving to four size ranges: $-18\text{ }\mu\text{m}$, $+18 - 37\text{ }\mu\text{m}$, $+37 - 85\text{ }\mu\text{m}$, and $+85\text{ }\mu\text{m}$). The $-18\text{ }\mu\text{m}$ coal which had been ground and then sieved produced significantly less coal than the coal which had been ground to $-20\text{ }\mu\text{m}$ (Figure 1-7). This was attributed to the greater quantity of extraneous mineral matter (including mineral matter which was originally extraneous and included mineral matter released during grinding) present in the $-18\text{ }\mu\text{m}$ ground and sieved coal. This agreed with the findings of the cleaning experiments where the presence of extraneous mineral matter appeared to reduce the yield of ash under $1\text{ }\mu\text{m}$.

1.5 Results - Process Simulation

The process simulation experiments compared particle size distributions of ash sampled from a pilot scale facility (with conditions adjusted to simulate those in full scale facilities) and ash sampled from full scale utility boilers. The particle size distributions from the two different scale facilities were comparable, thus validating the use of small scale facilities to study the mechanisms which control the formation of ash from the combustion of coal.

1.6 Conclusions

The primary objective of this program was to provide a basic understanding of the mechanisms that govern the formation of particulate matter in the $0.5 - 10\text{ }\mu\text{m}$ size range in pulverized coal flames. Particle sizes smaller than the $0.5 - 10\text{ }\mu\text{m}$ size range are generally accepted to result from a vaporization/condensation mechanism while particles larger than this size result from the

Figure 1-7. Comparison of ash size distributions of coal ground to the given size and coal ground first and subsequently sieved to the given size.

coalescence of ash in coal particles which may breakup as they burn. Two important findings resulted from this work.

Data taken under this program showed a relatively large fraction of ash present at 2 μm , approximately the same size as the mass mean diameter of included mineral matter (typically ranges from 0.5 μm to 5 μm). It was concluded that this ash resulted from included mineral matter which is released either during grinding or the early stages of combustion. Modification of the breakup model to account for the release of included mineral matter near the surface of the coal particles (and for the vaporization/condensation mechanism) allowed the model to fit the data.

Although the goal of this work was to study the formation mechanisms of ash particles in the 0.5 - 10 μm size range, the data obtained under this program provided information on a potential means for reducing the yield of ash under 0.5 μm . Ash under 0.5 μm results from minerals vaporized during combustion which subsequently nucleate and condense out of the gas phase on any available surface. Data taken under this program showed that cleaning coal by removing external mineral matter increased the yield of ash under 1 μm . This could be due to vaporized minerals condensing on external mineral matter which had become embedded on the surface of the coal particle during grinding. This suggests that adding external matter to a coal could reduce the yield of ash under 1 μm . Doing this for a coal which contained no external or included mineral matter (only atomically dispersed minerals) reduced the yield of ash under 1 μm by one-half. Adding the external mineral matter (or possibly, ash collected from the particulate collection device) during grinding could result in a greater reduction.

2.0 INTRODUCTION

The primary objective of this program was to provide a basic understanding of the principal processes that govern the formation of particulate matter in the 0.5 - 10 μm size range in pulverized coal flames. Particulate matter from the combustion of coal is generally recognized to fall into two categories:

- 1) A broadly size component that is usually termed the "fly ash" or "residual fly ash." This constitutes the bulk of the mineral matter generated by the flame. It is formed by direct physical and chemical transformations (such as melting and agglomeration) of the coal mineral matter and is the product of processes such as the melting and agglomeration.
- 2) A narrowly sized component that is formed from mineral matter which is vaporized and then nucleates, condensates and coagulates to form relatively small ash particles. These particles have been enriched in heavy metals and represent a potential health hazard. This component represents a small fraction of the total mineral emissions and is frequently termed the "submicron ash" or the "aerosol ash." The size of these particles does not exceed 0.5 μm .

Particles in the 0.5 - 10 μm are of interest for two reasons. Figure 2-1a illustrates a particle size distribution which is representative of uncontrolled emissions from pulverized coal fired power plants. The contribution of the two modes is clearly shown by (1) the narrow peak centered at 0.2 μm and (2) the broad peak centered in the 10 - 100 μm size range. The measured efficiency of an electrostatic precipitator (ESP), illustrated in Figure 2-1b, is plotted as the percent penetration and percent collection efficiency as a function of particle diameter.

If the collection efficiency shown in Figure 2-1b is combined with the uncontrolled emissions curve shown in Figure 2-1a, then an estimate of the particle size distribution exiting an ESP can be made. This is shown as the

Figure 2-1a. Changes in size distribution on a furnace emission caused by an ESP, and the subsequent alveolar retention size distribution.

Figure 2-1b. Precipitator efficiency curves.

Figure 2-1c. Absorption of particles in the human pulmonary system.

1-7

"after ESP" curve in Figure 2-1a. The resulting distribution is bimodal because of the original bimodality of the particle size distribution. Figure 2-1c illustrates the fractional retention of various sized particles in the human alveolar region. The various regimes in this figure are controlled by:

- Above 1 μm the retention of particles drops because larger particles are preferentially collected on the bronchial passageways by inertial impaction. Particles collected in the bronchial passageways are usually expelled by coughing, etc.
- The maximum at 1 μm is due to the preferential inertial impaction of those particles in the smaller size of the alveola.
- The minimum at 0.1 μm occurs because these particles lack the inertia to be efficiently impacted onto the alveola and are simply expelled.
- Below 0.1 μm the efficiency increases due the Brownian diffusion of particles into the alveolar walls.

Combining the "After ESP" curve of Figure 2-1a with Figure 2-1c provides an estimate of the size distribution of particles retained in the human lung ("Deposition in Aveola" in Figure 2-1a). This curve suggests that alveolar deposition due to the emission of particulate matter from the combustion of coal will be dominated by particles in the 0.5 - 10 μm size range.

Particles in the 0.5 - 10 μm size range are therefore most likely to be emitted from a power plant and to be retained in the human body where they may persist as an irritant. Particle is this size range also have a relatively large surface area and therefore tend to have their surfaces enriched with heavy metals vaporized during coal combustion. The toxicity of these heavy metals represents an additional health hazard.

The mechanism by which fly ash in the 0.5 - 10 μm size range is formed is not yet clear. Particles smaller than this size range result from the

vaporization/condensation mechanism and models have been developed which can predict their formation. Particles larger than this size range are generally accepted to result the breakup mechanism, where a coal particle breaks up into smaller particles (typically 3 - 5) as it burns, with all of the mineral matter within each of the smaller particles coalescing to form a single ash particle. The breakup model of Flagan and Friedlander (1978) has been successful in predicting ash particle size distributions above 10 μm . Combined predictions by the breakup model and models of the vaporization/condensation model, however, typically under-predict the yield of particulate matter in the 0.5 - 10 μm size range.

The goal of this program was to develop an understanding of the mechanism(s) which control the yield of particulate matter in the 0.5 - 10 μm size range. This was done by conducting an experimental program and using the results of this experimental work in the development of a model to predict the yield of fine particulate matter (0.5 - 10 μm).

The experimental portion of this project consists of a study of the fundamental mechanisms at laboratory scale. The experimental program was divided into three phases:

- Global experiments which were designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter. These experiments were conducted in a laboratory scale reactor designed so that the coal particles were injected in a dilute phase to reduce interactions between coal particles. This allowed the influence of parameters such as gas phase temperature and oxygen to be studied without the combustion of neighboring coal particles influencing their values.
- Mechanistic experiments which focussed on providing a quantitative evaluation of the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter. These experi-

ments were also run in a dilute phase in a laboratory scale reactor to reduce interactions between coal particles.

- Process simulation experiments which compared data taken in a pilot scale facility to data taken in a full scale boiler. These experiments were run in a pilot scale facility at coal densities similar to those found in full scale boilers in order to simulate full scale conditions as closely as possible.

The theoretical portion of the program involves the development of a model which predicts the particle size distribution of fine particulate matter in the 0.5 - 10 μm size range. The data obtained from the global and mechanistic experiments were used to determine the validity of the various mechanisms potentially responsible for the formation of fine particulate matter. Those mechanisms which appeared promising were incorporated into a breakup model to determine whether they could be used to predict the yield of particulate matter in the 0.5 - 10 μm size range. The model is used as an interpretive tool throughout this report.

3.0 EXPERIMENTAL APPROACH

Ash samples from various coal samples were obtained in the ITR, a bench scale isothermal reactor, and the Ash Characterization Furnace, a pilot scale reactor. Particle size measurements were performed in two ways: via a commercially available laser diffraction instrument (Malvern) and with a cascade impactor.

3.1 Isothermal Reactor

Testing is performed in the Isothermal Reactor (ITR) which is illustrated in Figure 3-1. The ITR consists of a 10 cm diameter ceramic tube mounted in a three-zone electric furnace. The heated zone is 0.9 m long. Three independently controlled heating zones, separated by baffles, ensure that a flat temperature profile is maintained over the heated length. The high temperature gas flow is supplied by a gas flame fired in the side chamber at the top of the reactor. The furnace is capable of operating at temperatures up to 1500°C.

The ITR is down fired by a precombustor coupled with a sliding burner (Figure 3-1) coupled with a sliding burner. The burner is a premixed, water-cooled, flat-flame burner in a square stainless steel chimney. Due to heat losses through the chimney, moving the burner position changes the downstream temperature independently of the gas velocity and burner stoichiometry. Coal is injected directly into the venturi throat illustrated in Figure 3-1. The venturi has a 60° cone located 1.3 cm below the coal injector which converges to 2.5 cm. This is followed by a 2.5 cm straight section and section which diverges at a 15° angle to the 10 cm diameter of the reactor. This venturi throat ensures that the coal is uniformly distributed across the width of the reactor.

3.2 Ash Characterization Furnace

The ash characterization furnace used in the process simulation is shown in Figure 3-2. This facility was designed to simulate the complete thermal history

Figure 3-1. Isothermal reactor and precombustor assembly.

Figure 3-2. Ash characterization furnace

of full scale utility boilers. The burner, with a nominal capacity of 70,000 BTU/hr, is located at the top of the combustion chamber and is down-fired. The combustion chamber is 25 cm. in diameter and the furnace zone comprises three separate sections insulated with four layers of refractory. A simulated convective zone consists of three refractory-lined, air or water jacketed sections, and one air cooled section made of a stainless steel pipe packed with W-shaped tubes. Either air or water can be used as the coolant for each of the three jacketed sections to allow changes in the heat extraction profile. Varying the amount of air through the W-shaped loops in the last convective section allows control of the final temperature.

3.3 Laser Diffraction Particle Size Measurements

A Malvern 2600 HSD laser diffraction particle size analyzer was used to measure particle size distributions of coal and ash samples. Coal size distributions were measured using standard procedures and by pneumatically spraying the coal in front of the instrument's Fourier transform lens.

The purpose of this program was to determine the mechanisms which control the formation of ash particles in the 0.5 to 10 μm size range. The Malvern was therefore modified to measure ash particles down to 0.5 μm .

3.3.1 Theoretical Background

The scattering and absorption of light by particles is one of the classical problems of physics. In general, the interaction of light with solid particles or liquid droplets can come about through a number of mechanisms. These include:

- Diffraction
- Refraction
- Scatter via induced dipole moment
- Reflection

To first principle, all of these processes are described by Maxwell's equations. These equations were solved for the region within and near spherical particles in 1908 to yield the Mie equations. The Mie equations, therefore, provide a complete description of the interaction of light with spherical particles, independent of wavelength.

The extreme complexity of the Mie equations has led to the development of simplified forms that are appropriate for specialized cases. If the particle is small relative to the wavelength, then most of the light scattering is due to the induced dipole within the particle. This leads to Rayleigh scattering. Of more practical importance for the present case is diffraction, which dominates when the particle is much larger than the wavelength. Diffraction can be thought of as arising from the bending of the light around the edge of an obstruction. This leads both to scattering (i.e., a change in light direction from the original course) and to interference (i.e., light scattered from different particle surfaces may add or interfere).

The Malvern instrument is generally based on diffraction. Specifically, this is Fraunhofer diffraction, which is a simplification which results when the light approaching the particle is parallel, and the scattering is obtained at distances which are large relative to the particle diameter. Figure 3-3 illustrates the geometry that describes Fraunhofer diffraction. The diffraction from the particle will cause a pattern to form on the spherical screen which will consist of a central maximum and series of light and dark concentric rings. (Note any non-diffracted incident light may be excluded. As shall be seen shortly, this exclusion can be accomplished by use of lenses.)

The maximum intensity occurs at $w = 0$ and is called I_0 . The diffracted light at any angle can thus be represented as the product of I_0 and a function that gives the shape of the scattering curve. For Fraunhofer diffraction this is:

$$I(w) = I_0 [2J_1(dw/\lambda)]^2 \quad (3-1)$$

Figure 3-3. Conceptual setup for evaluating diffracted light intensity at any angle ω from the initial light direction.

Here, λ is the light wavelength and J is the Bessel function of the first kind of order one. The value of I_0 is related only to the incident light intensity and wavelength, and to the size of the particle. In general, larger particles are characterized by a higher I_0 and a narrower scattering angle.

The Malvern instrument makes use of these scattering properties by the configuration shown in Figure 3-4. A collimated laser beam falls on a lens. The beam is focused through a pinhole in the detector board which is located one focal length behind the lens. The board is covered with an array of circular detectors, each of which is located at a given radius from the centerline. This setup allows undiffracted light to be dumped into a light trap. The particle shown in Figure 3-4 will exhibit a certain scattering intensity vs. angle relationship. Let us say we wish to characterize the intensity at 3° from centerline. Ray 1 and Ray 2 both emerge from the particle at 3° from centerline. Ray 1 proceeds through the lens and strikes Diode 4 on the detector board. Ray 2 also goes through the lens and also strikes Diode No. 4. Thus, the signal from Diode No. 4 will always represent light that was scattered at 3° from centerline. This means that the signal from the various diodes can represent the $I(\lambda)$ vs. λ characteristic for this particle. If two particles are present in the field, the diode signal will represent the sum of the scattering characteristic for the two particles. The following features summarize the optical approach.

- The diode signal is independent of the location of the scattering particle within the field.
- The diode signal represents the sum of the scattering characteristics of all of the particles within the field.

The instrument operates by (1) assuming a size distribution for the particles, (2) calculating the expected scattering from the assumed distribution, (3) comparing the calculated vs. measured scattering, and (4) adjusting the assumed distribution. These steps are repeated iteratively until the assumed particle size distribution yields scattering behavior which matches the measured value.

Figure 3-4. Configuration for diffraction sizing instrument.

The calculation of the scattering from the assumed size distribution is the key point. It is accomplished by use of the "T" matrix as follows:

$$\bar{E} = [T]\bar{X} \quad (3-2)$$

Here, $\bar{X}$ is a vector containing as members the assumed size distribution, as represented by mass fraction in each of the 16 size bins. The T-matrix contains elements which relate a series of scattering angles against a series of particle sizes. As an example consider the situation in which only three diodes are used and it is desired to resolve data into three particle size "bins". The calculation then has the form:

$$\begin{bmatrix} E_1 \\ E_2 \\ E_3 \end{bmatrix} = \begin{bmatrix} T_{11} & T_{12} & T_{13} \\ T_{21} & T_{22} & T_{23} \\ T_{31} & T_{32} & T_{33} \end{bmatrix} \begin{bmatrix} X_1 \\ X_2 \\ X_3 \end{bmatrix} \quad (3-3)$$

Thus, the light energy onto E_1 , the inner diode, will be calculated as follows:

$$E_1 = T_{11}X_1 + T_{12}X_2 + T_{13}X_3 \quad (3-4)$$

Since E_1 is made up of light scattered to only one angle (or more correctly, light scattered to a small range of angles), then it is calculated by summing the scattering contribution from each size class into that specific angle. Thus, T_{11} represents the energy/unit mass of light scattered into the angle contributions from each size class will give the total amount of energy onto Diode 1.

The dynamic range of the instrument covers about two orders of magnitude. Thus, a given configuration can, for example, resolve size distributions between 5 and 500 microns. This two order of magnitude resolution band can be adjusted to any point within the range of 1.2 to 1800 microns by choice of lens focal length and by concurrent adjustment of the T-matrix. Thus, the simplistic approach to resolving the 0.5 - 10 micron size range would be to reduce the focal length of the lens to 26 mm. A number of theoretical and hardware issues must be addressed to do this.

3.3.2 Theoretical Issues

The He/Ne laser light used by the Malvern is 0.6328 microns in wavelength. Thus, a 0.5 micron particle is well within the regime of comparable wavelength vs. particle size. This requires the use of rigorous Mie theory to calculate scattering characteristics. The first step is to determine how the Mie calculations compare with those on which the Malvern data reduction algorithm is based in the 0.5 - 10 micron range.

Diffraction is essentially independent of the composition of the particle. With Mie scattering, however, the induced dipole moment of the particle begins to assume importance. Thus, the calculations require an assumed value of the complex index of refraction ($n = m - iK$) for the coal ash. The value of m is normally about 1.55, while the value for K varies with both ash composition and wavelength. We have elected to treat K as a parameter which is allowed to range between 0 and 0.4. As the Mie equations are complex and extremely laborious to evaluate, a Mie code at the University of California - Irvine was used to develop the plots contained here.

Figure 3-5 compares the I/I_0 vs. angle characteristic for Fraunhofer and Mie scattering. The plot shows that the shape of the energy vs. angle characteristic for these small particles is only minimally affected by the use of the more rigorous and complex Mie equations. The change represents only a few percent, which is well within the error associated with the various experimental parameters. Thus, no alteration of the shape of the scattering characteristic need be considered.

Figure 3-6, however, brings up two problems. This is a plot of the total power scattered per particle, which may be thought of as being proportional to I_0 . The apparent deviation between Mie and Fraunhofer is significant on this log scale. In absolute terms, this figure shows that the smaller particles scatter more efficiently (by a factor of 2-3) than they would based on a strictly Fraunhofer calculation. This is a consequence of the fact that in the Mie range the particles both diffract and emit due to their dipole moment. This means that

Figure 3-5. Scattering angle/intensity relationship.

Figure 3-6. Mie scattering comparison to Fraunhofer.

the results will be at least somewhat dependent on the choice of value for index of refraction. The second difficulty is that signal detection becomes increasingly difficult below 1 microns. Thus, a 0.5 micron particle scatters only about 10 percent of the energy as a 1.0 micron particle when exposed to the same incident light flux. Given a "reasonable" ash size distribution, this problem is mitigated by the fact that the number density for the smaller particles will be much higher than that for the larger particles. Thus, if Figure 3-6 is replotted on a total energy scattered basis rather than on an energy/particle basis, the curve will be much more horizontal.

In summary, the theoretical portion of the approach contains the following elements:

- Change the geometry of the receiving apparatus such that the higher angles associated with the smaller particles can be accommodated by the optics.
- Alter the software to accommodate the increased scattering intensity from the small particles (relative to the Fraunhofer level).

It is key to note that Malvern has introduced Mie considerations into the T-matrix for the shorter focal length lenses. The results are insensitive to index of refraction (e.g., see Figure 3-6 for sizes above about 1 micron). Pure Fraunhofer is included only for focal lengths at or above 600 mm.

3.3.3 Modification Approach

The original approach was to place the sample cell in front of the collection lens, and use a short focal length lens as a means of collecting the widely scattered light. A number of problems were associated with this approach:

- At these short focal lengths, only a short sample cell can be accommodated. This limits the amount of material that can be characterized at any one time.

- The high angles associated with the proposed configuration introduced coma distortion into the scattering result. Coma comes about when parallel light beams arriving at different points on the lens face are focused to different points on the focal plane. This aberration is easily corrected in commercial 35 mm lenses, but only at the price of a substantial reduction in f-number, which renders the lens inappropriate for the present needs.

One means around this is to locate the sample cell behind the lens. As shown in Figure 3-7, the covering light from the lens interacts with the thin sample holder to yield the same scattering result as occurred when the sample was placed before the lens. The size range is then selected by adjusting the distance between the sample cell and the detector ("f" on the figure). Note that the entire arrangement is independent of the focal length of the lens.

The principal difficulty with this approach was the lack of sensitivity associated with the thin sample cell. Under reasonable coal loading conditions, not enough sample was present to yield an adequate signal. A secondary problem was the difficulty in keeping the windows clean.

A single solution to all of the difficulties of dirty windows, inadequate signal, and special lenses was developed. This solution is to perform the optical particle sizing measurements off-line on extracted particles samples. The samples are resuspended in a surfactant solution designed to eliminate agglomeration. Since the concentration of the particles can be controlled independently, the sensitivity threshold problems are eliminated. By mounting the sample cell between the lens and the detector, the requirements for a special lens are avoided. Finally, if the system is mounted vertically, as shown in Figure 3-8, then only a lower transparent window is needed; the upper surface can be exposed to the ambient. Lastly, since settling within the sample cell can occur only in the vertical direction, the settling that occurs during analysis will not affect either the amount of material within the measurement volume, or its size distribution.

Figure 3-7. Optical configuration for sample cell between lens and detector.

Figure 3-8. Orientation of the laser diffraction system.

This approach has been implemented and tested on well sized limestone samples with good results. The ability to rapidly collect samples, suspend them, and obtain results will preserve the rapid turnaround goal, while meeting the objectives of high resolution in the targeted size distribution.

One final hardware oriented correction has been incorporated into the data reduction algorithm. Figure 3-9 shows the pathway associated with an individual light beam in the present sampling arrangement. The diffraction of the light will not be affected by the fact that the surrounding medium is water or air. Thus, the light intensity vs. angle characteristic will be the same in both water and air. The difficulty arises when the diffracted light is refracted upon passing through the water/air interface. As shown on the figure, light scattered at 30° from the axis will be shifted to about 42° upon passing through the interface. If the holder is located at the nominal 26 mm from the detector, this light, which would otherwise strike the outermost diode, would miss the entire array. This can be corrected to first order by moving the sample cell to 16 mm from the detector. This will ensure that the light scattered from the particle at 30° will be intercepted by the outside detector.

Analysis of the ash samples were performed by suspending the ash in a commercially available surfactant solution (A-11, supplied by Micromeritics) within a glass sample cell. The ash concentration could be adjusted to obtain an optimum signal.

3.4 Cascade Impactor Measurements

Ash particles under $1 - 2 \mu\text{m}$ cannot typically be dispersed once the ash particles have come in contact with each other. Ash size distributions from 0.2 to $6 \mu\text{m}$ were therefore measured with an Anderson cascade impactor Mark III non-viable (ambient). Particle separation occurs in a cascade impactor by passing the sample gas stream through a series of dry impingement type inertial classifiers. The classifiers operate by impinging the aerosol stream as a gas jet against the plate, causing the gas in the jet to sharply change direction and flow around the plate. Particles leave the flow streamlines because of inertia

Figure 3-9. Schematic showing the influence of refraction at the liquid/air interface on the angle of scatter.

and deposit on the plate. Each successive stage operates at a higher impingement velocity, and thus collects smaller particles, than the previous stage. For the operation of a cascade impactor see Harris (1977).

3.5 Coal Preparation

Grinding of coals for the mechanistic experiments involved grinding coal (initial size greater than 1cm) by continuously passing the coal through a ball mill until the appropriate size range was reached. Cleaning of coals was done by a froth floatation process by Hazen, CO, in four stages which resulted in five cleaned cuts. Details of coal preparation are discussed in the relevant sections.

4.0 THEORETICAL APPROACH

The purpose of this program was to improve our understanding of the mechanisms which control the formation of fine ash particles in the 0.5 to 10 μm size range. Fine particulate matter may result from four mechanisms:

- Particle breakup/ash coalescence;
- Direct passage, fragmentation, or agglomeration of extraneous ash;
- Bubble formation/breakup; and
- Vaporization/condensation.

These mechanisms are illustrated in Figure 4-1.

4.1 Mineral Matter in Coal

The form of mineral matter in coal is expected to affect the formation of fine particles in coal combustion. Dahlin (1985) gives a review of the mineral matter in coal. Coal mineral matter is generally classified as either inherent, included, or extraneous.

Inherent mineral matter is organically bound to the coal matrix. It is generally evenly distributed throughout the coal, and inherent mineral "particles" are in the molecular size range. For these reasons, inherent mineral matter cannot be removed by conventional physical grinding and cleaning of the coal. Inherent mineral matter comprises from 5 to 20 percent of the total mineral content of most coals (Van Crevelen, 1961).

Included mineral matter is present in discrete packets which may be randomly distributed in the coal. The size and composition of the individual inclusions is highly variable. Sarofim, et al. (1977) report a mass median inclusion size of 1 - 2 microns for two coals. When coal is ground, breaks tend to occur at inclusion/coal interfaces, and discrete inclusions are often released. Thus, a portion of the included mineral matter can be separated from the coal by

PARTICLE BREAKUP / ASH COALESCENCE

BUBBLE FORMATION / BREAKUP

**DIRECT PASSAGE, FRAGMENTATION, OR
AGGLOMERATION OF EXTRANEEOUS ASH**

EVAPORATION / CONDENSATION

Figure 4-1. Mechanisms of fine particulate formation.

grinding and cleaning. Inclusions typically make up 60 to 80 percent of the mineral matter in coal (O'Gorman and Walker, 1972).

Extraneous mineral matter is present as chunks of dirt and rock which have been inadvertently mixed with the coal in the mining process. In the grinding process the extraneous mineral particles, being denser than coal, are recycled to the pulverizer more times. This, coupled with shedding of mineral inclusions during grinding, results in a mineral particle size distribution which is finer than the coal size distribution in the ground coal (Littlejohn, 1966). Extraneous mineral matter can be easily cleaned from the coal by flotation. It comprises about 5 to 20 percent of the coal as mined (Dahlin, 1985).

4.2 Submicron Aerosols

A significant number of measurements have demonstrated the existence of a distinct submicron mode in fly ash emissions. The emissions generally peak in terms of number concentration at about 0.1 micron (McCain et al., 1975) Schmidt et al., 1976). When plotted in terms of mass, the submicron mode is sometimes distinct from the fly ash mode (see Flagan, 1979) and occasionally merged into the tail of the fly ash size distribution (Linak and Peterson, 1984).

Research and modeling work performed on submicron aerosol formation have resulted in a relatively clear understanding of the formation mechanisms. The initial distribution of the mineral matter in the coal is as a dispersion of discrete particles within the organic matrix (Sarofim et al., 1977). These appear to average 1 - 2 micron in size. Although little mineral matter is chemically bound in bituminous coals, a significant portion may be bound in lignites, and this high dispersion may lead to enhanced mineral vaporization during the char combustion step (Quann and Sarofim, 1982).

During devolatilization very little mineral matter is expected to be released. As long as the endothermic devolatilization and cracking reactions are progressing, the coal particle should remain at a sufficiently low temperature to prevent metal vaporization. Two-color pyrometry has been used to suggest the existence

of a thermal overshoot in the vicinity of burning coal particles (Seeker et al., 1981) and individual particle imaging has established the existence of a fuel-rich gas-phase region near the particle surface (McLean et al., 1981; Seeker et al., 1981). This high temperature fuel-rich environment has been hypothesized to favor the reduction of refractory oxides (e.g., Mg and Ca) to suboxides and elements (Neville et al., 1981; Quann and Sarofim, 1982). In these forms, the minerals are much more volatile than in the fully oxidized state. This explains the fact that much higher vaporization rates are observed for these refractory species in coal flames, as measured by the appearance of submicron aerosol, than would be predicted by the volatility of the fully oxidized state. At the same time, considerably greater fractions of the more volatile elements (e.g., K, Na, Se, Hg) are vaporized.

Following vaporization, the refractory species are convected away from the coal particle into the boundary layer. Here, two key changes in the environment occur. Firstly, the temperature drops across the boundary layer as the vapor moves from the region of temperature overshoot into the free stream. Secondly, the environment changes from reducing to oxidizing across the boundary layer. Thus, the vapors quickly move into a region where they are highly supersaturated. This leads to homogeneous nucleation of these refractory oxides in the boundary layer region. The large number of particles produced will grow in diameter by subsequent coagulation and condensation. This interpretation was initially advanced to explain the appearance of refractory oxide materials at the center of submicron aerosols (Neville and Sarofim, 1982).

The initial nucleation events provide a large number of very small particles in the immediate vicinity of the char particles. This produces a high specific surface area for condensation. This high availability of surface area for condensation provides an easy sink for supersaturated vapors, and markedly reduces the driving force for further nucleation. Thus, after the initial nucleation events the submicron aerosol grows primarily through condensation of vapors onto the surface, and coagulation of colliding particles. At much later times the more volatile vapors (e.g., Na, Se, Hg compounds) will become saturated as the furnace gases are quenched. The relative slowness of the quench prevents

these vapors from becoming quickly supersaturated; thus, the condensation of these constituents onto available surface is favored over homogenous nucleation. Since the preponderance of available surface area is presented by the submicron aerosol, a majority of the volatile compounds condense onto these surfaces. This leads to the enrichment of volatile metals noted by many investigators in the fine fraction of coal combustion fly ash (some examples include: Davison et al., 1974, Block and Dams, 1976; Gladney et al., 1976; Hansen and Fisher, 1980).

The fundamental nature of the submicron aerosol formation problem has motivated many investigators to develop models through which insight into the process could be gained. Flagan and Freidlander (1978) developed a model in which approximately 1 percent of the ash was assumed to vaporize and form 1 nm particles. Coagulation of these particles was assumed to yield a self-preserving size distribution. Attempts to apply the model to field data (Flagan, 1979) indicated that the model predicted a higher number of finer particles than were seen in the data. Flagan attempted to rationalize the data by considering interparticle dispersion forces, which would tend to increase the coagulation rate. He also explored the possibility that imperfect mixing would lead to high local concentrations of aerosol within the fuel-rich pockets. This could cause a more rapid coagulation rate. Neither of these corrections were capable of fully resolving this discrepancy. Uncontrolled coagulation within the sample probe has been identified as a potential cause for this difference (Damle et al., 1982).

More recent models have attempted to account for the enhanced volatility of the metal species due to the reducing environment within the char, and for the high supersaturation that results when these vapors pass through the boundary layer into an oxidizing environment. Figure 4-2 shows the geometry of the model proposed by Senior and Flagan (1982). The oxidation of carbon to CO and its diffusion away from the particle provides the reducing environment in the immediate vicinity of the coal particle. Conservation equations are written which describe the diffusion of the vapor away from the coal particle, the nucleation process, the competition between further homogeneous nucleation and condensation on existing particles, and the coagulation of these particles. The

Figure 4-2. Geometry for the formation of aerosol in the coal particle boundary layer (from Senior and Flagan 1982).

relative timescales are such that nucleation is complete before any significant coagulation begins. Thus, the processes governing the appearance of the submicron aerosol do not depend on postflame parameters, such as heat extraction rate, but rather depend on parameters which influence coal type, coal grind, and free stream oxygen concentration. A similar model was developed for the nucleation of MgO in the coal particle boundary layer by Neville and Sarofim (1982), including particle growth and coalescence.

The foregoing fundamental studies represent a class of experiments in which the mass loading of the coal is sufficiently low that the coal particle environment is preset by the external reactor conditions. In practical combustion the coal reaction itself sets the environment in which the submicron ash is generated. Many of the independent variable in the fundamental experiments (e.g., oxygen concentration, temperature) become dependent variables in practical coal combustion. Linak and Peterson (1984) used a pulverized coal tunnel furnace to simulate actual firing conditions. The evolution of the fine aerosol mode was followed as it developed during the coal combustion sequence. Staging of the combustion did not strongly influence the yield of submicron aerosol from the bituminous coals, but it greatly enhanced the yield from the lignites.

One key question involves determination of the upper size limit of the submicron aerosol. This frequently presents an experimental problem in that two analytical techniques are usually required to characterize the size distribution between the submicron aerosol mode and the residual ash mode. A representative example is the concurrent use of an impactor to measure the 0.2 - 10 micron range and an electrical mobility analyzer (e.g., TSI 3030) to develop the distribution under 1 micron. In some cases, the distributions do not overlap (for example, see Neville et al., 1981), which leaves some uncertainty about the degree to which the residual ash mode and the aerosol mode overlap. In other cases, the measured size range does overlap, but the two measurement techniques do not yield fully consistent results. Thus, the question of the extent to which the aerosol mode extends about 0.5 microns partly involves measurement issues.

Figure 4-3 shows the measured ash size distributions from a lignite burned in a drop tube furnace (Neville et al., 1981). Although the measurement techniques do not overlap, the results clearly indicate a distinct peak in the 0.01 - 0.1 micron range. The figure also shows that both the mass yield, and the mean size in the submicron mode increase at increased free stream oxygen partial pressure. However, no information is available on the large diameter cutoff for the aerosol, due to the measurement method employed.

Figure 4-4 shows Flagan's (1979) attempt to correlate field size distribution measurements with both the submicron aerosol model and the breakup model for residual ash material. The model clearly shows that the aerosol mode does not extend to above 0.25 microns. Unfortunately, both the EAA analyzer and the cascade impactor are operating at their thresholds in the region of overlap. This leads to some uncertainty over the high diameter cutoff for the aerosol mode.

Aside from the modeling work, probably the most compelling evidence on the location of the large diameter cutoff for the aerosol is that of Linak and Peterson (1984). An example of their time resolved measurements are shown in Figure 4-5. In Figure 4-5b the development of the submicron particles is traced as a function of time. At the shortest time measure (2.7 sec.) a distinct mass peak centered at 0.02 microns is evident. At later times the small sized component is merged into a mode centered at about 0.1 microns through coagulation and condensation. The key point is that the data do not show any change in size distribution with time for diameters above 0.2 - 0.4 microns. This suggests that the aerosol formation mechanism does not supply particles into sizes above this limit. This important conclusion carries more weight because it was obtained under time-temperature histories and firing densities that are representative of full-scale practice.

These results suggest that the submicron aerosol formation mechanism in coal combustion does not strongly contribute to the 0.5 - 10 micron size range that is of interest here. There are three ways this mechanism may present some contribution to this size range:

Figure 4-3. Particle mass size distribution from a lignite. Squares are 15% oxygen, circles are 40% (Neville et al., 1981).

Figure 4-4. Comparison of size distributions from model and data (Flagan, 1979).

Figure 4-5. Comparison of number density and mass size distributions for unstaged Utah coal combustion. Circles are for a 2.7 sec. residence time, triangles are 4.4 sec., and squares are 6.6 sec. (Linak and Peterson, 1984).

1. The argument that the submicron aerosol size distribution does not have a significant tail reaching above 0.5 microns cannot be considered as fully established. Thus, the direct mechanism may contribute to this size range.
2. Helble et al. (1987) observed substantial aggregates of submicron aerosol. These aggregates are too large to be formed by free stream Brownian agglomeration; their formation mechanism is suggested to involve the formation of a high concentration of aerosol particles in the wake of a coal particle slipping through the combustion environment. This high concentration allows Brownian diffusion to be a realistic agglomeration mechanism.
3. The preponderance of vaporized material will condense onto the submicron aerosol due to the high relative surface area it presents. However, some condensation onto residual fly ash in the 0.5 - 10 micron size range will occur. Although this condensation will not strongly change the size of this material, it will change the character of the surface the material presents. Thus, there is a mechanism linking the vaporized ash fraction to the 0.5 - 10 micron size range.

4.3 Residual Fly Ash

Residual fly ash can generally be defined as any mineral emissions from a pulverized coal flame that are not formed directly from condensed mineral vapors. As such, this category covers a wide range of mineral forms and sizes. The present discussion is focused on those formation mechanisms which contribute particles to the 0.5 - 10 micron size range.

Probably the earliest and most straightforward mechanism for the formation of residual fly ash is the Breakup Mechanism proposed by Flagan and Friedlander (1978). As the coal is heated, the uniformly distributed mineral matter within the particle will begin to undergo physical and chemical transformation. These

are summarized by Raask (1985), although they do not strongly influence the fate of the inorganic matter under the breakup mechanism. When the particle reaches the char combustion stage the mineral inclusions melt, and the molten ash collects on the surface of the receding char. Because chars develop porous structures as they burn, the original char particle will normally break into several daughter particles as the pores coalesce and divide the structure. Each char particle will carry its associated mineral matter away with it, and after each daughter particle has burned out, its included mineral matter will coalesce into a single ash droplet.

In its original form, the breakup model is completed by the assumption that each coal particle, independent of size, breaks into a discrete number of char particles (usually of the order of 3 - 5). This is equivalent to assuming that each coal particle yields up its included mineral matter as, for example, four equally sized ash particles. Thus, the only information needed to complete the model is the coal mineral content, the coal size distribution, and the assumed number of daughter char particles which are sufficiently small that they are of same order of size as the mineral matter inclusions.

The breakup model has been found to provide an adequate representation of the bulk of the residual fly ash size distribution (see Flagan, 1979). However, three principal inadequacies, are apparent when attempting to apply the breakup model to the generation of 0.5 - 10 micron particles. These are:

1. Other mechanisms than the breakup model may be important in this size range (Damle et al., 1982). These will be discussed later.
2. There is no guarantee that the breakup of the char particle will yield a distribution of daughter char particle sizes, and hence a distribution of ash particles sizes. Also, the number of daughter char and ash particles produced from each parent coal particle can be expected to vary with coal type, coal size, and combustion conditions. While these factors may not strongly influence the bulk of the residual fly ash size

distribution, it can strongly influence the tail of the distribution, which lies in the 0.5 - 10 micron size range.

3. The breakup model is adequate only when the coal size is substantially larger than the mineral inclusion size. Very small coal particles either may or may not contain an inclusion, or the particles may vary significantly in the number of inclusions carried, and therefore vary significantly in their mineral matter content. Both factors will cause the breakup mechanism to yield an inadequate description of the fine end of the residual fly ash distribution (i.e., 0.5 - 10 microns).

To summarize, the breakup mechanism supplies an approximate description of the bulk of the residual fly ash mode. However, this mechanism is at its most inadequate in describing the fine side of the size distribution. In addition, the existence of other mechanisms beyond the breakup model have been indicated to be major contributors to the 0.5 - 10 micron size range.

The first alternative mechanism involves the ejection of non-agglomerated mineral matter inclusions. Inclusions have been observed to range from several microns to less than 0.1 micron (Sarofim et al., 1977; Allen and Carling, 1984; Allen and Vander Sande, 1982; Harris, 1982). These fine particles may agglomerate during char combustion. However, the opportunity exists for these fines to be "burned out" of the char without melting or agglomerates. Also, very small coal particles containing only one submicron inclusion will yield this as a single submicron ash particle upon heating.

Another mechanism is the formation of ash cenospheres, that is, hollow ash particles, during combustion. These particles typically account for less than 10 percent of the mass of the fly ash (Raask, 1968). However, cenospheres will contribute to a larger fraction of the ash of the large particles sizes (Fisher et al., 1977). These cenospheres appear to be formed by release of carbon oxides (Raask, 1968). However, cenospheres will contribute to a larger fraction of the ash of the large particle sizes (Fisher et al., 1977) inside molten ash spheres. The carbon oxides may be produced by dissociation of carbonates (Fisher et al.,

1977) or by the reactions of oxides with the coals (Raask, 1968). Formation of cenospheres by release of water of hydration has been discounted (Gluskoter et al., 1981) and recent evidence indicates that decomposition of carbonates is not related to the formation of cenospheres (Lauf, 1981). The most logical hypothesis remaining is that of formation of the carbon monoxide by interaction of mineral matter with the coal (Raask, 1968). In addition, formation of cenospheres has been related to the viscosity of the ash material (Lauf, 1981).

The fraction of the ash that appears as cenospheres is strongly correlated with the presence of iron in the ash, with little cenosphere formation noted until at least 5 percent iron, as Fe_2O_3 , is present in the ash (Raask, 1985). This is consistent with a mechanism in which CO is generated by the interaction of an iron carbide with silica:

The size range from cenospheres has been reported to be 20 - 200 microns, which strictly speaking places them beyond the 10 micron upper limit of this study. However, cenospheres can behave aerodynamically as much smaller particles. This is because an unfractured cenosphere will show an apparent specific gravity as low as 0.2. This implies:

- The inhalation characteristics of cenospheres will be much more like those of smaller particles.
- In cascade impactor size analysis, cenospheres will tend to be carried to the finer sized stages, relative to their geometrical diameter.

Thus, to some degree, cenospheres behave as if they were particles in the 0.5 - 10 micron range.

Plerospheres are similar to cenospheres in that the ash contains a relatively well defined structure. However, the mechanism is though to be somewhat different. Plerosphere formation appears to be most favored when the

coal contains a relatively high concentration of well dispersed mineral matter. Early in the char combustion sequence the surface ash melts to yield a uniform coating over the enclosed organic matter. If the temperature is not too high (about 1659 K) the structures will not coalesce into dense spheres. Those frequently appear within cenospheres. The conditions which favor cenosphere formation also favor plerosphere formation, with the additional requirement that some portion of the coal exhibit a relatively high mineral matter content (Raask, 1985).

A final residual fly ash mechanism involves the ejection of discrete mineral particles during coal grinding. If small inclusions are separated during grinding, and those are separated from the coal particle surface during firing, then the mineral particles will likely pass through the flame without any further change in mass.

In summary, residual fly ash formation appears to be reasonably well represented by the "breakup mechanism". However, this mechanism is less adequate at representing the fine end of the residual fly ash size distribution. The existence of other mechanisms have been hypothesized and characterized to greater or lesser degrees. Many of these mechanisms are key to understanding the influence of coal type and firing rate on the small end of the residual fly ash size distribution.

4.4 Breakup Model

The breakup model of Flagan (1979) assumes that the size distribution of ash from the combustion of coal is proportional to:

- The size distribution of the parent coal;
- The number of char particles formed from each coal particle;
- The ash content of the coal; and
- The ratio of ash density to coal density.

Several modifications to this model were made to this model in this program.

The breakup model can be written to account for the moisture content of the coal to yield the relationship between the ash particle size distribution and the ash particle size distribution:

$$d_a = d_c \left[\frac{x_a / \rho_a n}{x_m / \rho_m + x_w / \rho_w + (1 - x_m - x_w) / \rho_o} \right]^{1/3} \quad (4-1)$$

where:

d = particle diameter
 n = number of ash particles resulting from a single coal particle
 x = mass fraction in coal
 ρ = density

and the subscripts refer to:

a = ash
 m = mineral matter in coal
 o = organic phase in coal
 w = water

It is unlikely, however, that coal particles with the same initial diameter will yield n number of particles of the same size. Instead, a size distribution will result. It is also unlikely that coal particles with widely different diameters will break into the same number of particles. Larger particles may break into a greater number of particles than smaller particles. The breakup model was therefore modified to allow the breakup number to be varied as a function of coal particle size and to allow coal particles with the same initial diameter to form ash particles with a distribution of diameters. The ash size distribution is assigned a Gaussian distribution with no ash particles larger than the parent coal particle allowed. A typical distribution is illustrated in Figure 4-6.

Figure 4-6 Gaussian distribution used in modified breakup model.

The width of the Gaussian distribution and the breakup number were adjusted to match the data.

The procedure for finding the breakup number, n , is illustrated in Figure 4-7 for the simplified case where only a single size ash particle is produced from a coal particle and the breakup number was not allowed to vary with coal particle size. The line labeled breakup number 1 is the distribution which would be expected if one ash particle was produced by one coal particle. This breakup number, however, produces a distribution which is larger than the measured distribution of this ash. The breakup number was then adjusted until the predicted mass mean diameter matched the measured mass mean diameter (approximately 8 μm for this ash) which yielded a breakup number of five.

Figure 4-7. Illustration of how the breakup number is found.

5.0 GLOBAL EXPERIMENTS

Global experiments which were designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter. These experiments were conducted in the Isothermal Reactor (ITR), a laboratory scale reactor designed so that coal particles could be dispersed into a combustion environment in a sufficiently dilute manner so that the combustion of individual coal particles would be controlled by the properties of the surrounding gases and not influenced by the combustion of neighboring coal particles.

5.1 Results

The particle size distributions of the coals listed in Table 5-1 were measured and ash from these coals sampled from the ITR at the conditions given in the same table. The measured particle size distributions for these coals and the resultant ashes (measured with the Malvern as described in Section 2.0) are given in Appendix A. Proximate analyses of these coals, given in Table 5-2, were performed by Hazen Research of Boulder, Colorado.

No dependencies on either furnace temperature or oxygen concentration (over the ranges tested) were observed. This is illustrated in Figure 5-1 for data taken as a function of oxygen concentration.

5.2 Comparison to Original Breakup Model

The ash particle size distributions given in Appendix 1 were compared to the simple (original) breakup model (Eq. 4-1). The breakup numbers required to fit the data are given in Table 5-3. Correlations between the breakup number and various coal properties are shown in Figure 5-2. The lower rank coals generally had a higher breakup number while the higher rank coals had lower breakup numbers. (Although the breakup number increased with moisture content, this is not significant since moisture content is generally a function of coal rank.) This dependence of breakup number on rank has been correlated with the structural behavior of coal during devolatilization. The higher rank coals tend to form

Table 5-1. Coals Tested.

Coal	Coal Type	Temperature	% Oxygen
Utah	Bituminous	1100°C 1200°C 1350°C	10 10, 20, 25.5, 30 20, 30
Illinois No. 6	Bituminous	1200°C	20, 30
Illinois	Bituminous	1200°C	10, 20, 30
Australian Bit. #1	Bituminous	1200°C	20, 30
Australian Bit. #2	Bituminous	1200°C	20, 30
Australian Bit. #3	Bituminous	1200°C 1350°C	20, 30 20, 30
Australian Bit. #4	Bituminous	1200°C 1350°C	20, 30 20, 30
Canadian Bit. (Cleaned)	Bituminous	1200°C	20, 30
U.S. Bit. (Low S)	Bituminous	1200°C	20, 30
Indonesian Bit.	Bituminous	1200°C	20, 30
62% Illinois/ 38% Kentucky	Bituminous/ Bituminous	1200°C	10, 20, 30
Eagle Butte	Subbituminous	1200°C	20, 30
Big Brown	Subbituminous	1200°C	20, 30
Beulah	Lignite	1200°C 1350°C	20, 30 30

Table 5-2. Properties of Coals Tested.

Coal	Coal Type	% Ash*	% H ₂ O*	% Vol*	BTU/lb (dry)
Utah	Bit.	6.27	3.91	40.1	13,202
Illinois No. 6	Bit.	8.73	11.98	33.5	12,312
Illinois	Bit.	11.77	4.13	34.5	12,217
Australian Bit. #1	Bit.	16.28	1.41	31.4	12,536
Australian Bit. #2	Bit.	16.66	1.67	26.8	12,533
Australian Bit. #3	Bit.	11.96	2.70	22.0	13,032
Australian Bit. #4	Bit.	13.53	3.63	25.7	12,412
Canadian Bit. (Cleaned)	Bit.	6.92	0.74	16.8	13,804
U.S. Bit. (Low S)	Bit.	12.61	8.12	36.8	12,834
Indonesian Bit.	Bit.	1.61	3.54	40.0	12,384
62% Illinois/ 38% Kentucky	Bit./ Bit.	8.67	9.31	35.2	11,762
Eagle Butte	Subbit.	5.03	24.11	32.9	11,735
Big Brown	Subbit.	14.52	10.38	39.6	10,728
Beulah	Lignite	10.50	28.26	29.5	10,169

* - As Received

Figure 5-1. Influence of oxygen concentration on ash particle size.

Table 5-3. Number of Ash Particles per Coal Particle
Required to Fit the Data.

Coal	Coal Type	Temp.	%O ₂	Breakup Number
Utah	Bit.	1200°C	10	3.1
			20	1.8
			25.5	1
		1350°C	30	4.6
			20	1
			30	2.1
Illinois No. 6	Bit.	1200°C	20	1
			30	1
Illinois	Bit.	1200°C	10	2.7
			20	3.5
			30	2.2
Australian Bit. #1	Bit.	1200°C	20	2.9
			30	5
Australian Bit. #2	Bit.	1200°C	20	1
			30	1
Australian Bit. #3	Bit.	1200°C	20	1
			30	1
Australian Bit. #4	Bit.	1200°C	20	5
			30	5
Canadian Bit. (Cleaned)	Bit.	1200°C	20	1
			30	1
62% Illinois/ 38% Kentucky	Bit./ Bit.	1200°C	10	1
			20	6
			30	6
Eagle Butte	Subbit.	1200°C	20	5
			30	6
Big Brown	Subbit.	1200°C	20	7
			30	8
Beulah	Lignite	1200°C	20	11
			30	16

Figure 5-2. Correlation of breakup number with various coal properties.

more plastic masses during devolatilization and therefore have little macroporosity development during char combustion. The lower rank coals, however, tend to develop a very high surface area structure during char combustion that leads to extensive pore development. A highly porous char tends to break into several daughter particles as the pores coalesce. Each daughter char particle will carry its associated mineral matter away with it, and after each daughter particle has burned out, its included mineral matter will coalesce into a single molten ash droplet.

Three types of deviations from the breakup model's predictions were observed. In Figure 5-3 the model predictions for ash from the Australian Bituminous #2 were made with the minimum breakup number allowed, 1. At particle sizes larger than the mass mean diameter (approximately 10 μm) the ash sampled at 30% oxygen and especially the ash sampled at 20% oxygen had measured particle size distributions larger than could be predicted. The ash smaller than the mass mean diameter fit the data fairly well. This type of deviation could result from incomplete combustion of the larger particles. To determine if this was true, the ash samples were sieved with a 25 μm screen and analyzed for carbon content. The results given in Table 5-4 show that ash larger than 25 μm sampled at 20% oxygen had a substantially greater carbon content than did the smaller particles.

Table 5-4. Carbon Content of Australian Bit. #2 Ash

% O ₂	Size (μm)	%C
20	>25	14.3
20	<25	2.7
30	>25	3.9
30	<25	1.5

The second type of deviation occurred for the cleaned Canadian bituminous coal (Figure 5-4). The predicted ash size distributions shown in Figure 5-4, which were calculated using the minimum breakup number, 1, were substantially smaller than the measured ash particle size distributions. This could also result from incomplete combustion of the coal. As with the Australian Bituminous

Figure 5-3. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

Figure 5-4. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

#2, however, only the larger ash particles would be larger than predicted as the smaller coal particles would be expected to burn completely. When this coal was fed to the ITR there were problems with the coal sticking together and plugging the feed lines. If agglomerates were formed when the coal was fed to the reactor, then ash from each coal particle in the agglomerate may have coalesced with ash from other coal particles in the agglomerate and ash particles larger than those predicted by the breakup model would form.

The third type of deviation of the model from the measured ash size distributions is illustrated in Figure 5-5. This type of deviation occurred for a number of the coals tested. The model predictions fit the ash size distributions fairly well except at the smaller size fractions where it over predicts the amount of ash. This could result from;

- 1) The number of ash particles produced from a coal particle may vary with coal particle size. This trend could be predicted if the smaller coal particles broke into fewer ash particles than the larger coal particles.
- 2) The ash content may vary with particle size. The above trend could be predicted if the smaller coal particles had a lower ash content than the larger particles. This would result in the smaller coal particles. Or,
- 3) An inability to disperse ash particles under 2 μm in the surfactant solution when preparing the ash for particle size analysis.

To determine whether mineral content varied with coal particle size, six coals which exhibited this behavior were sieved into different size cuts and the different size cuts analyzed for mineral content (Figures 5-6 through 5-8). Of the six coals sieved, three had mineral contents which varied significantly with particle size (the Illinois, the 62% Illinois/38% Kentucky blend, and the Australian Bituminous #3) and three which did not (the Australian Bituminous #1, and the two lower rank coals, the Eagle Butte subbituminous and the Beulah lignite). (This lack of dependence of mineral content on coal particle size had been expected for the Beulah lignite since previous work had indicated that the

Figure 5-5. Comparison of ash particle size distributions and the distribution predicted by the breakup model.

Figure 5-6. Mineral content as a function of coal particle size.

Figure 5-7. Mineral content as a function of coal particle size.

Figure 5-8. Mineral content as a function of coal particle size.

bulk of the mineral matter in this coal was atomically dispersed in the coal.) The observed trend of increasing mineral content with decreasing coal size would not explain the third type of deviation, where the model over-predicts the ash yield at small particle sizes. The inclusion of the observed trend would cause the breakup model to over-predict the yield of small ash particles, thus indicating that the other two possibilities may be correct.

5.3 Comparison to Modified Breakup Model

The potential exists that the third explanation is responsible for this type of deviation. Further modeling efforts to explain this type of deviation were therefore conducted on particle size distributions taken with the cascade impactor. Figure 5-9 illustrates particle size distributions of ashes sampled from the ITR at 1200°C and 20% oxygen.

The breakup model and the data from Figure 5-9 are compared in Figures 5-10 through 5-13. In each figure breakup model predictions are shown using the simple breakup model (Eq. 4-1, shown by the dashed line) and the breakup model modified to calculate a distribution of ash particle sizes from a single coal particle (shown by the solid line). Breakup numbers used in making these predictions were taken from Table 5-3. In general, the use of the distributed breakup model improved predictions for these four coals by extending the predicted size distributions down to lower sizes (which could not be done by the simple breakup model alone).

Two further modifications to the model were made in order to fit the data in Figure 5-9. The four ash size distributions in Figure 5-9 can be observed to 'level off' between 0.2 and 0.5 μm and, in some cases, drop off at lower sizes as the particle size decreases. Ash particles in the 0.05 to 0.2 μm typically result from the vaporization/condensation mechanism (Damle, et al., 1982) thus suggesting that the observed behavior results from the vaporization/condensation mechanism. (A steep curve in a cumulative plot indicates the presence of particles while a flat curve indicates the absence of particles.) The model does not consider the vaporization/condensation mechanism. It was therefore assumed

Figure 5-9. Ash size distributions of raw coals.

Figure 5-10. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 5-11. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 5-12. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 5-13. Comparison of cascade impactor ash size distributions and the breakup model¹.

that a fraction of the ash present was due to this mechanism and the calculated ash size distribution modified to account for this. The percentage of ash produced by the vaporization/condensation mechanism was determined by assuming that all ash measured under $0.3\text{ }\mu\text{m}$ was produced by this mechanism.

The second modification involved the tendency of the data to 'level off' between 2.5 and $4\text{ }\mu\text{m}$. A differential plot of measured ash size distributions provides information on which ash particle sizes are most predominate. The data in Figure 5-9 are plotted in Figure 5-14 as the differential ash size distributions. All four coals exhibit a peak at approximately $1 - 2\text{ }\mu\text{m}$, the mass median size of included mineral matter reported by Sarofim, et al. (1977). The peak at $2\text{ }\mu\text{m}$ may result from inclusions released during grinding or during the early stages of the combustion process. The breakup model was therefore further modified by assuming that all mineral matter near the surface of a coal particle is released before it can coalesce to form larger ash particles and is present in the ash as $2\text{ }\mu\text{m}$ particles.

Predictions by the model modified to include the presence of ash from the vaporization/condensation mechanism and to include both modifications (plus the release of $2\text{ }\mu\text{m}$ included mineral matter) are plotted in Figures 5-15 through 5-18. Predictions which account for just the vaporization/condensation mechanism (the dashed lines in Figures 5-15 through 5-18) are substantially better than those by the simple breakup model (Figures 5-10 through 5-13). The predictions in Figures 5-15 through 5-17 which account for both vaporization/condensation mechanism and the release of $2\text{ }\mu\text{m}$ included mineral matter (the solid lines) appear to offer only a slight improvement over the just the dashed lines. This is, however, a result of plotting the percent mass axis logarithmically. Accounting for the release of $2\text{ }\mu\text{m}$ included mineral matter increases model predictions at $2.6\text{ }\mu\text{m}$ for the Utah coal from 7.7% to 16.6%, for the Illinois coal from 11.7% to 19.5%, and for the Eagle Butte coal from 21.6% to 32.6%, substantial improvements in predicted ash yield at these size.

Agreement between the model predictions and data for the Beulah coal, Figure 5-18, was excellent when just the vaporization/condensation mechanism was

Figure 5-14. Differential size distributions of four raw coals (taken from the data plotted in Figure 5-9).

Figure 5-15. Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.

Figure 5-16. Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.

Figure 5-17. Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism and the release of 2 μm inclusions.

Figure 5-18. Comparison of cascade impactor ash size distributions and the breakup model modified to include the vaporization/condensation mechanism.

included in the model. Accounting for the release of 2 μm included mineral matter would be inappropriate as previous work had indicated that the bulk of the mineral matter in this coal is not present as inclusions, but is atomically dispersed throughout the coal.

Also given in Figures 5-15 through 5-17 are the distances from the surface of the coal particle where inclusions were allowed to be released from the particle without coalescence. These were 1 μm for the Utah coal, 0.25 μm for the Illinois coal, and 0.5 μm for the Eagle Butte coal. All of these distances are reasonable. Mineral inclusions within 1 μm of the coal surface would have some part of their surface exposed and it is plausible that they could be released during grinding or the early stages of the combustion process. The reason for the variations in depth is not clear. The physical structure of the three coals may influence the ability of inclusions to be released, the ratio of included to atomically dispersed mineral matter may vary among these three coals, or variations in the sodium content may be important (the Illinois coal (1.4%) was higher than the Utah and Eagle Butte (1.0% and 0.9%) coals).

5.4 Summary

This portion of the program focussed on determining the influence of global parameters on the formation of ash particle size distributions. Varying oxygen concentration and temperature had no influence on the measured ash particle size distributions.

The data was compared against the simple breakup model in order to gain an understanding of the mechanisms which control the formation of ash particles. Comparison of the breakup model and data revealed that lower rank coals required higher breakup numbers to fit the data while higher rank coals required lower breakup numbers. Three types of deviations of the breakup model from the data were observed:

- The yield of ash particles greater than 10 μm were greater than could be predicted. This was attributed to incomplete combustion at lower oxygen concentrations.
- Ash particle size distributions were larger than could be predicted by the breakup model. This occurred for one coal and was attributed to the tendency of this coal to stick together and form large agglomerates.
- The yield of ash at particle sizes under 10 μm was less than could be predicted. It was determined that this was not due to variations in the mineral content in the coal with particle size. The possibility existed that the procedure used to disperse ash particles for the measurement of ash size distribution by the Malvern laser instrument could not disperse particles under 2 μm and therefore biased the results towards larger particles. Further modeling was therefore performed only on ash size distributions taken with the cascade impactor.

The data taken with the cascade impactor showed two deviations from the breakup model. First, ash size distributions for four coals measured with the cascade impactor showed percent fractions of ash under 0.3 μm ranging up to 6%. The breakup model, however, typically predicts that no particles will be present in under 0.3 μm . This was attributed to the contribution of ash particles from the vaporization/condensation mechanism. Second, differential plots of the ash size distributions showed a peak at 2 μm , a range where the breakup model predicts that the particle size distribution should be tailing off. The 2 μm peak was attributed to included ash which was released either during grinding or during the initial stages of the combustion process and retained its original size. Three modifications to the breakup model were made to improve its ability to match the measured data. These were:

- 1) Allow each size of coal particle to produce a distribution (Gaussian distribution) of ash particles.

- 2) Assumed that particles under $0.3\ \mu\text{m}$ resulted from the vaporization/-condensation mechanism.
- 3) Assumed that included mineral matter within a short distance of the coal's particle surface was released during grinding or during the early stages of combustion and retained its original size.

Including these modifications into the model substantially improved the match between the model and data for the Utah, Illinois, and Eagle Butte coals. The distances from the coal particle's surface used in the model within which included mineral matter was allowed to be released and retain its original size, $0.25 - 1.0\ \mu\text{m}$ for the three coals considered, are reasonable. The fit between the model and Beulah coal, which is known to not contain included mineral matter, was excellent when the third modification was not included.

6.0 MECHANISTIC EXPERIMENTS

The mechanistic experiments focussed on providing a quantitative evaluation of the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter in the 0.5 - 10 μm size range. These experiments were also conducted in the ITR to ensure that the formation of ash particles would not be influenced by the combustion of neighboring coal particles. The mechanistic experiments involved three sets of experiments. The first set of experiments involved cleaning and sizing three baseline coals (Utah, Beulah, and Illinois) and subsequently measuring the particle size distribution of ash from these various cuts. The second set of experiments involved separating both the raw and cleaned coals into different size cuts and measuring the resultant ash size distributions. The final set of experiments involved grinding a coal to different sizes to determine the influence of grinding on ash size distributions.

6.1 Cleaned Cuts

Cleaning was done by a froth floatation process by Hazen, CO, in four stages which resulted in five cuts. Results of the cleaning process are illustrated in Table 6-1 and the process itself is illustrated in Figure 6-1 for the Illinois coal. Particle size distributions of the cleaned coals are given in Appendix B. Also shown in Figure 6-1 is how 100 g of the original coal and its associated mineral matter were distributed between the cuts. The majority of the coal is deposited in the Third Cleaner Concentrate which had 55% of the mineral content of the original coal. The other four cuts represent relatively small fractions of the original coal mass and were highly enriched in minerals. The cumulative size distributions of ash sampled when each of these cuts were fired in the ITR are plotted in Figure 6-2.

The Rougher Cut produced the coarsest ash while all of the other cuts yielded substantially more material under 1 μm than the raw coal. Overall, however, the various cleaning cuts yielded less fine particulate matter under 5 μm than the raw coal. This would not be expected if the ash size distribution of the whole coal were simply the weighted sum of the various cleaned cuts. To

Table 6-1. Results from Coal Cleaning.

	% Wt. (AR)	% Ash Content (Dry Basis)	MMD (μm)
Utah Coal	100	6.53	38
First Process:			
Rougher Tail	5.41	47.66	N/A
1 st Cleaner Tail	14.87	13.26	100
2 nd Cleaner Tail	1.38	11.36	65
2 nd Cleaner Conc.	78.53	2.59	30
Second Process:			
Rougher Tail	32.45	12.66	85
1 st Cleaner Tail	5.81	9.11	45
2 nd Cleaner Tail	1.13	6.24	100
2 nd Cleaner Conc.	60.64	2.41	30
Beulah Coal	100	14.64	42
First Process:			
Rougher Tailing	50.77	14.94	70
Rougher Concentrate	49.23	13.40	45
Second Process:			
Rougher Tail	73.19	14.94	65
1 st Cleaner Tail	17.42	13.44	80
2 nd Cleaner Tail	3.55	13.58	50
2 nd Cleaner Conc.	5.84	11.49	25
Illinois Coal	100	12.28	29
Rougher Tail	4.1	61.0	18
1 st Cleaner Tail	2.5	61.0	22
2 nd Cleaner Tail	0.8	50.0	N/A
3 rd Cleaner Tail	14.0	16.0	80
3 rd Cleaner Conc.	78.6	6.6	29

Figure 6-1. Illustration of the application of the physical coal cleaning process to the Illinois coal.

Figure 6-2. Cumulative size distributions for ash from the firing of the various cleaning cuts. Data obtained with a cascade impactor.

determine if this were true, the ash size distributions of the cleaned cuts were averaged and compared to the ash output of the original coal. Shown in Figure 6-3, the cleaned cuts produced a greater fraction of fine particulate matter under $1\text{ }\mu\text{m}$ than did the raw coal but overall produced a smaller fraction of their ash under $5\text{ }\mu\text{m}$ than the raw coal. This suggests that the organically bound or included mineral matter is the source of the fine ash particles under $1\text{ }\mu\text{m}$. It also suggests that the presence of the extraneous ash may suppress the formation of fine particulate matter under $1\text{ }\mu\text{m}$. This type of behavior was also observed for the cleaned Utah coal. In Figure 6-4 the cleaned Utah coal had significantly higher levels of fine particulate matter under $1\text{ }\mu\text{m}$.

The weighted sum of the cleaned cut's ash size distributions are compared to the distribution of ash from the original whole coal in Figure 6-5. Cleaning of the coal caused an increase in the quantity of ash under $1\text{ }\mu\text{m}$ and a decrease in ash between 1 and $4\text{ }\mu\text{m}$. The presence of the extraneous mineral matter in the whole coal appears to reduce the yield of fine particulate matter under $1\text{ }\mu\text{m}$. This is not likely to result from in-flame collisions since the probability of such events is low. It is possible, however, that the extraneous mineral matter and the organic rich coal particles could come in contact during grinding and in the feeder and remain in contact when they enter the reactor. As the extraneous ash melts on the char surface, the fine particulate matter released as the char is consumed may become attached to the large extraneous ash melt. Removal of the extraneous mineral matter by cleaning the coal prevents this type of interaction from occurring and fine particulate matter is released.

To determine if this could provide a possible means of reducing the yield of fine particulate matter, 1 part rougher tails from the Utah coal were mixed with 9 parts of the Beulah raw coal. The resulting ash size distribution is compared against ash size distributions of the Beulah raw coal and the rougher tails in Figure 6-6. Although below approximately $0.5\text{ }\mu\text{m}$ the amount of fine particulate matter was cut in half, the decrease in fine particulate matter was not as great as observed for the Utah coal in Figure 6-4. This may indicate that the "casual" contact between extraneous mineral matter in the rougher tails and the extraneous mineral matter free Beulah coal particles in the feeder is

Figure 6-3. Quantitative comparison of ash size distributions from the original Illinois coal, and the sum of the ash from the cuts.

Figure 6-4. Cumulative size distributions for ash from whole and cleaned coal.

Figure 6-5. Ash size distributions normalized to the mineral content of the original coal for the Illinois original coal, the Rougher Cut, and the Third Cleaner Concentrate.

Figure 6-6. Ash size distributions of ashes.

not sufficient to ensure that they remain in contact after entering the reactor. It may be necessary for the extraneous mineral matter particles to become imbedded in the surface of the Beulah coal particles to ensure that they remain in contact upon entering the reactor. Grinding the Beulah coal in the presence of extraneous mineral matter may provide this necessary amount of contact.

Overall, cleaning the coal resulted in a reduction of the amount of fine particulate matter on an absolute mass basis. Figures 6-7 and 6-8 are plots of the mass of ash produced from 100 g raw and cleaned coal as a function of particle size. The lower fraction of ash under 5 μm and the lower overall ash content of the cleaned coals substantially reduces the amount of fine particulate matter produced by the cleaned coals.

6.2 Mechanistic Experiments - Sized Cuts

This set of experiments involved separating both the raw and cleaned coals into different size cuts and measuring the resultant ash size distributions. This was done for the raw Utah and Illinois coals and the cleaned Utah and Illinois coals. These coals were sized into -18 μm , +18 -37 μm , +37 -85 μm , and +85 μm size cuts by an air classification technique. Proximate analysis results are given in Table 6-2, mass mean diameters of the size cuts are given in Table 6-3, and particle size distributions are given in Appendix C. Ash content of the sized coals did not vary except for the Illinois raw coal.

Particle size distributions of the ash from these coals are given in Figures 6-9 through 6-12. At the largest size measured in the cascade impactor, 6 μm , the fraction of ash smaller than this size decreased as the size cut's increased for all four sets of coals. This is in agreement with the basis of the breakup model which states that the size of the ash particles is dependent on the size of the parent coal particles.

The data plotted in Figure 6-9 through 6-12 are plotted in Figures 6-13 through 6-16 as the differential size distribution. The peaks at 2 μm in the differential size distribution of the whole coals, plotted in Figure 5-14, indicated that included mineral matter released during grinding or the early

Figure 6-7. Ash size distributions of raw and cleaned coal.

Figure 6-8. Ash size distributions of raw and cleaned coal.

**Table 6-2. Proximate Analysis Results
(As Received)**

	% Moisture	% Ash	% Volatile
Utah Raw Coal			
-18	3.30	7.69	40.14
+18-37	3.67	4.87	41.26
+37-85	3.72	6.36	41.25
+85	3.50	5.52	41.99
Utah Cleaned Coal			
-18	3.19	2.34	41.29
+18-37	3.74	2.18	40.64
+37-85	3.27	2.38	41.26
+85	3.08	2.93	40.20
Illinois Raw Coal			
-18	3.46	17.09	31.90
+18-37	3.63	10.40	35.21
+37-85	3.98	9.91	35.30
+85	3.78	8.86	35.62
Ill. Cleaned Coal			
-18	3.88	7.17	35.23
+18-37	4.38	6.38	37.53
+37-85	6.47	5.89	34.94
+85	5.26	5.42	35.35

Table 6-3. Mass Mean Diameters of Size Cuts

Coal	-18	+18-37	+37-85	+85
Utah Raw Coal	16	30	60	140
Utah Cleaned Coal	17	32	55	133
Illinois Raw Coal	13	30	60	143
Illinois Cleaned Coal	16	28	62	132

Figure 6-9. Ash size distributions of sized coal.

Figure 6-10. Ash size distributions of cleaned and size coal.

Figure 6-11. Ash size distributions of sized coal.

Figure 6-12. Ash size distributions of sized coal.

stages of the combustion process contributed to the presence of ash in the 0.5 to 5 μm size range. Similar peaks are present in Figures 6-13 through 6-16 in some but not all distributions. The 2 μm peaks of the -18 μm and +18-37 μm size cuts are significantly higher than the 2 μm peaks for the larger size cuts and a general overall trend of increasing 2 μm peak height can be observed as the coal size is decreased. The height of the 2 μm peaks are plotted in Figure 6-17 reveal a consistent trend with the peak height decreasing as the coal particle size is increased. This agrees with the hypothesis that mineral matter near the surface is released during grinding or the early stages of combustion: smaller coal particles will have less included mineral matter near the surface than larger particles. The trends in Figure 6-17 should be treated with caution as the simple breakup model would predict such a trend. If this trend resulted from the breakup mechanism, however, it should also be observed at larger particle sizes. Examination of the data at the next two larger particle sizes reveals that although the trend can still be observed in a few of the plots, it is much less apparent and not as consistent as the peak at 2 μm .

Breakup model predictions and the data from Figures 6-9 through 6-12 are plotted in Figures 6-18 through 6-33. Predictions using the simple breakup model with the breakup number found for the whole coals in Section 4 are shown by the dashed line and the breakup model modified to account for the vaporization/-condensation mechanisms and the release of included mineral matter near the surface of the coal particle are shown by the solid line. The breakup numbers required to fit the data for both versions of the model are given in Table 6-4. Although extremely large breakup numbers were required to fit the data for the +37-85 μm and +85 μm size cuts, in general the modified breakup model required lower breakup numbers than the simple breakup model.

The simple breakup model was able to fit the data with a moderate degree of success for only two of the size cuts (the +37-85 μm raw Utah and the +37-85 μm cleaned Utah coals). The fit between the modified breakup model and the data for the -18 μm and the +18-37 μm size cuts of all four coals (the raw and cleaned Utah coal and the raw and cleaned Illinois coal) and some of the larger size cuts of the Illinois coals was excellent while the fit between the +37-85 μm and +85

Figure 6-13. Differential size distributions of four raw coals (taken from the data plotted in Figure 6-9).

Figure 6-14. Differential size distributions of four cleaned coals (taken from the data plotted in Figure 6-10).

Figure 6-15. Differential size distributions of four raw coals (taken from the data plotted in Figure 6-11).

Figure 6-16. Differential size distributions of four cleaned coals (taken from the data plotted in Figure 6-12).

Figure 6-17. Heights of 2 μm peaks from differential size distributions in Figures 6-13 through 6-16.

Figure 6-18. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-19. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-20. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-21. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-22. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-23. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-24. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-25. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-26. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-27. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-28. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-29. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-30. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-31. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-32. Comparison of cascade impactor ash size distributions and the breakup model.

Figure 6-23. Comparison of cascade impactor ash size distributions and the breakup model.

μm size cuts of the raw and cleaned Utah coals was moderately good. Inconsistencies between the model and ash size distributions for the larger size cuts may result from either:

- The use of an included mineral size of $2 \mu\text{m}$ (obtained from the literature) rather than the measured included size distributions of the individual coals; or
- A greater yield of aerosol ash by the larger coal particles.

Table 6-4. Breakup Numbers for Ash from Sized Coals.

Coal	Size	Breakup Number Simple Model		Breakup Model Modified	
		Raw	Cleaned	Raw	Cleaned
Utah	-18	1.8	1.8	1.8	1.8
	+18 -37	7	1.8	3.5	1.8
	+37 -85	50	1.8	3.0	1.0
	+85	200	50	100	4
Illinois	-18	1.0	3.5	1.0	3.5
	+18 -37	9	7	3.5	6
	+37 -85	300	30	50	10
	+85	300	100	25	20

6.3 Mechanistic Experiments - Grinding

The Utah raw coal was ground to four different size cuts: $-20 \mu\text{m}$, $+20-40 \mu\text{m}$, $+40-80 \mu\text{m}$, and $+80 \mu\text{m}$. The grinding process involved grinding four batches of raw Utah coal (initial size greater than 1 cm) by continuously passing the coal through a ball mill until the appropriate size range was reached. The size distributions of ash from the grinding ranges are plotted in Figure 6-34 and are plotted in a differential form in Figure 6-35. As in Section 6.2, a peak can be observed at $2 \mu\text{m}$ for the smaller size cuts.

Figure 6-34. Ash size distributions of Utah coal ground to various sizes.

Figure 6-35. Differential size distributions of Utah coal ground to various sizes and a coal ground to a specified size.

The size distributions of the ash from the grinding ranges are compared to the size distributions of ash from a Utah coal which had been sieved to similar size ranges from an initial grind with a mass mean diameter of 40 μm in Figures 6-36 through 6-39. In Figure 6-35 there is a significant difference in the amount of ash under 1 μm from the coal sieved to -18 μm and the coal ground to -20 μm . The primary difference between these two coal samples is the amount of extraneous mineral matter (including mineral matter which was originally extraneous and included mineral matter released during grinding). The -20 μm ground coal contains extraneous mineral matter from a single batch of coal ground down to 20 μm and smaller. The sieved coal, however, contains extraneous mineral matter from a batch of coal which had an initial mass approximately four times greater and had been sieved to a mass mean diameter of 40 μm . This larger batch was then sieved to -18 μm , +18-37 μm , +37-85 μm , and +85 μm size cuts. Since most of the extraneous mineral matter is smaller than 18 μm and the released included mineral matter has an average size of 2 μm , most of these two forms of mineral matter will be present in the -18 μm size cut. A higher ash content can be observed in Table 6-3 for both the Utah and Illinois -18 μm size cuts. The larger quantity of extraneous mineral matter in the sieved coal appears to reduce the production of ash under 1 μm . This conclusion agrees with similar findings discussed in Section 6.1.

The three larger ground size cuts did not behave different than the sieved coal. The three larger sieved size cuts would not contain any extraneous mineral matter and, if the hypothesis that external mineral matter prevents the formation of fine particulate matter under 1 μm is correct, would not exhibit a significant reduction in the quantity of ash under 1 μm .

6.4 Summary

The mechanistic experiments focussed on experiments designed to determine the influence of various mechanism which have the potential for contributing to the formation of fine particulate matter in the 0.5 - 10 μm size range. Three sets of experiments were performed: 1) a study to determine the influence of coal cleaning (removing extraneous mineral matter) of ash formation; 2) sizing

Figure 6-36. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.

Figure 6-37. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.

Figure 6-38. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.

Figure 6-39. Comparison of ash size distributions of coal ground to the given size and coal ground first and then sieved to the given size.

raw and cleaned coals (which had been ground first) to determine the influence of coal particle size; and 3) grinding a coal to different sizes to determine the influence of grinding.

Comparison of ash size distributions from raw and cleaned coal indicated that cleaning coals increased the yield of ash particles under $1\text{ }\mu\text{m}$. The presence of the extraneous mineral matter in the raw coal appeared to reduce the yield of fine particulate matter under $1\text{ }\mu\text{m}$. It was hypothesized that fine particulate matter released as the char particle is consumed may become attached to the relatively large extraneous mineral matter particles which were imbedded on the surface of coal particles during grinding. The addition of extraneous mineral matter to the Beulah coal, which does not contain any extraneous mineral matter, reduce the yield of fine particulate matter under $0.5\text{ }\mu\text{m}$.

The $2\text{ }\mu\text{m}$ peaks in the differential ash size distributions observed in the global experiments (Section 5.0) were also observed to occur in those of the sized coals. The height of the peaks decreased as coal particle size was increased, which is consistent with the hypothesis that the $2\text{ }\mu\text{m}$ peaks resulted from included mineral matter released either during grinding or the early stages of combustion. The fit between the modified breakup model and the ash size distributions from $-18\text{ }\mu\text{m}$ and $+18 - 37\text{ }\mu\text{m}$ coals was excellent while the fit for the larger sized coals was good. Inconsistencies between the model and the data for the larger sized coals was attributed to either: the use of an included mineral size of $2\text{ }\mu\text{m}$ (obtained from the literature) rather than the measured included size distributions of the individual coals; or, a greater degree of aerosol production by larger coal particles.

The grinding experiments involved grinding four batches of coal to four size ranges ($-20\text{ }\mu\text{m}$, $+20 - 40\text{ }\mu\text{m}$, $+40 - 80\text{ }\mu\text{m}$, $+80\text{ }\mu\text{m}$). As with the sized experiments (Section 6.2), a $2\text{ }\mu\text{m}$ peak could be observed in the differential particle size distributions of the smaller size cuts. This data was compared to that of the ash size distributions from the sized experiments (where a single batch of coal was prepared by first grinding and then sieving to four size ranges: $-18\text{ }\mu\text{m}$, $+18 - 37\text{ }\mu\text{m}$, $+37 - 85\text{ }\mu\text{m}$, and $+85\text{ }\mu\text{m}$). The $-18\text{ }\mu\text{m}$ coal which had

been ground and then sieved produced significantly less coal than the coal which had been ground to $-20\text{ }\mu\text{m}$. This was attributed to the greater quantity of extraneous mineral matter (including mineral matter which was originally extraneous and included mineral matter released during grinding) present in the $-18\text{ }\mu\text{m}$ ground and sieved coal. This agreed with the findings of the cleaning experiments (Section 6.1) where the presence of extraneous mineral matter appeared to reduce the yield of ash under $1\text{ }\mu\text{m}$.

7.0 PROCESS SIMULATION

The process simulation portion of the program involves comparing data taken in a pilot scale reactor to data taken in the field on full scale boilers. This comparison provides a link between data taken in pilot scale reactors and full scale boilers and validates the use of pilot scale data to study the formation of fine particulate matter. Particle size distributions of ash taken from the ash characterization furnace and ash taken from full scale boilers are plotted in Figure 7-1 through 7-5. Proximate analyses of the coals used in taking the data in Figures 7-1 through 7-5 are given in Table 7-1.

The ashes sampled from the full scale boilers were sampled from the inlet of the electrostatic precipitator. The curves for this data are taken from a polynomial fit of a number of particle size measurements. The pilot scale data is taken directly from a single cascade impactor run.

The agreement between the pilot scale and field data is reasonable. Two types of deviations can be observed. Two of the plots (Plants #1 and #2) show a lower level of ash at $0.3\text{ }\mu\text{m}$ by the full scale ash size distributions. This may result from the process of deposition of fly ash on the convective tubes. It was observed that the convective tubes were coated with fly ash completely around the circumference of the tube, not just the leading edge. Depositions on the trailing edge of the tubes would likely be very sensitive to eddies forming in this region and smaller particles would preferentially deposit there.

The second type of deviation observed is that the percentage ash at the largest size capable of being measured by the cascade impactor is smaller for the field data than the pilot scale data (Plants #2 and #7). This may result from the different grinding procedures used in preparing the pilot and full scale coals. The pilot scale coals were prepared in a small scale hammer mill while the full scale coals were ground in large ball mills. Large ball mills tend to produce relatively large amounts of coal particles under $10\text{ }\mu\text{m}$ due to the aerodynamics inside the mill. (Coal particles remain in the ball mill until their size is small enough that they can be removed by a flow of air.) The small

Figure 7-1. Comparison of particle size distributions of ash sampled from pilot and full scale facilities.

Figure 7-2. Comparison of particle size distributions of ash sampled from pilot and full scale facilities.

Figure 7-3. Comparison of particle size distributions of ash sampled from pilot and full scale facilities.

Figure 7-4. Comparison of particle size distributions of ash sampled from pilot and full scale facilities.

Figure 7-5. Comparison of particle size distributions of ash sampled from pilot and full scale facilities.

scale hammer mill grinds coal does not do this. It is thus possible that the coal size distributions in the full scale boilers have a greater fraction of small particles than the coal used in the pilot scale reactor.

Table 7-1. Properties of Coals Tested in Process Simulations.

Coal	Coal Type	% Ash*	% H ₂ O*	% Vol*	BTU/lb (dry)
Plant #1	Sub-Bit.	8.08	18.6	35.4	9,055
Plant #2	Bit.	12.55	9.06	35.5	10,869
Plant #7	Sub-Bit.	4.31	23.42	40.8	9,654
River Rouge	Bit.	12.12	4.31	35.4	12,316
Trenton	Bit.	7.15	5.70	33.6	13,101

* - As Received

8.0 CONCLUSIONS

The primary objective of this program was to provide a basic understanding of the mechanisms that govern the formation of particulate matter in the 0.5 - 10 μm size range in pulverized coal flames. These mechanisms were studied by measuring ash size distributions of coals as a function of combustion parameters such as temperature and oxygen concentration, and determining the influence of cleaning, sizing and grinding the parent coals. Two important findings resulted from this work.

Particle sizes smaller than the 0.5 - 10 μm size range are generally accepted to result from a vaporization/condensation mechanism while particles larger than this size result from the coalescence of ash in coal particles which may breakup as they burn. Data taken under this program showed a relatively large fraction of ash present at 2 μm , approximately the same size as the mass mean diameter of included mineral matter (typically ranges from 0.5 μm to 5 μm). It was concluded that this ash resulted from included mineral matter which is released either during grinding or the early stages of combustion. Modification of the breakup model to account for the release of included mineral matter near the surface of the coal particles (and for the vaporization/condensation mechanism) allowed the model to fit the data.

Although the goal of this work was to study the formation mechanisms of ash particles in the 0.5 - 10 μm size range, the data provided information on a potential means for reducing the yield of ash under 0.5 μm . Ash under 0.5 μm results from minerals vaporized during combustion which subsequently nucleate and condense out of the gas phase on any available surface. Data taken under this program showed that cleaning coal by removing external mineral matter increased the yield of ash under 1 μm . This could be due to vaporized minerals condensing on external mineral matter which had become embedded on the surface of the coal particle during grinding. This suggests that adding external matter to a coal could reduce the yield of ash under 1 μm . Doing this for a coal which contained no external or included mineral matter (only atomically dispersed minerals) reduced the yield of ash under 1 μm by one-half. Adding the external

mineral matter (or possibly, ash collected from the particulate collection device) during grinding could result in a greater reduction.

9.0 REFERENCES

- Allen, R. M., and R. W. Carling. Microstructural Changes in Coal During Low Temperature Ashing, Report No. SAND 84-8713, Sandia National Laboratories, Livermore, CA (May 1984).
- Allen, R. M., and J. B. van der Sande. ACS Division of Fuel Chemistry, Preprints 27(1), 124 (1982).
- Block, C., and R. Dams. Environ. Sci Technol. 10, 1011 (1976).
- Dahlin, R. S. "Modeling the Formation and Size Distribution of Flyash." Ph.D. Dissertation, University of Alabama (1985).
- Damle, A. S., D. S. Ensor, and M. B. Ranade. "Coal Combustion Aerosol Formation Mechanisms: A Review." Aerosol Science Tech. 1, 119 (1982).
- Davison, R. L., D. F. S. Natusch, J. R. Wallace, and C. A. Evans. Environ. Sci. Technol. 8, 1107 (1974).
- Flagan, R. C. "Submicron Particles from Coal Combustion." 17th Int. Symp. on Combustion, p. 97, The Combustion Institute (1979).
- Fisher, G. L., et al. ACS Division of Fuel Chemistry Preprints 22(4), 149 (1977).
- Fisher, G. L., D. P. Y. Cheng, and J. Brummer. Science 192, 553 (1976).
- Flagan, R. C., and S. K. Friedlander. "Particle Formation in Pulverized Coal Combustion - a Review." Recent Developments in Aerosol Science, D. T. Shaw, ed., Wiley, New York (1978).
- Gladney, E. S., J. A. Small, G. E. Gordon, and W. H. Zoller. Atmos. Environ. 10, 1071 (1976).

- Gluskoter, H. J., N. F. Shimp, and R. R. Ruch. "Coal Analysis, Trace Elements and Mineral Matter." Chemistry of Coal Utilization, Second Supplemental Volume." M. A. Elliott, Ed., Wiley, New York (1981).
- Hansen, O., and G. L. Fisher. Environ. Sci. Technol. 14, 1111 (1980).
- Harris, D. B., "Procedures for Cascade Impactor Calibration and operation in Process Streams." EPA-600/2-77-004 (1977).
- Harris, L. A. ACS Division of Fuel Chemistry Preprints 27(1), 131 (1982).
- Helble, J., M. Neville, and A. F. Sarofim. Aggregate Formation from Vaporized Ash During Pulverized Coal Combustion, 21st Int. Symp. Combust. The Combustion Institute in press (1987).
- Holve, D. J. "In Situ Measurements of Flyash Formation from Pulverized Coal." Combustion Science and Technology, 44, pp 269-288 (1986).
- Lauf, R. J. Fuel 60, 1177 (1981).
- Linak, W. P., and T. W. Peterson. Aerosol Sci. Technol. 3, 77 (1984).
- Littlejohn, R. F. "Mineral Matter and Ash Distribution in 'As-Fired' Samples of Pulverized Fuels." J. Inst. Fuel., 39, 301, pp. 59-67 (1966).
- McCain, J. D., J. P. Gooch, and W. B. Smith. J. Air Poll. Control Assoc. 25 117 (1975).
- McNellan, M. J., G. J. Yurek, and J. F. Elliot. Combustion and Flame 42, 45-60 (1981).
- Neville, M., R. J. Quann, B. S. Haynes, and A. F. Sarofim. 18th Int. Symp. Combust., p. 1267, The Combustion Institute (1981).

- Neville, M., and A. F. Sarofim. 19th Int. Symp. Combust., p. 1441, The Combustion Institute (1982).
- O'Gorman, J. V., and P. L. Walker. "Mineral Matter and Trace Elements in U.S. Coals." U.S. Department of the Interior Office of Coal Research, Research Development Report Number 61 (1972).
- Quann, R. J., and A. F. Sarofim. 19th Int. Symp. Combust., p. 1429, The Combustion Institute (1982).
- Raask, E. J. Inst. Fuel 43, 339 (1968).
- Raask, E. Mineral Impurities in Coal Combustion, Hemisphere (1985).
- Sarofim, A. F., J. M. Beer, and S. G. Kang. "Fundamental Studies of Mineral Matter Vaporization and Residual Ash Formation." PSI Technology Company, Quarterly Report No. 5, DOE Contract DE-AC22-85PC90751, (January, 1988).
- Sarofim, A. F., J. B. Howard, and A. S. Padia. Combust. Sci. Technol. 16, 187 (1977).
- Schmidt, E. W., J. A. Gieseke, and J. M. Allen. Atmos. Environ. 10, 1065 (1976).
- Seeker, W. R., G. S. Samuelsen, M. P. Heap, and J. D. Trolinger. 18th Int. Symp. Combust., p. 1213, The Combustion Institute (1981).
- Senior, C. L., and R. C. Flagan. Aerosol Sci. Technol. 1, 371 (1982).
- Van Crevelen, D. W. "Coal: Typology, Chemistry, Physics, and Constitution." Elsevier, Amsterdam (1961).

Appendix A
Particle Size Distributions of Raw Coals and Their Ashes

Appendix B
Particle Size Distributions of Cleaned Coals

Appendix C
Particle Size Distribution of Sized Coals

END

**DATE
FILMED**

8 / 10 / 92