REACTOR ENGINEERING DEPARTMENT

REACTOR TECHNOLOGY SECTION

KEYWORDS:

Physics
Reactor Safety
Mark 22

RETENTION:

CLASSIFICATION:
UNCLASSIFIED

K-14 SHUTDOWN REACTIVITY (U)

BY

JOHN R. CHANDLER

ISSUED: October 31, 1990

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

APPROVALS

Raymond L. Seid
Technical Reviewer

Date: 10/31/90

JR Chandler
Manager, Core Physics

Date: 10/31/90

FN Benton
Manager, Reactor Technology Section

Date: 10-31-90

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

72

WSRC-TR-90-42-137

October 31, 1990

TO: F. BERANEK, 704-C

FROM: J. R. CHANDLER, 707-C

JRC

K-14 SHUTDOWN REACTIVITY

INTRODUCTION AND SUMMARY

SRS reactor charges are designed to ensure the reactor remains subcritical during chargeback and shutdown conditions. Calculations have recently been performed to determine the shutdown k_{eff} for the K-14 charge. This document discusses the results and uncertainties.

SUMMARY

The best estimate for K-14 shutdown k_{eff} is 0.9411. Uncertainty in k_{eff} from reactivity calculations, control rod contents, safety rod worth, and assembly contents is 0.0169 at the 95% confidence level and 0.0279 at the 99% confidence level. Maximum shutdown k_{eff} is therefore 0.9580 with 95% confidence and 0.9690 with 99% confidence.

DISCUSSION

Best Estimate Shutdown Reactivity

The shutdown K-14 k_{eff} has been evaluated using the GLASS and GRIMHX computer codes with the method described in Reference 2. The calculated k_{eff} is 0.9275.² The calculation used the fabricated contents as reported in Reference 3. Input to these calculations includes a cross section modification factor to account for the presence of safety rods. The factor used in the calculations corresponds to the best estimate safety rod worth.⁴

Calculational bias of GRIMHX is nearly the same as for MARCO.⁵ This bias has been determined to be 0.0136.⁶ Adding the bias to the calculated value yields 0.9411, the best estimate for K-14 shutdown k_{eff} .

Calculation Uncertainties

Reactivity predictions contain uncertainties due to methodology, nuclear data, and contents for fuel tubes, target tubes, and control rods. It is not possible to completely separate these uncertainties. Thus they were all lumped into calculation uncertainties and evaluated as one.

The observed critical position from nine past Mark 22 cores has been used to determine the uncertainties in calculation bias for several different confidence intervals.⁶ This evaluation determined the uncertainty of the calculational bias discussed above. The uncertainty is given in Reference 6 in terms of tolerance intervals. Tolerance intervals describe the expected variation in individual future observations. They are limits which bound a proportion of individuals with a given probability. The choice of population proportion and probability is arbitrary. For simplicity I will adopt the definition that 95% confidence is a 95% proportion of future observations with a 95% probability. Using this definition the 95% confidence level uncertainty in k_{eff} is 0.0157 $\Delta k/k_{eff}$.⁶ The 99% confidence level uncertainty in k_{eff} is 0.0265 $\Delta k/k_{eff}$.⁶

Safety Rod Worth

The data in Reference 6 is for observed critical and therefore does not include safety rods. Safety rod uncertainties must be considered separately. The calculated best estimate shutdown k_{eff} using the GRIMHX code is 0.9275.² The shutdown calculation using best estimate safety rod worth minus 2 sigma yields 0.9357.^{2,4} The uncertainty in the safety rod worth is the difference (0.0082 Δk) between these two values. Thus the uncertainty at the 95% confidence level can be expressed as 0.0088 $\Delta k/k_{eff}$ for all values of k_{eff} . The corresponding uncertainty at the 99% confidence level (3 sigma uncertainty) can be determined from the 95% confidence level (2 sigma uncertainty) as 0.0132 $\Delta k/k_{eff}$.

Significance

The uncertainties described above are summarized in Table 1. The net effect of uncertainties was determined by taking the square root of the sum of the squares. The net uncertainty in shutdown k_{eff} is seen to be 0.0169 at the 95% confidence level and 0.0279 at the 99% confidence level. The estimate for maximum shutdown k_{eff} is therefore 0.9580 (95% confidence level) or 0.9690 (99% confidence level).

REFERENCES

1. R. A. Bond, K-14 Chargeback Predictions, WSRC-TR-90-42-046, June 29, 1990.
2. R. A. Bond, K-14 Shutdown Calculation Notes, OPS-RTS-900168, October 17, 1990.
3. K-14 Mark 22 Charge Match List, Rev.2, ID# 06/20/90 15:36:01:86, June 20, 1990 (Confidential).
4. P. B. Parks, W. E. Graves, and N. H. Kuehn, Estimates Of the Safety Rod Timing, Worth and Post-Power Peaking In Mark 22 Charges, DPSP-88-865, January, 1989, and Addendum 1, March, 1989.
5. R. L. Webb, The Mark 22 MARCO Library and Recent Updating Of the MARCO Code, DPST-86-234, January 15, 1986.
6. R. L. Webb, Uncertainties and Bias In Mark 22 MARCO Calculations, DPST-88-859, November, 1988.

TABLE 1
K-14 Shutdown Reactivity

<u>Value</u>	<u>Comments</u>
0.9275	Calculated k_{eff} with all control & safety rods inserted. Includes best estimate safety rod worth.
+0.0136	Correction for calculational bias.
<hr/> 0.9411	Best estimate shutdown k_{eff} .
± 0.0169	Uncertainty for 95% confidence (0.0180 $\Delta k/k_{eff}$). This includes 0.0157 $\Delta k/k_{eff}$ calculational uncertainty and 0.0088 $\Delta k/k_{eff}$ uncertainty for safety rod worth.
± 0.0279	Uncertainty for 99% confidence (0.0296 $\Delta k/k_{eff}$). This includes 0.0265 $\Delta k/k_{eff}$ calculational uncertainty and 0.0132 $\Delta k/k_{eff}$ uncertainty for safety rod worth.

**DATE
FILMED
8 10 7 1 9 2**