AIIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

100-100000

**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1994

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This is a **historical document** that is being released for public availability. This was made from the best available copy. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DECLASSIFIED

(CLASSIFICATION)
HANFORD TECHNICAL RECORD
GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

DOCUMENT NO.

HW-70740

SERIES AND COPY NO.

DATE

August 15, 1961

☒

RESTRICTED DATA

THIS DOCUMENT IS RESTRICTED DATA
DEFINED IN ATOMIC ENERGY ACT OF 1954.
ITS TRANSMISSION OR THE DISCLOSURE OF ITS
CONTENTS IN ANY MANNER NOT AUTHORIZED
HEREIN IS PROHIBITED.

TITLE

RECOMMENDED E-N CHARGE MODIFICATION
(SECOND CYCLE PT-IP-350-C E-N DEMONSTRATION LOAD)

☐

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING
THE NATIONAL DEFENSE OF THE UNITED STATES
WITHIN THE MEANING OF THE ESPIONAGE LAWS,
TITLE 18, U. S. C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER
TO AN UNAUTHORIZED PERSON IS PROHIBITED BY
LAW.

AUTHOR

R. D. Carter

CIRCULAR FILE

RECEIVED 100D AREA

AUG 17 1961

RETURN TO

TECHNICAL INFORMATION FILES

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS
TO IT. WHEN NOT IN USE IT MUST BE STORED IN AN APPROVED LOCKED CONTAINER WITHIN AN APPROVED
GUARDED AREA. IF IT IS YOUR POSSESSION AND UNDER YOUR CONTROL, YOU MUST OBTAIN A SIGNED RECEIPT FROM
CLASSIFIED PERSONNEL. IT IS YOUR RESPONSIBILITY TO RETURN IT AND ITS CONTENTS WITHIN THE LIMITS OF
THIS DOCUMENT AND FROM ANY UNAUTHORIZED SOURCE. ITS TRANSMITTAL TO, AND STORAGE AT YOUR PLACE,
WHICH IS PROHIBITED. IT IS NOT TO BE DUPLICATED. IF ADDITIONAL COPIES ARE REQUIRED,
OBTAIN THEM FROM THE RELATIONSHIP FILE. ALL PERSONS READING THIS DOCUMENT MUST SIGN IN THE SPACE PROVIDED BELOW.

ROUTE TO:

PAYROLL NO.

LOCATION

FILES ROUTE
DATE

SIGNATURE AND DATE

RECORD
COPY

Indefinite Retention

Disposal Date

Authority

Authority

(CLASSIFICATION)

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DECLASSIFIED

HW-70740

Page 1

DISTRIBUTION

1-2. AEC-HOO: Attn: AT Gifford	15. GL Madsen
3. AEC-HOO: Attn: RL Plum	16. WS Nechodom/DI Monnie
4. TW Ambrose	17. R Nilson
5. RW Bown	18. GF Owsley
6. JH Brown	19. T Prudich
7. RD Carter	20. RW Reid
8. BR Cremer	21. HG Spencer/CG Hough
9. EJ Filip	22. SL Stewart
10. GC Fullmer	23. AN Stinson
11. WD Gilbert	24. AD Vaughn
12. SM Graves	25. AP Vinther/IL Huffman
13. AK Hardin	26. 300 Files
14. LW Lang	27. Record Center

This document contains restricted information as defined in the Atomic Energy Act of 1954. Its transmittal and disclosure of its contents in any manner to any person is prohibited.

This document consists of
4 pages. No. 11 of
27 copies.

This document classified by

GC Fullmer

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of *RM-100*

CGPR-2, 3-2-94

By *J E Samsky 3-15-94*

Verified By *DK Hansen, 3-25-94*

August 15, 1961

A. P. Vinther, Manager
H Processing Operation
H Reactor Operation

RECOMMENDED E-N CHARGE MODIFICATION (SECOND CYCLE PT-IP-350-C E-N DEMONSTRATION LOAD)

INTRODUCTION AND SUMMARY

The original charge for the E-N core load at H reactor⁽¹⁾, consisting of five different types of charges, each group of five containing 199 .947 per cent enriched uranium E-pieces of six inch nominal length and 16 Li-Al I&E (N) pieces of four inch nominal length plus mixers, was intended to provide enough excess reactivity to operate the reactor at all times with reasonable but not excessive flexibility.

During actual operation the excess reactivity observed has been somewhat greater than conservatively planned. In addition, a very slight long-term gain rather than

MASTER

(1) HW-66300 PT2, Production Test IP-350-C, E-N Demonstration Load at H Reactor, R. D. Carter, 4/4/61.

the expected loss has been observed up to this time (73 MWD/column average exposure). On this basis, a modification of the original charge makeup has been determined which will permit increased conversion and operating efficiency.

RECOMMENDATIONS

The recommended modification consists of five different types of charges, each group of five columns to contain 198 E-pieces and 17 Li-Al pieces plus mixers. Specifically, the makeup of the respective charges for the second E-N loading at H reactor includes a standard downstream dummy pattern (SDDP) as used with a 32-piece natural uranium column and is as follows:

<u>Code No.</u>	<u>Charge Makeup - Rear-to-Front</u>
1	SDDP; 2-E; 1-N; 12-E; 1-N; 1-E; 1-Mixer; 9-E; 1-N; 11-E; 1-N; 4-E.
2	SDDP; 4-E; 1-N; 9-E; 1-Mixer; 2-E; 1-N; 11-E; 1-N; 11-E; 1-N; 2-E.
3	SDDP; 7-E; 1-N; 8-E; 1-Mixer; 2-E; 1-N; 11-E; 1-N; 12-E.
4	SDDP; 9-E; 1-N; 6-E; 1-Mixer; 5-E; 1-N; 11-E; 1-N; 9-E.
5	SDDP; 11-E; 1-N; 4-E; 1-Mixer; 7-E; 1-N; 11-E; 1-N; 7-E.

These various column charges should be loaded into the flattened zone as shown in Figure 1. Additional E-N charges may be loaded into the sixth lattice unit from the reflector to replace pure enrichment charges at the discretion of the H reactor physicist. Additional E-N tubes charged should continue the loading pattern as shown in Figure 1.

REACTIVITY STATUS SUMMARY

As of August 1, 1961, the adjustable reactivity compensation in H reactor consisted of ten PCCF columns each loaded with 29 six inch Li-Al pieces and one Pb-Cd piece displaced 51 inches downstream, eight permanent poison columns of similar makeup but centered, 23 splines, and 14 PCCF tubes consisting mostly of water columns or the equivalent. Since the base case assumed water only in the PCCF tubes, any increase in poison must be relative to this loading.

The total excess reactivity compensation (exclusive of control rods) by this definition is therefore as follows:

Li-Al in PCCF (10)	3.0 milli-k
Li-Al in process tubes (8)	5.0 milli-k
Splines (22)	<u>3.3</u> milli-k
Total	11.3 milli-k

DECLASSIFIED

HW-70740

Page 3

Therefore, there is at least 11.3 milli-k of adjustable poison now in the reactor. The addition of one Li-Al piece to every fifth tube is calculated to reduce the excess reactivity by 9.6 milli-k, leaving 1.7 milli-k of adjustable poison during normal operation equivalent to ten or eleven splines. Actually, an additional flexibility of at least one milli-k is available in the control rods and a maximum of two milli-k would be available by charging all PCCF tubes with bismuth slugs. Thus, the available flexible poison in the reactor should be more than adequate with the modified E-N loading.

R.D. Carter

Operational Physics Sub-Section
Research and Engineering Section
IRRADIATION PROCESSING DEPARTMENT

RD Carter:nmd

HW-70740
Page 4

HW-70740

Page 4

FIGURE 1

Numbers specify the type of E-N charge
Blank tubes in numbered region are PCCF columns
G represents graphite stringers

DATE

FILMED

6/22/94

END