NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

DOE/NV/10872--T26

DE92 014684

DESIGN MANAGEMENT AND STRESS ANALYSIS
OF A CIRCULAR ROCK TUNNEL FOR STORAGE
OF SPENT NUCLEAR FUEL* .

BY : NADIA KANDALAFT-LADKANY
UNDER THE
DIRECTION OF: DR. RICHARD WYMAN
DEPARTMENT OF CIVIL AND
ENVIRONMENTAL ENGINEERING

*PROJECT SUPPORTED BY THE U.S. DEPARTMENT OF ENERGY

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

I. TUNNEL DESIGN CONSIDERATIONS

1. SIZE OF CANISTER HOLES
2. SPACING OF CANISTER HOLE
3. TUNNEL SIZE AND SHAPE
4. TUNNEL SPACING
5. GRAVITY (OVERBURDEN)
6. GEOTHERMAL TEMPERATURE
7. TEMPERATURE DISTRIBUTION IN THE NEAR FIELD ROCK
8. ROCK MATERIAL PROPERTIES
9. TUNNEL VENTILATION

ABSTRACT

In this report a Critical Path Method (CPM) diagram and a logic net are proposed for the design cycle of the rock tunnel system of a high level nuclear waste repository.

Considerations for changes in the aspect ratios and geometry of the tunnel system, placement and spacing of the canisters, heat diffusion and heat transfer analysis, stresses analysis and boring techniques are included in the CPM diagram and in logic net.

This research project also deals with stress analysis, using the finite element method, of a circular rock tunnel, part of a system of tunnels used for the long term storage of high level nuclear waste.

In the analysis, *the pre-existing temperature*
The tunnel is subjected to *insitu* and overburden loads, at construction. High thermal stresses ~~also~~ *develop* ^{*later*} due to the long term influx of heat from the stored canisters.

Results indicate that thermal stresses reach a critical level for the rock in the vicinity of the canisters which may lead to local collapse of the rock and possible damage to the canisters.

Results of the analysis also imply the need for a continuous cooling scheme of the tunnel system to prevent overheating of the rock.

TABLE OF CONTENTS

Abstract

Section I

Introduction

Section II

Proposal for a design cycle of rock tunnel system using management techniques

Section III

1. Literature review
2. Criteria for the stability analysis of the rock tunnel system
3. Temperature distribution in the rock tunnels

Section IV

Stress analysis by finite element of a circular tunnel section and a vertical canister placement hole

1. Stresses and displacement in the tunnel due to gravity and geothermal loading
2. Stresses and displacements in the tunnel due to thermal loading and gravity

Section V

Analysis of the results

Section VI

Conclusions and recommendations

Section VII

Bibliography

Section VIII

Appendices

Section II

Proposal for a design cycle of rock tunnel system using management techniques

II. 1. Logic net

The logic net deals with the following aspects of the design and construction of a tunnel system in bedrock. They are:

- a. The canisters are transported down the ramps to the storage drifts horizontally. They may be placed in the drifts either horizontally or vertically. The final length and method of placement of the canister affect the size of storage drifts.
- b. The shape of the tunnel is determined by the proposed mining method adopted for the construction of the tunnel system.
- c. Heat transfer and heat diffusion determine the spacing between tunnels and between canisters.
- d. Tunnel ventilation will influence the design temperature in the near field rock.
- e. Site investigation is required to determine the material and thermal properties of the rock and the depth of the tunnel system.
- f. Method and rate of canister loading along with the mining method selected affect the overall boring speed and the final completion date of the repository
- g. Finite element stress analysis, taking into consideration the geometry of tunnels, their spacing, overburden and temperature distribution determines the stability of tunnel system.

The logic net shown takes into consideration all the design aspects mentioned. The final output determines the canister loading rate preceded by mining drilling and ventilation of the

tunnels.

II. 2. Critical Path Method Diagram (CPM)

The CPM diagram titled "Project Management Method" shows an orderly progress of the design cycle tasks. Our research has not determined the units of time required for completion of each task. This will require an input from several research laboratories and Geological Engineering sources.

Once the time units for the various activities are determined, a CPM program may be used to execute the proposed project management scheme.

CANISTER FOR VERTICAL EMPLACEMENT

Accepts:

Consolidated, 10 yr. HBU, 4 assems X 846w = 3384w
 Consolidated, 5 yr. ABU, 4 assems X 846w = 3384w
 Intact, 5 yr. HBU, 2 assems X 1316w = 2632w

Figure 10. PWR spent fuel canister, 2/4 assemblies, vertically emplaced.

Accepts:

Consolidated, 10 yr, HBU,*	12 assems	X	280w	=	3360w
Consolidated, 10 yr, ABU,	14 assems	X	190w	=	2660w
Consolidated, 5 yr, ABU,	12 assems	X	280w	=	3360w
Intact, 10 yr, ABU,	7 assems	X	190w	=	1330w
Intact, 5 yr, ABU,	7 assems	X	280w	=	1960w
Intact, 5 yr, HBU,	7 assems	X	435w	=	3045 w

*HBU = high burn up

ABU = average burn up

Figure 8. BWR spent fuel canister, 7/14 assemblies vertically employed.

Waste Package Boundary

I-2-a LENGTH OF CANISTER HOLE

I-2-b SPACING OF CANISTER HOLE

SHAPE AND SIZE OF TUNNEL

TUNNEL SPACING

I - 5 - GRAVITY (OVERBURDEN)

TUNNEL LOCATED IN TUFF - TSW2

1. PHYSICAL PROPERTIES

Bulk density = 2.34 g/c.cm

Grain density = 2.55 g/c.cm

Dry density = 2.25 g/c.cm

2. OVERBURDEN

UNIT	DENSITY	THICKNESS	PRESSURE
	g/c.cm	m	MPa
uo		9.14	(assumed) 0.5
TCw	2.31	26.8	0.61
PTn	1.58	38.1	0.59
TSW ₁	2.25	130.1	2.87
TSW ₂	2.32	82.01	1.865
		<hr/> 286.15	<hr/> 6.435

I - 6 GEO THERMAL TEMPERATURE

- a. INITIAL TEMPERATURE NEAR THE SURFACE IS 14° C
- b. THE CHANGE OF TEMPERATURE WITH DEPTH CORRESPOND TO AN
AVERAGE GEOTHERMAL GRADIENT ^{NT} OF $34^{\circ} / \text{Km}$

TEMPERATURE ALONG LINE 3 AT 11 YEARS

Figure 5-9. Comparison of Results for the Temperature along Line 1 (Figure 2-5) at 6 Yr

- Dotted lines represent data from Sandia Report

- Straight lines^{approximations} were used in the finite element analysis, since SAP interpolates linearly between temperature points.

TEMPERATURE ALONG LINE 1 AT 11 YEARS

TEMPERATURE ALONG LINE 2 AT 11 YEARS

Table 6-11. Physical properties of intact rock and rock mass for thermal/mechanical units^a at Yucca Mountain^b

Thermal/ mechanical unit	Grain density (g/cc)			Porosity			In situ saturation			Bulk density at in situ saturation (g/cc)			Dry bulk density (g/cc)		
	Design value ^c	Variability evaluation ^d value	range	Design value	Variability evaluation value	range	Design value	Variability evaluation value	range	Design value	Variability evaluation value	range	Design value	Variability evaluation value	range
TCW	2.51	2.51	±0.04	0.114	0.11	±0.04	0.8	0.67	±0.23	2.32	2.31		2.23	2.23	
PTn	2.37	2.37	±0.15	0.448	0.45	±0.15	0.8	0.61	±0.15	1.67	1.58		1.31	1.30	
TSW1 ^e	2.53	2.54	±0.04	0.148	0.14	±0.04	0.8	0.65	±0.19	2.27	2.25		2.15	2.15	
TSW1 ^f	2.53	2.53	±0.02	0.348	0.359	±0.039	0.8	0.65	±0.19	2.00	NA ^h		1.65	NA	
TSW2	2.55	2.55	±0.03	0.121	0.12	±0.03	0.8	0.65	±0.13	2.34	2.32		2.25	2.24	
TSW3	2.39	2.39	±0.02	0.043	0.04	±0.03	0.8	0.65	±0.19	2.34	2.32		2.25	2.29	
CHN1v	2.34	2.34	±0.05	0.365	0.36	±0.09	0.8	0.90	±0.06	1.78	1.82		1.49	1.50	
CHN1z	2.41	2.41	±0.06	0.327	0.33	±0.04	0.8	0.91	±0.06	1.96	1.92		1.63	1.61	
CHN2z	2.54	2.54	±0.12	0.286	0.29	±0.06	1.0	1.0 ¹	NA	1.96	2.09		1.63	1.80	
CHN3z	2.41	2.41	±0.04	0.360	0.36	±0.08	1.0	1.0 ¹	NA	1.96	1.90		1.63	1.54	
PPW	2.58	2.58	±0.04	0.240	0.24	±0.07	1.0	1.0 ¹	NA	2.20	2.20		1.96	1.96	
CFUn	2.43	2.43	±0.07	0.297	0.30	±0.08	1.0	1.0 ¹	NA	2.00	2.00		1.17	1.70	
BFw	2.60	2.60	±0.04	0.238	0.24	±0.08	1.0	1.0 ¹	NA	2.23	2.22		1.98	1.98	
CFMn1	2.41	2.41	±0.06	0.246	0.25	±0.05	1.0	1.0 ¹	NA	2.09	2.06		1.83	1.81	
CFMn2	2.52	2.52	±0.06	0.242	0.24	±0.03	1.0	1.0 ¹	NA	2.09	2.16		1.83	1.92	
CFMn3	2.44	2.44	±0.07	0.267	0.27	±0.03	1.0	1.0 ¹	NA	2.09	2.05		1.83	1.78	
TRW	2.63	2.63	±0.04	0.188	0.19	±0.05	1.0	1.0 ¹	NA	2.32	2.32		2.14	2.13	

^aThermal/mechanical units are defined in Figure 6-6.^bSee Appendix O of SNL (1987).^cDesign values represent the basis for the SCP-CDR.^dVariability evaluation represents more recent results of data analyses and establishes ranges for properties.^eNonlithophysal layers in unit TSW1.^fLithophysal layers in unit TSW1.^gFor lithophysal layers, the total porosity is $\phi_m = M + \phi_A + A + \phi_L$, where ϕ_m is matrix porosity, ϕ_A is the porosity of the vapor-phase-altered material, ϕ_L is the volume fraction lithophysal cavities, and M and A are volume fractions of matrix and vapor-phase-altered material, respectively (Price et al, 1985).^hNA = not available.ⁱThese units are at least partly below the water table. For the purpose of thermal/mechanical analyses, they have been assigned a saturation of 1.0.

Table 6-14. Mechanical properties of the rock mass for thermal/mechanical units^a at Yucca Mountain^b

Thermal/ mechanical unit	Deformation modulus (GPa)			Poisson's ratio			σ_c (MPa) ^c			Cohesion (MPa)			ϕ (deg) ^d		
	Design value	Design value	Variability evaluation range	Design value	Design value	Variability evaluation range	Design value	Design value	Variability evaluation range	Design value	Design value	Variability evaluation range	Design value	Design value	Variability evaluation range
TCw	15.4	20.0	± 5.55	0.10	0.10	NA ^g	77.5	120.0	± 81.75	22.5	26.0	± 10.13	29.7	44.7	± 0.20
PTn	1.1	1.9	± 1.95	0.18	0.19	NA	3.5	9.5	± 5.45	1.6	4.0	± 2.09	6.6	8.5	± 0.08
TSw1 ^h	15.1	15.9	± 4.2	0.20	0.22	± 0.05	75.0	63.5	± 33.30	22.1	18.0	± 5.70	29.2	34.9	± 0.15
TSw1 ⁱ	7.6	7.6	± 3.2	0.16	0.16	± 0.05	18.0	16.0	± 5.00	7.0	5.5	NA	14.3	12.5	NA
TSw2	15.1	15.2	± 4.2	0.20	0.22	± 0.05	75.4	83.0	± 33.30	22.1	17.8	± 5.70	29.2	23.5	± 0.15
TSw3	15.1	NA	NA	0.20	NA	NA	75.4	NA	NA	22.1	NA	NA	29.2	NA	NA
CHn1 ^v	2.4	3.6	± 2.2	0.15	0.15	NA	8.5	13.5	± 6.20	3.4	5.5	± 2.14	13.4	12.0	± 0.08
CHn1 ^z	3.5	3.6	± 2.1	0.17	0.16	± 0.08	13.5	13.5	± 4.50	5.1	5.4	± 1.08	15.8	7.6	± 2.60
CHn2 ^z	3.5	5.8	± 2.0	0.17	0.20	NA	13.5	20.0	± 6.35	5.1	7.5	± 1.67	15.8	16.4	± 0.06
CHn3 ^z	3.5	3.6	± 2.2	0.17	0.18	NA	13.5	13.5	± 5.50	5.1	5.5	± 1.87	15.8	12.0	± 0.07
PPw	6.1	8.2	± 3.9	0.20	0.19	NA	25.5	28.5	± 15.30	8.5	10.0	± 3.52	21.1	21.0	± 0.12
CFUn	3.8	3.8	± 2.95	0.16	0.16	NA	15.5	15.5	± 9.25	5.5	7.0	± 2.76	17.8	15.6	± 0.10
BFw	5.4	5.4	± 2.35	0.13	0.13	± 0.02	21.0	21.0	± 7.00	7.0	10.0	± 4.10	21.6	21.0	± 0.14
CFMn1	5.4	7.6	± 2.60	0.15	0.14	NA	22.3	26.0	± 9.70	7.7	9.9	± 2.61	20.5	19.9	± 0.09
CFMn2	5.4	8.2	± 1.7	0.15	0.17	NA	22.3	28.5	± 6.55	7.7	10.0	± 1.47	20.5	21.0	± 0.05
CFMn3	5.4	6.6	± 1.35	0.15	0.15	NA	22.3	22.5	NA	7.7	8.9	± 1.42	20.5	18.0	± 0.05
TRw	8.8	8.8	± 0.10	0.18	0.19	NA	36.0	36.0	± 11.50	11.5	13.5	± 4.56	24.8	27.6	± 0.14

^aThermal/mechanical units defined in Figure 6-6.^bSee Appendix O of SNL, (1987).^cDesign values represent the basis for the Site Characterization Plan-Conceptual Design Report (SNL, 1987).^dVariability evaluation values represent more recent results of data analyses and establish ranges for properties.^e σ_c - unconfined compressive strength.^f ϕ - angle of internal friction.^gNA - not available.^hNonlithophysal portions of unit TSw1.ⁱLithophysal portions of unit TSw1.

Note: 1) SHP extrapolated

between two α points explain

2) Rock property A, B

Recommendations for future work

a) Taken at ambient temperature:

Need data points for rock at
elevated temps.

b) Determine the thickness of
the disturbed zone at elevated
temperature & what the rock property
may be for the disturbed zone

c) Determine where the zone of
confined rock starts (outside the disturbed

I - 8 ROCK MATERIAL PROPERTIES

a. MECHANICAL PROPERTIES FOR ROCK MASS

Young's modulus	E = 15.2 GPa
Poisson's ratio	nu = 0.22
unconfined compressive strength	Gc = 75.4 MPa
cohesion	c = 22.1 MPa
angle of internal friction	σ = 29.2 degree

b. ROCK MASS THERMAL PROPERTIES

 THERMAL EXPANSION COEFFICIENT

$$\alpha = 8.8 \times 10^{-6} \text{ K}^{-1} \quad (T < 200^\circ \text{ C})$$

$$\alpha = 24.0 \times 10^{-6} \text{ K}^{-1} \quad (T > 200^\circ \text{ C})$$

II. FINITE ELEMENT MODEL

1. ELEMENT TYPES:

- a. QUADRILATERAL ISOPARAMETRIC FOUR NODE ELEMENT (LINEAR STRAIN VARIATIONS)
- b. TRIANGULAR THREE NODE ELEMENT (CONSTANT STRAIN)

2. ANALYSIS TYPE:

PLAIN-STRAIN -1- METER THICK ELEMENTS -
ANALYSIS ACCOUNTS FOR TEMPERATURE DEPENDENT MATERIAL
PROPERTIES

3. GRAVITY AND GEOTHERMAL STRESSES

4. GRAVITY AND TEMPERATURE DUE TO STORED FUEL

DIMENSION OF FINITE
ELEMENT MODEL

DIMENSION OF FINITE
ELEMENT MODEL

NODE NUMBERING

749	748	747	746	745	744	743	742	741	740	739	738	737	736	735
734	733	732	731	730	729	728	727	726	725	724	723	722	721	720
719	718	717	716	715	714	713	712	711	710	709	708	707	706	705
704	703	702	701	700	699	698	697	696	695	694	693	692	691	690
689	688	687	686	685	684	683	682	681	680	679	678	677	676	675
674	673	672	671	670	669	668	667	666	665	664	663	662	661	660
659	658	657	656	655	654	653	652	651	650	649	648	647	646	645
644	643	642	641	640	639	638	637	636	635	634	633	632	631	630
629	628	627	626	625	624	623	622	621	620	619	618	617	616	615
614	613	612	611	610	609	608	607	606	605	604	603	602	601	600
599	598	597	596	595	594	593	592	591	590	589	588	587	586	585
584	583	582	581	580	579	578	577	576	575	574	573	572	571	570
569	568	567	566	565	564	563	562	561	560	559	558	557	556	555
554	553	552	551	550	549	548	547	546	545	544	543	542	541	540
539	538	537	536	535	534	533	532	531	530	529	528	527	526	525
524	523	522	521	520	519	518	517	516	515	514	513	512	511	510
509	508	507	506	505	504	503	502	501	500	499	498	497	496	495
494	493	492	491	490	489	488	487	486	485	484	483	482	481	480
479	478	477	476	475	474	473	472	471	470	469	468	467	466	465
464	463	462	461	460	459	458	457	456	455	454	453	452	451	450
449	448	447	446	445	444	443	442	441	440	439	438	437	436	435
434	433	432	431	430	429	428	427	426	425	424	423	422	421	420
419	418	417	416	415	414	413	412	411	410	409	408	407	406	405
404	403	402	401	400	399	398	397	396	395	394	393	392	391	390
389	388	387	386	385	384	383	382	381	380	379	378	377	376	375
374	373	372	371	370	369	368	367	366	365	364	363	362	361	360
359	358	357	356	355	354	353	352	351	350	349	348	347	346	345
344	343	342	341	340	339	338	337	336	335	334	333	332	331	330
329	328	327	326	325	324	323	322	321	320	319	318	317	316	315
314	313	312	311	310	309	308	307	306	305	304	303	302	301	300
299	298	297	296	295	294	293	292	291	290	289	288	287	286	285
284	283	282	281	280	279	278	277	276	275	274	273	272	271	270
269	268	267	266	265	264	263	262	261	260	259	258	257	256	255
254	253	252	251	250	249	248	247	246	245	244	243	242	241	240
239	238	237	236	235	234	233	232	231	230	229	228	227	226	225
224	223	222	221	220	219	218	217	216	215	214	213	212	211	210
209	208	207	206	205	204	203	202	201	200	199	198	197	196	195
194	193	192	191	190	189	188	187	186	185	184	183	182	181	180
179	178	177	176	175	174	173	172	171	170	169	168	167	166	165
164	163	162	161	160	159	158	157	156	155	154	153	152	151	150
149	148	147	146	145	144	143	142	141	140	139	138	137	136	135
134	133	132	131	130	129	128	127	126	125	124	123	122	121	120
119	118	117	116	115	114	113	112	111	110	109	108	107	106	105
104	103	102	101	100	99	98	97	96	95	94	93	92	91	90
89	88	87	86	85	84	83	82	81	80	79	78	77	76	75
74	73	72	71	70	69	68	67	66	65	64	63	62	61	60
59	58	57	56	55	54	53	52	51	50	49	48	47	46	45
44	43	42	41	40	39	38	37	36	35	34	33	32	31	30
29	28	27	26	25	24	23	22	21	20	19	18	17	16	15

NODE NUMBERING

ELEMENT NUMBERING

630	629	628	627	626	625	624	623	622	621	620	619	618	617
616	615	614	613	612	611	610	609	608	607	606	605	604	603
602	601	600	599	598	597	596	595	594	593	592	591	590	589
588	587	586	585	584	583	582	581	580	579	578	577	576	575
574	573	572	571	570	569	568	567	566	565	564	563	562	561
560	559	558	557	556	555	554	553	552	551	550	549	548	547
546	545	544	543	542	541	540	539	538	537	536	535	534	533
532	531	530	529	528	527	526	525	524	523	522	521	520	519
518	517	516	515	514	513	512	511	510	509	508	507	506	505
504	503	502	501	500	499	498	497	496	495	494	493	492	491
490	489	488	487	486	485	484	483	482	481	480	479	478	477
476	475	474	473	472	471	470	469	468
467	466	465	464	463	462	461	460	459					
458	457	456	455	454	453	452	451	450					
447	446	445	444	443	442	441	440	439					
438	437	436	435	434	433	432	431	430					
427	426	425	424	423	422	421	420	419					
416	415	414	413	412	411	410	409	408					
407	406	405	404	403	402	401	400	399					
392	391	390	389	388	387	386	385	384					
383	382	381	380	379	378	377	376	375					
374	373	372	371	370	369	368	367	366	365	364	363	362	361
360	359	358	357	356	355	354	353	352	351	350	349	348	347
346	345	344	343	342	341	340	339	338	337	336	335	334	333
332	331	330	329	328	327	326	325	324	323	322	321	320	319
318	317	316	315	314	313	312	311	310	309	308	307	306	305
304	303	302	301	300	299	298	297	296	295	294	293	292	291
290	289	288	287	286	285	284	283	282	281	280	279	278	277
276	275	274	273	272	271	270	269	268	267	266	265	264	263
262	261	260	259	258	257	256	255	254	253	252	251	250	249
248	247	246	245	244	243	242	241	240	239	238	237	236	235
234	233	232	231	230	229	228	227	226	225	224	223	222	221
220	219	218	217	216	215	214	213	212	211	210	209	208	207
206	205	204	203	202	201	200	199	198	197	196	195	194	193
192	191	190	189	188	187	186	185	184	183	182	181	180	179
178	177	176	175	174	173	172	171	170	169	168	167	166	165
164	163	162	161	160	159	158	157	156	155	154	153	152	151
150	149	148	147	146	145	144	143	142	141	140	139	138	137
136	135	134	133	132	131	130	129	128	127	126	125	124	123
122	121	120	119	118	117	116	115	114	113	112	111	110	109
108	107	106	105	104	103	102	101	100	99	98	97	96	95
94	93	92	91	90	89	88	87	86	85	84	83	82	81
80	79	78	77	76	75	74	73	72	71	70	69	68	67
66	65	64	63	62	61	60	59	58	57	56	55	54	53
52	51	50	49	48	47	46	45	44	43	42	41	40	39
38	37	36	35	34	33	32	31	30	29	28	27	26	25
24	23	22	21	20	19	18	17	16	15	14	13	12	11
10	9	8	7	6	5	4	3	2	1				

ELEMENT NUMBERING

TEMPERATURE DISTRIBUTION CONTOUR LINE OF TEMPERATURE

TEMPERATURE DISTRIBUTION
CONTOUR LINE OF TEMPERATURE

max
in
angle

STRESSES FROM
GRAVITY ALONE

$$\begin{aligned}\sigma_1 &= -2.8 \\ \sigma_2 &= -6.81 \\ \sigma_3 &= -1.6 \\ \alpha &= 12.82\end{aligned}$$

E-139

$$\begin{aligned}\sigma_1 &= .5 \\ \sigma_2 &= .5 \\ \alpha &= 12.4\end{aligned}$$

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

E-138

$$\begin{aligned}\sigma_1 &= -2.1 \\ \sigma_2 &= -1.7 \\ \sigma_3 &= -7.7 \\ \alpha &= 16.92\end{aligned}$$

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

E-118

$$\begin{aligned}\sigma_1 &= -2.7 \\ \sigma_2 &= -2.3 \\ \sigma_3 &= -10.1 \\ \alpha &= 19.86\end{aligned}$$

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

E-117

$$\begin{aligned}\sigma_1 &= -2.6 \\ \sigma_2 &= -4.7 \\ \sigma_3 &= -6.9 \\ \alpha &= 15.18\end{aligned}$$

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

E-653

$$\begin{aligned}\sigma_1 &= -2.6 \\ \sigma_2 &= -4.95 \\ \sigma_3 &= -6.7 \\ \alpha &= 39.5\end{aligned}$$

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

E-652

$$\sigma_3 = -2.2$$

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

E-632

$$\sigma_3 = -2.4$$

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

$$\sigma_3 = -2.5$$

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

E-631

S_{11} , S_{22} not to scale

TRESSES FROM
TEMPERATURE ALONE

S_{11} , S_{22} not to scale
 stresses with no arrows
 are negative = compression

DISPLACEMENT FROM
TEMPERATURE ALONE

DISPLACEMENT FROM TEMPERATURE ALONE

PRINCIPLE STRESSES FOR TEMPERATURE & GRAVITY

$S_{12} \text{ max} = 29.3$

$S_{12} \text{ max} = 20.0$

E-139

E-138

167

166

165

164

163

$S_{12} \text{ max} = 31.5$

$S_{12} \text{ max} = 39.9$

$S_{12} \text{ max} = 46.4$

E-119

E-118

E-117

145

144

143

142

140

$S_{12} \text{ max} = 15.6$

$S_{12} \text{ max} = 11.5$

$S_{12} \text{ max} = 13.5$

$S_{12} \text{ max} = 19.8$

$S_{12} \text{ max} = 66$

E-653

E-652

125

124

123

122

121

E-632

E-631

$S_{12} \text{ max} = 2.5$

$S_{12} \text{ max} = 10.6$

$S_{12} \text{ max} = 10.6$

E-635

DISPLACEMENT FROM GRAVITY & TEMPERATURE

DISPLACEMENT FROM
GRAVITY & TEMPERATURE

STRESSES FROM GRAVITY
AWAY FROM THE
CANISTER HOLE

Mesh in X-Section Away From the Canisters²²

Simulation of zone, far from
the canister holes.

Nodes surrounding hole are fixed in the
horizontal (radial) direction just
like the nodes below the hole

STRESSES FROM TEMPERATURE AT
A CROSS SECTION AWAY
FROM THE CANISTER HOLE

Simulating a trench under
the causterst :

Nodes below the causter are
allowed to move radially
and vertically

STRESSES FROM TEMPERATURE
SIMULATING A TRENCH UNDER
THE CANISTER

u = 1.5 m

(- 1 m long trench under the
Carriker²)

Node 142 free to move radially
& horizontally) and vertically.

New mesh

WITH 1 m LONG STAND UNDER
THE CANISTER
STRESSES FROM TEMPERATURE

"2 meters long trench
under the canister"

Nodes 140, $\frac{1}{2}$, 121 are
free to move radially & vertically
(New mesh)

STRESSES FROM TEMPERATURE
WITH 2 m LONG STAND UNDER
THE CANISTER

$\sigma_{33} = -55.4$
 $\sigma_{11} = -34.2$
 $\sigma_{22} = -96.9$
 $\alpha = 64.25$

STRESSES FROM GRAVITY

E-139

E-133

E-118

E-117

E-647

E-646

E-645

E-653

E-652

E-631

E-635

Stresses are still high
~~exceed~~
~~beyond~~ failure even with
1 m & 2 m ~~from~~ trenches.

Rock mass unconfined
properties are used -

Dr Wyman suggested filling the
trenches with sand.

PRINCIPLE STRESSES FOR
TEMPERATURE & GRAVITY

S_{11} , S_{22} not to scale

STRESSES FROM GEOTHERMAL TEMPERATURE ALONE											
3.52 + .61 S12-28	3.75 + .42 S12-1	4.04 + .2 S12.19	4.18 + .04 E-714 S12+.34								
3.21 + .48 S12-0.4	3.25 + .39 S12-18	3.28 + .33 S12.51	3.44 + .49 S12	2.54 + .40 S12.01							
2.9 + .34 S12.21	2.8 + .30 S12.26	2.63 + .30 S12.48	2.18 + .34 S12+.79	1.76 + .50 S12+.01							
+	2.48 + .18 S12.31	2.23 + .17 S12.44	1.92 + .23 S12.55	1.37 + .3 S12.62	1.4 + .48 S12+.86	.46 + .21 S12.17					
+	+	2.05 + .1 S12.42	1.74 + .1 S12.48	1.43 + .14 S12.47	1.02 + .16 S12.49	.52 + .14 S12.35	.22 + .03 S12+.13	.07 + .04 S12-.01	.04 + .16 S12-.09	.03 + .11 S12-.06	.01 + .02 S12+.01
E-317 +	+	+	+	+	+	+	+	.24 + .07 S12+.2	.08 + .02 S12-.01	.01 + .01 S12-.05	E-306 .06 + .01 S12-.04
+	+	+	+	+	+	+	+	.47 + .08 S12.17	.26 + .07 S12.07	.07 + .04 S12.01	.13 + .01 S12-.01
E-275 +	+	+	+	1.56 + .11 S12.47	+	+	+	+	.41 + .03 S12.12	.16 + .02 S12.06	.10 + 0 S12.02
2.24 + .34 S12+.64	+	+	+	+	1.48 + .12 S12.47	+	+	+	.55 + .02 S12.15	.27 + 0 S12.08	.02 + 0 S12.02
E-233 +	+	+	1.92 + .21 S12.27	+	+	1.44 + .13 S12.47	+	+	.7 + .02 S12.18	.41 + .01 S12.1	.1 + 0 S12.03

DISPLACEMENT FROM GEOTHERMAL
TEMPERATURE ALONE

DISPLACEMENT FROM GEOTHERMAL TEMPERATURE ALONE

STRESSES FROM GRAVITY & GEOTHERMAL TEMPERATURE

III. DESIGN METHOD

FOR DESIGN CYCLE CONSIDERATIONS

1. LOGIC NET

ACTIVITIES NEEDED TO ARRIVE TO A WORKABLE TUNNEL DESIGN

2. PREPARATION OF PERT CHART

(PROJECT MANAGEMENT METHOD)

III

PERT CHART

PROJECT MANAGEMENT METHOD

NOTE:

DESIGN I; SPACING BETWEEN TUNNELS AND BETWEEN CANISTERS
FROM HEAT TRANSFER STUDIES

DESIGN II; INCLUDE VENTILATION IN THE DESIGN TEMPERATURES
WHICH AFFECT THE DESIGN OF TUNNELS IF NO SOLUTION
HAS SATISFIED STABILITY CONDITIONS

DESIGN III; TO FIND MINIMUM SPACING BETWEEN TUNNELS WHILE
SATISFYING STABILITY CONDITIONS IN BOTH CASES
WITH OR WITHOUT INCLUDING VENTILATION

DESIGN IV; FINAL DESIGN

CASE I GRAVITY & GEOTHERMAL TEMPERATURE

CASE II GRAVITY & TEMPERATURE AFTER LOADING CANISTERS

SOLUTIONS: STRUCTURAL MODIFICATIONS WITHOUT CHANGING THE
DESIGN TEMPERATURE

CASE II-A MODIFICATION OF CASE II IF IT FAILS
=> SOLUTION -1-

CASE II-B MODIFICATION OF CASE II-A IF IT FAILS
=> SOLUTION -2-

CASE II-C MODIFICATION OF CASE II-B IF IT FAILS
=> SOLUTION -3-
IF CASE II-C FAILS, THERE IS A NEED FOR A
CHANGE IN THE TEMPERATURE DISTRIBUTION

IV. RECOMMENDATIONS

1. CANISTER HOLE

a. INCREASE DIAMETER OF CANISTER HOLE

(LARGER AIR GAP)

b. INCREASE DEPTH OF CANISTER HOLE TO TRANSFER AREA OF
CRITICAL STRESS CONCENTRATION INTO A LOWER TEMPERATURE
ZONE BY PROVIDING A FILLER OF COMPOSITE MATERIAL TO
SUPPORT THE CANISTER

c. CONSTRUCT A 3-D MODEL OF CANISTER HOLE

2. TUNNEL AND CANISTER SPACING

PARAMETRIC STUDIES TO ESTABLISH OPTIMAL SPACING OF TUNNELS
AND CANISTERS

V. LIST OF REFERENCES

1. BATHE, Klaus-Jürgen; Wilson, Edward L. and Peterson, Fred E., (SAP IV, a structural analysis program for static and dynamic responses of linear systems); College of Engineering, University of California - Berkley, California, 1974.
2. COOK, Robert D.; (concepts and applications of finite element analysis, Third edition); John Wiley & Sons, 1988.
3. COSTIN, Lawrence S. and Bauer, Stephen; (Thermal & Mechanical codes, Part I: Thermal Analysis); Sandia National Laboratories, Sandia Report SAND 88 - 1221. UC-814; June 1990.
4. HARRISON - GIESLER, Diane J.; (Engineered Barrier System Workshop); Department of Energy; March 1, 1991.
5. O'NEAL, W.C., Gregg, D.W., Hockman, J.N.; Russell, E.W. and Stein, W.; (Preclosure Analysis of Conceptual Waste Package Designs for a Nuclear Waste Repository in Tuff); Lawrence Livermore National Laboratory; November 1, 1984.
6. Organization of the Waste Package plan; Department of Energy, DOE order 4700.1.
7. Civilian Radioactive Waste Management; December 1988.
8. SZABO, B.J. and Kyser, T.K.; (Ages and stable-isotope compositions of secondary calcite and opal in drill cores from Tertiary Volcanic rocks); Geological Society of American Bulletin; December 1990.

END

**DATE
FILMED**

7 / 13 / 92