**FUNDAMENTAL STUDIES IN PRODUCTION OF C_2-C_4
HYDROCARBONS FROM COAL**

FINAL REPORT

Contract Period 1 September, 1988 - 31 August, 1992

**Wendell H. Wiser, Principal Investigator
Alex G. Oblad, Co-Principal Investigator**

**Department of Chemical and Fuels Engineering
University of Utah
Salt Lake City, Utah 84112**

**Prepared for the United States Department of Energy
under Grant No. DE-FG22-88PC88940**

March, 1993

TABLE OF CONTENTS

	Page
ABSTRACT	iv
Chapter	
1. INTRODUCTION	1
2. BACKGROUND FOR THE RESEARCH	2
2.1 General	2
2.2 Earlier Results from Our Laboratory	2
2.3 Reaction Pathway	5
2.3.1 Thermal Cracking	5
2.3.2 Catalytic Cracking	5
2.3.3 Catalytic Hydrogenation	7
2.3.4 Hydrocracking	9
Hydrocracking of Paraffins	10
Hydrocracking of Alkyl Aromatics	10
Hydrocracking of Polycyclic Aromatics	12
3. EXPERIMENTAL	17
3.1 Apparatus	17
3.1.1 Experimental: Kinetic Studies	17
3.1.2 Unit for Carbonium Ion, Recycle Liquid	20
3.1.3 Unit for Catalyst Sulfiding	20
3.2 Feed Stock	20
3.2.1 Coal	20
3.2.2 Hydrogen-Donor Solvent	20
3.2.3 Catalyst	23
3.3 Experimental Procedure	23
3.3.1 Sulfide the Cataly.	23

	11
3.3.2 Study of Kinetics	23
3.3.3 Study of Reaction Pathway	28
3.3.4 Recycle Liquids as Donor Solvent	29
3.4 Analysis of Products	30
3.4.1 Elemental Analysis	30
3.4.2 Gas Chromatographic Analysis	30
3.4.3 GC-MS Analysis	30
3.4.4 Proton NMR Analysis	33
4. RESULTS AND DISCUSSION	34
4.1 Kinetics: Direct, Single-stage Gasification . . .	34
4.1.1 Experimental Results	34
4.1.2 Isothermal Approximation	45
4.1.3 Non-isothermal Mode	51
4.1.4 Discussion	77
Temperature Profile	77
Fast Coal Conversion	84
Reaction Kinetics	85
Possible Solvent Reaction	88
4.2 Reaction Pathway	92
4.2.1 Coal to Liquids	92
4.2.2 Liquids to Gases	94
4.3 Recycle Liquid as Hydrogen-donor Solvent	111
4.3.1 Experimental Results	113
4.3.2 Discussion	118
4.4 Equilibrium Concentrations of C -C	127
4.4.1 The Approach	127
4.4.2 The Method	128

	Selection of Compounds	128
	Calculation Procedures	129
	4.4.3 Results and Discussion	130
5.	CONCLUSIONS	137
	REFERENCES	139
	APPENDIX A: ORIGINAL KINETIC DATA.	143

ABSTRACT

In previous work in our laboratory, coal has been converted to a product containing C_2-C_4 hydrocarbon gases representing more than 50% by weight of the dry, mineral-matter-free coal, in a single stage, direct process. Using a stirred, batch autoclave reactor with feed injector, the kinetics of the conversion process have been examined. The observation is made that the coal is converted mostly to liquids in the first few minutes of reaction, with only a small amount of hydrocarbon gases. The liquids are then catalytically converted to hydrocarbon gases. A dual functional catalyst was used in the experiments, providing both a hydrogenation/hydrogenolysis function and a cracking function. The kinetics were first evaluated by an isothermal approximation technique, then by means of a computer-assisted non-isothermal technique. Conversion of the coal to liquids was observed to occur very fast. The slow, rate-determining step in the overall process was conversion of liquids to hydrocarbon gases, and was found to be first order with respect to the liquids. An activation energy of 23 kcal/mole was obtained by the isothermal technique, and 27 kcal/mole by the non-isothermal technique. The reactions leading directly to C_2-C_4 hydrocarbons were found to follow a carbonium ion mechanism. With the aid of a computer program, it was observed that the reactions are concluded long before equilibrium is achieved, and the production of C_2-C_4 hydrocarbons as the principal product is kinetically controlled.

CHAPTER 1

INTRODUCTION

U.S. research and development efforts related to fossil energy have been mainly concerned with developing substitutes for petroleum and natural gas. This direction of the nation's energy program resulted from the general belief that the world was running out of oil and substitutes would soon be required. After having been convinced of the truth of this belief for two decades or more, it finally became apparent that the oil supply of the world will last longer than predicted, and the urgency in producing synthetic fuels for reasons of impending world shortages no longer appeared justified. The program of federal financial support in synthetic fuels was dramatically reduced.

Notwithstanding the reduced urgency for synthetic fuels as substitutes for petroleum and natural gas, there has continued justification for some effort in synthetic fuels. There exists a need for three main lines of research with respect to obtaining synthetic fuels from coal: (1) continue the fundamental research on the structure of coal, coal liquefaction and gasification; (2) continue innovative research which would decrease the complexity of the technology and reduce the cost of producing synthetic fuels from coal; and (3) institute research leading to the development of new products from coal. The work pursued in this project has been concerned with Item 3.

CHAPTER 2

BACKGROUND FOR THE RESEARCH

2.1 General

For more than a decade, members of the Department of Fuels Engineering at the University of Utah have conducted research, and critically evaluated the literature, related to the chemical structure of coal. A concept was formulated of the probable representative structures in coal and the manner in which these structural units are joined in the coal. This concept was reduced to a drawing by Professor W. H. Wiser, and is presented in Figure 2.1. Armed with that concept, and drawing upon our extensive background relating to hydrocarbons in general and petroleum in particular, research work was initiated in an earlier project directed toward the catalytic hydrogenation and hydrocracking of coal at temperatures below 550 °C. We were aware that nearly all of the research effort for the production of hydrocarbons from coal had been directed either toward methane initiated at rather high temperatures (usually above 950 °C in the initial step), or liquids at low temperatures (usually 450 °C or lower). We wanted to explore the possibilities for taking apart the coal structure, as we visualized it to be (Figure 2.1), utilizing mid-range temperatures and appropriate selected catalysts to provide the desired selectivity and reaction rates.

2.2 Earlier Results Obtained in Our laboratory

We discovered while utilizing certain dual-functional catalysts, exhibiting both hydrogenation/hydrogenolysis activity and acid cracking activity, with reaction temperature of about

Figure 2.1 Schematic Representation of Structural Groups and Connecting Bridges in Bituminous Coal by Wiser.

500 °C, that the principal hydrocarbon product was neither methane, common to the higher temperature work, nor liquids, characteristic of the lower temperature work, but C₂, C₃, and C₄ hydrocarbons, representing more than 50 percent by weight of the coal. These experiments were conducted, and these results obtained, in a direct, single-stage process, at 2000 psia pressure, in an atmosphere of steam and hydrogen .

We performed experiments with a Utah high-volatile bituminous coal, a Wyoming sub-bituminous coal, and a Texas lignite. Representative experimental results are presented in Table 2.1.

Table 2.1

Products, Wt. % dry, mineral-matter-free coal

<u>Coal</u>	<u>C₁</u>	<u>C₂</u>	<u>C₃</u>	<u>C₄</u>	<u>Liquids</u>	<u>Char</u>
Utah HVB Bit.	11	9	36	4	23	17
Wyoming Sub-Bit.	8	29	31	2	16	14
Texas Lignite	8	32	35	2	9	14

The above research results revealed that there exists an envelope of reaction parameters, heretofore unexplored until our previous research, leading to a product of high market demand for many uses. The chief reaction parameters are a dual-functional catalyst of specific selectivities, a temperature spanning a range of only about 60 centigrade degrees, and reaction time. Pressure is typical of pressures required for coal conversion generally. All of these parameters must lie within the boundaries established by the parameter envelope in order to obtain the high yields of C₂-C₄ hydrocarbons.

2.3 Reaction Pathway

Single stage coal gasification to low molecular weight hydrocarbon gases potentially may involve various reactions including thermal cracking, catalytic cracking, hydrogenation and hydrocracking.

2.3.1 Thermal Cracking

When paraffinic hydrocarbons are brought to high temperatures in the absence of a catalyst, they undergo thermal cracking via a free-radical mechanism. The initiation step of such a process is the homolysis of a carbon-carbon bond, leading to the formation of free radicals. The radicals can undergo β -scission, chain transfer, or chain termination. Such a process typically leads to high yields of ethylene, low yields of methane, and low yields of higher olefins. The experimental product distribution resulting from the thermal cracking of n-hexadecane is plotted in Figure 2.2^{1,2}. This product distribution is in agreement with prediction by the Rice theory for a free-radical mechanism in thermal cracking of paraffins.

2.3.2 Catalytic Cracking

Cracking of hydrocarbons catalyzed by acidic surfaces proceeds via a carbonium ion mechanism. A carbonium ion can be formed by hydride abstraction from a saturated portion of the hydrocarbon, or in the case of an olefin or aromatic molecule, by proton addition from the acid catalyst to the unsaturated portion of the molecule. In the case of an aromatic molecule, a portion of the molecule must be hydrogenated before cracking will occur,

Figure 2.2 Products from Thermal Cracking of *n*-Hexadecane at 500°C

and cracking will occur only in the saturated portion of the molecule. Once a carbonium ion is formed, cracking may occur at a β -position relative to the location of the carbonium ion. Competing reactions may include H-transfer, β -C atom scission, rearrangement of the carbonium ion, and secondary reactions. The product distribution is characterized by high yield of C_3 - and C_4 hydrocarbons, moderate amounts of C_5 and C_6 hydrocarbons, less C_1 - and C_2 hydrocarbons, and small amounts of olefins and highly isomerized products. Coke is formed also to maintain the hydrogen balance in the cracking process. A comparison of the experimental product distribution from catalytic cracking of n-hexadecane over an alumina-zirconia-silica catalyst, with prediction of the carbonium ion theory¹, is presented in Figure 2.3. The agreement is good for hydrocarbons containing between 3 and 14 carbon atoms.

2.3.3 Catalytic Hydrogenation

In the coals ranging from lignite to high-volatile bituminous, demonstrated by our earlier work to be very useful for direct conversion to C_2 - C_4 hydrocarbons (Table 2.1), from about 50% to 75% of the carbon in the coal is aromatic carbon. The majority of the ring structures contain two or three rings per cluster, but with a substantial number of single-ring structures, especially in the lower rank coals. Hydrogenation and hydrogenolysis reactions therefore become very important in the conversion of these condensed units to HC gases containing two, three or four carbon atoms per molecule.

Figure 2.3 Catalytic Cracking of n-Hexadecane. The solid line represents experimental products at 24% conversion in the presence of silica-zirconia-alumina at 500°C and dashed line represents the calculated product distribution according to the carbonium ion roles.

Catalysts selected for the hydrogenation of hydrocarbons generally are transition elements including Fe, Co, Ni, Ru, Rh, Pd, Os, Ir, Pt. Other transition elements (or their oxides or sulfides) e.g. Cr, Mo, W, Cu, Zn. are also useful. Of these, nickel, platinum, palladium, rhodium, ruthenium, and iridium have been used most frequently.

Molybdenum and tungsten oxides and sulfides at elevated temperatures and pressures have been found to be of particular value for the hydrogenation of condensed polycyclic aromatic hydrocarbons. These elements have a partially filled d-orbital. The catalytic activity of these elements has been partially attributed to the presence of vacancies in their electron d-band which imparts an ionic-type bonding with electron transfer and conductivity. Another helpful factor in accounting for the effectiveness of these metals in catalytic reactions is the ability of the metals or their oxides to both adsorb reactants and desorb products in the appropriate energy ranges.

2.3.4 Hydrocracking

Hydrocracking is widely used for converting relatively high-boiling hydrocarbons to low-boiling products with an overall consumption of hydrogen. It is thus a combination of catalytic cracking and hydrogenation or hydrogenolysis. The hydrocracking catalysts are dual functional catalysts exhibiting both hydrogenation/hydrogenolysis and cracking activities. The hydrocracking of hydrocarbons has been thoroughly studied. Mechanisms and product distributions are reported in the literature.

Hydrocracking of Paraffins The mechanism for the hydrocracking of paraffins with a strongly acidic catalyst such as silica-alumina and a mild hydrogenation component such as nickel, tungsten, or cobalt sulfide is generally believed to be similar to that for catalytic cracking with features of hydrogenation and hydroisomerization superimposed. The following reaction steps are proposed for the hydrocracking of a normal paraffin reactant³⁻⁶.

(1) A normal olefin is formed by dehydrogenation of the normal paraffin reactant.

(2) The normal olefin is adsorbed on the acidic sites of the catalyst to form an ionic specie. (Ionic intermediates can also be formed by hydride ion exchange as observed in catalytic cracking.)

(3) The carbonium ion thus formed can isomerize to a more stable specie (a tertiary carbonium ion), crack to form a smaller ion and an olefin, or desorb as a normal olefin.

(4) The tertiary carbonium ion formed in the previous step can undergo further isomerization, crack, or desorb.

(5) Olefinic products are saturated by hydrogenation or hydrogen transfer reactions.

The product distribution of hydrocracking of n-hexadecane is plotted in Figure 2.4³.

Hydrocracking of Alkyl Aromatics The reactions occurring during the hydrocracking of alkyl aromatics are isomerization, dealkylation, alkyl transfer, pairing, and cyclization. Products vary with the specific structure of the reactants. Hydrocracking

Figure 2.4 Products from Hydrocracking of n-Hexadecane

of n-butylbenzene and n-decylbenzene were studied by Sullivan et.al. using nickel sulfide on silica-alumina⁷. Products from hydrocracking of alkybenzenes with short side chains, such as n-butylbenzene, are relatively simple. Benzene and butane are produced. With large alkyl side chains, such as n-decylbenzene, the reaction product becomes more complex. An important new reaction, cyclization, is observed. Simple dealkylation to benzene and decane is still the most important reaction, but many other reactions also occur. The paraffins with carbon numbers from 3 to 10 are produced as well as alkylbenzenes from 7 to 12 carbon number. Thus, in paraffin formation the bond between the aromatic ring and the α -carbon of the side chain is the most likely to be cleaved, but there is substantial cleavage of the other bonds in the side chain. Considerable amounts of polycyclic hydrocarbons with carbon numbers from 9 to 12, particularly tetralins and indanes, are formed by the cyclization reaction.

Hydrocracking of Polycyclic Aromatic Hydrocarbons The reactions of polycyclic aromatics over hydrocracking catalysts are complex. In hydrocracking of tetralin, ring opening is extensive yielding benzene and alkylbenzenes. Dehydrogenation also occurs producing substantial quantities of naphthalene. The tendency to produce naphthalene by dehydrogenation of tetralin is increased by both raising the temperature and lowering the pressure. Isoparaffins, such as butanes, pentanes, and hexanes are found in the products.

Hydrocracking of anthracene and of phenanthrene were studied by Sullivan et al⁷ using nickel sulfide on silica-alumina as catalyst. The product distribution for the hydrocracking of anthracene is given in Figure 2.5. Tetralin is the predominant cyclic product from cracking. The product distribution from phenanthrene hydrocracking by Sullivan et. al. is shown in Figure 2.6. The rate of phenanthrene hydrocracking is faster than that of anthracene.

The objectives of this research work are:

1. to determine the kinetic parameters, specifically the reaction order, the activation energy and the pre-exponential factor, for the formation of HC gases in a single-stage coal gasification operation, when low molecular weight hydrocarbon gases represent the principal product. The study of the kinetics is necessary for reactor design and scale-up in order to develop commercially-viable processes for deriving C_2-C_4 hydrocarbon gases from coal in a direct operation.

2. to gain some understanding of the reaction pathway in the direct formation of hydrocarbon gases from coal. The studies of the reaction pathway permit some conclusions as to the nature of conversion of condensed aromatic configurations, which constitute the dominant structures in coal, into C_2-C_4 hydrocarbon gases. More specifically, the validity of the carbonium ion mechanism relative to this conversion process required examination.

3. to evaluate the hydrogen-donor capability of the coal-derived liquids, to determine their effectiveness as solvent for the coal-solvent feed slurry.

Figure 2.5 Products from Hydrocracking of Anthracene

Figure 2.6 Products from Hydrocracking of Phenanthrene

4. to develop a computer program which would permit calculation of the equilibrium concentrations of C_2 , C_3 , and C_4 hydrocarbons in a system which produces data such as those presented in Table 2.1

CHAPTER 3

EXPERIMENTAL

3.1 Apparatus3.1.1 Experimental system for the Kinetic Studies

This system is a batch system. The equipment is shown in Figure 3.1. The central component of the system was a 300 cc stainless steel autoclave supplied by Autoclave Engineers, rated for 5400 psi at 650 °F (343 °C). The autoclave was equipped with a variable speed magnetic drive stirrer, a pressure gauge, a safety valve and a heating assembly. The heating assembly includes an electric resistance jacket furnace, a double-point temperature controller, and a recorder which displayed the temperature profile during the experiments. The reaction pressure was controlled by a metering valve and back pressure check valve.

A 150 cc high pressure feed injector, shown in Figure 3.2, was connected to the reactor. When the reactor reached the designated temperature, the coal-solvent slurry was fed to the reactor by means of the feed injector. By this means, no reaction occurred before reaching the designated temperature, and zero time for the kinetic evaluations was accurately defined. A condenser was located on the product gas outlet line, which removed the light liquid carried by the gases. The product outlet line also contained a sampling port, which collected the gas sample, and a wet test flow meter, which measured the total volume of gases in the reactor. A cooling system which is not shown was used to quench the reactor by cold water.

1. Gas Inlet	8. Double-Point Temperature Controller
2. Feed Injector	9. Heating Furnace
3. Pressure Gauge	10. Condensor
4. Magnetic Drive Assembly	11. Back Pressure Check Valve
5. Motor	12. Gas Sampling Port
6. Thermowell	13. Wet Test Flowmeter
7. Temperature Recorder	

Figure 3.1. Kinetic Study Unit

Figure 3.2. Feed Injector

3.1.2 Unit for Carbonium Ion and Recycle Liquid Studies

The unit for the study of the reaction pathway was the same as the kinetic study unit shown in Figure 3.1, except no feed injector and no condenser were needed for these studies. The studies of the hydrogen-donor capability of the recycle liquids were carried out in the same manner, in the same reactor, as the kinetic studies.

3.1.3 Catalyst Sulfiding Unit

The equipment for sulfiding the catalyst is shown in Figure 3.3. A 1.5 ft x 1 in quartz tube reactor was heated by a furnace supplied with a thermocouple and temperature controller. A stream of nitrogen, or 10% hydrogen sulfide in hydrogen, entered the reactor through the flowmeters. The exhaust gases from the reactor were passed through a scrubber filled with CdCl_2 solution and then vented to the vacuum hood.

3.2 Feed Stock

3.2.1 Coal

Wyodak subbituminous coal was used for all experiments in this study. The coal was crushed and sieved to -200 mesh Tyler Screen Series, then transferred to containers and sealed under nitrogen. Before the experiment coal was dried in a vacuum oven at 50 °C, over night. The proximate and ultimate analyses were determined and are shown in Table 3.1.

3.2.2 Hydrogen-Donor Solvent

The hydrogen donor solvent used in the experiments was 1,2,3,4-tetrahydronaphthalene (tetralin), 99%, provided by Aldrich Chemical Company, Inc.

Figure 3.3 The Equipment for Sulfiding the Catalyst

Table 3.1 Proximate and Ultimate Analysis of Wyodak Coal

<u>Proximate Analysis (wt %)</u>	
Moisture	29.34
Ash (dry basis)	10.22
Volatile Matter (dry basis)	55.73
Fixed Carbon (dry basis)	33.99
<u>Ultimate Analysis (wt %, dmmf Basis)</u>	
Carbon	72.96
Hydrogen	5.69
Nitrogen	1.02
Sulfur	0.97
Oxygen (by difference)	19.36
H/C (Atomic Ratio)	0.936

3.2.3 Catalyst

The catalyst used for all experiments was a mixture of sulfided nickel-molybdenum on alumina and 25% silica-75% alumina, with a ratio of 4:1. The physical properties of the nickel-molybdenum oxide form on alumina, provided by Engelhard Corporation, are given in Table 3.2. The properties of the silica-alumina catalyst, supplied by Gulf Research and Development Co., are shown in Table 3.3. The catalyst was ground and sieved to -20+40 mesh Tyler Screen Series. The two catalysts were first mixed, then sulfided in the catalyst sulfiding unit. The catalyst was then placed in a container, ready for use.

3.3 Experimental Procedure

3.3.1 Sulfiding of the Catalyst The procedure for sulfiding the catalyst involved the following steps:

1. About 50 gm of catalyst were placed in the reactor shown in Figure 3.3. The system was sealed with stop cock grease.
2. The reactor was purged with nitrogen to remove traces of oxygen, then heated to 400 °C under nitrogen flow.
3. The gas flow was changed to a 10% hydrogen sulfide in hydrogen. The reactor was maintained at 400 °C for two hours.
4. The reactor was cooled to room temperature, then purged with nitrogen to remove any excess hydrogen sulfide.
5. The sulfided catalyst was stored in a container.

3.3.2 Study of Kinetics

The reactor is shown in Figure 3.1. The experimental procedure involved the following steps:

Table 3.2 Properties of Ni-Mo Catalyst

Properties	Catalyst
Batch ID#	HPC-50
Size	1/2 "
Shape	extrudate
NiO (wt %)	4.75
MoO ₃ (wt %)	19.75
P ₂ O ₃ (wt %)	4.75
Average Micropore Radius (Å)	48.8

Table 3.3 Properties of 25% SiO₂-75% Al₂O₃ Catalyst

Properties	Value
Surface Area (m ² /gm)	416
Pore Volume (ml/gm)	0.65
Pore Radius (Å)	35.7

1. The autoclave reactor was cleaned with acetone.
2. The sulfided catalyst, about 6.25 gm, was placed in the autoclave reactor.
3. The autoclave was closed. The head bolts were greased with anti-seize and lubricating compound and uniformly torqued to 20 ft-lb.
4. The reactor was tested for leaking by filling with nitrogen to 2000 psi and holding over night. The allowable pressure drop must not be greater than 15 psi pressure drop in order for the experiment to proceed.
5. After the successful leaking test, the nitrogen was released from the reactor and hydrogen was admitted to 800 psi.
6. The reactor was heated to the reaction temperature. At this time reactor pressure was about 1100 psi.
7. Five gm of coal were mixed with 15 gm of tetralin in a small beaker. A 50 cc syringe was used to transfer the slurry feed into the feed injector. The feed injector was closed and pressurized to 1600 psi.
8. The ball valve was opened which connected the feed injector and reactor. The slurry feed was injected into the reactor and the ball valve was closed. The magnetic stirrer was started and set at about 1000 rpm. The injection was completed within seconds. The reactor was then pressurized to 1800 psi.
9. Zero reaction time was taken as the time of injection.
10. The reaction was continued for times ranging from 4 to 60 minutes as required to complete the time-reaction curves at each temperature for the kinetic studies.

11. At the termination of the experiment, the furnace was turned off and removed. Cold water in a plastic tank was raised around the reactor, thereby cooling the reactor and its contents to a temperature below 250 °C within one minute. By this means the total time of reaction could be accurately determined.

12. When the reactor reached room temperature the pressure was released by the back pressure check valve. Three gas samples were taken at different reactor pressures. In this way an average gas sample was obtained. The total volume of gases in the reactor was measured by the wet test flow meter. The gas weight was calculated from the total volume and the composition analyzed by the gas chromatograph.

13. After releasing the gases in the reactor, the autoclave was opened. The liquid product, solid residue and catalyst were recovered as completely as possible by scraping the inside of the autoclave with a spoon. Removing the product by scraping as much as possible, rather than washing it with solvent, was essential for a good material balance. When a solvent was used for product recovery, separating the solvent from the liquid products by vacuum evaporator led to loss of some light compounds. The balance of the product was recovered by wiping the reactor with tissue paper. The paper was weighed before and after wiping.

14. The liquid/solid separation was accomplished by solvent extraction using tetrahydrofuran (THF) solvent. The liquid and THF solvent separation was carried out in an evaporator under vacuum.

3.3.3 Study of Reaction Pathway

The experimental procedures are as follows:

1. About 3.15 gm of catalyst and about 7.5 gm of model compound were weighed separately, then transferred into the autoclave reactor.
2. The autoclave reactor was closed and torqued uniformly to 20 ft-lb torque.
3. The reactor was pressurized to 1100 psi at room temperature.
4. The reactor was heated to reaction temperature, requiring a time of about 35 mins for the reactor to reach the predetermined temperature. The reactor was maintained at the reaction temperature for 30 mins.
5. After the reaction was completed, the furnace was removed and a tank of cold water was raised around the outside of the reactor to quench the reaction.
6. When the reactor reached room temperature, the pressure of the reactor was released, which was about 1000 psi. During releasing the reactor pressure, three gas samples were taken at three different reactor pressures. An average gas composition was obtained from the three samples.
7. The reactor was opened and the liquid products and catalyst were recovered.
8. Utilizing filtration, THF solvent extraction and vacuum evaporation, the product was separated into the fractions liquid, solid and solvent.
9. The liquid was stored in a refrigerator for analysis.

3.3.4. Evaluation of Recycle Liquids as a Hydrogen-Donor Solvent

The experimental procedure involved the following steps:

1. The catalyst, coal and solvent were weighed separately, then mixed in a ratio of 1.25:1:3. For the first four runs, catalyst, coal and solvent were 5, 4 and 12 gm, respectively. For the fifth and sixth runs, catalyst, coal, and solvent were 3.75, 3 and 9 gm, respectively. For the seventh or last run, catalyst, coal and solvent were 2.5, 2 and 6 gm, respectively. Reducing the amount of feed was required because of the limited quantity of recycle liquid recovered from the previous run.
2. Catalyst, coal and solvent were placed into the reactor.
3. The reactor was closed and torqued uniformly to 20 ft-lb torque.
4. The reactor was heated to 500 °C and maintained at that temperature for 30 mins.
5. The reactor was cooled by raising a tank of cold water around the reactor.
6. When the temperature dropped to room temperature, three gas samples were taken at three different reactor pressures, from which an average gas composition was calculated.
7. The liquid, coal and catalyst were recovered with the use of THF solvent. In this way the liquid was recovered to the largest extent possible because the liquid would be recycled as a part, or all, of the solvent for the next run.
8. Solid and liquid separation was accomplished by extraction. Liquid and solvent separation was performed in a vacuum evaporator.

9. The liquid recovered was stored in the refrigerator for the next run and also for later analysis.

3.4 Analysis of Products

3.4.1 Elemental Analysis

The elemental compositions of coal, and of liquids from recycled runs, were determined in the Fuels Engineering Coal Characterization Laboratory. Carbon, hydrogen, and nitrogen were analyzed by a LECO CHN-600 Carbon, Hydrogen, Nitrogen Analyzer. A LECO SC-132 Total Sulfur Analyzer was used to determine the sulfur content. The oxygen was estimated by difference.

3.4.2 Gas Chromatographic Analysis

The hydrocarbon gas compositions were analyzed by a HP 5890 Series II Gas Chromatograph. The column used was 80/100 Chromosorb 102, 6' x 1/8" supplied by Supelco. The detector was a Flame Ionization Detector (FID). Standard gases utilized for calibration were provided by the Scott Co. The other parameters of operation of the gas chromatograph used in analyzing the gases are listed in Table 3.4. A good separation was obtained between olefin and paraffin gases under those conditions. The liquids from the hydrocracking of model compounds were analyzed by a HP 5890 gas chromatograph with a capillary column. The conditions were varied with different products in order to obtain a better separation. The conditions used for the analysis of liquid components are given in Table 3.5.

3.4.3 Gas Chromatography-Mass Spectrometry Analysis

The liquid compositions from the hydrocracking of model compounds were identified by a Finnigan MAT 95 high resolution

Table 3. 4 Hydrocarbon Gas Analysis Conditions by Gas
Chromatograph

Items	Conditions
Column	Chromosorb 102
Detector	FID
Carrier Gas	Helium, 30 cc/min.
Detector Temperature (°C)	250
Injection Temperature (°C)	150
Range	5
<u>Column Condition</u>	
Initial Temperature (°C)	40
Equilibrium Time (min.)	3
Initial Time (min.)	0.5
Rate (°C/min.)	5
Final Temperature (°C)	200
Final Time (min.)	0

**Table 3. 5 Hydrocarbon Liquid Analysis Conditions by
Gas Chromatograph**

	Liquid A	Liquid B	Liquid C
GC model	HP 5890 Series II	HP 5890	HP 5890
Column	HP-1	HP-5	HP-5
Detector	FID	FID	FID
Carrier Gas	Helium	Helium	Helium
Detector Temp. (°C)	160	280	300
Injection Temp. (°C)	160	250	250
Range	7	7	7
<u>Column Condition</u>			
Initial Temp. (°C)	30	40	80
Initial Time (min.)	2.0	2.0	2.0
Rate (°C/min.)	3.0	3.0	5.0
Final Temp. (°C)	50	130	280
Final Time (min.)	0	0	5
Rate A (°C/min.)	10	10	
Final Temp. (°C)	150	250	
Final Time (min.)	5	0	

Note: Liquid A = Liquid from Hydrocracking of n-Hexadecane.

 Liquid B = Liquid from Hydrocracking of Tetralin.

 Liquid C = Liquid from Hydrocracking of Anthracene and
 Phenanthrene.

gas chromatograph/mass spectrometer (GC-MS) with Finnigan MAT ICIS II operating system in the Chemistry Department, University of Utah. A 25 m BP-5 capillary column was used. The Shrader system GC/MS Data Processing Software helped to interpret the structure of each of the compounds.

3.4.4 Proton Nuclear Magnetic Resonance Analysis

Hydrogen distribution of recycle liquids was analyzed by a UXR-500 nuclear magnetic resonance spectrometer (NMR). Benzene was used as the solvent. Tetramethylsilane was used as the standard. Various types of hydrogen, such as aliphatic hydrogen and aromatic hydrogen present in the liquid, were determined both qualitatively and quantitatively.

CHAPTER 4

RESULTS AND DISCUSSION

4.1 Kinetics of Direct Single-Stage Coal Gasification

Prior research in our laboratory has demonstrated that direct production of light hydrocarbon gases from coal is thermodynamically feasible. In view of the need to develop commercially viable processes for deriving low molecular weight hydrocarbon gases from coal, the determination of coal gasification kinetics is necessary for reactor design and scaleup. Because of the complexity of the chemical structure of coal, a precise elemental step mechanism cannot be defined. The approach in kinetic studies has been to attempt to establish a kinetic model based on the experimental results and then derive kinetic parameters for this model.

4.1.1 Experimental Results

A typical temperature profile for a direct coal gasification reaction is shown in Figure 4.1. Reaction temperature for each gasification experiment increased to a value 40-50 °C higher than the intended run temperature in about 5 minutes after the slurry was injected into the reactor, then settled back to the assigned reaction temperature in about another 10 minutes. The reaction temperature became stable thereafter.

Data in Figure 4.2 show the total conversion of coal (dmmf) with reaction time at five different reaction temperatures. Total conversion was defined by:

$$\text{Conversion} = \frac{\text{wt coal(dmmf)} - \text{wt residue(dmmf)}}{\text{wt coal(dmmf)}} \times 100\%$$

Figure 4.1 A Typical Temperature Profile

Figure 4. 2 Effect of Reaction Time on Total Coal Conversion

The conversion of coal increased dramatically at the beginning of the experiment and reached about 75% in 10 minutes after the slurry was injected into the reactor. The total conversion remained at almost a constant value of about 78% after 10 minutes until 60 minutes, at which time the experiment was terminated.

Total gas (C_1-C_4) conversion (based on dmmf coal) with reaction time is described in Figure 4.3. Gas production was high in the first 10 minutes of the reaction. After that, the gas production rate was essentially constant, as shown in Figure 4.3, in which a straight line plot for gas conversion versus reaction time appeared after 10 mins of reaction. Gas conversion is also dependent on the reaction temperature, the higher the reaction temperature the higher the conversion between 440 °C and 500 °C.

Figure 4.4 shows weight percent liquids in the product (based on dmmf coal) versus reaction time. Liquid quantities in the product increased dramatically at the beginning of the reaction, reaching a maximum yield with a value of 50% to 60%, then decreased with reaction time.

Figures 4.5-4.9 describe total conversion, gas conversion and liquid conversion as a function of reaction time at temperatures 440, 455, 470, 485 and 500 °C, respectively. Coal conversion to liquids and gases was very fast in the first 10 mins. After that, gases increased by consumption of the liquids.

From the above results, a reaction sequence for the single stage coal gasification is suggested as follows:

Figure 4.3 Effect of Reaction Time on Gas Conversion

Figure 4.4 Effect of Reaction Time on wt% Liquids in Product

Figure 4.5 Relationship among Coal, Liquid and Gas Conversion at 440°C

Figure 4.6 Relationship among Coal, Liquid and Gas Conversion at 455 °C

Figure 4.7 Relationship among Coal, Liquid and Gas Conversion at 470 °C

Figure 4.8 Relationship among Coal, Liquid and Gas Conversion at 485 °C

Figure 4.9 Relationship among Coal, Liquid and Gas Conversion at 500 °C

To obtain the kinetic parameters of the above reactions, two approaches, isothermal, and computer modeling nonisothermal, were used and will be described separately in the following sections.

4.1.2 Isothermal Approximation

The gas product was derived from two sources. One was from coal directly, and the second was from liquids, including both coal-derived liquids and tetralin solvent. Figure 4.10 describes the gas production in which G_1 represents the gases from coal directly, G_2 represents the gases from the liquids, and $G_1 + G_2$ is the total gases produced in the experiment.

Since no further coal conversion was observed after 10 minutes of the reaction, it is suggested that essentially no gas production directly from coal occurs from then on. The observed gases after 10 minutes of reaction are thought to be from liquids only. The reaction temperature remains constant after about 18 minutes until the end of the experiment. An isothermal approximation method, utilizing data from 20 to 60 minutes, is used to obtain the kinetic parameters for reaction of liquids producing G_2 , as shown in equation 4.2.

The following equations were derived to describe the kinetics of gas production directly from coal, based upon the isothermal approximation technique.

$$\frac{dG}{dt} = \frac{d(G_1 + G_2)}{dt} = \frac{dG_1}{dt} + \frac{dG_2}{dt} \quad (4.3)$$

Figure 4.10 Gases Produced from Different Sources

$$\frac{dG}{dt} = \frac{dG_2}{dt} \quad \text{since} \quad \frac{dG_1}{dt} = 0 \quad (4.4)$$

$$\frac{dG}{dt} = kL^n \quad (4.5)$$

where k is the reaction rate constant for liquids to gases.

L is the weight of liquids, (g)

t is the reaction time, (min)

For solving equation (4.5), values for dG/dt are taken from the slopes of the gas curves in Figure 4.3. It is noted from Figure 4.11 that the total amount of liquids, including both solvent and coal-derived liquid, in the system changes only slightly between 20 minutes and 60 minutes. For the purpose of evaluating the reaction velocity constant in equation (4.5), an average, constant value for L is used.

$$dG = kL^n dt \quad (4.6)$$

$$G_t - G_0 = kL^n (t - t_0) \quad (4.7)$$

choose $t_0 = 20$ min

Since the amount of coal used in each experiment was slightly different, which affects the yield of gases, normalization of the gas amount was made based on the feed of coal as follows:

$$\left(\frac{G_t}{W_t} - \frac{G_0}{W_0} \right) \times W_a = kL^n (t - t_0) \quad (4.8)$$

where G_t is the weight of gas at reaction time t , minutes

G_0 is the weight of gas at reaction time 20 minutes

W_t is the weight of coal feed at reaction time t minutes

W_0 is weight of coal feed at reaction time 20 minutes

Figure 4.11 Amount of Liquid versus Reaction Time at 500°C

W_a is the average of coal feed from 20 to 60 minutes

L is the average of liquid from 20 to 60 minutes

By plotting the left side of equation (4.8) versus reaction time difference of $t - t_0$ (Figure 4.12), a linear relationship was obtained. The values of kL^n at various temperatures can be obtained from the slopes of those straight lines.

Reaction order was determined by changing the amount of liquids, which is indicated by equations 4.9 and 4.10.

$$\frac{\left(\frac{G_{12}}{W_{12}} - \frac{G_{11}}{W_{11}}\right) \times W_{1a}}{\left(\frac{G_{22}}{W_{22}} - \frac{G_{21}}{W_{21}}\right) \times W_{2a}} = \frac{kL_1^n}{kL_2^n} \times \frac{t_{12} - t_{11}}{t_{22} - t_{21}} \quad (4.9)$$

where G_{12}, G_{11} are the quantities of gas at two different times for liquid L_1
 G_{22}, G_{21} are the quantities of gas at two different times for liquid L_2
 W_{12}, W_{11} are the weight of coal at two different times for Liquid L_1
 W_{22}, W_{21} are the weight of coal at two different times for Liquid L_2
 W_{1a}, W_{2a} are the average weight of coal for liquid L_1 and liquid L_2 respectively

If the same reaction temperature and same reaction period are chosen, equation (4.9) is simplified as below:

$$\frac{\left(\frac{G_{12}}{W_{12}} - \frac{G_{11}}{W_{11}}\right) \times W_{1a}}{\left(\frac{G_{22}}{W_{22}} - \frac{G_{21}}{W_{21}}\right) \times W_{2a}} = \left(\frac{L_1}{L_2}\right)^n \quad (4.10)$$

Figure 4.12 Kinetics for Isothermal Approximation

The values of reaction order for conversion of liquids to gases are listed in Table 4.1. It shows that a first order reaction was obtained. Rate constants at various temperatures were calculated based on the first order reaction and are given in Table 4.2. The reaction constant, k , is in a range of 4.5×10^{-4} to 1.6×10^{-3} (1/min) from low temperature (440°C) to high temperature (500°C). The apparent activation energy was obtained from the following equations:

$$k = A \exp\left(-\frac{E}{RT}\right) \quad (4.11)$$

$$\ln k = \ln A - \frac{E}{R} \times \frac{1}{T} \quad (4.12)$$

where A is the Arrhenius preexponential factor
 E is the apparent activation energy
 R is the gas constant, $1.987 \text{ cal/mol-(K)}$, and
 T is the absolute temperature, $^\circ\text{K}$

A plot of $\ln k$ versus $1/T$ is given in Figure 4.13. Apparent activation energy and preexponential factor were obtained from the Arrhenius plot. The apparent activation energy is 22.6 kcal/mole and the preexponential factor is 4150 1/min .

4.1.3 Non-Isothermal Mode

The sample injection technique used in this study prevented the coal samples from contacting the catalyst before the reactor temperature was raised to the pre-set value, which normally took from 40 to 60 minutes. However, small amounts of the coal and liquid samples were always trapped in the injection tube. Hence, it was very difficult to control precisely the amount of sample injected every time. Furthermore, the reaction temperatures,

Table 4.1 Reaction Order for Liquids to Gases

	440 °C (g)	485 °C (g)
G ₁₂	0.8801	2.0009
W ₁₂	4.3644	4.6147
G ₁₁	0.7769	1.6801
W ₁₁	4.4412	4.5415
W _{1a}	4.4028	4.5781
L ₁	15.0975	14.5423
G ₂₂	0.3978	1.2470
W ₂₂	2.9181	2.8697
G ₂₁	0.3133	1.0462
W ₂₁	2.8582	2.7875
W _{2a}	2.8882	2.8286
L ₂	10.0279	9.0180
n	1.03	1.16

Note: At 440°C results are from reaction time 20 min and 40 min.
 At 485°C results are from reaction time 30 min and 40 min.

Table 4.2 Rate Constants of Liquids to Gases by Isothermal Approximation

Temperature °C	kL	k (1/min)
440	0.006907	0.00045141
455	0.010658	0.00070426
470	0.013500	0.00090067
485	0.017852	0.00121391
500	0.022803	0.00161645

Figure 4.13 Apparent Activation Energy by Isothermal Approximation

especially in the first ten minutes of the reaction, were not uniform. A more complex mathematical model was developed to account for these effects. The reaction sequence of coal gasification is expressed as follows:

There are five sets of runs at selected temperatures 440, 455, 470, 485 and 500 °C with eight experiments for each set of runs at different reaction times 4, 7, 10, 20, 30, 40, 50, and 60 minutes. Reaction rate constant is a function of temperature, while temperature changes with reaction time for each set of runs:

$$k = f(T) \quad (4.14)$$

$$T = f(t) \quad (4.15)$$

where T is reaction temperature, and t is reaction time.

The function $T = f(t)$ for each experimental run was obtained by a cubic spline interpolation method using 20 points read from the real temperature profile. Typical temperature profiles obtained by this numerical technique for five controller set points are presented in Figure 4.14.

Kinetic equations based on the reaction sequence were derived, assuming second order for coal to liquid conversion⁸ and first order for all other reactions.

$$W_c^t = W_c^0 - \int_0^t k_3(t) W_c^2 dt - \int_0^t k_2(t) W_c dt - \int_0^t k_4(t) W_c dt \quad (4.16)$$

Figure 4.14 Simulation of Temperature Profile

$$W_{\text{coke}}^t = \int_0^t k_4(t) W_c dt \quad (4.17)$$

$$W_g^t = \int_0^t k_1(t) W_1 dt + \int_0^t k_2(t) W_c dt \quad (4.18)$$

$$W_1^t = \int_0^t k_3(t) W_c^2 dt - \int_0^t k_1(t) W_1 dt \quad (4.19)$$

$$k = A \exp\left(-\frac{E_a}{RT}\right) \quad (4.20)$$

$$E(A_1, E_{a1}) = \sum_{n=1}^m \left\{ \left(\frac{W_g^t - W_{gE}^t}{W_{gE}^t} \right)^2 + \left(\frac{W_1^t - W_{1E}^t}{W_{1E}^t} \right)^2 + \left[\frac{(W_c^t + W_{\text{coke}}^t) - (W_{cE}^t + W_{\text{cokeE}}^t)}{W_{cE}^t + W_{\text{cokeE}}^t} \right]^2 \right\} \quad (4.21)$$

- where
- W_c^t is the weight of coal at time t , g.
 - W_c^0 is the weight of coal at initial time t_0 , g.
 - W_{coke}^t is the weight of coke at time t , g.
 - W_g^t is the weight of gas at time t , g.
 - W_1^t is the weight of liquid at time t , g.
 - W_c is the coal as a function of time, g.
 - W_1 is the liquid as a function of time, g.
 - A_1 is the preexponential index for four reaction paths.
 - E_{a1} is the apparent activation energy for four reaction paths.
 - W_{cE}^t is the weight of coal at time t by experiment, g.
 - W_{1E}^t is the weight of liquid at time t by experiment, g.

W_{gE}^t is the weight of gas at time t by experiment, g.

W_{cokeE}^t is the weight of coke at time t by experiment, g.

$E(A_i, E_{ai})$ is the error function.

m is the number of total experimental runs.

The eight unknown variables, namely A_i , E_{ai} , were determined by minimizing the error. A computer program written by Dr. K. S. Yang was used to carry out the calculation. The program converged at $E(A_i, E_{ai}) = 1.6$, which is equivalent to an average deviation of about 16% for each weight measurement of gas, liquid, or unreacted coal and coke. The amount of gas product using the values of A_i and E_{ai} obtained by simulation are compared with those by experiment in Figure 4.15 for all 40 runs at various reaction temperatures and times. As shown in the Figure, most of the data points fall on the 45° diagonal line. Figures 4.16 through 4.20 compare the amounts of gas product by simulation and those by experiment as a function of time at different selected temperatures. In general, the deviations between the predicted values and the experimental data are no more than the expected experimental error.

Similar plots for liquid and solid products are presented in Figures 4.21 to 4.26 and 4.27 to 4.32, respectively. The comparison of the results for the solid product are in general as good as those for the gas product. However, as shown in Figure 4.21, the amounts of liquid product by simulation are about 0.5 g smaller than those by experiment. As water was not separated from the liquid product before weighing, it is believed that the discrepancy is due to the water produced in the experiments.

Figure 4.15 Comparison of Gas Yield between Simulation and Experiments

Figure 4.16 Gas Yield Calculated by Simulation Method at 440 °C

Figure 4.17 Gas Yield Calculated by Simulation Method at 455°C

Figure 4.18 Gas Yield Calculated by Simulation Method at 470°C

Figure 4.19 Gas Yield Calculated by Simulation Method at 485°C

Figure 4.20 Gas Yield Calculated by Simulation Method at 500°C

Figure 4.21 Comparison of Liquid Yield between Simulation and Experiments

Figure 4.22 Liquid Yield Calculated by Simulation Method at 440°C

Figure 4.23 Liquid Yield Calculated by Simulation Method at 455°C

Figure 4.24 Liquid Yield Calculated by Simulation Method at 470°C

Figure 4.25 Liquid Yield Calculated by Simulation Method at 485°C

Figure 4.26 Liquid Yield Calculated by Simulation Method at 500°C

Figure 4.27 Comparison of Coal and Unreacted Coal Yield between Simulation and Experiments

Figure 4.28 Coke and Unreacted Coal Yield Calculated by Simulation Method at 440°C

Figure 4.29 Coke and Unreacted Coal Yield Calculated by Simulation Method at 455°C

Figure 4.30 Coke and Unreacted Coal Yield Calculated by Simulation Method at 470°C

Figure 4.31 Coke and Unreacted Coal Yield Calculated by Simulation Method at 485°C

Figure 4.32 Coke and Unreacted Coal Yield Calculated by Simulation Method at 500°C

Coal contains a significant amount of oxygen. Under the experimental conditions, most, if not all, of the oxygen is expected to react with hydrogen to form water.

Using the preexponential factors and apparent activation energies calculated by the computer program, the rate constants can be expressed as follows:

$$k_1 = 7.07 \times 10^4 \text{ Exp}(-26.55 \times 10^3 / RT) \quad (4.22)$$

$$k_2 = 2.16 \times 10^7 \text{ Exp}(-29.79 \times 10^3 / RT) \quad (4.23)$$

$$k_3 = 8.31 \times 10^7 \text{ Exp}(-29.75 \times 10^3 / RT) \quad (4.24)$$

$$k_4 = 4.94 \times 10^7 \text{ Exp}(-29.67 \times 10^3 / RT) \quad (4.25)$$

Reaction Rate Constants are calculated and presented in Table 4.3.

After the kinetic parameters were determined, a series of computer simulations was carried out to obtain the product distribution profiles under isothermal conditions, using values for feed composition of 5g of coal and 15g of liquid. The results are presented in Figures 4.33 through 4.37 for different reaction temperatures. As expected, the initial production rate of gas directly from coal is very high and becomes insignificant after about 10 minutes. Most of the gas produced after about 10 minutes is from coal-derived liquids and solvent at a nearly constant rate for a given temperature.

4.1.4 Discussion

Temperature Profile The large amount of heat released during the initial stage of the reaction is believed to be due to hydrogenation reactions. The first step in the coal conversion is thermal bond rupture of linkages between condensed units

Table 4.3 Reaction Rate Constants by Non-Isothermal Mode

Temp (°C)	Temp (K)	k1	k2	k3	k4
440	713.15	5.16E-04	1.60E-02	6.34E-02	3.99E-02
455	728.15	7.59E-04	2.47E-02	9.77E-01	6.14E-02
470	743.15	1.09E-03	3.74E-02	1.48E-01	9.26E-02
485	758.15	1.56E-03	5.58E-02	2.20E-01	1.38E-01
500	773.15	2.21E-03	8.19E-02	3.23E-01	1.90E-01

Figure 4.33 Gas Yield Produced from Coal and Liquid at 440°C

Figure 4.34 Gas Yield Produced from Coal and Liquid at 455°C

Figure 4.35 Gas Yield Produced from Coal and Liquid at 470°C

Figure 4.36 Gas Yield Produced from Coal and Liquid at 485°C

Figure 4.37 Gas Yield Produced from Coal and Liquid at 500°C

(clusters), resulting in the formation of free radicals. Since free radicals are unstable and highly reactive they would seek stabilization. It has been found⁹ that in non-donor vehicles these free radicals react with surrounding molecules to form high-molecular-weight substances which are not soluble in extracting solvent such as pyridine or benzene. Alternatively, when a hydrogen donor solvent such as tetralin is present, a great portion of the free radicals are stabilized by abstraction of hydrogen from tetralin. Products are then relatively low-molecular-weight molecules capable of being dissolved in benzene. Upon releasing hydrogen, tetralin is converted to naphthalene.

Wiser^{10,11} found that the dissolution process was first order with respect to unreacted but potentially reactive coal and first order with respect to unreacted tetralin. He also found that the formation of naphthalene and hydrogen from tetralin was essentially negligible at coal dissolution conditions in the absence of coal. Appreciable quantities of naphthalene and hydrogen were produced when tetralin and coal were heated together. Naphthalene can be rehydrogenated by H_2 .

Fast Coal Conversion A large amount of evidence has been accumulated to indicate that bituminous and subbituminous coals consist of aromatic clusters joined together by various linkages. These clusters contain from one to several aromatic rings in a fused or condensed configuration, with an average size for subbituminous coal of about 2. The linkages include C_1 - C_3 aliphatic bridges, ethers etc. These linkages are susceptible to

thermal cracking at temperatures above 350 °C. It has been observed in connection with thermal cracking of hydrocarbons in the petroleum industry that the decomposition rates double for each 10 degree C temperature rise¹². Interaction between a donating solvent (e.g. tetralin) and coal may appreciably reduce the activation energies associated with thermal rupture of bonds within the coal structure, thus permitting more extensive bond rupture leading to fast reaction of coal. In the temperature range of these experiments, from 450 °C to 500 °C, and with tetralin in the system, the rate of coal conversion is rapid and coal is almost converted completely within 10 mins.

Reaction Kinetics The reaction pathway of direct single stage coal gasification involves two main steps. The first step is coal to liquids with a small amount of gas and coke. The second step is liquids to gases. The first step is believed to follow a free radical mechanism, while the second step is believed to involve hydrocracking by carbonium ion chemistry, which will be discussed in detail in the next section.

The first step of the process is very similar to coal liquefaction in which heating of the coal-solvent mixture causes a thermolysis reaction to occur and the solvent limits the retrogressive reactions by donating and shuttling hydrogen that caps the free radicals. Several kinetic similarities have been observed among coal pyrolysis, coal dissolution in a donor solvent, and catalytic hydrogenation in the temperature range 400 to 450 °C^{8,11}. The rate-controlling step in the pyrolysis is second order with an activation energy of 36 kcal/mole. Solvent

extraction of the same coal in tetralin was also second order with an activation energy of 30 kcal/mole. The solution process is first order with respect to unreacted but potentially reactive coal and first order with respect to the concentration of solvent in the reaction zone. Catalytic hydrogenation of the same coal, stirred in a coal-derived vehicle oil, with a cobalt molybdate catalyst, was also second order overall with an activation energy of 38 kcal/mole. By comparison, Wiser also found that batch hydrogenation, pyrolysis, and coal dissolution under given conditions approach completion at similar rates, and they are believed to involve similar mechanisms, namely thermal bond rupture to yield free radicals, followed by radical stabilization as the rate-determining step.

The present study involves all three sources of stabilization of reactive fragments. Therefore the first step of coal to liquids can be expressed as:

$$\begin{aligned}\frac{dx}{dt} &= k_P(a_P - x)^2 + k_S(a_S - x)(b - x) + k_H(a_H - x)^2 \\ &= \left\{ k_P + k_S \frac{(b - x)}{(a - x)} + k_H \right\} (a - x)^2\end{aligned}\quad (4.26)$$

where, x = weight fraction of coal

$$b = 1.0^{11}$$

$$a_P = a_S = a_H = a = 1.0$$

When only pyrolysis is occurring, the production of liquids ceases when the supply of hydrogen from within the coal structures, useful for stabilization of the reactive fragments, is exhausted. For those cases, the value of a_P is of the order of 0.2 to 0.4 depending upon the temperature of reaction.

However, when a hydrogen-donor solvent, or a hydrogenation catalyst with molecular hydrogen, or both, are present in the system, it may be assumed that hydrogen for stabilization may continue to be provided from all sources present, until the reactions are completed, and a_p approaches a_h , and approaches a value of 1.0. Hence for the purpose of Equation (4.26), each $(a-x)$ is assumed to reach the same value.

$$\begin{aligned}\frac{dx}{dt} &= (k_p + k_s + k_H)(a-x)^2 \\ &= k_o(a-x)^2\end{aligned}\tag{4.27}$$

$$\text{where } k_o = k_p + k_s + k_H\tag{4.28}$$

$$k_o > k_p, k_s \text{ or } k_H\tag{4.29}$$

This indicates that the overall rate constant of the process is larger than that of the fastest reaction rate of individual reactions. The reaction is second order with respect to coal.

As noted earlier, the conversion of coal to liquids in these experiments is essentially completed in the first 10 minutes. The reactor system used could only provide two data points in that 10-minute interval, namely at 4 minutes and at 7 minutes, which is insufficient to derive kinetic data for the first step of the reaction sequence. However, the results obtained by the technique of the non-isothermal mode show that the rate constant k_3 (coal to liquid) is larger than k_2 (coal to gas) and k_4 (coal to coke). (Refer to Equation (4.13) and Table 4.3). The data indicate that coal to liquid is faster than coal to gas and coke and most of the coal was converted to liquid with a small amount of gas and coke.

The second step in the reaction sequence, coal-derived liquids to gases, is unique. The isothermal approximation assumes that this step is the rate-controlling step for the direct coal gasification process, which is confirmed by the non-isothermal calculation. The rate constant of liquid to gases is much smaller than any of the other rate constants. Most of the gas is produced from liquids, which is indicated in Figures 4.33 through 4.37. The kinetic parameters obtained by the two methods, isothermal approximation and non-isothermal mode, are close (Table 4.4), which indicates that the assumption made in the isothermal approximation is valid.

Our study yields an activation energy of 23 kcal/mol by the isothermal approximation and 27 kcal/mol by the non-isothermal mode, for liquids to gases, which values are consistent with hydrocracking of coal oil, anthracene and phenanthrene, which range from 18 to 21 kcal/mole, as observed by Qader¹³. No previous studies on the kinetics of hydrocracking of coal-derived liquids to hydrocarbon gases high in C₂-C₄ hydrocarbons are found in the literature. In these studies, conducted in the presence of a large excess of hydrogen, the rate of the reaction is first order with respect to liquids.

Possible Solvent Reaction During Gasification The hydrogen-donor solvent plays an important role in direct coal gasification as performed in this study. A study of the role of the solvent requires labeled isotopes. The solvent may act as a direct source of hydrogen (donor), an indirect source of hydrogen (hydrogen-transfer agent), or it may directly hydrocrack.

Table 4.4 Comparison of Rate Constants by Isothermal and Non-Isothermal Methods

Temperature °C	k, min ⁻¹	Isothermal	k, min ⁻¹	Non-Isothermal
440		4.51E-4		5.16E-4
455		7.04E-4		7.59E-4
470		9.01E-4		1.09E-3
485		1.21E-3		1.56E-3
500		1.62E-3		2.21E-3
Activation Energy, kcal/mole		22.65kcal/mole		26.55 kcal/mole

Kabe¹⁴ studied hydrocracking of Wandon coal liquid using tritium-labeled tetralin solvent, which contained a small amount of ¹⁴C-labeled naphthalene, at 400 °C, with a Ni-Mo-alumina catalyst. He also conducted experiments without a catalyst to monitor the fate of the tetralin solvent. It has been found that a part of the tetralin solvent (<20%) was converted to naphthalene and a smaller amount to decalin, with formation of some indan and butylbenzene. On the other hand, part of the naphthalene was catalytically hydrogenated to tetralin. In the presence of a catalyst the rates of production of 1-methylindan, butylbenzene and naphthalene were generally smaller than when the catalyst was absent. It was also observed that the larger molecules tend to be cracked thermally and react with the donor solvent directly. Smaller molecules were cracked catalytically. The donor solvent is more effective in coal liquefaction than in hydrogenation of coal-derived liquids.

Neavel⁹ observed that free radicals formed during thermal cleavage of chemical bonds in the coal were stabilized in the early stages by autogenous hydrogen transfer, and in later stages by abstraction of hydrogen from the hydrogen-donating tetralin (which was converted to dihydronaphthalene then to naphthalene).

Skowronski, et al¹⁵ studied ²H and/or tetralin-d₁₂ reacting with coal at temperatures ranging from 360-425 °C. They showed that the 1-position of tetralin is most reactive for the hydrogenation of coal, and that the abstraction of hydrogen from tetralin by a coal-derived radical is involved in the rate-determining step in the formation of soluble products.

Ratto¹⁶ used fully-deuterated tetralin, deuterium gas and bituminous coal at 400 °C and 15.2-20.7 MPa (no catalyst) to study the mechanisms of donor solvent. Approximately 35% of the hydrogen transfer resulted from tetralin donation to the coal. Hydrogen exchange between coal and a donor solvent as well as a non-donor solvent was also observed. Hydrogen exchange via the α -tetralinyl radical can have a significant role in quenching the reactive species which form from the thermal cleavage of coal.

On the other hand, tetralin undergoes similar hydrocracking reactions as other two- or three-ring aromatic compounds under the same reaction conditions, which will be discussed in detail later. Hydrogenation, isomerization, and catalytic cracking of tetralin all take place during the reaction, resulting in low molecular weight products, including gases. Some gasification of the solvent cannot be avoided. In the calculation of kinetic parameters, liquids consumed in gas production include the coal-derived liquids and the solvent, because gases come from both sources. How much of the solvent was gasified is unknown, but there are points which should be mentioned with respect to possible reaction of solvent and coal-derived liquid.

(1) Tetralin is an intermediate product of hydrocracking aromatic compounds.

(2) Some compounds in the coal-derived liquids have hydrogen donating capability similar to tetralin. Examples include two-ring, three-ring and higher-ring hydroaromatic compounds, and some phenolic compounds.

(3) Higher-ring hydrocarbons are more reactive.

4.2 Reaction Pathway

The reaction sequence of coal to gases as shown in equation 4.1 involves two steps. The first step is coal to liquids with small amounts of gases and coke. The second step is liquids to gases.

4.2.1 Coal to Liquids

When coal is heated to above 375 °C, the weak chemical bridges are broken resulting in the formation of free radicals. Wiser's coal structure model in Figure 2.3 indicates by arrows the kinds of linkages susceptible to thermal cleavage. The C-C bridges which are tri- or tetra-substituted are cleaved most easily¹⁷. Structures which contain two-carbon aliphatic chains as bridges connecting aryl groups are cleaved primarily at the central C-C bonds, not adjacent to the aryl rings. The presence of phenolic hydroxyl substituents enhances the cleavage of C-C bonds. The sulfur present as linkages is also susceptible to thermal cleavage.

Free radicals have been detected during the heat treatment of coal by electron spin resonance (ESR)¹⁸⁻²². The radical concentration of the coal changes with reaction temperature. Radical concentration increases sharply between 400 and 500 °C. This indicates thermal cleavage of the coal structure occurs rapidly in this temperature range.

Free radicals, which contain unpaired electrons, are very reactive species. If hydrogen is available to these highly reactive fragments the radicals are stabilized to form products of low molecular weight. Otherwise under conditions where

hydrogen is unavailable, the concentration of the free radicals becomes large, and condensation and retrogressive reactions can occur to give poor yields of liquid-size molecules. In our reaction system the hydrogen available for stabilizing these highly reactive fragments comes from redistribution of hydrogen within the coal (hydrogen shuttling), hydrogen donor solvent (tetralin) and molecular hydrogen (high H_2 pressure) in the presence of the catalyst.

In the thermal process a certain percentage of the coal can be converted to low-molecular weight products without a donor solvent or molecular hydrogen. The hydrogen is provided by the hydroaromatic structure of the coal and by condensed aromatic structures which are hydrogenated first.

A hydrogen donor solvent like tetralin used in our system has been proven to be very effective for quenching free radicals^{9,23,24}. Free radicals abstract hydrogen from tetralin. Tetralin is converted to dihydronaphthalene and then to naphthalene. The radical concentration in the coal heated with tetralin is about the same as that found for unheated natural coal. Nearly all of the thermally-produced radicals are quenched. The free radical concentration after thermal treatment correlates well with the propensity of a given solvent to donate its hydrogen. Hydrogen transfer from tetralin increases exponentially with increased conversion of the coal to benzene-soluble material.

Molecular hydrogen can participate directly in free radical reactions at coal conversion conditions (about 450 °C)²⁵.

Molecular hydrogen also promotes some hydrocracking reactions that do not occur to an appreciable extent in the donor system. High pressure hydrogen can accelerate the hydrocracking of some carbon-carbon bonds in the coal structure that are too strong to break thermally. Hydrogen also promotes ring opening in hydroaromatic molecules and it accelerates the dealkylation of aromatic systems.

A schematic representation of coal to liquids by a free-radical mechanism is shown in Figure 4.38.

4.2.2.. Liquids to Gases

Although the exact structure of the liquids produced in our experiments is not known, the structure of the liquids produced after the linkages are broken has been extensively studied. Anderson and coworkers²⁶ studied the structure of coal-derived liquids from hydrogenation of coal at 500 °C and 1800 psig with zinc chloride as catalyst. Products of the hydrogenation treatment included 10% gases, 5% light liquids (b.p. <250 °C), 55% heavy liquids, 15% char and 15% water (percents by weight of dry mineral-matter-free coal). Conversion was 85% assuming char as unreacted coal. After paraffinic materials were removed from the heavy liquid product, it was observed to retain some of the features of the feed coal. This fraction, defined as HVL-P, was used for characterization. The proposed structures are shown in Figure 4.39. The parameters of these structures are listed in Table 4.5. The average number of rings per cluster is 2.2. These results help us to understand the structure of coal liquids and the reaction pathway of conversion of the liquids to gases.

Chain Initiation:

Chain Transfer and Propagation:

Chain Termination:

Figure 4.38. Reaction Scheme for Coal to Liquids

Figure 4.39 Possible Structure Unit in the HVL-P Fraction

Table 4.5 Analytical Data on HVL-P and Its Fraction

	Yield (wt%)*	Mol. Wt	RA	RN	#cl	fA	RA/#cl
HVL-P	100	258	2.4	0.8	1.1	0.63	2.2
Light	19.2	183	1.2	0.6	1.0	0.55	1.2
Middle	15.7	210	1.6	0.7	1.1	0.58	1.5
Heavy	17.6	272	2.4	1.3	1.0	0.59	2.4
Resid	40.0	396	4.4	1.2	1.3	0.68	

* Weight % of Coal.

Note: RA = Number of Aromatic Rings.

RN = Number of Naphthenic and Saturated Rings.

#cl = Number of Aromatic Clusters.

fA = Fraction of Aromatic Carbons (= Aromaticity)

RA/#cl = Cluster Size.

The conversion of hydrocarbons to compounds of lower molecular weight under hydrogenation conditions has generally been described as hydrocracking. All hydrocracking catalysts have dual functions, consisting of hydrogenation metals on an acidic cracking support. Actually, hydrocracking can occur as two distinctly different reactions. The first of these is thermal cracking under a hydrogen atmosphere, in which the carbon-carbon bond breakage is caused by elevated temperatures and the cracking reaction proceeds by a free radical mechanism. This type of hydrocracking occurs in any hydrogenation process regardless of catalyst type when temperature becomes sufficiently high. The gas product from thermal cracking is mostly ethane. The second type of hydrocracking is catalyzed by acidic materials, such as silica-alumina, and proceeds by the carbonium ion mechanism, which functions in conventional catalytic cracking. The gas products from catalytic cracking consist mostly of C_3 and C_4 . Under hydrocracking conditions catalytic cracking is much faster than thermal cracking, so hydrocracking can be considered as catalytic cracking with hydrogenation superimposed.

In order, specifically, to draw conclusions concerning the validity of the carbonium ion mechanism relative to direct production of gases from liquids, several model compounds studied include long-chain normal paraffins, such as n-hexadecane, partially hydrogenated condensed aromatics, such as tetralin, and three-ring aromatics such as anthracene and phenanthrene. These compounds have been widely studied in carbonium ion chemistry,

and the conclusion that the hydrocracking of compounds of these types proceeds via carbonium ion mechanism is widely accepted. Products of these model compounds under present study conditions, compared with those found in the literature by hydrocracking, have been shown to proceed by the carbonium ion mechanism. Products from hydrocracking of n-hexadecane were analyzed by GC and are listed in Table 4.6. The comparison of data from these experiments with literature data by Archibald³ which have been shown to be obtained by carbonium ion chemistry, is presented in Figure 4.40. A similar product distribution is found for the two processes. An important feature of both results is the selective splitting of carbon-carbon bonds to give fragments of three or more carbon atoms. Thermal cracking gives a very different product as shown in Figure 2.5, in which C₂ is the most abundant.

Products from hydrocracking tetralin, anthracene and phenanthrene were analyzed by GC and GC-MS. Identification of liquid composition from hydrocracking tetralin by GC-MS is presented in Figure 4.41. The principal liquid product from tetralin is C₁₀ bicyclic cycloalkanes, including decalin and methylindans. Benzene, toluene, and other C₈, C₁₀ alkylbenzenes were produced. These liquid products are also the products suggested by Qader¹³ through carbonium ion chemistry (see Figure 2.8). Comparison of gas product distribution with Sullivan's result⁷ is shown in Figure 4.42. A very similar gas distribution was obtained for two kinds of processes. C₃ and C₄ represent the highest yields among the gas products which is a manifestation of a carbonium ion mechanism.

Table 4.6 Hydrocracking Product Distribution of n-Hexadecane*

Products	Wt% of Feed	Moles Product/100 Moles Feed
C ₁	0.317	4.47
C ₂	0.978	7.37
C ₃	7.074	36.33
C ₄	9.394	36.60
C ₅	5.674	17.81
C ₆	5.094	13.39
C ₇	4.115	9.30
C ₈	3.086	6.12
>C ₈	64.267	
Conversion (%)	51.73	

* Temperature: 450 °C;

Pressure: 1800 psia;

Reaction Time: 30 min;

Ni-Mo/Al₂O₃, SiO₂AlO₃ catalyst

Figure 4.40 Product Distribution for Hydrocracking n-Hexadecane

Figure 4.42 Gas Product Distribution for Hydrocracking Tetralin

Identification by GC-MS of liquids resulting from hydrocracking anthracene is shown in Figure 4.43. The principal products are partially hydrogenated anthracenes. Tetralin, indan and naphthalene derivatives are the next main products resulting from further hydrocracking of hydrogenated anthracenes. A small amount of toluene is also observed by the GC analysis which is not shown here. The comparison of gas distribution from these experimental results with Sullivan's result is plotted in Figure 4.44. The product distribution indicates that C_3 and C_4 , rather than C_2 , are the most abundant gas products obtained from both processes.

Analysis by GC-MS of the liquid products from hydrocracking phenanthrene is shown in Figure 4.45. The product distribution is similar to anthracene. Partially hydrogenated phenanthrene is the main product. Among the derivatives of tetralin and naphthalene, tetralin is the dominant one. Some benzene derivatives are also found in the products. The comparison of gas distribution between these experimental results and Sullivan's result is plotted in Figure 4.46. C_3 rather than C_2 is the most prominent in the gas products from these experiments.

Mass spectral analyses of liquid components from hydrocracking tetralin, anthracene and phenanthrene are given in Table 4.7.

The similarity between the product distribution from the experiments and that from hydrocracking of hydrocarbons, which has been shown to proceed via carbonium ion chemistry, suggests that the same mechanism occurs in both processes. Therefore, the

Figure 4.44 Gas Product Distribution for Hydrocracking Anthracene

Figure 4.45 Identification of Liquid Components of Hydrocracking Phenanthrene by GC-MS

Figure 4.46 Gas Product Distribution for Hydrocracking Phenanthrene

Table 4.7 Mass Spectral Analysis of Liquid Components Found in
Hydrocracking Model Compounds

Components	Molecular Peak, m/e	Fragments, m/e
Ethylbenzene (T)*	106	105, 92, 91, 77, 65, 51
Methyloctahydroindene(T)	138	118, 117, 115, 96, 68, 67
Trimethyl cyclohexanes (T)	140	111, 96, 81, 55, 41
Methylindans (T) (P)*	132	131, 117, 116, 115, 91, 39
Trans-decalin (T)	138	109, 96, 85, 82, 81, 67
Cis-decalin (T)	138	109, 96, 85, 82, 81, 67
Tetralin (T) (A)* (P)	132	117, 115, 104, 103, 91, 78
Naphthalene (T) (A) (P)	128	129, 127, 126, 102, 75, 63
Methyltetralins (A) (P)	146	145, 131, 128, 117, 115, 91
Methylnaphthalenes (A) (P)	142	143, 141, 116, 115, 91
C12-Alkyltetralins (A) (P)	160	145, 131, 129, 117, 105, 91
C12-Alkyl-naphthalenes (A)	156	142, 141, 131, 119, 115, 91
Tetradecahydroanthracene (A)	192	181, 169, 150, 135, 96, 81
Trimethylindans (A)	160	145, 131, 117, 115, 91, 69

Table 4.7 Continued

C ₁₄ -Alkyl-naphthalene (A) (P)	184	171, 143, 142, 141, 129, 115
Dimethyl-1,1'-Bipheyls (A)	182	168, 167, 165, 152, 89, 76
1,2,3,4,5,6,7,8-Octahydroanthracene (A)	186	158, 157, 145, 143, 129, 128
1,2,3,4, tetrahydro-anthracene (A)	182	183, 178, 167, 165, 154, 141, 115
Anthracene (A)	178	179, 176, 152, 89, 76, 63
Indan (P)	118	119, 117, 115, 116, 91, 89
C ₁₀ -Alkylbenzenes (P)	134	119, 105, 92, 91, 82, 67
Ethylenenaphthalene (P)	154	155, 153, 152, 128, 115, 105
Diethyltetralin (P)	188	131, 106, 105, 104, 92, 91
C ₁₄ -Alkyltetralin (P)	188	146, 145, 131, 117, 115, 91
9,10-Dihydrophenanthrene(P)	180	179, 178, 165, 152, 89, 76
1,2,3,4-Tetrahydrophenanthrene (P)	182	181, 165, 154, 152, 89, 76
1,2,3,4,5,6,7,8-Octahydrophenanthrene (P)	186	158, 157, 145, 143, 129, 115
Phenanthrene (P)	178	179, 175, 176, 152, 89, 76

* T, A and P represent tetralin, anthracene and phenanthrene products respectively.

pathway of conversion of coal-derived liquids to gases, as performed in this work, is presumed to be by carbonium ion chemistry.

As most of the coal-derived liquids consist of an average of 2-3 aromatic rings per cluster, anthracene was selected as a representative molecule for the coal-derived liquids to illustrate how C_2 - C_4 hydrocarbon gases may be formed by a carbonium ion mechanism (Figure 4.47). Anthracene is first hydrogenated in a step-wise manner forming di-, tetra- and octa-hydroanthracenes in that order. A carbonium ion can be generated either by protonation of an aromatic ring or by hydride abstraction from a naphthenic ring by action of the silica-alumina catalyst. A carbonium ion can be formed on the benzene ring of the structure as well as on the naphthenic unit. Once the carbonium ion is formed, hydrocracking follows the mechanism of catalytic cracking. Hydrogenation occurs fast. Reactions occurring on the acidic sites are rate-limiting, including isomerization of carbonium ions by skeletal rearrangement and β -scission, forming different small molecular hydrocarbons (mainly C_2 - C_4), the specie determined by the position of the carbonium ion.

4.3 Recycle Liquid as Hydrogen-Donor Solvent

In spite of the complex chemistry involved during direct coal gasification, there is no doubt that the hydrogen donor ability of the recycle solvent used in coal gasification is an important factor for success of the process. Hence, the quality of the recycle solvent must be maintained during processing.

Figure 4.47. Mechanism of Hydrocracking Anthracene by Carbonium Ion Chemistry

4.3.1 Experimental Results

These experiments were carried out with the same catalysts as used in the prior experiments, namely Ni-Mo/Alumina mixed with silica-alumina, at 500 °C, 1800 psig, 30 minutes, with a ratio of tetralin to coal to catalyst of 3:1:1.25. The first run used 100% fresh tetralin as the hydrogen donor solvent. The second run used 50% fresh tetralin, with the balance supplied from the liquids produced in the first run. The third run was 25% fresh tetralin, 75% liquids from run No. 2. The later runs used no fresh tetralin. Due to the limitation of the quantities of liquids available from the previous run, the amount of feed to the reactor was reduced for runs 5, 6 and 7.

The results indicating the effectiveness of recycle liquids as hydrogen donor solvent are presented in Table 4.8. Total conversion and conversion to gases versus run number are shown in Figure 4.48. Total conversion remains about the same, ranging from 80.5 to 84% of the dmmf coal. Gas yields did not decrease as more and more coal-derived liquid was used as solvent. However, more C₄ was produced, as shown in Figure 4.49. For run No.7, decreased conversion to gases was observed, which may be due to excessive reduction in the total amount of feed.

No degradation of the solvent was observed. Total conversion of coal was almost constant for seven runs. It indicates that there was enough hydrogen released from the recycle liquids used as solvent to stabilize the free radicals produced by the thermal rupture of linkages in the coal structure. The increased gas yield was probably due to the

Table 4.8. Effect of Recycle Liquid on Coal Gasification
Temperature = 500°C, Pressure = 1800 psig, Reaction Time = 30 minutes

	Run 1	Run 2	Run 3	Run 4	Run 5	Run 6	Run 7
Catalyst, g	4.9966	5.0026	5.0038	4.9992	3.7636	3.7583	2.5009
Coal, g	4.2031	4.2048	4.2040	4.2054	3.2395	3.2428	2.2609
Tetralin, g	12.0792	6.1162	3.1538	0	0	0	0
Recycle Liquid, g	0	6.1468	9.1863	12.0269	9.1230	9.5387	6.8065
Products:							
Gases, g	1.1556	1.4006	1.6963	1.9032	1.8713	2.5526	1.2737
Liquid, g	14.0930	14.0321	13.8075	13.1620	9.6664	9.3739	9.7131
Solid, g	1.0337	1.0351	1.0403	1.1671	0.8248	0.8550	0.5815

Table 4.8- Continued

	Run 1	Run 2	Run 3	Run 4	Run 5	Run 6	Run 7
Gas, wt%	30.62	37.09	44.94	50.41	64.34	87.68	62.75
Liquid, wt%	53.37	46.87	38.88	30.06	18.68	-5.66	19.98
Total Conversion, wt%	83.99	83.96	83.82	80.47	83.02	82.02	82.73
C1, wt%	8.17	9.37	10.51	11.27	12.26	14.42	12.41
C2, wt%	9.15	10.30	11.03	11.06	11.67	14.32	12.18
C3, wt%	8.76	10.24	11.91	13.26	21.41	22.08	16.74
C4, wt%	4.55	7.18	11.50	14.83	19.00	36.86	21.42

Note: All conversion numbers are based on dmmf coal.

Figure 4.48 Effect of Recycle Liquid on Coal and Gas Conversion

Figure 4.49 Effect of Recycle Liquid on Gas Composition

relatively longer reaction time of the liquid. The increase in C_4 hydrocarbon yield was due to more hydrocracking reaction.

Elemental analyses were performed on the recycle liquids from runs 1, 2, 4, and 7, and the results are presented in Table 4.9. It is observed that the hydrogen to carbon ratios of the recycle liquids were increased with further runs. It indicates that efficient hydrogenation of the liquid in the presence of the catalyst and hydrogen pressure occurs.

Further analyses by proton NMR were made for the recycle liquids. NMR spectra of recycle liquids from runs 1, 2, 4, and 7 are shown in Figures 4.50 through 4.53. Hydrogen distribution calculated from the proton NMR spectra is presented in Table 4.10. The ratio of aliphatic hydrogen to aromatic hydrogen increased, which is consistent with the higher hydrogen to carbon ratio shown in the elemental analysis.

In summary, although seven runs do not prove that the recycle solvent is all coal-derived liquid, no decrease in effectiveness of the solvent was observed with part of the coal-derived liquid as solvent.

4.3.2 Discussion

If the process were to be operated on a large scale, coal-derived liquid would be used as hydrogen-donor solvent rather than tetralin. It is of importance to observe how the hydrogen-donating ability of the coal-derived liquids compares with that of tetralin.

As discussed earlier in the possible tetralin reactions, tetralin may undergo isomerization and hydrocracking to small

Table 4.9 Elemental Analysis of Recycle Liquid

	C %	H %	H/C (Atomic)
Run 1	90.12	8.71	1.16
Run 2	88.82	8.76	1.18
Run 4	88.20	8.88	1.21
Run 7	84.34	9.41	1.34

Figure 4.50 NMR Results of Recycle Liquid from Run 1

Figure 4.51 ^1H NMR Results of Recycle Liquid from Run 2

Figure 4.52 NMR Results of Recycle Liquid from Run 4

Figure 4.53 NMR Results of Recycle Liquid from Run 7

Table 4.10 Hydrogen Distribution for Recycle Liquid by Proton NMR

	Aliphatic H 0.5-1.9 beta & gamma	Aliphatic H 1.9-4.0 alpha	Aliphatic H 0.5-4.0	Aromatic H 6.0-9.0	Total Aliphatic H + Aromatic H
Run 1	32.41	23.25	55.66	44.34	100
Run 2	32.61	24.60	57.21	42.78	100
Run 4	34.49	24.75	59.24	40.76	100
Run 7	41.54	29.28	70.82	29.17	100

molecular compounds, which will lead to poor donor capability. Two methods for restoring the solvent composition in the present study are possible: (1) coal can be converted to liquids which provide new additional solvent; and (2) the hydrogen-depleted solvent can be catalytically rehydrogenated by gaseous hydrogen.

Under our reaction conditions there is always net liquid produced from the coal. Coal liquid contains condensed aromatic and hydroaromatic structures. Hydroaromatic structures play the same role as tetralin in donating hydrogen to coal. Aromatic compounds behave as hydrogen shuttles to assist the donation of hydrogen from hydroaromatic structures. Condensed aromatic compounds are not net donors of hydrogen, but can thus "shuttle" hydrogen from one region of the coal to another. Whitehurst²⁷ showed that the structures which can contribute to good shuttling properties within recycle solvents are:

- .. Naphthalene and its alkyl derivatives
- Phenanthrene and other tri- and tetra-aromatic hydrocarbons and their alkyl derivatives.
- Heterocyclic polyaromatics, e.g., quinoline, benzofuran, benzothiophene, etc.

Several coal liquefaction processes use various hydrogen-donor solvents in a coal-oil slurry. Greater efficiencies with less hydrogen consumption were achieved²⁸. A comparison of major processes using hydrogen donor solvents is given in Table 4.11.

Thermodynamics show that the rehydrogenation of solvents is quite favorable; thus the question is one of rate. In our study

Table 4.11 Comparison of Major Coal Liquefaction Processes

	SRC-1	SRC-2	EDS	H-coal
Operating conditions:				
Pressure, MPa	10.3	13.4	10.3	12.3
Temperature, K	724	730	722	726
Residence time, min	40	60	40	30-70
Liquid yield, wt% maf coal	76	70	50	74
Coal conversion, wt% maf coal	95	95	70	94
H ₂ consumption, wt% maf coal	2.4	4.7	4.3	3.8-5.3
Recycle system	Recycle of process solvent	Recycle of reactor slurry	Recycle of hydrogenated solvent	Recycle of heavy distillate
Reactor	Upflow column reactor	Upflow column reactor	Upflow, plugflow tubular reactor	Ebullated-bed catalytic reactor
Catalyst		Mineral matter	Ni-Mo for solvent hydrogenation	Co-Mo or Ni-Mo

a hydrogenation catalyst and high pressure were both present, so the rate of hydrogenation of condensed aromatic compounds was appreciable.

4.4 Equilibrium Concentrations of C₂-C₄ Hydrocarbons

A computer program has been developed for calculation of the equilibrium concentrations of C₂, C₃, and C₄ hydrocarbons in a system which produces data such as those presented in Table 2.1.

With the objective in this research being to obtain the maximum yields of C₂-C₄ hydrocarbons, it is desirable to minimize the formation of methane. We have succeeded in obtaining much higher yields of ethane or propane than the amount of methane formed. While it is recognized that it would not be possible to avoid completely the formation of methane, it was considered to be instructive to see how high the yields of C₂-C₄ would be if such were to be achieved. This information may be useful in determining how far upstream from equilibrium one may wish to operate the system, or terminate the reactions. Therefore two scenarios were used: one where methane would be a product, and a second where methane would not be a product.

4.4.1 The Approach

The first step in this evaluation was identification of the major compounds to be found in the product and to estimate their concentrations at equilibrium, under reaction conditions used in the kinetic study reported above. Representative compounds were then used for establishing the computer program which would permit calculation of the desired equilibrium concentrations. A single representative aromatic compound was used for obtaining

actual equilibrium concentrations of C_2 , C_3 , and C_4 , as well as other compounds observed to be present in the products obtained in the experimental work presented above. The equilibrium results were then compared with the experimental data, to gain understanding of whether production of light hydrocarbons from coal is thermodynamically or kinetically limited.

4.4.2 The Method

Selection of Compounds The kinetic results presented above indicated that the process of conversion of coal to fluids (liquids and gases) was essentially completed in the first few minutes of reaction. Thereafter further production of gases resulted from continued hydrocracking of the liquids. It was observed that most of the total hydrocarbon gas product resulted from the hydrocracking of the liquids, both coal-derived liquids and original solvent. The rate-determining step in the overall process of coal-to-hydrocarbon gases is the conversion of liquids to gases. Therefore, for comparison purposes equilibrium calculations were conducted for the major components observed to be present in the liquids, and leading to the hydrocarbon gases which were experimentally observed to be formed by the reactions. The following criteria were used for selection of compounds to be included:

- a. Gas compounds of interest were methane, ethane, propane, butane, ethylene, propylene and butene.
- b. Liquid compounds included were those observed in significant amounts in the GC-MS spectra of the products from the experiments.

- c. Other liquid compounds were included which might be present in significant amounts at equilibrium, although not identified in the GC-MS spectra of the liquids produced in the non-equilibrium data from the experiments.

The selected compounds from the above criteria were further screened down to a total of about fifteen compounds, after initial calculations.

Calculation Procedures A tearing iteration method was adapted, which yielded acceptable numerical stability. The calculation procedures used are as follows:

- (1) Select two compounds which are likely to be the most abundant species at equilibrium. The concentrations of these key components are used as the tearing variables.
- (2) Express the concentrations of other compounds as functions of concentrations of hydrogen and selected key compounds, equilibrium constants, and fugacity coefficients.
- (3) Input into the computer program for each compound the following thermodynamic parameters: enthalpy at 298 °K, free energy of formation at 298 °K, polynomial coefficients for calculating heat capacities, critical temperature, critical pressure, and acentric factor.
- (4) Input reaction orders in the expressions obtained in (3).
- (5) Input the equilibrium temperature and pressure.
- (6) Input the initial guesses of the concentrations of the key compounds.
- (7) Calculate the equilibrium constants at the selected reaction temperature.

- (8) Calculate the fugacity coefficients for all compounds at the selected reaction temperature and pressure.
- (9) Estimate the concentrations of minor components.
- (10) Recalculate the concentrations of the key components.
- (11) Repeat steps (8) to (10) until convergence is observed.
- (12) Print out the results.

4.4.3 Results and Discussion

The liquid products formed from coal, under the conditions of the experiments of this study, are high in condensed aromatics, with two or three rings per cluster predominating, but with appreciable amounts of single-ring compounds present in the liquids. The pathway to hydrocarbon gases, as well as the products present at equilibrium, would be the same whether one started from a two-ring or a three-ring compound. Therefore naphthalene was selected as the compound on which the calculation of equilibrium concentrations of products is based.

It is to be expected that the conversion of naphthalene to hydrocarbon gases, as well as the nature of the products formed, may be limited by the amount of hydrogen introduced to the system. In the figures which follow, the mole ratio of hydrogen to naphthalene at the beginning of each operation is designated by R, and is varied from values of 1 to 5 for the calculations.

Figure 4.54 presents a representation of the calculated equilibrium concentrations of the major species at 480 °C (753 °K) and 1800 psi, assuming methane to be one of the major products of reaction. The results reflect the thermodynamic stability of methane among the products included in the

Figure 4.54 Compositions of the Major Compounds at Equilibrium, assuming Methane to be one of the Major Products

calculation. At R values up to 5, essentially all of the hydrogen added to the system is consumed by the conversion of the naphthalene, with methane representing essentially the only product remaining when equilibrium is reached. Only small traces of single-ring compounds remain, and no higher aliphatic compounds are in the equilibrium product. It is noted that compounds such as tetralin, with a saturated portion in the structure, also do not survive.

When methane is removed as a possible product, as discussed above, the product distribution at equilibrium becomes as presented in Figure 4.55. The figure indicates that ethane is not formed in such a dominant manner as is methane. Consequently at equilibrium considerable amounts of benzene, toluene and xylene survive. However saturated portions of condensed units, such as in tetralin, do not survive. Also, there are no aliphatic hydrocarbons larger than ethane in the products. It is also noted that, at equilibrium, some hydrogen remains unreacted in the system.

The data of Figure 4.55 reveal some interesting observations relative to the non-equilibrium data presented earlier. In those data the liquids in the final product were rich in single-ring compounds, with low concentrations of methane relative to the amounts of C_2-C_4 hydrocarbons. Also the total quantities of C_2-C_4 hydrocarbons begin to exceed the quantity of naphthalene at equilibrium.

Figure 4.56 shows the effect of an increase in the molar ratio of hydrogen to naphthalene upon the concentrations of the

Figure 4.55 Compositions of the Major Compounds at Equilibrium, assuming Methane is not one of the Major Products

Figure 4.56 The Effect of Hydrogen to Naphthalene Ratio on Composition of the Major Compounds at Equilibrium, assuming Methane is not one of the Major Products

major products at equilibrium. This figure again assumes that methane is not a major product. The calculations predict that ethane production will increase almost linearly with increasing R , while concentrations of the single-ring compounds are not strongly affected by R , and remain almost constant.

Figure 4.57 shows the effect of temperature on the equilibrium concentrations of the major products. At high temperature, ethane concentration decreases slightly, with a corresponding increase in hydrogen. However, it is of interest to note that the effect of temperature on the other products is very small through this temperature range.

Figure 4.57 The Effect of Temperature on Composition of the Major Compounds at Equilibrium, assuming Methane is not one of the Major Products

CHAPTER 5

CONCLUSIONS

The following conclusions can be drawn from the results obtained in this kinetic study of single stage coal gasification to hydrocarbon (HC) gases high in C_2 - C_4 hydrocarbons.

1. It was observed that the direct conversion of coal to HC gases involves two steps. The first step is thermal cleavage of the coal structure to produce liquids with small amounts of gases and coke. The second step is conversion of liquids to gases. Coal to liquids occurs very rapidly and was completed within 10 minutes. Liquids to gases is the rate-determining step of the overall process.

2. The conversion of liquids to gases was observed to follow first order kinetics. The first order kinetics treatment of the data by isothermal approximation gave an apparent activation energy of approximately 23 kcal/mol. The first order kinetics treatment of the data by a more rigorous non-isothermal method gave an activation energy of 26 kcal/mol.

3. The quantity of HC gases produced directly from coal reached a constant value of about 10% of the dmmf coal at a reaction time of 10 minutes. Most of the HC gases were produced from the liquids.

4. The study of model compounds shows that conversion of liquids to HC gases proceeds through a carbonium ion mechanism, and this accounts for the production of C_2 - C_4 gases. Liquid to gases occurs by a catalytic hydrocracking reaction.

5. No decrease in coal conversion and gas conversion were observed using coal-derived liquid as the major part of the hydrogen-donor solvent. This means that coal-derived liquids can be used in lieu of tetralin as a hydrogen-donor solvent.

6. The product distribution predicted by the thermodynamic calculations is very different from what is observed in the experiments. This indicates that in the experiments which produced high yields of C_2 , C_3 , and C_4 hydrocarbons, the reaction is terminated long before equilibrium is achieved. Therefore, the operation of the process for production of high yields of C_2 - C_4 hydrocarbons directly from coal is very strongly kinetically controlled, and time in the reactor is an extremely important parameter.

7. The calculation results indicate that, in the presence of hydrogen, the relative stability of the compounds included in the calculations follow the order:

Methane >> Ethane > Single-ring Compounds >> Two-ring Compounds >
Propane > Gas Olefins

REFERENCES

1. Gates, B. C., Katzer, J. R. and Schuit, G. C. A., Chemistry of Catalytic Processes. McGraw-Hill Book Company, New York, 1979.
2. Greensfelder, B. S., Voge, H. H. and Good, G. M., "Catalytic and Thermal Cracking of Pure Hydrocarbons," Ind. Eng. Chem. (1949), 41, 2573.
3. Archibald, R. C., Greensfelder, B. S., Holzman, G. and Rowe, D. H., "Catalytic Hydrocracking of Aliphatic Hydrocarbons," Ind. Eng. Chem. (1960), 52, 745.
4. Beuther, H. and Larson, O. A., "Role of Catalytic Metals in Hydrocracking," Ind. Eng. Chem., Proc. Des. Develop. (1965), 4, 177.
5. Flinn, R. A., Larson, O. A. and Beuther, H., "The Mechanism of Catalytic Hydrocracking," Ind. Eng. Chem. (1960), 52, 153.
6. Langlois, G. E. and Sullivan, R. F., "Chemistry of Hydrocracking.", Refining Petroleum For Chemicals, American Chemical Society, Washington. D. C., (1970), p. 38-67.
7. Sullivan, R. F., Egan, C. J. and Langlois, G. E., "Hydrocracking of Alkylbenzenes and Polycyclic Aromatic Hydrocarbins on Acidic Catalysts. Evidence for Cyclization of the Side Chains," J. of Catalysis (1964), 3, 183.
8. Wiser, W. H., Anderson, L. L., Qader, S. A. and Hill, G. R. "Kinetic Relationship of Coal Hydrogenation, Pyrolysis and Dissolution," J. Appl. Chem. Biotechnol. (1971), 21, 82-86.

9. Neavel, R. C., "Liquefaction of Coal in Hydrogen-Donor and Non-Donor Solvent," *Fuel* (1976), 55, 237.
10. Wiser, W. H., Hill, G. R. and Kertamus, N. J., "Kinetic Study of the Pyrolysis of a High-volatile Bituminous Coal," *Ind. Eng. Chem., Proc. Des. Develop.* (1967), 6, 133.
11. Wiser, W. H., "A Kinetic Comparison of Coal Pyrolysis and Coal Dissolution," *Fuel* (1968), 47, 475.
12. Nelson, W. L., Petroleum Refinery Engineering. McGraw-Hill, New York, 1958.
13. Qader, S. A. and McOmber, D. B., "Conversion of Complex Aromatic Structures to Alkylbenzenes.", *A. C. S. Div. of Petro. Chem.*, Vol. 20, (1975), p.479.
14. Kabe, T., Nitoh, O., Kawakami, A. Okuyama, S. and Yamamoto, K., "Liquefaction Mechanism of Wandoan Coal using Tritium and C Tracer Methods. 3. Hydrocracking of Wandoan Coal Liquid," *Fuel* (1989), 68, 178.
15. Skowronski, R. P., Ratto, J. J., Goldberg, I. B. and Heredy, L. A., "Hydrogen Incorporation during Coal Liquefaction," *Fuel* (1984), 63, 440.
16. Ratto, J. J., Heredy, L. A. and Skowronski, R. P., "An Isotopic Study of the Role of a Donor Solvent in Coal Liquefaction.", Coal Liquefaction Fundamentals, ACS Symposium Series 139, American Chemical Society, Washington, D. C., (1980), p. 347-370.
17. Benjamin, B. M., Raaen, V. F., Maupin, P. H., Brown, L. L. and Collins, C. J., "Thermal Cleavage of Chemical Bonds in Selected Coal-Related Structures," *Fuel* (1978), 57, 269.

18. Petrakis, L. and Grandy, D.W., "Electron Spin Resonance Spectrometric Study of Free Radicals in Coals," Anal. Chem. (1978), Vol.50, NO.2, 303.
19. Silbernagel, B. G., Gebhard, L. A. and Dyrkacz, G. R., "ESR of Carbon Radicals in Isolated Coal Macerals," Personal Communication with Dr. Wiser, W. H., (1983),
20. Grandy, D. W. and Petrakis, L., "E.S.R. Investigation of Free Radicals in Solvent-Refined-Coal Materials," Fuel (1979), 58, 239.
21. Collins, C. J., Raaen, V. F., Benjamin, B. M. and Kabalka, G. W., "Carbon-Carbon Cleavage During Asphaltene Formation," Fuel (1977), 56, 107.
22. Benjamin, B. M., "Pyrolysis of 1,2-Diphenylethane in the Presence of Tetralin," Fuel (1978), 57, 378.
23. Petrakis, L. and Grandy, D. W., "Free Radicals in Coals and Coal Conversion. 2. Effect of Liquefaction Processing Conditions on Formation and Quenching of Coal Free Radicals," Fuel (1980), 59, 227.
24. Yoon, W. L., Lee, H. T., Lee, I. C., Choi, I. S. and Lee, W. K., "Investigation of Effect of Solvent Quality on Indonesian Subbituminous Coal Liquefaction under Short Contact Time Conditions," Fuel (1990), 69, 962.
25. Vernon, L. W., "Free Radical Chemistry of Coal Liquefaction: Role of Molecular Hydrogen," Fuel (1980), 59, 102.
26. Anderson, L. L., Chung, K. E., Pugmire, R.J. and Shabtai, J., "Characteristics of Coal-Derived Liquids from Different Processes: Relationships to Coal Structure," New Approaches

in Coal Chemistry ACS Symposium Series No. 169, (1981),
223.

27. Whitehurst, D. D., Mitchell, T. O. and Farcasiu, M., Cla. Liquefaction. The Chemistry and Technology of Thermal Processes. Academic Press, New York, 1980.
28. Shah, Y. T., Reaction Engineering in Direct Coal Liquefaction. Addison-Wesley Publishing Company, London, 1981.

APPENDIX A**ORIGINAL KINETIC DATA**

440°C, 1800 psia

Rx Time	4 (min)	7 (min)	10 (min)	20 (min)	30 (min)	40 (min)	50 (min)	60 (min)
Cat (g)	6.2386	6.2184	6.2619	6.2271	6.2430	6.2408	6.2495	6.2537
Coal (g)	4.4782	3.7180	4.3619	4.4412	4.5474	4.3644	3.9518	4.6133
Tetralin (g)	13.0884	11.5199	12.7259	12.9795	13.1390	12.9187	13.0877	13.5378
Gas (g)	0.3650	0.3935	0.6096	0.7769	0.8620	0.8801	0.858	1.1069
Liquid (g)	15.4001	13.4816	14.7894	15.1632	15.4555	15.0317	15.001	15.8568
Solid (g)	1.8014	1.3682	1.6888	1.4184	1.3689	1.3713	1.1805	1.1874
Total Con. (%)	66.58	70.56	68.26	75.81	77.85	76.39	78.11	82.71
Gas Con. (%)	9.08	11.79	17.09	19.48	21.11	22.46	24.18	26.73
Liquid Con. (%)	57.50	58.77	51.17	56.33	55.83	53.93	54.85	55.98
C1 (%)	14.81	20.03	22.56	25.99	20.89	26.76	24.11	19.67
C2 (%)	18.91	23.10	25.13	24.98	19.92	24.47	22.19	16.92
C3 (%)	40.69	33.24	30.89	29.07	47.87	27.83	31.21	44.08
C4 (%)	25.58	23.63	21.41	19.96	11.31	20.94	22.48	19.32

455°C, 1800 psia

Rx Time	4 (min)	7 (min)	10 (min)	20 (min)	30 (min)	40 (min)	50 (min)	60 (min)
Cat (g)	6.2330	6.1511	6.2508	6.2116	6.2388	6.2640	6.2361	6.2291
Coal (g)	4.5981	4.5969	4.4793	4.1898	4.5129	4.8723	4.5566	4.0329
Tetralin (g)	13.5244	13.5379	13.0979	12.8088	13.4895	13.0170	13.2237	12.5424
Gas (g)	0.4590	0.7165	0.9088	0.8750	1.0044	1.1468	1.1970	1.2243
Liquid (g)	15.9987	15.9807	15.2271	14.9992	15.7909	15.3510	15.3349	14.1926
Solid (g)	1.6648	1.4376	1.4413	1.2244	1.2071	1.3915	1.2484	1.1584
Total Con. (%)	71.5	76.55	75.54	79.59	81.59	79.57	80.87	79.39
Gas Con. (%)	11.12	17.36	22.60	22.72	24.79	26.22	29.26	33.81
Liquid Con. (%)	59.93	59.19	52.94	56.87	56.80	53.35	51.61	45.58
C1 (%)	21.46	24.16	24.94	24.23	25.64	27.82	27.25	26.94
C2 (%)	25.63	28.70	28.15	25.14	25.37	25.14	25.20	24.76
C3 (%)	31.13	28.58	28.83	30.87	28.92	28.57	27.57	27.26
C4 (%)	21.77	18.56	18.08	19.75	20.07	18.47	19.99	21.04

470°C, 1800 psia

Rx Time	4 (min)	7 (min)	10 (min)	20 (min)	30 (min)	40 (min)	50 (min)	60 (min)
Cat (g)	6.2466	6.2575	6.2412	6.2368	6.2495	6.2486	6.2413	6.2479
Coal (g)	4.5220	4.5339	4.5875	4.4806	4.6839	4.5169	4.6006	4.4776
Tetralin (g)	13.2116	13.1392	12.9616	13.1853	13.5319	12.9891	13.2335	12.9913
Gas (g)	0.5034	0.6362	1.007	1.1553	1.2401	1.4431	1.4975	1.6825
Liquid (g)	15.5682	15.3733	14.9470	15.0346	15.7346	14.7625	14.9899	14.4224
Solid (g)	1.6620	1.6636	1.5951	1.4760	1.2411	1.3004	1.3467	1.3640
Total Con. (%)	70.65	70.51	72.65	74.69	81.87	79.32	78.78	77.45
Gas Con. (%)	12.40	15.63	24.45	28.72	29.49	35.58	36.26	41.85
Liquid Con. (%)	58.05	54.88	48.20	45.97	52.38	43.74	42.52	35.60
C1 (%)	21.80	23.34	26.35	26.18	26.79	28.68	27.98	28.38
C2 (%)	24.85	27.04	26.84	26.99	25.45	27.45	26.89	24.93
C3 (%)	30.72	29.62	28.83	30.14	28.57	26.67	27.94	27.99
C4 (%)	22.62	20.00	17.97	16.68	19.20	17.20	17.19	18.70

485°C, 1800 psia

Rx Time	4 (min)	7 (min)	10 (min)	20 (min)	30 (min)	40 (min)	50 (min)	60 (min)
Cat (g)	6.2631	6.2467	6.2545	6.2371	6.2414	6.2305	6.2395	6.2477
Coal (g)	4.7276	4.6439	3.6620	4.5092	4.5415	4.6147	4.6890	4.6752
Tetralin (g)	13.7194	13.4922	13.5474	13.1156	13.2394	13.3854	13.5527	13.5173
Gas (g)	0.6748	1.1190	0.9043	1.5282	1.6801	2.0009	2.1380	2.2894
Liquid (g)	15.8157	15.5045	15.2025	15.1356	14.5577	14.5298	14.6683	14.6473
Solid (g)	1.9565	1.5126	1.1009	1.4642	1.5431	1.4694	1.4354	1.2558
Total Con. (%)	65.29	75.10	77.90	75.22	73.51	75.92	77.29	81.46
Gas Con. (%)	15.60	26.84	27.50	37.74	41.20	48.29	50.79	54.54
Liquid Con. (%)	49.69	48.26	50.40	37.48	32.33	27.63	26.50	26.92
C1 (%)	23.40	24.54	23.94	26.44	24.43	27.75	28.03	26.74
C2 (%)	27.45	29.69	29.68	29.91	27.70	31.80	31.36	30.13
C3 (%)	39.96	29.12	39.02	28.78	32.98	26.77	26.52	27.66
C4 (%)	9.19	16.65	17.36	14.87	14.90	13.69	14.09	15.46

500°C, 1800 psia

Rx Time	4 (min)	7 (min)	10 (min)	20 (min)	30 (min)	40 (min)	50 (min)	60 (min)
Cat (g)	6.2448	6.2706	6.2374	6.2670	6.3317	6.2514	6.2404	6.2345
Coal (g)	4.3721	4.5091	4.3533	4.7690	4.3806	4.3084	4.4503	4.6588
Tetralin (g)	12.9351	13.2068	12.8817	13.4681	13.3951	13.0262	12.9693	13.6424
Gas (g)	0.9637	1.0288	1.2249	1.9382	1.9967	2.2346	2.5158	2.8152
Liquid (g)	14.8767	15.2250	14.6119	14.7656	14.4382	13.7476	13.5442	14.0386
Solid (g)	1.4632	1.4621	1.3983	1.5333	1.3408	1.3524	1.3596	1.4474
Total Con. (%)	74.11	75.27	75.61	75.57	77.29	76.42	77.35	76.78
Gas Con. (%)	24.64	25.41	31.34	45.27	50.77	57.77	62.97	67.31
Liquid Con. (%)	49.47	49.86	44.27	30.30	26.52	18.65	14.38	9.47
C1 (%)	21.41	21.65	27.48	23.64	26.71	27.19	28.20	25.43
C2 (%)	27.02	26.80	29.37	27.48	32.04	31.23	32.78	31.26
C3 (%)	31.88	32.08	28.40	29.12	27.36	28.01	27.94	28.04
C4 (%)	19.68	19.45	14.76	19.75	13.87	13.61	11.07	15.26

END

**DATE
FILMED**

7 / 15 / 93