ASSESSMENT OF COAL LIQUIDS AS REFINERY FEEDSTOCKS

**Prepared for
U.S. Department of Energy
Pittsburgh Energy Technology Center**

**Originally Prepared by
P. Zhou and S.N. Rao
November 1990**

**Revised by
P. Zhou
Burns and Roe Services Corporation**

February 1992

EXECUTIVE SUMMARY

The R&D of direct coal liquefaction has reached such a stage that current two-stage processes can produce coal liquids with high yields and improved quality at a reasonable cost. To fully realize the potential value, these coal liquids should be refined into high-value liquid transportation fuels. The purpose of this study is to assess coal liquids as feedstocks to be processed by modern petroleum refining technologies.

After the introduction, Section 2.0 summarizes ASTM specifications for major transportation fuels: gasoline, jet fuel, and diesel fuel, which serve as a target for coal-liquid refining. A concise description of modern refining processes follows with an emphasis on the requirements for the raw materials. These provide criteria to judge the quality of coal liquids as a refinery feedstock for the production of marketable liquid fuels.

Section 3.0 surveys the properties of coal liquids produced by various liquefaction processes. Compared with typical petroleum oils, the current two-stage coal liquids are:

- light in boiling range and free of resids and metals
- very low in sulfur but relatively high in oxygen
- relatively low in hydrogen and high in cyclics content
- essentially toxicologically inactive when end point is lower than 650°F, particularly after hydroprocessing.

Despite these characteristics, the coal liquids are basically similar to petroleum. The modern refining technology is capable of processing coal liquids into transportation fuels meeting all specifications, and hydroprocessing is obviously the major tool. The

important point is the determination of a reasonable product slate and an appropriate refining scheme.

The research results on coal-liquid refining documented in the past two decades were thoroughly reviewed and classified into three refining schemes as discussed in Sections 4.0 through 7.0. They are:

- Refining of coal liquid fractions after they are distilled from the crude coal Liquid.
- Hydrotreating of total coal liquids, and then distilling them into products.
- Hydrocracking of total coal liquids and separating them into products.

Most of the studies were done on coal liquids obtained from early stages of liquefaction process development. However, major conclusions drawn from these studies are applicable at least qualitatively to the refining of current two-stage liquids, since all coal-derived liquids bear fundamental similarity in composition and property.

Based on the experimental and test results accumulated to date, the quality of the liquid fuels that can be obtained from coal liquids is as follows:

Gasoline. The naphtha yield from two-stage coal liquids ranges from 20 wt% to 28 wt%. The raw naphtha contains 50-68 vol% of naphthenes and 7-22 vol% of aromatics. It has an octane number in the range of 70-83, and is an excellent source for gasoline production. Its high oxygen and nitrogen content is the major cause of fuel instability, and mild hydrotreating is required to produce a premium gasoline component for a refinery gasoline pool. After hydrotreatment, the coal naphtha is also a superior reformer feedstock to make high octane (95-100) gasoline with high reformat yields and a net production of hydrogen. Gasoline appears to be the most

profitable fuel product from coal liquids, and its yield can be maximized by hydrocracking coal-derived distillates heavier than naphtha (so called all-gasoline-mode of operation).

Jet Fuels. The kerosene fraction of two-stage coal liquids contains around 40-50 vol% of aromatics, and the low API gravity (~ 25) and smoke point (~ 10 mm) are two major obstacles for jet fuel production. High-severity hydrotreating is necessary for manufacturing coal-derived jet-fuels, and the success depends on the selection of suitable feedstocks and process parameters. Hydrocracking a proper coal distillate with an appropriate recycle cut point seems to be an efficient way to maximize jet fuel production. The coal-derived jet fuels are characterized by excellent cold-weather property and high volumetric heat value.

Diesel Fuels. The middle distillates from two-stage liquids contain high percentages of aromatics (up to 80 vol%), which are reflected in low cetane numbers (~ 20 -25). The heteroatoms are the cause of instability. A distillate of proper boiling range, after hydrotreating under medium-to-moderate severity and with the assistance of appropriate additives, can meet the specifications for light diesel fuels.

The gasoline-diesel product slate and all-gasoline-mode of production appear to be two realistic strategies for coal liquid refining. The manufacture of jet fuels from coal liquids is a difficult task and more investigation is needed. Tailoring the coal-derived jet fuels either as high-density jet-fuels or as a high-volumetric-heating-value range-extender component for jet-fuel blending, is advisable.

Regarding the three refining schemes mentioned above, total-coal-liquid hydrotreating is not recommended due to:

- difficulty in hydrotreating. The high end point of the total coal liquid makes its hydrotreating much more difficult and less efficient than hydrotreating of individual fractions.
- lack of selectivity and flexibility. The total coal liquid has to be hydrotreated under the highest severity required by one specific fraction and other fractions are thus over-hydrogenated, or vice versa.
- lower product quality. The multi-ring aromatics in the total coal liquid, which are outside the range of jet fuel or diesel fuel fractions, are also hydrogenated. The resultant cyclic compounds, which have lower boiling points than their precursors, enter the product fractions, thus lowering the fuel quality.

Hydrocracking of total coal liquids has similar disadvantages, but perhaps to a lesser extent. Therefore, separate refining of raw (or straight-run) coal-liquid fractions -- as petroleum has been processed in refineries for decades -- is the preferred scheme. This refining scheme has flexibility in product slate composition, selectivity in processing severity for different products, and better product quality.

Recommendations are made in Section 8.0 for systematic refining studies on two-stage coal liquids, paying special attention to the cut points of various coal liquid fractions, including an oxygen-rich fraction (350-450°F) for phenolics extraction. Engine tests for coal-derived gasoline and diesel fuel products are suggested. Economic studies on coal-liquid refining schemes, product slates, and refining process viabilities are strongly recommended. Further studies on physical and thermodynamic properties to develop specific correlations for coal liquids are highly justified.

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Objective	2
2.0 PETROLEUM REFINING PROCESSES AND PRODUCT REQUIREMENTS	3
2.1 Product Specifications	3
2.1.1 Automotive Gasoline	4
2.1.2 Aviation Gasoline	4
2.1.3 Aviation Turbine (Jet) Fuels	5
2.1.4 Diesel Fuel Oils	6
2.1.5 Fuel Oils	6
2.1.6 Gas Turbine Fuel Oils	7
2.2 Related Licensed Refining Processes	8
2.2.1 Catalytic Hydrotreating	8
2.2.2 Catalytic Hydrocracking	9
2.2.3 Catalytic Reforming	12
2.2.4 Catalytic Cracking	13
3.0 QUALITY OF COAL LIQUIDS	15
3.1 Composition and Properties of Coal Liquids	15
3.2 Heteroatoms in Coal Liquids	18
3.3 Toxicology of Coal-Derived Liquids	21
3.4 Summary	23
4.0 REFINING SCHEMES FOR COAL LIQUIDS	25
5.0 REFINING OF RAW COAL LIQUID FRACTIONS	28
5.1 Light Naphtha	28
5.2 Naphtha	29
5.3 Kerosene Fraction	35
5.4 Diesel Fuel Fraction	37
5.5 Heavy Distillates	43
5.6 Summary	47

TABLE OF CONTENTS continued

	<u>Page</u>
6.0 HYDROTREATING OF TOTAL COAL LIQUIDS	49
6.1 Naphtha from Hydrotreated Coal Liquids	53
6.2 Jet Fuel Fraction from Hydrotreated Coal Liquids	55
6.3 Diesel Fuel Fraction from Hydrotreated Coal Liquids	58
6.4 Fuel Oil Fraction from Hydrotreated Coal Liquids	60
6.5 Two-Step Hydrotreating of High End-Point Coal Liquids	61
6.6 Summary	61
7.0 HYDROCRACKING OF TOTAL COAL LIQUIDS	64
8.0 CONCLUSIONS AND RECOMMENDATIONS	67
8.1 Properties of Coal-Liquids	67
8.2 Product Slate from Coal Liquids	68
8.3 Coal-Liquid Refining Technologies	69
8.4 Refining Scheme for Coal Liquids	70
8.5 Research Recommendations	72
REFERENCES	75

LIST OF TABLES

		<u>Page</u>
Table 1.	Detailed Requirements for Gasoline	86
Table 2.	Gasoline Antiknock Indexes and Their Application	87
Table 3.	Detailed Requirements for Aviation Gasolines	88
Table 4.	Detailed Requirements for Aviation Turbine Fuels	90
Table 5.	Primary Military Aviation Fuel Specification Requirements . .	92
Table 6.	Average Jet Fuel Properties in the United States	93
Table 7.	Detailed Requirements for Diesel Fuel Oils	94
Table 8.	Detailed Requirements for Fuel Oils	95
Table 9.	Detailed Requirements for Gas Turbine Fuel Oils	97
Table 10.	Trace Metal Limits of Fuel Entering Turbine Combustors . . .	99
Table 11.	Residua and Heavy Oils Hydrotreating Processes	100
Table 12.	Distillate Hydrotreating Processes	101
Table 13.	Hydrocracking Processes	102
Table 14.	Catalytic Reforming Processes	104
Table 15.	Catalytic Cracking Processes	105
Table 16A.	Properties of Coal Liquids from Single-Stage Processes	107
Table 16B.	Properties of Coal Liquids from Two-Stage Processes	109
Table 17.	Properties of Crude Petroleum and Shale Oil	114
Table 18.	Comparison of Elemental Composition of H-Coal Fractions from Illinois No. 6 with Petroleum Fractions	115
Table 19.	Comparison of Typical Petroleum Fractions with Wilsonville Fractions	115
Table 20.	Light Naphtha from Illinois No. 6 ITSL	116
Table 21.	Properties of Raw Naphtha Fractions from Single-Stage Liquefaction Coal Liquids	117
Table 22A.	Properties of Raw Naphtha Fractions from Two-Stage Liquefaction Coal Liquids	119
Table 22B.	Properties of Straight-Run Naphthas from Recent Wilsonville CC-ITSL Runs	120
Table 23.	Compositional Analyses of Coal-Derived Naphthas	121
Table 24.	Hydrotreating of H-Coal Naphtha	122
Table 25A.	Properties of Raw Kerosene Fraction from Coal Liquids	123
Table 25B.	Properties of Jet Fuel Fraction from Two-Stage Coal Liquid	124
Table 26.	Properties of the 250°F-600°F Jet Fuels from Hydrotreated 600°F Redistilled Texas Lignite EDS Coal Liquids	125
Table 27.	Gas Turbine Test Fuels	126
Table 28A.	Properties of Raw Middle Distillates from Coal Liquids	127
Table 28B.	Properties of Diesel Fuel Fractions from Coal Liquids of Recent CC-ITSL Process	128

LIST OF TABLES
continued

	<u>Page</u>
Table 28C. Hydrotreating of Coal-Derived Middle Distillate	129
Table 29. Properties of Raw Heavy Distillates from Coal Liquids	130
Table 30. Hydrocracking of H-Coal Gas Oil	131
Table 31. Hydrotreating Tests of Coal Liquids	132
Table 32. Hydroupgrading of SRC-II Coal Liquid	133
Table 33. High Severity Hydrotreating Yields and Hydrogen Consumptions	134
Table 34. High Severity Hydrotreating Product Inspections	134
Table 35. Typical Naphthas from Hydrotreating of Coal-Derived Oils . .	135
Table 36. Properties of Selected Naphthas Derived from Shale Oil and Wyodak H-Coal	135
Table 37. Properties of Naphtha Products from SRC-II Liquids Hydrotreated at Intermediate and High Severities	136
Table 38. Composition of Naphtha Fractions from Eight Upgraded Coal Liquids	137
Table 39. Comparison of Kerosene Jet Fuel Products from Severely Hydrotreated Coal-Derived Oils with ASTM Jet A Specifications	138
Table 40. Representative 250°F-550°F Jet Fuels from Hydrotreated Coal Liquids	139
Table 41. Properties of Selected Jet Fuels Derived from Shale Oil and Wyodak H-Coal	139
Table 42. Jet Fuels from Hydrotreating and Hydrocracking Illinois ITSL Oil	140
Table 43. Detailed Analyses of Narrow-Boiling Fractions of Jet Fuel from Hydrotreated Wyodak ITSL Oil	141
Table 44. Detailed Analyses of Narrow-Boiling Fractions of Jet Fuel from Hydrotreated Wyodak CTSL Oil	142
Table 45. Group Analysis of Distillates from Upgraded TSL Coal Liquids	143
Table 46. Comparison of Severely Hydrotreated Coal Products with ASTM Diesel Fuel Specifications	144
Table 47. Properties of Selected Diesel Fuels Derived from Shale Oil and Wyodak H-Coal	145
Table 48. Properties of 250°F+ Fractions from ITSL Liquids	146
Table 49. Comparison of Moderately Hydrotreated Coal Oil Products with ASTM Specifications for Heating Fuel	147
Table 50. Detailed Analyses of Narrow-Boiling Fractions of Jet Fuel from Hydrotreated Illinois ITSL Oil	148
Table 51. Detailed Analyses of Narrow-Boiling Fractions of Jet Fuel from Hydrocracking of Hydrotreated Illinois ITSL Oil	149

LIST OF FIGURES

	<u>Page</u>
Figure 1. TBP Distillations for Arabian Light Crude, Shale Oil and Coal-Derived Liquids	150
Figure 2. TBP Distillations of Arabian Crudes and Coal-Derived Liquids	151
Figure 3. TBP Distillations of Coal Liquids	152
Figure 4. TBP Distillations of Coal Liquids	153
Figure 5. Hydrogen Content of Coal Liquid Fractions vs Boiling Range	154
Figure 6. Distribution of Heteroatom Content in H-Coal Fractions	155
Figure 7. Direct Oxygen Content vs Average Cut Temperature of Coal Liquids from Two Liquefaction Stages	156
Figure 8. Sulfur Level vs Average Cut Temperature of Coal Liquids from Two Liquefaction Stages	157
Figure 9. Total Nitrogen Content vs Average Cut Temperature of Coal Liquids	158
Figure 10. Basic Nitrogen Level vs Average Cut Temperature of Coal Liquids	159
Figure 11. Oxygen Distribution in CC-ITSL Coal Liquids	160
Figure 12. Hydrogen and Liquid Yield vs Octane for Upgraded Illinois No. 6 H-Coal Naphtha	161
Figure 13. Hydrogen and Liquid Yield vs Octane for Upgraded Illinois No. 6 SRC-II Naphtha	162
Figure 14. Hydrogen Consumption vs EDS Naphtha API Gravity Increase	163
Figure 15. C ₅ ⁺ Reformate Yield vs Octane Level for EDS Naphtha	164
Figure 16. Hydrogen Yield vs Octane Level for EDS Naphtha Reforming	165
Figure 17. Hydrotreating of Illinois No. 6 EDS Middle Distillate	166
Figure 18. Relationships of Cetane Number, Aromatics Concentration, and hydrogen Content of Coal-Derived Middle Distillates . .	167
Figure 19. Effect of Feedstock Hydrogen Content on Response to Fluid Catalytic Cracking (H-Coal Gas Oil)	168
Figure 20. Effect of Feedstock Hydrogen Content on Response to Fluid Catalytic Cracking (EDS Gas Oil)	169
Figure 21. C ₅ ⁺ Yield vs Product Aromatic Content	170
Figure 22. Product Nitrogen vs Hydrogen Consumption for Four Coal Liquids	171
Figure 23. Product Aromatic Content vs Hydrogen Consumption for Four Coal Liquids	172
Figure 24. Effect of Feed End Point on Catalyst Temperature for Hydrodenitrogenation of ITSL Oils	173
Figure 25. Effect of Aromatics on Smoke Point of Jet Fuels from Hydrotreated Coal-Derived Feed	174
Figure 26. Smoke Point of 250°F+ Jet Fuels from Different Hydrotreating Schemes	175

LIST OF FIGURES
continued

	<u>Page</u>
Figure 27. Effect of Aromatics on the Cetane Number of Diesel Fuels from Hydrotreated Coal-Derived Oils	176
Figure 28. Effect of Octyl Nitrate Cetane Number Improver on Two Coal-Derived Diesel Fuels	177
Figure 29. Yield-Octane Curve for H-Coal Hydrocrackate Platforming	178
Figure 30. Hydrocracking of Hydrotreated ITSL Oil-Effect of Recycle Cut Point on Yield and Smoke Point of 250°F + Jet Fuel Fraction	179
Figure 31. Effect of Boiling Range on Smoke Point of Narrow- Boiling Fractions of Hydrocracked ITSL Oil	180
Figure 32. Refining Scheme for Coal Liquids	181

ASSESSMENT OF COAL LIQUIDS AS REFINERY FEEDSTOCKS

1.0 INTRODUCTION

1.1 Background

The production of liquid fuels from coal is one of the lead missions of the Pittsburgh Energy Technology Center. R&D in the direct liquefaction of coal has progressed steadily and has decreased the cost of production of coal-derived liquid fuels remarkably in the 1980s.

In the early stages of coal liquefaction technology development coal-derived liquids were considered potential boiler fuels. It was soon realized that in order to attain their full value, products from direct liquefaction would have to be refined and upgraded to quality liquid fuels for both transportation and home heating uses. The coal liquefaction products soon became candidates as refinery feedstocks [1]. In the meantime, substantial improvements were achieved in coal liquefaction technology through two-stage liquefaction processes. This resulted in the production of coal liquids with virtually no resid or metals and low sulfur and nitrogen content, which make them prospective refinery feedstocks.

The petroleum industry has undergone tremendous expansion and changes in the past few decades. Enormous increases in the size of process units, new catalytic processes, shifting product demands, and new sources of feedstocks from tar sands, heavy oils, and oil shales have made present-day technology and economics of petroleum refining very complex and sophisticated. Theoretically, modern refining technology is capable of processing almost any liquid hydrocarbon feedstock to yield desired products. Coal liquids, when needed to supplement crude oil supplies, will be processed in units similar to those in petroleum refineries. The basic requirement, however, is the cost-effectiveness of manufacturing products that meet market

demand and strict specifications for commercial liquid fuels. As a result, the coal liquids produced by state-of-the-art coal liquefaction technology must be assessed relative to the specifications for marketable fuel products and to the requirements for feedstocks to various units in present-day refineries.

1.2 Objective

The objective of this report is to evaluate the quality and properties of liquid products from direct liquefaction processes relative to the specifications for petroleum fuel products and to the feed requirements for refinery processes that can be used to upgrade coal liquids. The report will attempt to determine the refinability of coal liquids and the suitability of various existing refining processes to produce commercial products from coal liquids. These processes include hydrotreating, hydrocracking, catalytic cracking, and naphtha reforming.

2.0 PETROLEUM REFINING PROCESSES AND PRODUCT REQUIREMENTS

Modern direct liquefaction processes are designed to produce coal liquids to be refined eventually to make transportation fuels that are currently manufactured primarily from petroleum. These fuels from coal liquids must meet market demand and quality requirements set forth by stringent product specifications. A detailed analysis of these specifications is therefore of vital importance to determine the gap between product quality requirements and the coal liquid properties. Thus, related fuel specifications and pertinent refining processes are reviewed in following subsections.

2.1 Product Specifications

The American Petroleum Institute conducted a survey of petroleum refineries and petrochemical plants, which revealed that over 2,000 products are made to meet a huge variety of specifications [2,3]. Generally, the products that dictate refinery design are relatively few in number, and the fundamental refinery processes are based on the large-quantity products such as gasoline, jet fuel, and diesel fuel.

Although lubricating oils and greases are very high-value products, they represent only a small fraction in terms of volume of refinery products. Moreover, based on available analytical data, coal-derived liquids are not suitable for the manufacture of lube oils. Therefore, only transportation fuels and home heating fuels, as a replacement for petroleum products, are considered as reasonable products to be manufactured from coal liquids. Since kerosene is an obsolete product with little chance of revival, discussion on kerosene is limited to its use as a jet fuel fraction.

2.1.1 Automotive Gasoline (ASTM Designation: D439-88b)

Detailed requirements for automotive gasoline are listed in Table 1. These standard specifications are a guide in establishing the requirements of gasoline for ground vehicles equipped with spark-ignition engines. A specification that encompasses all fuels for automotive spark-ignition engines, including blends of gasoline with oxygenates such as alcohols and ethers, is under development, and appears as Specification D4814.

The major performance requirements for gasoline are the following:

1) Volatility is varied for seasonal climatic changes by providing five volatility classes of gasoline, which correspond to seasonal and geographical distributions. This requirement is usually met by blending of light ends, which are always available in the refinery.

2) Antiknock index levels, defined as the average of the Research Octane Number (RON) and Motor Octane Number (MON), and their application are set forth in Table 2. For gasolines derived from coal liquids, especially after reforming, this requirement can be met very easily.

2.1.2 Aviation Gasoline (ASTM Designation: D910-88a)

This specification defines specific types of aviation gasoline for civil use. Three grades of aviation gasoline are provided, known as Grade 80, 100, and 100LL. Aviation gasoline grades are also identified by two numbers separated by a hyphen (-) or sometimes a slant line (/). The first number is called the "lean mixture rating" and the second the "rich mixture rating": 80-87 (80/87), 100-130 (100/130), and 100-130LL (100/130LL). Numbers below 100 are octane numbers, while numbers above 100 are performance numbers. At 100, octane number and performance

number are equal. The detailed requirements for aviation gasoline are listed in Table 3.

2.1.3 Aviation Turbine (Jet) Fuels (ASTM Designation: D1655-88a)

Aviation gas turbine fuels, or jet fuels, are the most critical products, in terms of quality, produced by the refining industry, although they represent only about 7% of the refinery products in the U.S.

Standard Specification D1655-88a defines the specific types of aviation turbine fuels for civil use. It does not include all fuels suitable for aviation turbine engines. Certain equipment or conditions of use may permit a wider or require a narrower range of characteristics than is shown in Table 4.

Aviation turbine fuel, except as otherwise specified herein, shall consist of blends of refined hydrocarbons derived from petroleum, natural gasoline, or blends thereof with synthetic hydrocarbons.

Three types of aviation turbine fuels are provided for civil use:

Jet A and Jet A-1 represent two grades of high flash point kerosene-type jet fuels that differ in freezing point. Jet A-1 requires a freezing point 7°C lower than Jet A. Jet B is a relatively wide boiling range volatile distillate, which is characterized with a boiling range between 150°F and 480°F.

The aviation turbine fuel shall be free of undissolved water, sediment, and suspended matter. The odor of the fuel should not be nauseating or irritating. No substance of known dangerous toxicity under usual conditions of handling and use can be present, except as permitted herein.

In 1951, the U.S. Air Force standardized aircraft operation on JP-4 jet fuel to optimize performance and availability. This fuel can be characterized as a "wide-cut" fuel. Some of the most important chemical and physical properties of JP-4 are depicted in Table 5. The commercial specification for the wide-cut fuel is designated as Jet B and is similar, with a few minor exceptions, to JP-4. The properties of JP-4 are required for high-altitude operations and low-ambient-temperature conditions at certain air bases. For operations where JP-4 may not be available, a kerosene-type jet fuel, Specification JP-8, may be used. The commercial equivalent for JP-8 is Jet A-1. The basic differences between Jet A-1 and JP-8 are the additives required for military operations. The Navy fuel specification is JP-5, which is identical to JP-8, except for a minimum flash point of 140°F, for safety on aircraft carriers. Table 6 carries the average jet fuel properties in the U.S.

The possibility of modifying jet fuel specification has been the objective of various research efforts over the years. Allowing the jet fuels to become more cyclic, thereby increasing fuel density, offers promise as a range extender for aircraft. This so-called high-density jet fuel is often referred to as JP-8X. It has the same volatility as JP-8 and Jet A-1, essentially a kerosene. Comparing the volumetric heating value of JP-8X with that of conventional JP-4, the energy increase could be more than 10%.

2.1.4 Diesel Fuel Oils (ASTM Designation: D975-88)

This specification covers three grades of diesel fuel oils suitable for various types of diesel engines.

Standard Specification D975 (Table 7) is intended as a statement of permissible limits of significant fuel properties used for specifying the wide variety of commercially available diesel fuel oils. The properties of these commercial fuel oils depend upon the refining practices employed and the nature of the crude oils from

which they are made. Distillate fuel oils, for example, may be produced within the boiling range of 150°C and 400°C (300°F and 755°F), with many possible combinations of various properties such as volatility, ignition quality, viscosity, and other characteristics.

2.1.5 Fuel Oils (ASTM Designation: D396-86)

This specification covers grades of fuel oil intended for use in various types of fuel-oil-burning equipment under various climatic and operating conditions. Standard Specification D396 divides fuel oils into grades based upon the types of burners for which they are suitable. It places limiting values on several of the properties of the oils in each grade, as shown in Table 8.

The grades of fuel oil specified herein shall be homogeneous hydrocarbon oil, free from inorganic acid, and free from excessive amounts of solids or fibrous foreign matter likely to make frequent cleaning of suitable strainers necessary. All grades containing residual components shall remain uniform in normal storage and not separate by gravity into light and heavy oil components outside the viscosity limits for the grade.

2.1.6 Gas Turbine Fuel Oils (ASTM Designation: D2880-88)

This specification covers the selection of fuels for gas turbines, except those used in aircraft.

The various grades of gas turbine fuel oil shall conform to the limiting requirements shown in Table 9. As noted in the supplementary footnotes to this table, the requirements for Grade Nos. 1-GT and 2-GT conform in most respects to corresponding Grade Nos. 1 and 2 fuels in Specification D396 (fuel oils), and to Grade Nos. 1-D and 2-D in Specification D975 (diesel fuels). The viscosity range of Grade

Nos. 3-GT and 4-GT fuels brackets the Grade Nos. 4, 5, and 6 of D396 and Grade No. 4-D of D975. It is the intention that fuels meeting Specification D396 and D975 requirements may also be listed under these specifications provided they meet the requirements listed in Table 9.

The particular significance of trace metals in gas turbine fuels is noted and upper limits of trace metals are recommended for various grades of gas turbine fuels (Table 10).

2.2 Related Licensed Refining Processes

Based on the information regarding coal liquid property and coal liquid refining accumulated in the past two decades, it is predictable that various hydroprocessing techniques will be principal refining tools for coal liquids derived from direct liquefaction. Pertinent technologies are described as follows.

2.2.1 Catalytic Hydrotreating

Hydrotreating or hydrotreating is applied to a wide range of feedstocks, from naphtha to reduced crude, in petroleum refineries. Objectionable elements removed by hydrotreating include sulfur, nitrogen, oxygen, halides, and trace metals. When the process is used specifically for sulfur removal, one of the main concerns in petroleum refineries, it is usually called hydrodesulfurization or HDS. Under certain circumstances, hydrogenation of unsaturated hydrocarbons may be another objective.

If nitrogen removal is a significant consideration, catalysts composed of nickel-cobalt-molybdenum or nickel-molybdenum compounds supported on alumina are more efficient. Nitrogen is generally more difficult to remove from hydrocarbon streams than is sulfur and any treatment that reduces nitrogen concentration to a satisfactory level will effectively eliminate excess sulfur. Nickel-containing catalysts usually

require activation by presulfiding with disulfide, mercaptans, or dimethyl sulfide before bringing them up to reaction temperature.

Although about 30 hydrotreating processes are available for licensing [4], most of them have essentially the same process flow for a given application. Some confusion may exist because of the many alternative processes that are available and because of the nomenclature that has been employed by the licensors.

The technical literature contains many references to processes that are reported to be suitable for the hydrodesulfurization of heavy oils and residue (Table 11) [5-18] as well as for distillates (Table 12) [19-28].

As shown in Tables 11 and 12, hydrotreating units designed for resids can handle feedstocks as heavy as 1050°F+, with Conradson carbon up to 28 wt%, sulfur up to 6 wt% and metals over 400 ppm. Distillate hydrotreating processes treat a wide variety of distillate feedstocks that may contain sulfur up to 3.6 wt% and nitrogen as high as 0.6 wt%. Two-stage coal liquefaction liquids can meet these standards easily. There are no clear limits on oxygen content for hydrotreating feedstocks, which merit close attention as far as coal liquids are concerned.

2.2.2 Catalytic Hydrocracking

The hydrocracking process was commercially developed by I.G. Farben Industrie in 1927 for converting lignite into gasoline and was brought to this country by ER&E in the early 1930s for use in upgrading petroleum feedstocks and products. Improved catalysts have been developed that permit operation at relatively low pressures, and a shift in demand has necessitated conversion of higher boiling petroleum materials to gasoline and jet fuels. Relatively few operations offer the versatility of catalytic hydrocracking.

In a modern refinery, catalytic cracking and hydrocracking work as a team. The catalytic cracker takes the more easily cracked straight-run gas oils as charge stocks, while the hydrocracker uses cycle oils and coker distillates as feed [29]. Highly aromatic feeds (such as cycle stocks from catalytic cracking) are very refractory, and using them as a component for fuel blending is limited as they burn with a smoky flame. But they make excellent feedstocks for hydrocracking.

In addition to middle distillates and cycle oils used as feed for hydrocracking units, it is also possible to process residual stocks and reduced crude by hydrocracking. This usually requires a different technology such as ebullated-bed technology. Thus, the hydrocracking operations can be broken into two general types of processes: those which process distillate feeds and those which process residual materials. These processes are similar and some of the licensed processes can be adapted to operate on both types of feedstocks. There is a major difference, however, between the two processes in regard to the type of catalyst and operating conditions.

A number of hydrocracking processes are available for licensing, as described in Table 13 [30-51].

Most of the hydrocracking catalysts consist of a crystalline mixture of silica-alumina, which serves as the cracking base, with a small amount of uniformly distributed transition metals contained within the crystalline lattice. The metals vary with the manufacturer. Those in most common use are platinum, palladium, tungsten oxide, and nickel [30], as well as molybdenum.

Different hydrocracking catalysts are susceptible, to a different extent, to poisoning by metallic salts, oxygen-, nitrogen-, and sulfur-compounds in the feedstock. The feedstock is first hydrotreated to saturate the olefins and remove the sulfur, nitrogen, and oxygen compounds. Certain metals are retained on the catalyst.

An increase in organic nitrogen content of the feed causes a decrease in conversion. For some types of hydrocracking catalysts, the presence of hydrogen sulfide in low concentrations inhibits the saturation of aromatic rings. This is beneficial when maximizing gasoline production as it conserves hydrogen and produces a higher octane product. However, hydrocracking in the presence of a small amount of hydrogen sulfide normally produces a low smoke point jet fuel. At high sulfide levels, corrosion of the equipment becomes important and the cracking activity of the catalyst is also affected adversely.

Many feedstocks have been processed successfully, such as vacuum gas oils (VGO's) of moderate to heavy qualities (50-70 wt% aromatics, 2-4 wt% S, 0.1-0.35 wt% N), and non-virgin feedstocks like pretreated pyrolysis fuel oil (>98 wt% polyaromatics). For some processes, a limit is set on the asphaltene content not to exceed 0.5 wt%. For some catalysts, run time may be decreased by irreversible poisoning caused by vanadium content in the feedstock, and therefore vanadium should be kept below 2.5 ppm for the Linde hydroconverter catalyst. Within the above limits, practically any feedstock can be fed [50].

In addition to the removal of the nitrogen and sulfur compounds and metals, it is also necessary to reduce the water content of the feed streams to less than 25 ppm. At the temperatures required for hydrocracking, steam causes the collapse of crystalline structure of the catalyst and the agglomeration of dispersed rare-earth atoms. The feed oxygen content may also be considered to affect the catalyst in a similar way. An exception to this is the Unicracking/JHC process, which can tolerate water contents as high as 400 to 500 ppm [42]. According to Unocal [52], the oxygen level of 2.7% in the Great Plains tar oil would be borderline acceptable, and the maximum allowable nitrogen level to the hydrocracker is about 5,000 ppm. If the oxygen level is too high, the resulting partial pressure of water vapor is deleterious and destroys the catalyst support. Unocal also specifies maximum particulates concentration in the 2-5 ppm range for its fixed bed operations.

2.2.3 Catalytic Reforming

The typical feedstocks to catalytic reforming are heavy straight-run naphthas (180°F-375°F), which have the following PONA analysis [30]:

Component	Vol%	
	Feed	Product
Paraffins	15-55	30-50
Olefins	0-2	0
Naphthenes	30-40	5-10
Aromatics	5-10	45-60

The active material in most reforming catalysts is platinum. Certain metals, hydrogen sulfide, ammonia, and organic nitrogen and sulfur compounds will deactivate the catalyst. Reformer catalysts require less than 0.5 wppm sulfur in the feed, or even lower into the range of 10 wppb. Not only sulfur but other contaminants such as water, nitrogen, oxygen, silica, phosphorus, and metals like copper, arsenic, and lead must be removed or reduced to very low levels in reformer reactor charge [53]. Normally, feeds are well hydrodesulfurized and stripped free of sulfur [54]. Fifty to 75 ppm of nitrogen in the naphtha feed would be the upper limit that most refineries could handle, and only when well blended with a more typical naphtha.

The process by which contaminants are reduced to acceptable concentrations in reformer feed is hydrotreating. The hydrotreater employs a cobalt-molybdenum catalyst to convert organic sulfur and nitrogen compounds to hydrogen sulfide and ammonia, which are then removed from the system with the unreacted hydrogen. The metals in the feed are retained by the hydrotreater catalyst acting as a guard bed for the reformer catalyst. Refiners consider it better to sacrifice a cobalt-moly or nickel-moly hydrotreating catalyst rather than to poison a bimetallic reforming catalyst.

Several major reforming processes are in use today as depicted in Table 14 [54-62]. Also available are some other commercial reformers, such as Rexforming (combination of Platforming and aromatics extraction), Hydroforming, Catforming, Ultraforming (licensed by Standard Oil of Indiana), Houdriforming and Iso-Plus Houdriforming (Houdry), Selectoforming, Hyperforming (moving bed), Thermoform Catalytic Reforming (Mobil, moving bed), and fluid-bed reforming [4,63].

2.2.4 Catalytic Cracking

This is the most important and widely used petroleum refining process for converting heavy oils into valuable gasoline and lighter products, with almost one million tons of oil processed per day in the U.S. [64].

The Thermoform Catalytic Cracking process (TCC) is representative of the moving-bed units and the Fluid Catalytic Cracker (FCC) is representative of the fluidized-bed units. Models II, III, and VI Fluid Catalytic Cracking units have long been known, and commercial catalytic processes are summarized in Table 15 [65-79].

Catalytic cracking of distillate feedstocks (gas oils usually have an average boiling point around 800°F) is the most common operation and has been practiced for a long time. However, the use of crackers for resids and asphalt-containing feedstocks increased dramatically in the early 1980s. The 1987 survey reported about 40% of U.S. FCC capacity to be resid cracking, with resid defined as containing over 5 LV% of 1000°F+ [80]. Conradson carbon of a few percent is usual and feedstocks with a Conradson carbon as high as 18% can be handled in resid cracking units.

There were not many units processing desulfurized feedstocks in the late 1970s and early 1980s, since then, however, desulfurization of high sulfur feeds, such as using hydrocracked feedstocks, has become common practice. In general, removing

65% to 75% of the sulfur does not profoundly improve the product yield pattern, and only deep desulfurization in combination with saturation of polyaromatic nuclei will significantly increase gasoline yield and reduce coke make [69,81]. The catalysts can tolerate feedstocks with a sulfur content up to 3%, and nitrogen contents ranging from 0.2% to 0.76% are not unusual. Metals content of a couple of hundred ppm is permissible for residue-processing crackers, while distillate crackers limit the metals content to a few ppm.

3.0 QUALITY OF COAL LIQUIDS

3.1 Composition and Properties of Coal Liquids

Properties of coal liquids derived from direct liquefaction were collected and summarized in Table 16A (single-stage processes [82-87]) and Table 16B (two-stage processes [85,87-95]), including data obtained from recent two-stage runs at Wilsonville facility.

Since none of the liquefaction processes has yet been applied commercially, properties of the liquefaction products may change as each process is developed and optimized. Moreover, for each process, yields and product distribution can vary appreciably depending on coal rank, operating conditions, distillation cut points, and amount of bottoms recycled. However, representative data were sought and gathered so that the data can be analyzed and trends can be reasonably assessed.

The coal liquids data in Tables 16A and B represent liquefaction products from different processes at different development stages. SRC-I contains essentially no distillate and can be regarded as a deashed, partially desulfurized coal rather than a coal oil. The other coal liquids are quite low-boiling. These coal liquids were obtained in various fairly well-developed processes, and they boil primarily in the naphtha and middle distillate range. Only a small portion boils above 700°F with virtually no resids (1000°F+).

The SRC-II, H-Coal, and EDS process liquids are representative of single-stage liquefaction products and are all quite similar. The few major differences that are observed could be due to any combination of the following factors: (1) differences in the liquefaction processes themselves, (2) differences among the feed coals, (3) differences in the distillation procedures, and (4) differences in storage and handling of the coal liquids.

The successful development of two-stage liquefaction (TSL) has been showing significant improvements in process efficiency, including increased distillate yield, reduced hydrogen consumption, and lower heteroatom content in liquid products. Data for Wilsonville two-stage coal liquids shown in Table 163 represent the recent achievements.

For comparison, properties of some crude petroleum and shale oils are listed in Table 17 [83,96,97].

Statistically, the proportions of the elements in petroleum vary over the following limits, compared with the ranges that modern two-stage coal liquids fall in:

	<u>Petroleum</u>	<u>Wilsonville Two-Stage Liquefaction Coal Liquids (After Run 251)</u>
Gravity, °API	11-33	16-36
Elemental analysis, wt%		
Carbon	83-87	85.5-87.5
Hydrogen	10-14	11.1-12.2
Sulfur	0.05-6.0	0.01-0.10
Oxygen	0.05-1.5	0.2-2.5
Nitrogen	0.1-2.0	0.1-0.5
H/C Atom Ratio	1.4-2.0	1.54-1.7
Metals, ppm	3-1000+	<10
Resid (1000°F +), wt%	16-58	0

The above comparison shows that the gravity and elemental compositions of coal liquids are comparable to those of petroleum, except for somewhat higher carbon content and lower hydrogen content. The heteroatom contents of the coal liquids are

well within the ranges for petroleum and in fact are close to the lower limits, except for oxygen. Specifically, comparing the data in Tables 16 and 17, coal liquids contain larger quantities of nitrogen and oxygen and less hydrogen than does Arabian light crude. However, the sulfur contents of these coal liquids (and shale oil also) are low compared to typical Middle Eastern crudes. In other words, when compared with typical sour petroleum, the coal liquids are light in boiling range, lower in sulfur, but slightly higher in nitrogen and oxygen. When compared with shale oil, coal liquid is lower boiling and contains about one-half of the nitrogen. A major difference between coal liquid and petroleum is the highly aromatic structure of the former and the absence of long paraffinic structures. Current coal liquids have H/C atom ratios of 1.5-1.7, which is significantly better than the H/C ratio of 1.0-1.2 reported for earlier processes [98].

Distillation curves of some coal liquids, crude petroleum, and shale oil are presented in Figures 1 and 2 [83,84]. The coal liquids contain very little high-boiling material compared with petroleum and shale oil because most of the high boilers are typically recycled in the liquefaction process and ultimately converted to lower-boiling products.

Although coal liquids are virtually alike, there are some significant quantitative differences among different coal liquids, particularly between the two-stage liquefaction products and the others. In general, the two-stage coal liquids contain a much larger middle distillate fraction (60-76 LV% 400- 700°F fraction) and less naphtha than single-stage liquids (~45 LV% 400-700°F fraction).

Coal rank also makes a difference. The coal liquids from subbituminous coals generally show a higher oxygen level, as compared with the bituminous coal liquids. They are also less cyclic and contain more N in the naphtha fraction. For instance, the subbituminous Clovis Point coal naphtha contains 32.6% paraffins, 50.5% naphthenes, and 17.0% aromatics, whereas the bituminous Illinois No. 6 naphtha

contains 15.9% paraffins, 60.7% naphthenes, and 23.4% aromatics. This result is indicative of the more paraffinic nature of subbituminous coal. The total distillates and gas-oil fractions for I (integrated) TSL liquids from Illinois No. 6 and Clovis Point coals are similar. The elemental analysis, ramscarbon, and refractive indices are nearly the same for similar fractions of these two ITSL liquids [88]. It is the naphtha fractions of these two liquids that show considerable compositional difference and may have significant impact on naphtha refining.

The distillation curves for H-Coal and TSL liquids for Illinois No. 6 and Wyodak coals are plotted in Figure 3 [87]. Coal liquids designated "A" have higher end points as noted in Table 16. The GLC simulated true-boiling-point (TBP) distillation curves for Ireland Mine coal and Black Thunder coal obtained in Wilsonville Runs 259G and 260D, respectively, are depicted in Figure 4. These are samples representative of current two-stage liquefaction products, which are relatively lighter in distillation.

Current two-stage coal liquids contain considerably more hydrogen than single-stage coal liquids. Figure 5 [87] shows that within a given boiling range, the two-stage product has higher hydrogen content than comparable H-Coal liquids. The H-Coal liquids may contain more of the comparatively H-rich low-boiling components than the two-stage liquids, probably as a result of the higher severity required for the single-stage process.

3.2 Heteroatoms in Coal Liquids

The heteroatoms content in the coal liquids has been an important concern, since it affects the upgrading performance of the coal liquids and the quality of the products derived therefrom.

Inferred from data in Table 16A, coal liquids from single-stage liquefaction contain heteroatoms in the following ranges (wt%): 0.025-0.89 sulfur (generally

around 0.2), 0.15-2.04 total nitrogen (generally around 0.4), 0.13-0.70 basic nitrogen, and 0.67-4.52 oxygen (generally around 2.0).

The distribution of heteroatoms in single-stage coal liquids can be represented by Figure 6, a plot of S, N, and O contents for Illinois No. 6 H-coal liquids [99]. Oxygen, being the most abundant heteroatom, shows a high peak content around 400°F boiling point, another peak in 620-720°F range, and an increasing level in heavy ends. The sulfur and nitrogen contents increase with increasing boiling point somewhat monotonically.

As a whole, the two-stage coal liquids contain much less heteroatoms than do the single-stage liquids. Data in Table 16B demonstrate that the heteroatom contents of two-stage liquids fall in the following ranges (wt%): 0.01-0.23 sulfur (generally 0.01-0.05), 0.07-0.50 total nitrogen, and 0.14-3.52 oxygen. The reduced heteroatoms content in two-stage liquids reflects one of the important achievements in the process development of two-stage coal liquefaction.

The heteroatoms distribution in two-stage coal liquids analyzed by Amoco [88] shows the oxygen (direct determination) distribution in coal liquids (Figure 7) from the two liquefaction stages of Wilsonville Run 246. Direct oxygen is usually about 0.5% higher than oxygen by difference. This plot reveals a predominate oxygen peak in the 300°F-600°F range of the first-stage product. NaOH extraction experiments prove that a large fraction of the oxygen compounds in first-stage product comprises phenols. Two sulfur peaks are observed (Figure 8) for the first-stage product, which are largely due to thiophenic sulfur. The second-stage coal liquid is low in sulfur, generally less than 0.1 wt%; however, the first cut from it has an unexpectedly high sulfur (between 300°F and 400°F) level (2.58 wt%). Only 20% of this sulfur is found to be thiophenic. The nitrogen content increases with increasing boiling range, while the basic nitrogen demonstrates a peak between 400°F and 500°F, for coal liquids

from both stages (Figures 9 and 10). The nitrogen level of the second-stage product is lower than that of the first-stage liquid.

The advanced CC (close-coupled)-ITSL process yields products with relatively low heteroatoms content. The three CC-ITSL liquids in Table 16B, all derived from subbituminous coals, contain <0.1 wt% S, 0.23-0.50 wt% N, and 1.13-2.49 wt% O. The distribution pattern of the heteroatoms in these three coal liquids is generally similar to that in other TSL liquids. The sulfur content decreases with increasing boiling point, and is predominantly in the naphtha fraction. The nitrogen level increases with increasing boiling point, and predominates in the vacuum gas oil fraction (650-1000°F). The oxygen distribution again shows a peak in the 350-450°F fraction, which consists mostly of phenolic compounds [92]. The nitrogen and oxygen contents of the coal liquid samples obtained from most recent Wilsonville runs (No. 259-261) are even lower (Table 16B).

Liquids derived from lower rank coals usually have higher oxygen contents than higher rank coal liquids. For instance, in Wilsonville ITSL Run 246 the Clovis Point (subbituminous) coal produced a liquid product containing 3.52 wt% oxygen, while in ITSL Run 244 the Illinois No. 6 coal liquid has only 1.92 wt% oxygen (both by direct method) [88]. As far as subbituminous and other low-rank coal liquids are concerned, recovery and utilization of oxygen compounds are therefore of more importance.

For Clovis Point coal liquid (Run 246), the yields of naphtha (IBP- 360°F) and 360-450°F fraction are 19.4 and 20.4 wt%, and the oxygen contents for these two fractions are 3.71 and 6.20 wt%, respectively [88]. The amounts of oxygen compounds in these fractions are roughly estimated to be 5 and 12 wt% of total coal liquid, respectively. For Illinois No. 6 ITSL liquid (Run 244), the oxygen compounds in the naphtha (IBP-360°F) and 360-450°F fractions constitute about 2 and 5 wt% of total liquid product. With this appreciable quantity, recovery is worth considering.

The oxygen compounds in the naphtha fraction and light distillate are mostly phenols. In Illinois No. 6 and Wyodak CC-ITSL liquids, most of the extractable phenols are concentrated in the same boiling range of 350- 600°F with a peak level at 446°F as shown in Figure 11. They chiefly consist of four types of ring structures: phenols, idanols, naphthanols, and biphenylols. Essentially all of these compounds are alkyl substituted with short chains (C₁ to C₄) [100].

When the naphtha and kerosene fractions of Black Thunder coal liquid (obtained from Wilsonville Run 260D) were caustic washed, phenolic species were selectively extracted. The results are given below [101]:

Run 260D Fraction	Phenolic -OH Concentration by FTIR meq/g Sample	
	Before Caustic Wash	After Caustic Wash
Naphtha (<380°F)	0.40	0.02
Kerosene (380-510°F)	0.92	0.07
Gas Oil (510-650°F)	0.52	0.27

The data demonstrate that about 3.6 wt% of the naphtha fraction and 10 wt% of the kerosene fraction are phenolic compounds and can be easily recovered.

With this appreciable quantity of phenolics in coal liquids, a study of their recovery and utilization, as well as an assessment of their market value, will be very meaningful.

3.3 Toxicology of Coal-Derived Liquids

Major health/environmental concerns have been related to the toxicological activity of coal derived liquids, and a large amount of research has been performed.

It is beyond the scope of this study, and readers are referred to an excellent comprehensive review edited by Gray et al. [102] for detailed information. A summary of major conclusions from this reference is provided below:

1. Although some quantitative differences exist, the chemical classes responsible for toxicological activity in coal-conversion materials are qualitatively the same regardless of the coal conversion process used to produce the material.

2. The chemical classes primarily responsible for mutagenic and carcinogenic activity of coal liquids and tars are high-molecular weight, polycyclic aromatic hydrocarbons (PAHs). Amino-PAHs are also prevalent and are a major source of mutagenic activity.

3. Toxicological activity of coal conversion materials can be predicted from their 95% distillation temperatures and their aromaticity. Toxicological activity is concentrated in those highly aromatic components boiling above 650°F and having hydrogen: carbon (H/C) ratios below 1.5. For a wide variety of materials studied, distillates with a boiling range above 700°F were toxicologically active, while those with a boiling range below 650°F were essentially inactive. Therefore distillation can be used to separate carcinogenic and mutagenic components of coal-derived liquids from those components that do not show toxicological activity.

4. Mild to moderate hydrotreatment decreases the mutagenic activity of coal-conversion products by reduction of primary amino functionalities and, to a lesser extent, by dearomatization of PAH structures through saturation and/or C-C bond cleavage. More severe hydrotreatment significantly decreases skin carcinogenicity of these materials, primarily from hydro-dearomatization of four- to six-ring PAH structures. Hence, hydrogenation can be used to reduce the adverse toxicological effects of coal liquids.

5. Efficient distillation of coal liquids, heavy-ends process recycle, and catalytic hydrotreating, singly or in combination, can effectively reduce toxicological activity through control of product boiling point and aromaticity.

6. The information available, although limited for gasification, suggests that suitable engineering controls, combined with good industrial- hygiene practices and medical surveillance, have effectively protected the health of workers in this industry [102].

A study on hydrotreatment of SRC-II liquid shows that the mutagenic activity of this coal liquid was reduced by an order of magnitude by 35% removal of nitrogen and 52% removal of oxygen. Liquid product with 67% nitrogen removal and 82% oxygen removal shows no distinguishable mutagenic activity [103].

Present day two-stage liquefaction technology recycles heavy distillates and resids to extinction, has high conversion efficiency, and produces coal liquids of much improved quality, including low end point and reduced heteroatoms content. This should greatly reduce the concentration of toxicological components in liquefaction products. The transportation fuels to be manufactured from coal liquids are gasoline, jet fuel, and diesel fuel, which would have been hydrotreated and have end points lower than 600°F. They should show no toxicological activity based on the above conclusions.

3.4 Summary

1. The successful development of two-stage liquefaction has shown remarkable improvements in process efficiency and liquid product properties, which are comparable to those of petroleum, except for somewhat lower hydrogen and higher oxygen contents. Present coal liquids are low-boiling, low in sulfur, and essentially free of residues and metals, which are superior to those of petroleum.

The naphtha fraction from subbituminous coal liquids contain more paraffins and less aromatics than that from the bituminous coal liquids, which is indicative of the more paraffinic nature of subbituminous coal.

2. The distribution pattern of the heteroatoms is generally similar with all TSL liquids. The sulfur content decreases with increasing boiling point and is predominantly contained in the naphtha fraction. The nitrogen level increases with increasing boiling point, and predominates in the VGO fraction. The oxygen distribution shows a peak in the 350-450°F fraction. The extractable phenols are concentrated in the 350-600°F boiling range with a peak level around 450°F.

Liquids derived from low-rank coals contain much more oxygen compound than high-rank coal liquids. Consequently, recovery and utilization of these oxygen compounds will be an important contribution to coal liquefaction economics.

3. The chemical classes primarily responsible for mutagenic and carcinogenic activity of coal liquids are high-molecular-weight polycyclic aromatic hydrocarbons (PAHs) and amino-PAHs. Distillates with a boiling range above 700°F are toxicologically active, while those with a boiling range below 650°F are essentially inactive. Hence, proper hydrotreating and efficient distillation of coal liquids can produce <650°F distillates essentially free of toxicological activity. Recycling of heavy distillates and resids to extinction during liquefaction is therefore necessary and beneficial not only for maximizing the light distillate yield but also for improving the product quality.

4.0 REFINING SCHEMES FOR COAL LIQUIDS

A number of earlier studies were made of the use of raw coal liquids in various applications where a high degree of refinement is not necessary. Combustion tests of SRC-I and SRC-II products have been conducted under the sponsorship of the Electric Power Research Institute, and tests of SRC-II distillates as stationary turbine fuels have been performed under a program carried out by the NASA Lewis Research Center [104]. An evaluation of SRC-II distillate as a low-speed diesel fuel has been made by Sulzer Brothers, Ltd. [105]. Raw coal naphthas have been found to have poor stability [106].

Current two-stage coal liquids are of much better quality, which suggests that high-value fuel products of better quality can be expected from their refining. Coal liquids from Wilsonville ITSL operations have been evaluated through the use of standard petroleum tests on several occasions [85,88,107,108], including the most recent work on coal-liquid products from Wilsonville Runs 259 and 260 [94,109]. The studies show that the present day coal liquids, although much superior in quality than before, still have to be refined to meet stringent specifications for high-value liquid fuel products.

Representative distillation cuts from two typical coal liquids, one from single-stage and another from two-stage liquefaction, both from Illinois No. 6 coal, are compared with their petroleum counterparts in Tables 18 and 19 [85,110]. In fact, coal-liquid fractions bear many similarities to petroleum streams of comparable boiling range. They do have lower API gravity and lower H/C ratio, reflecting higher proportions of aromatics, while the non-aromatic compounds tend to be naphthenic rather than paraffinic. They also contain considerable amounts of highly polar compounds, principally O- and N-containing compounds, whereas sulfur is not really a problem.

Modern refining processes are well developed to modify the characteristics of hydrocarbon feed streams of varying quality. Therefore, with appropriate processing, coal-derived liquids could be refined into specification fuels so that there is no inherent barrier to the use of coal-derived liquids as refinery feedstocks. Conventional refineries would be able to accept the coal liquids as feedstock if they were blended down to low concentrations or properly upgraded, either at the liquefaction plant or in the refinery.

It is generally recognized that the best refining strategy involves the use of each potential feedstock and fraction in a way in which it can most easily and efficiently be tailored to meet the market needs. The hydrogen content of coal liquids is close to the hydrogen level found in a high octane gasoline. Consequently, coal liquid naphtha is best suited for the gasoline market [111]. The diesel and jet fuel fractions require much higher levels of hydrogen to meet specifications, therefore the high aromaticity of coal liquids would have to be modified for these applications. Stability of transportation fuels is another important concern, which usually results in the need for thorough removal of nitrogen and oxygen.

Therefore, the coal liquefaction plant has to produce either finished fuel products meeting all the specifications and market requirements, or a product stream as refinery feed to be processed to required specifications [1]. The former would involve significant additional capital requirement for the liquefaction plant. The latter assures utilizing existing refineries with existing markets and minor modifications either in liquefaction or in the refinery. The present task focuses attention on the latter.

Blending coal liquids with petroleum as a supplementary source of refinery crude is a possible refining strategy, especially if they are blended with paraffinic crude oil. Incompatibility is unlikely with modern coal liquids. However, information

about refining coal liquid-petroleum mixtures is not yet available, and the discussion in this report focuses solely on the refining of coal-derived liquids.

Basically three refining routes may be considered when coal liquids are processed in the refinery:

1. The coal liquid is distilled to some straight-run fractions, which are refined or upgraded by whatever means necessary. One fraction may only need a caustic wash, another a mild hydrotreating, the third a severe hydrorefining, and the fourth may be subjected to destructive processing, like cracking or coking, etc.

2. The whole coal liquid is hydrotreated to a certain degree so that, after fractionation, the distillates could meet the product specifications or qualify as feed to a hydrocracker or catalytic cracker.

3. The whole coal liquid may be hydrocracked and then distilled into fractions, some of which may or may not need further treating to turn into refinery blending stocks, while some of them may be improved quality feedstocks for units like catalytic cracking or hydrocracking.

As a universal practice, refineries rarely make fuel products from one single stream. They always blend a number of stocks for a specific fuel, both for operational flexibility and refinery balancing. Blending of coal liquid fractions with petroleum-derived stocks is an important topic that needs to be studied. As a fundamental study for coal-liquid refining, the discussion here is based on producing various fuels entirely from coal liquids, mainly for the purpose of exploring the coal-liquid potential.

5.0 REFINING OF RAW COAL LIQUID FRACTIONS

The conventional way of petroleum refining in existing refineries is to first fractionate the crude petroleum, after desalting and dewatering, in an atmospheric and vacuum distillation unit into various fractions. These fractions are then processed in different refining units into a variety of product streams, which are finally blended into specification fuel products.

One of the refining schemes for coal liquids follows the routine petroleum refining procedure. Straight-run distillation of coal liquids is considered a preliminary step to prepare various cuts for further refining. Relevant information is discussed below, in the order of increasing boiling range of individual fractions.

5.1 Light Naphtha

A sample of light naphtha (IBP-285°F) was obtained by fractionation of a Wilsonville sample from Run 244, Illinois No. 6 ITSL, 8.3% of total liquefaction liquid. This clear, water-white liquid met many of the aviation gasoline specifications (Table 20) including freezing point, sulfur content, Reid vapor pressure (RVP), copper-corrosion, etc. However, it failed the D86 10% point, heat of combustion, octane number, and potential gum specification [85].

The sample may have suffered some light end loss during shipment, so that failure to meet D86 10% point and minimum vapor pressure is not considered to be serious and can be remedied without difficulty. The octane number and heat of combustion, which are a little lower than required, are not a problem for a blending stock. The only thing of concern is the stability (potential gum), which is most likely caused by nitrogen and oxygen compounds. It is reasonable to expect this light naphtha, after hydrotreating, to be a good blending stock for aviation gasoline blending.

5.2 Naphtha

Properties of some naphthas from raw coal liquids derived from different coals by both single-stage and two-stage liquefaction processes are documented in Tables 21 [110-113], 22A and B [85,88,92-94]. For all the 400°F-fractions obtained from H-Coal and EDS raw coal liquids, most of the distillation specifications are not met probably due to the loss of light ends during handling, which can be remedied by blending with light components and/or redistillation. The existent gum exceeds the limit implying instability, which is most likely attributed to the existence of abundant hetero-compounds and emphasizes the necessity of hydrotreating. Storage stability tests were conducted for the H-Coal naphtha over a one-year period. For all three samples, insolubles, gum, and total acidity increased substantially with time. The main component of the Illinois coal naphtha is ammonium sulfate, and the gums from Illinois and Wyodak naphtha have much higher N, O, and S contents but lower hydrogen levels than original liquids [110]. This is direct proof that the hetero-compounds are the main cause for instability. The two-stage coal liquefaction yields naphtha fractions with lower heteroatom content, especially the recent CC-ITSL runs, which give the naphtha very low sulfur level and much reduced nitrogen content. However, the total heteroatom level is still high relative to petroleum-derived naphtha.

The motor octane numbers for these naphthas range from 70 to 83 except for Wyodak naphtha. Based on the data in these tables, it seems that the EDS and H-Coal naphthas possess more aromatics (30-50%) and the ITSL naphthas more naphthenes (50-68%). The ITSL naphthas correspondingly have higher hydrogen content than do the single-stage naphthas, while the CC-ITSL naphthas have the highest hydrogen percentage (13.6-14.1 wt%, H/C atom ratio 1.94-2.01) and contain the largest amount of saturated hydrocarbons (87-88 vol%).

Any of the coal-derived naphthas makes an excellent source for gasoline production, especially the naphtha fraction from current CC-ITSL process, which

meets most of the gasoline specifications except stability (Table 22B). This is certainly related to its relatively high heteroatom content, which dictates the necessity of hydrotreating the naphtha to produce gasoline product.

Single-stage liquefaction processes yield more naphtha fraction (30%-45%), probably due to high liquefaction severity. With the Wyodak H-Coal naphtha yield as high as 74.4% was obtained, due partly to the higher cut point (400°F). Naphtha yields from TSL liquids are in the range of 20-28 wt%.

The cutpoint for TSL naphtha has usually been around 350°F. A higher cut point up to 380-400°F may be necessary to maximize gasoline production. As a consequence, the naphtha fraction will contain an appreciable amount of oxygen compounds, almost exclusively phenolics, as illustrated in Table 23 [86]. Raising the naphtha end point also increases the relative amount of aromatics in the hydrocarbon portion. To determine a proper cut point between naphtha and the next higher-boiling fraction (jet or diesel), a refining plan for the total coal liquid has to be considered.

The purpose of hydrotreating the coal-derived naphtha can be:

- 1) to generate a gasoline blending stock with improved stability and with an octane number in the approximate range of 70-80, or
- 2) to make a feedstock for catalytic reforming to produce a gasoline component of very high octane.

To date, research has been mostly conducted on the latter. H-Coal naphthas were hydrotreated to bring the hetero-compounds content within acceptable limits for reformer feed [114]. The IBP-400°F coal naphtha was first rerun and then hydrotreated over a commercial hydrotreating catalyst in a bench-scale continuous unit. The target levels of 30 wppm oxygen and < 1 wppm nitrogen were reached at

moderate severity of operation. Test results are summarized in Table 24. Only a trace amount of gas (C_1 - C_4) was produced and the yield of upgraded naphtha was almost 100%. The total hydrogen consumption was 480 SCF/bbl, of which 13.8% was required for the reduction of heteroatoms content to acceptable levels. As might be expected, a major portion (60%) of this amount of hydrogen was used in oxygen removal. The bulk of the total hydrogen consumed resulted in an increase in hydrogen content from 12.8% to 13.6% and, correspondingly, in an increase in saturates content from 70.1% to 81.1% and a decrease in aromatics content from 24.7% to 18.9%. The latter caused a reduction in RON from 80.3 to 66.8. However, the hydrogen consumed in saturation is "recoverable" and the octane number can be greatly improved via reforming.

The amount of hydrogen used in heteroatom elimination, however, is not recoverable. Therefore, extraction and recovery of these oxygen compounds as a by-product, instead of removing them by hydrogenation, is favored both technically and economically.

Since the hydrotreated coal naphthas are high naphthene feedstocks, the required temperatures for their reforming are relatively low, and high space velocity can be employed. At these low-severity conditions the yield of gasoline of a given octane number is generally very high. When an upgraded Illinois No. 6 H-Coal naphtha (properties shown in Table 24) was reformed over a commercial Platforming catalyst in bench-scale continuous units under 450 psig over a range of temperatures, a yield-octane curve was obtained as depicted in Figure 12, which shows that the reformat has a RON ranging from 94 to 102 (clear). The C_5+ yield ranges from 88% to 92.5%, while the hydrogen produced by reforming is 1250 to 1750 SCF/bbl, with a net hydrogen yield of 800 to 1250 SCF/bbl (480 SCF/bbl used for upgrading). The product distribution data obtained from MS analyses illustrate that, at moderate temperature, the aromatics in the reformates increased solely at the expense of

naphthenes. While at the highest temperature used in the tests, dehydrocyclization of the C_9+ paraffins became significant [114].

In the case of Illinois No. 6 upgraded SRC-II naphtha (Figure 13), the upgrading required 560 SCF/bbl of hydrogen. The reforming product has a research octane ranging from 88 to 100 with a C_5+ yield of 88 to 92 wt%, and the hydrogen produced ranges from 1200 to 1550 SCF/bbl, which results in a net hydrogen production between 650 and 1000 SCF/bbl [115]. All these results point to a successful reforming of the coal-derived naphtha.

Similar results are recorded in several EDS project reports [113,114,116]. An Illinois No. 6 raw EDS naphtha, and a Wyodak raw EDS naphtha, before and after caustic washing, were hydrotreated to make reformer feedstocks. It was found that:

1. Reformer feed qualities can be met with all four naphtha feedstocks by hydrotreating in a conventional, single-stage hydrotreater.
2. Minimum conditions required to meet reforming specifications were set by product nitrogen level. When a product target of <1 wppm is met, sulfur and Bromine No. are sufficiently low to permit reforming with either platinum or bi-metallic catalyst.
3. Both raw naphthas exhibited the same effect of caustic washing to remove phenolics: slightly more than a two-fold increase in space velocity along with a 50% reduction in hydrogen consumption for the washed naphtha.

Due to data scatter, hydrogen consumption was reported as a trend-line of hydrogen uptake versus API gravity increase (Figure 14). The hydrotreated naphthas were redistilled and blended to obtain reformer feedstocks with different end points.

Reforming results are exhibited in Figures 15 and 16 with Arabian Light naphtha as a reference, and corresponding conclusions were drawn [117-119]:

1. Because of their high cyclics content, coal naphthas reform much more readily than petroleum naphthas. At an equivalent octane (100 RON clear) a 600 to 700% increase in reformability (relative space velocity) and approximately 16% increase in reformate yield were observed with Wyodak naphtha (370°F EP) vs Arabian Light (360°F EP).

2. Naphthas from different coals, but having similar end points, have essentially the same reformability. Lowering the end point of coal naphtha facilitates reforming. A 25% increase in reformability was observed by lowering feed end point from 395°F to 340°F.

3. The abundant cyclic compounds in coal naphthas lead to high hydrogen yields and low yields of C_4 gases during reforming. Hydrogen yields in excess of 2000 SCF/bbl are twice as much as typical yields from petroleum naphthas, and light gas yields of less than 4 wt% are only 20% to 25% of what was obtained from petroleum feedstocks.

4. Coal naphthas contain significantly higher levels of condensed naphthenes and indanes compared with petroleum naphthas. These compounds increase catalyst deactivation rates and condensed aromatics content of the reformate. With a bimetallic reforming catalyst, a twofold increase in deactivation rate was observed with coal naphthas relative to comparable petroleum naphtha. However, by taking advantage of the high reformability of coal naphthas and thus a lower reforming temperature to achieve the same product octane, the deactivation rate is reduced to approximately one-half that encountered with petroleum naphthas.

5. The condensed aromatics impact engine performance. Nevertheless, by reducing feed end point and/or by operating at milder severity, condensed aromatics content could be limited to no higher than that obtained in petroleum reformates.

6. Coal naphtha reformates contain high levels of BTX, making them attractive chemical feedstocks. Depending on feed endpoint, benzene, toluene, and xylene yields fall in the following ranges: 7-12, 19-25, and 17-23 wt%, respectively.

7. Reforming admixtures of coal and virgin petroleum naphthas has no synergistic effects on reformat yield or catalyst deactivation.

Attention has been focused on the cut point of coal naphtha as reformer stock. Chevron used a cut point close to 325°F [118], apparently based on the amount of dinaphthenes in the reformer feedstock and on concerns about the end point of the reformat. Later work has indicated that, with modern reforming catalysts, feedstock end points as high as 350°F are feasible and economically preferable for gasoline production [104]. The EDS workers used a 350°F cut point for their reformer feedstock because the 350°F to 370°F fraction of the EDS naphtha, when reformed, produced enough condensed aromatics to adversely affect engine performance [113]. UOP employed 400°F end-point naphtha for hydrotreating and subsequent reforming. Plugging at the preheating section of the hydrotreating reactor was once encountered and attributed to the presence of gum in the feed, but no significant pressure drop across the reactor was observed in the later run with fresh catalyst and with preheater packings replaced [114].

In short, coal-derived naphthas are readily hydrotreated and the hydro-upgraded naphthas are excellent reformer feedstocks to make high-octane gasoline with very high yield. The hydrotreating and reforming of the naphtha fraction from current CC-ITSL coal liquids, although not studied, should be similar to or even better than the results described above.

The coal-naphtha reformat does have a very high octane number due to its high aromatics content, possibly 70-80%. However, the increasing concern about the aromatics content in gasoline makes coal naphtha reforming not so attractive as before. The more realistic way of coal-naphtha refining is mild hydrotreating to eliminate its heteroatoms thus improving its stability. The high saturates content (86-88%) and the relatively low aromatics content (usually less than 15%) of the naphtha fraction obtained from current two-stage coal liquids should be maintained. Studies on coal-naphtha hydrotreating with the sole purpose of stability improvement are very much required.

5.3 Kerosene Fraction

The naturally occurring hydrocarbons in petroleum can be fractionated with little additional processing to produce highly stable jet fuels. In petroleum refineries, jet fuel stocks may sometimes need mild hydrotreating to remove sulfur, but chemical conversion processes have not been necessary most of the time. This is not true with coal-derived jet fuel fractions. Properties of some coal liquid fractions in the jet fuel range are shown in Table 25A. Properties of the jet fuel fraction (380-510°F) obtained from the coal liquid produced in a recent Wilsonville Run No. 259G (Pittsburgh seam coal) are listed in Table 25B in comparison with the ASTM specifications [109].

The coal-derived kerosene fractions have lower hydrogen content than do naphthas from the same source, following the general trend that hydrogen content decreases with increasing boiling point. Kerosene fractions from CC-ITSL liquids are somewhat richer in hydrogen than ITSL counterparts, however, their hydrogen content is still low compared with that of petroleum-derived jet fuels (H 13.5-14.0 wt%). This low hydrogen level is reflected in their high aromatics content, typically around 50%, which makes the API gravity and the smoke point, two major properties for jet fuels, much lower than required.

Regarding the heteroatom content, the coal-derived kerosene fractions are loaded with hetero-compounds, especially oxygen-containing, when the initial boiling point is around 350°F. The hetero-compounds are believed to be responsible for the instability (failure of JFTOT test and very high gum content) of the coal-derived jet fuel fractions.

The low H/C ratio and high heteroatom level of the coal-derived kerosene fractions exclude the possibility of producing jet fuel by simple fractionation of coal liquids. Hydrotreating is absolutely necessary to saturate the aromatics and to remove the heteroatoms to manufacture quality jet fuel products.

Chevron prepared a 600°F- distillate by redistilling a Big Brown lignite EDS liquid product and hydrotreated over Chevron ICR 106 catalyst at a variety of conditions to make jet fuel [115]. The redistilled stocks are easy to hydrotreat in comparison to the whole crude, and all the heteroatoms are removed at the mildest severity studied: 1.5 LHSV, 1800 psig total pressure, and 700°F catalyst temperature. The 250°F-600°F jet fuel fraction contains 5 ppm nitrogen (Table 26). The smoke point of the jet fuels depends heavily upon the aromatics content and, in turn, upon the hydrogen partial pressure during hydrotreatment. It is inferred from Table 26 that jet fuels with smoke points of at least 20 mm can be made when the hydrogen partial pressure is about 1700 psia or greater. Similar work was done by Southwest Research Institute on EDS middle distillates [120]. Phenolic compounds were first removed from the feedstock by caustic extraction, and the raffinate was then hydrotreated under three levels of severity. The three hydrogenated coal distillates were redistilled to obtain three jet fuel fractions with a boiling range of 374-527°F. The aromatics content of the jet fuel fractions from mild-, medium-, and high-severity hydrotreating are 39.6, 20.7, and 10.4 vol%, respectively. The medium- and high-severity products passed the thermal stability test (JFTOT). However, both the API gravity and smoke point of all three samples are higher than specification. This is not in agreement with Chevron results

mentioned above [115]. Additional work, especially on CC-ITSL coal liquids, would be constructive.

The jet fuel fractions obtained from high rank coal liquids, containing much more aromatics than lignite kerosene fractions, need hydrotreating with higher severity to meet the specifications. However, related data are not available.

More work on the manufacture of coal-derived jet fuels has concentrated on hydrotreating the total liquefaction liquid product rather than hydrotreating proper fractions from raw coal liquids. Special discussion will be given in Section 6.0.

5.4 Diesel Fuel Fraction (Middle Distillates)

The direct use of middle distillates from early versions of coal liquefaction process was studied a long time ago. A number of middle distillates from different coal liquids were tested in an EPRI-sponsored stationary turbine test program conducted by Westinghouse, Inc., and their properties are summarized in Table 27 [114]. Analytical data, except for the EDS fuel, were obtained by Mobil. General observations and conclusions achieved in this program are as follows:

- 1) The lighter cuts of most coal-derived liquids are usable in current gas turbine power plants with only small modifications. Boiling point is not a basic limitation but correlates loosely with fuel-bound nitrogen and hydrogen contents. For fuels containing <0.25 wt% N, combustors with water injection are probably capable of meeting EPA standards. The lower limit of hydrogen content is likely due to combustor wall temperatures, smoke emissions, etc.; while some heavier and most lighter test fuels are comparable to No. 2 fuel oil as far as smoke emission is concerned. The major problem is that none of these coal-derived middle distillates meets the gravity specification for No. 2 fuel oil and No. 2 GT gas turbine fuel.

2) These coal-derived mid-distillates mix very well with petroleum No. 2 fuel oil. Corrosion tests were promising but long-term testing would be required for definitive conclusions.

3) Combustion tests of a 350-650°F distillate fraction from Illinois No. 6 EDS coal liquids were conducted in a conventional 1 gal/h home heating oil burner unit. This distillate contains aromatics 68.6 LV%, sulfur 0.79 wt%, and nitrogen 0.67 wt%. The tests demonstrated that this oil is operable in home heating oil burners. The smoke emission is comparable to petroleum No. 2 fuel oil, but NO_x emissions are roughly three times higher than typical petroleum No. 2 fuel oil, unless the coal-derived distillate is hydrotreated to less than 200 ppm N [110]. In a storage stability test with EDS Wyodak distillate (350-650°F), no changes were detected after three months storage at 150°F or after one month at 210°F but further testing is necessary [113].

4) Regarding storage stability of the test fuels of the above two programs, hydrotreating may be required prior to storage. Severe hydrotreating is indeed necessary to meet the petroleum-based gravity specifications for ASTM No. 2 fuel oil for domestic heating and for ASTM No. 2 GT gas turbine fuel. Hydrotreating results are demonstrated in Figure 17. To obtain an acceptable ASTM No. 2 fuel oil, approximately 2500 SCF/bbl of hydrogen must be invested to reduce the aromatics level (from > 80 LV% to ~ 20 LV%) in order to achieve a minimum specification value of 30°API [116]. No information is available for No. 2 fuel oil and gas turbine fuel production from TSL coal liquids.

Table 28A presents property data for a number of straight-run middle distillates or light gas oils from H-Coal, Wilsonville ITSL, and CC-ITSL coal liquids, derived from both bituminous and subbituminous coals. Their starting boiling points are somewhat different, but the end points are the same. Properties of diesel fuel fractions distilled

from coal liquid products of recent Wilsonville Runs 259G and 260D, in comparison with ASTM No. 1 diesel fuel specifications, are listed in Table 28B [93,94,109].

Generally, these middle distillates have less hydrogen than lighter distillates. They show very low cetane index, 20-21 for ITSL distillates in Table 28A. A higher IBP helps improve the cetane number to some extent, such as ~27 for diesel fuel fractions in Table 28B, but the number is still low compared with normal values of 35-50. Also, the viscosity is too high and 90% distillation point needs to be reduced.

The nitrogen content in these middle distillates increases compared with naphtha and kerosene fractions, while sulfur declines as boiling range goes up. Oxygen content is lower for fractions with IBP higher than 400°F, compared with the peak in the 350°F to 450°F fraction. There are not enough data to judge the stability of these fractions.

If the coal-derived middle distillates (or diesel fuel fractions) are intended to be refined to high-grade diesel fuels, gas turbine fuels, and fuel oils, hydrotreating is necessary to improve their combustion quality and emission performance.

Hydrotreating of the middle distillate of Wilsonville Run 254 product (Ohio No. 6 coal) was studied at Southwest Research Institute (SwRI) [108]. A maximum nitrogen concentration of 400 ppm was adopted as a guide for a stable diesel fuel product, and the minimum ignition quality was marked for 31.0 cetane number (before the addition of ignition improver) at which a production diesel engine might start unassisted. Preliminary tests showed that stability was the more restrictive product property than ignition quality. The hydrotreater feed and products obtained at two levels of operating severity are reported in Table 28C.

Data in Table 28C show that the wide-boiling feedstock (412-823°F) has a high density and low cetane number (21.3), which are consistent with the high proportion

(81.7 vol%) of aromatic hydrocarbons and low hydrogen content (10.4 wt%). Its viscosity is outside the range of 1.9-4.1 cSt specified for No. 2 diesel fuel. After being hydrotreated under high operating severity, the product has a reduced aromatics content (42.2 vol%) and a cetane number of 35.4. Relationships of cetane number, aromatics concentration, and hydrogen content of Wilsonville and EDS coal liquids are depicted in Figure 18 [108]. The viscosity of the high-severity product is just below the maximum allowable, while the result of accelerated stability test (1.60 mg/100 ml) is still marginally high compared with the 1.5 mg/100 ml allowed in the federal specification for diesel fuel [121]. It is, therefore, advisable to treat this diesel fraction with a multipurpose additive combining antioxidant, dispersant, corrosion inhibitor, and metal deactivator, in addition to an ignition improver additive.

Another refining route explored for coal-derived middle distillates is catalytic cracking. Coal-derived mid-distillates have been catalytically cracked to increase the yields of light fuels. Among the earliest work on catalytic cracking of coal liquids is a study on coal-tar fractions from low-temperature carbonization [122], where low conversion, low naphtha yield, and high coke make were observed. Polynuclear aromatics, the C₇ insolubles, gum, and high molecular-weight oxygenates are coke precursors. The poisoning effect of basic nitrogen compounds on active sites of cracking catalysts has also been investigated and reviewed [123], while coal liquids contain a significant amount of basic nitrogen. These are the disadvantages for coal liquid catalytic cracking.

Distillates from SRC-II liquids provided by Pittsburg and Midway Coal Refining Company [124] and from H-Coal atmospheric still bottoms obtained by UOP at Des Plaines, with and without hydrotreatment, were subjected to fluid-bed catalytic cracking over a commercial zeolite catalyst at UOP [125,126]. The results are as follows:

H-Coal Gas Oil

The H-Coal gas oil has a boiling range from 415°F to 769°F, with hydrogen, sulfur, nitrogen and oxygen contents of 9.14, 0.08, 0.41, and 0.52 wt%, respectively. Catalytic cracking of this gas oil results in low conversion (31-42 LV%), low gasoline yield (15.5-20.0 LV%) and high carbon yield (11.1-13.4 wt%). After different levels of hydrotreatment, the hydrogen content of this gas oil was increased to 10.68 and 12.88 wt%, respectively, with corresponding reductions in S, N, and O levels. The cracking behavior of these two hydrotreated gas oils were considerably improved, and the results are plotted in Figure 19 [125].

SRC-II Gas Oil

Similar results were obtained in the catalytic cracking of SRC-II gas oil, which has a boiling range of 421°F-738°F, with H, S, N, and O contents of 8.89, 0.29, 0.995, and 2.28 wt%, respectively. Two additional gas oils from the same source, but hydrotreated at different severities, have about the same boiling ranges as the raw gas oil, but with increased hydrogen and reduced heteroatoms contents. Catalytic cracking of the raw gas oil gives low conversion (45.3-51.6 LV%), low gasoline yield (25-28 LV%), and high carbon yield (12.2-13.9 wt%), while hydrotreated gas oils yield better results in parallel with their increased hydrogen content. The yields and product quality from SRC-II gas oils are compared below with data from a West Coast refinery feed hydrotreated to different hydrogen levels [124]. The latter was chosen for comparison because California crudes contain appreciable amounts of nitrogen.

	SRC-II Gas Oil				West Coast Refinery Feed			
Feed H content, wt%	8.66	8.89	9.98	10.59	11.78	12.46	12.50	13.47
Conversion, LV%	44.8	45.3	49.2	61.9	67.8	74.6	78.9	87.2
C ₆ + Gasoline, LV%	23.9	25.1	35.3	46.9	50.9	59.0	61.8	71.0
C ₄ , wt%	5.3	5.0	8.4	13.5	15.2	16.5	18.9	21.2
Carbon, wt%	11.6	12.2	7.3	3.9	7.4	5.7	5.5	4.8
RON Clear	---	106.7	101.8	97.5	---	---	---	---

EDS Gas Oil and Others

Figure 20 shows data patterns, similar to the above two cases, with an EDS gas oil and a West Coast refinery feedstock [127,128].

These correlations for the coal and petroleum gas oils are reasonably consistent in their general trends. As the hydrogen content of the feed increases, the catalytic cracking conversion and gasoline yield also increase, and the coke production decreases. If C₃ and C₄ in the cracked gas are to be alkylated, with severely hydrotreated coal-derived cracker feed, additional 10 wt% (based on cracker feed) of high octane gasoline component (C₆+ alkylate) is roughly estimated.

Based on the above information, it can be concluded that with proper hydrotreatment, the coal-derived gas oils can be processed via FCC and alkylation into a high-octane and high-quality gasoline with fairly good yield.

Obviously, the effect of coal-oil catalytic cracking depend on the extent of hydrotreating and associated hydrogen consumption. For the H-Coal gas oil, when its hydrogen content was brought up from 9.14 to 10.68 wt% by moderate hydro-upgrading, the total hydrogen consumed was 1130 SCF/bbl. Of this amount of hydrogen, 8.0% is involved in denitrogenation, desulfurization, and deoxygenation. The bulk (90.5%) of the total hydrogen consumed (1.6 wt% of raw gas oil feed)

increases the hydrogen content mainly in saturating the aromatic rings. When hydrotreating was carried out at severe conditions, the hydrogen consumption was 5.6 wt% of the feed (3640 SCF/bbl), which caused an increase in gas oil hydrogen content to 13.75 wt% and a reduction of aromatics from 90.2 to 7.2 LV%. Under severe conditions, hydrocracking also became very significant. UOP suggested that the optimum hydrotreating level is around 11.5-12.0 wt% hydrogen of the cracker feed [111].

Hydrotreatment plus catalytic cracking of middle distillates is a way of producing more gasoline from coal liquids. All the feedstocks (gas oils) used in the above-mentioned studies have a higher end point ($\sim 750^{\circ}\text{F}$) than that of diesel fuel fraction. For a coal-derived distillate with a lower end point (say 650°F), it might be more beneficial to produce diesel fuel simply by hydrotreatment.

5.5 Heavy Distillates

Heavy distillates ($650^{\circ}\text{F} +$), sometimes called vacuum gas oils (VGOs), obtained from coal liquids have even higher levels of aromatic and heteroatom compounds and pose additional problems in their utilization, such as toxicological activity and incompatibility with petroleum stocks.

Table 29 compiles data for some heavy distillates from EDS, H-Coal, and TSL liquid products. Yield of the heavy distillate varies over a wide range depending on liquefaction conditions, especially the recycle ratio. The heavy distillates from two-stage liquefaction are significantly richer in hydrogen than those obtained from single-stage processes. More S- and N- compounds are concentrated in VGO than in either naphtha, kerosene, or middle distillates. The two-stage VGOs have less heteroatoms content than the single-stage counterparts. VGOs from ITSL processes can have negligibly small amounts of sulfur and heavy metals.

The heavy distillates from coal liquids can be used as heavy fuel oils. H-Coal heavy distillate could be sold without further upgrading as a heavy industrial fuel oil (No. 6 fuel oil) [112]. Nevertheless, when the coal-derived VGOs are blended with petroleum products, incompatibility may become a problem. As an example, an EDS VGO (650-1000°F) is reported to be incompatible with petroleum No. 2 and heavier fuel oils [113].

Storage instability is another concern with heavy distillates. After one month of storage at 210°F, a viscosity increase was observed with EDS Wyodak fuel-oil blends (350-1000°F). When stored below 150°F, EDS fuel oil did not form wall deposits; however, at 200°F the fuel oil showed very high levels of deposits, indicating a strong effect of temperature on deposit formation [113]. In Mobil's storage stability tests on H-Coal fuel oils (400-975°F) derived from Illinois No. 6, Wyodak, and West Kentucky coals over a one-year period, it was found that insolubles and gum formed in all three fuel oils and increased appreciably with time. The same is true for the total acid numbers, while changes in gravity and viscosity were relatively minor [110]. No comparable data are available for TSL products.

Combustion studies were conducted on a wide-boiling EDS fuel-oil product in a pilot-scale 50 HP Cleaver-Brooks boiler. Illinois and Wyodak fuel-oil blends were prepared with boiling ranges of 400-1000°F and 350-1000°F, respectively. The coal liquid blends burn easily with smoke emissions equal to or lower than petroleum fuel oils at all levels of excess air. NO_x emissions are consistently higher relative to petroleum fuel oils, reflecting their higher fuel-bound nitrogen content. Particulate emissions are even lower than those obtained from petroleum fuel oil and are roughly equivalent to ash content. However, the coal fuel oils contain and emit significantly higher levels of polynuclear aromatics (PNA) [116].

Due to the incompatibility of coal vacuum gas oil with petroleum-derived industrial fuel oils, studies were performed at an Exxon R&D Laboratory to determine

the feasibility of hydrotreating as a means of upgrading. Although nitrogen is not a current resid fuel specification, it is anticipated that levels exceeding 0.2 wt% may be prohibited in certain applications (e.g., gas turbine fuel). To achieve this target, a high severity-hydrotreating would be required [116], and this may not be economical for the production of a low-value product like heavy industrial fuel oils.

Besides the elevated levels of hetero-compounds, the very high aromatics content of the coal-liquid heavy distillates is the primary difficulty encountered in refining. For instance, the heavy oils from the above-mentioned two ITSL runs (244 and 246) have extremely high concentrations of aromatics (C_A) (46 and 51.2, respectively) determined by ^{13}C NMR (Table 29). The aromatics content in single-stage VGOs is even higher. Typical petroleum gas oils have C_A values between 8 and 26. The very high C_A value with the coal-derived raw vacuum gas oils, especially when it is related to heavy polynuclear aromatics, makes the coal-derived VGOs extremely refractory and highly coke-producing during catalytic cracking.

Hydrocracking is a reasonable choice for refining this coal heavy distillate. Generally, two-stage hydrocracking is suitable for feedstocks that are high in hetero-compounds and/or aromatics. Typically, the first-stage reactor is essentially a hydrotreating-hydrocracking system where heteroatom removal takes place so that nitrogen content is reduced to a level tolerable to the second-stage where hydrocracking is completed to extinction of the feed.

In a study conducted by UOP, first-stage hydrocracking of a rerun H-Coal gas oil (435°F-850°F) was done in a once-through operation over a UOP-DCA catalyst in bench-scale continuous units. Under suitable conditions, nitrogen conversions of 99.9+ % can be achieved. Inspection of the feedstock and the first-stage product to be used as feedstock for second-stage hydrocracking is summarized in Table 30 [129]. Hydrogen consumption is a little over 2 wt% of feed, and the liquid yield exceeds 100%, representing hydrogen added to the feed and low gas yield.

Second-stage hydrocracking studies were carried out at maximum gasoline yield mode over a UOP-HCA catalyst, and the 375°F+ stream was recycled to extinction (Table 30). At conditions studied, gasoline with reasonably high octane number (RON, clear 92.1-93.6) was obtained at high liquid yields (92.42-97.38 LV%). At 3820-4400 SCF/bbl hydrogen consumption, the high rate of heat generation by saturation of polycyclics may exceed the heat transfer capacity of a second-stage reactor. It is therefore suggested that there can be a number of arrangements of different catalysts in several reactors for multistage hydrocracking.

Single-stage hydrocracking of the rerun H-Coal atmospheric still bottoms to No. 2 fuel oil, with 600°F+ product recycled to extinction over the UOP-DCA catalyst, can be performed under very severe conditions. But that may not be commercially practical. Two-stage hydrocracking to fuel oil is more flexible, and conditions can be less severe. The gasoline (C₅-375°F) yield is 15.3 LV%, C₄- yield is 4-5 wt%, and No. 2 fuel oil (375°F-600°F) yield is 90.2- 91.2 LV%. Overall hydrogen consumption is about 1600 SCF/bbl.

UOP estimated the hydrogen balance for two-stage hydrocracking of the above feedstock to gasoline. Reforming of the hydrocracker naphtha and steam reforming of C₁-C₃ could provide only 55% of total hydrogen consumed. UOP workers believe that including C₄ in the steam reformer feed should result in a hydrogen balance [129].

The yield of liquid product (C₅ +) is almost linearly correlated with the product aromatic content (Figure 21), which in turn dictates the chemical hydrogen consumption. The naphthenes in naphtha are eventually dehydrogenated during reforming; a naphthene content in hydrocrackate higher than required for 375°F+ extinction operation is therefore not necessary. This could lead to overload of both the hydrocracking and reforming reactors.

Hydrocracking of an EDS coal oil was also investigated by UOP. The hydrocracking feedstocks had an IBP around 400°F and a 90% point around 900°F. The volumetric yields of C₅ + gasoline and butanes from the gasoline mode operation ranged from 105% to 115.5% and 18% to 26%, respectively. The octane number of the C₅ + gasoline ranged from 75 to 83 RON clear. The overall hydrogen consumption ran from 3300 to 4200 SCF/bbl. In the fuel oil mode, yield of environmentally acceptable distillate was about 88%, which was obtained principally in the first stage. The overall hydrogen consumption was about 1650 SCF/bbl [130].

5.6 Summary

1. The naphtha fraction from coal liquids is rich in aromatics and naphthenes, high in octane rating, and therefore is an excellent source for gasoline production. It makes a superior reformer feedstock, and it is also a premium gasoline blending stock. In either case, hydrotreating is required. The heteroatom levels, especially oxygen level, of coal-derived naphthas are high and heteroatom removal by either hydrotreating or extraction is necessary.

2. A kerosene fraction distilled from Texas lignite EDS liquid was hydrotreated by Chevron to make jet fuels with smoke points of at least 20 mm under a hydrogen partial pressure of 1500 psia or higher. However, similar work done by Southwest Research Institute indicates that even the jet-fuel obtained by high-severity hydrotreating did not meet the specifications on API gravity and smoke point. Information on jet fuels from fractions of higher rank coal liquids is not available.

3. Due to its elevated aromatics content, the coal-derived diesel fuel has a very low cetane index, and it must be hydrogenated under a severity high enough to improve its combustion quality as well as its stability.

4. Tests with coal-derived middle distillates on a stationary turbine and a home heating oil burner showed that the smoke emissions are comparable to No. 2 fuel oil. The distillates can not meet the gravity specification for No. 2 fuel oil and No. 2 GT μ s turbine fuel due to high aromatics content, and NO_x emissions are much higher than those of petroleum No. 2 fuel oil. Therefore, hydrotreating is required to make No. 2 fuel oil from coal-derived middle distillates.

5. Coal-derived middle distillates must be hydrotreated to be a good catalytic cracker feed. The optimum hydrotreating level is suggested by UOP to be 11.5-12.0 wt% hydrogen of the cracker feed, which is comparable to petroleum feedstocks in catalytic cracking performance. It may be more beneficial to produce diesel fuel from middle distillates simply by hydrotreatment.

6. The heavy distillates ($650^\circ\text{F}+$) from coal liquids may be incompatible with petroleum counterparts to make heavy fuel oil blends. It is highly recommended that the coal-derived heavy distillates be converted to lighter distillates for producing more valuable transportation fuels. Two-stage hydrocracking of coal-derived heavy distillates can either produce high quality gasoline with high yields, or environmentally acceptable No. 2 fuel oil. If maximum gasoline yield is required, the hydrogen consumption would be as high as 3300-4400 SCF/bbl and the heat transfer capacity of the second-stage reactor may be exceeded. Recycling the $650^\circ\text{F}+$ VGO to extinction during liquefaction seems to be preferable.

7. A considerable portion of the hydrogen consumption during hydrotreating is attributed to oxygen elimination. The oxygen compounds in the peak region (350°F - 450°F) are mostly phenolics, and recovery of the phenolics as a by-product can reduce hydrogen consumption and increase product value.

6.0 HYDROTREATING OF TOTAL COAL LIQUIDS

Straight-run distillation and then refining individual fractions separately according to the product slate, as discussed in the previous section, is the conventional refinery schedule. As an alternative, the total coal liquid can be hydrotreated as a whole and then fractionated to various, supposedly finished products. This is discussed in the present section.

Chevron has done hydrotreating pilot plant studies on coal liquids with the goal of either making specification jet fuel or diesel fuel and a naphtha suitable for catalytic reforming in a single hydrotreating step, or making a product suitable for hydrocracking in a second step [87]. Coal liquids from five different liquefaction processes (SRC-II, EDS, H-Coal, ITSL, and CTSL) were catalytically hydrotreated in laboratory pilot plants. The two-stage coal liquids are: 1. Illinois No. 6 ITSL liquid produced by LCI in its ITSL pilot plant designated as LC-Fining Run 3LCF9 [131]; 2. Wyodak ITSL oil product by LCI [132]; and 3. Wyodak CTSL oil made by HRI in its CTSL pilot plant in Lawrenceville, N.J. [133]. The hydrotreated liquids were distilled to obtain different fractions. In some cases, the oil boiling above the jet fuel range was hydrocracked to extinction in a second catalytic stage to maximize jet fuel production. Test results are summarized in Table 31. The tests were made at 750°F average catalyst temperature, on a single commercial hydrotreating catalyst, Chevron's ICR 106 [84].

To meet either goal, almost all of the heteroatom contaminants had to be removed by hydrotreatment. Typically, the control target for product nitrogen content was <0.5 ppm. Sulfur is relatively easy to remove compared with nitrogen and, therefore, was of little concern in Chevron's study. Oxygen-containing compounds can be at least as hard to remove as nitrogen compounds; however, when the nitrogen was reduced to 0.5 ppm, organic oxygen content was also reduced to less than 5-10 ppm (based on limited analytic results). The relationship between product

nitrogen and hydrogen consumption for three coal liquids is depicted in Figure 22 with a shale oil for reference. More hydrogen is required for shale oil denitrogenation since the shale oil has a higher nitrogen content and its higher boiling range results in more cracking of the high-boilers during hydroprocessing [83].

In addition to the removal of heteroatoms, it is necessary to hydrogenate most of the aromatics in these fractions if finished jet or diesel fuel is to be the main product from a single hydrotreating step. Figure 23 is a comparison of the hydrogen consumption for the four coal liquids required to make products at a given aromatics concentration. The results reasonably conform to their hydrogen and heteroatom contents [83]. This information also indicates that the prime factors in process design and cost estimate for coal liquids refining can be based upon inspections of the coal liquids, without much knowledge of the coal source or the liquefaction process employed [134,135].

Full-boiling-range coal liquids require relatively high hydrotreating severities to remove the heteroatoms and increase the hydrogen content. Of these four single-stage total coal oils, the Wyodak H-Coal oil is the easiest to upgrade, probably because of its high hydrogen content and low average boiling range. For a given boiling range, coal liquids from two-stage liquefaction are easier to upgrade than those made in single-stage processes, due to the effect of the higher hydrogen and lower heteroatom content of two-stage liquids. For coal liquids from a given liquefaction process, a relatively small increase in end point can make the liquid much harder to upgrade. Distilled coal liquid fractions, especially fractions with end points lower than 600°F, are very easy to hydrotreat in comparison to the whole coal liquid [115]. A 900°F end-point Wyodak ITSL oil is much harder to process than 800°F end-point Illinois No. 6 ITSL liquids. The differences are believed to be the result of a higher end point of this Wyodak oil, rather than differences in coal properties [136]. A roughly linear correlation was found [84] between required catalyst temperature and coal-oil end point for a group of ITSL liquids, regardless of coal source (Figure 24). Moreover,

a lower average boiling range also makes processing easier. These are very important observations with respect to coal-liquid hydroprocessing.

If transportation fuels (gasoline, jet, and diesel fuel) are desired products, relatively high severities are required; for example, hydrogen pressure ranging from 1750-2300 psia, temperatures in the range of 750°F- 800°F, and LHSV of 0.5-1.5 vol. feed/vol. catalyst/hr. With the feed end points of <750°F, the catalyst is very stable, and catalyst lives of several years can be predicted. In spite of the relatively severe hydroprocessing conditions, there is little cracking to light gases for coal liquids with end points below 800°F. Liquid volume yields are typically higher than those obtained when hydrotreating petroleum, because of the higher hydrogen input [134-136].

The extent of upgrading is an important factor in final coal liquid composition. Work on Wyodak coal liquid hydroupgrading reveals that the more extensive the upgrading, the higher the yields of low-ring-number compounds produced. The possible causes are heteroatomic ring opening and breaking of alkyl linkages between rings, both contributing to formation of hydrocarbons with less ring numbers [137-140].

The coal rank seems to be another factor in determining the upgrading effect and the composition of upgraded product. For instance, under the same upgrading conditions, the extent of denitrogenation is greater for subbituminous Wyodak coal oil than for the higher-rank Illinois No. 6 coal liquid, and significantly higher yields of low-ring-number compound types were identified for the former. However, for coal liquids from different coal sources upgraded to about the same nitrogen content, no clear trend in terms of ring number distribution as a function of coal rank was evidenced [137].

After hydrotreating, products of similar boiling ranges from different liquefaction processes and different coals were quite similar. The products mainly comprise cyclic hydrocarbons, since heteroatom compounds have been removed. The hydrotreating severity determined the amount of hydrogenation of aromatics to naphthenes. Products from subbituminous coals contained more paraffins than those from bituminous coals. The hydrogen consumption needed for a given product quality from these coal liquids depends on their hydrogen content and heteroatom contents. The hydrogen required in coal-liquid hydrotreating is higher than that usually needed in petroleum hydrotreating [138-140].

An EDS coal-oil blend and an H-Coal oil blend from Illinois No. 6 coal, as well as a 400°F + SRC-II oil derived from Pittsburgh Seam coal, were hydrotreated under different severities to obtain coal-liquid samples with different nitrogen contents: 5000, 2000, 500 ppm, and acceptable levels for 30 °API fuel-oil product, for biological studies at Oak Ridge National Laboratory [141,142]. By adjusting the operating conditions and hence the severities, heteroatom removal and aromatics saturation can be realized to certain extents almost at will. As the hydrougrading severity and hydrogen consumption increase, the heteroatoms contents and aromatics level are reduced while hydrogen content and H/C atom ratio increase. Some data are compiled in Table 32. If severity is high enough, all the heteroatoms can eventually be removed to beyond the detection of certain analytical techniques, most of the aromatics can be hydrogenated, and the product is water-white in appearance [143]. When hydrogen content of SRC-II liquid is increased from 8.4 to 12.24 wt%, essentially 100% of the nitrogen and 95% of the oxygen have been removed. Calculated hydrogen consumptions for this range of conditions varies from 970 to 2880 SCF/bbl, which is within the range reported by other workers [144,145].

High severity hydrotreating of total liquids is required under most circumstances to produce quality transportation fuels, especially jet and diesel fuels. Tables 33 and

34 summarize the yields, hydrogen consumptions, and product inspections achieved by hydrotreating four coal liquids at high severities [104].

Properties of various products obtained from the total coal liquids, hydrotreated as a whole, are discussed in the following subsections.

6.1 Naphtha from Hydrotreated Coal Liquids

Properties of naphthas prepared by hydrotreating single-stage coal liquefaction oils are shown in Table 35. The naphthas are quite similar except that naphthas from low-rank coals are more paraffinic than naphthas derived from bituminous coals. H-Coal naphthas have a somewhat higher paraffin content than two-stage naphthas from the same coal, as revealed by the following data:

Parrafin Contents of Typical 150°F-350°F Naphthas
from
Hydrotreated Coal Liquids

<u>Feed Source</u>	<u>Parraffin, LV%</u>
Wyodak H-Coal	23
Wyodak CTSL	18
Illinois H-Coal	11
Illinois ITSL	7

All the hydrotreated coal naphthas have a high content of cyclic compounds. Compared with naphthas from shale oil, the naphthas from hydrotreated Wyodak H-Coal oil have higher octane ratings as a result of their high ring content (Table 36) [83].

At higher hydrotreating severities, almost all the aromatics in the naphtha fraction are saturated, and virtually no heteroatoms are left. They can be fed directly to the second stage of a catalytic reformer. Much of the hydrogen consumed in the prior hydrotreating step can be recovered in the reforming stage. Reforming yields will be high, as it is reported that with a given octane reformat, the liquid yields from EDS naphtha are at least 10 vol% higher than the expected yields for Arabian light naphtha [146].

Table 37 shows properties of the naphtha products obtained from SRC-II liquids hydrotreated at high and intermediate severities, with hydrogen consumption of > 2750 and 1750-2750 SCF/bbl, respectively [144]. At lower severity hydrotreating, the naphtha will require further hydrorefining in a conventional hydrotreater to remove the remaining heteroatoms before being sent to the reformer.

Analytical results of naphtha samples (< 392°F) derived from eight upgraded coal liquids are listed in Table 38. Obviously, these naphthas have high contents of cyclic compounds, especially cycloparaffins, which make them very suitable for reforming. No olefins were detected from these hydrotreated naphthas [137].

If the refining goal is mainly gasoline, then the portion of hydrotreated total coal liquid heavier than naphtha needs to be hydrocracked to maximize gasoline production. In the all-gasoline mode, the RONs of C₅-180°F and 180°F+ naphthas from hydrocracking Illinois and Wyodak H-Coal and SRC-II liquids (denitrified) are 88-90 and 69-75, respectively [147]. The hydrocracked naphtha can also be combined with the hydrotreated naphtha and the blend can then be reformed.

For the production of transportation fuels as primary products, there is an opinion that hydrotreating the naphtha and heavier distillates separately holds no particular advantage [83]. However, the total coal liquid must be hydrotreated at high severity to reduce the heteroatoms to very low levels (N < 1 ppm in Chevron's work)

for the naphtha to be acceptable to the reforming catalyst. Under such a high severity hydrotreatment (with hydrogen consumption > 2750 SCF/bbl), essentially all the aromatics in the naphtha are hydrogenated into naphthenes, which in turn are dehydrogenated back to aromatics during subsequent reforming. Referring to Section 5.2, hydrotreating an IBP-400°F raw naphtha cut from an H-Coal liquid to reformer stock can be achieved at moderate severity of operation with a hydrogen consumption of only 480 SCF/bbl. Moreover, fractions heavier than naphtha may not need a very high severity in hydrotreatment. Hydrotreating the coal-derived fractions separately is a definite advantage even if the naphtha is to be reformed.

6.2 Jet Fuel Fraction from Hydrotreated Coal Liquids

After the heteroatom contents have been reduced to acceptable levels, the critical point for jet fuel from coal-derived liquids is the aromatics content. To meet the ASTM smoke-point specification (20 mm, min), most of the aromatics in the fraction had to be hydrogenated. Figure 25 is a plot of smoke point data vs. aromatics content of kerosene-type jet fuels from various hydrotreated coal liquids. At a given aromatics content, those from Wyodak (subbituminous) coal have smoke points 2-3 mm higher than those from Illinois No. 6 (bituminous) coal, a consequence of the higher Wyodak paraffin content. The Illinois jet fuels meet the smoke specification of 20 mm at 10 LV% aromatics or lower, while the Wyodak jet fuels meet the specification at about 15 LV% aromatics [148].

Except for restrictions on aromatics and olefins (for stability consideration), the proportions of hydrocarbon types are not directly controlled. The requirements on density, energy content, and freezing point favor isoparaaffinic and naphthenic composition. The hydrocarbon constituents of most JP-4 fuels are primarily normal and iso-paraffins (50-70 LV%) and cycloparaffins (20-40 LV%), with alkyl benzenes less than 20 LV%. Refiners usually produce JP-4 from a blend of 60%-70% naphtha and 30%-40% kerosene fraction from petroleum.

Polycyclic naphthenes are considered to be ideal components for high-energy jet fuels. Regarding the heat of combustion, bicyclic naphthenes average about 135,000 Btu/gal, tricyclic naphthenes average about 145,000 Btu/gal, and four-ring naphthenes approach 150,000 Btu/gal [149]. In comparison, conventional jet fuels range from about 120,000 to 127,000 Btu/gal. Catalytic cracking cycle oils could be hydrogenated to high-energy jet fuels due to their high cyclic contents [150]. Naphthenes with two or three rings are believed to give the best compromise among various properties required for jet fuels: high volumetric heating value, satisfactory gravimetric heating value, acceptable thermal stability, very low freezing point, acceptable low-temperature viscosity, low volatility, high flash point, and acceptable flame characteristics (smoke point, etc.). No other hydrocarbons in the jet fuel range have all of these properties. The high cyclic contents of coal-derived liquids makes them a very promising feedstock for making high-energy jet fuels.

Severe hydrotreating of single-stage coal liquefaction liquids yields 75-87 LV% jet-fuel fraction (TBP 250°F-600°F). These fractions meet almost all of the specifications for kerosene-type Jet A fuel (Table 39). The only property that was not met consistently was the API gravity, for example, the SRC-II jet-fuel fraction in Table 39. The API gravity of these fractions could be met by adjusting the end point from 600°F to 550°F [83]. Representative jet fuels (250°F-550°F) made from hydrotreated coal liquids meet all ASTM Jet A specifications, as evidenced by the test data listed in Table 40 [148]. These coal liquids were obtained from Illinois No. 6, Wyodak, and Texas Big Brown coals by single-stage liquefaction processes. Table 41 is a comparison between jet fuels from different sources with Jet A specifications. Jet fuels produced from these hydrotreated coal liquids easily passed the very stringent thermal oxidation stability test (JFTOT) whenever the specifications for aromatics and smoke point were met. Severe stability requirements mean that heteroatom content must be very low, and usually the nitrogen content is less than 10 ppm for petroleum-derived jet fuel [83].

Properties of two sets of jet fuels from hydrotreated two-stage Illinois No. 6 coal liquids are shown in Table 42; the first set from hydrotreating alone, the second from hydrotreating plus hydrocracking of the total coal liquids. The first sample in each set boils between 250-550°F, the second between 350°F and 550°F. The jet fuel fractions from hydrotreated ITSL liquids meet Jet A specifications except those for gravity and viscosity [148]. Changing the initial point from 350°F to 250°F had little effect because ITSL liquids contain relatively little 250-350°F material, and little cracking occurred during hydrotreatment. This may indicate that coal-derived jet fuels should contain adequate amount of front-ends (250-350°F) to meet gravity and viscosity requirements.

Group analysis data for hydrotreated Wyodak ITSL and CTSL liquids are shown in Tables 43 and 44. Jet fuels from hydrotreated Wyodak coal liquids have somewhat higher paraffin contents, and products from CTSL processes have even higher concentration of paraffins than those obtained from ITSL process. Products from ITSL bituminous coal liquids have the lowest paraffin contents and the highest densities of any of the coal liquids studied [148].

Figure 26 plots the smoke point versus aromatics content for jet fuel obtained by hydrotreating a distillate from raw EDS liquid and by hydrotreating whole EDS liquid and then distilling. Obviously, the jet fuels obtained by hydrotreating the raw distillate cut have significantly higher smoke points than the jet fuels distilled from hydrotreated total coal oil. The smoke point advantage increased from zero, when both jet fuels contain about 40% aromatics, to 5 mm, when all the aromatics are saturated. The main reason for this difference is that for the total coal-oil hydrotreating, some heavy aromatics (which boil above 600°F) are saturated and the resultant polycyclic naphthenes boil below 600°F. These polycyclic naphthenes therefore enter into the jet fuel range. The polycyclic naphthenes have relatively low hydrogen content and low smoke point, and therefore lower the smoke point of the

jet fuel. Their presence also increases the average ring number per molecule, which is supported by analytical data [119].

Hence, it is clear that total coal-liquid hydrotreating produces a jet fuel with lower quality, and consequently separate hydrotreatment of different fractions is preferred when jet fuel is the main product.

6.3 Diesel Fuel Fraction from Hydrotreated Coal Liquids

Diesel fuel fractions from coal liquids are also characterized by high aromatics content. Group analysis data for 392-617°F fractions from eight upgraded TSL coal liquids are shown in Table 45. In most cases, the aromatics content is 50% or more [137]. According to Chevron's work, diesel products from both single-stage and two-stage liquefaction liquids meet typical ASTM specifications, provided a relatively high degree of hydrogenation of the total coal liquid is undertaken to satisfy the minimum cetane-number requirement of 40 for the diesel fuel cut [87].

The 250°F+ fractions from the hydrotreated coal liquids, at the conditions employed to prepare jet fuel, also meet all specifications for No. 1 diesel fuel within experimental error, as shown in Table 46. Comparison of diesel fuels from different sources is presented in Table 47. Heteroatoms must be removed to a certain level as required for stability, however, this level is not known for coal-derived diesel fuels. For petroleum diesel fuels, nitrogen level is usually 500 ppm or below [83], and Sullivan et al. [151] found that 400 ppm nitrogen was the maximum concentration at which hydrotreated shale oil products remained stable.

Table 48 lists some data for 250°F+ fractions from hydrotreated ITSL coal liquids [132,152]. These fractions do not meet smoke point specifications for jet fuel, but their cetane numbers qualified them for diesel fuels. Adjustments can be made to modify their boiling range and viscosity, etc.

No. 1-D fuel is used in small engines that require frequent speed or load adjustments. Diesel fuel No. 2-D is more widely used in engines for heavy mobile or industrial service, which requires a higher flash point of 125°F (min). If the 300°F+ fraction is cut, then the flash point requirement for No. 2-D fuel can be satisfied. For diesel fuel used in typical climates, the initial points could be adjusted further upward to meet viscosity and D86 90% point requirements. These diesel fuels also passed accelerated oxidation and thermal stability tests [83].

Figure 27 demonstrates the relationship of cetane number versus aromatics content for products from single-stage and two-stage processes. With the two-stage oils, the specification was met with an aromatics content of about 20 LV%, while an aromatics content of less than 10 LV% is required with a single-stage liquid. These differences, however, may be due to the differences in boiling ranges of the diesel fuels rather than the differences in processing (single stage vs. two stage). For instance, the following table compares pairs of samples of different boiling ranges, with essentially the same paraffin and aromatics contents within a given pair. For each pair, the higher boiling sample has the higher cetane number. Of course, more paraffinic diesel fuels have higher cetane numbers, with otherwise equal properties.

Effect of Boiling Range on Cetane Number [87]

Source	Initial, °F TBP	Midpoint, °F (TBP)	Cetane No.	Aromatics, LV%	Paraffins, LV%
Wyodak CTSL	250	414	44.2	3.9	9.5
	350	454	48.7	4.6	7.7
Illinois ITSL	250	520	43.1	9.8	<1
	350	538	4.3	11.7	<1
Illinois H-Coal	250	393	35.9	15.6	3.6
	350	438	37.7	18.5	3.7

As with the jet fuels described before, the hydrotreated coal-derived diesel fuels have excellent cold-weather properties and high volumetric energy contents, since they are essentially all cyclics, especially naphthenes.

Coal-derived liquids respond well to certain cetane improvers. Because of the high cost of hydrogen, it may be cost-effective to substitute cetane improvers for hydrotreating severity to some extent. For instance, adding 0.3 LV% octyl nitrate, a commercial cetane improver, to diesel fuels from hydrotreated Wyodak H-Coal oil was shown (Figure 28) to increase the cetane number by 6-8 points [83].

It is also reported that the calculated cetane indices for twelve coal-derived diesel fuels are lower than measured cetane numbers by an average of about eight units. This means that the cetane index (ASTM D976-66) method should not be used to predict cetane numbers for coal-derived diesel fuels without correction [83].

6.4 Fuel Oil Fraction from Hydrotreated Coal Liquids

No. 2 fuel oil equivalent product can be obtained from coal liquids by hydrotreatment. Table 49 lists properties of 250°F+ fractions from moderately hydrotreated single-stage coal liquids in comparison with ASTM No. 2 fuel oil specifications [83]. These fractions have about 50-60 LV% of aromatics and show very low pour points; they all have viscosities just below the ASTM minimum of 1.8-2.0 cSt. The gravities are below ASTM minimum of 30°API. Viscosity and gravity specifications could be met by increasing hydrotreating severity. For instance, hydrotreated at 2000 psig, the Texas lignite total liquid has an API gravity of 32.8, and its 600°F- distillate has an API gravity of 34.7 [153].

6.5 Two-Stage Hydrotreating of High End-Point Coal Liquids

The coal liquids with end points below 775°F can produce specification jet and diesel fuels after hydrotreatment under relatively severe conditions. However, with high end-point coal liquids, even after hydrotreating under severe conditions, the jet and diesel fuels produced have marginal properties and are too aromatic to meet specifications directly. Perhaps this is the reason why SwRI did not obtain a diesel fuel meeting all the specifications, since their feedstock has a high end point of 823°F [108]. Hence, for high end-point coal liquids, two-step hydrotreating was investigated by Chevron. The two steps are: 1. hydrotreating at relatively high temperatures to remove most of the heteroatoms, and 2. further hydrogenation at lower temperatures for more aromatics saturation under favorable conditions, since hydrogenation of some of the high-boiling polycyclic-aromatic compounds is thermodynamically favored at lower temperatures [87]. Experimental results show that two-stage hydrotreating with a second-stage temperature of 650°F reduced the aromatics content to 12 LV%. The jet and diesel fractions from hydrotreated coal liquids readily met and even exceeded smoke point and cetane number specifications. End-point reduction was also remarkable with less than 5% of the hydrotreated coal liquid boiling above the diesel range. Chevron suggested the two-step hydrotreating as an alternative to the hydrotreating/hydrocracking route for upgrading high end-point coal liquids, provided diesel fuel is a desired end product [87].

6.6 Summary

As an alternative refining scheme for coal liquids, the total coal liquid can be hydrotreated and then fractionated into various products.

1. Coal liquids from two-stage liquefaction processes are easier to upgrade than single-stage liquids with comparable boiling range due to lower N and O contents. Relatively small increases (viz. 750°F vs 650°F) in end points make the coal

liquids much harder to upgrade. After hydrotreatment, coal liquids of comparable boiling ranges from different liquefaction processes and different coals are quite similar. The hydrotreated coal liquids consist mainly of cyclic hydrocarbons. Hydrotreated coal liquids from subbituminous coals contain more paraffins than those from bituminous coals.

2. Products obtained from hydrotreated coal liquids have the following properties:

Naphtha -	The total coal liquid must be hydrotreated at a relatively high severity to yield a naphtha fraction acceptable as a reformer feedstock.
Jet Fuel -	The 250-550°F fraction obtained from severely hydrotreated single-stage coal liquids meet all ASTM specifications for kerosene-type Jet A fuel. The jet fuel fractions from hydrotreated ITSL liquids meet most of Jet A specifications except gravity and viscosity. Hydrotreating the total coal liquid does not appear to be a reasonable scheme to produce jet fuel from two-stage coal liquids.
Diesel Fuel -	Diesel fuels from both single-stage and two-stage liquids meet typical ASTM specifications, including the minimum cetane number requirement of 40, provided a relatively high degree of hydrogenation of the total coal liquid is undertaken. Coal-derived diesel fuels respond well to certain cetane improvers, such as octyl nitrate. The calculated cetane index for coal-derived diesel fuels

are lower than measured cetane numbers by an average of about 8 units.

Fuel Oil - Coal-liquid product equivalent to No. 2 fuel oil can be obtained by hydrotreating total coal liquids with medium severity.

3. The major disadvantage to hydrotreating the total liquids as a refining scheme is the difficulty posed by their wide boiling range and high end points. High severity is required for the total coal liquid hydrotreatment to make specification jet fuel or diesel fuel and a reformer feedstock. Almost all of the heterocompounds had to be removed; consequently, an essential part of the aromatics was saturated. This results in a much higher hydrogen consumption compared with the hydrogen consumption for moderate-severity hydrotreatment of a raw naphtha cut from coal liquids. An operation of saturating all the aromatics in naphtha by hydrotreating and then dehydrogenating them by reforming is a wasteful combination.

4. Another disadvantage to hydrotreating the total coal liquids is that the jet fuel fraction thus obtained has lower quality, particularly a lower smoke point, compared with hydrotreating the kerosene fraction from the same coal liquid under the same severity.

5. The operation of total-coal-liquid hydrotreating excludes the possibility of separating the 350-450°F fraction, which contains valuable chemicals such as phenols and cresols. The hydrogen consumed in converting oxygen to water lowers the hydrogen efficiency in hydrotreatment.

6. The total-coal-liquid hydrotreating scheme is therefore not recommended for coal-liquid refining due to the difficulty in hydrotreating, lack of process selectivity and flexibility, and lower product quality.

7.0 HYDROCRACKING OF TOTAL COAL LIQUIDS

When a relatively hydrogen-deficient, heteroatom-rich heavy coal liquid is to be converted to higher value, lighter fuel products with reduced heteroatom content, hydrocracking is a major tool. Hydrocracking is a versatile process that can be varied to make naphtha only, or a combination of naphtha and middle distillate. Similar to hydrotreating, hydrocracking may also be practiced in two ways: hydrocracking of heavy raw coal liquid distillates as described in Section 5.0; or hydrocracking the total coal liquid and then distilling into various fuel products, as will be discussed here.

Chevron studied hydrocracking of SRC-II, H-Coal, and ITSL liquids in its pilot plant. The results for recycle hydrocracking of some denitrified coal liquids in an "All Gasoline Mode" are summarized below [147].

Feedstock	Chemical H ₂ Consumption (SCF/bbl) of Feed		Yields, LV%	
	Hydrocracker only	Hydrocracker + Hydrotreater	C ₅ + Total	180- 315°F
350°F+ HDN Illinois H-Coal	1400	3100	92.8	62.1
350°F+ HDN Wyodak H-Coal	2450	1850*	93.1	56.6
350°F+ HDN SRC-II	2250	3850	95.9	62.2

*H₂ consumption data for Wyodak feed are suspicious.

**315°F recycle cut point for all samples.

The yield of total naphtha from the hydrocracker is excellent, between 93 and 96 LV%. The naphtha yield can be increased by 3 LV% if the recycle cut point (RCP) is raised to 350°F; and correspondingly, the hydrogen consumed can be reduced by 100-300 SCF/bbl. Total cyclics content in the C₅-180°F cut is above 40 LV%, and for 180°F-315°F cut it ranges from 85 to 89 LV%. The RON for the C₅-180°F cut is 88-90, and that for 180-315°F naphtha is between 70-75.

Hydrocracked coal naphthas are superior reforming feedstocks. Two naphthas obtained by hydrocracking H-Coal gas oil were reformed over a commercial Platforming catalyst by UOP [114]. Since these feeds are highly naphthenic, reforming temperature requirement is relatively low. The yield-octane correlation for 400°F EP naphtha reforming is illustrated in Figure 29. The naphthas from the hydrotreater and from the extinction recycle hydrocracker can also be severely reformed to produce BTX precursor compounds (C_6 , C_7 , and C_8 cyclics) with a yield of 52.5-58.9%.

The total coal liquids may be hydrotreated before hydrocracking. If the nitrogen is removed to less than 0.5 ppm in the whole coal-liquid hydrotreater, a first-stage hydrocracker is not necessary; the hydrocracker can be a single second-stage [154].

A hydrocracking pilot-plant test was also conducted on hydrotreated full-boiling-range ITSL liquids from Lummus to make both naphtha and jet fuel products. Particular interest was on the smoke point and yield of the jet fuel fractions, which are depicted in Figure 30 [119]. At a 550°F recycle cut point, the jet fuel meets the ASTM smoke point specification of 20 mm. The yield is 84 LV% based on fresh feed to the first-stage hydrotreater. When recycle cut points (RCP) are lower, the smoke points exceed the specification but the yields are lower. Figure 31 demonstrates the smoke points of narrow boiling fractions as a function of mid-boiling points. The fractions with a mid-boiling point below 450°F have a smoke point > 20 mm. The jet fuel gravity specification of 37 °API is fulfilled at recycle cut points up to 525°F. At 550°F cut point, the gravity of the fraction is 34.4°API, well below the current specification.

Therefore, by controlling the recycle cut point during coal-liquid hydrocracking, both the smoke point and gravity of the jet fuel obtained can meet or exceed the ASTM specifications. These two requirements are difficult to be satisfied by the jet fuel fraction obtained from total liquid-hydrotreating. Chevron workers concluded that

hydrocracking is an excellent way to maximize jet fuel production from two-stage liquefaction coal oils [119].

As discussed in Section 6.2, the jet-fuel fractions from hydrotreated two-stage liquids do not meet gravity and viscosity requirements, even if the smoke point is marginally satisfied. This is probably due to the lack of light-ends (250-350°F). To meet gravity specifications, hydrocracking is necessary for jet fuels to be produced from hydrotreated two-stage coal liquids. Since hydrocracking converts high-boiling fractions into lighter fractions, 250-550°F jet fuel fraction of hydrocracked ITSL liquids easily meet the viscosity specification, and the smoke point was above specification (Table 42). The gravimetric heats of combustion of these samples by ASTM D1405 were all about 18,400 Btu/lb, just meeting the ASTM specification. The API gravity can be adjusted further by controlling the RCP in hydrocracking.

Table 42 also lists group type composition for these fractions. It is evident that hydrocracking increased the naphthene content in the fraction and caused a shift in naphthene distributions to more rings per average molecule at a given boiling point. The jet fuel from hydrocracked coal liquids has a significant quantity of four-ring naphthenes, whereas the jet fuel from hydrotreated coal liquids does not. The former also has less alkyl substitution on the cyclics than the latter and can be explained by paring reaction and/or new ring formation. These phenomena are further proved by detailed analyses of narrow fractions in the jet-fuel range from hydrotreated and hydrotreated plus hydrocracked Illinois No. 6 ITSL liquids as reported in Tables 50 and 51 [148]. This suggests that in order to produce quality jet fuels, especially from two-stage coal liquids, hydrocracking the middle distillate but not the total coal liquid may be the best way.

8.0 CONCLUSIONS AND RECOMMENDATIONS

A number of studies on properties and refining of coal liquids, mostly obtained from liquefaction processes at earlier development stages, provide information which is principally applicable to the refining of coal liquids from current two stage liquefaction processes.

Modern refining technology is capable of processing coal liquids into various transportation fuels meeting all requirements. The major tool is hydroprocessing. The main task is to determine a reasonable product slate and the most cost-efficient refining scheme.

8.1 Properties of Coal Liquids

1. The liquid products from today's direct liquefaction processes are much lighter both in gravity and in boiling range, and contain much less hetero-compounds than before. They are essentially metal and resid-free and very low in sulfur. Their nitrogen content is comparable to petroleum, and their oxygen content is within the petroleum oxygen range but at the higher end. Coal liquids bear fundamental similarities with petroleum, but are characterized by their elevated cyclics content and relatively high oxygen level.

2. Coal liquids derived from different coals and different liquefaction processes are basically alike and differ only quantitatively in component content and distribution. Coals of lower ranks, viz. subbituminous coals and lignites, yield liquid products containing more paraffins and oxygen compounds than liquid products from high-rank coals. These features should be considered when cheaper coals with high liquid yields are sought for liquefaction as a cost-reduction measure as recently suggested [155].

8.2 Product Slate from Coal-Liquids

1. Coal liquids are an excellent source of gasoline production because of the high cyclics content (68-85%) in the naphtha fraction. The motor octane number (MON) of raw coal naphthas ranges from 70 to 83. Gasoline can be readily obtained by mildly hydrotreating a straight-run coal naphtha. Coal-derived naphthas are also superior reforming stocks. Gasoline production can be maximized by hydrocracking or catalytic cracking of hydrotreated middle distillates from coal liquids.

2. Although specification jet-fuels were obtained in certain cases, it is difficult in general to produce jet fuels meeting the smoke point and density specifications even if high-severity hydrotreatment is applied to coal liquids. Low-rank coal liquids may be an easier feedstock, and hydrocracking seems to be a better technology for jet fuel production from two-stage coal liquids. Coal-derived jet fuels have an excellent cold-weather performance and a high volumetric heat of combustion.

3. The coal-derived diesel fuel must be hydrogenated under a severity high enough to improve its combustion quality (cetane number) as well as stability. However, the diesel fuel is easier to produce from coal liquids than the jet fuel, and its good response to additives (such as cetane number improver) mitigates the severity required on hydrotreatment.

4. The recovery of phenolic compounds concentrated in the 350-450°F fraction of coal liquids may provide a valuable by-product and reduce hydrogen consumption, and therefore merits consideration.

5. A gasoline-diesel fuel product slate (by hydrotreating the coal-derived naphtha and middle distillate) and an "All-Gasoline" product slate (by hydrotreating the

naphtha and hydrocracking the distillate) are two realistic production schemes for coal-liquid refining.

8.3 Coal Liquid Refining Technologies

1. Various licensed hydrotreating processes are available for feedstocks with various levels of heteroatoms and Conradson carbon content. Hydrotreating of coal-derived liquids and their fractions is technically feasible, as confirmed by numerous experimental studies.

2. Reforming feedstocks are subject to stringent restrictions on sulfur (less than 10 ppm), nitrogen (usually less than 1 ppm) and oxygen (not exceeding 30 ppm); therefore, hydro-upgrading of coal naphtha before reforming is mandatory.

3. Hydrocracking is an efficient way to produce specification jet fuels and diesel fuels or to maximize gasoline production from coal liquids. However, coal-liquid hydrocrackers must be specifically designed and reactors properly arranged to take care of the reaction heat related to higher hydrogen consumption.

4. Coal liquids must be upgraded to higher hydrogen content to improve the conversion and gasoline yield and reduce coke make during catalytic cracking. The heteroatoms level will be significantly reduced during hydro-upgrading and poses no problem for the cracking catalysts.

In short, coal liquids can be processed by existing refining techniques and no extraordinary pretreatments are necessary.

8.4 Refining Scheme for Coal Liquids

1. Among the three refining schemes discussed in Sections 5.0, 6.0, and 7.0, the total-coal-liquid hydrotreating operation is not recommended because 1) it has to be conducted under the highest severity dictated by the most difficult product to make, 2) the heavy ends in the total coal liquid make the hydrotreating considerably less cost-effective, and 3) the quality of the jet fuel obtained in this scheme is significantly lower.

2. The simplest and most economical refining scheme is to distill the coal liquid into naphtha and diesel fuel fraction, then hydrotreating them separately to make a gasoline and diesel fuel (or blending stocks). Catalytic reforming of hydrotreated coal naphthas may not be a good way in view of the trend toward reduction of aromatics content in gasoline.

3. Based on coal-liquids characterization, maximizing gasoline production up to an all-gasoline mode of operation may be the most profitable refining strategy for coal liquids. This can be realized by hydrocracking or hydrotreating plus catalytic cracking of the 350° F⁺ fraction of coal liquids, and hydrocracking is probably a better way to manufacture gasoline with less aromatics content.

4. Jet fuel production from coal liquids is a difficult task as far as gravity and smoke-point requirements are concerned. The success in making jet fuels by hydrotreatment of coal liquid fractions needs further verification. Hydrocracking of coal-derived middle distillates, possibly including some ring-opening reactions, appears to be an effective way to maximize specification jet-fuel production.

5. The oxygen peak in the 350-450°F boiling range strongly suggests the separation of this fraction. Phenolics can be recovered by certain means such as

extraction. This will appreciably reduce hydrogen consumption and may improve the liquefaction economics.

6. A simplified block flowsheet, based on the refining scheme involving separate refining of coal-liquid fractions, is suggested (Figure 32). It also includes the recovery of oxygen compounds in the 350-450°F fraction. It is a flexible flowsheet that can be adjusted to different operating modes:

a) For a simple operation of gasoline-diesel fuel production, the crude coal liquid is fractionated into naphtha, 350-450°F fraction, and a 450°F+ fraction. The naphtha fraction is hydrotreated into a gasoline blending stock. The 350-450°F fraction is extracted to recover phenolics, and its raffinate joins the 450°F+ fraction, which is then hydrotreated to make diesel fuel. A small amount of fuel oil may be produced to maintain a proper end point of diesel fuel and can be used as process fuel;

b) For an all-gasoline mode of operation, the raffinate of the 350-450°F fraction combines with the 450°F+ fraction and the blend is then hydrocracked. Either the hydrotreated naphtha or the hydrocracked naphtha, or their combination, can be reformed if so desired; and

c) If jet fuel is the desired product, then the hydrocracker is operated at a recycle cut point suitable for jet fuel production.

In operating modes b) and c), no fuel oil is produced due to recycle hydrocracking.

This transportation-fuel type refinery comprises only five refining units: crude distillation, naphtha hydrotreating, reforming, phenolics recovery, and distillate

hydrotreating or hydrocracking. These units are available, except for phenolics extraction, in almost any petroleum refinery.

8.5 Research Recommendations

On the basis of research accomplishments accumulated to date, further research needs, especially on refining of modern two-stage coal liquids, are delineated as follows:

1) Gasoline Production.

Hydrotreatment of straight-run coal naphthas with different end points to make quality gasoline blending stocks should be thoroughly investigated. Oxidation stability is the major concern. Optimum cut point, hydrotreating severity and hydrogen consumption need to be determined.

The all-gasoline-mode hydrocracking of various coal-derived distillates (light, middle, heavy and wide-boiling) should be studied. The target is to define the optimal conditions to achieve highest gasoline yield with minimum hydrogen consumption.

Another route for all-gasoline operation is to hydrotreat the coal distillate plus catalytic cracking. The oxidation stability of the cracked gasoline must be studied to determine the necessity of product hydrotreating. An economic comparison between hydrocracking and hydrotreating plus catalytic cracking is necessary.

The determination of blending octane number of coal-derived gasoline (hydrotreated, cracked, and hydrocracked) could provide information not available in the literature. Engine tests for coal-derived gasoline, singly and blended with gasoline

components from other sources, such as petroleum and Fischer-Tropsch products, are appropriate at this stage of coal liquefaction development.

2) Diesel Fuel Production.

A reasonable route for manufacturing coal-derived diesel fuels is to hydrotreat coal distillates of proper boiling ranges with the addition of suitable additives. Studies are needed to determine the optimal boiling range and additives so that the lowest hydrotreating severity is required to produce specification diesel fuels. Hydrotreating a wide-boiling distillate with a very high end point is not justified, either technically or economically.

3) Jet Fuel Manufacture.

The major difficulty in jet fuel manufacture from coal liquids is to meet density and smoke-point specification. However, coal liquid hydrorefining can yield highly-naphthenic light distillates with high volumetric heating values. Tailoring the coal-derived light distillate as a high-density jet-fuel range-extender is advisable. To make jet fuels via hydrotreating, the critical point is to select a feedstock, either kerosene or a wide-boiling cut, with an appropriate boiling range. The same is true with hydrocracking a coal distillate to maximize jet-fuel production. In both cases, it is recommended that research efforts be concentrated on the selection of suitable feedstocks, and high end point must be avoided. Low-rank coal distillates seem easier to refine into jet fuels, a point that needs further verification.

4) Oxygen Compounds

It is recommended that studies on the separation and recovery of phenolic compounds from the 350-450°F fraction be conducted, and the extracts be identified. A market survey for phenolic by-products is needed.

Recovery and utilization of oxygen compounds as octane enhancers and cetane improvers is beyond the scope of this review. Substituted phenols have long been known to possess antiknock activity. Creosote, a phenolic mixture with high xylenol content, displays an antiknock activity similar to MTBE. Benzofuran, whose derivatives constitute the second largest oxygen-containing group in coal liquids, was also found to be characterized by significant antiknock capability [156]. This area merits further investigation.

5) Economic Studies

Economic studies are strongly recommended for coal-liquid refining, which include techno-economic comparison of different refining schemes; evaluation of refining technologies, such as hydrocracking vs. hydrotreating plus catalytic cracking of coal distillates; and naphtha hydrotreating vs. hydrotreating plus reforming. The economic viability of phenolics extraction also needs to be assessed.

6) Physical Properties and Thermodynamic Data

Due to the highly cyclic nature and high heteroatom content of coal liquids, application of traditional correlations for predicting physical and thermodynamic properties of petroleum and its fractions to coal liquids leads to substantial errors. Specific correlations for coal liquids are urgently needed, and continued research in this area is clearly justified.

REFERENCES

1. Rao, S.N.; Schindler, H.D.; McGurl, G.V.; and Hickey, R. "Direct Liquefaction Program - Development Status and Future," presented at 15th International Conference on Coal & Slurry Technology, Apr. 23-26, 1990, Clearwater, FL.
2. American Petroleum Institute. Inform. Bull. No. 11. Philadelphia, PA. 1958.
3. Annual Book of ASTM Standards, Section 5, "Petroleum Products, Lubricants and Fossil Fuels." 1989.
4. Hengstebek, R.J. "Petroleum Processing," McGraw-Hill, New York, 1959.
5. Hydrocarbon Processing, 63 (9), 88 (1984).
6. Hood, R.L., et al. API Refining Meeting, May 11-14, 1981. Chicago, IL.
7. Hydrocarbon Processing, 56 (5), 97 (1977); 63 (9), 87 (1984).
8. _____, 59 (6), 73 (1980); 63 (9), 85 (1984).
9. _____, 67 (9), 78 (1988).
10. Reynolds, et al. "Chevron's Pascagoula Residuum Hydrotreater Demonstrates Versatility," NPRA Annual Meeting, March 24-26, 1985. San Antonio, Texas.
11. Hydrocarbon Processing, 63 (9), 91 (1984).
12. Linsay, D.A., et al. API Meeting, May 16, 1984. New Orleans, LA.
13. Hydrocarbon Processing, 67 (9), 78 (1988).
14. Third Conference on Heavy Crude and Tar Sands, July 22-31, 1985. Long Beach, CA.
15. Hydrocarbon Processing, 63 (9), 77 (1984).
16. "Design and Process Modeling of a Heavy Gas Oil Hydrotreater," Third Iranian Congress of Chem. Eng., Autumn 1977.
17. Hydrocarbon Processing, 63 (9), 74 (1984); 58 (5), 103 (1979).
18. _____, 63 (9), 75 (1984); 52 (9), 131 (1973).

19. _____, 63 (9), 71 (1984).
20. _____, 63 (9), 90 (1984).
21. _____, 63 (9), 89 (1984).
22. _____, 58 (9), 136 (1979); 63 (9), 79 (1984).
23. _____, 63 (9), 84 (1984).
24. _____, 63 (9), 70 (1984).
25. _____, 67 (9), 79 (1988).
26. Baron, K., et al. Ketjen Catalyst Symposium, May 27-30, 1984. Amsterdam, The Netherlands.
27. Hydrocarbon Processing, 63 (9), 78 (1984).
28. Petroleum Engineer, 28 (3), C37 (1956).
29. Murphy, J.R.; Smith, M.R.; and Viens, C.H. Oil & Gas J. 88 (23), 108 (1970).
30. Gary, J.H. and Handwerk, G.E. "Petroleum Refining," Marcel Dekker, New York, 1959.
31. McFatter, W.; Meaux, E.; Mounce, W.; and Van Driesen, R. Oil & Gas J. 67 (27), 119 (1969).
32. Hydrocarbon Processing, 67 (9), 70 (1988).
33. Van Driesen, R.P., et al. "Technique for High Conversion Residual Hydrocracking Demonstrated," AIChE National Meeting, April 7, 1986.
- 33a. Beaton, W.I., et al. "Operating Experience with Amoco's LC-Fining Resid Crackers," presented at the 1986 NPRA Annual Meeting, March 23- 25, 1986, Los Angeles, CA.
- 33b. Van Driesen, R.P., et al. "Upgrading Heavy Oil to Pipeline Quality," presented at API Mid-Year Refining Meeting, May 14-17, 1979. San Francisco, CA.
34. Hydrocarbon Processing, 67 (9), 71 (1988).

35. Sue, H., et al. "Mild Resid Hydrocracking for Heavy Oil Upgrading," presented at UNITAR International Conference on Heavy Crude and Tar Sands, Aug. 7-12, 1988. Edmonton, Alberta, Canada.
36. Oil & Gas J., 82, March 26, 1984.
37. Hydrocarbon Processing, 63 (9), 101 (1984).
38. _____, 67 (9), 71 (1988).
39. Paper AM-84-35. NPRA Meeting, March 25-27, 1984.
40. Watkins, C.H. and Jacobs, W.L. Hydrocarbon Process. 45 (5), 164 (1966).
41. Craig, R.G.; White, E.A.; Henke, A.M.; and Kwolek, S.J. Hydrocarbon Process. 45 (5), 159 (1966).
42. Ward, J.W.; Hansford, R.C.; Reichle, A.D.; and Sosnowski, J. Oil & Gas J. 71 (22), 69 (1973).
43. Hydrocarbon Processing, 67 (9), 73 (1988).
44. Oil & Gas J., 79 (22), 102 (1981).
45. Hydrocarbon Processing, 57 (5), 117 (1978); 67 (9), 73 (1988).
46. "New Hydrocracking Catalysts for High Quality Distillate Production," NPRA Annual Meeting, 1987. San Antonio, Texas.
47. Hydrocarbon Processing, 67 (9), 69 (1988).
48. Laity, et al. "Maximizing Hydrocracking Flexibility Using Chevron Technology," Third Refinery Technology Conference, March 7-9, 1988. Visakhapatnam, India.
49. Hydrocarbon Processing, 63 (9), 98 (1984).
50. _____, 59 (10), 137 (1979); 67 (9), 72 (1988).
51. Frye, C.G.; Muffat, D.L.; and McAninch, H.W. Oil & Gas J. 68 (20), 69 (1970).
52. J.E. Sinor Consultants, Inc. "Market Assessment for Liquid By- Products from the Great Plains Gasification Plant," April, 1987.

53. Little, D.M. "Catalytic Reforming," Penn Well Books, Tulsa, OK. 1985.
54. Nevison, J.A.; Obaditch, C.J.; and Dalson, M.H. "Magnaforming Units Compared," Hydrocarbon Process., 53 (6), 111 (1974).
55. Hydrocarbon Processing, 67 (9), 81 (1988).
56. _____, 67 (9), 80 (1988).
57. Carter, J.L., et al. ACS Meeting, March 28, 1982. Las Vegas, Nevada.
58. Hydrocarbon Processing, 67, (9), 80 (1988).
59. _____, 67 (9), 79 (1988).
60. "Recent Catalyst and Process Improvements in Commercial Rheniforming," presented at NPRA Annual Meeting, March 23-25, 1980. New Orleans, LA.
61. Hydrocarbon Processing, 67 (9), 81 (1988).
62. Oil & Gas J., 74 (3), 48 (1976).
63. Speight, J.G. "The Chemistry and Technology of Petroleum," Marcel Dekker, Inc., NY, 1980.
64. Thomas, C.L. "Catalytic Processes and Proven Catalysts," Academic Press, New York, 1970.
65. Oil & Gas J., 71 (45), 79 (1973).
66. Hydrocarbon Processing, 67 (9), 68 (1988).
67. _____, 63 (9), 106 (1984).
68. _____, 67 (9), 67 (1988).
69. Murcia, A.A.; Soudek, M.; Quinn, G.P.; and D'Souza, G.J. "Add Flexibility to FCC's," Hydrocarbon Processing, 58 (9), 131 (1979).
70. Hydrocarbon Processing, 67 (9), 66 (1988).
71. _____, 63 (9), 105 (1984).
72. _____, 67 (9), 68 (1988).

73. Dean, R., et al. "Crude Oil Upgrading Utilizing Residual Oil Fluid Catalytic Cracking," presented at Katalistik's Eighth Annual FCC Symposium, 1987. Budapest, Hungary.
74. Oil & Gas J., 80 (12), 92 (1982).
75. Hydrocarbon Processing, 63 (9), 109 (1984).
76. _____, 63 (9), 110 (1984).
77. Oil & Gas J., 82 (22), 79 (1984).
78. "Modern Residue Upgrading by ART," presented at NPRA Annual Meeting, March 23-25, 1986.
79. Hydrocarbon Processing, 67 (9), 67 (1988).
80. Avidan, A.A.; Edwards, M.; and Owen, H. "Innovative Improvements Highlight FCC's Past and Future," Oil & Gas J., 88, Jan. 8, 36 (1990).
81. McCulloch, D.C. "Feed Hydrotreating Improves FCCU Performance," Oil & Gas J., 73, July 21, 53 (1975).
82. Sullivan, R.F. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Final Report, prepared for U.S. DOE, Contract No. DE-AC22-76ET10532, May, 1987.
83. Sullivan, R.F.; O'Rear, D.J.; and Frumkin, H.A. "Converting Syncrudes to Transportation Fuels," presented at 1981 Fuels and Lubricants Meeting, NPRA, November 5-6, 1981, Houston, Texas.
84. Sullivan, R.F., and Frumkin, H.A. "Refining Coal Liquids: Where We Stand," presented at 191st ACS National Meeting, April 13-18, 1986. New York.
85. Kowalski, T.L. and, Basu, A. "Wilsonville Product Evaluation, Illinois No. 6, ITSL Run 244," Amoco, EPRI Contract No. RP1604-5, June, 1984.
86. Nowaski, P. "Coal Liquefaction Process," Noyes Data Corp., NJ, 1979.
87. Sullivan, R.F. "Refining Comparisons: CTSL, ITSL, and H-Coal Syncrudes," presented at Direct Liquefaction Contractors' Review Meeting, Oct. 20-22, 1986. Monroeville, PA.

88. Amoco. "Subbituminous Synthetic Crude and Product Evaluations, Wilsonville Run 246, Draft Report," March 12, 1985.
89. Gray, D.; Tomlinson, G.; and El Sawy, A.E. "A Comparative Techno- Economic Analysis of HRI Co-Processing, Catalytic Two-Stage Liquefaction, and H-Oil," MITRE, Proceedings of Direct Liquefaction Contractors' Review Meeting, October 2-4, 1989, Pittsburgh, PA.
90. Comolli, A.G.; Johanson, E.S.; McLean, J B.; and Smith, T.O. "Low- Severity Catalytic Two-Stage Liquefaction Process," HRI, DOE Contract No. DE-AC22-85PC80002, September, 1988.
91. Wilsonville Report for Run 257.
92. Wilsonville Report for Run 258.
93. Winschel, R.A., and Zhou, P. "Inspection of Integrated Two-Stage Liquefaction Products by Petroleum Assay," presented at the 16th Annual EPRI Fuel Science Conference, June 18-20, 1991, Palo Alto, CA.
94. Kramer, R.L. Conoco Research Report No. 6210-0003-T000-1-91, Aug. 20, 1991.
95. Vimalchand, P.; Lee, J.M.; and Gollakota, S.V. "Recent Developments in Coal Liquefaction at the Wilsonville Facility," presented at the 16th EPRI Fuel Science Conference, June 18-20, 1991, Palo Alto, CA.
96. Rosenthal, J.W.; Dahlberg, A.J.; Kuehler, C.W.; and Shiun, J.H. "The Chevron Co-Refining Process," presented at 49th Midyear Refining Meeting Session on Heavy Oils Processing, May 16, 1984, New Orleans, LA.
97. Oil & Gas J. 67 (40), 91 (1969); 69 (20) 124 (1971).
98. Energy Engineering Board, Assembly of Engineering. "Refining Synthetic Liquids from Coal and Shale," National Academy Press, Washington, D.C. 1980.
99. Wilson, B.W.; Later, D.W.; Wright, C.W.; and Steward, D.L. "Chemical Analysis and Mutational Assay of Distilled Oils from the H-Coal Direct Liquefaction Process: A Status Report," Battelle, DOE Contract DE-AC06-76RLO1830, January, 1985.

100. Pauls, R.E.; Bambacht, M.E.; Bradley, C.; and Cronauer, D.C. "Distribution and Characterization of Phenolics in Distillates Derived from Two-Stage Coal Liquefaction," Amoco Research Center, 1988.
101. Burke, F.P.; Winschel, R.A.; Robbing, G.A.; and Brandes, S.D. Project Status Report under DOE Contract DE-AC22-89PC89883, November 6, 1991.
102. Gray, R.H.; Drucker, H.; and Massey, M.J. "Toxicology of Coal Conversion Processing," John Wiley & Sons, New York, 1988.
103. Sutterfield, D., and Lanning, W.C. "Hydrotreatment and Biological Test of SRC-II Coal Liquid," Chap. 5 in 'Upgrading Coal Liquids' (R.F. Sullivan, ed.), ACS Symposium Series 156, ACS, Washington, D.C., 1981.
104. Salmon, R. "Direct Liquefaction Technology Assessment. Task 1. Technical Readiness of the Developing Plant Functions," Appendix I, ORNL/TM-9181, September, 1985.
105. Pittsburg and Midway Coal Mining Co. "Solvent Refined Coal Process," Final Report, DOE/ET/10104-46, 2, May, 1982.
106. deRosset, A.J.; Tan, J.; and Hiffman, L. "Upgrade Coal-Derived Distillates," Hydrocarbon Processing, 58 (5), 152 (1979).
107. Bernier, E.J. "Wilsonville Synthetic Crude and Product Evaluations in Integrated Two-Stage Liquefaction of Subbituminous Coal," Southern Company Services, Inc. EPRI Report No. AP-5222, June, 1987.
108. Sefer, N.R., and Erwin, J. "Hydroprocessing of Direct Coal Liquefaction Product for Diesel Engine Fuel," SEA Paper No. 892131, September 1989.
109. Winschel, R.A.; Burke, F.P.; and Zhou, P. "Inspection of Integrated Two-Stage Liquefaction Products as Petroleum Refining Feedstocks," presented at 1991 International Conference on Coal Science, September 16-21, 1991, Newcastle, U.K.
110. Becker, M., et al. "Analytical Studies for the H-Coal Process," Mobil, Final Report, DOE Contract No. DE-AC05-77ET10112, July, 1982.
111. Fischer, R.H., and Hildebrand, R.E. "Refining of Coal-Derived Syncrudes," in 'Upgrading Coal Liquids', Chap. 12, ACS Symp. Series 156, ACS, Washington, DC, 1981.

112. MacArthur, J.B.; Duddy, J.E.; and Moonijy, A.V. "H-Coal Process Liquids - Upgrading Options for Fuels Production," presented at 1982 NPRA Annual Meeting, March 21-23, 1982, San Antonio, Texas.
113. ER&E. "EDS Coal Liquefaction Process Development, Phase V," Interim Report, DOE/ET/10069-T5, March, 1981.
114. Tan, G., and deRossett, A.G. "Hydrotreating and Reforming H-Coal Process-Derived Naphtha," DOE Report, FE-2566-12, March, 1978.
115. UOP. "Hydrotreating and Reforming SRC-II Naphtha," DOE Report, FE- 2566-27, June, 1979.
116. Epperly, W.R. "EDS Coal Liquefaction Process Development, Phase V, EDS Product Quality Final Report," FE-2893-97, Sept., 1982.
117. Fant, B.T., and Barton, W.J. "Refining Coal Liquids," presented at API Refining Dept. 43rd Midyear Meeting, May 10, 1978. Toronto, Canada.
118. Sullivan, R.F., and O'Rear, D.J. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Quarterly Report, January-March, 1980, FE-2315-52.
119. Sullivan, R.F., and O'Rear, D.J. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Monthly Report, DOE Contract No. DE-AC22-76ET10532, February, 1982.
120. Erwin, J., and Sefer, N.R. "Synthetic Fuels from Coal-Derived Distillate as Jet Fuels for High Mach Aircraft," presented at ACS Meeting, Div. Petrol. Chem., September 10-15, 1989. Miami Beach, FL.
121. Federal Specification VF-800D, Fuel Oil, Diesel, October 27, 1987.
122. Zhou, P.Z.; Zhang, Y.Z.; Wu, Z.H.; Wang, J.E.; and Ruam, J.Z. "Catalytic Cracking of Low-Temperature Carbonization Coal Tar Fractions," Chemical Bulletin (China), (1), 1 (1959).
123. Zhou, P.Z., and Wu, C. "Kinetics of Catalytic Cracking of Cumene and Poisoning of Silica-Alumina Catalysts," Acta Focalia Sinica, 4 (1), 1 (1959).
124. Riedl, F.J., and deRosset, A.J. "Hydrotreating and Fluid Catalytic Cracking of SRC-II Process Derived Gas Oils," UOP, Interim Report, DOE Contract No. EF-77-C-01-2566, July, 1980.

125. Tan, G., and deRosset, A.J. "Hydrotreating and Fluid Catalytic Cracking of H-Coal Process-Derived Gas Oils," UOP, Interim Report, DOE Contract No. EF-77-C-01-2566, August, 1978.
126. UOP. "Hydrotreating of H-Coal Gas Oil," DOE Report, FE-2566-33, November, 1978.
127. UOP. "Hydrotreating and Fluid Catalytic Cracking of EDS Gas Oil," DOE Report, FE-2566-30, August, 1979.
128. UOP. "Hydrotreating of EDS Gas Oil," DOE Report, FE-2566-33, November, 1979.
129. Tan, G., and deRosset, A.J. "Hydrocracking of H-Coal Process Derived Gas Oils," UOP, Interim Report, DOE Contract No. EF-77-C-01-2566, November, 1978.
130. Riedl, F.J., and deRosset, A.J. "Hydrocracking of EDS Process Derived Gas Oil," UOP, Interim Report, DOE Contract No. EF-77-C-01-2566, November, 1979.
131. Sullivan, R.F. "Processing of Illinois ITSL Oils: Experimental Studies," Eleventh Interim Report, DOE Contract No. DE-AC22- 76ET10532, May, 1985.
132. Sullivan, R.F. "Processing of Wyodak and Illinois No. 6 ITSL Oils: Experimental Studies," Twelfth Interim Report, DOE Contract No. DE- AC22-76ET10532, November, 1985.
133. Sullivan, R.F. "Processing of Wyodak CTSL Oil and Related Experimental Studies," Fourteenth Interim Report, DOE Contract No. DE-AC22- 76ET10532, August, 1986.
134. Chevron Research Co. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," DOE Report DOE/ET10532 Series, NTIS, U.S. Dept. of Commerce, Springfield, VA, 1987.
135. Chevron Research Co. "Processing of SRC-II," DOE Report FE-2345-47, May, 1980.
136. Sullivan, R.F. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Chevron, Quarterly Report, DOE Contract No. DE-AC22-76ET10532, November, 1984.

137. Sturm, Jr., G.P.; Dooley, J.E.; Thomson, J.S.; Woodward, P.W.; and Vogh, J.W. "The Composition of Coal Liquids from Coals of Different Ranks," in 'Upgrading Coal Liquids' (R.F. Sullivan ed.), Chap. 1, ACS Symposium Series 156, ACS, Washington, D.C, 1981.
138. Wiser, W.H.; Singh, S.; Qader, S.A.; and Hill, G.R. "Catalytic Hydrogenation of Multi-ring Aromatic Coal Tar Constituents," Ind. Eng. Chem. Prod. Res. Develop. 9 (3), 350 (1970).
139. Wu, W., and Haynes, Jr., H.W. "Hydrocracking Condensed-Ring Aromatics Over Non-Acidic Catalysts," Preprints, ACS Div. Petrol. Chem. 20 (2), 446 (1975).
140. Zielke, C.W.; Stuck, R.T.; Evans, J.M.; Constanza, C.P.; and Gorin, E. "Molten Salt Catalysts for Hydrocracking of Polynuclear Hydrocarbons," Ind. Eng. Chem. Proc. Dec. Develop. 5 (3), 151 (1966).
141. Sullivan, R.F. "Hydrotreating of EDS and H-Coal Blends for Biological Studies," Chevron, Interim Report, DOE Contract No. DE-AC22-76ET10532, January, 1983.
142. Sullivan, R.F. "Hydrotreating 400°F+ SRC-II Oil for Biological Studies," Chevron, Interim Report, DOE Contract No. DE-AC22-75ET10532, April, 1982.
143. Frumkin, H.A.; Sullivan, R.F.; and Stangeland, B.E. "Catalytic Upgrading of SRC-II Syncrude," Chap. 3 in 'Upgrading Coal Liquids' (R.F. Sullivan, ed.), ACS Symposium Series 156, ACS, Washington, D.C, 1981.
144. Frumkin, H.A.; Sullivan, R.F.; and Stangeland, B.E. "Converting SRC-II Process Product to Transportation Fuels," presented at the 87th National Meeting of AIChE, August 20, 1979, Boston, MA,.
145. Lanning, W.C. "The Refining of Synthetic Crude Oils," BETC/IC-76/2, July, 1976.
146. Zaczepinski, S.; Kamienski, P.W.; Toups, H.J.; Smith, R.S.; and Turner, D.W. "Upgrading of Coal Liquids," Proceedings, Refining Department, 44th Midyear Meeting, May 14-17, 1979, San Francisco, CA.
147. Sullivan, R.F.; O'Rear, D.J.; and Frumkin, H.A. "Processing of H-Coal Syncrude," Chevron, Fifth Interim Report, DOE Contract No. DE-AC22-76ET10532, September, 1981.

148. Sullivan, R.F. "High-Density Jet Fuels from Coal Syncrudes," Symposium on Structure of Future Jet Fuels, presented at the Div. Petroleum Chemistry, ACS, April 5-10, 1987. Denver, CO.
149. Beverly, J.B., and Marschner, R.F. Preprints Div. Petrol. Chem., ACS, 4 (2), B-41 (1959).
150. Zimmerschied, W.J.; Mickel, B.L.; Hunt, R.A.; and DerHerder, M.J. Preprints Div. Petrol. Chem., ACS, 4 (2), B-47 (1959).
151. Sullivan R.F.; Stangeland, B.E.; Rudy, C.E.; Green, D.C.; and Frumkin, H.A. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes - First Interim Report, Processing of Paraho Shale Oil," Chevron Research Co., DOE Report FE-2315-25, April 1978.
152. Sullivan, R.F. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Chevron, Quarterly Report for period April-June, 1983, DOE Contract No. DE-AC22-76ET10532, September, 1983.
153. Sullivan, R.F.; O'Rear, D.J.; and Frumkin, H.A. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Chevron, Ninth Interim Report, DEO Contract No. DE-AC22-76ET10532, August, 1984.
154. Sullivan, R.F., and Frumkin, H.A. "Refining and Upgrading of Synfuels form Coal and Oil Shales by Advanced Catalytic Processes," Chevron, Third Interim Report, DOE Contract No. DE-AC22-76ET10532, November, 1982.
155. Lumpkin, R.E. "Recent Progress in the Direct Liquefaction of Coal," Science, 239, 873 (1988).
156. Stournas, S.; Lois, E.; and Polyssis, P. "Performance Assessment of Novel Substitute Gasoline Components," Prep. 199th ACS National Meeting, Div. Fuel Chem. 35 (1), 258, April 22-27, 1990. Boston, MA.

TABLES

TABLE 1

DETAILED REQUIREMENTS FOR GASOLINE (D439-88b) [3]

Distillation Temperatures, °C (°F), at Percent Evaporated ^{a,b}										Vapor/Liquid Ratio (V/L) ^a	
Volatility Class	10 Vol%, max	50 Vol%		90 Vol%, max	End Point, max	Distillation Residue, Vol %, max	Test Temperature °C (°F)	V/L, max			
		min	max								
A	70 (158)	77 (170)	121 (250)	190 (374)	225 (437)	2	60 (140)	20			
B	65 (149)	77 (170)	118 (245)	190 (374)	225 (437)	2	56 (133)	20			
C	60 (140)	77 (170)	116 (240)	185 (365)	225 (437)	2	51 (124)	20			
D	55 (131)	77 (170)	113 (235)	185 (365)	225 (437)	2	47 (116)	20			
E	50 (122)	77 (170)	110 (230)	185 (365)	225 (437)	2	41 (105)	20			

Volatility Class	Reid Vapor Pressure, max, b kPa (psi)	Lead Content, max, g/L (g/gal)		Copper Strip Corrosion, max	Existent Gum, Max mg/100 mL	Sulfur, max, Mass %		Oxidation Stability, Minimum, Minutes	Antiknock Index
		Unleaded ^c	Leaded ^d			Unleaded	Leaded		
A	62 (9.0)	0.013 (0.05)	1.1 (4.2)	No. 1	5	0.10	0.15	240	e
B	69 (10.0)	0.013 (0.05)	1.1 (4.2)	No. 1	5	0.10	0.15	240	e
C	79 (11.5)	0.013 (0.05)	1.1 (4.2)	No. 1	5	0.10	0.15	240	e
D	93 (13.5)	0.013 (0.05)	1.1 (4.2)	No. 1	5	0.10	0.15	240	e
E	103 (15.0)	0.013 (0.05)	1.1 (4.2)	No. 1	5	0.10	0.15	240	e

^a At 101.3 kPa pressure (760 mm Hg).

^b If Federal legislation or regulatory action restricts Reid Vapor Pressure to a level lower than the seasonal and geographical volatility classes specified for a given time and place, the distillation temperature limits shall be consistent with the corresponding Reid Vapor Pressure in Table 1. If the Reid Vapor Pressure limit is between the two classes, the distillation temperature limits of either class are acceptable.

^c The international addition of lead or phosphorus compounds is not permitted. U.S. Environmental Protection Agency (EPA) regulations limit their maximum concentrations to 0.05 g of lead per gallon and 0.005 g of phosphorus per gallon (by Test Method D3231), respectively.

^d EPA regulations limit the lead concentration in leaded gasoline to no more than 0.1 g/gal (0.026 g/l) averaged for quarterly production by refinery.

^e See Table 2.

TABLE 2
GASOLINE ANTIKNOCK INDEXES AND THEIR APPLICATION [3]

<u>Leaded Gasoline (for vehicles that can or must use leaded gasoline)</u>	
<u>Antiknock Index ($\text{RON} + \text{MON}$)/2, min^d, b</u>	<u>Application</u>
87	Meets antiknock requirements of most 1971 and later model vehicles that can use leaded gasoline and of pre-1971 vehicles with low antiknock requirements.
88	Meets antiknock requirements of most 1970 and prior model vehicles that were designed to operate on leaded gasoline, and of 1971 and later model vehicles that can use leaded gasoline and have high antiknock requirements.
89	Meets antiknock requirements of medium and heavy duty trucks that require higher octane leaded gasoline.
92	Suitable for most vehicles with very high antiknock requirements that can use leaded gasoline.
<u>Unleaded Gasoline (for vehicles that can or must use unleaded gasoline)</u>	
<u>Antiknock Index ($\text{RON} + \text{MON}$)/2, min^d, b</u>	<u>Application</u>
85	For vehicles with low antiknock requirements.
87c	Meets antiknock requirements of most 1971 and later model vehicles.
90	For most 1971 and later model vehicles with high antiknock requirements.

^d Reductions for seasonal variations are allowed in accordance with certain specifications.

^b Reductions for altitude are allowed in accordance with certain specifications.

^c In addition, Motor octane number must not be less than 82.0.

TABLE 3

DETAILED REQUIREMENTS* FOR AVIATION GASOLINES* (D910-88a) [3]

	Grade 80	Grade 100	Grade 100LL	ASTM Test Method ^d
Knock value, min, octane number, lean rating	80	100	100	D2700 ^c
Knock value, min, rich rating:				
Minimum octane number	87	130	130	D909
Minimum performance number ^{o,p}		green	blue	D909
Color ^d	red ^e			D2392
Dye content:				
Permissible blue dye, ^f max, mg/gal	0.5	4.7	5.7	
Permissible yellow dye, ^g mg/gal	none	5.9	none	
Permissible red dye, ^h max, mg/gal	8.65	none	none	
Tetraethyllead, ⁱ max, mL/gal	0.5 ^e	4.0	2.0	D2547, D2599, or D3341
Requirements for All Grades				
Distillation temperature, of (°C)				D86
10% evaporated, max temp		167 (75)		
40% evaporated, min temp		167 (75)		
50% evaporated, max temp		221 (105)		
90% evaporated, max temp		275 (135)		
Final boiling point, max, of (°C)		338 (170)		
Sum ^a of 10% and 50% evaporated temp, min, of (°C)		307 (135)*		
Distillation recovery, min, %		97		
Distillation residue, max, %		1.5		
Distillation loss, max, %		1.5		
Net heat of combustion, ^j min, Btu/lb		18,720		D1405 or D3338
Vapor pressure:				
min, psi (kPa)		5.5 (38)		D323 or D2551
max, psi (kPa)		7.0 (49)		D323 or D2551
Copper strip corrosion, max		No. 1		D130
Potential gum (5 h aging gum), ^k max, mg/100 ml		6		D873
Visible lead precipitate, ^l max, mg/100 ml		3		D873
Sulfur, wt max, %		0.05		D1266 or D2622
Freezing point, max, of (°C)		72 (58)		D2386
Water reaction		volume change not to exceed 12 ml		D1094
Permissible antioxidants, ^m max, lb/1000 bbl (42 gal)		4.2		

TABLE 3, continued

- a Requirements contained herein are absolute and are not subject to correction for tolerance of the test methods. If multiple determinations are made, average results shall be used.
- b The test methods indicated in this table are referred to in Section 9 of 1989 Annual Book of ASTM Standards.
- c The values shown in Table 3 represent Aviation Method Ratings. Motor octane ratings obtained by Test Method D2700 should be converted to aviation ratings.
- d These colors have been approved by the Medical Director Chief, Division of Occupational Health, U.S. Department of Health, Education and Welfare.
- e If mutually agreed upon between the purchaser and the supplier, Grade 80 may be required to be free from tetraethyllead. In such a case, the fuel shall not contain any dye and the color as determined in accordance with Test Method D156 shall not be darker than 120.
- f The only blue dye which shall be present in the finished gasoline shall be essentially 1,4 dialkylaminoanthraquinone.
- g The only yellow dyes which shall be present in the finished gasoline shall be essentially p-diethylaminoazobenzene (Color Index No. 11020) or phenol, 2,2'-(3,3'-dimethyl)1,1'-biphenyl-4,4'-diylbis(azo)bis[4-nonyl] (Color Index Solvent Yellow No. 107).
- h The only red dyes which shall be present in the finished gasoline shall be essentially methyl derivatives of azobenzene-4-azo-2-naphthol (methyl derivatives of Color Index No. 26105) or alkyl derivatives of azobenzene-4-azo-2-naphthol.
- i The tetraethyllead shall be added in the form of an antiknock mixture containing not less than 61 wt% of tetraethyllead and sufficient ethylene dibromide to provide two bromine atoms per atom of lead. The balance shall contain no added ingredients other than kerosene, and an approved inhibitor, and blue dye, as specified, herein.
- j Use the value calculated from Table 1 in Method D1405. Test Method D2382 may be used as an alternative method. In case of dispute, Test Method D2382 must be used. In this latter case, the minimum values for the net heat of combustion in Btu's per pound shall be 18 700 for Grades 80, 100, and 100LL.
- *Note that the temperature conversion for the sum is $C_1 + C_2 = 5/9 (t_1 - 32 + t_2 - 32)$.
- k If mutually agreed upon between the purchaser and the supplier, aviation gasoline may be required to meet at 16 h aging gum test (Test Method D873) instead of the 5-h aging gum test. In such a case, the gum content shall not exceed 10 mg per 100 ml and the visible lead precipitate shall not exceed 4 mg per 100 ml. In such fuel the permissible antioxidants shall not exceed 8.4 lb per 1000 bbl (42 gal).
- l The visible lead precipitate requirement applies only to leaded fuels.
- m Permissible antioxidants are as follows: N,N'-diisopropyl-para-phenylenediamine, N,N'-di-secondary-butyl para-phenylenediamine, 2,4-dimethyl-6-tertiary-butylphenol, 2,6-ditertiary butyl-4-methylphenol, 2,6-ditertiary butylphenol, 75% min 2,6-ditertiary butylphenol plus 25% max tertiary and tritertiary butylphenols, 75% min di- and triisopropyl phenols plus 25% max di- and tri tertiarybutyl phenols. These inhibitors may be added to the gasoline separately or in combination not to exceed 4.2 lb of inhibitor (not including weight of solvent) per 1000 bbl (42 gal).
- n Listing of and requirements for Grades 91 98, 108 135, and 115 145 appear in the 1967 version of this specification.
- o A minimum performance number of 130 is equivalent to a knock value determined using isooctane plus 1.28 ml 111/gal (0.33 ml 111/l).
- p All performance numbers shall be reported to the nearest whole number.

TABLE 4

DETAILED REQUIREMENTS FOR AVIATION TURBINE FUELS* (D1655-88a) [3]

Property	Jet A or Jet A-1	Jet B	ASIM Test Method ^b
Acidity, total max, mg KOH/g	0.1	...	0974 c D3242
Aromatics, max, vol%	20 ^c	20 ^c	D1319
Sulfur, mercaptan, d max, wt%	0.003	0.003	D3227
Sulfur, total max, wt%	0.3	0.3	D1266, D1552, or D2622
Distillation temperature, °C:			D86
10% recovered, max, temp	205	...	
20% recovered, max, temp	...	145	
50% recovered, max, temp	report	190	
90% recovered, max, temp	report	245	
Final boiling point, max, temp	300	...	
Distillation residue, max, %	1.5	1.5	
Distillation loss, max, %	1.5	1.5	
Flash point, min, °C	38	...	
Density at 15°C, kg/m ³	775 to 840	751 to 802	D56 or D3828 ^k
Vapor pressure, 38°C, max, kPa	...	21	D1298 or D4052
Freezing point, max, °C	-40 Jet A ^e -47 Jet A-1 ^f	-50 ^e	D323 D2386
Viscosity -20°C, max, mm ² /s ⁿ	8.0		D445
Net heat of combustion, min, MJ/kg	42.89	42.89	D4529, D2382, or D3338
Combustion properties: one of the following requirements shall be met:			
(1) luminometer number, min, or	45	45	D1740
(2) Smoke point, min, mm, or	25	25	D1322
(3) Smoke point, min, mm, and	20 ^f	20 ^f	D1322
Naphthalenes, max, vol, %	3	3	D1840
Corrosion, copper strip, 2 h at 100°C, max	No. 1	No. 1	D130
Thermal stability: one of the following requirements shall be met:			
(1) filter pressure drop, max, mm Hg	76 ^l	76 ^l	D1660 ^h
Preheater deposit less than	Code 3	Code 3	D3241 ⁱ
(2) filter pressure drop, max, mm Hg	25 ^m	25 ^m	
tube deposit less than	Code 3	Code 3	
Existent gum, max, mg/100 ml	7	7	D381
Water reaction:			
Separation rating, max	(2)	(2)	D1094
Interface rating, max	1b	1b	D1094
Additives	See [3]	See [3]	
Electrical conductivity, pS/m			D2624 or D4308

TABLE 4, continued

- a The requirements herein are absolute and are not subject to correction for tolerance of the test methods. If multiple determinations are made, average results shall be used.
- b The test methods indicated in this table are referred to in Section 9 of reference [3].
- c Fuels with an aromatic content over 20 vol% but not exceeding 25 vol% are permitted provided the supplier (seller) notifies the purchaser of the volume, distribution and aromatic content within 90 days of date of shipment unless other reporting conditions are agreed to by both parties.
- d The mercaptan sulfur determination may be waived if the fuel is considered sweet by the doctor test described in 4.2 of Specification D235.
- e Other freezing points may be agreed upon between supplier and purchaser.
- f Fuels having a smoke point less than 20 but not less than 18 and a maximum of 3 vol% of naphthalenes are permitted provided the supplier (seller) notifies the purchaser of the volume, distribution and smoke point and naphthalenes content within 90 days of date of shipment unless other reporting conditions are agreed to by both parties.
- g For all grades use either the Eq 1 of the Table 1 in Test Method D4529 or Eq 2 in Test Method D3338. Test Method D2382 may be used as an alternative. In case of dispute Test Method D2382 must be used.
- h Thermal stability test shall be conducted for 5 h at 149°C preheater temperature, 204.50°C filter temperature and at a flow rate of 2.7 kg/h.
- i Thermal stability test (JFT01) shall be conducted for 2.5 h at a control temperature of 260°C, but if the requirements of Table 4 are not met, the test may be conducted at 250°C. Results of both temperatures shall be reported in this case. Tube deposits shall always be reported by the Visual Method: a rating by the Tube Deposit Rating (TDR) optical density method is desirable but not mandatory.
- j A limit of 50 to 450 conductivity units (pS/m) applies only when an electrical conductivity additive is used and under the condition at point of use. $1 \text{ pS/m} = 1 \times 10^{-12} \Omega^{-1} \text{ m}^{-1}$
- k Results obtained by Test Method D3828 may be up to 2°C lower than those obtained by Test Method D56 which is the preferred method. In case of dispute, Test Method D56 will apply.
- l Preferred SI units are 10 kPa, max.
- m Preferred SI units are 3.3 kPa, max.
- n $1 \text{ mm}^2/\text{s} = 1 \text{ cSt}$.

TABLE 5

PRIMARY MILITARY AVIATION FUEL SPECIFICATION REQUIREMENTS

	JP-4 (Jet B) <u>MIL-T-5624L</u>	JP-8 (Jet A-1) <u>MIL-T-83133A</u>
Specific Gravity, 60°F	0.751-0.802	0.775-0.840
Gravity, API @ 60°F	45-57	37-51
Distillation, max, °F		
10% Recovered	---	---
20% Recovered	293	401
50% Recovered	374	---
90% Recovered	473	---
Final Boiling Point	518	572
Freezing Point, °F	-72 (-58)	-54
Viscosity, Centistokes @ -40°F, max	---	8.0
Aromatics, vol%, max	25.0 (20.0)	25.0 (20.0)
Olefins, vol%, max	5.0	5.0
Sulfur, wt%, max	0.40 (0.30)	0.40 (0.30)
Net Heat of Combustion, Btu/lb, min	18,400	18,400
Hydrogen Content, wt%, min	13.6	13.6
Thermal Stability, JFTOT		
Pressure Drop, mm Hg, max	25	25
Tube Deposit, max	3	3
Flash Point, °F, min	---	100
Vapor Pressure, Reid, psi	2-3	---

TABLE 6
AVERAGE JET FUEL PROPERTIES IN THE UNITED STATES [52]

	<u>JP-4</u>	<u>JET A</u>	<u>JP-5</u>
Type	Naphtha	Kerosene	Kerosene
Gravity, °API	54.7	42.2	41.0
RVP, psi	2.6	---	---
Freezing Point, °F	-82	-50	-54
ASTM D86 Distillation % Overhead			
10%	195	369	387
50%	277	414	417
90%	378	472	462
Aromatic Content, vol%	12.3	17.8	18.8
Olefin Content, vol%	0.8	1.1	0.7
Heat of Combustion, Net, Btu/lb	18,706	18,698	18,504

Source: Bartlesville Energy Technology Center, 1986

TABLE 7

DETAILED REQUIREMENTS FOR DIESEL FUEL OILS^{a,h} [3]

Grade of Diesel Fuel Oil	Flash Point, °C (°F)	Cloud Point, °C	Water and Sediment, vol%	Carbon Residue on 10% Residuum, %	Ash, wt%	Distillation Temp., °C (°F)		Viscosity Kinematic, cStg Saybolt, SUS at 100°F				Sulfur, d wt%	Copper Strip Corrosion	Cetane Number ^e	
	Min	Max	Max	Max	Max	Min	Max	Min	Max	Min	Max	Max	Max	Min ^a	
No. 1-D A volatile distillate fuel oil for engines in service requiring frequent speed and load changes	38 (100)	b	0.05	0.15	0.01	...	288 (550)	...	1.3	2.4	...	34.4	0.50	No. 3	40 ^f
No. 2-D A distillate fuel oil of lower volatility for engines in industrial and heavy mobile service	52 (125)	b	0.05	0.35	0.01	282°C (540)	338 (640)	...	1.9	4.1	32.6	40.1	0.50	No. 3	40 ^f
No. 4-D A fuel oil for low and medium speed engines	55 (130)	b	0.50	...	0.10	...	...	...	5.5	24.0	45.0	125.0	2.0	...	30 ^f

a To meet special operating conditions, modifications of individual limiting requirements may be agreed upon between purchaser, seller, and manufacturer.

b It is unrealistic to specify low-temperature properties that will ensure satisfactory operation on a broad basis. Satisfactory operation should be achieved in most cases if the cloud point (or wax appearance point) is specified at 60°C above the tenth percentile minimum ambient temperature for the area in which the fuel will be used. The tenth percentile minimum ambient temperatures for the United States are shown in Appendix X2 of reference [3]. This guidance is of a general nature; some equipment designs, use flow improver additives, fuel properties, or a combination thereof, may allow higher or require lower cloud point fuels. Appropriate low temperature operability properties should be agreed upon between the fuel supplier and purchaser for the intended use and expected ambient temperatures.

c When cloud point less than -120°C (100°F) is specified, the minimum viscosity shall be 1.7 cSt (or mm²/s) and the 90% point shall be waived.

d In countries outside the United States, other sulfur limits may apply.

e Where cetane number by Method D613 is not available, Method D976 may be used as an approximation. Where there is disagreement, Method D613 shall be the referee method.

f Low-atmospheric temperatures as well as engine operation at high altitudes may require use of fuels with higher cetane ratings.

g 1 cSt = 1 mm²/s.

h The values stated in SI units are to be regarded as the standard. The values in inch-pound units are for information only.

*Editorially corrected.

TABLE 8

DETAILED REQUIREMENTS FOR FUEL OILS* [3]

Grade Description	No. 1	No. 2	No. 4 (Light)	No. 4	No. 5 (Light)	No. 5 (Heavy)	No. 6
	A distillate oil intended for vaporizing pot-type burners and other burners requiring this grade of fuel	A distillate oil for general purpose heating for use in burners not requiring No. 1 fuel oil	Preheating not usually required for handling or burning	Preheating not usually required for handling or burning	Preheating may be required depending on climate and equipment	Preheating may be required for burning and, in cold climates may be required for handling	Preheating required for handling and burning
Specific gravity, 60/60°F (deg API), max	0.8499 (35 min)	0.8762 (30 min)	...	...	...	...	...
Min	...	...	0.8762g (30 max)	...	...	...	...
Flash point, °C (°F) min	38 (100)	38 (100)	38 (100)	55 (130)	55 (130)	55 (130)	60 (140)
Flash point, °C (°F) max	-18°C (0)	-6°C (20)	-6°C (20)	-6°C (20)	...	...	h
Kinematic viscosity, mm ² /s (cSt) ^d							
At 38°C (100°F), min	1.4	2.0 ^c	2.0	5.8	>26.4	>65	...
max	2.2	3.6	5.8	26.4 ^f	65 ^f	194 ^f	...
At 40°C (104°F), min	1.3	1.9 ^c	...	5.5	>24.0	>58	...
max	2.1	3.4	...	24.0 ^f	(58) ^f	(168) ^f	...
At 100°C (212°F), min	...	...	...	...	5.0	9.0	15.0
max	...	...	...	...	8.9 ^f	14.9 ^f	50.0
Saybolt Viscosity: ^d							
Universal at 38°C (100°F), min	...	(32.6)	(32.6)	(45)	(>125)	(>300)	(>900)
max	...	(37.9)	(45)	(125)	(300)	(900)	(9000)
Fuel at 50°C (122°F), min	...	...	...	...	...	(23)	(>45)
max	...	...	...	...	...	(40)	(300)
Distillation Temperature, °C (°F)							
10% Point max	215 (420)	...	...	...	...	...	...
90% Point min	...	282 ^c (540)	...	...	...	...	...
max	288 (550)	338 (640)	...	...	...	...	...
Sulfur content, % mass, max	0.5	0.5 ^b	...	...	...	...	...
Corrosion copper strip, max	3	3	...	...	...	...	...
Ash, % mass, max	...	...	0.05	0.10	0.15	0.15	...
Carbon residue, 10% b; % m, max	0.15	0.35	...	...	...	...	...
Water and sediment, % vol, max	0.05	0.05	(0.50) ^e	(0.50) ^e	(1.00) ^e	(1.00) ^e	(2.00) ^e

TABLE 8, continued

- a It is the intent of these classifications that failure to meet any requirement of a given grade does not automatically place an oil in the next lower grade unless in fact it meets all requirements of the lower grade.
- b In countries outside the United States other sulfur limits may apply.
- c Lower or higher pour points may be specified whenever required by conditions of storage or use. When pour point less than -180C (00F) is specified, the minimum viscosity for grade No. 2 shall be 1.7 cSt (31.5 SUS) and the minimum 90% point shall be waived.
- d Viscosity values in parentheses are for information only and not necessarily limiting.
- e The amount of water by distillation plus the sediment by extraction shall not exceed the value shown in the table. For Grade No. 6 fuel oil, the amount of sediment by extraction shall not exceed 0.50 wt%, and a deduction in quantity shall be made for all water and sediment in excess of 1.0 wt%.
- f Where low sulfur fuel oil is required, fuel oil falling in the viscosity range of a lower numbered grade down to and including No. 4 may be supplied in agreement between purchaser and supplier. The viscosity range of the initial shipment shall be identified and advance notice shall be required when changing from one viscosity range to another. This notice shall be in sufficient time to permit the user to make the necessary adjustments.
- g This limit guarantees a minimum heating value and also prevents misrepresentation and misapplication of this product as Grade No. 2.
- h Where low sulfur fuel oil is required, Grade 6 fuel oil will be classified as low pour +150C (600F) max or high pour (no max). Low pour fuel oil should be used unless all tanks and lines are heated.

TABLE 9
DETAILED REQUIREMENTS FOR GAS TURBINE FUEL OILS' [3]

Designation	Grade of Gas Turbine Fuel Oil	Flash Point, °C (°F)	Pour Point, °C (°F)	Water and Sediment, vol %	Carbon Residue on 10% Residue, wt %	Ash wt %	Distillation Temperature, 90% Point, b		Kinematic Viscosity, cSt		Saybolt Viscosity, Sb		Specific Gravity 60/60° (API) max
		min	max	max	max	max	min	max	at 40°C (104°F) min	at 50°C (122°F) max	Universal at 38°C (100°F) min	Fuel at 50°C (122°F) max	
No. 0 GI	A naphtha or other low-flash hydrocarbon liquid.	d	...	0.05	0.15	0.01	...	...	d	...	...	...	...
No. 1 GI	A distillate for gas turbines requiring a fuel that burns cleaner than No. 2 GI.	38 (100)	-18 ^e (0)	0.05	0.15	0.01	...	288 (550)	1.3	2.4	...	(34.4)	0.850 (35 mi)
No. 2 GI	A distillate fuel of low ash suitable for gas turbines not requiring No. 1-GI.	38 (100)	-6 ^e (20)	0.05	0.35	0.01	282 (540)	338 (640)	1.9	4.1	(32.6)	(40.2)	0.876 (30 mi)
No. 3 GI	A low-ash fuel that may contain residual components.	55 (130)	...	1.0	...	0.03	...	...	5.5	...	(45)	(300)	...
No. 4 GI	A fuel containing residual components and having higher vanadium content than No. 3-GI.	66 (150)	...	1.0	...	...	...	...	5.5	...	(45)	(300)	...

TABLE 9, continued

- a No. 0-GT includes naphtha, Jet B fuel, and other volatile hydrocarbon liquids. No. 1-GT corresponds in general to Specification D396 Grade No. 1 fuel and Classification D975 Grade No. 1-D diesel fuel in physical properties. No. 2-GT corresponds in general to Specification D396 Grade No. 2 fuel and Classification D975 Grade No. 2-D diesel fuel in physical properties. No. 3-GT and No. 4-GT viscosity range brackets Specification D396 Grade No. 4, No. 5 (light), No. 5 (heavy), and No. 6 and Classification D975 Grade No. 4-D diesel fuel in physical properties.
- b Values in parentheses are for information only and may be approximate.
- c 1 cSt = 1 mm²/s.
- d When flash point is below 38°C, or when kinematic viscosity is below 1.3 cSt at 40°C, or when both conditions exist, the turbine manufacturer should be consulted with respect to safe handling and fuel system design.
- e For cold weather operation, the pour point should be specified 6°C below the ambient temperature at which the turbine is to be operated except where fuel heating facilities are provided. When a pour point less than -18°C is specified for Grade No. 2-GT, the minimum viscosity shall be 1.7 cSt, and the minimum 90% point shall be waived.
- f Gas turbines with waste heat recovery equipment may require sulfur limits in the fuel to prevent cold-end corrosion (see Appendix X1.4.1.9) in reference [3].

TABLE 10

TRACE METAL LIMITS OF FUEL ENTERING TURBINE COMBUSTOR(S)* [3]

<u>Designation</u>	<u>Trace Metal Limits, ppm by weight, (max)</u>			
	<u>Vanadium (V)</u>	<u>Sodium plus Potassium (Na + K)</u>	<u>Calcium (Ca)</u>	<u>Lead (Pb)</u>
No. 0-GT	0.5	0.5	0.5	0.5
No. 1-GT	0.5	0.5	0.5	0.5
No. 2-GT	0.5	0.5	0.5	0.5
No. 3-GT	0.5	0.5	0.5	0.5
No. 4-GT		(Consult turbine manufacturers)		

A Test Method D3605 may be used for determination of vanadium, sodium, calcium, and lead.

TABLE 11

RESIDUA AND HEAVY OILS HYDROTREATING PROCESSES

Process	Application	Typical Feed Properties						Licensor
		oAPI	Cut range, of	Con. Carb., wt%	S, wt%	N, wt%	Ni+V, wppm	
Residfining	Hydrotreating atm. and vac. resids to bottoms from heavy crudes	2.7-14.1	10500+ (41-100 LV%)	10.5-28.1	4.1-6.0		95-270	Exxon Research & Engineering Co. [5,6]
Resid HDS	Upgrading high-S resids, crudes, heavy crudes or bitumens	5.1-12.7			4.4-5.3		117-449	Gulf Research and Development Co. [7]
Residual Oil HDS	Improving quality of residual oils by removing S, metals, and asphaltenes							Shell
RCD Unibon	Upgrading sour reduced crudes, vacuum resids and demetallized oils to produce feeds for FCC or hydrocracking and low-S fuel oils							UOP [8]
RDS and VRDS Hydrotreating	To remove S, N, asphaltene and metals from resids, and convert partly into lighter products	5.3-12.7			4.2-5.5			Chevron [9,10]
Unicracking/HDS	To remove very high contents of S and metals in atm. and vac. resids	7.9-16.7	6500+		2.4-5.6	0.21-0.88	46-431	Unocal [11,12]
HVVANH	To upgrade or convert high metal atm. or vac. residues							Institut Francais du Petrole [13,14]
HGO-HDS	To desulfurize high-boiling distillates such as VGO to produce low-S fuel oil or FCC feed	20.8	750-1011		1.76	0.15	3	Arco [15,16]
GO-FINING	de-N, de-met and saturation of multi-ring aromatics in feeds such as coker GO and VGO	10.5-24.5	500-1050	0.5-3.1	1.9-5.3	0.08-0.52	1-11	[R&E [17]
VGO Gulfining	HDS of heavy gas oils and hydrogenation of thermal gas oils and distillates	24-28	372-1090	0.7	2.2-3.0		2	Air Products and Gulf [18]

TABLE 12

DISTILLATE HYDROTREATING PROCESSES

Process	Application	Typical feed Properties					Licensor
		oAPI	Cut Range, of	Bromine No.	Potential gum, mg/100 cc	S, wt%	N, wt%
HPG hydrotreating	To process pyrolysis liquids to produce stable, high-octane gasoline			50-90	>2000	up to 0.50	Lummus Crest, Inc. [19]
thermal naphtha hydrotreating	To reduce S, N and olefin content of thermal naphthas	29		40		0.60	Arco [20]
Smoke Point improvement	To convert aromatics in kerosene into naphthenes for improvement of smoke point/luminometer number	45.4	311-471				Shell [21]
Hydrofining	For distillate hydrotreating	24.0-67.5				0.02-3.6	ER&E [22]
Pyrolysis Distillates hydrogenation	To improve the qualities of pyrolysis distillates	42		75	4000 (4-h)	0.04	IFP [23]
Distillate HDS and Smoke Point improvement	Treating distillates ranging from light gasoline to heavy VGO by removing S, N, metals and hydrogenating olefins						IFP [24]
Unifining	HDS, HDN and hydrogenation of a wide variety of petroleum and chemical stocks	17.0-44.0	310-1000	26		0.4-2.3	Unocal [25,26]
BP Hydrofining	De-S of distillates from light gasoline to BGO		e.p. up to 1200				BP [27,28]

TABLE 13

HYDROCRACKING PROCESSES

Typical Feed							
Process	Application	OAPI	S, wt%	N, wt%	Ni+V, ppm	Con. Carb., wt%	ASTM Dist. of
							10% EP
H-Oil	To convert residue to light products, transportation fuels, FCC feed, low-S fuel oil	5.9	5.1		380		HRI and Texaco [31,32]
IC-Fining	To hydrocrack heavy hydrocarbons into distillates. Catalyst and activity can be varied for either hydrocracking or HDS	4.4-11.7 2.8	2.9-5.6		30-206 340-499		Lummus Crest, Inc. [33] [33a,b]
MRH (Mild Resid Hydrocracking)							The M.W. Kellogg/ Idemitsu Kosan [34,35]
CANMET hydro-cracking	To convert heavy oils and residuals into naphtha and distillates		4-6	0.9	high		Partec Lavalin/Petro-Canada [36]
IFP hydro-cracking	To upgrade and convert high metal residues into cleaner fuel oil or cracker feed	4.6-16.2	4-4.9		85-170		Cut range, of 700 ⁺ -1020 ⁺ IFP [37]
Mild hydro-cracking	Mild hydrocracking of VGO into middle distillates, very low-S fuel or FCC feed	21.5	3	0.10	2 max	0.4	Cut, of 715-1060 IFP and BASF AG [38,39]
Isomax							Standard Oil Co. (Calif.) and UOP [40]
H G hydro-cracking							Gulf and Houdry [41]

TABLE 13, continued

HYDROCRACKING PROCESSES

Process	Application	Typical Feed						Licensor	
		OAPI	S, wt%	N, wt%	Ni+V, ppm	Con. Carb., wt%	ASTM Dist. of		
							10%		EP
Shell hydro-cracking								Shell [30]	
Unicracking	To convert a variety of feedstocks to produce light products, cracker feed, or produce LPG from naphtha	8.4-27.8	0.54-4.57	0.024-0.27			481-640 674-1100	Unoca [42-44]	
HC Unibon	To hydrocrack heavy distillates into light products	24.0	1.8	0.1			1BP 940 655	UOP [45,46]	
Isocracking	To convert naphthas, AGO, VGO, and cracker oils into LPG, gasoline, reformer feed, jet blending stocks, diesel, etc., and feeds for FCC	21.6-72.5	0.005-2.5	0.05-0.10			154-290- 740 1100	Chevron [47,48]	
H H hydro-cracking	To produce lube oils from feedstocks normally considered unsuitable for lube oil manufacture							ARCO [49]	
Hydro-conversion	To convert AGO, VGO into light and middle distillates to cracker feed	22.6	2.50	0.02				L inde AG [50]	
Ultra-cracking								Standard Oil Co. (Indiana) [51]	

Shell [30]

Unocal [42-44]

UOP [45,46]

Chevron [47,48]

ARCO [49]

Linde AG [50]

Standard Oil Co.
(Indiana) [51]

TABLE 14
CATALYTIC REFORMING PROCESSES

Process	Typical Feed Properties					
	oAPI	Boiling Range, °F	Paraffins, LV%	Naphthenes, LV%	Aromatics LV%	S, ppm N, ppm
Platforming	59	200-380	69.4	21.4	9.2	UOP [55]
Powerforming	57.2		57	30		ER&E [56,57]
Magnaforming		160-400	55.5	34.4	10.6	Englehard [54,58]
Rheniforming		200-390	68.6-32.6	23.4-55.5	8.0-11.9	Chevron [59,60]
Catalytic Reforming		176-338			<0.2	IFP [61,62]

TABLE 15

CATALYTIC CRACKING PROCESSES

Process	Application	Typical Feed Properties						Licensor
		oAPI	Con. Carb., wt%	S, wt%	N, wt%	Ni+V, ppm	ASTM Dist. of 10%/90%	
UOP catalytic cracking	To convert gas oils and high boiling feedstocks to lighter products							UOP [65,66]
Gulf catalytic cracking	Processing a wide range of feed types while providing product slate flexibility	22.9-26.0	0.3-3.62	0.1-2.90			542-640/ 975-1014	Gulf [67]
Orthoflow and Ultra-Orthoflow*	To convert distillates and heavier fractions to lower molecular weight products	14.3-34	0.3-3.55	0.04-0.35			790-1058 (50% point)	The M.W. Kellogg [68,69]
Fluid catalytic cracking	To crack feedstocks ranging from naphtha to reduced crude using fluid and heavy oil cracking in combination to produce gasoline, middle distillates, or LPG	23-27	0.5-4			0.9-14		Air Products [70]
Flexicracking	To convert various and residuum containing feeds to lower molecular weight products	22.9-25.1					up to 1050 (EP)	ER&E [71]
Fluid catalytic cracking	To convert conventional gas oils and high asphalt content topped crudes							Stone & Webber [72,73]
Heavy Oil Cracking (HOC)	A special version of Orthoflow FCC to convert crude residue to light hydrocarbons, mainly transportation fuels, and to steam	12.6	13.3			120		Kellogg and Air Products-HRI [74,75]

TABLE 15, continued

CATALYTIC CRACKING PROCESSES

Process	Application	Typical Feed Properties					ASTM Dist. of 10%/90%	Licensor
		oAPI	Con. Carb., wt%	S, wt%	N, wt%	Ni+V, ppm		
RCC	To convert atm. petroleum residuum in a fluidized catalytic system yielding transportation fuels and other light products	19.2-21.3	4.5-6.9		0.14-0.19	44-65		UOP [76,77]
Asphalt Residual Treating (ART)	To reject carbon from petroleum residuum containing asphaltenes using the ART process which decomposes asphaltenes on the fluidized medium. It can process whole crudes, atm. and vac. bottoms, and bitumens.	2.1-23.5	11.2-18.0	1.0-3.0	0.3-0.76	73-264		Englehard [78,79]

*Ultra-Orthoflow is an Orthoflow unit employing high-temperature regeneration technique.

TABLE 16A

PROPERTIES OF COAL LIQUIDS FROM SINGLE-STAGE PROCESSES

Liquefaction Process	SRC-Id [83]	SRC-IIb [83]	H-COALC [84]		
Coal Type		Pittsburgh Seam	AG	Illinois No. 6 Mobil [85]	Bh
Physical appearance	solid flakes	liquid	liquid	---	liquid
Gravity, °API	-14.6	18.6	25.8	23.2	28.1
Molecular weight	---	132	147	---	---
Aniline point, °F	---	<30	<30	---	---
Ramsbottom carbon, wt%	58	0.70	0.29	---	---
Viscosity @ 100°F					
cSt	---	2.196	1.645	---	---
Saybolt, sec.	---	---	---	---	---
Asphaltene, wt%	---	---	---	---	---
Hot C, insoluble, wt%	96	0.047	0.35	---	0.0054
Ash, ppm	2,200	40	90	---	---
Pour point, °F	>400	<-80	<-80	---	---
Bromine No.	---	70	42	---	---
Elemental analysis:					
Carbon, wt%	86.5	84.6	87.0	87.1	86.1
Hydrogen, wt%	6.0	10.5	11.4	10.5	11.4
Sulfur, wt%	0.89	0.29	0.32	0.2	0.14
Oxygen, wt%	4.52	3.79	1.80	1.8	1.96
Total nitrogen, wt%	2.04	0.85	0.46	0.4	0.33
Basic nitrogen, wt%	---	0.70	0.30	---	---
Iron, ppm	182	8	22	---	---
Arsenic, ppm	---	0.01	---	---	---
H/C atom ratio	0.83	1.47	1.56	1.45	1.59
Aromatic carbon, wt%	---	---	37.7	---	---
TBP distillation, °F					
(ASTM D288)					
IBP/5%	159/943	56/189	56/177	---	56/170
10/30%	1017/1161	241/379	312/333	---	200/310
50%	---	424	404	---	380
70/90%	---	473/562	476/588	---	440/508
95/99%	---	642/820	654/765	---	538/589
Boiling range, LV%					
IBP-400°F	0	37	49	31 ^k	57
400°F-700°F	---	---	48	64 ^l	43
400°F-1000°F	9	63	---	---	---
700°F+	---	---	3	5 ^m	0
1000°F+	91	0	0	0	0

TABLE 16A, continued

PROPERTIES OF COAL LIQUIDS FROM SINGLE-STAGE PROCESSES

Liquefaction Process	H-Coal [86]	H-Coal ^c [84]		EDS ^d [87]
Coal Type	Illinois No. 6	Ag	Bh	Texas Lignite
Physical appearance	brownish blk	liquid	liquid	liquid
Gravity, °API	19.8	35.1	35.1	29.0
Molecular weight	---	130	---	130
Aniline point, °F	---	<32	---	---
Ramsbottom carbon, wt%	0.8	0.23	---	0.57
Viscosity @ 100°F				
cSt	---	1.225	---	---
Saybolt, sec.	35	---	---	---
Asphaltene, wt%	---	---	---	---
Hot C ₇ insoluble, wt%	---	0.07	0.001	0.13
Ash, ppm	---	<20	---	<30
Pour point, °F	<5	-55	---	-60
Bromine No.	---	26	---	0
Elemental analysis:				
Carbon, wt%	---	86.2	86.2	86.4
Hydrogen, wt%	---	12.7	13.0	11.2
Sulfur, wt%	0.21	0.04	0.025	0.12
Oxygen, wt%	---	0.85	0.67	1.92
Total nitrogen, wt%	0.44	0.17	0.15	0.30
Basic nitrogen, wt%	---	0.13	---	---
Iron, ppm	---	9	---	6
Arsenic, ppm	---	---	---	---
H/C atom ratio	---	1.76	1.81	1.55
Aromatic carbon, wt%	---	---	---	---
TBP distillation, °F				
(ASTM D288)				
IBP/5%	---	53/156	52/165	53/164
10/30%	---	173/261	178/269	203/317
50%	---	354	356	370
70/90%	---	429/535	424/509	452/662
95/99%	---	602/785	542/603	700/1000
Boiling range, LV%				
IBP-400°F	40.9	60	57	57
400°F-700°F	---	38	43	43
400°F-1000°F	---	---	---	---
700°F+	---	2	0	0
1000°F+	---	0	0	0

TABLE 16B

PROPERTIES OF COAL LIQUIDS FROM TWO-STAGE PROCESSES

Liquefaction Process	ITSL ^a [87]		ITSL ^a [87]		ITSL (Wilsonville) [85,88]	
Coal Type	Illinois No. 6		Wyodak		Illinois No. 6	Clovis Point
	A ^a	B ^h	A ^a	B ^h	Run 244	Run 246
Physical Appearance	liquid	liquid	liquid	liquid	---	---
Gravity, °API	13.6	17.6	8.8	15.8	19.4	24
Molecular weight	---	---	---	---	---	---
Aniline point, °F	---	---	---	---	---	---
Ramsbottom carbon, wt%	---	---	---	---	0.59	0.37
Viscosity @ 100°F						
cSt	---	---	---	---	4.17	2.5
Saybolt, sec.	---	---	---	---	1.52	---
					(@100°C)	
Asphaltene, wt%	---	---	---	---	---	---
Hot C ₇ insoluble, wt%	0.038	0.029	0.018	0.008	---	0.15
Ash, ppm	---	---	---	---	130	0
Pour point, °F	---	---	---	---	<-70	-35
Bromine No.	---	---	---	---	---	---
Elemental analysis:						
Carbon, wt%	89.4	89.0	89.8	89.0	86.9	85.5
Hydrogen, wt%	10.2	10.7	9.35	10.5	10.7	10.9
Sulfur, wt%	0.087	0.07	0.058	0.031	0.23	0.21
Oxygen, wt%	0.26	0.18	0.46	0.39	1.92 ⁱ	3.52
Total nitrogen, wt%	0.11	0.073	0.17	0.10	0.25	0.26
Basic nitrogen, wt%	---	---	---	---	---	0.17
Iron, ppm	---	---	---	---	43	61
Nickel, pp,	---	---	---	---	7	<2
Vanadium, ppm	---	---	---	---	<2	<2
H/C atom ratio	1.37	1.44	1.25	1.41	1.48	1.52
Aromatic carbon, wt%	---	---	---	---	36.5	35.6
TBP distillation, °F						
(ASTM D288)						
IBP/5%	97/275	97/214	295/353	295/340	128/---	54/---
10/30%	375/532	314/471	449/587	363/538	283/426	237/392
50%	602	560	653	587	523	466
70/90%	665/745	609/676	710/790	623/668	622/793	528/638
95/99%	793/859	703/763	840/941	689/731	1000 (EP)	871 (EP)
Boiling range, LV%						
IBP-400°F	12	18	8 (17)	13 (25)	20 ^j	---
400°F-700°F	69	76	57 (58)	84 (73)	50 ^k	---
400°F-1000°F +	---	---	---	---	---	---
700°F +	19	6	35(25)	2(2)	39 ^l	---
1000°F +	0	0	0	0	---	---

TABLE 16B, continued

PROPERTIES OF COAL LIQUIDS FROM TWO-STAGE PROCESSES

Liquefaction Process	CTSL ^f [87]		CTSL [89]	CTSL (Wilsonville)	
Coal Type	Wyodak			Illinois No. 6 Ohio No. 5/6 [90] Run 227	Illinois No. 6 [91] Run 257
	A ^a	B ^h			
Physical appearance	liquid	liquid	---	---	---
Gravity, °API	29.0	36.1	26	23.5-27.6	20.5
Molecular weight	---	---	---	---	---
Aniline point, °F	---	---	---	---	---
Ramsbottom carbon, wt%	---	---	---	---	---
Viscosity @ 100°F					
cSt	---	---	---	---	---
Saybolt, sec.	---	---	---	---	---
Asphaltene, wt%	---	---	---	---	---
Hot C ₇ insoluble, wt%	0.022	0.0054	---	---	---
Ash, ppm	---	---	---	---	---
Pour point, °F	---	---	---	---	---
Bromine No.	---	---	---	---	---
Elemental Analysis:					
Carbon, wt%	87.4	87.1	87.3	87.35-88.02	87.46
Hydrogen, wt%	12.1	12.7	12.0	11.20-11.97	12.16
Sulfur, wt%	0.014	0.0088	0.03	0.01-0.03	0.01
Oxygen, wt%	0.15	0.14	0.33	---	0.21
Total nitrogen, wt%	0.12	0.094	0.15	0.11-0.42	0.16 ⁿ
Basic nitrogen, wt%	---	---	---	---	---
Iron, ppm	---	---	---	---	---
Nickel, ppm	---	---	---	6.4-38.1 ^m	---
Vanadium, ppm	---	---	---	---	---
H/C atom ratio	1.68	1.74	---	1.54-1.64	1.67
Aromatic carbon	---	---	---	---	---
TBP distillation, °F (ASTM D288)					
IBP/5%	69/184	56/179	---	---	68/---
10/30%	216/375	206/312	---	---	241/405
50%	478	397	---	---	549
70/90%	566/706	470/539	---	---	643/709
95/99%	771/858	571/634	---	---	730/---
Boiling range, LV%					
IBP-400°F	34	51	---	---	30
400°F-700°F	55	49	---	---	60
400°F-1000°F	---	---	---	---	---
700°F +	11	0	1.2-8.7	---	10
1000°F	0	0	---	---	0

TABLE 16B, continued

PROPERTIES OF COAL LIQUIDS FROM TWO-STAGE PROCESSES

Liquefaction Process	Close-Coupled ITSL (Wilsonville) [92]		
Coal Type	Wyodak Subbituminous Run 251-IB	Spring Creek Subbituminous Run 258 B-F	Black Thunder Subbituminous Run 258-H-M
Physical Appearance	---	---	---
Gravity, °API	18.70	16.2-17.4	18.3-19.5
Molecular weight	---	---	---
Aniline point, °F	---	---	---
Ramsbottom carbon, wt%	---	---	---
Viscosity @ 100°F	---	---	---
cSt	---	---	---
Saybolt, sec.	---	---	---
Asphaltene, wt%	---	---	---
Hot C ₇ insoluble, wt%	---	---	---
Ash, ppm	---	---	---
Pour point, °F	---	---	---
Bromine No.	---	---	---
Elemental analysis:			
Carbon, wt%	86.4	86.2-86.9	85.5-86.6
Hydrogen, wt%	12.2	11.1-11.3	11.2-11.9
Sulfur, wt%	0.05	0.05-0.10	0.05-0.06
Oxygen, wt%	1.13	1.36-2.21	1.41-2.49
Total nitrogen, wt%	0.23	0.40-0.45	0.37-0.50
Basic nitrogen, wt%	---	---	---
Iron, ppm	---	---	---
Nickel, ppm	---	---	---
Vanadium, ppm	---	---	---
H/C atom ratio	1.70	1.54-1.58	1.56-1.66
Aromatic carbon	---	---	---
GC sim. distillation, °F (ASTM D288)			
IBP/5%	---	47-104/---	88-97/---
10/30%	---	245-301/354-514	209-246/343-
435			
50%	---	555-627	474-531
70/90%	---	636-722/697-778	568-606/638-
671			
EP (by dist.)	---	685-750	630-667
Boiling range, LV%			
IBP-350°	28.5	16.3-18.8	20.3-24.3
350°F-450°F	20.4	11.7-13.7	13.5-16.9
450°F-650°F	37.1	45.2-57.1	52.0-63.8
650°F-EP	14.1	12.1-25.3	0-5.2

TABLE 16B, continued

PROPERTIES OF COAL LIQUIDS FROM TWO-STAGE PROCESSES

Liquefaction Process	Close-Coupled ITSL (Wilsonville)		
Coal Type	Pittsburgh No. 8 Bituminous Run 259G [93]	Black Thunder Subbituminous Run 260D [94]	Illinois No. 6 Bituminous Run 261C [95]
Physical appearance	---	---	---
Gravity, °API	27.7	23.9	24.5
Molecular weight	---	---	---
Aniline point, °F	75.0	---	---
Ramsbottom carbon, wt%	0	0	---
Viscosity @ 100°F			
cSt	2.1	3.1	---
Saybolt, sec.	---	---	---
Asphaltene, wt%	---	---	---
Hot C ₇ insoluble, wt%	0.03	0.5	---
Ash, ppm	20	100	---
Pour point, °F	-74.9	-15	---
Bromine No.	8	4	---
Elemental analysis:			
Carbon, wt%	86.9	87.4	87.2
Hydrogen, wt%	11.55	11.2	11.8
Sulfur, wt%	0.05	0.05	0.02
Oxygen, wt% (diff.)	1.40	1.05	0.78
Total nitrogen, wt%	0.1	0.3	0.22
Basic nitrogen, wt%	0.078	0.18	---
Iron, ppm	2.5	23	---
Nickel, ppm	<0.5	<0.5	---
Vanadium, ppm	<1	<1	---
H/C atom ratio	1.59	1.54	1.62
Aromatic carbon, wt%	---	---	---
GC sim. distillation, °F (ASTM D288)			
IBP/5%	---/155	---/177	---
10/30%	215/371	207/417	---
50%	488	518	---
70/90%	554/652	606/689	---
EP (by dist.)	---	---	---
Boiling range, LV%			
IBP-350°F	23.6	25.0	22.3
350°-450°F	14.9	34.2	16.7
450°F-650°F	51.5	45.8	43.0
650°F-EP	10	20.0	18.0

TABLES 16 A and B, continued

Notes to Tables 16A and B

- a SRC-I, produced from bituminous coal and supplied by Pittsburg and Midway Coal Mining Company.
- b SRC-II, produced by same company as SRC-I and derived from bituminous from Pittsburgh seam (Blacksville No. 2 mine) in West Virginia.
- c H-COAL oils, supplied by HRI and derived from (1) Illinois No. 6, Burning Star mine, and (2) Wyodak, subbituminous.
- d EDS oil, made from Big Brown Texas lignite by Exxon.
- e ITSL oils, derived from (1) Illinois No. 6 Burning Star mine, and (2) Wyodak, subbituminous, much of the front end (500°F-) was missing (38 LV%) for this oil, numbers in parentheses were corrected for the missing part.
- f CTSL, from Wyodak coal by HRI.
- g A - blended from components in ratios to represent, as close as possible, "net whole-liquid products" from these processes.
- h B - redistilled A with recovery of LV%: 87 (Illinois No. 6 H-Coal), 96 (Wyodak H-Coal), 69 (Illinois No. 6 ITSL), 52 (Wyodak ITSL), 62 (Wyodak CTSL).
- i Direct determination.
- j IBP-360°F.
- k 360°F-650°F.
- l 650°F+.
- m Ni + V in 975°F+ residuum.
- n 0.11 by Kjeldahl.

TABLE 17

PROPERTIES OF CRUDE PETROLEUM AND SHALE OIL

	Arabian light crude [83]	Kern crude [96]	Boscan crude [96]	Paraho shale oil [83]	Alaskan North Slope crude [97]
Physical appearance	viscous liquid			waxy liquid	
Gravity, OAPI	33.4	14.0	10.9	20.2	25.7
Aniline point, of	---	---	---	---	---
Molecular weight	375	---	---	326	94.1
Viscosity, SUS @ 100°F, sec	---	---	---	2.5	5.99
Rambottom carbon, wt%	2.6	---	---	0.2	---
Hot C ₇ insolubles, wt%	0.44	---	---	300	---
Ash, ppm	100	---	---	90	20
Pour point, of	-15	---	---	---	---
Bromine number	---	---	---	---	---
Elementary analysis, wt%					
Carbon	85.0	---	---	84.3	---
Hydrogen	13.1	---	---	11.3	---
Sulfur	1.7	1.2	5.3	0.66	1.12
Oxygen	0.1	---	---	1.16	---
Total nitrogen	0.1	0.7	0.6	2.18	---
Basic nitrogen	---	---	---	---	---
Iron, ppm	<3	---	---	70	---
Arsenic, ppm	---	---	---	28	---
Nickel, ppm	---	60	89	---	14.4
Vanadium, ppm	---	33	940	---	24.9
H/C atom ratio	1.84	1.58	1.57	1.60	---
TBP distillation, of					
IBP/5	112/219	---	---	183/347	---
10/30	287/472	---	---	453/610	250/500
50	655	---	---	736	720
70/90	875/---	---	---	842/963	932/---
95/99	---	---	---	---	---
Boiling range, LV%					
18P 400°F	31	18 ^a	14 ^a	4	19.6
400°F 1000°F	53	45 ^b	28 ^b	86	57.2
1000°F ^c	16	37	58	10	23.2

^a 640°F
^b 650°F 1000°F

TABLE 18

COMPARISON OF ELEMENTAL COMPOSITION OF H-COAL FRACTIONS FROM ILLINOIS NO. 6
WITH PETROLEUM FRACTIONS [106]

wt%	IBP/400°F Naphtha		400°F/650°F Light Fuel Oil		650°F+ Heavy Fuel Oil	
	H-Coal	Petroleum ^a	H-Coal	Petroleum ^b	H-Coal	Petroleum ^c
Carbon	84.9	85.5	88.8	87.0	89.2	86.4
Hydrogen	11.6	14.5	9.7	12.9	8.0	11.2
Sulfur	0.2	0.05	0.1	0.09	0.2	2.0
Nitrogen	0.3	0.0001	0.4	0.008	1.3	0.4
Oxygen	3.0	0.003	1.4	ND(0.1)	1.3	0.3

^a Mid-continient Reformer Charge Stock

^b Commercial No. 2 Fuel Oil

^c El Palito No. 6 Fuel Oil

ND = Not detected at the level shown

TABLE 19

COMPARISON OF TYPICAL PETROLEUM FRACTIONS WITH WILSONVILLE FRACTIONS [85]

	Naphtha		Distillate		Gas Oil	
	Petroleum	Wilsonville	Petroleum	Wilsonville	Petroleum	Wilsonville
API	56.5	43.1	37.6	18.6	27.9	7.3
S	408 ppm	3,600 ppm	3,500 ppm	2,200 ppm	0.97%	0.16%
N	4 ppm	846 ppm	31 ppm	2,300 ppm	0.03%	0.31%
CA				34	16	46
Saturates	88.5	72.5				
Olefins	0.7	5.5				
Aromatics	10.8	22.0				

TABLE 20

LIGHT NAPHTHA (IBP-285°F) FROM ILLINOIS NO. 6 ITSL (RUN 244) [85]

	Run 244 IBP-285°F Cut	Specification	Remarks
Distillation temperature, °F			
IBP	171	---	
10% evaporated	198	167 (max)	Fail
40% evaporated	208	167 (min)	
50% evaporated	212	221 (max)	
90% evaporated	242	275 (max)	
FBP	287	338 (max)	
Sum of 10% and 50% evap. temp.	410	307	
Distillation recovery, %	98.1	97 (min)	
Distillation residue, %	0.8	1.5 (max)	
Distillation loss, %	1.1	1.5 (max)	
Net heat of combustion, Btu/lb	18,313	18,720 (min)	Fail
Reid vapor pressure, psi	2.9	5.5 (min)	Fail
Copper strip corrosion	1a	1 (max)	
Potential gum, mg/100 ml	10.4	6 (max)	Fail
Sulfur, wt%	0.0027	0.05 (max)	
Freezing point, °F	-112	-72 (max)	
Octane no., lean rating	74	80 (Grade 80 min)	Fail
Elementary analysis, %			
C	86.85		
H	13.15		
S	0.0027		
N	0.0058		
FIA, %			
Aromatic	24.5		
Olefin	1.5		
Saturates	74.0		
API gravity	48.1		
Aniline point	64.9		

TABLE 21

PROPERTIES OF RAW NAPHTHA FRACTIONS (IBP-400°F) FROM SINGLE-STAGE LIQUEFACTION COAL LIQUIDS

Source	ASTM	H-Coal [110]	H-Coal [110]	H-Coal [11,112]	EDS [113]	EDS [113]
Coal	Specification	Wyodak	W. Kentucky No. 11	Illinois No. 6	Illinois No. 6	Wyodak
Gravity, °API	---	---	---	35.0	42.0	38.0
RVP, psi	---	2.5	2.0	2.4	---	---
Copper Strip Corrosion	10 (max) ^a	No. 1A	No. 1A	No. 1B	---	---
Gum, mg/100 ml	No. 1 (max)	58	47	22	---	---
Sediment, mg/l	5 (max)	1.4	10.5	1.6	---	---
Bromine No. cg/g	---	13.8	25.1	35.6	35.6	30.6
Distillation, of	---	---	---	---	---	---
IBP	---	---	---	98d	160	147
10%	149a	---	---	182	212	212
30%	---	---	---	237	253	270
50%	---	---	---	322	284	312
90%	245 (max) ^a	---	---	400	340	362
EP	374 (max) ^a	---	---	452	382	411
437 (max) ^a	---	---	---	---	---	---
Elementary Comp.	---	---	---	84.9	84.41	85.04
C, wt%	---	---	---	11.6	12.49	11.95
H, wt%	---	---	---	0.3	0.112	0.153
N, wt%	---	---	---	0.2	0.88	0.118
S, wt%	0.10 (max) ^b	0.1	0.2	675	---	---
Mercaptan S, wppm	---	219	250	3.0	1.52	2.08
O, wt% (diff.)	---	---	---	---	23	18
Fe, wppm	---	---	---	5	2.2	5.5
Cl, wppm	---	0.13	0.19	0.07	---	---
Total Acid No.	---	---	---	---	---	---
PIANO, LV%	---	---	---	10.3	---	---
Paraffin	---	---	---	34.0	---	---
Naphthene	---	---	---	50.8	---	---
Aromatics	---	---	---	---	---	---
FIA, LV%	---	---	---	---	63.6	55.5
Saturates	---	---	---	4.9	6.8	5.4
Olefins	---	---	---	---	29.6	39.0
Aromatics	---	---	---	---	---	---
MIN	82 (min) ^c	65.2	73.3	82.9	---	---
RON	---	---	---	---	---	---
Yield on Total Coal	---	74.4	28.8	44.5	---	---
Liquid, wt%	---	---	---	---	---	---

TABLE 21, continued

- a Volatility class B.
- b Unleaded.
- c For antiknock index 87 (min).
- d GC simulated distillation.

TABLE 22A

PROPERTIES OF RAW NAPHTHA FRACTIONS FROM TWO-STAGE LIQUEFACTION COAL LIQUIDS

Source	Wilsonville ITSL [85,88]	Wilsonville ITSL [88]	Wilsonville CC-ITSL [92]
Coal	Illinois No. 6, Run 244	Clovis Point, Run 246	Myodak, Run 251-11B Spring Creek, Run 258 B-G Black Thunder, Run 258 H-M
Cut	IBP-360°F	IBP-360°F	IBP-350°F IBP-350°F
Gravity, OAPI	43.1	48	45.6 42.3-44.7
GC Simulated Dist., of			
IBP	60	---	---
10%	165	126	69-132 68-133
30%	204	206	97-150 97-152
50%	250	260	176-209 176-209
90%	343	356	241-248 241-248
100%	386	---	350-357 350-360
Elemental Comp.			360-364 360-365
C, %	85.21	83.06	84.16 83.06-84.64
H, %	12.86	13.23	14.10 13.56-14.01
N, ppm	84.6	1800	1300 1300-3000
S, %	0.36	0.51	0.11 0.07-0.40
O, % (direct)	---	3.71	---
O, % (diff.)	1.50	3.02	1.50 1.37-2.68
Fe, ppm	<2	<2	---
Ni, ppm	---	<2	---
V, ppm	---	<2	---
Cl, ppm	---	<2	---
PIANO, %			
Paraffin	15.9	32.6	---
Naphthene	60.7	50.5	---
Aromatics	23.4	17.0	---
FlA, %			
Paraffins & Naphthenes	72.5	85.5	---
Olefins	5.5	7.0	---
Aromatics	22.0	7.5	---
Motor Octane Number	73.4	70.4	---
Research Octane Number	---	74.0	---
Yield on Total Coal			
Liquid, wt%	18.4	19.4	28.5 16.3-18.8 20.3-24.3

TABLE 22B

PROPERTIES OF STRAIGHT-RUN NAPHTHAS FROM RECENT WILSONVILLE
CC-ITSL RUNS

Coal Run No.	Pittsburgh Seam 259G [93]	Black Thunder 260D [94]
Boiling range, °F	IBP-380	IBP-380
Yield, wt% of total distillate	26.72	23.65
<u>Properties</u>		
Gravity, °API	48.9	50.9
Elemental analysis, wt%		
Carbon	85.3	84.3
Hydrogen	13.3	13.6
Sulfur	0.05	0.08
Nitrogen	<0.1	0.1
Basic nitrogen	0.028	0.046
Oxygen (by diff.)	1.25	1.92
Group analysis, vol%		
Paraffins	19.3	88.0
Naphthenes	67.5	
Olefins	---	5.0
Aromatics	13.2	7.0
Bromine number	---	16
Octane number (by GC)	86.5	87.1
Reid vapor pressure, Psia	2.8	3.1
Copper strip corrosion	1A	1A
Existent gum, mg/100 ml	26.2	56.2
Oxidation stability (held 100 psi for 5 h @ 212°F)	Pass	Pass
Acidity, mg KOH/g	---	0.38
Phenolic -OH conc., meq/g	0.18	0.40
ASTM distillation, °F		
IBP	109	---
10%	196	176
50%	258	240
90%	341	340
EP	368	399

TABLE 23

COMPOSITIONAL ANALYSES OF COAL-DERIVED NAPHTHAS (BERC/RI-76/10)

<u>Naphtha Cut</u>	<u>IBP-397°F</u>	<u>IBP-387°F</u>
Chemical Class Type, wt%		
Acids	22.3	14.5
Bases		
Pyridines	0.19	0.1
Anilines	0.88	0.7
Total Bases	1.07	0.8
Hydrocarbons		
Saturates	33.9	42.6
Olefins	5.9	3.6
Monoaromatics	34.2	31.4
Diaromatics	Trace	0.2
Total hydrocarbons	74.0	77.8
Loss	2.6	6.85

TABLE 24

HYDROTREATING OF H-COAL NAPHTHA [114]

<u>Property</u>	<u>Rerun Naphtha</u>	<u>Upgraded Naphtha</u>
Gravity, °API	43.7	46.8
D86 Distillation, °F		
IBP	132	153
10%	189	199
30%	233	231
50%	260	263
70%	312	306
90%	-	352
EP	396	393
Elementary Composition		
C, wt%	85.90	86.45
H, wt%	12.80	13.59
S, wppm	1389	3.9
N, wppm	1930	0.63
O, wppm	5944	34
Cl, wppm	23	4
FIA, LV%		
Aromatics	24.7	18.9
Olefins	5.2	0.0
Saturates	70.1	81.1
MS Hydrocarbon Types, LV%		
Aromatics	18.6	17.6
Naphthenes	55.5 ^a	63.4
Paraffins	16.2	19.0
N ₂ Jet Gum, mg/100 ml	40.0	---
RON, clear	80.3	66.8

^a LV% of polars and olefins are 4.2 and 5.5, respectively.

PROPERTIES OF RAW KEROSENE FRACTIONS FROM COAL LIQUIDS

123

TABLE 25B

**PROPERTIES OF JET FUEL FRACTION FROM TWO-STAGE COAL LIQUID
(WILSONVILLE RUN 259G, PITTSBURGH SEAM COAL)**

Property	Actual	Jet A-1 Specification
Gravity, °API	25.9	37-51
Kin. viscosity @ -20°C mm ² /sec.	1.75	8 max
Freezing pt., °C	-53.5	-47 max
Reid vapor pressure, kPa	1.4	20.7 max ^(a)
Flash pt., °C	76.1	38 min
Sulfur, wt%	0.04	0.30 max
Mercaptan sulfur, wt%	0.003	0.003 max
Smoke pt, mm	10.8	25 min
Aromatics, vol%	44.0	25 max
Olefins, vol%	3.0	5 max ^(a)
JFTOT	Fail	25/3 min
Cu strip corrosion	1A	1 max
Existent gum, mg/100 ml	69.0	7 max
Acidity, mg KOH/g	0.05	0.1 max
Net heat value, MJ/kg	42.2 ^(b)	42.8 min
Distillation, °C		
10%	219.6	205 max
FBP	263.3	300 max

^(a) Applicable to Jet B, not Jet A or Jet A-1.

^(b) Calculated (ASTM D-1405)

TABLE 26

PROPERTIES OF THE 250°F-600°F JET FUELS FROM HYDROTREATING 600°F- REDISTILLED
TEXAS EDS COAL LIQUIDS [115]

Operating Conditions	2500	2500	2000	2000	1800	1800
Nominal Total Pressure, psig	2139	2137	1698	1692	1592	1517
Avg. H ₂ Partial Pressure, psia	750	725	750	726	750	702
Catalyst Temperature, °F						
Gravity, OAPI						
Aniline Point, °F	38.0	38.5	38.1	37.3	37.1	35.4
Mole Weight	119.1	112.7	116.0	110.1	109.1	91.4
Viscosity, cSt	157	156	157	158	152	157
at -40°F						
at 100°F						
Flash Point (D56), °F	4.098	4.416	3.955	---	3.948	3.992
Freeze Point, °F	1.324	1.402	1.382	1.391	1.314	1.557
Pour Point, °F	100	97	109	96	104	96
Cloud Point, °F	-58	-67	-54	-54	<-94	-53
Smoke Point, mm	<-80	<-80	-80	-80	-80	<-80
Cu Strip Corrosion (2-h at 212°F)	-74	-60	-38	-72	-60	<-80
Carbon by Combustion, wt%	25	26	20	20	20	18
Hydrogen by Combustion, wt%	18	1A	1B	1B	---	1B
Sulfur, ppm	86.31	86.25	86.41	85.63	86.68	87.18
Nitrogen, ppm	13.68	13.74	13.58	13.46	13.32	12.81
Oxygen, ppm	1.8	2.8	5.8	6.3	---	---
Group Types by MS, LV%	0.61	0.12	0.11	0.60	0.14	5.2
Paraffins	60	60	70	80	40	40
Naphthenes						
Aromatics						
Naphthalene by D1840, LV%						
D86 Distillation by LV%, °F						
10P/5	280/306	289/306	288/300	290/304	302/315	298/311
10/30	317/340	314/336	310/334	310/336	320/337	320/341
50	362	356	359	362	362	368
70/90	392/448	390/460	388/458	390/461	392/454	400/475
95/EP	483/543	498/545	496/536	490/530	484/544	504/545

TABLE 27

GAS TURBINE TEST FUELS [116]

	H-Coal Light Distillate	H-Coal Medium Distillate	SRC Light Distillate	SRC Wash Solvent	SRC Recycle Solvent	Partially Hydrotreated		Petroleum No. 2 Fuel
						EDS Distillate	Reprocessed EDS Distillate	
Nominal Boiling Range, of	210-480	370-590	125-394	301-458	375-709	340-715	340-650	---
Aromatic Carbon, wt%	34	55	28	61	74	48	47	15
Gravity, OAPI	30.2	18.4	43.0	18.6	5.7	16.0	17.1	34.0
Pour Point, of	<-65	<-65	<-65	<-65	35	<-36	<-36	---
Flash Point, of	12	145	<75	95	235	101	122	150
Heat Content, BTU/lb	18,800	18,330	19,000	17,050	17,230	18,340	18,400	19,500
Viscosity, cSt								
+40°C	1.14	2.56	10 @ 100°C	1.75	6.04	2.67	2.34	2.61
+100°C	0.61	0.99	---	0.77	1.45	1.11	1.00	109
Conradson Carbon, wt%	0.03	0.08	<0.01	0.07	4.95	0.03	<0.01	<0.01
Composition								
Hydrogen, wt%	11.3	10.0	12.0	9.2	7.7	10.0	10.2	13.0
Nitrogen, wt%	0.16	0.33	0.29	0.35	0.69	0.08	0.044	0.006
Sulfur, wt%	0.14	0.09	0.57	0.26	0.30	0.03	0.02	0.2
Oxygen, wt%	1.3	1.2	3.3	5.7	2.2	0.3	0.5	<0.1
Ash, wt%	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Trace Metals, wppm								
Li	<2	0.1	<1	<1	<1	<0.1	---	<0.1
Na	1.1	0.7	0.6	0.7	0.6	12	---	0.6
K	0.2	0.3	0.1	0.1	0.1	1.2	---	0.4
Ca	0.2	0.3	0.2	1.0	0.4	2.6	---	0.2
V	0.9	<0.1	<0.1	0.1	0.1	<0.1	---	<0.1
Pb	<0.1	0.1	0.1	0.2	0.1	0.3	---	---
Fe	1	3.7	4.8	13	2.3	3.1	---	0.2
P	<0.2	---	<0.1	0.2	<0.2	1.8	---	---

a

aAromatic ring carbon by NMR.

TABLE 28A

PROPERTIES OF RAW MIDDLE DISTILLATES FROM COAL LIQUIDS

Source	H-Coal [110]	Wilsonville ITSL [85,88]	Wilsonville ITSL [88]	Wyodak, Run 251-11B	Wilsonville CC-ITSL [92]
Coal	Illinois No. 6	Illinois No. 6, Run 244	Clovis Point, Run 246	Spring Creek, Run 258 B-G	Black Thunder, Run 258 H-M
Cut	400°F-650°F	360°F-650°F	360°F-650°F	450°F-650°F	450°F-650°F
Gravity, °API	15.1	18.6	20	25.0	4.70-11.50
Viscosity, cSt @ 40°C	3.37	---	3.69	---	---
@ 100°C	1.22	---	1.75	---	---
Ramsbottom Carbon, %	---	0.15	0.08	---	---
Hot C ₇ Insolubles, %	---	0.48	0.02	---	---
GC Simulated Dist., of					
IBP	408	319	342	---	360-444
10%	443	380	420	---	486-492
30%	477	426	460	---	531-549
50%	509	482	490	---	568-598
90%	583	602	562	---	676
FBP	657	714	647	---	685-722
Elemental Comp.					
C%	88.8	86.34	86.09	87.11	87.07-88.07
H%	9.7	10.73	10.80	11.68	10.54-10.76
N%	0.4	0.23	0.25	0.37	0.25-0.64
Basic N%	---	---	0.17	---	---
S%	0.1	0.22	0.07	0.03	0.02-0.04
O% (direct)	---	2.10	3.26	---	---
O% (diff.)	1.0	2.48	2.79	0.81	0.66-1.78
Fe, ppm	---	<2	<2	---	---
Ni, ppm	---	---	<2	---	---
V, ppm	---	---	<2	---	---
Cl, ppm	28	43.5	3	---	---
Aromatic Carbon, %	85.7 (Arom. %)	34.0	37.7	---	---
Cetane Index	---	21	20.3	---	---
H/C Atom Ratio	1.31	1.49	1.51	1.61	1.44-1.47
Yields on Total liquids, wt%	50.1	45.7	68.9	37.1	52.0-63.8

TABLE 28B

PROPERTIES OF DIESEL FUEL FRACTIONS FROM COAL LIQUIDS
OF RECENT CC-ITSL PROCESS

Run No.	259G	260D	Diesel Fuel No. 1 Specifications
Coal	Pittsburgh Seam	Black Thunder	
Boiling range, °F	510+	510- 650	
<u>Properties</u>			
Gravity, °API	16.3	17.7	
Elemental, wt%			
C	88.4	87.0	
H	10.5	10.7	
S	0.04	0.03	0.50 max
N	0.1	0.3	
Bromine number, g/100 g	7.4	17	
Kin. viscosity @ 100°F, cSt	8.97	6.2	1.3-2.4
Ash, wt%	0.02	0.00	0.01 max
Copper strip corrosion	1A	1A	
Acidity, mg KOH/g	---	0.14	
Flash pt, °F	---	255	100 min
Cetane number	26.5 ^(a)	27.7 ^(a)	40 min
90% off, °F	689 ^(b)	610 ^(b)	550 max

^(a) Cetane index by ASTM D976.

^(b) GC simulated.

TABLE 28C

HYDROTREATING OF COAL-DERIVED MIDDLE DISTILLATE [108]

<u>Property</u>	<u>ASTM Method</u>	<u>Hydrotreater Feed</u>	<u>Products</u>	
			<u>Low Severity</u>	<u>High Severity</u>
Gravity, °API		15.3	21.7	23.7
Distillation, F	D86			
IBP/5		412/445	348/402	356/407
10/20		463/496	422/464	427/459
30/40		530/565	492/524	490/520
50/60		600/629	560/592	548/578
70/80		675/722	624/670	610/652
90/FBP		785/823	740/788	708/794
Cetane number	D613	21.3	30.1	35.4
Cetane index	D976	28.2	32.9	34.4
Cetane index	D4737	24.4	30.7	32.6
Hydrocarbon type, V%	D1319			
Aromatics		81.7	67.6	42.2
Olefins		0	0	0
Saturates		18.3	32.4	57.8
Aromatic carbon, M%	UV			
Monocyclic		16.22	17.24	11.87
Dicyclic		10.51	5.37	3.02
Tricyclic		3.52	1.16	0.67
Elemental Analysis, M%				
Carbon	D1378	89.19	88.15	87.27
Hydrogen	MOD	10.39	11.64	12.00
Sulfur	D2622	0.05	0.04	<0.01
Nitrogen	D4629	0.394	0.008	0.002
Viscosity, cSt @ 40°C	D445	6.72	4.47	3.95
Accel. Stab., mg/100ml	D2274	---	3.26	1.60

TABLE 29

PROPERTIES OF RAW HEAVY DISTILLATES FROM COAL LIQUIDS

Source	EDS [1113]	H-Coal [1112]	Wilsonville ITSL [85,88]	Wilsonville CC-ITSL [92]
Coal	Illinois No. 6	Illinois No. 6	Illinois No. 6, Run 244	Spring Creek, Run 258 B-G
Cut	650°F+	650°F+	650°F-1000°F	650°F+
Gravity, OAPI	-7.6	1.3	7.3	2.40-4.60
Viscosity, cSt @ 40°C	---	121.7	---	1.90-6.00
Ramscarbon, wt%	594 (SSU)	6.37	---	cP @ 1220F 98-158 @ 2300F 2-22
Hot C, insolubles, wt%	11.35 (Con.)	---	0.4	70-144
Pour point, of	---	---	1.87	6-24
Flash point (PM), of	>120	50	---	---
Elemental Composition	360	---	---	---
C%	87.80	89.2	89.07	88.88-89.78
H%	7.03	8.0	9.69	8.76-9.47
N%	1.08	1.3	0.31	0.59-0.79
S%	0.70	0.2	0.16	0.02-0.05
O% (Diff.)	3.30	1.3	0.76	0.31-1.37
Fe, ppm	302	---	<2	---
Cl, ppm	---	---	---	---
Ni, ppm	---	---	<2	---
V, ppm	---	---	<2	---
Aromatic Carbon, wt%	81.7	93.5	46	---
GC Simulated Dist., of	---	---	51.2	---
IBP	593	604	600	---
10/30%	667/758	634/661	647/681	---
50%	900	681	714	---
70/90%	963/1030	700/746	756/822	---
FBP	---	883	932	---
Yield on total liquid, wt%	---	5.4	11.5	0-5.2
				12.1-25.3
				14.1

TABLE 30

HYDROCRACKING OF H-COAL GAS OIL [129]

Property	Feed	First-Stage Product	Second-Stage Product
Gravity, °API	10.8	19.2	49.5-51.0
ASTM Distillation, °F			
IBP	435	315	61-70
10%	505	458	143-158
30%	535	498	193-204
50%	571	530	229-242
70%	627	573	280-293
90%	715	660	335-340
EP	850	748	379-459
Hydrogen, wt%	9.36	10.69	---
Carbon, wt%	89.32	88.41	---
Sulfur, wppm	700	1.4	---
Nitrogen, wppm	3900	4.8	---
Oxygen, wppm	5700	530.4	---
Con. Carbon, wt%	0.08		
C ₇ Insoluble, wt%	0.06		
FIA, LV%			
A	85.5	69.7	23.6-28.3
O	0	0	0
P+N	14.5	30.3	71.7-76.4
Steam Jet Gum, mg/100 ml	447	---	---

TABLE 31

HYDROTREATING TESTS OF COAL LIQUIDS
(Coal liquids listed in increasing order of hydrotreating difficulty) [84]

LHSV H ₂ Pressure, psia	0.5 2300	1.0 2300	1.5 2300	1.5 1800	1.5 1700	1.5 900
Wyodak CTSL B (EP=634°F)						
Temperature, °F	680	705	715	715	715	715
H ₂ Consumption, SCF/B	775	725	725	690	450	180
Product Nitrogen, ppm	0.5	<0.3	<0.3	<0.3	<0.3	<0.3
Product Aromatics, LV%	3	3	4	6	14	25
Wyodak H-Coal B (EP=603°F) ^a						
Illinois H-Coal B (EP=589°F)						
Temperature, °F		750	750			
H ₂ Consumption, SCF/B		2000	1950			
Product Nitrogen, ppm		<0.3	<0.3			
Product Aromatics, LV%		2	5			
Wyodak ITSL B (EP=731°F)						
Temperature, °F	683					
H ₂ Consumption, SCF/B	1650					
Product Nitrogen, ppm	<0.3					
Product Aromatics, LV%	14					
Wyodak H-Coal A (EP=785°F)						
Temperature, °F		750	750			
H ₂ Consumption, SCF/B		1225	950			
Product Nitrogen, ppm		<0.3	<0.3			
Product Aromatics, LV%		3	13			
Illinois ITSL B (EP=763°F)						
Temperature, °F	710	730	745	745		
H ₂ Consumption, SCF/B	1600	1400	950	600		
Product Nitrogen, ppm	<0.2	<0.2	0.4	6		
Product Aromatics, LV%	10	26	38	58		
Illinois H-Coal A (EP=765°F)						
Temperature, °F	750	750	750	750		
H ₂ Consumption, SCF/B	2150	1600	1275	825		
Product Nitrogen, ppm	<0.3	0.3	10	50		
Product Aromatics, LV%	2	20	35	45		
Wyodak CTSL A (EP=858°F)						
Temperature, °F	750					
H ₂ Consumption, SCF/B	825					
Product Nitrogen, ppm	0.3					
Product Aromatics, LV%	21					
Illinois ITSL A (EP=859°F) ^a						
Wyodak ITSL A (EP=941°F)						
Temperature, °F	750					
H ₂ Consumption, SCF/B	1825					
Product Nitrogen, ppm	4					
Product Aromatics, LV%	42					

^a Rank estimated from tests at other conditions [83].

TABLE 32

HYDROUPGRADING OF SRC-II COAL LIQUIDS¹ [143]

Severity	High		Intermediate		Moderate	
	Fresh ICR-106	Aged ICR-106	Fresh ICR-106	Aged ICR-106	Aged ICR-113	Crude Oil
Catalyst					SRC-II	
H ₂ Pressure, psia	2300	2300	2300	2300	1750	---
Avg. Cat. Temp., of	750	776	750	768	750	---
LHSV	0.5	0.5	1.5	1.5	1.0	---
H ₂ Cons. (Chemical), SCF/bbl	3100	2900	2000	2000	1740	---
Total C ₅ + Yield, wt%	98.4	97.8	97.1	96.9	96.6	100
Total C ₅ + Yield, LV%	112.4	111.0	107.7	106.6	104.2	100
Inspections of Total Liquid Product						
Gravity, OAPI	39.3	38.4	34.1	32.7	29.9	18.6
Aniline Point, of	116.9	105.4	67.5	54.8	38.1	<30
Sulfur, ppm	5	3	5	21	8	2900
Nitrogen, ppm	0.25	0.27	20	52	453	8500
Hydrogen, wt%	13.7	13.5	12.4	11.8	11.4	10.46
Oxygen, ppm ²	40	40	630	680	2800	37,900
H/C Atom Ratio	1.90	1.87	1.70	1.61	1.54	1.47
Group Type, LV%						
Paraffins	6.4	7.5	7.8	8.4	7.1	---
Naphthenes	89.9	79.4	57.2	47.7	43.7	---
Aromatics	4.3	13.1	35.0	43.9	49.4	---
TBP Distillation, of						
IBP/5	65/181	65/181	59/175	66/179	59/181	56/189
10/30	215/276	215/277	109/279	213/286	216/309	241/379
50	365	364	370	380	401	424
70/90	410/499	410/498	435/518	442/528	454/545	473/562
95/99	546/648	543/657	570/685	581/705	608/746	642/820

1. Source: W. Virginia Coal (Pittsburgh Seam, Blacksville No. 2 Mine of the Consolidation Coal Company).
2. Includes dissolved water.

TABLE 33

HIGH SEVERITY HYDROTREATING YIELDS AND HYDROGEN CONSUMPTIONS [104]

	<u>SRC-II Pittsburgh Seam Coal</u>	<u>EDS Texas Lignite</u>	<u>H-Coal Illinois No. 6</u>	<u>H-Coal Wyodak</u>
Yields, LV%				
C ₅ - 180°F	5	10	4	10
180°F - 250°F	16	18	18	19
250°F - 600°F	85	73	84	72
Total C ₅ - 600°F	106	101	106	101
Yields for Jet Fuel Production				
Naphtha, LV%	25	29	21	29
Jet A, LV%	85	74	88	75
Yields for Diesel Production				
Naphtha, LV%	25	29	21	29
Diesel fuel, LV%	87	77	90	77
Hydrogen consumption, scf/bbl feed	3100	1800	2150	1230

TABLE 34

HIGH SEVERITY HYDROTREATING PRODUCT INSPECTIONS [104]

	<u>SRC-II 300°F-500°F</u>	<u>SRC-II 350°F+</u>	<u>EDS</u>	<u>H-Coal Illinois No. 6</u>	<u>H-Coal Wyodak</u>
Gravity, °API	34.9	32.8	35.0	37.8	39.7
Boiling Range, °F	300-500	350+	300-600	250+	250+
Aniline Point, °F	121	129	125	122	132
Freeze Point, °F	<-94	-62	-59	-51	
Pour Point, °F		-55	<-80		-60
Cloud Point, °F			-72		
Sulfur, ppm			0.7		
Nitrogen, ppm		0.3	0.3		
Smoke Point, mm			20-23	21	21
Cetane Number		36.2			

TABLE 35

TYPICAL NAPHTHAS FROM HYDROTREATING OF COAL-DERIVED OILS [83]

<u>Feed</u>	<u>SRC-II</u>	<u>Illinois H-Coal</u>	<u>Wyodak H-Coal</u>	<u>EDS</u>
C ₅ -180°F Naphtha				
Gravity, °API	61	64	67	66
Group Type, LV%				
Paraffins	31	36	46	39
Naphthenes	64	59	52	56
Aromatics	5	5	2	5
180°F-350°F Naphtha				
Gravity, °API	48	47	50	53
Group Type, LV%				
Paraffins	9	9	18	21
Naphthenes	78	76	74	71
Aromatics	13	15	8	8

TABLE 36

PROPERTIES OF SELECTED NAPHTHAS DERIVED FROM SHALE OIL AND
WYODAK H-COAL [83]

	<u>Hydrotreated Shale Oil</u>	<u>Hydrotreated Wyodak H-Coal</u>
C ₅ -180°F		
Gravity, °API	85	66
Octane No., F-1 Clear	70	79
Group Type, LV%		
Paraffins	90	42
Naphthenes	9	57
Aromatics	1	1
iC ₅ /nC ₆	0.7	0.4
iC ₆ /nC ₆	1.2	0.6
180°F-300°F		
Gravity, °API	58	50
Octane No., F-1 Clear	51	56
Group Type, LV%		
Paraffins	51	18
Naphthenes	39	80
Aromatics	10	2

TABLE 37

PROPERTIES OF NAPHTHA PRODUCTS FROM SRC-II LIQUIDS
HYDROTREATED AT INTERMEDIATE AND HIGH SEVERITIES [144]

Severity	High		Intermediate	
Catalyst Condition	Fresh	Aged	Fresh	Aged
Inspections, C ₅ -180°F Product				
Gravity, °API	60.7	58.6	59.9	59.9
Group Type, LV%				
Paraffins	31.2	26.2	30.0	32.8
Naphthenes	65.4	66.3	62.3	58.0
Aromatics	3.4	7.4	7.7	9.1
Olefins		0.1		0.1
Octane Number				
F-1 Clear	81.1	82.2	81.5	81.1
F-2 Clear	77.0		77.4	
Inspections, 180°F-300°F Product				
Gravity, °API	51.6	49.9	49.0	48.4
Aniline Point, °F	108.8	96.8	87.4	79.2
Nitrogen, ppm	0.1	0.1	2.1	2.0
Oxygen, ppm	<20	<20	280	300
Group Type, LV%				
Paraffins	7.1	10.1	10.1	11.3
Naphthenes	90.1	79.5	75.8	69.3
Aromatics	2.8	10.4	14.1	19.4
Octane Number				
F-1 Clear	66.0	68.4	69.2	72.0
F-2 Clear	66.0	66.9	67.3	68.5

TABLE 38

COMPOSITION OF NAPHTHA FRACTION (<392°F) FROM EIGHT UPGRADED COAL LIQUIDS [137]

Coal Source	Pittsburgh	Illinois No. 6	W. Kentucky	Colstrip	Wyodak	Lignite
Specific gravity	0.829	0.825-0.827	0.832	0.822	0.819-0.810	0.822
API gravity	39.2	40.0-39.6	38.6	40.6	41.3-43.2	40.6
Sulfur, wt%	<0.01	0.02-0.01	<0.01	<0.01	<0.01	<0.01
Nitrogen, wt%	0.003	0.068-0.001	0.096	0.023	0.003-<0.001	0.007
Compound type, wt%						
0-ring paraffin	7.8	7.1-6.8	20.8	10.3	12.7-11.3	9.1
1-ring paraffin	43.4	50.4-48.4	45.3	47.0	47.3-54.0	50.2
2-ring paraffin	29.1	17.5-22.5	16.9	22.2	21.2-25.4	19.8
Alkyl benzenes	14.9	15.7-16.0	13.6	11.0	13.4-7.4	15.0
Indans/Tetralins	4.7	8.8-6.2	3.4	9.1	5.5-1.9	5.9
Naphthalenes	0.1	0.5-0.2	---	0.26	---	---

TABLE 39

COMPARISON OF KEROSENE JET FUEL PRODUCTS FROM
SEVERELY HYDROTREATED COAL-DERIVED LIQUIDS WITH ASTM JET A SPECIFICATIONS [83]

Property	Jet A Specification ASTM D1655-78	250°F-600°F Products			
		Illinois H-Coal	Wyodak ^b H-Coal	SRC-II	EDS ^a
Gravity, OAPI	37-51	37	39.7	36.3	37
Smoke Point, mm	>20	23	21	22	20
Freeze Point, °F	<-40	-53	<-40	-75	-63
Thermal Stability, JFTOT at 260°C	Pass	Pass	Pass	Pass	
Aromatics, LV%	<20	2.3	3.6	5.0	9
Existent Gum, ppm	<7	1	1	2	
Cu Strip Corrosion, 2 hr at 212°F	No. 1	No. 1	No. 1	No. 1	No. 1
End Point, D86, °F	<570	554	<554	550	
Flash Point, °F	>100	108	>100	104	113
Yield from Syncrude, LV%		87	75	84	76

^a Inspections are incomplete at the time of writing.

^b It contains 8 LV% paraffins, 88 LV% cycloparaffins, 4 LV% aromatics, and 0.1 ppm nitrogen.

TABLE 40

REPRESENTATIVE 250°F-550°F JET FUELS FROM HYDROTREATED COAL LIQUIDS [148]

Liquefaction Process	H-Coal	H-Coal	EDS	Jet A Spec.
Coal Type	Bituminous	Subbituminous	Lignite	
Property/Composition ^a				
Gravity, OAPI	37.8	39.3	38.0	37 min
Smoke point, mm	21	20	25	20 min
Freeze point, °F	-68	<-94	-58	-40 max
Flash point, °F	105	103	100	100 min
Viscosity, cSt at -40°F	4.7	4.0	4.1	8 max
Naphthalenes, LV%	0.2	0.6	0.02	3 max
ASTM D86 end point, °F	536	498	543	572 max
Group Type, LV%				
Paraffins	3.6	10.0	8.0	
Naphthenes	90.7	75.8	84.7	
Aromatics	5.7	14.2	7.3	20 max

^a These samples or similar samples also met all other ASTM Jet A specifications.

TABLE 41

PROPERTIES OF SELECTED JET FUELS DERIVED FROM SHALE OIL AND WYODAK H-COAL [148]

Property/Composition	Acceptable Petroleum Jet A	350°F-500°F Hydrotreated Shale Oil	300°F-535°F Hydrocracked Shale Oil	250°F-600°F Hydrotreated Wyodak H-Coal
Gravity, OAPI	37-51	42	47	40
Group Type, LV%				
Paraffins		35	55	8
Cycloparaffins		45	40	88
Aromatics	<20	20	5	4
Smoke point, mm	>20	21	35	21
Freeze point, °F	<-40	-42	-65	<-40
Nitrogen, ppm	^a	2	0.1	0.1

^a In addition, severe stability requirements mean that heteroatom content must be very low (usually the nitrogen content is less than 10 ppm for petroleum-derived jet fuel).

TABLE 42

JET FUELS FROM HYDROTREATING AND HYDROCRACKING ILLINOIS ITSLS LIQUID [148]

Description	From Hydrotreated Coal Liquids		From Hydrotreated and Hydrocracked Coal Liquids		Jet A Spec.
Boiling Range, of	250-550	350-550	250-550	350-550	
Property/Composition ^a					
Gravity, OAPI	30.0	28.3	35.1	31.1	37 min
Hydrogen, wt%	13.5	13.4	13.6	13.3	20 min
Smoke point, mm	20	20	23	21	-40 max
Freeze point, of	<-94	<-94	<-94	<-94	100 min
Flash point, of	126	NA	105	NA	8 max
Viscosity, cSt at -40F	10.2	NA	6.2	NA	3 max
Naphthalenes, LV%	0.07	NA	<0.05	<0.05	572 max
Heat of combustion, Btu/gal (est.)	134,000	137,000	130,000	133,000	
ASTM D86 end point, of	531	540	NA	NA	
ASTM D2887 Dist., of (TBP)					
IBP/5	221/303	333/361	234/267	335/353	
10/30	340/393	375/417	286/349	363/396	
50	456	450	393	445	
70/90	502/527	499/535	461/521	484/527	
95/99	535/549	544/555	535/551	540/552	
Group type, LV%					
Total Paraffins	1.3	0.0	2.3	0.5	
Total Naphthenes	90.5	91.2	95.5	96.8	
Total Aromatics	8.2	8.7	2.2	2.7	20 max
Naphthene Distribution					
1-Ring	37.6	30.2	40.2	27.7	
2-Rings	39.8	36.5	29.7	23.2	
3-Rings	13.1	18.7	20.1	28.8	
4-Rings			5.6	8.1	

^a In addition, these or similar samples consistently met or exceeded other jet specifications [thermal stability (JF10F), gum, corrosion, sulfur, etc.].

^b The gravimetric heats of combustion of these samples by ASTM D1405 were all about 18,400 Btu/lb, just meeting the ASTM specification.

NA = Not Analyzed.

TABLE 43

DETAILED ANALYSES OF NARROW-BOILING FRACTIONS OF JET FUEL
FROM HYDROTREATED WYODAK ITSL LIQUID [148]

<u>Boiling Range, °F</u>	<u>400-450</u>	<u>450-500</u>	<u>500-550</u>
<u>Inspections</u>			
Gravity, °API	31.3	26.5	22.5
Hydrogen, wt%	13.3	13.0	12.8
Smoke point, mm	22	15	15
Freeze point, °F			-56
Group type, LV%			
Total Paraffins	3.9	0.0	0.0
Total Naphthenes	81.4	85.2	85.0
Total Aromatics	14.7	14.8	15.0
Naphthene Distribution			
1-Ring	34.2	30.1	16.5
2-Rings	42.7	36.3	29.3
3-Rings	4.4	18.8	39.2
Aromatic Distribution			
1-Ring	10.5	11.4	12.0
2-Rings Total			
1-Arom. Ring	3.3	2.4	1.3
2-Arom. Rings	0.8	0.8	1.0
3-Rings Total			
1-Arom. Ring			0.7

TABLE 44
DETAILED ANALYSES OF NARROW-BOILING FRACTIONS OF JET FUEL FROM HYDROTREATED WYODAK CTSL LIQUID [148]

Boiling Range, of	250-300	300-350	350-400	400-450	450-500	500-550
Wt% of 250°F-550°F Product	11.6	16.3	22.0	21.4	21.9	6.8
LV% of 250°F-550°F Product	12.4	17.0	21.9	21.2	21.0	6.5
Inspections						
Gravity, OAPI	51.1	44.3	36.9	35.3	31.1	30.8
Hydrogen, wt%	14.5	14.1	13.6	13.6	13.4	13.4
Smoke point, mm	38	25	25	23	23	20
Freeze point, °F						-27
Group type, LV%						
Total Paraffins	17.3	13.5	4.9	9.4	7.8	10.9
Total Naphthenes	79.5	83.9	85.9	80.1	81.3	78.5
Total Aromatics	3.3	2.6	9.2	10.5	10.9	10.6
Naphthene Distribution						
1-Ring	75.2	56.5	49.3	35.3	30.0	28.7
2-Rings	4.3	27.4	36.0	41.2	38.7	29.9
3-Rings			0.6	3.7	12.7	19.9
Aromatic Distribution						
1-Ring	3.3	2.4	7.4	7.3	7.8	6.6
2-Rings Total						
1-Arom. Ring		0.2	1.6	2.4	1.9	1.6
2-Arom. Rings			0.1	0.7	0.8	1.1
3-Rings Total						
1-Arom. Ring				0.1	0.4	1.3

TABLE 45

GROUP ANALYSIS OF DISTILLATES FROM UPGRADED TSL COAL LIQUIDS [137]

Coal Source	Pittsburgh	Illinois No. 6	W. Kentucky	Colstrip	Wyodak	Lignite
3920F-6170F						
Saturates	54.9	29.0-42.1	45.3	50.0	56.4-75.0	48.8
Monoaromatics	35.8	55.0-49.5	46.0	41.5	37.9-20.6	42.2
Diaromatics	6.3	8.7-5.5	5.0	4.7	3.8-1.7	4.2
Polyaromatic-Polar	1.7	7.3-2.9	2.5	3.6	1.9-1.6	4.8
6170F-7970F						
Saturates	26.8	10.2-17.2	21.6	27.7	32.8-61.6	25.2
Monoaromatics	50.1	33.4-43.1	41.5	40.4	39.8-22.1	38.0
Diaromatics	12.4	31.0-22.6	19.6	15.1	14.6-8.6	15.9
Polyaromatic-Polar	10.5	25.4-16.3	17.4	16.2	12.8-7.7	19.6
7970F-10040F						
Saturates	8.8	3.2-3.6	11.8	15.6	19.7-35.0	13.8
Monoaromatics	22.4	7.9-8.1	12.8	17.2	19.7-21.6	14.7
Diaromatics	22.5	21.8-21.7	23.7	21.7	19.0-14.8	17.8
Polyaromatic-Polar	46.2	67.0-66.6	50.4	45.5	41.6-28.6	52.5

TABLE 46

COMPARISON OF SEVERELY HYDROTREATED COAL PRODUCTS WITH ASTM DIESEL FUEL SPECIFICATIONS [83]

Property	Diesel Specifications ASTM D975-88				250°F+ Products from		
	No. 1D		No. 2D		Illinois H-Coal	Wyodak H-Coal	SRC-II
	All Climates	Typical Climates	Cold Climates				
Cetane No.	>40	>40	>40		~42	~41	~38
Cloud point, °F	Varies	Varies	<10		~50	~20	<~80
Sulfur	<0.5	<0.5	<0.05		0.001	0.002	0.002
Flash (P-M), °F	>100	>125	>125		116	~115	~115
Ash, wt%	<0.01	<0.01	<0.01		<0.002	<0.002	<0.002
D86, 90%, °F	<550	540-640	<640		511	499	492
Viscosity at 40°C, cSt	1.3-2.4	1.9-4.1	1.7-4.1		1.678	1.441	1.606
Viscosity at 100°F, SUS	<34.4	32.6-40.1	---		32.1	<32	<32
Cu Corrosion	<No. 3	<No. 3	<No. 3		No. 1	No. 1	No. 1
Aromatics	---	---	---		2.7	3.6	3.8
300°F+ Products							
Flash (P-M), °F					130	~130	130
D86, 90%, °F					534	<499	~503
Viscosity at 40°C, cSt					1.898	1.701	1.869
Yield from Total Liquid, LV%							
250°F					90	77	87
300°F					78	63	74

TABLE 47

PROPERTIES OF SELECTED DIESEL FUELS DERIVED FROM
SHALE OIL AND WYODAK H-COAL [83]

	Typical Diesel from Petroleum	350°F-650°F Hydrotreated Shale Oil	350°F-600°F Hydrotreated Shale Oil Coker Distillate	300°F+ Hydrotreated Wyodak H-Coal
Gravity, °API	>30	38	41	36
Cetane No.	>40	46	48	40
Pour point, °F	<+15	-5	-20	-45
Group type, LV%				
Paraffins		37	41	9
Naphthenes		44	41	89
Aromatics		19	18	2
Nitrogen, ppm		350	350	<1

TABLE 48

PROPERTIES OF 250°F+ FRACTIONS FROM ITSL LIQUIDS
(Hydrotreated with ICR-106 catalyst at 0.5 LHSV, 683°F-730°F) [132,152]

<u>Coal Source</u>	<u>Illinois No. 6</u>	<u>Wyodak</u>
Product Inspections		
Gravity, °API	24.7-25.8	25.2-25.6
Aniline Point, °F	126.1-132.1	129.6-132.9
Smoke Point, mm	14-15	---
Cetane Number	-43	41.1-43.5
Pour Point, °F	<-80	<-30
Cloud Point, °F	<-80	+10
Freeze Point, °F	<-70	-26
Flash Point, °F	---	185
Viscosity, cSt at 104°F	---	4.0-4.1
Group Type, LV%		
Paraffins	0	3.1-5.7
Naphthenes	85.2-90.1	77.7-81.3
Aromatics	9.8-14.8	13.0-19.1
Carbon, wt%	86.8-87.3	87.0
Hydrogen, wt%	12.7-13.2	13.0
ASTM D86 Dist., °F		
IBP	334-338	344-351
10%	405-411	420-423
30%	474-484	510-514
50%	527-539	552-563
70%	566-576	578-594
90%	610-620	612-636
FBP	659-674	671-694

TABLE 49

COMPARISON OF 250°F + FRACTIONS FROM MODERATELY HYDROTREATED COAL LIQUIDS
WITH ASTM SPECIFICATIONS FOR HEATING FUEL [83]

Property	No. 2 Fuel Oil Specifications D396-88		250°F+ Product from			
	Typical Climate	Cold Climate	Illinois H-Coal	Wyodak H-Coal	SRC-II	EDS
Gravity, °API	>30	>30	28	33	~27	29
Flash, °F	>100	>100	116	114	>100	113
Pour, °F	<20	<0	<-80	-45	<-80	-25
D86, 90%, °F	540-640	<640	560	527	~550	
Viscosity at 100°F, cSt	2.0-3.6	1.8-3.6	1.8	1.5	~1.6	1.7
Cu Corrosion	<No. 3	<No. 3	No.1	No. 1	No. 1	No. 1
Sulfur, ppm	<5000	<5000	2	0.8	4	2
Aromatics, LV%	---	---	54	49	58	
Yield from Total Coal Liquid, LV%				84	77	80

TABLE 50

DETAILED ANALYSES OF NARROW-BOILING FRACTIONS OF JET FUEL FROM HYDROTREATED ILLINOIS ITS L LIQUID [148]

Boiling Range, °F	250-300	300-350	350-400	400-450	450-500	500-550
Wt% of 250°F-550°F Product	4.6	6.0	18.8	16.7	21.1	32.8
LV% of 250°F-550°F Product	5.1	6.5	19.2	26.8	20.8	31.6
<u>Inspections</u>						
Gravity, °API	48.5	42.0	33.7	31.2	27.2	23.9
Hydrogen, wt%	14.1	13.7	13.4	13.2	13.0	12.7
Smoke point, mm	34	25	20	20	19	17
Freeze point, °F					<-94	<-94
Group type, LV%						
Total Paraffins	5.2	5.3	0.0	0.0	0.0	0.0
Total Naphthenes	89.4	90.2	88.1	90.3	90.0	90.1
Total Aromatics	5.5	4.4	11.9	9.6	10.0	9.9
Naphthene Distribution						
1-Ring	85.3	63.5	51.1	39.5	43.0	23.6
2-Rings	4.1	26.7	36.6	48.3	35.0	34.3
3-Rings			0.3	2.5	12.0	32.2
Aromatic Distribution						
1-Ring	5.5	4.1	10.7	6.8	6.4	6.9
2-Rings Total						
1-Arom. Ring		0.2	1.0	2.4	2.8	1.7
2-Arom. Rings		0.1	0.2	0.4	0.5	0.6
3-Rings Total						
1-Arom. Ring					0.3	0.7

TABLE 51

DETAILED ANALYSES OF NARROW-BOILING FRACTIONS OF JET FUEL FROM
HYDROCRACKING OF HYDROTREATED ILLINOIS ITSLS LIQUID [148]
Extinction Recycle of 550°F + Feed

Boiling Range, of	250-300	300-350	350-400	400-450	450-500	500-550
Wt% of 250°F-550°F Product	12.8	15.7	20.3	17.6	14.4	19.3
LV% of 250°F-550°F Product	13.9	16.4	20.4	17.3	13.9	18.2
<u>Inspections</u>						
Gravity, OAPI	50.1	42.6	36.2	32.7	29.2	25.6
Hydrogen, wt%	14.4	13.9	13.5	13.4	13.2	13.2
Smoke point, mm	32	25	23	20	20	21
Freeze point, of					<-94	<-94
Group type, LV%						
Total Paraffins	4.9	6.6	0.7	0.2	0.0	0.9
Total Naphthenes	95.0	91.6	96.7	97.6	95.9	96.8
Total Aromatics	0.1	1.8	2.6	2.2	4.1	2.3
Naphthene Distribution						
1-Ring	88.5	52.9	48.0	23.2	21.0	14.5
2-Rings	6.5	38.7	42.3	33.6	30.7	20.4
3-Rings			6.3	40.9	44.2	30.6
4-Rings						31.2
Aromatic Distribution						
1-Ring	0.1	1.8	2.6	2.2	4.1	1.9
2-Rings Total						
1-Arom. Ring						0.3
2-Arom. Rings						0.1

FIGURES

FIGURE 1. TBP DISTILLATIONS OF ARABIAN LIGHT CRUDE, SHALE OIL AND COAL-DERIVED LIQUIDS [83]

FIGURE 2. TBP DISTILLATIONS OF ARABIAN CRUDES AND COAL-DERIVED LIQUIDS [84]

FIGURE 3. TBP DISTILLATIONS OF COAL LIQUIDS [87]

FIGURE 4. TBP DISTILLATIONS OF COAL LIQUIDS

FIGURE 5. HYDROGEN CONTENT OF COAL LIQUID FRACTIONS VS. BOILING RANGE [87]

FIGURE 6. DISTRIBUTION OF HETEROATOM CONTENT IN H-COAL FRACTIONS [99]

FIGURE 7. DIRECT OXYGEN CONTENT VS. AVERAGE CUT TEMPERATURE OF COAL LIQUIDS FROM TWO LIQUEFACTION STAGES [88]

FIGURE 8. SULFUR LEVEL VS. AVERAGE CUT TEMPERATURE OF COAL LIQUIDS FROM TWO LIQUEFACTION STAGES [88]

FIGURE 9. TOTAL NITROGEN CONTENT VS. AVERAGE CUT TEMPERATURE OF COAL LIQUIDS [88]

FIGURE 10. BASIC NITROGEN LEVEL VS. AVERAGE CUT TEMPERATURE OF COAL LIQUIDS [88]

FIGURE 11. OXYGEN DISTRIBUTION IN CC-ITSL COAL LIQUIDS [100]

FIGURE 12. HYDROGEN AND LIQUID YIELD VS. OCTANE
FOR UPGRADED ILLINOIS NO. 6 H-COAL
NAPHTHA [114]

**FIGURE 13. HYDROGEN AND LIQUID YIELD VS. OCTANE
FOR UPGRADED ILLINOIS NO. 6 SRC-II
NAPHTHA [115]**

**FIGURE 14. HYDROGEN CONSUMPTION
VS. EDS NAPHTHA API GRAVITY
INCREASE [118]**

FIGURE 15. C_5^+ REFORMAT YIELD VS. OCTANE LEVEL
FOR EDs NAPHTHA [118]

FIGURE 16. HYDROGEN YIELD VS. OCTANE LEVEL FOR
EDS NAPHTHA REFORMING [118]

**FIGURE 17. HYDROTREATING OF ILLINOIS NO. 6 EDS
MIDDLE DISTILLATE [116]**

FIGURE 18. RELATIONSHIPS OF CETANE NUMBER, AROMATICS CONCENTRATION, AND HYDROGEN CONTENT OF COAL-DERIVED MIDDLE DISTILLATES

FIGURE 19. EFFECT OF FEEDSTOCK HYDROGEN CONTENT ON RESPONSE TO FLUID CATALYTIC CRACKING (H-Coal Gas Oil)
[125]

FIGURE 20. EFFECT OF FEEDSTOCK HYDROGEN CONTENT ON RESPONSE TO FLUID CATALYTIC CRACKING (EDS Gas Oil) [127]

FIGURE 21. C_5^+ YIELD VS. PRODUCT AROMATIC CONTENT
[129]

NO. 19,776

FIGURE 22. PRODUCT NITROGEN VS. HYDROGEN CONSUMPTION FOR COAL LIQUIDS [83]

FIGURE 23. PRODUCT AROMATIC CONTENT VS. HYDROGEN CONSUMPTION FOR COAL LIQUIDS [83]

FIGURE 24. EFFECT OF FEED END POINT ON CATALYST TEMPERATURE FOR HYDRODENITROGENATION OF ITSL OILS [84]

FIGURE 26. SMOKE POINT OF 250°F+ JET FUELS FROM DIFFERENT HYDROTREATING SCHEMES [119]

- By hydrotreating a distillate (250-600°F) from raw EDS liquid.
- By hydrotreating the whole EDS liquid and then distilling.

FIGURE 27. EFFECT OF AROMATICS ON THE CETANE NUMBER OF DIESEL FUELS FROM HYDROTREATED COAL-DERIVED OILS [87]

NO 119,778

**FIGURE 28. EFFECT OF OCTYL NITRATE
CETANE NUMBER IMPROVER
ON TWO COAL-DERIVED
DIESEL FUELS [33]**

**FIGURE 29. YIELD-OCTANE CURVE FOR H-COAL
HYDROCRACKATE PLATFORMING [114]**

FIGURE 30. HYDROCRACKING OF HYDROTREATED ITSL OIL-EFFECT OF RECYCLE CUT POINT ON YIELD AND SMOKE POINT OF 250°F+ JET FUEL FRACTION [119]

NO. 19.779

FIGURE 31. EFFECT OF BOILING RANGE ON SMOKE POINT OF NARROW-BOILING FRACTIONS OF HYDROCRACKED ITSIL OIL [119]

FIGURE 32. REFINING SCHEME FOR COAL LIQUIDS

NOJ19.782

END

**DATE
FILMED**

5 / 24 / 93