DOE/PC/89883-41
(DE92015559)

**COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND
EVALUATION**

Chromatographic and Spectroscopic Techniques

Topical Report

**By
Larry T. Taylor
John W. Hellgeth
Anna Sequeira
F. P. Burke
R. A. Winschel
S. D. Brandes**

January 1992

Work Performed Under Contract No. AC22-89PC89883

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

and

**CONSOL Inc.
Library, Pennsylvania**

**By
Virginia Polytechnic Institute and State University
Blacksburg, Virginia**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, ~~DTIC 605 8401~~.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Coal Liquefaction Process Streams Characterization and Evaluation

Chromatographic and Spectroscopic Techniques

Topical Report

Prepared by:

Virginia Polytechnic Institute
and State University
Department of Chemistry
Blacksburg, VA 24061-0212

Larry T. Taylor
John W. Hellgeth
Anna Sequeira

Prepared for:

CONSOL INC.
Research & Development
4000 Brownsville Road
Liberty, PA 15129

F. P. Burke
R. A. Winschel
S. D. Brandes

January 1992

Under Contract to:

United States Department of Energy
Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on January 15, 1992

PROJECT ASSESSMENT

Introduction

Under subcontract to Consolidation Coal Co. (U.S. DOE Contract No. DE-AC22-89PC89883), Virginia Polytechnic Institute and State University (VPI) studied the use of two separation methods for the analysis of coal-derived materials. Separation methods are often used as stand-alone analytical methods in the analysis of coal liquids, e.g., solubility fractionation into oils, asphaltenes and preasphaltenes, and the SESC¹ and SARA² methods. In addition, separation methods are frequently used to fractionate complex coal liquids into better defined fractions to facilitate further analysis. The two methods studied by VPI were 1) preparative-scale liquid column chromatography (LC) followed by analytical-scale normal-phase liquid chromatography - Fourier transform infrared spectroscopic (LC-FTIR) analysis of the fractions, and 2) supercritical fluid extraction (SFE). Prior to conducting the separations, VPI inspected the samples by infrared spectroscopy. The full report authored by the VPI researchers is presented here. The following assessment briefly highlights the major findings of the project, and provides Consol's evaluation of the potential of the methods for application to process development. These results will be incorporated by Consol into a general overview of the application of novel analytical techniques to coal-derived materials at the conclusion of this contract.

Summary

This study was designed to demonstrate the use of two different methods for the separation of direct coal liquefaction process-derived materials into defined fractions. The two methods, liquid chromatography (LC) and supercritical fluid extraction (SFE), were employed to determine if the same or complementary information could be obtained by the two methods. The primary objective was to evaluate the potential of supplementing or replacing the conventional LC method with SFE and in so doing to exploit the advantages of SFE. A solvent density gradient can be employed in SFE in much the same way that a gradient of solvent strength or polarity is employed in LC. Alternatively, modifiers or co-solvents can be used in SFE to change the extraction properties of the primary solvent.

Potential advantages of SFE over LC include: a relatively low amount of solvent is necessary to effect separation, SFE solvents are usually non-flammable and non-toxic, solvent disposal problems are minimized, separation is frequently faster.

Preparative-scale liquid chromatography was successful in separating the tetrahydrofuran (THF)-soluble resids into four fractions of differing polarity. Two of the fractions, originally believed to be the oxygen- and nitrogen-rich, were subsequently characterized by LC-FTIR. The LC method shows some potential usefulness for process development support. However, the time requirement for this method should be improved and the chemical fractionation should be better understood to improve the utility of the method.

Seven different extraction conditions were employed in the SFE fractionation of eighteen samples. The samples could only be minimally extracted (<16 wt %) at the conditions chosen. The low extract yields prevented the completion of planned LC-FTIR characterization of the extracts. The SFE method, as employed in this work, was not successful in effecting a selective separation of liquefaction resids into multiple fractions. Still, SFE methods appear to hold potential for use as selective separation techniques. Further methods development work appears warranted.

Further development of these analytical methods will be required before their use as process development tools can be recommended.

Program Description

This report describes the work performed at Virginia Polytechnic Institute and State University (VPI) under a subcontract to Consolidation Coal Co., Research and Development. Consol's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process

improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. Consol is providing well-documented samples from different direct coal liquefaction development facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

VPI applied preparative-scale liquid column chromatographic (LC) fractionation followed by normal-phase liquid chromatography-Fourier transform infrared spectroscopy (LC-FTIR) analyses of the resulting fractions, and supercritical fluid extraction (SFE) to eighteen tetrahydrofuran (THF)-soluble portions of direct coal liquefaction distillation resid (850°F⁺). VPI also inspected the samples by infrared spectroscopy prior to conducting the separations. A Task Summary is given in the Work Plan presented below.

The samples were produced at three different continuous coal liquefaction facilities: the Wilsonville pilot plant, the Hydrocarbon Research Inc. (HRI) bench unit, and the Lummus process development unit. The major processing parameters which were varied among the Wilsonville runs were feed coal, catalyst, ash recycle, and sampling location in the plant. Samples from Wilsonville were taken from two different locations in the plant. These samples are expected to represent different extents of coal liquefaction. Some of the Wilsonville samples were composites of samples taken over long periods of single runs; others were samples obtained from a single run day. The HRI samples were also obtained from different plant locations and thus represent material which has undergone different degrees of processing. HRI samples were chosen to compare materials produced with a raw feed coal and with a feed coal that had been

thermally pretreated to reduce its oxygen content. The Lummus samples were representative of ashy and deashed recycle streams. The experimental procedures used in VPI's work are described on pages 7-8, pages 16-17, and page 19 of the attached report.

Participant's Major Findings

The following principal observations for the application of preparative-scale liquid column chromatography and LC-FTIR to coal liquefaction materials were reported by VPI. An expanded discussion can be found in the attached report, pages 8-15.

Prior to separation, each sample was examined by diffuse reflectance infrared spectroscopy (DRIFT). Though the spectra showed the same basic features, significant differences were apparent in the O-H, N-H and C=O regions of the spectra. The presence of the carbonyl band in some of the samples may indicate that those samples (or their precursors) had become oxidized during storage or handling.

The samples were separated by preparative-scale liquid column chromatography on a silica gel column with four solvents (hexane, hexane/hloroform, acetonitrile, THF) into four fractions of increasing polarity. The relative quantities of the four fractions (F1, non-polars; F2, intermediate polars; F3, polars; F4, very polars) show some correspondence with feed coal, processing plant, and thermal treatment (Table IV, page 25). In addition, a correlation can be observed between the phenolic -OH content of the samples (as measured by Consol) and the yield of fraction F4 (very polars), as shown in the following figure.

Phenolic -OH Concentration vs wt % Very Polar Fraction (F4), Corrected

NOTE: Numbers in Parentheses are sample numbers

Each of the four separated fractions from several samples was examined by DRIFT analysis. Increasing functionality was observed for progressive fractions. Analytical-scale LC-FTIR analyses were performed on Fractions 2 and 3 from each sample. Prior to this work, Fractions 2 and 3 were expected to be oxygen- and nitrogen-rich, respectively. The Fractions 2 prepared from all samples showed a near absence of O-H, C=O and ether bands; however, in some cases minor carbonyl bands were observed and some evidence for the presence of phenols was observed in the Wilsonville samples. VPI concluded that, in retrospect, Fraction 2 apparently contained very low concentrations of oxygen-containing species. The Fractions 3 prepared from all samples showed no evidence of nitrogen-containing species; however, many of the spectra showed strong carbonyl bands and in some cases, phenolic or etheric bands.

Seven different experimental conditions were employed in the supercritical CO₂ extraction of eighteen THF-soluble distillation resids to examine the impact of those conditions on the yield of extractables. As expected, increasing the supercritical CO₂ density from 0.3 to 0.9 g/mL

increased the yield of material extracted. However, the yield of extracted material was less than 10 wt% for all samples when pure CO₂ was the solvent. Methanol, toluene, and acetonitrile (1 to 4 wt %) were added to the supercritical CO₂ to modify the solvating power of the extracting fluid; surprisingly, extract yields were lower than with pure CO₂ in all but one case. VPI identified several limitations in the SFE experiments: the method for determining extract yield may have been biased low, extraction time was probably insufficient for the sample size used, some samples fused in the extraction vessel and probably had poor contact with the extracting fluid. The VPI team believe that these problems, which are discussed on pages 16-21, could be overcome with additional work. The low extract yields (<16 wt % in all cases) precluded the planned characterization of the extracts by LC-FTIR.

Consol Evaluation

The preparative-scale liquid chromatographic technique used in this study provides a separation of complex resids into four chemically distinct fractions. The fraction yields are correlatable to gross processing changes; thus, this method has some potential for use in process monitoring and development. This conclusion must be tempered because the chemical nature of the fractions is apparently strongly affected by the sample being analyzed. For example, Fractions 2 and 3 from these samples were chemically quite different from the respective fractions from samples analyzed earlier by VPI. The method is relatively inexpensive in terms of consumables (on the order of \$300/sample for supplies) and can be executed by trained laboratory technicians; however, sample turn-around time is several days.

The LC-FTIR method can provide detailed chemical class information on complex mixtures. Unlike gas chromatography and mass spectrometry, it is applicable to non-volatile species. The cost of the LC equipment used in this study is about \$20,000. The FTIR detection can be done with any of a number of commercially available instruments which range in cost from \$50,000 to \$150,000.

The value of the SFE method for analysis of direct coal liquefaction materials cannot be evaluated from this study. The conditions tested

were chosen on the basis of VPI's experience with other samples. In light of the uniformly low extraction yields obtained, it appears that the chosen conditions were far from optimum. This study was aimed at application of established techniques; it was not designed to accommodate development of methodology. Optimization of extraction conditions and further testing of SFE is recommended to discover if the method has a potential use for the support of direct coal liquefaction process development. The equipment cost for SFE, as detailed in the accompanying report, is approximately \$50,000.

Further Development

There are a number of avenues for further development of the techniques described here. LC techniques have frequently been used to reduce complex mixtures, including coal liquids, into chemically analyzable fractions (for example the SESC¹ and the SARA² procedures). The simple four-fraction separation used in this study may be sufficient to observe changes in processing conditions or to provide fractions for further analysis that are chemically less complex than the original sample. A better understanding of the chemical nature of the fractions would improve the usefulness of the method. A reduction in analysis time would also make the preparatory-scale LC procedure used here more useful. It may be possible to perform the same preparative separation under pressure in a high performance liquid chromatography (HPLC) system, with a subsequent reduction in analysis time.

The LC-FTIR method, because of its ability to deal with non-volatile samples and its speed, shows potential usefulness as a characterization tool for process development. The 2-D LC/FTIR contour plots may contain more information relating to processing conditions than was detailed in this scoping study. Possible on-line application of this method is indicated in this study; this aspect requires further study.

Supercritical fluid extraction of coal liquefaction process materials will require additional development before the technique has practical application. A multi-dimensional study of solvent/modifier/pressure/temperature/time would be required to establish appropriate analytical conditions.

Contractor's Statement of Work

The analysis of coal liquefaction process streams for heteroatomic species, particularly oxygen- and nitrogen-containing compounds, is of particular importance. The nitrogen-containing compounds are poisons for downstream refining catalysts. The oxygen compounds appear to be important in retrogressive reactions in the conversion process. In order to obtain a better understanding of the species present in relation to process performance, VPI will use liquid chromatography (LC) and supercritical fluid extraction (SFE) to separate a number of coal liquefaction-derived resids into fractions. These fractions then will be analyzed to determine oxygen- and nitrogen-containing species. The fractions generated by LC will be analyzed by Fourier transform infrared (FTIR) spectroscopy. The fractions generated by SFE will be further fractionated using supercritical fluid chromatography (SFC) coupled to appropriate detectors inclusive of FTIR, nitrogen chemiluminescence, or nitrogen-phosphorous (NPD) for analysis.

Liquid chromatography will be performed on eight samples described below in the Task Summary. This method will yield well-defined classes of compounds. However, the tetrahydrofuran (THF) soluble resids will first be separated on a preparatory-scale into fractions of varying polarity (as described in Ametis, P. G. and L. T. Taylor, *Chromatographia* 1984, 18(4), pp. 175-182). Supercritical fluid extraction (SFE) will be employed on the unfractionated sample as a comparative method for the separation and characterization of the THF soluble resids. The technique of supercritical fluid extraction (SFE) will be used to separate the materials into multiple fractions so as to be comparable to the LC fractions. Multiple fractions will be generated in three ways. The first method will be by using a density gradient of the extracting fluid; twelve samples, as designated in the attached Task Summary, will be separated. The second and third methods involve the use of modifiers which are added to the bulk solvent to vary its selectivity. In the second method, modifiers will be used to generate multiple fractions by varying the concentration of a single modifier in the bulk solvent as the experiment proceeds. The third method will be to change the modifier and, therefore, the extraction power of the supercritical fluid at designated points in the extraction. The polar modifiers to be used are

designated in the attached Task Summary. Samples for the second and third methods are designated in the attached Task Summary.

The LC-FTIR method and the SFE-SFC method are not applicable to solids-containing samples and, therefore, a sample set has been selected which contains only the tetrahydrofuran (THF) soluble portion of distillation resid from different process streams. Consol will supply to VPI eighteen THF-soluble resid samples. These samples will be supplied with the following information (as available): elemental analyses, phenolic - OH concentration, calorific value, hydrogen classes by ¹H-NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). At least 20 g of each sample will be supplied. Replicate analyses will be performed as appropriate to define precision.

REFERENCES

1. Farcasiu, M. "Fractionation and Structural Characterization of Coal Liquids", *Fuel* 1977, 57, 47.
2. Given, P. H.; Cronauer, D. C.; Spakman, W.; Lovell, H. L.; Davis, A.; Biswas, B. *Fuel* 1975, 54, 34.

Final Report

ANALYSIS OF COAL LIQUEFACTION PROCESS STREAMS

Submitted to:

**Consolidation Coal Co.
Research & Development
4000 Brownsville Road
Liberty, PA 15129**

by:

**Larry T. Taylor - Principal Investigator
John W. Hellgeth - Research Associate
Anna Sequeira - Graduate Project Assistant**

**Virginia Polytechnic Institute and State University
Department of Chemistry
Blacksburg, VA 24061-0212**

November 1991

Executive Summary

In January 1991, Virginia Polytechnic Institute and State University began the analysis of coal liquefaction process products under a subcontract from Consolidation Coal Company. The prime contractor for this effort has been the U.S. Department of Energy (Contract #DE-AC22-89PC89883). The goals of the overall project were to identify promising analytical methodologies for supporting direct coal liquefaction process development and to demonstrate their application to well-documented samples obtained from process development units. This report provides a description of the analytical techniques employed at Virginia Polytechnic Institute and State University, their application to a discrete set of eighteen tetrahydrofuran (THF) soluble resid products, an interpretation of the results in the context of the liquefaction process and an evaluation of the chosen methodologies with regard to liquefaction process understanding and development.

To attain the goals previously mentioned, a set of six specific task objectives (5 experimental, 1 report) was proposed. Briefly, the five experimental objectives involved the application of preparative scale column fractionation, normal phase LC/FT-IR and quantitative supercritical fluid extraction for the characterization the THF soluble process stream resids. As these methods are currently under utilized, the intent of these objectives was to fully exploit their application concerning liquefaction products and to evaluate their usefulness for further process development.

Preparative scale column fractionation was applied to eight resid specimens. Elution of approximately five grams of each resid with hexane/chloroform (80/20) and chloroform/acetonitrile (90/10) gave rise to what we believed to be an oxygen enriched (~20%) and a nitrogen enriched (~40%) fraction. These two fractions were then characterized via LC/FT-IR as developed by Amateis et al. The study revealed predominantly hydrocarbon content for both fractions although phenolics, carbonyls and in several cases ethers were observed. More specifically, the suspected oxygen enriched fraction (#2) proved to be mostly hydrocarbon and to a lesser degree phenolic in character. The suspected nitrogen enriched fraction (#3) turned out to contain an abundance of

carbonyl and ether components as no infrared absorbances due to nitrogen were observed. Our inability to preliminarily "fine-tune" both the preparative step and the spectrometric parameters employed in order to compensate for the unknown samples agreed to for investigation was a serious impediment to the overall quality of the data obtained. For example dissimilarities in chromatographic column packing, column dimensions and infrared flow cell geometry had a considerable impact upon the quality of the information yielded here. In spite of these difficulties infrared appears to have excellent potential for readily assessing carbonyl and ether heteroatoms in coal-derived products. Phenolics were not as quickly detected due to either their lower abundance and/or their lower infrared absorbing capacity.

Rather than chromatographically separate resids by perceived differences in polarity, four resids in another study were evaluated for extractability with supercritical fluids under eight different conditions. The SFE conditions differed in terms of CO₂ fluid density, modifier type (methanol, toluene, etc.), and percent modifier content (1-4%) in the supercritical fluid. The arbitrarily chosen extraction parameters (i.e. not optimized) yielded small amounts of extractables in each resid. The amounts were relatively low probably because of limited mass transfer and non-exhaustive extraction procedures. Since the LC/FT-IR protocol chosen for this work was analytical scale, the small quantity of extractables (which differ in solubility) precluded our applying the LC/FT-IR methodology to these solubility fractions. Employing what at the time were our "best" perceived extraction conditions, seven THF soluble resids yielded again only a small amount of extractable material. Sufficient data were obtained, however, to indicate the future success of this approach. Again LC/FT-IR of these fractions employing an analytical scale column was precluded. In spite of our inability to perform LC/FT-IR on supercritical fluid extracted fractions, this six month project yielded a staggering amount of data and little extra time to reflect on the data's significance and impact.

A number of observations and recommendations can be made from this six month project.

1. The budget did not allow us to utilize an optimized analytical scale LC/FT-IR system since our work with coal-derived products ceased in 1987 due to the lack of DOE funding.

2. Miniaturization of LC/FT-IR would enable smaller size samples to be studied and would consume much less organic solvents.
3. The number of tasks and samples were too large and gave rise to insufficient time for data interpretation.
4. Both LC/FT-IR and SFE of unknown samples require a certain amount of optimization time. The amount of work to perform an analysis on one sample is not too different from the amount of work necessary for ten samples. The ten-fold increase in data, however, requires considerably more time for interpretation.
5. The issue of repeatability could not be addressed because of the large sample load. For example, Task I generated 32 fractions and Task II gave rise to 16 LC/FT-IR runs, each of which generated at least 100 spectra for interpretation.
6. Supercritical fluid extraction should be seriously examined in this type study because of the tremendous volume of organic solvent used especially in the preparative separation task (i.e. 3 liters per fraction generated). Solvent disposal costs and environmental concerns are major disadvantages to traditional coal fractionation procedures.
7. Closer inspection of each LC/FT-IR fraction in terms of computer spectral (solution phase) library searching and compound modeling would have yielded more specific information.
8. Infrared analysis of coal resid fractions on-line with chromatography affords unique chemical class information that is readily interpretable with minimal training. For example the presence of carbonylic material is immediately obvious without extensive data manipulation and no chemical derivatization.
9. Both SFE and FT-IR are readily quantifiable and are most amenable to non volatile species in contrast to gas chromatography and mass spectrometry.
10. A study should be commissioned to determine if LC/FT-IR can ascertain differences in processing with the same raw coal. The samples agreed to for study compared mostly differences in coal origin.

INTRODUCTION

The purpose of the study described herein was to determine the applicability of normal phase liquid chromatography (LC) and supercritical fluid extraction (SFE) for fractionation of tetrahydrofuran (THF) soluble resids prior to Fourier transform infrared analysis (FT-IR). The analysis of coal liquefaction process streams for heteroatomic species, particularly oxygen-and nitrogen-containing compounds, is of importance. FT-IR has the potential for readily yielding information concerning the presence of such non-volatile materials. The complexity of these resids dictated the necessity to preliminarily sub-divide the sample into a simpler (i.e. fewer chemical classes) mixture in order for more meaningful spectrometric data to be gathered. Two separation strategies were adopted (i.e. fractionation via chemical class and via solubility). Chemical class separation involved two dimensional LC; while, separation by solubility was achieved with SFE.

It was not the intention of the project to foster development of completely new analytical techniques, but to fully exploit the potential of existing yet currently under utilized techniques. When this project was initiated, the analytical laboratory at Virginia Polytechnic Institute and State University was not involved in any type of coal or coal liquefaction research. With the termination of Department of Energy funding in 1987 after 10 years, our analytical methods development work that was addressed towards fossil energy ceased. The consequences of this action meant that much optimized experimental equipment (columns, flow cells, extraction vessels, spectral libraries, etc.) was not available in 1991 in our laboratory. Since the project budget did not allow for the acquisition of any new items, most experiments were performed with whatever could be found in the laboratory or departmental stock room. Budgetary restrictions and sample load also precluded most experimental reproducibility assessments. All the laboratory investigations were carried-out by Anna Sequeira (graduate student) and John Hellgeth (Research Associate). The samples provided to us by Consolidated Coal Co. are listed in Table I. The samples on which the various analyses were attempted was determined in consultation with Consolidated Coal Co.

The project consisted of five Tasks as listed below:

TASK I	Preparative separation and infrared spectroscopy of as-received THF soluble resids
TASK II	Infrared spectroscopy of as-received THF soluble resids
TASK III	Normal phase liquid chromatography-Fourier transform infrared spectrometry of THF soluble resid fractions
TASK IV	Supercritical fluid extraction survey of as-received THF soluble resids
TASK V	Normal phase liquid chromatography/Fourier transform infrared spectrometry of supercritical fluid extracts
TASK VI	Supercritical fluid extraction of THF soluble resids under "Best" conditions

TASK I PREPARATIVE SEPARATION OF THF SOLUBLE RESIDS

Eight resids were provided by Consol for this task. The procedure described by Amateis and Taylor in *Chromatographia*, (1984), 18, 175-182 was generally followed. Although the Task only called for qualitative separations, we thought it would be more informative to quantify the preparative scale separations. Column packing, sample loading and elution, and fraction concentration coupled with drying and weighing required approximately four days per sample. The separation employed the short column chromatography technique developed by Rigby and Hunt (*Chem. Ind.* (1967) 1868).

The equipment tabulated below was used to perform the separation.

Column: Pyrex, 90 mm in diameter (3.5 in) by 60 cm (2 ft) with 4 mm teflon stopcock.

Silica gel: EM Silica G-60, 70-230 mesh. 500 gram obtained from Fisher Scientific Co.

Solvents: Hexane, chloroform (ethanol free), acetonitrile, methanol. Obtained from Fisher Scientific Co. and Burdick and Jackson. HPLC grade or better.

Other Materials: Sea sand (washed and ignited), glass wool, filter paper (Whatman #1 porosity), assorted flasks and glassware. All obtained from Fisher Scientific Co.

The column was prepared by first washing silica gel with copious amounts of methanol in order to remove the fines and soluble materials. The gel was then isolated from the methanol via vacuum filtration in a large Buchner funnel. The silica gel was subsequently dried at 110°C in a convection oven to remove the methanol and to activate the gel. Once dried, the silica gel was directly mixed with approximately 2 liters of hexane in a large Erlenmeyer flask. A sample to silica gel ratio of 1:25 was utilized. The column was next prepared for packing by placing a plug of glass wool into the short length of glass tubing that connects the column to the stopcock followed by enough sand to give an approximately 1/8 inch layer on the flat bottom of the column. Hexane was then added such that it filled the column to a depth of approximately 304 times the column

diameter. The column was then mounted to a perfectly vertical position. Flow rate was adjusted to 2-3 drops per second. The hexane slurry previously described was then poured into the column in a single portion. The smooth, flat layer of sand at the bottom of the column was not disturbed. The gel was then allowed to settle after which the stopcock was completely opened. The column was subsequently tapped with a cork ring while rotating the column through 360° in its supporting clamps in order to give an homogeneous absorbent bed. The top of the absorbent bed was next compacted by first allowing the column to run dry (i.e. all eluent stops dripping from column output) and then tapping gently again with a cork ring.

The sample was applied to the column in the following manner. A previously weighed sample (~5 grams) was initially mixed with hexane and a small amount of silica (60-200 mesh). The hexane was then evaporated from the sample and silica on a rotary evaporator. The dried silica with adsorbed coal resid was then carefully added to the top of the column. A thin layer of sand was then added in order to guard against the sample being disturbed.

Once the sample was introduced to the column, four fractions were sequentially eluted by successive applications of 2-3 liters of four solvents at a flow rate of 30-40 mL/min (Scheme I). The solvents and designated fractions were

Fraction 1 - Nonpolars - hexane

Fraction 2 - Intermediate Polars - hexane/20% CHCl_3

Fraction 3 - Polars - CHCl_3 /10% Acetonitrile

Fraction 4 - Very Polars - Tetrahydrofuran

Each fraction was then isolated from the respective solvent via rotary evaporation and subsequent drying at 1 torr and 40°C overnight. A weight for each fraction was then obtained. The weight distributions of each fraction are given in Table II; while, the data expressed on a percent of sample basis are given in Table III. In some cases (samples 16, 18 and 1) mass balances were high due to the fact that several fractions retained residual solvent even after vacuum drying. It should also be noted that fraction 1 in certain specimens (samples 16 and 18) yielded a liquid material possessing the consistency of axle grease instead of a solid. This observation suggested that complete solvent

removal had not been achieved during the drying procedure. All other samples yielded essentially 100% recovery. The slightly low values probably reflect errors in weighing, losses in solvent removal or the fact that some material may be irreversibly bound to the column packing material. The large quantity of solvents used did not allow for a repeat of this experiment. Our feeling is that with the exception of those three samples which retained solvent, acceptable mass balance was achieved. Furthermore, these findings indicated that column activity and elution solvent strength were near perfect.

It may also be useful to consider these data in the following light. For those samples that exceed 100% recovery, we might assume that the excess solvent would elute as fraction #1 and if this fraction is not sufficiently large any additional solvent could elute as fraction #3. For those situations where less than 100% recovery was realized, the deficiency may be considered to be "very polar" material not removed from the column. This amount could logically be added to fraction #4. Following these guidelines Table IV was generated which puts things on a 100% of sample recovered basis. It may be significant that "nonpolar" are found in these THF soluble residues (e. g. > 20% for samples 8, 11, 16, and 18) when one would have thought all these components would have been eliminated after the 850+ F treatment. Their elution as "nonpolar" may reflect either sterically hindered "polars" or adducted (essentially neutralized) "polars". Alternatively, hydrocarbon cracking and occlusion may have happened during the 850+ F treatment, which upon dissolution become released.

Preparative Scale Fractionation of THF Resids

TASK II INFRARED SPECTROSCOPY OF AS-RECEIVED THF SOLUBLE RESIDS

Prior to preparatively separating each as-received sample, each of the 18 samples was examined by FT-IR employing a diffuse reflectance interface. Each sample was diluted with KCl, placed into a small cup and the contents were spectrometrically analyzed. While a cursory look at all the spectra (Figures 1-18) showed the same basic features, closer inspection reveal significant differences. Table V list some of the major diagnostic infrared absorbances and their molecular assignment. Each sample revealed major absorbances due to aliphatic and aromatic C-H linkages. The greatest variability was found in the O-H, N-H and C=O regions. Samples 1 and 2 were essentially identical with not only aliphatic ($\sim 2900\text{ cm}^{-1}$) and aromatic (3050 cm^{-1}) C-H but also signal mostly due to bonded O-H (3500 cm^{-1}). The broad but significant absorbance between

3400 cm^{-1} and 3200 cm^{-1} is difficult to assign but it is suggestive of amines (i.e. nitrogen containing). Bands at 1600 cm^{-1} and 700 cm^{-1} also suggest aromatic structures. Carbonylic material is obvious in both samples as evidenced by the shoulder near 1700 cm^{-1} . Samples 3 and 4 (Ohio 6 - Holmes Mine) exhibited no carbonyl absorbance but the phenolic, amine, aliphatic and aromatic portions appeared to be unchanged relative to fractions 1 and 2. Samples 5 and 6 (Ohio 6 - Crooksville Mine) contained a measurable amount of carbonyl as well as all the other previously mentioned features. Samples 7 and 8 (Illinois No. 6) contained an even greater relative amount of carbonyl but significantly less aromatic. The phenol region duplicated all previous spectra. Samples 9 and 10 (Pittsburgh) resembled the Ohio 6 - Holmes Mine samples; although, the relative amount of O-H and N-H may be less in the Pittsburgh case. There also appear to be weak absorbances indicating low levels of more than one type carbonyl. Samples 11, 12, 13, 15, 16, 17 and 18 appear identical to samples 7 and 8. Sample 14 on the other hand exhibited much less carbonyl and phenol which implies that the interstage separation removed heteroatom.

In summary, the need for fractionation is apparent since FT-IR via reflectance spectroscopy of the as-received samples can only detect gross changes. However, the quick, definitive detection of carbonylic material without fractionation could be useful on a process line. In addition, closer inspection of each infrared spectrum than was possible here may yield valuable information concerning the effects of various processing parameters such as the gross changes in phenol/carbonyl arising from the processing of Illinois No. 6 coal at Wilsonville with and without an interstage separation (Figures 13 and 14).

Preparative LC fractions 1-4 of samples 16 and 18 were also examined by diffuse reflectance FT-IR. The spectral differences between fractions suggested that a separation based upon chemical class occurred. For example with sample 16, fraction 1 (Figure 19) exhibited no O-H, N-H or C=O. In fraction 2 (Figure 20) some evidence for either bonded O-H or N-H was found (3400 cm^{-1}). The ratio of aromatic/aliphatic content was relatively unchanged between fractions 1 and 2. Some evidence for several carbonyl functionalities was observed. Fraction 3 (Figure 21) showed lots of carbonyl and considerably more bonded O-H and N-H. Surprisingly

no free O-H was in evidence. Fraction 4 (Figure 22) contains now two different, well resolved carbonyl stretches. The quality of the spectra was not as high for sample 18 but it was apparent that the trends from fractions 1 to 4 (Figures 23-26) were similar to the fractions of sample 16.

TASK III NORMAL PHASE LIQUID CHROMATOGRAPHY-FOURIER TRANSFORM INFRARED SPECTROMETRY OF THE SOLUBLE RESID FRACTIONS

The oxygen enriched and nitrogen enriched fractions of the samples preparatively separated in Task I were further separated by normal phase liquid chromatography (LC) with Fourier transform infrared spectrometric detection. A modification of the procedure reported earlier was adopted (Ind. Eng. Chem. Res., 26, 768 (1987)). The parameters employed are listed in Table VI, along with the conditions reported originally in 1987. Budgetary restrictions coupled with a large sample load precluded our duplication of what would have been more optimized conditions. Fractions 2 and 3 were selected in the belief that they were the oxygen enriched and nitrogen enriched fractions respectively. The sensitivity of the current method should have been increased five times over the previously reported method because a 1.0 mm path length flow cell was employed instead of a 0.2 mm. The column efficiency, however, was only 25% of the older method because column length was only 25 cm as opposed to originally 100 cm.. Infrared detector, data collection, and spectral resolution were comparable.

Each of the fractions studied for all eight resids gave a single broad, tailing peak in the Gram-Schmidt reconstruction (GSR). GSR is basically total infrared signal versus elution time. In certain cases the GSR peak exhibited an easily discernable shoulder (Figure 27 for example). No other features however were evident. Both fractions 2 and 3 in each sample showed basically early eluting non-aromatic material and late eluting aromatic components which contained a significant portion of aliphatic substitution. Three modes of data presentation were utilized and are provided in this report: (1) GSR's, (2) individual file spectra of components eluting from column and (3) contour plots derived from Fourier transformed data which give an overall impression of spectral information obtained in an LC/FT-IR run. These data presentations are shown for sample

18, fraction 2 in Figures 27-31. The contour plot gives the best overall picture of the chemical nature of all eluting species. Files 240-245 revealed elution of totally aliphatic components. Beginning around file 250 aromatics ($> 3000\text{ cm}^{-1}$) elute. Some phenols (3600 cm^{-1}) are suspected between files 265 and 270. All fraction 2's in general look strikingly similar. In retrospect, fraction 2 may contain very little oxygen as evidenced by the absence of O-H, carbonyl and ether vibrational modes in all spectra. This is surprising since previous studies had suggested fraction 2 (elution with hexane/ CHCl_3 (80/20)) would be oxygen enriched. Reflectance, DRIFT, spectra of samples 16 and 18 fraction 2 discussed earlier (Figures 20 and 24) gave detectable O-H but LC/FT-IR (e.g. solution phase) of these fractions showed no evidence of these functionalities. An explanation for this observation could be either (1) KCl powder used to dilute sample was wet, (2) O-H functionalities were below detection limit in the IR flow cell, (3) hydroxyl moieties are present in a later fraction, or (4) species are irreversibly absorbed to the chromatographic stationary phase (e.g. aminopropyl silica). Given our high chromatographic flow rates and rapid infrared data acquisition times, poor detection is most likely to be the reason. A closer examination of the contour plots for fraction 2 of certain samples, strongly hints of the presence of phenols, and maybe carbonyls. Consol #1 (Figure 32) while showing no phenols does give evidence of carbonyls ($1600\text{-}1800\text{ cm}^{-1}$). The only Wilsonville fraction #2 not showing some sign of phenols was Consol #3 (Ohio 6), Figure 33. Consol # 8, 9, 11 and 13 (Illinois No. 6, Pittsburgh, Wyodak) exhibited a small amount of phenol eluting at the maximum (highest concentration) of the GSR trace, Figures 34-37. The two HRI samples (Consol #16 and #18) afforded no hint of phenolics, Figures 28 and 38.

Fraction 3 was produced by next eluting the same samples with chloroform/acetonitrile (90/10). Each of these fractions was then further separated and detected via LC/FT-IR in a manner similar to fraction 2. A single broad peak (Figure 39) was observed again as with fraction 2. In some cases the peak exhibited a slight shoulder and in all cases the peak showed extensive tailing. Our failure to resolve the broad signal into several peaks was due to the fact that only a 25 cm column was used (Figure 40). Much greater variability was seen among all the samples

concerning this fraction. Surprisingly again few O-H or N-H stretching vibrational modes were seen in all fraction 3's. The aliphatic/aromatic ratio through the chromatographic (GSR) peak varied with the sample. The variety of carbonyl species also changed with the sample. In several cases clear evidence for the presence of ether functionalities was obtained.

Consol #1 exhibited clear evidence for the presence of carbonyls in files 276-280 (Figure 41). The absorbance frequency was near 1670 cm^{-1} which suggested a conjugated (e.g. aromatic) ketone. The bulk of fraction 3, however, appeared to be early eluting aliphatic with later eluting alkyl substituted aromatics. No hint of phenols could be detected. Consol #3 was even more void of functionality. Any presence of carbonyl would be highly speculative (Figure 42).

Consol # 8 was dramatically different from the previous samples, Figure 43. After an initial solely aliphatic eluate, aromatic and carbonyl character became apparent. No phenolics were again detected. Individual file spectra were more informative than the contour plot. For example, file 160 shows only aliphatics; while, file 170 indicates carbonyls of at least two types (1701 cm^{-1} and 1658 cm^{-1}), Figure 44. It is difficult to assign these signals to a specific type of carbonyl given the spectra-structure correlations in Table V, because our file spectra are taken in solution.. The data in Table V are for the solid (or neat) state. A library of infrared spectra obtained in solution should be compiled in order to make reliable assignments. Additionally, intramolecular interactions can also lead to significant spectral shifts. In contrast to Consol #3, carbonyls dominate the complete elution pattern of Consol #8 as evidenced by file spectra 195, Figure 45. A comparison of run 256 (Consol #3) with run 257 (Consol #8) each at Wilsonville is worthwhile. The presence of carbonyls in the latter may reflect the use of Illinois No. 6 coal as opposed to Ohio 6. The low carbonyl level in resid from Ohio 6 is unexpected since the coal was moderately oxidized when received at Wilsonville. The status of Illinois No. 6 coal is unclear. Alternatively, Ohio 6 was processed with Shell Catalyst; whereas Illinios No. 6 employed Amoco catalyst. These results suggest that the Amoco catalyst may not be as effective an hydrogenation catalyst. It should also be noted that the Ohio 6 was recycle stream but Illinois No. 6 was interstage stream.

Consol #9 (Pittsburgh) fraction 3 also shows no evidence of phenols throughout the chromatographic run. Intense absorbances are seen for both carbonyl (1700 cm^{-1}) and (for the first time) ether (1200 cm^{-1}) moieties, Figure 46. File 266 demonstrated the presence of a ketone at 1721 cm^{-1} , Figure 47, and two ethers at 1290 and 1278 cm^{-1} . The ethers have disappeared by file 280, but numerous carbonyls persist. The shoulder at 1647 cm^{-1} is probably not amide but conjugated (or unsaturated) carbonyls, Figure 48. Obviously Consol #8 and #3 differ in the source of feed coal, but both use Shell catalyst at essentially the same temperature, H_2 pressure and space velocity. Yet, the Pittsburgh coal yields a rich abundance of carbonyls; while Ohio 6 does not. Additional study is justified here.

Consol #11, (Wyodak) fraction 3 gave considerably less aromatic C-H stretching absorbance than any of the previous sample. This observation may indicate more condensed rings, Figure 49. The number of carbonyls appeared less as evidenced by file spectrum 265. Consol #13 (Illinois No. 6) appeared identical to Consol #13 (Figure 50). Even though Illinois No. 6 coal was used to generate Consol #8 and #13, the nature of the resids was quite different. The thermal/catalytic ITSL process appears to be more effective in treating carbonyls than the catalytic/catalytic ITSL scheme. Alternatively, if carbonyls come about from oxidation of liquefaction products, the additional catalytic stage employed for Consol #13 may more completely reduce the coal.

Consol #16 and #18 (HRI process) were strikingly similar even in the times when certain functionalities elute. Compare contour plots in Figures 51 and 52. Varied carbonyls are seen in file spectra 285 for example, Figure 53, in Consol #16. Similar observations hold for file 286 in Consol #18, Figure 54. A small band of ethers was also apparent in the LC/FT-IR of Consol #16 and #18. In conclusion more careful study of these data no doubt would bring out other significant findings, however, the six month time period and limited funding level did not allow for this effort.

TASK IV SUPERCRITICAL FLUID EXTRACTION SURVEY OF AS-RECEIVED THF SOLUBLE RESIDS

Background

All extractions were performed on the HP 7680A supercritical fluid extractor. This extractor (Figure 55) is capable of utilizing three extraction solvent tanks. After leaving the tanks the supercritical fluid enters a cryogenically cooled, dual head reciprocating pump. This pump is capable of pumping up to 4 mL/min of liquid CO₂ and of maintaining pressures in excess of 5000 psi. After leaving the pump, the extraction fluid can flow through a bypass or through the extraction vessel. The bypass is used to allow the instrument to reach supercritical fluid conditions prior to extraction. When set parameters are reached, supercritical fluid is passed through the extraction vessel. The supercritical fluid proceeds to the variable restrictor (nozzle), where supercritical conditions are maintained and flow and density are regulated. The supercritical fluid then passes out of the nozzle into the solid phase trap. The chamber and nozzle are thermally controlled with a temperature range of 40 to 80°C. The solid phase trap is commercially available in either stainless steel beads (100 µm) or C-18 (40 µm) particles. The trap can be cryogenically cooled to 5°C or heated to 80°C. Analytes are rinsed off the trap by solvents and deposited into a fractionator.

The state-of-the-art extractor described above currently provides one the best opportunity for performing analytical SFE (i.e. quantitative extraction, trapping and recovery). With certain analyte/matrix combinations (i.e. nonpolars and intermediate polars) the technique functions exceedingly well in an analytical fashion. For more polar material many times considerable extraction optimization is required. Such parameters as

- Type of fluid
- Density of fluid
- Temperature of fluid
- Mass of fluid
- Trapping medium
- Temperature of trap
- Rinse solvent

should be explored. In addition to these variables, there are three modes of extraction which should be considered..

- static mode
- dynamic mode
- static-dynamic mode

Several other factors are critical in developing a successful SFE experiment: (a) sample size to vessel size ratio, (b) sample particle size, (c) matrix alteration to enhance extractability, (d) method for determining extractability, etc. All parameters were carefully considered in carrying out the proposed work. The large sample load and limited time did not allow opportunity to fully optimize the extraction process. Certain protocol decisions had to be made given our experience in SFE and coal chemistry. Given the extremely large volumes of organic solvent consumed and disposed of in Tasks I and III, the SFE approach to fractionation is strongly justified.

All the extractions called for in Tasks IV (32) and VI (7) were performed in the order agreed to. Initially 100% CO₂ was used for extraction. Table VII describes the results of these studies. Densities of 0.3, 0.6 and 0.9 g/mL were employed. Pertinent extraction parameters which were used are listed below:

Thimble (extraction vessel) size:	1.5 mL
Sample mass:	~0.8 gm
Extraction temperature:	53°C
Volume of supercritical fluid used:	45 mL (30 thimble volumes)
Trapping material:	Stainless steel spheres (100 µm)
Trap temperature:	7°C
Trap rinse solvent:	THF (2 mL)
CO ₂ pressure :	200-400 atm (depending on density employed)

Since the solvating power of CO₂ increases with an increase in density, highest percent extraction would be expected for 0.9 g/mL. Furthermore, from the nature of the dynamic extraction and the pre-set requirement of always 30 thimble volumes, the time and mass of CO₂ used at 0.9 g/mL was also greater which served to make for a more complete extraction. See Table VII for mass-time-density for each of the three experimental protocols. Even though all extraction results were low (<10%), the anticipated trend was realized. Without further work on at least some of these

samples the absolute accuracy of these numbers could be questioned. For homogeneous samples, relative standard deviations should be 10% or less. It is also significant that these fractionations required less than an hour; whereas, conventional LC consumed at least two days for just the sample concentration step.

Percent extraction was measured by noting the weight of the sample plus the extraction vessel before and after extraction as opposed to weighing the dried extract which was rinsed from the stainless steel trap. Hindsight would suggest that both measurements would be necessary in order to establish clearly the mass balance and percent extraction. The basis for this statement is that all THF soluble resids initially gained weight during the dynamic extraction step even though it was obvious from the trap that some colored material had been solubilized. In other words, many resids expanded in volume during extraction because CO₂ was absorbed. The trap, however, contained extract as evidenced by the colored solution which resulted when the trap was rinsed. Over a three day period each extract residue steadily lost weight. Percent extraction was established after the (sample plus vessel) weight appeared to stabilize. Unfortunately, the sample plus vessel were never heated to determine if additional weight (CO₂) loss was possible. Obviously a greater weight loss would result in a greater percent extraction. Therefore, our percent extraction results may represent a lower limit. It should also be noted that in a few cases the system actually "overpressured" during the extraction which may have been prompted by a very large volume expansion of the THF soluble resid due to CO₂ absorption. In addition, several of the resids changed in physical appearance during extraction with 100% CO₂. All resids as-received were dark powders. Samples #10, #11 and #15 formed solid masses or developed a crust over the surface during extraction. Fusion of the powder may have adversely affected the extent of extraction. Less efficient mixing (or channeling) of the CO₂ fluid with these matrices seems highly probable with these samples. Smaller sample sizes or the use of an inert diluent in the matrix should be attempted to test this notion. Since most of the samples gave similar percent extraction, the time of extraction was probably insufficient for the sample size that was chosen.

Much smaller sample sizes, we feel would yield measureable differences in extractability between samples.

Dynamic extractions are characterized by continuous flow of the fluid through the matrix. If the kinetics of extraction are slow, the dynamic mode may not yield the greatest amount extracted especially when liquid CO₂ flow and supercritical fluid (0.9 g/mL) flow approximates 2 mL/min as was the case in these experiments. For this reason a combination static (fixed amount of fluid for 30 min) and dynamic (0.9 g/mL, 40.5 g, 21.9 min) extraction of sample #8 was performed. Surprisingly the percent extracted was only 2.8%; whereas, the dynamic (alone) extraction yielded 8.5%. It should be noted, however, that the residue from the static/dynamic mode required a much longer time to weight stabilize than the dynamic mode even though the former material had been heated at 100°C overnight (atmospheric pressure). Further work obviously is required to verify the absence of CO₂ in the extracted THF soluble resids. Thermogravimetry coupled with mass spectrometry of the extracted resid would provide needed answers.

It is customary in SFE to employ modified CO₂ when extraction yields are poor. Methanol, toluene and acetonitrile have been studied in conjunction with CO₂. Small portions of these polar compounds have been shown to markedly increase the fluid's solvating power. The samples studied and conditions employed are outlined in Task VIII. A comparison of Tables VII and VIII reveals several puzzling situations. For example, in several cases the percent extraction with modified CO₂ was less than with 100% CO₂ (e.g. Consol #7 and #8). Unfortunately, only four samples were extracted with 100% CO₂ at 0.9 g/mL where valid comparisons were possible. Only Consol #15 exhibited greater than 10% extraction. It is difficult to draw any conclusions from the relative effectiveness of various modifiers given such a limited study. Only Consol #8 was extracted with every fluid mixture. Since the percent modifier differed from one fluid to the next it would be risky to say with this sample that methanol is better than acetonitrile for example. Only with Consol #8 can toluene and acetonitrile be compared. In this case, both seem comparable, however, one is unable to tell if the same components were extracted without spectrometric analysis of each extract. Furthermore, trapping efficiency of the stainless steel beads

may be quite different with one modifier versus the next. The trap could only be cooled to 5°C and different liquid modifier would probably coat the beads thereby altering the trapping efficiency and trap chemistry.

Dynamic type extractions with modifier were performed in all cases. CO₂ density was 0.9 g/mL, time was 21.9 min, mass of CO₂ was 40.5 g and 1-4% modifier was introduced to the fluid prior to the extraction (Scott Specialty Gases). Trapping and recovery steps were unchanged from the 100% CO₂ extractions. Percent extraction was determined in the same manner as previously but 4-5 days were required to obtain a stable weight of the non-extracted portion. This weighing operation was made more problematical because the samples became hygroscopic after extraction such that weight actually began to increase rather than decrease after 5 days standing in the air.

Some workers have discovered with certain samples that it is more advantageous to place modifier in the matrix rather than in the fluid. In order to determine if this would be beneficial with THF soluble resids sample #8 (0.915 g) was spiked with 100 µL of methanol. A traditional dynamic extraction was next performed. The results were DISASTEROUS! The sample was apparently too large for our commercial system. The system over-pressured because of matrix expansion. Leaks developed because seals ruptured. Extracted material deposited throughout the plumbing of the extraction device. Certainly it would be most interesting to redo this experiment with a much smaller sample. In summary, the usefulness of modifiers in the extraction of THF soluble resids is certainly advantageous. Percent extractions increased 400-500% on the average where comparisons could be made. If given sufficient time to optimize all extraction parameters, considerably higher extractions would result. Certainly a combination of SFE and LC could result in reduced organic solvent usage. Clearly much additional work should be carried-out in order to establish the potential of SFE for coal liquids analysis. The study reported here provides encouragement that success can be achieved.

TASK V: NORMAL PHASE LIQUID CHROMATOGRAPHY/FOURIER TRANSFORM INFRARED SPECTROMETRY OF SUPERCRITICAL FLUID EXTRACTS

Due to the small amount of extractable materials recovered in Task IV, activities outlined in Task V were impossible to perform. The difficulty stemmed from a mismatch in chromatograph scale. We were set-up to perform LC/FT-IR with analytical scale (4.6 mm i.d.) columns. The mass recovered for many fractions in Task IV was very low (i.e. under 10 mg) and would preclude further analytical scale work in this regard. The use of smaller diameter columns (e.g. microbore (1.0 mm, i.d.) and packed capillary) appears quite feasible with micro-flow cells and FT-IR detection; however, additional funding would have been required. Alternatively, larger scale SFE could be carried-out with greater trapping capacity in order to obtain sufficient sample for analytical scale LC/FT-IR.

TASK VI: SUPERCRITICAL FLUID EXTRACTION OF THF SOLUBLE RESIDS UNDER "BEST" CONDITIONS

Task VI called for the "best" conditions which we interpreted to mean the greatest percent extraction. As best we could judge with the limited data available, 4% methanol/96% CO₂ afforded in general the "best" conditions. Identical extraction conditions were employed in the dynamic mode on a new set of THF soluble coal resid samples. Unfortunately, the resids chosen for this aspect of the project (Table IX) did not yield as high percent extraction as most of those listed in Table VIII and re-stated in Table IX for comparison. It is not clear why the samples chosen for this task gave lower results. In retrospect, inspection of the mass of extractable (trapped) material in this case might have been a better procedure than attempting to weigh the residue after extraction since we believe the resid retained CO₂ even after drying. As has been stated previously, development work is needed in the application of analytical SFE to coal derived products. The study reported here does not adequately reflect the potential of this method. From an environmental point of view, the Department of Energy will need to seek options to the use of

organic solvents for the routine coal liquefaction analyses required for support of coal conversion processes. CO₂-based supercritical fluids may afford this option.

TABLE I

<u>Ref. No.</u>	<u>Coal Feed</u>	<u>Source/Conditions</u>	<u>Comments</u>
1	Wyodak	Lummus; 3LCF10; P 0110F+0111F	Feed to LCF
2	Wyodak	Lummus; 3LCF10; P 0128F+0202F	Feed to LCF
3	Ohio 6 (H)	W; 256 B; C/C	Recycle Stream
4	Ohio 6 (H)	W; 256 B; C/C	Interstage Stream
5	Ohio 6 (C)	W; 256 E; C/C	Recycle Stream
6	Ohio 6 (C)	W; 256 E; C/C	Interstage Stream
7	Illinois No. 6	W; 257; C/C	Recycle Stream
8	Illinois No. 6	W; 257; C/C	Interstage Stream
9	Pittsburgh	W; 259; C/C	Recycle Stream
10	Pittsburgh	W; 259; C/C	Interstage Stream
11	Wyodak	W; 251-III; C/C	Recycle Stream
12	Wyodak	W; 251-III; C/C	Interstage Stream
13	Illinois No. 6	W; 250; T/C	Recycle Stream
14	Illinois No. 6	W; 250; T/C	Interstage Stream
15	Black Thunder	HRI; CC-2 (227-57)	First Stage; FL
16	Black Thunder	HRI; CC-2 (227-57)	PFL
17	Black Thunder	HRI; CC-5 (227-62)	First Stage; FL
18	Black Thunder	HRI; CC-5 (227-62)	PFL

Notes: T/C = thermal/catalytic; C/C = catalytic/catalytic; PFL = pressure filter liquid; P = period; W = Wilsonville; (H) = Holmes Mine; (C) = Crooksville Mine; LCF = LC-Fining Pilot Plant; FL= Filter Liquid;

- o Samples 1-18 are THF soluble portions of the distillation resid.

TABLE II

Fractional Weight (gms) Distribution
THF Soluble Resids

<u>Sample</u>	<u>Weight Fractionated</u>	<u>F1 Nonpolars</u>	<u>F2 Intermediate Polars</u>	<u>F3 Polars</u>	<u>F4 Very Polars</u>	<u>Weight Recovered</u>
1	4.4952	0.0971	0.9398	3.5645	0.8219	5.4233
3	4.9833	-	0.9694	2.2345	1.8161	5.0200
8	4.8515	1.0097	0.8346	1.8384	0.8072	4.4899
9	5.0085	0.3928	1.4778	2.3143	0.6283	4.7132
11	5.0782	1.3878	0.8927	2.3617	0.2687	4.9109
13	4.9995	0.7407	1.1622	2.2790	0.5990	4.7809
16	5.0259	2.6475	0.8082	1.6414	0.2509	5.3480
18	4.9771	1.8633	1.0823	2.2880	0.2873	5.5209

TABLE III

SAMPLE	#	Percent By Weight				
		F1	F2	F3	F4	Total
Lummas 3LCF10 Feed to LCF	1	2.2	20.9	79.3	18.3	120.6
Wilsonville Run 256B Recycle	3	---	19.5	44.8	36.4	100.7
Wilsonville Run 257 Interstage	8	20.8	17.2	37.9	16.6	92.5
Wilsonville Run 259 Recycle	9	7.8	29.5	46.2	12.5	94.1
Wilsonville Run 251-III Recycle	11	27.3	17.6	46.5	5.3	96.7
Wilsonville Run 250 Recycle	13	14.8	23.2	45.6	12.0	95.6
HRI Run CC-2 PFL	16	52.7	16.1	32.7	4.9	106.4
HRI Run CC-5 PFL	18	37.4	21.7	46.0	5.8	110.9

TABLE IV

Percent By Weight						
SAMPLE	#	F1	F2	F3	F4	Total
Lummus 3LCF10 Feed to LCF	1	---	20.9	60.9	18.3	100.0
Wilsonville Run 256B Recycle	3	---	19.5	44.1	36.4	100.0
Wilsonville Run 257 Interstage	8	20.8	17.2	37.9	24.1	100.0
Wilsonville Run 259 Recycle	9	7.8	29.5	46.2	18.4	100.0
Wilsonville Run 251-III Recycle	11	27.3	17.6	46.5	8.6	100.0
Wilsonville Run 250 Recycle	13	14.8	23.2	45.6	16.4	100.0
HRI Run CC-2 PFL	16	46.3	16.1	32.7	4.9	100.0
HRI Run CC-5 PFL	18	26.5	21.7	46.0	5.8	100.0

TABLE V

Diagnostic Frequencies (cm^{-1}) of Molecular Fragments

Hydrocarbon

Methyl C-H STR. 2962 (as) 2872 (s)

Methylene C-H STR 2926 (as), 2853 (s)

Aromatic C-H STR. 3030

Hydroxyl

Alcohol	O-H STR. (Non bonded)	3630 (Sharp)
---------	-----------------------	--------------

Alcohol	O-H STR (Bonded)	3500 (Broad)
---------	------------------	--------------

Alcohol	C-O STR	1050
---------	---------	------

Phenol	O-H STR (Non Bonded)	3610 (Sharp)
--------	----------------------	--------------

Phenol	O-H STR (Bonded)	3500 (Broad)
--------	------------------	--------------

Phenol	C-O STR	1230
--------	---------	------

Carbonyl

Anhydride	1820
-----------	------

Acid	1760
------	------

Ester	1735
-------	------

Aldehyde	1725
----------	------

Ketone	1715
--------	------

Amine	1690
-------	------

TABLE VI

Parameters	Original Procedure	Procedure Used Here
Column Dimensions	2X (50 cm x 1.0 mm i.d.)	25 cm x 2 mm, i.d.
Stationary Phase	Aminopropyl Silica, 5 μ m	Aminopropyl silica, 5 μ m
Mobile Phase	70/30 v/v, CDCl ₃ /CCl ₄ + 0.02% Et ₃ N	Same
Flow Rate	50 μ L/min	150 μ L/min
Volume Injected	-	5 μ L (250 μ g)
Path Length	0.2 mm parallel plate	1.0 mm cylindrical
Flow Cell Volume	~3.2 μ L	~10 μ L
FTIR Resolution	4 cm ⁻¹	4 cm ⁻¹
Scans/Seg./File	12	10

Table VII
PERCENT EXTRACTION* WITH PURE CO₂

<u>SAMPLE</u>	Mass-Time-Density of CO ₂		
	(13.5g) (7.3 min) <u>0.3 g/mL</u>	(27.0 g) (14.6 min) <u>0.6 g/mL</u>	(40.5 g) (21.9 min) <u>0.9 g/mL</u>
7	-	-	8.2
8	0.7	7.6	8.5
10	0.3	0.4	-
11	-	-	8.4
12	0.7	7.2	7.8
15	0.5	-	-
17	-	7.4	-

*Determined by noting weight of resid before and after extraction. Sample equilibrated in air at atmospheric pressure after extraction for three days in order to achieve constant weight. Samples 10, 11 and 15 before extraction were powders but after extraction each developed into a solid mass which was difficult to remove from the extraction thimble.

TABLE VIII
PERCENT EXTRACTION WITH MODIFIED CO₂*
Modifier Employed (w/w)

<u>Sample</u>	<u>1% MeOH</u>	<u>4% MeOH</u>	<u>2% Toluene</u>	<u>2% ACN</u>
1	**	-	5.8	-
3	0.2	0.2	-	-
7	0.9	5.4	-	-
8	5.9	8.8	4.8	4.7
9	-	1.6	0.8	-
11	-	4.9	**	**
13	-	5.5	-	4.3
15	-	15.4	-	5.5

*CO₂ density = 0.9 g/mL

**Weight after extraction not obtained.

TABLE IX
PERCENT EXTRACTION FOR "BEST" CONDITIONS

<u>Sample (Task IV)</u>	<u>Sample (Task VI)</u>	<u>Percent Extraction</u>
---	2	0.7
3	---	0.2
---	4	0.5
---	5	0.4
---	6	1.6
7	---	5.4
8	---	8.8
9	---	1.6
11	---	4.9
13	---	5.5
---	14	0.8
15	---	15.4
---	16	0.8
---	18	0.7

*0.9 g/mL CO₂ (96%)/Methanol (4%)

Figure 1

Figure 2

Figure 3

WILSONVILLE 256B R-1236 RESID THF SOL

Figure 4

Figure

WILSONVILLE 256 E R-1235 RESID COMPOSITE

Figure 6

Figure 7

Figure 8

WILSONVILLE 259 V-131B RESID COMPOSITE

Figure 9

Figure 10

Figure 11

Figure 12

Figure 13

Figure 14

Figure 15

Figure 16

Figure 17

Figure 18

Figure 19

Figure 20

Figure 21

Figure 22

Figure 23

Figure 24

Figure 25

Figure 26

GSR OF CONSOL #18, FRACTION #2

Figure 27

CONSOL # 18 FRACTION # 2

Figure 28

Figure 29

Figure 30

CONSOL #1 FRACTION #2

Figure 32

CONSOL # 3 FRACTION#2

Figure 33

CONSOL #8 FRACTION #2

Figure 34

CONSOL #9 FRACTION #2

Figure 35

CONSOL # 11 FRACTION # 2

Figure 36

CONSOL #13 FRACTION #2

Figure 37

CONSOL # 16 FRACTION #2

Figure 38

CSR OF CONSOL #8, FRACTION #3

Figure 39

GSR OF CONSOL #9, FRACTION #3

Figure 40

Figure 41

CONSOL # 3 FRACTION # 3

Figure 42

CONSOL #8 FRACTION # 3

Figure 43

Figure 44

Figure 45

Figure 46

CONSOL # 9 FRACTION # 3

Figure 47

Figure 48

CONSOL # 11 FRACTION # 3

Figure 49

Figure 50

Figure 51

CONSOL # 16 FRACTION # 3

CONSOL # 18 FRACTION # 3

Figure 52

Figure 53

Figure 54

Figure 55

END DATE
8-10-92