DOE/PC/79743--T7

MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS FROM COAL FLAMES

DOE/PC/79743--T7

DE92 013724

Quarterly Technical Progress Report No. 8
Reporting Period: July 1, 1989 - September 30, 1989

Prepared for:

U. S. Department of Energy
Pittsburgh Energy Technology Center

Under:

Contract No. DE-AC22-87PC79743

Prepared by:

G. H. Newton
C. Schieber
R. G. Socha
W. D. Clark
J. C. Kramlich

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718-2798

October, 1989

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Section	Page
ABSTRACT.	iii
1.0 INTRODUCTION.	1
2.0 EXPERIMENTAL PROGRAM.	3
3.0 ENGINEERING ANALYSIS.	26
4.0 FUTURE WORK	33
APPENDICES	

ABSTRACT

During this reporting period the global experiments were concluded. The final activities under these experiments involved measuring mineral content of coals as a function of coal particle size. The principal activities during this quarter involved the mechanistic experiments. Three baseline coals were cleaned and two of these sized. The ash from these various cuts were sampled from a bench scale reactor. The ash size distributions were compared to distributions predicted by the breakup model.

1.0 INTRODUCTION

The overall objectives of this project are to provide a basic understanding of the principal processes that govern fine particulate formation in pulverized coal flames. This understanding is to be used to develop a model (or models) which will predict the yield and size distribution of fine particulate matter as a function of coal type, coal processing, and combustion conditions. The goal of the model is to provide an engineering tool that will enable the practitioner to estimate the consequences of design decisions and fuel selection on the fine particulate yield. The practitioner can then make rational decisions regarding the required technology and costs associated with effluent cleanup while still in the design phase.

Long term work is presently supported by PETC that will develop detailed models of the entire mineral transformation process. The present work is directed toward global models of behavior which will become available on a shorter time frame and will be immediately usable in engineering activities.

Particles in the 0.5-10.0 μm size band are of interest for several reasons. First, a considerable portion of the fly ash generated in pulverized coal combustion falls within this size range. Particulate control devices, in particular electrostatic precipitators, are at their least efficient in this size band. Also, particles in this size range are most efficiently collected within the alveolar passages of the human lung. In coal combustion, a considerable portion of the heavy, toxic metals are vaporized within the flame. As the furnace gases cool, these metals will condense on the available surface area. Since most of the surface area is present on the smaller particles, they will become enriched in these toxic metals. Thus, those particles that are deposited in the alveoli may be coated with toxic compounds and create a health hazard that is well beyond the toxic material proportion in the original mineral matter.

Finally, the mechanism by which this fine fly ash is formed is not yet clear. Obviously, predicting the yield will require some definition of the dominant mechanisms. Also, the manner in which these mechanisms respond to

differing coal types and combustion conditions will have to be understood to make predictions. The project objective is being accomplished through a combination of literature research, experimentation, and model development activities. The program tasks include:

Task 1. Literature review and program plan.

Task 2. Engineering analysis.

Task 3. Experimental program.

Task 4. Reporting.

Task 1 has been completed. This report describes work performed under Tasks 2 and 3 during the period from July 1, 1989 through September 31, 1989. The principal activity during this period involved mechanistic experiments. Three baseline coals were cleaned and sized. Ash from these cuts were sampled from the Isothermal Reactor (ITR). The ash size distributions were compared to distributions predicted by the breakup model.

2.0 EXPERIMENTAL PROGRAM

The experimental portion of this project consists of a study of the fundamental mechanisms at laboratory scale, followed by a process simulation study conducted at the bench-scale. The experimental program was divided into two phases:

- Global experiments which are designed to determine the influence of global parameters such as coal type and combustion parameters on the yield of fine particulate matter. This task is complete.
- Mechanistic experiments which focus on providing a quantitative evaluation of the influence of various mechanisms which have the potential for contributing to the formation of fine particulate matter.

Testing is performed in the Isothermal Reactor (ITR) which is illustrated in Figure 2-1. The ITR consists of a 10 cm diameter ceramic tube mounted in a three-zone electric furnace. The high temperature gas flow is supplied by a gas flame fired in the side chamber at the top of the reactor. The furnace is capable of operating at temperatures up to 1500°C.

Coal size distributions were measured by pneumatically spraying the coal in front of a Malvern 2600 HSD laser diffraction particle size analyzer. Ash size distributions were measured by collecting the ash in a cascade impactor.

2.1 Global Experiments

A final set of experiments were conducted to conclude the global experiments. Analysis of ash particle size distributions by the break up model (reported in an earlier quarterly) had suggested that mineral content may vary as a function of particle size in some of the coals. These coals were sieved into different size cuts and the different size cuts analyzed for mineral content (Figures 2-2 through 2-4). Of the six coals sieved, three had mineral contents which varied significantly with particle size (the Illinois, the 62% Illinois/38%

Figure 2-1. The Isothermal Reactor.

Figure 2-2. Mineral content as a function of coal particle size.

Figure 2-3. Mineral content as a function of coal particle size.

Figure 2-4. Mineral content as a function of coal particle size.

Kentucky blend, and the Australian Bituminous #3) and three which did not (the Australian Bituminous #1, and the two lower rank coals, the Eagle Butte subbituminous and the Beulah lignite). This lack of dependence of mineral content on particle size had been expected for the Beulah lignite since previous work had indicated that the bulk of mineral in this coal were atomically dispersed in the coal.

Ash size distributions of several coals were also taken with the cascade impactor. The ash size distributions are shown in Figure 2-5.

2.2 Mechanistic Experiments - Cleaned Cuts

The mechanistic experiments involve cleaning and sizing three baseline coals (Utah, Beulah, and Illinois) and subsequently measuring the particle size distribution of ash from these various cuts. Cleaning was done by a froth floatation process by Hazen, CO, in four stages which resulted in five cuts. Results of the cleaning process are illustrated in Table 2-1 and the process itself is illustrated in Figure 2-6 for the Illinois coal. Particle size distributions of the cleaned coals are given in Appendix A. Also shown in Figure 2-6 is how 100 g of the original coal and its associated mineral matter were distributed between the cuts. The majority of the coal is deposited in the Third Cleaner Concentrate which had 55% of the mineral content of the original coal. The other four cuts represent relatively small fractions of the original coal mass and were highly enriched in minerals. The cumulative size distributions of ash sampled when each of these cuts were fired in the ITR are plotted in Figure 2-7.

The Rougher Cut produced the coarsest ash while all of the other cuts yielded substantially more material under 1 μm than the raw coal. Overall, however, the various cleaning cuts yielded less fine particulate matter under 5 μm than the raw coal. This would not be expected if the ash size distribution of the whole coal were simply the weighted sum of the various cleaned cuts.

Figure 2-5. Ash size distributions of raw coals.

Figure 2-6. Illustration of the application of the physical coal cleaning process to the Illinois coal.

Figure 2-7. Cumulative size distributions for ash from the firing of the various cleaning cuts. Data obtained with a cascade impactor.

Table 2-1. Results from Coal Cleaning.

	% Wt. (AR)	% Ash Content (Dry Basis)	MMD (μm)
Utah Coal	100	6.53	38
First Process:			
Rougher Tail	5.41	47.66	N/A
1 st Cleaner Tail	14.87	13.26	100
2 nd Cleaner Tail	1.38	11.36	65
2 nd Cleaner Conc.	78.53	2.59	30
Second Process:			
Rougher Tail	32.45	12.66	85
1 st Cleaner Tail	5.81	9.11	45
2 nd Cleaner Tail	1.13	6.24	100
2 nd Cleaner Conc.	60.64	2.41	30
Beulah Coal	100	14.64	42
First Process:			
Rougher Tailing	50.77	14.94	70
Rougher Concentrate	49.23	13.40	45
Second Process:			
Rougher Tail	73.19	14.94	65
1 st Cleaner Tail	17.42	13.44	80
2 nd Cleaner Tail	3.55	13.58	50
2 nd Cleaner Conc.	5.84	11.49	25
Illinois Coal	100	12.28	29
Rougher Tail	4.1	61.0	18
1 st Cleaner Tail	2.5	61.0	22
2 nd Cleaner Tail	0.8	50.0	N/A
3 rd Cleaner Tail	14.0	16.0	80
3 rd Cleaner Conc.	78.6	6.6	29

To determine if this were true, the ash size distributions of the cleaned cuts were averaged and compared to the ash output of the original coal. Shown in Figure 2-8, the cleaned cuts produced a greater fraction of fine particulate matter under $1\text{ }\mu\text{m}$ than did the raw coal but overall produced a smaller fraction of their ash under $5\text{ }\mu\text{m}$ than the raw coal. This suggests that the organically bound or included mineral matter is the source of the fine ash particles under $1\text{ }\mu\text{m}$. It also suggests that the presence of the extraneous ash may suppress the formation of fine particulate matter under $1\text{ }\mu\text{m}$. This type of behavior was also observed for the cleaned Utah coal. In Figure 2-9 the cleaned Utah coal had significantly higher levels of fine particulate matter under $1\text{ }\mu\text{m}$.

The weighted sum of the cleaned cut's ash size distributions are compared to the distribution of ash from the original whole coal in Figure 2-10. Cleaning of the coal caused an increase in the quantity of ash under $1\text{ }\mu\text{m}$ and a decrease in ash between 1 and $4\text{ }\mu\text{m}$. The presence of the extraneous mineral matter in the whole coal appears to reduce the yield of fine particulate matter under $1\text{ }\mu\text{m}$. This is not likely to result from in-flame collisions since the probability of such events is low. It is possible, however, that the extraneous mineral matter and the organic rich coal particles could come in contact during grinding and in the feeder and remain in contact when they enter the reactor. As the extraneous ash melts on the char surface, the fine particulate matter released as the char is consumed may become attached to the large extraneous ash melt. Removal of the extraneous mineral matter by cleaning the coal prevents this type of interaction from occurring and fine particulate matter is released.

To determine if this could provide a possible means of reducing the yield of fine particulate matter, 1 part rougher tails from the Utah coal were mixed with 9 parts of the Beulah raw coal. The resulting ash size distribution is compared against ash size distributions of the Beulah raw coal and the rougher tails in Figure 2-11. Although below approximately $0.5\text{ }\mu\text{m}$ the amount of fine particulate matter was cut in half, the decrease in fine particulate matter was not as great as observed for the Utah coal in Figure 2-9. This may indicate that the "casual" contact between extraneous mineral matter in the rougher tails and the extraneous mineral matter free Beulah coal particles in the feeder is

Figure 2-8. Quantitative comparison of ash size distributions from the original Illinois coal, and the sum the ash from the cuts.

Figure 2-9. Cumulative size distributions for ash from whole and cleaned coal.

Figure 2-10. Ash size distributions normalized to the mineral content of the original coal for the Illinois original coal, the Rougher Cut, and the Third Cleaner Concentrate.

Figure 2-11. Ash size distributions of ashes.

not sufficient to ensure that they remain in contact after entering the reactor. It may be necessary for the extraneous mineral matter particles to become imbedded in the surface of the Beulah coal particles to ensure that they remain in contact upon entering the reactor. Grinding the Beulah coal in the presence of extraneous mineral matter may provide this necessary amount of contact.

Overall, cleaning the coal resulted in a reduction of the amount of fine particulate matter on an absolute mass basis. Figures 2-12 and 2-13 are plots of the mass of ash produced from 100 g raw and cleaned coal as a function of particle size. The lower fraction of ash under 5 μm and the lower overall ash content of the cleaned coals substantially reduces the amount of fine particulate matter produced by the cleaned coals.

2.3 Mechanistic Experiments - Sized Cuts

This set of experiments involved separating both the raw and cleaned coals into different size cuts and measuring the resultant ash size distributions. This was done for the raw Utah and Illinois coals and the cleaned Utah and Illinois coals. These coals were sized into -18 μm , +18 -37 μm , +37 -85 μm , and +85 μm size cuts by an air classification technique. Proximate analysis results are given in Table 2-2 and mass mean diameters of the size cuts are given in Table 2-3. Particle size distributions of these coal size cuts, which did not vary significantly, are given in Appendix B. Ash content of the sized coals did not vary except for the Illinois raw coal.

Particle size distributions of the ash from these coals are given in Figure 2-14 through 2-17. At the largest size measured in the cascade impactor, 6 μm , the fraction of ash smaller than this size decreased as the size of the size cut increased for all four sets of coals. This is in agreement with the basis of the breakup model which states that the size of the ash particles is dependent on the size of the parent coal particles.

Figure 2-12. Ash size distributions of raw and cleaned coal.

Figure 2-13. Ash size distributions of raw and cleaned coal.

Table 2-2. Proximate Analysis Results
(As Received)

	% Moisture	% Ash	% Volatile
Utah Raw Coal			
-18	3.30	7.69	40.14
+18-37	3.67	4.87	41.26
+37-85	3.72	6.36	41.25
+85	3.50	5.52	41.99
Utah Cleaned Coal			
-18	3.19	2.34	41.29
+18-37	3.74	2.18	40.64
+37-85	3.27	2.38	41.26
+85	3.08	2.93	40.20
Illinois Raw Coal			
-18	3.46	17.09	31.90
+18-37	3.63	10.40	35.21
+37-85	3.98	9.91	35.30
+85	3.78	8.86	35.62
Ill. Cleaned Coal			
-18	3.88	7.17	35.23
+18-37	4.38	6.38	37.53
+37-85	6.47	5.89	34.94
+85	5.26	5.42	35.35

Table 2-3. Mass Mean Diameters of Size Cuts

Coal	-18	+18-37	+37-85	+85
Utah Raw Coal	16	30	60	140
Utah Cleaned Coal	17	32	55	133
Illinois Raw Coal	13	30	60	143
Illinois Cleaned Coal	16	28	62	132

Figure 2-14. Ash size distributions of sized coal.

Figure 2-15. Ash size distributions of sized coal.

Figure 2-16. Ash size distributions of sized coal.

Figure 2-17. Ash size distributions of sized coal.

3.0 ENGINEERING ANALYSIS

Analysis of the data was performed with the breakup model. According to the breakup model, the ash size distribution is related to the coal size distribution by:

$$f_a(d) = R_c(d) \cdot f_c(d)$$

where $R_c(d)$ is the ratio of the diameter of the ash particle to the diameter of the parent coal particle. If $R_c(d)$ is assumed to be constant as a function of coal particle size, it is given by:

$$R_c = \left[\frac{x_a / \rho_a^n}{x_m / \rho_m + x_w / \rho_w + (1 - x_m - x_w) / \rho_o} \right]^{1/3}$$

where: x = mass fraction in coal;
 ρ = density;
 n = number of ash particles resulting from a single coal particle;

and the subscripts refer to:

a = ash;
 m = mineral matter in coal;
 w = water; and
 o = organic phase in coal.

The procedure for finding the breakup number, n , is illustrated in Figure 3-1. The line labeled breakup number 1 is the distribution which would be expected if one ash particle was produced by one coal particle. This breakup number, however, produces a distribution which is larger than the measured distribution of this ash. The breakup number was then adjusted until the predicted mass mean diameter matched the measured mass mean diameter (approximately 80 μm for this ash) which yielded a breakup number of five.

Figure 3-1. Illustration of how the breakup number is found.

The breakup model was compared against the measured ash size distributions of the sized Utah and Illinois coals. This was done only for the -18 μm size cuts as model predictions obtained using the larger coal size cuts (+18-35, +35-85, and +85 μm) would not extend down into the under 10 μm ash sizes without using unreasonable breakup numbers. The model predictions for the -18 μm size cuts are compared against the measured ash size distributions in Figures 3-2 through 3-5. The model under predicts the amount of ash in the 0.2 to 6 μm size range using a breakup number of one. Although using a greater breakup number would allow the model to fit the data in these plots, this would not be realistic since the predicted and measured distributions should have approximately equal mass mean diameters.

Figure 3-2. Comparison of ash size distributions and breakup model predictions.

Figure 3-3. Comparison of ash size distributions and breakup model predictions.

Figure 3-4. Comparison of ash size distributions and breakup model predictions.

Figure 3-5. Comparison of ash size distributions and breakup model predictions.

4.0 FUTURE WORK

During the next reporting period experiments will focus on the influence of grinding on the formation of fine particulate matter. The data obtained to date indicates that the finer the grind is, the smaller the ash will be. Development of a model which will be able to predict the size distribution in the 0.5 to 10 μm size range will begin during the next reporting period. Modifications to the model which will allow it to more accurately predict ash size distributions in this size range may include assigning a size distribution to each size bin in the coal size distribution and considering the size of mineral matter imbedded in the coal particles (as opposed to mineral matter which is atomically dispersed in the coal).

Appendix A
Particle Size Distributions of Cleaned Coals

Appendix B
Particle Size Distribution of Sized Coals

END

**DATE
FILMED**

8 / 11 / 92