WSRC-TR-92-500

PRELIMINARY REMEDIAL ACTION OBJECTIVES FOR THE TANK 16 GROUNDWATER OPERABLE UNIT (U)

by W. C. Miles, Jr.

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

WSRC-TR--92-500

DE93 008502

Other Authors:

RECEIVED
MAR 01 1993
DOTI

MASTER

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

WSRC-TR-92-500

PRELIMINARY REMEDIAL ACTION OBJECTIVES

FOR THE

TANK 16 GROUNDWATER OPERABLE UNIT (U)

Unclassified

Author: W. C Miles, Jr.
Environmental Restoration Department

M. A. Elora 11/16/92
Authorized Derivative Classifier (ADC) / Date

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29803

Prepared for the U.S. Department of Energy under Contract No. De-AC09-89R18035

**PRELIMINARY REMEDIAL ACTION OBJECTIVES
FOR THE TANK 16
GROUNDWATER OPERABLE UNIT**

**Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29803**

Table of Contents

List of Tables	3
List of Figures	3
Executive Summary	4
1.0 Purpose	5
2.0 Introduction	5
3.0 Media of Concern	7
4.0 Chemicals of Concern	11
5.0 Future Land Use	17
6.0 Applicable Or Relevant And Appropriate Requirements (ARARs)	22
7.0 Exposure Pathways	24
8.0 Preliminary Remedial Action Objectives	26
9.0 Preliminary General Response Actions	27
10.0 Remedial Technology Types	28
11.0 References	29

List of Tables

3.1	Tank 16 Radiochemical Content.....	9
4.1	Chemical Composition Of H-Area High Activity Waste (aged ~10 years)	12
4.2	Physical Properties Of Aged Waste (aged ~10 years)	12
4.3	Low Concentration Nonradioactive Constituents Of H-Area Supernate	13
4.4	Radioactive Constituents Of H-Area Supernatant	13
4.5	Tank 16 Sample Analysis	14
4.6	Estimated Quantity Of Material Released From Tank 16	16
6.1.1	PDWS for the Tank 16 Primary Chemicals of Concern	22
6.1.2	General Radionuclide Contaminant MCLs	22
6.4.1	Maximum Permissible Concentrations In Air And Water For Occupational Exposures Of Radionuclides ($\mu\text{Ci/ml}$)	23

List of Figures

2.1	Section Through Waste Storage Tank 16	6
3.1	Local Groundwater Water Table Contour Map	10
5.1	Map Of The Savannah River Site	18
5.2	H-Area Location Map	19
5.3	H-Area Tank Farm	20
5.4	Tank 16 Features	21

EXECUTIVE SUMMARY

Tank 16 is a High Level Radioactive Waste tank in the H-Area Tank Farm on the Savannah River Site that was placed into service in May 1959. A leak was detected in one of the construction weld joints while the tank was being filled. Before jet evacuation of the tank waste was completed, the leak overflowed the annulus pan and an estimated 16 to 700 gallons of waste escaped to the environment (soil and groundwater) over a six hour period contaminating approximately 1,600 - 70,000 cubic feet of soil with up to 5000 curies of activity (principally Cs¹³⁷). The Tank 16 bottom is constructed below the groundwater table which resulted in almost immediate contamination of that medium. Low groundwater flow rates, the ion exchange property of adjacent soils, and the distance to the nearest surface water bodies (1,500 to 8,000 feet) indicates that surface water and sediment outcrop of contaminants may be expected between 44 and 530 years (Poe et al., 1974).

The Tank 16 structure (tank primary, tank annulus, and interior process equipment) is contaminated with high and low heat waste. Waste removal from Tank 16 was initiated in 1972 as a result of additional leakage. Only residual wastes, 75 gallons of water-insoluble waste containing 56,000 curies of activity in the tank primary (principally Sr⁹⁰) and approximately 22,000 pounds of waste containing 30,000 curies of activity remain in the tank annulus (principally Cs¹³⁷). Any liquids remaining at the time of waste removal have solidified leaving only solid wastes within the tank areas.

The H-Area Tank Farm is forecasted to remain operational for the next 30 years in support of the Separations Areas and the Defense Waste Processing Facility. Specific processes are planned for continued use in Savannah River Site support, such as; the In Tank Precipitation Facility, evaporators, and select tanks for feed and feed storage to the Defense Waste Processing Facility. Although decontamination and decommissioning activities may be initiated and completed over the next 30 years, government controlled access of the Savannah River Site is expected well beyond final closure.

The only applicable or relevant and appropriate requirements, ARARs, identified for the radionuclides ⁹⁰Sr and ¹³⁷Cs, which are the primary chemicals of concern, and the groundwater medium were chemical-specific maximum contaminant levels (MCLs) from the Primary Drinking Water Regulations. No location or action-specific ARARs have been initially identified. However, to be considered (TBCs) ARARs, dealing with occupational exposure of radionuclides for air and water were identified.

Exposure pathways and receptors identified are primarily associated with H-Area Tank Farm personnel contact with contaminated soils or groundwater during operational, maintenance, or potential decontamination and decommissioning activities. Potential exposure to the public and the environment is primarily limited to groundwater transport of contaminants.

Remedial action objectives consist of medium-specific and operable unit specific goals for protecting human health and the environment. These objectives are specific and do not limit the range of alternatives that may be developed. By development of these objectives prior to site characterization, remedial staff are provided long-term goals to use during analysis and selection of remedial technologies and alternatives resulting in a potential streamlining of the remedial alternative selection process. Goals for ingestion of groundwater and dermal exposure of groundwater to workers were developed.

A range of remedial technologies, which provides for treatment, containment, and removal requirements of contaminated media remaining at the Tank 16 groundwater operable unit, is identified and developed for each general response action.

1.0 **PURPOSE**

The purpose of developing preliminary remedial action objectives (RAOs) is to provide the remedial staff with long-term goals to use during analysis and selection of remedial technologies and alternatives. Through early development of preliminary RAOs in the decision making process, the remedial staff may be able to streamline the consideration of remedial alternatives.

2.0 **INTRODUCTION**

Tank 16 is one of twenty-nine carbon steel High Level Radioactive Waste tanks in the H-Area Tank Farm used for processing of waste from the separation areas and located near the heart of the Savannah River Site (SRS). This tank was constructed in 1958-59 and placed into service in May 1959. Tank 16 is a "Type II" tank with a single carbon steel container sitting in a five foot annulus pan and encased in a concrete structure (see Figure 2.1). The tank is 27 feet high, 85 feet in diameter, and has a capacity of 1.03 million gallons.

Tank 16 is positioned in the southeastern corner of the old tank farm area within the Tank 13-16 quadraplex. The Tank 16 area is congested with overhead wires, surface structures, and subsurface pipelines. These structures are portions of the operational aspects of the H-Area Tank Farm.

In 1960, while the tank was being filled, a leak was detected in one of the construction weld joints. An annulus jet was prepared for cleaning the leak but prior to complete jet evacuation of the tank waste, the leak overflowed the annulus pan and escaped to the environment. Estimates are that 16 to 700 gallons of waste may have leaked to the soil over a six hour period before jetting was initiated and waste transferred from the Tank 16 annulus to Tank 14. During that time there was leakage of waste through the concrete encasement, probably along the construction joint in the concrete encasement. Up to 5000 curies, principally Cesium-137, may have been released.

The tank was refilled with low heat waste in 1968. The use of Tank 16 ceased after reoccurring leaks resumed in 1972. The supernate was transferred to Tank 13 and jetting was performed on accessible areas of the tank. (No waste leakage to the environment was identified.)

The Tank 16 groundwater operable unit is in the RFI/RI Program and is pending workplan approval by the USEPA and SCDHEC to perform groundwater characterization.

FIGURE 2.1
 SECTION THROUGH WASTE STORAGE TANK 16

Modified from Poe et al. (1974).

3.0 MEDIA OF CONCERN

The following media have been evaluated with regard to contaminants associated with the Tank 16 operable unit: groundwater, soil, surface water, sediment, air, structures, solid wastes, liquid wastes, and sludges. Each media that is either

- currently contaminated media to which individuals may be exposed or through which chemicals may be transported to potential receptors, or
- currently uncontaminated media that may become contaminated in the future due to contaminant transport has been described in the sections below. Since the focus of the development of these remedial action objectives is the groundwater operable unit, other media were evaluated based on its potential to become contaminated by the groundwater or serve as a source for continuing contamination of the groundwater medium.

Wetlands and biota (flora/fauna) impacts will be addressed in future evaluations.

3.1 GROUNDWATER

Since the Tank 16 bottom is below the water table, any radioactivity that escaped from the concrete encasement reached the groundwater water table aquifer immediately. Due to the low flow rate of groundwater in this area and the ion exchange capabilities of the surrounding soil radioactivity migration is thought to be minimal.

Numerous monitoring wells and soil borings (proximal to Tank 16 and drilled to the top of the construction pad) constructed immediately after the release detected the presence of contaminants. Groundwater monitoring wells near Tank 16 have been used to track the release. Groundwater samples taken from a well installed next to Tank 16 showed the ratio of ^{137}Cs to ^{134}Cs to be 8 to 1 which is consistent with the calculated $^{137}\text{Cs}/^{134}\text{Cs}$ ratio for waste stored in Tank 16 (Poe et al., 1974). The potential of migration of contaminants into the lower aquifer (McBean) will be addressed in the implementation of the *RFI/RI Work Plan for Tank 16*.

3.2 SOIL

The Tank 16 leak to the environment was below grade and available data does not indicate any outcrop into surrounding surface soils. (Surface soils may have been contaminated by other non Tank 16 releases.) It is estimated that one gallon of Tank 16 waste would be equilibrated by ion exchange with approximately 100 cubic feet of soil comparable with that in the Tank 16 vicinity (Poe et al., 1974). On the basis of this equilibration ratio and the estimated waste release of 16-700 gallons, approximately 1,600 - 70,000 cubic feet (60-2600 cyds) of subsurface soils may have been contaminated.

3.3 SURFACE WATER

The Tank 16 leak to the environment was below grade and available data does not indicate any outcrop into surface water. The nearest surface water bodies are Upper Three Runs Creek which is approximately 8000 feet north of the H-Area Tank Farm, a tributary to Upper Three Runs Creek (McQueen Branch) which is 2500 feet east of Tank 16, a tributary to Upper Three Runs Creek (Crouch Branch) which is 2500 feet west of H-Area (see Figure 3.1) and a tributary to Four Mile Creek which is 1500 feet southwest of Tank 16. Low groundwater flow rates and the ion exchange property of the Tank 16 adjacent soils indicate that surface water outcrop of contaminants originating from the Tank 16 leakage to the environment is estimated at between 44 and 530 years. (Poe et al., 1974.)

3.4 SEDIMENT

The Tank 16 leak to the environment was below grade and available data does not indicate any outcrop into sediment. The nearest locations for sediment contamination are associated with Upper Three Runs Creek which is approximately 8000 feet north of the H-Area Tank Farm, a tributary to Upper Three Runs Creek (McQueen Branch) which is 2500 feet east of Tank 16, a tributary to Upper Three Runs Creek (Crouch Branch) which is 2500 feet west of H-Area (see Figure 3.1) and a tributary to Four Mile Branch which is 1500 feet southwest of Tank 16. Low groundwater flow rates and the ion exchange property of the Tank 16 adjacent soils indicate that sediment contamination originating from the Tank 16 leakage to the environment is estimated at between 44 and 530 years (Poe et al., 1974.).

3.5 AIR

The Tank 16 leak to the environment was below grade and available data does not indicate any outcrop in surrounding surface soils or sediments. Significant airborne releases could occur should excavation be performed in the subsurface soils surrounding Tank 16 and the H-Area Tank Farm. Should contaminants reach surface soils or sediment, airborne releases could occur as the result of wet/dry seasonal fluctuations.

3.6 STRUCTURES

The Tank 16 structure is currently intact and managed by Waste Management. The tank, annulus, and interior process equipment are contaminated with high heat waste (HHW) and low heat waste (LHW). Waste was removed from the tank following reoccurring leaks in 1972. Jetting was performed on accessible areas of the tank.

Any additional activities to remove residual wastes could increase personnel exposure. Monitoring of Tank 16 will continue until decontamination and decommissioning (D&D) activities are complete. Tank 16 is located within a designated Radiologically Controlled Area (RCA).

3.7 SOLID WASTES

Waste removal from Tank 16 was initiated in 1972 as a result of additional leakage. (No waste leakage to the environment was identified.) Only residual wastes were left in the tank and annulus areas. Any liquids remaining at the time of waste removal have solidified leaving only solid wastes within the tank and annulus areas. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

Approximately 75 gallons of water-insoluble waste containing 56,000 curies (Ci) of activity remain in the tank primary (see Table 3.1). The insoluble waste is mainly ferrous oxalate. The activity in the tank primary is primarily Sr^{90} .

An estimated 22,000 pounds of waste (natrodavyne and sand) containing 30,000 curies of activity remain in the tank annulus (see Table 3.1). The activity in the tank annulus is due primarily to Cs^{137} .

Should groundwater infiltrate the tank area (the tank bottom was constructed below the water table), it is conceivable that solid waste in the primary tank and tank annulus could be resuspended and migrate to the environment.

3.8 LIQUID WASTES

No liquid wastes are present in Tank 16 or its annulus. Any liquids remaining at the time of waste removal have solidified leaving only solid wastes within the tank and annulus areas. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

3.9 SLUDGES

Although initial Tank 16 wastes were characterized as sludge and supernatant, all sludges have solidified since the last waste removal in 1972. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

TABLE 3.1
TANK 16 RADIOCHEMICAL CONTENT

	Activity Concentration (mCi/g)	Activity (Ci)
Primary		
⁹⁰ Sr	87.0000	56,000.000
¹³⁷ Cs	0.0040	2.600
^{238,239} Pu	0.0006	0.400
Annulus		
¹³⁷ Cs*	43.0000	30,000.000

* Concentration calculated based on 22,000 lbs. of insoluble solids containing 30,000 curies.

Modified from Abel et al. (1987).

FIGURE 3.1
LOCAL WATER TABLE CONTOUR MAP

First Quarter Calendar Year 1992 Groundwater Data.

4.0 CHEMICALS OF CONCERN

The primary source of highly radioactive liquid waste is the chemical separations processes where enriched uranium and plutonium is recovered. Liquid wastes are categorized as HHW and LHW. The HHW contains most of the radioactive fission products processed in the separations area or concentrated in canyon evaporators. The HHW is principally sodium nitrate, sodium aluminate, and sodium hydroxide with some sulfate and carbonate. Tank 16 was initially filled with HHW [decay heat of 0.5 to 5 Btu/(hr)(gal)] from enriched uranium processing when the initial leak occurred in 1960. The tank was then refilled with LHW in 1968. (LHW has a fission product content 1/1000 to 1/100,000 that of HHW and comprised of solutions from secondary solvent extraction cycles and solvent washers.) In 1972 the use of Tank 16 ceased after leakage resumed with the supernate transferred to Tank 13. (No waste leakage to the environment was identified.)

HHW received into a waste tank for storage has a dissolved solid content of about 35 weight percent. While the waste ages, suspended solids settle into a sludge layer at the bottom of the tank. The sludge layer is a mixture of oxides and hydroxides of uranium, plutonium, mercury, and essentially all the fission products from the irradiated fuel. Cesium is the major fission product that remains in the supernate. The major chemical and physical properties of aged (approximately ten years) H-Area wastes are outlined in Tables 4.1 and 4.2. The non-radioactive minor components of the H-Area waste supernate (primarily Ag, Cr(IV), Hg, and Pb) are provided in Table 4.3 while Table 4.4 gives radioactive elements representative of wastes that have cooled approximately 5 years.

The principal long-term biological hazards in aged wastes are from the radioactive constituents that are most concentrated in the sludge with the exception of cesium. (Cesium is primarily concentrated in the supernatant.) Analysis shows that the sludge layer of aged waste contains greater than 99% of the strontium and plutonium and about 10% of the cesium and mercury. (The supernatant layer of aged waste contains the remaining 1% of the strontium and plutonium and about 90% of the cesium and mercury.) These biological hazards are identified below.

Supernate

- Cesium-137, a 30 year half-life fission product, is a gamma/beta emitter with a specific activity of 87 curies per gram. Its concentration in the supernate is 1 to 20 curies per gallon.

Sludge

- Strontium-90, a 28 year half-life fission product, is a beta emitter with a specific activity of 142 curies per gram. Its concentration in the sludge is 10 to 100 curies per gallon.
- Plutonium-238, an 87 year half-life actinide, is an alpha emitter with a specific activity of 17 curies per gram. Plutonium-238 is the predominant plutonium activity in the H-Area waste for the first 800-1000 years. Its concentration in the sludge approaches 0.2 curies per gallon.
- Plutonium-239, a 24,000 year half-life actinide element, is an alpha emitter with a specific activity of 0.06 curies per gram. Its concentration in the sludge varies from 3 to 30 millicuries per gallon.

The waste that overflowed the annulus pan had not completely separated into sludge and supernate. (Radiation and temperature profiles of the tank confirm that the sludge layer was only 30% of its expected final level.) The waste supernate phase that leaked into the annulus pan contained more Sr, Zr-Nb, and Ru than the supernate listed in Table 4.4.

Assuming the waste released was primarily composed of constituents observed in a sample of Tank 16 supernate (see Table 4.5) and those expected to be present by Poe et al. (1974), the ranges of contaminate quantities (including nonradioactive substances) that may have been released are listed in Table 4.6.

Of the radionuclides present in the waste that leaked into the soil, ^{137}Cs is in the largest quantity and has the largest biological hazard. The ^{90}Sr concentration is relatively low (currently 0.084 Ci/gal) but should be considered. ^{95}Zr , ^{95}Nb , ^{103}Ru , and ^{106}Ru were present in low concentrations at the time of the leak, and due to their relatively short half lives have been calculated to have decayed to less than 1×10^{-9} Ci/gal in the thirty-two years since the leak.

Although H-Area Tank Farm waste and specific waste sample analysis from Tank 16 indicate potential contamination by non-hazardous/non-radioactive and hazardous/non-radioactive constituents, the primary chemicals of concern in development of remedial action objectives are the radioactive constituents ^{137}Cs and ^{90}Sr .

TABLE 4.1
CHEMICAL COMPOSITION OF H-AREA HIGH ACTIVITY WASTE
(aged ~10 years)

	Constituent	Concentration
Supernate		
	NaNO_3 , NaNO_2	4 - 5 M
	Na_2CO_3	0.1 M
	Na_2SO_4	0.05 - 0.1 M
	NaAlO_2	0.5 - 1 M
	NaOH	1 - 1.5 M
	^{137}Cs	1 - 20 Ci/gal
Sludge		
	$\text{Fe}(\text{OH})_3$, MnO_2 , $\text{Al}(\text{OH})_3$	Settled Volume 5-8% of supernate volume
	^{90}Sr	10 - 500 Ci/gal
	^{239}Pu	$3 - 30 \times 10^{-3}$ Ci/gal
	^{238}Pu	2×10^{-1} Ci/gal

From Poe et al. (1974).

TABLE 4.2
PHYSICAL PROPERTIES OF AGED WASTE
(aged ~10 years)

Supernate		
	Specific Gravity	1.2 - 1.4
	Viscosity	~2 cp
	Heat Generation, % of total (Practically all from cesium)	50
Sludge		
	Specific Gravity	1.5 - 1.8
	Viscosity	Very High
	Heat Generation, % of total (Practically all from strontium)	50

From Poe et al. (1974).

TABLE 4.3
LOW CONCENTRATION
NONRADIOACTIVE CONSTITUENTS OF H-AREA SUPERNATE
(cooled ~5 years)

Constituent	Concentration
CO ₃ ⁻²	<0.1 - 0.3 M
SO ₄ ⁻²	0.02 - 0.08 M
PO ₄ ⁻³	<0.01 - 0.05 M
Cl ⁻	0.005 - 0.029 M
CrO ₄ ⁻²	0.001 - 0.005 M
F ⁻	0.001 - 0.004 M
Fe	6 x 10 ⁻⁵ - 0.2 M
Hg	60 - 340 µg/ml
NH ₄ ⁺	<1 - 67 µg/ml
Ag	0.1 - 4 µg/ml
Pb	2 - 58 µg/ml
U	0.4 - 6 µg/ml
Reducing normalities	<0.01 - 0.3 N

From Poe et al. (1974).

TABLE 4.4
RADIOACTIVE CONSTITUENTS OF H-AREA SUPERNATANT
(cooled ~5 years)

Constituent	Concentration, µCi/gal
⁶⁰ Co	<3 - 12
⁸⁹ Sr	<0.3 - <35
⁹⁰ Sr	30 - 3,600
⁹⁵ Zr	<5 - <10
⁹⁵ Nb	<1 - 2
¹⁰³ Ru	<2 - 4,900
¹⁰⁶ Ru	1,500 - 6,800
¹³⁴ Cs	100,000 - 170,000
¹³⁷ Cs	1,000,000 - 20,000,000
¹⁴¹ Ce	<1 - <44
¹⁴⁴ Ce	<8 - <440
¹⁵⁴ Eu	<3 - 5
Pu	0.01 - 4
²⁴³ Am	<1 - 4
³ H (tritium)	~75

From Poe et al. (1974).

TABLE 4.5
TANK 16 SAMPLE ANALYSIS

Date Reported	5/60	5/60	9/60	4/65
Description of Sample	Supernate	Sludge	Annulus	Supernate
Date Sampled	5/25/60	5/25/60	9/17/60	3/30/65
Total Solids	45.5 wt. %	50.3 wt. %	42 wt. %	31.28 wt. %
Specific Gravity	1.37		1.36	1.385
pH	>11	>11	>11	11.7 - 12.3
NaNO ₃				4.74 wt. %
NaOH				5.80 wt. %
NaAlO ₃	64.8 g/l	300 g/l		0.44 wt. %
Na ₂ CO ₃				0.39 wt. %
Na ₂ SO ₄				0.75 wt. %
U	2.4×10^{-3} g/l	$1.1 \times 10^{-3/1}$		
Cl ⁻	0.6 g/l			29 ppm
PO ₄ ⁻³				<0.02 g/l
Fe ⁺³				0.011 g/l
Al	25.5 g/l			
Gross Alpha ^{/2}	7.6×10^3	3.4×10^4	5.2×10^3	3.23×10^3
Pu Alpha ^{/2}	8.7×10^3	3.2×10^4		1.71×10^3
²⁴¹ Am Alpha ^{/2}	$<2.5 \times 10^3$	500		
²³⁷ Np Alpha ^{/2}	22	16.6		
Gross Beta ^{/3}	1.6×10^8	2.5×10^7	2.1×10^8	1.45×10^8
Gross Gamma ^{/3}	1.1×10^8	1.3×10^6	1.2×10^8	6.97×10^7
⁹⁵ Zr-Nb ^{/3}	8.6×10^6	5.8×10^5		
⁹⁰ Sr ^{/3}	4.4×10^6	1.3×10^6		4.63×10^5
¹⁴⁴ Ce ^{/3}	1.1×10^5	460		
^{103,106} Ru ^{/3}	4.5×10^6	2.7×10^5		
¹³⁷ Cs ^{/3}	8.0×10^7	3.9×10^5		6.67×10^7

^{/1} mg/mg

^{/2} d/m/ml

^{/3} c/m/ml

TABLE 4.5 (continued)
TANK 16 SAMPLE ANALYSIS

Date Reported		3/72		3/72		3/72	
Description of Sample		Salt From Top of Crust on Annulus Floor		Salt From Edge of Annulus Pan Ledge		Salt From Top of Annulus Pan Ledge	
Water Solubility, wt %		82		99		99	
Cations		Soluble	Insoluble	Soluble	Insoluble	Soluble	Insoluble
Major (10-100 %)		Na	Al	Na	Al	Na	
			Ca		Ca		
			Si		Si		
Minor (1-10 %)		Cr			Cr		
					Ca	Si	
				Al	Cd		
					Fe		
					Ni		
Trace (0.1-1 %)		Al		Ca	Mg	Li	
		Ca		Cd	Pb	Mo	
				Fe		Pb	
				Si			
				Cr			
Faint Trace (0.01-1 %)		Mg		Mg	Cu	Ca	
					Mn	Mg	
Anions, %	NO ₃	34		45		38	
	OH	0		1.7		0.1	
	SO ₄	0.1		0.7		0.8	
	CO ₃	0.6		3.2		0.5	
Radiation, R/hr		2		0.3		0.1	
¹³⁷ Cs, d/m/g		1.5 x 10 ⁹		8.3 x 10 ⁸		4.5 x 10 ⁸	
¹³⁴ Cs, d/m/g *		2.5 x 10 ⁸		5.5 x 10 ⁶		3.7 x 10 ⁶	
¹³⁷ Cs/ ¹³⁴ Cs Ratio		6		151		122	
Age, Years (Assuming X yrs. at ¹³⁷ Cs/ ¹³⁴ Cs Ratio = 6)		X		X + 10.6		X + 9.9	

* Reference document has ¹³⁷Cs, d/m/g which is clearly a typographical error.
Note: Absence of values indicates data not reported in source document.

From Davis et al. (1977)

TABLE 4.6
ESTIMATED QUANTITY OF MATERIAL RELEASED FROM TANK 16

Waste	Minimum 16 gallons	Maximum 700 gallons
Chromium	1 gram (g)	300 grams (g)
Mercury	4 g	900 g
Lead	0.1 g	150 g
Silver	0.01 g	10 g
¹³⁷ Cs	16 Curies (Ci)	14000 Curies (Ci)
⁹⁰ Sr	0.001 Ci	2 Ci
Other beta-gamma	2 Ci	130 Ci
Alpha	<0.0001 Ci	0.2 Ci
Tritium	0.0001 Ci	0.05 Ci

From RFI/RI Workplan for Tank 16 (1991).

5.0 FUTURE LAND USE

The Tank 16 operable unit is located within the H-Area Tank Farm which is located near the heart of the Savannah River Site (see Figure 5.1). The H-Area Tank Farm (see Figure 5.2) is an operational facility which contains twenty-nine tanks used for processing of waste from the separation areas. The H-Area Tank Farm is divided into two distinct areas, the old hill and the new hill.

Tank 16 is positioned in the southeastern corner of the old tank farm area within the Tank 13-16 quadraplex (see Figure 5.3). The Tank 16 area is congested with overhead wires, surface structures, and subsurface pipelines. These structures are portions of the operational aspects of the H-Area Tank Farm (see Figure 5.4).

The Tank Farm will continue to provide operational support to other facilities. The H-Area Tank Farm is forecasted to remain operational for the next 30 years in support of the Separations and the Defense Waste Processing Facility (DWPF). Specific processes are planned for continued use in SRS support, such as, the In Tank Precipitation Facility (ITP), evaporators, and select tanks for feed and feed storage to the DWPF.

FIGURE 5.1
MAP OF THE SAVANNAH RIVER SITE

Modified from RFI/RI Work Plan for Tank 16 (1991).

FIGURE 5.2
H-AREA LOCATION MAP

Modified from RFI/RI Work Plan for Tank 16 (1991).

FIGURE 5.3
H-AREA TANK FARM

Modified from RFI/RI Work Plan for Tank 16 (1991).

FIGURE 5.4
TANK 16 FEATURES

From RFI/RI Work Plan for Tank 16 (1991).

6.0 APPLICABLE OR RELEVANT AND APPROPRIATE REQUIREMENTS

Applicable or relevant and appropriate requirements (ARARs) may be subdivided into three types: chemical-specific, location-specific, and action-specific. Chemical-specific ARARs are usually health or risk based numbers or methodologies which result in the establishment of numerical values (e.g., concentrations in a given medium). Location-specific ARARs are restrictions placed upon the concentration of a hazardous substances or conduct of activities solely because they are in special locations (e.g., wetlands). Action-specific ARARs are usually technology or activity based requirements or limitations on actions taken with respect to hazardous wastes.

To be considered (TBCs) ARARs are requirements that include nonpromulgated criteria, advisories, guidance, and proposed standards issued by Federal and State governments. TBCs should be considered to determine preliminary remediation goals when no ARARs exist for particular contaminants.

6.1 CHEMICAL-SPECIFIC ARARS

Chemical-specific ARARs (Primary Drinking Water Standards, PDWS) for the Tank 16 groundwater operable unit primary chemicals of concern (^{137}Cs and ^{90}Sr) have been identified in Table 6.1.1. (^{134}Cs has also been identified.) General radionuclide maximum contaminant levels (MCLs) have been identified in Table 6.1.2. Occupational exposure guidelines have been identified as TBCs.

TABLE 6.1.1
PDWS^a FOR THE TANK 16 PRIMARY CHEMICALS OF CONCERN

Analyte	Unit	Level	Status	Reference
Cesium-137	pCi/L	2E+02	Final	EPA, 1977
Cesium-134	pCi/L	8.13E+01 ^b	Proposed	EPA, 1977
Strontium-90	pCi/L	8E+00 ^c	Final	CFR, 1991

^a Drinking water standards set by EPA (1977) correspond to the level at which each radionuclide contributes 4 mrem/yr dose to an individual consuming 2 liters of contaminated liquid a day.

^b The proposed standard is used because it is a lower value; final PDWS in 1977 may have been in error.

^c Critical organ is bone marrow.

TABLE 6.1.2
GENERAL RADIONUCLIDE CONTAMINANT MCLS

Constituent	Current MCL	Eff. Date	Proposed MCL ^a	Publ. Date	Citation
Adjusted Gross Alpha (AGA) Emitters (including Ra226/excluding Rn & U)	15 pCi/L	7/24/77			41FR28404
Adjusted Gross Alpha (AGA) Emitters(excluding U, Ra226, Rn 222)			15 pCi/L	7/18/91	56FR33050
Beta Particle & Photon Emitters	4 mrem/yr	7/24/77			41FR28404
Beta Particle & Photon Emitters (exclud. Ra228)			4 mrem ede/yr ^b	7/18/91	56FR33050

^a Proposed National Primary Drinking Water Regulations (NPDWR) for radionuclides are projected to become final 4/93.

^b The term "mrem ede/yr" refers to the dose committed over a period of 50 years to reference man from an annual intake at a rate of 2 liters of drinking water per day.

6.2 LOCATION-SPECIFIC ARARS

No location-specific ARARs for the Tank 16 location have been identified at this time.

6.3 ACTION-SPECIFIC ARARS

No action-specific ARARs for the Tank 16 groundwater operable unit have been identified since technology identification and evaluation is in its initial phase.

6.4 TO BE CONSIDERED

Occupational exposure guidelines have been identified as TBCs for the Tank 16 operable unit. Identified occupational exposure guidelines for applicable radionuclides are listed in the Table 6.4.1. No soil and sediment criteria have been identified.

TABLE 6.4.1
AIR AND WATER MPCs FOR OCCUPATIONAL EXPOSURES¹ OF RADIONUCLIDES ($\mu\text{Ci}/\text{ml}$)

Radionuclide	Primary emission	Radiotoxicity ²	(MPC) _w ³	(MPC) _a ⁴
⁹⁰ Strontium	beta	very high	4×10^{-6}	3×10^{-10}
¹³⁷ Cesium	beta; gamma	moderate	4×10^{-4}	6×10^{-8}
²³⁹ Plutonium	alpha	very high	10^{-4}	2×10^{-12}
Tritium	beta	slight	0.1	5×10^{-6}
Unidentified	alpha	---	10^{-7}	4×10^{-13}
Unidentified	beta	---	10^{-7}	4×10^{-13}

¹ From "Radiological Health Handbook", U.S. Department of Health, Education, and Welfare, Washington, D.C.

² From "Safe Handling of Radionuclides", Safety Series No. 1, International Atomic Energy Agency, Vienna.

³ (MPC)_w = Maximum Permissible Concentration in water except (MPCU)_w for unidentified radionuclides.

⁴ (MPC)_a = Maximum Permissible Concentration in air except (MPCU)_a for unidentified radionuclides.

Modified from RFI/RI Work Plan for Tank 16 (1991).

7.0 EXPOSURE PATHWAYS

Exposure pathways are those avenues by which contaminants have or may come in contact with receptors such as workers, the public, and the environment. These pathways identify real or potential hazard migration from contaminated/potentially contaminated media to identifiable receptors. The identified pathways for the media of concern (groundwater) described in section 3.0 assuming industrial/commercial land use are described in the following sections.

Wetlands and biota (flora/fauna) impacts will be addressed in future evaluations.

7.1 GROUNDWATER

The contaminated water table aquifer in the Tank 16 area is not used for potable purposes. This groundwater aquifer is monitored by SRS personnel resulting in potential exposure through dermal absorption. The potential of migration of contaminants into the lower aquifer (McBean) will be addressed in the implementation of the *RFI/RI Work Plan for Tank 16*. The McBean aquifer flow rate is characteristically faster than the water table.

7.2 SOIL

Subsurface soils have been contaminated and may pose exposure to SRS workers during D&D activities and subsurface maintenance in the H-Area Tank Farm through inhalation of particulates and direct external exposure of radionuclides. Subsurface soils also pose as a continuing source of contamination of the groundwater.

7.3 SURFACE WATER

No surface water contamination has been detected that is solely identifiable with the Tank 16 groundwater operable unit. (Tritium has been detected in Upper Three Runs Creek.)

7.4 SEDIMENT

No sediment contamination has been detected that is solely identifiable with the Tank 16 groundwater operable unit.

7.5 AIR

Exposure via air transport is dependent on the fate of soils at the Tank 16 operable unit as well as migration of groundwater as a primary transport means.

7.6 STRUCTURES

Tank Farm maintenance activities and future D&D activities could result in further exposure of radionuclides to the environment (*i.e.*, groundwater).

7.7 SOLID WASTES

Waste removal from Tank 16 was initiated in 1972 as a result of additional leakage. Only residual wastes were left in the tank and annulus areas. Any liquids remaining at the time of waste removal have solidified leaving only solid wastes within the tank and annulus areas. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

Approximately 75 gallons of water-insoluble waste containing 56,000 curies (Ci) of activity remain in the tank primary (see Table 3.1). The insoluble waste is mainly ferrous oxalate. The activity in the tank primary is primarily Sr^{90} .

An estimated 22,000 pounds of waste (natrodavyne and sand) containing 30,000 curies of activity remain in the tank annulus (see Table 3.1). The activity in the tank annulus is due primarily to Cs^{137} .

Any additional activities to remove waste residuals could increase the potential exposure of radionuclides to the environment (*i.e.*, groundwater).

7.8 LIQUID WASTES

No liquid wastes are present in Tank 16 or its annulus. Any liquids remaining at the time of waste removal have solidified leaving only solid wastes within the tank and annulus areas. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

7.9 SLUDGES

Although initial Tank 16 wastes were characterized as sludge and supernatant, all sludges have solidified since the last waste removal in 1972. Subsequent remote observations of the Tank 16 primary and annulus have verified the solid nature of remaining tank waste.

8.0 PRELIMINARY REMEDIAL ACTION OBJECTIVES

Preliminary remedial action objectives (RAOs) consist of medium/operable unit specific goals for protecting human health and the environment. These objectives are specific and do not limit the range of alternatives that may be developed. The preliminary RAOs specify the contaminants of concern and exposure limits for human health and environmental protection for each media of concern.

The human health based RAOs were developed using MCLs identified in Tables 6.1.1 and 6.1.2. for ingestion of water from the groundwater medium. In the absence of environmental standards and identifiable ARARs for determining environmental protection based RAOs, TBC occupational exposure guidelines (see Table 6.4.1) were used for the development of preliminary RAOs for dermal adsorption by workers of the groundwater medium.

Preliminary RAOs for the Tank 16 groundwater operable unit are described below. RAOs for the other media (soils, surface water, sediment, air, structures, solid wastes, liquid wastes, and sludges) will be evaluated as assessment of the Tank 16 source unit proceeds.

GROUNDWATER MEDIUM

•For Human Health

- Prevent dermal absorption of water having a total excess cancer risk for all contaminants of 10^{-6} .
- Prevent ingestion of water having a total excess cancer risk for all contaminants of 10^{-6} .
- Prevent ingestion of water having ^{137}Cs in excess of $2 \times 10^{-7} \mu\text{Ci/ml}$.
- Prevent ingestion of water having ^{134}Cs in excess of $8.13 \times 10^{-8} \mu\text{Ci/ml}$.
- Prevent ingestion of water having ^{90}Sr in excess of $8 \times 10^{-9} \mu\text{Ci/ml}$.
- Prevent ingestion of water having adjusted gross alpha emitters (including Ra226/ excluding Rn & U) which result in a total body or organ dose of $1.5 \times 10^{-5} \mu\text{Ci/ml}$.
- Prevent ingestion of water having adjusted gross alpha emitters (excluding U, Ra226, Rn222) which result in a total body or organ dose of $1.5 \times 10^{-5} \mu\text{Ci/ml}$.
- Prevent ingestion of water having beta particle and photon emitters which result in a total body or organ dose of 4 mrem/yr.
- Prevent ingestion of water having beta particle and photon emitters (excluding Ra228) which result in a total body or organ dose of 4 mrem ede/yr.

No dermal exposure MCLs have been identified for radionuclides. Worker exposure standards that must be adhered to during remedial activities (occupational exposure levels) have been used to provide an RAO dermal exposure starting point for the evaluation of remedial alternatives.

- Prevent dermal exposure of water having ^{137}Cs in excess of $4 \times 10^{-4} \mu\text{Ci/ml}$.
- Prevent dermal exposure of water having ^{90}Sr in excess of $4 \times 10^{-6} \mu\text{Ci/ml}$.
- Prevent dermal exposure of water having unidentified alpha in excess of $10^{-7} \mu\text{Ci/ml}$.
- Prevent dermal exposure of water having unidentified beta in excess of $10^{-7} \mu\text{Ci/ml}$.

•For Environmental Protection

RAOs that identify goals relating to the prevention of radionuclide contaminated groundwater migration to surface water, sediments, and soils and the prevention of continued radionuclide contamination of groundwater from source media which are primarily soil, structure, and solid waste will be determined in the ecological risk assessment.

9.0 PRELIMINARY GENERAL RESPONSE ACTIONS

Preliminary general response actions (GRAs) describe medium specific actions (treatment, containment, excavation, extraction, disposal, institutional actions, and no action) which will satisfy the preliminary RAOs. An initial determination of areas or volumes of media which are applicable to GRAs is made. Only the groundwater medium was evaluated. The other media (soils, surface water, sediment, air, structures, solid wastes, liquid wastes, and sludges) will be evaluated as assessment of the Tank 16 source unit proceeds.

GROUNDWATER MEDIUM

- *No Action/Institutional Controls*
 - No Action
 - Access Control/Restrictions
 - Monitoring
- *Containment*
 - Constructed Barrier
- *Recovery/Removal*
Not Applicable
- *Treatment*
 - Collection/Treatment/Discharge
 - Insitu Treatment
- *Disposal*
Not Applicable

10.0 REMEDIAL TECHNOLOGY TYPES

A range of remedial technologies (e.g. chemical/physical treatment, thermal destruction, isolation, prevention, stabilization, etc.) which provides for treatment, containment, and removal requirements of any contaminated media remaining at the operable unit are identified/developed which will satisfy the preliminary RAOs. Several broad technology types are identified for each preliminary GRA. Specific process options have been identified but are not thoroughly addressed in this report. The Remedial Action Assessment System (RAAS) Technology Information System (White et al., 1991), available reference material, SRS reports, and regulatory guidance were used as initial tools for the screening of remedial technologies for the Tank 16 groundwater operable unit. The following summarizes key technology types identified for the groundwater medium specific GRAs.

GROUNDWATER MEDIUM

- *No Action/Institutional Controls*
 - No Action
 - a) No Further Action
 - Access Control/Restrictions
 - a) Institutional controls through Site Use Permits
 - Monitoring
 - a) Establish monitoring program to observe contaminant migration
- *Containment*
 - Constructed Barriers
 - a) Vertical barriers
 - Slurry wall
 - Grout curtain
 - Sheet piling
 - b) Horizontal barriers
 - Grout injection
 - Capping
- *Recovery/Removal*
Not Applicable
- *Treatment*
 - Collection/Treatment/Discharge
 - a) Groundwater collection/pumping
 - b) Physical treatment
 - pH adjustment
 - Filtering
 - c) Chemical treatment
 - Ion exchange
 - Reverse osmosis
 - Insitu Treatment
 - a) Fixation
- *Disposal*
Not Applicable

11.0 REFERENCES

- 11.1 Abel, M.D., Cook, J.R., 1987, "Tank 16 Decommissioning Demonstration: VGA Basic Data", DPSP-87-1219, E. I. duPont de Nemours and Company, Savannah River Plant, Aiken, SC.
- 11.2 Comprehensive Environmental Response, Compensation and Liability Act of 1980 CERCLA (Superfund), PL 96-410, As amended by PL 97-216, July 18, 1982; PL 97-272, September 30, 1982; PL 98-45, July 12, 1983; and PL 99-499, October 17, 1986.
- 11.3 Davis, T. L., Tharin, D. W., Jones, D. W., and Lohr, D. R., 1977, "History of Waste Tank 16, 1959 through 1974", DPSPU-77-11-17, E. I. duPont de Nemours and Company, Savannah River Plant, Aiken, SC.
- 11.4 "Risk Assessment Guidance for Superfund: Volume 1 - Human Health Evaluation Manual (Part B, Development of Risk-based Preliminary Remediation Goals)", OSWER Directive 9285.7-01B, December 1991.
- 11.5 "Guidance for Conducting Remedial Investigations and Feasibility Studies under CERCLA Interim Final", EPA/540/G-89/004, OSWER Directive 9355.3-01, October 1988.
- 11.6 "National Interim Primary Drinking Water Regulations", 1977, EPA-570/9-76-003.
- 11.7 "National Oil and Hazardous Substances Pollution Contingency Plan", 40 CFR 300, Final Rule, March 8, 1990.
- 11.8 "National Primary Drinking Water Regulations", 1991, 40 CFR (Code of Federal Regulations).
- 11.9 "National Primary Drinking Water Regulations; Radionuclides; Proposed Rule", July 18, 1991, U. S. Environmental Protection Agency, Federal Register.
- 11.10 Prendergast, J.T., 1982, "Decommissioning Alternatives for Waste Tank 16", DPST-82-456, E. I. duPont de Nemours and Company, Savannah River Plant, Aiken, SC.
- 11.11 Poe, W. L., Fenimore, J. W., Horton, J. H., Marine, I. W., and Prout, W. E., 1974, "Leakage From Waste Tank 16, Amount, Fate, and Impact", DP-1358, E. I. duPont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- 11.12 "RFI/RI Work Plan for Tank 16", WSRC-RP-90-497, February 25, 1991, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.
- 11.13 Thomas, C.J. to Morris, O.M., 1985, "Tank 16 Decommissioning Plan", DPSP-85-17-2, E. I. duPont de Nemours and Company, Savannah River Plant, Aiken, SC.
- 11.14 "Technological Approaches to the Cleanup of Radiologically Contaminated Superfund Sites", EPA/540/2-88/002, August, 1988.
- 11.15 "Technology Screening Guide for Treatment of CERCLA Soils and Sludges", EPA/540/2-88/004, September 1988.

- 11.16 "Water Pollution Control; National Primary Drinking Water Regulations; Radionuclides (Proposed)", September 30, 1986, U. S. Environmental Protection Agency, Federal Register.

END

**DATE
FILMED**

5 / 12 / 93