WSRC-TR--91-72

DE92 009449

RECEIVED
MAR 1 1992

**ESTIMATING DEPOSITION VELOCITY FROM ATMOSPHERIC RELEASES
OF IODINE (U)**

Charles E. Murphy Jr.

**Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808**

SAVANNAH RIVER SITE

MASTER

Handwritten signature

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared by Westinghouse Savannah River Company (WSRC) for the United States Department of Energy under Contract No. DE-AC09-89SR18035 and is an account of work performed under that contract. Neither the United States Department of Energy, nor WSRC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, or product or process disclosed herein or represents that its use will not infringe privately owned rights. Reference herein to any specific commercial product, process, , or service by trademark, name, manufacturer or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring of same by WSRC or by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

D.B. Moore

D.B. Moore, Manager
Authorized Derivative Classifier

**ESTIMATING DEPOSITION VELOCITY FROM ATMOSPHERIC RELEASES
OF IODINE (U)**

Charles E. Murphy Jr.

Publication Date: February 5, 1991

Approved By: D.B. Moore, Manager
Environmental Sciences Section
Savannah River Laboratory

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

SAVANNAH RIVER SITE

THIS DOCUMENT WAS PREPARED IN CONNECTION WITH WORK UNDER THE U.S. DEPARTMENT OF
ENERGY (CONTRACT DE-AC09-89SR18035).

ABSTRACT

Deposition velocity is a parameter used in atmospheric transport models to specify the amount an atmospheric constituent transferred from the atmosphere to the surface of the earth. The material may deposit on the surface of soil, water, or vegetation. The deposition may be the result of rainfall or diffusion. A method for the calculation of deposition velocity based upon the decrease in deposition with distance from a point source is presented. The method does not require a knowledge of the time over which the deposition occurs or the concentration of the material in the atmosphere. However, the method does assume that the deposition rate is proportional to the air concentration. The sensitivity to errors resulting from certain errors in the measurements and from violation of some of the assumptions of the model underlining the calculations are also be discussed. The method has been used to estimate the deposition velocity of I-129. Two sets of I-129 deposition data at various distances from the center of SRS were used in the calculations. The results indicate that the deposition velocity is near a value of 0.2 cm/s. This is consistent with the processes that are known to control iodine deposition.

CONTENTS

INTRODUCTION	1
DISCUSSION	1
The Effect of Deposition Velocity	2
The Effect of Brackground	2
The Effect of Vertical Mixing	4
Estimation of I-129 Deposition Velocity	5
SUMMARY	7
REFERENCES	8

LIST OF FIGURES

1. The effect of deposition on concentration versus distance from a point source	3
2. The effect of background on concentration versus distance from a point source	3
3. The effect of vertical mixing on concentration versus distance from a point source	4

LIST OF TABLES

1. The Effect of the Atmospheric and Measurement Conditions on the Apparent Slope of the Relationship between Concentration and Distance from the Source	5
2. I-129 Concentrations in the Vicinity of SRS	6
3. I-129 Deposition Velocities Estimated from SRS Data	7

ESTIMATING DEPOSITION VELOCITY FROM ATMOSPHERIC RELEASES OF IODINE

By C.E. Murphy Jr.

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

INTRODUCTION

Deposition velocity is a parameter used in atmospheric transport models to specify the amount an atmospheric constituent that is transferred from the atmosphere to the surface of the earth. The material may deposit on the surface of soil, water, or vegetation. The deposition may be the result of rainfall or diffusion. The deposition velocity can be specified as an average of all these processes or can be specified for certain conditions, i.e. the dry deposition velocity. The need for integrated, average deposition velocity or process specific deposition velocity depends on the type of model used. Deposition velocities for materials are often determined by field measurements using the meteorological methods of gradient or eddy flux or by measuring the accumulation of material on the surface over fixed periods of time. Deposition velocity is also calculated by summing the results of laboratory measurements of the uptake of the material by the individual elements of the surface, e.g. plant leaves and stems, soils, etc.

This report will discuss a method for the calculation of deposition velocity based upon the decrease in deposition with distance from a point source. The method does not require a knowledge of the time over which the deposition occurs or the concentration of the material in the atmosphere. However, the method does assume that the deposition rate is proportional to the air concentration. The sensitivity to errors resulting from certain errors in the measurements and from violation of some of the assumptions of the model underlining the calculations are also be discussed. The method has been used to estimate the deposition velocity of I-129. Two sets of I-129 deposition data at various distances from the center of SRS were used in the calculations. The results indicate that the deposition velocity is near a value of 0.2 cm/s. This is consistent with the processes that are known to control iodine deposition.

DISCUSSION

The model used in the calculation of deposition velocity is based on the assumption that, over a long period of time, and at some distance removed from the source, the dispersion of a material from a point source can be described as radial advection through an average, fixed layer of the atmosphere. Deposition from the atmosphere is proportional to the atmospheric concentration and the surface area at any radial distance from the source. The mass balance of material in the atmosphere, under these assumptions leads to

$$dC/C = [1.0/r + 2 \pi v_d / (uL)] dr \quad 1)$$

This can be solved for concentration as a function of distance

$$C/C_0 = (r/r_0)^{-n} \exp[-2 \pi v_d(r-r_0)/(uL)] \quad 2)$$

where

$n=1.0$

C = concentration (pCi/cu m) or deposition (pCi/sq m)

r = radial distance from the source

v_d = deposition velocity

u = wind speed

L = mixing depth of the atmosphere

$_0$ = subscript indicating at a reference point.

Equation 2) specifies that concentration (or deposition which is proportional to concentration) decrease with distance is a straight line when plotted on logarithmic coordinates. This has been shown to be a reasonable approximation of decrease in concentration for a number of radionuclides monitored at SRS. However, the slope of the concentration with distance (logarithmic) usually is not equal to negative one, as would be expected for a material which remains in the atmosphere (is not deposited) as it disperses from SRS.

The Effect of Deposition Velocity

Figure 1. illustrates the effect of deposition on the decrease in concentration with distance from a source. The effect is to decrease the concentration more than that caused by the dilution from radial dispersion into a larger volume of air. The deviation from the case with no deposition will depend on the rate of deposition, i.e. the deposition velocity and the mixed depth of the atmosphere. If deposition is present, the decrease in concentration is not described by a straight line. The increasing surface area at greater distances from the source causes an increasing effect of deposition with distance from the source. However, short segments of the curve of decreasing concentration with distance can be approximated as straight lines with slope less than negative 1.0. This explains why field data often appears to plot as a straight line on logarithmic paper but with a slope other than negative 1.0.

The Effect of Background

The term background is used here as the concentration due to releases from other sources that are evenly distributed in the vicinity of the location where measurements are made. Figure 2. illustrates the effect of a background that is half the concentration at the point furthest from the source. The effect of the background is greater at lower concentration, i.e. further from the source. This will cause the curve describing the concentration decrease with distance to bend upward. A straight line fit to approximate this curve will have a slope greater than negative 1.0. Thus the effect of an uncorrected background will be in the opposite direction of the effect of deposition from the atmosphere.

Figure 1. The effect of deposition on concentration versus distance from a point source.

Figure 2. The effect of background on concentration versus distance from a point source.

The Effect of Vertical Mixing

If the assumption of complete mixing of the material in the atmosphere is not met, the concentration at the surface (and thus the deposition) will be great close to the source than the simple radial dispersion model would predict. In this case the slope of the line approximating the decrease in concentration with distance would be more negative than expected from radial dispersion. In this case, the effect of vertical mixing will be the same as the effect of deposition. If the source is from a stack or other elevated location, the material will not reach the ground for some distance away from the stack. In this case the concentration will increase with distance from the stack, finally reaching a maximum, and then decreasing with distance. The effect on the slope of a straight line approximation of concentration decrease with distance can be either to make the slope less negative near the source and more negative away from the source. This is illustrated in figure 3.

Figure 1. The effect of vertical mixing on concentration versus distance from a point source.

The effects of background and vertical mixing place some restraints on the use of equation 2) to estimate deposition. Either the background concentration of the material of interest must be very low, or well defined so that it can be subtracted from the measurements. Measurements should be made as far away from the source as possible to minimize the effect of vertical mixing and release height. To some extent these, these two restraints work against each other. The further measurements are made from the source, the more likely the background will become a significant fraction of the measurement. Table 1. lists the results of calculations of the slope of concentration with distance made from the curves in figure 1. through 3. The illustration used a mixing depth of 2000 meters, a wind speed of 3 m/s, a stack height of 60 meters, a deposition velocity of 1 m/s, and neutral atmospheric temperature stratification.

Table 1. The Effect of the Atmospheric and Measurement Conditions on the Apparent Slope of the Relationship between Concentration and Distance from the Source.

	<u>Ideal</u>	<u>Background</u>	<u>Deposition</u>	<u>Mixing Depth</u>
Distance (km)				
10-20	-1.00	-0.93	-1.15	-0.98
20-50	-1.00	-0.86	-1.34	-0.99
50-100	-1.00	-0.74	-1.76	-1.00

Estimation of I-129 Deposition Velocity

The deposition of I-129 in soils and vegetation has been made in the vicinity of SRS. The low specific activity of I-129 has made routine measurements difficult. However, the long half-life has meant that I-129 has accumulated, at low levels, in the soil around SRS. This material is recycled through the vegetation. Thus, the concentration of I-129 in soil and vegetation is a measure of the long-term deposition. The deposition velocity calculated from this data should be the integrated average for all processes involved in the exchange between the atmosphere and the surface. However, because of the relatively low amount of time involved with wet deposition (rainfall), the deposition velocity should be weighted towards the dry deposition velocity. The deposition velocity can be determined by rearranging equation 2).

$$v_d = - \ln [C/C_0/(r/r_0)^{-n}] / [2 \pi(r-r_0)/(uL)] \quad 2)$$

If the left hand side of equation 3) is plotted against the right hand side, the deposition velocity will be the slope of the straight line through the data points.

Table 2. shows the results of two measurements of I-129 at various distances from the center of SRS. Hochel's (1976) results are the average of a number of measurements taken at the indicated distances. Kantelo et al. (1981) results are two points taken along a straight line though the data plotted in logarithmic coordinates. Hochel's data is reported in units of concentration while Kantelo's in units of deposition.

The resulting deposition velocities are shown in Table 3. An average wind speed of 3 m/s and an average mixed depth of the atmosphere of 540 meters was used in the calculations. The average wind speed (to the nearest m/s) was taken from Laurinat (1987). The average mixing depth was calculated from the environmental monitoring data, as summarized in Murphy et al. (1990), using the model described in this report. The resulting equation is:

$$L = F/(2 \pi r u C) \quad 3)$$

where F is the rate of tritium released during the period when the average tritium concentration, C was measured. The plant perimeter monitoring stations were used in the calculation. Notice that the estimate of wind speed and mixed layer are linked in the same way in equations 2) and 3). This means that any error in estimate of the wind speed will be compensated by the estimate mixing depth.

Table 2. I-129 Concentrations in the Vicinity of SRS

(Hochel, 1976)

Soil

<u>r (km)</u>	<u>C (pCi/gm)</u>	<u>C/C₀</u>	<u>r/r₀</u>	<u>(C/C₀)(r/r₀)</u>
20	0.021	1	1	1
40	0.005	2	0.238	0.476
160	0.001	8	0.047	0.381

Vegetation

<u>r (km)</u>	<u>C (pCi/gm)</u>	<u>C/C₀</u>	<u>r/r₀</u>	<u>(C/C₀)(r/r₀)</u>
20	0.009	1	1	1
40	0.004	2	0.444	0.888

(Kantelo et al. 1981)

<u>r (km)</u>	<u>C (pCi/sq m)</u>	<u>C/C₀</u>	<u>r/r₀</u>	<u>(C/C₀)(r/r₀)</u>
20	109	1	1	1
40	48	2	0.440	0.881

SUMMARY

The results are suggest a mean deposition velocity of 0.2 cm/s. This is somewhat lower than the average deposition velocity for water vapor, which is around 0.4-0.8 cm/s. However, the molecular diffusivity of iodine vapor is about 5 time less than that of water vapor. When this is taken into account the results suggests that iodine is deposited by the same processes as determine the deposition of many other gases such as water vapor or SO₂, i.e vapor diffusion and deposition by solution inside vegetation and soil.

Table 3. I-129 Deposition Velocities Estimated from SRS Data.

	slope (eq. 3) <u>km⁻¹</u>	deposition velocity <u>cm/s</u>
<u>Hochel (1976)</u>		
soil	-0.00689	0.18
vegetation	-0.00588	0.15
<u>Kantello et al. (1981)</u>		
soil	-0.00634	0.16

REFERENCES

Hochel, R.C. 1976. Preliminary I-129 Measurements in the SRP Environs. DPST-76-221, E.I. du Pont de Nemours & CO., Inc., Savannah River Laboratory, Aiken, S.C. 15 pp.

Kantelo, M.V., B. Tiffany, and T.J. Anderson. 1981. Iodine-129 distribution in the terrestrial environment surrounding a nuclear fuel reprocessing plant after 25 years of operation. International Symposium on Migration in the Terrestrial Environment of Long-lived Radionuclides from the Nuclear Fuel Cycle. IAEA-SM-257/53P. p 86.

Laurinat, J.E. 1987. Average Wind Statistics for SRP Area Meteorological Towers. DPST-87-341. E.I. du Pont de Nemours & CO., Inc., Savannah River Laboratory, Aiken, S.C. 15 pp.

Murphy, C.E., Jr., L.R. Bauer, D.W. Hayes, W.L. Marter, C.C. Zeigler, D.E. Stephenson, D.D. Hoel, and D.M. Hamby. 1990. Tritium in the Savannah River Environment. WSRC-RP-90-424-1, Westinghouse Savannah River Company, Savannah River Site, Aiken, S.C. 29808, 133 pp.

NCRP. 1978. Tritium in the Environment. National Council on Radiation Protection and Measurements Report No. 62., Washington, D.C. p 25.

END

DATE
FILMED
4 12 81 92