2
DOE/PC/91310--T1

DOE/PC/91310--T1

DE92 010837

**USE OF SOLID-STATE NMR TECHNIQUES FOR THE ANALYSIS OF
WATER IN COAL AND THE EFFECT OF DIFFERENT COAL DRYING
TECHNIQUES ON THE STRUCTURE AND REACTIVITY OF COAL**

by
Daniel A. Netzel

Quarterly Report: September 1 - November 30, 1991

Work Performed Under Grant Agreement
DE-FG22-91PC91310

For
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236-0940

By
University of Wyoming Research Corporation
a.k.a. Western Research Institute
Laramie, Wyoming

U.S. DOE Patent Clearance is Not Required Prior to the Publication of
This Document

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

MAR 2 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

JAN 8 0 1982

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.....	1
OBJECTIVES.....	2
ACCOMPLISHMENTS.....	3
PROCEDURE.....	3
RESULTS.....	4

INTRODUCTION

One area for improvement in the economics of coal liquefaction is coal drying, particularly for the lower rank coals. However, there is considerable evidence to show that drying has a detrimental effect on the liquefaction behavior of coals. Regarding the liquefaction of coal, there does not appear to have been any systematic study of the methods of coal drying on coal structure and the role water plays in enhancing or lessening coal reactivity toward liquefaction. In part, this may have been the result of not having the techniques that are now available, such as solid-state NMR.

There are many theoretical advantages to drying coal prior to liquefaction. Direct liquefaction conversion and kinetics are heavily dependent upon the partial pressure of hydrogen in the liquefaction reactor; thus, the removal of moisture in the coal allows the partial pressure of hydrogen to be increased without increasing the operating pressure. In addition, removal of most of the water from the coal prior to liquefaction reduces the cost of shipping coal to the liquefaction reactor. Finally, moisture in the coal reduces the throughput of coal on a dry basis if the liquefaction reactor has a fixed capacity.

The problem associated with drying coal is that removing the moisture prior to liquefaction reduces the reactivity of coal to liquefaction, and hence, the amount of coal converted to liquid during the liquefaction process is reduced. Therefore, to derive economic benefits from coal drying, the causes of the lower reactivity of dried

coals must be understood, or other methods of drying must be developed that circumvent this problem.

With the solid-state nuclear magnetic resonance (NMR) techniques of combined rotation and multiple pulse spectroscopy (CRAMPS) and cross polarization with magic-angle spinning (CP/MAS), studies of chemical structural changes that may occur in coals as a result of drying are feasible. In fact, the CRAMPS technique is only now emerging as a method for studying coal structure even though multiple-pulse techniques were applied to the study of coal over a decade ago. These solid-state NMR techniques can be extremely useful for determining structural changes induced by drying by different methods and for determining the extent of condensation/retrograde reactions that may occur during drying. However, before these changes can be evaluated, an appropriate method for determining the amount of water in coal must be developed. In particular, we need to know the chemical environment in which water exists in the coal structure.

OBJECTIVES

The overall objectives of this study are to develop an NMR method for measuring the water in coal, to measure the changes in coal structure that occur during coal drying, to determine what effect water has on retrograde/condensation reactions, and to determine the mechanism by which water may enhance coal reactivity toward liquefaction. Different methods of drying will be investigated to determine if drying

can be accomplished without destroying coal reactivity toward liquefaction, thereby making coal drying an attractive and economical method for coal pretreatment. Coal drying methods will include thermal drying under different atmospheres and temperatures, drying with microwave radiation, and low-temperature chemical dehydration.

The objectives for this quarterly report period were (1) to hire a student to help on the program, (2) to define the coals to be investigated and acquire the samples, (3) to order the necessary reagents and supplies, and (4) to conduct preliminary experiments for determining water quantitatively using 2,2'-dimethoxypropane and ^1H NMR.

ACCOMPLISHMENTS

The quarterly objectives have been met. A student was hired to assist in the development of a method for determining water by NMR. The necessary coal samples, reagents, and supplies have been ordered and received, and an NMR technique for determining water in coals was partially developed.

PROCEDURE

Eagle Butte coal, a high-moisture subbituminous coal from the Amax Eagle Butte mine located in the Powder River Basin of Wyoming was selected for developing the methodology for the determination of water

in coal by NMR. The method will be applied to other coals selected from the suite of coal samples received from the Argonne Premium Coal Sample Program. These coal samples vary in moisture content.

To develop the water analysis method using ^1H NMR, known amounts of water dissolved in dioxane was treated with 2, -2'-dimethoxypropane. After a reaction time of 5 minutes, an aliquot of the solution was removed and diluted with CDCl_3 containing TMS as the chemical shift reference and cycloheptane as the internal hydrogen standard. The amount of water was calculated from the integrated hydrogen NMR spectrum of the solution.

RESULTS

Preliminary experiments for determining water in dioxane by ^1H NMR gave an error of less than $\pm 1\%$. Corrections for residual water in dioxane and small impurities in the hydrogen standard have not been made. With these corrections and improved laboratory technique, the errors associated with this method should be reduced considerably.

END

**DATE
FILMED
6/01/92**