12
6/10/92 Dr ①

PNL-8059
UC-602

Steady-State Analysis of the Fate of Volatile Contaminants During In Situ Vitrification

W. L. Kuhn

May 1992

Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute

PNL-8059

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831;
prices available from (615) 576-8401. FTS 626-8401.

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

PNL--8059

DE92 014601

STEADY-STATE ANALYSIS OF THE FATE OF
VOLATILE CONTAMINANTS DURING
IN SITU VITRIFICATION

W. L. Kuhn

May 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

THIS DOCUMENT IS UNCLASSIFIED

EB

SUMMARY

A mathematical simulation has been developed to describe the transport of water, steam, and trace concentrations of volatile contaminants in soil during the application of the In Situ Vitrification (ISV) process. The ISV process creates a mass of molten soil that grows during processing. Testing has shown that the vast majority of water encountered and vaporized by the growing melt is expelled from the soil and directed to an off-gas treatment system. The simulation addresses the question: under what conditions will other volatile species also be expelled from the soil and be directed to the off-gas system (or oxidized or pyrolyzed in transit)?

The simulation is based on an assumed spherical symmetry of temperature, liquid saturation, and contaminant concentration profiles adjacent to an assumed expanding hemispherical melt. A set of coupled, nonlinear ordinary differential equations are solved numerically to predict the transport of water and steam in two regions: a boiling region (essentially a heat pipe) assumed to be devoid of air, and a diffusion region assumed to be at constant pressure.

The transport of contaminants is predicted in terms of the velocity of the location of an assumed "bell-shaped" contaminant concentration profile. For volatile and immiscible species, the degree of sorption of the contaminant on the soil determines if the contaminant moves outward faster than the growing melt. If the velocity of the location of the contaminant is slow enough, the melt will overrun and vaporize the contaminant. Then, the contaminant will either be directed to the off-gas treatment system or be destroyed in the soil near the melt.

The results of the simulation are presented in terms of the degree of sorption in soil required to predict that the contaminant is captured by the growing ISV melt. Results are presented for carbon tetrachloride, benzene, and acetone. The results are very favorable for acetone; success in capturing immiscible species such as carbon tetrachloride depend on the organic content of the soil, which affects sorption of organic species.

CONTENTS

SUMMARY	iii
1.0 INTRODUCTION	1.1
2.0 THE ISV PROCESS RELEVANT TO CONTAMINANT TRANSPORT	2.1
2.1 GENERAL BACKGROUND	2.1
2.2 BEHAVIOR OF WATER	2.2
2.3 BEHAVIOR OF ORGANIC SPECIES	2.2
2.4 ANALOGOUS PROCESSES	2.4
3.0 IMPORTANCE OF WATER AND STEAM TRANSPORT	3.1
4.0 TECHNICAL APPROACH TO PREDICT CAPTURE OF VOLATILE CONTAMINANTS	4.1
4.1 DEFINITION OF THE MODEL	4.1
4.2 ASSUMPTIONS	4.2
4.3 DEFINITION OF CAPTURE OF VOLATILE CONTAMINANTS BY ISV	4.4
5.0 SORPTION OF CONTAMINANTS ON SOIL	5.1
6.0 SELECTION OF MODEL PARAMETERS	6.1
7.0 RESULTS OF MODEL CALCULATIONS	7.1
7.1 TABULATED RESULTS	7.1
7.2 BEHAVIOR AT THE BOILING/DRY INTERFACE	7.3
8.0 DISCUSSION	8.1
9.0 CONCLUSIONS	9.1
10.0 REFERENCES	10.1
APPENDIX - TECHNICAL APPROACH AND EQUATIONS	A.1

FIGURES

4.1	Depiction of Water and Steam Transport in the Dry, Boiling, and Diffusion Regions	4.3
4.2	Schematic of Concentration Profile Across a Spherical Shell of Contaminant in Soil	4.4
7.2	Typical Profiles of Saturation and Temperature	7.2

TABLES

7.1	Results of Required Sorption Coefficient Calculations	7.1
7.2	Thickness of Boiling Region as Predicted by Model	7.3

1.0 INTRODUCTION

In situ vitrification (ISV) is an environmental restoration process whereby contaminated soil is immobilized and rendered inert by melting it in place. A large mass of molten soil forms and expands by melting surrounding soil during processing. Gases expelled from the soil are contained under a hood and directed to an off-gas treatment system. The process has been tested at numerous sites including prepared sites in which organic species have been placed. The ability of the process to capture or destroy high boiling point ($>100^{\circ}\text{C}$) organic species such as polychlorinated biphenyls (PCBs) and volatile organic species residing in containers has been demonstrated, but little empirical data exist regarding the ability to capture volatile organic species (boiling point $<100^{\circ}\text{C}$) sorbed in the soil. Therefore, it is useful to develop a model based on first principles that can be used to predict the behavior of volatile contaminants. Even though ISV would not usually be considered a primary treatment alternative for sites containing exclusively volatile organic contaminants, this issue is important when volatile organic species coexist with other target contaminants, such as radionuclides and heavy metals.

Water is an abundant volatile species that is also refractory and hence is not destroyed by the ISV process. Water originally in the volume of soil that is melted is captured by the process as part of the gas expelled by the process. Clearly, processes other than distillation occur that cause water to be overrun and captured by the advancing molten soil. The fate of other volatile species present in small concentrations is not as clear. However, the behavior of water demonstrates that volatile material can be captured by the ISV process. The remaining question is: what are the behaviors of specific volatile contaminants, given that water is expelled from the soil as fast as it is encountered by the advancing melt? The purpose of this report is to predict the fate of volatile contaminants in soil under conditions consistent with those under which water is captured during ISV processing.

2.0 THE ISV PROCESS RELEVANT TO CONTAMINANT TRANSPORT

2.1 GENERAL BACKGROUND

In situ vitrification uses electrical resistance heating to melt soil. In most cases, the required temperatures (e.g., 1600°C) are generated by inserting and lowering an array of four vertical electrodes into the soil. A graphite starter path is placed on the ground surface to electrically connect the electrodes. Electric current is conducted initially through this starter material and begins to heat the surrounding soil. As resistive heating melts the soil, the soil becomes electrically conductive and the melt begins to grow, usually in a large, roughly hemispherical or "teardrop" configuration. The affected soil, rock, and nonvolatile waste materials melt and subsequently cool into a highly inert glass and crystalline block. Details of the ISV process and its various applications are described elsewhere (Buel et al. 1987; Battelle-Northwest 1988).^(a)

Many engineering-, pilot-, and large-scale ISV tests have been conducted by Pacific Northwest Laboratory^(b) for the U.S. Department of Energy (DOE) and industry. As a result of the ISV process, steam and other volatiles are either destroyed (e.g., pyrolyzed) or expelled from the soil, captured in a hood, and conveyed to an off-gas system (Timmerman and Peterson 1990). Non-volatile inorganic species and radionuclides are retained in the molten soil and immobilized once the molten mass has cooled. These successes point to the use of ISV as a permanent treatment option. More than 150 ISV tests have been completed over the past several years, ranging from bench-scale melting of a few kilograms of soil to large-scale tests treating hundreds of tons of soil.

-
- (a) Battelle, Pacific Northwest Laboratories. 1988. Application of In Situ Vitrification to Organic-Contaminated Soils and Sludges. PNWD-1264, position paper prepared by Battelle, Pacific Northwest Laboratories, Richland, Washington.
 - (b) Pacific Northwest Laboratory is operated by Battelle Memorial Institute for the U.S. Department of Energy under Contract DE-AC06-76RLO 1830.

2.2 BEHAVIOR OF WATER

Water is usually the most abundant volatile material in the soil, and hence it is important to understand its behavior during ISV. We would expect similarities between transport of soil, water and other (e.g., organic) volatiles during ISV. A mass balance is much easier to obtain for water than for other volatiles, since the water is removed rather than destroyed and can be captured and measured directly. ISV field testing has shown that essentially all of the water in the soil displaced by melting is removed to the off-gas system. Relocation of water to surrounding soil via vaporization, outward transport of steam, and condensation evidently is not the dominant transport process.

In a large-scale ISV test, the water calculated to be initially present in the melted soil was compared to the water actually collected in the off-gas system during ISV (Buelte and Bonner 1989). This water balance agreed to within ~1%. This accuracy is greater than expected, considering the uncertainty likely in sampling and analyzing the soil moisture content and determining contributions from water in the air pulled into the off-gas system.

In a pilot-scale test conducted at a site contaminated with fuel oil, a similar water mass balance was satisfied to within ~5% (Timmerman and Peterson 1990). This water balance actually showed 5% more water collected in the off-gas system than was originally calculated to be in the soil. However, this error in the balance is reasonable, since initial analyses of the soil moisture content varied significantly. In addition, this mass balance did not include the water content of the ambient air drawn into the off-gas hood; accounting for this water would improve the mass balance.

2.3 BEHAVIOR OF ORGANIC SPECIES

ISV test results indicate that, like water, transport of organic contaminants to surrounding soil is negligible. An overall PCB balance for a bench-scale test showed that more than 99.94% of the PCBs were destroyed (or

removed) by the melt.^(a) For this test, a container of sludge containing about 1 wt% PCBs was vitrified. At the end of the test, six soil samples were analyzed for PCBs. Only half of the samples contained detectable amounts of PCBs, and the results were within a factor of three of the detection limit. The highest concentration (250 ppb) was presumed in calculating the amount of PCBs that remained untreated in all the surrounding soil. This conservative calculational approach was the basis for the 99.94% destruction fraction cited above.

PCB destruction (or removal) was demonstrated in an early engineering-scale test (Timmerman 1986). For this test, a container of soil contaminated with about 500 ppm PCBs was vitrified. Almost 20 samples of surrounding soil were obtained after the test. Each sample contained less than 1 ppm PCBs, and most samples contained less than 0.1 ppm PCBs.

In a recent comprehensive test (Liikala 1991), the ability of ISV to capture and remove or destroy PCBs was demonstrated in a carefully monitored engineering-scale test. More than 80 statistically specified surrounding soil samples were taken after the test, which were analyzed using congener specific PCB analytical methods (detection limits ranged from 8 to 65 ppb). No PCBs were detected throughout the soil after the test.

A pilot-scale test for vitrifying soil contaminated with fuel oil (Timmerman and Peterson 1990) also indicated that a high fraction of organics does not migrate away from the melt. The melt did not extend past the contaminated area. Pretest soil samples taken from soil cores showed an organic concentration of 0.1 to 2.5 mg/g, depending on soil position, while only one of the posttest soil analyses showed concentrations greater than 0.5 mg/g. The concentration decreased in the region close to the edge of the melt. There was no indication of a region outside the melt where organic migration would have resulted in a detectably higher concentration than before vitrification.

(a) Reimus, M.A.H. 1988. Feasibility Testing of In Situ Vitrification of New Bedford Harbor Sediments. PNWD-1310, Battelle, Pacific Northwest Laboratories, Richland, Washington.

2.4 ANALOGOUS PROCESSES

The behavior of volatile organic contaminants in a heated system is also illustrated by the performance of an analogous process. Radio frequency in situ heating has been tested as another process for decontamination of soils (Dev et al. 1988). This process also heats soil, although the conditions are much milder than in ISV. Soil temperatures are in the range of 100° to 300°C. Concentrated vaporized contaminants plus steam are recovered at the surface of the soil. Test results have demonstrated that vapor phase transport toward the heated zone occurs resulting in a net reduction of contaminant concentration in the soil underlying the heated volume. The process removes 90% to 99% of fuels and solvents and 72% to 99% of PCB 1242. The removal of PCBs may have been limited because the PCBs were only partially vaporized at the relatively low soil temperature.

3.0 IMPORTANCE OF WATER AND STEAM TRANSPORT

The transport of volatile contaminants is influenced by the transport of water. During ISV, water boils to steam. The ensuing steam flow causes convective transport in the gas phase to be more important than diffusive transport, as illustrated below. In the liquid phase, the diffusion coefficient is much smaller than in the gas phase, and virtually any convective transport of water will dominate the transport of contaminants dissolved in the water. Therefore, understanding contaminant transport also requires understanding steam and water transport.

Water is abundant in the soil, occupying a significant fraction (e.g., 20%) of the void space. The conversion of water to steam at 100°C and 1 atm results in a volume change from 1 cm³/g to 1700 cm³/g. This expansion can result in a significant velocity in the vapor phase. Therefore, any transport of volatiles in this phase will include both a diffusive and a convective contribution.

The relative importance of convective-to-diffusive transport is characterized by the Peclet number:

$$Pe = \frac{v L}{D_{AB}} \quad (3.1)$$

where v is the superficial vapor phase velocity, L is a characteristic length over which the transport occurs, and D_{AB} is the mass diffusivity in the vapor phase. We are interested in transport over the thermally affected region near the advancing melt front; the order of magnitude of its length is 100 cm. The mass diffusivity in the vapor phase will be on the order of 0.3 cm²/s at the boiling point of water. Hence, the Peclet number will be on the order of 300 v , where v is in cm/s. This means that if the vapor phase velocity is on the order of only 1/300 cm/s, then convective transport will be comparable to diffusive transport. As the velocity increases, its importance relative to diffusion increases proportionately.

An order-of-magnitude estimate of the steam velocity in the vapor phase is found by assuming that water boils at a rate matching the rate of advance of the melt front. From the conservation of mass, the superficial velocity (i.e., based on total cross sectional area of the porous medium) of steam is:

$$v = v_m s \epsilon \frac{\rho_L}{\rho_V} \quad (3.2)$$

where v_m = velocity of advance of the melt

s = volume fraction saturation of water in the void space

ϵ = void fraction

ρ_L = density of liquid (water)

ρ_V = density of vapor (steam).

During a recent test at Oak Ridge National Laboratory (ORNL) (Spalding and Jacobs 1989), a melt with a volume of 23.7 m³ was formed in 110 h. Assuming a hemispherical melt as a simplified model and assuming that the growth rate of its volume is constant, the growth rate of the melt was 28.6 cm³/s and the final rate of advance of the melt, v_m , was 1.9 x 10⁻⁴ cm/s (0.27 in./h), compared to 5.7 x 10⁻⁴ cm/s (0.8 in./h) averaged over the duration of the test.

For the ORNL test results, $\epsilon = 0.47$ and $s = 0.2$ (calculated from ϵ and a reported 7 wt% water). This gives $v \sim 0.1$ cm/s and the Peclet number is 30. Therefore, we expect convective transport of volatiles to dominate diffusive transport in moist soils, and understanding and quantifying the transport of volatile contaminants depends on understanding and quantifying the transport of steam. Since the flow of steam is ultimately upward into the off-gas system, the removal of volatile contaminants may be essentially a matter of steam stripping, especially for the more volatile (<100°C boiling point) species.

4.0 TECHNICAL APPROACH TO PREDICT CAPTURE OF VOLATILE CONTAMINANTS

4.1 DEFINITION OF THE MODEL

To develop a tractable model, we define three regions in the soil near an advancing ISV melt. Adjacent to the melt is the *dry region* where there is no liquid water in the void space. In this region steam flows inward (since water is captured), and any contaminants in the gas phase will be swept toward the melt and ultimately into the off-gas system. Adjacent to the dry region is the *boiling region* where water boils to form steam, which entirely occupies the void space. The concentration of air in this region is zero. Transport in the gas phase is by convection driven by a pressure gradient. Adjacent to the boiling region is the *diffusion region* where the gas pressure is constant and independent of temperature, and transport in the gas phase is by diffusion only. In addition, furthest from the melt is the *ambient region* where all gradients are essentially zero.

Once a volatile species reaches the interface between the boiling region and dry region, the inward flow of steam will carry the species toward the melt where either it or its pyrolysis products will be carried upward with steam into the hood and then into the off-gas system. Therefore, we must determine if volatile species can transport across the diffusion region to the boiling region, or across the boiling region to the interface with the dry region. These determinations require a model of:

- the effect of the advancing melt front
- the transport of water and steam
- the transport of volatile species within the water and steam
- the distribution of volatile species between steam and water
- the distribution (sorption) of volatile species between water and soil
- the transport of enthalpy (heat).

4.2 ASSUMPTIONS

To provide a tractable model, we make the following assumptions:

1. Water is expelled from the soil as steam as quickly as it is vaporized by the advancing melt (a constraint imposed for consistency with the observation that most of the water is captured).
2. The melt grows as a hemisphere with the flat face upward; the center of the flat face is a center of symmetry.
3. All transport behavior surrounding the melt is spherically symmetric. All variables can be represented as functions of only the radius from the center of the face of the hemisphere. Accordingly, the effect of gravity on liquid water transport is neglected. The dry region, boiling region, and diffusion region take the form of finite hemispherical shells surrounding the melt.
4. The volumetric growth rate of the melt is constant. This corresponds roughly to providing constant power to the melt, since the volume melted generally increases linearly with the energy provided.
5. In the boiling region, the gas pressure is in equilibrium with water boiling from the void space at the local temperature.
6. In the diffusion region, the partial pressure of water is assumed to be that of saturated steam at the local temperature.
7. Air is assumed to be expelled out into surrounding soil by the ISV process; no air flows from the void space in the soil into the off-gas. This imposes a outward mass flux of air matching the outward growth of the melt.
8. We assume the transport of water and steam is adequately described by the expressions for Darcy's law, capillary pressure, and relative permeability found by Udell (1985) to describe a steady-state heat pipe operating in porous media.
9. A volatile contaminant is present at infinite dilution. It is distributed as a spherically symmetric shell outside the melt. The concentration varies across the shell as a Dirac delta function (a "bell-shaped" profile with vanishing "tails"). The peak value, half-width, and location of the mid-point of the concentration profile are assumed to be functions of time.
10. The vapor pressure of the volatile contaminant at concentrations in water less than the miscibility limit is described by the "two-suffix Margules" expression for the activity coefficient relative to Raoult's law. This involves a single adjustable parameter that

we estimate by equating the partial pressure of the volatile contaminant at its miscibility limit to its vapor pressure.

The technical approach, including conservation laws and resulting equations, is described in the Appendix. An initial value problem comprising a set of nonlinear, coupled differential equations is developed. The differential equations are integrated over distance both inward (boiling region) and outward (diffusion region) from the boiling/diffusion interface to predict the profiles of temperature and liquid saturation. The profiles are used to determine the transport of steam and water, which in turn are used to characterize the transport of a volatile contaminant and to predict its fate during ISV. Transport behavior of water and steam are depicted qualitatively in Figure 4.1.

FIGURE 4.1. Depiction of Water and Steam Transport in the Dry, Boiling, and Diffusion Regions

4.3 DEFINITION OF CAPTURE OF VOLATILE CONTAMINANTS BY ISV

The predicted ability of the ISV process to capture a volatile contaminant depends on the velocity of the location of the assumed contaminant shell relative to the velocity of the melt front: if the velocity of the shell relative to the melt is negative, the contaminant is overrun and captured by the melt. Therefore, our technical approach is to determine the velocity of the location of the assumed contaminant shell relative to the velocity of the melt. The contaminant profile, the distance between the melt and the mid-plane of the contaminant shell, and the height and width of the profile are depicted in Figure 4.2, which is explained further in the Appendix.

FIGURE 4.2. Schematic of Concentration Profile Across a Spherical Shell of Contaminant in Soil. Distances are in terms of the volumetric variable x (see Appendix for further explanation).

5.0 SORPTION OF CONTAMINANTS ON SOIL

Of the processes directly involving contaminants--vapor-liquid equilibrium and partitioning between water and soil--data are much more readily available for the former, which can be inferred from vapor pressure and solubility data. Partitioning of contaminants between water and specific soils must be determined directly by experiment. Data were found for carbon tetrachloride, benzene, and acetone in terms of coefficients normalized for organic carbon in the soil. To estimate an effective distribution coefficient, the first coefficient is corrected by multiplying by the fractional organic content of the soil. Unfortunately, this fractional organic content must be determined for each soil.

Uncorrected (normalized) partition coefficients K_{oc} for two species considered in this study are as follows (Mabey et al. 1982):

carbon tetrachloride	439 (dimensionless)
benzene	65 (dimensionless).

We define a distribution coefficient k_{sc} as the ratio of contaminant mass per volume of soil divided by the mass fraction of contaminant in water contacting the soil. This is related to K_{oc} above by the following relation:

$$k_{sc} = \frac{\rho_L}{\rho_S} f_{oc} K_{oc} \quad (5.1)$$

where ρ_L is the density of water, ρ_S is the bulk density of the soil, and f_{oc} is the mass fraction of organic carbon in the soil. For example, if the bulk density of the soil is 2.0 and the organic carbon content is 10%, we would estimate k_{sc} is about 22 for carbon tetrachloride and 3.2 for benzene. Unfortunately, the effect of increasing temperature on the sorption coefficient is unknown. Since sorption tends to be an entropic rather than an energetic process, the effect of temperature is not necessarily large.

6.0 SELECTION OF MODEL PARAMETERS

The region outside the melt is considered either a water-steam equilibrium region or a constant pressure region. This simplifies the analysis: the partial pressure of air needs to be considered only where the total pressure is constant, and the total pressure needs to be considered only where it is determined by water vapor-liquid equilibrium. However, this approach requires that boundary conditions on temperature and concentration of liquid water be specified independently, since neither simplified analysis relates temperature, water concentration, and total pressure simultaneously. The temperature at the boiling/diffusion interface was set at 100°C, the normal boiling point of water.

To satisfy the specification that water is expelled as fast as it is vaporized by the advancing melt, there cannot be an appreciable accumulation of water in the form of a saturation profile in the boiling and diffusion regions that is significantly above the ambient saturation. We found that this is satisfied for a range of permeabilities if the liquid saturation boundary condition (i.e., at the boiling/diffusion boundary) is very nearly the ambient saturation. Therefore, we set the boundary condition at a small increase (0.001) above the ambient saturation for all cases. This removed the boundary condition as an independent parameter in the sensitivity analysis.

The parameters investigated are as follows:

1. Permeability. This parameter relates the pressure gradient required to force a single fluid through the soil at a given velocity. Permeabilities can vary by orders-of-magnitude. Values in the range $1e-9$ to $1e-5$ were investigated for clay-like soil to very porous sand, respectively. As the permeability increases, the predicted thickness of the boiling region increases. At the largest permeability considered, the predicted thickness of the boiling (isothermal) region was on the order of one-half-meter thick, a thickness that can be inferred from thermocouple data (Spalding and Jacobs 1989).
2. Ambient Saturation. This is the volume fraction of water in the void space of the soil at all locations in and around the vitrification area before processing and far from the melt before and

after processing. Values of 10, 20, and 30 vol% were considered; ambient saturations can vary considerably.

3. Radius to the Boiling/Diffusion Interface. This was taken to approximate the radius to the melt surface, which varies depending on the scale of the application. Values of 2, 3, and 5 m were considered, which correspond roughly to pilot- and full-scale applications.
4. Growth Rate of the Melt Volume. Values of 100, 200, and 400 cm³/sec were considered. These correspond to melt front velocities on the order of 1 in./h, which is typical for ISV applications.
5. The Identity of the Volatile Contaminant. Carbon tetrachloride, benzene, and acetone were considered. The first two are volatile and fairly immiscible in water, while acetone is volatile and miscible. As discussed above, information was limited for the sorption properties of carbon tetrachloride and benzene; no information was found for acetone. The vapor-liquid equilibrium over water was estimated using vapor pressure and solubility data and a one-parameter correlation for the activity coefficient in water.

The results are determined in terms of the sorption coefficient, k_{sc} , predicted to be required for the distance to decrease with time between the location of the contaminant shell and the melt, corresponding to the advancing melt overrunning the contaminant.

7.0 RESULTS OF MODEL CALCULATIONS

7.1 TABULATED RESULTS

The results in terms of required sorption coefficient are presented in Table 7.1, which lists the predicted value of k_{sc} required for the melt to overrun the contaminant for the listed model parameters. A plot of typical saturation and temperature profiles is shown in Figure 7.1. It is apparent from the table that:

- the predicted sorption coefficient required to cause net inward transport of volatiles in the boiling region is much larger than in the diffusion region
- the predicted sorption coefficient for the boiling region is nearly insensitive to soil parameters (permeability, ambient saturation), process parameters (rate of growth and radius of melt), and assumed saturation at the outer boundary of the boiling region, s_0

TABLE 7.1. Results of Required Sorption Coefficient Calculations

Species	Permeability, cm ²	s_{∞}	dR ₃ /dt cm ³ /sec	R ₀ , cm	s_0	Required k_{sc}	
						Boiling	Diffusion
CCl ₄	1e-05	0.2	200	300	0.201	20.67	4.48
CCl ₄	1e-06	0.2	200	300	0.201	20.76	4.49
CCl ₄	1e-07	0.2	200	300	0.201	21.04	4.52
CCl ₄	1e-08	0.2	200	300	0.201	21.88	4.61
CCl ₄	1e-09	0.2	200	300	0.201	24.07	4.92
CCl ₄	1e-07	0.1	200	300	0.101	20.28	5.88
CCl ₄	1e-07	0.3	200	300	0.301	22.70	3.32
CCl ₄	1e-07	0.2	100	300	0.201	20.93	4.43
CCl ₄	1e-07	0.2	400	300	0.201	21.09	4.56
CCl ₄	1e-07	0.2	200	200	0.201	21.08	4.55
CCl ₄	1e-07	0.2	200	500	0.201	20.97	4.46
CCl ₄	1e-07	0.2	200	300	0.300	21.13	3.09
Benzene	1e-07	0.2	200	300	0.201	11.05	2.61
Acetone	1e-07	0.2	200	300	0.201	0.07	0.01

FIGURE 7.1. Typical Profiles of Saturation and Temperature.
 Permeability = $1e-7 \text{ cm}^2$, $s_{\infty} = 0.2$, s_0 , $R^0 = 300 \text{ cm}$,
 $dR^3/dt = 200 \text{ cm}^3/\text{sec}$

- the predicted sorption coefficient is sensitive to the identity of the contaminant species (through its vapor-liquid equilibrium and miscibility characteristics).

The thickness of the boiling region can be up to one meter, as inferred from measurements taken by spatially distributed thermocouples during ISV tests. The thickness predicted by the model for this report is presented in Table 7.2 in terms of the same parameters listed in Table 7.1. The last column lists the predicted thickness of the boiling region. The values range up to 0.5 m for the largest permeability (10^{-5} cm^2), but most of the predicted values are ~15 cm or less. If the assumed value of the liquid saturation at the interface between the boiling and diffusion regions is increased to 0.1 above the ambient value, the predicted thickness of the boiling region

TABLE 7.2. Thickness of Boiling Region as Predicted by Model

Permeability, cm ²	s_{∞}	dR^3/dt cm ³ /sec	R_0 , cm	s_0	Thickness, cm
1e-05	0.2	200	300	0.201	52.29
1e-06	0.2	200	300	0.201	21.83
1e-07	0.2	200	300	0.201	6.20
1e-08	0.2	200	300	0.201	1.99
1e-09	0.2	200	300	0.201	0.64
1e-07	0.1	200	300	0.101	0.98
1e-07	0.3	200	300	0.301	10.29
1e-07	0.2	100	300	0.201	13.61
1e-07	0.2	400	300	0.201	3.27
1e-07	0.2	200	200	0.201	2.85
1e-07	0.2	200	500	0.201	17.00
1e-07	0.2	200	500	0.300	47.04

increases substantially. However, we find this also increases the predicted fraction of water encountered by the melt that remains in the soil (primarily in the diffusion region), so it is not clear if the model is sufficient to explain both a thick boiling region and the capture of most of the water. Nevertheless, the predicted required sorption coefficient is not affected substantially as the soil parameters are varied.

7.2 BEHAVIOR AT THE BOILING/DRY INTERFACE

The results for the boiling region require some interpretation. The predicted required value of k_{sc} is found to decrease as one moves inward from the outside boundary (boiling/diffusion interface) of the boiling region, and then increase suddenly (e.g., more than an order of magnitude) as one approaches the inside (boiling/dry interface). The increase is caused by the extreme gradient in liquid saturation near the inside boundary as the saturation drops rapidly toward zero. The diffusivity depends on the liquid saturation, and the gradient in the diffusivity contributes to the predicted required value of k_{sc} , causing the sudden increase.

The linearized analysis is used to estimate the rate of change of the contaminant shell location, but the result is spurious. If the result were real, and if one considered *only* the location of the contaminant shell, then the contaminant would buildup at the boiling/dry interface. However, the diffusive transport, and the gradient in diffusivity in particular, would also cause the width of the shell to increase, such that it would extend into the dry zone. Also, as one approaches the boiling/dry interface, there will be a transition to an inward steam flow, which would carry the contaminant into the dry zone. We use a particular model of the capillary pressure difference at gas-liquid interfaces in the void volume that does not account for the expected sudden large increase in capillary pressure difference as the saturation approaches zero. The model adequately describes other phenomena, but becomes inaccurate at the boiling/dry interface. Considering both problems--properly accounting for the gradient in diffusivity and recognizing the inward flow of steam at the boiling/dry interface--then, to obtain a meaningful result, the predicted required value of k_{sc} at the boiling/diffusion interface is reported as the maximum for the boiling region.

8.0 DISCUSSION

The predicted sorption coefficient required to capture a contaminant is roughly 20 for carbon tetrachloride and 10 for benzene. Unfortunately, the actual sorption coefficient is unknown. However, from the above trial calculation, a value of 20 for carbon tetrachloride is plausible, but a value of 10 may not be plausible for benzene. The result depends strongly on the organic content of the soil. We assume that for soils with a greater humus content the sorption would be stronger, and the ability to capture volatile organic species would be correspondingly greater. The very small (0.1) predicted coefficient required for acetone suggests sorption may not be needed at all; the acetone might be captured by distribution to the water alone. This is caused by the miscibility of acetone, which reduces its partial pressure over water relative to immiscible species.

The assumption that the distribution of a contaminant between water and soil can be described by an equilibrium coefficient may be conservative. This assumption implies that the release kinetics of the sorbed contaminant from the soil is instantaneous relative to the time of soil passage into and through the boiling region. This time would be on the order of a day for many ISV applications.

Actual desorption behavior in natural materials is sometimes described by a two-phase model involving sorbent retained both at the surface of soil particles and in the interior of particles or of an organic substrate on the particles. In that case, desorption kinetics involving phenomena such as diffusion from micropores in soil particles or diffusion within a solid organic substrate on the soil might be slow enough to prevent substantial volatilization of the contaminant until the soil has reached (relative to the moving melt front) the dry zone. At that point, the temperature begins to substantially exceed the boiling point of water, and the steam flow is inward, causing all subsequently released contaminant to move toward the melt.

9.0 CONCLUSIONS

The following conclusions are based on the simulation described in this report.

- For conditions consistent with the observed capture of water during ISV processing, the combined transport and equilibrium processes associated with heating in soil do not inevitably cause transport of volatile contaminant species away from an advancing melt.
- The ability of ISV to capture particular volatile contaminants depends strongly on the sorption of contaminants on soil. Soils with a large humus content should provide increased sorption and a correspondingly increased ability for capture or destruction of volatile contaminants.
- If simple linear, equilibrium sorption is assumed, the capture of immiscible volatile species such as carbon tetrachloride and benzene is plausible but uncertain, based on model predictions. The effect of temperature on sorption is unknown. Actual sorption behavior must be determined.
- The capture of miscible volatile species such as acetone is expected, since only very slight sorption is required. However, the actual sorption behavior needs to be determined.
- The predicted ability of ISV to capture volatile contaminants does not depend significantly on soil parameters, such as permeability and ambient saturation, or on process parameters, such as size and growth rate of the melt.
- If desorption of contaminants is kinetically limited, the ability of ISV to capture the contaminants would be greater than predicted by the model developed for this report.

10.0 REFERENCES

Buelt, J. L., and W. F. Bonner. 1989. In Situ Vittrification: Test Results for a Contaminated Soil Melting Process. PNL-SA-16584, Pacific Northwest Laboratory, Richland, Washington.

Buelt, J. L., C. L. Timmerman, K. H. Oma, V. F. FitzPatrick, and J. G. Carter. 1987. In Situ Vittrification of Transuranic Waste: An Updated Systems Evaluation and Applications Assessment. PNL-4800, Supplement 1, Pacific Northwest Laboratory, Richland, Washington.

Dev, H., G. C. Sresty, J. E. Bridges, and D. Downey. 1988. "Field Test of the Radio Frequency In Situ Soil Decontamination Process." In Proceedings of the 9th National Superfund Conference, November 28-30, 1988, Washington, D.C. Hazardous Materials Control Research Institute, Silver Springs, Maryland.

Liikala, S. 1991. Engineering-Scale Tests of In Situ Vittrification to PCB and Radioactive Contaminated Soils, presented at the Environmental Remediation 91 Conference: "Cleaning Up the Environment for the 21st Century," Pasco, Washington, September 8-11, 1991. Pacific Testing Laboratories, Seattle, Washington.

Mabey, W. R., J. H. Smith, R. T. Podoll, H. L. Johnson, T. Mill, T.-W. Chou, J. Gates, I. Waight Partridge, H. Jaber, and D. Vandenberg. 1982. Aquatic Fate Process Data for Organic Priority Pollutants. EPA Report No. 440/4-81-014, SRI International, Menlo Park, California.

Spalding, B. P., and G. K. Jacobs. 1989. Evaluation of an In Situ Vittrification Field Demonstration of a Simulated Radioactive Liquid Waste Trench. ORNL/TM-10992, Oak Ridge National Laboratory, Oak Ridge, Tennessee.

Timmerman, C. L. 1986. In Situ Vittrification of PCB-Contaminated Soils. EPRI-CS-4839, Electric Power Research Institute, Palo Alto, California.

Timmerman, C. L., and M. E. Peterson. 1990. Pilot-Scale Testing of In Situ Vittrification of Arnold Engineering Development Center Site 10 Contaminated Soils. PNL-7211, Pacific Northwest Laboratory, Richland, Washington.

Udell, K. S. 1985. "Heat Transfer in Porous Media Considering Phase Change and Capillarity--The Heat Pipe Effect." Int. J. Heat Transfer 28:485.

APPENDIX

TECHNICAL APPROACH AND EQUATIONS

APPENDIX

TECHNICAL APPROACH AND EQUATIONS

A.1 TRANSPORT EQUATIONS FOR THE CONTAMINANT

The transport of a volatile contaminant is controlled by the conservation of mass (contaminant, liquid water, steam, and soil) and of energy (enthalpy). The transient conservation of mass for a contaminant species "C" is described by

$$\frac{\partial \rho'_C}{\partial t} = -\frac{1}{r^2} \frac{\partial}{\partial r}(r^2 n_C) \quad (1)$$

where t = time

r = radius from the center of symmetry

n_C = superficial mass flux of "C"

ρ'_C = the concentration of the contaminant in the soil-liquid-gas system

The prime (') denotes superficial concentration: mass per total system volume. The contaminant is assumed to exist in or on three phases: the solid (soil), liquid (water), and gas (steam or steam and air). The concentration is the sum of the concentrations in the respective phases, as follows:

$$\rho'_C = \rho'_{sC} + \rho'_{LC} + \rho'_{gC} \quad (2)$$

The superficial concentration in the soil depends on the void fraction ϵ and the density of the soil particles ρ_s , and the concentration averaged over the volume (including its surface) of a soil particle is assumed to be proportional to the mass fraction " w_C " of contaminant in water contacting the soil, where k_{sC} is the constant of proportionality (i.e., the sorption coefficient). This gives:

$$\begin{aligned}\rho'_{SC} &= \rho'_S k_{SC} w_C \\ &= (1 - \epsilon) \rho_S k_{SC} w_C\end{aligned}\quad (3)$$

Similarly, the contaminant concentration in the liquid phase is given directly by:

$$\rho'_{LC} = \epsilon s \rho_L w_C \quad (4)$$

where s is the volume fraction of water in the void space, and ρ_L is the density of water. The concentration of contaminant in the gas phase is:

$$\rho'_{gC} = \epsilon (1 - s) \rho_{gC} \quad (5)$$

where ρ_{gC} is the concentration of contaminant in the gas phase. Assuming the ideal gas law applies, the concentration in the gas phase is given by:

$$\rho_{gC} = \frac{P_C(T, w_C)}{R T} = k_{gC}(T) w_C \quad (6)$$

where P_C = partial pressure of the contaminant

T = absolute temperature

R = the gas constant

k_{gC} = a constant of proportionality

The partial pressure is assumed to be in equilibrium with the liquid phase, and that it can be described by an activity coefficient relative to Raoult's law as follows:

$$P_C = \gamma(x, T) x P_o(T) \quad (7)$$

where $\gamma(x, T)$ is the activity coefficient, a function of mole fraction x of contaminant in the liquid phase and temperature T , and P_o is the vapor pressure of the contaminant. Assuming the activity coefficient can be described by the "two-suffix Margules" form gives:

$$\ln \gamma(x, T) = \frac{A}{RT} (1-x)^2 \quad (8)$$

where A is an adjustable parameter. Since the partial pressure is equal to the vapor pressure when the contaminant is at its mole fraction solubility limit, x_{sol} , at temperature T_{sol} , then solving for A gives:

$$\frac{A}{R} = \frac{T_{sol} \ln \left(\frac{1}{x_{sol}} \right)}{(1-x_{sol})^2} \quad (9)$$

Therefore, vapor pressure and solubility information can be combined to provide a rough description of nonideal (immiscible) behavior of the contaminant in water. The mole fraction and mass fraction are related by:

$$w_c = \lim_{x \rightarrow 0} \left[\frac{M_c x}{M_c x + M_w (1-x)} \right] = \frac{M_c}{M_w} x \quad (10)$$

where M_c and M_w are the molecular weights of the contaminant and water, and we consider the limiting case of infinite dilution of the contaminant. Combining the above with $x = 0$ gives

$$k_{gc}(T) = \frac{p_{gc}}{w_c} = \frac{P_c}{w_c RT} = \gamma(0, T) \frac{P_o(T) M_v}{RT} = e^{\left(\frac{A}{RT}\right)} \frac{P_o(T) M_v}{RT} \quad (11)$$

We estimate the vapor pressure of the contaminant using the Antoine equation:

$$\ln P_o(T) = A - \frac{B}{T - C} \quad (12)$$

where A, B, and C are constants tabulated in handbooks for many organic species.

The superficial mass flux of the contaminant includes three parts: convective transport of the species dissolved in the liquid phase, convective transport

of the species mixed in the gas phase, and diffusion in the gas phase. Thus, we have

$$n_c = w_c n_L + \rho_{gc} v_g + j_{gc} \quad (13)$$

where n_L is the superficial mass flux of the liquid phase, v_g is the superficial velocity of the gas phase, and j_{gc} is the diffusive flux of the contaminant species in the gas phase. Because the contaminant is present at infinite dilution, the mass flux is described by Fick's law with a concentration-independent diffusivity, as follows:

$$j_{gc} = -\rho_g D \frac{\partial y_{gc}}{\partial r} \quad (14)$$

$$y_{gc} = \frac{\rho_{gc}}{\rho_g}, \quad \rho_{gc} \ll \rho_g$$

Here, ρ_g is the density of the gas phase, D is the diffusivity of the contaminant in the gas phase, and y_{gc} is the mass fraction of contaminant in the gas phase, which is related to the contaminant and total gas phase densities as shown.

The diffusivity is a function of temperature, void fraction, and liquid saturation, as follows:

$$D(S) = D_o \left(\frac{T}{T_o} \right)^{3/2} \epsilon^{4/3} (1-S)^{10/3} \quad (15)$$

where D_o is the diffusivity in an open gas phase at temperature T_o . The expression accounts for the effect of temperature on the open gas phase diffusivity and the effect of void fraction and liquid saturation on the tortuosity of the diffusion path and occlusion of the diffusion path by the liquid phase (see Falta et al, 1990).

Substitution for ρ'_c and n_c into the conservation of mass gives:

$$\frac{\partial w_c}{\partial t} = h_1 w_c + h_2 \frac{\partial w_c}{\partial x} + h_3 \frac{\partial^2 w_c}{\partial x^2} \quad (16)$$

where h_1 , h_2 , and h_3 are as follows:

$$h_1 = \frac{1}{f_1} \left(\dot{R}^3 \frac{\partial f_1}{\partial x} - \frac{\partial(3r^2 f_2)}{\partial x} + \frac{\partial(3r^2 g_1)}{\partial x} \right) \quad (17)$$

$$h_2 = \frac{1}{f_1} \left(\dot{R}^3 f_1 - 3r^2 f_2 + 3r^2 g_1 + \frac{\partial(3r^2 g_2)}{\partial x} \right) \quad (18)$$

$$h_3 = (3r^2 g_2) \quad (19)$$

where f_1 , f_2 , g_1 , and g_2 are as follows:

$$f_1 = \rho'_s k_{sc} + \rho'_L + \epsilon(1-s) k_{gc} \quad (20)$$

$$f_2 = k_{gc} v_g + n_L \quad (21)$$

$$g_1 = 3r^2 \rho_g D \frac{\partial}{\partial x} \left(\frac{k_{gc}}{\rho_g} \right) \quad (22)$$

$$g_2 = 3r^2 D k_{gc} \quad (23)$$

A.2 EQUATIONS FOR WATER AND STEAM TRANSPORT

The conservation of mass for water vapor in spherical coordinates is:

$$\frac{\partial \rho'_v}{\partial t} = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 n_v) + E \quad (24)$$

where ρ'_v is the superficial mass concentration of water vapor, n_v is the superficial mass flux of water vapor, and E is the evaporation rate of water per unit volume. Similarly, the conservation of mass for liquid water is:

$$\frac{\partial \rho'_L}{\partial t} = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 n_L) - E \quad (25)$$

where ρ'_L is the superficial mass concentration of liquid water and n_L is the superficial mass flux of liquid water. Combining these gives:

$$\frac{\partial}{\partial t} (\rho'_v + \rho'_L) = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 (n_v + n_L)) \quad (26)$$

The conservation of mass for air, where its concentration is not zero (i.e., in the diffusion region), is:

$$\frac{\partial \rho'_A}{\partial t} = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 n_A) \quad (27)$$

where ρ'_A is the superficial mass concentration of air and n_A is the superficial mass flux of air.

The conservation of energy written in terms of enthalpy, H , is:

$$\frac{\partial}{\partial t} (H_v \rho'_v + H_L \rho'_L + H_A \rho'_A) = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 (H_v n_v + H_L n_L + H_A n_A + q)) \quad (28)$$

where the subscripts V, L, and A have the same meaning as above, and q is the conductive heat flux.

The above expressions can be simplified by introducing a new independent spatial variable x :

$$\begin{aligned} x(r, t) &= r^3 - R(t)^3 \\ \therefore r^3 &= (R(t)^3 + x)^{\frac{2}{3}} \end{aligned} \quad (29)$$

Here, $R(t)$ is the radius to the boundary between the boiling and diffusion regions. It is a function of time because the volume of melt grows with time. The variable x is volumetric; i.e. it has units of volume, and is zero at the surface of the melt. Hence, $x = 0$ denotes the location (in volume units) of the surface of the melt. Partial derivatives in r - t coordinates are related to those in x - t coordinates as follows:

$$\begin{aligned} \left(\frac{\partial}{\partial t}\right)_r &= \left(\frac{\partial}{\partial t}\right)_x \left(\frac{\partial t}{\partial t}\right)_r + \left(\frac{\partial}{\partial x}\right)_t \left(\frac{\partial x}{\partial t}\right)_r \\ \left(\frac{\partial}{\partial r}\right)_t &= \left(\frac{\partial}{\partial t}\right)_x \left(\frac{\partial t}{\partial r}\right)_t + \left(\frac{\partial}{\partial x}\right)_t \left(\frac{\partial x}{\partial r}\right)_t \end{aligned} \quad (30)$$

From the definition of x we have:

$$\begin{aligned} \left(\frac{\partial t}{\partial t}\right)_r &= 1 \\ \left(\frac{\partial x}{\partial t}\right)_r &= -\frac{dR^3}{dt} = -\dot{R}^3 \\ \left(\frac{\partial t}{\partial r}\right)_t &= 0 \\ \left(\frac{\partial x}{\partial r}\right)_t &= 3r^2 \end{aligned} \quad (31)$$

Substituting the transformation of partial derivatives into the conservation of mass of water vapor, liquid water, air, and into the conservation of energy gives:

$$\frac{\partial}{\partial t}(\rho'_V + \rho'_L) - \dot{R}^3 \frac{\partial}{\partial x}(\rho'_V + \rho'_L)x = -3 \frac{\partial}{\partial x}(r^2(n_V + n_L)) \quad (32)$$

$$\frac{\partial \rho'_A}{\partial t} - \dot{R}^3 \frac{\partial \rho'_A}{\partial x} = -3 \frac{\partial}{\partial x}(r^2(n_A)) \quad (33)$$

$$\begin{aligned} \frac{\partial}{\partial t}(H_V \rho'_V + H_L \rho'_L + H_A \rho'_A) - \dot{R}^3 \frac{\partial}{\partial x}(H_V \rho'_V + H_L \rho'_L + H_A \rho'_A) \\ = -3 \frac{\partial}{\partial x}(r^2(H_V n_V + H_L n_L + H_A n_A + q)) \end{aligned} \quad (34)$$

A.3 PSEUDO-STEADY STATE APPROXIMATION

The observation that most water originally in the volume of melted soil is captured in the off-gas system signifies that water is removed from the soil as fast as it is encountered by the growing melt. Consequently, the rate at which the mass of water in the soil decreases should equal the product of the growth rate of the melt volume and the nominal superficial mass concentration of water originally characterizing the site. The mass of water in the soil is found by integrating the mass concentration over volume outward from the location R_m of the surface of the melt. Taking the time derivative of this and equating it to the above rate gives:

$$-\frac{d}{dt} \int_{R_m}^{\infty} \rho'_L 2\pi r^2 dr = \frac{2\pi}{3} \dot{R}_m^3 \rho'_{L\infty} \quad (35)$$

Differentiating the integral and using $\rho_L'(r = R_m) = 0$ (dry soil next to the melt) gives:

$$\int_{R_m}^{\infty} \left(\frac{\partial \rho_L'}{\partial t} \right)_r 2\pi r^2 dr + \frac{2\pi}{3} R_m^3 \rho_{L\infty}' = 0 \quad (36)$$

The partial derivative can be converted to x-t coordinates and dr written in terms of dx to give:

$$\frac{2\pi}{3} \int_0^{\infty} \left(\frac{\partial \rho_L'}{\partial t} \right)_x dx - \frac{2\pi}{3} R_m^3 \int_0^{\infty} \left(\frac{\partial \rho_L'}{\partial x} \right)_t dx + \frac{2\pi}{3} R_m^3 \rho_{L\infty}' = 0 \quad (37)$$

The second integral is just $\rho_L'(\infty) - \rho_L'(0) = \rho_{L\infty}'$, which cancels the last term. Therefore, we have:

$$\int_0^{\infty} \left(\frac{\partial \rho_L'}{\partial t} \right)_x dx = 0 \quad (38)$$

For this to be true ρ_L' must be a function of x but not t. Therefore, the saturation can be a function of x only, and since the transport processes are linked, the observation that water is captured as fast as it is encountered leads to:

$$\left(\frac{\partial}{\partial t} \right)_x = 0 \quad (39)$$

One consequence of this pseudo-steady state approximation is that the volume between the melt and the boiling-diffusion interface is constant, and hence the time derivative of R_m^3 equals that of R^3 . Consequently, we need consider

only the derivative of R^3 . Using the above relations, the conservation of masses and conservation of energy simplify to give:

$$\frac{\partial}{\partial x} [\dot{R}^3 (\rho'_V + \rho'_L) - 3r^2 (n_V + n_L)] = 0 \quad (40)$$

$$\frac{\partial}{\partial x} [\dot{R}^3 \rho'_A - 3r^2 n_A] = 0 \quad (41)$$

$$\frac{\partial}{\partial x} [\dot{R}^3 (H_V \rho'_V + H_L \rho'_L + H_A \rho'_A) - 3r^2 (H_V n_V + H_L n_L + H_A n_A + q)] = 0 \quad (42)$$

These expressions can be integrated from $x = 0$ to $x = \infty$ to give the following form:

$$\int_0^{\infty} \left(\frac{\partial}{\partial x} [\dot{R}^3 (\rho'_V + \rho'_L) - 3r^2 (n_V + n_L)] \right) dx = 0 \quad (43)$$

We assume that far from the melt the mass flows of water vapor and liquid water vanish, such that the mass fluxes behave as follows:

$$\begin{aligned} \lim_{r \rightarrow \infty} (3r^2 n_V) &\rightarrow 0 \\ \lim_{r \rightarrow \infty} (3r^2 n_L) &\rightarrow 0 \end{aligned} \quad (44)$$

Substitution then gives:

$$\dot{R}^3 (\rho_V - \rho'_{V\infty} + \rho'_L - \rho'_{L\infty}) - 3r^2 (n_V + n_L) = 0 \quad (45)$$

We assume that the mass flow of air relative to the moving melt front is zero everywhere; i.e., no air originally in the soil is captured by the ISV

process. Consequently,

$$[\text{mass flow of air}]_x = \left[\frac{\partial \left(\frac{2\pi}{3} r^3 \right)}{\partial t} \rho_A \right]_x - [2\pi r^2 n_A]_x \quad (46)$$

Since

$$\left[\frac{\partial(r^3)}{\partial t} \right]_x = \dot{R}^3 \quad (47)$$

then we have:

$$\begin{aligned} \dot{R}^3 \rho'_A &= 3 r^2 n_A \\ \dot{R}^3 \rho'_{A\infty} &= (3 r^2 n_A)_\infty \end{aligned} \quad (48)$$

Substituting this result into the conservation of energy gives:

$$\begin{aligned} \dot{R}^3 (H_V \rho'_V - H_{V\infty} \rho'_{V\infty} + H_L \rho'_L - H_{L\infty} \rho'_{L\infty} + H_A \rho'_A - H_{A\infty} \rho'_{A\infty}) \\ - 3 r^2 (H_V n_V + H_L n_L + H_A n_A + Q) + (3 r^2 n_A)_\infty = 0 \end{aligned} \quad (49)$$

A.4 FLUX RELATIONS

The velocity of the gas phase is given by Darcy's law as follows:

$$v_G = - \frac{k k_{rV}}{\mu_V} \frac{\partial P}{\partial r} \quad (50)$$

where k = absolute (dry) permeability of the soil

k_{rV} = relative permeability for vapor transport

μ_V = viscosity of the vapor

P = pressure in the gas phase

Similarly, Darcy's law for liquid transport is:

$$v_L = - \frac{k k_{rL}}{\mu_L} \frac{\partial}{\partial x} (P - P_{cap}) \quad (51)$$

where the subscript L denotes liquid in the corresponding symbols, and P_{cap} is the capillary pressure difference between the gas and liquid phases.

Following Udeli (1985), we use a dimensionless expression to describe the capillary pressure difference:

$$\begin{aligned} P_{cap} &= \frac{\sigma}{\sqrt{k/\epsilon}} f(s') \\ s' &= \frac{s - s_{irr}}{1 - s_{irr}} \end{aligned} \quad (52)$$

where s = liquid saturation (the volume fraction of liquid in the void space)

σ = the surface tension at the liquid-gas interface

$f(s')$ = a dimensionless capillary pressure function

s' = modified saturation

s_{irr} = irreducible saturation, a characteristic of the soil

Again following Udeli, the relative permeabilities are also functions of s' , as follows (Fatt and Klikoff, 1959):

$$\begin{aligned} k_{rL} &= (s')^3 \\ k_{rG} &= (1 - s')^3 \end{aligned} \quad (53)$$

The vapor pressure in equilibrium with the boiling water is given by the Kelvin equation:

$$P_v(T, s) = P_{sat}(T) e^{-\frac{P_{cap}(s) V_L}{RT}} \quad (54)$$

where P_{sat} is the pressure of saturated water vapor, and V_L is the molar volume

of water. The vapor pressure is calculated using the Antoine equation, as follows:

$$\ln P_{sat}(T) = A_w + \frac{B_w}{T + C_w} \quad (55)$$

Following Udell, we use for the dimensionless capillary pressure the function (Leverett, 1941):

$$\begin{aligned} f(s) &= a_1(1-s') + a_2(1-s')^2 + a_3(1-s')^3 \\ a_1 &= 1.417 \\ a_2 &= -2.120 \\ a_3 &= 1.263 \end{aligned} \quad (56)$$

where s' has the same meaning as before. The s -derivative of $f(s)$ is given by:

$$\begin{aligned} f'(s) &\equiv \frac{df}{ds} = \frac{df}{ds} \frac{ds}{ds'} \\ &= [-a_1 - 2a_2(1-s') - 3a_3(1-s')^2] \left(\frac{1}{1-s_{irr}} \right) \end{aligned} \quad (57)$$

Finally, in the boiling region, where there is only water vapor in the gas phase, the mass fluxes of vapor and liquid are related to the above expressions by:

$$\begin{aligned} n_L &= \rho_L V_L \\ n_V &= \rho_V V_G \end{aligned} \quad (58)$$

where the densities are of the liquid and gas in the void space (i.e., they are not superficial mass concentrations).

A.5 DIFFERENTIAL EQUATIONS FOR TEMPERATURE AND SATURATION

A.5.1 Boiling Region

In the boiling region, we have the following equations describing the conservation of mass and energy:

$$\begin{aligned} \dot{R}^3 (\rho'_V - \rho'_{V\infty} + \rho'_L - \rho'_{L\infty}) - 3r^2 (n_V + n_L) + 3r_\infty^2 (n_{V\infty} + n_{L\infty}) &= 0 \\ \dot{R}^3 [(\rho'_S C_{pS} + \rho'_{V\infty} C_{pV} + \rho'_{L\infty} C_{pL}) (T - T_\infty) - (\rho'_L - \rho'_{L\infty}) \Delta H_V] & \\ - 3r^2 (-\Delta H_V n_L + q) + 3r_\infty^2 (-n_{V\infty} C_{pV} + n_{L\infty} C_{pL}) (T - T_\infty) + q_\infty &= 0 \end{aligned} \quad (59)$$

The superficial mass concentrations are given by:

$$\begin{aligned} \rho'_V &= \epsilon (1-s) \rho_V(T) \\ \rho'_{V\infty} &= \epsilon (1-s_\infty) \rho_V(T_\infty) \\ \rho'_L &= \epsilon s \rho_L \\ \rho'_{L\infty} &= \epsilon s_\infty \rho_L \end{aligned} \quad (60)$$

Substitution for fluxes, derivatives, and superficial mass concentration gives the following sequence of equations. First, the fluxes are written in the following form:

$$\begin{aligned} n_L &= \alpha_{LT}(T, s) 3r^2 \frac{dT}{dx} + \alpha_{Ls}(T, s) 3r^2 \frac{ds}{dx} \\ n_V &= \alpha_{VT}(T, s) 3r^2 \frac{dT}{dx} + \alpha_{Vs}(T, s) 3r^2 \frac{ds}{dx} \\ q &= \alpha_{QT}(s) 3r^2 \frac{dT}{dx} \end{aligned} \quad (61)$$

Next, a set of functions f are defined as follows:

$$\begin{aligned}
f_{10} &= \dot{R}^3 \epsilon (\rho_V - \rho_{V\infty} + \rho_L (S - S_\infty)) \\
f_{1T} &= -\alpha_{VT} - \alpha_{LT} \\
f_{1S} &= -\alpha_{VS} - \alpha_{LS} \\
f_{20} &= \dot{R}^3 [(1-\epsilon) \rho_S C_{pS} + \epsilon (1-S_\infty) \rho_{V\infty} C_{pV} + \epsilon \rho_L S_\infty C_{pL}] (T - T_\infty) \\
&\quad - \epsilon \rho_L (S - S_\infty) \Delta H_V + 3r_\infty^2 (n_{V\infty} C_{pV} + n_{L\infty} C_{pL}) (T - T_\infty) + q_\infty \\
f_{2T} &= \Delta H_V \alpha_{LT} - \alpha_{OT} \\
f_{2S} &= \Delta H_V \alpha_{VS}
\end{aligned} \tag{62}$$

Finally, the conservation of mass and energy are written in the form:

$$\begin{aligned}
f_{10}(T, S) + f_{1T} 9r^4 \frac{dT}{dx} + f_{1S}(T, S) 9r^4 \frac{dS}{dx} &= 0 \\
f_{20}(T, S) + f_{2T} 9r^4 \frac{dT}{dx} + f_{2S}(T, S) 9r^4 \frac{dS}{dx} &= 0
\end{aligned} \tag{63}$$

This pair of equations is solved for the T - and S -derivatives to provide a pair of coupled, nonlinear, ordinary differential equations. The differential equations are integrated from the outer boundary condition at $x = 0$ in the negative x -direction until the saturation approaches zero, which defines the inner boundary of the boiling region.

In the boiling region, there is no air, and pressure gradients cause flow of the gas phase, so that:

boiling:

$$\begin{aligned}
n_V &= -\rho_V \frac{k k_{rG}}{\mu_V} \left(\frac{\partial P_V}{\partial T} \frac{\partial T}{\partial r} + \frac{\partial P_V}{\partial S} \frac{\partial S}{\partial r} \right) \quad [j_V = 0] \\
n_L &= -\rho_L \frac{k k_{rL}}{\mu_L} \left(\frac{\partial P_V}{\partial T} \frac{\partial T}{\partial r} + \frac{\partial P_V}{\partial S} \frac{\partial S}{\partial r} - \frac{\partial P_{cap}}{\partial S} \frac{\partial S}{\partial r} \right)
\end{aligned} \tag{64}$$

Therefore, for the boiling region the alpha coefficients are as follows:

$$\begin{aligned}
 \alpha_{VT} &= -\rho_V \frac{k k_{rG}}{\mu_V} \frac{\partial P_V}{\partial T} \\
 \alpha_{VS} &= -\rho_V \frac{k k_{rG}}{\mu_V} \frac{\partial P_V}{\partial S} \\
 \alpha_{LT} &= -\rho_L \frac{k k_{rL}}{\mu_L} \frac{\partial P_V}{\partial T} \\
 \alpha_{LS} &= -\rho_L \frac{k k_{rL}}{\mu_L} \left(\frac{\partial P_V}{\partial S} - \frac{\partial P_{cap}}{\partial S} \right)
 \end{aligned} \tag{65}$$

The derivatives of the pressure of the vapor phase are:

$$\begin{aligned}
 \frac{\partial P_V}{\partial T} &= \left[\frac{\partial P_{sat}}{\partial T} + P_{sat} \left(\frac{P_{cap} V_L}{RT^2} \right) \right] e^{\left(\frac{-P_{cap} V_L}{RT} \right)} \\
 \frac{\partial P_V}{\partial S} &= -P_{sat} e^{\left(\frac{-P_{cap} V_L}{RT} \right)} \left(\frac{\partial P_{cap}}{\partial S} \frac{V_L}{RT} \right)
 \end{aligned} \tag{66}$$

A.5.2 Diffusion Region

The conservation laws for the mass of liquid water and steam in the diffusion region are:

$$\begin{aligned}
 \dot{R}^3 (\rho'_V + \rho'_L - \rho'_{L\infty}) - 3r^2 n_V - 3r^2 n_L &= 0 \\
 \dot{R}^3 [(\rho'_S C_{pS} + \rho'_{L\infty} C_{pL}) (T - T_\infty) - (\rho'_L - \rho'_{L\infty}) \Delta H_V] \\
 + \Delta H_V 3r^2 n_L - 3r^2 q &= 0
 \end{aligned} \tag{67}$$

The mass flux of vapor in the diffusion region is found from:

$$n_v = \frac{\rho_v}{\rho_v + \rho_A} (n_v + n_A) + j_v \quad (68)$$

$$n_v \left(1 - \frac{\rho_v}{\rho_v + \rho_A} \right) = n_v \left(\frac{\rho_A}{\rho_v + \rho_A} \right) = n_A \left(\frac{\rho_v}{\rho_v + \rho_A} \right) + j_v$$

The diffusive flux of vapor, j_v , is found from Fick Law:

$$j_v = -\rho_g D \frac{\partial y_v}{\partial r}, \quad P_v < P \quad (\text{diffusion}) \quad (69)$$

$$j_v = 0, \quad P_v = P \quad (\text{boiling})$$

where the diffusivity D is for interdiffusion of air and water vapor, and y_v is the mass fraction of vapor in the gas phase (which is unity in the boiling region). The mass fraction is related to the vapor pressure P_v by:

$$y_v = \frac{\rho_v}{\rho_v + \rho_A} = \frac{M_v P_v}{M_v P_v + M_A (P - P_v)} \quad (70)$$

Therefore, the spatial derivative of the mass fraction is:

$$\begin{aligned} \frac{\partial y_v}{\partial r} &= \frac{M_v (\partial P_v / \partial r)}{M_v P_v + M_A (P - P_v)} - \frac{M_v P_v}{(M_v P_v + M_A (P - P_v))^2} (M_v - M_A) (\partial P_v / \partial r) \\ &= \frac{M_v M_A P}{(M_v P_v + M_A (P - P_v))^2} \frac{\partial P_v}{\partial r} \end{aligned} \quad (71)$$

In the diffusion region, the soil does not approach zero saturation, and we can neglect the effect of liquid concentration (saturation) in the porous solid on the vapor pressure of water in the void space. Then, in the diffusion region, the vapor pressure becomes a function of temperature only,

so that:

$$\frac{\partial P_v}{\partial r} = \frac{dP_v}{dT} \frac{\partial T}{\partial r} \quad (72)$$

Substituting for the temperature derivative gives:

$$\frac{\partial y_v}{\partial r} = \frac{M_v M_A P}{(M_v P_v + M_A (P - P_v))^2} \frac{dP_v}{dT} \frac{\partial T}{\partial r} \quad (73)$$

Substituting for the spatial derivative of the mass fraction gives:

$$j_v = - \frac{D}{RT} \frac{M_v M_A P}{M_v P_v + M_A (P - P_v)} \frac{dP_v}{dT} \frac{\partial T}{\partial r} \quad (74)$$

Substituting for the diffusive flux gives:

$$\begin{aligned} n_v \left(\frac{\rho_A}{\rho_v + \rho_A} \right) &= \frac{\dot{R}^3 \epsilon (1-s)}{3r^2} \rho_A \left(\frac{\rho_v}{\rho_v + \rho_A} \right) \\ &\quad - \frac{D}{RT} \frac{M_v M_A P \left(\frac{dP_v}{dT} \right)}{M_v P_v + M_A (P - P_v)} 3r^2 \frac{dT}{dx} \\ \therefore n_v &= \frac{M_v P_v}{RT} \frac{\dot{R}^3 \epsilon (1-s)}{3r^2} - \frac{D}{RT} M_v \frac{P \left(\frac{dP_v}{dT} \right)}{P - P_v} 3r^2 \frac{dT}{dx} \end{aligned} \quad (75)$$

Since there is no pressure gradient in the gas phase in the diffusion region, the mass flux of liquid water reduces to:

$$n_L = -\rho_L \frac{k k_{rL}}{\mu_L} \left(- \frac{\partial P_{cap}}{\partial s} \frac{\partial s}{\partial r} \right) \quad (76)$$

The resulting system of equations is analogous to that for the boiling region,

with the following differences. The f functions are:

$$\begin{aligned}
 f_{10} &= \dot{R}^3 (\rho_L - \rho_{L\infty}) \\
 f_{1T} &= -\alpha_{VT} \\
 f_{1s} &= 0 \\
 f_{20} &= \dot{R}^3 [(1-\epsilon) \rho_S C_{PS} + \epsilon S_{\infty} \rho_{L\infty} C_{PL} (T-T_{\infty}) - \epsilon \rho_L (s-s_{\infty}) \Delta H_V] \\
 f_{2T} &= 0 \\
 f_{2s} &= \alpha_{LS}
 \end{aligned} \tag{77}$$

and for the diffusion region the alpha coefficients are:

$$\begin{aligned}
 \alpha_{VT} &= -\frac{D}{RT} M_V \frac{P \left(\frac{dP_V}{dT} \right)}{P - P_V} \\
 \alpha_{VS} &= 0 \\
 \alpha_{LT} &= 0 \\
 \alpha_{LS} &= -\rho_L \frac{k k_{TL}}{\mu_L} \left(-\frac{\partial P_{cap}}{\partial s} \right)
 \end{aligned} \tag{78}$$

A.5.3 Integration

The ordinary differential equations in T and s for both the boiling and diffusion regions are solved by choosing values of s and T as boundary conditions at x = 0. The differential equations were solved using the "improved Euler's method," a simple predictor-corrector method. The calculations were performed as a spreadsheet on a personal computer.

Once T and s are found by integration, their derivatives are used to calculate the mass fluxes in the liquid and gas phases. The profiles of T, s, and the mass fluxes are used to calculate the transport of volatile contaminant species, as is discussed below.

A.6 TREATMENT OF CONTAMINANT CONCENTRATION PROFILE

The volatile contaminant is assumed to reside in a hemispherical shell outside the melt, with the concentration profile described by:

$$\begin{aligned} w_c &= A(t) e^{-u^2} \\ u &= \frac{x - x_o(t)}{\delta(t)} \end{aligned} \quad (79)$$

where $A(t)$ is the peak concentration, $x_o(t)$ is the location (in the x -coordinate system) of the mid-point of the shell, and $\delta(t)$ is the characteristic half-width of the shell (see Figure 4.2). Of particular interest is $x_o(t)$: if its value decreases with time, then the shell grows closer to the melt, signifying that the contaminant will be captured by the ISV process. Therefore, we seek to determine those conditions for which (dx_o/dt) is negative.

Substituting for w_c gives the following relations:

$$\frac{\partial w_c}{\partial x} = -\frac{2u}{\delta} A e^{-u^2} \quad (80)$$

$$\frac{\partial^2 w_c}{\partial x^2} = \left(\frac{4u^2}{\delta^2} - \frac{2}{\delta^2} \right) A e^{-u^2} \quad (81)$$

$$\begin{aligned} & \left[\frac{d \ln A}{dt} + 2u \left(\frac{1}{\delta} \frac{dx_o}{dt} + u \frac{d \ln \delta}{dt} \right) \right] A e^{-u^2} \\ &= h_1 A e^{-u^2} - \frac{2u}{\delta} h_2 A e^{-u^2} + \left(\frac{4u^2}{\delta^2} - \frac{2}{\delta^2} \right) h_3 A e^{-u^2} \end{aligned} \quad (82)$$

where the above expression is the transient conservation of mass for the

contaminant. Setting $u = 0$ in this expression gives:

$$\frac{\partial \ln A}{\partial t} = h_1 - \frac{2}{\delta^2} h_3 \quad (83)$$

The conservation of mass can also be integrated over the thickness of the shell. Since the functional form for $w_c(x)$ vanishes rapidly to either side of the shell, formally we can integrate over x from $-\infty$ to ∞ . This is the zeroeth moment of the integrand. Finally, we can multiply the entire expression by u before integrating, which gives the first moment of the integrand. These result in the appearance of the following integrals:

$$\begin{aligned} I_0 &\equiv \int_{-\infty}^{\infty} e^{-u^2} du \\ I_1 &\equiv \int_{-\infty}^{\infty} e^{-u^2} u du \\ I_2 &\equiv \int_{-\infty}^{\infty} e^{-u^2} u^2 du \\ I_3 &\equiv \int_{-\infty}^{\infty} e^{-u^2} u^3 du \end{aligned} \quad (84)$$

The odd-subscript integrals are zero by symmetry. Considering the zeroeth moment gives:

$$\frac{d \ln \delta}{dt} = \frac{2}{\delta^2} h_3 \quad (85)$$

Considering the first moment gives:

$$\frac{dx_0}{dt} = -h_2 \quad (86)$$

This is the desired expression for the motion of the shell of contaminant

relative to the advancing melt front. Substituting for h_2 , f_2 , g_1 , and g_2 gives:

$$\begin{aligned} \frac{dx_o}{dt} &= -h_2 = -\frac{1}{f_1} \left(\dot{R}^3 f_1 - 3r^2 g_1 + \frac{\partial(3r^2 g_2)}{\partial x} \right) \\ &= -\frac{1}{f_1} \left[\dot{R}^3 f_1 - 3r^2 (k_{gc} v_g + n_L) + 9r^4 \rho_g D \frac{\partial}{\partial x} \left(\frac{k_{gc}}{\rho_g} \right) \right. \\ &\quad \left. + \frac{\partial(9r^4)}{\partial x} D k_{gc} + 9r^4 \left(\frac{\partial D}{\partial x} k_{gc} + D \frac{\partial k_{gc}}{\partial x} \right) \right] \end{aligned} \quad (87)$$

A.7 DETERMINING CONDITIONS FOR CAPTURE OF THE CONTAMINANT

The conditions for which the velocity of the melt is greater than the outward velocity of the location of the contaminant shell correspond to the case:

$$\begin{aligned} 0 &< \dot{R}^3 (\rho'_s k_{sc} + \rho'_L + \epsilon(1-s) k_{gc}) - 3r^2 (k_{gc} v_g + n_L) \\ &+ 9r^4 \rho_g D \frac{\partial}{\partial x} \left(\frac{k_{gc}}{\rho_g} \right) + \frac{\partial(9r^4)}{\partial x} D k_{gc} + 9r^4 \left(\frac{\partial D}{\partial x} k_{gc} + D \frac{\partial k_{gc}}{\partial x} \right) \end{aligned} \quad (88)$$

where we have substituted for f_1 . Solving for k_{sc} gives:

$$\begin{aligned} k_{gc} &> \frac{1}{\dot{R}^3 \rho'_s} \left[(\dot{R}^3 \rho'_L - 3r^2 n_L) + (\dot{R}^3 \epsilon(1-s) - 3r^2 v_g) k_{gc} \right. \\ &\quad \left. + 9r^4 \rho_g D \frac{\partial}{\partial x} \left(\frac{k_{gc}}{\rho_g} \right) + \frac{\partial(9r^4)}{\partial x} D k_{gc} + 9r^4 \left(\frac{\partial D}{\partial x} k_{gc} + D \frac{\partial k_{gc}}{\partial x} \right) \right] \end{aligned} \quad (89)$$

This defines a lower limit for k_{sc} that can be calculated from calculated values of the temperature and saturation profiles and the fluxes and concentrations that depend on them.

REFERENCES

Falta, R. W., K. Pruess, I. Javandel, and P. A. Witherspoon. 1990. Numerical Modeling of Steam Injection for the Removal of Nonaqueous Phase Liquids from the Subsurface, 1. Numerical Formulation. LBL-29615, Lawrence Berkeley Laboratory, University of California, Berkeley, California.

Fatt, I., and W. A. Klikoff. 1959. "Effect of Fractional Wettability on Multiphase Flow Through Porous Media." (AIME Technical Note #2043) *AIME Transactions* 216:246.

Leverett, M. C. 1941. "Capillary Behavior in Porous Solids." *AIME Transactions* 142:142.

Udell, K. S. 1985. "Heat Transfer in Porous Media Considering Phase Change and Capillarity--The Heat Pipe Effect." Int. J. Heat Transfer 28:485.

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

12 DOE/Office of Scientific and
Technical Information

21 DOE Office of Environmental
Restoration and Waste
Management

Trevion II Building
12800 Middlebrook Road
Germantown, MD 20874

ATTN: W. W. Alexander
T. D. Anderson
J. E. Baublitz
D. L. Biancasino
J. O. Boda
J. Coleman
S. P. Cowan
J. J. Flore
C. W. Frank
K. O. Hain
J. M. Lankford
J. C. Lehr
S. C. Lein
J. E. Lytle
S. A. Mann
S. M. Prestwich
M. Shupe
C. H. Sink
L. H. Taylor
H. F. Walter
R. P. Whitfield

2 DOE Albuquerque Operations
Office

P.O. Box 5400
Albuquerque, NM 87115
ATTN: P. A. Saxman
D. H. Bandy

W. Holman
DOE San Francisco Field
Office
1333 Broadway
Oakland, CA 94612

J. Haugen
DOE Chicago Field Office
9800 South Cass Avenue
Argonne, IL 60439

J. Hall
DOE Nevada Field Office
P.O. Box 98518
Las Vegas, NV 89193-8518

R. Tyler
DOE Rocky Flats Office
DOE Building 116
Golden, CO 80402-0928

S. Ketola
DOE West Valley Project
P.O. Box 191
West Valley, NY 14171

W. Fitch
DOE Idaho Operations Office
785 DOE Place
Idaho Falls, ID 83402

M. O'Rear
DOE Savannah River Operations
Office
P.O. Box A
Aiken, SC 29801

4 DOE Oak Ridge Office
P.O. Box 2001
Oak Ridge, TN 37831
ATTN: J. Moore (2)
J. Sweeney (2)

3 Battelle Memorial Institute
505 King Avenue
Columbus, OH 43201
ATTN: W. A. Carbeiner
R. A. Nathan
Technical Library

No. of
Copies

Jesse L. Yow, Jr.
Lawrence Livermore National
Laboratory
7000 East Avenue
Livermore, CA 94550

M.A.H. Reimus
Los Alamos National Laboratory
P.O. Box 1663
Los Alamos, NM 87545

J. Koger
Martin Marietta Energy Systems
P.O. Box 2009
Oak Ridge, TN 37831-8097

P. T. Owen
Martin Marietta Energy Systems
P.O. Box 2003
Oak Ridge, TN 37831-7256

- 8 Oak Ridge National Laboratory
P.O. Box Y
Oak Ridge, TN 37830
ATTN: G. K. Jacobs (4)
M. Naney (2)
B. P. Spalding (2)

K. Nuhfer
Westinghouse Materials Co. of
Ohio
P.O. Box 398704
Cincinnati, OH 45239-8704

- 5 Sandia Laboratories
P.O. Box 5800
Albuquerque, NM 87185
ATTN: D. Berry
R. Knowlton
J. Phelan
L. D. Tyler
Technical Library

No. of
Copies

- 4 EG&G Idaho
P.O. Box 1625
Idaho Falls, ID 83415
ATTN: S. K. Merrill
D. F. Nickelson
R. R. Stiger
S. Stiger

L. Rogers
EG&G Energy Measurements, Inc.
P.O. Box 1912, MS RSL-11
Las Vegas, NV 89125

J. R. Berreth
Westinghouse Idaho Nuclear
Co., Inc.
P.O. Box 4000
Idaho Falls, ID 83401

B. Haas
Ames Laboratory
7 Spedding Hall
Iowa State University
Ames, IA 50011

- 6 Westinghouse Savannah River
Company
P.O. Box 616
Aiken, SC 29801
ATTN: J. S. Haselow
C. M. Jantzen
M. J. Plodinec
J. F. Sproull
J. L. Steele
T. Walton

J. M. Pope
West Valley Nuclear
Services Co.
P.O. Box 191
West Valley, NY 14171

No. of
Copies

4 Geosafe Corporation
2000 Logston Boulevard
Richland, WA 99352
ATTN: C. L. Timmerman (2)
B. E. Campbell
J. E. Hanson

ONSITE

13 DOE Richland Field Office

E. A. Bracken, A6-95
K. W. Bracken, A5-22
R. P. Carter, A5-21
P. K. Clark, A6-80
P. F. Dunigan, A6-95
J. K. Erickson, A5-19
R. D. Freeburg, A5-19
M. J. Furman, A6-80
R. E. Gerton, A6-80
J. D. Goodenough, A5-22
J. M. Hennig, A5-21
R. D. Izatt, A6-95
J. J. Sutey, A5-90

13 Westinghouse Hanford Company

W. C. Alaconis, L4-92
H. Babad, B3-68
J. D. Berger, L0-18
J. W. Cammann, H4-54
K. R. Fecht, H4-56
R. E. Lerch, B2-35
H. E. McGuire, B2-35
J. W. Shade, R4-03
D. A. Turner, R1-10
D. D. Wodrich, R1-48
R. D. Wojtasek, B2-15
B. A. Wolfe, L5-61
R. L. Gilchrist, L5-63

No. of
Copies

49 Pacific Northwest Laboratory

L. Ballou, P7-18
T. M. Bergsman, P7-41
W. F. Bonner, P7-44
J. L. Buelt, P7-41 (5)
H. C. Burkholder, P7-41
C. C. Chapman, P7-41
T. T. Claudson, K1-66
W. O. Heath, P7-41
C. H. Kindle, P7-41
W. L. Kuhn, P8-38 (10)
P. A. Lowery, K7-15
J. Luey, P7-41
J. L. McElroy, P7-46
M. E. Peterson, P7-41 (5)
T. D. Powell, P7-39
M. R. Shay, K6-25
S. C. Slate, K1-25
S. L. Stein, PNWD
L. E. Thompson, P7-41 (5)
J. S. Tixier, P7-41
R. G. Winkelman, P7-41
S. L. Woosley, P7-41
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

7 / 8 / 92