WSRC-RP-92-361

FOAM APPLICATION OF OXALIC ACID AS A DECONTAMINATION WASTE MINIMIZATION TOOL (U)

by K. D. Peterson

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

WSRC-RP--92-361

DE93 008510

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY**

**Keywords: Decontamination Technology,
Foams, Nitric Acid, Oxalic Acid**

WSRC-RP-92-361

**CC W. L. Tamosaitis, 773-A S. T. Wach, 703-H
W. N. Rankin, 773-A B. L. Lewis, 703-H
J. F. McGlynn, 773-A W. C. Clark, 703-H
K. L. Dykes, 773-43A R. W. Harral, 703-H
R. J. Hinds, 773-43A T. R. Jones, 703-H
D. T. Hobbs, 773-A N. R. Pasala, 703-H
W. F. Yau, 773-A S. F. Putnam, 703-H
R. H. Smith, 221-H R. J. Petras, 703-H
D. Young, 221-H G. K. Georgetown, 703-H
P. N. Cakanic, 703-F N. R. Davis, 241-120H
S. A. Yano, 221-H V. L. Davis, 242-24H
SRL Records (4)**

March 9, 1992

TO: W. E. Stevens, 773-43A

FROM: K. D. Peterson, 773-43A *KDP*

**FOAM APPLICATION OF OXALIC ACID AS A DECONTAMINATION WASTE
MINIMIZATION TOOL (U)**

SUMMARY

The use of foam in applying decontamination solutions has proven to be an effective waste minimization strategy. Initial trials in 299-H indicated a 70% reduction in waste volume. An overpressurization of the equipment during a decon operation, however, indicated the need to better define chemical compatibility and to develop inherently safer equipment. A foamer system with an open solution vessel and 1:1 ratio pneumatically actuated pump was modified, tested and found to operate satisfactorily. Laboratory tests indicate no significant incompatibilities between the foam agent and oxalic or dilute nitric acid solutions.¹ Oxalic acid/foam agent compatibility was verified in the foamer vessel for concentrations up to 4 weight percent. It is recommended, however, that 1 weight percent oxalic acid be used in plant decon operations. The defoamer used previously is no longer in production. A new defoamer remains to be tested.² Limited use of the foamer in 299-H can now be initiated. Long term use of foam and its impact on waste tank processes is being reviewed.

BACKGROUND

When in a foam state, decon solutions can be applied in a thin layer to a variety of surface geometries, including vertical and overhead surfaces. Because foams cling to surfaces and therefore increase dwell time, the decon solution is better exploited, minimizing waste. The need for a large, expensive, wasteful dip tank is also eliminated. The use of foam as a means of minimizing decontamination waste at SRS was initiated in early 1987. A DuBois FOAMALL "10" unit was demonstrated in June of 1989 using DuBois' organic foamer agent, Fome-Add, and water. The unit utilizes a solution vessel which is pressurized from an external compressed air source to feed the solution. A proposal to use up to 50 gallons of Fome-Add and 10 gallons of ISM-25A defoamer in 299-H was assessed to have "...little impact on waste tank or DWPF operations."³ WMO used the equipment successfully in 12 decon operations between December of 1989 and March of 1990. The solution was composed of concentrated nitric acid and Fome-Add mixed in a ratio of 24:1. On March 5, 1990, the solution was mixed at a ratio of 3:1, resulting in a runaway chemical reaction which overwhelmed the relief valve and overpressurized the solution vessel. The Investigation Report - Judgement of Needs called for additional technical support from WMT and SRL.⁴ This is being given through expanded guidance on foam solution chemical compatibility and development of equipment which is tolerant of chemical reactivity.

DEVELOPMENTAL

The DuBois FOAMALL "10" unit that was used in 299-H (Figure 1) utilizes a vessel which is closed and pressurized after the decon solution and foam agent have been mixed. The solution is forced to the mixing body, where it combines with compressed air. The mixture is then delivered to the spray wand where it expands to ambient pressure, creating a foam. SRL recognized that a relief valve was required on the vessel and proactively installed a Circle-Seal model D559T1-2M-100 ASME valve. It was later found that a sufficiently energetic reaction could overwhelm the valve's relieving capability. The pressure generated in the incident cited was sufficient to rupture the vessel. An analysis of the event states that the "...direct reaction between HNO₃ and organic matter is usually very slow, but it proceeds much more rapidly, in a closed system, by the following autocatalytic route: ..."5

Equipment alternatives were discussed with R. M. Wallace and W. F. Yau in December of 1990. It was concluded that a system which utilized a pneumatically driven pump to feed the decon solution to the mixer from an open vessel would minimize the consequences of a chemical reaction. The use of an open vessel not only precludes the possibility of overpressurization of the vessel due to a chemical incompatibility, but also allows any gaseous products of a reaction to dissipate, eliminating the autocatalytic effect of the gases discussed in the analysis. As an added safety measure, disabling the trigger on the spray wand would serve to prevent the mixer and hose from acting as a small closed vessel. In addition, the constant air stream (created by this modification) passing through the mixer, foam hose and spray wand would also quickly evacuate these components whenever the solution feed is stopped, thus removing the potential source of overpressurization itself.

A DuBois FOAMALL 910-114 (Figure 2) was requisitioned and received in May of 1990. In place of a pressurized closed vessel, the unit utilizes a 5:1 ratio pneumatically driven solution pump. The solution vessel is an open drum which cannot be pressurized. The open drum also provides a continuous view of the solution so that it can be monitored before and during operation. A diaphragm valve connected to the

mixing body shuts off the air supply to the pump when the pressure in the mixing body is greater than that in the air supply line. This would normally occur whenever the spray wand trigger is released during operation or as the result of a chemical reaction within the mixing body or foam hose. During a discussion of the project, T. R. Jones pointed out the possibility (albeit remote) of the 5:1 ratio pump overpressurizing the system. This could happen if an obstruction occurred in the solution hose between the pump and mixing body. The diaphragm valve would not sense the pressure rise and the pump could pressurize the solution line to 5 times the air supply pressure. With a 100 psi input, 500 psi could be developed, which is twice the hose's rated working pressure. Changing the pump to a lower ratio was considered, but the vendor indicated that lower ratio pumps in stainless steel were not available.

Figure 1. Dubois Foamall 10

Figure 2. DuBois Foamall Unit 910-114

A report by K. A. Meigs at the West Valley Demonstration Project chronicles the successful use of an ARO® foamer which utilizes a 1:1 ratio stainless steel pump.⁶ This feature precludes the possibility of pump-induced buildup of pressure above that of the air supply. When the spray wand valve is closed, the pump simply stalls, so a diaphragm valve is unnecessary. Otherwise, its principle of operation is the same as that of the DuBois unit. An ARO® model 613119 (Figure 3) was requisitioned in July of 1991 for testing and comparison with the DuBois unit.

Various modifications and additions were made to the standard foamers:

- The spray wand trigger on the DuBois unit was disabled and the ball valve on the ARO® spray wand was removed. As discussed before, these modifications prevent the mixing body and foam hose from acting as a small closed vessel when foam is not being applied. This "open system" not only provides a continuous outlet for the (potential) products of reaction generated by the solution within the mixing body and foam hose, but the constant air stream also serves to flush the reactants themselves from within the system whenever the pump is shut off.
- A ball valve was added to the inlet air line of the ARO® foamer to allow isolating the system from the air supply
- An oiler was added to the ARO® unit. This is necessary to ensure pump life expectancy. It is important to locate the oiler between the tee, which feeds air directly to the mixer, and the pump. This avoids the unnecessary addition of oil contamination to the foam solution.
- A ball valve was added to both units just upstream of the pump needle valve. This allows the operator to turn the pump on and off without losing the needle valve adjustment.
- Two stainless steel 35 gallon drums were obtained from Salvage. Drain pipes and valves were added. Stainless steel drum dollies were requisitioned. The drum tops were partially closed off to increase operator protection and reduce the possibility of oil spilling into the decon solution from the air line oiler reservoir.
- The spray wand on the DuBois unit was altered to accept quick-change nozzles supplied by T. R. Jones.
- The DuBois pump bracket was scrapped and redesigned to provide better support and guarding.
- Two pneumatically driven mixers were ordered (ARO® model 31678-105 with stainless steel propellers - option #651102-B). The mixers will ensure solution homogeneity while reducing operator fatigue and exposure.
- A pneumatic muffler and overrun valve were ordered for the ARO® unit. The muffler was found to be unnecessary and the overrun valve was judged to be too cumbersome for routine use.

Figure 3. ARO Foamer 613119

in previous operations, use of the foamer was followed by the application of a defoamer to the solution prior to disposal. DuBois ISM-25A was used, but it is no longer in production. Remaining stock of ISM-25A is small. WM has indicated that the defoamer used in the waste tank evaporators would be a preferred alternate for future foam decon operations. Defoamer tests will be performed as soon as the current defoamer in use is identified.

Waste tank compatibility is another program element. D. T. Hobbs currently provides guidance in this capacity. The H and F Canyons Waste Processing Flow Diagram was delivered to Hobbs in June of 1991. Proprietary composition information for Fome-Add was provided to D. T. Hobbs and G. T. Georgetown. A current assessment of waste tank impact from the use of Fome-Add and the defoamer, with a preliminary recommendation for use, remains to be obtained. WM is collecting information as a precursor to requesting a recommendation by SRL. In addition, Hobbs has indicated the need to obtain waste samples (following foam decon operations) for analysis in order to make long term recommendations on the use of Fome-Add and the defoamer.

EXPERIMENTAL

Laboratory tests indicate no significant incompatibilities between the DuBois Fome-Add foaming agent and oxalic acid or dilute nitric acid. That conclusion is, however, qualified to note the small scale of the experiments and the potential for different results in larger quantity mixtures, as would be used in the foamer. More substantive conclusions can only be drawn from tests with the actual volumes to be used. Full scale trials to demonstrate foamer performance and solution compatibility/viability were then conducted. Tests included various concentrations of oxalic acid and the defoamer.

RESULTS

Initial tests were performed to confirm basic operational performance. Both units were run with water only, followed by solutions consisting of water and Fome-Add mixed in a 200:1 ratio. A very dry foam was achieved. DuBois ISM-25A defoamer was diluted in the foamer tank and sprayed over the foam solution. A final rinse was also applied via the foamer. This served to help break down the foam and rinse the foamer interior. Both units performed well, but the DuBois spray wand delivered the foam at a more even rate and with a greater trajectory. Despite this, it was agreed that the simplicity and inherent safety of the APO® unit made it the preferred unit. The DuBois spray wand was perceived as the critical component in the DuBois unit's superior performance and was transferred to the ARO® unit.

The next test was with a 2 weight percent solution of oxalic acid with Fome-Add mixed at a ratio of 200:1 in the "SRL-modified" ARO® foamer. Appreciable surging of the solution occurred and the foam was unacceptably wet, offering very little adherence. It was unclear, however, whether these phenomena were due to the introduction of oxalic acid to the solution or to the mating of the ARO® unit with the DuBois spray wand. Adding sufficient Fome-Add to effect a 100:1 ratio was found to produce an acceptable foam consistency. The surging was found to be the result of an inadequate air supply. The high flow rate of the system resulted in insufficient system pressure, in turn creating an inadequate pressure differential between the mixer pressure and pump supply pressure. The injection of foam solution into the mixer created additional back pressure, sufficient to stall the pump. As the foam solution exited the nozzle, the back pressure was reduced and the pump resumed

operation. An attempt was made to increase the pressure differential by reducing the mixer pressure. This resulted in a diminished air flow to the mixer tee which was insufficient for creating properly aerated foam. After defoaming, neutralization of the solution was achieved by the addition of 8 molar sodium hydroxide.

To solve the air starvation problem, the 5/16" ID air supply hose was replaced with a 3/8" ID hose. Water and Fome-Add were mixed at a 200:1 ratio and acceptable operation was achieved. The larger hose was able to simultaneously provide sufficient air flow to the mixer tee for proper foam consistency and maintain an adequate pressure differential between the mixer and pump air inlet to promote uniform foam delivery. A variety of quick-change nozzles supplied by T. R. Jones were tried, with the smallest orifice size and narrowest spray width (Spraying Systems Co. part #QLU-SS-25150) yielding the most usable spray pattern.

A test with 4 weight percent oxalic acid and Fome-Add mixed at a ratio of 100:1 was then conducted. Satisfactory performance was achieved, but misting of the solution created noxious fumes and the test was terminated.

Information on current defoamer use in the waste tank evaporators was unavailable at the writing of this report. Defoamer selection and testing is a near-term project priority.

CONCLUSIONS

The "SRL-modified" ARO® foamer provides the best combination of safety, simplicity and performance. Its 1:1 ratio pump and straightforward plumbing are significant attributes. Lab tests indicated no incompatibility between oxalic acid and Fome-Add. Tests at TNX confirmed this with 2 and 4 weight percent oxalic acid. Noxious misting prevented testing at greater concentrations.

It is important to provide an adequate air supply to the foamer. A minimum of 10 cfm @ 60 psi is required. Inadequate air feed will cause erratic operation and unacceptable foam consistency. The quick-change nozzles supplied by T. R. Jones are a convenient means by which the foam spray pattern can be tailored to the specific job. Nozzles with a variety of flow rates and spray angles have been requisitioned. Nozzles with too low a flow rate will increase back pressure, creating flow oscillation, and should be avoided.

Although the wetted metallic parts of the ARO® foamer pump are stainless steel, many of the pump's nonmetallic parts and peripheral components are constructed of materials which are not compatible with the various solutions that might be used. The foam mixer tee is a brass alloy, which is not recommended for service with oxalic acid (or nitric acid). Stainless steel mixers have been fabricated as replacements. Many other components, some in direct contact with the solution, are made of incompatible materials. A list of chemically tolerant replacement parts, which are on order, is attached. These parts are compatible for use with caustic, nitric acid and oxalic acid solutions. Preferred materials are stainless steel, Teflon® and Viton®. The exterior of the upper half of the pump is anodized aluminum.

RECOMMENDATIONS

Decon operations should not be carried out with oxalic acid concentrations greater than 4 weight percent without prior testing at full scale. These tests should be conducted in a controlled environment with adequate personnel protection from aerosols. The 299-H decon cell might be an appropriate facility. Although the maximum solubility of oxalic acid is 12.5 weight percent at ambient temperature, W. N. Rankin has advised that concentrations above 1 weight percent do not yield significantly better decontamination factors. Testing, therefore, above 4 weight percent may only be required to define compatibility in case of accidental use of concentrated oxalic acid. For routine decontamination, a 1% oxalic acid solution mixed with Fome-Add at a ratio of 100:1 is recommended. The defoamer should be applied via the foamer, followed by a rinse, at least some of which is applied via the foamer.

Disabling the trigger on the spray wand was performed to prevent the hose and mixer from acting as a closed vessel, with the resulting known hazard associated with a chemical incompatibility. Although it is recognized that on/off control of the foamer from the main unit is awkward and somewhat less efficient, safety concerns warrant the modification. It is recommended that all foamers be modified accordingly before being placed in service. In addition, B. L. Lewis has noted the need to do a preoperational process hazards review.

The procedures used for foamer operation at TNX are attached. They are provided as a reference only, and should not be interpreted as adequate for actual plant decontamination operations. The need for flexibility in testing routines required dependence on the Cognizant Technical Function to a degree which is unacceptable in plant operations. Radiation and contamination protection are not addressed. Recommendations for plant procedures are:

- Only the specific amount of each chemical required for the operation should be provided. 100 liters of water requires 1 kg of oxalic acid crystals and 100 ml of Fome-Add to achieve a 1% solution. These premeasured quantities can be provided in containers which are simply added to the correct amount of water. No other foam decontamination solutions should be used until adequate testing and review has been performed.
- If possible, the foamer should remain outside the decon cell, with the solution delivered through a penetration. This would reduce personnel exposure and minimize the impact of an equipment failure. Clear visual and oral communication must be maintained between the foam applicator and the foamer operator.

PROGRAM

Laboratory tests similar to those conducted with oxalic acid will be performed with SC-200 (or Purex) cleaner. No incompatibilities are anticipated. Lab tests will be followed by demonstrations at TNX. Selection and testing of the defoamer to be used will be conducted as soon as the desired defoamer is identified. Trials of the just-received pneumatic mixers will be done concurrent with defoamer testing. Later tests are planned with a range of nitric acid solution concentrations.

The issue of long term disposal impact of the foam and defoamer solutions remains to be resolved. Data from foam use should be provided for the study. This would include analysis of waste samples taken from foam decon operations and volumetric generation data.

REFERENCES

- ¹Clark, S.B. & Toole, P.A., February, 1992, WSRC-RP-92-243, "Chemical Compatibility of Fome-Add with Dilute Nitric and Oxalic Acids (U)".
- ²Patrick, A.L. & Hobbs, D.T., November, 1990, WSRC-TR-90-490, "Laboratory Evaluation of Defoamers for Use in High Level Waste Evaporators (U)".
- ³Eibling, R.E., September, 1989, WSRC-RP-89-893, "Preliminary Assessment of Waste Management Decontamination Chemicals (U)".
- ⁴United States Department of Energy, Savannah River Operations Office, Aiken, SC, May, 1990, "Foam Generator Feed Tank Rupture at the Savannah River Site on March 5, 1990".
- ⁵Wallace, R.M., June, 1990, WSRC-RP-90-457, "Cause of the 299-H Tank Rupture (U)", pg. 1.
- ⁶Meigs, R.A., May, 1987, West Valley Nuclear Services Company, Inc., "Use of Foam Chemicals for Decontamination".

END

DATE
FILMED

5 / 17 / 93